

Oracle® Database

Reference

11g Release 2 (11.2)

E24448-01

August 2011

Primary Author: Bert Rich

Contributors: Nipun Agarwal, Rick Anderson, Mark Bauer, Neerja Bhatt, Tudor Bosman, George Candea, Wilson Chan, Sumanta Chatterjee, Eugene Chong, Connie Dialeris Green, Harvey Eneman, Bruce Ernst, Ira Greenberg, Steve Harris, Thuvan Hoang, Lilian Hobbs, Namit Jain, Hakkan Jakobsson, Bob Jenkins, Mark Johnson, Jonathan Klein, Sushil Kumar, Tirthankar Lahiri, Bill Lee, Yunrui Li, Juan Loaiza, Rich Long, Diana Lorentz, Catherine Luu, Neil MacNaughton, Ari Mozes, Gopal Mulagund, Subramanian Muralidhar, Ravi Murthy, Karuna Muthiah, Arvind Nithrakashyap, Ronald Obermarck, Kant Patel, Christopher Racicot, Mark Ramacher, Shankar Raman, Suvendu Ray, Ann Rhee, Beth Roeser, Kathy Rich, Vivian Schupmann, Debbie Steiner, Seema Sundara, Juan Tellez, Alex Tsukerman, Kothanda Umamageswaran, Randy Urbano, Steve Vivian, Eric Voss, Tak Wang, Steve Wertheimer, Andy Witkowski, Daniel Wong, Graham Wood, Brian Wright, Aravind Yalamanchi, Qin Yu, Mohamed Ziauddin

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	liii
Audience	liii
Documentation Accessibility	liii
Related Documents	liv
Conventions	liv
 What's New in Oracle Database Reference?	lv
Oracle Database 11g Release 2 (11.2.0.3) New Features	lv
Oracle Database 11g Release 2 (11.2.0.2) New Features	lv
Oracle Database 11g Release 2 (11.2.0.1) New Features	lvi
Oracle Database 11g Release 1 (11.1) New Features	lviii
 Part I Initialization Parameters	
 1 Initialization Parameters	
Uses of Initialization Parameters	1-1
Types of Initialization Parameters	1-2
Derived Parameters	1-2
Operating System-Dependent Parameters	1-2
Variable Parameters	1-2
Basic Initialization Parameters	1-3
Parameter Files	1-3
Server Parameter Files	1-3
Initialization Parameter Files	1-4
Specifying Values in an Initialization Parameter File	1-4
Changing Parameter Values in a Parameter File	1-6
Parameters by Functional Category	1-6
Modifiable Parameters	1-12
Displaying Current Parameter Values	1-17
Parameters You Should Not Specify in the Parameter File	1-18
When Parameters Are Set Incorrectly	1-18
Reading the Parameter Descriptions	1-18
Initialization Parameter Descriptions	1-19
ACTIVE_INSTANCE_COUNT	1-19
AQ_TM_PROCESSES	1-20

ARCHIVE_LAG_TARGET	1-21
ASM_DISKGROUPS	1-21
ASM_DISKSTRING	1-22
ASM_POWER_LIMIT	1-23
ASM_PREFERRED_READ_FAILURE_GROUPS	1-23
AUDIT_FILE_DEST	1-23
AUDIT_SYS_OPERATIONS	1-24
AUDIT_SYSLOG_LEVEL	1-24
AUDIT_TRAIL	1-25
AWR_SNAPSHOT_TIME_OFFSET	1-26
BACKGROUND_CORE_DUMP	1-27
BACKGROUND_DUMP_DEST	1-27
BACKUP_TAPE_IO_SLAVES	1-28
BITMAP_MERGE_AREA_SIZE	1-29
BLANK_TRIMMING	1-29
CIRCUITS	1-30
CLIENT_RESULT_CACHE_LAG	1-30
CLIENT_RESULT_CACHE_SIZE	1-30
CLUSTER_DATABASE	1-31
CLUSTER_DATABASE_INSTANCES	1-31
CLUSTER_INTERCONNECTS	1-32
COMMIT_LOGGING	1-33
COMMIT_POINT_STRENGTH	1-33
COMMIT_WAIT	1-34
COMMIT_WRITE	1-34
COMPATIBLE	1-35
CONTROL_FILE_RECORD_KEEP_TIME	1-36
CONTROL_FILES	1-36
CONTROL_MANAGEMENT_PACK_ACCESS	1-37
CORE_DUMP_DEST	1-38
CPU_COUNT	1-38
CREATE_BITMAP_AREA_SIZE	1-39
CREATE_STORED_OUTLINES	1-39
CURSOR_BIND_CAPTURE_DESTINATION	1-40
CURSOR_SHARING	1-41
CURSOR_SPACE_FOR_TIME	1-41
DB_nK_CACHE_SIZE	1-42
DB_BLOCK_BUFFERS	1-43
DB_BLOCK_CHECKING	1-44
DB_BLOCK_CHECKSUM	1-44
DB_BLOCK_SIZE	1-45
DB_CACHE_ADVICE	1-46
DB_CACHE_SIZE	1-47
DB_CREATE_FILE_DEST	1-47
DB_CREATE_ONLINE_LOG_DEST_n	1-48
DB_DOMAIN	1-48
DB_FILE_MULTIBLOCK_READ_COUNT	1-49

DB_FILE_NAME_CONVERT	1-50
DB_FILES	1-51
DB_FLASH_CACHE_FILE	1-52
DB_FLASH_CACHE_SIZE	1-52
DB_FLASHBACK_RETENTION_TARGET	1-53
DB_KEEP_CACHE_SIZE	1-53
DB_LOST_WRITE_PROTECT	1-53
DB_NAME	1-54
DB_RECOVERY_FILE_DEST	1-55
DB_RECOVERY_FILE_DEST_SIZE	1-55
DB_RECYCLE_CACHE_SIZE	1-56
DB_SECUREFILE	1-56
DB_ULTRA_SAFE	1-57
DB_UNIQUE_NAME	1-58
DB_UNRECOVERABLE_SCN_TRACKING	1-58
DB_WRITER_PROCESSES	1-59
DBWR_IO_SLAVES	1-59
DDL_LOCK_TIMEOUT	1-60
DEFERRED_SEGMENT_CREATION	1-60
DG_BROKER_CONFIG_FILE <i>n</i>	1-60
DG_BROKER_START	1-61
DIAGNOSTIC_DEST	1-61
DISK_ASYNC_IO	1-62
DISPATCHERS	1-63
DISTRIBUTED_LOCK_TIMEOUT	1-66
DML_LOCKS	1-66
DST_UPGRADE_INSERT_CONV	1-67
ENABLE_DDL_LOGGING	1-68
EVENT	1-68
FAL_CLIENT	1-68
FAL_SERVER	1-69
FAST_START_MTTR_TARGET	1-69
FAST_START_PARALLEL_ROLLBACK	1-70
FILE_MAPPING	1-70
FILEIO_NETWORK_ADAPTERS	1-71
FILESYSTEMIO_OPTIONS	1-71
FIXED_DATE	1-71
GCS_SERVER_PROCESSES	1-72
GLOBAL_CONTEXT_POOL_SIZE	1-72
GLOBAL_NAMES	1-73
GLOBAL_TXN_PROCESSES	1-73
HASH_AREA_SIZE	1-74
HI_SHARED_MEMORY_ADDRESS	1-74
HS_AUTOREGISTER	1-75
IFILE	1-75
INSTANCE_GROUPS	1-76
INSTANCE_NAME	1-76

INSTANCE_NUMBER	1-77
INSTANCE_TYPE	1-77
JAVA_JIT_ENABLED	1-78
JAVA_MAX_SESSIONSPACE_SIZE	1-78
JAVA_POOL_SIZE	1-79
JAVA_SOFT_SESSIONSPACE_LIMIT	1-79
JOB_QUEUE_PROCESSES	1-80
LARGE_POOL_SIZE	1-80
LDAP_DIRECTORY_ACCESS	1-81
LDAP_DIRECTORY_SYSAUTH	1-82
LICENSE_MAX_SESSIONS	1-82
LICENSE_MAX_USERS	1-83
LICENSE_SESSIONS_WARNING	1-83
LISTENER_NETWORKS	1-84
LOCAL_LISTENER	1-85
LOCK_NAME_SPACE	1-85
LOCK_SGA	1-86
LOG_ARCHIVE_CONFIG	1-86
LOG_ARCHIVE_DEST	1-87
LOG_ARCHIVE_DEST_ <i>n</i>	1-88
LOG_ARCHIVE_DEST_STATE_ <i>n</i>	1-91
LOG_ARCHIVE_DUPLEX_DEST	1-92
LOG_ARCHIVE_FORMAT	1-93
LOG_ARCHIVE_LOCAL_FIRST	1-94
LOG_ARCHIVE_MAX_PROCESSES	1-95
LOG_ARCHIVE_MIN_SUCCEED_DEST	1-95
LOG_ARCHIVE_TRACE	1-96
LOG_BUFFER	1-97
LOG_CHECKPOINT_INTERVAL	1-98
LOG_CHECKPOINT_TIMEOUT	1-99
LOG_CHECKPOINTS_TO_ALERT	1-100
LOG_FILE_NAME_CONVERT	1-100
MAX_DISPATCHERS	1-101
MAX_DUMP_FILE_SIZE	1-101
MAX_ENABLED_ROLES	1-102
MAX_SHARED_SERVERS	1-102
MEMORY_MAX_TARGET	1-103
MEMORY_TARGET	1-103
NLS_CALENDAR	1-104
NLS_COMP	1-105
NLS_CURRENCY	1-106
NLS_DATE_FORMAT	1-107
NLS_DATE_LANGUAGE	1-107
NLS_DUAL_CURRENCY	1-108
NLS_ISO_CURRENCY	1-109
NLS_LANGUAGE	1-109
NLS_LENGTH_SEMANTICS	1-110

NLS_NCHAR_CONV_EXCP	1-111
NLS_NUMERIC_CHARACTERS.....	1-111
NLS_SORT.....	1-112
NLS_TERRITORY.....	1-113
NLS_TIMESTAMP_FORMAT.....	1-114
NLS_TIMESTAMP_TZ_FORMAT	1-114
O7_DICTIONARY_ACCESSIBILITY	1-115
OBJECT_CACHE_MAX_SIZE_PERCENT.....	1-116
OBJECT_CACHE_OPTIMAL_SIZE	1-116
OLAP_PAGE_POOL_SIZE.....	1-117
OPEN_CURSORS	1-117
OPEN_LINKS	1-117
OPEN_LINKS_PER_INSTANCE	1-118
OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES.....	1-119
OPTIMIZER_DYNAMIC_SAMPLING.....	1-119
OPTIMIZER_FEATURES_ENABLE	1-119
OPTIMIZER_INDEX_CACHING.....	1-121
OPTIMIZER_INDEX_COST_ADJ.....	1-121
OPTIMIZER_MODE	1-122
OPTIMIZER_SECURE_VIEW_MERGING	1-123
OPTIMIZER_USE_INVISIBLE_INDEXES	1-123
OPTIMIZER_USE_PENDING_STATISTICS	1-124
OPTIMIZER_USE_SQL_PLAN_BASELINES	1-124
OS_AUTHENT_PREFIX	1-124
OS_ROLES.....	1-125
PARALLEL_ADAPTIVE_MULTI_USER.....	1-126
PARALLEL_AUTOMATIC_TUNING	1-126
PARALLEL_DEGREE_LIMIT.....	1-127
PARALLEL_DEGREE_POLICY.....	1-127
PARALLEL_EXECUTION_MESSAGE_SIZE	1-128
PARALLEL_FORCE_LOCAL.....	1-129
PARALLEL_INSTANCE_GROUP	1-129
PARALLEL_IO_CAP_ENABLED.....	1-130
PARALLEL_MAX_SERVERS.....	1-130
PARALLEL_MIN_PERCENT	1-131
PARALLEL_MIN_SERVERS.....	1-132
PARALLEL_MIN_TIME_THRESHOLD	1-132
PARALLEL_SERVERS_TARGET.....	1-133
PARALLEL_THREADS_PER_CPU	1-133
PGA_AGGREGATE_TARGET	1-134
PLSCOPE_SETTINGS.....	1-135
PLSQL_CCFLAGS	1-135
PLSQL_CODE_TYPE.....	1-136
PLSQL_DEBUG.....	1-136
PLSQL_OPTIMIZE_LEVEL	1-137
PLSQL_V2_COMPATIBILITY.....	1-138
PLSQL_WARNINGS	1-138

PRE_PAGE_SGA	1-140
PROCESSES	1-140
QUERY_REWRITE_ENABLED	1-141
QUERY_REWRITE_INTEGRITY	1-142
RDBMS_SERVER_DN	1-142
READ_ONLY_OPEN_DELAYED	1-143
RECOVERY_PARALLELISM	1-143
RECYCLEBIN	1-144
REDO_TRANSPORT_USER	1-144
REMOTE_DEPENDENCIES_MODE	1-145
REMOTE_LISTENER	1-145
REMOTE_LOGIN_PASSWORDFILE	1-146
REMOTE_OS_AUTHENT	1-146
REMOTE_OS_ROLES	1-147
REPLICATION_DEPENDENCY_TRACKING	1-147
RESOURCE_LIMIT	1-148
RESOURCE_MANAGER_CPU_ALLOCATION	1-148
RESOURCE_MANAGER_PLAN	1-149
RESULT_CACHE_MAX_RESULT	1-149
RESULT_CACHE_MAX_SIZE	1-150
RESULT_CACHE_MODE	1-150
RESULT_CACHE_REMOTE_EXPIRATION	1-151
RESUMABLE_TIMEOUT	1-151
ROLLBACK_SEGMENTS	1-151
SEC_CASE_SENSITIVE_LOGON	1-152
SEC_MAX_FAILED_LOGIN_ATTEMPTS	1-153
SEC_PROTOCOL_ERROR_FURTHER_ACTION	1-153
SEC_PROTOCOL_ERROR_TRACE_ACTION	1-154
SEC_RETURN_SERVER_RELEASE_BANNER	1-154
SERIAL_REUSE	1-155
SERVICE_NAMES	1-156
SESSION_CACHED_CURSORS	1-156
SESSION_MAX_OPEN_FILES	1-157
SESSIONS	1-157
SGA_MAX_SIZE	1-158
SGA_TARGET	1-158
SHADOW_CORE_DUMP	1-159
SHARED_MEMORY_ADDRESS	1-160
SHARED_POOL_RESERVED_SIZE	1-160
SHARED_POOL_SIZE	1-161
SHARED_SERVER_SESSIONS	1-162
SHARED_SERVERS	1-162
SKIP_UNUSABLE_INDEXES	1-163
SMTP_OUT_SERVER	1-163
SORT_AREA_RETAINED_SIZE	1-164
SORT_AREA_SIZE	1-165
SPFILE	1-166

SQL_TRACE.....	1-166
SQL92_SECURITY	1-167
SQLTUNE_CATEGORY	1-168
STANDBY_ARCHIVE_DEST	1-168
STANDBY_FILE_MANAGEMENT	1-168
STAR_TRANSFORMATION_ENABLED	1-169
STATISTICS_LEVEL	1-170
STREAMS_POOL_SIZE	1-171
TAPE_ASYNC_IO	1-171
THREAD	1-172
TIMED_OS_STATISTICS	1-172
TIMED_STATISTICS	1-173
TRACE_ENABLED	1-173
TRACEFILE_IDENTIFIER	1-174
TRANSACTIONS	1-175
TRANSACTIONS_PER_ROLLBACK_SEGMENT	1-175
UNDO_MANAGEMENT	1-176
UNDO_RETENTION	1-176
UNDO_TABLESPACE.....	1-177
USE_INDIRECT_DATA_BUFFERS.....	1-177
USER_DUMP_DEST	1-178
UTL_FILE_DIR	1-179
WORKAREA_SIZE_POLICY.....	1-179
XML_DB_EVENTS	1-180

Part II Static Data Dictionary Views

2 Static Data Dictionary Views: ALL_ALL_TABLES to ALL_OUTLINES

About Static Data Dictionary Views.....	2-1
Oracle Replication Views	2-1
Oracle Workspace Manager Views	2-3
Recovery Catalog Views	2-4
Static Data Dictionary View Descriptions.....	2-5
ALL_ALL_TABLES	2-5
ALL_APPLY	2-8
ALL_APPLY_CHANGE_HANDLERS	2-9
ALL_APPLY_CONFLICT_COLUMNS	2-10
ALL_APPLY_DML_HANDLERS	2-10
ALL_APPLY_ENQUEUE.....	2-11
ALL_APPLY_ERROR.....	2-12
ALL_APPLY_ERROR_MESSAGES	2-12
ALL_APPLY_EXECUTE	2-13
ALL_APPLY_KEY_COLUMNS	2-13
ALL_APPLY_PARAMETERS	2-14
ALL_APPLY_PROGRESS.....	2-14
ALL_APPLY_TABLE_COLUMNS.....	2-15

ALL_ARGUMENTS.....	2-16
ALL_ASSEMBLIES.....	2-17
ALL_ASSOCIATIONS.....	2-18
ALL_AUDIT_POLICIES.....	2-18
ALL_AUDIT_POLICY_COLUMNS.....	2-20
ALL_AW_PS.....	2-20
ALL_AWS.....	2-20
ALL_BASE_TABLE_MVIEWS.....	2-21
ALL_CAPTURE.....	2-22
ALL_CAPTURE_EXTRA_ATTRIBUTES.....	2-23
ALL_CAPTURE_PARAMETERS.....	2-24
ALL_CAPTURE_PREPARED_DATABASE.....	2-24
ALL_CAPTURE_PREPARED_SCHEMAS.....	2-25
ALL_CAPTURE_PREPARED_TABLES.....	2-26
ALL_CATALOG.....	2-27
ALL_CHANGE_PROPAGATION_SETS.....	2-27
ALL_CHANGE_PROPAGATIONS.....	2-27
ALL_CHANGE_SETS.....	2-28
ALL_CHANGE_SOURCES.....	2-28
ALL_CHANGE_TABLES.....	2-29
ALL_CLUSTER_HASH_EXPRESSIONS.....	2-29
ALL_CLUSTERS.....	2-30
ALL_COL_COMMENTS.....	2-31
ALL_COL_PENDING_STATS.....	2-31
ALL_COL_PRIVS.....	2-32
ALL_COL_PRIVS_MADE.....	2-33
ALL_COL_PRIVS_RECD.....	2-33
ALL_COLL_TYPES.....	2-34
ALL_CONS_COLUMNS.....	2-34
ALL_CONS_OBJ_COLUMNS.....	2-35
ALL_CONSTRAINTS.....	2-35
ALL_CONTEXT.....	2-37
ALL_CUBE_ATTR_VISIBILITY.....	2-38
ALL_CUBE_ATTRIBUTES.....	2-38
ALL_CUBE_BUILD_PROCESSES.....	2-39
ALL_CUBE_CALCULATED_MEMBERS.....	2-39
ALL_CUBE_DIM_LEVELS.....	2-40
ALL_CUBE_DIM_MODELS.....	2-40
ALL_CUBE_DIM_VIEW_COLUMNS.....	2-41
ALL_CUBE_DIM_VIEWS.....	2-41
ALL_CUBE_DIMENSIONALITY.....	2-42
ALL_CUBE_DIMENSIONS.....	2-42
ALL_CUBE_HIER_LEVELS.....	2-43
ALL_CUBE_HIER_VIEW_COLUMNS.....	2-43
ALL_CUBE_HIER_VIEWS.....	2-44
ALL_CUBE_HIERARCHIES.....	2-45
ALL_CUBE_MEASURES.....	2-46

ALL_CUBE_VIEW_COLUMNS	2-46
ALL_CUBE_VIEWS	2-47
ALL_CUBES	2-47
ALL_DB_LINKS	2-48
ALL_DEF_AUDIT_OPTS	2-48
ALL_DEPENDENCIES	2-49
ALL_DEQUEUE_QUEUES.....	2-50
ALL_DIM_ATTRIBUTES	2-50
ALL_DIM_CHILD_OF.....	2-51
ALL_DIM_HIERARCHIES	2-51
ALL_DIM_JOIN_KEY.....	2-52
ALL_DIM_LEVEL_KEY.....	2-52
ALL_DIM_LEVELS.....	2-52
ALL_DIMENSIONS	2-53
ALL_DIRECTORIES	2-53
ALL_EDITION_COMMENTS.....	2-53
ALL_EDITIONING_VIEW_COLS	2-54
ALL_EDITIONING_VIEW_COLS_AE.....	2-54
ALL_EDITIONING_VIEWS.....	2-55
ALL_EDITIONING_VIEWS_AE	2-55
ALL_EDITIONS	2-56
ALL_ENCRYPTED_COLUMNS.....	2-56
ALL_ERRORS	2-57
ALL_ERRORS_AE	2-58
ALL_EVALUATION_CONTEXT_TABLES	2-58
ALL_EVALUATION_CONTEXT_VARS	2-59
ALL_EVALUATION_CONTEXTS	2-59
ALL_EXTERNAL_LOCATIONS	2-60
ALL_EXTERNAL_TABLES	2-60
ALL_FILE_GROUP_EXPORT_INFO	2-61
ALL_FILE_GROUP_FILES.....	2-62
ALL_FILE_GROUP_TABLES.....	2-62
ALL_FILE_GROUP_TABLESPACES.....	2-63
ALL_FILE_GROUP_VERSIONS.....	2-63
ALL_FILE_GROUPS.....	2-64
ALL_HISTOGRAMS.....	2-64
ALL_IDENTIFIERS	2-64
ALL_IND_COLUMNS	2-65
ALL_IND_EXPRESSIONS	2-66
ALL_IND_PARTITIONS	2-66
ALL_IND_PENDING_STATS	2-69
ALL_IND_STATISTICS	2-69
ALL_IND_SUBPARTITIONS.....	2-70
ALL_INDEXES.....	2-72
ALL_INDEXTYPE_ARRAYTYPES	2-76
ALL_INDEXTYPE_COMMENTS	2-76
ALL_INDEXTYPE_OPERATORS	2-77

ALL_INDEXTYPES	2-77
ALL_INTERNAL_TRIGGERS	2-78
ALL_JAVA_ARGUMENTS	2-78
ALL_JAVA_CLASSES	2-79
ALL_JAVA_COMPILER_OPTIONS	2-80
ALL_JAVA_DERIVATIONS	2-80
ALL_JAVA_FIELDS	2-81
ALL_JAVA_IMPLEMENTES	2-82
ALL_JAVA_INNERS	2-82
ALL_JAVA_LAYOUTS	2-83
ALL_JAVA_METHODS	2-84
ALL_JAVA_NCOMPS	2-85
ALL_JAVA_RESOLVERS	2-85
ALL_JAVA_THROWS	2-86
ALL_JOBS	2-86
ALL_JOIN_IND_COLUMNS	2-87
ALL_LIBRARIES	2-87
ALL_LOB_PARTITIONS	2-88
ALL_LOB_SUBPARTITIONS	2-90
ALL_LOB_TEMPLATES	2-92
ALL_LOBS	2-93
ALL_LOG_GROUP_COLUMNS	2-95
ALL_LOG_GROUPS	2-95
ALL_MEASURE_FOLDER_CONTENTS	2-96
ALL_MEASURE_FOLDERS	2-96
ALL_METHOD_PARAMS	2-97
ALL_METHOD_RESULTS	2-98
ALL_MINING_MODEL_ATTRIBUTES	2-98
ALL_MINING_MODEL_SETTINGS	2-99
ALL_MINING_MODELS	2-100
ALL_MVIEW_AGGREGATES	2-101
ALL_MVIEW_ANALYSIS	2-102
ALL_MVIEW_COMMENTS	2-103
ALL_MVIEW_DETAIL_PARTITION	2-103
ALL_MVIEW_DETAIL_RELATIONS	2-104
ALL_MVIEW_DETAIL_SUBPARTITION	2-105
ALL_MVIEW_JOINS	2-105
ALL_MVIEW_KEYS	2-106
ALL_MVIEW_LOGS	2-107
ALL_MVIEW_REFRESH_TIMES	2-107
ALL_MVIEWS	2-108
ALL_NESTED_TABLE_COLS	2-111
ALL_NESTED_TABLES	2-113
ALL_OBJ_COLATTRS	2-113
ALL_OBJECT_TABLES	2-114
ALL_OBJECTS	2-117
ALL_OBJECTS_AE	2-117

ALL_OPANCILLARY	2-118
ALL_OPARGUMENTS	2-119
ALL_OPBINDINGS.....	2-119
ALL_OPERATOR_COMMENTS	2-120
ALL_OPERATORS.....	2-120
ALL_OUTLINE_HINTS.....	2-121
ALL_OUTLINES.....	2-121

3 Static Data Dictionary Views: ALL_PART_COL_STATISTICS to DATABASE_PROPERTIES

ALL_PART_COL_STATISTICS	3-1
ALL_PART_HISTOGRAMS	3-2
ALL_PART_INDEXES	3-3
ALL_PART_KEY_COLUMNS.....	3-5
ALL_PART_LOBS	3-5
ALL_PART_TABLES	3-8
ALL_PARTIAL_DROP_TABS.....	3-11
ALL_PENDING_CONV_TABLES	3-11
ALL_PLSQL_OBJECT_SETTINGS	3-11
ALL_POLICIES	3-12
ALL_POLICY_CONTEXTS	3-13
ALL_POLICY_GROUPS	3-14
ALL_PROCEDURES.....	3-14
ALL_PROPAGATION	3-15
ALL_PUBLISHED_COLUMNS.....	3-16
ALL_QUEUE_SCHEDULES.....	3-16
ALL_QUEUE_SUBSCRIBERS	3-18
ALL_QUEUE_TABLES	3-18
ALL_QUEUES	3-19
ALL_REFRESH	3-20
ALL_REFRESH_CHILDREN	3-21
ALL_REFRESH_DEPENDENCIES.....	3-21
ALL_REFS.....	3-22
ALL_REGISTERED_MVIEWS	3-22
ALL_REGISTRY_BANNERS	3-23
ALL_REWRITE_EQUIVALENCES.....	3-23
ALL_RULE_SET_RULES	3-24
ALL_RULE_SETS	3-24
ALL_RULES.....	3-25
ALL_SCHEDULER_CHAIN_RULES	3-25
ALL_SCHEDULER_CHAIN_STEPS.....	3-26
ALL_SCHEDULER_CHAINS.....	3-27
ALL_SCHEDULER_CREDENTIALS	3-28
ALL_SCHEDULER_DB_DESTS	3-28
ALL_SCHEDULER_DESTS	3-29
ALL_SCHEDULER_EXTERNAL_DESTS	3-29
ALL_SCHEDULER_FILE_WATCHERS.....	3-30

ALL_SCHEDULER_GLOBAL_ATTRIBUTE.....	3-31
ALL_SCHEDULER_GROUP_MEMBERS.....	3-31
ALL_SCHEDULER_GROUPS.....	3-31
ALL_SCHEDULER_JOB_ARGS.....	3-32
ALL_SCHEDULER_JOB_CLASSES.....	3-33
ALL_SCHEDULER_JOB_DESTS.....	3-33
ALL_SCHEDULER_JOB_LOG.....	3-34
ALL_SCHEDULER_JOB_RUN_DETAILS.....	3-35
ALL_SCHEDULER_JOBS.....	3-36
ALL_SCHEDULER_NOTIFICATIONS.....	3-39
ALL_SCHEDULER_PROGRAM_ARGS.....	3-40
ALL_SCHEDULER_PROGRAMS.....	3-41
ALL_SCHEDULER_REMOTE_DATABASES.....	3-42
ALL_SCHEDULER_REMOTE_JOBSTATE.....	3-42
ALL_SCHEDULER_RUNNING_CHAINS.....	3-43
ALL_SCHEDULER_RUNNING_JOBS.....	3-44
ALL_SCHEDULER_SCHEDULES.....	3-45
ALL_SCHEDULER_WINDOW_DETAILS.....	3-46
ALL_SCHEDULER_WINDOW_GROUPS.....	3-47
ALL_SCHEDULER_WINDOW_LOG.....	3-47
ALL_SCHEDULER_WINDOWS.....	3-48
ALL_SCHEDULER_WINGROUP_MEMBERS.....	3-49
ALL_SEC_RELEVANT_COLS.....	3-49
ALL_SECONDARY_OBJECTS.....	3-49
ALL_SEQUENCES.....	3-50
ALL_SERVICES.....	3-50
ALL_SOURCE.....	3-51
ALL_SOURCE_AE.....	3-52
ALL_SOURCE_TABLES.....	3-52
ALL_SQLJ_TYPE_ATTRS.....	3-52
ALL_SQLJ_TYPE_METHODS.....	3-53
ALL_SQLJ_TYPES.....	3-54
ALL_SQLSET.....	3-55
ALL_SQLSET_BINDS.....	3-55
ALL_SQLSET_PLANS.....	3-56
ALL_SQLSET_REFERENCES.....	3-59
ALL_SQLSET_STATEMENTS.....	3-60
ALL_STAT_EXTENSIONS.....	3-61
ALL_STORED_SETTINGS.....	3-62
ALL_STREAMS_COLUMNS.....	3-62
ALL_STREAMS_GLOBAL_RULES.....	3-63
ALL_STREAMS_MESSAGE_CONSUMERS.....	3-64
ALL_STREAMS_MESSAGE_RULES.....	3-64
ALL_STREAMS_NEWLY_SUPPORTED.....	3-65
ALL_STREAMS_RULES.....	3-65
ALL_STREAMS_SCHEMA_RULES.....	3-67
ALL_STREAMS_STMT_HANDLERS.....	3-67

ALL_STREAMS_STMTS.....	3-68
ALL_STREAMS_TABLE_RULES.....	3-68
ALL_STREAMS_TRANSFORM_FUNCTION.....	3-70
ALL_STREAMS_UNSUPPORTED.....	3-70
ALL_SUBPART_COL_STATISTICS.....	3-71
ALL_SUBPART_HISTOGRAMS.....	3-72
ALL_SUBPART_KEY_COLUMNS.....	3-73
ALL_SUBPARTITION_TEMPLATES.....	3-73
ALL_SUBSCRIBED_COLUMNS.....	3-74
ALL_SUBSCRIBED_TABLES.....	3-74
ALL_SUBSCRIPTIONS.....	3-74
ALL_SUMDELTA.....	3-74
ALL_SYNC_CAPTURE.....	3-74
ALL_SYNC_CAPTURE_PREPARED_TABS.....	3-75
ALL_SYNC_CAPTURE_TABLES.....	3-75
ALL_SYNONYMS.....	3-75
ALL_TAB_COL_STATISTICS.....	3-77
ALL_TAB_COLS.....	3-77
ALL_TAB_COLUMNS.....	3-79
ALL_TAB_COMMENTS.....	3-81
ALL_TAB_HISTGRM_PENDING_STATS.....	3-81
ALL_TAB_HISTOGRAMS.....	3-82
ALL_TAB_MODIFICATIONS.....	3-82
ALL_TAB_PARTITIONS.....	3-83
ALL_TAB_PENDING_STATS.....	3-86
ALL_TAB_PRIVS.....	3-86
ALL_TAB_PRIVS_MADE.....	3-87
ALL_TAB_PRIVS_RECD.....	3-87
ALL_TAB_STAT_PREFS.....	3-88
ALL_TAB_STATISTICS.....	3-88
ALL_TAB_STATS_HISTORY.....	3-89
ALL_TAB_SUBPARTITIONS.....	3-89
ALL_TABLES.....	3-91
ALL_TRIGGER_COLS.....	3-94
ALL_TRIGGER_ORDERING.....	3-95
ALL_TRIGGERS.....	3-96
ALL_TSTZ_TAB_COLS.....	3-97
ALL_TSTZ_TABLES.....	3-98
ALL_TYPE_ATTRS.....	3-98
ALL_TYPE_METHODS.....	3-99
ALL_TYPE_VERSIONS.....	3-100
ALL_TYPES.....	3-101
ALL_UNUSED_COL_TABS.....	3-101
ALL_UPDATABLE_COLUMNS.....	3-102
ALL_USERS.....	3-102
ALL_USTATS.....	3-103
ALL_VARRAYS.....	3-103

ALL_VIEWS	3-104
ALL_VIEWS_AE.....	3-105
ALL_WARNING_SETTINGS.....	3-105
ALL_XML_INDEXES.....	3-106
ALL_XML_SCHEMAS	3-107
ALL_XML_TAB_COLS.....	3-108
ALL_XML_TABLES	3-109
ALL_XML_VIEW_COLS.....	3-109
ALL_XML_VIEWS	3-110
ALL_XSTREAM_INBOUND	3-110
ALL_XSTREAM_INBOUND_PROGRESS.....	3-111
ALL_XSTREAM_OUTBOUND.....	3-112
ALL_XSTREAM_OUTBOUND_PROGRESS.....	3-113
ALL_XSTREAM_RULES	3-113
AUDIT_ACTIONS.....	3-114
CAT.....	3-114
CATALOG.....	3-115
CHAINED_ROWS	3-115
CHANGE_PROPAGATION_SETS.....	3-115
CHANGE_PROPAGATIONS	3-115
CHANGE_SETS	3-115
CHANGE_SOURCES.....	3-115
CHANGE_TABLES	3-115
CLIENT_RESULT_CACHE_STAT\$.....	3-116
CLU	3-116
COL	3-116
COLS.....	3-116
DATABASE_PROPERTIES	3-116

4 Static Data Dictionary Views: DBA_2PC_NEIGHBORS to DBA_HIST_JAVA_POOL_ADVICE

DBA_2PC_NEIGHBORS	4-1
DBA_2PC_PENDING.....	4-1
DBA_ADDM_FDG_BREAKDOWN.....	4-2
DBA_ADDM_FINDINGS.....	4-2
DBA_ADDM_INSTANCES	4-3
DBA_ADDM_SYSTEM_DIRECTIVES.....	4-4
DBA_ADDM_TASK_DIRECTIVES.....	4-4
DBA_ADDM_TASKS.....	4-5
DBA_ADVISOR_ACTIONS.....	4-7
DBA_ADVISOR_COMMANDS.....	4-8
DBA_ADVISOR_DEF_PARAMETERS.....	4-8
DBA_ADVISOR_DEFINITIONS	4-9
DBA_ADVISOR_DIR_DEFINITIONS	4-9
DBA_ADVISOR_DIR_INSTANCES	4-10
DBA_ADVISOR_DIR_TASK_INST	4-10
DBA_ADVISOR_EXEC_PARAMETERS	4-11

DBA_ADVISOR_EXECUTION_TYPES	4-12
DBA_ADVISOR_EXECUTIONS	4-12
DBA_ADVISOR_FDG_BREAKDOWN	4-13
DBA_ADVISOR_FINDING_NAMES	4-13
DBA_ADVISOR_FINDINGS	4-13
DBA_ADVISOR_JOURNAL	4-14
DBA_ADVISOR_LOG	4-15
DBA_ADVISOR_OBJECT_TYPES	4-15
DBA_ADVISOR_OBJECTS	4-16
DBA_ADVISOR_PARAMETERS	4-17
DBA_ADVISOR_RATIONALE	4-18
DBA_ADVISOR_RECOMMENDATIONS	4-19
DBA_ADVISOR_SQLA_REC_SUM	4-20
DBA_ADVISOR_SQLA_TABLES	4-21
DBA_ADVISOR_SQLA_WK_MAP	4-21
DBA_ADVISOR_SQLA_WK_STMTS	4-21
DBA_ADVISOR_SQLPLANS	4-23
DBA_ADVISOR_SQLSTATS	4-25
DBA_ADVISOR_SQLW_JOURNAL	4-26
DBA_ADVISOR_SQLW_PARAMETERS	4-27
DBA_ADVISOR_SQLW_STMTS	4-27
DBA_ADVISOR_SQLW_SUM	4-28
DBA_ADVISOR_SQLW_TABLES	4-29
DBA_ADVISOR_SQLW_TEMPLATES	4-29
DBA_ADVISOR_TASKS	4-30
DBA_ADVISOR_TEMPLATES	4-31
DBA_ADVISOR_USAGE	4-32
DBA_ALERT_HISTORY	4-32
DBA_ALL_TABLES	4-33
DBA_APPLICATION_ROLES	4-33
DBA_APPLY	4-33
DBA_APPLY_CHANGE_HANDLERS	4-33
DBA_APPLY_CONFLICT_COLUMNS	4-33
DBA_APPLY_DML_HANDLERS	4-34
DBA_APPLY_ENQUEUE	4-34
DBA_APPLY_ERROR	4-34
DBA_APPLY_ERROR_MESSAGES	4-34
DBA_APPLY_EXECUTE	4-34
DBA_APPLY_INSTANTIATED_GLOBAL	4-34
DBA_APPLY_INSTANTIATED_OBJECTS	4-35
DBA_APPLY_INSTANTIATED_SCHEMAS	4-35
DBA_APPLY_KEY_COLUMNS	4-35
DBA_APPLY_OBJECT_DEPENDENCIES	4-35
DBA_APPLY_PARAMETERS	4-36
DBA_APPLY_PROGRESS	4-36
DBA_APPLY_SPILL_TXN	4-36
DBA_APPLY_TABLE_COLUMNS	4-36

DBA_APPLY_VALUE_DEPENDENCIES	4-37
DBA_AQ_AGENT_PRIVS	4-37
DBA_AQ_AGENTS	4-37
DBA_ARGUMENTS	4-37
DBA_ASSEMBLIES	4-38
DBA_ASSOCIATIONS	4-38
DBA_ATTRIBUTE_TRANSFORMATIONS	4-38
DBA_AUDIT_EXISTS	4-38
DBA_AUDIT_MGMT_CLEAN_EVENTS	4-40
DBA_AUDIT_MGMT_CLEANUP_JOBS	4-40
DBA_AUDIT_MGMT_CONFIG_PARAMS	4-40
DBA_AUDIT_MGMT_LAST_ARCH_TS	4-41
DBA_AUDIT_OBJECT	4-41
DBA_AUDIT_POLICIES	4-43
DBA_AUDIT_POLICY_COLUMNS	4-43
DBA_AUDIT_SESSION	4-43
DBA_AUDIT_STATEMENT	4-44
DBA_AUDIT_TRAIL	4-45
DBA_AUTO_SEGADV_CTL	4-47
DBA_AUTO_SEGADV_SUMMARY	4-48
DBA_AUTOTASK_CLIENT	4-48
DBA_AUTOTASK_CLIENT_HISTORY	4-49
DBA_AUTOTASK_CLIENT_JOB	4-50
DBA_AUTOTASK_JOB_HISTORY	4-50
DBA_AUTOTASK_OPERATION	4-51
DBA_AUTOTASK_SCHEDULE	4-51
DBA_AUTOTASK_TASK	4-51
DBA_AUTOTASK_WINDOW_CLIENTS	4-54
DBA_AUTOTASK_WINDOW_HISTORY	4-55
DBA_AW_PS	4-55
DBA_AWS	4-55
DBA_BASE_TABLE_MVIEWS	4-55
DBA_BLOCKERS	4-55
DBA_CAPTURE	4-55
DBA_CAPTURE_EXTRA_ATTRIBUTES	4-55
DBA_CAPTURE_PARAMETERS	4-56
DBA_CAPTURE_PREPARED_DATABASE	4-56
DBA_CAPTURE_PREPARED_SCHEMAS	4-56
DBA_CAPTURE_PREPARED_TABLES	4-56
DBA_CATALOG	4-56
DBA_CHANGE_NOTIFICATION_REGS	4-57
DBA_CLU_COLUMNS	4-57
DBA_CLUSTER_HASH_EXPRESSIONS	4-57
DBA_CLUSTERS	4-57
DBA_COL_COMMENTS	4-58
DBA_COL_PENDING_STATS	4-58
DBA_COL_PRIVS	4-58

DBA_COLL_TYPES	4-58
DBA_COMMON_AUDIT_TRAIL	4-58
DBA_COMPARISON	4-60
DBA_COMPARISON_COLUMNS	4-61
DBA_COMPARISON_ROW_DIF	4-62
DBA_COMPARISON_SCAN	4-62
DBA_COMPARISON_SCAN_VALUES	4-63
DBA_CONNECT_ROLE_GRANTEES	4-63
DBA_CONS_OBJ_COLUMNS	4-64
DBA_CONSTRAINTS	4-64
DBA_CONTEXT	4-64
DBA_CPOOL_INFO	4-64
DBA_CPU_USAGE_STATISTICS	4-64
DBA_CQ_NOTIFICATION_QUERIES	4-65
DBA_CUBE_ATTR_VISIBILITY	4-65
DBA_CUBE_ATTRIBUTES	4-65
DBA_CUBE_BUILD_PROCESSES	4-65
DBA_CUBE_CALCULATED_MEMBERS	4-66
DBA_CUBE_DIM_LEVELS	4-66
DBA_CUBE_DIM_MODELS	4-66
DBA_CUBE_DIM_VIEW_COLUMNS	4-66
DBA_CUBE_DIM_VIEWS	4-66
DBA_CUBE_DIMENSIONALITY	4-66
DBA_CUBE_DIMENSIONS	4-66
DBA_CUBE_HIER_LEVELS	4-66
DBA_CUBE_HIER_VIEW_COLUMNS	4-67
DBA_CUBE_HIER_VIEWS	4-67
DBA_CUBE_HIERARCHIES	4-67
DBA_CUBE_MEASURES	4-67
DBA_CUBE_VIEW_COLUMNS	4-67
DBA_CUBE_VIEWS	4-67
DBA_CUBES	4-67
DBA_DATA_FILES	4-68
DBA_DATAPUMP_JOBS	4-68
DBA_DATAPUMP_SESSIONS	4-69
DBA_DB_LINKS	4-69
DBA_DDL_LOCKS	4-69
DBA_DEPENDENCIES	4-70
DBA_DIM_ATTRIBUTES	4-70
DBA_DIM_CHILD_OF	4-70
DBA_DIM_HIERARCHIES	4-70
DBA_DIM_JOIN_KEY	4-70
DBA_DIM_LEVEL_KEY	4-71
DBA_DIM_LEVELS	4-71
DBA_DIMENSIONS	4-71
DBA_DIRECTORIES	4-71
DBA_DML_LOCKS	4-71

DBA_DMT_FREE_SPACE.....	4-72
DBA_DMT_USED_EXTENTS.....	4-72
DBA_EDITION_COMMENTS	4-72
DBA_EDITIONING_VIEW_COLS.....	4-72
DBA_EDITIONING_VIEW_COLS_AE.....	4-72
DBA_EDITIONING_VIEWS.....	4-73
DBA_EDITIONING_VIEWS_AE	4-73
DBA_EDITIONS	4-73
DBA_ENABLED_AGGREGATIONS	4-73
DBA_ENABLED_TRACES.....	4-73
DBA_ENCRYPTED_COLUMNS.....	4-74
DBA_EPG_DAD_AUTHORIZATION	4-74
DBA_ERRORS.....	4-74
DBA_ERRORS_AE	4-74
DBA_EVALUATION_CONTEXT_TABLES.....	4-74
DBA_EVALUATION_CONTEXT_VARS	4-75
DBA_EVALUATION_CONTEXTS	4-75
DBA_EXP_FILES	4-75
DBA_EXP_OBJECTS	4-75
DBA_EXP_VERSION	4-75
DBA_EXTENTS	4-75
DBA_EXTERNAL_LOCATIONS	4-76
DBA_EXTERNAL_TABLES	4-76
DBA_FEATURE_USAGE_STATISTICS	4-76
DBA_FGA_AUDIT_TRAIL.....	4-81
DBA_FILE_GROUP_EXPORT_INFO	4-82
DBA_FILE_GROUP_FILES.....	4-82
DBA_FILE_GROUP_TABLES.....	4-82
DBA_FILE_GROUP_TABLESPACES.....	4-82
DBA_FILE_GROUP_VERSIONS	4-82
DBA_FILE_GROUPS.....	4-83
DBA_FLASHBACK_ARCHIVE	4-83
DBA_FLASHBACK_ARCHIVE_TABLES.....	4-83
DBA_FLASHBACK_ARCHIVE_TS	4-84
DBA_FLASHBACK_TXN_REPORT	4-84
DBA_FLASHBACK_TXN_STATE	4-84
DBA_FREE_SPACE.....	4-85
DBA_FREE_SPACE_COALESCED	4-85
DBA_HIGH_WATER_MARK_STATISTICS	4-86
DBA_HIST_ACTIVE_SESS_HISTORY.....	4-86
DBA_HIST_BASELINE	4-90
DBA_HIST_BASELINE_DETAILS.....	4-91
DBA_HIST_BASELINE_METADATA.....	4-92
DBA_HIST_BASELINE_TEMPLATE	4-92
DBA_HIST_BG_EVENT_SUMMARY.....	4-93
DBA_HIST_BUFFER_POOL_STAT.....	4-93
DBA_HIST_BUFFERED_QUEUES.....	4-94

DBA_HIST_BUFFERED_SUBSCRIBERS	4-95
DBA_HIST_CLUSTER_INTERCON	4-96
DBA_HIST_COLORED_SQL	4-96
DBA_HIST_COMP_IOSTAT	4-97
DBA_HIST_CR_BLOCK_SERVER	4-97
DBA_HIST_CURRENT_BLOCK_SERVER	4-98
DBA_HIST_DATABASE_INSTANCE	4-99
DBA_HIST_DATAFILE	4-99
DBA_HIST_DB_CACHE_ADVICE	4-99
DBA_HIST_DISPATCHER	4-100
DBA_HIST_DLM_MISC	4-100
DBA_HIST_DYN_REMASTER_STATS	4-101
DBA_HIST_ENQUEUE_STAT	4-101
DBA_HIST_EVENT_HISTOGRAM	4-102
DBA_HIST_EVENT_NAME	4-102
DBA_HIST_FILEMETRIC_HISTORY	4-102
DBA_HIST_FILESTATXS	4-103
DBA_HIST_IC_CLIENT_STATS	4-104
DBA_HIST_IC_DEVICE_STATS	4-104
DBA_HIST_INST_CACHE_TRANSFER	4-105
DBA_HIST_INSTANCE_RECOVERY	4-106
DBA_HIST_INTERCONNECT_PINGS	4-107
DBA_HIST_IOSTAT_DETAIL	4-108
DBA_HIST_IOSTAT_FILETYPE	4-109
DBA_HIST_IOSTAT_FILETYPE_NAME	4-109
DBA_HIST_IOSTAT_FUNCTION	4-110
DBA_HIST_IOSTAT_FUNCTION_NAME	4-110
DBA_HIST_JAVA_POOL_ADVICE	4-110

5 Static Data Dictionary Views: DBA_HIST_LATCH to DBA_STORED_SETTINGS

DBA_HIST_LATCH	5-1
DBA_HIST_LATCH_CHILDREN	5-1
DBA_HIST_LATCH_MISSES_SUMMARY	5-2
DBA_HIST_LATCH_NAME	5-2
DBA_HIST_LATCH_PARENT	5-3
DBA_HIST_LIBRARYCACHE	5-3
DBA_HIST_LOG	5-4
DBA_HIST_MEM_DYNAMIC_COMP	5-5
DBA_HIST_MEMORY_RESIZE_OPS	5-6
DBA_HIST_MEMORY_TARGET_ADVICE	5-6
DBA_HIST_METRIC_NAME	5-7
DBA_HIST_MTTR_TARGET_ADVICE	5-7
DBA_HIST_MUTEX_SLEEP	5-8
DBA_HIST_OPTIMIZER_ENV	5-8
DBA_HIST_OSSTAT	5-9
DBA_HIST_OSSTAT_NAME	5-9

DBA_HIST_PARAMETER.....	5-9
DBA_HIST_PARAMETER_NAME	5-10
DBA_HIST_PERSISTENT_QMN_CACHE.....	5-10
DBA_HIST_PERSISTENT_QUEUES.....	5-11
DBA_HIST_PERSISTENT_SUBS.....	5-12
DBA_HIST_PGA_TARGET_ADVICE.....	5-13
DBA_HIST_PGASTAT.....	5-13
DBA_HIST_PLAN_OPERATION_NAME.....	5-14
DBA_HIST_PLAN_OPTION_NAME	5-14
DBA_HIST_PROCESS_MEM_SUMMARY	5-15
DBA_HIST_RESOURCE_LIMIT	5-15
DBA_HIST_ROWCACHE_SUMMARY.....	5-16
DBA_HIST_RSRC_CONSUMER_GROUP	5-16
DBA_HIST_RSRC_PLAN	5-18
DBA_HIST_RULE_SET	5-19
DBA_HIST_SEG_STAT	5-19
DBA_HIST_SEG_STAT_OBJ.....	5-21
DBA_HIST_SERVICE_NAME	5-21
DBA_HIST_SERVICE_STAT	5-22
DBA_HIST_SERVICE_WAIT_CLASS.....	5-22
DBA_HIST_SESS_TIME_STATS.....	5-22
DBA_HIST_SESSMETRIC_HISTORY.....	5-23
DBA_HIST_SGA.....	5-23
DBA_HIST_SGA_TARGET_ADVICE.....	5-24
DBA_HIST_SGASTAT.....	5-24
DBA_HIST_SHARED_POOL_ADVICE	5-24
DBA_HIST_SHARED_SERVER_SUMMARY	5-25
DBA_HIST_SNAP_ERROR.....	5-26
DBA_HIST_SNAPSHOT.....	5-26
DBA_HIST_SQL_BIND_METADATA	5-27
DBA_HIST_SQL_PLAN	5-27
DBA_HIST_SQL_SUMMARY.....	5-29
DBA_HIST_SQL_WORKAREA_HSTGRM.....	5-29
DBA_HIST_SQLBIND.....	5-30
DBA_HIST_SQLCOMMAND_NAME.....	5-31
DBA_HIST_SQLSTAT	5-31
DBA_HIST_SQLTEXT	5-34
DBA_HIST_STAT_NAME.....	5-34
DBA_HIST_STREAMS_APPLY_SUM	5-35
DBA_HIST_STREAMS_CAPTURE	5-35
DBA_HIST_STREAMS_POOL_ADVICE.....	5-36
DBA_HIST_SYS_TIME_MODEL.....	5-36
DBA_HIST_SYSMETRIC_HISTORY	5-37
DBA_HIST_SYSMETRIC_SUMMARY.....	5-37
DBA_HIST_SYSSTAT	5-38
DBA_HIST_SYSTEM_EVENT	5-38
DBA_HIST_TABLESPACE_STAT.....	5-38

DBA_HIST_TBSPC_SPACE_USAGE	5-39
DBA_HIST_TEMPFILE.....	5-39
DBA_HIST_TEMPSTATXS	5-39
DBA_HIST_THREAD	5-40
DBA_HIST_TOPLEVELCALL_NAME.....	5-40
DBA_HIST_UNDOSTAT	5-41
DBA_HIST_WAITCLASSMET_HISTORY.....	5-42
DBA_HIST_WAITSTAT	5-42
DBA_HIST_WR_CONTROL	5-43
DBA_HISTOGRAMS.....	5-43
DBA_IDENTIFIERS	5-43
DBA_IND_COLUMNS.....	5-43
DBA_IND_EXPRESSIONS	5-43
DBA_IND_PARTITIONS.....	5-43
DBA_IND_PENDING_STATS	5-44
DBA_IND_STATISTICS.....	5-44
DBA_IND_SUBPARTITIONS.....	5-44
DBA_INDEXES.....	5-44
DBA_INDEXTYPE_ARRAYTYPES	5-44
DBA_INDEXTYPE_COMMENTS	5-44
DBA_INDEXTYPE_OPERATORS	5-44
DBA_INDEXTYPES.....	5-45
DBA_INTERNAL_TRIGGERS	5-45
DBA_JAVA_ARGUMENTS.....	5-45
DBA_JAVA_CLASSES.....	5-45
DBA_JAVA_COMPILER_OPTIONS.....	5-45
DBA_JAVA_DERIVATIONS.....	5-45
DBA_JAVA_FIELDS	5-45
DBA_JAVA_IMPLEMENTES	5-45
DBA_JAVA_INNERS.....	5-46
DBA_JAVA_LAYOUTS.....	5-46
DBA_JAVA_METHODS	5-46
DBA_JAVA_NCOMPS	5-46
DBA_JAVA_POLICY.....	5-46
DBA_JAVA_RESOLVERS.....	5-47
DBA_JAVA_THROWS	5-47
DBA_JOBS.....	5-47
DBA_JOBS_RUNNING.....	5-48
DBA_JOIN_IND_COLUMNS	5-48
DBA_KGLLOCK.....	5-48
DBA_LIBRARIES.....	5-48
DBA_LMT_FREE_SPACE.....	5-49
DBA_LMT_USED_EXTENTS.....	5-49
DBA_LOB_PARTITIONS.....	5-49
DBA_LOB_SUBPARTITIONS.....	5-49
DBA_LOB_TEMPLATES	5-49
DBA_LOBS	5-49

DBA_LOCK.....	5-50
DBA_LOCK_INTERNAL	5-50
DBA_LOCKS.....	5-50
DBA_LOG_GROUP_COLUMNS.....	5-50
DBA_LOG_GROUPS	5-50
DBA_LOGMNR_LOG	5-51
DBA_LOGMNR_PURGED_LOG.....	5-51
DBA_LOGMNR_SESSION	5-52
DBA_LOGSTDBY_EVENTS	5-52
DBA_LOGSTDBY_HISTORY	5-53
DBA_LOGSTDBY_LOG.....	5-54
DBA_LOGSTDBY_NOT_UNIQUE.....	5-55
DBA_LOGSTDBY_PARAMETERS.....	5-56
DBA_LOGSTDBY_PROGRESS.....	5-57
DBA_LOGSTDBY_SKIP	5-57
DBA_LOGSTDBY_SKIP_TRANSACTION	5-57
DBA_LOGSTDBY_UNSUPPORTED.....	5-57
DBA_LOGSTDBY_UNSUPPORTED_TABLE.....	5-58
DBA_MEASURE_FOLDER_CONTENTS.....	5-58
DBA_MEASURE_FOLDERS	5-58
DBA_METHOD_PARAMS	5-58
DBA_METHOD_RESULTS.....	5-59
DBA_MINING_MODEL_ATTRIBUTES	5-59
DBA_MINING_MODEL_SETTINGS	5-59
DBA_MINING_MODELS.....	5-59
DBA_MVIEW_AGGREGATES	5-59
DBA_MVIEW_ANALYSIS.....	5-59
DBA_MVIEW_COMMENTS.....	5-59
DBA_MVIEW_DETAIL_PARTITION	5-60
DBA_MVIEW_DETAIL_RELATIONS.....	5-60
DBA_MVIEW_DETAIL_SUBPARTITION	5-60
DBA_MVIEW_JOINS	5-60
DBA_MVIEW_KEYS	5-60
DBA_MVIEW_LOG_FILTER_COLS.....	5-60
DBA_MVIEW_LOGS	5-60
DBA_MVIEW_REFRESH_TIMES.....	5-60
DBA_MVIEWS	5-61
DBA_NESTED_TABLE_COLS	5-61
DBA_NESTED_TABLES.....	5-61
DBA_NETWORK_ACL_PRIVILEGES	5-61
DBA_NETWORK_ACLS	5-61
DBA_OBJ_AUDIT_OPTS.....	5-62
DBA_OBJ_COLATTRS	5-62
DBA_OBJECT_SIZE	5-63
DBA_OBJECT_TABLES.....	5-63
DBA_OBJECTS.....	5-63
DBA_OBJECTS_AE	5-63

DBA_OPANCILLARY	5-63
DBA_OPARGUMENTS	5-63
DBA_OPBINDINGS	5-64
DBA_OPERATOR_COMMENTS	5-64
DBA_OPERATORS	5-64
DBA_OPTSTAT_OPERATIONS	5-64
DBA_ORPHAN_KEY_TABLE	5-64
DBA_OUTLINE_HINTS	5-65
DBA_OUTLINES	5-65
DBA_OUTSTANDING_ALERTS	5-66
DBA_PARALLEL_EXECUTE_CHUNKS	5-67
DBA_PARALLEL_EXECUTE_TASKS	5-67
DBA_PART_COL_STATISTICS	5-68
DBA_PART_HISTOGRAMS	5-69
DBA_PART_INDEXES	5-69
DBA_PART_KEY_COLUMNS	5-69
DBA_PART_LOBS	5-69
DBA_PART_TABLES	5-69
DBA_PARTIAL_DROP_TABS	5-69
DBA_PENDING_CONV_TABLES	5-69
DBA_PENDING_TRANSACTIONS	5-70
DBA_PLSQL_OBJECT_SETTINGS	5-70
DBA_POLICIES	5-70
DBA_POLICY_CONTEXTS	5-70
DBA_POLICY_GROUPS	5-70
DBA_PRIV_AUDIT_OPTS	5-70
DBA_PROCEDURES	5-71
DBA_PROFILES	5-71
DBA_PROPAGATION	5-71
DBA_PROXIES	5-71
DBA_PUBLISHED_COLUMNS	5-72
DBA_QUEUE_SCHEDULES	5-72
DBA_QUEUE_SUBSCRIBERS	5-72
DBA_QUEUE_TABLES	5-73
DBA_QUEUES	5-73
DBA_RCHILD	5-73
DBA_RECOVERABLE_SCRIPT	5-73
DBA_RECOVERABLE_SCRIPT_BLOCKS	5-73
DBA_RECOVERABLE_SCRIPT_ERRORS	5-74
DBA_RECOVERABLE_SCRIPT_HIST	5-74
DBA_RECOVERABLE_SCRIPT_PARAMS	5-74
DBA_RECYCLEBIN	5-75
DBA_REDEFINITION_ERRORS	5-76
DBA_REDEFINITION_OBJECTS	5-76
DBA_REFRESH	5-77
DBA_REFRESH_CHILDREN	5-77
DBA_REFS	5-77

DBA_REGISTERED_ARCHIVED_LOG.....	5-77
DBA_REGISTERED_MVIEW_GROUPS.....	5-78
DBA_REGISTERED_MVIEWS.....	5-78
DBA_REGISTRY.....	5-78
DBA_REGISTRY_HIERARCHY.....	5-79
DBA_REGISTRY_HISTORY.....	5-80
DBA_REGISTRY_LOG.....	5-80
DBA_REPAIR_TABLE.....	5-80
DBA_RESOURCE_INCARNATIONS.....	5-81
DBA_RESUMABLE.....	5-81
DBA_REWRITE_EQUIVALENCES.....	5-82
DBA_RGROUP.....	5-82
DBA_ROLE_PRIVS.....	5-83
DBA_ROLES.....	5-83
DBA_ROLLBACK_SEGS.....	5-83
DBA_RSRC_CATEGORIES.....	5-84
DBA_RSRC_CONSUMER_GROUP_PRIVS.....	5-84
DBA_RSRC_CONSUMER_GROUPS.....	5-85
DBA_RSRC_GROUP_MAPPINGS.....	5-85
DBA_RSRC_IO_CALIBRATE.....	5-85
DBA_RSRC_MANAGER_SYSTEM_PRIVS.....	5-86
DBA_RSRC_MAPPING_PRIORITY.....	5-86
DBA_RSRC_PLAN_DIRECTIVES.....	5-87
DBA_RSRC_PLANS.....	5-88
DBA_RULE_SET_RULES.....	5-89
DBA_RULE_SETS.....	5-89
DBA_RULES.....	5-89
DBA_SCHEDULER_CHAIN_RULES.....	5-89
DBA_SCHEDULER_CHAIN_STEPS.....	5-89
DBA_SCHEDULER_CHAINS.....	5-89
DBA_SCHEDULER_CREDENTIALS.....	5-89
DBA_SCHEDULER_DB_DESTS.....	5-90
DBA_SCHEDULER_DESTS.....	5-90
DBA_SCHEDULER_EXTERNAL_DESTS.....	5-90
DBA_SCHEDULER_FILE_WATCHERS.....	5-90
DBA_SCHEDULER_GLOBAL_ATTRIBUTE.....	5-90
DBA_SCHEDULER_GROUP_MEMBERS.....	5-90
DBA_SCHEDULER_GROUPS.....	5-90
DBA_SCHEDULER_JOB_ARGS.....	5-91
DBA_SCHEDULER_JOB_CLASSES.....	5-91
DBA_SCHEDULER_JOB_DESTS.....	5-91
DBA_SCHEDULER_JOB_LOG.....	5-91
DBA_SCHEDULER_JOB_ROLES.....	5-91
DBA_SCHEDULER_JOB_RUN_DETAILS.....	5-92
DBA_SCHEDULER_JOBS.....	5-92
DBA_SCHEDULER_NOTIFICATIONS.....	5-93
DBA_SCHEDULER_PROGRAM_ARGS.....	5-93

DBA_SCHEDULER_PROGRAMS	5-93
DBA_SCHEDULER_REMOTE_DATABASES	5-93
DBA_SCHEDULER_REMOTE_JOBSTATE	5-93
DBA_SCHEDULER_RUNNING_CHAINS	5-93
DBA_SCHEDULER_RUNNING_JOBS	5-93
DBA_SCHEDULER_SCHEDULES	5-94
DBA_SCHEDULER_WINDOW_DETAILS	5-94
DBA_SCHEDULER_WINDOW_GROUPS	5-94
DBA_SCHEDULER_WINDOW_LOG	5-94
DBA_SCHEDULER_WINDOWS	5-94
DBA_SCHEDULER_WINGROUP_MEMBERS	5-94
DBA_SEC_RELEVANT_COLS	5-94
DBA_SECONDARY_OBJECTS	5-95
DBA_SEGMENTS	5-95
DBA_SEGMENTS_OLD	5-96
DBA_SEQUENCES	5-97
DBA_SERVER_REGISTRY	5-97
DBA_SERVICES	5-98
DBA_SOURCE	5-98
DBA_SOURCE_AE	5-98
DBA_SOURCE_TABLES	5-98
DBA_SQL_MANAGEMENT_CONFIG	5-98
DBA_SQL_PATCHES	5-99
DBA_SQL_PLAN_BASELINES	5-99
DBA_SQL_PROFILES	5-100
DBA_SQLJ_TYPE_ATTRS	5-101
DBA_SQLJ_TYPE_METHODS	5-101
DBA_SQLJ_TYPES	5-101
DBA_SQLSET	5-102
DBA_SQLSET_BINDS	5-102
DBA_SQLSET_PLANS	5-102
DBA_SQLSET_REFERENCES	5-102
DBA_SQLSET_STATEMENTS	5-102
DBA_SQLTUNE_BINDS	5-102
DBA_SQLTUNE_PLANS	5-102
DBA_SQLTUNE_RATIONALE_PLAN	5-105
DBA_SQLTUNE_STATISTICS	5-105
DBA_SSCR_CAPTURE	5-106
DBA_SSCR_RESTORE	5-106
DBA_STAT_EXTENSIONS	5-107
DBA_STMT_AUDIT_OPTS	5-107
DBA_STORED_SETTINGS	5-107

6 Static Data Dictionary Views: DBA_STREAMS_ADD_COLUMN to XS_SESSION_ROLES

DBA_STREAMS_ADD_COLUMN	6-1
DBA_STREAMS_ADMINISTRATOR	6-1

DBA_STREAMS_COLUMNS	6-2
DBA_STREAMS_DELETE_COLUMN	6-2
DBA_STREAMS_GLOBAL_RULES	6-2
DBA_STREAMS_KEEP_COLUMNS	6-2
DBA_STREAMS_MESSAGE_CONSUMERS	6-3
DBA_STREAMS_MESSAGE_RULES	6-3
DBA_STREAMS_NEWLY_SUPPORTED	6-3
DBA_STREAMS_RENAME_COLUMN	6-3
DBA_STREAMS_RENAME_SCHEMA	6-4
DBA_STREAMS_RENAME_TABLE	6-4
DBA_STREAMS_RULES	6-4
DBA_STREAMS_SCHEMA_RULES	6-4
DBA_STREAMS_SPLIT_MERGE	6-4
DBA_STREAMS_SPLIT_MERGE_HIST	6-6
DBA_STREAMS_STMT_HANDLERS	6-8
DBA_STREAMS_STMTS	6-8
DBA_STREAMS_TABLE_RULES	6-8
DBA_STREAMS_TP_COMPONENT	6-8
DBA_STREAMS_TP_COMPONENT_LINK	6-9
DBA_STREAMS_TP_COMPONENT_STAT	6-9
DBA_STREAMS_TP_DATABASE	6-10
DBA_STREAMS_TP_PATH_BOTTLENECK	6-10
DBA_STREAMS_TP_PATH_STAT	6-11
DBA_STREAMS_TRANSFORM_FUNCTION	6-11
DBA_STREAMS_TRANSFORMATIONS	6-11
DBA_STREAMS_UNSUPPORTED	6-12
DBA_SUBPART_COL_STATISTICS	6-13
DBA_SUBPART_HISTOGRAMS	6-13
DBA_SUBPART_KEY_COLUMNS	6-13
DBA_SUBPARTITION_TEMPLATES	6-13
DBA_SUBSCR_REGISTRATIONS	6-13
DBA_SUBSCRIBED_COLUMNS	6-14
DBA_SUBSCRIBED_TABLES	6-15
DBA_SUBSCRIPTIONS	6-15
DBA_SYNC_CAPTURE	6-16
DBA_SYNC_CAPTURE_PREPARED_TABS	6-16
DBA_SYNC_CAPTURE_TABLES	6-16
DBA_SYNONYMS	6-16
DBA_SYS_PRIVS	6-16
DBA_TAB_COL_STATISTICS	6-17
DBA_TAB_COLS	6-17
DBA_TAB_COLUMNS	6-17
DBA_TAB_COMMENTS	6-17
DBA_TAB_HISTGRM_PENDING_STATS	6-17
DBA_TAB_HISTOGRAMS	6-17
DBA_TAB_MODIFICATIONS	6-17
DBA_TAB_PARTITIONS	6-18

DBA_TAB_PENDING_STATS	6-18
DBA_TAB_PRIVS	6-18
DBA_TAB_STATISTICS	6-18
DBA_TAB_STAT_PREFS	6-18
DBA_TAB_STATS_HISTORY	6-19
DBA_TAB_SUBPARTITIONS	6-19
DBA_TABLES	6-19
DBA_TABLESPACE_GROUPS	6-19
DBA_TABLESPACE_THRESHOLDS	6-19
DBA_TABLESPACE_USAGE_METRICS	6-20
DBA_TABLESPACES	6-20
DBA_TEMP_FILES	6-22
DBA_TEMP_FREE_SPACE	6-22
DBA_THRESHOLDS	6-23
DBA_TRANSFORMATIONS	6-24
DBA_TRIGGER_COLS	6-24
DBA_TRIGGER_ORDERING	6-24
DBA_TRIGGERS	6-24
DBA_TS_QUOTAS	6-24
DBA_TSM_DESTINATION	6-25
DBA_TSM_SOURCE	6-25
DBA_TSTZ_TAB_COLS	6-26
DBA_TSTZ_TABLES	6-26
DBA_TUNE_MVIEW	6-26
DBA_TYPE_ATTRS	6-27
DBA_TYPE_METHODS	6-27
DBA_TYPE_VERSIONS	6-27
DBA_TYPES	6-27
DBA_UNDO_EXTENTS	6-27
DBA_UNUSED_COL_TABS	6-28
DBA_UPDATABLE_COLUMNS	6-28
DBA_USERS	6-28
DBA_USERS_WITH_DEFPWD	6-29
DBA_USTATS	6-29
DBA_VARRAYS	6-29
DBA_VIEWS	6-29
DBA_VIEWS_AE	6-30
DBA_WAITERS	6-30
DBA_WALLET_ACLS	6-30
DBA_WARNING_SETTINGS	6-30
DBA_WORKLOAD_CAPTURES	6-30
DBA_WORKLOAD_CONNECTION_MAP	6-32
DBA_WORKLOAD_FILTERS	6-32
DBA_WORKLOAD_REPLAY_DIVERGENCE	6-33
DBA_WORKLOAD_REPLAYS	6-34
DBA_XML_INDEXES	6-36
DBA_XML_SCHEMAS	6-36

DBA_XML_TAB_COLS	6-36
DBA_XML_TABLES	6-36
DBA_XML_VIEW_COLS	6-36
DBA_XML_VIEWS	6-37
DBA_XSTREAM_ADMINISTRATOR.....	6-37
DBA_XSTREAM_INBOUND.....	6-37
DBA_XSTREAM_INBOUND_PROGRESS.....	6-37
DBA_XSTREAM_OUT_SUPPORT_MODE	6-37
DBA_XSTREAM_OUTBOUND.....	6-38
DBA_XSTREAM_OUTBOUND_PROGRESS	6-38
DBA_XSTREAM_RULES	6-38
DBFS_CONTENT.....	6-38
DBFS_CONTENT_PROPERTIES	6-40
DBMS_ALERT_INFO.....	6-40
DBMS_LOCK_ALLOCATED	6-40
DEPTREE	6-40
DICT	6-41
DICT_COLUMNS	6-41
DICTIONARY.....	6-41
DM_USER_MODELS.....	6-41
DOCUMENT_LINKS.....	6-43
ERROR_SIZE	6-43
EXCEPTIONS	6-43
FLASHBACK_TRANSACTION_QUERY	6-43
GLOBAL_NAME.....	6-44
HS_ALL_CAPS	6-44
HS_ALL_DD	6-44
HS_ALL_INITS.....	6-45
HS_BASE_CAPS.....	6-45
HS_BASE_DD.....	6-45
HS_CLASS_CAPS	6-45
HS_CLASS_DD	6-46
HS_CLASS_INIT.....	6-46
HS_FDS_CLASS.....	6-46
HS_FDS_INST	6-46
HS_INST_CAPS	6-47
HS_INST_DD	6-47
HS_INST_INIT	6-47
IDEPTREE.....	6-48
IND.....	6-48
INDEX_HISTOGRAM.....	6-48
INDEX_STATS.....	6-48
LOGSTDBY_UNSUPPORTED_TABLES	6-49
MAP_OBJECT.....	6-50
NLS_DATABASE_PARAMETERS	6-50
NLS_INSTANCE_PARAMETERS	6-50
NLS_SESSION_PARAMETERS.....	6-50

OBJ	6-51
PATH_VIEW	6-51
PLAN_TABLE	6-51
PLUGGABLE_SET_CHECK	6-54
PRODUCT_COMPONENT_VERSION	6-55
PROXY_USERS	6-55
PSTUBTBL	6-55
PUBLIC_DEPENDENCY	6-56
PUBLICSYN	6-56
QUEUE_PRIVILEGES	6-56
RECYCLEBIN	6-56
REPORT_COMPONENTS	6-57
REPORT_FILES	6-57
REPORT_FORMATS	6-57
RESOURCE_COST	6-58
RESOURCE_MAP	6-58
RESOURCE_VIEW	6-58
ROLE_ROLE_PRIVS	6-59
ROLE_SYS_PRIVS	6-59
ROLE_TAB_PRIVS	6-59
SCHEDULER_BATCH_ERRORS	6-59
SEQ	6-60
SESSION_CONTEXT	6-60
SESSION_PRIVS	6-60
SESSION_ROLES	6-60
SOURCE_SIZE	6-60
STMT_AUDIT_OPTION_MAP	6-60
SYN	6-61
SYNONYMS	6-61
SYS_OBJECTS	6-61
SYSCATALOG	6-61
SYSFILES	6-61
SYSSEGOBJ	6-61
SYSTEM_PRIVILEGE_MAP	6-61
TAB	6-62
TABLE_PRIVILEGE_MAP	6-62
TABQUOTAS	6-62
TABS	6-62
TRUSTED_SERVERS	6-62
TS_PITR_CHECK	6-63
TS_PITR_OBJECTS_TO_BE_DROPPED	6-63
UNI_PLUGGABLE_SET_CHECK	6-63
USER_ADDM_FDG_BREAKDOWN	6-64
USER_ADDM_FINDINGS	6-64
USER_ADDM_INSTANCES	6-64
USER_ADDM_TASKS	6-64
USER_ADVISOR_ACTIONS	6-64

USER_ADVISOR_DIR_TASK_INST	6-65
USER_ADVISOR_EXEC_PARAMETERS.....	6-65
USER_ADVISOR_EXECUTIONS	6-65
USER_ADVISOR_FDG_BREAKDOWN	6-65
USER_ADVISOR_FINDINGS	6-65
USER_ADVISOR_JOURNAL	6-65
USER_ADVISOR_LOG	6-65
USER_ADVISOR_OBJECTS	6-66
USER_ADVISOR_PARAMETERS	6-66
USER_ADVISOR_RATIONALE.....	6-66
USER_ADVISOR_RECOMMENDATIONS	6-66
USER_ADVISOR_SQLA_REC_SUM	6-66
USER_ADVISOR_SQLA_TABLES	6-66
USER_ADVISOR_SQLA_WK_MAP	6-66
USER_ADVISOR_SQLA_WK_STMTS.....	6-67
USER_ADVISOR_SQLPLANS	6-67
USER_ADVISOR_SQLSTATS	6-67
USER_ADVISOR_SQLW_JOURNAL.....	6-67
USER_ADVISOR_SQLW_PARAMETERS	6-67
USER_ADVISOR_SQLW_STMTS	6-67
USER_ADVISOR_SQLW_SUM.....	6-67
USER_ADVISOR_SQLW_TABLES.....	6-68
USER_ADVISOR_SQLW_TEMPLATES	6-68
USER_ADVISOR_TASKS.....	6-68
USER_ADVISOR_TEMPLATES.....	6-68
USER_ALL_TABLES.....	6-68
USER_AQ_AGENT_PRIVS	6-68
USER_ARGUMENTS.....	6-68
USER_ASSEMBLIES	6-69
USER_ASSOCIATIONS	6-69
USER_ATTRIBUTE_TRANSFORMATIONS.....	6-69
USER_AUDIT_OBJECT.....	6-69
USER_AUDIT_POLICIES	6-69
USER_AUDIT_POLICY_COLUMNS	6-69
USER_AUDIT_SESSION	6-69
USER_AUDIT_STATEMENT	6-70
USER_AUDIT_TRAIL.....	6-70
USER_AW_PS	6-70
USER_AWS.....	6-70
USER_BASE_TABLE_MVIEWS.....	6-70
USER_CATALOG	6-70
USER_CHANGE_NOTIFICATION_REGS	6-70
USER_CLU_COLUMNS.....	6-70
USER_CLUSTER_HASH_EXPRESSIONS	6-71
USER_CLUSTERS.....	6-71
USER_COL_COMMENTS	6-71
USER_COL_PENDING_STATS	6-71

USER_COL_PRIVS	6-71
USER_COL_PRIVS_MADE	6-71
USER_COL_PRIVS_RECD	6-71
USER_COLL_TYPES	6-72
USER_COMPARISON	6-72
USER_COMPARISON_COLUMNS	6-72
USER_COMPARISON_ROW_DIF	6-72
USER_COMPARISON_SCAN	6-72
USER_COMPARISON_SCAN_VALUES	6-72
USER_CONS_COLUMNS	6-72
USER_CONS_OBJ_COLUMNS	6-72
USER_CONSTRAINTS	6-73
USER_CQ_NOTIFICATION_QUERIES	6-73
USER_CUBE_ATTR_VISIBILITY	6-73
USER_CUBE_ATTRIBUTES	6-73
USER_CUBE_BUILD_PROCESSES	6-73
USER_CUBE_CALCULATED_MEMBERS	6-73
USER_CUBE_DIM_LEVELS	6-73
USER_CUBE_DIM_MODELS	6-73
USER_CUBE_DIM_VIEW_COLUMNS	6-74
USER_CUBE_DIM_VIEWS	6-74
USER_CUBE_DIMENSIONALITY	6-74
USER_CUBE_DIMENSIONS	6-74
USER_CUBE_HIER_LEVELS	6-74
USER_CUBE_HIER_VIEW_COLUMNS	6-74
USER_CUBE_HIER_VIEWS	6-74
USER_CUBE_HIERARCHIES	6-74
USER_CUBE_MEASURES	6-74
USER_CUBE_VIEW_COLUMNS	6-75
USER_CUBE_VIEWS	6-75
USER_CUBES	6-75
USER_DATAPUMP_JOBS	6-75
USER_DB_LINKS	6-75
USER_DBFS_HS_FILES	6-75
USER_DEPENDENCIES	6-76
USER_DIM_ATTRIBUTES	6-76
USER_DIM_CHILD_OF	6-76
USER_DIM_HIERARCHIES	6-76
USER_DIM_JOIN_KEY	6-76
USER_DIM_LEVEL_KEY	6-76
USER_DIM_LEVELS	6-76
USER_DIMENSIONS	6-76
USER_EDITIONING_VIEW_COLS	6-76
USER_EDITIONING_VIEW_COLS_AE	6-77
USER_EDITIONING_VIEWS	6-77
USER_EDITIONING_VIEWS_AE	6-77
USER_ENCRYPTED_COLUMNS	6-77

USER_EPG_DAD_AUTHORIZATION.....	6-77
USER_ERRORS	6-77
USER_ERRORS_AE.....	6-77
USER_EVALUATION_CONTEXT_TABLES	6-78
USER_EVALUATION_CONTEXT_VARS.....	6-78
USER_EVALUATION_CONTEXTS	6-78
USER_EXTENTS	6-78
USER_EXTERNAL_LOCATIONS	6-78
USER_EXTERNAL_TABLES.....	6-78
USER_FILE_GROUP_EXPORT_INFO.....	6-78
USER_FILE_GROUP_FILES	6-79
USER_FILE_GROUP_TABLES.....	6-79
USER_FILE_GROUP_TABLESPACES.....	6-79
USER_FILE_GROUP_VERSIONS.....	6-79
USER_FILE_GROUPS.....	6-79
USER_FLASHBACK_ARCHIVE	6-79
USER_FLASHBACK_ARCHIVE_TABLES.....	6-80
USER_FLASHBACK_TXN_REPORT.....	6-80
USER_FLASHBACK_TXN_STATE	6-80
USER_FREE_SPACE.....	6-80
USER_HISTOGRAMS.....	6-80
USER_IDENTIFIERS.....	6-80
USER_IND_COLUMNS	6-80
USER_IND_EXPRESSIONS	6-81
USER_IND_PARTITIONS	6-81
USER_IND_PENDING_STATS	6-81
USER_IND_STATISTICS.....	6-81
USER_IND_SUBPARTITIONS.....	6-81
USER_INDEXES.....	6-81
USER_INDEXTYPE_ARRAYTYPES.....	6-81
USER_INDEXTYPE_COMMENTS	6-81
USER_INDEXTYPE_OPERATORS	6-82
USER_INDEXTYPES	6-82
USER_INTERNAL_TRIGGERS.....	6-82
USER_JAVA_ARGUMENTS.....	6-82
USER_JAVA_CLASSES.....	6-82
USER_JAVA_COMPILER_OPTIONS	6-82
USER_JAVA_DERIVATIONS	6-82
USER_JAVA_FIELDS.....	6-83
USER_JAVA_IMPLEMENTES	6-83
USER_JAVA_INNERS	6-83
USER_JAVA_LAYOUTS.....	6-83
USER_JAVA_METHODS.....	6-83
USER_JAVA_NCOMPS.....	6-83
USER_JAVA_POLICY.....	6-83
USER_JAVA_RESOLVERS	6-84
USER_JAVA_THROWS	6-84

USER_JOBS.....	6-84
USER_JOIN_IND_COLUMNS	6-84
USER_LIBRARIES.....	6-84
USER_LOB_PARTITIONS.....	6-84
USER_LOB_SUBPARTITIONS.....	6-84
USER_LOB_TEMPLATES	6-84
USER_LOBS	6-85
USER_LOG_GROUP_COLUMNS	6-85
USER_LOG_GROUPS	6-85
USER_MEASURE_FOLDER_CONTENTS.....	6-85
USER_MEASURE_FOLDERS	6-85
USER_METHOD_PARAMS	6-85
USER_METHOD_RESULTS.....	6-85
USER_MINING_MODEL_ATTRIBUTES	6-85
USER_MINING_MODEL_SETTINGS	6-86
USER_MINING_MODELS.....	6-86
USER_MVIEW_AGGREGATES	6-86
USER_MVIEW_ANALYSIS	6-86
USER_MVIEW_COMMENTS.....	6-86
USER_MVIEW_DETAIL_PARTITION.....	6-86
USER_MVIEW_DETAIL_RELATIONS.....	6-87
USER_MVIEW_DETAIL_SUBPARTITION	6-87
USER_MVIEW_JOINS.....	6-87
USER_MVIEW_KEYS	6-87
USER_MVIEW_LOGS	6-87
USER_MVIEW_REFRESH_TIMES	6-87
USER_MVIEWS	6-87
USER_NESTED_TABLE_COLS	6-87
USER_NESTED_TABLES.....	6-88
USER_NETWORK_ACL_PRIVILEGES	6-88
USER_OBJ_AUDIT_OPTS.....	6-88
USER_OBJ_COLATTRS	6-88
USER_OBJECT_SIZE	6-88
USER_OBJECT_TABLES	6-88
USER_OBJECTS	6-88
USER_OBJECTS_AE	6-89
USER_OPANCILLARY	6-89
USER_OPARGUMENTS	6-89
USER_OPBINDINGS.....	6-89
USER_OPERATOR_COMMENTS	6-89
USER_OPERATORS.....	6-89
USER_OUTLINE_HINTS.....	6-89
USER_OUTLINES.....	6-89
USER_PARALLEL_EXECUTE_CHUNKS	6-90
USER_PARALLEL_EXECUTE_TASKS	6-90
USER_PART_COL_STATISTICS	6-90
USER_PART_HISTOGRAMS	6-90

USER_PART_INDEXES	6-90
USER_PART_KEY_COLUMNS.....	6-90
USER_PART_LOBS.....	6-90
USER_PART_TABLES	6-91
USER_PARTIAL_DROP_TABS.....	6-91
USER_PASSWORD_LIMITS.....	6-91
USER_PENDING_CONV_TABLES	6-91
USER_PLSQL_OBJECT_SETTINGS	6-91
USER_POLICIES.....	6-91
USER_POLICY_CONTEXTS	6-91
USER_POLICY_GROUPS	6-92
USER_PROCEDURES.....	6-92
USER_PROXIES	6-92
USER_PUBLISHED_COLUMNS.....	6-92
USER_QUEUE_SCHEDULES.....	6-92
USER_QUEUE_SUBSCRIBERS	6-92
USER_QUEUE_TABLES	6-92
USER_QUEUES	6-93
USER_RECYCLEBIN.....	6-93
USER_REFRESH	6-93
USER_REFRESH_CHILDREN	6-93
USER_REFS.....	6-93
USER_REGISTERED_MVIEWS.....	6-93
USER_REGISTRY	6-93
USER_RESOURCE_LIMITS.....	6-93
USER_RESUMABLE	6-94
USER_REWRITE_EQUIVALENCES.....	6-94
USER_ROLE_PRIVS	6-94
USER_RSRC_CONSUMER_GROUP_PRIVS.....	6-94
USER_RSRC_MANAGER_SYSTEM_PRIVS.....	6-94
USER_RULE_SET_RULES	6-94
USER_RULE_SETS	6-95
USER_RULES.....	6-95
USER_SCHEDULER_CHAIN_RULES	6-95
USER_SCHEDULER_CHAIN_STEPS.....	6-95
USER_SCHEDULER_CHAINS.....	6-95
USER_SCHEDULER_CREDENTIALS	6-95
USER_SCHEDULER_DB_DESTS	6-95
USER_SCHEDULER_DESTS	6-96
USER_SCHEDULER_FILE_WATCHERS.....	6-96
USER_SCHEDULER_GROUP_MEMBERS.....	6-96
USER_SCHEDULER_GROUPS	6-96
USER_SCHEDULER_JOB_ARGS	6-96
USER_SCHEDULER_JOB_DESTS.....	6-96
USER_SCHEDULER_JOB_LOG	6-96
USER_SCHEDULER_JOB_RUN_DETAILS	6-97
USER_SCHEDULER_JOBS.....	6-97

USER_SCHEDULER_NOTIFICATIONS	6-97
USER_SCHEDULER_PROGRAM_ARGS	6-97
USER_SCHEDULER_PROGRAMS	6-97
USER_SCHEDULER_REMOTE_JOBSTATE	6-97
USER_SCHEDULER_RUNNING_CHAINS	6-97
USER_SCHEDULER_RUNNING_JOBS	6-98
USER_SCHEDULER_SCHEDULES	6-98
USER_SEC_RELEVANT_COLS	6-98
USER_SECONDARY_OBJECTS	6-98
USER_SEGMENTS	6-98
USER_SEQUENCES	6-98
USER_SOURCE	6-98
USER_SOURCE_AE	6-99
USER_SOURCE_TABLES	6-99
USER_SQLJ_TYPE_ATTRS	6-99
USER_SQLJ_TYPE_METHODS	6-99
USER_SQLJ_TYPES	6-99
USER_SQLSET	6-99
USER_SQLSET_BINDS	6-99
USER_SQLSET_PLANS	6-100
USER_SQLSET_REFERENCES	6-100
USER_SQLSET_STATEMENTS	6-100
USER_SQLTUNE_BINDS	6-100
USER_SQLTUNE_PLANS	6-100
USER_SQLTUNE_RATIONALE_PLAN	6-100
USER_SQLTUNE_STATISTICS	6-100
USER_STAT_EXTENSIONS	6-101
USER_STORED_SETTINGS	6-101
USER_SUBPART_COL_STATISTICS	6-101
USER_SUBPART_HISTOGRAMS	6-101
USER_SUBPART_KEY_COLUMNS	6-101
USER_SUBPARTITION_TEMPLATES	6-101
USER_SUBSCR_REGISTRATIONS	6-101
USER_SUBSCRIBED_COLUMNS	6-102
USER_SUBSCRIBED_TABLES	6-102
USER_SUBSCRIPTIONS	6-102
USER_SYNONYMS	6-102
USER_SYS_PRIVS	6-102
USER_TAB_COL_STATISTICS	6-102
USER_TAB_COLS	6-102
USER_TAB_COLUMNS	6-103
USER_TAB_COMMENTS	6-103
USER_TAB_HISTGRM_PENDING_STATS	6-103
USER_TAB_HISTOGRAMS	6-103
USER_TAB_MODIFICATIONS	6-103
USER_TAB_PARTITIONS	6-103
USER_TAB_PENDING_STATS	6-104

USER_TAB_PRIVS	6-104
USER_TAB_PRIVS_MADE.....	6-104
USER_TAB_PRIVS_RECD.....	6-104
USER_TAB_STAT_PREFS	6-104
USER_TAB_STATISTICS	6-104
USER_TAB_STATS_HISTORY.....	6-104
USER_TAB_SUBPARTITIONS	6-104
USER_TABLES.....	6-105
USER_TABLESPACES.....	6-105
USER_TRANSFORMATIONS	6-105
USER_TRIGGER_COLS.....	6-105
USER_TRIGGER_ORDERING.....	6-105
USER_TRIGGERS	6-105
USER_TS_QUOTAS	6-106
USER_TSTZ_TAB_COLS	6-106
USER_TSTZ_TABLES	6-106
USER_TUNE_MVIEW	6-106
USER_TYPE_ATTRS	6-106
USER_TYPE_METHODS	6-106
USER_TYPE_VERSIONS	6-106
USER_TYPES	6-107
USER_UNUSED_COL_TABS.....	6-107
USER_UPDATABLE_COLUMNS.....	6-107
USER_USERS.....	6-107
USER_USTATS	6-107
USER_VARRAYS.....	6-107
USER_VIEWS	6-107
USER_VIEWS_AE.....	6-108
USER_WARNING_SETTINGS.....	6-108
USER_XML_INDEXES.....	6-108
USER_XML_SCHEMAS	6-108
USER_XML_TAB_COLS.....	6-108
USER_XML_TABLES	6-108
USER_XML_VIEW_COLS.....	6-108
USER_XML_VIEWS	6-108
XS_SESSION_ROLES	6-109

Part III Dynamic Performance Views

7 Dynamic Performance (V\$) Views: V\$ACCESS to V\$HVMMASTER_INFO

About Dynamic Performance Views	7-1
V\$ Views.....	7-2
GV\$ Views.....	7-2
Dynamic Performance View Descriptions	7-2
V\$ACCESS.....	7-2
V\$ACTIVE_INSTANCES	7-2
V\$ACTIVE_SERVICES	7-3

V\$ACTIVE_SESS_POOL_MTH.....	7-3
V\$ACTIVE_SESSION_HISTORY	7-3
V\$ADVISOR_PROGRESS.....	7-7
V\$ALERT_TYPES.....	7-8
V\$AQ	7-8
V\$ARCHIVE	7-9
V\$ARCHIVE_DEST.....	7-9
V\$ARCHIVE_DEST_STATUS	7-12
V\$ARCHIVE_GAP.....	7-14
V\$ARCHIVE_PROCESSES.....	7-14
V\$ARCHIVED_LOG	7-14
V\$ASM_ACFS_ENCRYPTION_INFO	7-16
V\$ASM_ACFS_SECURITY_INFO	7-17
V\$ASM_ACFSSNAPSHOTS	7-17
V\$ASM_ACFSVOLUMES.....	7-17
V\$ASM_ALIAS.....	7-17
V\$ASM_ATTRIBUTE.....	7-18
V\$ASM_CLIENT.....	7-18
V\$ASM_DISK.....	7-19
V\$ASM_DISK_IOSTAT	7-22
V\$ASM_DISK_STAT.....	7-22
V\$ASM_DISKGROUP.....	7-23
V\$ASM_DISKGROUP_STAT	7-24
V\$ASM_FILE.....	7-24
V\$ASM_FILESYSTEM.....	7-25
V\$ASM_OPERATION	7-26
V\$ASM_TEMPLATE	7-27
V\$ASM_USER	7-27
V\$ASM_USERGROUP	7-27
V\$ASM_USERGROUP_MEMBER.....	7-28
V\$ASM_VOLUME.....	7-28
V\$ASM_VOLUME_STAT.....	7-29
V\$AW_AGGREGATE_OP.....	7-29
V\$AW_ALLOCATE_OP	7-29
V\$AW_CALC.....	7-30
V\$AW_LONGOPS	7-30
V\$AW_OLAP.....	7-31
V\$AW_SESSION_INFO.....	7-32
V\$BACKUP	7-32
V\$BACKUP_ARCHIVELOG_DETAILS	7-33
V\$BACKUP_ARCHIVELOG_SUMMARY	7-33
V\$BACKUP_ASYNC_IO	7-34
V\$BACKUP_CONTROLFILE_DETAILS	7-35
V\$BACKUP_CONTROLFILE_SUMMARY	7-35
V\$BACKUP_COPY_DETAILS	7-36
V\$BACKUP_COPY_SUMMARY	7-37
V\$BACKUP_CORRUPTION	7-37

V\$BACKUP_DATAFILE	7-38
V\$BACKUP_DATAFILE_DETAILS.....	7-39
V\$BACKUP_DATAFILE_SUMMARY	7-40
V\$BACKUP_DEVICE.....	7-40
V\$BACKUP_FILES	7-41
V\$BACKUP_PIECE.....	7-43
V\$BACKUP_PIECE_DETAILS	7-44
V\$BACKUP_REDOLOG	7-45
V\$BACKUP_SET.....	7-46
V\$BACKUP_SET_DETAILS	7-46
V\$BACKUP_SET_SUMMARY	7-48
V\$BACKUP_SPFILE.....	7-48
V\$BACKUP_SPFILE_DETAILS	7-48
V\$BACKUP_SPFILE_SUMMARY.....	7-49
V\$BACKUP_SYNC_IO	7-49
V\$BGPROCESS.....	7-50
V\$BH.....	7-50
V\$BLOCK_CHANGE_TRACKING	7-51
V\$BLOCKING_QUIESCE.....	7-51
V\$BUFFER_POOL.....	7-52
V\$BUFFER_POOL_STATISTICS.....	7-52
V\$BUFFERED_PUBLISHERS.....	7-53
V\$BUFFERED_QUEUES.....	7-54
V\$BUFFERED_SUBSCRIBERS	7-55
V\$CACHE.....	7-56
V\$CACHE_LOCK	7-57
V\$CACHE_TRANSFER	7-59
V\$CIRCUIT	7-59
V\$CLASS_CACHE_TRANSFER.....	7-60
V\$CLIENT_STATS.....	7-61
V\$CLUSTER_INTERCONNECTS.....	7-61
V\$CONFIGURED_INTERCONNECTS	7-61
V\$CONTEXT.....	7-62
V\$CONTROLFILE	7-62
V\$CONTROLFILE_RECORD_SECTION.....	7-62
V\$COPY_CORRUPTION	7-63
V\$CORRUPT_XID_LIST	7-64
V\$CPOOL_CC_INFO	7-64
V\$CPOOL_CC_STATS.....	7-64
V\$CPOOL_CONN_INFO	7-65
V\$CPOOL_STATS.....	7-65
V\$CR_BLOCK_SERVER.....	7-66
V\$CURRENT_BLOCK_SERVER	7-67
V\$DATABASE.....	7-68
V\$DATABASE_BLOCK_CORRUPTION.....	7-73
V\$DATABASE_INCARNATION	7-73
V\$DATAFILE.....	7-74

V\$DATAFILE_COPY	7-75
V\$DATAFILE_HEADER	7-77
V\$DATAGUARD_CONFIG	7-78
V\$DATAGUARD_STATS	7-78
V\$DATAGUARD_STATUS	7-79
V\$DB_CACHE_ADVICE	7-79
V\$DB_OBJECT_CACHE	7-80
V\$DB_PIPES	7-81
V\$DB_TRANSPORTABLE_PLATFORM	7-81
V\$DBFILE	7-81
V\$DBLINK	7-82
V\$DELETED_OBJECT	7-82
V\$DISPATCHER	7-83
V\$DISPATCHER_CONFIG	7-84
V\$DISPATCHER_RATE	7-85
V\$DNFS_CHANNELS	7-88
V\$DNFS_FILES	7-88
V\$DNFS_SERVERS	7-89
V\$DNFS_STATS	7-89
V\$DYNAMIC_REMASTER_STATS	7-90
V\$EMON	7-90
V\$ENABLEDPRIVS	7-91
V\$ENCRYPTED_TABLESPACES	7-91
V\$ENCRYPTION_WALLET	7-92
V\$ENQUEUE_LOCK	7-92
V\$ENQUEUE_STAT	7-93
V\$ENQUEUE_STATISTICS	7-93
V\$EVENT_HISTOGRAM	7-94
V\$EVENT_NAME	7-94
V\$EVENTMETRIC	7-94
V\$EXECUTION	7-95
V\$FALSE_PING	7-95
V\$FAST_START_SERVERS	7-96
V\$FAST_START_TRANSACTIONS	7-96
V\$FILE_CACHE_TRANSFER	7-97
V\$FILE_HISTOGRAM	7-97
V\$FILEMETRIC	7-97
V\$FILEMETRIC_HISTORY	7-98
V\$FILESPACE_USAGE	7-98
V\$FILESTAT	7-99
V\$FIXED_TABLE	7-99
V\$FIXED_VIEW_DEFINITION	7-99
V\$FLASHBACK_DATABASE_LOG	7-100
V\$FLASHBACK_DATABASE_LOGFILE	7-100
V\$FLASHBACK_DATABASE_STAT	7-100
V\$FLASHBACK_TXN_GRAPH	7-101
V\$FLASHBACK_TXN_MODS	7-101

V\$FOREIGN_ARCHIVED_LOG	7-102
V\$FS_FAILOVER_STATS.....	7-104
V\$GC_ELEMENT	7-104
V\$GC_ELEMENTS_WITH_COLLISIONS	7-105
V\$GCSHVMaster_INFO	7-105
V\$GCSPFMaster_INFO	7-105
V\$GES_BLOCKING_ENQUEUE.....	7-105
V\$GES_CONVERT_LOCAL	7-106
V\$GES_CONVERT_REMOTE	7-107
V\$GES_ENQUEUE	7-108
V\$GES_LATCH	7-108
V\$GES_RESOURCE	7-109
V\$GES_STATISTICS	7-109
V\$GLOBAL_BLOCKED_LOCKS	7-109
V\$GLOBAL_TRANSACTION	7-109
V\$HM_CHECK.....	7-110
V\$HM_CHECK_PARAM.....	7-111
V\$HM_FINDING	7-111
V\$HM_INFO	7-112
V\$HM_RECOMMENDATION	7-112
V\$HM_RUN	7-113
V\$HS_AGENT	7-113
V\$HS_PARAMETER	7-114
V\$HS_SESSION	7-114
V\$HVMaster_INFO	7-114

8 Dynamic Performance (V\$) Views: V\$INDEXED_FIXED_COLUMN to V\$RULE_SET_AGGREGATE_STATS

V\$INDEXED_FIXED_COLUMN	8-1
V\$INSTANCE	8-1
V\$INSTANCE_CACHE_TRANSFER.....	8-2
V\$INSTANCE_RECOVERY	8-3
V\$IO_CALIBRATION_STATUS	8-5
V\$IOFUNCMETRIC	8-5
V\$IOFUNCMETRIC_HISTORY	8-5
V\$IOSTAT_CONSUMER_GROUP	8-6
V\$IOSTAT_FILE	8-6
V\$IOSTAT_FUNCTION	8-7
V\$IOSTAT_FUNCTION_DETAIL	8-8
V\$IOSTAT_NETWORK.....	8-9
V\$JAVA_LIBRARY_CACHE_MEMORY	8-9
V\$JAVA_POOL_ADVICE	8-9
V\$LATCH.....	8-10
V\$LATCH_CHILDREN	8-11
V\$LATCH_MISSES	8-11
V\$LATCH_PARENT	8-12
V\$LATCHHOLDER	8-12

V\$LATCHNAME.....	8-12
V\$LIBCACHE_LOCKS	8-12
V\$LIBRARY_CACHE_MEMORY	8-13
V\$LIBRARYCACHE	8-13
V\$LICENSE	8-14
V\$LOADISTAT	8-14
V\$LOADPSTAT	8-15
V\$LOCK	8-15
V\$LOCK_ACTIVITY	8-16
V\$LOCK_TYPE.....	8-16
V\$LOCKED_OBJECT.....	8-17
V\$LOG	8-17
V\$LOG_HISTORY	8-18
V\$LOGFILE	8-18
V\$LOGHIST	8-19
V\$LOGMNR_CONTENTS	8-19
V\$LOGMNR_DICTIONARY	8-23
V\$LOGMNR_DICTIONARY_LOAD	8-24
V\$LOGMNR_LATCH	8-24
V\$LOGMNR_LOGS	8-25
V\$LOGMNR_PARAMETERS	8-26
V\$LOGMNR_PROCESS.....	8-26
V\$LOGMNR_SESSION	8-27
V\$LOGMNR_STATS.....	8-28
V\$LOGSTDBY	8-29
V\$LOGSTDBY_PROCESS.....	8-30
V\$LOGSTDBY_PROGRESS.....	8-31
V\$LOGSTDBY_STATE	8-31
V\$LOGSTDBY_STATS	8-31
V\$LOGSTDBY_TRANSACTION.....	8-33
V\$MANAGED_STANDBY	8-34
V\$MAP_COMP_LIST	8-35
V\$MAP_ELEMENT	8-35
V\$MAP_EXT_ELEMENT.....	8-36
V\$MAP_FILE.....	8-36
V\$MAP_FILE_EXTENT	8-37
V\$MAP_FILE_IO_STACK.....	8-37
V\$MAP_LIBRARY	8-38
V\$MAP_SUBELEMENT	8-38
V\$MEMORY_CURRENT_RESIZE_OPS.....	8-38
V\$MEMORY_DYNAMIC_COMPONENTS.....	8-39
V\$MEMORY_RESIZE_OPS	8-40
V\$MEMORY_TARGET_ADVICE	8-40
V\$METRIC	8-41
V\$METRICGROUP	8-42
V\$METRIC_HISTORY.....	8-42
V\$METRICNAME	8-43

V\$MTTR_TARGET_ADVICE	8-43
V\$MUTEX_SLEEP	8-43
V\$MUTEX_SLEEP_HISTORY	8-44
V\$MVREFRESH	8-44
V\$MYSTAT	8-45
V\$NFS_CLIENTS	8-45
V\$NFS_LOCKS	8-45
V\$NFS_OPEN_FILES	8-45
V\$NLS_PARAMETERS	8-46
V\$NLS_VALID_VALUES	8-46
V\$OBJECT_DEPENDENCY	8-46
V\$OBJECT_PRIVILEGE	8-47
V\$OBJECT_USAGE	8-47
V\$OBSOLETE_BACKUP_FILES	8-47
V\$OBSOLETE_PARAMETER	8-49
V\$OFFLINE_RANGE	8-49
V\$OPEN_CURSOR	8-50
V\$OPTION	8-50
V\$OSSTAT	8-51
V\$PARALLEL_DEGREE_LIMIT_MTH	8-52
V\$PARAMETER	8-52
V\$PARAMETER_VALID_VALUES	8-53
V\$PARAMETER2	8-53
V\$PERSISTENT_PUBLISHERS	8-55
V\$PERSISTENT_QMN_CACHE	8-55
V\$PERSISTENT_QUEUES	8-56
V\$PERSISTENT_SUBSCRIBERS	8-57
V\$PGA_TARGET_ADVICE	8-58
V\$PGA_TARGET_ADVICE_HISTOGRAM	8-59
V\$PGASTAT	8-60
V\$PQ_SESSTAT	8-61
V\$PQ_SLAVE	8-62
V\$PQ_SYSSTAT	8-62
V\$PQ_TQSTAT	8-63
V\$PROCESS	8-64
V\$PROCESS_MEMORY	8-64
V\$PROPAGATION_RECEIVER	8-65
V\$PROPAGATION_SENDER	8-65
V\$PROXY_ARCHIVEDLOG	8-67
V\$PROXY_ARCHIVELOG_DETAILS	8-68
V\$PROXY_ARCHIVELOG_SUMMARY	8-68
V\$PROXY_COPY_DETAILS	8-69
V\$PROXY_COPY_SUMMARY	8-70
V\$PROXY_DATAFILE	8-70
V\$PWFILE_USERS	8-72
V\$PX_INSTANCE_GROUP	8-72
V\$PX_PROCESS	8-73

V\$PX_PROCESS_SYSSTAT	8-73
V\$PX_SESSION.....	8-74
V\$PX_SESSTAT	8-75
V\$QMON_COORDINATOR_STATS	8-75
V\$QMON_SERVER_STATS	8-76
V\$QMON_TASK_STATS	8-77
V\$QMON_TASKS	8-77
V\$QUEUE	8-78
V\$QUEUEING_MTH	8-78
V\$RECOVER_FILE	8-78
V\$RECOVERY_AREA_USAGE	8-78
V\$RECOVERY_FILE_DEST	8-79
V\$RECOVERY_FILE_STATUS	8-79
V\$RECOVERY_LOG	8-80
V\$RECOVERY_PROGRESS	8-80
V\$RECOVERY_STATUS.....	8-80
V\$REDO_DEST_RESP_HISTOGRAM.....	8-81
V\$REPLPROP	8-81
V\$REPLQUEUE.....	8-82
V\$REQDIST	8-83
V\$RESERVED_WORDS	8-83
V\$RESOURCE	8-83
V\$RESOURCE_LIMIT	8-84
V\$RESTORE_POINT	8-84
V\$RESULT_CACHE_DEPENDENCY.....	8-85
V\$RESULT_CACHE_MEMORY	8-85
V\$RESULT_CACHE_OBJECTS	8-85
V\$RESULT_CACHE_STATISTICS.....	8-86
V\$RMAN_BACKUP_JOB_DETAILS	8-87
V\$RMAN_BACKUP_SUBJOB_DETAILS.....	8-88
V\$RMAN_BACKUP_TYPE.....	8-89
V\$RMAN_COMPRESSION_ALGORITHM.....	8-90
V\$RMAN_CONFIGURATION	8-90
V\$RMAN_ENCRYPTION_ALGORITHMS	8-91
V\$RMAN_OUTPUT	8-91
V\$RMAN_STATUS.....	8-91
V\$ROLLNAME.....	8-92
V\$ROLLSTAT	8-92
V\$ROWCACHE.....	8-93
V\$ROWCACHE_PARENT	8-94
V\$ROWCACHE_SUBORDINATE	8-94
V\$RSRC_CONS_GROUP_HISTORY	8-95
V\$RSRC_CONSUMER_GROUP	8-96
V\$RSRC_CONSUMER_GROUP_CPU_MTH.....	8-98
V\$RSRC_PLAN	8-99
V\$RSRC_PLAN_CPU_MTH.....	8-100
V\$RSRC_PLAN_HISTORY.....	8-100

V\$RSRC_SESSION_INFO	8-101
V\$RSRCMGRMETRIC	8-104
V\$RSRCMGRMETRIC_HISTORY	8-105
V\$RULE	8-105
V\$RULE_SET	8-105
V\$RULE_SET_AGGREGATE_STATS	8-106

9 Dynamic Performance (V\$) Views: V\$\$SCHEDULER_RUNNING_JOBS to V\$\$XSTREAM_TRANSACTION

V\$\$SCHEDULER_RUNNING_JOBS.....	9-1
V\$\$SECUREFILE_TIMER	9-1
V\$\$SEGMENT_STATISTICS	9-2
V\$\$SEGSTAT	9-2
V\$\$SEGSTAT_NAME.....	9-2
V\$\$SERV_MOD_ACT_STATS	9-3
V\$\$SERVICE_EVENT	9-3
V\$\$SERVICE_STATS.....	9-3
V\$\$SERVICE_WAIT_CLASS	9-4
V\$\$SERVICEMETRIC.....	9-4
V\$\$SERVICEMETRIC_HISTORY	9-5
V\$\$SERVICES.....	9-5
V\$\$SES_OPTIMIZER_ENV	9-6
V\$\$SESS_IO	9-6
V\$\$SESS_TIME_MODEL.....	9-6
V\$\$SESSION.....	9-8
V\$\$SESSION_BLOCKERS.....	9-15
V\$\$SESSION_CONNECT_INFO	9-15
V\$\$SESSION_CURSOR_CACHE.....	9-16
V\$\$SESSION_EVENT	9-16
V\$\$SESSION_FIX_CONTROL	9-17
V\$\$SESSION_LONGOPS	9-17
V\$\$SESSION_OBJECT_CACHE.....	9-18
V\$\$SESSION_WAIT	9-19
V\$\$SESSION_WAIT_CLASS	9-20
V\$\$SESSION_WAIT_HISTORY	9-21
V\$\$SESSMETRIC.....	9-21
V\$\$SESSTAT	9-21
V\$\$SGA	9-22
V\$\$SGA_CURRENT_RESIZE_OPS	9-22
V\$\$SGA_DYNAMIC_COMPONENTS	9-22
V\$\$SGA_DYNAMIC_FREE_MEMORY	9-23
V\$\$SGA_RESIZE_OPS	9-23
V\$\$SGA_TARGET_ADVICE.....	9-24
V\$\$SGAINFO	9-24
V\$\$SGASTAT.....	9-24
V\$\$SHARED_POOL_ADVICE	9-25
V\$\$SHARED_POOL_RESERVED	9-25

V\$SHARED_SERVER	9-26
V\$SHARED_SERVER_MONITOR	9-26
V\$SORT_SEGMENT	9-27
V\$SPPARAMETER	9-28
V\$SQL	9-28
V\$SQL_BIND_CAPTURE	9-31
V\$SQL_BIND_DATA	9-32
V\$SQL_BIND_METADATA	9-33
V\$SQL_CS_HISTOGRAM	9-33
V\$SQL_CS_SELECTIVITY	9-33
V\$SQL_CS_STATISTICS	9-34
V\$SQL_CURSOR	9-34
V\$SQL_JOIN_FILTER	9-35
V\$SQL_MONITOR	9-35
V\$SQL_OPTIMIZER_ENV	9-38
V\$SQL_PLAN	9-38
V\$SQL_PLAN_MONITOR	9-40
V\$SQL_PLAN_STATISTICS	9-42
V\$SQL_PLAN_STATISTICS_ALL	9-43
V\$SQL_REDIRECTION	9-46
V\$SQL_SHARED_CURSOR	9-46
V\$SQL_SHARED_MEMORY	9-49
V\$SQL_WORKAREA	9-49
V\$SQL_WORKAREA_ACTIVE	9-50
V\$SQL_WORKAREA_HISTOGRAM	9-52
V\$SQLAREA	9-52
V\$SQLAREA_PLAN_HASH	9-55
V\$SQLCOMMAND	9-58
V\$SQLFN_ARG_METADATA	9-58
V\$SQLFN_METADATA	9-58
V\$SQLSTATS	9-59
V\$SQLSTATS_PLAN_HASH	9-61
V\$SQLTEXT	9-61
V\$SQLTEXT_WITH_NEWLINES	9-61
V\$STANDBY_EVENT_HISTOGRAM	9-62
V\$STANDBY_LOG	9-62
V\$STATISTICS_LEVEL	9-63
V\$STATNAME	9-63
V\$STREAMS_APPLY_COORDINATOR	9-64
V\$STREAMS_APPLY_READER	9-65
V\$STREAMS_APPLY_SERVER	9-67
V\$STREAMS_CAPTURE	9-69
V\$STREAMS_MESSAGE_TRACKING	9-71
V\$STREAMS_POOL_ADVICE	9-72
V\$STREAMS_POOL_STATISTICS	9-73
V\$STREAMS_TRANSACTION	9-73
V\$SUBCACHE	9-74

V\$SUBSCR_REGISTRATION_STATS	9-74
V\$SYS_OPTIMIZER_ENV	9-75
V\$SYS_TIME_MODEL	9-76
V\$SYSAUX_OCCUPANTS	9-76
V\$SYSMETRIC	9-76
V\$SYSMETRIC_HISTORY	9-77
V\$SYSMETRIC_SUMMARY	9-77
V\$SYSSTAT	9-77
V\$SYSTEM_CURSOR_CACHE	9-78
V\$SYSTEM_EVENT	9-78
V\$SYSTEM_FIX_CONTROL	9-79
V\$SYSTEM_PARAMETER	9-79
V\$SYSTEM_PARAMETER2	9-80
V\$SYSTEM_WAIT_CLASS	9-81
V\$TABLESPACE	9-82
V\$TEMP_CACHE_TRANSFER	9-82
V\$TEMP_EXTENT_MAP	9-83
V\$TEMP_EXTENT_POOL	9-83
V\$TEMP_SPACE_HEADER	9-83
V\$TEMPFILE	9-84
V\$TEMPORARY_LOBS	9-84
V\$TEMPSEG_USAGE	9-84
V\$TEMPSTAT	9-85
V\$THREAD	9-85
V\$THRESHOLD_TYPES	9-86
V\$TIMER	9-86
V\$TIMEZONE_NAMES	9-87
V\$TOPLEVELCALL	9-87
V\$TRANSACTION	9-87
V\$TRANSACTION_ENQUEUE	9-88
V\$TRANSPORTABLE_PLATFORM	9-89
V\$TYPE_SIZE	9-89
V\$UNDOSTAT	9-89
V\$UNUSABLE_BACKUPFILE_DETAILS	9-90
V\$VERSION	9-91
V\$VPD_POLICY	9-91
V\$WAIT_CHAINS	9-92
V\$WAITCLASSMETRIC	9-93
V\$WAITCLASSMETRIC_HISTORY	9-93
V\$WAITSTAT	9-94
V\$WALLET	9-94
V\$WORKLOAD_REPLAY_THREAD	9-94
V\$XML_AUDIT_TRAIL	9-95
V\$XSTREAM_CAPTURE	9-97
V\$XSTREAM_MESSAGE_TRACKING	9-100
V\$XSTREAM_OUTBOUND_SERVER	9-100
V\$XSTREAM_TRANSACTION	9-103

A Database Limits

Datatype Limits	A-1
Physical Database Limits	A-2
Logical Database Limits	A-3
Process and Runtime Limits	A-4

B SQL Scripts

Creating the Data Dictionary	B-1
Creating Additional Data Dictionary Structures	B-2
The "NO" Scripts	B-4
Upgrade and Downgrade Scripts	B-4
Java Scripts	B-5

C Oracle Wait Events

Classes of Wait Events	C-1
Descriptions of Common Wait Event Parameters	C-2
Descriptions of Wait Events	C-5
alter system set dispatcher	C-5
batched allocate scn lock request	C-5
BFILE check if exists	C-5
BFILE check if open	C-5
BFILE closure	C-5
BFILE get length	C-6
BFILE get name object	C-6
BFILE get path object	C-6
BFILE internal seek	C-6
BFILE open	C-6
BFILE read	C-7
broadcast mesg queue transition	C-7
broadcast mesg recovery queue transition	C-7
buffer busy waits	C-7
buffer deadlock	C-8
buffer latch	C-8
buffer read retry	C-8
checkpoint completed	C-9
cleanup of aborted processes	C-9
control file parallel write	C-9
control file sequential read	C-9
control file single write	C-10
cursor: mutex S	C-10
cursor: mutex X	C-10
cursor: pin S	C-11
cursor: pin S wait on X	C-11
cursor: pin X	C-11
Data Guard: process clean up	C-11
Data Guard: process exit	C-12

Data Guard Broker: single instance.....	C-12
db file parallel read	C-12
db file parallel write.....	C-12
db file scattered read.....	C-12
db file sequential read	C-13
db file single write.....	C-13
DFS db file lock.....	C-13
DFS lock handle.....	C-13
direct path read.....	C-14
direct path sync	C-14
direct path write	C-14
Disk file operations I/O	C-15
dispatcher shutdown	C-15
dispatcher timer.....	C-15
duplicate cluster key	C-15
enq: OW - initialization	C-16
enq: OW - termination.....	C-16
enqueue.....	C-16
flashback buf free by RVWR.....	C-16
flashback logfile sync.....	C-16
free buffer waits.....	C-17
free global transaction table entry	C-17
free process state object	C-17
gc recovery quiesce	C-17
GCS lock open S	C-18
GCS lock open X.....	C-18
gcs remastering wait for drop pkey	C-18
global cache busy	C-18
global cache lock cleanup.....	C-19
global cache freelist.....	C-19
inactive session.....	C-19
inactive transaction branch.....	C-19
index block split	C-19
instance state change	C-20
io done	C-20
kcl bg acks	C-20
ksxr wait for mount shared	C-21
ktm: instance recovery.....	C-21
latch activity.....	C-21
latch free	C-21
library cache load lock.....	C-22
library cache lock.....	C-22
library cache pin.....	C-22
library cache shutdown.....	C-23
LMON global data update.....	C-23
lock manager wait for remote message	C-23
Log archive I/O.....	C-23

log buffer space.....	C-23
log file parallel write.....	C-23
log file sequential read	C-24
log file single write.....	C-24
log file switch (archiving needed)	C-24
log file switch (checkpoint incomplete)	C-24
log file switch (clearing log file).....	C-25
log file switch (private strand flush incomplete).....	C-25
log file switch completion	C-25
log file sync	C-25
log switch/archive	C-25
optimizer stats update retry	C-25
parallel recovery change buffer free.....	C-26
parallel recovery control message reply	C-26
parallel recovery coord send blocked	C-26
parallel recovery coord wait for reply	C-26
parallel recovery coordinator waits for slave cleanup	C-26
parallel recovery read buffer free	C-26
parallel recovery slave next change.....	C-26
pending global transaction(s).....	C-27
pipe get	C-27
pipe put.....	C-27
PL/SQL lock timer	C-27
pmon timer.....	C-27
prewarm transfer retry	C-28
prior process spawner to be cleaned up	C-28
process startup.....	C-28
PX Dequeue wait	C-28
PX qref latch.....	C-29
PX server shutdown.....	C-29
PX signal server	C-29
rdbms ipc message.....	C-29
rdbms ipc message block	C-29
rdbms ipc reply.....	C-30
read by other session	C-30
recovery read	C-30
resmgr:become active	C-30
resmgr:cpu quantum	C-31
resmgr:pq queued	C-31
rolling migration: cluster quiesce	C-31
row cache lock	C-31
RVWR wait for flashback copy	C-32
sbtbufinfo	C-32
sbtgetbuf	C-32
sbtmapbuf.....	C-32
sbtrelbuf.....	C-32
scginq AST call	C-32

SGA: allocation forcing component growth.....	C-32
SGA: MMAN sleep for component shrink.....	C-33
SGA: sga_target resize.....	C-33
Shared IO Pool Memory.....	C-33
single-task message.....	C-33
shared server idle wait	C-33
smon timer	C-33
SQL*Net break/reset to client.....	C-34
SQL*Net break/reset to dblink.....	C-34
SQL*Net message from client.....	C-34
SQL*Net message from dblink.....	C-34
SQL*Net message to client.....	C-35
SQL*Net message to dblink.....	C-35
SQL*Net more data from client.....	C-35
SQL*Net more data from dblink.....	C-35
SQL*Net more data to client.....	C-36
SQL*Net more data to dblink.....	C-36
Streams AQ: waiting for messages in the queue	C-36
switch logfile command	C-36
TCP Socket (KGAS).....	C-36
timer in sksawat	C-37
transaction	C-37
unbound tx	C-37
undo_retention publish retry	C-37
undo segment extension	C-38
undo segment recovery	C-38
undo segment tx slot.....	C-38
virtual circuit status	C-38
virtual circuit wait.....	C-38
WCR: replay client notify.....	C-39
WCR: replay clock.....	C-39
WCR: replay lock order.....	C-39
WCR: replay paused	C-39
WCR: Sync context busy	C-39
WMON goes to sleep	C-40
write complete waits.....	C-40
writes stopped by instance recovery or database suspension.....	C-40

D Oracle Enqueue Names

E Statistics Descriptions

Displaying Statistics	E-1
Statistics Descriptions	E-1

F Background Processes

Index

Preface

This manual provides reference information about database initialization parameters, static data dictionary views, dynamic performance views, database limits, and SQL scripts that are part of the Oracle Database.

Oracle Database Reference contains information that describes the features and functionality of the Oracle Database (also known as the standard edition) and the Oracle Database Enterprise Edition products. The Oracle Database and the Oracle Database Enterprise Edition have the same basic features. However, several advanced features are available only with the Enterprise Edition, and some of these are optional. For example, to use application failover, you must have the Enterprise Edition with the Real Application Clusters option.

See Also: *Oracle Database New Features Guide* for information about the differences between the Oracle Database and the Oracle Database Enterprise Edition and the features and options that are available to you.

This preface contains these topics:

- [Audience](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Conventions](#)

Audience

Oracle Database Reference is intended for database administrators, system administrators, and database application developers.

To use this document, you need TO BE FAMILIAR WITH THE FOLLOWING:

- Oracle database management system (DBMS) concepts
- Your operating system environment

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

For more information, see these Oracle resources:

- *Oracle Database Concepts* for a comprehensive introduction to the concepts and terminology used in this manual
- *Oracle Database Administrator's Guide* for information about administering the Oracle Database
- *Oracle Database Upgrade Guide* for the procedures for upgrading a previous release of Oracle to the new release
- *Oracle Database SQL Language Reference* for information on Oracle's SQL commands and functions
- *Oracle Database Advanced Application Developer's Guide* for information about developing database applications within the Oracle Database

Many of the examples in this book use the sample schemas, which are installed by default when you select the Basic Installation option with an Oracle Database installation. Refer to *Oracle Database Sample Schemas* for information on how these schemas were created and how you can use them yourself.

Printed documentation is available for sale in the Oracle Store at

<http://shop.oracle.com/>

To download free release notes, installation documentation, white papers, or other collateral, please visit the Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

<http://www.oracle.com/technology>

You can go directly to the documentation section of the OTN Web site at

<http://www.oracle.com/technology/documentation>

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

What's New in Oracle Database Reference?

This section describes new features of Oracle Database 11g release 1 (11.1) and provides pointers to additional information. For information on features that were new in earlier releases of the Oracle Database, refer to the documentation for the earlier release.

The following sections describe the new features in Oracle Database Reference:

- [Oracle Database 11g Release 2 \(11.2.0.3\) New Features](#)
- [Oracle Database 11g Release 2 \(11.2.0.2\) New Features](#)
- [Oracle Database 11g Release 2 \(11.2.0.1\) New Features](#)
- [Oracle Database 11g Release 1 \(11.1\) New Features](#)

Oracle Database 11g Release 2 (11.2.0.3) New Features

The following initialization parameter is new to Oracle Database 11g Release 2 (11.2.0.3):

AWR_SNAPSHOT_TIME_OFFSET

See Also: [Part I, "Initialization Parameters"](#) for more information about this initialization parameter

Oracle Database 11g Release 2 (11.2.0.2) New Features

The following initialization parameters are new to Oracle Database 11g Release 2 (11.2.0.2):

CURSOR_BIND_CAPTURE_DESTINATION
DB_FLASH_CACHE_FILE
DB_FLASH_CACHE_SIZE
DB_UNRECOVERABLE_SCN_TRACKING

See Also: [Part I, "Initialization Parameters"](#) for more information about these initialization parameters

The following static data dictionary views are new to Oracle Database 11g Release 2 (11.2.0.2):

ALL_ Views

ALL_APPLY_ERROR_MESSAGES

DBA_ Views

DBA_APPLY_ERROR_MESSAGES

USER_ Views

ALL_ Views	DBA_ Views	USER_ Views
	DBA_HIST_PERSISTENT_QMN_CACHE	
	DBA_XSTREAM_ADMINISTRATOR	
	DBA_XSTREAM_OUT_SUPPORT_MODE	

See Also: [Part II, "Static Data Dictionary Views"](#) for more information about these static data dictionary views

The following dynamic performance views are new to Oracle Database 11g Release 2 (11.2.0.2):

GV\$ Views	V\$ Views
GV\$ASM_ACFS_ENCRYPTION_INFO	V\$ASM_ACFS_ENCRYPTION_INFO
GV\$ASM_ACFS_SECURITY_INFO	V\$ASM_ACFS_SECURITY_INFO
GV\$XSTREAM_CAPTURE	V\$XSTREAM_CAPTURE
GV\$XSTREAM_MESSAGE_TRACKING	V\$XSTREAM_MESSAGE_TRACKING
GV\$XSTREAM_OUTBOUND_SERVER	V\$XSTREAM_OUTBOUND_SERVER
GV\$XSTREAM_TRANSACTION	V\$XSTREAM_TRANSACTION

See Also: [Part III, "Dynamic Performance Views"](#) for more information about these dynamic performance views

Oracle Database 11g Release 2 (11.2.0.1) New Features

The following initialization parameters are new to Oracle Database 11g Release 2 (11.2.0.1):

DEFERRED_SEGMENT_CREATION
DST_UPGRADE_INSERT_CONV
LISTENER_NETWORKS
PARALLEL_DEGREE_LIMIT
PARALLEL_DEGREE_POLICY
PARALLEL_FORCE_LOCAL
PARALLEL_MIN_TIME_THRESHOLD
PARALLEL_SERVERS_TARGET

See Also: [Part I, "Initialization Parameters"](#) for more information about these initialization parameters

The following static data dictionary views are new to Oracle Database 11g Release 2 (11.2.0.1):

ALL_ Views	DBA_ Views	USER_ Views
ALL_APPLY_CHANGE_HANDLERS	DBA_APPLY_CHANGE_HANDLERS	
	DBA_HIST_DISPATCHER	
	DBA_HIST_DYN_REMASTER_STATS	
	DBA_HIST_IOSTAT_DETAIL	
	DBA_HIST_PLAN_OPERATION_NAME	

ALL_ Views	DBA_ Views	USER_ Views
	DBA_HIST_PLAN_OPTION_NAME	
	DBA_HIST_SHARED_SERVER_SUMMARY	
	DBA_HIST_SQLCOMMAND_NAME	
	DBA_HIST_TOPLEVELCALL_NAME	
	DBA_PARALLEL_EXECUTE_CHUNKS	USER_PARALLEL_EXECUTE_CHUNKS
	DBA_PARALLEL_EXECUTE_TASKS	USER_PARALLEL_EXECUTE_TASKS
ALL_QUEUE_SCHEDULES		
	DBA_RECOVERABLE_SCRIPT_HIST	
ALL_SCHEDULER_DB_DESTS	DBA_SCHEDULER_DB_DESTS	USER_SCHEDULER_DB_DESTS
ALL_SCHEDULER_DESTS	DBA_SCHEDULER_DESTS	USER_SCHEDULER_DESTS
ALL_SCHEDULER_EXTERNAL_DESTS	DBA_SCHEDULER_EXTERNAL_DESTS	
ALL_SCHEDULER_FILE_WATCHERS	DBA_SCHEDULER_FILE_WATCHERS	USER_SCHEDULER_FILE_WATCHERS
ALL_SCHEDULER_GROUP_MEMBERS	DBA_SCHEDULER_GROUP_MEMBERS	USER_SCHEDULER_GROUP_MEMBERS
ALL_SCHEDULER_GROUPS	DBA_SCHEDULER_GROUPS	USER_SCHEDULER_GROUPS
ALL_SCHEDULER_JOB_DESTS	DBA_SCHEDULER_JOB_DESTS	USER_SCHEDULER_JOB_DESTS
ALL_SCHEDULER_NOTIFICATIONS	DBA_SCHEDULER_NOTIFICATIONS	USER_SCHEDULER_NOTIFICATIONS
	DBA_STREAMS_KEEP_COLUMNS	
	DBA_STREAMS_SPLIT_MERGE	
	DBA_STREAMS_SPLIT_MERGE_HIST	
ALL_STREAMS_STMT_HANDLERS	DBA_STREAMS_STMT_HANDLERS	
ALL_STREAMS_STMTS	DBA_STREAMS_STMTS	
ALL_TSTZ_TAB_COLS	DBA_TSTZ_TAB_COLS	USER_TSTZ_TAB_COLS
ALL_TSTZ_TABLES	DBA_TSTZ_TABLES	USER_TSTZ_TABLES
	DBA_WALLET_ACLS	

The following additional static data dictionary views are new to Oracle Database 11g Release 2 (11.2.0.1):

DBFS_CONTENT
DBFS_CONTENT_PROPERTIES

See Also: [Part II, "Static Data Dictionary Views"](#) for more information about these static data dictionary views

The following dynamic performance views are new to Oracle Database 11g Release 2 (11.2.0.1):

GV\$ Views	V\$ Views
GV\$ASM_ACFSSNAPSHOTS	V\$ASM_ACFSSNAPSHOTS
GV\$ASM_ACFSVOLUMES	V\$ASM_ACFSVOLUMES
GV\$ASM_FILESYSTEM	V\$ASM_FILESYSTEM
GV\$ASM_USER	V\$ASM_USER
GV\$ASM_USERGROUP	V\$ASM_USERGROUP
GV\$ASM_USERGROUP_MEMBER	V\$ASM_USERGROUP_MEMBER

GV\$ Views	V\$ Views
GV\$ASM_VOLUME	V\$ASM_VOLUME
GV\$ASM_VOLUME_STAT	V\$ASM_VOLUME_STAT
GV\$CPOOL_CONN_INFO	V\$CPOOL_CONN_INFO
GV\$DATAGUARD_STATS	
GV\$EMON	V\$EMON
GV\$IOSTAT_FUNCTION_DETAIL	V\$IOSTAT_FUNCTION_DETAIL
GV\$LIBCACHE_LOCKS	V\$LIBCACHE_LOCKS
GV\$PERSISTENT_QMN_CACHE	V\$PERSISTENT_QMN_CACHE
GV\$QMON_COORDINATOR_STATS	V\$QMON_COORDINATOR_STATS
GV\$QMON_SERVER_STATS	V\$QMON_SERVER_STATS
GV\$QMON_TASK_STATS	V\$QMON_TASK_STATS
GV\$QMON_TASKS	V\$QMON_TASKS
GV\$SQLCOMMAND	V\$SQLCOMMAND
	V\$STANDBY_EVENT_HISTOGRAM
GV\$STREAMS_POOL_STATISTICS	V\$STREAMS_POOL_STATISTICS
GV\$TOPLEVELCALL	V\$TOPLEVELCALL

See Also: [Part III, "Dynamic Performance Views"](#) for more information about these dynamic performance views

Oracle Database 11g Release 1 (11.1) New Features

The following initialization parameters are new to Oracle Database 11g Release 1 (11.1):

ASM_PREFERRED_READ_FAILURE_GROUPS
 CLIENT_RESULT_CACHE_LAG
 CLIENT_RESULT_CACHE_SIZE
 COMMIT_LOGGING
 COMMIT_WAIT
 CONTROL_MANAGEMENT_PACK_ACCESS
 DB_LOST_WRITE_PROTECT
 DB_SECUREFILE
 DB_ULTRA_SAFE
 DDL_LOCK_TIMEOUT
 DIAGNOSTIC_DEST
 GLOBAL_TXN_PROCESSES
 JAVA_JIT_ENABLED
 LDAP_DIRECTORY_SYSAUTH
 MEMORY_MAX_TARGET
 MEMORY_TARGET
 OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES
 OPTIMIZER_USE_INVISIBLE_INDEXES
 OPTIMIZER_USE_PENDING_STATISTICS
 OPTIMIZER_USE_SQL_PLAN_BASELINES
 PARALLEL_IO_CAP_ENABLED
 PLSCOPE_SETTINGS

REDO_TRANSPORT_USER
 RESOURCE_MANAGER_CPU_ALLOCATION
 RESULT_CACHE_MAX_RESULT
 RESULT_CACHE_MAX_SIZE
 RESULT_CACHE_MODE
 RESULT_CACHE_REMOTE_EXPIRATION
 SEC_CASE_SENSITIVE_LOGON
 SEC_MAX_FAILED_LOGIN_ATTEMPTS
 SEC_PROTOCOL_ERROR_FURTHER_ACTION
 SEC_PROTOCOL_ERROR_TRACE_ACTION
 SEC_RETURN_SERVER_RELEASE_BANNER
 XML_DB_EVENTS

See Also: [Part I, "Initialization Parameters"](#) for more information about these initialization parameters

The following static data dictionary views are new to Oracle Database 11g Release 1 (11.1)::

ALL_ Views	DBA_ Views	USER_ Views
	DBA_ADDM_FDG_BREAKDOWN	USER_ADDM_FDG_BREAKDOWN
	DBA_ADDM_FINDINGS	USER_ADDM_FINDINGS
	DBA_ADDM_INSTANCES	USER_ADDM_INSTANCES
	DBA_ADDM_SYSTEM_DIRECTIVES	
	DBA_ADDM_TASK_DIRECTIVES	USER_ADDM_TASK_DIRECTIVES
	DBA_ADDM_TASKS	USER_ADDM_TASKS
	DBA_ADVISOR_DIR_DEFINITIONS	
	DBA_ADVISOR_DIR_INSTANCES	
	DBA_ADVISOR_DIR_TASK_INST	USER_ADVISOR_DIR_TASK_INST
	DBA_ADVISOR_EXEC_PARAMETERS	USER_ADVISOR_EXEC_PARAMETERS
	DBA_ADVISOR_EXECUTION_TYPES	
	DBA_ADVISOR_EXECUTIONS	USER_ADVISOR_EXECUTIONS
	DBA_ADVISOR_FDG_BREAKDOWN	USER_ADVISOR_FDG_BREAKDOWN
	DBA_ADVISOR_FINDING_NAMES	
	DBA_ADVISOR_SQLA_COLVOL	USER_ADVISOR_SQLA_COLVOL
	DBA_ADVISOR_SQLA_TABLES	USER_ADVISOR_SQLA_TABLES
	DBA_ADVISOR_SQLA_TABVOL	USER_ADVISOR_SQLA_TABVOL
	DBA_ADVISOR_SQLA_WK_SUM	USER_ADVISOR_SQLA_WK_SUM
	DBA_ADVISOR_SQLPLANS	USER_ADVISOR_SQLPLANS
	DBA_ADVISOR_SQLSTATS	USER_ADVISOR_SQLSTATS
	DBA_ARGUMENTS	
ALL_ASSEMBLIES	DBA_ASSEMBLIES	USER_ASSEMBLIES
	DBA_AUTOTASK_CLIENT	
	DBA_AUTOTASK_CLIENT_HISTORY	
	DBA_AUTOTASK_CLIENT_JOB	
	DBA_AUTOTASK_OPERATION	
	DBA_AUTOTASK_SCHEDULE	
	DBA_AUTOTASK_TASK	

ALL_ Views	DBA_ Views	USER_ Views
	DBA_AUTOTASK_WINDOW_CLIENTS	
	DBA_AUTOTASK_WINDOW_HISTORY	
ALL_CHANGE_PROPAGATION_SETS		
ALL_CHANGE_PROPAGATIONS		
ALL_CHANGE_SETS		
ALL_CHANGE_SOURCES		
ALL_CHANGE_TABLES		
ALL_COL_PENDING_STATS	DBA_COL_PENDING_STATS	USER_COL_PENDING_STATS
	DBA_COMPARISON	USER_COMPARISON
	DBA_COMPARISON_COLUMNS	USER_COMPARISON_COLUMNS
	DBA_COMPARISON_ROW_DIF	USER_COMPARISON_ROW_DIF
	DBA_COMPARISON_SCAN	USER_COMPARISON_SCAN
	DBA_COMPARISON_SCAN_SUMMARY	USER_COMPARISON_SCAN_SUMMARY
	DBA_COMPARISON_SCAN_VALUES	USER_COMPARISON_SCAN_VALUES
	DBA_CPOOL_INFO	
	DBA_CQ_NOTIFICATION_QUERIES	USER_CQ_NOTIFICATION_QUERIES
ALL_CUBE_ATTR_VISIBILITY	DBA_CUBE_ATTR_VISIBILITY	USER_CUBE_ATTR_VISIBILITY
ALL_CUBE_ATTRIBUTES	DBA_CUBE_ATTRIBUTES	USER_CUBE_ATTRIBUTES
ALL_CUBE_BUILD_PROCESSES	DBA_CUBE_BUILD_PROCESSES	USER_CUBE_BUILD_PROCESSES
ALL_CUBE_CALCULATED_MEMBERS	DBA_CUBE_CALCULATED_MEMBERS	USER_CUBE_CALCULATED_MEMBERS
ALL_CUBE_DIM_LEVELS	DBA_CUBE_DIM_LEVELS	USER_CUBE_DIM_LEVELS
ALL_CUBE_DIM_MODELS	DBA_CUBE_DIM_MODELS	USER_CUBE_DIM_MODELS
ALL_CUBE_DIM_VIEW_COLUMNS	DBA_CUBE_DIM_VIEW_COLUMNS	USER_CUBE_DIM_VIEW_COLUMNS
ALL_CUBE_DIM_VIEWS	DBA_CUBE_DIM_VIEWS	USER_CUBE_DIM_VIEWS
ALL_CUBE_DIMENSIONALITY	DBA_CUBE_DIMENSIONALITY	USER_CUBE_DIMENSIONALITY
ALL_CUBE_DIMENSIONS	DBA_CUBE_DIMENSIONS	USER_CUBE_DIMENSIONS
ALL_CUBE_HIER_LEVELS	DBA_CUBE_HIER_LEVELS	USER_CUBE_HIER_LEVELS
ALL_CUBE_HIER_VIEW_COLUMNS	DBA_CUBE_HIER_VIEW_COLUMNS	USER_CUBE_HIER_VIEW_COLUMNS
ALL_CUBE_HIER_VIEWS	DBA_CUBE_HIER_VIEWS	USER_CUBE_HIER_VIEWS
ALL_CUBE_HIERARCHIES	DBA_CUBE_HIERARCHIES	USER_CUBE_HIERARCHIES
ALL_CUBE_MEASURES	DBA_CUBE_MEASURES	USER_CUBE_MEASURES
ALL_CUBE_VIEW_COLUMNS	DBA_CUBE_VIEW_COLUMNS	USER_CUBE_VIEW_COLUMNS
ALL_CUBE_VIEWS	DBA_CUBE_VIEWS	USER_CUBE_VIEWS
ALL_CUBES	DBA_CUBES	USER_CUBES
	DBA_EPG_DAD_AUTHORIZATION	USER_EPG_DAD_AUTHORIZATION
	DBA_FLASHBACK_ARCHIVE	USER_FLASHBACK_ARCHIVE
	DBA_FLASHBACK_ARCHIVE_TABLES	USER_FLASHBACK_ARCHIVE_TABLES
	DBA_FLASHBACK_ARCHIVE_TS	
	DBA_FLASHBACK_TXN_REPORT	USER_FLASHBACK_TXN_REPORT
	DBA_FLASHBACK_TXN_STATE	USER_FLASHBACK_TXN_STATE
	DBA_HIST_BASELINE_DETAILS	
	DBA_HIST_BASELINE_METADATA	
	DBA_HIST_BASELINE_TEMPLATE	

ALL_ Views	DBA_ Views	USER_ Views
	DBA_HIST_CLUSTER_INTERCON	
	DBA_HIST_COLORED_SQL	
	DBA_HIST_EVENT_HISTOGRAM	
	DBA_HIST_IC_CLIENT_STATS	
	DBA_HIST_IC_DEVICE_STATS	
	DBA_HIST_INTERCONNECT_PINGS	
	DBA_HIST_IOSTAT_FILETYPE	
	DBA_HIST_IOSTAT_FILETYPE_NAME	
	DBA_HIST_IOSTAT_FUNCTION	
	DBA_HIST_IOSTAT_FUNCTION_NAME	
	DBA_HIST_MEM_DYNAMIC_COMP	
	DBA_HIST_MEMORY_RESIZE_OPS	
	DBA_HIST_MEMORY_TARGET_ADVICE	
	DBA_HIST_MUTEX_SLEEP	
	DBA_HIST_PERSISTENT_QUEUES	
	DBA_HIST_PERSISTENT_SUBS	
	DBA_HIST_RSRC_CONSUMER_GROUP	
	DBA_HIST_RSRC_PLAN	
ALL_IDENTIFIERS	DBA_IDENTIFIERS	USER_IDENTIFIERS
ALL_IND_PENDING_STATS	DBA_IND_PENDING_STATS	USER_IND_PENDING_STATS
	DBA_INVALID_OBJECTS	
ALL_JAVA_COMPILER_OPTIONS	DBA_JAVA_COMPILER_OPTIONS	USER_JAVA_COMPILER_OPTIONS
	DBA_LOGSTDBY_UNSUPPORTED_TABLE	
ALL_MEASURE_FOLDER_CONTENTS	DBA_MEASURE_FOLDER_CONTENTS	USER_MEASURE_FOLDER_CONTENTS
ALL_MEASURE_FOLDERS	DBA_MEASURE_FOLDERS	USER_MEASURE_FOLDERS
ALL_MINING_MODEL_ATTRIBUTES	DBA_MINING_MODEL_ATTRIBUTES	USER_MINING_MODEL_ATTRIBUTES
ALL_MINING_MODEL_SETTINGS	DBA_MINING_MODEL_SETTINGS	USER_MINING_MODEL_SETTINGS
ALL_MINING_MODELS	DBA_MINING_MODELS	USER_MINING_MODELS
ALL_MVIEW_DETAIL_PARTITION	DBA_MVIEW_DETAIL_PARTITION	USER_MVIEW_DETAIL_PARTITION
ALL_MVIEW_DETAIL_SUBPARTITION	DBA_MVIEW_DETAIL_SUBPARTITION	USER_MVIEW_DETAIL_SUBPARTITION
	DBA_NETWORK_ACL_PRIVILEGES	USER_NETWORK_ACL_PRIVILEGES
	DBA_NETWORK_ACLS	
	DBA_OLDIMAGE_COLUMNS	USER_OLDIMAGE_COLUMNS
	DBA_REGISTRY_DATABASE	
	DBA_REGISTRY_DEPENDENCIES	
	DBA_REGISTRY_PROGRESS	
	DBA_RSRC_CAPABILITY	
	DBA_RSRC_CATEGORIES	
	DBA_RSRC_INSTANCE_CAPABILITY	
	DBA_RSRC_IO_CALIBRATE	
	DBA_RSRC_STORAGE_POOL_MAPPING	
ALL_SCHEDULER_CREDENTIALS	DBA_SCHEDULER_CREDENTIALS	USER_SCHEDULER_CREDENTIALS
	DBA_SCHEDULER_JOB_ROLES	

ALL_ Views	DBA_ Views	USER_ Views
ALL_SCHEDULER_REMOTE_DATABASES	DBA_SCHEDULER_REMOTE_DATABASES	
ALL_SCHEDULER_REMOTE_JOBSTATE	DBA_SCHEDULER_REMOTE_JOBSTATE	USER_SCHEDULER_REMOTE_JOBSTATE
	DBA_SQL_MANAGEMENT_CONFIG	
	DBA_SQL_PATCHES	
	DBA_SQL_PLAN_BASELINES	
ALL_STAT_EXTENSIONS	DBA_STAT_EXTENSIONS	USER_STAT_EXTENSIONS
ALL_STREAMS_COLUMNS	DBA_STREAMS_COLUMNS	
	DBA_STREAMS_TP_COMPONENT	
	DBA_STREAMS_TP_COMPONENT_LINK	
	DBA_STREAMS_TP_COMPONENT_STAT	
	DBA_STREAMS_TP_DATABASE	
	DBA_STREAMS_TP_PATH_BOTTLENECK	
	DBA_STREAMS_TP_PATH_STAT	
	DBA_SUBSCR_REGISTRATIONS	USER_SUBSCR_REGISTRATIONS
ALL_SYNC_CAPTURE	DBA_SYNC_CAPTURE	
ALL_SYNC_CAPTURE_PREPARED_TABS	DBA_SYNC_CAPTURE_PREPARED_TABS	
ALL_SYNC_CAPTURE_TABLES	DBA_SYNC_CAPTURE_TABLES	
ALL_TAB_HISTGRM_PENDING_STATS	DBA_TAB_HISTGRM_PENDING_STATS	USER_TAB_HISTGRM_PENDING_STATS
ALL_TAB_PENDING_STATS	DBA_TAB_PENDING_STATS	USER_TAB_PENDING_STATS
ALL_TAB_STAT_PREFS	DBA_TAB_STAT_PREFS	USER_TAB_STAT_PREFS
	DBA_TEMP_FREE_SPACE	
ALL_TRIGGER_ORDERING	DBA_TRIGGER_ORDERING	USER_TRIGGER_ORDERING
	DBA_USERS_WITH_DEFPWD	
	DBA_WORKLOAD_CAPTURES	
	DBA_WORKLOAD_CONNECTION_MAP	
	DBA_WORKLOAD_FILTERS	
	DBA_WORKLOAD_REPLAY_DIVERGENCE	
	DBA_WORKLOAD_REPLAYS	

See Also: [Part II, "Static Data Dictionary Views"](#) for more information about these static data dictionary views

The following dynamic performance views are new to Oracle Database 11g Release 1 (11.1)::

GV\$ Views	V\$ Views
GV\$ASM_ATTRIBUTE	V\$ASM_ATTRIBUTE
GV\$ASM_DISK_IOSTAT	V\$ASM_DISK_IOSTAT
GV\$CALLTAG	V\$CALLTAG
GV\$CORRUPT_XID_LIST	V\$CORRUPT_XID_LIST
GV\$CPOOL_CC_INFO	V\$CPOOL_CC_INFO
GV\$CPOOL_CC_STATS	V\$CPOOL_CC_STATS
GV\$CPOOL_STATS	V\$CPOOL_STATS

GV\$ Views	V\$ Views
GV\$DETACHED_SESSION	V\$DETACHED_SESSION
GV\$DIAG_INFO	V\$DIAG_INFO
GV\$DNFS_CHANNELS	V\$DNFS_CHANNELS
GV\$DNFS_FILES	V\$DNFS_FILES
GV\$DNFS_SERVERS	V\$DNFS_SERVERS
GV\$DNFS_STATS	V\$DNFS_STATS
GV\$DYNAMIC_REMASTER_STATS	V\$DYNAMIC_REMASTER_STATS
GV\$ENCRYPTED_TABLESPACES	V\$ENCRYPTED_TABLESPACES
GV\$ENCRYPTION_WALLET	V\$ENCRYPTION_WALLET
	V\$FLASHBACK_TXN_GRAPH
	V\$FLASHBACK_TXN_MODS
GV\$FOREIGN_ARCHIVED_LOG	V\$FOREIGN_ARCHIVED_LOG
GV\$FS_FAILOVER_HISTOGRAM	V\$FS_FAILOVER_HISTOGRAM
GV\$FS_FAILOVER_STATS	V\$FS_FAILOVER_STATS
GV\$HM_CHECK	V\$HM_CHECK
GV\$HM_CHECK_PARAM	V\$HM_CHECK_PARAM
GV\$HM_FINDING	V\$HM_FINDING
GV\$HM_INFO	V\$HM_INFO
GV\$HM_RECOMMENDATION	V\$HM_RECOMMENDATION
GV\$HM_RUN	V\$HM_RUN
GV\$INCMETER_CONFIG	V\$INCMETER_CONFIG
GV\$INCMETER_INFO	V\$INCMETER_INFO
GV\$INCMETER_SUMMARY	V\$INCMETER_SUMMARY
GV\$IOFUNCMETRIC	V\$IOFUNCMETRIC
GV\$IOFUNCMETRIC_HISTORY	V\$IOFUNCMETRIC_HISTORY
GV\$IOSTAT_CONSUMER_GROUP	V\$IOSTAT_CONSUMER_GROUP
GV\$IOSTAT_FILE	V\$IOSTAT_FILE
GV\$IOSTAT_FUNCTION	V\$IOSTAT_FUNCTION
GV\$IOSTAT_NETWORK	V\$IOSTAT_NETWORK
GV\$IO_CALIBRATION_STATUS	V\$IO_CALIBRATION_STATUS
GV\$IR_FAILURE	V\$IR_FAILURE
GV\$IR_FAILURE_SET	V\$IR_FAILURE_SET
GV\$IR_MANUAL_CHECKLIST	V\$IR_MANUAL_CHECKLIST
GV\$IR_REPAIR	V\$IR_REPAIR
GV\$LOBSTAT	V\$LOBSTAT
GV\$MEMORY_CURRENT_RESIZE_OPS	V\$MEMORY_CURRENT_RESIZE_OPS
GV\$MEMORY_DYNAMIC_COMPONENTS	V\$MEMORY_DYNAMIC_COMPONENTS
GV\$MEMORY_RESIZE_OPS	V\$MEMORY_RESIZE_OPS

GV\$ Views	V\$ Views
GV\$MEMORY_TARGET_ADVICE	V\$MEMORY_TARGET_ADVICE
GV\$NFS_CLIENTS	V\$NFS_CLIENTS
GV\$NFS_LOCKS	V\$NFS_LOCKS
GV\$NFS_OPEN_FILES	V\$NFS_OPEN_FILES
	V\$OBJECT_PRIVILEGE
GV\$PERSISTENT_PUBLISHERS	V\$PERSISTENT_PUBLISHERS
GV\$PERSISTENT_QUEUES	V\$PERSISTENT_QUEUES
GV\$PERSISTENT_SUBSCRIBERS	V\$PERSISTENT_SUBSCRIBERS
GV\$PROCESS_GROUP	V\$PROCESS_GROUP
GV\$PX_INSTANCE_GROUP	V\$PX_INSTANCE_GROUP
GV\$REDO_DEST_RESP_HISTOGRAM	V\$REDO_DEST_RESP_HISTOGRAM
GV\$RESULT_CACHE_DEPENDENCY	V\$RESULT_CACHE_DEPENDENCY
GV\$RESULT_CACHE_MEMORY	V\$RESULT_CACHE_MEMORY
GV\$RESULT_CACHE_OBJECTS	V\$RESULT_CACHE_OBJECTS
GV\$RESULT_CACHE_STATISTICS	V\$RESULT_CACHE_STATISTICS
GV\$RMAN_COMPRESSION_ALGORITHM	V\$RMAN_COMPRESSION_ALGORITHM
	V\$RMAN_ENCRYPTION_ALGORITHMS
GV\$RSRCMGRMETRIC	V\$RSRCMGRMETRIC
GV\$RSRCMGRMETRIC_HISTORY	V\$RSRCMGRMETRIC_HISTORY
GV\$SECUREFILE_TIMER	V\$SECUREFILE_TIMER
	V\$SESSION_FIX_CONTROL
GV\$SQL_CS_HISTOGRAM	V\$SQL_CS_HISTOGRAM
GV\$SQL_CS_SELECTIVITY	V\$SQL_CS_SELECTIVITY
GV\$SQL_CS_STATISTICS	V\$SQL_CS_STATISTICS
GV\$SQL_FEATURE	V\$SQL_FEATURE
GV\$SQL_FEATURE_DEPENDENCY	V\$SQL_FEATURE_DEPENDENCY
GV\$SQL_FEATURE_HIERARCHY	V\$SQL_FEATURE_HIERARCHY
GV\$SQL_HINT	V\$SQL_HINT
GV\$SQL_MONITOR	V\$SQL_MONITOR
GV\$SQL_PLAN_MONITOR	V\$SQL_PLAN_MONITOR
GV\$SQLFN_ARG_METADATA	V\$SQLFN_ARG_METADATA
GV\$SQLFN_METADATA	V\$SQLFN_METADATA
GV\$STREAMS_MESSAGE_TRACKING	V\$STREAMS_MESSAGE_TRACKING
GV\$SUBSCR_REGISTRATION_STATS	V\$SUBSCR_REGISTRATION_STATS
	V\$SYSTEM_FIX_CONTROL
	V\$WAIT_CHAINS
GV\$WORKLOAD_REPLAY_THREAD	V\$WORKLOAD_REPLAY_THREAD

See Also: [Part III, "Dynamic Performance Views"](#) for more information about these dynamic performance views

Part I

Initialization Parameters

This part describes the database initialization parameters that can be specified in a parameter file to start or configure an instance. This part contains the following chapter:

- [Chapter 1, "Initialization Parameters"](#)

Initialization Parameters

This chapter contains detailed descriptions (in alphabetical order) of the database initialization parameters.

This chapter contains the following topics:

- [Uses of Initialization Parameters](#)
- [Basic Initialization Parameters](#)
- [Parameter Files](#)
- [Changing Parameter Values in a Parameter File](#)
- [Reading the Parameter Descriptions](#)
- [Initialization Parameter Descriptions](#)

Uses of Initialization Parameters

Initialization parameters fall into various functional groups. For example, parameters perform the following functions:

- Set limits for the entire database
- Set user or process limits
- Set limits on database resources
- Affect performance (these are called **variable parameters**)

Variable parameters are of particular interest to database administrators, because these parameters are used primarily to improve database performance.

Database administrators can use initialization parameters to:

- Optimize performance by adjusting memory structures, such as the number of database buffers in memory
- Set database-wide defaults, such as the amount of space initially allocated for a context area when it is created
- Set database limits, such as the maximum number of database users
- Specify names of files or directories required by the database

Many initialization parameters can be fine-tuned to improve database performance. Other parameters should never be altered or should be altered only under the supervision of Oracle Support Services.

All initialization parameters are optional. Oracle has a default value for each parameter. This value may be operating system-dependent, depending on the parameter.

Types of Initialization Parameters

The Oracle database server has the following types of initialization parameters:

- [Derived Parameters](#)
- [Operating System-Dependent Parameters](#)
- [Variable Parameters](#) (these can be dynamic parameters or any of the preceding ones)

Derived Parameters

Some initialization parameters are **derived**, meaning that their values are calculated from the values of other parameters. Normally, you should not alter values for derived parameters, but if you do, then the value you specify will override the calculated value.

For example, the default value of the `SESSIONS` parameter is derived from the value of the `PROCESSES` parameter. If the value of `PROCESSES` changes, then the default value of `SESSIONS` changes as well, unless you override it with a specified value.

Operating System-Dependent Parameters

The valid values or value ranges of some initialization parameters depend upon the host operating system. For example, the parameter `DB_BLOCK_BUFFERS` indicates the number of data buffers in main memory, and its maximum value depends on the operating system. The size of those buffers, set by `DB_BLOCK_SIZE`, has an operating system-dependent default value.

See Also: Your operating system-specific Oracle documentation for more information on operating system-dependent Oracle parameters and operating system parameters

Variable Parameters

The variable initialization parameters offer the most potential for improving system performance. Some variable parameters set capacity limits but do not affect performance. For example, when the value of `OPEN_CURSORS` is 10, a user process attempting to open its eleventh cursor receives an error. Other variable parameters affect performance but do not impose absolute limits. For example, reducing the value of `DB_BLOCK_BUFFERS` does not prevent work even though it may slow down performance.

Increasing the values of variable parameters may improve your system's performance, but increasing most parameters also increases the system global area (SGA) size. A larger SGA can improve database performance up to a point. In virtual memory operating systems, an SGA that is too large can degrade performance if it is swapped in and out of memory. Operating system parameters that control virtual memory working areas should be set with the SGA size in mind. The operating system configuration can also limit the maximum size of the SGA.

Basic Initialization Parameters

The following is a list of the database basic initialization parameters. Most databases should only need to have basic parameters set to run properly and efficiently. Oracle advises you to become familiar with the basic parameters and only use other parameters when directed to by feature documentation or in special circumstances:

```
CLUSTER_DATABASE
COMPATIBLE
CONTROL_FILES
DB_BLOCK_SIZE
DB_CREATE_FILE_DEST
DB_CREATE_ONLINE_LOG_DEST_n
DB_DOMAIN
DB_NAME
DB_RECOVERY_FILE_DEST
DB_RECOVERY_FILE_DEST_SIZE
DB_UNIQUE_NAME
INSTANCE_NUMBER
LDAP_DIRECTORY_SYSAUTH
LOG_ARCHIVE_DEST_n
LOG_ARCHIVE_DEST_STATE_n
NLS_LANGUAGE
NLS_TERRITORY
OPEN_CURSORS
PGA_AGGREGATE_TARGET
PROCESSES
REMOTE_LISTENER
REMOTE_LOGIN_PASSWORDFILE
SESSIONS
SGA_TARGET
SHARED_SERVERS
STAR_TRANSFORMATION_ENABLED
UNDO_TABLESPACE
```

Parameter Files

A **parameter file** is a file that contains a list of initialization parameters and a value for each parameter. You specify initialization parameters in a parameter file that reflect your particular installation. Oracle supports the following two types of parameter files:

- [Server Parameter Files](#)
- [Initialization Parameter Files](#)

Server Parameter Files

A **server parameter file** is a binary file that acts as a repository for initialization parameters. The server parameter file can reside on the machine where the Oracle database server executes. Initialization parameters stored in a server parameter file are persistent, in that any changes made to the parameters while an instance is running can persist across instance shutdown and startup.

Initialization Parameter Files

An **initialization parameter file** is a text file that contains a list of initialization parameters. The file should be written in the client's default character set.

The following are sample entries in an initialization parameter file:

```
PROCESSES = 100
OPEN_LINKS = 12
GLOBAL_NAMES = true
```

The name of the initialization parameter file varies depending on the operating system. For example, it can be in mixed case or lowercase, or it can have a logical name or a variation of the name `init.ora`. Also supplied is an `initdw.ora` file, which contains suggested parameter settings for data warehouses and data marts. The database administrator can choose a different filename for the initialization parameter file.

Refer to your operating system-specific Oracle documentation for the default locations and filenames for initialization parameter files on your operating system. The initialization parameter file is read by the client-side tool used to start the server (such as SQL*Plus).

Sample initialization parameter files are provided on the Oracle distribution medium for each operating system. A sample file is sufficient for initial use, but you will probably want to modify the file to tune the database for best performance. Any changes will take effect after you completely shut down and restart the instance.

Specifying Values in an Initialization Parameter File

This section describes several aspects of setting parameter values in an initialization parameter file.

Rules Governing Initialization Parameter Files The following rules govern the specification of parameters in initialization parameter files:

- An initialization parameter file should contain only parameters and comments. A pound sign (#) starts a comment line. The rest of the line is ignored.
- You can specify parameters in any order.
- Case (upper or lower) in filenames is significant only if case is significant on the host operating system.
- To enter several parameters on one line, use spaces between parameter names and values, as in the following example:

```
PROCESSES = 100 CPU_COUNT = 1 OPEN_CURSORS = 10
```

- Some parameters, such as `ROLLBACK_SEGMENTS`, accept multiple values. Any of the following represent valid syntax.

- Enter multiple values enclosed in parentheses and separated by commas. For example:

```
ROLLBACK_SEGMENTS = (SEG1, SEG2, SEG3, SEG4, SEG5)
```

- Enter multiple values without parentheses and commas. For example:

```
ROLLBACK_SEGMENTS = SEG1 SEG2 SEG3 SEG4 SEG5
```

- Enter multiple values, one per line. For example:

```
ROLLBACK_SEGMENTS = SEG1
```



```

ROLLBACK_SEGMENTS = SEG2
ROLLBACK_SEGMENTS = SEG3
ROLLBACK_SEGMENTS = SEG4
ROLLBACK_SEGMENTS = SEG5

```

If you enter values for one parameter on multiple lines, then the entries must be on consecutive lines. If they are not, then the first entry will not be processed properly. For example, in the following entry the setting for SEG3 and SEG4 will override the setting for SEG1 and SEG2:

```

ROLLBACK_SEGMENTS = SEG1 SEG2
OPEN_CURSORS = 10
ROLLBACK_SEGMENTS = SEG3 SEG4

```

- A backslash (\), also known as an escape character, indicates continuation of the parameter specification. If a backslash continues a line, then the continued line must have no leading spaces. For example:

```

ROLLBACK_SEGMENTS = (SEG1, SEG2, \
SEG3, SEG4, SEG5)

```

- You can use the `IFILE` initialization parameter to embed the contents of another initialization parameter file into the current initialization parameter file.
- Enclose in quotation marks any parameter values that contain spaces or tabs. You can use either single or double quotation marks unless otherwise indicated. For example:

```
NLS_TERRITORY = 'CZECH REPUBLIC'
```

Note: Listing parameters in alphabetical order in the initialization parameter file can help you to find them and can help ensure that each parameter is specified only once.

- Enclose in quotation marks any parameter value that contains a special character.

See Also:

- Your operating system-specific Oracle documentation for more information on initialization parameter files
- ["IFILE"](#) on page 1-75

Using Special Characters in Parameter Values If a parameter value contains a special character, then the special character must be preceded by a backslash or the entire parameter value must be enclosed in quotation marks. For example, you can specify special characters using either of the following:

```
DB_DOMAIN = 'JAPAN.ACME#.COM'
```

```
DB_DOMAIN = JAPAN.ACME\#.COM
```

[Table 1-1](#) lists the special characters you can use in initialization parameter files.

Table 1-1 Special Characters in Initialization Parameter Files

Character	Name	Description
#	Number sign	Comment

Table 1–1 (Cont.) Special Characters in Initialization Parameter Files

Character	Name	Description
(	Left parenthesis	Start list of values
)	Right parenthesis	End list of values
"	Double quotation mark	Start or end of quoted string
'	Single quotation mark	Start or end of quoted string
=	Equal sign	Separator of keyword and values
,	Comma	Separator of elements
-	Minus sign	Precedes UNIX-style keywords
\	Backslash	Escape character

If a special character must be treated literally in an initialization parameter file, then it must either be preceded by the backslash character, or the entire string containing the special character must be enclosed in quotation marks.

Using the Escape Character As described in ["Rules Governing Initialization Parameter Files"](#) on page 1-4, the backslash (\) can also signify a line continuation. If the backslash is followed by an alphanumeric character, then the backslash is treated as a normal character in the input. If it is not followed by an alphanumeric character, then the backslash is treated either as a backslash or as a continuation character.

Using Quotation Marks Quotation marks can be nested in one of two ways. The first method is to double the quotation marks in the nested string. For example:

```
NLS_DATE_FORMAT = '''Today is'' MM/DD/YYYY'
```

The second method is to alternate single and double quotation marks. For example:

```
NLS_DATE_FORMAT = '"Today is" MM/DD/YYYY'
```

Changing Parameter Values in a Parameter File

You change the value of a parameter in a parameter file in one of the following ways:

- By editing an initialization parameter file
In most cases, the new value takes effect the next time you start an instance of the database.
- By issuing an `ALTER SYSTEM SET ... SCOPE=SPFILE` statement to update a server parameter file
- By issuing an `ALTER SYSTEM RESET ... SCOPE=SPFILE` statement to remove a parameter from a server parameter file, causing the default value to take effect the next time you start an instance of the database.

Parameters by Functional Category

The following list shows the initialization parameters by their functional category:

- **ANSI Compliance**
BLANK_TRIMMING

- **Backup and Restore**

BACKUP_TAPE_IO_SLAVES
RECYCLEBIN
TAPE_ASYNC_IO

- **BFILEs**

SESSION_MAX_OPEN_FILES

- **Buffer Cache and I/O**

CLIENT_RESULT_CACHE_LAG
CLIENT_RESULT_CACHE_SIZE
DB_nK_CACHE_SIZE
DB_BLOCK_BUFFERS
DB_BLOCK_SIZE
DB_CACHE_ADVICE
DB_CACHE_SIZE
DB_FILE_MULTIBLOCK_READ_COUNT
DB_KEEP_CACHE_SIZE
DB_RECYCLE_CACHE_SIZE
DB_WRITER_PROCESSES
DBWR_IO_SLAVES
DISK_ASYNC_IO
FILESYSTEMIO_OPTIONS
READ_ONLY_OPEN_DELAYED
RESULT_CACHE_MAX_RESULT
RESULT_CACHE_MAX_SIZE
RESULT_CACHE_MODE
USE_INDIRECT_DATA_BUFFERS

- **Cursors and Library Cache**

CURSOR_BIND_CAPTURE_DESTINATION
CURSOR_SHARING
CURSOR_SPACE_FOR_TIME
OPEN_CURSORS
SESSION_CACHED_CURSORS

- **Database/Instance Identification**

DB_DOMAIN
DB_NAME
INSTANCE_NAME

- **Diagnostics and Statistics**

AWR_SNAPSHOT_TIME_OFFSET
BACKGROUND_CORE_DUMP
BACKGROUND_DUMP_DEST
CORE_DUMP_DEST
DB_BLOCK_CHECKING
DB_BLOCK_CHECKSUM
DIAGNOSTIC_DEST
EVENT
MAX_DUMP_FILE_SIZE

SHADOW_CORE_DUMP
STATISTICS_LEVEL
TIMED_OS_STATISTICS
TIMED_STATISTICS
TRACE_ENABLED
TRACEFILE_IDENTIFIER
USER_DUMP_DEST

■ **Distributed, Replication**

COMMIT_POINT_STRENGTH
DISTRIBUTED_LOCK_TIMEOUT
GLOBAL_NAMES
HS_AUTOREGISTER
OPEN_LINKS
OPEN_LINKS_PER_INSTANCE
REPLICATION_DEPENDENCY_TRACKING

■ **File Locations, Names, and Sizes**

AUDIT_FILE_DEST
BACKGROUND_CORE_DUMP
BACKGROUND_DUMP_DEST
CONTROL_FILES
CORE_DUMP_DEST
DB_CREATE_FILE_DEST
DB_CREATE_ONLINE_LOG_DEST_1
DB_FILES
DB_RECOVERY_FILE_DEST
DB_RECOVERY_FILE_DEST_SIZE
FILE_MAPPING
IFILE
LOG_ARCHIVE_DEST_1
SPFILE

■ **Globalization**

NLS_CALENDAR
NLS_COMP
NLS_CURRENCY
NLS_DATE_FORMAT
NLS_DATE_LANGUAGE
NLS_DUAL_CURRENCY
NLS_ISO_CURRENCY
NLS_LANGUAGE
NLS_LENGTH_SEMANTICS
NLS_NCHAR_CONV_EXCP
NLS_NUMERIC_CHARACTERS
NLS_SORT
NLS_TERRITORY
NLS_TIMESTAMP_FORMAT
NLS_TIMESTAMP_TZ_FORMAT

■ **Java**

JAVA_JIT_ENABLED
JAVA_MAX_SESSIONSPACE_SIZE

JAVA_POOL_SIZE
JAVA_SOFT_SESSIONSPACE_LIMIT

- **Job Queues**

JOB_QUEUE_PROCESSES

- **License Limits**

LICENSE_MAX_SESSIONS
LICENSE_MAX_USERS
LICENSE_SESSIONS_WARNING

- **Memory**

MEMORY_MAX_TARGET
MEMORY_TARGET

- **Miscellaneous**

AQ_TM_PROCESSES
ASM_PREFERRED_READ_FAILURE_GROUPS
COMPATIBLE
FIXED_DATE
LDAP_DIRECTORY_SYSAUTH
XML_DB_EVENTS

- **Networking**

LOCAL_LISTENER
REMOTE_LISTENER
SERVICE_NAMES

- **Objects and LOBs**

OBJECT_CACHE_MAX_SIZE_PERCENT
OBJECT_CACHE_OPTIMAL_SIZE

- **OLAP**

OLAP_PAGE_POOL_SIZE

- **Optimizer**

OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES
OPTIMIZER_DYNAMIC_SAMPLING
OPTIMIZER_FEATURES_ENABLE
OPTIMIZER_INDEX_CACHING
OPTIMIZER_INDEX_COST_ADJ
OPTIMIZER_MODE
OPTIMIZER_SECURE_VIEW_MERGING
OPTIMIZER_USE_PENDING_STATISTICS
OPTIMIZER_USE_SQL_PLAN_BASELINES
QUERY_REWRITE_ENABLED
QUERY_REWRITE_INTEGRITY
STAR_TRANSFORMATION_ENABLED

- **Parallel Execution**

PARALLEL_ADAPTIVE_MULTI_USER

PARALLEL_EXECUTION_MESSAGE_SIZE
PARALLEL_MAX_SERVERS
PARALLEL_MIN_PERCENT
PARALLEL_MIN_SERVERS
PARALLEL_THREADS_PER_CPU

- **PL/SQL**

PLSQL_V2_COMPATIBILITY
REMOTE_DEPENDENCIES_MODE
UTL_FILE_DIR

- **PL/SQL Compiler**

PLSCOPE_SETTINGS
PLSQL_CCFLAGS
PLSQL_CODE_TYPE
PLSQL_DEBUG
PLSQL_OPTIMIZE_LEVEL
PLSQL_WARNINGS
NLS_LENGTH_SEMANTICS

- **SGA Memory**

DB_nK_CACHE_SIZE
DB_CACHE_SIZE
HI_SHARED_MEMORY_ADDRESS
JAVA_POOL_SIZE
LARGE_POOL_SIZE
LOCK_SGA
OLAP_PAGE_POOL_SIZE
PRE_PAGE_SGA
SGA_MAX_SIZE
SGA_TARGET
SHARED_MEMORY_ADDRESS
SHARED_POOL_RESERVED_SIZE
SHARED_POOL_SIZE
STREAMS_POOL_SIZE

- **Oracle RAC**

ACTIVE_INSTANCE_COUNT
CLUSTER_DATABASE
CLUSTER_DATABASE_INSTANCES
CLUSTER_INTERCONNECTS
INSTANCE_NUMBER
PARALLEL_INSTANCE_GROUP
THREAD

- **Redo Logs, Archiving, and Recovery**

CONTROL_FILE_RECORD_KEEP_TIME
DB_CREATE_ONLINE_LOG_DEST_n
DB_RECOVERY_FILE_DEST
DB_RECOVERY_FILE_DEST_SIZE
DB_UNRECOVERABLE_SCN_TRACKING
FAST_START_MTTR_TARGET
LOG_BUFFER

LOG_CHECKPOINT_INTERVAL
LOG_CHECKPOINT_TIMEOUT
LOG_CHECKPOINTS_TO_ALERT
LOG_ARCHIVE_CONFIG
LOG_ARCHIVE_DEST_*n*
LOG_ARCHIVE_DEST_STATE_*n*
LOG_ARCHIVE_DUPLEX_DEST
LOG_ARCHIVE_FORMAT
LOG_ARCHIVE_MAX_PROCESSES
LOG_ARCHIVE_MIN_SUCCEED_DEST
LOG_ARCHIVE_TRACE
REDO_TRANSPORT_USER
RECOVERY_PARALLELISM

■ **Resource Manager**

RESOURCE_LIMIT
RESOURCE_MANAGER_CPU_ALLOCATION
RESOURCE_MANAGER_PLAN

■ **Security and Auditing**

AUDIT_FILE_DEST
AUDIT_SYS_OPERATIONS
AUDIT_SYSLOG_LEVEL
AUDIT_TRAIL
COMMIT_LOGGING
COMMIT_WAIT
O7_DICTIONARY_ACCESSIBILITY
OS_AUTHENT_PREFIX
OS_ROLES
RDBMS_SERVER_DN
REMOTE_LOGIN_PASSWORDFILE
REMOTE_OS_AUTHENT
REMOTE_OS_ROLES
SEC_CASE_SENSITIVE_LOGON
SEC_MAX_FAILED_LOGIN_ATTEMPTS
SEC_PROTOCOL_ERROR_FURTHER_ACTION
SEC_PROTOCOL_ERROR_TRACE_ACTION
SEC_RETURN_SERVER_RELEASE_BANNER
SQL92_SECURITY

■ **Sessions and Processes**

CPU_COUNT
PROCESSES
SESSIONS

■ **Shared Server Architecture**

CIRCUITS
DISPATCHERS
MAX_DISPATCHERS
MAX_SHARED_SERVERS
SHARED_SERVER_SESSIONS
SHARED_SERVERS

- **Standby Database**

ARCHIVE_LAG_TARGET
 DB_FILE_NAME_CONVERT
 DB_UNIQUE_NAME
 DG_BROKER_CONFIG_FILE*n*
 DG_BROKER_START
 FAL_CLIENT
 FAL_SERVER
 LOG_FILE_NAME_CONVERT
 STANDBY_FILE_MANAGEMENT

- **Temporary Sort Space**

BITMAP_MERGE_AREA_SIZE
 CREATE_BITMAP_AREA_SIZE
 HASH_AREA_SIZE
 PGA_AGGREGATE_TARGET
 SORT_AREA_RETAINED_SIZE
 SORT_AREA_SIZE
 WORKAREA_SIZE_POLICY

- **Transactions**

COMMIT_LOGGING
 COMMIT_WAIT
 DB_LOST_WRITE_PROTECT
 DDL_LOCK_TIMEOUT
 DML_LOCKS
 FAST_START_PARALLEL_ROLLBACK
 GLOBAL_TXN_PROCESSES
 TRANSACTIONS

- **Undo Management**

RESUMABLE_TIMEOUT
 ROLLBACK_SEGMENTS
 TRANSACTIONS_PER_ROLLBACK_SEGMENT
 UNDO_MANAGEMENT
 UNDO_RETENTION
 UNDO_TABLESPACE

Modifiable Parameters

Some initialization parameters can be modified using the `ALTER SESSION` or `ALTER SYSTEM` statements while an instance is running. Use the following syntax to modify initialization parameters:

```
ALTER SESSION SET parameter_name = value
ALTER SYSTEM SET parameter_name = value [DEFERRED]
```

Whenever a parameter is modified using the `ALTER SYSTEM` statement, the Oracle Database records the statement that modifies the parameter in the alert log.

The `ALTER SESSION` statement changes the value of the specified parameter for the duration of the session that invokes the statement. The value of the parameter does not

change for other sessions in the instance. The value of the following initialization parameters can be changed with ALTER SESSION:

```
ASM_POWER_LIMIT
COMMIT_LOGGING
COMMIT_WAIT
COMMIT_WRITE
CREATE_STORED_OUTLINES
CURSOR_BIND_CAPTURE_DESTINATION
CURSOR_SHARING
DB_BLOCK_CHECKING
DB_CREATE_FILE_DEST
DB_CREATE_ONLINE_LOG_DEST_n
DB_FILE_MULTIBLOCK_READ_COUNT
DB_FILE_NAME_CONVERT
DB_SECUREFILE
DB_UNRECOVERABLE_SCN_TRACKING
DDL_LOCK_TIMEOUT
DEFERRED_SEGMENT_CREATION
DST_UPGRADE_INSERT_CONV
ENABLE_DDL_LOGGING
GLOBAL_NAMES
HASH_AREA_SIZE
JAVA_JIT_ENABLED
LOG_ARCHIVE_DEST_n
LOG_ARCHIVE_DEST_STATE_n
LOG_ARCHIVE_MIN_SUCCEED_DEST
MAX_DUMP_FILE_SIZE
NLS_CALENDAR
NLS_COMP
NLS_CURRENCY
NLS_DATE_FORMAT
NLS_DATE_LANGUAGE
NLS_DUAL_CURRENCY
NLS_ISO_CURRENCY
NLS_LANGUAGE
NLS_LENGTH_SEMANTICS
NLS_NCHAR_CONV_EXCP
NLS_NUMERIC_CHARACTERS
NLS_SORT
NLS_TERRITORY
NLS_TIMESTAMP_FORMAT
NLS_TIMESTAMP_TZ_FORMAT
OBJECT_CACHE_MAX_SIZE_PERCENT
OBJECT_CACHE_OPTIMAL_SIZE
OLAP_PAGE_POOL_SIZE
OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES
OPTIMIZER_DYNAMIC_SAMPLING
OPTIMIZER_FEATURES_ENABLE
OPTIMIZER_INDEX_CACHING
OPTIMIZER_INDEX_COST_ADJ
OPTIMIZER_MODE
OPTIMIZER_USE_INVISIBLE_INDEXES
OPTIMIZER_USE_PENDING_STATISTICS
OPTIMIZER_USE_SQL_PLAN_BASELINES
PARALLEL_DEGREE_LIMIT
```

PARALLEL_DEGREE_POLICY
PARALLEL_FORCE_LOCAL
PARALLEL_INSTANCE_GROUP
PARALLEL_IO_CAP_ENABLED
PARALLEL_MIN_PERCENT
PARALLEL_MIN_TIME_THRESHOLD
PLSCOPE_SETTINGS
PLSQL_CCFLAGS
PLSQL_CODE_TYPE
PLSQL_DEBUG
PLSQL_OPTIMIZE_LEVEL
PLSQL_V2_COMPATIBILITY
PLSQL_WARNINGS
QUERY_REWRITE_ENABLED
QUERY_REWRITE_INTEGRITY
RECYCLEBIN
REMOTE_DEPENDENCIES_MODE
RESULT_CACHE_MODE
RESULT_CACHE_REMOTE_EXPIRATION
RESUMABLE_TIMEOUT
SEC_PROTOCOL_ERROR_FURTHER_ACTION
SEC_PROTOCOL_ERROR_TRACE_ACTION
SESSION_CACHED_CURSORS
SKIP_UNUSABLE_INDEXES
SMTP_OUT_SERVER
SORT_AREA_RETAINED_SIZE
SORT_AREA_SIZE
SQL_TRACE
SQLTUNE_CATEGORY
STAR_TRANSFORMATION_ENABLED
STATISTICS_LEVEL
TIMED_OS_STATISTICS
TIMED_STATISTICS
TRACEFILE_IDENTIFIER
WORKAREA_SIZE_POLICY
XML_DB_EVENTS

The `ALTER SYSTEM` statement without the `DEFERRED` keyword modifies the global value of the parameter for all sessions in the instance, for the duration of the instance (until the database is shut down). The value of the following initialization parameters can be changed with `ALTER SYSTEM`:

AQ_TM_PROCESSES
ARCHIVE_LAG_TARGET
ASM_DISKGROUPS
ASM_DISKSTRING
ASM_POWER_LIMIT
ASM_PREFERRED_READ_FAILURE_GROUPS
AWR_SNAPSHOT_TIME_OFFSET
BACKGROUND_DUMP_DEST
CIRCUITS
COMMIT_LOGGING
COMMIT_WAIT
COMMIT_WRITE
CONTROL_FILE_RECORD_KEEP_TIME
CONTROL_MANAGEMENT_PACK_ACCESS

CORE_DUMP_DEST
CPU_COUNT
CREATE_STORED_OUTLINES
CURSOR_BIND_CAPTURE_DESTINATION
CURSOR_SHARING
DB_nK_CACHE_SIZE
DB_BLOCK_CHECKING
DB_BLOCK_CHECKSUM
DB_CACHE_ADVICE
DB_CACHE_SIZE
DB_CREATE_FILE_DEST
DB_CREATE_ONLINE_LOG_DEST_n
DB_FILE_MULTIBLOCK_READ_COUNT
DB_FLASH_CACHE_SIZE
DB_FLASHBACK_RETENTION_TARGET
DB_KEEP_CACHE_SIZE
DB_LOST_WRITE_PROTECT
DB_RECOVERY_FILE_DEST
DB_RECOVERY_FILE_DEST_SIZE
DB_RECYCLE_CACHE_SIZE
DB_SECUREFILE
DB_UNRECOVERABLE_SCN_TRACKING
DDL_LOCK_TIMEOUT
DEFERRED_SEGMENT_CREATION
DG_BROKER_CONFIG_FILEn
DG_BROKER_START
DIAGNOSTIC_DEST
DISPATCHERS
DST_UPGRADE_INSERT_CONV
ENABLE_DDL_LOGGING
FAL_CLIENT
FAL_SERVER
FAST_START_MTTR_TARGET
FAST_START_PARALLEL_ROLLBACK
FILE_MAPPING
FIXED_DATE
GLOBAL_NAMES
GLOBAL_TXN_PROCESSES
HS_AUTOREGISTER
JAVA_JIT_ENABLED
JAVA_POOL_SIZE
JOB_QUEUE_PROCESSES
LARGE_POOL_SIZE
LDAP_DIRECTORY_ACCESS
LICENSE_MAX_SESSIONS
LICENSE_MAX_USERS
LICENSE_SESSIONS_WARNING
LISTENER_NETWORKS
LOCAL_LISTENER
LOG_ARCHIVE_CONFIG
LOG_ARCHIVE_DEST
LOG_ARCHIVE_DEST_n
LOG_ARCHIVE_DEST_STATE_n
LOG_ARCHIVE_DUPLEX_DEST
LOG_ARCHIVE_LOCAL_FIRST

LOG_ARCHIVE_MAX_PROCESSES
LOG_ARCHIVE_MIN_SUCCEED_DEST
LOG_ARCHIVE_TRACE
LOG_CHECKPOINT_INTERVAL
LOG_CHECKPOINT_TIMEOUT
LOG_CHECKPOINTS_TO_ALERT
MAX_DISPATCHERS
MAX_DUMP_FILE_SIZE
MAX_SHARED_SERVERS
MEMORY_TARGET
NLS_LENGTH_SEMANTICS
NLS_NCHAR_CONV_EXCP
OPEN_CURSORS
OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES
OPTIMIZER_DYNAMIC_SAMPLING
OPTIMIZER_FEATURES_ENABLE
OPTIMIZER_INDEX_CACHING
OPTIMIZER_INDEX_COST_ADJ
OPTIMIZER_MODE
OPTIMIZER_SECURE_VIEW_MERGING
OPTIMIZER_USE_INVISIBLE_INDEXES
OPTIMIZER_USE_PENDING_STATISTICS
OPTIMIZER_USE_SQL_PLAN_BASELINES
PARALLEL_ADAPTIVE_MULTI_USER
PARALLEL_DEGREE_LIMIT
PARALLEL_DEGREE_POLICY
PARALLEL_FORCE_LOCAL
PARALLEL_INSTANCE_GROUP
PARALLEL_IO_CAP_ENABLED
PARALLEL_MAX_SERVERS
PARALLEL_MIN_SERVERS
PARALLEL_MIN_TIME_THRESHOLD
PARALLEL_SERVERS_TARGET
PARALLEL_THREADS_PER_CPU
PGA_AGGREGATE_TARGET
PLSCOPE_SETTINGS
PLSQL_CCFLAGS
PLSQL_CODE_TYPE
PLSQL_DEBUG
PLSQL_OPTIMIZE_LEVEL
PLSQL_V2_COMPATIBILITY
PLSQL_WARNINGS
QUERY_REWRITE_ENABLED
QUERY_REWRITE_INTEGRITY
REDO_TRANSPORT_USER
REMOTE_DEPENDENCIES_MODE
REMOTE_LISTENER
RESOURCE_LIMIT
RESOURCE_MANAGER_CPU_ALLOCATION
RESOURCE_MANAGER_PLAN
RESULT_CACHE_MAX_RESULT
RESULT_CACHE_MAX_SIZE
RESULT_CACHE_MODE
RESULT_CACHE_REMOTE_EXPIRATION
RESUMABLE_TIMEOUT

```

SEC_CASE_SENSITIVE_LOGON
SEC_PROTOCOL_ERROR_FURTHER_ACTION
SEC_PROTOCOL_ERROR_TRACE_ACTION
SERVICE_NAMES
SGA_TARGET
SHARED_POOL_SIZE
SHARED_SERVER_SESSIONS
SHARED_SERVERS
SKIP_UNUSABLE_INDEXES
SMTP_OUT_SERVER
SPFILE
SQL_TRACE
SQLTUNE_CATEGORY
STANDBY_ARCHIVE_DEST
STANDBY_FILE_MANAGEMENT
STAR_TRANSFORMATION_ENABLED
STATISTICS_LEVEL
STREAMS_POOL_SIZE
THREAD
TIMED_OS_STATISTICS
TIMED_STATISTICS
TRACE_ENABLED
UNDO_RETENTION
UNDO_TABLESPACE
USER_DUMP_DEST
WORKAREA_SIZE_POLICY
XML_DB_EVENTS

```

The `ALTER SYSTEM ... DEFERRED` statement does not modify the global value of the parameter for existing sessions, but the value will be modified for future sessions that connect to the database. The value of the following initialization parameters can be changed with `ALTER SYSTEM ... DEFERRED`:

```

AUDIT_FILE_DEST
BACKUP_TAPE_IO_SLAVES
OBJECT_CACHE_MAX_SIZE_PERCENT
OBJECT_CACHE_OPTIMAL_SIZE
OLAP_PAGE_POOL_SIZE
RECYCLEBIN
SORT_AREA_RETAINED_SIZE
SORT_AREA_SIZE

```

Displaying Current Parameter Values

To see the current settings for initialization parameters, use the following SQL*Plus command:

```
SQL> SHOW PARAMETERS
```

This command displays all parameters in alphabetical order, along with their current values.

Enter the following text string to display all parameters having `BLOCK` in their names:

```
SQL> SHOW PARAMETERS BLOCK
```

You can use the `SPOOL` command to write the output to a file.

Parameters You Should Not Specify in the Parameter File

You should not specify the following two types of parameters in your parameter files:

- Parameters that you never alter except when instructed to do so by Oracle to resolve a problem
- Derived parameters, which normally do not need altering because their values are calculated automatically by the Oracle database server

When Parameters Are Set Incorrectly

Some parameters have a minimum setting below which an Oracle instance will not start. For other parameters, setting the value too low or too high may cause Oracle to perform badly, but it will still run. Also, Oracle may convert some values outside the acceptable range to usable levels.

If a parameter value is too low or too high, or you have reached the maximum for some resource, then Oracle returns an error. Frequently, you can wait a short while and retry the operation when the system is not as busy. If a message occurs repeatedly, then you should shut down the instance, adjust the relevant parameter, and restart the instance.

Reading the Parameter Descriptions

The parameter descriptions in this chapter adhere to the following format.

PARAMETER_NAME

Property	Description
Parameter type	Specifies the type of the parameter: ■ A Boolean parameter accepts either <code>true</code> or <code>false</code> as its value. ■ A string parameter accepts any sequence of characters as its value, subject to the syntax for the parameter. ■ An integer parameter accepts a 4-byte value that can range from 0 to $2^{32} - 1$. ■ A parameter file parameter accepts an initialization parameter file specification as its value. ■ A big integer parameter accepts an 8-byte value that can range from 0 to $2^{64} - 1$. You specify a value for a big integer as an integer together with an optional modifier such as K, M, or G, which respectively denotes kilobytes, megabytes, or gigabytes. For example, 1000, 100 KB, 50 MB and 2 GB are valid specifications for big integers.
Syntax	For string and big integer parameters, specifies the valid syntax for specifying the parameter.
Default value	Specifies the value this parameter assumes if not explicitly specified.

Property	Description
Modifiable	Specifies whether the parameter can be changed for the current session (by an <code>ALTER SESSION</code> statement) or for all sessions in the current instance (by an <code>ALTER SYSTEM</code> statement): ■ <code>ALTER SESSION</code> overrides the instance-wide setting of the parameter for the current session only. You can restore the instance-wide setting for that session only by issuing another <code>ALTER SESSION</code> statement. ■ <code>ALTER SYSTEM</code> can be used to change the value in the server parameter file (SPFILE) of any initialization parameter. Such a change takes effect only in subsequent instances. The parameter descriptions indicate only those parameters that can be modified for the current instance.
Range of values	Specifies the valid range of values that this parameter can assume, shown as a minimum and maximum value. Not applicable to all parameters.
Oracle RAC	Specifies how the values for this parameter must be specified for multiple instances in an Oracle Real Application Clusters environment. Not applicable to all parameters.

For each parameter, paragraphs following these details further describe the parameter and the effects of different settings.

Initialization Parameter Descriptions

The remainder of this chapter describes the initialization parameters in alphabetical order. Initialization parameter values apply to the entire database, not to an individual user, unless otherwise specified.

Note: Parameters that have become obsolete are not documented.

See Also:

- *Oracle Database Upgrade Guide* for information about obsolete parameters
- Your system release bulletins or other operating system-specific Oracle documentation

ACTIVE_INSTANCE_COUNT

Property	Description
Parameter type	Integer
Default value	There is no default value.
Modifiable	No
Range of values	1 or $\geq$ the number of instances in the cluster. (Values other than 1 have no effect on the active or standby status of any instances.)
Basic	No

Property	Description
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

Note: The `ACTIVE_INSTANCE_COUNT` parameter is deprecated. It is retained for backward compatibility only.

`ACTIVE_INSTANCE_COUNT` enables you to designate one instance in a two-instance cluster as the primary instance and the other instance as the secondary instance. This parameter has no functionality in a cluster with more than two instances.

When you set this parameter to 1, the first instance you start up becomes the primary instance and accepts client connections. The second instance starts up as a secondary instance and can accept client connections only if the first instance fails. In such an event, the secondary instance becomes the primary instance.

When the failed instance can once again be started up, it starts up as the secondary instance, and will not accept client connections unless the current primary instance fails.

Note: This parameter functions only in a cluster with only two instances.

See Also: The *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Installation Guide* for your operating system for more information on setting this parameter

AQ_TM_PROCESSES

Property	Description
Parameter type	Integer
Default value	1
Modifiable	ALTER SYSTEM
Range of values	0 to 40
Basic	No

`AQ_TM_PROCESSES` controls time monitoring on queue messages and controls processing of messages with delay and expiration properties specified. You do not need to specify a value for this parameter because Oracle Database automatically determines the number of processes and autotunes them, as necessary. Therefore, Oracle highly recommends that you leave the `AQ_TM_PROCESSES` parameter unspecified and let the system autotune.

The default value for `AQ_TM_PROCESSES` is used if the client does not explicitly set a value for the parameter in the `init.ora` file or using the `ALTER SYSTEM` command.

Note: If you want to disable the Queue Monitor Coordinator, then you must set AQ_TM_PROCESSES to 0 in your parameter file. Oracle strongly recommends that you do NOT set AQ_TM_PROCESSES to 0. If you are using Oracle Streams, then setting this parameter to zero (which Oracle Database respects no matter what) can cause serious problems.

See Also: *Oracle Streams Advanced Queuing User's Guide* for more information about this parameter and Advanced Queuing

ARCHIVE_LAG_TARGET

Property	Description
Parameter type	Integer
Default value	0 (disabled)
Modifiable	ALTER SYSTEM
Range of values	0 or any integer in [60, 7200]
Basic	No
Oracle RAC	Multiple instances should use the same value.

ARCHIVE_LAG_TARGET limits the amount of data that can be lost and effectively increases the availability of the standby database by forcing a log switch after the specified amount of time elapses.

A 0 value disables the time-based thread advance feature; otherwise, the value represents the number of seconds. Values larger than 7200 seconds are not of much use in maintaining a reasonable lag in the standby database. The typical, or recommended value is 1800 (30 minutes). Extremely low values can result in frequent log switches, which could degrade performance; such values can also make the archiver process too busy to archive the continuously generated logs.

See Also: *Oracle Data Guard Concepts and Administration* for more information about criteria for setting this parameter

ASM_DISKGROUPS

Property	Description
Parameter type	String
Syntax	ASM_DISKGROUPS = <i>diskgroup</i> [, <i>diskgroup</i>] ...
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Range of values	Comma-separated list of strings, up to 30 characters
Oracle RAC	Multiple instances can have different values.

Note: This parameter may only be specified in an Automatic Storage Management instance.

ASM_DISKGROUPS specifies a list of names of disk groups to be mounted by an Automatic Storage Management instance at instance startup. Oracle ignores the value that you set for ASM_DISKGROUPS when you specify the NOMOUNT option at startup or when a `ALTER DISKGROUP ALL MOUNT` statement is issued.

Automatic Storage Management (ASM) automatically adds a disk group to this parameter when the disk group is successfully created or mounted, and automatically removes a disk group from this parameter when the disk group is dropped or dismounted.

Issuing the `ALTER DISKGROUP...ALL MOUNT` or `ALTER DISKGROUP...ALL DISMOUNT` command does not affect the value of this parameter.

ASM_DISKSTRING

Property	Description
Parameter type	String
Syntax	<code>ASM_DISKSTRING = discovery_string [, discovery_string] ...</code>
Default value	The null string; Automatic Storage Management discovery finds all disks in an operating system-specific location to which the Automatic Storage Management instance has read/write access.
Modifiable	<code>ALTER SYSTEM</code>
Oracle RAC	Multiple instances can have different values. Different nodes might see the same disks under different names; however, each instance must be able to use its ASM_DISKSTRING to discover the same physical media as the other nodes in the cluster.

Note: This parameter may only be specified in an Automatic Storage Management instance.

ASM_DISKSTRING specifies an operating system-dependent value used by Automatic Storage Management to limit the set of disks considered for discovery. When a new disk is added to a disk group, each Automatic Storage Management instance that has the disk group mounted must be able to discover the new disk using the value of ASM_DISKSTRING.

In most cases, the default value will be sufficient. Using a more restrictive value may reduce the time required for Automatic Storage Management to perform discovery, and thus improve disk group mount time or the time for adding a disk to a disk group. A "?" at the beginning of the string gets expanded to the Oracle home directory. Depending on the operating system, wildcard characters can be used.

It may be necessary to dynamically change ASM_DISKSTRING before adding a disk so that the new disk will be discovered.

An attempt to dynamically modify ASM_DISKSTRING will be rejected and the old value retained if the new value cannot be used to discover a disk that is in a disk group that is already mounted.

ASM_POWER_LIMIT

Property	Description
Parameter type	Integer
Default value	1
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	0 to 11 ¹
Oracle RAC	Multiple instances can have different values.

¹ Beginning with Oracle Database 11g Release 2 (11.2.0.2), if the COMPATIBLE.ASM disk group attribute is set to 11.2.0.2 or higher, then the range of values is 0 to 1024.

Note: This parameter may only be specified in an Automatic Storage Management instance.

ASM_POWER_LIMIT specifies the maximum power on an Automatic Storage Management instance for disk rebalancing. The higher the limit, the faster rebalancing will complete. Lower values will take longer, but consume fewer processing and I/O resources.

If the POWER clause of a rebalance operation is not specified, then the default power will be the value of ASM_POWER_LIMIT.

ASM_PREFERRED_READ_FAILURE_GROUPS

Property	Description
Parameter type	String
Syntax	ASM_PREFERRED_READ_FAILURE_GROUPS = <diskgroup_name>.<failure_group_name>, ...
Default value	NULL
Modifiable	ALTER SYSTEM
Basic	No
Oracle RAC	The value is different on different nodes

ASM_PREFERRED_READ_FAILURE_GROUPS specifies the failure groups that contain preferred read disks. Preferred disks are instance specific. This parameter is only valid in ASM instances.

AUDIT_FILE_DEST

Property	Description
Parameter type	String
Syntax	AUDIT_FILE_DEST = 'directory'

Property	Description
Default value	The first default value is: <i>ORACLE_BASE/admin/ORACLE_SID/adump</i> The second default value, which is used if the first default value does not exist or is unusable, is: <i>ORACLE_HOME/rdbms/audit</i> Both of these default values are for Unix systems. Other platforms may have different defaults.
Modifiable	ALTER SYSTEM ... DEFERRED
Basic	No

AUDIT_FILE_DEST specifies the operating system directory into which the audit trail is written when the AUDIT_TRAIL initialization parameter is set to **os**, **xml**, or **xml,extended**. The audit records will be written in XML format if the AUDIT_TRAIL initialization parameter is set to **xml** or **xml, extended**. It is also the location to which mandatory auditing information is written and, if so specified by the AUDIT_SYS_OPERATIONS initialization parameter, audit records for user SYS.

AUDIT_SYS_OPERATIONS

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false
Basic	No

AUDIT_SYS_OPERATIONS enables or disables the auditing of top-level operations, which are SQL statements directly issued by users when connecting with SYSDBA or SYSOPER privileges. (SQL statements run from within PL/SQL procedures or functions are not considered top-level.) The audit records are written to the operating system's audit trail. The audit records will be written in XML format if the AUDIT_TRAIL initialization parameter is set to **xml** or **xml, extended**.

On UNIX platforms, if the AUDIT_SYSLOG_LEVEL parameter has also been set, then it overrides the AUDIT_TRAIL parameter and SYS audit records are written to the system audit log using the SYSLOG utility.

AUDIT_SYSLOG_LEVEL

Property	Description
Parameter type	String
Syntax	AUDIT_SYSLOG_LEVEL = ' <i>facility_clause.priority_clause</i> '

Property	Description
	facility_clause::= { USER LOCAL[0 1 2 3 4 5 6 7] SYSLOG DAEMON KERN MAIL AUTH LPR NEWS UUCP CRON } priority_clause::= { NOTICE INFO DEBUG WARNING ERR CRIT ALERT EMERG }
Default value	There is no default value.
Modifiable	No
Basic	No
Examples	AUDIT_SYSLOG_LEVEL = 'KERN.EMERG'; AUDIT_SYSLOG_LEVEL = 'LOCAL1.WARNING';

AUDIT_SYSLOG_LEVEL allows SYS and standard OS audit records to be written to the system audit log using the SYSLOG utility.

If you use this parameter, it is best to assign a file corresponding to every combination of facility and priority (especially KERN.EMERG) in `syslog.conf`. Sometimes these are assigned to print to the console in the default `syslog.conf` file. This can become annoying and will be useless as audit logs. Also, if you use this parameter, it is best to set the maximum length of syslog messages in the system to 512 bytes.

If AUDIT_SYSLOG_LEVEL is set and SYS auditing is enabled (AUDIT_SYS_OPERATIONS = TRUE), then SYS audit records are written to the system audit log. If AUDIT_SYSLOG_LEVEL is set and standard audit records are being sent to the operating system (AUDIT_TRAIL = OS), then standard audit records are written to the system audit log.

See Also: *Oracle Database Security Guide* for more information about configuring the syslog audit trail by using the AUDIT_SYSLOG_LEVEL parameter

AUDIT_TRAIL

Property	Description
Parameter type	String
Syntax	AUDIT_TRAIL = { none os db [, extended] xml [, extended] }
Default value	none
Modifiable	No
Basic	No

AUDIT_TRAIL enables or disables database auditing.

Values:

- none

Disables standard auditing. This value is the default if the AUDIT_TRAIL parameter was not set in the initialization parameter file or if you created the

database using a method other than Database Configuration Assistant. If you created the database using Database Configuration Assistant, then the default is `db`.

- `os`

Directs all audit records to an operating system file. Oracle recommends that you use the `os` setting, particularly if you are using an ultra-secure database configuration.

- `db`

Directs audit records to the database audit trail (the `SYS.AUD$` table), except for records that are always written to the operating system audit trail. Use this setting for a general database for manageability.

If the database was started in read-only mode with `AUDIT_TRAIL` set to `db`, then Oracle Database internally sets `AUDIT_TRAIL` to `os`. Check the alert log for details.

- `db, extended`

Performs all actions of `AUDIT_TRAIL=db`, and also populates the SQL bind and SQL text CLOB-type columns of the `SYS.AUD$` table, when available. These two columns are populated only when this parameter is specified.

If the database was started in read-only mode with `AUDIT_TRAIL` set to `db, extended`, then Oracle Database internally sets `AUDIT_TRAIL` to `os`. Check the alert log for details.

- `xml`

Writes to the operating system audit record file in XML format. Records all elements of the `AuditRecord` node except `Sql_Text` and `Sql_Bind` to the operating system XML audit file.

- `xml, extended`

Performs all actions of `AUDIT_TRAIL=xml`, and populates the SQL bind and SQL text CLOB-type columns of the `SYS.AUD$` table, wherever possible. These columns are populated only when this parameter is specified.

You can use the SQL `AUDIT` statement to set auditing options regardless of the setting of this parameter.

AWR_SNAPSHOT_TIME_OFFSET

Property	Description
Parameter type	Integer
Default value	There is no offset by default
Modifiable	<code>ALTER SYSTEM</code>
Range of values	0 - 3599, or the special value 1000000
Basic	No
Oracle RAC	Multiple instances should use the same value

`AWR_SNAPSHOT_TIME_OFFSET` specifies an offset for the AWR snapshot start time.

AWR snapshots normally start at the top of the hour (12:00, 1:00, 2:00, and so on). This parameter allows DBAs to specify an offset for the AWR snapshot start time.

This is a useful parameter to avoid CPU spikes from multiple instances all starting their AWR snapshots at the same time. If you have a large system with many instances on it (like many Exadata installations), and you are experiencing such CPU spikes, this parameter can be very useful.

The parameter is specified in seconds. Normally, you set it to a value less than 3600. If you set the special value 1000000 (1,000,000), you get an automatic mode, in which the offset is based on the database name.

The automatic mode is an effective way of getting a reasonable distribution of offset times when you have a very large number of instances running on the same node.

BACKGROUND_CORE_DUMP

Property	Description
Parameter type	String
Syntax	<code>BACKGROUND_CORE_DUMP = { partial full }</code>
Default value	<code>partial</code>
Modifiable	No
Basic	No

`BACKGROUND_CORE_DUMP` specifies whether Oracle includes the SGA in the core file for Oracle background processes.

Values:

- `partial`
Oracle does not include the SGA in the core dump.
- `full`
Oracle includes the SGA in the core dump.

See Also: ["SHADOW_CORE_DUMP"](#) on page 1-159

BACKGROUND_DUMP_DEST

Property	Description
Parameter type	String
Syntax	<code>BACKGROUND_DUMP_DEST = { pathname directory }</code>
Default value	Operating system-dependent
Modifiable	<code>ALTER SYSTEM</code>
Range of values	Any valid local path, directory, or disk
Basic	No

BACKGROUND_DUMP_DEST specifies the pathname (directory or disc) where debugging trace files for the background processes (LGWR, DBWn, and so on) are written during Oracle operations.

An **alert file** in the directory specified by BACKGROUND_DUMP_DEST logs significant database events and messages. Anything that affects the database instance or global database is recorded here. The alert file is a normal text file. Its filename is operating system-dependent. For platforms that support multiple instances, it takes the form alert_sid.log, where sid is the system identifier. This file grows slowly, but without limit, so you might want to delete it periodically. You can delete the file even when the database is running.

Note: This parameter is ignored by the new diagnosability infrastructure introduced in Oracle Database 11g Release 1, which places trace and core files in a location controlled by the DIAGNOSTIC_DEST initialization parameter.

See Also:

- *Oracle Database Administrator's Guide* for more information on setting this parameter and on alert files
- Your operating system-specific Oracle documentation for the default value of this parameter
- ["USER_DUMP_DEST"](#) on page 1-178 for information on setting a destination for server process trace files

BACKUP_TAPE_IO_SLAVES

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SYSTEM ... DEFERRED
Range of values	true false
Basic	No

BACKUP_TAPE_IO_SLAVES specifies whether I/O server processes (also called **slaves**) are used by Recovery Manager to back up, copy, or restore data to tape. When the value is set to true, Oracle uses an I/O server process to write to or read from a tape device. When the value is set to false (the default), Oracle does not use I/O server process for backups. Instead, the shadow process engaged in the backup accesses the tape device.

Note: You cannot perform duplexed backups unless you enable this parameter. Otherwise, Oracle returns an error. When this parameter is enabled, Recovery Manager will configure as many server processes as needed for the number of backup copies requested.

See Also:

- *Oracle Database Backup and Recovery User's Guide* for more information on duplexed backups
- ["DBWR_IO_SLAVES"](#) on page 1-59

BITMAP_MERGE_AREA_SIZE

Property	Description
Parameter type	Integer
Default value	1048576 (1 MB)
Modifiable	No
Range of values	Operating system-dependent
Basic	No

Note: Oracle does not recommend using the `BITMAP_MERGE_AREA_SIZE` parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting `PGA_AGGREGATE_TARGET` instead. `BITMAP_MERGE_AREA_SIZE` is retained for backward compatibility.

`BITMAP_MERGE_AREA_SIZE` is relevant only for systems containing bitmap indexes. It specifies the amount of memory Oracle uses to merge bitmaps retrieved from a range scan of the index. The default value is 1 MB. A larger value usually improves performance, because the bitmap segments must be sorted before being merged into a single bitmap.

See Also: *Oracle Database Performance Tuning Guide* for more information on setting this parameter

BLANK_TRIMMING

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false
Basic	No

`BLANK_TRIMMING` specifies the data assignment semantics of character datatypes.

Values:

- `TRUE`

Allows the data assignment of a source character string or variable to a destination character column or variable even though the source length is longer than the destination length. In this case, however, the additional length over the destination

length must be all blanks, else an exception condition is raised. This value complies with the semantics of SQL-92 Transitional Level and above.

- FALSE

Disallows the data assignment if the source length is longer than the destination length and reverts to SQL92 Entry Level semantics.

CIRCUITS

Property	Description
Parameter type	Integer
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Basic	No

CIRCUITS specifies the total number of virtual circuits that are available for inbound and outbound network sessions. It is one of several parameters that contribute to the total SGA requirements of an instance.

You should not specify a value for this parameter unless you want to limit the number of virtual circuits.

See Also: *Oracle Database Concepts* for more information on memory structures and processes

CLIENT_RESULT_CACHE_LAG

Property	Description
Parameter type	Big integer
Syntax	CLIENT_RESULT_CACHE_LAG = <i>integer</i> [K M G]
Default value	3000
Modifiable	No
Range of values	0 to operating system-dependent
Basic	No

CLIENT_RESULT_CACHE_LAG specifies the maximum time (in milliseconds) since the last round trip to the server, before which the OCI client query execute makes a round trip to get any database changes related to the queries cached on the client.

See Also: *Oracle Call Interface Programmer's Guide* for more information about the client query cache feature

CLIENT_RESULT_CACHE_SIZE

Property	Description
Parameter type	Big integer

Property	Description
Syntax	<code>CLIENT_RESULT_CACHE_SIZE = integer [K M G]</code>
Default value	0
Modifiable	No
Range of values	0 to operating system-dependent
Basic	No

`CLIENT_RESULT_CACHE_SIZE` specifies the maximum size of the client per-process result set cache (in bytes). All OCI client processes inherit this maximum size. Setting a nonzero value enables the client query cache feature. This can be overridden by the client configuration parameter `OCI_RESULT_CACHE_MAX_SIZE`.

See Also: *Oracle Call Interface Programmer's Guide* for more information about the client query cache feature

CLUSTER_DATABASE

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false
Basic	Yes
Oracle RAC	For all instances, the value must be set to true.

`CLUSTER_DATABASE` is an Oracle RAC parameter that specifies whether or not Oracle RAC is enabled.

See Also: *Oracle Real Application Clusters Administration and Deployment Guide*

CLUSTER_DATABASE_INSTANCES

Property	Description
Parameter type	Integer
Default value	If <code>CLUSTER_DATABASE</code> is set to false, then 1 If <code>CLUSTER_DATABASE</code> is set to true: ■ If ASM, then 4 ■ Otherwise, the number of configured Oracle RAC instances
Modifiable	No
Range of values	Any nonzero value
Basic	No
Oracle RAC	Multiple instances must have the same value.

CLUSTER_DATABASE_INSTANCES is an Oracle RAC parameter that specifies the number of instances that are configured as part of the cluster database. You must set this parameter for every instance. Normally you should set this parameter to the number of instances in your Oracle RAC environment. A proper setting for this parameter can improve memory use.

Oracle uses the value of this parameter to compute the default value of the LARGE_POOL_SIZE parameter when the PARALLEL_AUTOMATIC_TUNING parameter is set to true. Note that the PARALLEL_AUTOMATIC_TUNING parameter has been deprecated.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on tuning parallel execution
- *Oracle Real Application Clusters Administration and Deployment Guide* for information on Real Application Clusters

CLUSTER_INTERCONNECTS

Property	Description
Parameter type	String
Syntax	CLUSTER_INTERCONNECTS = <i>ifn</i> [: <i>ifn</i>] ...
Default value	There is no default value.
Modifiable	No
Range of values	One or more IP addresses, separated by colons
Basic	No

CLUSTER_INTERCONNECTS can be used in Oracle Real Application Clusters environments to indicate cluster interconnects available for use for the database traffic. Use this parameter if you need to override the default interconnect configured for the database traffic, which is stored in the cluster registry. This procedure also may be useful with Data Warehouse systems that have reduced availability requirements and high interconnect bandwidth demands.

CLUSTER_INTERCONNECTS specifically overrides the following:

- Network classifications stored by `oi.fcfg` in the OCR.
- The default interconnect chosen by Oracle.

If you want to load-balance the interconnect, then Oracle recommends that you use link-bonding at the operating system level, even if you have two databases on the same server, so that multiple interconnects use the same address. Note that multiple private addresses provide load balancing, but do not provide failover unless bonded. If you specify multiple addresses in `init.ora` using CLUSTER_INTERCONNECTS, instead of bonding multiple addresses at the operating system level, then typically availability is reduced, because each network interface card failure will take down that instance.

Refer to your vendor documentation for information about bonding interfaces. Some vendor bonding architectures may require the use of this parameter.

If you have multiple database instances on Oracle Real Application Clusters nodes and want to use a specific interface for each instance, then you can set the CLUSTER_INTERCONNECTS initialization parameter to the IP address for each database instance. For example:

```
hr1.init.ora.cluster_interconnects="192.0.2.111"
oltp3.init.ora.cluster_interconnects="192.0.2.112"
```

If the Oracle RAC interconnect is configured to run on a different interface than the Oracle Clusterware interconnect, then this configuration can cause reduced availability, as failovers or instance evictions can be delayed if the Oracle RAC interconnect fails while the Oracle Clusterware NIC remains up.

See Also: *Oracle Real Application Clusters Administration and Deployment Guide* for additional platform-specific information about using CLUSTER_INTERCONNECTS

COMMIT_LOGGING

Property	Description
Parameter type	String
Syntax	COMMIT_LOGGING = { IMMEDIATE BATCH }
Default value	There is no default value.
Modifiable	Yes (at both session-level and system-level)
Basic	No
Oracle RAC	Each instance may have its own setting

COMMIT_LOGGING is an advanced parameter used to control how redo is batched by Log Writer.

If COMMIT_LOGGING is altered after setting COMMIT_WAIT to FORCE_WAIT, then the FORCE_WAIT option is no longer valid.

COMMIT_POINT_STRENGTH

Property	Description
Parameter type	Integer
Default value	1
Modifiable	No
Range of values	0 to 255
Basic	No

COMMIT_POINT_STRENGTH is relevant only in distributed database systems. It specifies a value that determines the **commit point site** in a distributed transaction. The node in the transaction with the highest value for COMMIT_POINT_STRENGTH will be the commit point site.

The commit point site of a database should reflect the amount of critical shared data in the database. For example, a database on a mainframe computer typically shares more data among users than one on a personal computer. Therefore, COMMIT_POINT_STRENGTH should be set to a higher value for the mainframe computer.

The commit point site stores information about the status of transactions. Other computers in a distributed transaction require this information during Oracle's

two-phase commit, so it is desirable to have machines that are always available as commit point sites. Therefore, set `COMMIT_POINT_STRENGTH` to a higher value on your more available machines.

See Also:

- *Oracle Database Concepts* and *Oracle Database Administrator's Guide* for information on two-phase commit
- Your operating system-specific Oracle documentation for the default value of this parameter

COMMIT_WAIT

Property	Description
Parameter type	String
Syntax	<code>COMMIT_WAIT = { NOWAIT WAIT FORCE_WAIT }</code>
Default value	There is no default value.
Modifiable	Yes (at both session-level and system-level)
Basic	No
Oracle RAC	Each instance may have its own setting

`COMMIT_WAIT` is an advanced parameter used to control when the redo for a commit is flushed to the redo logs.

Be aware that the `NOWAIT` option can cause a failure that occurs after the database receives the commit message, but before the redo log records are written. This can falsely indicate to a transaction that its changes are persistent. Also, it can violate the durability of ACID (Atomicity, Consistency, Isolation, Durability) transactions if the database shuts down unexpectedly.

If the parameter is set to `FORCE_WAIT`, the default behavior (immediate flushing of the redo log buffer with wait) is used. If this is a system setting, the session level and transaction level (`COMMIT_WRITE`) options will be ignored. If this is a session level setting, the transaction level options will be ignored. If `COMMIT_WAIT` is altered after it has been set to `FORCE_WAIT`, then the `FORCE_WAIT` option is no longer valid.

COMMIT_WRITE

Property	Description
Parameter type	String
Syntax	<code>COMMIT_WRITE = '{IMMEDIATE BATCH}, {WAIT NOWAIT}'</code>

Property	Description
Default value	If this parameter is not explicitly specified, then database commit behavior defaults to writing commit records to disk before control is returned to the client. If only <code>IMMEDIATE</code> or <code>BATCH</code> is specified, but not <code>WAIT</code> or <code>NOWAIT</code>, then <code>WAIT</code> mode is assumed. If only <code>WAIT</code> or <code>NOWAIT</code> is specified, but not <code>IMMEDIATE</code> or <code>BATCH</code>, then <code>IMMEDIATE</code> mode is assumed. Be aware that the <code>NOWAIT</code> option can cause a failure that occurs after the database receives the commit message, but before the redo log records are written. This can falsely indicate to a transaction that its changes are persistent. Also, it can violate the durability of ACID (Atomicity, Consistency, Isolation, Durability) transactions if the database shuts down unexpectedly.
Modifiable	Yes (at both session-level and system-level). Values supplied for <code>COMMIT_WRITE</code> in an <code>ALTER SYSTEM</code> or <code>ALTER SESSION</code> statement must be separated by a comma.
Range of values	Single-quoted, comma-separated list of either <code>IMMEDIATE</code> or <code>BATCH</code> , and either <code>WAIT</code> or <code>NOWAIT</code> .
Basic	No
Oracle RAC	Each instance may have its own setting

`COMMIT_WRITE` is an advanced parameter used to control how redo for transaction commits is written to the redo logs. The `IMMEDIATE` and `BATCH` options control how redo is batched by Log Writer. The `WAIT` and `NOWAIT` options control when the redo for a commit is flushed to the redo logs.

Note: The `COMMIT_WRITE` parameter is deprecated. It is retained for backward compatibility only. It is replaced by the `COMMIT_LOGGING` and `COMMIT_WAIT` parameters.

COMPATIBLE

Property	Description
Parameter type	String
Syntax	<code>COMPATIBLE = release_number</code>
Default value	<code>11.2.0</code>
Modifiable	No
Range of values	<code>10.0.0</code> to default release
Basic	Yes
Oracle RAC	Multiple instances must have the same value.

`COMPATIBLE` allows you to use a new release of Oracle, while at the same time guaranteeing backward compatibility with an earlier release. This is helpful if it becomes necessary to revert to the earlier release.

This parameter specifies the release with which Oracle must maintain compatibility. It allows you to take advantage of the maintenance improvements of a new release

immediately in your production systems without testing the new functionality in your environment. Some features of the release may be restricted.

When using a standby database, this parameter must have the same value on both the primary and standby databases.

See Also: *Oracle Database Upgrade Guide* for more information on setting this parameter

CONTROL_FILE_RECORD_KEEP_TIME

Property	Description
Parameter type	Integer
Default value	7 (days)
Modifiable	ALTER SYSTEM
Range of values	0 to 365 (days)
Basic	No

CONTROL_FILE_RECORD_KEEP_TIME specifies the minimum number of days before a reusable record in the control file can be reused. In the event a new record needs to be added to a reusable section and the oldest record has not aged enough, the record section expands. If this parameter is set to 0, then reusable sections never expand, and records are reused as needed.

If the number of reusable records in the control file exceeds the circular reuse record limit UB4MAXVAL, then reusable records will be overwritten even if CONTROL_FILE_RECORD_KEEP_TIME has not elapsed. UB4MAXVAL is defined in the oratypes.h header file, which is found in the public directory. Its value may vary according to the operating system you are using.

Note: This parameter applies only to records in the control file that are circularly reusable (such as archive log records and various backup records). It does not apply to records such as datafile, tablespace, and redo thread records, which are never reused unless the corresponding object is dropped from the tablespace.

See Also:

- ["CONTROL_FILES"](#) on page 1-36
- *Oracle Database Backup and Recovery User's Guide*

CONTROL_FILES

Property	Description
Parameter type	String

Property	Description
Syntax	CONTROL_FILES = <i>filename</i> [, <i>filename</i>] ... Note: The control file name can be an OMF (Oracle Managed Files) name. This occurs when the control file is re-created using the CREATE CONTROLFILE REUSE statement.
Default value	Operating system-dependent
Modifiable	No
Range of values	1 to 8 filenames
Basic	Yes
Oracle RAC	Multiple instances must have the same value.

Every database has a **control file**, which contains entries that describe the structure of the database (such as its name, the timestamp of its creation, and the names and locations of its datafiles and redo files). CONTROL_FILES specifies one or more names of control files, separated by commas.

Oracle recommends that you multiplex multiple control files on different devices or mirror the file at the operating system level.

See Also:

- *Oracle Database Performance Tuning Guide*
- *Oracle Database Administrator's Guide*

CONTROL_MANAGEMENT_PACK_ACCESS

Property	Description
Parameter type	String
Syntax	CONTROL_MANAGEMENT_PACK_ACCESS = { NONE DIAGNOSTIC DIAGNOSTIC+TUNING }
Default value	Enterprise Edition: DIAGNOSTIC+TUNING All other editions: NONE
Modifiable	ALTER SYSTEM
Basic	No

CONTROL_MANAGEMENT_PACK_ACCESS specifies which of the Server Manageability Packs should be active. The following packs are available:

- The DIAGNOSTIC pack includes AWR, ADDM, and so on.
- The TUNING pack includes SQL Tuning Advisor, SQLAccess Advisor, and so on.

A license for DIAGNOSTIC is required for enabling the TUNING pack.

Values:

- NONE
Both packs are not available.
- DIAGNOSTIC
Only the DIAGNOSTIC pack is available.

- DIAGNOSTIC+TUNING

Both packs are available. This is the default.

See Also: *Oracle Database Licensing Information*

CORE_DUMP_DEST

Property	Description
Parameter type	String
Syntax	CORE_DUMP_DEST = <i>directory</i>
Default value	ORACLE_HOME/DBS
Modifiable	ALTER SYSTEM
Basic	No

CORE_DUMP_DEST is primarily a UNIX parameter and may not be supported on your platform. It specifies the directory where Oracle dumps core files.

CPU_COUNT

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Range of values	0 to unlimited
Basic	No

CPU_COUNT specifies the number of CPUs available for Oracle Database to use. On core architectures, it specifies the number of available CPU cores. Various components of Oracle Database are configured based on the number of CPUs, such as the Optimizer, Parallel Query, and Resource Manager.

If CPU_COUNT is set to 0 (its default setting), then Oracle Database continuously monitors the number of CPUs reported by the operating system and uses the current count. If CPU_COUNT is set to a value other than 0, then Oracle Database will use this count rather than the actual number of CPUs, thus disabling dynamic CPU reconfiguration. When Resource Manager is enabled, setting CPU_COUNT limits the CPU utilization to approximately CPU_COUNT processors.

Note: Setting CPU_COUNT to a value greater than the current number of CPUs results in an error. However, if CPU_COUNT is set to a value greater than the current number of CPUs in the initialization parameter file, then CPU_COUNT is capped to the current number of CPUs.

CREATE_BITMAP_AREA_SIZE

Property	Description
Parameter type	Integer
Default value	8388608 (8 MB)
Modifiable	No
Range of values	Operating system-dependent
Basic	No

Note: Oracle does not recommend using the `CREATE_BITMAP_AREA_SIZE` parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting `PGA_AGGREGATE_TARGET` instead. `CREATE_BITMAP_AREA_SIZE` is retained for backward compatibility.

`CREATE_BITMAP_AREA_SIZE` is relevant only for systems containing bitmap indexes. It specifies the amount of memory (in bytes) allocated for bitmap creation. The default value is 8 MB. A larger value may speed up index creation.

Cardinality is the number of unique values in a column in relation to the number of rows in the table. If cardinality is very small, you can set a small value for this parameter. For example, if cardinality is only 2, then the value can be on the order of kilobytes rather than megabytes. As a general rule, the higher the cardinality, the more memory is needed for optimal performance.

See Also: *Oracle Database Performance Tuning Guide* for more information on using bitmap indexes

CREATE_STORED_OUTLINES

Property	Description
Parameter type	String
Syntax	<code>CREATE_STORED_OUTLINES = { true false category_name } [NOOVERRIDE]</code>
Default value	There is no default value.
Modifiable	<code>ALTER SESSION, ALTER SYSTEM</code>
Basic	No

`CREATE_STORED_OUTLINES` determines whether Oracle automatically creates and stores an outline for each query submitted during the session.

Values:

- `true`
Enables automatic outline creation for subsequent queries in the same session. These outlines receive a unique system-generated name and are stored in the `DEFAULT` category. If a particular query already has an outline defined for it in the

DEFAULT category, then that outline will remain and a new outline will not be created.

- `false`

Disables automatic outline creation during the session. This is the default.

- `category_name`

Enables the same behavior as `true` except that any outline created during the session is stored in the `category_name` category.

- `NOOVERRIDE`

`NOOVERRIDE` specifies that this system setting will not override the setting for any session in which this parameter was explicitly set. If you do not specify `NOOVERRIDE`, then this setting takes effect in all sessions.

See Also: *Oracle Database Performance Tuning Guide* for more information on setting this parameter

CURSOR_BIND_CAPTURE_DESTINATION

Property	Description
Parameter type	String
Syntax	<code>CURSOR_BIND_CAPTURE_DESTINATION = { off memory memory+disk }</code>
Default value	<code>memory+disk</code>
Modifiable	<code>ALTER SESSION, ALTER SYSTEM</code>
Basic	No

`CURSOR_BIND_CAPTURE_DESTINATION` determines the location at which bind variables that are captured from SQL cursors are available.

Values:

- `off`

Bind variables are not captured from SQL cursors.

- `memory`

Bind variables are captured from SQL cursors, and are available only in memory (V\$ views).

- `memory+disk`

Bind variables are captured from SQL cursors, and are available in memory (V\$ views) and disk (Automatic Workload Repository tables, SQL Tuning Set tables, and so on).

Note: The `CURSOR_BIND_CAPTURE_DESTINATION` initialization parameter is available starting with Oracle Database 11g Release 2 (11.2.0.2).

CURSOR_SHARING

Property	Description
Parameter type	String
Syntax	CURSOR_SHARING = { SIMILAR EXACT FORCE }
Default value	EXACT
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

CURSOR_SHARING determines what kind of SQL statements can share the same cursors.

Values:

- **FORCE**
Allows the creation of a new cursor if sharing an existing cursor, or if the cursor plan is not optimal.
- **SIMILAR**
Causes statements that may differ in some literals, but are otherwise identical, to share a cursor, unless the literals affect either the meaning of the statement or the degree to which the plan is optimized.
- **EXACT**
Only allows statements with identical text to share the same cursor.

Notes:

- If you set CURSOR_SHARING, then Oracle recommends the FORCE setting unless you are in a DSS environment. FORCE limits the growth of child cursors that can occur when the setting is SIMILAR.
- The value of the CURSOR_SHARING parameter has performance implications. Refer to *Oracle Database Performance Tuning Guide* before setting this parameter.

CURSOR_SPACE_FOR_TIME

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false
Basic	No

Note: The `CURSOR_SPACE_FOR_TIME` parameter is deprecated. It is retained for backward compatibility only.

`CURSOR_SPACE_FOR_TIME` lets you use more space for cursors in order to save time. It affects both the shared SQL area and the client's private SQL area.

Most users will not need to set this parameter because of the significantly enhanced concurrency modifications introduced in Oracle Database 10g Release 2 (10.2.0.2) and later.

Values:

- `true`

Shared SQL areas are kept pinned in the shared pool. As a result, shared SQL areas are not aged out of the pool as long as an open cursor references them. Because each active cursor's SQL area is present in memory, execution is faster. However, the shared SQL areas never leave memory while they are in use. Therefore, you should set this parameter to `true` only when the shared pool is large enough to hold all open cursors simultaneously.

In addition, a setting of `true` retains the private SQL area allocated for each cursor between executions instead of discarding it after cursor execution, saving cursor allocation and initialization time.

- `false`

Shared SQL areas can be deallocated from the library cache to make room for new SQL statements.

Note: If this parameter is set to `true`, then the `SERIAL_REUSE` parameter is disabled.

See Also:

- *Oracle Database Concepts* and *Oracle Database Performance Tuning Guide*
- ["SERIAL_REUSE"](#) on page 1-155

DB_nK_CACHE_SIZE

Property	Description
Parameter type	Big integer
Syntax	<code>DB_[2 4 8 16 32]K_CACHE_SIZE = integer [K M G]</code>
Default value	0 (additional block size caches are not configured by default)
Modifiable	<code>ALTER SYSTEM</code>
Range of values	Minimum: 0 (values greater than zero are automatically modified to be either the granule size * number of processor groups, or 4 MB * number of CPUs, whichever is greater) Maximum: operating system-dependent

Property	Description
Basic	No

DB_ *n*K_CACHE_SIZE (where *n* = 2, 4, 8, 16, 32) specifies the size of the cache for the *n*K buffers. You can set this parameter only when DB_BLOCK_SIZE has a value other than *n*K. For example, if DB_BLOCK_SIZE=4096, then it is illegal to specify the parameter DB_4K_CACHE_SIZE (because the size for the 4 KB block cache is already specified by DB_CACHE_SIZE).

Do not set this parameter to zero if there are any online tablespaces with an *n*K block size.

Operating system-specific block size restrictions apply. For example, you cannot set DB_32K_CACHE_SIZE if the operating system's maximum block size is less than 32 KB. Also, you cannot set DB_2K_CACHE_SIZE if the minimum block size is greater than 2 KB.

See Also: Your operating system-specific Oracle documentation for more information on block size restrictions

DB_BLOCK_BUFFERS

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No
Range of values	50 to an operating system-specific maximum
Basic	No
Oracle RAC	Multiple instances can have different values, and you can change the values as needed.

Note: DB_BLOCK_BUFFERS cannot be combined with the dynamic DB_CACHE_SIZE parameter; combining these parameters in the same parameter file will produce an error.

DB_BLOCK_BUFFERS specifies the number of database buffers in the buffer cache. It is one of several parameters that contribute to the total memory requirements of the SGA of an instance.

This parameter, together with DB_BLOCK_SIZE, determines the total size of the buffer cache. Effective use of the buffer cache can greatly reduce the I/O load on the database. DB_BLOCK_SIZE can be specified only when the database is first created, so you use DB_BLOCK_BUFFERS to control the size of the buffer cache.

DB_BLOCK_CHECKING

Property	Description
Parameter type	String
Syntax	DB_BLOCK_CHECKING = { FALSE OFF LOW MEDIUM TRUE FULL }
Default value	FALSE
Modifiable	ALTER SYSTEM
Basic	No

DB_BLOCK_CHECKING specifies whether or not Oracle performs block checking for database blocks.

Values:

- OFF or FALSE
No block checking is performed for blocks in user tablespaces. However, semantic block checking for SYSTEM tablespace blocks is always turned on.
- LOW
Basic block header checks are performed after block contents change in memory (for example, after UPDATE or INSERT statements, on-disk reads, or inter-instance block transfers in Oracle RAC).
- MEDIUM
All LOW checks and full semantic checks are performed for all objects except indexes (whose contents can be reconstructed by a drop+rebuild on encountering a corruption).
- FULL or TRUE
All LOW and MEDIUM checks and full semantic checks are performed for all objects.

Oracle checks a block by going through the data in the block, making sure it is logically self-consistent. Block checking can often prevent memory and data corruption. Block checking typically causes 1% to 10% overhead, depending on workload and the parameter value. The more updates or inserts in a workload, the more expensive it is to turn on block checking. You should set DB_BLOCK_CHECKING to FULL if the performance overhead is acceptable.

For backward compatibility, the use of FALSE (implying OFF) and TRUE (implying FULL) is preserved.

DB_BLOCK_CHECKSUM

Property	Description
Parameter type	String
Syntax	DB_BLOCK_CHECKSUM = { OFF FALSE TYPICAL TRUE FULL }
Default value	TYPICAL
Modifiable	ALTER SESSION, ALTER SYSTEM

Property	Description
Basic	No

DB_BLOCK_CHECKSUM determines whether DBWn and the direct loader will calculate a checksum (a number calculated from all the bytes stored in the block) and store it in the cache header of every data block when writing it to disk. Checksums are verified when a block is read - only if this parameter is TYPICAL or FULL and the last write of the block stored a checksum. In FULL mode, Oracle also verifies the checksum before a change application from update/delete statements and recomputes it after the change is applied. In addition, Oracle gives every log block a checksum before writing it to the current log.

Starting with Oracle Database 11g, most of the log block checksum is done by the generating foreground processes, while the LGWR performs the rest of the work, for better CPU and cache efficiency. Prior to Oracle Database 11g, the LGWR solely performed the log block checksum. When this parameter is set to FULL, the LGWR verifies the checksum of each log block generated by the foreground processes before writing it to disk.

If this parameter is set to OFF, DBWn calculates checksums only for the SYSTEM tablespace, but not for user tablespaces. In addition, no log checksum is performed when this parameter is set to OFF.

Checksums allow Oracle to detect corruption caused by underlying disks, storage systems, or I/O systems. If set to FULL, DB_BLOCK_CHECKSUM also catches in-memory corruptions and stops them from making it to the disk. Turning on this feature in TYPICAL mode causes only an additional 1% to 2% overhead. In the FULL mode it causes 4% to 5% overhead. Oracle recommends that you set DB_BLOCK_CHECKSUM to TYPICAL.

For backward compatibility the use of TRUE (implying TYPICAL) and FALSE (implying OFF) values is preserved.

DB_BLOCK_SIZE

Property	Description
Parameter type	Integer
Default value	8192
Modifiable	No
Range of values	2048 to 32768, but your operating system may have a narrower range
Basic	Yes
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

Caution: Set this parameter at the time of database creation. Do not alter it afterward.

DB_BLOCK_SIZE specifies (in bytes) the size of Oracle database blocks. Typical values are 4096 and 8192. The value of this parameter must be a multiple of the physical block size at the device level.

The value for DB_BLOCK_SIZE in effect at the time you create the database determines the size of the blocks. The value must remain set to its initial value.

For Real Application Clusters, this parameter affects the maximum value of the FREELISTS storage parameter for tables and indexes. Oracle uses one database block for each freelist group. Decision support system (DSS) and data warehouse database environments tend to benefit from larger block size values.

Note:

- 32-bit operating systems support a maximum DB_BLOCK_SIZE value of 16384
 - 64-bit operating systems support a maximum DB_BLOCK_SIZE value of 32768
-

See Also:

- *Oracle Database Performance Tuning Guide* and *Oracle Database Administrator's Guide* for information on setting this parameter
- *Oracle Database SQL Language Reference* for information on freelist groups
- *Oracle Database Performance Tuning Guide* for more information on the DSS and data warehouse environments
- *Oracle Database Concepts* for general information on block sizes

DB_CACHE_ADVICE

Property	Description
Parameter type	String
Syntax	DB_CACHE_ADVICE = { ON READY OFF }
Default value	If STATISTICS_LEVEL is set to TYPICAL or ALL, then ON If STATISTICS_LEVEL is set to BASIC, then OFF
Modifiable	ALTER SYSTEM
Basic	No

DB_CACHE_ADVICE enables or disables statistics gathering used for predicting behavior with different cache sizes through the V\$DB_CACHE_ADVICE performance view.

Values:

- OFF
Advisory is turned off and the memory for the advisory is not allocated.
- READY

Advisory is turned off but the memory for the advisory remains allocated. Allocating the memory before the advisory is actually turned on avoids the risk of an error when you switch the parameter to ON.

If the parameter is switched to this state from ON, the contents of the view are preserved and the memory for the advisory is retained.

If the parameter is switched to this state from OFF, you may get an error.

- ON

Advisory is turned on. CPU and memory overheads are incurred. Attempting to set the parameter to this state when it is already in the OFF state may result in an error. Otherwise, the view (V\$DB_CACHE_ADVICE) is reset and statistics are gathered to the newly refreshed view.

If the parameter is in the READY state, you can set it to ON without any errors because the memory is already allocated. The view is reset and statistics are displayed in the newly refreshed view.

DB_CACHE_SIZE

Property	Description
Parameter type	Big integer
Syntax	DB_CACHE_SIZE = <i>integer</i> [K M G]
Default value	If SGA_TARGET is set: If the parameter is not specified, then the default is 0 (internally determined by the Oracle Database). If the parameter is specified, then the user-specified value indicates a minimum value for the memory pool. If SGA_TARGET is not set, then the default is either 48 MB or 4 MB * number of CPUs, whichever is greater
Modifiable	ALTER SYSTEM
Basic	No

DB_CACHE_SIZE specifies the size of the DEFAULT buffer pool for buffers with the primary block size (the block size defined by the DB_BLOCK_SIZE initialization parameter).

The value must be at least 4M * number of cpus (smaller values are automatically rounded up to this value). A user-specified value larger than this is rounded up to the nearest granule size. A value of zero is illegal because it is needed for the DEFAULT memory pool of the primary block size, which is the block size for the SYSTEM tablespace.

See Also: *Oracle Database Performance Tuning Guide* and *Oracle Database Administrator's Guide* for more information on setting this parameter

DB_CREATE_FILE_DEST

Property	Description
Parameter type	String
Syntax	DB_CREATE_FILE_DEST = <i>directory</i> <i>disk group</i>

Property	Description
Default value	There is no default value.
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	Yes

DB_CREATE_FILE_DEST specifies the default location for Oracle-managed datafiles. This location is also used as the default location for Oracle-managed control files and online redo logs if none of the DB_CREATE_ONLINE_LOG_DEST_n initialization parameters are specified.

If a file system directory is specified as the default location, then the directory must already exist; Oracle does not create it. The directory must have appropriate permissions that allow Oracle to create files in it. Oracle generates unique names for the files, and a file thus created is an Oracle Managed File.

See Also: *Oracle Database Administrator's Guide* for more information on setting this parameter and on Oracle Managed Files

DB_CREATE_ONLINE_LOG_DEST_n

Property	Description
Parameter type	String
Syntax	DB_CREATE_ONLINE_LOG_DEST_[1 2 3 4 5] = <i>directory</i> <i>disk group</i>
Default value	There is no default value.
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	Yes

DB_CREATE_ONLINE_LOG_DEST_n (where $n = 1, 2, 3, \dots, 5$) specifies the default location for Oracle-managed control files and online redo logs. If more than one DB_CREATE_ONLINE_LOG_DEST_n parameter is specified, then the control file or online redo log is multiplexed across the locations of the other DB_CREATE_ONLINE_LOG_DEST_n parameters. One member of each online redo log is created in each location, and one control file is created in each location.

Specifying at least two parameters provides greater fault tolerance for the control files and online redo logs if one of the locations should fail.

If a file system directory is specified as the default location, then the directory must already exist; Oracle does not create it. The directory must have appropriate permissions that allow Oracle to create files in it. Oracle generates unique names for the files, and a file thus created is an Oracle Managed File.

See Also: *Oracle Database Administrator's Guide* for more information on setting this parameter and on Oracle Managed Files

DB_DOMAIN

Property	Description
Parameter type	String

Property	Description
Syntax	<code>DB_DOMAIN = domain_name</code>
Default value	There is no default value.
Modifiable	No
Range of values	Any legal string of name components, separated by periods and up to 128 characters long (including the periods).
Basic	Yes
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

In a distributed database system, `DB_DOMAIN` specifies the logical location of the database within the network structure. You should set this parameter if this database is or ever will be part of a distributed system. The value consists of the extension components of a global database name, consisting of valid identifiers (any alphanumeric ASCII characters), separated by periods.

Note: Oracle recommends that you specify `DB_DOMAIN` as a unique string for all databases in a domain.

This parameter allows one department to create a database without worrying that it might have the same name as a database created by another department. If one sales department's `DB_DOMAIN` is `JAPAN.ACME.COM`, then their `SALES` database (`SALES.JAPAN.ACME.COM`) is uniquely distinguished from another database with `DB_NAME = SALES` but with `DB_DOMAIN = US.ACME.COM`.

If you omit the domains from the name of a database link, Oracle expands the name by qualifying the database with the domain of your local database as it currently exists in the data dictionary, and then stores the link name in the data dictionary. The characters valid in a database domain name are: alphanumeric characters, underscore (`_`), and number sign (`#`).

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- The data dictionary view "[GLOBAL_NAME](#)" on page 6-44

DB_FILE_MULTIBLOCK_READ_COUNT

Property	Description
Parameter type	Integer
Default value	The default value corresponds to the maximum I/O size that can be efficiently performed and is platform-dependent
Modifiable	<code>ALTER SESSION</code> , <code>ALTER SYSTEM</code>
Range of values	Operating system-dependent
Basic	No

DB_FILE_MULTIBLOCK_READ_COUNT is one of the parameters you can use to minimize I/O during table scans. It specifies the maximum number of blocks read in one I/O operation during a sequential scan. The total number of I/Os needed to perform a full table scan depends on such factors as the size of the table, the multiblock read count, and whether parallel execution is being utilized for the operation.

As of Oracle Database 10g release 2, the default value of this parameter is a value that corresponds to the maximum I/O size that can be performed efficiently. This value is platform-dependent and is 1MB for most platforms.

Because the parameter is expressed in blocks, it will be set to a value that is equal to the maximum I/O size that can be performed efficiently divided by the standard block size. Note that if the number of sessions is extremely large the multiblock read count value is decreased to avoid the buffer cache getting flooded with too many table scan buffers.

Even though the default value may be a large value, the optimizer will not favor large plans if you do not set this parameter. It would do so only if you explicitly set this parameter to a large value.

Online transaction processing (OLTP) and batch environments typically have values in the range of 4 to 16 for this parameter. DSS and data warehouse environments tend to benefit most from maximizing the value of this parameter. The optimizer is more likely to choose a full table scan over an index if the value of this parameter is high.

The maximum value is the operating system's maximum I/O size expressed as Oracle blocks ((max I/O size)/DB_BLOCK_SIZE). If you set this parameter to a value greater than the maximum, Oracle uses the maximum.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter

DB_FILE_NAME_CONVERT

Property	Description
Parameter type	String
Syntax	<pre>DB_FILE_NAME_CONVERT = 'string1' , 'string2' , 'string3' , 'string4' , ...</pre> Where: ■ <i>string1</i> is the pattern of the primary database filename ■ <i>string2</i> is the pattern of the standby database filename ■ <i>string3</i> is the pattern of the primary database filename ■ <i>string4</i> is the pattern of the standby database filename You can use as many pairs of primary and standby replacement strings as required. You can use single or double quotation marks. The following are example settings that are acceptable: <pre>DB_FILE_NAME_CONVERT = '/dbs/t1/' , '/dbs/t1/s' , 'dbs/t2/' , 'dbs/t2/s_'</pre>
Default value	There is no default value.
Modifiable	ALTER SESSION

Property	Description
Basic	No

DB_FILE_NAME_CONVERT is useful for creating a duplicate database for recovery purposes. It converts the filename of a new datafile on the primary database to a filename on the standby database. If you add a datafile to the primary database, you must add a corresponding file to the standby database. When the standby database is updated, this parameter converts the datafile name on the primary database to the datafile name on the standby database. The file on the standby database must exist and be writable, or the recovery process will halt with an error.

If you specify an odd number of strings (the last string has no corresponding replacement string), an error is signalled during startup. If the filename being converted matches more than one pattern in the pattern/replace string list, the first matched pattern takes effect. There is no limit on the number of pairs that you can specify in this parameter (other than the hard limit of the maximum length of multivalue parameters).

Set the value of this parameter to two strings. The first string is the pattern found in the datafile names on the primary database. The second string is the pattern found in the datafile names on the standby database.

You can also use DB_FILE_NAME_CONVERT to rename the datafiles in the clone control file when setting up a clone database during tablespace point-in-time recovery.

See Also:

- *Oracle Database Backup and Recovery User's Guide*
- *Oracle Data Guard Concepts and Administration*

DB_FILES

Property	Description
Parameter type	Integer
Default value	200
Modifiable	No
Range of values	Minimum: the largest among the absolute file numbers of the datafiles in the database Maximum: operating system-dependent
Basic	No
Oracle RAC	Multiple instances must have the same value.

DB_FILES specifies the maximum number of database files that can be opened for this database. The maximum valid value is the maximum number of files, subject to operating system constraint, that will ever be specified for the database, including files to be added by ADD DATAFILE statements.

If you increase the value of DB_FILES, then you must shut down and restart all instances accessing the database before the new value can take effect. If you have a primary and standby database, then they should have the same value for this parameter.

See Also:

- *Oracle Real Application Clusters Administration and Deployment Guide* for information on setting this parameter in an Oracle RAC environment
- Your operating system-specific Oracle documentation for the default value of this parameter

DB_FLASH_CACHE_FILE

Property	Description
Parameter type	String
Syntax	<code>DB_FLASH_CACHE_FILE = filename disk group</code>
Default value	There is no default value.
Modifiable	No
Basic	No

`DB_FLASH_CACHE_FILE` filename for the flash memory or disk group representing a collection of flash memory.

Specifying this parameter without also specifying the `DB_FLASH_CACHE_SIZE` initialization parameter is not allowed.

See Also: ["DB_FLASH_CACHE_SIZE"](#) on page 1-52

DB_FLASH_CACHE_SIZE

Property	Description
Parameter type	Big integer
Syntax	<code>DB_FLASH_CACHE_SIZE = integer [K M G]</code>
Default value	0
Modifiable	<code>ALTER SYSTEM</code>
Range of values	Minimum: 0 Maximum: operating system-dependent
Basic	No

`DB_FLASH_CACHE_SIZE` specifies the size of the Database Smart Flash Cache (flash cache). This parameter may only be specified at instance startup. You can dynamically change this parameter to 0 (disabling the flash cache) after the database is started. You can re-enable flash cache by setting this parameter to the original value when the database was started. Dynamic resizing of `DB_FLASH_CACHE_SIZE` or re-enabling flash cache to a different size is not supported.

See Also: ["DB_FLASH_CACHE_FILE"](#) on page 1-52

DB_FLASHBACK_RETENTION_TARGET

Property	Description
Parameter type	Integer
Default value	1440 (minutes)
Modifiable	ALTER SYSTEM ... SID='*'
Range of values	0 to $2^{31} - 1$
Basic	No

DB_FLASHBACK_RETENTION_TARGET specifies the upper limit (in minutes) on how far back in time the database may be flashed back. How far back one can flashback a database depends on how much flashback data Oracle has kept in the fast recovery area.

DB_KEEP_CACHE_SIZE

Property	Description
Parameter type	Big integer
Syntax	DB_KEEP_CACHE_SIZE = <i>integer</i> [K M G]
Default value	0 (DB_KEEP_CACHE_SIZE is not configured by default)
Modifiable	ALTER SYSTEM
Range of values	Minimum: 0 (values greater than zero are automatically modified to be either the granule size * number of processor groups, or 4 MB * number of CPUs, whichever is greater) Maximum: operating system-dependent
Basic	No

DB_KEEP_CACHE_SIZE specifies the size of the KEEP buffer pool. The size of the buffers in the KEEP buffer pool is the primary block size (the block size defined by the DB_BLOCK_SIZE initialization parameter).

See Also:

- ["DB_RECYCLE_CACHE_SIZE"](#) on page 1-56
- *Oracle Database Performance Tuning Guide* for information on setting these parameters and on using multiple buffer pools

DB_LOST_WRITE_PROTECT

Property	Description
Parameter type	String
Syntax	DB_LOST_WRITE_PROTECT = { NONE TYPICAL FULL }
Default value	NONE
Modifiable	ALTER SYSTEM

Property	Description
Basic	No
Oracle RAC	In Oracle RAC instances, the parameter value is system-wide.

`DB_LOST_WRITE_PROTECT` enables or disables lost write detection. A data block lost write occurs when an I/O subsystem acknowledges the completion of the block write, while in fact the write did not occur in the persistent storage.

When the parameter is set to `TYPICAL` on the primary database, the instance logs buffer cache reads for read-write tablespaces in the redo log, which is necessary for detection of lost writes.

When the parameter is set to `FULL` on the primary database, the instance logs reads for read-only tablespaces as well as read-write tablespaces.

When the parameter is set to `TYPICAL` or `FULL` on the standby database or on the primary database during media recovery, the instance performs lost write detection.

When the parameter is set to `NONE` on either the primary database or the standby database, no lost write detection functionality is enabled.

DB_NAME

Property	Description
Parameter type	String
Syntax	<code>DB_NAME = database_name</code>
Default value	There is no default value.
Modifiable	No
Basic	Yes
Oracle RAC	You must set this parameter for every instance. Multiple instances must have the same value, or the same value must be specified in the <code>STARTUP OPEN SQL*Plus</code> command or the <code>ALTER DATABASE MOUNT SQL</code> statement.

`DB_NAME` specifies a database identifier of up to 8 characters. This parameter must be specified and must correspond to the name specified in the `CREATE DATABASE` statement.

If you have multiple databases, the value of this parameter should match the Oracle instance identifier of each one to avoid confusion with other databases running on the system. The value of `DB_NAME` should be the same in both the standby and production initialization parameter files.

The database name specified in either the `STARTUP` command or the `ALTER DATABASE . . . MOUNT` statement for each instance of the cluster database must correspond to the `DB_NAME` initialization parameter setting.

The following characters are valid in a database name: alphanumeric characters, underscore (`_`), number sign (`#`), and dollar sign (`$`). No other characters are valid. Oracle removes double quotation marks before processing the database name. Therefore you cannot use double quotation marks to embed other characters in the name. The database name is case insensitive.

See Also: *Oracle Database Administrator's Guide* and *Oracle Real Application Clusters Administration and Deployment Guide* for more information on setting this parameter

DB_RECOVERY_FILE_DEST

Property	Description
Parameter type	String
Syntax	<code>DB_RECOVERY_FILE_DEST = directory disk group</code>
Default value	There is no default value.
Modifiable	<code>ALTER SYSTEM ... SID='*'</code>
Basic	Yes
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

`DB_RECOVERY_FILE_DEST` specifies the default location for the fast recovery area. The fast recovery area contains multiplexed copies of current control files and online redo logs, as well as archived redo logs, flashback logs, and RMAN backups.

Specifying this parameter without also specifying the `DB_RECOVERY_FILE_DEST_SIZE` initialization parameter is not allowed.

See Also:

- *Oracle Database Backup and Recovery User's Guide* for information on setting up and configuring the fast recovery area
- ["DB_RECOVERY_FILE_DEST_SIZE"](#) on page 1-55

DB_RECOVERY_FILE_DEST_SIZE

Property	Description
Parameter type	Big integer
Syntax	<code>DB_RECOVERY_FILE_DEST_SIZE = integer [K M G]</code>
Default value	There is no default value.
Modifiable	<code>ALTER SYSTEM ... SID='*'</code>
Basic	Yes
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

`DB_RECOVERY_FILE_DEST_SIZE` specifies (in bytes) the hard limit on the total space to be used by target database recovery files created in the fast recovery area.

Note that neither block 0 nor the OS block header of each Oracle file is included in this size. Allow an extra 10% for this data when computing the actual disk usage required for the fast recovery area.

See Also:

- *Oracle Database Backup and Recovery User's Guide* for information on setting up and configuring the fast recovery area
- ["DB_RECOVERY_FILE_DEST"](#) on page 1-55

DB_RECYCLE_CACHE_SIZE

Property	Description
Parameter type	Big integer
Syntax	DB_RECYCLE_CACHE_SIZE = <i>integer</i> [K M G]
Default value	0 (DB_RECYCLE_CACHE_SIZE is not configured by default)
Modifiable	ALTER SYSTEM
Range of values	Minimum: 0 (values greater than zero are automatically modified to be either the granule size * number of processor groups, or 4 MB * number of CPUs, whichever is greater) Maximum: operating system-dependent
Basic	No

DB_RECYCLE_CACHE_SIZE specifies the size of the RECYCLE buffer pool. The size of the buffers in the RECYCLE pool is the primary block size (the block size defined by the DB_BLOCK_SIZE initialization parameter).

See Also:

- ["DB_KEEP_CACHE_SIZE"](#) on page 1-53
- *Oracle Database Performance Tuning Guide* for information on setting these parameters and on using multiple buffer pools

DB_SECUREFILE

Property	Description
Parameter type	String
Syntax	DB_SECUREFILE = { NEVER PERMITTED ALWAYS IGNORE }
Default value	PERMITTED
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

DB_SECUREFILE specifies whether or not to treat LOB files as SecureFiles.

Values:

- NEVER

Any LOBs that are specified as SecureFiles are created as BasicFile LOBs. All SecureFile-specific storage options and features (for example, compress, encrypt, deduplicate) will cause an exception. The BasicFile LOB defaults will be used for storage options not specified.

- **PERMITTED**

LOBs are allowed to be created as SecureFiles.

- **ALWAYS**

Attempts to create all LOBs as SecureFile LOBs but creates any LOBs not in an Automatic Segment Space Managed tablespace as BasicFile LOBs, unless **SECUREFILE** is explicitly specified. Any BasicFile LOB storage options that are specified will be ignored and the SecureFile defaults will be used for all storage options not specified.

- **IGNORE**

The **SECUREFILE** keyword and all SecureFile options are ignored.

If the **COMPATIBLE** initialization parameter is not set to 11.1.0 or higher, then LOBs are not treated as SecureFiles.

If there is a LOB column with two partitions (one that has a tablespace for which ASSM is enabled and one that has a tablespace for which ASSM is not enabled), then LOBs in the partition with the ASSM-enabled tablespace will be treated as SecureFiles and LOBs in the other partition will be treated as BasicFile LOBs.

DB_ULTRA_SAFE

Property	Description
Parameter type	String
Syntax	DB_ULTRA_SAFE = { OFF DATA_ONLY DATA_AND_INDEX }
Default value	OFF
Modifiable	No
Basic	No

DB_ULTRA_SAFE sets the default values for other parameters that control protection levels.

Values:

- **OFF**

When any of **DB_BLOCK_CHECKING**, **DB_BLOCK_CHECKSUM**, or **DB_LOST_WRITE_PROTECT** are explicitly set, no changes are made.

- **DATA_ONLY**

- **DB_BLOCK_CHECKING** will be set to **MEDIUM**.
- **DB_LOST_WRITE_PROTECT** will be set to **TYPICAL**.
- **DB_BLOCK_CHECKSUM** will be set to **FULL**.

- **DATA_AND_INDEX**

- **DB_BLOCK_CHECKING** will be set to **FULL**.
- **DB_LOST_WRITE_PROTECT** will be set to **TYPICAL**.
- **DB_BLOCK_CHECKSUM** will be set to **FULL**.

DB_UNIQUE_NAME

Property	Description
Parameter type	String
Syntax	DB_UNIQUE_NAME = <i>database_unique_name</i>
Default value	Database instances: the value of DB_NAME Automatic Storage Management instances: +ASM
Modifiable	No
Basic	Yes
Oracle RAC	Multiple instances must have the same value.

DB_UNIQUE_NAME specifies a globally unique name for the database. Databases with the same DB_NAME within the same DB_DOMAIN (for example, copies of a database created for reporting or a physical standby) must have a unique DB_UNIQUE_NAME. Every database's DB_UNIQUE_NAME must be unique within the enterprise.

The value of DB_UNIQUE_NAME can be up to 30 characters and is case insensitive. The following characters are valid in a database name: alphanumeric characters, underscore (_), number sign (#), and dollar sign (\$).

See Also: *Oracle Data Guard Concepts and Administration* and *Oracle Database Administrator's Guide* for more information on setting this parameter

DB_UNRECOVERABLE_SCN_TRACKING

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No
Oracle RAC	Multiple instances must have the same value

DB_UNRECOVERABLE_SCN_TRACKING enables or disables the tracking of unrecoverable (NOLOGGING) direct-path insert and load operations.

When the value is set to true, updates are made to the controlfile that maintains the V\$DATAFILE.UNRECOVERABLE_CHANGE# and V\$DATAFILE.UNRECOVERABLE_TIME columns. When the value is set to false, updates are not made to the controlfile. Setting this parameter to false may improve performance of direct-path NOLOGGING operations.

Note: The DB_UNRECOVERABLE_SCN_TRACKING initialization parameter is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DB_WRITER_PROCESSES

Property	Description
Parameter type	Integer
Default value	1 or CPU_COUNT / 8, whichever is greater. If the number of processor groups is less than 36 but greater than the number of DB writer processes, then the number of DB writer processes is adjusted to be a multiple of the number of processor groups. If the number of DB writer processes is greater than or equal to the number of processor groups, then there is no adjustment.
Modifiable	No
Range of values	1 to 36
Basic	No

DB_WRITER_PROCESSES specifies the initial number of database writer processes (DBW0, ... DBW9 and DBWa, ... DBWz) for an instance. This parameter is useful for systems that modify data heavily.

See Also:

- *Oracle Database Concepts* for more information on the database writer processes
- *Oracle Database Performance Tuning Guide* for information on setting this parameter

DBWR_IO_SLAVES

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No
Range of values	0 to operating system-dependent
Basic	No

DBWR_IO_SLAVES is relevant only on systems with only one database writer process (DBW0). It specifies the number of I/O server processes used by the DBW0 process. The DBW0 process and its server processes always write to disk. By default, the value is 0 and I/O server processes are not used.

If you set DBWR_IO_SLAVES to a nonzero value, the number of I/O server processes used by the ARCH and LGWR processes is set to 4. However, the number of I/O server processes used by Recovery Manager is set to 4 only if asynchronous I/O is disabled (either your platform does not support asynchronous I/O or disk_asynch_io is set to false).

Typically, I/O server processes are used to simulate asynchronous I/O on platforms that do not support asynchronous I/O or that implement it inefficiently. However, you can use I/O server processes even when asynchronous I/O is being used. In that case the I/O server processes will use asynchronous I/O.

I/O server processes are also useful in database environments with very large I/O throughput, even if asynchronous I/O is enabled.

See Also: ["BACKUP_TAPE_IO_SLAVES"](#) on page 1-28

DDL_LOCK_TIMEOUT

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SESSION
Range of values	0 to 1,000,000 (in seconds)
Basic	No

DDL_LOCK_TIMEOUT specifies a time limit for how long DDL statements will wait in a DML lock queue. The default value of zero indicates a status of NOWAIT. The maximum value of 1,000,000 seconds will result in the DDL statement waiting forever to acquire a DML lock.

If a lock is not acquired before the timeout period expires, then an error is returned.

DEFERRED_SEGMENT_CREATION

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No

DEFERRED_SEGMENT_CREATION specifies the semantics of deferred segment creation. If set to true, then segments for tables and their dependent objects (LOBs, indexes) will not be created until the first row is inserted into the table.

Before creating a set of tables, if it is known that a significant number of them will not be populated, then consider setting this parameter to true. This saves disk space and minimizes install time.

DG_BROKER_CONFIG_FILE*n*

Property	Description
Parameter type	String
Syntax	DG_BROKER_CONFIG_FILE[1 2] = <i>filename</i>
Default value	Operating system-dependent
Modifiable	ALTER SYSTEM

Property	Description
Range of values	One filename
Basic	No

DG_BROKER_CONFIG_FILE n (where $n = 1, 2$) specifies the names for the Data Guard broker configuration files.

Every database that is part of a Data Guard broker configuration has two broker configuration files, which contain entries that describe the state and properties of the configuration (such as the sites and databases that are part of the configuration, the roles and properties of each of the databases, and the state of each of the elements of the configuration). Two files are provided so as to always maintain the last known good state of the configuration.

If DG_BROKER_CONFIG_FILE n is not explicitly defined, then it is set to an operating system-specific default value at instance startup. The parameter can only be altered when the DMON (Data Guard broker) process is not running.

See Also: *Oracle Data Guard Broker* for more information about setting this parameter

DG_BROKER_START

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SYSTEM
Range of values	true false
Basic	No

DG_BROKER_START enables Oracle to determine whether or not the Data Guard broker (DMON) process should be started. DMON is a non-fatal Oracle background process and exists as long as the instance exists, whenever this parameter is set to true.

If the site is never going to be configured in a Data Guard broker configuration, then you can leave the parameter unspecified and accept the default value of false. If the site is part of a Data Guard broker configuration, then automatic startup of the DMON process is simplified by setting DG_BROKER_START to true in the initialization parameter file.

DIAGNOSTIC_DEST

Property	Description
Parameter type	String
Syntax	DIAGNOSTIC_DEST = { pathname directory }

Property	Description
Default value	Derived from the value of the \$ORACLE_BASE environment variable. If \$ORACLE_BASE is not set, then derived from ORACLE_BASE as set by the Oracle Universal Installer. If ORACLE_BASE is not set, then \$ORACLE_HOME/rdbms/log is used.
Modifiable	ALTER SYSTEM
Basic	No
Oracle RAC	This parameter can be set on each instance. Oracle recommends that each instance in a cluster specify a DIAGNOSTIC_DEST directory location that is located on shared disk and that the same value for DIAGNOSTIC_DEST be specified for each instance.

As of Oracle Database 11g Release 1, the diagnostics for each database instance are located in a dedicated directory, which can be specified through the DIAGNOSTIC_DEST initialization parameter. The structure of the directory specified by DIAGNOSTIC_DEST is as follows:

```
<diagnostic_dest>/diag/rdbms/<dbname>/<instname>
```

This location is known as the Automatic Diagnostic Repository (ADR) Home. For example, if the database name is proddb and the instance name is proddb1, the ADR home directory would be <diagnostic_dest>/diag/rdbms/proddb/proddb1.

The following files are located under the ADR home directory:

- Trace files - located in subdirectory <adr-home>/trace
- Alert logs - located in subdirectory <adr-home>/alert. In addition, the alert.log file is now in XML format, which conforms to the Oracle ARB logging standard.
- Core files - located in the subdirectory <adr-home>/cdumdl
- Incident files - the occurrence of each serious error (for example, ORA-600, ORA-1578, ORA-7445) causes an incident to be created. Each incident is assigned an ID and dumping for each incident (error stack, call stack, block dumps, and so on) is stored in its own file, separated from process trace files. Incident dump files are located in <adr-home>/incident/<incdir#>. You can find the incident dump file location inside the process trace file.

DISK_ASYNCH_IO

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	No
Range of values	true false
Basic	No

DISK_ASYNCH_IO controls whether I/O to datafiles, control files, and logfiles is asynchronous (that is, whether parallel server processes can overlap I/O requests with CPU processing during table scans). If your platform supports asynchronous I/O to disk, Oracle recommends that you leave this parameter set to its default value.

However, if the asynchronous I/O implementation is not stable, you can set this parameter to `false` to disable asynchronous I/O. If your platform does not support asynchronous I/O to disk, this parameter has no effect.

If you set `DISK_ASYNC_IO` to `false`, then you should also set `DBWR_IO_SLAVES` to a value other than its default of zero in order to simulate asynchronous I/O.

See Also:

- ["DBWR_IO_SLAVES"](#) on page 1-59
- *Oracle Database Performance Tuning Guide* for more information on asynchronous I/O and on setting this parameter

DISPATCHERS

Property	Description
Parameter type	String
Syntax	<pre>DISPATCHERS = 'dispatch_clause'</pre> dispatch_clause::= <pre>(PROTOCOL = protocol) (ADDRESS = address) (DESCRIPTION = description) [options_clause]</pre> options_clause::= <pre>(DISPATCHERS = integer SESSIONS = integer CONNECTIONS = integer TICKS = seconds POOL = {1 ON YES TRUE BOTH ({IN OUT} = ticks) 0 OFF NO FALSE ticks} MULTIPLEX = {1 ON YES TRUE 0 OFF NO FALSE BOTH IN OUT} LISTENER = tnsname SERVICE = service INDEX = integer)</pre>
Default value	If <code>SHARED_SERVERS</code> is greater than 0, then <code>DISPATCHERS</code> defaults to <code>'(PROTOCOL=tcp)'</code> , causing 1 TCP/IP dispatcher to be created.
Modifiable	<code>ALTER SYSTEM</code>
Basic	No

`DISPATCHERS` configures dispatcher processes in the shared server architecture. The parsing software supports a name-value syntax to enable the specification of attributes in a position-independent, case-insensitive manner. For example:

```
DISPATCHERS = '(PROTOCOL=TCP) (DISPATCHERS=3)'
```

Attributes may be specified using the full attribute name or any substring beginning with the first 3 characters. For example, `SESSIONS` can be specified as `SES`, `SESS`, `SESSI`, and so on.

Specify only one of the following attributes: `PROTOCOL`, `ADDRESS`, or `DESCRIPTION`. If you specify either `ADDRESS` or `DESCRIPTION`, then you can specify additional network attributes. Doing so supports multi-homed hosts.

dispatch_clause

- `PROTOCOL`
The network protocol for which the dispatcher generates a listening endpoint.
- `ADDRESS`
The network protocol address of the endpoint on which the dispatchers listen.
- `DESCRIPTION`
The network description of the endpoint on which the dispatchers listen, including the protocol address.

options_clause

- `DISPATCHERS`
The initial number of dispatchers to start. The default is 1.
- `SESSIONS`
The maximum number of network sessions to allow for each dispatcher. The default is operating system-specific. Most operating systems have a default of 16 KB.
- `CONNECTIONS`
The maximum number of network connections to allow for each dispatcher. The default is operating system-specific.
- `TICKS`
The length of a network tick in seconds. The default is 1 second.
- `POOL`
Enables Connection Pooling.
 - An integer indicates that Connection Pooling is enabled for both incoming and outgoing network connections. The number specified is the timeout in ticks for both incoming and outgoing network connections.
 - `ON`, `YES`, `TRUE`, and `BOTH` indicate that Connection Pooling is enabled for both incoming and outgoing network connections. A default timeout of 10 ticks is used for both incoming and outgoing network connections.
 - `IN` indicates that Connection Pooling is enabled for incoming network connections and the default timeout of 10 ticks is used for incoming network connections.
 - `OUT` indicates that Connection Pooling is enabled for outgoing network connections and the default timeout of 10 ticks is used for outgoing network connections.
 - `NO`, `OFF`, and `FALSE` indicate that Connection Pooling is disabled for both incoming and outgoing network connections. This is the default.

POOL can also be assigned a name-value string such as "(IN=10)", "(OUT=20)", or "(IN=10)(OUT=20)". In such cases:

- If an IN numeric value is specified, then Connection Pooling is enabled for incoming connections, and the number specified is the timeout in ticks for incoming network connections.
- If an OUT numeric value is specified, then Connection Pooling is enabled for outgoing network connections, and the number specified is the timeout in ticks for outgoing network connections.
- If the numeric value of a specified timeout is 1, then the default value of 10 ticks is used. If the numeric value is 0, then pooling is not on.

■ MULTIPLEX

Enables the Oracle Connection Manager session multiplexing feature.

- The values 1, ON, YES, TRUE, and BOTH indicate that Network Session Multiplex is enabled for both incoming and outgoing network connections.
- The value IN indicates that Network Session Multiplex is enabled for incoming network connections.
- The value OUT indicates that Network Session Multiplexing is enabled for outgoing network connections.
- The values 0, NO, OFF, and FALSE indicate that Network Session Multiplexing is disabled for both incoming and outgoing network connections. This is the default.

■ LISTENER

Specifies the network name of an address or address list of the Oracle Net listeners with which the dispatchers will register.

The LISTENER attribute facilitates administration of multi-homed hosts. This attribute specifies the appropriate listeners with which the dispatchers will register. The LISTENER attribute takes precedence over the LOCAL_LISTENER and REMOTE_LISTENER parameters. See "[LOCAL_LISTENER](#)" on page 1-85 and "[REMOTE_LISTENER](#)" on page 1-145.

■ SERVICE

Specifies one or more names by which clients can connect to the dispatchers. The SERVICE attribute takes precedence over the SERVICE_NAMES parameter.

■ INDEX

Use this attribute in an ALTER SYSTEM SET DISPATCHERS statement to indicate which dispatcher configuration you want to modify. (If you specify INDEX in the initialization parameter file, the Oracle Database ignores it.) In an ALTER SYSTEM statement, INDEX specifies the order in which the parameter's values were initialized. The value ranges from 0 (for the first dispatcher configuration) to one less than the total number of dispatcher configurations you define.

For example, if you specify 3 dispatcher configurations in the initialization parameter file, you would modify the third dispatcher configuration by specifying INDEX=2 in the ALTER SYSTEM statement. You could also add an additional dispatcher configuration in the ALTER SYSTEM statement by specifying INDEX=3.

If INDEX is not specified in the ALTER SYSTEM statement, then the PROTOCOL, ADDRESS, or DESCRIPTION attributes must be specified, and if a dispatcher

configuration matching this `PROTOCOL`, `ADDRESS`, or `DESCRIPTION` exists, then that configuration will be modified. Otherwise, a new configuration will be added.

See Also: *Oracle Database Net Services Administrator's Guide* and *Oracle Database Administrator's Guide* for more information on setting this parameter

DISTRIBUTED_LOCK_TIMEOUT

Property	Description
Parameter type	Integer
Default value	60
Modifiable	No
Range of values	1 to unlimited
Basic	No

`DISTRIBUTED_LOCK_TIMEOUT` specifies the amount of time (in seconds) for distributed transactions to wait for locked resources.

See Also: *Oracle Database Concepts* and *Oracle Database Administrator's Guide* for more information on data concurrency

DML_LOCKS

Property	Description
Parameter type	Integer
Default value	Derived: 4 * <code>TRANSACTIONS</code>
Modifiable	No
Range of values	20 to unlimited; a setting of 0 disables enqueues
Basic	No
Oracle RAC	You must set this parameter for every instance, and all instances must have positive values or all must be 0.

A **DML lock** is a lock obtained on a table that is undergoing a DML operation (insert, update, delete). `DML_LOCKS` specifies the maximum number of DML locks—one for each table modified in a transaction. The value should equal the grand total of locks on tables currently referenced by all users. For example, if three users are modifying data in one table, then three entries would be required. If three users are modifying data in two tables, then six entries would be required.

The default value assumes an average of four tables referenced for each transaction. For some systems, this value may not be enough.

Enqueues are shared memory structures that serialize access to database resources. If you set the value of `DML_LOCKS` to 0, enqueues are disabled and performance is slightly increased. However, you should be aware of the following restrictions when you set you `DML_LOCKS` to 0:

- You cannot use `DROP TABLE`, `CREATE INDEX` statements

- You cannot use explicit lock statements such as `LOCK TABLE IN EXCLUSIVE MODE`
- Enterprise Manager cannot run on any instances for which `DML_LOCKS` is set to 0

Oracle holds more locks during parallel DML than during serial execution. Therefore, if your database supports a lot of parallel DML, you may need to increase the value of this parameter.

See Also:

- *Oracle Database Concepts* for a discussion of lock and enqueue resources needed for parallel DML
- *Oracle Real Application Clusters Administration and Deployment Guide*, *Oracle Database Concepts*, and *Oracle Database Administrator's Guide* for more information on data concurrency

DST_UPGRADE_INSERT_CONV

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No

`DST_UPGRADE_INSERT_CONV` specifies whether or not internal operators will be allocated on top of `TIMESTAMP WITH TIME ZONE` (TSTZ) columns of tables which have not been upgraded during the upgrade window of daylight saving time patching for `TIMESTAMP WITH TIME ZONE` data.

Values:

- `true`
Internal operators will be allocated on top of TSTZ columns of tables which have not been upgraded. This is the default.
- `false`
Internal operators will not be allocated on top of TSTZ columns of tables which have not been upgraded.

When `DST_UPGRADE_INSERT_CONV` is set to `true` during the upgrade window of the daylight saving time patching process:

- `SELECT` queries on tables with TSTZ data which have not been upgraded will use internal operators on top of TSTZ columns to present TSTZ data as if they were recorded using the new time zone translation rules.
- DML on tables with TSTZ data which have not been upgraded will use internal operators on top of TSTZ columns to ensure that the TSTZ data is recorded using the old time zone translation rules in order to be consistent with the existing TSTZ data in the same tables.

Note: Oracle strongly recommends that this parameter is set to `true` throughout the upgrade window of the daylight saving time patching process. This parameter reduces the performance impact since indexes on TSTZ columns will be disabled whenever internal operators are allocated. If the parameter is set to `false`, then indexes will be used and this may affect performance of queries against TSTZ data during the DST upgrade window. Turning off this parameter during the upgrade window may corrupt data on disk when DMLs occur for tables with TSTZ data which have not yet been upgraded.

ENABLE_DDL_LOGGING

Property	Description
Parameter type	Boolean
Default value	<code>false</code>
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	<code>true</code> <code>false</code>
Basic	No

ENABLE_DDL_LOGGING enables or disables the writing of a subset of DDL statements to the alert log.

Note: The DDL statement written to the alert log may be truncated. You can use DDL triggers to view the entire DDL statement. See *Oracle Database PL/SQL Language Reference* for more information about DDL triggers.

EVENT

Property	Description
Parameter type	String
Default value	There is no default value.
Modifiable	No
Basic	No

EVENT is a parameter used only to debug the system. Do not alter the value of this parameter except under the supervision of Oracle Support Services staff.

FAL_CLIENT

Property	Description
Parameter type	String

Property	Description
Syntax	<code>FAL_CLIENT = string</code>
Default value	There is no default value.
Modifiable	<code>ALTER SYSTEM</code>
Basic	No

`FAL_CLIENT` specifies the FAL (fetch archive log) client name that is used by the FAL service, configured through the `FAL_SERVER` initialization parameter, to refer to the FAL client. The value is an Oracle Net service name, which is assumed to be configured properly on the FAL server system to point to the FAL client (standby database).

See Also: *Oracle Data Guard Concepts and Administration* for more information about FAL server

FAL_SERVER

Property	Description
Parameter type	String
Syntax	<code>FAL_SERVER = string</code>
Default value	There is no default value.
Modifiable	<code>ALTER SYSTEM</code>
Basic	No

`FAL_SERVER` specifies the FAL (fetch archive log) server for a standby database. The value is an Oracle Net service name, which is assumed to be configured properly on the standby database system to point to the desired FAL server.

See Also: *Oracle Data Guard Concepts and Administration* for more information about FAL server

FAST_START_MTTR_TARGET

Property	Description
Parameter type	Integer
Default value	0
Modifiable	<code>ALTER SYSTEM</code>
Range of values	0 to 3600 seconds
Basic	No
Oracle RAC	Multiple instances can have different values, and you can change the values at runtime.

`FAST_START_MTTR_TARGET` enables you to specify the number of seconds the database takes to perform crash recovery of a single instance. When specified, `FAST_START_MTTR_TARGET` is overridden by `LOG_CHECKPOINT_INTERVAL`.

FAST_START_PARALLEL_ROLLBACK

Property	Description
Parameter type	String
Syntax	FAST_START_PARALLEL_ROLLBACK = { HI LO FALSE }
Default value	LOW
Modifiable	ALTER SYSTEM
Basic	No

FAST_START_PARALLEL_ROLLBACK specifies the degree of parallelism used when recovering terminated transactions. Terminated transactions are transactions that are active before a system failure. If a system fails when there are uncommitted parallel DML or DDL transactions, then you can speed up transaction recovery during startup by using this parameter.

Values:

- FALSE
Parallel rollback is disabled
- LOW
Limits the maximum degree of parallelism to 2 * CPU_COUNT
- HIGH
Limits the maximum degree of parallelism to 4 * CPU_COUNT

If you change the value of this parameter, then transaction recovery will be stopped and restarted with the new implied degree of parallelism.

FILE_MAPPING

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SYSTEM
Range of values	true false
Basic	No

FILE_MAPPING specifies whether or not file mapping is enabled. The FMON background process is started to manage the mapping information when file mapping is enabled.

See Also: *Oracle Database Administrator's Guide* for more information about the file mapping feature

FILEIO_NETWORK_ADAPTERS

Property	Description
Parameter type	String
Syntax	<code>FILEIO_NETWORK_ADAPTERS = adapter_name [, adapter_name] ...</code>
Default value	There is no default value.
Modifiable	No
Range of values	One or more network adapter names, separated by commas
Basic	No

`FILEIO_NETWORK_ADAPTERS` specifies a list of network adapters that can be used to access the disk storage. On platforms where the database files reside in network attached storage, this parameter provides the storage access library the list of network adapters that can be used to access the storage.

The network adapter name is a fully qualified address name of the network card that can be accessed through the host name database or using the Network Information Service. The components of the adapter name are separated by periods. For example, the following is a fully qualified adapter name:

`ib1.oracle.com`

FILESYSTEMIO_OPTIONS

Property	Description
Parameter type	String
Syntax	<code>FILESYSTEMIO_OPTIONS = { none setall directIO asynch }</code>
Default value	There is no default value.
Modifiable	No
Basic	No

`FILESYSTEMIO_OPTIONS` specifies I/O operations for file system files.

FIXED_DATE

Property	Description
Parameter type	String
Syntax	<code>FIXED_DATE = [YYYY-MM-DD-HH24:MI:SS (or the default Oracle date format) NONE]</code>
Default value	There is no default value.
Modifiable	<code>ALTER SYSTEM</code>
Basic	No

`FIXED_DATE` enables you to set a constant date that `SYSDATE` will always return instead of the current date. To undo a fixed date setting, specify `FIXED_DATE=NONE`. This parameter is useful primarily for testing. The value can be in the format shown above or in the default Oracle date format, without a time.

GCS_SERVER_PROCESSES

Property	Description
Parameter type	Integer
Default value	If 1 - 3 CPUS, then 1 If 4 - 15 CPUs, then 2 If 16 or more CPUs, then $2 + (\text{CPUs} / 32)$. If the result includes a fraction, then the fraction is disregarded. For example, if you had 20 CPUs, then $2 + (20 / 32)$ would equal 2 GCS processes. If <code>CLUSTER_DATABASE</code> is set to <code>false</code> , then 0 If ASM, then 1
Modifiable	No
Range of values	1 to 36
Basic	No
Oracle RAC	Multiple instances can have different values.

`GCS_SERVER_PROCESSES` specifies the number of background GCS server processes (LMS0, ... LMS9 and LMSa, ... LMSz) to serve the inter-instance traffic among Oracle RAC instances. GCS server processes are only seen in an Oracle RAC environment.

GLOBAL_CONTEXT_POOL_SIZE

Property	Description
Parameter type	String
Default value	NULL
Modifiable	No
Range of values	Any integer value in MB
Basic	No

Note: The `GLOBAL_CONTEXT_POOL_SIZE` parameter is deprecated. It is retained for backward compatibility only.

`GLOBAL_CONTEXT_POOL_SIZE` specifies the amount of memory to allocate in the SGA for storing and managing global application context.

GLOBAL_NAMES

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No

GLOBAL_NAMES specifies whether a database link is required to have the same name as the database to which it connects.

If the value of GLOBAL_NAMES is false, then no check is performed. If you use or plan to use distributed processing, then Oracle recommends that you set this parameter to true to ensure the use of consistent naming conventions for databases and links in a networked environment.

See Also: *Oracle Database Administrator's Guide* for more information on setting this parameter

GLOBAL_TXN_PROCESSES

Property	Description
Parameter type	Integer
Default value	1
Modifiable	ALTER SYSTEM
Range of values	0 to 20
Basic	No
Oracle RAC	Multiple instances can have different values.

GLOBAL_TXN_PROCESSES specifies the initial number of GTX n background processes (GTX0, ... GTX9 and GTXa, ... GTXj) per instance to support global (XA) transactions in an Oracle RAC environment.

If you want to disable the GTX n background processes, then you must set GLOBAL_TXN_PROCESSES to 0 in your parameter file. Setting this parameter to 0 will disable the XA support on an Oracle RAC database. Error ORA-55712 will be returned if you try to run XA transactions on an Oracle RAC database with this parameter set to zero. You can change the setting to a nonzero value at runtime to turn on the support for XA.

GLOBAL_TXN_PROCESSES is useful for systems that process global (XA) transactions heavily. You do not need to specify a value for this parameter since Oracle Database automatically determines the number of processes and autotunes them, as necessary. GTX n background processes are only seen in an Oracle RAC environment.

See Also: *Oracle Database Advanced Application Developer's Guide* for more information about this parameter and Oracle XA

HASH_AREA_SIZE

Property	Description
Parameter type	Integer
Default value	Derived: 2 * SORT_AREA_SIZE
Modifiable	ALTER SESSION
Range of values	0 to operating system-dependent
Basic	No

Note: Oracle does not recommend using the `HASH_AREA_SIZE` parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting `PGA_AGGREGATE_TARGET` instead. `HASH_AREA_SIZE` is retained for backward compatibility.

`HASH_AREA_SIZE` is relevant to parallel execution operations and to the query portion of DML or DDL statements. It specifies the maximum amount of memory, in bytes, to be used for hash joins.

See Also:

- *Oracle Database Concepts* for information on hash joins in general
- *Oracle Database Performance Tuning Guide* for information on calculating an appropriate value for this parameter

HI_SHARED_MEMORY_ADDRESS

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No
Basic	No

`HI_SHARED_MEMORY_ADDRESS` specifies the starting address at runtime of the system global area (SGA). It is ignored on platforms that specify the SGA's starting address at linktime.

On 64-bit platforms, use `HI_SHARED_MEMORY_ADDRESS` to specify the high-order 32 bits of a 64-bit address. Use `SHARED_MEMORY_ADDRESS` to specify the low-order 32 bits of the address (see "[SHARED_MEMORY_ADDRESS](#)" on page 1-160). If both parameters are 0 or unspecified, the SGA address defaults to a platform-specific location.

HS_AUTOREGISTER

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SYSTEM
Range of values	true false
Basic	No

HS_AUTOREGISTER enables or disables automatic self-registration of Heterogeneous Services (HS) agents. When enabled, information is uploaded into the server's data dictionary to describe a previously unknown agent class or a new agent version.

Oracle recommends that you set this parameter to `true`. Oracle incurs less overhead when establishing subsequent connections through the same agent if self-registered information is available in the server's data dictionary.

See Also: *Oracle Database Heterogeneous Connectivity User's Guide* for more information on HS agents

IFILE

Property	Description
Parameter type	Parameter file
Syntax	<code>IFILE = parameter_file_name</code>
Default value	There is no default value.
Modifiable	No
Range of values	Valid parameter filenames
Basic	No
Oracle RAC	Multiple instances can have different values.

Use IFILE to embed another parameter file within the current parameter file. For example:

```
IFILE = COMMON.ORA
```

You can have up to three levels of nesting. In this example, the file `COMMON.ORA` could contain a second `IFILE` parameter for the file `COMMON2.ORA`, which could contain a third `IFILE` parameter for the file `GCPARMS.ORA`. You can also include multiple parameter files in one parameter file by listing `IFILE` several times with different values:

```
IFILE = DBPARMS.ORA
IFILE = GCPARMS.ORA
IFILE = LOGPARMS.ORA
```

Note: You must list multiple entries on contiguous lines of the parameter file.

INSTANCE_GROUPS

Property	Description
Parameter type	String
Syntax	<code>INSTANCE_GROUPS = group_name [, group_name] ...</code>
Default value	There is no default value.
Modifiable	No
Range of values	One or more instance group names, separated by commas
Basic	No
Oracle RAC	Multiple instances can have different values.

Note: The `INSTANCE_GROUPS` parameter is deprecated. It is retained for backward compatibility only.

`INSTANCE_GROUPS` is an Oracle RAC parameter that you can specify only in parallel mode. Used in conjunction with the `PARALLEL_INSTANCE_GROUP` parameter, it lets you restrict parallel query operations to a limited number of instances.

This parameter specifies one or more instance groups and assigns the current instance to those groups. If one of the specified groups is also specified in the `PARALLEL_INSTANCE_GROUP` parameter, then Oracle allocates query processes for a parallel operation from this instance.

See Also:

- *Oracle Real Application Clusters Administration and Deployment Guide* for more information on parallel query execution in a Real Application Clusters environment
- ["PARALLEL_INSTANCE_GROUP"](#) on page 1-129

INSTANCE_NAME

Property	Description
Parameter type	String
Syntax	<code>INSTANCE_NAME = instance_id</code>
Default value	The instance's SID Note: The SID identifies the instance's shared memory on a host, but may not uniquely distinguish this instance from other instances.
Modifiable	No
Range of values	Any alphanumeric characters and the underscore (_) character
Basic	No

In a Real Application Clusters environment, multiple instances can be associated with a single database service. Clients can override Oracle's connection load balancing by

specifying a particular instance by which to connect to the database. `INSTANCE_NAME` specifies the unique name of this instance.

In a single-instance database system, the instance name is usually the same as the database name.

See Also: *Oracle Real Application Clusters Administration and Deployment Guide* and *Oracle Database Net Services Administrator's Guide* for more information

INSTANCE_NUMBER

Property	Description
Parameter type	Integer
Default value	0 (zero)
Modifiable	No
Range of values	1 to maximum number of instances specified when the database was created
Basic	Yes
Oracle RAC	You must set this parameter for every instance, and all instances must have different values.

`INSTANCE_NUMBER` is an Oracle RAC parameter that can be specified in parallel mode or exclusive mode. It specifies a unique number that maps the instance to one free list group for each database object created with storage parameter `FREELIST GROUPS`.

The `INSTANCE` parameter of the `ALTER TABLE . . . ALLOCATE EXTENT` statement assigns an extent to a particular free list group. If you set `INSTANCE_NUMBER` to the value specified for the `INSTANCE` parameter, the instance uses that extent for inserts and for updates that expand rows.

The practical maximum value of this parameter is the maximum number of instances specified in the `CREATE DATABASE` statement. The absolute maximum is operating system-dependent.

See Also: *Oracle Real Application Clusters Administration and Deployment Guide* for more information

INSTANCE_TYPE

Property	Description
Parameter type	String
Syntax	<code>INSTANCE_TYPE = { RDBMS ASM }</code>
Default value	RDBMS
Modifiable	No
Basic	No
Oracle RAC	Multiple instances must have the same value.

INSTANCE_TYPE specifies whether the instance is a database instance or an Automatic Storage Management instance.

Values:

- RDBMS
The instance is a database instance.
- ASM
The instance is an Automatic Storage Management instance.

JAVA_JIT_ENABLED

Property	Description
Parameter type	Boolean
Default value	Operating system-dependent
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No

JAVA_JIT_ENABLED enables or disables the Just-in-Time (JIT) compiler for the Oracle Java Virtual Machine (OracleJVM) environment.

For platforms that support the JIT compiler, the default value of this parameter is `true`; otherwise the default value is `false`. Attempting to set this parameter to `true` on unsupported platforms will result in an error.

See Also: *Oracle Database Java Developer's Guide* for more information about setting this parameter

JAVA_MAX_SESSIONSPACE_SIZE

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No
Range of values	0 to 2 GB - 1
Basic	No

Java session space is the memory that holds Java state from one database call to another. JAVA_MAX_SESSIONSPACE_SIZE specifies (in bytes) the maximum amount of session space made available to a Java program executing in the server. When a user's session-duration Java state attempts to exceed this amount, the Java virtual machine kills the session with an out-of-memory failure.

See Also:

- *Oracle Database Java Developer's Guide*
- ["JAVA_SOFT_SESSIONSPACE_LIMIT"](#) on page 1-79

JAVA_POOL_SIZE

Property	Description
Parameter type	Big integer
Syntax	<code>JAVA_POOL_SIZE = integer [K M G]</code>
Default value	If <code>SGA_TARGET</code> is set: If the parameter is not specified, then the default is 0 (internally determined by the Oracle Database). If the parameter is specified, then the user-specified value indicates a minimum value for the memory pool. If <code>SGA_TARGET</code> is not set: 24 MB, rounded up to the nearest granule size
Modifiable	<code>ALTER SYSTEM</code>
Range of values	Minimum: 0 (values greater than zero are rounded up to the nearest granule size) Maximum: operating system-dependent
Basic	No

`JAVA_POOL_SIZE` specifies (in bytes) the size of the Java pool, from which the Java memory manager allocates most Java state during runtime execution. This memory includes the shared in-memory representation of Java method and class definitions, as well as the Java objects that are migrated to the Java session space at end-of-call.

See Also: *Oracle Database Java Developer's Guide* for information on adjusting this parameter

JAVA_SOFT_SESSIONSPACE_LIMIT

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No
Range of values	0 to 2 GB - 1
Basic	No

Java session space is the memory that holds Java state from one database call to another. `JAVA_SOFT_SESSIONSPACE_LIMIT` specifies (in bytes) a **soft limit** on Java memory usage in a session, as a means to warn you if a user's session-duration Java state is using too much memory. When a user's session-duration Java state exceeds this size, Oracle generates a warning that goes into the trace files.

See Also:

- *Oracle Database Java Developer's Guide* for more information on this parameter
- ["JAVA_MAX_SESSIONSPACE_SIZE"](#) on page 1-78

JOB_QUEUE_PROCESSES

Property	Description
Parameter type	Integer
Default value	1000
Modifiable	ALTER SYSTEM
Range of values	0 to 1000
Basic	No
Oracle RAC	Multiple instances can have different values.

JOB_QUEUE_PROCESSES specifies the maximum number of job slaves per instance that can be created for the execution of DBMS_JOB jobs and Oracle Scheduler (DBMS_SCHEDULER) jobs. DBMS_JOB and Oracle Scheduler share the same job coordinator and job slaves, and they are both controlled by the JOB_QUEUE_PROCESSES parameter.

If the value of JOB_QUEUE_PROCESSES is set to 0, then DBMS_JOB jobs and Oracle Scheduler jobs will not run on the instance.

If JOB_QUEUE_PROCESSES is set to a value in the range of 1 to 1000, then DBMS_JOB jobs and Oracle Scheduler jobs will run. The actual number of job slaves created for Oracle Scheduler jobs is auto-tuned by the Scheduler depending on several factors, including available resources, Resource Manager settings, and currently running jobs. However, the combined total number of job slaves running DBMS_JOB jobs and Oracle Scheduler jobs on an instance can never exceed the value of JOB_QUEUE_PROCESSES for that instance.

Advanced replication uses Oracle Scheduler for data refreshes. Oracle Streams Advanced Queuing uses Oracle Scheduler for message propagation. Materialized views use Oracle Scheduler for automatic refreshes. Setting JOB_QUEUE_PROCESS to 0 will disable these features as well as any other features that use Oracle Scheduler or DBMS_JOB.

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information on the DBMS_SCHEDULER package
- *Oracle Database Advanced Replication and Oracle Database Data Warehousing Guide* for more information on managing materialized views
- *Oracle Streams Advanced Queuing User's Guide* for more information on message propagation
- *Oracle Database Administrator's Guide* for more information about the maximum number of scheduler job processes

LARGE_POOL_SIZE

Property	Description
Parameter type	Big integer

Property	Description
Syntax	<code>LARGE_POOL_SIZE = integer [K M G]</code>
Default value	If <code>SGA_TARGET</code> is set, but a value is not specified for <code>LARGE_POOL_SIZE</code>, then the default is 0 (internally determined by the Oracle database). If <code>LARGE_POOL_SIZE</code> is specified, then the user-specified value indicates a minimum value for the memory pool. If <code>SGA_TARGET</code> is not set, 0 if both of the following are true: ■ The pool is not required by parallel execution ■ <code>DBWR_IO_SLAVES</code> is not set Otherwise, derived from the values of <code>PARALLEL_MAX_SERVERS</code>, <code>PARALLEL_THREADS_PER_CPU</code>, <code>CLUSTER_DATABASE_INSTANCES</code>, <code>DISPATCHERS</code>, and <code>DBWR_IO_SLAVES</code>. Note that a value derived in this way does not take into account the requirements used for Automatic Storage Management files. As a general guideline, you should add 600K to the size of the SGA on a database instance using ASM.
Modifiable	<code>ALTER SYSTEM</code>
Range of values	Minimum: the granule size Maximum: operating system-dependent
Basic	No

`LARGE_POOL_SIZE` specifies (in bytes) the size of the large pool allocation heap. The large pool allocation heap is used in shared server systems for session memory, by parallel execution for message buffers, and by backup processes for disk I/O buffers. Parallel execution allocates buffers out of the large pool only when `SGA_TARGET` is set.

Caution: When Oracle derives a default value, it adds 250K for each session for the shared server if `DISPATCHERS` is configured. The final derived value also includes a port-specific amount of memory for backup I/O buffers. The total derived default value can either be too large to allocate or can cause performance problems. In that case, set `LARGE_POOL_SIZE` to a number sufficiently small so that the database can start.

You can specify the value of this parameter using a number, optionally followed by K or M to specify kilobytes or megabytes, respectively. If you do not specify K or M, then the number is taken as bytes.

See Also: *Oracle Database Performance Tuning Guide* and *Oracle Database Upgrade Guide* for more information on setting this parameter

LDAP_DIRECTORY_ACCESS

Property	Description
Parameter type	String
Syntax	<code>LDAP_DIRECTORY_ACCESS = { NONE PASSWORD SSL }</code>
Default value	NONE
Modifiable	<code>ALTER SYSTEM</code>

Property	Description
Basic	No

LDAP_DIRECTORY_ACCESS specifies whether Oracle refers to Oracle Internet Directory for user authentication information. If directory access is turned on, then this parameter also specifies how users are authenticated.

Values:

- NONE
Oracle does not refer to Oracle Internet Directory for Enterprise User Security information.
- PASSWORD
Oracle tries to connect to the enterprise directory service using the database password stored in the database wallet. If that fails, then the Oracle Internet Directory connection fails and the database will not be able to retrieve enterprise roles and schema mappings upon enterprise user login.
- SSL
Oracle tries to connect to Oracle Internet Directory using SSL.

See Also: *Oracle Database Advanced Security Administrator's Guide* for more information on Enterprise User Security

LDAP_DIRECTORY_SYSAUTH

Property	Description
Parameter type	String
Syntax	LDAP_DIRECTORY_SYSAUTH = { yes no }
Default value	no
Modifiable	No
Basic	Yes

LDAP_DIRECTORY_SYSAUTH enables or disables directory-based authorization for SYSDBA and SYSOPER.

LICENSE_MAX_SESSIONS

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Range of values	0 to number of session licenses
Basic	No

Property	Description
Oracle RAC	Multiple instances can have different values, but the total for all instances mounting a database should be less than or equal to the total number of sessions licensed for that database.

`LICENSE_MAX_SESSIONS` specifies the maximum number of concurrent user sessions allowed. When this limit is reached, only users with the `RESTRICTED SESSION` privilege can connect to the database. Users who are not able to connect receive a warning message indicating that the system has reached maximum capacity.

A zero value indicates that concurrent usage (session) licensing is not enforced. If you set this parameter to a nonzero number, you might also want to set `LICENSE_SESSIONS_WARNING` (see "[LICENSE_SESSIONS_WARNING](#)" on page 1-83).

Do not enable both concurrent usage licensing and user licensing. Set either `LICENSE_MAX_SESSIONS` or `LICENSE_MAX_USERS` to zero.

See Also: *Oracle Database Administrator's Guide* for more information on setting this parameter

LICENSE_MAX_USERS

Property	Description
Parameter type	Integer
Default value	0
Modifiable	<code>ALTER SYSTEM</code>
Range of values	0 to number of user licenses
Basic	No
Oracle RAC	Oracle recommends that multiple instances have the same value.

`LICENSE_MAX_USERS` specifies the maximum number of users you can create in the database. When you reach this limit, you cannot create more users. You can, however, increase the limit.

Do not enable both concurrent usage (session) licensing and user licensing. Set either `LICENSE_MAX_SESSIONS` or `LICENSE_MAX_USERS` to zero.

See Also: *Oracle Database Administrator's Guide* for more information on setting this parameter

LICENSE_SESSIONS_WARNING

Property	Description
Parameter type	Integer
Default value	0
Modifiable	<code>ALTER SYSTEM</code>
Range of values	0 to value of <code>LICENSE_MAX_SESSIONS</code> parameter
Basic	No

Property	Description
Oracle RAC	Multiple instances can have different values.

`LICENSE_SESSIONS_WARNING` specifies a warning limit on the number of concurrent user sessions. When this limit is reached, additional users can connect, but Oracle writes a message in the alert file for each new connection. Users with `RESTRICTED SESSION` privilege who connect after the limit is reached receive a warning message stating that the system is nearing its maximum capacity.

If this parameter is set to zero, no warning is given as you approach the concurrent usage (session) limit. If you set this parameter to a nonzero number, you should also set `LICENSE_MAX_SESSIONS` (see "[LICENSE_MAX_SESSIONS](#)" on page 1-82).

See Also:

- *Oracle Database Administrator's Guide* for more information on setting this parameter
- *Oracle Real Application Clusters Administration and Deployment Guide* for more information on calculating an appropriate value for this parameter

LISTENER_NETWORKS

Property	Description
Parameter type	String
Syntax	<pre>LISTENER_NETWORKS = ' ((NAME=network_name) (LOCAL_LISTENER=["] listener_address[, ...] ["]) [(REMOTE_LISTENER=["] listener_address[, ...] ["])]) ' [, ...]</pre>
Default value	There is no default value.
Modifiable	<code>ALTER SYSTEM</code>
Basic	No

`LISTENER_NETWORKS` specifies one or more sets of local & remote listeners for cross-registration. All listeners within the same *network_name* will cross-register.

If a *network_name* is specified multiple times, then the resulting listener set is the union of each specification. This can be used to specify sets that require more than 255 characters, which is the per element limit.

The *listener_address* specifies a string that is an address, address list, or an alias that resolves to an address or address list of Oracle Net listeners. If an alias, the address or address list is specified in the `TNSNAMES.ORA` file or another address repository as configured for your system.

If a comma is used to specify a *listener_address* list, then the set of addresses must be surrounded by double quotes.

See Also: *Oracle Database Net Services Administrator's Guide* for more information on setting this parameter

LOCAL_LISTENER

Property	Description
Parameter type	String
Syntax	<code>LOCAL_LISTENER = network_name</code>
Default value	<code>(ADDRESS = (PROTOCOL=TCP) (HOST=hostname) (PORT=1521))</code> where <i>hostname</i> is the network name of the local host.
Modifiable	<code>ALTER SYSTEM</code>
Basic	No

`LOCAL_LISTENER` specifies a network name that resolves to an address or address list of Oracle Net local listeners (that is, listeners that are running on the same machine as this instance). The address or address list is specified in the `TNSNAMES.ORA` file or other address repository as configured for your system.

See Also:

- *Oracle Database Concepts* for more information about instances, listener processes, and dispatcher processes
- *Oracle Database Net Services Administrator's Guide* and your operating system-specific Oracle documentation for more information about specifying network addresses for the protocols on your system

LOCK_NAME_SPACE

Property	Description
Parameter type	String
Syntax	<code>LOCK_NAME_SPACE = namespace</code>
Default value	There is no default value.
Modifiable	No
Range of values	Up to 8 alphanumeric characters. No special characters allowed.
Basic	No

Note: The `LOCK_NAME_SPACE` parameter is deprecated. It is retained for backward compatibility only.

`LOCK_NAME_SPACE` specifies the namespace that the distributed lock manager (DLM) uses to generate lock names. Consider setting this parameter if a standby or clone database has the same database name on the same cluster as the primary database.

If the standby database resides on the same file system as the primary database, then set `LOCK_NAME_SPACE` in the standby parameter file to a distinct value such as the following:

```
LOCK_NAME_SPACE = standby
```

LOCK_SGA

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false
Basic	No

LOCK_SGA locks the entire SGA into physical memory. It is usually advisable to lock the SGA into real (physical) memory, especially if the use of virtual memory would include storing some of the SGA using disk space. This parameter is ignored on platforms that do not support it.

LOG_ARCHIVE_CONFIG

Property	Description
Parameter type	String
Syntax	<pre>LOG_ARCHIVE_CONFIG = { [SEND NOSEND] [RECEIVE NORECEIVE] [DG_CONFIG=(remote_db_unique_name1 [, ... remote_db_ unique_name9) NODG_CONFIG] }</pre>
Default value	'SEND, RECEIVE, NODG_CONFIG'
Modifiable	ALTER SYSTEM
Basic	No

LOG_ARCHIVE_CONFIG enables or disables the sending of redo logs to remote destinations and the receipt of remote redo logs, and specifies the unique database names (DB_UNIQUE_NAME) for each database in the Data Guard configuration.

Values:

- SEND
Enables the sending of redo logs to remote destinations
- NOSEND
Disables the sending of redo logs to remote destinations
- RECEIVE
Enables the receipt of remotely archived redo logs
- NORECEIVE
Disables the receipt of remotely archived redo logs
- DG_CONFIG

Specifies a list of up to 9 unique database names (defined with the DB_UNIQUE_NAME initialization parameter) for all of the databases in the Data Guard configuration.

- NODG_CONFIG

Eliminates the list of service provider names previously specified with the DG_CONFIG option.

LOG_ARCHIVE_DEST

Property	Description
Parameter type	String
Syntax	LOG_ARCHIVE_DEST = <i>filespec</i>
Default value	Null
Modifiable	ALTER SYSTEM
Range of values	Any valid path or device name, except raw partitions
Basic	No
Oracle RAC	Multiple instances can have different values.

Note: For Enterprise Edition users, this parameter has been deprecated in favor of the LOG_ARCHIVE_DEST_1 parameters. If Oracle Enterprise Edition is not installed or it is installed, but you have not specified any LOG_ARCHIVE_DEST_1 parameters, this parameter is valid.

LOG_ARCHIVE_DEST is applicable only if you are running the database in ARCHIVELOG mode or are recovering a database from archived redo logs. LOG_ARCHIVE_DEST is incompatible with the LOG_ARCHIVE_DEST_1 parameters, and must be defined as the null string ("" or ' ') when any LOG_ARCHIVE_DEST_1 parameter has a value other than a null string. Use a text string to specify the default location and root of the disk file or tape device when archiving redo log files. (Archiving to tape is not supported on all operating systems.) The value cannot be a raw partition.

If LOG_ARCHIVE_DEST is not explicitly defined and all the LOG_ARCHIVE_DEST_1 parameters have null string values, LOG_ARCHIVE_DEST is set to an operating system-specific default value on instance startup.

To override the destination that this parameter specifies, either specify a different destination for manual archiving or use the SQL*Plus statement ARCHIVE LOG START *filespec* for automatic archiving, where *filespec* is the new archive destination. To permanently change the destination, use the statement ALTER SYSTEM SET LOG_ARCHIVE_DEST = *filespec*, where *filespec* is the new archive destination.

Neither LOG_ARCHIVE_DEST nor LOG_ARCHIVE_FORMAT have to be complete file or directory specifiers themselves; they only need to form a valid file path after the variables are substituted into LOG_ARCHIVE_FORMAT and the two parameters are concatenated together.

See Also:

- *Oracle Database Backup and Recovery User's Guide*
- ["LOG_ARCHIVE_DUPLEX_DEST"](#) on page 1-92, ["LOG_ARCHIVE_MIN_SUCCEED_DEST"](#) on page 1-95, and ["V\\$ARCHIVE_DEST"](#) on page 7-9 for more information on setting this parameter
- Your Oracle operating system-specific documentation for the default value and for an example of how to specify the destination path or filename using LOG_ARCHIVE_DEST

LOG_ARCHIVE_DEST_n

Property	Description
Parameter type	String
Syntax	<pre>LOG_ARCHIVE_DEST__[1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31] = { null_string { LOCATION=path_name SERVICE=service_name } [MANDATORY] [REOPEN[=seconds]] [DELAY[=minutes]] [NOREGISTER] [TEMPLATE=template] [ALTERNATE=destination] [MAX_FAILURE=count] [SYNC ASYNC] [AFFIRM NOAFFIRM] [NET_TIMEOUT=seconds] [VALID_FOR=(redo_log_type,database_role)] [DB_UNIQUE_NAME] [MAX_CONNECTIONS=count] [COMPRESSION={ENABLE DISABLE}] }</pre>
Default value	There is no default value.
Modifiable	Most attributes are modifiable by ALTER SESSION and ALTER SYSTEM, but some are not. See <i>Oracle Data Guard Concepts and Administration</i> for further information.
Basic	Yes

The LOG_ARCHIVE_DEST_n initialization parameter defines up to 31 (where *n* = 1, 2, 3, ... 31) destinations, each of which *must* specify either the LOCATION or the SERVICE attribute to specify where to archive the redo data. All other attributes are optional. Note that whether you are specifying the LOCATION attribute or the SERVICE attribute, it must be the first attribute supplied in the list of attributes.

If you choose not to enter any attributes, then you can specify a NULL string by entering the following:

```
LOG_ARCHIVE_DEST_n=' ';
```

You set the attributes for the LOG_ARCHIVE_DEST_n initialization parameter to control different aspects of how redo transport services transfer redo data from a production or primary database destination to another (standby) database destination. You can query the V\$ARCHIVE_DEST view to see the current attribute settings for each destination (n).

Note: Some of the attributes for this parameter are deprecated, but are being retained for backward compatibility. See "[Deprecated Attributes for LOG_ARCHIVE_DEST_n](#)" on page 1-91.

For every LOG_ARCHIVE_DEST_n initialization parameter that you define, you must specify a corresponding LOG_ARCHIVE_DEST_STATE_n parameter. The LOG_ARCHIVE_DEST_STATE_n (where n is an integer from 1 to 31) initialization parameter specifies whether the corresponding destination is currently enabled or disabled.

See Also: "[LOG_ARCHIVE_DEST_STATE_n](#)" on page 1-91

Destinations LOG_ARCHIVE_DEST_11 through LOG_ARCHIVE_DEST_31 do not support the SYNC, ARCH, LOCATION, MANDATORY, or ALTERNATE attributes, and cannot be specified as the target of the ALTERNATE attribute.

LOG_ARCHIVE_DEST_11 through LOG_ARCHIVE_DEST_31 can only be used when the COMPATIBLE initialization parameter is set to 11.2.0 or higher.

Values:

See Also: *Oracle Data Guard Concepts and Administration* for detailed descriptions of all the values listed in this section

- **AFFIRM and NOAFFIRM**
Control whether a redo transport destination acknowledges received redo data before or after writing it to the standby redo log. The default is NOAFFIRM.
- **ALTERNATE=LOG_ARCHIVE_DEST_n**
Specifies an alternate archiving destination to be used when the original destination fails. There is no default value; if an alternate destination is not specified, then archiving does not automatically change to another destination if the original destination fails.
- **ASYN**
The redo data generated by a transaction need not have been received at a destination which has this attribute before that transaction can commit. This is the default behavior if neither SYNC nor ASYN is specified.
- **COMPRESSION**
Indicates whether network compression is enabled or disabled.
The COMPRESSION attribute is ignored if the Advanced Compression option has not been enabled.
- **DB_UNIQUE_NAME=name**
Specifies a unique name for the database at this destination. You must specify a name; there is no default value.
- **DELAY[=minutes]**

Specifies a minimum time lag between when redo data is archived on a standby site and when the archived redo log file is applied to the standby database. If you specify the DELAY attribute without a time interval, the default is 30 minutes.

- LOCATION=*local_disk_directory* or USE_DB_RECOVERY_FILE_DEST

Specifies either a local file system destination or the directory, file system, or Automatic Storage Manager disk group that will serve as the fast recovery area. You must specify this attribute for at least one destination. You can specify either a local disk directory or fast recovery area with the LOCATION attribute. You *must* include either the LOCATION or the SERVICE attribute for each destination to specify where to archive the redo data.

- MANDATORY

Specifies that the transmission of redo data to the destination must succeed before the local online redo log file can be made available for reuse. If the MANDATORY attribute is not specified, then the destination is optional.

- MAX_CONNECTIONS

Specifies the maximum number of network connections that can be used to transmit redo data to this destination. The default is 1.

- MAX_FAILURE

Controls the consecutive number of times redo transport services attempt to reestablish communication and transmit redo data to a failed destination before the primary database permanently gives up on the standby database.

- NET_TIMEOUT=*seconds*

Specifies the number of seconds the log writer process on the primary system waits for status from the network server (LNS*n*) process before terminating the network connection. The default is 30 seconds.

- NOREGISTER

Indicates that the location of the archived redo log file is not to be recorded at the corresponding destination.

- REOPEN[=*seconds*]

Specifies the minimum number of seconds before the archiver processes (ARC*n*) or the log writer process (LGWR) should try again to access a previously failed destination. The default is 300 seconds.

- SERVICE=*net_service_name*

Specifies a valid Oracle Net service name (SERVICE=*net_service_name*) that identifies the remote Oracle database instance to which redo data will be sent. Each destination *must* specify either the LOCATION or the SERVICE attribute. There is no default net service name.

- SYNC

The redo data generated by a transaction must have been received by every enabled destination which has this attribute before that transaction can commit.

- TEMPLATE=*filename_template_%t_%s_%r*

Specifies a pathname and a filename template for archived redo log files created at a redo transport destination that contain redo data from the database where this attribute is specified. This attribute overrides the value of the LOG_ARCHIVE_

FORMAT initialization parameter at a redo transport destination. This attribute does not have a default value.

- `VALID_FOR=(redo_log_type, database_role)`

Identifies when redo transport services can transmit redo data to destinations based on the following factors:

- `redo_log_type`—whether online redo log files, standby redo log files, or both are *currently* being archived on the database at this destination
- `database_role`—whether the database is *currently* running in the primary or the standby role

Deprecated Attributes for LOG_ARCHIVE_DEST_#

The following attributes are deprecated for the LOG_ARCHIVE_DEST_# parameter. They are retained for backward compatibility only.

Table 1–2 *Deprecated Attributes on the LOG_ARCHIVE_DEST_# Initialization Parameter*

Deprecated Attribute	Alternative
ARCH	Specify SYNC or ASYNC. ASYNC is the default if neither attribute is specified.
LGWR	Specify SYNC or ASYNC. ASYNC is the default if neither attribute is specified.
OPTIONAL	Destinations are optional by default.
VERIFY	None. This attribute is only used with the deprecated ARCH attribute.

In addition, note the following changes to the ASYNC and SYNC attributes:

- The BLOCKS keyword on the ASYNC attribute is no longer needed.
It is no longer necessary to set this keyword because Data Guard dynamically adjusts the block count up or down to an appropriate number of blocks, as necessary.
- The PARALLEL and NOPARALLEL keywords on the SYNC attribute are no longer needed.

LOG_ARCHIVE_DEST_#

Property	Description
Parameter type	String
Syntax	LOG_ARCHIVE_DEST_STATE_[1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31] = { enable defer alternate }
Default value	enable
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	Yes

The LOG_ARCHIVE_DEST_STATE_ *n* parameters (where *n* = 1, 2, 3, ... 31) specify the availability state of the corresponding destination. The parameter suffix (1 through 31) specifies one of the corresponding LOG_ARCHIVE_DEST_ *n* destination parameters.

Values:

- `enable`
Specifies that a valid log archive destination can be used for a subsequent archiving operation (automatic or manual). This is the default.
- `defer`
Specifies that valid destination information and attributes are preserved, but the destination is excluded from archiving operations until re-enabled.
- `alternate`
Specifies that a log archive destination is not enabled but will become enabled if communications to another destination fail.

The LOG_ARCHIVE_DEST_STATE_ *n* parameters have no effect on the ENABLE state for the LOG_ARCHIVE_DEST or LOG_ARCHIVE_DUPLEX_DEST parameters.

The V\$ARCHIVE_DEST dynamic performance view shows values in use for the current session. The DEST_ID column of that view corresponds to the archive destination suffix *n*.

See Also:

- *Oracle Database Backup and Recovery User's Guide* and *Oracle Database Administrator's Guide* for more information and examples
- ["V\\$ARCHIVE_DEST"](#) on page 7-9

LOG_ARCHIVE_DUPLEX_DEST

Property	Description
Parameter type	String
Syntax	LOG_ARCHIVE_DUPLEX_DEST = <i>filespec</i>
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Range of values	Either a null string or any valid path or device name, except raw partitions
Basic	No

Note: If you are using Oracle Enterprise Edition, this parameter is deprecated in favor of the LOG_ARCHIVE_DEST_ *n* parameters. If Oracle Enterprise Edition is not installed or it is installed but you have not specified any LOG_ARCHIVE_DEST_ *n* parameters, this parameter is valid.

LOG_ARCHIVE_DUPLEX_DEST is similar to the initialization parameter LOG_ARCHIVE_DEST. This parameter specifies a second archive destination: the **duplex** archive destination. This duplex archive destination can be either a must-succeed or a

best-effort archive destination, depending on how many archive destinations must succeed (as specified in the `LOG_ARCHIVE_MIN_SUCCEED_DEST` parameter).

The default setting of a null string ('') or (' ') indicates that a duplex archive destination does not exist.

See Also:

- ["LOG_ARCHIVE_DEST_n"](#) on page 1-88
- ["LOG_ARCHIVE_MIN_SUCCEED_DEST"](#) on page 1-95
- ["V\\$ARCHIVE_DEST"](#) on page 7-9

LOG_ARCHIVE_FORMAT

Property	Description
Parameter type	String
Syntax	<code>LOG_ARCHIVE_FORMAT = filename</code>
Default value	Operating system-dependent
Modifiable	No
Range of values	Any string that resolves to a valid filename
Basic	No
Oracle RAC	Multiple instances can have different values, but identical values are recommended.

`LOG_ARCHIVE_FORMAT` is applicable only if you are using the redo log in `ARCHIVELOG` mode. Use a text string and variables to specify the default filename format when archiving redo log files. The string generated from this format is appended to the string specified in the `LOG_ARCHIVE_DEST` parameter.

The following variables can be used in the format:

%s log sequence number

%S log sequence number, zero filled

%t thread number

%T thread number, zero filled

%a activation ID

%d database ID

%r resetlogs ID that ensures unique names are constructed for the archived log files across multiple incarnations of the database

Using uppercase letters for the variables (for example, `%S`) causes the value to be fixed length and padded to the left with zeros. An example of specifying the archive redo log filename format follows:

```
LOG_ARCHIVE_FORMAT = 'log%t_%s_%r.arc'
```

Archive log file names must contain each of the elements `%s` (sequence), `%t` (thread), and `%r` (resetlogs ID) to ensure that all archive log file names are unique. If the `LOG_ARCHIVE_FORMAT` initialization parameter is set in the parameter file, then make sure

the parameter value contains the %s, %t, and %r elements. Otherwise, the following error is displayed at the time of instance startup:

```
ORA-19905: log_archive_format must contain %s, %t and %r
```

Neither LOG_ARCHIVE_DEST nor LOG_ARCHIVE_FORMAT have to be complete file or directory specifiers themselves; they only need to form a valid file path after the variables are substituted into LOG_ARCHIVE_FORMAT and the two parameters are concatenated together.

See Also:

- *Oracle Database Backup and Recovery User's Guide, Oracle Data Guard Concepts and Administration, and Oracle Real Application Clusters Administration and Deployment Guide* for more information on setting this parameter
- Your operating system- specific Oracle documentation for the default value and range of values for LOG_ARCHIVE_FORMAT

LOG_ARCHIVE_LOCAL_FIRST

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SYSTEM
Range of values	true false
Basic	No

Note: The LOG_ARCHIVE_LOCAL_FIRST parameter is deprecated. It is retained for backward compatibility only.

LOG_ARCHIVE_LOCAL_FIRST specifies when the archiver processes (ARC*n*) transmit redo data to remote standby database destinations.

Values:

- `true`

Directs the ARC*n* process to transmit redo data after the online redo log file has been completely and successfully archived to at least one local destination. This is the default value.

Because the online redo log files are archived locally first, the LGWR process reuses the online redo log files much earlier than would be possible if the ARC*n* processes archived to the standby database concurrently with the local destination. This behavior is useful when archiving to remote destinations that use a slow network connection, such as a long-distance wide area network (WAN).
- `false`

Directs the ARC*n* process to transmit redo data at the same time the online redo log file is archived to the local destinations. This results in redo data being promptly dispatched to the remote standby database destination.

Setting `LOG_ARCHIVE_LOCAL_FIRST` to `false` is most useful for faster network connections, such as high-speed local area networks (LAN).

If `LOG_ARCHIVE_LOCAL_FIRST` is set to `true`, then it is not used on a physical standby database and any database for which the following attributes have been specified in the `LOG_ARCHIVE_DEST_n` initialization parameter:

- MANDATORY
- LOCAL

If `LOG_ARCHIVE_LOCAL_FIRST` is set to `true`, then it is ignored during certain operations, such as during a switchover, which requires synchronized archival operations. If the destination was explicitly configured to use the log writer process (by specifying the `LGWR` attribute in the `LOG_ARCHIVE_DEST_n` initialization parameter), but for some reason the log writer process becomes unable to archive to the destination, then Data Guard will revert to using the `ARCn` process to complete archival operations using the default behavior, even if `LOG_ARCHIVE_LOCAL_FIRST` is set to `false`.

For example, if a standby database problem or a network problem causes the `LGWR` process to fail, then the `ARCn` process will complete the archival. Data Guard minimizes the effect on the primary database as much as possible by archiving to the local destination first to ensure the online redo log files are available to the `LGWR` process as quickly as possible.

See Also: *Oracle Data Guard Concepts and Administration* for more information about the `LOG_ARCHIVE_LOCAL_FIRST` initialization parameter and its effect on `ARCn` behavior

LOG_ARCHIVE_MAX_PROCESSES

Property	Description
Parameter type	Integer
Default value	4
Modifiable	ALTER SYSTEM
Range of values	1 to 30
Basic	No

`LOG_ARCHIVE_MAX_PROCESSES` specifies the maximum number of `ARCn` processes that can be created.

See Also: *Oracle Database Concepts*

LOG_ARCHIVE_MIN_SUCCEED_DEST

Property	Description
Parameter type	Integer
Default value	1
Modifiable	ALTER SESSION, ALTER SYSTEM

Property	Description
Range of values	1 to 10 if you are using LOG_ARCHIVE_DEST_ <i>n</i> 1 or 2 if you are using LOG_ARCHIVE_DEST and LOG_ARCHIVE_DUPLEX_DEST
Basic	No

LOG_ARCHIVE_MIN_SUCCEED_DEST defines the minimum number of destinations that must succeed in order for the online logfile to be available for reuse.

- If you are using the LOG_ARCHIVE_DEST_ *n* parameters and automatic archiving is enabled, then the value of this parameter cannot exceed the number of enabled, valid destinations specified as MANDATORY plus the number of enabled, valid destinations that are configured with the OPTIONAL and LOCATION attributes.
- If you are using LOG_ARCHIVE_DEST and LOG_ARCHIVE_DUPLEX_DEST and automatic archiving is enabled, a value of 1 specifies that the destination specified in LOG_ARCHIVE_DEST must succeed. A value of 2 specifies that the destinations specified in both parameters must succeed.

If the value of this parameter is less than the number of enabled, valid MANDATORY destinations, this parameter is ignored in favor of the MANDATORY destination count. If the value is more than the number of enabled, valid MANDATORY destinations, then some of the enabled, valid destinations configured with the OPTIONAL and LOCATION attributes are treated as MANDATORY.

You can switch dynamically from using the older parameters to the LOG_ARCHIVE_DEST_ *n* parameter using ALTER SYSTEM, as follows:

1. Set LOG_ARCHIVE_MIN_SUCCEED_DEST to 1.
2. Set the value of LOG_ARCHIVE_DEST and LOG_ARCHIVE_DUPLEX_DEST to the null string.
3. Set the desired number of destinations for the LOG_ARCHIVE_DEST_ *n* parameters.
4. Reset LOG_ARCHIVE_MIN_SUCCEED_DEST to the desired value.

See Also:

- *Oracle Database Administrator's Guide* for more information on setting this parameter
- "[LOG_ARCHIVE_DEST_ *n*](#)" on page 1-88, "[LOG_ARCHIVE_DUPLEX_DEST](#)" on page 1-92, and "[V\\$ARCHIVE_DEST](#)" on page 7-9 for information on related parameters

LOG_ARCHIVE_TRACE

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Range of values	0, 1, 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024, 2048, 4096, 8192
Basic	No

Property	Description
Oracle RAC	Multiple instances can have different values.

LOG_ARCHIVE_TRACE controls output generated by the archivelog process.

This process can be initiated by any of the following:

- An ARC n background process (designated as ARC n in the output logs)
- An explicit session-invoked foreground process (designated as ARCH in the output logs)

The valid values have the following meanings:

- 0: Disable archivelog tracing (this is the default)
- 1: Track archival of redo log file
- 2: Track archival status of each archivelog destination
- 4: Track archival operational phase
- 8: Track archivelog destination activity
- 16: Track detailed archivelog destination activity
- 32: Track archivelog destination parameter modifications
- 64: Track ARC n process state activity
- 128: Track FAL (fetch archived log) server related activities
- 256: Track RFS Logical Client
- 512: Track LGWR redo shipping network activity
- 1024: Track RFS Physical Client
- 2048: Track RFS/ARC n Ping Heartbeat
- 4096: Track Real Time Apply
- 8192: Track Redo Apply (Media Recovery or Physical Standby)

You can combine tracing levels by adding together the values of the desired tracing levels. For example, a setting of 3 will generate level 1 and level 2 trace output. You can set different values for the primary and standby database.

When this parameter is set to the default value of 0, Oracle will still generate appropriate alert and trace entries in response to error conditions. If you change the value of this parameter dynamically in an ALTER SYSTEM statement, the changes will take effect at the start of the next archivelog operation.

See Also: *Oracle Database Administrator's Guide*

LOG_BUFFER

Property	Description
Parameter type	Integer
Default value	5 MB to 32 MB, depending on the size of the SGA, CPU count, and whether the operating system is 32-bit or 64-bit
Modifiable	No

Property	Description
Range of values	2 MB to 64 MB (32-bit operating systems) 2 MB to 256 MB (64-bit operating systems)
Basic	No

LOG_BUFFER specifies the amount of memory (in bytes) that Oracle uses when buffering redo entries to a redo log file. Redo log entries contain a record of the changes that have been made to the database block buffers. The LGWR process writes redo log entries from the log buffer to a redo log file.

The log buffer size depends on the number of redo strands in the system. One redo strand is allocated for every 16 CPUs and has a default size of 2 MB. Oracle allocates a minimum of 2 redo strands per instance. When the log buffer size is not specified, any remaining memory in the redo granules is given to the log buffer.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- Your operating system-specific Oracle documentation for the default value and range of values

LOG_CHECKPOINT_INTERVAL

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Range of values	0 to $2^{31} - 1$
Basic	No
Oracle RAC	Multiple instances can have different values.

LOG_CHECKPOINT_INTERVAL specifies the frequency of checkpoints in terms of the number of redo log file blocks that can exist between an incremental checkpoint and the last block written to the redo log. This number refers to physical operating system blocks, not database blocks.

Regardless of this value, a checkpoint always occurs when switching from one online redo log file to another. Therefore, if the value exceeds the actual redo log file size, checkpoints occur only when switching logs. Checkpoint frequency is one of the factors that influence the time required for the database to recover from an unexpected failure.

Notes:

- Specifying a value of 0 (zero) for LOG_CHECKPOINT_INTERVAL has the same effect as setting the parameter to infinity and causes the parameter to be ignored. Only nonzero values of this parameter are considered meaningful.
- Recovery I/O can also be limited by setting the LOG_CHECKPOINT_TIMEOUT parameter or by the size specified for the smallest redo log. For information on which mechanism is controlling checkpointing behavior, query the V\$INSTANCE_RECOVERY view.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- "LOG_CHECKPOINT_TIMEOUT" on page 1-99, and "V\$INSTANCE_RECOVERY" on page 8-3

LOG_CHECKPOINT_TIMEOUT

Property	Description
Parameter type	Integer
Default value	1800
Modifiable	ALTER SYSTEM
Range of values	0 to $2^{31} - 1$
Basic	No
Oracle RAC	Multiple instances can have different values.

LOG_CHECKPOINT_TIMEOUT specifies (in seconds) the amount of time that has passed since the incremental checkpoint at the position where the last write to the redo log (sometimes called the **tail of the log**) occurred. This parameter also signifies that no buffer will remain dirty (in the cache) for more than *integer* seconds.

Specifying a value of 0 for the timeout disables time-based checkpoints. Hence, setting the value to 0 is not recommended unless FAST_START_MTTR_TARGET is set.

Notes:

- A checkpoint scheduled to occur because of this parameter is delayed until the completion of the previous checkpoint if the previous checkpoint has not yet completed.
- Recovery I/O can also be limited by setting the LOG_CHECKPOINT_INTERVAL parameter or by the size specified for the smallest redo log. For information on which mechanism is controlling checkpointing behavior, query the V\$INSTANCE_RECOVERY view.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- ["LOG_CHECKPOINT_TIMEOUT"](#) on page 1-99, and ["V\\$INSTANCE_RECOVERY"](#) on page 8-3

LOG_CHECKPOINTS_TO_ALERT

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SYSTEM
Range of values	true false
Basic	No

LOG_CHECKPOINTS_TO_ALERT lets you log your checkpoints to the alert file. Doing so is useful for determining whether checkpoints are occurring at the desired frequency.

LOG_FILE_NAME_CONVERT

Property	Description
Parameter type	String
Syntax	<pre>LOG_FILE_NAME_CONVERT = 'string1' , 'string2' , 'string3' , 'string4' , ...</pre> Where: ■ <i>string1</i> is the pattern of the primary database filename ■ <i>string2</i> is the pattern of the standby database filename ■ <i>string3</i> is the pattern of the primary database filename ■ <i>string4</i> is the pattern of the standby database filename You can use as many pairs of primary and standby replacement strings as required. You can use single or double quotation marks. The following are example settings that are acceptable: <pre>LOG_FILE_NAME_CONVERT = '/dbs/t1/' , '/dbs/t1/s' , 'dbs/t2/ ' , 'dbs/t2/s_'</pre>
Default value	There is no default value.
Modifiable	ALTER SESSION
Basic	No

LOG_FILE_NAME_CONVERT converts the filename of a new log file on the primary database to the filename of a log file on the standby database. If you add a log file to the primary database, you must add a corresponding file to the standby database.

If you specify an odd number of strings (the last string has no corresponding replacement string), an error is signalled during startup. If the filename being converted matches more than one pattern in the pattern/replace string list, the first

matched pattern takes effect. There is no limit on the number of pairs that you can specify in this parameter (other than the hard limit of the maximum length of multivalue parameters).

When the standby database is updated, this parameter converts the log file name on the primary database to the log file name on the standby database. The file must exist on the standby database and must be writable or the recovery process will halt with an error.

The first string is the pattern found in the log file names on the primary database. The second string is the pattern found in the log file names on the standby database.

You should also use `LOG_FILE_NAME_CONVERT` to rename the logfiles in the clone control file when setting up the clone database during tablespace point-in-time recovery.

See Also: *Oracle Database Backup and Recovery User's Guide* and *Oracle Data Guard Concepts and Administration*

MAX_DISPATCHERS

Property	Description
Parameter type	Integer
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Range of values	If <code>MAX_DISPATCHERS</code> is specified, then it should be greater than or equal to the number of dispatchers specified by the <code>DISPATCHERS</code> parameter and less than the number of processes specified by the <code>PROCESSES</code> parameter.
Basic	No

`MAX_DISPATCHERS` specifies the maximum number of dispatcher processes allowed to be running simultaneously. It can be overridden by the `DISPATCHERS` parameter and is maintained for backward compatibility with older releases.

See Also:

- *Oracle Database Administrator's Guide* for more information on setting this parameter
- Your operating system-specific Oracle documentation for the default value and range of values

MAX_DUMP_FILE_SIZE

Property	Description
Parameter type	String
Syntax	<code>MAX_DUMP_FILE_SIZE = { integer [K M G] UNLIMITED }</code>
Default value	UNLIMITED
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	0 to unlimited, or UNLIMITED

Property	Description
Basic	No

`MAX_DUMP_FILE_SIZE` specifies the maximum size of trace files (excluding the alert file). Change this limit if you are concerned that trace files may use too much space.

- A numerical value for `MAX_DUMP_FILE_SIZE` specifies the maximum size in operating system blocks.
- A number followed by a K or M suffix specifies the file size in kilobytes or megabytes.
- The special value string `UNLIMITED` means that there is no upper limit on trace file size. Thus, dump files can be as large as the operating system permits.

See Also: *Oracle Database Administrator's Guide* and *Oracle Database Performance Tuning Guide* for more information on setting this parameter

MAX_ENABLED_ROLES

Property	Description
Parameter type	Integer
Default value	30
Modifiable	No
Range of values	0 to 148
Basic	No

Note: The `MAX_ENABLED_ROLES` parameter is deprecated. It is retained for backward compatibility only.

`MAX_ENABLED_ROLES` specifies the maximum number of database roles that users can enable, including roles contained within other roles. The actual number of roles that users can enable is 2 plus the value of `MAX_ENABLED_ROLES`, because each user has two additional roles, `PUBLIC` and the user's own role.

For example, if `MAX_ENABLED_ROLES` is set to 5, then user `HR` can have seven roles enabled (the five enabled by `MAX_ENABLED_ROLES`, plus `PUBLIC` and `HR`).

MAX_SHARED_SERVERS

Property	Description
Parameter type	Integer
Default value	There is no default value.
Modifiable	<code>ALTER SYSTEM</code>
Range of values	If <code>MAX_SHARED_SERVERS</code> is specified, then it should be greater than or equal to <code>SHARED_SERVERS</code> and less than <code>PROCESSES</code> .

Property	Description
Basic	No

MAX_SHARED_SERVERS specifies the maximum number of shared server processes allowed to be running simultaneously. Setting this parameter enables you to reserve process slots for other processes, such as dedicated servers.

When you want to reduce the range of shared servers, you can reduce MAX_SHARED_SERVERS before reducing SHARED_SERVERS. If MAX_SHARED_SERVERS is lower than SHARED_SERVERS, then the number of shared servers will not vary but will remain at the constant level specified by SHARED_SERVERS. If MAX_SHARED_SERVERS is not specified, then a shared server process may be spawned as long as the number of free process slots is greater than 1 / 8 the maximum number of processes, or 2 if PROCESSES is less than 24.

See Also:

- *Oracle Database Administrator's Guide* for more information on setting this parameter
- *Oracle Database Concepts* for information on processes
- Your operating system-specific Oracle documentation for the default value and range of values

MEMORY_MAX_TARGET

Property	Description
Parameter type	Big integer
Syntax	MEMORY_MAX_TARGET = <i>integer</i> [K M G]
Default value	0
Modifiable	No
Range of values	0 to the physical memory size available to the Oracle Database
Basic	No

MEMORY_MAX_TARGET specifies the maximum value to which a DBA can set the MEMORY_TARGET initialization parameter. See the description of MEMORY_TARGET for more information about how the settings of MEMORY_MAX_TARGET and MEMORY_TARGET affect each other.

See Also: *Oracle Database Administrator's Guide* for more information about managing memory

MEMORY_TARGET

Property	Description
Parameter type	Big integer
Syntax	MEMORY_TARGET = <i>integer</i> [K M G]
Default value	0 (SGA autotuning is disabled for DEFERRED mode autotuning requests, but allowed for IMMEDIATE mode autotuning requests)

Property	Description
Modifiable	ALTER SYSTEM
Range of values	152 MB to MEMORY_MAX_TARGET
Basic	No

MEMORY_TARGET specifies the Oracle system-wide usable memory. The database tunes memory to the MEMORY_TARGET value, reducing or enlarging the SGA and PGA as needed.

In a text-based initialization parameter file, if you omit MEMORY_MAX_TARGET and include a value for MEMORY_TARGET, then the database automatically sets MEMORY_MAX_TARGET to the value of MEMORY_TARGET. If you omit the line for MEMORY_TARGET and include a value for MEMORY_MAX_TARGET, the MEMORY_TARGET parameter defaults to zero. After startup, you can then dynamically change MEMORY_TARGET to a nonzero value, provided that it does not exceed the value of MEMORY_MAX_TARGET.

Total memory usage can grow beyond the value of MEMORY_TARGET. For example, memory is allocated to PL/SQL tables and varrays regardless of the value of MEMORY_TARGET as long as memory is available at the operating system level.

In the **Default value** field, IMMEDIATE mode autotuning requests are necessary to avoid ORA-04031 errors. The DEFERRED and IMMEDIATE modes are reflected in the OPER_MODE column of the V\$MEMORY_RESIZE_OPS view.

Note: The default value of SGA_MAX_SIZE depends on the values of MEMORY_TARGET and MEMORY_MAX_TARGET.

See Also: *Oracle Database Administrator's Guide* for more information about managing memory

NLS_CALENDAR

Property	Description
Parameter type	String
Syntax	NLS_CALENDAR = "calendar_system"
Default value	None
Modifiable	ALTER SESSION
Range of values	Any valid calendar format name
Basic	No

NLS_CALENDAR specifies which calendar system Oracle uses. It can have one of the following values:

- Arabic Hijrah
- English Hijrah
- Gregorian
- Japanese Imperial

- Persian
- ROC Official (Republic of China)
- Thai Buddha

For example, suppose NLS_CALENDAR is set to "Japanese Imperial", the date format is "E YY-MM-DD". ("E" is the date format element for the abbreviated era name.) If the date is May 15, 1997, then the SYSDATE is displayed as follows:

```
SELECT SYSDATE FROM DUAL;
SYSDATE
-----
H 09-05-15
```

Note: The value of this initialization parameter NLS_CALENDER is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined.

See Also: *Oracle Database Globalization Support Guide* for a listing of available calendar systems

NLS_COMP

Property	Description
Parameter type	String
Syntax	NLS_COMP = { BINARY LINGUISTIC ANSI }
Default value	BINARY
Modifiable	ALTER SESSION
Basic	No

NLS_COMP specifies the collation behavior of the database session.

Values:

- BINARY
Normally, comparisons in the WHERE clause and in PL/SQL blocks is binary unless you specify the NLSSORT function.
- LINGUISTIC
Comparisons for all SQL operations in the WHERE clause and in PL/SQL blocks should use the linguistic sort specified in the NLS_SORT parameter. To improve the performance, you can also define a linguistic index on the column for which you want linguistic comparisons.
- ANSI
A setting of ANSI is for backwards compatibility; in general, you should set NLS_COMP to LINGUISTIC

Note: Unless you explicitly set the value for NLS_COMP in your initialization parameter file, a default value of NULL is shown in the following views: V\$PARAMETER, V\$SYSTEM_PARAMETER, V\$PARAMETER2, V\$SYSTEM_PARAMETER2, and NLS_INSTANCE_PARAMETERS. However, the actual default value, and behavior, is BINARY. Note that you cannot change the default to NULL, because NULL is not among the valid values.

Note: The value of this initialization parameter NLS_COMP is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also: *Oracle Database Globalization Support Guide* for more information on setting this parameter

NLS_CURRENCY

Property	Description
Parameter type	String
Syntax	NLS_CURRENCY = <i>currency_symbol</i>
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION
Range of values	Any valid character string, with a maximum of 10 bytes (not including null)
Basic	No

NLS_CURRENCY specifies the string to use as the local currency symbol for the L number format element. The default value of this parameter is determined by NLS_TERRITORY.

Note: The value of this initialization parameter NLS_CURRENCY is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for more information on setting this parameter
- *Oracle Database SQL Language Reference* for information on number format elements

NLS_DATE_FORMAT

Property	Description
Parameter type	String
Syntax	NLS_DATE_FORMAT = "format"
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION
Range of values	Any valid date format mask but not exceeding a fixed length
Basic	No

NLS_DATE_FORMAT specifies the default date format to use with the TO_CHAR and TO_DATE functions. The default value of this parameter is determined by NLS_TERRITORY.

The value of this parameter can be any valid date format mask, and the value must be surrounded by double quotation marks. For example:

```
NLS_DATE_FORMAT = "MM/DD/YYYY"
```

Note: The value of this initialization parameter NLS_DATE_FORMAT is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for more information on setting this parameter
- *Oracle Database Heterogeneous Connectivity User's Guide* for information on setting this parameter in heterogeneous systems

NLS_DATE_LANGUAGE

Property	Description
Parameter type	String
Syntax	NLS_DATE_LANGUAGE = language

Property	Description
Default value	Derived from NLS_LANGUAGE
Modifiable	ALTER SESSION
Range of values	Any valid NLS_LANGUAGE value

NLS_DATE_LANGUAGE specifies the language to use for the spelling of day and month names and date abbreviations (a.m., p.m., AD, BC) returned by the TO_DATE and TO_CHAR functions.

Note: The value of this initialization parameter NLS_DATE_LANGUAGE is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for more information on setting this parameter
- *Oracle Database SQL Language Reference* for information on the TO_DATE and TO_CHAR functions.
- *Oracle Database Heterogeneous Connectivity User's Guide* for information on setting this parameter in heterogeneous systems

NLS_DUAL_CURRENCY

Property	Description
Parameter type	String
Syntax	NLS_DUAL_CURRENCY = <i>currency_symbol</i>
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION
Range of values	Any valid format name up to 10 characters

NLS_DUAL_CURRENCY specifies the dual currency symbol (such as "Euro") for the territory. The default is the dual currency symbol defined in the territory of your current language environment.

Note: The value of this initialization parameter `NLS_DUAL_CURRENCY` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also: *Oracle Database Globalization Support Guide* for more information on setting this parameter

NLS_ISO_CURRENCY

Property	Description
Parameter type	String
Syntax	<code>NLS_ISO_CURRENCY = territory</code>
Default value	Derived from <code>NLS_TERRITORY</code>
Modifiable	<code>ALTER SESSION</code>
Range of values	Any valid <code>NLS_TERRITORY</code> value

`NLS_ISO_CURRENCY` specifies the string to use as the international currency symbol for the C number format element.

Local currency symbols can be ambiguous. For example, a dollar sign (\$) can refer to U.S. dollars or Australian dollars. ISO Specification 4217 1987-07-15 defines unique "international" currency symbols for the currencies of specific territories or countries.

Note: The value of this initialization parameter `NLS_ISO_CURRENCY` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for more information on setting this parameter
- *Oracle Database SQL Language Reference* for information on number format elements

NLS_LANGUAGE

Property	Description
Parameter type	String

Property	Description
Syntax	<code>NLS_LANGUAGE = language</code>
Default value	Operating system-dependent, derived from the <code>NLS_LANG</code> environment variable
Modifiable	<code>ALTER SESSION</code>
Range of values	Any valid language name
Basic	Yes

`NLS_LANGUAGE` specifies the default language of the database. This language is used for messages, day and month names, symbols for AD, BC, a.m., and p.m., and the default sorting mechanism. This parameter also determines the default values of the parameters `NLS_DATE_LANGUAGE` and `NLS_SORT`.

Note: The value of this initialization parameter `NLS_LANGUAGE` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for a complete list of languages and additional information on this parameter
- Your operating system-specific Oracle documentation and the release notes for your country

NLS_LENGTH_SEMANTICS

Property	Description
Parameter type	String
Syntax	<code>NLS_LENGTH_SEMANTICS = string</code> Example: <code>NLS_LENGTH_SEMANTICS = 'CHAR'</code>
Default value	BYTE
Modifiable	<code>ALTER SESSION</code>
Range of values	BYTE CHAR

The session-level value of `NLS_LENGTH_SEMANTICS` specifies the default length semantics to use for `VARCHAR2` and `CHAR` table columns, user-defined object attributes, and PL/SQL variables in database objects created in the session. This default may be overridden by the explicit length semantics qualifiers `BYTE` and `CHAR` in column, attribute, and variable definitions.

The instance-level value of `NLS_LENGTH_SEMANTICS` provides a default for the session-level value if `NLS_LENGTH_SEMANTICS` it is not set explicitly by the database client through the `NLS_LENGTH_SEMANTICS` client environment variable (does not

apply to JDBC Thin clients), or the ALTER SESSION SET NLS_LENGTH_SEMANTICS statement.

NCHAR, NVARCHAR2, CLOB, and NCLOB columns are always character-based.

Sessions logged in as SYS do not use the NLS_LENGTH_SEMANTICS parameter. They use BYTE length semantics for all created objects unless overridden by the explicit BYTE and CHAR qualifiers in object definitions (SQL DDL statements).

Caution: Oracle strongly recommends that you do NOT set the NLS_LENGTH_SEMANTICS parameter to CHAR in the instance or server parameter file. This may cause many existing installation scripts to unexpectedly create columns with character length semantics, resulting in runtime errors, including buffer overflows.

NLS_NCHAR_CONV_EXCP

Property	Description
Parameter type	String
Syntax	NLS_NCHAR_CONV_EXCP = { TRUE FALSE }
Default value	FALSE
Modifiable	ALTER SESSION

NLS_NCHAR_CONV_EXCP determines whether an error is reported when there is data loss during an implicit or explicit character type conversion between NCHAR/NVARCHAR and CHAR/VARCHAR2. The default value results in no error being reported.

See Also: *Oracle Database Globalization Support Guide* for more information on setting this parameter

NLS_NUMERIC_CHARACTERS

Property	Description
Parameter type	String
Syntax	NLS_NUMERIC_CHARACTERS = "decimal_character group_separator"
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION

NLS_NUMERIC_CHARACTERS specifies the characters to use as the group separator and decimal character. It overrides those characters defined implicitly by NLS_TERRITORY. The group separator separates integer groups (that is, thousands, millions, billions, and so on). The decimal separates the integer portion of a number from the decimal portion.

You can specify any character as the decimal or group separator. The two characters specified must be single-byte and must be different from each other. The characters

cannot be any numeric character or any of the following characters: plus (+), minus sign (-), less than sign (<), greater than sign (>). Either character can be a space.

For example, if you wish to specify a comma as the decimal character and a space as the group separator, you would set this parameter as follows:

```
NLS_NUMERIC_CHARACTERS = ", "
```

Note: The value of this initialization parameter `NLS_NUMERIC_CHARACTERS` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also: *Oracle Database Globalization Support Guide* for more information on setting this parameter

NLS_SORT

Property	Description
Parameter type	String
Syntax	<code>NLS_SORT = { BINARY linguistic_definition }</code>
Default value	Derived from <code>NLS_LANGUAGE</code>
Modifiable	<code>ALTER SESSION</code>
Range of values	<code>BINARY</code> or any valid linguistic definition name

`NLS_SORT` specifies the collating sequence for character value comparison in various SQL operators and clauses, for example, `ORDER BY`, `GROUP BY`, comparison conditions (`=`, `<>`, `<=`, `>=`), `IN`, `BETWEEN`, `LIKE`, `MIN/MAX`, `GREATEST/LEAST`, and `INSTR`.

- If the value is `BINARY`, then comparison is based directly on byte values in the binary encoding of the character values being compared. The ordering depends on the character set of the compared values, which is either the database character set (for `VARCHAR2`, `CHAR`, `LONG`, and `CLOB`) or the national character set (for `NVARCHAR2`, `NCHAR`, and `NCLOB`).
- If the value is a named linguistic sort, then comparison is defined by this sort. A linguistic sort uses various rules to achieve ordering expected by speakers of one or more natural languages. This is usually the same ordering that is used in dictionaries and/or telephone directories in those languages.

The exact operators and query clauses that obey the `NLS_SORT` parameter depend on the value of the `NLS_COMP` parameter. If an operator or clause does not obey the `NLS_SORT` value, as determined by `NLS_COMP`, the collation used is `BINARY`.

The `BINARY` comparison is faster and uses less resources than any linguistic comparison but for text in a natural language, it does not provide ordering expected by users.

The value of `NLS_SORT` affects execution plans of queries. Because a standard index cannot be used as a source of values sorted in a linguistic order, an explicit sort operation must usually be performed instead of an index range scan. A functional index on the `NLSSORT` function may be defined to provide values sorted in a linguistic order and reintroduce the index range scan to the execution plan.

Note: The value of the initialization parameter `NLS_SORT` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for more information about this parameter and a current listing of values you can specify
- *Oracle Database Concepts* for more information on this parameter

NLS_TERRITORY

Property	Description
Parameter type	String
Syntax	<code>NLS_TERRITORY = territory</code>
Default value	Operating system-dependent
Modifiable	<code>ALTER SESSION</code>
Range of values	Any valid territory name
Basic	Yes

`NLS_TERRITORY` specifies the name of the territory whose conventions are to be followed for day and week numbering.

This parameter also establishes the default date format, the default decimal character and group separator, and the default ISO and local currency symbols.

For information on these settings, see ["NLS_DATE_FORMAT"](#) on page 1-107, ["NLS_NUMERIC_CHARACTERS"](#) on page 1-111, ["NLS_CURRENCY"](#) on page 1-106, and ["NLS_ISO_CURRENCY"](#) on page 1-109.

Note: The value of this initialization parameter `NLS_TERRITORY` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for a complete list of territories
- Your operating system-specific Oracle documentation for the territory-dependent default values for these parameters

NLS_TIMESTAMP_FORMAT

Property	Description
Parameter type	String
Syntax	NLS_TIMESTAMP_FORMAT = " <i>format</i> "
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION
Range of values	Any valid datetime format mask

NLS_TIMESTAMP_FORMAT defines the default timestamp format to use with the TO_CHAR and TO_TIMESTAMP functions.

The value must be surrounded by quotation marks as follows:

```
NLS_TIMESTAMP_FORMAT = 'YYYY-MM-DD HH:MI:SS.FF'
```

You can specify the value of NLS_TIMESTAMP_FORMAT by setting it in the initialization parameter file. You can specify its value for a client as a client environment variable.

You can also alter the value of NLS_TIMESTAMP_FORMAT by changing its value in the initialization parameter and then restarting the instance. To alter the value during a session use the ALTER SESSION SET statement.

Note: The value of this initialization parameter NLS_TIMESTAMP_FORMAT is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

NLS_TIMESTAMP_TZ_FORMAT

Property	Description
Parameter type	String
Syntax	NLS_TIMESTAMP_TZ_FORMAT = " <i>format</i> "
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION
Range of values	Any valid datetime format mask

NLS_TIMESTAMP_TZ_FORMAT defines the default timestamp with time zone format to use with the TO_CHAR and TO_TIMESTAMP_TZ functions.

The value must be surrounded by quotation marks as follows:

```
NLS_TIMESTAMP_TZ_FORMAT = 'YYYY-MM-DD HH:MI:SS.FF TZH:TZM'
```

You can specify the value of NLS_TIMESTAMP_TZ_FORMAT by setting it in the initialization parameter file. You can specify its value for a client as a client environment variable.

You can also alter the value of NLS_TIMESTAMP_TZ_FORMAT by changing its value in the initialization parameter and then restarting the instance. To alter the value during a session use the ALTER SESSION SET statement.

Note: The value of this initialization parameter NLS_TIMESTAMP_TZ_FORMAT is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

O7_DICTIONARY_ACCESSIBILITY

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false

O7_DICTIONARY_ACCESSIBILITY controls restrictions on SYSTEM privileges. If the parameter is set to true, access to objects in the SYS schema is allowed (Oracle7 behavior). The default setting of false ensures that system privileges that allow access to objects in "any schema" do not allow access to objects in the SYS schema.

For example, if O7_DICTIONARY_ACCESSIBILITY is set to false, then the SELECT ANY TABLE privilege allows access to views or tables in any schema except the SYS schema (data dictionary tables cannot be accessed). The system privilege EXECUTE ANY PROCEDURE allows access on the procedures in any schema except the SYS schema.

If this parameter is set to false and you need to access objects in the SYS schema, then you must be granted explicit object privileges. The following roles, which can be granted to the database administrator, also allow access to dictionary objects:

- SELECT_CATALOG_ROLE
- EXECUTE_CATALOG_ROLE
- DELETE_CATALOG_ROLE

See Also:

- *Oracle Database Upgrade Guide* for more information on this parameter and the roles mentioned here
- *Oracle Database SQL Language Reference* for information on granting roles

OBJECT_CACHE_MAX_SIZE_PERCENT

Property	Description
Parameter type	Integer
Default value	10
Modifiable	ALTER SESSION, ALTER SYSTEM ... DEFERRED
Range of values	0 to operating system-dependent maximum

The **object cache** is a memory block on the client that allows applications to store entire objects and to navigate among them without round trips to the server. `OBJECT_CACHE_MAX_SIZE_PERCENT` specifies the percentage of the optimal cache size that the session object cache can grow past the optimal size. The maximum size is equal to the optimal size plus the product of this percentage and the optimal size. When the cache size exceeds this maximum size, the system will attempt to shrink the cache to the optimal size.

See Also:

- ["OBJECT_CACHE_OPTIMAL_SIZE"](#) on page 1-116 for a description of the object cache
- *Oracle Database Concepts*, *Pro*C/C++ Programmer's Guide*, and *Oracle Call Interface Programmer's Guide* for information on precompiler use of the object cache

OBJECT_CACHE_OPTIMAL_SIZE

Property	Description
Parameter type	Integer
Default value	102400 (100K)
Modifiable	ALTER SESSION, ALTER SYSTEM ... DEFERRED
Range of values	10 KB to operating system-dependent maximum

The **object cache** is a memory block on the client that allows applications to store entire objects and to navigate among them without round trips to the server. `OBJECT_CACHE_OPTIMAL_SIZE` specifies (in bytes) the size to which the session object cache is reduced when the size of the cache exceeds the maximum size.

See Also: *Oracle Database Concepts*, *Pro*C/C++ Programmer's Guide*, and *Oracle Call Interface Programmer's Guide* for information on precompiler use of the object cache

OLAP_PAGE_POOL_SIZE

Property	Description
Parameter type	Big integer
Syntax	<code>OLAP_PAGE_POOL_SIZE = integer [K M G]</code>
Default value	0
Modifiable	<code>ALTER SESSION, ALTER SYSTEM ... DEFERRED</code>
Range of values	0 to 2 GB

`OLAP_PAGE_POOL_SIZE` specifies (in bytes) the size of the OLAP page pool.

See Also: *Oracle OLAP User's Guide* for more information about the OLAP page pool

OPEN_CURSORS

Property	Description
Parameter type	Integer
Default value	50
Modifiable	<code>ALTER SYSTEM</code>
Range of values	0 to 65535
Basic	Yes

`OPEN_CURSORS` specifies the maximum number of open cursors (handles to private SQL areas) a session can have at once. You can use this parameter to prevent a session from opening an excessive number of cursors.

It is important to set the value of `OPEN_CURSORS` high enough to prevent your application from running out of open cursors. The number will vary from one application to another. Assuming that a session does not open the number of cursors specified by `OPEN_CURSORS`, there is no added overhead to setting this value higher than actually needed.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- Your operating system-specific Oracle documentation for the range of values

OPEN_LINKS

Property	Description
Parameter type	Integer
Default value	4
Modifiable	No

Property	Description
Range of values	0 to 255

`OPEN_LINKS` specifies the maximum number of concurrent open connections to remote databases in one session. These connections include database links, as well as external procedures and cartridges, each of which uses a separate process.

Oracle counts one open link for the following:

- For each user that references a public or private database link
- For each external procedure or cartridge connection when it is executed for the first time

Both types of connections close when the session ends. You can also close a database link connection explicitly by issuing an `ALTER SESSION CLOSE DATABASE LINK` statement.

You should set this parameter to allow for the external procedure and cartridge connections expected during the session plus the number of databases referred to in typical distributed transactions (that is, a single SQL statement that references multiple databases), so that all the databases can be open to execute the statement. For example, if queries alternately access databases A, B, and C, and `OPEN_LINKS` is set to 2, time will be lost waiting while one connection is broken and another made. Increase the value if many different databases are accessed over time.

This parameter refers only to connections used for distributed transactions. Direct connections to a remote database specified as an application connects are not counted.

If you set `OPEN_LINKS` to 0, then no distributed transactions are allowed.

See Also: ["OPEN_LINKS_PER_INSTANCE"](#) on page 1-118 for information on setting open connections globally for a database instance

OPEN_LINKS_PER_INSTANCE

Property	Description
Parameter type	Integer
Default value	4
Modifiable	No
Range of values	0 to 4294967295 (4 GB -1)
Oracle RAC	Multiple instances can have different values.

`OPEN_LINKS_PER_INSTANCE` specifies the maximum number of migratable open connections globally for each database instance. XA transactions use migratable open connections so that the connections are cached after a transaction is committed. Another transaction can use the connection, provided the user who created the connection is the same as the user who owns the transaction.

`OPEN_LINKS_PER_INSTANCE` is different from `OPEN_LINKS`, which indicates the number of connections from a session. The `OPEN_LINKS` parameter is not applicable to XA applications.

See Also: ["OPEN_LINKS"](#) on page 1-117

OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No

OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES enables or disables the automatic recognition of repeatable SQL statements, as well as the generation of SQL plan baselines for such statements.

OPTIMIZER_DYNAMIC_SAMPLING

Property	Description
Parameter type	Integer
Default value	If OPTIMIZER_FEATURES_ENABLE is set to 10.0.0 or higher, then 2 If OPTIMIZER_FEATURES_ENABLE is set to 9.2.0, then 1 If OPTIMIZER_FEATURES_ENABLE is set to 9.0.1 or lower, then 0
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	0 to 10

OPTIMIZER_DYNAMIC_SAMPLING controls the level of dynamic sampling performed by the optimizer.

See Also: *Oracle Database Performance Tuning Guide* for more information on setting this parameter

OPTIMIZER_FEATURES_ENABLE

Property	Description
Parameter type	String
Syntax	OPTIMIZER_FEATURES_ENABLE = { 8.0.0 8.0.3 8.0.4 8.0.5 8.0.6 8.0.7 8.1.0 8.1.3 8.1.4 8.1.5 8.1.6 8.1.7 9.0.0 9.0.1 9.2.0 9.2.0.8 10.1.0 10.1.0.3 10.1.0.4 10.1.0.5 10.2.0.1 10.2.0.2 10.2.0.3 10.2.0.4 10.2.0.5 11.1.0.6 11.1.0.7 11.2.0.1 }
Default value	11.2.0.1
Modifiable	ALTER SESSION, ALTER SYSTEM

OPTIMIZER_FEATURES_ENABLE acts as an umbrella parameter for enabling a series of optimizer features based on an Oracle release number.

For example, if you upgrade your database from release 10.1 to release 11.1, but you want to keep the release 10.1 optimizer behavior, you can do so by setting this parameter to 10.1.0. At a later time, you can try the enhancements introduced in releases up to and including release 11.1 by setting the parameter to 11.1.0.6.

[Table 1–3](#) describes some of the optimizer features that are enabled when you set the OPTIMIZER_FEATURES_ENABLE parameter to a 9.0 release or a 9.2 release.

[Table 1–4](#) describes some of the optimizer features that are enabled when you set the OPTIMIZER_FEATURES_ENABLE parameter to a 10.1 release or a 10.2 release.

[Table 1–5](#) describes some of the optimizer features that are enabled when you set the OPTIMIZER_FEATURES_ENABLE parameter to a 11.1 release.

See Also: *Oracle Database Performance Tuning Guide* for more information about the optimizer and for information about the features listed in the following tables

Table 1–3 Optimizer Features for Oracle9i Releases

Features	9.0.0	9.0.1	9.2.0
Index fast full scan	X	X	X
Consideration of bitmap access to paths for tables with only B-tree indexes	X	X	X
Complex view merging	X	X	X
Peeking into user-defined bind variables	X	X	X
Index joins	X	X	X

Table 1–4 Optimizer Features for Oracle Database 10g Releases

Features	10.1.0	10.1.0.3	10.1.0.4	10.1.0.5	10.2.0.1	10.2.0.2
Index fast full scan	X	X	X	X	X	X
Consideration of bitmap access to paths for tables with only B-tree indexes	X	X	X	X	X	X
Complex view merging	X	X	X	X	X	X
Peeking into user-defined bind variables	X	X	X	X	X	X
Index joins	X	X	X	X	X	X
Dynamic sampling	X	X	X	X	X	X
Query rewrite enables	X	X	X	X	X	X
Skip unusable indexes	X	X	X	X	X	X
Automatically compute index statistics as part of creation	X	X	X	X	X	X
Cost-based query transformations	X	X	X	X	X	X
Allow rewrites with multiple MVs and/or base tables					X	X

Table 1–5 Optimizer Features for Oracle Database 11g Releases

Features	11.1.0.6
Enhanced Bind Peeking	X
Use extended statistics to estimate selectivity	X
Use native implementation for full outer joins	X
Partition pruning using join filtering	X
Group by placement optimization	X
Null aware antijoins	X

OPTIMIZER_INDEX_CACHING

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	0 to 100

OPTIMIZER_INDEX_CACHING lets you adjust the behavior of cost-based optimization to favor nested loops joins and IN-list iterators.

The cost of executing an index using an IN-list iterator or of executing a nested loops join when an index is used to access the inner table depends on the caching of that index in the buffer cache. The amount of caching depends on factors that the optimizer cannot predict, such as the load on the system and the block access patterns of different users.

You can modify the optimizer's assumptions about index caching for nested loops joins and IN-list iterators by setting this parameter to a value between 0 and 100 to indicate the percentage of the index blocks the optimizer should assume are in the cache. Setting this parameter to a higher value makes nested loops joins and IN-list iterators look less expensive to the optimizer. As a result, it will be more likely to pick nested loops joins over hash or sort-merge joins and to pick indexes using IN-list iterators over other indexes or full table scans. The default for this parameter is 0, which results in default optimizer behavior.

See Also: *Oracle Database Performance Tuning Guide* for more information on setting this parameter

OPTIMIZER_INDEX_COST_ADJ

Property	Description
Parameter type	Integer
Default value	100
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	1 to 10000

OPTIMIZER_INDEX_COST_ADJ lets you tune optimizer behavior for access path selection to be more or less index friendly—that is, to make the optimizer more or less prone to selecting an index access path over a full table scan.

The default for this parameter is 100 percent, at which the optimizer evaluates index access paths at the regular cost. Any other value makes the optimizer evaluate the access path at that percentage of the regular cost. For example, a setting of 50 makes the index access path look half as expensive as normal.

Note: The adjustment does not apply to user-defined cost functions for domain indexes.

See Also: *Oracle Database Performance Tuning Guide* for more information on setting this parameter, and on its relationship to ["OPTIMIZER_INDEX_CACHING"](#)

OPTIMIZER_MODE

Property	Description
Parameter type	String
Syntax	OPTIMIZER_MODE = { first_rows_[1 10 100 1000] first_rows all_rows }
Default value	all_rows
Modifiable	ALTER SESSION, ALTER SYSTEM

OPTIMIZER_MODE establishes the default behavior for choosing an optimization approach for the instance.

Values:

- `first_rows_n`
The optimizer uses a cost-based approach and optimizes with a goal of best response time to return the first *n* rows (where *n* = 1, 10, 100, 1000).
- `first_rows`
The optimizer uses a mix of costs and heuristics to find a best plan for fast delivery of the first few rows.
- `all_rows`
The optimizer uses a cost-based approach for all SQL statements in the session and optimizes with a goal of best throughput (minimum resource use to complete the entire statement).

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- *Oracle Database Concepts* and *Oracle Database Performance Tuning Guide* for more information about the optimizer

OPTIMIZER_SECURE_VIEW_MERGING

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SYSTEM
Range of values	true false
Basic	No
Oracle RAC	Multiple instances can have different values

OPTIMIZER_SECURE_VIEW_MERGING enables the optimizer to use view merging to improve query performance without performing the checks that would otherwise be performed to ensure that view merging does not violate any security intentions of the view creator.

Values:

- false
Oracle does not perform security checks that may prevent view merging and predicate move-around.
- true
Oracle performs checks to ensure that view merging and predicate move-around do not violate any security intentions of the view creator.

To take advantage of query rewrite for a particular query, you must disable the OPTIMIZER_SECURE_VIEW_MERGING parameter.

OPTIMIZER_USE_INVISIBLE_INDEXES

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No

OPTIMIZER_USE_INVISIBLE_INDEXES enables or disables the use of invisible indexes.

Values:

- true
Invisible indexes are treated as visible (normal) indexes.
- false
Invisible indexes will not be considered by the optimizer but will still be maintained by DML operations.

OPTIMIZER_USE_PENDING_STATISTICS

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No

OPTIMIZER_USE_PENDING_STATISTICS specifies whether or not the optimizer uses pending statistics when compiling SQL statements.

See Also: *Oracle Database Performance Tuning Guide* for more information on setting this parameter

OPTIMIZER_USE_SQL_PLAN_BASELINES

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No

OPTIMIZER_USE_SQL_PLAN_BASELINES enables or disables the use of SQL plan baselines stored in SQL Management Base. When enabled, the optimizer looks for a SQL plan baseline for the SQL statement being compiled. If one is found in SQL Management Base, then the optimizer will cost each of the baseline plans and pick one with the lowest cost.

OS_AUTHENT_PREFIX

Property	Description
Parameter type	String
Syntax	OS_AUTHENT_PREFIX = <i>authentication_prefix</i>
Default value	OPPS\$
Modifiable	No

OS_AUTHENT_PREFIX specifies a prefix that Oracle uses to authenticate users attempting to connect to the server. Oracle concatenates the value of this parameter to the beginning of the user's operating system account name and password. When a connection request is attempted, Oracle compares the prefixed username with Oracle usernames in the database.

The default value of this parameter is OPS\$ for backward compatibility with previous versions. However, you might prefer to set the prefix value to "" (a null string), thereby eliminating the addition of any prefix to operating system account names.

Note: The text of the OS_AUTHENT_PREFIX parameter is case sensitive on some operating systems.

See Also:

- *Oracle Database Advanced Security Administrator's Guide* for more information on setting this parameter
- Your operating system-specific Oracle documentation for the default value

OS_ROLES

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false

OS_ROLES determines whether Oracle or the operating system identifies and manages the roles of each username.

Values:

- TRUE

The operating system completely manages the role grants for all database usernames. When a user attempts to create a session, the username's security domain is initialized using the roles identified by the operating system. A user can subsequently enable as many roles identified by the operating system as specified by the parameter MAX_ENABLED_ROLES.

Revocation by Oracle of roles granted by the operating system is ignored, as are any roles previously granted by Oracle.

- FALSE

Oracle identifies and manages the roles.

See Also:

- *Oracle Database Administrator's Guide* and *Oracle Database Advanced Security Administrator's Guide* for more information on roles and on setting this parameter
- ["REMOTE_OS_ROLES"](#) on page 1-147

PARALLEL_ADAPTIVE_MULTI_USER

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SYSTEM
Range of values	true false

PARALLEL_ADAPTIVE_MULTI_USER, when set to `true`, enables an adaptive algorithm designed to improve performance in multiuser environments that use parallel execution. The algorithm automatically reduces the requested degree of parallelism based on the system load at query startup time. The effective degree of parallelism is based on the default degree of parallelism, or the degree from the table or hints, divided by a reduction factor.

The algorithm assumes that the system has been tuned for optimal performance in a single-user environment.

Tables and hints use the default degree of parallelism.

See Also: *Oracle Database Performance Tuning Guide* for more information on tuning parallel execution and on the algorithm described here

PARALLEL_AUTOMATIC_TUNING

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false

Note: The PARALLEL_AUTOMATIC_TUNING parameter is deprecated. It is retained for backward compatibility only.

When PARALLEL_AUTOMATIC_TUNING is set to `true`, Oracle determines the default values for parameters that control parallel execution. In addition to setting this parameter, you must specify the PARALLEL clause for the target tables in the system. Oracle then tunes all subsequent parallel operations automatically.

If you used parallel execution in a previous release and are now enabling PARALLEL_AUTOMATIC_TUNING, then you should reduce the amount of memory allocated from the shared pool to account for the decreased demand on that pool. This memory will now be allocated from the large pool, and will be computed automatically if LARGE_POOL_SIZE is not specified.

As part of the automatic tuning, Oracle will enable the PARALLEL_ADAPTIVE_MULTI_USER parameter. You can override any of the system-provided defaults if desired.

PARALLEL_DEGREE_LIMIT

Property	Description
Parameter type	String
Syntax	<code>PARALLEL_DEGREE_LIMIT = { CPU IO integer }</code>
Default value	CPU
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

With automatic degree of parallelism, Oracle automatically decides whether or not a statement should execute in parallel and what degree of parallelism the statement should use. The optimizer automatically determines the degree of parallelism for a statement based on the resource requirements of the statement. However, the optimizer will limit the degree of parallelism used to ensure parallel server processes do not flood the system. This limit is enforced by `PARALLEL_DEGREE_LIMIT`.

Values:

- CPU

The maximum degree of parallelism is limited by the number of CPUs in the system. The formula used to calculate the limit is `PARALLEL_THREADS_PER_CPU * CPU_COUNT * the number of instances available` (by default, all the opened instances on the cluster but can be constrained using `PARALLEL_INSTANCE_GROUP` or service specification). This is the default.

- IO

The maximum degree of parallelism the optimizer can use is limited by the I/O capacity of the system. The value is calculated by dividing the total system throughput by the maximum I/O bandwidth per process. You must run the `DBMS_RESOURCE_MANAGER.CALIBRATE_IO` procedure on the system in order to use the `IO` setting. This procedure will calculate the total system throughput and the maximum I/O bandwidth per process.

- *integer*

A numeric value for this parameter specifies the maximum degree of parallelism the optimizer can choose for a SQL statement when automatic degree of parallelism is active. Automatic degree of parallelism is only enabled if `PARALLEL_DEGREE_POLICY` is set to `AUTO` or `LIMITED`.

See Also:

- *Oracle Database VLDB and Partitioning Guide* for information about automatic degree of parallelism
- *Oracle Database PL/SQL Packages and Types Reference* for information on the `DBMS_RESOURCE_MANAGER.CALIBRATE_IO` procedure

PARALLEL_DEGREE_POLICY

Property	Description
Parameter type	String

Property	Description
Syntax	PARALLEL_DEGREE_POLICY = { MANUAL LIMITED AUTO }
Default value	MANUAL
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

PARALLEL_DEGREE_POLICY specifies whether or not automatic degree of Parallelism, statement queuing, and in-memory parallel execution will be enabled.

Values:

- **MANUAL**
Disables automatic degree of parallelism, statement queuing, and in-memory parallel execution. This reverts the behavior of parallel execution to what it was prior to Oracle Database 11g Release 2 (11.2). This is the default.
- **LIMITED**
Enables automatic degree of parallelism for some statements but statement queuing and in-memory Parallel Execution are disabled. Automatic degree of parallelism is only applied to those statements that access tables or indexes decorated explicitly with the DEFAULT degree of parallelism using the PARALLEL clause. Statements that do not access any tables or indexes decorated with the DEFAULT degree of parallelism will retain the MANUAL behavior.
- **AUTO**
Enables automatic degree of parallelism, statement queuing, and in-memory parallel execution.

See Also: *Oracle Database VLDB and Partitioning Guide* for information about automatic degree of parallelism, statement queuing, and in-memory parallel execution

PARALLEL_EXECUTION_MESSAGE_SIZE

Property	Description
Parameter type	Integer
Default value	Operating system-dependent
Modifiable	No
Range of values	Minimum: 2148 Maximum: 32768, but some operating systems may have a smaller value
Oracle RAC	Multiple instances must have the same value.

PARALLEL_EXECUTION_MESSAGE_SIZE specifies the size of messages used for parallel execution (formerly referred to as parallel query, PDML, Parallel Recovery, replication).

On most platforms, the default value is as follows:

- 16384 bytes if COMPATIBLE is set to 11.2.0 or higher

- 4096 bytes if COMPATIBLE is less than 11.2.0 and PARALLEL_AUTOMATIC_TUNING is set to true
- 2148 bytes if COMPATIBLE is less than 11.2.0 and PARALLEL_AUTOMATIC_TUNING is set to false

The default value is adequate for most applications. Larger values require a larger shared pool. Larger values result in better performance at the cost of higher memory use. For this reason, replication gets no benefit from increasing the size.

Note: When PARALLEL_AUTOMATIC_TUNING is set to TRUE, message buffers are allocated out of the large pool. In this case, the default is generally higher. Note that the PARALLEL_AUTOMATIC_TUNING parameter has been deprecated.

PARALLEL_FORCE_LOCAL

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No

PARALLEL_FORCE_LOCAL controls parallel execution in an Oracle RAC environment. By default, the parallel server processes selected to execute a SQL statement can operate on any or all Oracle RAC nodes in the cluster. By setting PARALLEL_FORCE_LOCAL to true, the parallel server processes are restricted so that they can only operate on the same Oracle RAC node where the query coordinator resides (the node on which the SQL statement was executed on).

PARALLEL_INSTANCE_GROUP

Property	Description
Parameter type	String
Syntax	PARALLEL_INSTANCE_GROUP = <i>service_name</i> <i>group_name</i>
Default value	There is no default value; parallel execution is enabled across all currently active instances.
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	Any service name or any group name specified in the INSTANCE_GROUPS parameter of any active instance
Oracle RAC	Multiple instances can have different values.

PARALLEL_INSTANCE_GROUP is an Oracle RAC parameter that you can specify in parallel mode only. Used in conjunction with services or with the INSTANCE_GROUPS parameter, it lets you restrict parallel query operations to a limited number of instances. Note that the INSTANCE_GROUPS parameter has been deprecated.

This parameter identifies the parallel instance group Oracle will use for spawning parallel execution processes. If used in conjunction with services, then parallel operations will spawn parallel execution processes only on instances defined in the service. If used in conjunction with `INSTANCE_GROUPS`, then parallel operations will spawn parallel execution processes only on instances that specify a matching group in their `INSTANCE_GROUPS` parameter.

If the value assigned to `PARALLEL_INSTANCE_GROUP` is the name of a service or group that does not exist, then the operation runs serially. No parallelism is used.

See Also: *Oracle Real Application Clusters Administration and Deployment Guide* for more information on parallel query execution in a Real Application Clusters environment

PARALLEL_IO_CAP_ENABLED

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false
Basic	No
Oracle RAC	Multiple instances can have different values.

Note: The `PARALLEL_IO_CAP_ENABLED` parameter is deprecated. It is retained for backward compatibility only. It is replaced by the `PARALLEL_DEGREE_LIMIT` parameter when set to `IO`.

`PARALLEL_IO_CAP_ENABLED` specifies whether or not Oracle caps the default degree of parallelism to no greater than what the I/O system can support. This new value is calculated based on the results of the resource manager's I/O calibration package.

If `PARALLEL_IO_CAP_ENABLED` is set to `true` and the database I/O capacity has been calibrated, then Oracle will reduce the default degree of parallelism if the I/O capacity cannot support the available number of CPUs. To calibrate the I/O capacity, use the `DBMS_RESOURCE_MANAGER.CALIBRATE_IO` procedure to measure the system's I/O capacity. Oracle then computes the degree of parallelism so as not to exceed the system's I/O capacity.

See Also: *Oracle Database Data Warehousing Guide* for information on initializing and tuning parameters for parallel execution

PARALLEL_MAX_SERVERS

Property	Description
Parameter type	Integer
Default value	<code>PARALLEL_THREADS_PER_CPU * CPU_COUNT * concurrent_parallel_users * 5</code>

Property	Description
Modifiable	ALTER SYSTEM
Range of values	0 to 3600
Oracle RAC	Multiple instances can have different values.

Note: This parameter applies to parallel execution in exclusive mode as well as in a Real Application Clusters environment.

PARALLEL_MAX_SERVERS specifies the maximum number of parallel execution processes and parallel recovery processes for an instance. As demand increases, Oracle Database increases the number of processes from the number created at instance startup up to this value.

In the formula, the value assigned to *concurrent_parallel_users* running at the default degree of parallelism on an instance is dependent on the memory management setting. If automatic memory management is disabled (manual mode), then the value of *concurrent_parallel_users* is 1. If PGA automatic memory management is enabled, then the value of *concurrent_parallel_users* is 2. If global memory management or SGA memory target is used in addition to PGA automatic memory management, then the value of *concurrent_parallel_users* is 4.

If you set this parameter too low, then some queries may not have a parallel execution process available to them during query processing. If you set it too high, then memory resource shortages may occur during peak periods, which can degrade performance.

See Also: *Oracle Database Performance Tuning Guide* for more information on tuning parallel execution

PARALLEL_MIN_PERCENT

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SESSION
Range of values	0 to 100
Oracle RAC	Multiple instances can have different values.

PARALLEL_MIN_PERCENT lets you specify the minimum percentage of the requested number of parallel execution processes required for parallel execution. Setting this parameter ensures that parallel operations will not execute unless adequate resources are available. The default value of 0 means that no minimum percentage of processes has been set.

Consider the following settings:

```
PARALLEL_MIN_PERCENT = 50
PARALLEL_MIN_SERVERS = 5
PARALLEL_MAX_SERVERS = 10
```

If 8 of the 10 parallel execution processes are busy, only 2 processes are available. If you then request a query with a degree of parallelism of 8, the minimum 50% will not be met.

You can use this parameter in conjunction with `PARALLEL_ADAPTIVE_MULTI_USER`. In a multi-user environment, an individual user or application can set `PARALLEL_MIN_PERCENT` to a minimum value until sufficient resources are available on the system and an acceptable degree of parallelism is returned.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on tuning parallel execution
- ["PARALLEL_MAX_SERVERS"](#) on page 1-130, ["PARALLEL_MIN_SERVERS"](#) on page 1-132, and ["PARALLEL_ADAPTIVE_MULTI_USER"](#) on page 1-126

PARALLEL_MIN_SERVERS

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Range of values	0 to value of <code>PARALLEL_MAX_SERVERS</code>
Oracle RAC	Multiple instances can have different values.

Note: This parameter applies to parallel execution in exclusive mode as well as in a Real Application Clusters environment.

`PARALLEL_MIN_SERVERS` specifies the minimum number of parallel execution processes for the instance. This value is the number of parallel execution processes Oracle creates when the instance is started.

See Also: *Oracle Database Performance Tuning Guide* for more information on tuning parallel execution

PARALLEL_MIN_TIME_THRESHOLD

Property	Description
Parameter type	String
Syntax	<code>PARALLEL_MIN_TIME_THRESHOLD = { AUTO integer }</code>
Default value	AUTO
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

`PARALLEL_MIN_TIME_THRESHOLD` specifies the minimum execution time a statement should have before the statement is considered for automatic degree of

parallelism. By default, this is set to 10 seconds. Automatic degree of parallelism is only enabled if `PARALLEL_DEGREE_POLICY` is set to `AUTO` or `LIMITED`.

See Also: *Oracle Database VLDB and Partitioning Guide* for information about automatic degree of parallelism

PARALLEL_SERVERS_TARGET

Property	Description
Parameter type	Integer
Default value	<code>PARALLEL_THREADS_PER_CPU * CPU_COUNT * concurrent_parallel_users * 2</code>
Modifiable	<code>ALTER SYSTEM</code>
Range of values	0 to <code>PARALLEL_MAX_SERVERS</code>
Basic	No

`PARALLEL_SERVERS_TARGET` specifies the number of parallel server processes allowed to run parallel statements before statement queuing will be used. When the parameter `PARALLEL_DEGREE_POLICY` is set to `AUTO`, Oracle will queue SQL statements that require parallel execution, if the necessary parallel server processes are not available. Statement queuing will begin once the number of parallel server processes active on the system is equal to or greater than `PARALLEL_SERVERS_TARGET`.

By default, `PARALLEL_SERVERS_TARGET` is set lower than the maximum number of parallel server processes allowed on the system (`PARALLEL_MAX_SERVERS`) to ensure each parallel statement will get all of the parallel server resources required and to prevent overloading the system with parallel server processes.

The number of concurrent parallel users running at default degree of parallelism on an instance is dependent on the memory management setting. If automatic memory management is disabled (manual mode), then the number of concurrent parallel users is 1. If PGA automatic memory management is enabled, the number of concurrent parallel users is 2. If global memory management or SGA memory target is used in addition to PGA automatic memory management, then the number of concurrent parallel users is 4.

Note that all serial (non-parallel) statements will execute immediately even if statement queuing has been activated.

PARALLEL_THREADS_PER_CPU

Property	Description
Parameter type	Integer
Default value	Operating system-dependent, usually 2
Modifiable	<code>ALTER SYSTEM</code>
Range of values	Any nonzero number

Note: This parameter applies to parallel execution in exclusive mode as well as in a Real Application Clusters environment.

PARALLEL_THREADS_PER_CPU specifies the default degree of parallelism for the instance and determines the parallel adaptive and load balancing algorithms. The parameter describes the number of parallel execution processes or **threads** that a CPU can handle during parallel execution.

The default is platform-dependent and is adequate in most cases. You should decrease the value of this parameter if the machine appears to be overloaded when a representative parallel query is executed. You should increase the value if the system is I/O bound.

See Also: *Oracle Database Performance Tuning Guide* for more information on tuning parallel execution

PGA_AGGREGATE_TARGET

Property	Description
Parameter type	Big integer
Syntax	PGA_AGGREGATE_TARGET = <i>integer</i> [K M G]
Default value	10 MB or 20% of the size of the SGA, whichever is greater
Modifiable	ALTER SYSTEM
Range of values	Minimum: 10 MB Maximum: 4096 GB - 1
Basic	Yes

PGA_AGGREGATE_TARGET specifies the target aggregate PGA memory available to all server processes attached to the instance.

Setting PGA_AGGREGATE_TARGET to a nonzero value has the effect of automatically setting the WORKAREA_SIZE_POLICY parameter to AUTO. This means that SQL working areas used by memory-intensive SQL operators (such as sort, group-by, hash-join, bitmap merge, and bitmap create) will be automatically sized. A nonzero value for this parameter is the default since, unless you specify otherwise, Oracle sets it to 20% of the SGA or 10 MB, whichever is greater.

Setting PGA_AGGREGATE_TARGET to 0 automatically sets the WORKAREA_SIZE_POLICY parameter to MANUAL. This means that SQL workareas are sized using the *_AREA_SIZE parameters.

Oracle attempts to keep the amount of private memory below the target specified by this parameter by adapting the size of the work areas to private memory. When increasing the value of this parameter, you indirectly increase the memory allotted to work areas. Consequently, more memory-intensive operations are able to run fully in memory and less will work their way over to disk.

See Also: *Oracle Database Performance Tuning Guide* for more information about setting and tuning the PGA_AGGREGATE_TARGET parameter

PLSCOPE_SETTINGS

Property	Description
Parameter type	String
Syntax	PLSCOPE_SETTINGS = IDENTIFIERS:{ NONE ALL }
Default value	IDENTIFIERS:NONE
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

PLSCOPE_SETTINGS controls the compile time collection, cross reference, and storage of PL/SQL source code identifier data.

Values:

- IDENTIFIERS:NONE
Disables collection of identifier data. This is the default.
- IDENTIFIERS:ALL
Enables the collection of all source code identifier data.

PLSCOPE_SETTINGS can be set on a session, system, or per-library unit (ALTER COMPILER) basis. The current setting of PLSCOPE_SETTINGS for any library unit can be attained by querying the *_PLSQL_OBJECT_SETTINGS views. Any identifier data collected by setting this parameter can be accessed using the *_IDENTIFIERS views.

See Also:

- ["ALL_PLSQL_OBJECT_SETTINGS"](#) on page 3-11, ["DBA_PLSQL_OBJECT_SETTINGS"](#) on page 5-70, and ["USER_PLSQL_OBJECT_SETTINGS"](#) on page 6-91
- ["ALL_IDENTIFIERS"](#) on page 2-64, ["DBA_IDENTIFIERS"](#) on page 5-43, and ["USER_IDENTIFIERS"](#) on page 6-80

PLSQL_CCFLAGS

Property	Description
Parameter type	String
Syntax	PLSQL_CCFLAGS = '<v1>:<c1>,<v2>:<c2>,...,<vn>:<cn>'
Default value	Empty string
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	Any string literal that satisfies the internal syntax
Examples	ALTER SESSION SET PLSQL_CCFLAGS = 'DeBug:True'; ALTER SESSION SET PLSQL_CCFLAGS = 'debug:TRUE';

PLSQL_CCFLAGS provides a mechanism that allows PL/SQL programmers to control conditional compilation of each PL/SQL library unit independently.

Values:

- `<vi>` has the form of an unquoted PL/SQL identifier. It is unrestricted and can be a reserved word or a keyword. The text is insensitive to case. Each one is known as a flag or flag name. Each `<vi>` can occur more than once in the string, each occurrence can have a different flag value, and the flag values can be of different kinds.
- `<ci>` is one of the following: a PL/SQL boolean literal, a `PLS_INTEGER` literal, or the literal `NULL`. The text is insensitive to case. Each one is known as a flag value and corresponds to a flag name.

You can define any allowable value for `PLSQL_CCFLAGS`. However, Oracle recommends that this parameter be used for controlling the conditional compilation of debugging or tracing code. It is recommended that the following identifiers not be used as flag name values:

- Names of Oracle parameters (for example, `NLS_LENGTH_SEMANTICS`)
- Identifiers with any of the following prefixes: `PLS_`, `PLSQL_`, `PLSCC_`, `ORA_`, `ORACLE_`, `DBMS_`, `SYS_`

PLSQL_CODE_TYPE

Property	Description
Parameter type	String
Syntax	<code>PLSQL_CODE_TYPE = { INTERPRETED NATIVE }</code>
Default value	<code>INTERPRETED</code>
Modifiable	<code>ALTER SESSION</code> , <code>ALTER SYSTEM</code>

`PLSQL_CODE_TYPE` specifies the compilation mode for PL/SQL library units.

Values:

- `INTERPRETED`
PL/SQL library units will be compiled to PL/SQL bytecode format. Such modules are executed by the PL/SQL interpreter engine.
- `NATIVE`
PL/SQL library units (with the possible exception of top-level anonymous PL/SQL blocks) will be compiled to native (machine) code. Such modules will be executed natively without incurring any interpreter overhead.

When the value of this parameter is changed, it has no effect on PL/SQL library units that have already been compiled. The value of this parameter is stored persistently with each library unit.

If a PL/SQL library unit is compiled native, all subsequent automatic recompilations of that library unit will use native compilation.

PLSQL_DEBUG

Property	Description
Parameter type	Boolean
Default value	<code>false</code>

Property	Description
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false

Note: The PLSQL_DEBUG parameter is deprecated. It is retained for backward compatibility only.

PLSQL_DEBUG specifies whether or not PL/SQL library units will be compiled for debugging.

Values:

- true
PL/SQL library units will be compiled for debugging
- false
PL/SQL library units will be compiled for normal execution

When PLSQL_DEBUG is set to true, PL/SQL library units are always compiled INTERPRETED in order to be debuggable.

When the value of this parameter is changed, it has no effect on PL/SQL library units that have already been compiled. The value of this parameter is stored persistently with each library unit.

PLSQL_OPTIMIZE_LEVEL

Property	Description
Parameter type	Integer
Default value	2
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	0 to 3

PLSQL_OPTIMIZE_LEVEL specifies the optimization level that will be used to compile PL/SQL library units. The higher the setting of this parameter, the more effort the compiler makes to optimize PL/SQL library units.

Values:

- 0
Maintains the evaluation order and hence the pattern of side effects, exceptions, and package initializations of Oracle9i and earlier releases. Also removes the new semantic identity of BINARY_INTEGER and PLS_INTEGER and restores the earlier rules for the evaluation of integer expressions. Although code will run somewhat faster than it did in Oracle9i, use of level 0 will forfeit most of the performance gains of PL/SQL in Oracle Database 10g.
- 1

Applies a wide range of optimizations to PL/SQL programs including the elimination of unnecessary computations and exceptions, but generally does not move source code out of its original source order.

- 2

Applies a wide range of modern optimization techniques beyond those of level 1 including changes which may move source code relatively far from its original location.

- 3

Applies a wide range of optimization techniques beyond those of level 2, automatically including techniques not specifically requested.

Generally, setting this parameter to 2 pays off in better execution performance. If, however, the compiler runs slowly on a particular source module or if optimization does not make sense for some reason (for example, during rapid turnaround development), then setting this parameter to 1 will result in almost as good a compilation with less use of compile-time resources.

The value of this parameter is stored persistently with the library unit.

PLSQL_V2_COMPATIBILITY

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false

Note: The PLSQL_V2_COMPATIBILITY parameter is deprecated. It is retained for backward compatibility only.

PL/SQL Version 2 allows some abnormal behavior that Version 8 disallows. If you want to retain that behavior for backward compatibility, set PLSQL_V2_COMPATIBILITY to true. If you set it to false, then PL/SQL Version 8 behavior is enforced and Version 2 behavior is not allowed.

See Also: *Oracle Database PL/SQL Language Reference* for a description of the differences between PL/SQL Version 2 and Version 8, and for more information on setting this parameter

PLSQL_WARNINGS

Property	Description
Parameter type	String
Syntax	PLSQL_WARNINGS = 'value_clause' [, 'value_clause'] ...

Property	Description
	value_clause::= <pre> { ENABLE DISABLE ERROR } : { ALL SEVERE INFORMATIONAL PERFORMANCE { integer (integer [, integer] ...) } } </pre>
Default value	'DISABLE:ALL'
Modifiable	ALTER SESSION, ALTER SYSTEM
Examples	<pre> PLSQL_WARNINGS = 'ENABLE:SEVERE', 'DISABLE:INFORMATIONAL'; PLSQL_WARNINGS = 'DISABLE:ALL'; PLSQL_WARNINGS = 'DISABLE:5000', 'ENABLE:5001', 'ERROR:5002'; PLSQL_WARNINGS = 'ENABLE:(5000,5001,5002)', 'DISABLE:(6000,6001)'; </pre>

PLSQL_WARNINGS enables or disables the reporting of warning messages by the PL/SQL compiler, and specifies which warning messages to show as errors.

value_clause

Multiple value clauses may be specified, enclosed in quotes and separated by commas. Each value clause is composed of a qualifier, a colon (:), and a modifier.

Qualifier values:

- **ENABLE**
Enable a specific warning or a set of warnings
- **DISABLE**
Disable a specific warning or a set of warnings
- **ERROR**
Treat a specific warning or a set of warnings as errors

Modifier values:

- **ALL**
Apply the qualifier to all warning messages
- **SEVERE**
Apply the qualifier to only those warning messages in the SEVERE category
- **INFORMATIONAL**
Apply the qualifier to only those warning messages in the INFORMATIONAL category
- **PERFORMANCE**

Apply the qualifier to only those warning messages in the PERFORMANCE category

PRE_PAGE_SGA

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false

PRE_PAGE_SGA determines whether Oracle reads the entire SGA into memory at instance startup. Operating system page table entries are then prebuilt for each page of the SGA. This setting can increase the amount of time necessary for instance startup, but it is likely to decrease the amount of time necessary for Oracle to reach its full performance capacity after startup.

Note: This setting does not prevent your operating system from paging or swapping the SGA after it is initially read into memory.

PRE_PAGE_SGA can increase the process startup duration, because every process that starts must access every page in the SGA. The cost of this strategy is fixed; however, you might simply determine that 20,000 pages must be touched every time a process starts. This approach can be useful with some applications, but not with all applications. Overhead can be significant if your system frequently creates and destroys processes by, for example, continually logging on and logging off.

The advantage that PRE_PAGE_SGA can afford depends on page size. For example, if the SGA is 80 MB in size and the page size is 4 KB, then 20,000 pages must be touched to refresh the SGA ($80,000 / 4 = 20,000$).

If the system permits you to set a 4 MB page size, then only 20 pages must be touched to refresh the SGA ($80,000 / 4,000 = 20$). The page size is operating system-specific and generally cannot be changed. Some operating systems, however, have a special implementation for shared memory whereby you can change the page size.

PROCESSES

Property	Description
Parameter type	Integer
Default value	100
Modifiable	No
Range of values	6 to operating system dependent
Basic	Yes
Oracle RAC	Multiple instances can have different values.

PROCESSES specifies the maximum number of operating system user processes that can simultaneously connect to Oracle. Its value should allow for all background processes such as locks, job queue processes, and parallel execution processes.

The default values of the SESSIONS and TRANSACTIONS parameters are derived from this parameter. Therefore, if you change the value of PROCESSES, you should evaluate whether to adjust the values of those derived parameters.

See Also:

- *Oracle Database Administrator's Guide* for information on setting this parameter in exclusive mode
- *Oracle Real Application Clusters Administration and Deployment Guide* for information on setting this parameter in an Oracle RAC environment
- Your operating system-specific Oracle documentation for the range of values

QUERY_REWRITE_ENABLED

Property	Description
Parameter type	String
Syntax	QUERY_REWRITE_ENABLED = { false true force }
Default value	If OPTIMIZER_FEATURES_ENABLE is set to 10.0.0 or higher, then true If OPTIMIZER_FEATURES_ENABLE is set to 9.2.0 or lower, then false
Modifiable	ALTER SESSION, ALTER SYSTEM
Oracle RAC	Multiple instances can have different values.

QUERY_REWRITE_ENABLED allows you to enable or disable query rewriting globally for the database.

Values:

- false
Oracle does not use rewrite.
- true
Oracle costs the query with rewrite and without rewrite and chooses the method with the lower cost.
- force
Oracle always uses rewrite and does not evaluate the cost before doing so. Use force when you know that the query will always benefit from rewrite and when reduction in compile time is important.

To take advantage of query rewrite for a particular materialized view, you must enable query rewrite for that materialized view, and you must enable cost-based optimization.

See Also:

- *Oracle Database Data Warehousing Guide* for information on query rewrite of materialized views
- *Oracle Database Performance Tuning Guide* and "[OPTIMIZER_MODE](#)" on page 1-122 for information on cost-based optimization

QUERY_REWRITE_INTEGRITY

Property	Description
Parameter type	String
Syntax	<code>QUERY_REWRITE_INTEGRITY = { enforced trusted stale_tolerated }</code>
Default value	enforced
Modifiable	ALTER SESSION, ALTER SYSTEM
Oracle RAC	Multiple instances can have different values.

QUERY_REWRITE_INTEGRITY determines the degree to which Oracle must enforce query rewriting. At the safest level, Oracle does not use query rewrite transformations that rely on unenforced relationships.

Values:

- `enforced`
Oracle enforces and guarantees consistency and integrity.
- `trusted`
Oracle allows rewrites using relationships that have been declared, but that are not enforced by Oracle.
- `stale_tolerated`
Oracle allows rewrites using unenforced relationships. Materialized views are eligible for rewrite even if they are known to be inconsistent with the underlying detail data.

RDBMS_SERVER_DN

Property	Description
Parameter type	X.500 Distinguished Name
Default value	There is no default value.
Modifiable	No
Range of values	All X.500 Distinguished Name format values

RDBMS_SERVER_DN specifies the Distinguished Name (DN) of the Oracle server. It is used for retrieving Enterprise Roles from an enterprise directory service.

If you do not want to use a directory for enterprise user and privilege management, but prefer to use SSL authentication alone, do not set this parameter.

See Also: *Oracle Database Advanced Security Administrator's Guide* for more information on enterprise roles and the enterprise directory service

READ_ONLY_OPEN_DELAYED

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false

READ_ONLY_OPEN_DELAYED determines when datafiles in read-only tablespaces are accessed.

Values:

- true
The datafiles are accessed for the first time only when an attempt is made to read data stored within them.
- false
The datafiles are accessed at database open time.

You can use this parameter to speed up some operations (primarily opening the database) for very large databases when substantial portions of the database are stored in read-only tablespaces. Consider setting this parameter to `true` for such databases, especially if portions of the read-only data are stored on slow-access devices or hierarchical storage.

See Also: *Oracle Database Administrator's Guide* for information on the consequences of delaying access of datafiles in read-only tablespaces

RECOVERY_PARALLELISM

Property	Description
Parameter type	Integer
Default value	System-determined parallel recovery
Modifiable	No
Range of values	System-determined, but cannot exceed PARALLEL_MAX_SERVERS initialization parameter setting

RECOVERY_PARALLELISM specifies the number of processes to participate in instance or crash recovery. To force serial crash and instance recovery, set the RECOVERY_PARALLELISM parameter to 0 or 1. 0 or 1 disable parallel instance and crash recovery on a system that has multiple CPUs. An alert log displays the degree of parallelism that was chosen when the database instance/recovery starts.

See Also:

- *Oracle Database Performance Tuning Guide* for information on setting this parameter in exclusive mode
- *Oracle Real Application Clusters Administration and Deployment Guide* for information on setting this parameter in an Oracle RAC environment

RECYCLEBIN

Property	Description
Parameter type	String
Syntax	RECYCLEBIN = { on off }
Default value	on
Modifiable	ALTER SESSION, ALTER SYSTEM ... DEFERRED
Basic	No

RECYCLEBIN is used to control whether the Flashback Drop capability is turned on or off. If the parameter is set to `off`, then dropped tables do not go into the recycle bin. If this parameter is set to `on`, then dropped tables go into the recycle bin and can be recovered.

REDO_TRANSPORT_USER

Property	Description
Parameter type	String
Syntax	REDO_TRANSPORT_USER = <i>user_name</i>
Default value	There is no default value.
Range of values	Any character string that matches the name of a user who has been granted the SYSDBA or SYSOPER privilege
Modifiable	ALTER SYSTEM
Basic	No
Oracle RAC	Every instance should use the same value

REDO_TRANSPORT_USER specifies the name of the user whose password verifier is used when a remote login password file is used for redo transport authentication. This user must have the SYSDBA or SYSOPER privilege and must have the same password in the database that initiates the redo transport session and in the database that is the target of the redo transport session.

The value of this parameter is case sensitive and must exactly match the value of the USERNAME column of a row in the V\$PWFILE_USERS view. The value of the SYSDBA or SYSOPER column of the row must also be TRUE.

If this parameter is not specified, then the password verifier of the SYS user will be used when a remote login password file is used for redo transport authentication.

REMOTE_DEPENDENCIES_MODE

Property	Description
Parameter type	String
Syntax	REMOTE_DEPENDENCIES_MODE = { TIMESTAMP SIGNATURE }
Default value	TIMESTAMP
Modifiable	ALTER SESSION, ALTER SYSTEM

REMOTE_DEPENDENCIES_MODE specifies how Oracle should handle dependencies upon remote PL/SQL stored procedures.

Values:

- **TIMESTAMP**

The client running the procedure compares the timestamp recorded on the server-side procedure with the current timestamp of the local procedure and executes the procedure only if the timestamps match.

- **SIGNATURE**

Oracle allows the procedure to execute as long as the signatures are considered safe. This setting allows client PL/SQL applications to be run without recompilation.

See Also: *Oracle Database Advanced Application Developer's Guide* for information about the consequences of the settings of this parameter

REMOTE_LISTENER

Property	Description
Parameter type	String
Syntax	REMOTE_LISTENER = <i>network_name</i>
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Basic	Yes

REMOTE_LISTENER specifies a network name that resolves to an address or address list of Oracle Net remote listeners (that is, listeners that are not running on the same machine as this instance). The address or address list is specified in the TNSNAMES.ORA file or other address repository as configured for your system.

See Also:

- *Oracle Database Concepts* for more information about instances, listener processes, and dispatcher processes
- *Oracle Database Net Services Administrator's Guide* and your operating system-specific Oracle documentation for more information about specifying network addresses for the protocols on your system

REMOTE_LOGIN_PASSWORDFILE

Property	Description
Parameter type	String
Syntax	REMOTE_LOGIN_PASSWORDFILE = { shared exclusive none }
Default value	exclusive
Modifiable	No
Basic	Yes
Oracle RAC	Multiple instances must have the same value.

REMOTE_LOGIN_PASSWORDFILE specifies whether Oracle checks for a password file.

Values:

- **shared**
One or more databases can use the password file. The password file can contain SYS as well as non-SYS users.
- **exclusive**
The password file can be used by only one database. The password file can contain SYS as well as non-SYS users.
- **none**
Oracle ignores any password file. Therefore, privileged users must be authenticated by the operating system.

Notes:

- When REMOTE_LOGIN_PASSWORDFILE is set to either exclusive or shared, but the password file does not exist, then the behavior is the same as setting REMOTE_LOGIN_PASSWORDFILE to none.
 - If you change REMOTE_LOGIN_PASSWORDFILE to exclusive or shared from none, then ensure that the password file is in sync with the dictionary passwords. See *Oracle Database Administrator's Guide* for more information.
-
-

REMOTE_OS_AUTHENT

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false

REMOTE_OS_AUTHENT specifies whether remote clients will be authenticated with the value of the OS_AUTHENT_PREFIX parameter.

Note: The REMOTE_OS_AUTHENT parameter is deprecated. It is retained for backward compatibility only.

See Also:

- *Oracle Database Advanced Security Administrator's Guide* for more information on setting this parameter
- ["OS_AUTHENT_PREFIX"](#) on page 1-124

REMOTE_OS_ROLES

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false

REMOTE_OS_ROLES specifies whether operating system roles are allowed for remote clients. The default value, `false`, causes Oracle to identify and manage roles for remote clients.

See Also:

- *Oracle Database Administrator's Guide* for more information on setting this parameter
- ["OS_ROLES"](#) on page 1-125

REPLICATION_DEPENDENCY_TRACKING

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	No
Range of values	true false

REPLICATION_DEPENDENCY_TRACKING enables or disables dependency tracking for read/write operations to the database. Dependency tracking is essential for propagating changes in a replicated environment in parallel.

Values:

- TRUE
Enables dependency tracking.
- FALSE

Allows read/write operations to the database to run faster, but does not produce dependency information for Oracle to perform parallel propagation.

Note: Do not specify this value unless you are sure that your application will not perform any read/write operations to the replicated tables.

See Also: *Oracle Database Advanced Replication* for more information on parallel propagation dependency tracking

RESOURCE_LIMIT

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SYSTEM
Range of values	true false

RESOURCE_LIMIT determines whether resource limits are enforced in database profiles.

Values:

- TRUE
Enables the enforcement of resource limits
- FALSE
Disables the enforcement of resource limits

See Also: *Oracle Database Administrator's Guide* and *Oracle Database SQL Language Reference* for more information on setting resource limits for profiles

RESOURCE_MANAGER_CPU_ALLOCATION

Property	Description
Parameter type	Integer
Default value	The number of logical CPUs reported by the operating system.
Modifiable	ALTER SYSTEM
Range of values	0 to operating system-specific
Basic	No

Note: The RESOURCE_MANAGER_CPU_ALLOCATION parameter is deprecated. It is retained for backward compatibility only.

RESOURCE_MANAGER_CPU_ALLOCATION specifies the number of CPUs that the Resource Manager should utilize. The Resource Manager controls how a system's CPUs are utilized by its database's sessions.

The Resource Manager schedules database sessions on the CPUs according to a Resource Plan that has been configured and enabled by the DBA. Normally, the Resource Manager schedules enough database sessions to keep all CPUs utilized. However, in some scenarios, a DBA may only want to schedule enough database sessions to keep a subset of the CPUs utilized.

RESOURCE_MANAGER_PLAN

Property	Description
Parameter type	String
Syntax	RESOURCE_MANAGER_PLAN = <i>plan_name</i>
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Range of values	Any valid character string

RESOURCE_MANAGER_PLAN specifies the top-level resource plan to use for an instance. The resource manager will load this top-level plan along with all its descendants (subplans, directives, and consumer groups). If you do not specify this parameter, the resource manager is off by default.

You can change the setting of this parameter using the ALTER SYSTEM statement to turn on the resource manager (if it was previously off) or to turn off the resource manager or change the current plan (if it was previously on). If you specify a plan that does not exist in the data dictionary, Oracle returns an error message.

See Also:

- *Oracle Database Administrator's Guide* for information on resource plans
- *Oracle Database PL/SQL Packages and Types Reference* for information on the DBMS_RESOURCE_MANAGER and DBMS_RESOURCE_MANAGER_PRIVS packages
- "[DBA_RSRC_PLANS](#)" on page 5-88, "[DBA_RSRC_PLAN_DIRECTIVES](#)" on page 5-87, and the various V\$RSRC_* dynamic performance views in [Part III](#) for information on existing resource plans

RESULT_CACHE_MAX_RESULT

Property	Description
Parameter type	Integer
Default value	5 percent
Modifiable	ALTER SYSTEM
Range of values	0 to 100
Basic	No

RESULT_CACHE_MAX_RESULT specifies the percentage of RESULT_CACHE_MAX_SIZE that any single result can use.

RESULT_CACHE_MAX_SIZE

Property	Description
Parameter type	Big integer
Syntax	RESULT_CACHE_MAX_SIZE = <i>integer</i> [K M G]
Default value	Derived from the values of SHARED_POOL_SIZE, SGA_TARGET, and MEMORY_TARGET
Modifiable	ALTER SYSTEM
Range of values	0 to operating system-dependent
Basic	No
Oracle RAC	You must either set this parameter to 0 on all instances to disable the result cache, or use a nonzero value on all instances. Disabling the result cache on some instances may lead to incorrect results.

RESULT_CACHE_MAX_SIZE specifies the maximum amount of SGA memory (in bytes) that can be used by the Result Cache. Values of this parameter greater than 0 are rounded up to the next multiple of 32 KB. If the value of this parameter is 0, then the feature is disabled.

RESULT_CACHE_MODE

Property	Description
Parameter type	String
Syntax	RESULT_CACHE_MODE = { MANUAL FORCE }
Default value	MANUAL
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

RESULT_CACHE_MODE specifies when a ResultCache operator is spliced into a query's execution plan.

Values:

- **MANUAL**
The ResultCache operator is added only when the query is annotated (that is, hints).
- **FORCE**
The ResultCache operator is added to the root of all SELECT statements (provided that it is valid to do so).

For the FORCE setting, if the statement contains a NO_RESULT_CACHE hint, then the hint takes precedence over the parameter setting.

RESULT_CACHE_REMOTE_EXPIRATION

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	0 to operating system-dependent
Basic	No

RESULT_CACHE_REMOTE_EXPIRATION specifies the number of minutes that a result using a remote object is allowed to remain valid. Setting this parameter to 0 implies that results using remote objects should not be cached. Setting this parameter to a nonzero value can produce stale answers (for example, if the remote table used by a result is modified at the remote database).

RESUMABLE_TIMEOUT

Property	Description
Parameter type	Integer
Default value	0 (seconds)
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	0 to $2^{31} - 1$ (in seconds)
Oracle RAC	Multiple instances can have different values.

RESUMABLE_TIMEOUT enables or disables resumable statements and specifies resumable timeout at the system level.

See Also: *Oracle Database Administrator's Guide* for more information about enabling resumable space allocation, what conditions are correctable, and what statements can be made resumable

ROLLBACK_SEGMENTS

Property	Description
Parameter type	String
Syntax	ROLLBACK_SEGMENTS = (segment_name [, segment_name] ...)
Default value	If you do not specify this parameter, the instance uses public rollback segments by default, unless the UNDO_MANAGEMENT initialization parameter is set to AUTO. In that case, the ROLLBACK_SEGMENTS parameter is ignored and automatic undo management is used.
Modifiable	No
Range of values	Any rollback segment names listed in DBA_ROLLBACK_SEGS except SYSTEM
Basic	No

Property	Description
Oracle RAC	Multiple instances must have different values.

ROLLBACK_SEGMENTS allocates one or more rollback segments by name to this instance. If you set this parameter, the instance acquires all of the rollback segments named in this parameter, even if the number of rollback segments exceeds the minimum number required by the instance (calculated as `TRANSACTIONS / TRANSACTIONS_PER_ROLLBACK_SEGMENT`).

You cannot change the value of this parameter dynamically, but you can change its value and then restart the instance. Although this parameter usually specifies private rollback segments, it can also specify public rollback segments if they are not already in use.

To find the name, segment ID number, and status of each rollback segment in the database, query the data dictionary view `DBA_ROLLBACK_SEGS`.

When `UNDO_MANAGEMENT` is set to `AUTO`, `ROLLBACK_SEGMENTS` is ignored.

See Also:

- *Oracle Database Administrator's Guide* for more information on setting this parameter
- *Oracle Real Application Clusters Administration and Deployment Guide* for information on setting this parameter in an Oracle RAC environment
- ["DBA_ROLLBACK_SEGS"](#) on page 5-83

SEC_CASE_SENSITIVE_LOGON

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SYSTEM
Range of values	true false
Basic	No

`SEC_CASE_SENSITIVE_LOGON` enables or disables password case sensitivity in the database.

Values:

- true
Database logon passwords are case sensitive.
- false
Database logon passwords are not case sensitive.

SEC_MAX_FAILED_LOGIN_ATTEMPTS

Property	Description
Parameter type	Integer
Default value	10
Modifiable	No
Range of values	1 to unlimited
Basic	No

`SEC_MAX_FAILED_LOGIN_ATTEMPTS` specifies the number of authentication attempts that can be made by a client on a connection to the server process. After the specified number of failure attempts, the connection will be automatically dropped by the server process.

SEC_PROTOCOL_ERROR_FURTHER_ACTION

Property	Description
Parameter type	String
Syntax	<code>SEC_PROTOCOL_ERROR_FURTHER_ACTION = { CONTINUE (DELAY, integer) (DROP, integer) }</code>
Default value	CONTINUE
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

`SEC_PROTOCOL_ERROR_FURTHER_ACTION` specifies the further execution of a server process when receiving bad packets from a possibly malicious client.

Values:

- CONTINUE

The server process continues execution. The database server may be subject to a Denial of Service (DoS) if bad packets continue to be sent by a malicious client.

- (DELAY, integer)

The client experiences a delay of *integer* seconds before the server process accepts the next request from the same client connection. Malicious clients are prevented from excessive consumption of server resources while legitimate clients experience a degradation in performance but can continue to function.

- (DROP, integer)

The server forcefully terminates the client connection after *integer* cumulative bad packets. The server protects itself at the expense of the client (for example, a client transaction may be lost). The client may reconnect and attempt the same operation.

SEC_PROTOCOL_ERROR_TRACE_ACTION

Property	Description
Parameter type	String
Syntax	SEC_PROTOCOL_ERROR_TRACE_ACTION = { NONE TRACE LOG ALERT }
Default value	TRACE
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

SEC_PROTOCOL_ERROR_TRACE_ACTION specifies the action that the database should take when bad packets are received from a possibly malicious client.

Values:

- NONE
The database server ignores the bad packets and does not generate any trace files or log messages.
- TRACE
A detailed trace file is generated when bad packets are received, which can be used to debug any problems in client/server communication.
- LOG
A minimal log message is printed in the alert logfile and in the server trace file. A minimal amount of disk space is used.
- ALERT
An alert message is sent to a DBA or monitoring console.

SEC_RETURN_SERVER_RELEASE_BANNER

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false
Basic	No

SEC_RETURN_SERVER_RELEASE_BANNER specifies whether or not the server returns complete database software information to unauthenticated clients.

Values:

- true
Returns complete database version information to the client.
- false
Returns a generic version string to the client.

See Also: *Oracle Call Interface Programmer's Guide* and *Oracle Database Security Guide* for more information on controlling the display of the database version banner.

SERIAL_REUSE

Property	Description
Parameter type	String
Syntax	<code>SERIAL_REUSE = { disable all select dml plsql force }</code>
Default value	disable
Modifiable	No
Basic	No

Note: The SERIAL_REUSE parameter is deprecated. It is retained for backward compatibility only.

SERIAL_REUSE specifies which types of cursors make use of the serial-reusable memory feature. This feature allocates private cursor memory in the SGA so that it can be reused (serially, not concurrently) by sessions executing the same cursor.

Values:

- `disable`
Disables the option for all SQL statement types. This value overrides any other values included in the list.
- `all`
Enables the option for both DML and SELECT statements. Equivalent to setting `select`, `dml`, and `plsql`.
- `select`
Enables the option for SELECT statements.
- `dml`
Enables the option for DML statements.
- `plsql`
Currently has no effect (although PLSQL packages do support the serial-reuse memory option using PLSQL pragmas).

Note: If CURSOR_SPACE_FOR_TIME is set to `true`, then the value of SERIAL_REUSE is ignored and treated as if it were set to `disable`.

See Also: ["CURSOR_SPACE_FOR_TIME"](#) on page 1-41

SERVICE_NAMES

Property	Description
Parameter type	String
Syntax	<code>SERVICE_NAMES =</code> <code>db_service_name [, db_service_name [...]]</code>
Default value	DB_UNIQUE_NAME.DB_DOMAIN if defined
Modifiable	ALTER SYSTEM
Range of values	Any ASCII string or comma-separated list of string names
Basic	No
Oracle RAC	Do not set the SERVICE_NAMES parameter for Oracle RAC environments. Instead, define services using Oracle Enterprise Manager and manage those services using Server Control (SRVCTL) utility.

SERVICE_NAMES specifies one or more names by which clients can connect to the instance. The instance registers its service names with the listener. When a client requests a service, the listener determines which instances offer the requested service and routes the client to the appropriate instance.

You can specify multiple service names in order to distinguish among different uses of the same database. For example:

```
SERVICE_NAMES = sales.acme.com, widgetsales.acme.com
```

You can also use service names to identify a single service that is available from two different databases through the use of replication.

If you do not qualify the names in this parameter with a domain, Oracle qualifies them with the value of the DB_DOMAIN parameter. If DB_DOMAIN is not specified, then no domain will be applied to the non-qualified SERVICE_NAMES values.

See Also:

- *Oracle Database Net Services Administrator's Guide* for more information on this parameter and its settings
- *Oracle Real Application Clusters Administration and Deployment Guide* for information about defining and administering services in an Oracle RAC environment
- ["DB_DOMAIN"](#) on page 1-48

SESSION_CACHED_CURSORS

Property	Description
Parameter type	Integer
Default value	50
Modifiable	ALTER SESSION
Range of values	0 to operating system-dependent
Oracle RAC	Multiple instances can have different values.

`SESSION_CACHED_CURSORS` specifies the number of session cursors to cache. Repeated parse calls of the same SQL (including recursive SQL) or PL/SQL statement cause the session cursor for that statement to be moved into the session cursor cache. Subsequent parse calls will find the cursor in the cache and do not need to reopen the cursor. Oracle uses a least recently used algorithm to remove entries in the session cursor cache to make room for new entries when needed.

See Also: *Oracle Database Performance Tuning Guide* for more information on setting this parameter and its uses

SESSION_MAX_OPEN_FILES

Property	Description
Parameter type	Integer
Default value	10
Modifiable	No
Range of values	1 to either 50 or the value of <code>MAX_OPEN_FILES</code> defined at the operating system level, whichever is less

`SESSION_MAX_OPEN_FILES` specifies the maximum number of BFILEs that can be opened in any session. Once this number is reached, subsequent attempts to open more files in the session by using `DBMS_LOB.FILEOPEN()` or `OCILOBFileOpen()` will fail. The maximum value for this parameter depends on the equivalent parameter defined for the underlying operating system.

See Also:

- *Oracle Database SecureFiles and Large Objects Developer's Guide* for information on LOBs in general and BFILEs in particular
- *Oracle Database PL/SQL Packages and Types Reference* for information on the `DBMS_LOB.FILEOPEN()` procedure
- *Oracle Call Interface Programmer's Guide* for information on the `OCILOBFileOpen()` procedure

SESSIONS

Property	Description
Parameter type	Integer
Default value	Derived: $(1.5 * \text{PROCESSES}) + 22$
Modifiable	No
Range of values	1 to 2^{31}
Basic	Yes

`SESSIONS` specifies the maximum number of sessions that can be created in the system. Because every login requires a session, this parameter effectively determines the maximum number of concurrent users in the system. You should always set this parameter explicitly to a value equivalent to your estimate of the maximum number of

concurrent users, plus the number of background processes, plus approximately 10% for recursive sessions.

Oracle uses the default value of this parameter as its minimum. Values between 1 and the default do not trigger errors, but Oracle ignores them and uses the default instead.

The default values of the `ENQUEUE_RESOURCES` and `TRANSACTIONS` parameters are derived from `SESSIONS`. Therefore, if you increase the value of `SESSIONS`, you should consider whether to adjust the values of `ENQUEUE_RESOURCES` and `TRANSACTIONS` as well. (Note that `ENQUEUE_RESOURCES` is obsolete as of Oracle Database 10g release 2 (10.2).)

In a shared server environment, the value of `PROCESSES` can be quite small. Therefore, Oracle recommends that you adjust the value of `SESSIONS` to approximately 1.1 * total number of *connections*.

See Also:

- *Oracle Database Concepts* for more information on memory structures and processes

SGA_MAX_SIZE

Property	Description
Parameter type	Big integer
Syntax	<code>SGA_MAX_SIZE = integer [K M G]</code>
Default value	Initial size of SGA at startup, dependent on the sizes of different pools in the SGA, such as buffer cache, shared pool, large pool, and so on.
Modifiable	No
Range of values	0 to operating system-dependent

`SGA_MAX_SIZE` specifies the maximum size of the SGA for the lifetime of the instance.

On 64-bit platforms and non-Windows 32-bit platforms, when either `MEMORY_TARGET` or `MEMORY_MAX_TARGET` is specified, the default value of `SGA_MAX_SIZE` is set to the larger of the two parameters. This causes more address space to be reserved for expansion of the SGA.

On Windows 32-bit platforms, the default value of `SGA_MAX_SIZE` is the largest of the following values:

- 60% of `MEMORY_TARGET`, if specified
- 60% of `MEMORY_MAX_TARGET`, if specified
- 25% of the total available virtual address space

SGA_TARGET

Property	Description
Parameter type	Big integer
Syntax	<code>SGA_TARGET = integer [K M G]</code>
Default value	0 (SGA autotuning is disabled for <code>DEFERRED</code> mode autotuning requests, but allowed for <code>IMMEDIATE</code> mode autotuning requests)

Property	Description
Modifiable	ALTER SYSTEM
Range of values	64 MB to operating system-dependent
Basic	Yes

SGA_TARGET specifies the total size of all SGA components. If SGA_TARGET is specified, then the following memory pools are automatically sized:

- Buffer cache (DB_CACHE_SIZE)
- Shared pool (SHARED_POOL_SIZE)
- Large pool (LARGE_POOL_SIZE)
- Java pool (JAVA_POOL_SIZE)
- Streams pool (STREAMS_POOL_SIZE)

If these automatically tuned memory pools are set to nonzero values, then those values are used as minimum levels by Automatic Shared Memory Management. You would set minimum values if an application component needs a minimum amount of memory to function properly.

The following pools are manually sized components and are not affected by Automatic Shared Memory Management:

- Log buffer
- Other buffer caches, such as KEEP, RECYCLE, and other block sizes
- Fixed SGA and other internal allocations

The memory allocated to these pools is deducted from the total available for SGA_TARGET when Automatic Shared Memory Management computes the values of the automatically tuned memory pools.

In the **Default value** field, IMMEDIATE mode autotuning requests are necessary to avoid ORA-04031 errors. The DEFERRED and IMMEDIATE modes are reflected in the OPER_MODE column of the V\$MEMORY_RESIZE_OPS view.

See Also:

- *Oracle Database Concepts* for information on automatic SGA management
- *Oracle Database Administrator's Guide* for information on managing the SGA

SHADOW_CORE_DUMP

Property	Description
Parameter type	String
Syntax	SHADOW_CORE_DUMP = { partial full none }
Default value	partial
Modifiable	No

SHADOW_CORE_DUMP specifies whether Oracle includes the SGA in the core file for foreground (client) processes.

Values:

- `partial`
Oracle does not include the SGA in the core dump.
- `full`
Oracle includes the SGA in the core dump.
- `none`
No core files will be generated for foreground processes.

See Also: ["BACKGROUND_CORE_DUMP"](#) on page 1-27

SHARED_MEMORY_ADDRESS

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No

SHARED_MEMORY_ADDRESS and HI_SHARED_MEMORY_ADDRESS specify the starting address at runtime of the system global area (SGA). This parameter is ignored on the many platforms that specify the SGA's starting address at linktime.

Use this parameter to specify the entire address on 32-bit platforms and to specify the low-order 32 bits of a 64-bit address on 64-bit platforms. Use HI_SHARED_MEMORY_ADDRESS to specify the high-order 32 bits of a 64-bit address on 64-bit platforms. If both parameters are 0 or unspecified, the SGA address defaults to a platform-specific location.

See Also: ["HI_SHARED_MEMORY_ADDRESS"](#) on page 1-74

SHARED_POOL_RESERVED_SIZE

Property	Description
Parameter type	Big integer
Syntax	SHARED_POOL_RESERVED_SIZE = <i>integer</i> [K M G]
Default value	5% of the value of SHARED_POOL_SIZE
Modifiable	No
Range of values	Minimum: 5000 Maximum: one half of the value of SHARED_POOL_SIZE

SHARED_POOL_RESERVED_SIZE specifies (in bytes) the shared pool space that is reserved for large contiguous requests for shared pool memory.

You can use this parameter to avoid performance degradation in the shared pool in situations where pool fragmentation forces Oracle to search for and free chunks of unused pool to satisfy the current request.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- ["SHARED_POOL_SIZE"](#) on page 1-161

SHARED_POOL_SIZE

Property	Description
Parameter type	Big integer
Syntax	<code>SHARED_POOL_SIZE = integer [K M G]</code>
Default value	If <code>SGA_TARGET</code> is set: If the parameter is not specified, then the default is 0 (internally determined by the Oracle Database). If the parameter is specified, then the user-specified value indicates a minimum value for the memory pool. If <code>SGA_TARGET</code> is not set (32-bit platforms): 64 MB, rounded up to the nearest granule size. If <code>SGA_TARGET</code> is not set (64-bit platforms): 128 MB, rounded up to the nearest granule size. For considerations when dealing with database instances using ASM, see "SHARED_POOL_SIZE and Automatic Storage Management" on page 1-161.
Modifiable	<code>ALTER SYSTEM</code>
Range of values	Minimum: the granule size Maximum: operating system-dependent

`SHARED_POOL_SIZE` specifies (in bytes) the size of the shared pool. The shared pool contains shared cursors, stored procedures, control structures, and other structures. If you set `PARALLEL_AUTOMATIC_TUNING` to `false`, then Oracle also allocates parallel execution message buffers from the shared pool. Larger values improve performance in multi-user systems. Smaller values use less memory.

You can monitor utilization of the shared pool by querying the view `V$SGASTAT`.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- *Oracle Database Upgrade Guide* for information on parallel execution message buffers
- ["PARALLEL_AUTOMATIC_TUNING"](#) on page 1-126 and ["V\\$SGASTAT"](#) on page 9-24

SHARED_POOL_SIZE and Automatic Storage Management

On a database instance using ASM, additional memory is required to store extent maps. As a general guideline, you can aggregate the values from the following queries to obtain current database storage size that is either already on ASM or will be stored

in ASM. Then determine the redundancy type that is used (or will be used), and calculate the value for SHARED_POOL_SIZE, using the aggregated value as input.

```
SELECT SUM(BYTES)/(1024*1024*1024) FROM V$DATAFILE;
SELECT SUM(BYTES)/(1024*1024*1024) FROM V$LOGFILE a, V$LOG b
WHERE a.group#=b.group#;
SELECT SUM(BYTES)/(1024*1024*1024) FROM V$TEMPFILE WHERE
status='ONLINE';
```

Additionally, keep the following guidelines in mind:

- For diskgroups using external redundancy:
(Every 100G of space needs 1M of extra shared pool) + 2M
- For diskgroups using normal redundancy:
(Every 50G of space needs 1M of extra shared pool) + 4M
- For diskgroups using high redundancy:
(Every 33G of space needs 1M of extra shared pool) + 6M

SHARED_SERVER_SESSIONS

Property	Description
Parameter type	Integer
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Range of values	If SHARED_SERVER_SESSIONS is specified, then it should be less than SESSIONS. If SHARED_SERVER_SESSIONS is not specified, then a shared server session may be created as long as there is a free session slot.

SHARED_SERVER_SESSIONS specifies the total number of shared server sessions to allow. Setting this parameter enables you to reserve user sessions for dedicated servers.

See Also: *Oracle Database Concepts* for more information on sessions

SHARED_SERVERS

Property	Description
Parameter type	Integer
Default value	0, meaning that shared server is not on. If you are using shared server architecture or if the DISPATCHERS parameter is set such that the total number of dispatchers is more than 0, then the default value is 1.
Modifiable	ALTER SYSTEM
Range of values	The value of this parameter should be less than MAX_SHARED_SERVERS. If it is greater than or equal to MAX_SHARED_SERVERS, then the number of servers will not be self-tuned but will remain constant, as specified by SHARED_SERVERS.
Basic	Yes

SHARED_SERVERS specifies the number of server processes that you want to create when an instance is started. If system load decreases, then this minimum number of servers is maintained. Therefore, you should take care not to set SHARED_SERVERS too high at system startup.

See Also: *Oracle Database Administrator's Guide* for more information on setting this parameter

SKIP_UNUSABLE_INDEXES

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false

SKIP_UNUSABLE_INDEXES enables or disables the use and reporting of tables with unusable indexes or index partitions. If a SQL statement uses a hint that forces the usage of an unusable index, then this hint takes precedence over initialization parameter settings, including SKIP_UNUSABLE_INDEXES. If the optimizer chooses an unusable index, then an ORA-01502 error will result. (See *Oracle Database Administrator's Guide* for more information about using hints.)

Values:

- true

Disables error reporting of indexes and index partitions marked UNUSABLE. This setting allows all operations (inserts, deletes, updates, and selects) on tables with unusable indexes or index partitions.

Note: If an index is used to enforce a UNIQUE constraint on a table, then allowing insert and update operations on the table might violate the constraint. Therefore, this setting does not disable error reporting for unusable indexes that are unique.

- false

Enables error reporting of indexes marked UNUSABLE. This setting does not allow inserts, deletes, and updates on tables with unusable indexes or index partitions.

SMTP_OUT_SERVER

Property	Description
Parameter type	String
Syntax	SMTP_OUT_SERVER = <i>server_clause</i> [, <i>server_clause</i>] ... server_clause::= <i>host_name</i> [: <i>port</i>]

Property	Description
Default value	There is no default value.
Modifiable	ALTER SESSION, ALTER SYSTEM

SMTP_OUT_SERVER specifies the SMTP host and port to which UTL_MAIL delivers out-bound E-mail. Multiple servers may be specified, separated by commas.

If the first server in the list is unavailable, then UTL_MAIL tries the second server, and so on.

If SMTP_OUT_SERVER is not specified, then the SMTP server name defaults to the value of DB_DOMAIN, the port number defaults to 25, and the SMTP domain defaults to the suffix of DB_DOMAIN.

See Also: *Oracle Database PL/SQL Packages and Types Reference* for information on the UTL_MAIL package

SORT_AREA_RETAINED_SIZE

Property	Description
Parameter type	Integer
Default value	Derived from SORT_AREA_SIZE
Modifiable	ALTER SESSION, ALTER SYSTEM ... DEFERRED
Range of values	From the value equivalent of two database blocks to the value of SORT_AREA_SIZE

Note: Oracle does not recommend using the SORT_AREA_RETAINED_SIZE parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting PGA_AGGREGATE_TARGET instead. SORT_AREA_RETAINED_SIZE is retained for backward compatibility.

SORT_AREA_RETAINED_SIZE specifies (in bytes) the maximum amount of the user global area (UGA) memory retained after a sort run completes. The retained size controls the size of the read buffer, which Oracle uses to maintain a portion of the sort in memory. This memory is released back to the UGA, not to the operating system, after the last row is fetched from the sort space.

Oracle may allocate multiple sort spaces of this size for each query. Usually, only one or two sorts occur at one time, even for complex queries. In some cases, however, additional concurrent sorts are required, and each sort keeps its own memory area. If the shared server is used, allocation is to the SGA until the value in SORT_AREA_RETAINED_SIZE is reached. The difference between SORT_AREA_RETAINED_SIZE and SORT_AREA_SIZE is allocated to the PGA.

Note: The default value as reflected in the V\$PARAMETER dynamic performance view is 0. However, if you do not explicitly set this parameter, Oracle actually uses the value of the SORT_AREA_SIZE parameter.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- ["SORT_AREA_SIZE"](#) on page 1-165

SORT_AREA_SIZE

Property	Description
Parameter type	Integer
Default value	65536
Modifiable	ALTER SESSION, ALTER SYSTEM ... DEFERRED
Range of values	Minimum: the value equivalent of six database blocks Maximum: operating system-dependent

Note: Oracle does not recommend using the SORT_AREA_SIZE parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting PGA_AGGREGATE_TARGET instead. SORT_AREA_SIZE is retained for backward compatibility.

SORT_AREA_SIZE specifies (in bytes) the maximum amount of memory Oracle will use for a sort. After the sort is complete, but before the rows are returned, Oracle releases all of the memory allocated for the sort, except the amount specified by the SORT_AREA_RETAINED_SIZE parameter. After the last row is returned, Oracle releases the remainder of the memory.

Increasing SORT_AREA_SIZE size improves the efficiency of large sorts.

Each sort in a query can consume memory up to the amount specified by SORT_AREA_SIZE, and there can be multiple sorts in a query. Also, if a query is executed in parallel, each PQ slave can consume memory up to the amount specified by SORT_AREA_SIZE for each sort it does.

SORT_AREA_SIZE is also used for inserts and updates to bitmap indexes. Setting this value appropriately results in a bitmap segment being updated only once for each DML operation, even if more than one row in that segment changes.

Larger values of SORT_AREA_SIZE permit more sorts to be performed in memory. If more space is required to complete the sort than will fit into the memory provided, then temporary segments on disk are used to hold the intermediate sort runs.

The default is adequate for most OLTP operations. You might want to adjust this parameter for decision support systems, batch jobs, or large CREATE INDEX operations.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- *Oracle Database Concepts* for information on logical storage structures such as sort areas
- Your operating system-specific Oracle documentation for the default value on your system
- ["SORT_AREA_RETAINED_SIZE"](#) on page 1-164

SPFILE

Property	Description
Parameter type	String
Syntax	<code>SPFILE = spfile_name</code>
Default value	<code>ORACLE_HOME/dbs/spfile.ora</code>
Modifiable	No
Range of values	Any valid SPFILE
Oracle RAC	Multiple instances should have the same value.

The value of this parameter is the name of the current server parameter file (SPFILE) in use. This parameter can be defined in a client side PFILE to indicate the name of the server parameter file to use.

When the default server parameter file is used by the server, the value of SPFILE is internally set by the server.

The SPFILE resides in the `ORACLE_HOME/dbs` directory; however, users can place it anywhere on their machine as long as it is specified in an initialization parameter file.

See Also: *Oracle Database Administrator's Guide* for more information about creating the server parameter file

SQL_TRACE

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Range of values	true false

SQL_TRACE enables or disables the SQL trace facility. Setting this parameter to true provides information on tuning that you can use to improve performance.

Caution: Using this initialization parameter to enable the SQL trace facility for the entire instance can have a severe performance impact. Enable the facility for specific sessions using the `ALTER SESSION` statement. If you must enable the facility on an entire production environment, then you can minimize performance impact by:

- Maintaining at least 25% idle CPU capacity
 - Maintaining adequate disk space for the `USER_DUMP_DEST` location
 - Striping disk space over sufficient disks
-

See Also: *Oracle Database Performance Tuning Guide* for more information about performance diagnostic tools

Note: The `SQL_TRACE` parameter is deprecated. Oracle recommends that you use the `DBMS_MONITOR` and `DBMS_SESSION` packages instead. `SQL_TRACE` is retained for backward compatibility only.

SQL92_SECURITY

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Range of values	true false

The SQL standard specifies that security administrators should be able to require that users have `SELECT` privilege on a table when executing an `UPDATE` or `DELETE` statement that references table column values in a `WHERE` or `SET` clause. `SQL92_SECURITY` specifies whether users must have been granted the `SELECT` object privilege in order to execute such `UPDATE` or `DELETE` statements.

Values:

- true

The user must have `SELECT` privilege on a column in order to reference it in the `WHERE` clause of a `DELETE` or `UPDATE` statement, on the right hand side of an assignment in the `SET` clause of an `UPDATE` statement.

- false

A user with `DELETE` privilege on the target table of a `DELETE` statement may reference any column of that target table in the `WHERE` clause. A user with `UPDATE` privilege on the target table of an `UPDATE` statement may reference any column of that target in the `WHERE` clause or on the right hand side of any assignment in the `SET` clause of the `UPDATE` statement.

SQLTUNE_CATEGORY

Property	Description
Parameter type	String
Syntax	SQLTUNE_CATEGORY = <i>category_name</i>
Default value	DEFAULT
Modifiable	ALTER SESSION, ALTER SYSTEM

SQLTUNE_CATEGORY specifies the category name for use by sessions to qualify the lookup of SQL profiles during SQL compilation.

See Also: *Oracle Database PL/SQL Packages and Types Reference* for information on the DBMS_SQLTUNE package

STANDBY_ARCHIVE_DEST

Property	Description
Parameter type	String
Syntax	STANDBY_ARCHIVE_DEST = <i>filespec</i>
Default value	Operating system-specific
Modifiable	ALTER SYSTEM
Range of values	A valid path or device name other than RAW

Note: The STANDBY_ARCHIVE_DEST parameter is deprecated. It is retained for backward compatibility only.

STANDBY_ARCHIVE_DEST can be used to specify where archived logs received from a primary database are stored on a standby database. It is no longer necessary to set this parameter, because an appropriate location is automatically chosen.

See Also: *Oracle Data Guard Concepts and Administration* for more information

STANDBY_FILE_MANAGEMENT

Property	Description
Parameter type	String
Syntax	STANDBY_FILE_MANAGEMENT = { MANUAL AUTO }
Default value	MANUAL
Modifiable	ALTER SYSTEM

STANDBY_FILE_MANAGEMENT enables or disables automatic standby file management. When automatic standby file management is enabled, operating system file additions and deletions on the primary database are replicated on the standby

database. `STANDBY_FILE_MANAGEMENT` is only applicable to physical standby databases.

Values:

- `MANUAL`
disables automatic standby file management
- `AUTO`
enables automatic standby file management

Setting `STANDBY_FILE_MANAGEMENT` to `AUTO` causes Oracle to automatically create files on the standby database and, in some cases, overwrite existing files. Care must be taken when setting `STANDBY_FILE_MANAGEMENT` and `DB_FILE_NAME_CONVERT` so that existing standby files will not be accidentally overwritten.

If the standby database is on the same system as the primary database, then ensure that the primary and standby systems do not point to the same files.

See Also: *Oracle Data Guard Concepts and Administration* for more information about setting this parameter

STAR_TRANSFORMATION_ENABLED

Property	Description
Parameter type	String
Syntax	<code>STAR_TRANSFORMATION_ENABLED = { FALSE TRUE TEMP_DISABLE }</code>
Default value	<code>FALSE</code>
Modifiable	<code>ALTER SESSION, ALTER SYSTEM</code>
Basic	Yes

`STAR_TRANSFORMATION_ENABLED` determines whether a cost-based query transformation will be applied to star queries.

Values:

- `FALSE`
The transformation will not be applied.
- `TRUE`
The optimizer will consider performing a cost-based query transformation on the star query.
- `TEMP_DISABLE`
The optimizer will consider performing a cost-based query transformation on the star query but will not use temporary tables in the star transformation.

See Also:

- *Oracle Database Concepts* for information on star queries
- *Oracle Database Performance Tuning Guide* for information on enabling star query

STATISTICS_LEVEL

Property	Description
Parameter type	String
Syntax	STATISTICS_LEVEL = { ALL TYPICAL BASIC }
Default value	TYPICAL
Modifiable	ALTER SESSION, ALTER SYSTEM

STATISTICS_LEVEL specifies the level of collection for database and operating system statistics. The Oracle Database collects these statistics for a variety of purposes, including making self-management decisions.

The default setting of TYPICAL ensures collection of all major statistics required for database self-management functionality and provides best overall performance. The default value should be adequate for most environments.

When the STATISTICS_LEVEL parameter is set to ALL, additional statistics are added to the set of statistics collected with the TYPICAL setting. The additional statistics are timed OS statistics and plan execution statistics.

Setting the STATISTICS_LEVEL parameter to BASIC disables the collection of many of the important statistics required by Oracle Database features and functionality, including:

- Automatic Workload Repository (AWR) Snapshots
- Automatic Database Diagnostic Monitor (ADDM)
- All server-generated alerts
- Automatic SGA Memory Management
- Automatic optimizer statistics collection
- Object level statistics
- End to End Application Tracing (V\$CLIENT_STATS)
- Database time distribution statistics (V\$SESS_TIME_MODEL and V\$SYS_TIME_MODEL)
- Service level statistics
- Buffer cache advisory
- MTTR advisory
- Shared pool sizing advisory
- Segment level statistics
- PGA Target advisory
- Timed statistics
- Monitoring of statistics

Note: Oracle strongly recommends that you do not disable these important features and functionality.

When the `STATISTICS_LEVEL` parameter is modified by `ALTER SYSTEM`, all advisories or statistics are dynamically turned on or off, depending on the new value of `STATISTICS_LEVEL`. When modified by `ALTER SESSION`, the following advisories or statistics are turned on or off in the local session only. Their system-wide state is not changed:

- Timed statistics
- Timed OS statistics
- Plan execution statistics

The `V$STATISTICS_LEVEL` view displays information about the status of the statistics or advisories controlled by the `STATISTICS_LEVEL` parameter. See ["V\\$STATISTICS_LEVEL"](#) on page 9-63.

STREAMS_POOL_SIZE

Property	Description
Parameter type	Big integer
Syntax	<code>STREAMS_POOL_SIZE = integer [K M G]</code>
Default value	0
Modifiable	<code>ALTER SYSTEM</code>
Range of values	Minimum: 0 (values greater than zero are rounded up to the nearest granule size) Maximum: operating system-dependent

Oracle's Automatic Shared Memory Management feature manages the size of the Streams pool when the `SGA_TARGET` initialization parameter is set to a nonzero value. If the `STREAMS_POOL_SIZE` initialization parameter also is set to a nonzero value, then Automatic Shared Memory Management uses this value as a minimum for the Streams pool.

If the `STREAMS_POOL_SIZE` initialization parameter is set to a nonzero value, and the `SGA_TARGET` parameter is set to 0 (zero), then the Streams pool size is the value specified by the `STREAMS_POOL_SIZE` parameter, in bytes.

If both the `STREAMS_POOL_SIZE` and the `SGA_TARGET` initialization parameters are set to 0 (zero), then, by default, the first use of Streams in a database transfers an amount of memory equal to 10% of the shared pool from the buffer cache to the Streams pool.

See Also: *Oracle Streams Replication Administrator's Guide*

TAPE_ASYNCH_IO

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	No
Range of values	true false

`TAPE_ASYNC_IO` controls whether I/O to sequential devices (for example, backup or restore of Oracle data to or from tape) is asynchronous—that is, whether parallel server processes can overlap I/O requests with CPU processing during table scans. If your platform supports asynchronous I/O to sequential devices, Oracle recommends that you leave this parameter set to its default. However, if the asynchronous I/O implementation is not stable, you can set `TAPE_ASYNC_IO` to `false` to disable asynchronous I/O. If your platform does not support asynchronous I/O to sequential devices, this parameter has no effect.

See Also: *Oracle Database Performance Tuning Guide* for more information on asynchronous I/O and on setting this parameter

THREAD

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No
Range of values	0 to the maximum number of enabled threads
Oracle RAC	If specified, multiple instances must have different values.

`THREAD` has been superseded by the `INSTANCE_NAME` and `INSTANCE_NUMBER` parameters, and will be made obsolete in a future release of the Oracle Database.

See Also: ["INSTANCE_NAME"](#) on page 1-76 and ["INSTANCE_NUMBER"](#) on page 1-77

TIMED_OS_STATISTICS

Property	Description
Parameter type	Integer
Default value	If <code>STATISTICS_LEVEL</code> is set to <code>ALL</code> , then 5 If <code>STATISTICS_LEVEL</code> is set to <code>BASIC</code> or <code>TYPICAL</code> , then 0
Modifiable	<code>ALTER SESSION</code> , <code>ALTER SYSTEM</code>
Range of values	Unlimited

`TIMED_OS_STATISTICS` specifies (in seconds) the interval at which Oracle collects operating system statistics when a request is made from the client to the server or when a request completes.

- On dedicated servers, Oracle collects operating system statistics at user logon and after each subsequent client invocation through the OCI into the Oracle server as a remote procedure call message.
- On shared servers, Oracle collects statistics when client calls to Oracle are processed.

A value of zero specifies that operating system statistics are not gathered. To collect statistics, set a value meaningful for your application and site needs.

Note: Gathering operating system statistics is very expensive. Oracle recommends that you set this parameter in an `ALTER SYSTEM` statement rather than in the initialization parameter file, and that you reset the value to zero as soon as the needed statistics have been gathered.

TIMED_STATISTICS

Property	Description
Parameter type	Boolean
Default value	If <code>STATISTICS_LEVEL</code> is set to <code>TYPICAL</code> or <code>ALL</code> , then <code>true</code> If <code>STATISTICS_LEVEL</code> is set to <code>BASIC</code> , then <code>false</code>
Modifiable	<code>ALTER SESSION</code> , <code>ALTER SYSTEM</code>
Range of values	<code>true</code> <code>false</code>

`TIMED_STATISTICS` specifies whether or not statistics related to time are collected.

Values:

- `true`
The statistics are collected and stored in trace files or displayed in the `V$SESSTATS` and `V$SYSSTATS` dynamic performance views.
- `false`
The value of all time-related statistics is set to zero. This setting lets Oracle avoid the overhead of requesting the time from the operating system.

Starting with release 11.1.0.7.0, the value of the `TIMED_STATISTICS` parameter cannot be set to `false` if the value of `STATISTICS_LEVEL` is set to `TYPICAL` or `ALL`.

On some systems with very fast timer access, Oracle might enable timing even if this parameter is set to `false`. On these systems, setting the parameter to `true` can sometimes produce more accurate statistics for long-running operations.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter and on performance diagnostic tools in general
- [Appendix E, "Statistics Descriptions"](#) indicates which statistics depend on the setting of this parameter.

TRACE_ENABLED

Property	Description
Parameter type	Boolean
Default value	<code>true</code>
Modifiable	<code>ALTER SYSTEM</code>
Range of values	<code>true</code> <code>false</code>

Property	Description
Oracle RAC	The default value is <code>TRUE</code> . Oracle recommends that multiple instances have the same value.

`TRACE_ENABLED` controls tracing of the execution history, or code path, of Oracle. Oracle Support Services uses this information for debugging.

When `TRACE_ENABLED` is set to `true`, Oracle records information in specific files when errors occur.

Oracle records this information for all instances, even if only one instance terminates. This allows Oracle to retain diagnostics for an entire cluster.

Although the overhead incurred from this processing is not excessive, you can improve performance by setting `TRACE_ENABLED` to `false`. You might do this, for example, to meet high-end benchmark requirements. However, if you leave this parameter set to `false`, you may lose valuable diagnostic information. Therefore, always set `TRACE_ENABLED` to `true` to trace system problems and to reduce diagnostic efforts in the event of unexplained instance failures.

TRACEFILE_IDENTIFIER

Property	Description
Parameter type	String
Syntax	<code>TRACEFILE_IDENTIFIER = "traceid"</code>
Default value	There is no default value.
Modifiable	<code>ALTER SESSION</code>
Range of values	Any characters that can occur as part of a file name on the customer platform

`TRACEFILE_IDENTIFIER` specifies a custom identifier that becomes part of the Oracle Trace file name. Such a custom identifier is used to identify a trace file simply from its name and without having to open it or view its contents.

Each time this parameter is dynamically modified, the next trace dump will be written to a trace file which has the new parameter value embedded in its name. Trace file continuity information is automatically added to both the old and new trace files to indicate that these trace files belong to the same process.

This parameter can only be used to change the name of the foreground process' trace file; the background processes continue to have their trace files named in the regular format. For foreground processes, the `TRACEID` column of the `V$PROCESS` view contains the current value of the `TRACEFILE_IDENTIFIER` parameter. When this parameter value is set, the trace file name has the following format:

sid_ora_pid_traceid.trc

In this example, *sid* is the Oracle instance ID, *pid* is the process ID, and *traceid* is the value of the `TRACEFILE_IDENTIFIER` parameter.

See Also: This parameter is not supported on all operating systems. See your operating system-specific Oracle documentation for more information.

TRANSACTIONS

Property	Description
Parameter type	Integer
Default value	Derived: (1.1 * SESSIONS)
Modifiable	No
Range of values	4 to 2^{32}
Oracle RAC	Multiple instances can have different values.

TRANSACTIONS specifies how many rollback segments to online when UNDO_MANAGEMENT = MANUAL. The maximum number of concurrent transactions is now restricted by undo tablespace size (UNDO_MANAGEMENT = AUTO) or the number of online rollback segments (UNDO_MANAGEMENT = MANUAL).

See Also:

- *Oracle Database Administrator's Guide* for information on setting this parameter
- *Oracle Real Application Clusters Administration and Deployment Guide* for the relationship of this parameter to the number of rollback segments

TRANSACTIONS_PER_ROLLBACK_SEGMENT

Property	Description
Parameter type	Integer
Default value	5
Modifiable	No
Range of values	1 to operating system-dependent
Oracle RAC	Multiple instances can have different values.

TRANSACTIONS_PER_ROLLBACK_SEGMENT specifies the number of concurrent transactions you expect each rollback segment to have to handle. The minimum number of rollback segments acquired at startup is TRANSACTIONS divided by the value for this parameter. For example, if TRANSACTIONS is 101 and this parameter is 10, then the minimum number of rollback segments acquired would be the ratio 101/10, rounded up to 11.

You can acquire more rollback segments by naming them in the parameter ROLLBACK_SEGMENTS.

See Also:

- *Oracle Database Administrator's Guide* for information on setting this parameter.
- *Oracle Real Application Clusters Administration and Deployment Guide* for how Oracle acquires rollback segments.
- Your operating system-specific Oracle documentation for the range of values for this parameter.

UNDO_MANAGEMENT

Property	Description
Parameter type	String
Syntax	UNDO_MANAGEMENT = { MANUAL AUTO }
Default value	AUTO
Modifiable	No
Basic	No
Oracle RAC	Multiple instances must have the same value.

UNDO_MANAGEMENT specifies which undo space management mode the system should use. When set to AUTO, the instance starts in automatic undo management mode. In manual undo management mode, undo space is allocated externally as rollback segments.

UNDO_RETENTION

Property	Description
Parameter type	Integer
Default value	900
Modifiable	ALTER SYSTEM
Range of values	0 to $2^{31} - 1$
Oracle RAC	Oracle recommends that multiple instances have the same value.

UNDO_RETENTION specifies (in seconds) the low threshold value of undo retention. For AUTOEXTEND undo tablespaces, the system retains undo for at least the time specified in this parameter, and automatically tunes the undo retention period to satisfy the undo requirements of the queries. For fixed-size undo tablespaces, the system automatically tunes for the maximum possible undo retention period, based on undo tablespace size and usage history, and ignores UNDO_RETENTION unless retention guarantee is enabled.

The setting of this parameter should account for any flashback requirements of the system. Automatic tuning of undo retention is not supported for LOBs. The RETENTION value for LOB columns is set to the value of the UNDO_RETENTION parameter.

The UNDO_RETENTION parameter can only be honored if the current undo tablespace has enough space. If an active transaction requires undo space and the undo tablespace does not have available space, then the system starts reusing unexpired undo space. This action can potentially cause some queries to fail with a "snapshot too old" message.

The amount of time for which undo is retained for the Oracle Database for the current undo tablespace can be obtained by querying the TUNED_UNDORETENTION column of the V\$UNDOSTAT dynamic performance view.

See Also:

- *Oracle Database SQL Language Reference* for more information about creating undo tablespaces
- *Oracle Database Administrator's Guide* for more information about managing undo data

UNDO_TABLESPACE

Property	Description
Parameter type	String
Syntax	UNDO_TABLESPACE = <i>undoname</i>
Default value	The first available undo tablespace in the database.
Modifiable	ALTER SYSTEM
Range of values	Legal name of an existing undo tablespace
Basic	Yes
Oracle RAC	Each instance must have a unique value for this parameter, when it is set.

UNDO_TABLESPACE specifies the undo tablespace to be used when an instance starts up. If this parameter is specified when the instance is in manual undo management mode, then an error will occur and startup will fail.

If the UNDO_TABLESPACE parameter is omitted, the first available undo tablespace in the database is chosen. If no undo tablespace is available, the instance will start without an undo tablespace. In such cases, user transactions will be executed using the SYSTEM rollback segment. You should avoid running in this mode under normal circumstances.

You can replace an undo tablespace with another undo tablespace while the instance is running.

See Also: *Oracle Database SQL Language Reference.*

USE_INDIRECT_DATA_BUFFERS

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No

Property	Description
Range of values	true false

USE_INDIRECT_DATA_BUFFERS controls how the system global area (SGA) uses memory. It enables or disables the use of the extended buffer cache mechanism for 32-bit platforms that can support more than 4 GB of physical memory. On platforms that do not support this much physical memory, this parameter is ignored.

See Also:

- ["LOCK_SGA"](#) on page 1-86, ["SHARED_MEMORY_ADDRESS"](#) on page 1-160, and ["HI_SHARED_MEMORY_ADDRESS"](#) on page 1-74, which are other parameters that control how the SGA uses memory.
- *Oracle Database Concepts* for more information about the SGA.

USER_DUMP_DEST

Property	Description
Parameter type	String
Syntax	USER_DUMP_DEST = { <i>pathname</i> <i>directory</i> }
Default value	Operating system-dependent
Modifiable	ALTER SYSTEM
Range of values	Any valid local path, directory, or disk

USER_DUMP_DEST specifies the pathname for a directory where the server will write debugging trace files on behalf of a user process.

For example, this directory might be set as follows:

- On MS-DOS: C:\ORACLE\UTRC
- On UNIX: /oracle/utrc
- On VMS: DISK\$UR3 : [ORACLE.UTRC]

Note: This parameter is ignored by the new diagnosability infrastructure introduced in Oracle Database 11g Release 1, which places trace and core files in a location controlled by the DIAGNOSTIC_DEST initialization parameter.

See Also:

- *Oracle Database Performance Tuning Guide* for more information about the use of trace files
- Your operating system-specific Oracle documentation for the range of values

UTL_FILE_DIR

Property	Description
Parameter type	String
Syntax	UTL_FILE_DIR = <i>pathname</i>
Default value	There is no default value.
Modifiable	No
Range of values	Any valid directory path

UTL_FILE_DIR lets you specify one or more directories that Oracle should use for PL/SQL file I/O. If you are specifying multiple directories, you must repeat the UTL_FILE_DIR parameter for each directory on separate lines of the initialization parameter file.

All users can read or write to all files specified by this parameter. Therefore all PL/SQL users must be trusted with the information in the directories specified by this parameter.

Note: If you list multiple values, all entries of this parameter must be on contiguous lines of the parameter file. If you separate them with other parameters, Oracle will read only the last (contiguous) lines.

WORKAREA_SIZE_POLICY

Property	Description
Parameter type	String
Syntax	WORKAREA_SIZE_POLICY = { AUTO MANUAL }
Default value	AUTO
Modifiable	ALTER SESSION, ALTER SYSTEM

WORKAREA_SIZE_POLICY specifies the policy for sizing work areas. This parameter controls the mode in which working areas are tuned.

Values:

■ AUTO

Work areas used by memory-intensive operators are sized automatically, based on the PGA memory used by the system, the target PGA memory set in PGA_AGGREGATE_TARGET, and the requirement of each individual operator.

■ MANUAL

The sizing of work areas is manual and based on the values of the *_AREA_SIZE parameter corresponding to the operation (for example, a sort uses SORT_AREA_SIZE). Specifying MANUAL may result in sub-optimal performance and poor PGA memory utilization.

XML_DB_EVENTS

Property	Description
Parameter type	String
Syntax	<code>XML_DB_EVENTS = { enable disable }</code>
Default value	enable
Modifiable	ALTER SESSION, ALTER SYSTEM
Basic	No

`XML_DB_EVENTS` enables or disables XML DB Events.

Changing this parameter through an `ALTER SESSION` statement affects only the current session. Only users with the `XDBADMIN` role are allowed to change this parameter in a session.

Changing this parameter through an `ALTER SYSTEM` statement will make a system-wide change of this parameter; however, the change is only registered by new sessions started after the change. Currently running sessions need to be restarted to pick up the new change. Users must have the `ALTER SYSTEM` privilege to make a system-wide change.

Part II

Static Data Dictionary Views

This part describes data dictionary tables and views. These tables and views are called **static**, because they change only when a change is made to the data dictionary (for example, when a new table is created or when a user is granted new privileges). This part contains the following chapters:

- Chapter 2, "Static Data Dictionary Views: ALL_ALL_TABLES to ALL_OUTLINES"
- Chapter 3, "Static Data Dictionary Views: ALL_PART_COL_STATISTICS to DATABASE_PROPERTIES"
- Chapter 4, "Static Data Dictionary Views: DBA_2PC_NEIGHBORS to DBA_HIST_JAVA_POOL_ADVICE"
- Chapter 5, "Static Data Dictionary Views: DBA_HIST_LATCH to DBA_STORED_SETTINGS"
- Chapter 6, "Static Data Dictionary Views: DBA_STREAMS_ADD_COLUMN to XS_SESSION_ROLES"

Note: Oracle also maintains tables that monitor ongoing database activity. These **dynamic performance tables** are described in Part III, "Dynamic Performance Views".

Static Data Dictionary Views: ALL_ALL_TABLES to ALL_OUTLINES

This chapter describes the first set (in alphabetical order) of static data dictionary views. The remaining static data dictionary views appear in alphabetical order in [Chapter 3](#) through [Chapter 6](#).

This chapter contains the following topics:

- [About Static Data Dictionary Views](#)
- [Static Data Dictionary View Descriptions](#)

About Static Data Dictionary Views

Data dictionary tables are not directly accessible, but you can access information in them through data dictionary views. To list the data dictionary views available to you, query the view `DICTIONARY`.

Many data dictionary tables have three corresponding views:

- An `ALL_` view displays all the information accessible to the current user, including information from the current user's schema as well as information from objects in other schemas, if the current user has access to those objects by way of grants of privileges or roles.
- A `DBA_` view displays all relevant information in the entire database. `DBA_` views are intended only for administrators. They can be accessed only by users with the `SELECT ANY TABLE` privilege. This privilege is assigned to the `DBA` role when the system is initially installed.
- A `USER_` view displays all the information from the schema of the current user. No special privileges are required to query these views.

The columns of the `ALL_`, `DBA_`, and `USER_` views corresponding to a single data dictionary table are usually nearly identical. Therefore, these views are described in full only once in this chapter, at their first occurrence alphabetically, and are listed without full descriptions at their other occurrences.

Oracle Replication Views

A number of data dictionary views are relevant only if you are using Oracle Replication. [Table 2-1](#) lists these views.

Table 2–1 Oracle Replication Data Dictionary Views

ALL_ Views	DBA_ Views	USER_ Views
ALL_REPCAT	DBA_REPCAT	USER_REPCAT
	DBA_REPCAT_EXCEPTIONS	
ALL_REPCAT_REFRESH_TEMPLATES	DBA_REPCAT_REFRESH_TEMPLATES	USER_REPCAT_REFRESH_TEMPLATES
ALL_REPCAT_TEMPLATE_OBJECTS	DBA_REPCAT_TEMPLATE_OBJECTS	USER_REPCAT_TEMPLATE_OBJECTS
ALL_REPCAT_TEMPLATE_PARS	DBA_REPCAT_TEMPLATE_PARS	USER_REPCAT_TEMPLATE_PARS
ALL_REPCAT_TEMPLATE_SITES	DBA_REPCAT_TEMPLATE_SITES	USER_REPCAT_TEMPLATE_SITES
ALL_REPCAT_USER_AUTHORIZATIONS	DBA_REPCAT_USER_AUTHORIZATIONS	USER_REPCAT_USER_AUTHORIZATIONS
ALL_REPCAT_USER_PARM_VALUES	DBA_REPCAT_USER_PARM_VALUES	USER_REPCAT_USER_PARM_VALUES
ALL_REPCATLOG	DBA_REPCATLOG	USER_REPCATLOG
ALL_REPCOLUMN	DBA_REPCOLUMN	USER_REPCOLUMN
ALL_REPCOLUMN_GROUP	DBA_REPCOLUMN_GROUP	USER_REPCOLUMN_GROUP
ALL_REPCONFLICT	DBA_REPCONFLICT	USER_REPCONFLICT
ALL_REPDDL	DBA_REPDDL	USER_REPDDL
	DBA_REPEXTENSIONS	
ALL_REPFLAVOR_COLUMNS	DBA_REPFLAVOR_COLUMNS	USER_REPFLAVOR_COLUMNS
ALL_REPFLAVOR_OBJECTS	DBA_REPFLAVOR_OBJECTS	USER_REPFLAVOR_OBJECTS
ALL_REPFLAVORS	DBA_REPFLAVORS	USER_REPFLAVORS
ALL_REPGENERATED	DBA_REPGENERATED	USER_REPGENERATED
ALL_REPGENOBJECTS	DBA_REPGENOBJECTS	USER_REPGENOBJECTS
ALL_REPGROUP	DBA_REPGROUP	USER_REPGROUP
ALL_REPGROUP_PRIVILEGES	DBA_REPGROUP_PRIVILEGES	USER_REPGROUP_PRIVILEGES
ALL_REPGROUPED_COLUMN	DBA_REPGROUPED_COLUMN	USER_REPGROUPED_COLUMN
ALL_REPKEY_COLUMNS	DBA_REPKEY_COLUMNS	USER_REPKEY_COLUMNS
ALL_REPOBJECT	DBA_REPOBJECT	USER_REPOBJECT
ALL_REPPARAMETER_COLUMN	DBA_REPPARAMETER_COLUMN	USER_REPPARAMETER_COLUMN
ALL_REPPRIORITY	DBA_REPPRIORITY	USER_REPPRIORITY
ALL_REPPRIORITY_GROUP	DBA_REPPRIORITY_GROUP	USER_REPPRIORITY_GROUP
ALL_REPPROP	DBA_REPPROP	USER_REPPROP
ALL_REPRESOL_STATS_CONTROL	DBA_REPRESOL_STATS_CONTROL	USER_REPRESOL_STATS_CONTROL
ALL_REPRESOLUTION	DBA_REPRESOLUTION	USER_REPRESOLUTION
ALL_REPRESOLUTION_METHOD	DBA_REPRESOLUTION_METHOD	USER_REPRESOLUTION_METHOD
ALL_REPRESOLUTION_STATISTICS	DBA_REPRESOLUTION_STATISTICS	USER_REPRESOLUTION_STATISTICS
ALL_REPSHEMA	DBA_REPSHEMA	USER_REPSHEMA
ALL_REPSITES	DBA_REPSITES	USER_REPSITES
	DBA_REPSITES_NEW	

The following are additional Oracle Replication data dictionary views:

DEFCALL
 DEFCALLDEST
 DEFDEFAULTDEST
 DEFERRCOUNT
 DEFERROR
 DEFLOB

DEFPROPAGATOR
 DEFSCHEDULE
 DEFTRAN
 DEFTRANDEST

See Also: *Oracle Database Advanced Replication Management API Reference* for information about these views

Oracle Workspace Manager Views

A number of data dictionary views are relevant only if you are using Oracle Workspace Manager. [Table 2–2](#) lists these views.

Table 2–2 Oracle Workspace Manager Data Dictionary Views

ALL_ Views	DBA_ Views	USER_ Views
ALL_MP_GRAPH_WORKSPACES		USER_MP_GRAPH_WORKSPACES
ALL_MP_PARENT_WORKSPACES		USER_MP_PARENT_WORKSPACES
ALL_REMOVED_WORKSPACES		USER_REMOVED_WORKSPACES
ALL_VERSION_HVIEW		
ALL_WM_CONS_COLUMNS		USER_WM_CONS_COLUMNS
ALL_WM_CONSTRAINTS		USER_WM_CONSTRAINTS
ALL_WM_IND_COLUMNS		USER_WM_IND_COLUMNS
ALL_WM_IND_EXPRESSIONS		USER_WM_IND_EXPRESSIONS
ALL_WM_LOCKED_TABLES		USER_WM_LOCKED_TABLES
ALL_WM_MODIFIED_TABLES		USER_WM_MODIFIED_TABLES
		USER_WM_PRIVS
ALL_WM_RIC_INFO		USER_WM_RIC_INFO
	DBA_WM_SYS_PRIVS	
ALL_WM_TAB_TRIGGERS		USER_WM_TAB_TRIGGERS
ALL_WM_VERSIONED_TABLES		USER_WM_VERSIONED_TABLES
ALL_WM_VT_ERRORS	DBA_WM_VT_ERRORS	USER_WM_VT_ERRORS
ALL_WORKSPACE_PRIVS		USER_WORKSPACE_PRIVS
ALL_WORKSPACE_SAVEPOINTS		USER_WORKSPACE_SAVEPOINTS
	DBA_WORKSPACE_SESSIONS	
ALL_WORKSPACES	DBA_WORKSPACES	USER_WORKSPACES

The following are additional Oracle Workspace Manager data dictionary views:

ROLE_WM_PRIVS
 WM_COMPRESS_BATCH_SIZES
 WM_COMPRESSIBLE_TABLES
 WM_EVENTS_INFO
 WM_INSTALLATION
 WM_REPLICATION_INFO

See Also: *Oracle Database Workspace Manager Developer's Guide* for information about these views

Recovery Catalog Views

The following data dictionary views are only available after you create an optional recovery catalog (which contains schemas containing information about backups) for use with Recovery Manager:

RC_ARCHIVED_LOG
RC_BACKUP_ARCHIVELOG_DETAILS
RC_BACKUP_ARCHIVELOG_SUMMARY
RC_BACKUP_CONTROLFILE
RC_BACKUP_CONTROLFILE_DETAILS
RC_BACKUP_CONTROLFILE_SUMMARY
RC_BACKUP_COPY_DETAILS
RC_BACKUP_COPY_SUMMARY
RC_BACKUP_CORRUPTION
RC_BACKUP_DATAFILE
RC_BACKUP_DATAFILE_DETAILS
RC_BACKUP_DATAFILE_SUMMARY
RC_BACKUP_FILES
RC_BACKUP_PIECE
RC_BACKUP_PIECE_DETAILS
RC_BACKUP_REDOLOG
RC_BACKUP_SET
RC_BACKUP_SET_DETAILS
RC_BACKUP_SET_SUMMARY
RC_BACKUP_SPFILE
RC_BACKUP_SPFILE_DETAILS
RC_BACKUP_SPFILE_SUMMARY
RC_CHECKPOINT
RC_CONTROLFILE_COPY
RC_COPY_CORRUPTION
RC_DATABASE
RC_DATABASE_BLOCK_CORRUPTION
RC_DATABASE_INCARNATION
RC_DATAFILE
RC_DATAFILE_COPY
RC_LOG_HISTORY
RC_OFFLINE_RANGE
RC_PROXY_ARCHIVEDLOG
RC_PROXY_ARCHIVELOG_DETAILS
RC_PROXY_ARCHIVELOG_SUMMARY
RC_PROXY_CONTROLFILE
RC_PROXY_COPY_DETAILS
RC_PROXY_COPY_SUMMARY
RC_PROXY_DATAFILE
RC_REDO_LOG
RC_REDO_THREAD
RC_RESTORE_POINT
RC_RESYNC
RC_RMAN_BACKUP_JOB_DETAILS
RC_RMAN_BACKUP_SUBJOB_DETAILS
RC_RMAN_BACKUP_TYPE
RC_RMAN_CONFIGURATION
RC_RMAN_OUTPUT
RC_RMAN_STATUS
RC_SITE

RC_STORED_SCRIPT
 RC_STORED_SCRIPT_LINE
 RC_TABLESPACE
 RC_TEMPFILE
 RC_UNUSABLE_BACKUPFILE_DETAILS

See Also: *Oracle Database Backup and Recovery Reference* for information about these views

Static Data Dictionary View Descriptions

The remainder of this chapter describes the static data dictionary views in alphabetical order.

ALL_ALL_TABLES

ALL_ALL_TABLES describes the object tables and relational tables accessible to the current user.

Related Views

- DBA_ALL_TABLES describes all object tables and relational tables in the database.
- USER_ALL_TABLES describes the object tables and relational tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the table; NULL for partitioned, temporary, and index-organized tables
CLUSTER_NAME	VARCHAR2 (30)		Name of the cluster, if any, to which the table belongs
IOT_NAME	VARCHAR2 (30)		Name of the index-organized table, if any, to which the overflow or mapping table entry belongs. If the IOT_TYPE column is not NULL, then this column contains the base table name.
STATUS	VARCHAR2 (8)		If a previous DROP TABLE operation failed, indicates whether the table is unusable (UNUSABLE) or valid (VALID)
PCT_FREE	NUMBER		Minimum percentage of free space in a block; NULL for partitioned tables
PCT_USED	NUMBER		Minimum percentage of used space in a block; NULL for partitioned tables
INI_TRANS	NUMBER		Initial number of transactions; NULL for partitioned tables
MAX_TRANS	NUMBER		Maximum number of transactions; NULL for partitioned tables
INITIAL_EXTENT	NUMBER		Size of the initial extent (in bytes); NULL for partitioned tables
NEXT_EXTENT	NUMBER		Size of secondary extents (in bytes); NULL for partitioned tables
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment; NULL for partitioned tables

Column	Datatype	NULL	Description
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment; NULL for partitioned tables
PCT_INCREASE	NUMBER		Percentage increase in extent size; NULL for partitioned tables
FREELISTS	NUMBER		Number of process freelists allocated to the segment; NULL for partitioned tables
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to the segment
LOGGING	VARCHAR2 (3)		Indicates whether or not changes to the table are logged: ■ YES ■ NO
BACKED_UP	VARCHAR2 (1)		Indicates whether the table has been backed up since the last modification (Y) or not (N)
NUM_ROWS	NUMBER		Number of rows in the table
BLOCKS	NUMBER		Number of used blocks in the table
EMPTY_BLOCKS	NUMBER		Number of empty (never used) blocks in the table
AVG_SPACE	NUMBER		Average available free space in the table
CHAIN_CNT	NUMBER		Number of rows in the table that are chained from one data block to another or that have migrated to a new block, requiring a link to preserve the old rowid. This column is updated only after you analyze the table.
AVG_ROW_LEN	NUMBER		Average row length, including row overhead
AVG_SPACE_FREELIST_BLOCKS	NUMBER		Average freespace of all blocks on a freelist
NUM_FREELIST_BLOCKS	NUMBER		Number of blocks on the freelist
DEGREE	VARCHAR2 (10)		Number of threads per instance for scanning the table, or DEFAULT
INSTANCES	VARCHAR2 (10)		Number of instances across which the table is to be scanned, or DEFAULT
CACHE	VARCHAR2 (5)		Indicates whether the table is to be cached in the buffer cache (Y) or not (N)
TABLE_LOCK	VARCHAR2 (8)		Indicates whether table locking is enabled (ENABLED) or disabled (DISABLED)
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the table
LAST_ANALYZED	DATE		Date on which the table was most recently analyzed
PARTITIONED	VARCHAR2 (3)		Indicates whether the table is partitioned (YES) or not (NO)
IOT_TYPE	VARCHAR2 (12)		If the table is an index-organized table, then IOT_TYPE is IOT, IOT_OVERFLOW, or IOT_MAPPING. If the table is not an index-organized table, then IOT_TYPE is NULL.
OBJECT_ID_TYPE	VARCHAR2 (16)		Indicates whether the object ID (OID) is USER-DEFINED or SYSTEM GENERATED
TABLE_TYPE_OWNER	VARCHAR2 (30)		If an object table, owner of the type from which the table is created
TABLE_TYPE	VARCHAR2 (30)		If an object table, type of the table
TEMPORARY	VARCHAR2 (1)		Indicates whether the table is temporary (Y) or not (N)
SECONDARY	VARCHAR2 (1)		Indicates whether the table is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge to contain the contents of a domain index (Y) or not (N)
NESTED	VARCHAR2 (3)		Indicates whether the table is a nested table (YES) or not (NO)

Column	Datatype	NULL	Description
BUFFER_POOL	VARCHAR2 (7)		Buffer pool to be used for table blocks: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for table blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for table blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
ROW_MOVEMENT	VARCHAR2 (8)		If a partitioned table, indicates whether row movement is enabled (ENABLED) or disabled (DISABLED)
GLOBAL_STATS	VARCHAR2 (3)		For partitioned tables, indicates whether statistics for the table as a whole (global statistics) are accurate (YES) or whether they were not collected and have to be estimated from statistics on underlying partitions and subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
DURATION	VARCHAR2 (15)		Indicates the duration of a temporary table: SYS\$SESSION - Rows are preserved for the duration of the session SYS\$TRANSACTION - Rows are deleted after COMMIT Null - Permanent table
SKIP_CORRUPT	VARCHAR2 (8)		Indicates whether Oracle Database ignores blocks marked corrupt during table and index scans (ENABLED) or raises an error (DISABLED). To enable this feature, run the DBMS_REPAIR.skip_corrupt_blocks procedure.
MONITORING	VARCHAR2 (3)		Indicates whether the table has the MONITORING attribute set (YES) or not (NO)
CLUSTER_OWNER	VARCHAR2 (30)		Owner of the cluster, if any, to which the table belongs
DEPENDENCIES	VARCHAR2 (8)		Indicates whether row-level dependency tracking is enabled (ENABLED) or disabled (DISABLED)
COMPRESSION	VARCHAR2 (8)		Indicates whether table compression is enabled (ENABLED) or not (DISABLED); NULL for partitioned tables
COMPRESS_FOR	VARCHAR2 (12)		Default compression for what kind of operations: ■ BASIC ■ OLTP ■ QUERY LOW¹ ■ QUERY HIGH¹ ■ ARCHIVE LOW¹ ■ ARCHIVE HIGH¹ ■ NULL

Column	Datatype	NULL	Description
DROPPED	VARCHAR2 (3)		Indicates whether the table has been dropped and is in the recycle bin (YES) or not (NO); NULL for partitioned tables
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the table segment has been created (YES) or not (NO)

¹ Hybrid columnar compression is a feature of Oracle Exadata. See Oracle Exadata Storage Server Software documentation for more information.

See Also:

- ["DBA_ALL_TABLES"](#) on page 4-33
- ["USER_ALL_TABLES"](#) on page 6-68

ALL_APPLY

ALL_APPLY displays information about the apply processes that dequeue messages from queues accessible to the current user.

Related View

DBA_APPLY displays information about all apply processes in the database.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2 (30)	NOT NULL	Name of the apply process
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue from which the apply process dequeues
QUEUE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the queue from which the apply process dequeues
APPLY_CAPTURED	VARCHAR2 (3)		Indicates whether the apply process applies captured messages (YES) or user-enqueued messages (NO)
RULE_SET_NAME	VARCHAR2 (30)		Name of the positive rule set used by the apply process for filtering
RULE_SET_OWNER	VARCHAR2 (30)		Owner of the positive rule set used by the apply process for filtering
APPLY_USER	VARCHAR2 (30)		User who is applying messages
APPLY_DATABASE_LINK	VARCHAR2 (128)		Database link to which changes are applied. If NULL, then changes are applied to the local database.
APPLY_TAG	RAW (2000)		Tag associated with redo log records that are generated when changes are made by the apply process
DDL_HANDLER	VARCHAR2 (98)		Name of the user-specified DDL handler, which handles DDL logical change records
PRECOMMIT_HANDLER	VARCHAR2 (98)		Name of the user-specified pre-commit handler
MESSAGE_HANDLER	VARCHAR2 (98)		Name of the user-specified procedure that handles dequeued messages other than logical change records
STATUS	VARCHAR2 (8)		Status of the apply process: ■ DISABLED ■ ENABLED ■ ABORTED

Column	Datatype	NULL	Description
MAX_APPLIED_MESSAGE_NUMBER	NUMBER		System change number (SCN) corresponding to the apply process high watermark for the last time the apply process was stopped using the DBMS_APPLY_ADM.STOP_APPLY procedure with the <code>force</code> parameter set to <code>false</code> . The apply process high watermark is the SCN beyond which no messages have been applied.
NEGATIVE_RULE_SET_NAME	VARCHAR2 (30)		Name of the negative rule set used by the apply process for filtering
NEGATIVE_RULE_SET_OWNER	VARCHAR2 (30)		Owner of the negative rule set used by the apply process for filtering
STATUS_CHANGE_TIME	DATE		Time that the STATUS of the apply process was changed
ERROR_NUMBER	NUMBER		Error number if the apply process was aborted
ERROR_MESSAGE	VARCHAR2 (4000)		Error message if the apply process was aborted
MESSAGE_DELIVERY_MODE	VARCHAR2 (10)		Reserved for internal use
PURPOSE ¹	VARCHAR2 (19)		Purpose of the apply process: - Streams - An apply process in an Oracle Streams configuration - XStream Streams - An apply process in an Oracle Streams configuration with XStream capabilities enabled by the DBMS_XSTREAM_ADM.ENABLE_GG_XSTREAM_FOR_STREAMS procedure - XStream Out - An XStream outbound server in an XStream Out configuration - XStream In - An XStream inbound server in an XStream In configuration - AUDIT VAULT - An apply process in an audit vault configuration - CHANGE DATA CAPTURE - An apply process in a change data capture configuration

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also: ["DBA_APPLY"](#) on page 4-33

ALL_APPLY_CHANGE_HANDLERS

ALL_APPLY_CHANGE_HANDLERS displays information about the change handlers on the tables accessible to the current user.

Related View

DBA_APPLY_CHANGE_HANDLERS displays information about the change handlers on all tables in the database.

Column	Datatype	NULL	Description
CHANGE_TABLE_OWNER	VARCHAR2 (30)		Owner of the change table
CHANGE_TABLE_NAME	VARCHAR2 (30)		Name of the change table
SOURCE_TABLE_OWNER	VARCHAR2 (30)		Owner of the source table
SOURCE_TABLE_NAME	VARCHAR2 (30)		Name of the source table
HANDLER_NAME	VARCHAR2 (30)		Name of the statement-based change handler
CAPTURE_VALUES	VARCHAR2 (3)		Indicates whether to capture the old (OLD), new (NEW), or both (*) values
APPLY_NAME	VARCHAR2 (30)		Name of the apply process

Column	Datatype	NULL	Description
OPERATION_NAME	VARCHAR2 (10)		Name of the DML operation to which the DML handler is set: ▪ DEFAULT ▪ INSERT ▪ UPDATE ▪ DELETE ▪ LOB_UPDATE
CREATION_TIME	TIMESTAMP (6)		Change handler creation time
MODIFICATION_TIME	TIMESTAMP (6)		Change handler modification time

See Also: ["DBA_APPLY_CHANGE_HANDLERS"](#) on page 4-33

ALL_APPLY_CONFLICT_COLUMNS

ALL_APPLY_CONFLICT_COLUMNS displays information about the conflict handlers on the tables accessible to the current user.

Related View

DBA_APPLY_CONFLICT_COLUMNS displays information about the conflict handlers on all tables in the database.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)		Owner of the object on which the update conflict handler is defined
OBJECT_NAME	VARCHAR2 (30)		Name of the object on which the update conflict handler is defined
METHOD_NAME	VARCHAR2 (92)		Name of the update conflict handler used to resolve conflicts
RESOLUTION_COLUMN	VARCHAR2 (4000)		Name of the column used to resolve conflicts
COLUMN_NAME	VARCHAR2 (30)		Name of a column in the column list for the update conflict handler
APPLY_DATABASE_LINK	VARCHAR2 (128)		Database link to which changes are applied. If null, then changes are applied to the local database.

See Also: ["DBA_APPLY_CONFLICT_COLUMNS"](#) on page 4-33

ALL_APPLY_DML_HANDLERS

ALL_APPLY_DML_HANDLERS displays information about the DML handlers on the tables accessible to the current user.

Related View

DBA_APPLY_DML_HANDLERS displays information about the DML handlers on all tables in the database.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object on which the DML handler is specified
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object on which the DML handler is specified

Column	Datatype	NULL	Description
OPERATION_NAME	VARCHAR2 (13)		Name of the DML operation for which the DML handler is used: ■ DEFAULT ■ INSERT ■ UPDATE ■ DELETE ■ LOB_UPDATE ■ ASSEMBLE_LOBS
USER_PROCEDURE	VARCHAR2 (98)		Name of the user-specified DML handler, which handles row logical change records that contain the DML operation in the OPERATION_NAME column on the object
ERROR_HANDLER	VARCHAR2 (1)		Indicates whether the DML handler handles only the relevant row logical change records that result in apply errors (Y) or all relevant row logical change records (N)
APPLY_DATABASE_LINK	VARCHAR2 (128)		Database link to which changes are applied. If null, then changes are applied to the local database.
APPLY_NAME	VARCHAR2 (30)		Name of the apply process for the given object
ASSEMBLE_LOBS	VARCHAR2 (1)		Indicates whether LOB assembly is used for LOB columns in logical change records (LCRs) processed by the handler (Y) or not (N) LOB assembly combines multiple LCRs for a LOB column resulting from a single row change into one row LCR before passing the LCR to the handler.
HANDLER_NAME	VARCHAR2 (30)		Name of the apply DML handler; NULL for error and procedural handlers
HANDLER_TYPE	VARCHAR2 (17)		Type of the apply DML handler: ■ STMT_HANDLER ■ ERROR_HANDLER ■ PROCEDURE_HANDLER

See Also: ["DBA_APPLY_DML_HANDLERS"](#) on page 4-34

ALL_APPLY_ENQUEUE

ALL_APPLY_ENQUEUE displays information about the apply enqueue actions for the rules where the destination queue exists and is accessible to the current user.

Related View

DBA_APPLY_ENQUEUE displays information about the apply enqueue actions for all rules in the database.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule
DESTINATION_QUEUE_NAME	VARCHAR2 (4000)		Name of the queue where events satisfying the rule will be enqueued

See Also: ["DBA_APPLY_ENQUEUE"](#) on page 4-34

ALL_APPLY_ERROR

ALL_APPLY_ERROR displays information about the error transactions generated by the apply processes that dequeue messages from queues accessible to the current user.

Related View

DBA_APPLY_ERROR displays information about the error transactions generated by all apply processes in the database.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2 (30)		Name of the apply process at the local database which processed the transaction
QUEUE_NAME	VARCHAR2 (30)		Name of the queue at the local database from which the transaction was dequeued
QUEUE_OWNER	VARCHAR2 (30)		Owner of the queue at the local database from which the transaction was dequeued
LOCAL_TRANSACTION_ID	VARCHAR2 (22)		Local transaction ID for the error transaction
SOURCE_DATABASE	VARCHAR2 (128)		Database where the transaction originated
SOURCE_TRANSACTION_ID	VARCHAR2 (128)		Original transaction ID at the source database
SOURCE_COMMIT_SCN	NUMBER		Original commit system change number (SCN) for the transaction at the source database
MESSAGE_NUMBER	NUMBER		Identifier for the message in the transaction that raised an error
ERROR_NUMBER	NUMBER		Error number of the error raised by the transaction
ERROR_MESSAGE	VARCHAR2 (4000)		Error message of the error raised by the transaction
RECIPIENT_ID	NUMBER		User ID of the original user that applied the transaction
RECIPIENT_NAME	VARCHAR2 (30)		Name of the original user that applied the transaction
MESSAGE_COUNT	NUMBER		Total number of messages inside the error transaction
ERROR_CREATION_TIME	DATE		Time that the error was created
SOURCE_COMMIT_POSITION	RAW (64)		Original commit position for the transaction
ERROR_TYPE ¹	VARCHAR2 (11)		NULL if the apply process can access all of the LCRs in the error transaction. When the ERROR_TYPE is NULL, manage the error transactions using the instructions in <i>Oracle Streams Concepts and Administration</i> . EAGER ERROR if the apply process cannot access all of the LCRs in the error transaction. This error type typically means that the apply process was applying LCRs in a large transaction. When the ERROR_TYPE is EAGER ERROR, manage the error transaction using the instructions in <i>Oracle Database XStream Guide</i> .

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also: ["DBA_APPLY_ERROR"](#) on page 4-34

ALL_APPLY_ERROR_MESSAGES

ALL_APPLY_ERROR_MESSAGES displays information about the individual messages in an error transaction generated by the apply processes that dequeue messages from queues accessible to the current user.

Related View

DBA_APPLY_ERROR_MESSAGES displays information about the individual messages in all of the error transactions generated by all apply processes in the database.

Note: Messages that were spilled from memory to hard disk do not appear in this view.

Column	Datatype	NULL	Description
MESSAGE_ID	RAW (16)		Unique identifier of the message stored in the error queue
LOCAL_TRANSACTION_ID	VARCHAR2 (22)		Local transaction ID for the error transaction
TRANSACTION_MESSAGE_NUMBER	NUMBER		Message number of the message that raised the error. The message number is a sequence number for the messages in the transaction, starting with 1.
ERROR_NUMBER	NUMBER		Error number of the error raised by the transaction. The error number is populated only for the LCR that raised the error. This field is NULL for the other LCRs in the transaction.
ERROR_MESSAGE	VARCHAR2 (4000)		Error message of the error raised by the transaction. The error message is populated only for the LCR that raised the error. This field is NULL for the other LCRs in the transaction.

See Also: ["DBA_APPLY_ERROR_MESSAGES"](#) on page 4-34

Note: The ALL_APPLY_ERROR_MESSAGES view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

ALL_APPLY_EXECUTE

ALL_APPLY_EXECUTE displays information about the apply execute actions for the rules visible to the current user.

Related View

DBA_APPLY_EXECUTE displays information about the apply execute actions for all rules in the database.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule
EXECUTE_EVENT	VARCHAR2 (2)		Indicates whether the event satisfying the rule is executed

See Also: ["DBA_APPLY_EXECUTE"](#) on page 4-34

ALL_APPLY_KEY_COLUMNS

ALL_APPLY_KEY_COLUMNS displays information about the substitute key columns for the tables accessible to the current user. Substitute key columns are set using the DBMS_APPLY_ADM.SET_KEY_COLUMNS procedure.

Related View

DBA_APPLY_KEY_COLUMNS displays information about the substitute key columns for all tables in the database.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object on which substitute key columns are set
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object on which substitute key columns are set
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Column name of a column specified as a substitute key column
APPLY_DATABASE_LINK	VARCHAR2 (128)		Database link to which changes are applied. If null, then changes are applied to the local database.

See Also: ["DBA_APPLY_KEY_COLUMNS"](#) on page 4-35

ALL_APPLY_PARAMETERS

ALL_APPLY_PARAMETERS displays information about the parameters for the apply processes that dequeue events from queues accessible to the current user.

Related View

DBA_APPLY_PARAMETERS displays information about the parameters for all apply processes in the database.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2 (30)	NOT NULL	Name of the apply process
PARAMETER	VARCHAR2 (128)	NOT NULL	Name of the parameter
VALUE	VARCHAR2 (4000)		Parameter value
SET_BY_USER	VARCHAR2 (3)		Indicates whether the parameter value was set by the user (YES) or was not set by the user (NO). If NO for a parameter, then the parameter is set to its default value. If YES for a parameter, then the parameter may or may not be set to its default value.

See Also: ["DBA_APPLY_PARAMETERS"](#) on page 4-36

ALL_APPLY_PROGRESS

ALL_APPLY_PROGRESS displays information about the progress made by the apply processes that dequeue events from queues accessible to the current user. This view only contains information about captured events. It does not contain information about user-enqueued events.

Related View

DBA_APPLY_PROGRESS displays information about the progress made by all apply processes in the database.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2 (30)	NOT NULL	Name of the apply process
SOURCE_DATABASE	VARCHAR2 (128)	NOT NULL	Global name of the source database of the changes that are applied by the apply process

Column	Datatype	NULL	Description
APPLIED_MESSAGE_NUMBER	NUMBER	NOT NULL	Message number up to which all transactions have definitely been applied. This value is the low watermark for the apply process. That is, messages with a commit message number less than or equal to this message number have definitely been applied, but some messages with a higher commit message number may also have been applied.
OLDEST_MESSAGE_NUMBER	NUMBER	NOT NULL	Earliest message number of the transactions currently being dequeued and applied
APPLY_TIME	DATE		Time at which the message with the message number displayed in the APPLIED_MESSAGE_NUMBER column was applied
APPLIED_MESSAGE_CREATE_TIME	DATE		Time at which the message with the message number displayed in the APPLIED_MESSAGE_NUMBER column was created at its source database
OLDEST_TRANSACTION_ID	VARCHAR2 (128)		Oldest transaction ID of interest. (useful for detecting long-running or large transactions)
SPILL_MESSAGE_NUMBER	NUMBER		Spill low watermark. Any message with a lower SCN has either been applied or spilled to disk (it will be dequeued from the Streams queue and capture will not need to resend any logical change records (LCRs) with a lower SCN). Spilled messages may not have been applied yet.

See Also: ["DBA_APPLY_PROGRESS"](#) on page 4-36

ALL_APPLY_TABLE_COLUMNS

ALL_APPLY_TABLE_COLUMNS displays, for the tables accessible to the current user, information about the nonkey table columns for which Oracle Streams apply processes do not detect conflicts for updates and deletes.

Conflict detection for nonkey columns can be stopped using the DBMS_APPLY_ADM.COMPARE_OLD_VALUES procedure.

Related View

DBA_APPLY_TABLE_COLUMNS displays, for all tables in the database, information about the nonkey table columns for which Oracle Streams apply processes do not detect conflicts for updates and deletes.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)		Owner of the table
OBJECT_NAME	VARCHAR2 (30)		Name of the table
COLUMN_NAME	VARCHAR2 (4000)		Name of the column
COMPARE_OLD_ON_DELETE	VARCHAR2 (3)		Indicates whether to Compare the old value of the column on deletes (YES) or not (NO)
COMPARE_OLD_ON_UPDATE	VARCHAR2 (3)		Indicates whether to Compare the old value of the column on updates (YES) or not (NO)
APPLY_DATABASE_LINK	VARCHAR2 (128)		For remote tables, name of the database link pointing to the remote database

See Also: ["DBA_APPLY_TABLE_COLUMNS"](#) on page 4-36

ALL_ARGUMENTS

`ALL_ARGUMENTS` lists the arguments of the procedures and functions that are accessible to the current user.

Related Views

- `DBA_ARGUMENTS` lists the arguments of the procedures and functions that are available in the database.
- `USER_ARGUMENTS` lists the arguments of the procedures and functions that are owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2 (30)		Name of the procedure or function
PACKAGE_NAME	VARCHAR2 (30)		Name of the package
OBJECT_ID	NUMBER	NOT NULL	Object number of the object
OVERLOAD	VARCHAR2 (40)		Indicates the <i>n</i> th overloading ordered by its appearance in the source; otherwise, it is NULL.
SUBPROGRAM_ID	NUMBER		Unique subprogram identifier
ARGUMENT_NAME	VARCHAR2 (30)		If the argument is a scalar type, then the argument name is the name of the argument. A null argument name is used to denote a function return. If the function return or argument is a composite type, this view will have one row for each attribute of the composite type. Attributes are recursively expanded if they are composite. The meanings of <code>ARGUMENT_NAME</code>, <code>POSITION</code>, <code>SEQUENCE</code>, and <code>DATA_LEVEL</code> are interdependent. Together, as a tuple, they represent a node of a flattened tree. <code>ARGUMENT_NAME</code> can refer to any of the following: ■ Return type, if <code>ARGUMENT_NAME</code> is null and <code>DATA_LEVEL</code> = 0 ■ The argument that appears in the argument list if <code>ARGUMENT_NAME</code> is not null and <code>DATA_LEVEL</code> = 0 ■ Attribute name of the composite type if <code>ARGUMENT_NAME</code> is not null and <code>DATA_LEVEL</code> > 0; ■ A collection element type if <code>ARGUMENT_NAME</code> is null and <code>DATA_LEVEL</code> > 0;
POSITION	NUMBER	NOT NULL	If <code>DATA_LEVEL</code> is zero, then this column holds the position of this item in the argument list, or zero for a function return value. If <code>DATA_LEVEL</code> is greater than zero, then this column holds the position of this item with respect to its siblings at the same <code>DATA_LEVEL</code>. So, for a referenced record field, this is the index of the field within the record. For a referenced collection element, this is 1 (because collection elements do not have siblings.)
SEQUENCE	NUMBER	NOT NULL	Defines the sequential order of the argument and its attributes. Argument sequence starts from 1. Return type and its recursively expanded (preorder tree walk) attributes will come first, and each argument with its recursively expanded (preorder tree walk) attributes will follow.
DATA_LEVEL	NUMBER	NOT NULL	Nesting depth of the argument for composite types
DATA_TYPE	VARCHAR2 (30)		Datatype of the argument
DEFAULTED	VARCHAR2 (1)		Specifies whether or not the argument is defaulted
DEFAULT_VALUE	LONG		Reserved for future use

Column	Datatype	NULL	Description
DEFAULT_LENGTH	NUMBER		Reserved for future use
IN_OUT	VARCHAR2 (9)		Direction of the argument: - IN - OUT - IN/OUT
DATA_LENGTH	NUMBER		Length of the column (in bytes)
DATA_PRECISION	NUMBER		Length in decimal digits (NUMBER) or binary digits (FLOAT)
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
RADIX	NUMBER		Argument radix for a number
CHARACTER_SET_NAME	VARCHAR2 (44)		Character set name for the argument
TYPE_OWNER	VARCHAR2 (30)		Owner of the type of the argument
TYPE_NAME	VARCHAR2 (30)		Name of the type of the argument. If the type is a package local type (that is, it is declared in a package specification), then this column displays the name of the package.
TYPE_SUBNAME	VARCHAR2 (30)		Relevant only for package local types. Displays the name of the type declared in the package identified in the TYPE_NAME column.
TYPE_LINK	VARCHAR2 (128)		Relevant only for package local types when the package identified in the TYPE_NAME column is a remote package. This column displays the database link used to refer to the remote package.
PLS_TYPE	VARCHAR2 (30)		For numeric arguments, the name of the PL/SQL type of the argument. Null otherwise.
CHAR_LENGTH	NUMBER		Character limit for string datatypes
CHAR_USED	VARCHAR2 (1)		Indicates whether the byte limit (B) or char limit (C) is official for the string

See Also:

- ["DBA_ARGUMENTS"](#) on page 4-37
- ["USER_ARGUMENTS"](#) on page 6-68

ALL_ASSEMBLIES

ALL_ASSEMBLIES provides information about assemblies accessible to the current user.

Related Views

- DBA_ASSEMBLIES provides information about all assemblies in the database.
- USER_ASSEMBLIES provides information about all assemblies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the assembly
ASSEMBLY_NAME	VARCHAR2 (30)	NOT NULL	Name of the assembly
FILE_SPEC	VARCHAR2 (4000)		Operating system file specification of the assembly
SECURITY_LEVEL	VARCHAR2 (10)		The maximum security level of the assembly
IDENTITY	VARCHAR2 (4000)		The identity of the assembly

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (7)		Status of the assembly

See Also:

- ["DBA_ASSEMBLIES"](#) on page 4-38
- ["USER_ASSEMBLIES"](#) on page 6-69

ALL_ASSOCIATIONS

ALL_ASSOCIATIONS describes user-defined statistics associated with objects accessible to the current user.

Related Views

- DBA_ASSOCIATIONS describes all user-defined statistics in the database.
- USER_ASSOCIATIONS describes user-defined statistics associated with objects owned by the current user.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object for which the association is being defined
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object for which the association is being defined
COLUMN_NAME	VARCHAR2 (30)		Column name in the object for which the association is being defined
OBJECT_TYPE	VARCHAR2 (9)		Kind of object with which statistics are being associated: column, type, package or function, indextype, or domain index.
STATSTYPE_SCHEMA	VARCHAR2 (30)		Owner of the statistics type
STATSTYPE_NAME	VARCHAR2 (30)		Name of statistics type that contains the cost, selectivity or statistics functions
DEF_SELECTIVITY	NUMBER		Default selectivity of the object, if any
DEF_CPU_COST	NUMBER		Default CPU cost of the object, if any
DEF_IO_COST	NUMBER		Default I/O cost of the object, if any
DEF_NET_COST	NUMBER		Default networking cost of the object, if any
INTERFACE_VERSION	NUMBER		Identifies the version number of the ODCIStats interface. Value is 1 for statistics type implementing Oracle8i 8.1; 0 for types implementing Oracle9i 9.0.0.
MAINTENANCE_TYPE	VARCHAR2 (14)		Specifies whether the object is system-managed or user-managed

See Also:

- ["DBA_ASSOCIATIONS"](#) on page 4-38
- ["USER_ASSOCIATIONS"](#) on page 6-69

ALL_AUDIT_POLICIES

ALL_AUDIT_POLICIES describes the fine-grained auditing policies on the tables and views accessible to the current user.

Related Views

- `DBA_AUDIT_POLICIES` describes all fine-grained auditing policies in the database.
- `USER_AUDIT_POLICIES` describes the fine-grained auditing policies on the tables and views owned by the current user. This view does not display the `OBJECT_SCHEMA` column.

Column	Datatype	NULL	Description
<code>OBJECT_SCHEMA</code>	<code>VARCHAR2 (30)</code>		Owner of the table or view
<code>OBJECT_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the table or view
<code>POLICY_OWNER</code>	<code>VARCHAR2 (30)</code>		Owner of the policy
<code>POLICY_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the policy
<code>POLICY_TEXT</code>	<code>VARCHAR2 (4000)</code>		Audit condition
<code>POLICY_COLUMN</code>	<code>VARCHAR2 (30)</code>		Relevant column
<code>PF_SCHEMA</code>	<code>VARCHAR2 (30)</code>		Owner of the audit handler function
<code>PF_PACKAGE</code>	<code>VARCHAR2 (30)</code>		Name of the package containing the audit handler function
<code>PF_FUNCTION</code>	<code>VARCHAR2 (30)</code>		Name of the audit handler function
<code>ENABLED</code>	<code>VARCHAR2 (3)</code>		Indicates whether the policy is enabled (YES) or disabled (NO)
<code>SEL</code>	<code>VARCHAR2 (3)</code>		Indicates whether the policy is applied to queries on the object (YES) or not (NO)
<code>INS</code>	<code>VARCHAR2 (3)</code>		Indicates whether the policy is applied to INSERT statements on the object (YES) or not (NO)
<code>UPD</code>	<code>VARCHAR2 (3)</code>		Indicates whether the policy is applied to UPDATE statements on the object (YES) or not (NO)
<code>DEL</code>	<code>VARCHAR2 (3)</code>		Indicates whether the policy is applied to DELETE statements on the object (YES) or not (NO)
<code>AUDIT_TRAIL</code>	<code>VARCHAR2 (12)</code>		Indicates the audit trail to which the audit records generated by this audit policy will be written: ■ DB - Audit records are written to <code>DBA_FGA_AUDIT_TRAIL</code> (fine-grained audit trail) ■ DB+EXTENDED - Audit records are written to <code>DBA_FGA_AUDIT_TRAIL</code> (fine-grained audit trail) and the <code>SQL_TEXT</code> and <code>SQL_BIND</code> columns are populated for this policy ■ XML - Audit records are written to <code>V\$XML_AUDIT_TRAIL</code> (XML audit files) ■ XML+EXTENDED - Audit records are written to <code>V\$XML_AUDIT_TRAIL</code> (XML audit files) and the <code>SQL_TEXT</code> and <code>SQL_BIND</code> columns are populated for this policy
<code>POLICY_COLUMN_OPTIONS</code>	<code>VARCHAR2 (11)</code>		Indicates whether all columns in the <code>AUDIT_COLUMN</code> parameter (<code>ALL_COLUMNS</code>) or any of the columns in the <code>AUDIT_COLUMN</code> parameter (<code>ANY_COLUMNS</code>) are considered for triggering fine-grained auditing

See Also:

- ["DBA_AUDIT_POLICIES"](#) on page 4-43
- ["USER_AUDIT_POLICIES"](#) on page 6-69

ALL_AUDIT_POLICY_COLUMNS

ALL_AUDIT_POLICY_COLUMNS describes the fine-grained auditing policy columns on the tables and views accessible to the current user.

Related Views

- DBA_AUDIT_POLICY_COLUMNS describes all fine-grained auditing policy columns in the database.
- USER_AUDIT_POLICY_COLUMNS describes the fine-grained auditing policy columns on the tables and views owned by the current user.

Column	Datatype	NULL	Description
OBJECT_SCHEMA	VARCHAR2 (30)		Owner of the table or view
OBJECT_NAME	VARCHAR2 (30)		Name of the table or view
POLICY_NAME	VARCHAR2 (30)		Name of the policy
POLICY_COLUMN	VARCHAR2 (30)		Relevant column of the policy

See Also:

- ["DBA_AUDIT_POLICY_COLUMNS"](#) on page 4-43
- ["USER_AUDIT_POLICY_COLUMNS"](#) on page 6-69

ALL_AW_PS

ALL_AW_PS describes the page spaces in the analytic workspaces accessible to the current user.

Related Views

- DBA_AW_PS describes the page spaces in all analytic workspaces in the database.
- USER_AW_PS describes the page spaces in the analytic workspaces owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the analytic workspace
AW_NUMBER	NUMBER	NOT NULL	Number of the analytic workspace
AW_NAME	VARCHAR2 (30)		Name of the analytic workspace
PSNUMBER	NUMBER (10)		Number of the page space
GENERATIONS	NUMBER		Number of active generations in the page space
MAXPAGES	NUMBER		Maximum pages allocated in the page space

See Also:

- ["DBA_AW_PS"](#) on page 4-55
- ["USER_AW_PS"](#) on page 6-70
- *Oracle OLAP User's Guide* for more information about these views

ALL_AWS

ALL_AWS describes the analytic workspaces accessible to the current user.

Related Views

- `DBA_AWS` describes all analytic workspaces in the database.
- `USER_AWS` describes the analytic workspaces owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	<code>NOT NULL</code>	Owner of the analytic workspace
<code>AW_NUMBER</code>	<code>NUMBER</code>		Number of the analytic workspace
<code>AW_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the analytic workspace
<code>AW_VERSION</code>	<code>VARCHAR2 (4)</code>		Format version of the analytic workspace: ■ 9.1 ■ 10.1 ■ 10.2 ■ 11.1
<code>PAGESPACES</code>	<code>NUMBER</code>		Number of pagespaces in the analytic workspace
<code>GENERATIONS</code>	<code>NUMBER</code>		Number of active generations in the analytic workspace
<code>FROZEN</code>	<code>VARCHAR2 (6)</code>		Freeze state of the analytic workspace: ■ Frozen ■ NoThaw

See Also:

- ["DBA_AWS"](#) on page 4-55
- ["USER_AWS"](#) on page 6-70
- *Oracle OLAP User's Guide* for more information about these views

ALL_BASE_TABLE_MVIEWS

`ALL_BASE_TABLE_MVIEWS` describes the materialized views using materialized view logs accessible to the current user. A materialized view log can be created for a master, base table, or master materialized view. Query this view at the master site or the master materialized view site to show one row for each materialized view using a materialized view log.

Related Views

- `DBA_BASE_TABLE_MVIEWS` describes all materialized views using materialized view logs in the database.
- `USER_BASE_TABLE_MVIEWS` describes the materialized views using materialized view logs owned by the current user.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	<code>NOT NULL</code>	Schema in which the master table or the master materialized view was created
<code>MASTER</code>	<code>VARCHAR2 (30)</code>	<code>NOT NULL</code>	Name of the master table or the master materialized view
<code>MVIEW_LAST_REFRESH_TIME</code>	<code>DATE</code>	<code>NOT NULL</code>	Date when the materialized view based on the master was last refreshed
<code>MVIEW_ID</code>	<code>NUMBER (38)</code>		Unique identifier of the materialized view that is based on the master

See Also:

- ["DBA_BASE_TABLE_MVIEWS"](#) on page 4-55
- ["USER_BASE_TABLE_MVIEWS"](#) on page 6-70

ALL_CAPTURE

ALL_CAPTURE displays information about the capture processes that enqueue the captured changes into queues accessible to the current user.

Related View

DBA_CAPTURE displays information about all capture processes in the database.

Column	Datatype	NULL	Description
CAPTURE_NAME	VARCHAR2 (30)	NOT NULL	Name of the capture process
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue used for staging captured changes
QUEUE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the queue used for staging captured changes
RULE_SET_NAME	VARCHAR2 (30)		Name of the positive rule set used by the capture process for filtering
RULE_SET_OWNER	VARCHAR2 (30)		Owner of the positive rule set
CAPTURE_USER	VARCHAR2 (30)		Current user who is enqueueing captured messages
START_SCN	NUMBER		System change number (SCN) from which the capture process will start to capture changes
STATUS	VARCHAR2 (8)		Status of the capture process: ■ DISABLED ■ ENABLED ■ ABORTED
CAPTURED_SCN	NUMBER		System change number (SCN) of the last redo log record scanned
APPLIED_SCN	NUMBER		System change number (SCN) of the most recent message dequeued by the relevant apply processes. All changes below this SCN have been dequeued by all apply processes that apply changes captured by this capture process.
USE_DATABASE_LINK	VARCHAR2 (3)		Indicates whether the source database name is used as the database link to connect to the source database from the downstream database (YES) or not (NO). If the capture process was created at the source database, then this column will be NULL.
FIRST_SCN	NUMBER		System change number (SCN) from which the capture process can be restarted
SOURCE_DATABASE	VARCHAR2 (128)		Global name of the source database
SOURCE_DBID	NUMBER		Database ID of the source database
SOURCE_RESETLOGS_SCN	NUMBER		Resetlogs system change number (SCN) of the source database
SOURCE_RESETLOGS_TIME	NUMBER		Resetlogs time of the source database
LOGMINER_ID	NUMBER		Session ID of the LogMiner session associated with the capture process
NEGATIVE_RULE_SET_NAME	VARCHAR2 (30)		Name of the negative rule set used by the capture process for filtering
NEGATIVE_RULE_SET_OWNER	VARCHAR2 (30)		Owner of the negative rule set used by the capture process for filtering

Column	Datatype	NULL	Description
MAX_CHECKPOINT_SCN	NUMBER		System change number (SCN) at which the last checkpoint was taken by the capture process
REQUIRED_CHECKPOINT_SCN	NUMBER		Lowest checkpoint SCN for which the capture process requires redo information
LOGFILE_ASSIGNMENT	VARCHAR2 (8)		Logfile assignment type for the capture process: ■ IMPLICIT ■ EXPLICIT
STATUS_CHANGE_TIME	DATE		Time that the STATUS of the capture process was changed
ERROR_NUMBER	NUMBER		Error number if the capture process was aborted
ERROR_MESSAGE	VARCHAR2 (4000)		Error message if the capture process was aborted
VERSION	VARCHAR2 (64)		Version number of the capture process
CAPTURE_TYPE	VARCHAR2 (10)		Type of the capture process: ■ DOWNSTREAM ■ LOCAL
LAST_ENQUEUED_SCN	NUMBER		Last enqueued system change number (SCN)
CHECKPOINT_RETENTION_TIME	NUMBER		Checkpoint retention time Note: When the checkpoint retention time for a capture process is set to INFINITE, then the value displayed in this column is 4294967295.
START_TIME ¹	TIMESTAMP (6)		Time from which the capture process will start to capture changes
PURPOSE ¹	VARCHAR2 (19)		Purpose of the capture process: ■ Streams - A capture process in an Oracle Streams configuration ■ XStream Streams - A capture process in an Oracle Streams configuration with XStream capabilities enabled by the DBMS_XSTREAM_ADM.ENABLE_GG_XSTREAM_FOR_STREAMS procedure ■ XStream Out - A capture process in an XStream Out configuration ■ AUDIT VAULT - A capture process in an audit vault configuration ■ CHANGE DATA CAPTURE - A capture process in a change data capture configuration

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also: ["DBA_CAPTURE"](#) on page 4-55

ALL_CAPTURE_EXTRA_ATTRIBUTES

ALL_CAPTURE_EXTRA_ATTRIBUTES displays information about the extra attributes for the capture processes accessible to the current user.

Related View

DBA_CAPTURE_EXTRA_ATTRIBUTES displays information about the extra attributes for all capture processes in the database.

Column	Datatype	NULL	Description
CAPTURE_NAME	VARCHAR2 (30)	NOT NULL	Name of the capture process

Column	Datatype	NULL	Description
ATTRIBUTE_NAME	VARCHAR2 (30)	NOT NULL	Name of the extra attribute
INCLUDE	VARCHAR2 (3)		Indicates whether the extra attribute is included (YES) or not (NO)
ROW_ATTRIBUTE	VARCHAR2 (3)		Indicates whether the extra attribute is a row LCR attribute (YES) or not (NO)
DDL_ATTRIBUTE	VARCHAR2 (3)		Indicates whether the extra attribute is a DDL LCR attribute (YES) or not (NO)

See Also: ["DBA_CAPTURE_EXTRA_ATTRIBUTES"](#) on page 4-55

ALL_CAPTURE_PARAMETERS

ALL_CAPTURE_PARAMETERS displays information about the parameters for the capture processes that enqueue the captured changes into queues accessible to the current user.

Related View

DBA_CAPTURE_PARAMETERS displays information about the parameters for all capture processes in the database.

Column	Datatype	NULL	Description
CAPTURE_NAME	VARCHAR2 (30)	NOT NULL	Name of the capture process
PARAMETER	VARCHAR2 (128)	NOT NULL	Name of the parameter
VALUE	VARCHAR2 (4000)		Parameter value
SET_BY_USER	VARCHAR2 (3)		Indicates whether the parameter value was set by the user (YES) or was not set by the user (NO). If NO, then the parameter is set to its default value. If YES, then the parameter may or may not be set to its default value.

See Also: ["DBA_CAPTURE_PARAMETERS"](#) on page 4-56

ALL_CAPTURE_PREPARED_DATABASE

ALL_CAPTURE_PREPARED_DATABASE displays information about when the local database was prepared for instantiation. If the local database was not prepared for instantiation, then this view contains no rows.

Related View

DBA_CAPTURE_PREPARED_DATABASE displays information about when the local database was prepared for instantiation.

Column	Datatype	NULL	Description
TIMESTAMP	DATE		Date and time at which the local database was ready to be instantiated
SUPPLEMENTAL_LOG_DATA_PK	VARCHAR2 (8)		Status of database-level PRIMARY KEY COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO

Column	Datatype	NULL	Description
SUPPLEMENTAL_LOG_DATA_UI	VARCHAR2 (8)		Status of database-level UNIQUE INDEX COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO
SUPPLEMENTAL_LOG_DATA_FK	VARCHAR2 (8)		Status of database-level FOREIGN KEY COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO
SUPPLEMENTAL_LOG_DATA_ALL	VARCHAR2 (8)		Status of database-level ALL COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO

See Also:

- ["DBA_CAPTURE_PREPARED_DATABASE"](#) on page 4-56
- *Oracle Streams Concepts and Administration* for more information about the possible values for the supplemental logging columns in this view

ALL_CAPTURE_PREPARED_SCHEMAS

ALL_CAPTURE_PREPARED_SCHEMAS displays information about the schemas prepared for instantiation that are accessible to the current user at the local database.

Related View

DBA_CAPTURE_PREPARED_SCHEMAS displays information about all schemas prepared for instantiation at the local database.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Name of the schema that is ready to be instantiated
TIMESTAMP	DATE		Date and time at which the schema was ready to be instantiated
SUPPLEMENTAL_LOG_DATA_PK	VARCHAR2 (8)		Status of schema-level PRIMARY KEY COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO
SUPPLEMENTAL_LOG_DATA_UI	VARCHAR2 (8)		Status of schema-level UNIQUE INDEX COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO
SUPPLEMENTAL_LOG_DATA_FK	VARCHAR2 (8)		Status of schema-level FOREIGN KEY COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO

Column	Datatype	NULL	Description
SUPPLEMENTAL_LOG_DATA_ALL	VARCHAR2 (8)		Status of schema-level ALL COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO

See Also:

- ["DBA_CAPTURE_PREPARED_SCHEMAS"](#) on page 4-56
- *Oracle Streams Concepts and Administration* for more information about the possible values for the supplemental logging columns in this view

ALL_CAPTURE_PREPARED_TABLES

ALL_CAPTURE_PREPARED_TABLES displays information about the tables prepared for instantiation that are accessible to the current user at the local database.

Related View

DBA_CAPTURE_PREPARED_TABLES displays information about all tables prepared for instantiation at the local database.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table that is ready to be instantiated
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table that is ready to be instantiated
SCN	NUMBER	NOT NULL	Smallest system change number (SCN) for which the table can be instantiated
TIMESTAMP	DATE		Date and time at which the table was ready to be instantiated
SUPPLEMENTAL_LOG_DATA_PK	VARCHAR2 (8)		Status of table-level PRIMARY KEY COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO
SUPPLEMENTAL_LOG_DATA_UI	VARCHAR2 (8)		Status of table-level UNIQUE INDEX COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO
SUPPLEMENTAL_LOG_DATA_FK	VARCHAR2 (8)		Status of table-level FOREIGN KEY COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO
SUPPLEMENTAL_LOG_DATA_ALL	VARCHAR2 (8)		Status of table-level ALL COLUMNS supplemental logging: ■ IMPLICIT ■ EXPLICIT ■ NO

See Also:

- ["DBA_CAPTURE_PREPARED_TABLES"](#) on page 4-56
- *Oracle Streams Concepts and Administration* for more information about the possible values for the supplemental logging columns in this view

ALL_CATALOG

ALL_CATALOG displays the tables, clusters, views, synonyms, and sequences accessible to the current user.

Related Views

- DBA_CATALOG displays all tables, clusters, views, synonyms, and sequences in the entire database.
- USER_CATALOG displays the tables, clusters, views, synonyms, and sequences in the current user's schema. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the TABLE, CLUSTER, VIEW, SYNONYM, SEQUENCE, or UNDEFINED
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the TABLE, CLUSTER, VIEW, SYNONYM, SEQUENCE, or UNDEFINED
TABLE_TYPE	VARCHAR2 (11)		Type of the TABLE, CLUSTER, VIEW, SYNONYM, SEQUENCE, or UNDEFINED

ALL_CHANGE_PROPAGATION_SETS

ALL_CHANGE_PROPAGATION_SETS displays information about the Change Data Capture propagated change sets.

Column	Datatype	NULL	Description
PROPAGATION_SOURCE_NAME	VARCHAR2 (30)	NOT NULL	Name of the change source
PROPAGATION_NAME	VARCHAR2 (30)	NOT NULL	Name of the propagation
STAGING_DATABASE	VARCHAR2 (128)	NOT NULL	Name of the staging database for the propagation
CHANGE_SET_PUBLISHER	VARCHAR2 (30)	NOT NULL	Publisher of the distributed change set
CHANGE_SET_NAME	VARCHAR2 (30)	NOT NULL	Name of the distributed change set

ALL_CHANGE_PROPAGATIONS

ALL_CHANGE_PROPAGATIONS displays information about Change Data Capture propagations.

Column	Datatype	NULL	Description
PROPAGATION_SOURCE_NAME	VARCHAR2 (30)	NOT NULL	Name of the change source
PROPAGATION_NAME	VARCHAR2 (30)	NOT NULL	Name of the propagation
STAGING_DATABASE	VARCHAR2 (128)	NOT NULL	Name of the staging database for the propagation
DESTINATION_QUEUE_PUBLISHER	VARCHAR2 (30)	NOT NULL	Owner of the destination queue

Column	Datatype	NULL	Description
DESTINATION_QUEUE	VARCHAR2 (30)	NOT NULL	Name of the destination queue

ALL_CHANGE_SETS

ALL_CHANGE_SETS displays information about Change Data Capture change sets.

Column	Datatype	NULL	Description
SET_NAME	VARCHAR2 (30)	NOT NULL	Name of the change set
CHANGE_SOURCE_NAME	VARCHAR2 (30)	NOT NULL	Change source to which the change set belongs
BEGIN_DATE	DATE		Starting point for capturing change data
END_DATE	DATE		Stopping point for capturing change data
BEGIN_SCN	NUMBER		Reserved for future use
END_SCN	NUMBER		Reserved for future use
FRESHNESS_DATE	DATE		Reserved for future use
FRESHNESS_SCN	NUMBER		Reserved for future use
ADVANCE_ENABLED	CHAR (1)		Indicates whether the change set is enabled (Y) or disabled (N), or whether capture is disabled and apply is enabled (C)
IGNORE_DDL	VARCHAR2 (1)		Reserved for future use
CREATED	DATE	NOT NULL	Creation date of the change set
ROLLBACK_SEGMENT_NAME	VARCHAR2 (30)		Reserved for future use
ADVANCING	VARCHAR2 (1)	NOT NULL	Reserved for future use
PURGING	VARCHAR2 (1)	NOT NULL	Reserved for future use
LOWEST_SCN	NUMBER		Low watermark for change data in the change set
TABLESPACE	VARCHAR2 (30)		Reserved for future use
CAPTURE_ENABLED	VARCHAR2 (1)		Indicates whether capture is enabled for the change set (Y) or not (N)
STOP_ON_DDL	VARCHAR2 (1)	NOT NULL	Indicates whether the change set stops on DDL (Y) or not (N)
CAPTURE_ERROR	CHAR (1)		Indicates whether there is a capture error (Y) or not (N)
CAPTURE_NAME	VARCHAR2 (30)		Name of the Streams capture process
QUEUE_NAME	VARCHAR2 (30)		Name of the Streams queue
QUEUE_TABLE_NAME	VARCHAR2 (30)		Name of the Streams queue table
APPLY_NAME	VARCHAR2 (30)		Name of the Streams apply process
SET_DESCRIPTION	VARCHAR2 (255)		Description of the change set
PUBLISHER	VARCHAR2 (30)		Publisher of the change set
LOWEST_TIMESTAMP	DATE		Timestamp of the record with the lowest SCN in the change set
MAP_NAME	VARCHAR2 (30)		Name of the mapping table; maps SCN to timestamp

ALL_CHANGE_SOURCES

ALL_CHANGE_SOURCES displays information about Change Data Capture change sources.

Column	Datatype	NULL	Description
SOURCE_NAME	VARCHAR2 (30)	NOT NULL	Name of the change source

Column	Datatype	NULL	Description
DBID	NUMBER		Database identifier
LOG_DIRECTORY	VARCHAR2 (2000)		Log file directory location
LOGFILE_PATTERN	VARCHAR2 (30)		Wildcard pattern for log file names
SOURCE_DESCRIPTION	VARCHAR2 (255)		Description of the change source
CREATED	DATE	NOT NULL	Creation date of the change source
SOURCE_TYPE	VARCHAR2 (18)		Capture mode of the change source: - AUTOLOG - HOTLOG - SYNCHRONOUS - DISTRIBUTED HOTLOG - AUTOLOG ONLINE
SOURCE_DATABASE	VARCHAR2 (128)		Global name of the source database
FIRST_SCN	NUMBER		SCN of a LogMiner dictionary at which capture can begin
PUBLISHER	VARCHAR2 (30)		Publisher of the change source
CAPTURE_NAME	VARCHAR2 (30)		Name of the Streams capture process
CAPTURE_QUEUE_NAME	VARCHAR2 (30)		Name of the Streams capture queue name
CAPTURE_QUEUE_TABLE_NAME	VARCHAR2 (30)		Name of the Streams capture table
SOURCE_ENABLED	VARCHAR2 (1)		Indicates whether the change source is enabled (Y) or not (N)

ALL_CHANGE_TABLES

ALL_CHANGE_TABLES displays information about Change Data Capture change tables.

Column	Datatype	NULL	Description
CHANGE_TABLE_SCHEMA	VARCHAR2 (30)	NOT NULL	Owner of the change table
CHANGE_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the change table
CHANGE_SET_NAME	VARCHAR2 (30)	NOT NULL	Name of the change set to which the change table belongs
SOURCE_SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Owner of the source table for the change table
SOURCE_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the source table for the change table
CREATED	DATE	NOT NULL	Creation date of the change table
CREATED_SCN	NUMBER		Creation SCN of the change table
CAPTURED_VALUES	VARCHAR2 (1)	NOT NULL	Indicates whether old (O), new (N), or both (B) update values are captured
PUB_ID	NUMBER	NOT NULL	Publication ID displayed to users for the change table

ALL_CLUSTER_HASH_EXPRESSIONS

ALL_CLUSTER_HASH_EXPRESSIONS displays hash functions for all hash clusters accessible to the current user.

Related Views

- DBA_CLUSTER_HASH_EXPRESSIONS displays hash functions for all hash clusters in the database.

- **USER_CLUSTER_HASH_EXPRESSIONS** displays hash functions for all hash clusters owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cluster
CLUSTER_NAME	VARCHAR2 (30)	NOT NULL	Name of the cluster
HASH_EXPRESSION	LONG		Text of the hash function of the hash cluster

ALL_CLUSTERS

ALL_CLUSTERS describes all clusters accessible to the current user.

Related Views

- **DBA_CLUSTERS** describes all clusters in the database.
- **USER_CLUSTERS** describes all clusters owned by the current user. This view does not display the **OWNER** column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cluster
CLUSTER_NAME	VARCHAR2 (30)	NOT NULL	Name of the cluster
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace containing the cluster
PCT_FREE	NUMBER		Minimum percentage of free space in a block
PCT_USED	NUMBER		Minimum percentage of used space in a block
KEY_SIZE	NUMBER		Estimated size of cluster key plus associated rows
INI_TRANS	NUMBER	NOT NULL	Initial number of transactions
MAX_TRANS	NUMBER	NOT NULL	Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes
MIN_EXTENTS	NUMBER	NOT NULL	Minimum number of extents allowed in the segment
MAX_EXTENTS	NUMBER	NOT NULL	Maximum number of extents allowed in the segment
PCT_INCREASE	NUMBER		Percentage increase in extent size
FREELISTS	NUMBER		Number of process freelists allocated to this segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to this segment
AVG_BLOCKS_PER_KEY	NUMBER		Number of blocks in the table divided by number of cluster keys
CLUSTER_TYPE	VARCHAR2 (5)		Type of the cluster: ■ INDEX - B*-Tree index ■ HASH - Hash
FUNCTION	VARCHAR2 (15)		If the cluster is a hash cluster, the hash function
HASHKEYS	NUMBER		If the cluster is a hash cluster, the number of hash keys (hash buckets)
DEGREE	VARCHAR2 (10)		Number of threads per instance for scanning the cluster, or DEFAULT
INSTANCES	VARCHAR2 (10)		Number of instances across which the cluster is to be scanned , or DEFAULT
CACHE	VARCHAR2 (5)		Indicates whether the cluster is to be cached in the buffer cache (Y) or not (N)

Column	Datatype	NULL	Description
BUFFER_POOL	VARCHAR2 (7)		Buffer pool to be used for cluster blocks: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for cluster blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for cluster blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
SINGLE_TABLE	VARCHAR2 (5)		Indicates whether this is a single-table cluster (Y) or not (N)
DEPENDENCIES	VARCHAR2 (8)		Indicates whether row-level dependency tracking is enabled (ENABLED) or disabled (DISABLED)

ALL_COL_COMMENTS

ALL_COL_COMMENTS displays comments on the columns of the tables and views accessible to the current user.

Related Views

- DBA_COL_COMMENTS displays comments on the columns of all tables and views in the database.
- USER_COL_COMMENTS displays comments on the columns of the tables and views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column
COMMENTS	VARCHAR2 (4000)		Comment on the column

See Also:

- ["DBA_COL_COMMENTS"](#) on page 4-58
- ["USER_COL_COMMENTS"](#) on page 6-71

ALL_COL_PENDING_STATS

ALL_COL_PENDING_STATS describes the pending statistics of the columns accessible to the current user.

Related Views

- `DBA_COL_PENDING_STATS` describes the pending statistics of all columns in the database.
- `USER_COL_PENDING_STATS` describes the pending statistics of the columns owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2(30)</code>		Owner of the table
<code>TABLE_NAME</code>	<code>VARCHAR2(30)</code>		Name of the table
<code>PARTITION_NAME</code>	<code>VARCHAR2(30)</code>		Name of the partition
<code>SUBPARTITION_NAME</code>	<code>VARCHAR2(30)</code>		Name of the subpartition
<code>COLUMN_NAME</code>	<code>VARCHAR2(30)</code>		Name of the column
<code>NUM_DISTINCT</code>	<code>NUMBER</code>		Number of distinct values in the column
<code>LOW_VALUE</code>	<code>RAW(32)</code>		Low value in the column
<code>HIGH_VALUE</code>	<code>RAW(32)</code>		High value in the column
<code>DENSITY</code>	<code>NUMBER</code>		If a histogram is available on <code>COLUMN_NAME</code> , then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on <code>COLUMN_NAME</code> , then the value of this column is $1/\text{NUM\_DISTINCT}$.
<code>NUM_NULLS</code>	<code>NUMBER</code>		Number of NULLs in the column
<code>AVG_COL_LEN</code>	<code>NUMBER</code>		Average length of the column (in bytes)
<code>SAMPLE_SIZE</code>	<code>NUMBER</code>		Sample size used in analyzing the column
<code>LAST_ANALYZED</code>	<code>DATE</code>		Most recent date on which the column was analyzed

See Also:

- ["DBA_COL_PENDING_STATS" on page 4-58](#)
- ["USER_COL_PENDING_STATS" on page 6-71](#)

ALL_COL_PRIVS

`ALL_COL_PRIVS` describes the following types of grants:

- Column object grants for which the current user is the object owner, grantor, or grantee
- Column object grants for which an enabled role or `PUBLIC` is the grantee

Related Views

- `DBA_COL_PRIVS` describes all column object grants in the database.
- `USER_COL_PRIVS` describes the column object grants for which the current user is the object owner, grantor, or grantee.

Column	Datatype	NULL	Description
<code>GRANTOR</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the user who performed the grant
<code>GRANTEE</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the user or role to whom access was granted
<code>TABLE_SCHEMA</code>	<code>VARCHAR2(30)</code>	NOT NULL	Schema of the object

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Privilege on the column
GRANTABLE	VARCHAR2 (3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)

See Also:

- ["DBA_COL_PRIVS"](#) on page 4-58
- ["USER_COL_PRIVS"](#) on page 6-71

ALL_COL_PRIVS_MADE

ALL_COL_PRIVS_MADE describes the column object grants for which the current user is the object owner or grantor.

Related View

USER_COL_PRIVS_MADE describes the column object grants for which the current user is the object owner. This view does not display the OWNER column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	Name of the user or role to whom access was granted
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column
GRANTOR	VARCHAR2 (30)	NOT NULL	Name of the user who performed the grant
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Privilege on the column
GRANTABLE	VARCHAR2 (3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)

See Also: ["USER_COL_PRIVS_MADE"](#) on page 6-71

ALL_COL_PRIVS_RECD

ALL_COL_PRIVS_RECD describes the following types of grants:

- Column object grants for which the current user is the grantee
- Column object grants for which an enabled role or PUBLIC is the grantee

Related View

USER_COL_PRIVS_RECD describes the column object grants for which the current user is the grantee. This view does not display the GRANTEE column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	Name of the user or role to whom access was granted
OWNER	VARCHAR2 (30)	NOT NUL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column

Column	Datatype	NULL	Description
GRANTOR	VARCHAR2 (30)	NOT NULL	Name of the user who performed the grant
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Privilege on the column
GRANTABLE	VARCHAR2 (3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)

See Also: ["USER_COL_PRIVS_REC'D"](#) on page 6-71

ALL_COLL_TYPES

ALL_COLL_TYPES describes all named collection types (varrays and nested tables) accessible to the current user.

Related Views

- DBA_COLL_TYPES describes all named collection types in the database.
- USER_COLL_TYPES describes all named collection types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the collection
TYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the collection
COLL_TYPE	VARCHAR2 (30)	NOT NULL	Description of the collection, such as VARYING ARRAY, [nested] TABLE
UPPER_BOUND	NUMBER		For varrays only, maximum size
ELEM_TYPE_MOD	VARCHAR2 (7)		Type modifier of the element
ELEM_TYPE_OWNER	VARCHAR2 (30)		Owner of the type upon which the collection is based. This value is useful primarily in the case of a user-defined type.
ELEM_TYPE_NAME	VARCHAR2 (30)		Name of the datatype or user-defined type upon which the collection is based
LENGTH	NUMBER		Length of CHAR elements or maximum length of VARCHAR or VARCHAR2 elements
PRECISION	NUMBER		Decimal precision of NUMBER or DECIMAL elements; binary precision of FLOAT elements
SCALE	NUMBER		Scale of NUMBER or DECIMAL elements
CHARACTER_SET_NAME	VARCHAR2 (44)		Name of the character set (CHAR_CS NCHAR_CS)
ELEM_STORAGE	VARCHAR2 (7)		Obsolete column
NULLS_STORED	VARCHAR2 (3)		Obsolete column

ALL_CONS_COLUMNS

ALL_CONS_COLUMNS describes columns that are accessible to the current user and that are specified in constraints.

Related Views

- DBA_CONS_COLUMNS describes all columns in the database that are specified in constraints.
- USER_CONS_COLUMNS describes columns that are owned by the current user and that are specified in constraints.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the constraint definition
CONSTRAINT_NAME	VARCHAR2 (30)	NOT NULL	Name of the constraint definition
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table with the constraint definition
COLUMN_NAME	VARCHAR2 (4000)		Name of the column or attribute of the object type column specified in the constraint definition Note: If you create a constraint on a user-defined REF column, the system creates the constraint on the attributes that make up the REF column. Therefore, the column names displayed in this view are the attribute names, with the REF column name as a prefix, in the following form: "REF_name"."attribute"
POSITION	NUMBER		Original position of the column or attribute in the definition of the object

ALL_CONS_OBJ_COLUMNS

ALL_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in the tables accessible to the current user.

Related Views

- DBA_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in all tables in the database.
- USER_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table containing the object column or attribute
COLUMN_NAME	VARCHAR2 (4000)		Fully qualified name of the object column or attribute
CONS_TYPE_OWNER	VARCHAR2 (30)		Owner of the type that the column (or element) is constrained to
CONS_TYPE_NAME	VARCHAR2 (30)		Name of the type that the column (or element) is constrained to
CONS_TYPE_ONLY	VARCHAR2 (15)		Indicates whether the column (or element) is constrained to ONLY type (Y) or not (N)

See Also:

- ["DBA_CONS_OBJ_COLUMNS"](#) on page 4-64
- ["USER_CONS_OBJ_COLUMNS"](#) on page 6-72

ALL_CONSTRAINTS

ALL_CONSTRAINTS describes constraint definitions on tables accessible to the current user.

Related Views

- `DBA_CONSTRAINTS` describes all constraint definitions in the database.
- `USER_CONSTRAINTS` describes constraint definitions on tables in the current user's schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the constraint definition
CONSTRAINT_NAME	VARCHAR2 (30)	NOT NULL	Name of the constraint definition
CONSTRAINT_TYPE	VARCHAR2 (1)		Type of the constraint definition: ■ C - Check constraint on a table ■ P - Primary key ■ U - Unique key ■ R - Referential integrity ■ V - With check option, on a view ■ O - With read only, on a view ■ H - Hash expression ■ F - Constraint that involves a REF column ■ S - Supplemental logging
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name associated with the table (or view) with the constraint definition
SEARCH_CONDITION	LONG		Text of search condition for a check constraint
R_OWNER	VARCHAR2 (30)		Owner of the table referred to in a referential constraint
R_CONSTRAINT_NAME	VARCHAR2 (30)		Name of the unique constraint definition for the referenced table
DELETE_RULE	VARCHAR2 (9)		Delete rule for a referential constraint: ■ CASCADE ■ SET NULL ■ NO ACTION
STATUS	VARCHAR2 (8)		Enforcement status of the constraint: ■ ENABLED ■ DISABLED
DEFERRABLE	VARCHAR2 (14)		Indicates whether the constraint is deferrable (DEFERRABLE) or not (NOT DEFERRABLE)
DEFERRED	VARCHAR2 (9)		Indicates whether the constraint was initially deferred (DEFERRED) or not (IMMEDIATE)
VALIDATED	VARCHAR2 (13)		When STATUS = ENABLED, possible values are: ■ VALIDATED - All data obeys the constraint (that is, the existing data in the table was validated when the constraint was enabled, as well as any subsequent data entered into the table) ■ NOT VALIDATED - All data may not obey the constraint (that is, the existing data in the table was not validated when the constraint was enabled, but subsequent data entered into the table was validated) When STATUS = DISABLED, possible values are: ■ VALIDATED - All data obeys the constraint, but the unique index on the constraint has been dropped. This setting is useful in data warehousing environments, but has some restrictions. Refer to <i>Oracle Database Data Warehousing Guide</i> for more information on this setting. ■ NOT VALIDATED - All data may not obey the constraint

Column	Datatype	NULL	Description
GENERATED	VARCHAR2 (14)		Indicates whether the name of the constraint is user-generated (USER_NAME) or system-generated (GENERATED_NAME)
BAD	VARCHAR2 (3)		Indicates whether this constraint specifies a century in an ambiguous manner (BAD) or not (NULL). To avoid errors resulting from this ambiguity, rewrite the constraint using the TO_DATE function with a four-digit year. See Also: the TO_DATE function in <i>Oracle Database SQL Language Reference</i> and <i>Oracle Database Advanced Application Developer's Guide</i>
RELY	VARCHAR2 (4)		When VALIDATED = NOT VALIDATED, this column indicates whether the constraint is to be taken into account for query rewrite (RELY) or not (NULL). When VALIDATED = VALIDATED, this column is not meaningful. See Also: <i>constraints</i> in <i>Oracle Database SQL Language Reference</i>
LAST_CHANGE	DATE		When the constraint was last enabled or disabled
INDEX_OWNER	VARCHAR2 (30)		Name of the user owning the index
INDEX_NAME	VARCHAR2 (30)		Name of the index (only shown for unique and primary-key constraints)
INVALID	VARCHAR2 (7)		Indicates whether the constraint is invalid (INVALID) or not (NULL)
VIEW_RELATED	VARCHAR2 (14)		Indicates whether the constraint depends on a view (DEPEND ON VIEW) or not (NULL)

ALL_CONTEXT

ALL_CONTEXT describes all context namespaces in the current session for which attributes and values have been specified using the DBMS_SESSION.SET_CONTEXT procedure. This view does not display the TYPE column.

Related View

DBA_CONTEXT describes all context namespaces defined in the database, regardless whether any attributes have been specified for them using the DBMS_SESSION.SET_CONTEXT procedure.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2 (30)	NOT NULL	Name of the context namespace
SCHEMA	VARCHAR2 (30)	NOT NULL	Schema name of the designated package that can set attributes using this namespace
PACKAGE	VARCHAR2 (30)	NOT NULL	Package name of the designated package that can set attributes using this namespace
TYPE	VARCHAR2 (22)		Type of the context: ■ ACCESSED LOCALLY ■ INITIALIZED EXTERNALLY ■ ACCESSED GLOBALLY ■ INITIALIZED GLOBALLY

ALL_CUBE_ATTR_VISIBILITY

ALL_CUBE_ATTR_VISIBILITY describes the OLAP attributes visible for the dimensions, hierarchies, and levels accessible to the current user.

Related Views

- DBA_CUBE_ATTR_VISIBILITY describes all OLAP attributes visible for the dimensions, hierarchies, and levels in the database.
- USER_CUBE_ATTR_VISIBILITY describes the OLAP attributes visible for the dimensions, hierarchies, and levels owned by the current user. This view does not display the OWNER column.

See Also:

- ["DBA_CUBE_ATTR_VISIBILITY"](#) on page 4-65
- ["USER_CUBE_ATTR_VISIBILITY"](#) on page 6-73

ALL_CUBE_ATTRIBUTES

ALL_CUBE_ATTRIBUTES describes the attributes for the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_ATTRIBUTES describes the attributes for all OLAP cube dimensions in the database.
- USER_CUBE_ATTRIBUTES describes the attributes for the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube dimension (such as TIME)
ATTRIBUTE_NAME	VARCHAR2 (30)	NOT NULL	Name of an attribute of the dimension (such as LONG_DESCRIPTION or END_DATE)
TARGET_DIMENSION_NAME	VARCHAR2 (30)		Name of the target dimension of the attribute
ATTRIBUTE_ROLE	VARCHAR2 (17)		Special role this attribute plays; NULL if none: ■ SHORT_DESCRIPTION ■ LONG_DESCRIPTION ■ DESCRIPTION ■ TIME_SPAN ■ END_DATE
DESCRIPTION	NVARCHAR2 (300)		Description of the attribute in the session language
DATA_TYPE	VARCHAR2 (106)		Data type of the attribute, (such as VARCHAR2 or FLOAT)
DATA_LENGTH	NUMBER	NOT NULL	Length of a text data type
DATA_PRECISION	NUMBER		Precision of a numeric data type
DATA_SCALE	NUMBER		Scale of a numeric data type

See Also:

- ["DBA_CUBE_ATTRIBUTES"](#) on page 4-65
- ["USER_CUBE_ATTRIBUTES"](#) on page 6-73

ALL_CUBE_BUILD_PROCESSES

ALL_CUBE_BUILD_PROCESSES describes the OLAP build processes and maintenance scripts accessible to the current user.

Related Views

- DBA_CUBE_BUILD_PROCESSES describes all OLAP build processes and maintenance scripts in the database.
- USER_CUBE_BUILD_PROCESSES describes the OLAP build processes and maintenance scripts owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the build process
BUILD_PROCESS_NAME	VARCHAR2 (30)	NOT NULL	Name of the build process
BUILD_PROCESS	CLOB		Syntax of the build process
DESCRIPTION	NVARCHAR2 (300)		Description of the build process in the session language

See Also:

- ["DBA_CUBE_BUILD_PROCESSES"](#) on page 4-65
- ["USER_CUBE_BUILD_PROCESSES"](#) on page 6-73

ALL_CUBE_CALCULATED_MEMBERS

ALL_CUBE_CALCULATED_MEMBERS describes the calculated members for the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_CALCULATED_MEMBERS describes the calculated members for all OLAP cube dimensions in the database.
- USER_CUBE_CALCULATED_MEMBERS describes the calculated members for the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube dimension
MEMBER_NAME	VARCHAR2 (30)	NOT NULL	Name of a calculated member in the cube dimension
IS_CUSTOM_AGGREGATE	VARCHAR2 (3)		Indicates whether the calculated member is a custom aggregate (YES) or not (NO)
STORAGE_TYPE	VARCHAR2 (10)		Storage type of the calculated member: ■ DYNAMIC - Value of the member is calculated for a query ■ PRECOMPUTE - Value of the member is calculated and stored during data maintenance
EXPRESSION	CLOB		Expression used to generate the value of the calculated member

See Also:

- ["DBA_CUBE_CALCULATED_MEMBERS"](#) on page 4-66
- ["USER_CUBE_CALCULATED_MEMBERS"](#) on page 6-73

ALL_CUBE_DIM_LEVELS

ALL_CUBE_DIM_LEVELS describes the OLAP dimension levels accessible to the current user.

Related Views

- DBA_CUBE_DIM_LEVELS describes all OLAP dimension levels in the database.
- USER_CUBE_DIM_LEVELS describes the OLAP dimension levels owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a dimension, such as CUSTOMER
LEVEL_NAME	VARCHAR2 (30)	NOT NULL	Name of a level in the dimension, such as WAREHOUSE
DESCRIPTION	NVARCHAR2 (300)		Description of the dimension level in the session language

See Also:

- ["DBA_CUBE_DIM_LEVELS"](#) on page 4-66
- ["USER_CUBE_DIM_LEVELS"](#) on page 6-73

ALL_CUBE_DIM_MODELS

ALL_CUBE_DIM_MODELS describes the models for the OLAP dimensions accessible to the current user.

Related Views

- DBA_CUBE_DIM_MODELS describes the models for all OLAP dimensions in the database.
- USER_CUBE_DIM_MODELS describes the models for the OLAP dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube dimension
MODEL_NAME	VARCHAR2 (30)	NOT NULL	Name of a model for the cube dimension
DESCRIPTION	NVARCHAR2 (300)		Description of the model in the session language

See Also:

- ["DBA_CUBE_DIM_MODELS"](#) on page 4-66
- ["USER_CUBE_DIM_MODELS"](#) on page 6-73

ALL_CUBE_DIM_VIEW_COLUMNS

ALL_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of all OLAP cube dimensions in the database.
- USER_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the cube dimension
DIMENSION_NAME	VARCHAR2 (30)		Name of a cube dimension, such as PRODUCT
VIEW_NAME	VARCHAR2 (30)		Name of a view of the dimension, such as PRODUCT_VIEW
COLUMN_NAME	VARCHAR2 (30)		Name of a column in the view, such as LONG_DESCRIPTION or WAREHOUSE_ID
COLUMN_TYPE	VARCHAR2 (11)		Type of the column: ■ KEY - A key of the dimension view (that is, the dimension value itself) ■ LEVEL_NAME - Name of the level (if any) corresponding to a row in the view ■ DIM_ORDER - A column by which the results may be ordered (if present) ■ MEMBER_TYPE ■ ATTRIBUTE - An attribute owned by the dimension
OBJECT_NAME	VARCHAR2 (30)		Name of the level or attribute represented in the column, such as LONG_DESCRIPTION or WAREHOUSE_ID

See Also:

- ["DBA_CUBE_DIM_VIEW_COLUMNS"](#) on page 4-66
- ["USER_CUBE_DIM_VIEW_COLUMNS"](#) on page 6-74

ALL_CUBE_DIM_VIEWS

ALL_CUBE_DIM_VIEWS describes the relational views of the OLAP dimensions accessible to the current user.

Related Views

- DBA_CUBE_DIM_VIEWS describes the relational views of all OLAP dimensions in the database.
- USER_CUBE_DIM_VIEWS describes the relational views of the OLAP dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube dimension, such as PRODUCT

Column	Datatype	NULL	Description
VIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of a view of the cube dimension, such as PRODUCT_VIEW

See Also:

- ["DBA_CUBE_DIM_VIEWS"](#) on page 4-66
- ["USER_CUBE_DIM_VIEWS"](#) on page 6-74

ALL_CUBE_DIMENSIONALITY

ALL_CUBE_DIMENSIONALITY describes the dimension order for the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBE_DIMENSIONALITY describes the dimension order for all OLAP cubes in the database.
- USER_CUBE_DIMENSIONALITY describes the dimension order for the OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube
CUBE_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube, such as UNITS_CUBE
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a dimension of the cube, such as PRODUCT
ORDER_NUM	NUMBER	NOT NULL	Order number of the dimension in the cube
IS_SPARSE	NUMBER		Indicates whether the dimension is sparse in the cube (1) or not sparse (0)
ET_ATTR_PREFIX	VARCHAR2 (200)		Specifies the prefix that will be added to the column names in the Materialized Views to ensure uniqueness. If the user does not specify an ET_ATTR_PREFIX for any dimensions in a cube, then they default in the pattern D1_, D2_, and so on.

See Also:

- ["DBA_CUBE_DIMENSIONALITY"](#) on page 4-66
- ["USER_CUBE_DIMENSIONALITY"](#) on page 6-74

ALL_CUBE_DIMENSIONS

ALL_CUBE_DIMENSIONS describes the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_DIMENSIONS describes all OLAP cube dimensions in the database.
- USER_CUBE_DIMENSIONS describes the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube dimension

Column	Datatype	NULL	Description
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube dimension, such as TIME
DIMENSION_TYPE	VARCHAR2 (17)		Type of the OLAP cube dimension: - STANDARD - TIME
AW_NAME	VARCHAR2 (30)		Name of the analytic workspace that contains the cube dimension, such as GLOBAL
DEFAULT_HIERARCHY_NAME	VARCHAR2 (30)		Name of the default hierarchy for the cube dimension, such as FISCAL
DESCRIPTION	NVARCHAR2 (300)		Description of the cube dimension in the session language

See Also:

- ["DBA_CUBE_DIMENSIONS"](#) on page 4-66
- ["USER_CUBE_DIMENSIONS"](#) on page 6-74

ALL_CUBE_HIER_LEVELS

ALL_CUBE_HIER_LEVELS describes the hierarchy levels for the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_HIER_LEVELS describes the hierarchy levels for all OLAP cube dimensions in the database.
- USER_CUBE_HIER_LEVELS describes the hierarchy levels for the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube dimension, such as TIME
HIERARCHY_NAME	VARCHAR2 (30)	NOT NULL	Name of a hierarchy for the dimension, such as CALENDAR
LEVEL_NAME	VARCHAR2 (30)	NOT NULL	Name of the dimension level, such as MONTH
ORDER_NUM	NUMBER	NOT NULL	Order number of the level within the hierarchy; 0 is the top level
DESCRIPTION	NVARCHAR2 (300)		Description of the level in the session language

See Also:

- ["DBA_CUBE_HIER_LEVELS"](#) on page 4-66
- ["USER_CUBE_HIER_LEVELS"](#) on page 6-74

ALL_CUBE_HIER_VIEW_COLUMNS

ALL_CUBE_HIER_VIEW_COLUMNS describes the columns of the relational hierarchy views of the OLAP cube dimensions accessible to the current user.

Related Views

- `DBA_CUBE_HIER_VIEW_COLUMNS` describes the columns of the relational hierarchy views of all OLAP cube dimensions in the database.
- `USER_CUBE_HIER_VIEW_COLUMNS` describes the columns of the relational hierarchy views of the OLAP cube dimensions owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>		Owner of the cube dimension
<code>DIMENSION_NAME</code>	<code>VARCHAR2 (30)</code>		Name of a cube dimension, such as <code>TIME</code>
<code>HIERARCHY_NAME</code>	<code>VARCHAR2 (30)</code>		Name of a hierarchy for the cube dimension, such as <code>CALENDAR</code>
<code>VIEW_NAME</code>	<code>VARCHAR2 (30)</code>		Name of a view of the hierarchy, such as <code>TIME_CALENDAR_VIEW</code>
<code>COLUMN_NAME</code>	<code>VARCHAR2 (30)</code>		Name of a column in the view, such as <code>CALENDAR_QUARTER</code> or <code>PARENT</code>
<code>COLUMN_TYPE</code>	<code>VARCHAR2 (11)</code>		Type of the column: ■ <code>KEY</code> - A key of the hierarchy view (that is, the hierarchy value itself) ■ <code>PARENT</code> - Dimension value of the parent of the current row in the view (or <code>NULL</code> if no parent) ■ <code>LEVEL_NAME</code> - Name of the level (if any) corresponding to a row in the view ■ <code>DEPTH</code> - Depth in the hierarchy tree of the current row in the view ■ <code>HIER_ORDER</code> - A column by which the results may be ordered (if present) ■ <code>MEMBER_TYPE</code> ■ <code>ATTRIBUTE</code> - An attribute owned by the hierarchy ■ <code>LEVEL</code> - One of the level columns comprising the hierarchy
<code>OBJECT_NAME</code>	<code>VARCHAR2 (30)</code>		Name of a level or attribute for the dimension

See Also:

- ["DBA_CUBE_HIER_VIEW_COLUMNS" on page 4-67](#)
- ["USER_CUBE_HIER_VIEW_COLUMNS" on page 6-74](#)

ALL_CUBE_HIER_VIEWS

`ALL_CUBE_HIER_VIEWS` describes the hierarchies for the OLAP cube dimensions accessible to the current user.

Related Views

- `DBA_CUBE_HIER_VIEWS` describes the hierarchies for all OLAP cube dimensions in the database.
- `USER_CUBE_HIER_VIEWS` describes the hierarchies for the OLAP cube dimensions owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	<code>NOT NULL</code>	Owner of the cube dimension

Column	Datatype	NULL	Description
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube dimension, such as TIME
HIERARCHY_NAME	VARCHAR2 (30)	NOT NULL	Name of a hierarchy for the cube dimension, such as CALENDAR
VIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of a view of the hierarchy, such as TIME_CALENDAR_VIEW

See Also:

- ["DBA_CUBE_HIER_VIEWS"](#) on page 4-67
- ["USER_CUBE_HIER_VIEWS"](#) on page 6-74

ALL_CUBE_HIERARCHIES

ALL_CUBE_HIERARCHIES describes the OLAP dimension hierarchies accessible to the current user.

Related Views

- DBA_CUBE_HIERARCHIES describes all OLAP dimension hierarchies in the database.
- USER_CUBE_HIERARCHIES describes the OLAP dimension hierarchies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of a dimension, such as TIME
HIERARCHY_NAME	VARCHAR2 (30)	NOT NULL	Name of a hierarchy for the dimension, such as CALENDAR
HIERARCHY_TYPE	VARCHAR2 (5)		Type of the hierarchy: ■ LEVEL ■ VALUE
DESCRIPTION	NVARCHAR2 (300)		Description of the hierarchy in the session language
IS_RAGGED	NUMBER		Indicates whether ragged hierarchies are permitted in subsequent builds. User dimensions that are enabled for materialized views and Time dimensions are set to 0. Builds then check the data for ragged hierarchies and fail if one is detected. When User dimensions are set to 1, the builds do not check for ragged hierarchies.
IS_SKIP_LEVEL	NUMBER		Indicates whether skip-level hierarchies are permitted in subsequent builds. User dimensions that are enabled for materialized views and Time dimensions are set to 0. Builds then check the data for skip-level hierarchies and fail if one is detected. When User dimensions are set to 1, the builds do not check for skip-level hierarchies.

See Also:

- ["DBA_CUBE_HIERARCHIES"](#) on page 4-67
- ["USER_CUBE_HIERARCHIES"](#) on page 6-74

ALL_CUBE_MEASURES

ALL_CUBE_MEASURES describes the measures for the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBE_MEASURES describes the measures for all OLAP cubes in the database.
- USER_CUBE_MEASURES describes the measures for the OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube
CUBE_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube, such as UNITS_CUBE
MEASURE_NAME	VARCHAR2 (30)	NOT NULL	Name of a measure in the cube, such as SALES
OVERRIDE_SOLVE_SPEC	CLOB		Syntax text for the measure's consistent solve specification that overrides that of its cube
MEASURE_TYPE	VARCHAR2 (7)		Type of the OLAP measure: ■ BASE - Base measures store the data ■ DERIVED - Derived measures calculate the data from base measures; also called calculated measures
EXPRESSION	CLOB		Expression that provides the values of the measure
DESCRIPTION	NVARCHAR2 (300)		Description of the measure in the session language
DATA_TYPE	VARCHAR2 (106)		Data type of the measure, such as NUMBER
DATA_LENGTH	NUMBER	NOT NULL	Length of a character data type
DATA_PRECISION	NUMBER		Precision of a numeric data type
DATA_SCALE	NUMBER		Scale of a numeric data type

See Also:

- ["DBA_CUBE_MEASURES"](#) on page 4-67
- ["USER_CUBE_MEASURES"](#) on page 6-74

ALL_CUBE_VIEW_COLUMNS

ALL_CUBE_VIEW_COLUMNS describes the columns of the relational views of the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBE_VIEW_COLUMNS describes the columns of relational views of all OLAP cubes in the database.
- USER_CUBE_VIEW_COLUMNS describes the columns of relational views of OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the cube
CUBE_NAME	VARCHAR2 (30)		Name of a cube, such as UNITS_CUBE
VIEW_NAME	VARCHAR2 (30)		Name of a view of the cube, such as PRODUCT_VIEW

Column	Datatype	NULL	Description
COLUMN_NAME	VARCHAR2 (30)		Name of a column in the view, such as DIM_KEY or LEVEL_NAME
COLUMN_TYPE	VARCHAR2 (7)		Type of the column: - MEASURE - KEY
OBJECT_NAME	VARCHAR2 (30)		Name of the measure or dimension represented in the column

See Also:

- ["DBA_CUBE_VIEW_COLUMNS"](#) on page 4-67
- ["USER_CUBE_VIEW_COLUMNS"](#) on page 6-75

ALL_CUBE_VIEWS

ALL_CUBE_VIEWS describes the relational views of the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBE_VIEWS describes the relational views of all OLAP cubes in the database.
- USER_CUBE_VIEWS describes the relational views of the OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube
CUBE_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube, such as UNITS_CUBE
VIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of a view of the cube, such as UNITS_CUBE_VIEW

See Also:

- ["DBA_CUBE_VIEWS"](#) on page 4-67
- ["USER_CUBE_VIEWS"](#) on page 6-75

ALL_CUBES

ALL_CUBES describes the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBES describes all OLAP cubes in the database.
- USER_CUBES describes the OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the cube
CUBE_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube, such as UNITS_CUBE
AW_NAME	VARCHAR2 (30)		Name of the analytic workspace that contains the cube, such as GLOBAL

ALL_DB_LINKS

Column	Datatype	NULL	Description
CONSISTENT_SOLVE_SPEC	CLOB		Default aggregation rules for the cube
DESCRIPTION	NVARCHAR2 (300)		Description of the cube in the session language
SPARSE_TYPE	VARCHAR2 (200)		Text value indicating the type of sparsity for the OLAP cube
PRECOMPUTE_CONDITION	CLOB		Condition syntax representing the precompute condition of the OLAP cube
PRECOMPUTE_PERCENT	NUMBER		Percentage of aggregate data values that are calculated and stored during data maintenance. If the cube is partitioned, then this percentage is for the bottom partitions.
PRECOMPUTE_PERCENT_TOP	NUMBER		Percentage of aggregate data values in the top partition that are calculated and stored during data maintenance
PARTITION_DIMENSION_NAME	VARCHAR2 (30)		Name of the dimension used to partition the cube, such as TIME
PARTITION_HIERARCHY_NAME	VARCHAR2 (30)		Name of the dimension hierarchy used to partition the cube, such as CALENDAR
PARTITION_LEVEL_NAME	VARCHAR2 (30)		Name of the level used to partition the cube, such as QUARTER

See Also:

- ["DBA_CUBES"](#) on page 4-67
- ["USER_CUBES"](#) on page 6-75

ALL_DB_LINKS

ALL_DB_LINKS describes the database links accessible to the current user.

Related Views

- DBA_DB_LINKS describes all database links in the database.
- USER_DB_LINKS describes the database links owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the database link
DB_LINK	VARCHAR2 (128)	NOT NULL	Name of the database link
USERNAME	VARCHAR2 (30)		Name of the user when logging in
HOST	VARCHAR2 (2000)		Oracle Net connect string
CREATED	DATE	NOT NULL	Creation time of the database link

See Also:

- ["DBA_DB_LINKS"](#) on page 4-69
- ["USER_DB_LINKS"](#) on page 6-75

ALL_DEF_AUDIT_OPTS

ALL_DEF_AUDIT_OPTS contains default object-auditing options that will be applied when objects are created. The output for each column takes one of the following forms:

- - / -: no default auditing

- S/-: auditing whenever successful
- -/S: auditing whenever not successful

Column	Datatype	NULL	Description
ALT	VARCHAR2 (3)		Auditing ALTER WHENEVER SUCCESSFUL / UNSUCCESSFUL
AUD	VARCHAR2 (3)		Auditing AUDIT WHENEVER SUCCESSFUL / UNSUCCESSFUL
COM	VARCHAR2 (3)		Auditing COMMENT WHENEVER SUCCESSFUL / UNSUCCESSFUL
DEL	VARCHAR2 (3)		Auditing DELETE WHENEVER SUCCESSFUL / UNSUCCESSFUL
GRA	VARCHAR2 (3)		Auditing GRANT WHENEVER SUCCESSFUL / UNSUCCESSFUL
IND	VARCHAR2 (3)		Auditing INDEX WHENEVER SUCCESSFUL / UNSUCCESSFUL
INS	VARCHAR2 (3)		Auditing INSERT WHENEVER SUCCESSFUL / UNSUCCESSFUL
LOC	VARCHAR2 (3)		Auditing LOCK WHENEVER SUCCESSFUL / UNSUCCESSFUL
REN	VARCHAR2 (3)		Auditing RENAME WHENEVER SUCCESSFUL / UNSUCCESSFUL
SEL	VARCHAR2 (3)		Auditing SELECT WHENEVER SUCCESSFUL / UNSUCCESSFUL
UPD	VARCHAR2 (3)		Auditing UPDATE WHENEVER SUCCESSFUL / UNSUCCESSFUL
REF	CHAR (3)		This column is obsolete and maintained for backward compatibility. The value of this column is always -/-
EXE	VARCHAR2 (3)		Auditing EXECUTE WHENEVER SUCCESSFUL / UNSUCCESSFUL
FBK	VARCHAR2 (3)		Auditing FLASHBACK WHENEVER SUCCESSFUL / UNSUCCESSFUL
REA	VARCHAR2 (3)		Auditing READ WHENEVER SUCCESSFUL / UNSUCCESSFUL

ALL_DEPENDENCIES

ALL_DEPENDENCIES describes dependencies between procedures, packages, functions, package bodies, and triggers accessible to the current user, including dependencies on views created without any database links. This view does not display the SCHEMAID column.

Related Views

- DBA_DEPENDENCIES describes all dependencies between objects in the database. This view does not display the SCHEMAID column.
- USER_DEPENDENCIES describes dependencies between objects in the current user's schema. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
NAME	VARCHAR2 (30)	NOT NULL	Name of the object
TYPE	VARCHAR2 (17)		Type of the object

Column	Datatype	NULL	Description
REFERENCED_OWNER	VARCHAR2 (30)		Owner of the referenced object (remote owner if remote object)
REFERENCED_NAME	VARCHAR2 (64)		Name of the referenced object
REFERENCED_TYPE	VARCHAR2 (17)		Type of the referenced object
REFERENCED_LINK_NAME	VARCHAR2 (128)		Name of the link to the parent object (if remote)
SCHEMAID	NUMBER		ID of the current schema
DEPENDENCY_TYPE	VARCHAR2 (4)		Indicates whether the dependency is a REF dependency (REF) or not (HARD)

ALL_DEQUEUE_QUEUES

ALL_DEQUEUE_QUEUES describes all queues on which the current user has dequeue privileges. If the user has any Advanced Queuing system privileges, such as DEQUEUE ANY QUEUE or MANAGE ANY QUEUE, then this view describes all queues in the database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the queue
NAME	VARCHAR2 (30)	NOT NULL	Name of the queue
QUEUE_TABLE	VARCHAR2 (30)	NOT NULL	Name of the table in which the queue data resides
QID	NUMBER	NOT NULL	Object number of the queue
QUEUE_TYPE	VARCHAR2 (20)		Type of the queue: ■ EXCEPTION_QUEUE ■ NORMAL_QUEUE
MAX_RETRIES	NUMBER		Maximum number of retries allowed when dequeuing from the queue
RETRY_DELAY	NUMBER		Time interval between retries
ENQUEUE_ENABLED	VARCHAR2 (7)		Indicates whether the queue is enabled for enqueue (YES) or not (NO)
DEQUEUE_ENABLED	VARCHAR2 (7)		Indicates whether the queue is enabled for dequeue (YES) or not (NO)
RETENTION	VARCHAR2 (40)		Time interval that processed messages are retained in the queue, or FOREVER
USER_COMMENT	VARCHAR2 (50)		User-specified comment
NETWORK_NAME	VARCHAR2 (512)		Network name of the queue service

ALL_DIM_ATTRIBUTES

ALL_DIM_ATTRIBUTES describes the relationship between a dimension level and a functionally dependent column. The level columns and the dependent column must be in the same table.

Related Views

- DBA_DIM_ATTRIBUTES describes all such dimension relationships in the database.
- USER_DIM_ATTRIBUTES describes all such dimension attributes in the current user's schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of the dimension
ATTRIBUTE_NAME	VARCHAR2 (30)		Name of the attribute
LEVEL_NAME	VARCHAR2 (30)		Name of the hierarchy level
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Dependent column name
INFERRED	CHAR (1)		Indicates whether the attribute is inferred from a JOIN KEY specification (Y) or not (N)

ALL_DIM_CHILD_OF

ALL_DIM_CHILD_OF describes hierarchical relationships of 1 to n between the pairs of levels in the dimensions accessible to the current user.

Related Views

- DBA_DIM_CHILD_OF describes all such hierarchical relationships in the database.
- USER_DIM_CHILD_OF describes all such hierarchical attributes in the current user's schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of the dimension
HIERARCHY_NAME	VARCHAR2 (30)		Hierarchy name
POSITION	NUMBER	NOT NULL	Hierarchical position within this hierarchy, position 1 being the most detailed
CHILD_LEVEL_NAME	VARCHAR2 (30)		Child side of 1:n relationship
JOIN_KEY_ID	VARCHAR2 (40)		If non-null, then the child joins to the parent
PARENT_LEVEL_NAME	VARCHAR2 (30)		Parent side of 1:n relationship in relation to the CHILD_LEVEL_NAME

ALL_DIM_HIERARCHIES

ALL_DIM_HIERARCHIES describes all dimension hierarchies accessible to the current user.

Related Views

- DBA_DIM_HIERARCHIES describes all such hierarchies in the database.
- USER_DIM_HIERARCHIES describes all such hierarchies owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of the dimension
HIERARCHY_NAME	VARCHAR2 (30)		Hierarchy name

ALL_DIM_JOIN_KEY

ALL_DIM_JOIN_KEY describes the joins between two dimension tables that are accessible to the current user. The join is always specified between a parent dimension level column and a child column.

Related Views

- DBA_DIM_JOIN_KEY describes all such joins in the database.
- USER_DIM_JOIN_KEY describes all such joins owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of the dimension
DIM_KEY_ID	NUMBER	NOT NULL	Join key ID (unique within a dimension)
LEVEL_NAME	VARCHAR2 (30)		Name of the hierarchy level
KEY_POSITION	NUMBER	NOT NULL	Ordinal position of the key column within the level
HIERARCHY_NAME	VARCHAR2 (30)		Name of the hierarchy
CHILD_JOIN_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the join column table
CHILD_JOIN_TABLE	VARCHAR2 (30)	NOT NULL	Name of the join column table
CHILD_JOIN_COLUMN	VARCHAR2 (30)	NOT NULL	Name of the join column
CHILD_LEVEL_NAME	VARCHAR2 (30)		Name of the child hierarchy level of the join key

ALL_DIM_LEVEL_KEY

ALL_DIM_LEVEL_KEY describes a column of a dimension level accessible to the current user. The position of a column within a level is specified by KEY_POSITION.

Related Views

- DBA_DIM_LEVEL_KEY describes all columns of dimension levels in the database.
- USER_DIM_LEVEL_KEY describes all columns of dimension levels owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of the dimension
LEVEL_NAME	VARCHAR2 (30)		Name of the hierarchy level
KEY_POSITION	NUMBER	NOT NULL	Ordinal position of the key column within the level
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the key column

ALL_DIM_LEVELS

ALL_DIM_LEVELS describes the dimension levels accessible to the current user. All columns of a dimension level must come from the same relation.

Related Views

- DBA_DIM_LEVELS describes all dimension levels in the database.
- USER_DIM_LEVELS describes the levels of all dimensions owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of the dimension
LEVEL_NAME	VARCHAR2 (30)		Unique within a dimension
NUM_COLUMNS	NUMBER		Number of columns in the level definition
DETAILOBJ_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the detail object that the keys of this level come from
DETAILOBJ_NAME	VARCHAR2 (30)	NOT NULL	Name of the table that the keys of this level come from
SKIP_WHEN_NULL	VARCHAR2 (1)		Indicates whether the level is declared with the SKIP WHEN NULL clause (Y) or not (N)

ALL_DIMENSIONS

ALL_DIMENSIONS describes the dimension objects accessible to the current user.

Related Views

- DBA_DIMENSIONS describes all dimensions in the database.
- USER_DIMENSIONS describes the dimensions in the current user's schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2 (30)	NOT NULL	Name of the dimension
INVALID	VARCHAR2 (1)		Indicates whether the dimension is invalid (Y) or valid (N)
COMPILE_STATE	VARCHAR2 (13)		Compile status of the dimension: ■ INVALID ■ NEEDS_COMPILE ■ ERROR
REVISION	NUMBER		Dimension revision level

ALL_DIRECTORIES

ALL_DIRECTORIES describes all directories accessible to the current user.

Related View

DBA_DIRECTORIES describes all directories in the database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the directory (always SYS)
DIRECTORY_NAME	VARCHAR2 (30)	NOT NULL	Name of the directory
DIRECTORY_PATH	VARCHAR2 (4000)		Operating system pathname for the directory

ALL_EDITION_COMMENTS

ALL_EDITION_COMMENTS describes the comments on the editions accessible to the current user.

Related View

DBA_EDITION_COMMENTS describes the comments on all editions in the database.

Column	Datatype	NULL	Description
EDITION_NAME	VARCHAR2 (30)	NOT NULL	Name of the edition
COMMENTS	VARCHAR2 (4000)		Edition comments

See Also: ["DBA_EDITION_COMMENTS"](#) on page 4-72

ALL_EDITIONING_VIEW_COLS

ALL_EDITIONING_VIEW_COLS describes the relationship between the columns of the editioning views accessible to the current user and the table columns to which they map.

Related Views

- DBA_EDITIONING_VIEW_COLS describes the relationship between the columns of all editioning views in the database and the table columns to which they map.
- USER_EDITIONING_VIEW_COLS describes the relationship between the columns of the editioning views owned by the current user and the table columns to which they map. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of an editioning view
VIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of an editioning view
VIEW_COLUMN_ID	NUMBER	NOT NULL	Column number within the editioning view
VIEW_COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column in the editioning view
TABLE_COLUMN_ID	NUMBER	NOT NULL	Column number of a table column to which this editioning view column maps
TABLE_COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of a table column to which this editioning view column maps

See Also:

- ["DBA_EDITIONING_VIEW_COLS"](#) on page 4-72
- ["USER_EDITIONING_VIEW_COLS"](#) on page 6-76

ALL_EDITIONING_VIEW_COLS_AE

ALL_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of the editioning views (across all editions) accessible to the current user and the table columns to which they map.

Related Views

- DBA_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of all editioning views (across all editions) in the database and the table columns to which they map.
- USER_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of the editioning views (across all editions) owned by the current user and the table columns to which they map. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of an editioning view
VIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of an editioning view
VIEW_COLUMN_ID	NUMBER	NOT NULL	Column number within the editioning view
VIEW_COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column in the editioning view
TABLE_COLUMN_ID	NUMBER	NOT NULL	Column number of a table column to which this editioning view column maps
TABLE_COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of a table column to which this editioning view column maps
EDITION_NAME	VARCHAR2 (30)		Name of the application edition where the editioning view is defined

See Also:

- ["DBA_EDITIONING_VIEW_COLS_AE"](#) on page 4-72
- ["USER_EDITIONING_VIEW_COLS_AE"](#) on page 6-77

ALL_EDITIONING_VIEWS

ALL_EDITIONING_VIEWS describes the editioning views accessible to the current user.

Related Views

- DBA_EDITIONING_VIEWS describes all editioning views in the database.
- USER_EDITIONING_VIEWS describes the editioning views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of an editioning view
VIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of an editioning view
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of an editioning view's base table

See Also:

- ["DBA_EDITIONING_VIEWS"](#) on page 4-73
- ["USER_EDITIONING_VIEWS"](#) on page 6-77

ALL_EDITIONING_VIEWS_AE

ALL_EDITIONING_VIEWS_AE describes the editioning views (across all editions) accessible to the current user.

Related Views

- DBA_EDITIONING_VIEWS_AE describes all editioning views (across all editions) in the database.
- USER_EDITIONING_VIEWS_AE describes the editioning views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of an editioning view
VIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of an editioning view
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of an editioning view's base table
EDITION_NAME	VARCHAR2 (30)		Name of the application edition where the editioning view is defined

See Also:

- ["DBA_EDITIONING_VIEWS_AE"](#) on page 4-73
- ["USER_EDITIONING_VIEWS_AE"](#) on page 6-77

ALL_EDITIONS

ALL_EDITIONS describes the editions accessible to the current user.

Related View

DBA_EDITIONS describes all editions in the database.

Column	Datatype	NULL	Description
EDITION_NAME	VARCHAR2 (30)	NOT NULL	Name of the edition
PARENT_EDITION_NAME	VARCHAR2 (30)		Name of the parent edition for this edition
USABLE	VARCHAR2 (3)		Indicates whether the edition is usable (YES) or unusable (NO)

See Also: ["DBA_EDITIONS"](#) on page 4-73

ALL_ENCRYPTED_COLUMNS

ALL_ENCRYPTED_COLUMNS displays encryption algorithm information for the encrypted columns in the tables accessible to the current user.

Related Views

- DBA_ENCRYPTED_COLUMNS displays encryption algorithm information for all encrypted columns in the database.
- USER_ENCRYPTED_COLUMNS displays encryption algorithm information for the encrypted columns in the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column
ENCRYPTION_ALG	VARCHAR2 (29)		Encryption algorithm used to protect secrecy of data in this column: ■ 3 Key Triple DES 168 bits key ■ AES 128 bits key ■ AES 192 bits key ■ AES 256 bits key

Column	Datatype	NULL	Description
SALT	VARCHAR2 (3)		Indicates whether the column is encrypted with SALT (YES) or not (NO)
INTEGRITY_ALG	VARCHAR2 (12)		Integrity algorithm used for the column: ■ SHA-1 ■ NOMAC

ALL_ERRORS

ALL_ERRORS describes the current errors on the stored objects accessible to the current user.

Related Views

- DBA_ERRORS describes the current errors on all stored objects in the database.
- USER_ERRORS describes the current errors on the stored objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
NAME	VARCHAR2 (30)	NOT NULL	Name of the object
TYPE	VARCHAR2 (12)		Type of the object: ■ VIEW ■ PROCEDURE ■ FUNCTION ■ PACKAGE ■ PACKAGE BODY ■ TRIGGER ■ TYPE ■ TYPE BODY ■ LIBRARY ■ JAVA SOURCE ■ JAVA CLASS ■ DIMENSION
SEQUENCE	NUMBER	NOT NULL	Sequence number (for ordering purposes)
LINE	NUMBER	NOT NULL	Line number at which the error occurred
POSITION	NUMBER	NOT NULL	Position in the line at which the error occurred
TEXT	VARCHAR2 (4000)	NOT NULL	Text of the error
ATTRIBUTE	VARCHAR2 (9)		Indicates whether the error is an error (ERROR) or a warning (WARNING)
MESSAGE_NUMBER	NUMBER		Numeric error number (without any prefix)

See Also:

- ["DBA_ERRORS"](#) on page 4-74
- ["USER_ERRORS"](#) on page 6-77

ALL_ERRORS_AE

ALL_ERRORS_AE describes the current errors on the stored objects (across all editions) accessible to the current user.

Related Views

- DBA_ERRORS_AE describes the current errors on all stored objects (across all editions) in the database.
- USER_ERRORS_AE describes the current errors on the stored objects (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
NAME	VARCHAR2 (30)	NOT NULL	Name of the object
TYPE	VARCHAR2 (12)		Type of the object: ■ TYPE ■ TYPE BODY ■ VIEW ■ PROCEDURE ■ FUNCTION ■ PACKAGE ■ PACKAGE BODY ■ TRIGGER ■ JAVA SOURCE ■ JAVA CLASS
SEQUENCE	NUMBER	NOT NULL	Sequence number (for ordering purposes)
LINE	NUMBER	NOT NULL	Line number at which this error occurred
POSITION	NUMBER	NOT NULL	Position in the line at which this error occurred
TEXT	VARCHAR2 (4000)	NOT NULL	Text of the error
ATTRIBUTE	VARCHAR2 (9)		Indicates whether the error is an error (ERROR) or a warning (WARNING)
MESSAGE_NUMBER	NUMBER		Numeric error number (without any prefix)
EDITION_NAME	VARCHAR2 (30)		Name of the edition in which the object is actual

See Also:

- ["DBA_ERRORS_AE"](#) on page 4-74
- ["USER_ERRORS_AE"](#) on page 6-77

ALL_EVALUATION_CONTEXT_TABLES

ALL_EVALUATION_CONTEXT_TABLES describes the tables in the rule evaluation contexts accessible to the current user.

Related Views

- DBA_EVALUATION_CONTEXT_TABLES describes the tables in all rule evaluation contexts in the database.

- `USER_EVALUATION_CONTEXT_TABLES` describes the tables in the rule evaluation contexts owned by the current user. This view does not display the `EVALUATION_CONTEXT_OWNER` column.

Column	Datatype	NULL	Description
<code>EVALUATION_CONTEXT_OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the evaluation context
<code>EVALUATION_CONTEXT_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the evaluation context
<code>TABLE_ALIAS</code>	<code>VARCHAR2 (30)</code>		Alias for a table in the evaluation context
<code>TABLE_NAME</code>	<code>VARCHAR2 (4000)</code>		Name of the table referred to by the table alias

See Also:

- ["DBA_EVALUATION_CONTEXT_TABLES"](#) on page 4-74
- ["USER_EVALUATION_CONTEXT_TABLES"](#) on page 6-78

ALL_EVALUATION_CONTEXT_VARS

`ALL_EVALUATION_CONTEXT_VARS` describes the variables in the rule evaluation contexts accessible to the current user.

Related Views

- `DBA_EVALUATION_CONTEXT_VARS` describes the variables in all rule evaluation contexts in the database.
- `USER_EVALUATION_CONTEXT_VARS` describes the variables in the rule evaluation contexts owned by the current user. This view does not display the `EVALUATION_CONTEXT_OWNER` column.

Column	Datatype	NULL	Description
<code>EVALUATION_CONTEXT_OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the evaluation context
<code>EVALUATION_CONTEXT_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the evaluation context
<code>VARIABLE_NAME</code>	<code>VARCHAR2 (30)</code>		Name of a variable in the evaluation context
<code>VARIABLE_TYPE</code>	<code>VARCHAR2 (4000)</code>		Datatype of the variable
<code>VARIABLE_VALUE_FUNCTION</code>	<code>VARCHAR2 (4000)</code>		Function used to retrieve the value of the variable; NULL for variables that are not implicit
<code>VARIABLE_METHOD_FUNCTION</code>	<code>VARCHAR2 (228)</code>		Function used to retrieve the result of method invocation on the variable. Such a function can speed up evaluation, if there are many simple rules that invoke the method on the variable.

See Also:

- ["DBA_EVALUATION_CONTEXT_VARS"](#) on page 4-75
- ["USER_EVALUATION_CONTEXT_VARS"](#) on page 6-78

ALL_EVALUATION_CONTEXTS

`ALL_EVALUATION_CONTEXTS` describes the rule evaluation contexts accessible to the current user.

Related Views

- `DBA_EVALUATION_CONTEXTS` describes all rule evaluation contexts in the database.
- `USER_EVALUATION_CONTEXTS` describes the rule evaluation contexts owned by the current user. This view does not display the `EVALUATION_CONTEXT_OWNER` column.

Column	Datatype	NULL	Description
<code>EVALUATION_CONTEXT_OWNER</code>	<code>VARCHAR2(30)</code>	NOT NULL	Owner of the evaluation context
<code>EVALUATION_CONTEXT_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the evaluation context
<code>EVALUATION_FUNCTION</code>	<code>VARCHAR2(4000)</code>		Evaluation function associated with the evaluation context, if any
<code>EVALUATION_CONTEXT_COMMENT</code>	<code>VARCHAR2(4000)</code>		Comment specified with the evaluation context, if any

See Also:

- ["DBA_EVALUATION_CONTEXTS"](#) on page 4-75
- ["USER_EVALUATION_CONTEXTS"](#) on page 6-78

ALL_EXTERNAL_LOCATIONS

`ALL_EXTERNAL_LOCATIONS` describes the locations (data sources) of the external tables accessible to the current user.

Related Views

- `DBA_EXTERNAL_LOCATIONS` describes the locations (data sources) of all external tables in the database.
- `USER_EXTERNAL_LOCATIONS` describes the locations (data sources) of the external tables owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2(30)</code>	NOT NULL	Owner of the external table location
<code>TABLE_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the corresponding external table
<code>LOCATION</code>	<code>VARCHAR2(4000)</code>		External table location clause
<code>DIRECTORY_OWNER</code>	<code>CHAR(3)</code>		Owner of the directory containing the external table location
<code>DIRECTORY_NAME</code>	<code>VARCHAR2(30)</code>		Name of the directory containing the external table location

See Also:

- ["DBA_EXTERNAL_LOCATIONS"](#) on page 4-76
- ["USER_EXTERNAL_LOCATIONS"](#) on page 6-78

ALL_EXTERNAL_TABLES

`ALL_EXTERNAL_TABLES` describes the external tables accessible to the current user.

Related Views

- `DBA_EXTERNAL_TABLES` describes all external tables in the database.
- `USER_EXTERNAL_TABLES` describes the external tables owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2(30)</code>	NOT NULL	Owner of the external table
<code>TABLE_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the external table
<code>TYPE_OWNER</code>	<code>CHAR(3)</code>		Owner of the implementation type for the external table access driver
<code>TYPE_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the implementation type for the external table access driver
<code>DEFAULT_DIRECTORY_OWNER</code>	<code>CHAR(3)</code>		Owner of the default directory for the external table
<code>DEFAULT_DIRECTORY_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the default directory for the external table
<code>REJECT_LIMIT</code>	<code>VARCHAR2(40)</code>		Reject limit for the external table, or <code>UNLIMITED</code>
<code>ACCESS_TYPE</code>	<code>VARCHAR2(7)</code>		Type of access parameters for the external table: ■ <code>BLOB</code> ■ <code>CLOB</code>
<code>ACCESS_PARAMETERS</code>	<code>CLOB</code>		Access parameters for the external table
<code>PROPERTY</code>	<code>VARCHAR2(10)</code>		Property of the external table: ■ <code>REFERENCED</code> - Referenced columns ■ <code>ALL</code> - All columns

See Also:

- ["DBA_EXTERNAL_TABLES"](#) on page 4-76
- ["USER_EXTERNAL_TABLES"](#) on page 6-78

ALL_FILE_GROUP_EXPORT_INFO

`ALL_FILE_GROUP_EXPORT_INFO` shows export-related information for each version accessible to the current user. There will only be information in this view for versions that have a valid Data Pump dump file.

Related Views

- `DBA_FILE_GROUP_EXPORT_INFO` shows export-related information for each version in the database that has a valid Data Pump dump file.
- `USER_FILE_GROUP_EXPORT_INFO` shows export-related information for all file groups owned by the current user. This view does not display the `FILE_GROUP_OWNER` column.

Column	Datatype	NULL	Description
<code>FILE_GROUP_OWNER</code>	<code>VARCHAR2(30)</code>	NOT NULL	Owner of the file group
<code>FILE_GROUP_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the file group
<code>VERSION_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	User-specified name for the version
<code>VERSION</code>	<code>NUMBER</code>	NOT NULL	Internal version number
<code>EXPORT_VERSION</code>	<code>VARCHAR2(30)</code>	NOT NULL	Version of exported objects

Column	Datatype	NULL	Description
PLATFORM_NAME	VARCHAR2 (101)	NOT NULL	Platform on which the export was performed
EXPORT_TIME	DATE	NOT NULL	Time at which the export job was performed
EXPORT_SCN	NUMBER		SCN of the export job
SOURCE_GLOBAL_NAME	VARCHAR2 (128)		Global name of the exporting database

ALL_FILE_GROUP_FILES

ALL_FILE_GROUP_FILES shows the file set for each versioned file group accessible to the current user.

Related Views

- DBA_FILE_GROUP_FILES shows the file set for each versioned group in the database.
- USER_FILE_GROUP_FILES shows the file set for each versioned group owned by the current user. This view does not display the FILE_GROUP_OWNER column.

Column	Datatype	NULL	Description
FILE_GROUP_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the file group
FILE_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the file group
VERSION_NAME	VARCHAR2 (30)	NOT NULL	Name of the version to which the file belongs
VERSION	NUMBER	NOT NULL	Internal version number of the file group version to which the file belongs
FILE_NAME	VARCHAR2 (512)	NOT NULL	Name of the file
FILE_DIRECTORY	VARCHAR2 (30)	NOT NULL	Directory object for the directory where the file is stored
FILE_TYPE	VARCHAR2 (32)		User-specified file type
FILE_SIZE	NUMBER		Size of the file
FILE_BLOCK_SIZE	NUMBER		Block size for the file
COMMENTS	VARCHAR2 (4000)		Comments about the file group

ALL_FILE_GROUP_TABLES

ALL_FILE_GROUP_TABLES shows information about the tables accessible to the current user that can be imported using the file set.

Related Views

- DBA_FILE_GROUP_TABLES shows information about all the tables in the database that can be imported using the file set.
- USER_FILE_GROUP_TABLES shows information about tables owned by the current user that can be imported using the file set. This view does not display the FILE_GROUP_OWNER column.

Column	Datatype	NULL	Description
FILE_GROUP_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the file group
FILE_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the file group
VERSION_NAME	VARCHAR2 (30)	NOT NULL	Version of the file group that contains the table
VERSION	NUMBER	NOT NULL	Internal version number

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Schema to which the table belongs
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace to which the table belongs
SCN	NUMBER		SCN at which the table was exported (available only for Streams-prepared tables)

ALL_FILE_GROUP_TABLESPACES

ALL_FILE_GROUP_TABLESPACES shows information about the transportable tablespaces present (partially or completely) in the file groups accessible to the current user (when the file groups contain dump files).

Related Views

- DBA_FILE_GROUP_TABLESPACES shows information about the transportable tablespaces present (partially or completely) in all file groups in the database (when the file groups contain dump files).
- USER_FILE_GROUP_TABLESPACES shows information about the transportable tablespaces present (partially or completely) in the file groups owned by the current user (when the file groups contain dump files). This view does not display the FILE_GROUP_OWNER column.

Column	Datatype	NULL	Description
FILE_GROUP_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the file group
FILE_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the file group
VERSION_NAME	VARCHAR2 (30)	NOT NULL	Version of the file group that contains the tablespace
VERSION	NUMBER	NOT NULL	Internal version number
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace

ALL_FILE_GROUP_VERSIONS

ALL_FILE_GROUP_VERSIONS shows top-level version information for the file groups accessible to the current user.

Related Views

- DBA_FILE_GROUP_VERSIONS shows top-level version information for all file groups in the database.
- USER_FILE_GROUP_VERSIONS shows top-level version information for all file groups owned by the current user. This view does not display the FILE_GROUP_OWNER column.

Column	Datatype	NULL	Description
FILE_GROUP_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the file group
FILE_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the file group
VERSION_NAME	VARCHAR2 (30)	NOT NULL	User-specified name for the version
VERSION	NUMBER	NOT NULL	Internal version number
CREATOR	VARCHAR2 (30)	NOT NULL	User who created the version
CREATED	TIMESTAMP (6) WITH TIME ZONE	NOT NULL	Time at which the version was created

Column	Datatype	NULL	Description
COMMENTS	VARCHAR2 (4000)		Comments about the file group
DEFAULT_DIRECTORY	VARCHAR2 (30)		Default directory object for this version, if specified

ALL_FILE_GROUPS

ALL_FILE_GROUPS shows top-level metadata about the file groups accessible to the current user.

Related Views

- DBA_FILE_GROUPS shows top-level metadata about all file groups in the database.
- USER_FILE_GROUPS shows top-level metadata about file groups owned by the current user. This view does not display the FILE_GROUP_OWNER column.

Column	Datatype	NULL	Description
FILE_GROUP_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the file group
FILE_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the file group
KEEP_FILES	VARCHAR2 (1)	NOT NULL	A value of Y or N to indicate whether or not files should be deleted when a version is purged
MIN_VERSIONS	NUMBER	NOT NULL	Autopurge should not drop a version if this condition will become violated
MAX_VERSIONS	NUMBER	NOT NULL	Autopurge will drop the oldest version when this condition is violated
RETENTION_DAYS	NUMBER	NOT NULL	Autopurge will drop versions older than this if doing so does not violate MIN_VERSIONS
CREATED	TIMESTAMP (6) WITH TIME ZONE	NOT NULL	Time at which the file group was created
COMMENTS	VARCHAR2 (4000)		Comments about the file group
DEFAULT_DIRECTORY	VARCHAR2 (30)		Name of the default directory object

ALL_HISTOGRAMS

ALL_HISTOGRAMS is a synonym for ALL_TAB_HISTOGRAMS.

See Also: ["ALL_TAB_HISTOGRAMS"](#) on page 3-82

ALL_IDENTIFIERS

ALL_IDENTIFIERS displays information about the identifiers in the stored objects accessible to the current user.

Related Views

- DBA_IDENTIFIERS displays information about the identifiers in all stored objects in the database.
- USER_IDENTIFIERS displays information about the identifiers in the stored objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the identifier

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)		Name of the identifier
SIGNATURE	VARCHAR2 (32)		Signature of the identifier
TYPE	VARCHAR2 (18)		Type of the identifier
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object where the identifier action occurred
OBJECT_TYPE	VARCHAR2 (13)		Type of the object where the identifier action occurred
USAGE	VARCHAR2 (11)		Type of the identifier usage: ■ DECLARATION ■ DEFINITION ■ CALL ■ REFERENCE ■ ASSIGNMENT
USAGE_ID	NUMBER		Unique key for the identifier usage within the object
LINE	NUMBER		Line number of the identifier action
COL	NUMBER		Column number of the identifier action
USAGE_CONTEXT_ID	NUMBER		Context USAGE_ID of the identifier usage

See Also:

- ["DBA_IDENTIFIERS"](#) on page 5-43
- ["USER_IDENTIFIERS"](#) on page 6-80

ALL_IND_COLUMNS

ALL_IND_COLUMNS describes the columns of indexes on all tables accessible to the current user.

Related Views

- DBA_IND_COLUMNS describes the columns of indexes on all tables in the database.
- USER_IND_COLUMNS describes the columns of indexes owned by the current user and columns of indexes on tables owned by the current user. This view does not display the INDEX_OWNER or TABLE_OWNER columns.

Note: For join indexes, the TABLE_NAME and TABLE_OWNER columns in this view may not match the TABLE_NAME and TABLE_OWNER columns you find in the *_INDEXES (and other similar) data dictionary views.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the index
INDEX_NAME	VARCHAR2 (30)	NOT NULL	Name of the index
TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table or cluster
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table or cluster
COLUMN_NAME	VARCHAR2 (4000)		Column name or attribute of the object type column

Column	Datatype	NULL	Description
			Note: If you create an index on a user-defined REF column, the system creates the index on the attributes that make up the REF column. Therefore, the column names displayed in this view are the attribute names, with the REF column name as a prefix, in the following form: "REF_name"."attribute"
COLUMN_POSITION	NUMBER	NOT NULL	Position of the column or attribute within the index
COLUMN_LENGTH	NUMBER	NOT NULL	Indexed length of the column
CHAR_LENGTH	NUMBER		Maximum codepoint length of the column
DESCEND	VARCHAR2 (4)		Indicates whether the column is sorted in descending order (DESC) or ascending order (ASC)

ALL_IND_EXPRESSIONS

ALL_IND_EXPRESSIONS describes the expressions of function-based indexes on tables accessible to the current user.

Related Views

- DBA_IND_EXPRESSIONS describes the expressions of all function-based indexes in the database.
- USER_IND_EXPRESSIONS describes the expressions of function-based indexes on tables owned by the current user. This view does not display the INDEX_OWNER or TABLE_OWNER columns.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the index
INDEX_NAME	VARCHAR2 (30)	NOT NULL	Name of the index
TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table or cluster
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table or cluster
COLUMN_EXPRESSION	LONG		Function-based index expression defining the column
COLUMN_POSITION	NUMBER	NOT NULL	Position of the column or attribute within the index

ALL_IND_PARTITIONS

ALL_IND_PARTITIONS describes, for each index partition accessible to the current user, the partition-level partitioning information, the storage parameters for the partition, and various partition statistics collected by ANALYZE statements.

Related Views

- DBA_IND_PARTITIONS describes all index partitions in the database.
- USER_IND_PARTITIONS describes the index partitions owned by the current user. This view does not display the INDEX_OWNER column.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2 (30)		Owner of the index
INDEX_NAME	VARCHAR2 (30)		Name of the index
COMPOSITE	VARCHAR2 (3)		Indicates whether the partition belongs to a local index on a composite-partitioned table (YES) or not (NO)

Column	Datatype	NULL	Description
PARTITION_NAME	VARCHAR2 (30)		Name of the partition
SUBPARTITION_COUNT	NUMBER		If a local index on a composite-partitioned table, the number of subpartitions in the partition
HIGH_VALUE	LONG		Partition bound value expression
HIGH_VALUE_LENGTH	NUMBER		Length of the partition bound value expression
PARTITION_POSITION	NUMBER		Position of the partition within the index
STATUS	VARCHAR2 (8)		Indicates whether the index partition is usable (USABLE) or not (UNUSABLE)
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the partition
PCT_FREE	NUMBER		Minimum percentage of free space in a block
INI_TRANS	NUMBER		Initial number of transactions
MAX_TRANS	NUMBER		Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes
MIN_EXTENT	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENT	NUMBER		Maximum number of extents allowed in the segment
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment
PCT_INCREASE	NUMBER		Percentage increase in extent size
FREELISTS	NUMBER		Number of process freelists allocated in this segment
FREELIST_GROUPS	NUMBER		Number of process freelist groups allocated in this segment
LOGGING	VARCHAR2 (7)		Indicates whether or not changes to the index are logged: ■ NONE - Not specified See Also: the *_IND_SUBPARTITIONS view ■ YES ■ NO
COMPRESSION	VARCHAR2 (8)		Indicates whether key compression is enabled or disabled for a partitioned index; NULL for a nonpartitioned index: ■ NONE - Not specified See Also: the *_IND_SUBPARTITIONS view ■ ENABLED ■ DISABLED
BLEVEL	NUMBER		B*-Tree level (depth of the index from its root block to its leaf blocks). A depth of 0 indicates that the root block and leaf block are the same.
LEAF_BLOCKS	NUMBER		Number of leaf blocks in the index partition
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index partition
AVG_LEAF_BLOCKS_PER_KEY	NUMBER		Average number of leaf blocks in which each distinct value in the index appears, rounded to the nearest integer. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is always 1.
AVG_DATA_BLOCKS_PER_KEY	NUMBER		Average number of data blocks in the table that are pointed to by a distinct value in the index rounded to the nearest integer. This statistic is the average number of data blocks that contain rows that contain a given value for the indexed columns.

Column	Datatype	NULL	Description
CLUSTERING_FACTOR	NUMBER		Indicates the amount of order of the rows in the table based on the values of the index. ■ If the value is near the number of blocks, then the table is very well ordered. In this case, the index entries in a single leaf block tend to point to rows in the same data blocks. ■ If the value is near the number of rows, then the table is very randomly ordered. In this case, it is unlikely that index entries in the same leaf block point to rows in the same data blocks.
NUM_ROWS	NUMBER		Number of rows returned by the ANALYZE statement
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this partition
LAST_ANALYZED	DATE		Date on which this partition was most recently analyzed
BUFFER_POOL	VARCHAR2 (7)		Actual buffer pool for the partition: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for partition blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for partition blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
PCT_DIRECT_ACCESS	NUMBER		If a secondary index on index-organized table, the percentage of rows with VALID guess
GLOBAL_STATS	VARCHAR2 (3)		Indicates whether statistics for the partition were collected for the partition as a whole (YES) or were estimated from statistics on underlying subpartitions (NO)
DOMIDX_OPSTATUS	VARCHAR2 (6)		Status of the operation on a domain index: ■ NULL - Index is not a domain index ■ VALID - Operation performed without errors ■ FAILED - Operation failed with an error
PARAMETERS	VARCHAR2 (1000)		For a domain index, the parameter string
INTERVAL	VARCHAR2 (3)		Indicates whether the partition is in the interval section of an interval partitioned table (YES) or whether the partition is in the range section (NO)
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the index partition segment has been created (YES) or not (NO); N/A indicates that this index is subpartitioned and no segment exists at the partition level

ALL_IND_PENDING_STATS

ALL_IND_PENDING_STATS describes the pending statistics for tables, partitions, and subpartitions accessible to the current user.

Related Views

- DBA_IND_PENDING_STATS describes pending statistics for all tables, partitions, and subpartitions in the database.
- USER_IND_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Name of the index owner
INDEX_NAME	VARCHAR2 (30)		Index name
TABLE_OWNER	VARCHAR2 (30)		Table owner name
TABLE_NAME	VARCHAR2 (30)		Name of the table
PARTITION_NAME	VARCHAR2 (30)		Name of the partition
SUBPARTITION_NAME	VARCHAR2 (30)		Name of the subpartition
BLEVEL	NUMBER		Number of levels in the index
LEAF_BLOCKS	NUMBER		Number of leaf blocks in the index
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index
AVG_LEAF_BLOCKS_PER_KEY	NUMBER		Average number of leaf blocks per key
AVG_DATA_BLOCKS_PER_KEY	NUMBER		Average number of data blocks per key
CLUSTERING_FACTOR	NUMBER		Clustering factor
NUM_ROWS	NUMBER		Number of rows in the index
SAMPLE_SIZE	NUMBER		Sample size
LAST_ANALYZED	DATE		Time of the last analysis

ALL_IND_STATISTICS

ALL_IND_STATISTICS displays optimizer statistics for the indexes on the tables accessible to the current user.

Related Views

- DBA_IND_STATISTICS displays optimizer statistics for all indexes in the database.
- USER_IND_STATISTICS displays optimizer statistics for the indexes on the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the index
INDEX_NAME	VARCHAR2 (30)		Name of the index
TABLE_OWNER	VARCHAR2 (30)		Owner of the indexed object
TABLE_NAME	VARCHAR2 (30)		Name of the indexed object
PARTITION_NAME	VARCHAR2 (30)		Name of the partition

Column	Datatype	NULL	Description
PARTITION_POSITION	NUMBER		Position of the partition within the index
SUBPARTITION_NAME	VARCHAR2 (30)		Name of the subpartition
SUBPARTITION_POSITION	NUMBER		Position of the subpartition within the partition
OBJECT_TYPE	VARCHAR2 (12)		Type of the object: - INDEX - PARTITION - SUBPARTITION
BLEVEL	NUMBER		B-Tree level
LEAF_BLOCKS	NUMBER		Number of leaf blocks in the index
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index
AVG_LEAF_BLOCKS_PER_KEY	NUMBER		Average number of leaf blocks per key
AVG_DATA_BLOCKS_PER_KEY	NUMBER		Average number of data blocks per key
CLUSTERING_FACTOR	NUMBER		Indicates the amount of order of the rows in the table based on the values of the index. - If the value is near the number of blocks, then the table is very well ordered. In this case, the index entries in a single leaf block tend to point to rows in the same data blocks. - If the value is near the number of rows, then the table is very randomly ordered. In this case, it is unlikely that index entries in the same leaf block point to rows in the same data blocks.
NUM_ROWS	NUMBER		Number of rows in the index
AVG_CACHED_BLOCKS	NUMBER		Average number of blocks in the buffer cache
AVG_CACHE_HIT_RATIO	NUMBER		Average cache hit ratio for the object
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the index
LAST_ANALYZED	DATE		Date of the most recent time the index was analyzed
GLOBAL_STATS	VARCHAR2 (3)		Indicates whether statistics were calculated without merging underlying partitions (YES) or not (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
STATTYPE_LOCKED	VARCHAR2 (5)		Type of statistics lock
STALE_STATS	VARCHAR2 (3)		Whether statistics for the object are stale or not

See Also:

- ["DBA_IND_STATISTICS"](#) on page 5-44
- ["USER_IND_STATISTICS"](#) on page 6-81

ALL_IND_SUBPARTITIONS

ALL_IND_SUBPARTITIONS describes, for each index subpartition accessible to the current user, the partition-level partitioning information, the storage parameters for the subpartition, and various partition statistics collected by ANALYZE statements.

Related Views

- DBA_IND_SUBPARTITIONS describes all index subpartitions in the database.

- USER_IND_SUBPARTITIONS describes the index subpartitions owned by the current user. This view does not display the INDEX_OWNER column.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the index
INDEX_NAME	VARCHAR2 (30)	NOT NULL	Name of the index
PARTITION_NAME	VARCHAR2 (30)		Name of the partition
SUBPARTITION_NAME	VARCHAR2 (30)		Name of the subpartition
HIGH_VALUE	LONG		Subpartition bound value expression
HIGH_VALUE_LENGTH	NUMBER	NOT NULL	Length of the subpartition bound value expression
SUBPARTITION_POSITION	NUMBER		Position of a subpartition within a partition
STATUS	VARCHAR2 (8)		Indicates whether the index partition is usable (USABLE) or not (UNUSABLE)
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace containing the partition
PCT_FREE	NUMBER	NOT NULL	Minimum percentage of free space in a block
INI_TRANS	NUMBER	NOT NULL	Initial number of transactions
MAX_TRANS	NUMBER	NOT NULL	Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes
MIN_EXTENT	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENT	NUMBER		Maximum number of extents allowed in the segment
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment
PCT_INCREASE	NUMBER	NOT NULL	Percentage increase in extent size
FREELISTS	NUMBER		Number of process freelists allocated in this segment
FREELIST_GROUPS	NUMBER		Number of process freelist groups allocated in this segment
LOGGING	VARCHAR2 (3)		Indicates whether or not changes to the index are logged: ■ YES ■ NO
COMPRESSION	VARCHAR2 (8)		Indicates whether this subpartition is compressed (ENABLED) or not (DISABLED)
BLEVEL	NUMBER		B-Tree level (depth of the index from its root block to its leaf blocks). A depth of 0 indicates that the root block and leaf block are the same.
LEAF_BLOCKS	NUMBER		Number of leaf blocks in the index
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index partition
AVG_LEAF_BLOCKS_PER_KEY	NUMBER		Average number of leaf blocks in which each distinct value in the index appears, rounded to the nearest integer. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is always 1.
AVG_DATA_BLOCKS_PER_KEY	NUMBER		Average number of data blocks in the table that are pointed to by a distinct value in the index rounded to the nearest integer. This statistic is the average number of data blocks that contain rows that contain a given value for the indexed columns.

Column	Datatype	NULL	Description
CLUSTERING_FACTOR	NUMBER		Indicates the amount of order of the rows in the table based on the values of the index. ■ If the value is near the number of blocks, then the table is very well ordered. In this case, the index entries in a single leaf block tend to point to rows in the same data blocks. ■ If the value is near the number of rows, then the table is very randomly ordered. In this case, it is unlikely that index entries in the same leaf block point to rows in the same data blocks.
NUM_ROWS	NUMBER		Number of rows in this index subpartition
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this subpartition
LAST_ANALYZED	DATE		Date on which this partition was most recently analyzed
BUFFER_POOL	VARCHAR2 (7)		Buffer pool for the subpartition: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for subpartition blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for subpartition blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
GLOBAL_STATS	VARCHAR2 (3)		Indicates whether column statistics for the subpartition statistics were collected by analyzing the table as a whole (YES) or estimated from statistics gathered on partitions and subpartitions (NO)
INTERVAL	VARCHAR2 (3)		Indicates whether the partition is in the interval section of an interval partitioned table (YES) or whether the partition is in the range section (NO)
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the index subpartition segment has been created (YES) or not (NO); N/A indicates that this index is not subpartitioned

ALL_INDEXES

ALL_INDEXES describes the indexes on the tables accessible to the current user. To gather statistics for this view and the related views DBA_INDEXES and USER_INDEXES, use the SQL ANALYZE statement.

Related Views

- DBA_INDEXES describes all indexes in the database.
- USER_INDEXES describes the indexes owned by the current user. This view does not display the OWNER column.

Note: Column names followed by an asterisk are populated only if you collect statistics on the index using the ANALYZE statement or the DBMS_STATS package.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the index
INDEX_NAME	VARCHAR2 (30)	NOT NULL	Name of the index
INDEX_TYPE	VARCHAR2 (27)		Type of the index: ■ NORMAL ■ NORMAL/REV ■ BITMAP ■ FUNCTION-BASED NORMAL ■ FUNCTION-BASED NORMAL/REV ■ FUNCTION-BASED BITMAP ■ CLUSTER ■ IOT - TOP ■ DOMAIN
TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the indexed object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the indexed object
TABLE_TYPE	CHAR (5)		Type of the indexed object: ■ NEXT OBJECT ■ INDEX ■ TABLE ■ CLUSTER ■ VIEW ■ SYNONYM ■ SEQUENCE
UNIQUENESS	VARCHAR2 (9)		Indicates whether the index is unique (UNIQUE) or nonunique (NONUNIQUE)
COMPRESSION	VARCHAR2 (8)		Indicates whether index compression is enabled (ENABLED) or not (DISABLED)
PREFIX_LENGTH	NUMBER		Number of columns in the prefix of the compression key
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the index
INI_TRANS	NUMBER		Initial number of transactions
MAX_TRANS	NUMBER		Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent
NEXT_EXTENT	NUMBER		Size of secondary extents
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment
PCT_INCREASE	NUMBER		Percentage increase in extent size
PCT_THRESHOLD	NUMBER		Threshold percentage of block space allowed per index entry
INCLUDE_COLUMN	NUMBER		Column ID of the last column to be included in index-organized table primary key (non-overflow) index. This column maps to the COLUMN_ID column of the *_TAB_COLUMNS view.
FREELISTS	NUMBER		Number of process freelists allocated to this segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to this segment

Column	Datatype	NULL	Description
PCT_FREE	NUMBER		Minimum percentage of free space in a block
LOGGING	VARCHAR2 (3)		Indicates whether or not changes to the index are logged: ■ YES ■ NO
BLEVEL*	NUMBER		B*-Tree level (depth of the index from its root block to its leaf blocks). A depth of 0 indicates that the root block and leaf block are the same.
LEAF_BLOCKS*	NUMBER		Number of leaf blocks in the index
DISTINCT_KEYS*	NUMBER		Number of distinct indexed values. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is the same as the number of rows in the table (*_TABLES.NUM_ROWS)
AVG_LEAF_BLOCKS_PER_KEY*	NUMBER		Average number of leaf blocks in which each distinct value in the index appears, rounded to the nearest integer. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is always 1.
AVG_DATA_BLOCKS_PER_KEY*	NUMBER		Average number of data blocks in the table that are pointed to by a distinct value in the index rounded to the nearest integer. This statistic is the average number of data blocks that contain rows that contain a given value for the indexed columns.
CLUSTERING_FACTOR*	NUMBER		Indicates the amount of order of the rows in the table based on the values of the index. ■ If the value is near the number of blocks, then the table is very well ordered. In this case, the index entries in a single leaf block tend to point to rows in the same data blocks. ■ If the value is near the number of rows, then the table is very randomly ordered. In this case, it is unlikely that index entries in the same leaf block point to rows in the same data blocks. For bitmap indexes, this column is not applicable and is not used.
STATUS	VARCHAR2 (8)		Indicates whether a nonpartitioned index is VALID or UNUSABLE
NUM_ROWS	NUMBER		Number of rows in the index
SAMPLE_SIZE	NUMBER		Size of the sample used to analyze the index
LAST_ANALYZED	DATE		Date on which this index was most recently analyzed
DEGREE	VARCHAR2 (40)		Number of threads per instance for scanning the index, or DEFAULT
INSTANCES	VARCHAR2 (40)		Number of instances across which the indexes to be scanned, or DEFAULT
PARTITIONED	VARCHAR2 (3)		Indicates whether the index is partitioned (YES) or not (NO)
TEMPORARY	VARCHAR2 (1)		Indicates whether the index is on a temporary table (Y) or not (N)
GENERATED	VARCHAR2 (1)		Indicates whether the name of the index is system-generated (Y) or not (N)
SECONDARY	VARCHAR2 (1)		Indicates whether the index is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)

Column	Datatype	NULL	Description
BUFFER_POOL	VARCHAR2 (7)		Buffer pool to be used for index blocks: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for index blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for index blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
DURATION	VARCHAR2 (15)		Indicates the duration of a temporary table: ■ SYS\$SESSION - Rows are preserved for the duration of the session ■ SYS\$TRANSACTION - Rows are deleted after COMMIT NNUL - Permanent table
PCT_DIRECT_ACCESS	NUMBER		For a secondary index on an index-organized table, the percentage of rows with VALID guess
ITYP_OWNER	VARCHAR2 (30)		For a domain index, the owner of the indextype
ITYP_NAME	VARCHAR2 (30)		For a domain index, the name of the indextype
PARAMETERS	VARCHAR2 (1000)		For a domain index, the parameter string
GLOBAL_STATS	VARCHAR2 (3)		For partitioned indexes, indicates whether statistics were collected by analyzing the index as a whole (YES) or were estimated from statistics on underlying index partitions and subpartitions (NO)
DOMIDX_STATUS	VARCHAR2 (12)		Status of a domain index: ■ NULL - Index is not a domain index ■ VALID - Index is a valid domain index ■ IDXTYP_INVLD - Indextype of the domain index is invalid
DOMIDX_OPSTATUS	VARCHAR2 (6)		Status of the operation on a domain index: ■ NULL - Index is not a domain index ■ VALID - Operation performed without errors ■ FAILED - Operation failed with an error
FUNCIDX_STATUS	VARCHAR2 (8)		Status of a function-based index: ■ NULL - Index is not a function-based index ■ ENABLED - Function-based index is enabled ■ DISABLED - Function-based index is disabled
JOIN_INDEX	VARCHAR2 (3)		Indicates whether the index is a join index (YES) or not (NO)

Column	Datatype	NULL	Description
IOT_REDUNDANT_PKEY_ELIM	VARCHAR2 (3)		Indicates whether redundant primary key columns are eliminated from secondary indexes on index-organized tables (YES) or not (NO)
DROPPED	VARCHAR2 (3)		Indicates whether the index has been dropped and is in the recycle bin (YES) or not (NO); NULL for partitioned tables
VISIBILITY	VARCHAR2 (10)		Indicates whether the index is <code>VISIBLE</code> or <code>INVISIBLE</code> to the optimizer
DOMIDX_MANAGEMENT	VARCHAR2 (14)		If this is a domain index, indicates whether the domain index is system-managed (<code>SYSTEM_MANAGED</code>) or user-managed (<code>USER_MANAGED</code>)
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the index segment has been created (YES) or not (NO)

ALL_INDEXTYPE_ARRAYTYPES

`ALL_INDEXTYPE_ARRAYTYPES` displays information about the array types specified by the indextypes accessible to the current user.

Related Views

- `DBA_INDEXTYPE_ARRAYTYPES` displays information about the array types specified by all indextypes in the database.
- `USER_INDEXTYPE_ARRAYTYPES` displays information about the array types specified by the indextypes owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the indextype
INDEXTYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the indextype
BASE_TYPE_SCHEMA	VARCHAR2 (30)		Name of the base type schema
BASE_TYPE_NAME	VARCHAR2 (30)		Name of the base type name
BASE_TYPE	VARCHAR2 (30)		Datatype of the base type
ARRAY_TYPE_SCHEMA	VARCHAR2 (30)	NOT NULL	Name of the array type schema
ARRAY_TYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the array type name

See Also:

- ["DBA_INDEXTYPE_ARRAYTYPES" on page 5-44](#)
- ["USER_INDEXTYPE_ARRAYTYPES" on page 6-81](#)

ALL_INDEXTYPE_COMMENTS

`ALL_INDEXTYPE_COMMENTS` displays comments for the user-defined indextypes accessible to the current user.

Related Views

- `DBA_INDEXTYPE_COMMENTS` displays comments for all user-defined indextypes in the database.
- `USER_INDEXTYPE_COMMENTS` displays comments for the user-defined indextypes owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the user-defined indextype
INDEXTYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the user-defined indextype
COMMENTS	VARCHAR2 (4000)		Comment for the user-defined indextype

See Also:

- ["DBA_INDEXTYPE_COMMENTS"](#) on page 5-44
- ["USER_INDEXTYPE_COMMENTS"](#) on page 6-81

ALL_INDEXTYPE_OPERATORS

ALL_INDEXTYPE_OPERATORS lists all operators supported by indextypes accessible to the current user.

Related Views

- DBA_INDEXTYPE_OPERATORS lists all operators supported by indextypes in the database.
- USER_INDEXTYPE_OPERATORS lists all operators supported by indextypes owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the indextype
INDEXTYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the indextype
OPERATOR_SCHEMA	VARCHAR2 (30)	NOT NULL	Name of the operator schema
OPERATOR_NAME	VARCHAR2 (30)	NOT NULL	Name of the operator for which the indextype is defined
BINDING#	NUMBER	NOT NULL	Binding number associated with the operator

See Also:

- ["DBA_INDEXTYPE_OPERATORS"](#) on page 5-44
- ["USER_INDEXTYPE_OPERATORS"](#) on page 6-82

ALL_INDEXTYPES

ALL_INDEXTYPES displays information about the indextypes accessible to the current user.

Related Views

- DBA_INDEXTYPES displays information about all indextypes in the database.
- USER_INDEXTYPES displays information about the indextypes owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the indextype
INDEXTYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the indextype
IMPLEMENTATION_SCHEMA	VARCHAR2 (30)	NOT NULL	Name of the schema for the indextype implementation (that is, containing the indextype operators)

Column	Datatype	NULL	Description
IMPLEMENTATION_NAME	VARCHAR2 (30)	NOT NULL	Name of the indextype implementation type
INTERFACE_VERSION	NUMBER		Version of the indextype interface
IMPLEMENTATION_VERSION	NUMBER	NOT NULL	Version of the indextype implementation
NUMBER_OF_OPERATORS	NUMBER		Number of operators associated with the indextype
PARTITIONING	VARCHAR2 (10)		Kinds of local partitioning supported by the indextype: - NONE - Indextype does not support local domain indexes - RANGE - Indextype can support range partitioned local user managed domain indexes - LOCAL - Indextype can support local system managed domain indexes (both range and list partitioned)
ARRAY_DML	VARCHAR2 (3)		Indicates whether the indextype supports array DML (YES) or not (NO)
MAINTENANCE_TYPE	VARCHAR2 (14)		Indicates whether the indextype is system-managed (SYSTEM_MANAGED) or user-managed (USER_MANAGED)

See Also:

- ["DBA_INDEXTYPES"](#) on page 5-45
- ["USER_INDEXTYPES"](#) on page 6-82

ALL_INTERNAL_TRIGGERS

ALL_INTERNAL_TRIGGERS describes internal triggers on tables accessible to the current user. Internal triggers are internal pieces of code executed when a particular flag is set for a table. This view does not display the OWNER_NAME column.

Related Views

- DBA_INTERNAL_TRIGGERS describes internal triggers on all tables in the database.
- USER_INTERNAL_TRIGGERS describes all internal triggers on tables owned by the current user. This view does not display the OWNER_NAME column.

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2 (30)		Name of the table on which the trigger is defined
OWNER_NAME	VARCHAR2 (30)		Owner of the table
INTERNAL_TRIGGER_TYPE	VARCHAR2 (19)		Indicates the type of internal trigger on the table

ALL_JAVA_ARGUMENTS

ALL_JAVA_ARGUMENTS displays argument information about the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_ARGUMENTS displays argument information about all stored Java classes in the database.
- USER_JAVA_ARGUMENTS displays argument information about the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Java class
NAME	VARCHAR2 (4000)		Name of the Java class
METHOD_INDEX	NUMBER		Index of the hosting method of the argument
METHOD_NAME	VARCHAR2 (4000)		Name of the hosting method of the argument
ARGUMENT_POSITION	NUMBER		Position of the argument, starting from 0
ARRAY_DEPTH	NUMBER		Array depth of the type of the argument
BASE_TYPE	VARCHAR2 (7)		Base type of the type of the argument: - int - long - float - double - boolean - byte - char - short - class
ARGUMENT_CLASS	VARCHAR2 (4000)		Actual class name of the argument if the base type is class

See Also:

- ["DBA_JAVA_ARGUMENTS"](#) on page 5-45
- ["USER_JAVA_ARGUMENTS"](#) on page 6-82

ALL_JAVA_CLASSES

ALL_JAVA_CLASSES displays class level information about the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_CLASSES displays class level information about all stored Java classes in the database.
- USER_JAVA_CLASSES displays class level information about the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Java class
NAME	VARCHAR2 (4000)		Name of the Java class
MAJOR	NUMBER		Major version number of the Java class, as defined in the JVM specification
MINOR	NUMBER		Minor version number of the Java class, as defined in the JVM specification
KIND	VARCHAR2 (9)		Indicates whether the stored object is a Java class (CLASS) or a Java interface (INTERFACE)
ACCESSIBILITY	VARCHAR2 (6)		Accessibility of the Java class
IS_INNER	VARCHAR2 (3)		Indicates whether this Java class is an inner class (YES) or not (NO)

Column	Datatype	NULL	Description
IS_ABSTRACT	VARCHAR2 (3)		Indicates whether this Java class is an abstract class (YES) or not (NO)
IS_FINAL	VARCHAR2 (3)		Indicates whether this Java class is a final class (YES) or not (NO)
IS_DEBUG	VARCHAR2 (3)		Indicates whether this Java class contains debug information (YES) or not (NO)
SOURCE	VARCHAR2 (4000)		Source designation of the Java class
SUPER	VARCHAR2 (4000)		Super class of this Java class
OUTER	VARCHAR2 (4000)		Outer class of this Java class if this Java class is an inner class

See Also:

- ["DBA_JAVA_CLASSES"](#) on page 5-45
- ["USER_JAVA_CLASSES"](#) on page 6-82

ALL_JAVA_COMPILER_OPTIONS

ALL_JAVA_COMPILER_OPTIONS displays information about the native compiler options accessible to the current user.

Related Views

- DBA_JAVA_COMPILER_OPTIONS displays information about all native compiler options in the database.
- USER_JAVA_COMPILER_OPTIONS displays information about the native compiler options owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the native compiler option
OPTION_NAME	VARCHAR2 (64)		Name of the native compiler option
VALUE	VARCHAR2 (4000)		Value of the native compiler option

See Also:

- ["DBA_JAVA_COMPILER_OPTIONS"](#) on page 5-45
- ["USER_JAVA_COMPILER_OPTIONS"](#) on page 6-82

ALL_JAVA_DERIVATIONS

ALL_JAVA_DERIVATIONS displays mapping information about Java source objects and their derived Java class objects and Java resource objects for the Java classes accessible to the current user.

Related Views

- DBA_JAVA_DERIVATIONS displays mapping information about Java source objects and their derived Java class objects and Java resource objects for all Java classes in the database.

- `USER_JAVA_DERIVATIONS` displays mapping information about Java source objects and their derived Java class objects and Java resource objects for the Java classes owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the Java source object
<code>SOURCE_NAME</code>	<code>VARCHAR2 (4000)</code>		Name of the Java source object
<code>CLASS_INDEX</code>	<code>NUMBER</code>		Index of the derived Java class object
<code>CLASS_NAME</code>	<code>VARCHAR2 (4000)</code>		Name of the derived Java class object

See Also:

- ["DBA_JAVA_DERIVATIONS"](#) on page 5-45
- ["USER_JAVA_DERIVATIONS"](#) on page 6-82

ALL_JAVA_FIELDS

`ALL_JAVA_FIELDS` displays field information about the stored Java classes accessible to the current user.

Related Views

- `DBA_JAVA_FIELDS` displays field information about all stored Java classes in the database.
- `USER_JAVA_FIELDS` displays field information about the stored Java classes owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the Java class
<code>NAME</code>	<code>VARCHAR2 (4000)</code>		Name of the Java class
<code>FIELD_INDEX</code>	<code>NUMBER</code>		Index of the field
<code>FIELD_NAME</code>	<code>VARCHAR2 (4000)</code>		Name of the field identified by the <code>FIELD_INDEX</code> column
<code>ACCESSIBILITY</code>	<code>VARCHAR2 (9)</code>		Accessibility of the field: ■ <code>PUBLIC</code> ■ <code>PRIVATE</code> ■ <code>PROTECTED</code>
<code>IS_STATIC</code>	<code>VARCHAR2 (3)</code>		Indicates whether the field is a static field (YES) or not (NO)
<code>IS_FINAL</code>	<code>VARCHAR2 (3)</code>		Indicates whether the field is a final field (YES) or not (NO)
<code>IS_VOLATILE</code>	<code>VARCHAR2 (3)</code>		Indicates whether the field is volatile (YES) or not (NO)
<code>IS_TRANSIENT</code>	<code>VARCHAR2 (3)</code>		Indicates whether the field is transient (YES) or not (NO)
<code>ARRAY_DEPTH</code>	<code>NUMBER</code>		Array depth of the type of the field

Column	Datatype	NULL	Description
BASE_TYPE	VARCHAR2 (7)		Base type of the type of the field: ▪ int ▪ long ▪ float ▪ double ▪ boolean ▪ byte ▪ char ▪ short ▪ class
FIELD_CLASS	VARCHAR2 (4000)		Actual class name of the base object if the base type is class

See Also:

- ["DBA_JAVA_FIELDS"](#) on page 5-45
- ["USER_JAVA_FIELDS"](#) on page 6-83

ALL_JAVA_IMPLEMENTS

ALL_JAVA_IMPLEMENTS describes interfaces implemented by the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_IMPLEMENTS describes interfaces implemented by all stored Java classes in the database.
- USER_JAVA_IMPLEMENTS describes interfaces implemented by the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Java class
NAME	VARCHAR2 (4000)		Name of the Java class
INTERFACE_INDEX	NUMBER		Index of the interfaces implemented by the Java class
INTERFACE_NAME	VARCHAR2 (4000)		Name of the interface identified by the INTERFACE_INDEX column

See Also:

- ["DBA_JAVA_IMPLEMENTS"](#) on page 5-45
- ["USER_JAVA_IMPLEMENTS"](#) on page 6-83

ALL_JAVA_INNERS

ALL_JAVA_INNERS displays information about inner classes referred to by the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_INNERS displays information about inner classes referred to by all stored Java classes in the database.

- **USER_JAVA_INNERS** displays information about inner classes referred to by the stored Java classes owned by the current user. This view does not display the **OWNER** column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Java class
NAME	VARCHAR2 (4000)		Name of the Java class
INNER_INDEX	NUMBER		Index of the referred inner class
SIMPLE_NAME	VARCHAR2 (4000)		Simple name of the referred inner class
FULL_NAME	VARCHAR2 (4000)		Full name of the referred inner class
ACCESSIBILITY	VARCHAR2 (9)		Accessibility of the referred inner class: ■ PUBLIC ■ PRIVATE ■ PROTECTED
IS_STATIC	VARCHAR2 (3)		Indicates whether the referred inner class is declared static in the source file (YES) or not (NO)
IS_FINAL	VARCHAR2 (3)		Indicates whether the referred inner class is declared final in the source file (YES) or not (NO)
IS_ABSTRACT	VARCHAR2 (3)		Indicates whether the referred inner class is declared abstract in the source file (YES) or not (NO)
IS_INTERFACE	VARCHAR2 (3)		Indicates whether the referred inner class is declared interface in the source file (YES) or not (NO)

See Also:

- ["DBA_JAVA_INNERS"](#) on page 5-46
- ["USER_JAVA_INNERS"](#) on page 6-83

ALL_JAVA_LAYOUTS

ALL_JAVA_LAYOUTS displays class layout information about the stored Java classes accessible to the current user.

Related Views

- **DBA_JAVA_LAYOUTS** displays class layout information about all stored Java classes in the database.
- **USER_JAVA_LAYOUTS** displays class layout information about the stored Java classes owned by the current user. This view does not display the **OWNER** column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Java class
NAME	VARCHAR2 (4000)		Name of the Java class
INTERFACES	NUMBER		Number of interfaces that this Java class implements
INNER_CLASSES	NUMBER		Number of inner classes that this Java class contains
FIELDS	NUMBER		Number of locally declared fields that this Java class contains
STATIC_FIELDS	NUMBER		Number of locally declared static fields that this Java class contains
METHODS	NUMBER		Number of locally declared methods that this Java class contains

Column	Datatype	NULL	Description
STATIC_METHODS	NUMBER		Number of locally declared static methods that this Java class contains
NATIVE_METHODS	NUMBER		Number of locally declared native methods that this Java class contains

See Also:

- ["DBA_JAVA_LAYOUTS"](#) on page 5-46
- ["USER_JAVA_LAYOUTS"](#) on page 6-83

ALL_JAVA_METHODS

ALL_JAVA_METHODS displays method information about the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_METHODS displays method information about all stored Java classes in the database.
- USER_JAVA_METHODS displays method information about the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Java class
NAME	VARCHAR2 (4000)		Name of the Java class
METHOD_INDEX	NUMBER		Index of the method
METHOD_NAME	VARCHAR2 (4000)		Name of the method identified by the METHOD_INDEX column
ACCESSIBILITY	VARCHAR2 (9)		Accessibility of the method: ■ PUBLIC ■ PRIVATE ■ PROTECTED
IS_STATIC	VARCHAR2 (3)		Indicates whether the method is a static method (YES) or not (NO)
IS_FINAL	VARCHAR2 (3)		Indicates whether the method is a final method (YES) or not (NO)
IS_SYNCHRONIZED	VARCHAR2 (3)		Indicates whether the method is a synchronized method (YES) or not (NO)
IS_NATIVE	VARCHAR2 (3)		Indicates whether the method is a native method (YES) or not (NO)
IS_ABSTRACT	VARCHAR2 (3)		Indicates whether the method is an abstract method (YES) or not (NO)
IS_STRICT	VARCHAR2 (3)		Indicates whether the method is a strict method (YES) or not (NO)
ARGUMENTS	NUMBER		Number of arguments of the method
THROWS	NUMBER		Number of exceptions thrown by the method
ARRAY_DEPTH	NUMBER		Array depth of the return type of the method

Column	Datatype	NULL	Description
BASE_TYPE	VARCHAR2 (7)		Base type of the return type of the method: - int - long - float - double - boolean - byte - char - short - class - void
RETURN_CLASS	VARCHAR2 (4000)		Actual class name of the return value if the base type is class
IS_COMPILED	VARCHAR2 (3)		Indicates whether the Java method has been natively compiled by the JIT compiler (YES) or not (NO)

See Also:

- ["DBA_JAVA_METHODS"](#) on page 5-46
- ["USER_JAVA_METHODS"](#) on page 6-83

ALL_JAVA_NCOMPS

ALL_JAVA_NCOMPS displays ncomp-related information about the Java classes accessible to the current user.

Related Views

- DBA_JAVA_NCOMPS displays ncomp-related information about all Java classes in the database.
- USER_JAVA_NCOMPS displays ncomp-related information about the Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Java class object
NAME	VARCHAR2 (4000)		Name of the Java class object
SOURCE	VARCHAR2 (4000)		ncomp source shown in this row
INITIALIZER	VARCHAR2 (4000)		ncomp initializer shown in this row
LIBRARYFILE	VARCHAR2 (4000)		ncomp library file shown in this row
LIBRARY	VARCHAR2 (4000)		ncomp library shown in this row

See Also:

- ["DBA_JAVA_NCOMPS"](#) on page 5-46
- ["USER_JAVA_NCOMPS"](#) on page 6-83

ALL_JAVA_RESOLVERS

ALL_JAVA_RESOLVERS displays information about resolvers of the Java classes accessible to the current user.

Related Views

- [DBA_JAVA_RESOLVERS](#) displays information about resolvers of all Java classes in the database.
- [USER_JAVA_RESOLVERS](#) displays information about resolvers of the Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Java class object
NAME	VARCHAR2 (4000)		Name of the Java class object
TERM_INDEX	NUMBER		Index of the resolver term in this row
PATTERN	VARCHAR2 (4000)		Resolver pattern of the resolver term identified by the TERM_INDEX column
SCHEMA	VARCHAR2 (64)		Resolver schema of the resolver term identified by the TERM_INDEX column

See Also:

- ["DBA_JAVA_RESOLVERS"](#) on page 5-47
- ["USER_JAVA_RESOLVERS"](#) on page 6-84

ALL_JAVA_THROWS

[ALL_JAVA_THROWS](#) displays information about exceptions thrown from methods of the Java classes accessible to the current user.

Related Views

- [DBA_JAVA_THROWS](#) displays information about exceptions thrown from methods of all Java classes in the database.
- [USER_JAVA_THROWS](#) displays information about exceptions thrown from methods of the Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Java class
NAME	VARCHAR2 (4000)		Name of the Java class
METHOD_INDEX	NUMBER		Index of the throwing method of the exception
METHOD_NAME	VARCHAR2 (4000)		Name of the throwing method of the exception
EXCEPTION_INDEX	NUMBER		Index of the exception
EXCEPTION_CLASS	VARCHAR2 (4000)		Class of the exception

See Also:

- ["DBA_JAVA_THROWS"](#) on page 5-47
- ["USER_JAVA_THROWS"](#) on page 6-84

ALL_JOBS

[ALL_JOBS](#) is a synonym for [USER_JOBS](#).

See Also: ["USER_JOBS"](#) on page 6-84

ALL_JOIN_IND_COLUMNS

ALL_JOIN_IND_COLUMNS describes the join conditions of bitmap join indexes accessible to the current user. Bitmap join indexes are indexes built on a child table with an index key containing columns from associated parent tables, where all of the tables are connected through join conditions. There is one row for each join condition.

Related Views

- DBA_JOIN_IND_COLUMNS describes all join conditions in the database.
- USER_JOIN_IND_COLUMNS describes the join conditions owned by the current user. This view does not display the INDEX_OWNER column.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the bitmap join index
INDEX_NAME	VARCHAR2 (30)	NOT NULL	Name of the bitmap join index
INNER_TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the fact table
INNER_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the fact table
INNER_TABLE_COLUMN	VARCHAR2 (30)	NOT NULL	Name of the fact table join column
OUTER_TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the dimension table
OUTER_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the dimension table
OUTER_TABLE_COLUMN	VARCHAR2 (30)	NOT NULL	Name of the dimension table join column

ALL_LIBRARIES

ALL_LIBRARIES describes the libraries accessible to the current user.

Related Views

- DBA_LIBRARIES describes all libraries in the database.
- USER_LIBRARIES describes the libraries owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the library
LIBRARY_NAME	VARCHAR2 (30)	NOT NULL	Library name
FILE_SPEC	VARCHAR2 (2000)		Operating system file specification associated with the library
DYNAMIC	VARCHAR2 (1)		Indicates whether the library is dynamically loadable (Y) or not (N)
STATUS	VARCHAR2 (7)		Status of the library: ■ N/A ■ VALID ■ INVALID

See Also:

- ["DBA_LIBRARIES"](#) on page 5-48
- ["USER_LIBRARIES"](#) on page 6-84

ALL_LOB_PARTITIONS

ALL_LOB_PARTITIONS displays the LOB partitions in the tables accessible to the current user.

Related Views

- DBA_LOB_PARTITIONS displays all LOB partitions in the database.
- USER_LOB_PARTITIONS displays the LOB partitions owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table
COLUMN_NAME	VARCHAR2 (4000)		Name of the LOB column
LOB_NAME	VARCHAR2 (30)		Name of the partitioned LOB item
PARTITION_NAME	VARCHAR2 (30)		Name of the table partition
LOB_PARTITION_NAME	VARCHAR2 (30)		Name of the LOB data partition
LOB_INDPART_NAME	VARCHAR2 (30)		Name of the corresponding LOB index partition
PARTITION_POSITION	NUMBER		Position of the LOB data partition within the LOB item
COMPOSITE	VARCHAR2 (3)		Indicates whether the partition is composite (YES) or not (NO)
CHUNK	NUMBER		Value of the CHUNK attribute of the LOB data partition
PCTVERSION	NUMBER		Value of the PCTVERSION attribute of the LOB data partition
CACHE	VARCHAR2 (10)		Indicates whether and how the LOB data is to be cached in the buffer cache: ■ YES - LOB data is placed in the buffer cache ■ NO - LOB data either is not brought into the buffer cache or is brought into the buffer cache and placed at the least recently used end of the LRU list ■ CACHEREADS - LOB data is brought into the buffer cache only during read operations but not during write operations
IN_ROW	VARCHAR2 (3)		Indicates whether the STORAGE IN ROW attribute is enabled for the LOB data partition (YES) or not (NO)
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the LOB data partition
INITIAL_EXTENT	VARCHAR2 (40)		Size (in bytes) of the initial extent of the LOB data partition, or DEFAULT
NEXT_EXTENT	VARCHAR2 (40)		Size (in bytes) of secondary extents of the LOB data partition, or DEFAULT
MIN_EXTENTS	VARCHAR2 (40)		Minimum number of extents allowed in the segment of the LOB data partition, or DEFAULT
MAX_EXTENTS	VARCHAR2 (40)		Maximum number of extents allowed in the segment of the LOB data partition, or DEFAULT
MAX_SIZE	VARCHAR2 (40)		Maximum number of blocks allowed in the segment of the LOB data partition, or DEFAULT

Column	Datatype	NULL	Description
RETENTION	VARCHAR2 (7)		Retention option. Possible values for a SecureFiles segment: - NONE - AUTO - MIN - MAX - DEFAULT - INVALID Possible values for a BasicFiles segment: ¹ - YES - NO
MINRETENTION	VARCHAR2 (40)		Minimum retention duration for a SecureFiles segment, or DEFAULT
PCT_INCREASE	VARCHAR2 (40)		Percentage increase in extent size for the LOB data partition, or DEFAULT
FREELISTS	VARCHAR2 (40)		Number of process freelists allocated in the segment of the LOB data partition, or DEFAULT
FREELIST_GROUPS	VARCHAR2 (40)		Number of freelist groups allocated in the segment of the LOB data partition, or DEFAULT
LOGGING	VARCHAR2 (7)		Indicates whether or not changes to the LOB are logged: - NONE - Not specified See Also: the *_LOB_SUBPARTITIONS view - YES - NO
BUFFER_POOL	VARCHAR2 (7)		Buffer pool for the LOB partition blocks: - DEFAULT - KEEP - RECYCLE - NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for partition blocks: - DEFAULT - KEEP - NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for partition blocks: - DEFAULT - KEEP - NONE See Also: Oracle Exadata Storage Server Software documentation for more information
ENCRYPT	VARCHAR2 (4)		Indicates whether or not the LOB is encrypted. Possible values for SecureFiles: - YES - NO Possible value for BasicFiles: - NONE - Not applicable

Column	Datatype	NULL	Description
COMPRESSION	VARCHAR2 (6)		Level of compression used for this LOB. Possible values for SecureFiles: - LOW - MEDIUM - HIGH - NO - Compression is off Possible value for BasicFiles: - NONE - Not applicable
DEDUPLICATION	VARCHAR2 (15)		Kind of deduplication used for this LOB. Possible values for SecureFiles: - LOB - Deduplicate - NO - Keep duplicates Possible value for BasicFiles: - NONE - Not applicable
SECUREFILE	VARCHAR2 (3)		Indicates whether the LOB is SecureFiles (YES) or not (NO)
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the LOB partition segment has been created (YES) or not (NO); N/A indicates that this LOB is subpartitioned and no segment exists at the partition level

¹ The values listed for a BasicFiles segment are supported starting with Oracle Database 11g Release 2 (11.2.0.2). In previous releases, the value for this column for a BasicFiles segment is NULL.

ALL_LOB_SUBPARTITIONS

ALL_LOB_SUBPARTITIONS displays partition-level attributes of the LOB data subpartitions accessible to the current user.

Related Views

- DBA_LOB_SUBPARTITIONS displays partition-level attributes of all LOB data subpartitions in the database.
- USER_LOB_SUBPARTITIONS displays the LOB subpartitions owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2 (4000)		Name of the LOB column
LOB_NAME	VARCHAR2 (30)	NOT NULL	Name of the partitioned LOB item
LOB_PARTITION_NAME	VARCHAR2 (30)		Name of the LOB data partition to which this LOB data subpartition belongs
SUBPARTITION_NAME	VARCHAR2 (30)		Name of the table subpartition to which this LOB subpartition corresponds
LOB_SUBPARTITION_NAME	VARCHAR2 (30)		Name of the LOB subpartition
LOB_INDSUBPART_NAME	VARCHAR2 (30)		Name of the corresponding LOB index subpartition
SUBPARTITION_POSITION	NUMBER		Position of the LOB data partition within the LOB item
CHUNK	NUMBER		Value of the CHUNK attribute of the LOB data partition
PCTVERSION	NUMBER	NOT NULL	Value of the PCTVERSION attribute of the LOB data partition

Column	Datatype	NULL	Description
CACHE	VARCHAR2 (10)		Indicates whether and how the LOB data is to be cached in the buffer cache: ■ YES - LOB data is placed in the buffer cache ■ NO - LOB data either is not brought into the buffer cache or is brought into the buffer cache and placed at the least recently used end of the LRU list ■ CACHEREADS - LOB data is brought into the buffer cache only during read operations but not during write operations
IN_ROW	VARCHAR2 (3)		Indicates whether the STORAGE IN ROW attribute of the LOB data partition is enabled (YES) or not (NO)
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace containing the LOB data partition
INITIAL_EXTENT	NUMBER		Size in bytes of the initial extent for the LOB data partition
NEXT_EXTENT	NUMBER		Size in bytes of secondary extents for the LOB data partition
MIN_EXTENTS	NUMBER	NOT NULL	Minimum number of extents allowed in the segment of the LOB data partition
MAX_EXTENTS	NUMBER	NOT NULL	Maximum number of extents allowed in the segment of the LOB data partition
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment of the LOB data partition
RETENTION	VARCHAR2 (7)		Retention option. Possible values for a SecureFiles segment: ■ NONE ■ AUTO ■ MIN ■ MAX ■ DEFAULT ■ INVALID Possible values for a BasicFiles segment: ¹ ■ YES ■ NO
MINRETENTION	NUMBER		Minimum retention duration for a SecureFiles segment
PCT_INCREASE	NUMBER		Percentage increase in extent size for the LOB data partition
FREELISTS	NUMBER		Number of process freelists allocated in the segment of the LOB data partition
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated in the segment of the LOB data partition
LOGGING	VARCHAR2 (3)		Indicates whether or not changes to the LOB are logged: ■ YES ■ NO
BUFFER_POOL	VARCHAR2 (7)		Buffer pool to be used for the LOB data partition blocks: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL

Column	Datatype	NULL	Description
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for subpartition blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for subpartition blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
ENCRYPT	VARCHAR2 (4)		Indicates whether or not the LOB is encrypted. Possible values for SecureFiles: ■ YES ■ NO Possible value for BasicFiles: ■ NONE - Not applicable
COMPRESSION	VARCHAR2 (6)		Level of compression used for this LOB. Possible values for SecureFiles: ■ LOW ■ MEDIUM ■ HIGH ■ NO - Compression is off Possible value for BasicFiles: ■ NONE - Not applicable
DEDUPLICATION	VARCHAR2 (15)		Kind of deduplication used for this LOB. Possible values for SecureFiles: ■ LOB - Deduplicate ■ NO - Keep duplicates Possible value for BasicFiles: ■ NONE - Not applicable
SECUREFILE	VARCHAR2 (3)		Indicates whether the LOB is SecureFiles (YES) or not (NO)
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the LOB subpartition segment has been created (YES) or not (NO); N/A indicates that this LOB is not subpartitioned

¹ The values listed for a BasicFiles segment are supported starting with Oracle Database 11g Release 2 (11.2.0.2). In previous releases, the value for this column for a BasicFiles segment is NULL.

ALL_LOB_TEMPLATES

ALL_LOB_TEMPLATES describes the LOB subpartition templates accessible to the current user.

Related Views

- DBA_LOB_TEMPLATES describes all LOB subpartition templates in the database.
- USER_LOB_TEMPLATES describes the LOB subpartition templates owned by the current user. This view does not display the USER_NAME column.

Column	Datatype	NULL	Description
USER_NAME	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
LOB_COL_NAME	VARCHAR2 (4000)		Name of the LOB column
SUBPARTITION_NAME	VARCHAR2 (34)	NOT NULL	Name of the subpartition
LOB_SEGMENT_NAME	VARCHAR2 (34)	NOT NULL	Name of the LOB segment
TABLESPACE_NAME	VARCHAR2 (30)		Tablespace name of the subpartition

See Also:

- ["DBA_LOB_TEMPLATES"](#) on page 5-49
- ["USER_LOB_TEMPLATES"](#) on page 6-84

ALL_LOBS

ALL_LOBS displays the large objects (LOBs) contained in tables accessible to the current user. LOBs include binary large objects (BLOBs) and character large objects (CLOBs). Binary files (BFILEs) are stored outside the database, so they are not displayed by this view or the related views.

Related Views

- DBA_LOBS describes all LOBs in the database.
- USER_LOBS describes the LOBs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the object containing the LOB
TABLE_NAME	VARCHAR2 (30)		Name of the object containing the LOB
COLUMN_NAME	VARCHAR2 (4000)		Name of the LOB column or attribute
SEGMENT_NAME	VARCHAR2 (30)		Name of the LOB segment
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the LOB segment
INDEX_NAME	VARCHAR2 (30)		Name of the LOB index
CHUNK	NUMBER		Size (in bytes) of the LOB chunk as a unit of allocation or manipulation
PCTVERSION	NUMBER		Maximum percentage of the LOB space used for versioning
RETENTION	NUMBER		Maximum time duration for versioning of the LOB space
FREEPOOLS	NUMBER		Number of freepools for this LOB segment
CACHE	VARCHAR2 (10)		Indicates whether and how the LOB data is to be cached in the buffer cache: ■ YES - LOB data is placed in the buffer cache ■ NO - LOB data either is not brought into the buffer cache or is brought into the buffer cache and placed at the least recently used end of the LRU list ■ CACHEREADS - LOB data is brought into the buffer cache only during read operations but not during write operations

Column	Datatype	NULL	Description
LOGGING	VARCHAR2 (7)		Indicates whether or not changes to the LOB are logged: - NONE - Not specified See Also: the *_LOB_SUBPARTITIONS view - YES - NO
ENCRYPT	VARCHAR2 (4)		Indicates whether or not the LOB is encrypted. Possible values for SecureFiles: - YES - NO Possible value for BasicFiles: - NONE - Not applicable
COMPRESSION	VARCHAR2 (6)		Level of compression used for this LOB. Possible values for SecureFiles: - LOW - MEDIUM - HIGH - NO - Compression is off Possible value for BasicFiles: - NONE - Not applicable
DEDUPLICATION	VARCHAR2 (15)		Kind of deduplication used for this LOB. Possible values for SecureFiles: - LOB - Deduplicate - NO - Keep duplicates Possible value for BasicFiles: - NONE - Not applicable
IN_ROW	VARCHAR2 (3)		Indicates whether some of the LOBs are stored inline with the base row (YES) or not (NO). For partitioned objects, refer to the *_LOB_PARTITIONS and *_PART_LOBS views.
FORMAT	VARCHAR2 (15)		Indicates whether the LOB storage format is dependent on the endianness of the platform: - NOT APPLICABLE - ENDIAN SPECIFIC - ENDIAN NEUTRAL
PARTITIONED	VARCHAR2 (3)		Indicates whether the LOB column is in a partitioned table (YES) or not (NO)
SECUREFILE	VARCHAR2 (3)		Indicates whether the LOB is SecureFiles (YES) or not (NO)
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the LOB segment has been created (YES) or not (NO)

Column	Datatype	NULL	Description
RETENTION_TYPE ¹	VARCHAR2 (7)		Type of retention used for this LOB. Possible values for SecureFiles: - NONE - AUTO - MIN - MAX - DEFAULT - INVALID Possible values for BasicFiles: - YES - NO
RETENTION_VALUE ¹	NUMBER		Minimum retention time (in seconds). This column is only meaningful for SecureFiles with RETENTION_TYPE set to MIN.

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

ALL_LOG_GROUP_COLUMNS

ALL_LOG_GROUP_COLUMNS describes columns that are accessible to the current user and that are specified in log groups.

Related Views

- DBA_LOG_GROUP_COLUMNS describes all columns in the database that are specified in log groups.
- USER_LOG_GROUP_COLUMNS describes columns that are owned by the current user and that are specified in log groups.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the log group definition
LOG_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the log group definition
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table in which the log group is defined
COLUMN_NAME	VARCHAR2 (4000)		Name of the column or attribute of the object type column specified in the log group definition
POSITION	NUMBER		Original position of the column or attribute in the definition of the object
LOGGING_PROPERTY	VARCHAR2 (6)		Indicates whether the column or attribute would be supplementally logged (LOG) or not (NO LOG)

ALL_LOG_GROUPS

ALL_LOG_GROUPS describes the log group definitions on the tables accessible to the current user.

Related Views

- DBA_LOG_GROUPS describes the log group definitions on all tables in the database.
- USER_LOG_GROUPS describes the log group definitions on the tables owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the log group definition
LOG_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the log group definition
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table on which the log group is defined
LOG_GROUP_TYPE	VARCHAR2 (19)		Type of the log group: ■ PRIMARY KEY LOGGING ■ UNIQUE KEY LOGGING ■ FOREIGN KEY LOGGING ■ ALL COLUMN LOGGING ■ USER LOG GROUP
ALWAYS	VARCHAR2 (11)		Y indicates the log group is logged any time a row is updated; N indicates the log group is logged any time a member column is updated
GENERATED	VARCHAR2 (14)		Indicates whether the name of the supplemental log group was system generated (GENERATED_NAME) or not (USER_NAME)

ALL_MEASURE_FOLDER_CONTENTS

ALL_MEASURE_FOLDER_CONTENTS describes the contents of the OLAP measure folders accessible to the current user.

Related Views

- DBA_MEASURE_FOLDER_CONTENTS describes the contents of all OLAP measure folders in the database.
- USER_MEASURE_FOLDER_CONTENTS describes the contents of the OLAP measure folders owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the measure folder
MEASURE_FOLDER_NAME	VARCHAR2 (30)	NOT NULL	Name of a measure folder
CUBE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cube
CUBE_NAME	VARCHAR2 (30)	NOT NULL	Name of a cube included in the measure folder
MEASURE_NAME	VARCHAR2 (30)	NOT NULL	Name of a measure in the cube
ORDER_NUM	NUMBER	NOT NULL	Order number of the measure in the folder

See Also:

- ["DBA_MEASURE_FOLDER_CONTENTS"](#) on page 5-58
- ["USER_MEASURE_FOLDER_CONTENTS"](#) on page 6-85

ALL_MEASURE_FOLDERS

ALL_MEASURE_FOLDERS describes the OLAP measure folders accessible to the current user.

Related Views

- DBA_MEASURE_FOLDERS describes all OLAP measure folders in the database.

- `USER_MEASURE_FOLDERS` describes the OLAP measure folders owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the measure folder
<code>MEASURE_FOLDER_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of a measure folder
<code>DESCRIPTION</code>	<code>NVARCHAR2 (300)</code>		Description of the measure folder in the session language

See Also:

- ["DBA_MEASURE_FOLDERS"](#) on page 5-58
- ["USER_MEASURE_FOLDERS"](#) on page 6-85

ALL_METHOD_PARAMS

`ALL_METHOD_PARAMS` describes the method parameters of the object types accessible to the current user.

Related Views

- `DBA_METHOD_PARAMS` describes the method parameters of all object types in the database.
- `USER_METHOD_PARAMS` describes the method parameters of the object types owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the type
<code>TYPE_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the type
<code>METHOD_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the method
<code>METHOD_NO</code>	<code>NUMBER</code>	NOT NULL	For an overloaded method, a number distinguishing this method from others of the same. Do not confuse this number with the object ID.
<code>PARAM_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the parameter
<code>PARAM_NO</code>	<code>NUMBER</code>	NOT NULL	Parameter number (position)
<code>PARAM_MODE</code>	<code>VARCHAR2 (6)</code>		Mode of the parameter (IN, OUT, IN OUT)
<code>PARAM_TYPE_MOD</code>	<code>VARCHAR2 (7)</code>		Whether this parameter is a REF to another object
<code>PARAM_TYPE_OWNER</code>	<code>VARCHAR2 (30)</code>		Owner of the type of the parameter
<code>PARAM_TYPE_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the type of the parameter
<code>CHARACTER_SET_NAME</code>	<code>VARCHAR2 (44)</code>		Whether the character set or the method is fixed-length character set (<code>CHAR_CS</code>) or fixed-length national character set (<code>NCHAR_CS</code>), or a particular character set specified by the user

See Also:

- ["DBA_METHOD_PARAMS"](#) on page 5-58
- ["USER_METHOD_PARAMS"](#) on page 6-85

ALL_METHOD_RESULTS

ALL_METHOD_RESULTS describes the method results of the object types accessible to the current user.

Related Views

- DBA_METHOD_RESULTS describes the method results of all object types in the database.
- USER_METHOD_RESULTS describes the method results of the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the type
TYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the type
METHOD_NAME	VARCHAR2 (30)	NOT NULL	Name of the method
METHOD_NO	NUMBER	NOT NULL	For an overloaded method, a number distinguishing this method from others of the same. Do not confuse this number with the object ID.
RESULT_TYPE_MOD	VARCHAR2 (7)	NOT NULL	Whether this result is a REF to another object
RESULT_TYPE_OWNER	VARCHAR2 (30)		Owner of the type of the result
RESULT_TYPE_NAME	VARCHAR2 (30)		Name of the type of the result
CHARACTER_SET_NAME	VARCHAR2 (44)		Whether the character set or the method is fixed-length character set (CHAR_CS) or fixed-length national character set (NCHAR_CS), or a particular character set specified by the user

See Also:

- ["DBA_METHOD_RESULTS"](#) on page 5-59
- ["USER_METHOD_RESULTS"](#) on page 6-85

ALL_MINING_MODEL_ATTRIBUTES

ALL_MINING_MODEL_ATTRIBUTES describes the attributes of the mining models accessible to the current user.

Attributes correspond to the columns of data used to build a model. Columns with the same names and data types should be available in any data set to which the model is applied.

Related Views

- DBA_MINING_MODEL_ATTRIBUTES describes the attributes of all mining models in the database.
- USER_MINING_MODEL_ATTRIBUTES describes the attributes of the mining models owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the mining model
MODEL_NAME	VARCHAR2 (30)	NOT NULL	Name of the mining model
ATTRIBUTE_NAME	VARCHAR2 (30)	NOT NULL	Name of the attribute

Column	Datatype	NULL	Description
ATTRIBUTE_TYPE	VARCHAR2 (11)		Logical type of the attribute. The type is identified during the model build or apply process: - NUMERICAL - Numeric data - CATEGORICAL - Character data
DATA_TYPE	VARCHAR2 (12)		Data type of the attribute: - VARCHAR2 - NUMBER - FLOAT - CHAR - NESTED TABLE
DATA_LENGTH	NUMBER		Length of the data type
DATA_PRECISION	NUMBER		Precision of a fixed point number. Precision, which is the total number of significant decimal digits, is represented as <i>p</i> in the data type NUMBER (<i>p</i> , <i>s</i>).
DATA_SCALE	NUMBER		Scale of a fixed point number. Scale, which is the number of digits from the decimal to the least significant digit, is represented as <i>s</i> in the data type NUMBER (<i>p</i> , <i>s</i>).
USAGE_TYPE	VARCHAR2 (8)		Indicates whether the attribute was used to construct the model (ACTIVE) or not (INACTIVE). Some attributes may be eliminated by transformations or algorithmic processing. The *_MINING_MODEL_ATTRIBUTES view only lists the attributes used by the model, therefore the value of this column is always ACTIVE.
TARGET	VARCHAR2 (3)		Indicates whether the attribute is the target of a predictive model (YES) or not (NO). The target describes the result that is produced when the model is applied.

See Also:

- ["DBA_MINING_MODEL_ATTRIBUTES"](#) on page 5-59
- ["USER_MINING_MODEL_ATTRIBUTES"](#) on page 6-85
- *Oracle Data Mining Concepts* for information about model attributes

ALL_MINING_MODEL_SETTINGS

ALL_MINING_MODEL_SETTINGS describes the settings of the mining models accessible to the current user.

Model settings can be specified in a settings table that is used as input to the model build process. The settings associated with a model are algorithm-dependent. Setting values can be provided as input to the model build process. If no values are provided, then default values are used.

Related Views

- DBA_MINING_MODEL_SETTINGS describes the settings of all mining models in the database.
- USER_MINING_MODEL_SETTINGS describes the settings of the mining models owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the mining model

Column	Datatype	NULL	Description
MODEL_NAME	VARCHAR2 (30)	NOT NULL	Name of the mining model
SETTING_NAME	VARCHAR2 (30)	NOT NULL	Name of the setting
SETTING_VALUE	VARCHAR2 (4000)		Value of the setting
SETTING_TYPE	VARCHAR2 (7)		Indicates whether the default value (DEFAULT) or a user-specified value (INPUT) is used by the model

See Also:

- ["DBA_MINING_MODEL_SETTINGS"](#) on page 5-59
- ["USER_MINING_MODEL_SETTINGS"](#) on page 6-86
- *Oracle Database PL/SQL Packages and Types Reference* and *Oracle Data Mining Application Developer's Guide* for descriptions of model settings

ALL_MINING_MODELS

ALL_MINING_MODELS describes the mining models accessible to the current user.

Related Views

- DBA_MINING_MODELS describes all mining models in the database.
- USER_MINING_MODELS describes the mining models owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the mining model
MODEL_NAME	VARCHAR2 (30)	NOT NULL	Name of the mining model
MINING_FUNCTION	VARCHAR2 (30)		Function of the mining model. The function identifies the class of problems that can be solved by this model. The mining function is specified when the model is built: ■ CLASSIFICATION ■ REGRESSION ■ CLUSTERING ■ FEATURE_EXTRACTION ■ ASSOCIATION_RULES ■ ATTRIBUTE_IMPORTANCE
ALGORITHM	VARCHAR2 (30)		Algorithm used by the model. Each mining function has a default algorithm. The default can be overridden with a model setting (see *_MINING_MODEL_SETTINGS): ■ NAIVE_BAYES ■ ADAPTIVE_BAYES_NETWORK ■ DECISION_TREE ■ SUPPORT_VECTOR_MACHINES ■ KMEANS ■ O_CLUSTER ■ NONNEGATIVE_MATRIX_FACTOR ■ GENERALIZED_LINEAR_MODEL ■ APRIORI_ASSOCIATION_RULES ■ MINIMUM_DESCRIPTION_LENGTH

Column	Datatype	NULL	Description
CREATION_DATE	DATE	NOT NULL	Date that the model was created
BUILD_DURATION	NUMBER		Time (in seconds) of the model build process
MODEL_SIZE	NUMBER		Size of the model (in megabytes)
COMMENTS	VARCHAR2 (4000)		Comment applied to the model with a SQL COMMENT statement

See Also:

- ["DBA_MINING_MODELS"](#) on page 5-59
- ["USER_MINING_MODELS"](#) on page 6-86
- *Oracle Data Mining Administrator's Guide* for information about mining model schema objects
- *Oracle Data Mining Concepts* for information about Data Mining

ALL_MVIEW_AGGREGATES

ALL_MVIEW_AGGREGATES describes the grouping functions (aggregate operations) that appear in the SELECT list of materialized aggregate views accessible to the current user.

Related Views

- DBA_MVIEW_AGGREGATES describes all such grouping functions defined for all materialized views in the database.
- USER_MVIEW_AGGREGATES describes all such grouping functions defined for all materialized views owned by the current user.

Note: All three views exclude materialized views that reference remote tables or that include references to a nonstatic value such as SYSDATE or USER. These views also exclude materialized views that were created as "snapshots" prior to Oracle8i and that were never altered to enable query rewrite.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of the materialized view
POSITION_IN_SELECT	NUMBER	NOT NULL	Ordinal position of this aggregation within the SELECT list. For the position of nonaggregate elements of the select list, see "ALL_MVIEW_KEYS" on page 2-106.
CONTAINER_COLUMN	VARCHAR2 (30)	NOT NULL	Name of this column in the container table
AGG_FUNCTION	VARCHAR2 (8)		Aggregation function
DISTINCTFLAG	VARCHAR2 (1)		Indicates whether this aggregation is distinct (Y) or not (N)
MEASURE	LONG		SQL text of the measure, excluding the aggregation function. Equal to * for COUNT (*).

ALL_MVIEW_ANALYSIS

ALL_MVIEW_ANALYSIS describes the materialized views accessible to the current user. It provides additional information for analysis by applications. Minimal information is displayed for materialized views that do not support query rewrite (such as materialized views with remote master tables or nondeterministic functions).

Related Views

- DBA_MVIEW_ANALYSIS describes all such materialized views in the database.
- USER_MVIEW_ANALYSIS describes all such materialized views owned by the current user.

Note: All of the information in these views is also displayed in ALL_MVIEWS and its related views. Oracle recommends that you refer to ALL_MVIEWS for this information instead of these views.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of the materialized view
MVIEW_TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the container table (see next column)
CONTAINER_NAME	VARCHAR2 (30)		Name of the internal container in which the materialized view data is held. Normally this is the same as MVIEW_NAME. For materialized views created prior to Oracle8i, Oracle Database attaches the 6-byte prefix SNAP\$_ . If MVIEW_NAME has more than 19 bytes, then Oracle Database truncates the name to 19 bytes and adds a 4-byte sequence number as a suffix to produce a nonambiguous CONTAINER_NAME.
LAST_REFRESH_SCN	NUMBER		System change number (SCN) of the last refresh operation
LAST_REFRESH_DATE	DATE		SYSDATE of the last refresh
REFRESH_METHOD	VARCHAR2 (8)		Default refresh method: ■ FORCE ■ FAST ■ COMPLETE ■ NEVER
SUMMARY	VARCHAR2 (1)		Indicates whether this materialized view includes a GROUP BY clause or aggregation (Y) or not (N)
FULLREFRESHTIM	NUMBER		Approximate refresh time, in seconds, for full refresh (defined only when SUMMARY = Y)
INCREFRESHTIM	NUMBER		Approximate refresh time, in seconds, for fast refresh (defined only when SUMMARY = Y)
CONTAINS_VIEWS	VARCHAR2 (1)		Indicates whether this materialized view contains a view in its definition (Y) or not (N)
UNUSABLE	VARCHAR2 (1)		Indicates whether this materialized view is UNUSABLE (inconsistent data) (Y) or not (N). A materialized view can be UNUSABLE if a system failure occurs during a full refresh.
RESTRICTED_SYNTAX	VARCHAR2 (1)		Indicates whether this materialized view had a restriction in its defining query that limits the use of query rewrite (Y) or not (N). More complete information is provided by the REWRITE_CAPABILITY column of the *_MVIEWS view.

Column	Datatype	NULL	Description
INC_REFRESHABLE	VARCHAR2 (1)		Indicates whether this materialized view can be fast refreshed (Y) or not (N)
KNOWN_STALE	VARCHAR2 (1)		Indicates whether the data contained in the materialized view is known to be inconsistent with the master table data because that has been updated since the last successful refresh (Y) or not (N)
INVALID	VARCHAR2 (1)		Indicates whether this materialized view is in an invalid state (inconsistent metadata) (Y) or not (N)
REWRITE_ENABLED	VARCHAR2 (1)		Indicates whether this materialized view is currently enabled for query rewrite (Y) or not (N)
QUERY_LEN	NUMBER		Length (in bytes) of the query field
QUERY	LONG		SELECT expression of the materialized view definition
REVISION	NUMBER	NOT NULL	Reserved for internal use

ALL_MVIEW_COMMENTS

ALL_MVIEW_COMMENTS displays comments on the materialized views accessible to the current user.

Related Views

- DBA_MVIEW_COMMENTS displays comments on the materialized views in the database.
- USER_MVIEW_COMMENTS displays comments on the materialized views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of the materialized view
COMMENTS	VARCHAR2 (4000)		Comment on the materialized view

See Also:

- ["DBA_MVIEW_COMMENTS"](#) on page 5-59
- ["USER_MVIEW_COMMENTS"](#) on page 6-86

ALL_MVIEW_DETAIL_PARTITION

ALL_MVIEW_DETAIL_PARTITION displays the freshness information of the materialized views, with respect to a PCT detail partition, accessible to the current user.

Related Views

- DBA_MVIEW_DETAIL_PARTITION displays freshness information for all materialized views in the database, with respect to a PCT detail partition.
- USER_MVIEW_DETAIL_PARTITION displays freshness information for all materialized views, with respect to a PCT detail partition, owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of the materialized view
DETAILOBJ_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the detail object
DETAILOBJ_NAME	VARCHAR2 (30)	NOT NULL	Name of the detail object
DETAIL_PARTITION_NAME	VARCHAR2 (30)		Name of the detail object partition
DETAIL_PARTITION_POSITION	NUMBER		Position of the detail object partition
FRESHNESS	CHAR (5)		Freshness state (FRESH, STALE, UNKNOWN, NA, and so on)

ALL_MVIEW_DETAIL_RELATIONS

ALL_MVIEW_DETAIL_RELATIONS describes the named detail relations that are either specified in the FROM list of the subquery that defines a materialized view accessible to the current user, or that are indirectly referenced through views in that FROM list. Inline views in the materialized view definition are not represented in this view or the related views.

Related Views

- DBA_MVIEW_DETAIL_RELATIONS describes all such detail relations defined for all materialized views in the database.
- USER_MVIEW_DETAIL_RELATIONS describes such detail relations defined for all materialized views owned by the current user.

Note: All three views exclude materialized views that reference remote tables or that includes references to a nonstatic value such as SYSDATE or USER. These views also exclude materialized views that were created as *snapshots* prior to Oracle8i and that were never altered to enable query rewrite.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of the materialized view
DETAILOBJ_OWNER	VARCHAR2 (30)	NOT NULL	Detail object owner
DETAILOBJ_NAME	VARCHAR2 (30)	NOT NULL	Detail object name (that is, the name of a table or view)
DETAILOBJ_TYPE	VARCHAR2 (9)		Detail object type: ■ TABLE ■ VIEW ■ SNAPSHOT ■ CONTAINER ■ UNDEFINED
DETAILOBJ_ALIAS	VARCHAR2 (30)		Implicit or explicit alias for detail relation
DETAILOBJ_PCT	VARCHAR2 (1)		Indicates whether the detail object PCT is supported (Y) or not (N)
NUM_FRESH_PCT_PARTITIONS	NUMBER		Number of fresh PCT partitions

Column	Datatype	NULL	Description
NUM_STALE_PCT_PARTITIONS	NUMBER		Number of stale PCT partitions

ALL_MVIEW_DETAIL_SUBPARTITION

ALL_MVIEW_DETAIL_SUBPARTITION displays the freshness information of the materialized views, with respect to a PCT detail subpartition, accessible to the current user.

Related Views

- DBA_MVIEW_DETAIL_SUBPARTITION displays freshness information for all materialized views in the database, with respect to a PCT detail subpartition.
- USER_MVIEW_DETAIL_SUBPARTITION displays freshness information for all materialized views, with respect to a PCT detail subpartition, owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of the materialized view
DETAILOBJ_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the detail object
DETAILOBJ_NAME	VARCHAR2 (30)	NOT NULL	Name of the detail object
DETAIL_PARTITION_NAME	VARCHAR2 (30)		Name of the detail object partition
DETAIL_SUBPARTITION_NAME	VARCHAR2 (30)		Name of the detail object subpartition
DETAIL_SUBPARTITION_POSITION	NUMBER		Position of the detail object subpartition
FRESHNESS	CHAR (5)		Freshness state (FRESH, STALE, UNKNOWN, NA, and so on)

ALL_MVIEW_JOINS

ALL_MVIEW_JOINS describes joins between two columns in the WHERE clause of the subquery that defines a materialized view accessible to the current user.

Related Views

- DBA_MVIEW_JOINS describes all such joins for all materialized views in the database.
- USER_MVIEW_JOINS describes such joins for all materialized views owned by the current user.

Note: All three views exclude materialized views that reference remote tables or that includes references to a nonstatic value such as SYSDATE or USER. These views also exclude materialized views that were created as "snapshots" prior to Oracle8i and that were never altered to enable query rewrite.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view

Column	Datatype	NULL	Description
MVIEW_NAME	VARCHAR2 (30)	NOT NULL	Materialized view name
DETAILOBJ1_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the first object in the join ¹
DETAILOBJ1_RELATION	VARCHAR2 (30)	NOT NULL	Name of the first object in the join ¹
DETAILOBJ1_COLUMN	VARCHAR2 (30)	NOT NULL	Join column of the first object in the join ¹
OPERATOR	CHAR (1)		Join operator ¹
OPERATOR_TYPE	VARCHAR2 (1)		Indicates whether the join is an inner join (I) or the DETAILOBJ1 table is the left side of an outer join (L) ¹
DETAILOBJ2_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the second object in the join ¹
DETAILOBJ2_RELATION	VARCHAR2 (30)	NOT NULL	Name of the second object in the join ¹
DETAILOBJ2_COLUMN	VARCHAR2 (30)	NOT NULL	Join column of the second object in the join ¹

¹ These rows relate only to materialized join views and materialized aggregate views. They describe the two detail objects of a materialized view join.

ALL_MVIEW_KEYS

ALL_MVIEW_KEYS describes the columns or expressions in the SELECT list upon which materialized views accessible to the current user are based.

Related Views

- DBA_MVIEW_KEYS describes such columns and expressions for all materialized views in the database.
- USER_MVIEW_KEYS describes such columns and expressions for all materialized views owned by the current user.

Note: All three views exclude materialized views that reference remote tables or that includes references to a nonstatic value such as SYSDATE or USER. These views also exclude materialized views that were created as *snapshots* prior to Oracle8i and that were never altered to enable query rewrite.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2 (30)	NOT NULL	Materialized view name
POSITION_IN_SELECT	NUMBER	NOT NULL	Ordinal position of this key within the SELECT list
CONTAINER_COLUMN	VARCHAR2 (30)	NOT NULL	Name of the column in the container table
DETAILOBJ_OWNER	VARCHAR2 (30)	NOT NULL	Detail object owner
DETAILOBJ_NAME	VARCHAR2 (30)	NOT NULL	Detail object name (for example, the name of a table or view)
DETAILOBJ_ALIAS	VARCHAR2 (30)		Implicit or explicit alias for detail relation
DETAILOBJ_TYPE	VARCHAR2 (5)		Detail object type: ■ TABLE ■ VIEW
DETAILOBJ_COLUMN	VARCHAR2 (30)	NOT NULL	Name of the detail relation column

ALL_MVIEW_LOGS

ALL_MVIEW_LOGS describes all materialized view logs accessible to the current user.

Related Views

- DBA_MVIEW_LOGS describes all materialized view logs in the database.
- USER_MVIEW_LOGS describes all materialized view logs owned by the current user.

Column	Datatype	NULL	Description
LOG_OWNER	VARCHAR2 (30)		Owner of the materialized view log
MASTER	VARCHAR2 (30)		Name of the master table or master materialized view whose changes are logged
LOG_TABLE	VARCHAR2 (30)		Name of the table where the changes to the master table or master materialized view are logged
LOG_TRIGGER	VARCHAR2 (30)		Obsolete with Oracle8i and later. Set to NULL. Formerly, this parameter was an after-row trigger on the master which inserted rows into the log.
ROWIDS	VARCHAR2 (3)		Indicates whether rowid information is recorded (YES) or not (NO)
PRIMARY_KEY	VARCHAR2 (3)		Indicates whether primary key information is recorded (YES) or not (NO)
OBJECT_ID	VARCHAR2 (3)		Indicates whether object identifier information in an object table is recorded (YES) or not (NO)
FILTER_COLUMNS	VARCHAR2 (3)		Indicates whether filter column information is recorded (YES) or not (NO)
SEQUENCE	VARCHAR2 (3)		Indicates whether the sequence value, which provides additional ordering information, is recorded (YES) or not (NO)
INCLUDE_NEW_VALUES	VARCHAR2 (3)		Indicates whether both old and new values are recorded (YES) or old values are recorded but new values are not recorded (NO)
PURGE_ASYNCHRONOUS	VARCHAR2 (3)		Indicates whether the materialized view log is purged asynchronously (YES) or not (NO)
PURGE_DEFERRED	VARCHAR2 (3)		Indicates whether the materialized view log is purged in a deferred manner (YES) or not (NO)
PURGE_START	DATE		For deferred purge, the purge start date
PURGE_INTERVAL	VARCHAR2 (200)		For deferred purge, the purge interval
LAST_PURGE_DATE	DATE		Date of the last purge
LAST_PURGE_STATUS	NUMBER		Status of the last purge (error code or 0 for success)
NUM_ROWS_PURGED	NUMBER		Number of rows purged in the last purge
COMMIT_SCN_BASED	VARCHAR2 (3)		Indicates whether the materialized view log is commit SCN-based (YES) or not (NO)

See Also:

- ["DBA_MVIEW_LOGS"](#) on page 5-60
- ["USER_MVIEW_LOGS"](#) on page 6-87

ALL_MVIEW_REFRESH_TIMES

ALL_MVIEW_REFRESH_TIMES describes refresh times of the materialized views accessible to the current user.

Related Views

- `DBA_MVIEW_REFRESH_TIMES` describes refresh times of all materialized views in the database.
- `USER_MVIEW_REFRESH_TIMES` describes refresh times of the materialized views owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view
NAME	VARCHAR2 (30)	NOT NULL	Name of the materialized view
MASTER_OWNER	VARCHAR2 (30)		Owner of the master table
MASTER	VARCHAR2 (30)		Name of the master table
LAST_REFRESH	DATE		<code>SYSDATE</code> from the master site at the time of the last refresh

See Also:

- ["DBA_MVIEW_REFRESH_TIMES"](#) on page 5-60
- ["USER_MVIEW_REFRESH_TIMES"](#) on page 6-87

ALL_MVIEWS

`ALL_MVIEWS` describes all materialized views accessible to the current user.

Related views

- `DBA_MVIEWS` describes all materialized views in the database.
- `USER_MVIEWS` describes all materialized views owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Schema in which the materialized view was created
MVIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of the materialized view
CONTAINER_NAME	VARCHAR2 (30)	NOT NULL	Name of the container in which the materialized view's data is held. Normally this is the same as <code>MVIEW_NAME</code> . For materialized views created prior to Oracle8i, Oracle Database attaches the 6-byte prefix <code>SNAP\$_</code> . If <code>MVIEW_NAME</code> has more than 19 bytes, then Oracle Database truncates the name to 19 bytes and may add a 4-byte sequence number as a suffix to produce a nonambiguous <code>CONTAINER_NAME</code> .
QUERY	LONG		Query that defines the materialized view
QUERY_LEN	NUMBER (38)		Length (in bytes) of the defining query
UPDATABLE	VARCHAR2 (1)		Indicates whether the materialized view is updatable (Y) or not (N)
UPDATE_LOG	VARCHAR2 (30)		For updatable materialized views, the filename of the update log
MASTER_ROLLBACK_SEG	VARCHAR2 (30)		Rollback segment for the master site or the master materialized view site
MASTER_LINK	VARCHAR2 (128)		Database link for the master site or the master materialized view site
REWRITE_ENABLED	VARCHAR2 (1)		Indicates whether rewrite is enabled (Y) or not (N)

Column	Datatype	NULL	Description
REWRITE_CAPABILITY	VARCHAR2 (9)		Indicates whether the materialized view is eligible for rewrite, and if so, what rules must be followed: - NONE - Materialized view cannot be used for rewrite, because rewrite is disallowed or prevented - TEXTMATCH - Defining query of the materialized view contained restrictions on the use of query rewrite - GENERAL - Defining query of the materialized view contained no restrictions on the use of query rewrite, so Oracle Database can apply any rewrite rule that is supported
REFRESH_MODE	VARCHAR2 (6)		Refresh mode of the materialized view: - DEMAND - Oracle Database refreshes this materialized view whenever an appropriate refresh procedure is called - COMMIT - Oracle Database refreshes this materialized view when a transaction on one of the materialized view's masters commits - NEVER - Oracle Database never refreshes this materialized view
REFRESH_METHOD	VARCHAR2 (8)		Default method used to refresh the materialized view (can be overridden through the API): - COMPLETE - Materialized view is completely refreshed from the masters - FORCE - Oracle Database performs a fast refresh if possible, otherwise a complete refresh - FAST - Oracle Database performs an incremental refresh applying changes that correspond to changes in the masters since the last refresh - NEVER - User specified that Oracle Database should not refresh this materialized view
BUILD_MODE	VARCHAR2 (9)		Indicates how the materialized view was populated during creation: - IMMEDIATE - Populated from the masters during creation - DEFERRED - Not populated during creation. Must be explicitly populated later by the user. - PREBUILT - Populated with an existing table during creation. The relationship of the contents of this prebuilt table to the materialized view's masters is unknown to Oracle Database.
FAST_REFRESHABLE	VARCHAR2 (18)		Indicates whether the materialized view is eligible for incremental (fast) refresh. Oracle Database calculates this value statically, based on the materialized view definition query: - NO - Materialized view is not fast refreshable, and hence is complex - DML - Fast refresh is supported only for DML operations - DIRLOAD_DML - Fast refresh is supported for both direct loads and DML operations - DIRLOAD_LIMITEDDML - Fast refresh is supported for direct loads and a subset of DML operations
LAST_REFRESH_TYPE	VARCHAR2 (8)		Method used for the most recent refresh: - COMPLETE - Most recent refresh was complete - FAST - Most recent refresh was fast (incremental) - NA - Materialized view has not yet been refreshed (for example, if it was created DEFERRED)

Column	Datatype	NULL	Description
LAST_REFRESH_DATE	DATE		Date on which the materialized view was most recently refreshed (blank if not yet populated)
STALENESS	VARCHAR2 (19)		Relationship between the contents of the materialized view and the contents of the materialized view's masters: ■ FRESH - Materialized view is a read-consistent view of the current state of its masters ■ STALE - Materialized view is out of date because one or more of its masters has changed. If the materialized view was FRESH before it became STALE, then it is a read-consistent view of a former state of its masters. ■ UNUSABLE - Materialized view is not a read-consistent view of its masters from any point in time ■ UNKNOWN - Oracle Database does not know whether the materialized view is in a read-consistent view of its masters from any point in time (this is the case for materialized views created on prebuilt tables) ■ UNDEFINED - Materialized view has remote masters. The concept of staleness is not defined for such materialized views.
AFTER_FAST_REFRESH	VARCHAR2 (19)		Specifies the staleness value that will occur if a fast refresh is applied to this materialized view. Its values are the same as for the STALENESS column, plus the value NA, which is used when fast refresh is not applicable to this materialized view.
UNKNOWN_PREBUILT	VARCHAR2 (1)		Indicates whether the materialized view is prebuilt (Y) or not (N)
UNKNOWN_PLSQL_FUNC	VARCHAR2 (1)		Indicates whether the materialized view contains PL/SQL functions (Y) or not (N)
UNKNOWN_EXTERNAL_TABLE	VARCHAR2 (1)		Indicates whether the materialized view contains external tables (Y) or not (N)
UNKNOWN_CONSIDER_FRESH	VARCHAR2 (1)		Indicates whether the materialized view is considered fresh (Y) or not (N)
UNKNOWN_IMPORT	VARCHAR2 (1)		Indicates whether the materialized view is imported (Y) or not (N)
UNKNOWN_TRUSTED_FD	VARCHAR2 (1)		Indicates whether the materialized view uses trusted constraints for refresh (Y) or not (N)
COMPILE_STATE	VARCHAR2 (19)		Validity of the materialized view with respect to the objects upon which it depends: ■ VALID - Materialized view has been validated without error, and no object upon which it depends has changed since the last validation ■ NEEDS_COMPILE - Some object upon which the materialized view depends has changed. An ALTER MATERIALIZED VIEW . . . COMPILE statement is required to validate this materialized view. ■ ERROR - Materialized view has been validated with one or more errors
USE_NO_INDEX	VARCHAR2 (1)		Indicates whether the materialized view was created using the USING NO INDEX clause (Y) or the materialized view was created with the default index (N). The USING NO INDEX clause suppresses the creation of the default index.
STALE_SINCE	DATE		Time from when the materialized view became stale
NUM_PCT_TABLES	NUMBER		Number of PCT detail tables
NUM_FRESH_PCT_REGIONS	NUMBER		Number of fresh PCT partition regions

Column	Datatype	NULL	Description
NUM_STALE_PCT_REGIONS	NUMBER		Number of stale PCT partition regions

See Also:

- ["DBA_MVIEWS"](#) on page 5-61
- ["USER_MVIEWS"](#) on page 6-87
- *Oracle Database Advanced Replication* for more information on materialized views to support replication
- *Oracle Database Data Warehousing Guide* for more information on materialized views to support data warehousing

ALL_NESTED_TABLE_COLS

ALL_NESTED_TABLE_COLS describes the columns of the nested tables accessible to the current user. To gather statistics for this view, use the ANALYZE SQL statement or the DBMS_STATS package.

Related Views

- DBA_NESTED_TABLE_COLS describes the columns of all nested tables in the database.
- USER_NESTED_TABLE_COLS describes the columns of the nested tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the nested table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the nested table
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Column name
DATA_TYPE	VARCHAR2 (106)		Datatype of the column
DATA_TYPE_MOD	VARCHAR2 (3)		Datatype modifier of the column
DATA_TYPE_OWNER	VARCHAR2 (30)		Owner of the datatype of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER datatype; binary precision for FLOAT datatype; NULL for all other datatypes
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
NULLABLE	VARCHAR2 (1)		Indicates whether a column allows NULLs. The value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY.
COLUMN_ID	NUMBER		Sequence number of the column as created
DEFAULT_LENGTH	NUMBER		Length of the default value for the column
DATA_DEFAULT	LONG		Default value for the column
NUM_DISTINCT	NUMBER		Number of distinct values in the column ¹
LOW_VALUE	RAW (32)		Low value in the column ¹
HIGH_VALUE	RAW (32)		High value in the column ¹

Column	Datatype	NULL	Description
DENSITY	NUMBER		If a histogram is available on <code>COLUMN_NAME</code>, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on <code>COLUMN_NAME</code>, then the value of this column is $1/\text{NUM\_DISTINCT}$.¹
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in the histogram for the column Note: The number of buckets in a histogram is specified in the <code>SIZE</code> parameter of the <code>ANALYZE SQL</code> statement. However, Oracle Database does not create a histogram with more buckets than the number of rows in the sample. Also, if the sample contains any values that are very repetitious, Oracle Database creates the specified number of buckets, but the value indicated by this column may be smaller because of an internal compression algorithm.
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
CHARACTER_SET_NAME	VARCHAR2 (44)		Name of the character set: - CHAR_CS - NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
GLOBAL_STATS	VARCHAR2 (3)		For partitioned tables, indicates whether column statistics were collected for the table as a whole (YES) or were estimated from statistics on underlying partitions and subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
CHAR_LENGTH	NUMBER		Displays the length of the column in characters. This value only applies to the following datatypes: - CHAR - VARCHAR2 - NCHAR - NVARCHAR
CHAR_USED	VARCHAR2 (1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the datatype is not any of the following (NULL): - CHAR - VARCHAR2 - NCHAR - NVARCHAR2
V80_FMT_IMAGE	VARCHAR2 (3)		Indicates whether the column data is in release 8.0 image format (YES) or not (NO)
DATA_UPGRADED	VARCHAR2 (3)		Indicates whether the column data has been upgraded to the latest type version format (YES) or not (NO)
HIDDEN_COLUMN	VARCHAR2 (3)		Indicates whether the column is a hidden column (YES) or not (NO)
VIRTUAL_COLUMN	VARCHAR2 (3)		Indicates whether the column is a virtual column (YES) or not (NO)
SEGMENT_COLUMN_ID	NUMBER		Sequence number of the column in the segment
INTERNAL_COLUMN_ID	NUMBER	NOT NULL	Internal sequence number of the column

Column	Datatype	NULL	Description
HISTOGRAM	VARCHAR2 (15)		Indicates existence/type of histogram: ■ NONE ■ FREQUENCY ■ HEIGHT BALANCED
QUALIFIED_COL_NAME	VARCHAR2 (4000)		Qualified column name

¹ These columns remain for backward compatibility with Oracle7. This information is now in the {TAB | PART}_COL_STATISTICS views.

ALL_NESTED_TABLES

ALL_NESTED_TABLES describes the nested tables in tables accessible to the current user.

Related Views

- DBA_NESTED_TABLES describes all nested tables in the database.
- USER_NESTED_TABLES describes nested tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the nested table
TABLE_NAME	VARCHAR2 (30)		Name of the nested table
TABLE_TYPE_OWNER	VARCHAR2 (30)		Owner of the type of which the nested table was created
TABLE_TYPE_NAME	VARCHAR2 (30)		Name of the type of the nested table
PARENT_TABLE_NAME	VARCHAR2 (30)		Name of the parent table containing the nested table
PARENT_TABLE_COLUMN	VARCHAR2 (4000)		Column name of the parent table that corresponds to the nested table
STORAGE_SPEC	VARCHAR2 (30)		Indicates whether storage for the nested table is USER_SPECIFIED or DEFAULT
RETURN_TYPE	VARCHAR2 (20)		Return type of the varray column (LOCATOR) or (VALUE)
ELEMENT_SUBSTITUTABLE	VARCHAR2 (25)		Indicates whether the nested table element is substitutable (Y) or not (N)

ALL_OBJ_COLATTRS

ALL_OBJ_COLATTRS describes object columns and attributes contained in the tables accessible to the current user.

Related Views

- DBA_OBJ_COLATTRS describes object columns and attributes contained in all tables in the database.
- USER_OBJ_COLATTRS describes object columns and attributes contained in the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table containing the object column or attribute
COLUMN_NAME	VARCHAR2 (4000)		Fully qualified name of the object column or attribute

Column	Datatype	NULL	Description
SUBSTITUTABLE	VARCHAR2 (15)		Indicates whether the column is substitutable (Y) or not (N)

See Also:

- ["DBA_OBJ_COLATTRS"](#) on page 5-62
- ["USER_OBJ_COLATTRS"](#) on page 6-88

ALL_OBJECT_TABLES

ALL_OBJECT_TABLES describes the object tables accessible to the current user.

Related Views

- DBA_OBJECT_TABLES describes all object tables in the database.
- USER_OBJECT_TABLES describes the object tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the table; NULL for partitioned, temporary, and index-organized tables
CLUSTER_NAME	VARCHAR2 (30)		Name of the cluster, if any, to which the table belongs
IOT_NAME	VARCHAR2 (30)		Name of the index-organized table, if any, to which the overflow or mapping table entry belongs. If the IOT_TYPE column is not NULL, then this column contains the base table name.
STATUS	VARCHAR2 (8)		If a previous DROP TABLE operation failed, indicates whether the table is unusable (UNUSABLE) or valid (VALID)
PCT_FREE	NUMBER		Minimum percentage of free space in a block; NULL for partitioned tables
PCT_USED	NUMBER		Minimum percentage of used space in a block; NULL for partitioned tables
INI_TRANS	NUMBER		Initial number of transactions; NULL for partitioned tables
MAX_TRANS	NUMBER		Maximum number of transactions; NULL for partitioned tables
INITIAL_EXTENT	NUMBER		Size of the initial extent (in bytes); NULL for partitioned tables
NEXT_EXTENT	NUMBER		Size of secondary extents (in bytes); NULL for partitioned tables
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment; NULL for partitioned tables
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment; NULL for partitioned tables
PCT_INCREASE	NUMBER		Percentage increase in extent size; NULL for partitioned tables
FREELISTS	NUMBER		Number of process freelists allocated to the segment; NULL for partitioned tables
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to the segment; NULL for partitioned tables

Column	Datatype	NULL	Description
LOGGING	VARCHAR2 (3)		Indicates whether or not changes to the table are logged: ■ YES ■ NO
BACKED_UP	VARCHAR2 (1)		Indicates whether the table has been backed up since the last modification (Y) or not (N)
NUM_ROWS	NUMBER		Number of rows in the table
BLOCKS	NUMBER		Number of used blocks in the table
EMPTY_BLOCKS	NUMBER		Number of empty (never used) blocks in the table
AVG_SPACE	NUMBER		Average available free space in the table
CHAIN_CNT	NUMBER		Number of chained rows in the table
AVG_ROW_LEN	NUMBER		Average row length, including row overhead
AVG_SPACE_FREELIST_BLOCKS	NUMBER		Average free space of all blocks on a freelist
NUM_FREELIST_BLOCKS	NUMBER		Number of blocks on the freelist
DEGREE	VARCHAR2 (10)		Number of parallel execution processes per instance for scanning the table, or DEFAULT
INSTANCES	VARCHAR2 (10)		Number of instances across which the table is to be scanned, or DEFAULT
CACHE	VARCHAR2 (5)		Indicates whether the table is to be cached in the buffer cache (Y) or not (N)
TABLE_LOCK	VARCHAR2 (8)		Indicates whether table locking is enabled (ENABLED) or disabled (DISABLED)
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this table
LAST_ANALYZED	DATE		Date on which this table was most recently analyzed
PARTITIONED	VARCHAR2 (3)		Indicates whether the table is partitioned (YES) or not (NO)
IOT_TYPE	VARCHAR2 (12)		If the table is an index-organized table, then IOT_TYPE is IOT, IOT_OVERFLOW, or IOT_MAPPING. If the table is not an index-organized table, then IOT_TYPE is NULL.
OBJECT_ID_TYPE	VARCHAR2 (16)		Indicates whether the object ID (OID) is USER-DEFINED or SYSTEM GENERATED
TABLE_TYPE_OWNER	VARCHAR2 (30)		Owner of the type of the table
TABLE_TYPE	VARCHAR2 (30)		Type of the table
TEMPORARY	VARCHAR2 (1)		Indicates whether this is a temporary table (Y) or not (N)
SECONDARY	VARCHAR2 (1)		Indicates whether the object table is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)
NESTED	VARCHAR2 (3)		Indicates whether the table is a nested table (YES) or not (NO)
BUFFER_POOL	VARCHAR2 (7)		Buffer pool to be used for table blocks: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for table blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.

Column	Datatype	NULL	Description
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for table blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
ROW_MOVEMENT	VARCHAR2 (8)		Indicates whether partitioned row movement is enabled (ENABLED) or disabled (DISABLED)
GLOBAL_STATS	VARCHAR2 (3)		For partitioned tables, indicates whether statistics for the table as a whole (global statistics) are accurate (YES) or whether they were not collected and have to be estimated from statistics on underlying partitions and subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
DURATION	VARCHAR2 (15)		Indicates the duration of a temporary table: ■ SYS\$SESSION - Rows are preserved for the duration of the session ■ SYS\$TRANSACTION - Rows are deleted after COMMIT Null - Permanent table
SKIP_CORRUPT	VARCHAR2 (8)		Indicates whether Oracle Database ignores blocks marked corrupt during table and index scans (ENABLED) or raises an error (DISABLED). To enable this feature, run the DBMS_REPAIR.SKIP_CORRUPT_BLOCKS procedure.
MONITORING	VARCHAR2 (3)		Indicates whether the table has the MONITORING attribute set (YES) or not (NO)
CLUSTER_OWNER	VARCHAR2 (30)		Owner of the cluster, if any, to which the table belongs
DEPENDENCIES	VARCHAR2 (8)		Indicates whether row-level dependency tracking is enabled (ENABLED) or disabled (DISABLED)
COMPRESSION	VARCHAR2 (8)		Indicates whether table compression is enabled (ENABLED) or not (DISABLED); NULL for partitioned tables
COMPRESS_FOR	VARCHAR2 (12)		Default compression for what kind of operations: ■ BASIC ■ OLTP ■ QUERY LOW¹ ■ QUERY HIGH¹ ■ ARCHIVE LOW¹ ■ ARCHIVE HIGH¹ ■ NULL
DROPPED	VARCHAR2 (3)		Indicates whether the table has been dropped and is in the recycle bin (YES) or not (NO); NULL for partitioned tables
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the table segment has been created (YES) or not (NO)

¹ Hybrid columnar compression is a feature of Oracle Exadata. See Oracle Exadata Storage Server Software documentation for more information.

See Also:

- ["DBA_OBJECT_TABLES"](#) on page 5-63
- ["USER_OBJECT_TABLES"](#) on page 6-88

ALL_OBJECTS

ALL_OBJECTS describes all objects accessible to the current user.

Related Views

- DBA_OBJECTS describes all objects in the database.
- USER_OBJECTS describes all objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
SUBOBJECT_NAME	VARCHAR2 (30)		Name of the subobject (for example, partition)
OBJECT_ID	NUMBER	NOT NULL	Dictionary object number of the object
DATA_OBJECT_ID	NUMBER		Dictionary object number of the segment that contains the object
			Note: OBJECT_ID and DATA_OBJECT_ID display data dictionary metadata. Do not confuse these numbers with the unique 16-byte object identifier (<i>object ID</i>) that Oracle Database assigns to row objects in object tables in the system.
OBJECT_TYPE	VARCHAR2 (19)		Type of the object (such as TABLE, INDEX)
CREATED	DATE	NOT NULL	Timestamp for the creation of the object
LAST_DDL_TIME	DATE	NOT NULL	Timestamp for the last modification of the object resulting from a DDL statement (including grants and revokes)
TIMESTAMP	VARCHAR2 (19)		Timestamp for the specification of the object (character data)
STATUS	VARCHAR2 (7)		Status of the object: ▪ VALID ▪ INVALID ▪ N/A
TEMPORARY	VARCHAR2 (1)		Indicates whether the object is temporary (the current session can see only data that it placed in this object itself) (Y) or not (N)
GENERATED	VARCHAR2 (1)		Indicates whether the name of this object was system-generated (Y) or not (N)
SECONDARY	VARCHAR2 (1)		Indicates whether this is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)
NAMESPACE	NUMBER	NOT NULL	Namespace for the object
EDITION_NAME	VARCHAR2 (30)		Name of the edition in which the object is actual

ALL_OBJECTS_AE

ALL_OBJECTS_AE describes the objects (across all editions) accessible to the current user. Dropped objects appear in this view with OBJECT_TYPE = NON-EXISTENT.

Related Views

- [DBA_OBJECTS_AE](#) describes all objects (across all editions) in the database.
- [USER_OBJECTS_AE](#) describes the objects (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
SUBOBJECT_NAME	VARCHAR2 (30)		Name of the subobject (for example, partition)
OBJECT_ID	NUMBER	NOT NULL	Dictionary object number of the object
DATA_OBJECT_ID	NUMBER		Dictionary object number of the segment which contains the object
OBJECT_TYPE	VARCHAR2 (19)		Type of the object
CREATED	DATE	NOT NULL	Timestamp for the creation of the object
LAST_DDL_TIME	DATE	NOT NULL	Timestamp for the last modification of the object resulting from a DDL statement (including grants and revokes)
TIMESTAMP	VARCHAR2 (19)		Timestamp for the specification of the object (character data)
STATUS	VARCHAR2 (7)		Status of the object: ■ VALID ■ INVALID ■ N/A
TEMPORARY	VARCHAR2 (1)		Indicates whether the object is temporary (the current session can see only data that it placed in this object itself) (Y) or not (N)
GENERATED	VARCHAR2 (1)		Indicates whether the name of this object was system-generated (Y) or not (N)
SECONDARY	VARCHAR2 (1)		Indicates whether this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y) or not (N)
NAMESPACE	NUMBER	NOT NULL	Namespace for the object
EDITION_NAME	VARCHAR2 (30)		Name of the edition in which the object is actual

See Also:

- ["DBA_OBJECTS_AE"](#) on page 5-63
- ["USER_OBJECTS_AE"](#) on page 6-89

ALL_OPANCILLARY

`ALL_OPANCILLARY` describes operators whose bindings are ancillary to other (primary) operators.

Related Views

- `DBA_OPANCILLARY` describes such information about all operators in the database.
- `USER_OPANCILLARY` describes such information about operators owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the ancillary operator
OPERATOR_NAME	VARCHAR2 (30)	NOT NULL	Name of the ancillary operator
BINDING#	NUMBER	NOT NULL	Binding number the of ancillary operator
PRIMOP_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the primary operator
PRIMOP_NAME	VARCHAR2 (30)	NOT NULL	Name of the primary operator
PRIMOP_BIND#	NUMBER	NOT NULL	Binding number of the primary operator

ALL_OPARGUMENTS

ALL_OPARGUMENTS describes arguments for each operator binding accessible to the current user.

Related Views

- DBA_OPARGUMENTS describes arguments of all operator bindings in the database.
- USER_OPARGUMENTS describes arguments of all operator bindings owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the operator argument
OPERATOR_NAME	VARCHAR2 (30)	NOT NULL	Name of the operator argument
BINDING#	NUMBER	NOT NULL	Binding number of the operator argument
POSITION	NUMBER	NOT NULL	Position of the operator argument (1, 2, 3, ...)
ARGUMENT_TYPE	VARCHAR2 (61)		Datatype of the operator argument

ALL_OPBINDINGS

ALL_OPBINDINGS describes the binding functions and methods on the operators accessible to the current user.

Related Views

- DBA_OPBINDINGS describes the binding functions and methods on all operators in the database.
- USER_OPBINDINGS describes the binding functions and methods on the operators owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the operator
OPERATOR_NAME	VARCHAR2 (30)	NOT NULL	Name of the operator
BINDING#	NUMBER	NOT NULL	Binding number of the operator
FUNCTION_NAME	VARCHAR2 (92)		Name of the binding function or method as specified by the user
RETURN_SCHEMA	VARCHAR2 (30)		Name of the schema of the return type if the return type of the binding is an object type
RETURN_TYPE	VARCHAR2 (30)		Name of the return type

Column	Datatype	NULL	Description
IMPLEMENTATION_TYPE_SCHEMA	VARCHAR2 (30)		If the operator was created WITH INDEX CONTEXT or SCAN CONTEXT, then this column displays the schema of the implementation type used by the functional implementation of the operator as a scan context (null if the operator was created without this syntax). See Also: the CREATE OPERATOR statement in <i>Oracle Database SQL Language Reference</i>
IMPLEMENTATION_TYPE	VARCHAR2 (30)		If the operator was created WITH INDEX CONTEXT or SCAN CONTEXT, then this column displays the name of the implementation type used by the functional implementation of the operator as a scan context (null if the operator was created without this syntax). See Also: the CREATE OPERATOR statement in <i>Oracle Database SQL Language Reference</i>
PROPERTY	VARCHAR2 (43)		Property of the operator binding: - WITH INDEX CONTEXT - COMPUTE ANCILLARY DATA - ANCILLARY TO - WITH COLUMN CONTEXT - WITH INDEX, COLUMN CONTEXT - COMPUTE ANCILLARY DATA, WITH COLUMN CONTEXT

See Also:

- ["DBA_OPBINDINGS"](#) on page 5-64
- ["USER_OPBINDINGS"](#) on page 6-89

ALL_OPERATOR_COMMENTS

ALL_OPERATOR_COMMENTS displays comments for the user-defined operators accessible to the current user.

Related Views

- DBA_OPERATOR_COMMENTS displays comments for all user-defined operators in the database.
- USER_OPERATOR_COMMENTS displays comments for the user-defined operators owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the user-defined operator
OPERATOR_NAME	VARCHAR2 (30)	NOT NULL	Name of the user-defined operator
COMMENTS	VARCHAR2 (4000)		Comment for the user-defined operator

See Also:

- ["DBA_OPERATOR_COMMENTS"](#) on page 5-64
- ["USER_OPERATOR_COMMENTS"](#) on page 6-89

ALL_OPERATORS

ALL_OPERATORS describes the operators accessible to the current user.

Related Views

- `DBA_OPERATORS` describes all operators in the database.
- `USER_OPERATORS` describes the operators owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the operator
OPERATOR_NAME	VARCHAR2 (30)	NOT NULL	Name of the operator
NUMBER_OF_BINDS	NUMBER	NOT NULL	Number of bindings associated with the operator

See Also:

- ["DBA_OPERATORS"](#) on page 5-64
- ["USER_OPERATORS"](#) on page 6-89

ALL_OUTLINE_HINTS

`ALL_OUTLINE_HINTS` is a synonym for `USER_OUTLINE_HINTS`.

See Also: ["USER_OUTLINE_HINTS"](#) on page 6-89

ALL_OUTLINES

`ALL_OUTLINES` is a synonym for `USER_OUTLINES`.

See Also: ["USER_OUTLINES"](#) on page 6-89

Static Data Dictionary Views: ALL_PART_COL_STATISTICS to DATABASE_PROPERTIES

This chapter contains the static data dictionary views ALL_PART_COL_STATISTICS through DATABASE_PROPERTIES.

ALL_PART_COL_STATISTICS

ALL_PART_COL_STATISTICS displays column statistics and histogram information for the table partitions accessible to the current user.

Related Views

- DBA_PART_COL_STATISTICS displays column statistics and histogram information for all table partitions in the database.
- USER_PART_COL_STATISTICS displays column statistics and histogram information for the table partitions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the partitioned table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
PARTITION_NAME	VARCHAR2 (30)		Name of the table partition
COLUMN_NAME	VARCHAR2 (4000)		Name of the column
NUM_DISTINCT	NUMBER		Number of distinct values in the column
LOW_VALUE	RAW (32)		Low value in the column
HIGH_VALUE	RAW (32)		High value in the column
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in histogram for the column
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the column
LAST_ANALYZED	DATE		Date on which the column was most recently analyzed

Column	Datatype	NULL	Description
GLOBAL_STATS	VARCHAR2 (3)		Indicates whether column statistics were collected for the partition as a whole (YES) or were estimated from statistics on underlying subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
HISTOGRAM	VARCHAR2 (15)		Indicates existence/type of histogram: ■ NONE ■ FREQUENCY ■ HEIGHT BALANCED

See Also:

- ["DBA_PART_COL_STATISTICS"](#) on page 5-68
- ["USER_PART_COL_STATISTICS"](#) on page 6-90

ALL_PART_HISTOGRAMS

ALL_PART_HISTOGRAMS displays the histogram data (endpoints per histogram) for the histograms on the table partitions accessible to the current user.

Related Views

- DBA_PART_HISTOGRAMS displays the histogram data for the histograms on all table partitions in the database.
- USER_PART_HISTOGRAMS displays the histogram data for the histograms on the table partitions owned by the current user. This view does not display the OWNER column.

Note: These views are populated only if you collect statistics on the index using the ANALYZE statement or the DBMS_STATS package.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table
PARTITION_NAME	VARCHAR2 (30)		Name of the table partition
COLUMN_NAME	VARCHAR2 (4000)		Name of the column
BUCKET_NUMBER	NUMBER		Bucket number of the histogram
ENDPOINT_VALUE	NUMBER		Normalized endpoint values for the bucket
ENDPOINT_ACTUAL_VALUE	VARCHAR2 (1000)		Actual (not normalized) string value of the endpoint for the bucket

See Also:

- ["DBA_PART_HISTOGRAMS"](#) on page 5-69
- ["USER_PART_HISTOGRAMS"](#) on page 6-90

ALL_PART_INDEXES

ALL_PART_INDEXES displays the object-level partitioning information for the partitioned indexes accessible to the current user.

Related Views

- DBA_PART_INDEXES displays the object-level partitioning information for all partitioned indexes in the database.
- USER_PART_INDEXES displays the object-level partitioning information for the partitioned indexes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the partitioned index
INDEX_NAME	VARCHAR2 (30)	NOT NULL	Name of the partitioned index
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the partitioned table
PARTITIONING_TYPE	VARCHAR2 (9)		Type of the partitioning method: ■ NONE - Not specified See Also: the *_INDEXES view ■ RANGE ■ HASH ■ SYSTEM ■ LIST ■ REFERENCE
SUBPARTITIONING_TYPE	VARCHAR2 (9)		Type of the composite partitioning method: ■ NONE - Not specified See Also: the *_INDEXES view ■ RANGE ■ HASH ■ SYSTEM ■ LIST ■ REFERENCE
PARTITION_COUNT	NUMBER	NOT NULL	Number of partitions in the index
DEF_SUBPARTITION_COUNT	NUMBER		For a composite-partitioned index, the default number of subpartitions, if specified
PARTITIONING_KEY_COUNT	NUMBER	NOT NULL	Number of columns in the partitioning key
SUBPARTITIONING_KEY_COUNT	NUMBER		For a composite-partitioned index, the number of columns in the subpartitioning key
LOCALITY	VARCHAR2 (6)		Indicates whether the partitioned index is local (LOCAL) or global (GLOBAL)
ALIGNMENT	VARCHAR2 (12)		Indicates whether the partitioned index is prefixed (PREFIXED) or non-prefixed (NON_PREFIXED)
DEF_TABLESPACE_NAME	VARCHAR2 (30)		For a local index, the default tablespace to be used when adding or splitting a table partition
DEF_PCT_FREE	NUMBER	NOT NULL	For a local index, the default PCTFREE value to be used when adding a table partition
DEF_INI_TRANS	NUMBER	NOT NULL	For a local index, the default INITRANS value to be used when adding a table partition
DEF_MAX_TRANS	NUMBER	NOT NULL	For a local index, the default MAXTRANS value to be used when adding a table partition

Column	Datatype	NULL	Description
DEF_INITIAL_EXTENT	VARCHAR2 (40)		For a local index, the default INITIAL value (in Oracle blocks) to be used when adding a table partition, or DEFAULT if no INITIAL value was specified
DEF_NEXT_EXTENT	VARCHAR2 (40)		For a local index, the default NEXT value (in Oracle blocks) to be used when adding a table partition, or DEFAULT if no NEXT value was specified
DEF_MIN_EXTENTS	VARCHAR2 (40)		For a local index, the default MINEXTENTS value to be used when adding a table partition, or DEFAULT if no MINEXTENTS value was specified
DEF_MAX_EXTENTS	VARCHAR2 (40)		For a local index, the default MAXEXTENTS value to be used when adding a table partition, or DEFAULT if no MAXEXTENTS value was specified
DEF_MAX_SIZE	VARCHAR2 (40)		For a local index, the default MAXSIZE value to be used when adding a table partition, or DEFAULT if no MAXSIZE value was specified
DEF_PCT_INCREASE	VARCHAR2 (40)		For a local index, the default PCTINCREASE value to be used when adding a table partition, or DEFAULT if no PCTINCREASE value was specified
DEF_FREELISTS	NUMBER	NOT NULL	For a local index, the default FREELISTS value to be used when adding a table partition
DEF_FREELIST_GROUPS	NUMBER	NOT NULL	For a local index, the default FREELIST GROUPS value to be used when adding a table partition
DEF_LOGGING	VARCHAR2 (7)		For a local index, the default LOGGING attribute to be used when adding a table partition: - NONE - Not specified See Also: the *_INDEXES view - YES - NO
DEF_BUFFER_POOL	VARCHAR2 (7)		For a local index, the default buffer pool to be used when adding a table partition: - DEFAULT - KEEP - RECYCLE - NULL
DEF_FLASH_CACHE	VARCHAR2 (7)		For a local index, the default Database Smart Flash Cache hint to be used when adding a table partition: - DEFAULT - KEEP - NONE Solaris and Oracle Linux functionality only.
DEF_CELL_FLASH_CACHE	VARCHAR2 (7)		For a local index, the default cell flash cache hint to be used when adding a table partition: - DEFAULT - KEEP - NONE See Also: Oracle Exadata Storage Server Software documentation for more information
DEF_PARAMETERS	VARCHAR2 (1000)		Default parameter string for domain indexes
INTERVAL	VARCHAR2 (1000)		String of the interval value

See Also:

- ["DBA_PART_INDEXES"](#) on page 5-69
- ["USER_PART_INDEXES"](#) on page 6-90

ALL_PART_KEY_COLUMNS

ALL_PART_KEY_COLUMNS describes the partitioning key columns for the partitioned objects accessible to the current user.

Related Views

- DBA_PART_KEY_COLUMNS describes the partitioning key columns for all partitioned objects in the database.
- USER_PART_KEY_COLUMNS describes the partitioning key columns for the partitioned objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the partitioned table or index
NAME	VARCHAR2 (30)		Name of the partitioned table or index
OBJECT_TYPE	CHAR (5)		Object type: ■ TABLE ■ INDEX
COLUMN_NAME	VARCHAR2 (4000)		Name of the column
COLUMN_POSITION	NUMBER		Position of the column within the partitioning key

See Also:

- ["DBA_PART_KEY_COLUMNS"](#) on page 5-69
- ["USER_PART_KEY_COLUMNS"](#) on page 6-90

ALL_PART_LOBS

ALL_PART_LOBS displays table-level information about the partitioned LOBs accessible to the current user, including default attributes for LOB data partitions.

Related Views

- DBA_PART_LOBS displays table-level information about all partitioned LOBs in the database.
- USER_PART_LOBS displays table-level information about the partitioned LOBs owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the partitioned table containing the LOBs
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the partitioned table containing the LOBs
COLUMN_NAME	VARCHAR2 (4000)		Name of the LOB column
LOB_NAME	VARCHAR2 (30)	NOT NULL	Name of the partitioned LOB
LOB_INDEX_NAME	VARCHAR2 (30)	NOT NULL	Name of the partitioned LOB index

Column	Datatype	NULL	Description
DEF_CHUNK	NUMBER	NOT NULL	Default value of CHUNK for a LOB data partition to be used when adding a partition
DEF_PCTVERSION	NUMBER	NOT NULL	Default value of PCTVERSION for a LOB data partition to be used when adding a partition
DEF_CACHE	VARCHAR2 (10)		Indicates whether and how the LOB data is cached by default in the buffer cache: ■ YES - LOB data is placed in the buffer cache ■ NO - LOB data either is not brought into the buffer cache or is brought into the buffer cache and placed at the least recently used end of the LRU list ■ CACHEREADS - LOB data is brought into the buffer cache only during read operations but not during write operations
DEF_IN_ROW	VARCHAR2 (3)		Indicates whether LOB data < 4000 bytes is stored by default inline (in the row) (YES) or not (NO); that is, whether or not ENABLE STORAGE IN ROW was specified when the LOB column was created or last altered
DEF_TABLESPACE_NAME	VARCHAR2 (30)		Default tablespace for a LOB data partition to be used when adding a partition
DEF_INITIAL_EXTENT	VARCHAR2 (40)		Default value of INITIAL for a LOB data partition to be used when adding a partition, or DEFAULT if no INITIAL value was specified
DEF_NEXT_EXTENT	VARCHAR2 (40)		Default value of NEXT for a LOB data partition to be used when adding a partition, or DEFAULT if no NEXT value was specified
DEF_MIN_EXTENTS	VARCHAR2 (40)		Default value of MINEXTENTS for a LOB data partition to be used when adding a partition, or DEFAULT if no MINEXTENTS value was specified
DEF_MAX_EXTENTS	VARCHAR2 (40)		Default value of MAXEXTENTS for a LOB data partition to be used when adding a partition, or DEFAULT if no MAXEXTENTS value was specified
DEF_MAX_SIZE	VARCHAR2 (40)		Default value of MAXSIZE for a LOB data partition to be used when adding a partition, or DEFAULT if no MAXSIZE value was specified
DEF_RETENTION	VARCHAR2 (7)		Default value of RETENTION for a LOB data partition to be used when adding a partition. Possible values for SecureFiles: ■ NONE ■ AUTO ■ MIN ■ MAX ■ DEFAULT ■ INVALID Possible values for BasicFiles: ¹ ■ YES ■ NO
DEF_MINRET	VARCHAR2 (40)		Default value of RETENTION MIN for a LOB data partition to be used when adding a partition, or DEFAULT if no RETENTION MIN value was specified
DEF_PCT_INCREASE	VARCHAR2 (40)		Default value of PCTINCREASE for a LOB data partition to be used when adding a partition, or DEFAULT if no PCTINCREASE value was specified
DEF_FREELISTS	VARCHAR2 (40)		Default value of FREELISTS for a LOB data partition to be used when adding a partition, or DEFAULT if no FREELISTS value was specified

Column	Datatype	NULL	Description
DEF_FREELIST_GROUPS	VARCHAR2 (40)		Default value of FREELIST_GROUPS for a LOB data partition to be used when adding a partition, or DEFAULT if no FREELIST_GROUPS value was specified
DEF_LOGGING	VARCHAR2 (7)		Default LOGGING attribute for a LOB data partition to be used when adding a partition: - NONE - Not specified See Also: the *_LOBS and *_LOB_PARTITIONS views - YES - NO
DEF_BUFFER_POOL	VARCHAR2 (7)		Default buffer pool for a LOB data partition to be used when adding a partition: - DEFAULT - KEEP - RECYCLE - NULL
DEF_FLASH_CACHE	VARCHAR2 (7)		Default Database Smart Flash Cache hint to be used when adding a partition: - DEFAULT - KEEP - NONE Solaris and Oracle Linux functionality only.
DEF_CELL_FLASH_CACHE	VARCHAR2 (7)		Default cell flash cache hint to be used when adding a partition: - DEFAULT - KEEP - NONE See Also: Oracle Exadata Storage Server Software documentation for more information
DEF_ENCRYPT	VARCHAR2 (4)		Default value of ENCRYPT for a LOB data partition to be used when adding a partition. Possible values for SecureFiles: - YES - NO Possible value for BasicFiles: - NONE - Not applicable
DEF_COMPRESS	VARCHAR2 (6)		Default value of COMPRESS for a LOB data partition to be used when adding a partition. Possible values for SecureFiles: - LOW - MEDIUM - HIGH - NO - Compression is off Possible value for BasicFiles: - NONE - Not applicable
DEF_DEDUPLICATE	VARCHAR2 (15)		Default value of DEDUPLICATE for a LOB data partition to be used when adding a partition. Possible values for SecureFiles: - LOB - Deduplicate - NO - Keep duplicates Possible values for BasicFiles: - NONE - Not applicable

Column	Datatype	NULL	Description
DEF_SECUREFILE	VARCHAR2 (3)		Indicates whether the LOB is SecureFiles (YES) or not (NO)

¹ The values listed for BasicFiles are supported starting with Oracle Database 11g Release 2 (11.2.0.2). In previous releases, the value for this column for BasicFiles is NULL.

See Also:

- ["DBA_PART_LOBS"](#) on page 5-69
- ["USER_PART_LOBS"](#) on page 6-90

ALL_PART_TABLES

ALL_PART_TABLES displays the object-level partitioning information for the partitioned tables accessible to the current user.

Related Views

- DBA_PART_TABLES displays the object-level partitioning information for all partitioned tables in the database.
- USER_PART_TABLES displays the object-level partitioning information for the partitioned tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the partitioned table
TABLE_NAME	VARCHAR2 (30)		Name of the partitioned table
PARTITIONING_TYPE	VARCHAR2 (9)		Type of the partitioning method: ■ UNKNOWN - Not specified See Also: the *_TABLES view ■ RANGE ■ HASH ■ SYSTEM ■ LIST ■ REFERENCE
SUBPARTITIONING_TYPE	VARCHAR2 (9)		Type of the composite partitioning method: ■ NONE - Not subpartitioned See Also: the *_TABLES view ■ RANGE ■ HASH ■ SYSTEM ■ LIST ■ REFERENCE
PARTITION_COUNT	NUMBER		Number of partitions in the table. For interval partitioned tables, the value of this column is always 1048575.
DEF_SUBPARTITION_COUNT	NUMBER		For a composite-partitioned table, the default number of subpartitions, if specified
PARTITIONING_KEY_COUNT	NUMBER		Number of columns in the partitioning key
SUBPARTITIONING_KEY_COUNT	NUMBER		For a composite-partitioned table, the number of columns in the subpartitioning key

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (8)		If a previous DROP TABLE operation failed, indicates whether the table is unusable (UNUSABLE) or valid (VALID)
DEF_TABLESPACE_NAME	VARCHAR2 (30)		Default tablespace to be used when adding a partition
DEF_PCT_FREE	NUMBER		Default value of PCTFREE to be used when adding a partition
DEF_PCT_USED	NUMBER		Default value of PCTUSED to be used when adding a partition
DEF_INI_TRANS	NUMBER		Default value of INITRANS to be used when adding a partition
DEF_MAX_TRANS	NUMBER		Default value of MAXTRANS to be used when adding a partition
DEF_INITIAL_EXTENT	VARCHAR2 (40)		Default value of INITIAL (in Oracle blocks) to be used when adding a partition, or DEFAULT if no INITIAL value was specified
DEF_NEXT_EXTENT	VARCHAR2 (40)		Default value of NEXT (in Oracle blocks) to be used when adding a partition, or DEFAULT if no NEXT value was specified
DEF_MIN_EXTENTS	VARCHAR2 (40)		Default value of MINEXTENTS to be used when adding a partition, or DEFAULT if no MINEXTENTS value was specified
DEF_MAX_EXTENTS	VARCHAR2 (40)		Default value of MAXEXTENTS to be used when adding a partition, or DEFAULT if no MAXEXTENTS value was specified
DEF_MAX_SIZE	VARCHAR2 (40)		Default value of MAXSIZE to be used when adding a partition, or DEFAULT if no MAXSIZE value was specified
DEF_PCT_INCREASE	VARCHAR2 (40)		Default value of PCTINCREASE to be used when adding a partition, or DEFAULT if no PCTINCREASE value was specified
DEF_FREELISTS	NUMBER		Default value of FREELISTS to be used when adding a partition
DEF_FREELIST_GROUPS	NUMBER		Default value of FREELIST GROUPS to be used when adding a partition
DEF_LOGGING	VARCHAR2 (7)		Default LOGGING attribute to be used when adding a partition: ■ NONE - Not specified See Also: the *_TABLES view ■ YES ■ NO
DEF_COMPRESSION	VARCHAR2 (8)		Default compression to be used when adding a partition: ■ NONE - Not specified See Also: the *_TABLES view ■ ENABLED ■ DISABLED

Column	Datatype	NULL	Description
DEF_COMPRESS_FOR	VARCHAR2 (12)		Default compression for what kind of operations to be used when adding a partition: ■ BASIC ■ OLTP ■ QUERY LOW¹ ■ QUERY HIGH¹ ■ ARCHIVE LOW¹ ■ ARCHIVE HIGH¹ ■ UNKNOWN ■ NULL
DEF_BUFFER_POOL	VARCHAR2 (7)		Default buffer pool to be used when adding a partition: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
DEF_FLASH_CACHE	VARCHAR2 (7)		Default Database Smart Flash Cache hint to be used when adding a partition: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
DEF_CELL_FLASH_CACHE	VARCHAR2 (7)		Default cell flash cache hint to be used when adding a partition: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
REF_PTN_CONSTRAINT_NAME	VARCHAR2 (30)		Name of the partitioning referential constraint for reference-partitioned tables
INTERVAL	VARCHAR2 (1000)		String of the interval value
IS_NESTED	VARCHAR2 (3)		Indicates whether the partitioned table is a nested table (YES) or not (NO) See Also: the *_NESTED_TABLES view for the parent table name/column
DEF_SEGMENT_CREATION ²	VARCHAR2 (4)		Indicates whether a table partition segment has been created (YES) or not (NO). N/A indicates that this table is subpartitioned and no segment exists at the partition level

¹ Hybrid columnar compression is a feature of Oracle Exadata. See Oracle Exadata Storage Server Software documentation for more information.

² This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also:

- ["DBA_PART_TABLES"](#) on page 5-69
- ["USER_PART_TABLES"](#) on page 6-91

ALL_PARTIAL_DROP_TABS

ALL_PARTIAL_DROP_TABS describes tables accessible to the current user that have partially completed DROP COLUMN operations. Such operations might have been interrupted by the user or by a system crash.

Related Views

- DBA_PARTIAL_DROP_TABS describes all tables in the database that have partially completed DROP COLUMN operations.
- USER_PARTIAL_DROP_TABS describes tables in the schema of the current user that have partially completed DROP COLUMN operations. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table

ALL_PENDING_CONV_TABLES

ALL_PENDING_CONV_TABLES describes the pending conversion tables (tables which are not upgraded to the latest type version) accessible to the current user.

Related Views

- DBA_PENDING_CONV_TABLES describes all pending conversion tables in the database.
- USER_PENDING_CONV_TABLES describes the pending conversion tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table

See Also:

- ["DBA_PENDING_CONV_TABLES"](#) on page 5-69
- ["USER_PENDING_CONV_TABLES"](#) on page 6-91

ALL_PLSQL_OBJECT_SETTINGS

ALL_PLSQL_OBJECT_SETTINGS displays information about the compiler settings for the stored objects accessible to the current user.

Related Views

- DBA_PLSQL_OBJECT_SETTINGS displays information about the compiler settings for all stored objects in the database.
- USER_PLSQL_OBJECT_SETTINGS displays information about the compiler settings for the stored objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
NAME	VARCHAR2 (30)	NOT NULL	Name of the object
TYPE	VARCHAR2 (12)		Type of the object: ■ PROCEDURE ■ FUNCTION ■ PACKAGE ■ PACKAGE BODY ■ TRIGGER ■ TYPE ■ TYPE BODY
PLSQL_OPTIMIZE_LEVEL	NUMBER		Optimization level that was used to compile the object
PLSQL_CODE_TYPE	VARCHAR2 (4000)		Compilation mode for the object
PLSQL_DEBUG	VARCHAR2 (4000)		Indicates whether the object was compiled with debug information or not
PLSQL_WARNINGS	VARCHAR2 (4000)		Compiler warning settings that were used to compile the object
NLS_LENGTH_SEMANTICS	VARCHAR2 (4000)		NLS length semantics that were used to compile the object
PLSQL_CCFLAGS	VARCHAR2 (4000)		Conditional compilation flag settings that were used to compile the object
PLSCOPE_SETTINGS	VARCHAR2 (4000)		Settings for using PL/Scope

See Also:

- ["DBA_PLSQL_OBJECT_SETTINGS"](#) on page 5-70
- ["USER_PLSQL_OBJECT_SETTINGS"](#) on page 6-91

ALL_POLICIES

ALL_POLICIES describes all Oracle Virtual Private Database (VPD) security policies for objects accessible to the current user. A security policy is a list of security requirements and rules that regulate access to those database objects.

Related Views

- DBA_POLICIES describes all Oracle Virtual Private Database (VPD) security policies in the database.
- USER_POLICIES describes all Oracle Virtual Private Database (VPD) security policies associated with objects owned by the current user. This view does not display the OBJECT_OWNER column.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the synonym, table, or view
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the synonym, table, or view
POLICY_GROUP	VARCHAR2 (30)	NOT NULL	Name of the policy group
POLICY_NAME	VARCHAR2 (30)	NOT NULL	Name of the policy
PF_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the policy function
PACKAGE	VARCHAR2 (30)		Name of the package containing the policy function
FUNCTION	VARCHAR2 (30)	NOT NULL	Name of the policy function

Column	Datatype	NULL	Description
SEL	VARCHAR2 (3)		Indicates whether the policy is applied to queries on the object (YES) or not (NO)
INS	VARCHAR2 (3)		Indicates whether the policy is applied to INSERT statements on the object (YES) or not (NO)
UPD	VARCHAR2 (3)		Indicates whether the policy is applied to UPDATE statements on the object (YES) or not (NO)
DEL	VARCHAR2 (3)		Indicates whether the policy is applied to DELETE statements on the object (YES) or not (NO)
IDX	VARCHAR2 (3)		Indicates whether the policy is enforced for index maintenance on the object (YES) or not (NO)
CHK_OPTION	VARCHAR2 (3)		Indicates whether the check option is enforced for the policy (YES) or not (NO)
ENABLE	VARCHAR2 (3)		Indicates whether the policy is enabled (YES) or disabled (NO)
STATIC_POLICY	VARCHAR2 (3)		Indicates whether the policy is static (YES) or not (NO)
POLICY_TYPE	VARCHAR2 (24)		Policy type: ■ STATIC ■ SHARED_STATIC ■ CONTEXT_SENSITIVE ■ SHARED_CONTEXT_SENSITIVE ■ DYNAMIC
LONG_PREDICATE	VARCHAR2 (3)		Indicates whether the policy function can return a maximum of 32 KB of predicate (YES) or not (NO). If NO, the default maximum predicate size is 4000 bytes.

See Also:

- ["DBA_POLICIES"](#) on page 5-70
- ["USER_POLICIES"](#) on page 6-91
- *Oracle Database Concepts* for an overview of security policies and fine-grained access control
- *Oracle Database Security Guide* for information about implementing security policies
- The DBMS_RLS package in *Oracle Database PL/SQL Packages and Types Reference* for information on administering security policies

ALL_POLICY_CONTEXTS

ALL_POLICY_CONTEXTS describes the driving contexts defined for the synonyms, tables, and views accessible to the current user.

Related Views

- DBA_POLICY_CONTEXTS describes all driving contexts in the database.
- USER_POLICY_CONTEXTS describes the driving contexts defined for the synonyms, tables, and views owned by the current user. This view does not display the OBJECT_OWNER column.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the synonym, table, or view

Column	Datatype	NULL	Description
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the synonym, table, or view
NAMESPACE	VARCHAR2 (30)	NOT NULL	Namespace of the driving context
ATTRIBUTE	VARCHAR2 (30)	NOT NULL	Attribute of the driving context

See Also:

- ["DBA_POLICY_CONTEXTS"](#) on page 5-70
- ["USER_POLICY_CONTEXTS"](#) on page 6-91

ALL_POLICY_GROUPS

ALL_POLICY_GROUPS describes the policy groups defined for the synonyms, tables, and views accessible to the current user.

Related Views

- DBA_POLICY_GROUPS describes all policy groups in the database.
- USER_POLICY_GROUPS describes the policy groups defined for the synonyms, tables, and views owned by the current user. This view does not display the OBJECT_OWNER column.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the synonym, table, or view
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the synonym, table, or view
POLICY_GROUP	VARCHAR2 (30)	NOT NULL	Name of the policy group

See Also:

- ["DBA_POLICY_GROUPS"](#) on page 5-70
- ["USER_POLICY_GROUPS"](#) on page 6-92

ALL_PROCEDURES

ALL_PROCEDURES lists all functions and procedures, along with associated properties. For example, ALL_PROCEDURES indicates whether or not a function is pipelined, parallel enabled or an aggregate function. If a function is pipelined or an aggregate function, the associated implementation type (if any) is also identified.

Related Views

- DBA_PROCEDURES lists all functions and procedures, along with associated properties.
- USER_PROCEDURES lists all functions and procedures, along with associated properties. It does not contain the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the procedure
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object: top-level function, procedure, or package name
PROCEDURE_NAME	VARCHAR2 (30)		Name of the procedure

Column	Datatype	NULL	Description
OBJECT_ID	NUMBER		Object number of the object
SUBPROGRAM_ID	NUMBER		Unique subprogram identifier
OVERLOAD	VARCHAR2 (40)		Overload unique identifier
OBJECT_TYPE	VARCHAR2 (19)		The typename of the object
AGGREGATE	VARCHAR2 (3)		Indicates whether the procedure is an aggregate function (YES) or not (NO)
PIPELINED	VARCHAR2 (3)		Indicates whether the procedure is a pipelined table function (YES) or not (NO)
IMPLTYPEOWNER	VARCHAR2 (30)		Owner of the implementation type, if any
IMPLTYPENAME	VARCHAR2 (30)		Name of the implementation type, if any
PARALLEL	VARCHAR2 (3)		Indicates whether the procedure or function is parallel-enabled (YES) or not (NO)
INTERFACE	VARCHAR2 (3)		YES, if the procedure/function is a table function implemented using the ODCI interface; otherwise NO
DETERMINISTIC	VARCHAR2 (3)		YES, if the procedure/function is declared to be deterministic; otherwise NO
AUTHID	VARCHAR2 (12)		Indicates whether the procedure/function is declared to execute as DEFINER or CURRENT_USER (invoker)

ALL_PROPAGATION

ALL_PROPAGATION displays information about the Streams propagations that have a source queue accessible to the current user.

Related View

DBA_PROPAGATION displays information about all Streams propagations in the database.

Column	Datatype	NULL	Description
PROPAGATION_NAME	VARCHAR2 (30)	NOT NULL	Name of the Streams propagation
SOURCE_QUEUE_OWNER	VARCHAR2 (30)		Owner of the source queue of the propagation
SOURCE_QUEUE_NAME	VARCHAR2 (30)		Name of the source queue of the propagation
DESTINATION_QUEUE_OWNER	VARCHAR2 (30)		Owner of the destination queue of the propagation
DESTINATION_QUEUE_NAME	VARCHAR2 (30)		Name of the destination queue of the propagation
DESTINATION_DBLINK	VARCHAR2 (128)		Database link to propagate events from the source queue to the destination queue
RULE_SET_OWNER	VARCHAR2 (30)		Owner of the propagation positive rule set
RULE_SET_NAME	VARCHAR2 (30)		Name of the propagation positive rule set
NEGATIVE_RULE_SET_OWNER	VARCHAR2 (30)		Owner of the propagation negative rule set
NEGATIVE_RULE_SET_NAME	VARCHAR2 (30)		Name of the propagation negative rule set
QUEUE_TO_QUEUE	VARCHAR2 (5)		Indicates whether the propagation is a queue-to-queue propagation (TRUE) or not (FALSE). A queue-to-queue propagation always has its own exclusive propagation job to propagate messages from the source queue to the destination queue.

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (8)		Status of the propagation: ■ DISABLED ■ ENABLED ■ ABORTED
ERROR_MESSAGE	VARCHAR2 (4000)		Error message last encountered by propagation
ERROR_DATE	DATE		Time that propagation last encountered an error
ORIGINAL_PROPAGATION_NAME	VARCHAR2 (30)		Original propagation from which the propagation is cloned
ORIGINAL_SOURCE_QUEUE_OWNER	VARCHAR2 (30)		Source queue owner of the original propagation
ORIGINAL_SOURCE_QUEUE_NAME	VARCHAR2 (30)		Source queue name of the original propagation
ACKED_SCN	NUMBER		Acknowledged SCN of the subscribers of captured messages in the destination queue for the propagation
AUTO_MERGE_THRESHOLD	NUMBER		Merge threshold value for merging the propagation back to the original source queue. This is used as the value for the <code>merge_threshold</code> parameter in the <code>DBMS_STREAMS_ADM.MERGE_STREAMS_JOB</code> procedure.

See Also: ["DBA_PROPAGATION"](#) on page 5-71

ALL_PUBLISHED_COLUMNS

ALL_PUBLISHED_COLUMNS is a synonym for USER_PUBLISHED_COLUMNS.

See Also: ["USER_PUBLISHED_COLUMNS"](#) on page 6-92

ALL_QUEUE_SCHEDULES

ALL_QUEUE_SCHEDULES describes the propagation schedules whose source queues are accessible to the current user.

Related Views

- DBA_QUEUE_SCHEDULES describes all propagation schedules in the database.
- USER_QUEUE_SCHEDULES describes the propagation schedules whose source queues are owned by the current user. This view does not display the SCHEMA column.

Column	Datatype	NULL	Description
SCHEMA	VARCHAR2 (30)		Source queue owner
QNAME	VARCHAR2 (30)		Source queue name
DESTINATION	VARCHAR2 (128)		Destination name, currently limited to be a DBLINK name
START_DATE	TIMESTAMP (6) WITH TIME ZONE		Date at which to start propagation
START_TIME	VARCHAR2 (8)		Time of day at which to start propagation (in HH:MI:SS format)
PROPAGATION_WINDOW	NUMBER		Duration for the propagation window (in seconds)
NEXT_TIME	VARCHAR2 (4000)		Function to compute the start of the next propagation window

Column	Datatype	NULL	Description
LATENCY	NUMBER		Maximum wait time to propagate a message during the propagation window
SCHEDULE_DISABLED	VARCHAR2 (1)		Indicates whether the schedule is disabled (Y) or enabled (N). If disabled, then the schedule will not be executed.
PROCESS_NAME	VARCHAR2 (4)		Name of the process executing the schedule; NULL if not currently executing
SESSION_ID	VARCHAR2 (82)		Session ID and session serial number of the job executing this schedule (SID, SERIAL#); NULL if not currently executing
INSTANCE	NUMBER		Cluster database instance number executing the schedule
LAST_RUN_DATE	TIMESTAMP (6) WITH TIME ZONE		Date of the last successful execution
LAST_RUN_TIME	VARCHAR2 (8)		Time of day of the last successful execution (in HH:MI:SS format)
CURRENT_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Date at which the current window of this schedule was started
CURRENT_START_TIME	VARCHAR2 (8)		Time of day at which the current window of this schedule was started (in HH:MI:SS format)
NEXT_RUN_DATE	TIMESTAMP (6) WITH TIME ZONE		Date at which the next window of this schedule will be started
NEXT_RUN_TIME	VARCHAR2 (8)		Time of day at which the next window of this schedule will be started (in HH:MI:SS format)
TOTAL_TIME	NUMBER		Total time spent by the system in executing this schedule (in seconds)
TOTAL_NUMBER	NUMBER		Total number of messages propagated in this schedule
TOTAL_BYTES	NUMBER		Total number of bytes propagated in this schedule
MAX_NUMBER	NUMBER		Maximum number of messages propagated in a propagation window
MAX_BYTES	NUMBER		Maximum number of bytes propagated in a propagation window
AVG_NUMBER	NUMBER		Average number of messages propagated in a propagation window
AVG_SIZE	NUMBER		Average size of a propagated message (in bytes)
AVG_TIME	NUMBER		Average time to propagate a message (in seconds)
FAILURES	NUMBER		Number of consecutive times schedule execution has failed, if any. After 16 consecutive failures, a propagation job becomes disabled automatically.
LAST_ERROR_DATE	DATE		Date of the last unsuccessful execution
LAST_ERROR_TIME	VARCHAR2 (8)		Time of day of the last unsuccessful execution (in HH:MI:SS format)
LAST_ERROR_MSG	VARCHAR2 (4000)		Error number and error message text of the last unsuccessful execution
MESSAGE_DELIVERY_MODE	VARCHAR2 (10)		Message delivery mode: ■ PERSISTENT ■ BUFFERED
ELAPSED_DEQUEUE_TIME	NUMBER		Elapsed dequeue time (in hundredths of a second)
ELAPSED_PICKLE_TIME	NUMBER		Elapsed pickle time (time taken to linearize a logical change record (LCR) into a stream of bytes that can be sent over the network) (in hundredths of a second)
JOB_NAME	VARCHAR2 (30)		Name of the Scheduler job

See Also:

- ["DBA_QUEUE_SCHEDULES"](#) on page 5-72
- ["USER_QUEUE_SCHEDULES"](#) on page 6-92

ALL_QUEUE_SUBSCRIBERS

ALL_QUEUE_SUBSCRIBERS displays the list of subscribers that the current user has privilege to dequeue from.

Related Views

- DBA_QUEUE_SUBSCRIBERS displays the list of subscribers on all queues in the database.
- USER_QUEUE_SUBSCRIBERS displays the list of subscribers on queues that are under the current user's schema. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue
QUEUE_TABLE	VARCHAR2 (30)	NOT NULL	Name of the queue table on which the queue is defined
CONSUMER_NAME	VARCHAR2 (30)		Name of the subscriber
ADDRESS	VARCHAR2 (1024)		Address of the subscriber
PROTOCOL	NUMBER		Protocol of the subscriber
TRANSFORMATION	VARCHAR2 (61)		Transformation for the subscriber
RULE	CLOB		Rule condition for the subscriber
DELIVERY_MODE	VARCHAR2 (22)		Message delivery mode for the subscriber: ■ PERSISTENT ■ BUFFERED ■ PERSISTENT_OR_BUFFERED
IF_NONDURABLE_SUBSCRIBER	VARCHAR2 (24)		Indicates whether the subscriber is a non-durable subscriber (YES) or not (NO)
QUEUE_TO_QUEUE	VARCHAR2 (5)		Indicates whether the subscriber is a queue-to-queue subscriber (TRUE) or not (FALSE)

ALL_QUEUE_TABLES

ALL_QUEUE_TABLES describes the queues in the queue tables accessible to the current user.

Related Views

- DBA_QUEUE_TABLES describes the queues in all queue tables in the database.
- USER_QUEUE_TABLES describes the queues in the queue tables created in the current user's schema. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the queue table
QUEUE_TABLE	VARCHAR2 (30)		Name of the queue table

Column	Datatype	NULL	Description
TYPE	VARCHAR2 (7)		Type of user data: ■ RAW - Raw type ■ OBJECT - User-defined object type ■ VARIANT - Variant type (for internal use only)
OBJECT_TYPE	VARCHAR2 (61)		Object type of the payload when TYPE is OBJECT
SORT_ORDER	VARCHAR2 (22)		User-specified sort order
RECIPIENTS	VARCHAR2 (8)		SINGLE or MULTIPLE recipients
MESSAGE_GROUPING	VARCHAR2 (13)		NONE or TRANSACTIONAL
COMPATIBLE	VARCHAR2 (6)		Lowest release level which the queue table is compatible with (for example, 8.0.3)
PRIMARY_INSTANCE	NUMBER		Indicates the instance number of the instance which is the primary owner of the queue table. A value of 0 indicates that there is no primary owner.
SECONDARY_INSTANCE	NUMBER		Indicates the instance number of the instance which is the secondary owner of the queue table. This instance becomes the owner of the queue table if the primary owner is not alive. A value of 0 indicates that there is no secondary owner.
OWNER_INSTANCE	NUMBER		Instance number of the instance which currently owns the queue table
USER_COMMENT	VARCHAR2 (50)		Comment supplied by the user
SECURE	VARCHAR2 (3)		Indicates whether the queue table is secure (YES) or not (NO)

See Also:

- ["DBA_QUEUE_TABLES"](#) on page 5-73
- ["USER_QUEUE_TABLES"](#) on page 6-92
- *Oracle Streams Advanced Queuing User's Guide* for more information about these views and Advanced Queuing

ALL_QUEUES

ALL_QUEUES describes all queues on which the current user has enqueue or dequeue privileges. If the user has any Advanced Queuing system privileges, like `MANAGE ANY QUEUE`, `ENQUEUE ANY QUEUE` or `DEQUEUE ANY QUEUE`, then this view describes all queues in the database.

Related Views

- DBA_QUEUES describes all queues in the database.
- USER_QUEUES describes the operational characteristics of every queue owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the queue
NAME	VARCHAR2 (30)	NOT NULL	Name of the queue
QUEUE_TABLE	VARCHAR2 (30)	NOT NULL	Name of the table the queue data resides in
QID	NUMBER	NOT NULL	Object number of the queue

Column	Datatype	NULL	Description
QUEUE_TYPE	VARCHAR2 (20)		Type of the queue: ■ EXCEPTION_QUEUE ■ NON_PERSISTENT_QUEUE ■ NORMAL_QUEUE
MAX_RETRIES	NUMBER		Maximum number of retries allowed when dequeuing from the queue
RETRY_DELAY	NUMBER		Time interval between retries
ENQUEUE_ENABLED	VARCHAR2 (7)		Indicates whether the queue is enabled for enqueue (YES) or not (NO)
DEQUEUE_ENABLED	VARCHAR2 (7)		Indicates whether the queue is enabled for dequeue (YES) or not (NO)
RETENTION	VARCHAR2 (40)		Time interval (in seconds) processed messages are retained in the queue, or FOREVER
USER_COMMENT	VARCHAR2 (50)		User specified comment
NETWORK_NAME	VARCHAR2 (512)		Network name

See Also: *Oracle Streams Advanced Queuing User's Guide* for more information about these views and Advanced Queuing

ALL_REFRESH

ALL_REFRESH describes all the refresh groups accessible to the current user.

Related Views

- DBA_REFRESH describes all refresh groups in the database.
- USER_REFRESH describes all refresh groups owned by the current user.

Column	Datatype	NULL	Description
ROWNER	VARCHAR2 (30)	NOT NULL	Owner of the refresh group
RNAME	VARCHAR2 (30)	NOT NULL	Name of the refresh group
REFGROUP	NUMBER		Internal identifier of the refresh group
IMPLICIT_DESTROY	VARCHAR2 (1)		Indicates whether the refresh group is destroyed when its last item is subtracted (Y) or not (N)
PUSH_DEFERRED_RPC	VARCHAR2 (1)		Indicates whether changes are pushed from the snapshot to the master before refresh (Y) or not (N)
REFRESH_AFTER_ERRORS	VARCHAR2 (1)		Indicates whether to proceed with refresh despite errors when pushing deferred RPCs (Y) or not (N)
ROLLBACK_SEG	VARCHAR2 (30)		Name of the rollback segment to use while refreshing
JOB	NUMBER		Identifier of the job used to refresh the group automatically
NEXT_DATE	DATE		Date that this job will next be refreshed automatically, if not broken
INTERVAL	VARCHAR2 (200)		A date function used to compute the next NEXT_DATE
BROKEN	VARCHAR2 (1)		Indicates whether the job is broken and will never be run (Y) or not (N)
PURGE_OPTION	NUMBER (38)		Method for purging the transaction queue after each push (1 indicates quick purge option; 2 indicates precise purge option)
PARALLELISM	NUMBER (38)		Level of parallelism for transaction propagation

Column	Datatype	NULL	Description
HEAP_SIZE	NUMBER (38)		Size of the heap

ALL_REFRESH_CHILDREN

ALL_REFRESH_CHILDREN describes all the objects in refresh groups that are accessible to the current user.

Related Views

- DBA_REFRESH_CHILDREN describes the objects in all refresh groups in the database.
- USER_REFRESH_CHILDREN describes the objects in all refresh groups owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object in the refresh group
NAME	VARCHAR2 (30)	NOT NULL	Name of the object in the refresh group
TYPE	VARCHAR2 (30)		Type of the object in the refresh group
ROWNER	VARCHAR2 (30)	NOT NULL	Owner of the refresh group
RNAME	VARCHAR2 (30)	NOT NULL	Name of the refresh group
REFGROUP	NUMBER		Internal identifier of the refresh group
IMPLICIT_DESTROY	VARCHAR2 (1)		Indicates whether the refresh group is destroyed when its last item is subtracted (Y) or not (N)
PUSH_DEFERRED_RPC	VARCHAR2 (1)		Indicates whether changes are pushed from the snapshot to the master before refresh (Y) or not (N)
REFRESH_AFTER_ERRORS	VARCHAR2 (1)		Indicates whether to proceed with refresh despite errors when pushing deferred RPCs (Y) or not (N)
ROLLBACK_SEG	VARCHAR2 (30)		Name of the rollback segment to use while refreshing
JOB	NUMBER		Identifier of the job used to refresh the group automatically
NEXT_DATE	DATE		Date that this job will next be refreshed automatically, if not broken
INTERVAL	VARCHAR2 (200)		A date function used to compute the next NEXT_DATE
BROKEN	VARCHAR2 (1)		Indicates whether the job is broken and will never be run (Y) or not (N)
PURGE_OPTION	NUMBER (38)		Method for purging the transaction queue after each push. 1 indicates quick purge option; 2 indicates precise purge option
PARALLELISM	NUMBER (38)		Level of parallelism for transaction propagation
HEAP_SIZE	NUMBER (38)		Size of the heap

ALL_REFRESH_DEPENDENCIES

ALL_REFRESH_DEPENDENCIES displays the names of the dependent detail or container tables of all the materialized views in the current schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Table name, unique within this schema
PARENT_OBJECT_TYPE	CHAR (17)		MATERIALIZED VIEW

Column	Datatype	NULL	Description
OLDEST_REFRESH_SCN	NUMBER		Minimum SCN of any summary or materialized view that has TABLE_NAME as a detail table
OLDEST_REFRESH_DATE	DATE		SYSDATE when last refreshed

ALL_REFS

ALL_REFS describes the REF columns and REF attributes in object type columns accessible to the current user.

Related Views

- DBA_REFS describes all REF columns and REF attributes in the database.
- USER_REFS describes the REF columns and REF attributes in object type columns owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2 (4000)		Name of the REF column or attribute. If it is not a top-level attribute, the value of COLUMN_NAME should be a path name starting with the column name.
WITH_ROWID	VARCHAR2 (3)		Indicates whether the REF value is stored with ROWID (YES) or not (NO)
IS_SCOPED	VARCHAR2 (3)		Indicates whether the REF column is scoped (YES) or not (NO)
SCOPE_TABLE_OWNER	VARCHAR2 (30)		Owner of the scope table, if it exists and is accessible by the user
SCOPE_TABLE_NAME	VARCHAR2 (30)		Name of the scope table, if it exists and is accessible by the user
OBJECT_ID_TYPE	VARCHAR2 (33)		Indicates whether the object ID (OID) is USER-DEFINED or SYSTEM GENERATED

ALL_REGISTERED_MVIEWS

ALL_REGISTERED_MVIEWS describes all registered materialized views (registered at a master site or a master materialized view site) accessible to the current user.

Related Views

- DBA_REGISTERED_MVIEWS describes all registered materialized views in the database.
- USER_REGISTERED_MVIEWS describes all registered materialized views owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the materialized view
NAME	VARCHAR2 (30)	NOT NULL	Name of the materialized view
MVIEW_SITE	VARCHAR2 (128)	NOT NULL	Global name of the materialized view site
CAN_USE_LOG	VARCHAR2 (3)		Indicates whether the materialized view can use a materialized view log (YES) or the materialized view is too complex to use a log (NO)

Column	Datatype	NULL	Description
UPDATABLE	VARCHAR2 (3)		Indicates whether the materialized view is updatable (YES) or not and the materialized view is read only (NO)
REFRESH_METHOD	VARCHAR2 (11)		Indicates whether the materialized view uses primary key (PRIMARY KEY), rowids (ROWID), or object identifiers (OBJECT ID) for fast refresh
MVIEW_ID	NUMBER (38)		Identifier for the materialized view used by the masters for fast refresh
VERSION	VARCHAR2 (26)		Oracle version of the materialized view Note: Oracle Database materialized views show ORACLE 8 MATERIALIZED VIEW.
QUERY_TXT	LONG		Query that defines the materialized view

See Also:

- ["DBA_REGISTERED_MVIEWS"](#) on page 5-78
- ["USER_REGISTERED_MVIEWS"](#) on page 6-93

ALL_REGISTRY_BANNERS

ALL_REGISTRY_BANNERS displays the valid components loaded into the database.

Column	Datatype	NULL	Description
BANNER	VARCHAR2 (80)		Component display banner

ALL_REWRITE_EQUIVALENCES

ALL_REWRITE_EQUIVALENCES describes the rewrite equivalences accessible to the current user.

Related Views

- DBA_REWRITE_EQUIVALENCES describes all rewrite equivalences in the database.
- USER_REWRITE_EQUIVALENCES describes the rewrite equivalences owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rewrite equivalence
NAME	VARCHAR2 (30)	NOT NULL	Name of the rewrite equivalence
SOURCE_STMT	CLOB		Source statement of the rewrite equivalence
DESTINATION_STMT	CLOB		Destination of the rewrite equivalence
REWRITE_MODE	VARCHAR2 (10)		Rewrite mode of the rewrite equivalence: ■ DISABLED ■ TEXT_MATCH ■ GENERAL ■ RECURSIVE

See Also:

- ["DBA_REWRITE_EQUIVALENCES"](#) on page 5-82
- ["USER_REWRITE_EQUIVALENCES"](#) on page 6-94

ALL_RULE_SET_RULES

ALL_RULE_SET_RULES describes the rules in the rule sets accessible to the current user.

Related Views

- DBA_RULE_SET_RULES describes the rules in all rule sets in the database.
- USER_RULE_SET_RULES describes the rules in the rule sets owned by the current user. This view does not display the RULE_SET_OWNER column.

Column	Datatype	NULL	Description
RULE_SET_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule set
RULE_SET_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule set
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule
RULE_SET_RULE_ENABLED	VARCHAR2 (8)		Indicates whether the rule is enabled in the rule set (ENABLED) or not (DISABLED)
RULE_SET_RULE_EVAL_CTX_OWNER	VARCHAR2 (30)		Owner of the evaluation context specified when the rule was added to the rule set, if any
RULE_SET_RULE_EVAL_CTX_NAME	VARCHAR2 (30)		Name of the evaluation context specified when the rule was added to the rule set, if any
RULE_SET_RULE_COMMENT	VARCHAR2 (4000)		Comment specified when the rule was added to the rule set, if any

See Also:

- ["DBA_RULE_SET_RULES"](#) on page 5-89
- ["USER_RULE_SET_RULES"](#) on page 6-94

ALL_RULE_SETS

ALL_RULE_SETS describes the rule sets accessible to the current user.

Related Views

- DBA_RULE_SETS describes all rule sets in the database.
- USER_RULE_SETS describes the rule sets owned by the current user. This view does not display the RULE_SET_OWNER column.

Column	Datatype	NULL	Description
RULE_SET_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule set
RULE_SET_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule set
RULE_SET_EVAL_CONTEXT_OWNER	VARCHAR2 (30)		Owner of the evaluation context associated with the rule set, if any
RULE_SET_EVAL_CONTEXT_NAME	VARCHAR2 (30)		Name of the evaluation context associated with the rule set, if any
RULE_SET_COMMENT	VARCHAR2 (4000)		Comment specified with the rule set, if any

See Also:

- ["DBA_RULE_SETS"](#) on page 5-89
- ["USER_RULE_SETS"](#) on page 6-95

ALL_RULES

ALL_RULES describes the rules accessible to the current user.

Related Views

- DBA_RULES describes all rules in the database.
- USER_RULES describes the rules owned by the current user. This view does not display the RULE_OWNER column.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule
RULE_CONDITION	CLOB		Expressions and operators that constitute the rule condition
RULE_EVALUATION_CONTEXT_OWNER	VARCHAR2 (30)		Owner of the evaluation context associated with the rule, if any
RULE_EVALUATION_CONTEXT_NAME	VARCHAR2 (30)		Name of the evaluation context associated with the rule, if any
RULE_ACTION_CONTEXT	RE\$NV_LIST		Action context associated with the rule, if any
RULE_COMMENT	VARCHAR2 (4000)		Comment specified with the rule, if any

See Also:

- ["DBA_RULES"](#) on page 5-89
- ["USER_RULES"](#) on page 6-95

ALL_SCHEDULER_CHAIN_RULES

ALL_SCHEDULER_CHAIN_RULES displays information about the rules for the chains accessible to the current user (that is, those chains that the user has ALTER or EXECUTE privileges for).

Related Views

- DBA_SCHEDULER_CHAIN_RULES displays information about the rules for all chains in the database.
- USER_SCHEDULER_CHAIN_RULES displays information about the rules for the chains owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Scheduler chain that the rule is in
CHAIN_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler chain that the rule is in
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2 (30)		Name of the rule
CONDITION	VARCHAR2 (4000)		Boolean condition triggering the rule

Column	Datatype	NULL	Description
ACTION	VARCHAR2 (4000)		Action to be performed when the rule is triggered
COMMENTS	VARCHAR2 (4000)		User-specified comments about the rule

See Also:

- ["DBA_SCHEDULER_CHAIN_RULES"](#) on page 5-89
- ["USER_SCHEDULER_CHAIN_RULES"](#) on page 6-95

ALL_SCHEDULER_CHAIN_STEPS

ALL_SCHEDULER_CHAIN_STEPS displays information about the defined steps of the chains accessible to the current user (that is, those chains that the user has ALTER or EXECUTE privileges for).

Related Views

- DBA_SCHEDULER_CHAIN_STEPS displays information about the defined steps of all chains in the database.
- USER_SCHEDULER_CHAIN_STEPS displays information about the defined steps of the chains owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Scheduler chain the step is in
CHAIN_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler chain the step is in
STEP_NAME	VARCHAR2 (30)	NOT NULL	Name of the chain step
PROGRAM_OWNER	VARCHAR2 (98)		Owner of the program that runs during the step
PROGRAM_NAME	VARCHAR2 (98)		Name of the program that runs during the step
EVENT_SCHEDULE_OWNER	VARCHAR2 (98)		Owner of the event schedule that this step waits for
EVENT_SCHEDULE_NAME	VARCHAR2 (98)		Name of the event schedule that this step waits for
EVENT_QUEUE_OWNER	VARCHAR2 (30)		Owner of the source queue into which the event will be raised
EVENT_QUEUE_NAME	VARCHAR2 (30)		Name of the source queue into which the event will be raised
EVENT_QUEUE_AGENT	VARCHAR2 (30)		Name of the AQ agent used by the user on the event source queue (for a secure queue)
EVENT_CONDITION	VARCHAR2 (4000)		Boolean expression used as the subscription rule for an event on the source queue
CREDENTIAL_OWNER	VARCHAR2 (30)		Owner of the credential to be used for an external step job
CREDENTIAL_NAME	VARCHAR2 (30)		Name of the credential to be used for an external step job
DESTINATION	VARCHAR2 (128)		Destination host on which a remote step job will run
SKIP	VARCHAR2 (5)		Indicates whether the step should be skipped (TRUE) or not (FALSE)
PAUSE	VARCHAR2 (5)		Indicates whether the step should be paused after running (TRUE) or not (FALSE)
PAUSE_BEFORE ¹	VARCHAR2 (5)		Indicates whether the step should be paused before running (TRUE) or not (FALSE)

Column	Datatype	NULL	Description
RESTART_ON_RECOVERY	VARCHAR2 (5)		Indicates whether the step should be restarted on database recovery (TRUE) or not (FALSE)
RESTART_ON_FAILURE	VARCHAR2 (5)		Indicates whether the step should be restarted on application failure (TRUE) or not (FALSE)
STEP_TYPE	VARCHAR2 (14)		Type of the step: ■ EVENT_SCHEDULE ■ INLINE_EVENT ■ SUBCHAIN ■ PROGRAM
TIMEOUT	INTERVAL DAY (3) TO SECOND (0)		Timeout for waiting on an event schedule

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also:

- ["DBA_SCHEDULER_CHAIN_STEPS"](#) on page 5-89
- ["USER_SCHEDULER_CHAIN_STEPS"](#) on page 6-95

ALL_SCHEDULER_CHAINS

ALL_SCHEDULER_CHAINS displays information about the chains accessible to the current user (that is, those chains that the user has ALTER or EXECUTE privileges for).

Related Views

- DBA_SCHEDULER_CHAINS displays information about all chains in the database.
- USER_SCHEDULER_CHAINS displays information about the chains owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Scheduler chain
CHAIN_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler chain
RULE_SET_OWNER	VARCHAR2 (30)		Owner of the rule set describing the dependencies
RULE_SET_NAME	VARCHAR2 (30)		Name of the rule set describing the dependencies
NUMBER_OF_RULES	NUMBER		Number of rules in the chain
NUMBER_OF_STEPS	NUMBER		Number of defined steps in the chain
ENABLED	VARCHAR2 (5)		Indicates whether the chain is enabled (TRUE) or disabled (FALSE)
EVALUATION_INTERVAL	INTERVAL DAY (3) TO SECOND (0)		Periodic interval at which to reevaluate rules for the chain
USER_RULE_SET	VARCHAR2 (5)		Indicates whether the chain uses a user-specified rule set (TRUE) or not (FALSE)
COMMENTS	VARCHAR2 (240)		Comments on the chain

See Also:

- ["DBA_SCHEDULER_CHAINS"](#) on page 5-89
- ["USER_SCHEDULER_CHAINS"](#) on page 6-95

ALL_SCHEDULER_CREDENTIALS

ALL_SCHEDULER_CREDENTIALS displays information about the credentials accessible to the current user (that is, those credentials that the user has ALTER or EXECUTE privileges for).

Related Views

- DBA_SCHEDULER_CREDENTIALS displays information about all credentials in the database.
- USER_SCHEDULER_CREDENTIALS displays information about the credentials owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Scheduler credential
CREDENTIAL_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler credential
USERNAME	VARCHAR2 (64)	NOT NULL	Name of the user that will be used to log in to the remote database or operating system
DATABASE_ROLE	VARCHAR2 (7)		For a database target, the database role to use when logging in: ■ SYSDBA ■ SYSOPER
WINDOWS_DOMAIN	VARCHAR2 (30)		For a Windows target, the Windows domain to use when logging in
COMMENTS	VARCHAR2 (240)		Comments on the credential

See Also:

- ["DBA_SCHEDULER_CREDENTIALS"](#) on page 5-89
- ["USER_SCHEDULER_CREDENTIALS"](#) on page 6-95

ALL_SCHEDULER_DB_DESTS

ALL_SCHEDULER_DB_DESTS displays information about the destination objects accessible to the current user pointing to remote databases.

Related Views

- DBA_SCHEDULER_DB_DESTS displays information about all destination objects in the database pointing to remote databases.
- USER_SCHEDULER_DB_DESTS displays information about the destination objects owned by the current user pointing to remote databases. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of this destination object
DESTINATION_NAME	VARCHAR2 (30)	NOT NULL	Name of this destination object
CONNECT_INFO	VARCHAR2 (4000)		Connect string to connect to the remote database
AGENT	VARCHAR2 (30)		Name of the agent through which the connection to the remote database is being made
ENABLED	VARCHAR2 (5)		Indicates whether this destination object is enabled (TRUE) or disabled (FALSE)

Column	Datatype	NULL	Description
REFS_ENABLED	VARCHAR2 (5)		Indicates whether all referenced objects are enabled (TRUE) or disabled (FALSE)
COMMENTS	VARCHAR2 (240)		Optional comment

See Also:

- ["DBA_SCHEDULER_DB_DESTS"](#) on page 5-90
- ["USER_SCHEDULER_DB_DESTS"](#) on page 6-95

ALL_SCHEDULER_DESTS

ALL_SCHEDULER_DESTS displays information about the destination objects for jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_DESTS displays information about all destination objects for jobs in the database.
- USER_SCHEDULER_DESTS displays information about the destination objects for jobs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of this destination object
DESTINATION_NAME	VARCHAR2 (30)	NOT NULL	Name of this destination object
DESTINATION_TYPE	VARCHAR2 (8)		Type of this destination object: ■ EXTERNAL ■ DATABASE
ENABLED	VARCHAR2 (5)		Indicates whether this destination object is enabled (TRUE) or disabled (FALSE)
COMMENTS	VARCHAR2 (240)		Optional comment

See Also:

- ["DBA_SCHEDULER_DESTS"](#) on page 5-90
- ["USER_SCHEDULER_DESTS"](#) on page 6-96

ALL_SCHEDULER_EXTERNAL_DESTS

ALL_SCHEDULER_EXTERNAL_DESTS displays information about the destination objects accessible to the current user pointing to remote agents.

Related View

DBA_SCHEDULER_EXTERNAL_DESTS displays information about all destination objects in the database pointing to remote agents.

Column	Datatype	NULL	Description
DESTINATION_NAME	VARCHAR2 (30)	NOT NULL	Name of this destination object
HOSTNAME	VARCHAR2 (256)		Name or IP address of the host on which the agent is located
PORT	NUMBER		Port that the agent is listening on

Column	Datatype	NULL	Description
IP_ADDRESS	VARCHAR2 (64)		IP address of the host on which the agent is located
ENABLED	VARCHAR2 (5)		Indicates whether this destination object is enabled (TRUE) or disabled (FALSE)
COMMENTS	VARCHAR2 (240)		Optional comment

See Also: ["DBA_SCHEDULER_EXTERNAL_DESTS"](#) on page 5-90

ALL_SCHEDULER_FILE_WATCHERS

ALL_SCHEDULER_FILE_WATCHERS displays information about the Scheduler file watch requests accessible to the current user.

Related Views

- DBA_SCHEDULER_FILE_WATCHERS displays information about all Scheduler file watch requests in the database.
- USER_SCHEDULER_FILE_WATCHERS displays information about the Scheduler file watch requests owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the file watch request
FILE_WATCHER_NAME	VARCHAR2 (30)	NOT NULL	Name of the file watch request
ENABLED	VARCHAR2 (5)		Indicates whether this file watch request is enabled (TRUE) or disabled (FALSE)
DESTINATION_OWNER	VARCHAR2 (128)		Owner of the named destination object
DESTINATION	VARCHAR2 (128)		Name of the destination object
DIRECTORY_PATH	VARCHAR2 (4000)	NOT NULL	Name of the directory path where the file will arrive
FILE_NAME	VARCHAR2 (512)	NOT NULL	Name or pattern specifying the files that need to be monitored
CREDENTIAL_OWNER	VARCHAR2 (30)		Owner of the credential that should be used to authorize the file watch
CREDENTIAL_NAME	VARCHAR2 (30)		Name of the credential that should be used to authorize the file watch
MIN_FILE_SIZE	NUMBER	NOT NULL	Minimum size of the file being monitored
STEADY_STATE_DURATION	INTERVAL DAY (3) TO SECOND (0)		Time to wait before concluding that the file has stopped growing
LAST_MODIFIED_TIME	TIMESTAMP (6) WITH TIME ZONE		Time at which this file watcher was last modified
COMMENTS	VARCHAR2 (240)		Comments on the file watch request

See Also:

- ["DBA_SCHEDULER_FILE_WATCHERS"](#) on page 5-90
- ["USER_SCHEDULER_FILE_WATCHERS"](#) on page 6-96

ALL_SCHEDULER_GLOBAL_ATTRIBUTE

ALL_SCHEDULER_GLOBAL_ATTRIBUTE displays the values of all scheduler attributes (for example, DEFAULT_TIMEZONE and CURRENT_OPEN_WINDOW).

Related View

DBA_SCHEDULER_GLOBAL_ATTRIBUTE displays the values of all scheduler attributes in the database.

Column	Datatype	NULL	Description
ATTRIBUTE_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler attribute
VALUE	VARCHAR2 (128)		Value of the Scheduler attribute

See Also: ["DBA_SCHEDULER_GLOBAL_ATTRIBUTE"](#) on page 5-90

ALL_SCHEDULER_GROUP_MEMBERS

ALL_SCHEDULER_GROUP_MEMBERS displays information about the members of the Scheduler object groups accessible to the current user.

Related Views

- DBA_SCHEDULER_GROUP_MEMBERS displays information about the members of all Scheduler object groups in the database.
- USER_SCHEDULER_GROUP_MEMBERS displays information about the members of the Scheduler object groups owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the group
GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the group
MEMBER_NAME	VARCHAR2 (131)		Name of the member of this group

See Also:

- ["DBA_SCHEDULER_GROUP_MEMBERS"](#) on page 5-90
- ["USER_SCHEDULER_GROUP_MEMBERS"](#) on page 6-96

ALL_SCHEDULER_GROUPS

ALL_SCHEDULER_GROUPS displays information about the Scheduler object groups accessible to the current user.

Related Views

- DBA_SCHEDULER_GROUPS displays information about all Scheduler object groups in the database.
- USER_SCHEDULER_GROUPS displays information about the Scheduler object groups owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the group
GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the group
GROUP_TYPE	VARCHAR2 (13)		Type of object contained in the group: ■ WINDOW ■ JOB ■ DB_DEST ■ EXTERNAL_DEST
ENABLED	VARCHAR2 (5)		Indicates whether the group is enabled (TRUE) or disabled (FALSE)
NUMBER_OF_MEMBERS	NUMBER		Number of members in this group
COMMENTS	VARCHAR2 (240)		An optional comment about this group

See Also:

- ["DBA_SCHEDULER_GROUPS"](#) on page 5-90
- ["USER_SCHEDULER_GROUPS"](#) on page 6-96

ALL_SCHEDULER_JOB_ARGS

ALL_SCHEDULER_JOB_ARGS displays information about the arguments of the Scheduler jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_JOB_ARGS displays information about the arguments of all Scheduler jobs in the database.
- USER_SCHEDULER_JOB_ARGS displays information about the arguments of the Scheduler jobs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the job to which the argument belongs
JOB_NAME	VARCHAR2 (30)		Name of the job to which the argument belongs
ARGUMENT_NAME	VARCHAR2 (30)		Optional name of the argument
ARGUMENT_POSITION	NUMBER		Position of the argument in the argument list
ARGUMENT_TYPE	VARCHAR2 (61)		Datatype of the argument
VALUE	VARCHAR2 (4000)		Value of the argument (in string format) if the argument is a string
ANYDATA_VALUE	ANYDATA		Value of the argument (in AnyData format)
OUT_ARGUMENT	VARCHAR2 (5)		Reserved for future use

See Also:

- ["DBA_SCHEDULER_JOB_ARGS"](#) on page 5-91
- ["USER_SCHEDULER_JOB_ARGS"](#) on page 6-96

ALL_SCHEDULER_JOB_CLASSES

ALL_SCHEDULER_JOB_CLASSES displays information about the Scheduler job classes accessible to the current user.

Related View

DBA_SCHEDULER_JOB_CLASSES displays information about all Scheduler job classes in the database.

Column	Datatype	NULL	Description
JOB_CLASS_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler job class
RESOURCE_CONSUMER_GROUP	VARCHAR2 (30)		Resource consumer group associated with the class
SERVICE	VARCHAR2 (64)		Name of the service the class is associated with
LOGGING_LEVEL	VARCHAR2 (11)		Amount of logging that will be done pertaining to the class: ▪ OFF ▪ RUNS ▪ FAILED RUNS ▪ FULL
LOG_HISTORY	NUMBER		History (in days) to maintain in the job log for the class
COMMENTS	VARCHAR2 (240)		Comments on the class

See Also: ["DBA_SCHEDULER_JOB_CLASSES"](#) on page 5-91

ALL_SCHEDULER_JOB_DESTS

ALL_SCHEDULER_JOB_DESTS displays information about the state of the jobs accessible to the current user at each of their destinations.

Related Views

- DBA_SCHEDULER_JOB_DESTS displays information about the state of all jobs in the database at each of their destinations.
- USER_SCHEDULER_JOB_DESTS displays information about the state of the jobs owned by the current user at each of their destinations. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the Scheduler job
JOB_NAME	VARCHAR2 (30)		Name of the Scheduler job
JOB_SUBNAME	VARCHAR2 (31)		Subname of the Scheduler job
CREDENTIAL_OWNER	VARCHAR2 (30)		Owner of the credential used for the remote destination
CREDENTIAL_NAME	VARCHAR2 (30)		Name of the credential used for the remote destination
DESTINATION_OWNER	VARCHAR2 (128)		Owner of the destination object that points to the destination
DESTINATION	VARCHAR2 (128)		Name of the destination object or the name of the destination itself
JOB_DEST_ID	NUMBER		Numerical ID assigned to the job at this destination
ENABLED	VARCHAR2 (5)		Indicates whether the parent job is enabled (TRUE) or disabled (FALSE)

Column	Datatype	NULL	Description
REFS_ENABLED	VARCHAR2 (5)		Indicates whether this destination and its agent are enabled (TRUE) or disabled (FALSE)
STATE	VARCHAR2 (15)		State of this job at this destination: ■ DISABLED ■ RUNNING ■ CHAIN_STALLED ■ SCHEDULED ■ RETRY SCHEDULED ■ READY TO RUN ■ COMPLETED ■ BROKEN ■ FAILED ■ SUCCEEDED ■ REMOTE ■ STOPPED
NEXT_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Next start time of this job at this destination
RUN_COUNT	NUMBER		Number of times this job has run at this destination
RETRY_COUNT	NUMBER		Number of times this job has been retried at this destination
FAILURE_COUNT	NUMBER		Number of times this job has failed at this destination
LAST_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Last time this job started at this destination
LAST_END_DATE	TIMESTAMP (6) WITH TIME ZONE		Last time this job ended at this destination

See Also:

- ["DBA_SCHEDULER_JOB_DESTS"](#) on page 5-91
- ["USER_SCHEDULER_JOB_DESTS"](#) on page 6-96

ALL_SCHEDULER_JOB_LOG

ALL_SCHEDULER_JOB_LOG displays log information for the Scheduler jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_JOB_LOG displays log information for all Scheduler jobs in the database.
- USER_SCHEDULER_JOB_LOG displays log information for the Scheduler jobs owned by the current user.

Column	Datatype	NULL	Description
LOG_ID	NUMBER	NOT NULL	Unique identifier that identifies a row
LOG_DATE	TIMESTAMP (6) WITH TIME ZONE		Date of the log entry
OWNER	VARCHAR2 (30)		Owner of the Scheduler job
JOB_NAME	VARCHAR2 (65)		Name of the Scheduler job
JOB_SUBNAME	VARCHAR2 (65)		Subname of the Scheduler job (for a chain step job)

Column	Datatype	NULL	Description
JOB_CLASS	VARCHAR2 (30)		Class that the job belonged to at the time of entry
OPERATION	VARCHAR2 (30)		Operation corresponding to the log entry
STATUS	VARCHAR2 (30)		Status of the operation, if applicable. Possible values for this column are dependent on the value in the OPERATION column. In most cases, STATUS will be NULL. Only for job run operations will it have a value. STATUS will be NULL when OPERATION is one of the following: - CREATE - Job was created - UPDATE - One or more job attributes have been modified - ENABLE - Job has been enabled - DISABLE - Job has been disabled - COMPLETED - For repeating jobs only, job has reached its end date or maximum number of runs - BROKEN - Job has reached its maximum number of failures STATUS can be SUCCEEDED (job run completed successfully), FAILED (job run failed), or STOPPED (job run was stopped) when OPERATION is one of the following: - RUN - Regular job run - RETRY_RUN - Job is being retried because the previous run resulted in an error and RESTARTABLE is set to TRUE - RECOVERY_RUN - Job is being rerun because the database went down, or the job slave crashed and RESTARTABLE is set to TRUE
USER_NAME	VARCHAR2 (30)		Name of the user who performed the operation, if applicable
CLIENT_ID	VARCHAR2 (64)		Client identifier of the user who performed the operation, if applicable
GLOBAL_UID	VARCHAR2 (32)		Global user identifier of the user who performed the operation, if applicable
CREDENTIAL_OWNER	VARCHAR2 (65)		Owner of the credential used for this remote job run
CREDENTIAL_NAME	VARCHAR2 (65)		Name of the credential used for this remote job run
DESTINATION_OWNER	VARCHAR2 (128)		Owner of the destination object used in this remote job run; NULL if no object used
DESTINATION	VARCHAR2 (128)		Destination for a remote job operation
ADDITIONAL_INFO	CLOB		Additional information on the entry, if applicable

See Also:

- ["DBA_SCHEDULER_JOB_LOG"](#) on page 5-91
- ["USER_SCHEDULER_JOB_LOG"](#) on page 6-96

ALL_SCHEDULER_JOB_RUN_DETAILS

ALL_SCHEDULER_JOB_RUN_DETAILS displays log run details for the Scheduler jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_JOB_RUN_DETAILS displays log run details for all Scheduler jobs in the database.

- `USER_SCHEDULER_JOB_RUN_DETAILS` displays log run details for the Scheduler jobs owned by the current user.

Column	Datatype	NULL	Description
LOG_ID	NUMBER		Unique identifier of the log entry (foreign key of the *_ SCHEDULER_JOB_LOG views)
LOG_DATE	TIMESTAMP (6) WITH TIME ZONE		Date of the log entry
OWNER	VARCHAR2 (30)		Owner of the Scheduler job
JOB_NAME	VARCHAR2 (65)		Name of the Scheduler job
JOB_SUBNAME	VARCHAR2 (65)		Subname of the Scheduler job (for a chain step job)
STATUS	VARCHAR2 (30)		Status of the job run
ERROR#	NUMBER		Error number in the case of an error
REQ_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Requested start date of the job run
ACTUAL_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Actual date on which the job was run
RUN_DURATION	INTERVAL DAY (3) TO SECOND (0)		Duration of the job run
INSTANCE_ID	NUMBER		Identifier of the instance on which the job was run
SESSION_ID	VARCHAR2 (30)		Session identifier of the job run
SLAVE_PID	VARCHAR2 (30)		Process identifier of the slave on which the job was run
CPU_USED	INTERVAL DAY (3) TO SECOND (2)		Amount of CPU used for the job run
CREDENTIAL_OWNER	VARCHAR2 (65)		Owner of the credential used for this remote job run
CREDENTIAL_NAME	VARCHAR2 (65)		Name of the credential used for this remote job run
DESTINATION_OWNER	VARCHAR2 (128)		Owner of the destination object used in this remote job run; NULL if no object used
DESTINATION	VARCHAR2 (128)		Destination for a remote job operation
ADDITIONAL_INFO	VARCHAR2 (4000)		Additional information on the job run, if applicable

See Also:

- ["DBA_SCHEDULER_JOB_RUN_DETAILS"](#) on page 5-92
- ["USER_SCHEDULER_JOB_RUN_DETAILS"](#) on page 6-97

ALL_SCHEDULER_JOBS

`ALL_SCHEDULER_JOBS` displays information about the Scheduler jobs accessible to the current user.

Related Views

- `DBA_SCHEDULER_JOBS` displays information about all Scheduler jobs in the database.
- `USER_SCHEDULER_JOBS` displays information about the Scheduler jobs owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the Scheduler job

Column	Datatype	NULL	Description
JOB_NAME	VARCHAR2 (30)		Name of the Scheduler job
JOB_SUBNAME	VARCHAR2 (30)		Subname of the Scheduler job (for a job running a chain step)
JOB_STYLE	VARCHAR2 (11)		Job style: - REGULAR - LIGHTWEIGHT
JOB_CREATOR	VARCHAR2 (30)		Original creator of the job
CLIENT_ID	VARCHAR2 (64)		Client identifier of the user creating the job
GLOBAL_UID	VARCHAR2 (32)		Global user identifier of the user creating the job
PROGRAM_OWNER	VARCHAR2 (4000)		Owner of the program associated with the job
PROGRAM_NAME	VARCHAR2 (4000)		Name of the program associated with the job
JOB_TYPE	VARCHAR2 (16)		Inline job action type: - PLSQL_BLOCK - STORED_PROCEDURE - EXECUTABLE - CHAIN
JOB_ACTION	VARCHAR2 (4000)		Inline job action
NUMBER_OF_ARGUMENTS	NUMBER		Inline number of job arguments
SCHEDULE_OWNER	VARCHAR2 (4000)		Owner of the schedule that the job uses (can be a window or a window group)
SCHEDULE_NAME	VARCHAR2 (4000)		Name of the schedule that the job uses (can be a window or a window group)
SCHEDULE_TYPE	VARCHAR2 (12)		Type of the schedule that the job uses: - IMMEDIATE - Start date and repeat interval are NULL - ONCE - Repeat interval is NULL - PLSQL - PL/SQL expression used as schedule - CALENDAR - Oracle calendaring expression used as schedule - EVENT - Event schedule - NAMED - Named schedule - WINDOW - Window used as schedule - WINDOW_GROUP - Window group used as schedule
START_DATE	TIMESTAMP (6) WITH TIME ZONE		Original scheduled start date of the job (for an inline schedule)
REPEAT_INTERVAL	VARCHAR2 (4000)		Inline schedule PL/SQL expression or calendar string
EVENT_QUEUE_OWNER	VARCHAR2 (30)		Owner of the source queue into which the event will be raised
EVENT_QUEUE_NAME	VARCHAR2 (30)		Name of the source queue into which the event will be raised
EVENT_QUEUE_AGENT	VARCHAR2 (256)		Name of the AQ agent used by the user on the event source queue (if it is a secure queue)
EVENT_CONDITION	VARCHAR2 (4000)		Boolean expression used as the subscription rule for the event on the source queue
EVENT_RULE	VARCHAR2 (65)		Name of the rule used by the coordinator to trigger the event-based job
FILE_WATCHER_OWNER	VARCHAR2 (65)		Owner of the file watcher on which this job is based
FILE_WATCHER_NAME	VARCHAR2 (65)		Name of the file watcher on which this job is based
END_DATE	TIMESTAMP (6) WITH TIME ZONE		Date after which the job will no longer run (for an inline schedule)

Column	Datatype	NULL	Description
JOB_CLASS	VARCHAR2 (30)		Name of the job class associated with the job
ENABLED	VARCHAR2 (5)		Indicates whether the job is enabled (TRUE) or disabled (FALSE)
AUTO_DROP	VARCHAR2 (5)		Indicates whether the job will be dropped when it has completed (TRUE) or not (FALSE)
RESTARTABLE	VARCHAR2 (5)		Indicates whether the job can be restarted (TRUE) or not (FALSE)
STATE	VARCHAR2 (15)		Current state of the job: ■ DISABLED ■ RETRY SCHEDULED ■ SCHEDULED ■ RUNNING ■ COMPLETED ■ BROKEN ■ FAILED ■ REMOTE ■ SUCCEEDED ■ CHAIN_STALLED
JOB_PRIORITY	NUMBER		Priority of the job relative to other jobs in the same class
RUN_COUNT	NUMBER		Number of times the job has run
MAX_RUNS	NUMBER		Maximum number of times the job is scheduled to run
FAILURE_COUNT	NUMBER		Number of times the job has failed to run
MAX_FAILURES	NUMBER		Number of times the job will be allowed to fail before being marked broken
RETRY_COUNT	NUMBER		Number of times the job has retried, if it is retrying
LAST_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Last date on which the job started running
LAST_RUN_DURATION	INTERVAL DAY (9) TO SECOND (6)		Amount of time the job took to complete during the last run
NEXT_RUN_DATE	TIMESTAMP (6) WITH TIME ZONE		Next date on which the job is scheduled to run
SCHEDULE_LIMIT	INTERVAL DAY (3) TO SECOND (0)		Time after which a job which has not run yet will be rescheduled
MAX_RUN_DURATION	INTERVAL DAY (3) TO SECOND (0)		Maximum amount of time for which the job will be allowed to run
LOGGING_LEVEL	VARCHAR2 (11)		Amount of logging that will be done pertaining to the job: ■ OFF ■ RUNS ■ FAILED RUNS ■ FULL
STOP_ON_WINDOW_CLOSE	VARCHAR2 (5)		Indicates whether the job will stop if a window associated with the job closes (TRUE) or not (FALSE)
INSTANCE_STICKINESS	VARCHAR2 (5)		Indicates whether the job is sticky (TRUE) or not (FALSE)

Column	Datatype	NULL	Description
RAISE_EVENTS	VARCHAR2 (4000)		List of job events to raise for the job: ■ JOB_STARTED ■ JOB_SUCCEEDED ■ JOB_FAILED ■ JOB_BROKEN ■ JOB_COMPLETED ■ JOB_STOPPED ■ JOB_SCH_LIM_REACHED ■ JOB_DISABLED ■ JOB_CHAIN_STALLED ■ JOB_OVER_MAX_DUR
SYSTEM	VARCHAR2 (5)		Indicates whether the job is a system job (TRUE) or not (FALSE)
JOB_WEIGHT	NUMBER		Weight of the job
NLS_ENV	VARCHAR2 (4000)		NLS environment of the job
SOURCE	VARCHAR2 (128)		Source global database identifier
NUMBER_OF_DESTINATIONS	NUMBER		Number of destinations associated with this job
DESTINATION_OWNER	VARCHAR2 (128)		Owner of the destination object (if used), else NULL
DESTINATION	VARCHAR2 (128)		Destination that this job will run on
CREDENTIAL_OWNER	VARCHAR2 (30)		Owner of the credential to be used for an external job
CREDENTIAL_NAME	VARCHAR2 (30)		Name of the credential to be used for an external job
INSTANCE_ID	NUMBER		Instance on which the user requests the job to run
DEFERRED_DROP	VARCHAR2 (5)		Indicates whether the job will be dropped when completed due to user request (TRUE) or not (FALSE)
ALLOW_RUNS_IN_RESTRICTED_MODE	VARCHAR2 (5)		Indicates whether the job is allowed to run in restricted session mode (TRUE) or not (FALSE)
COMMENTS	VARCHAR2 (240)		Comments on the job
FLAGS	NUMBER		This column is for internal use

See Also:

- ["DBA_SCHEDULER_JOBS"](#) on page 5-92
- ["USER_SCHEDULER_JOBS"](#) on page 6-97

ALL_SCHEDULER_NOTIFICATIONS

ALL_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for the jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for all jobs in the database.
- USER_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for the jobs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the job this notification is for
JOB_NAME	VARCHAR2 (30)	NOT NULL	Name of the job this notification is for
JOB_SUBNAME	VARCHAR2 (30)		Subname of the job this notification is for
RECIPIENT	VARCHAR2 (4000)	NOT NULL	E-mail address to send this E-mail notification to
SENDER	VARCHAR2 (4000)		E-mail address to send this E-mail notification from
SUBJECT	VARCHAR2 (4000)		Subject of the notification E-mail
BODY	VARCHAR2 (4000)		Body of the notification E-mail
FILTER_CONDITION	VARCHAR2 (4000)		Filter specifying which job events to send notifications for
EVENT	VARCHAR2 (19)		Job event to send notifications for: ■ JOB_STARTED ■ JOB_SUCCEEDED ■ JOB_FAILED ■ JOB_BROKEN ■ JOB_COMPLETED ■ JOB_STOPPED ■ JOB_SCH_LIM_REACHED ■ JOB_DISABLED ■ JOB_CHAIN_STALLED ■ JOB_OVER_MAX_DUR
EVENT_FLAG	NUMBER	NOT NULL	Event number of the job event to send notifications for

See Also:

- ["DBA_SCHEDULER_NOTIFICATIONS"](#) on page 5-93
- ["USER_SCHEDULER_NOTIFICATIONS"](#) on page 6-97

ALL_SCHEDULER_PROGRAM_ARGS

ALL_SCHEDULER_PROGRAM_ARGS displays information about the arguments of the Scheduler programs accessible to the current user.

Related Views

- DBA_SCHEDULER_PROGRAM_ARGS displays information about the arguments of all Scheduler programs in the database.
- USER_SCHEDULER_PROGRAM_ARGS displays information about the arguments of the Scheduler programs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the program to which the argument belongs
PROGRAM_NAME	VARCHAR2 (30)	NOT NULL	Name of the program to which the argument belongs
ARGUMENT_NAME	VARCHAR2 (30)		Optional name of the argument
ARGUMENT_POSITION	NUMBER	NOT NULL	Position of the argument in the argument list
ARGUMENT_TYPE	VARCHAR2 (61)		Datatype of the argument

Column	Datatype	NULL	Description
METADATA_ATTRIBUTE	VARCHAR2 (19)		Metadata attribute: - JOB_NAME - JOB_OWNER - JOB_START - WINDOW_START - WINDOW_END - JOB_SUBNAME - EVENT_MESSAGE - JOB_SCHEDULED_START
DEFAULT_VALUE	VARCHAR2 (4000)		Default value taken by the argument (in string format) if the argument is a string
DEFAULT_ANYDATA_VALUE	ANYDATA		Default value taken by the argument (in AnyData format)
OUT_ARGUMENT	VARCHAR2 (5)		Reserved for future use

See Also:

- ["DBA_SCHEDULER_PROGRAM_ARGS" on page 5-93](#)
- ["USER_SCHEDULER_PROGRAM_ARGS" on page 6-97](#)

ALL_SCHEDULER_PROGRAMS

ALL_SCHEDULER_PROGRAMS displays information about the Scheduler programs accessible to the current user.

Related Views

- DBA_SCHEDULER_PROGRAMS displays information about all Scheduler programs in the database.
- USER_SCHEDULER_PROGRAMS displays information about the Scheduler programs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Scheduler program
PROGRAM_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler program
PROGRAM_TYPE	VARCHAR2 (16)		Type of the program action: - PLSQL_BLOCK - STORED_PROCEDURE - EXECUTABLE
PROGRAM_ACTION	VARCHAR2 (4000)		String specifying the program action
NUMBER_OF_ARGUMENTS	NUMBER		Number of arguments accepted by the program
ENABLED	VARCHAR2 (5)		Indicates whether the program is enabled (TRUE) or disabled (FALSE)
DETACHED	VARCHAR2 (5)		This column is for internal use
SCHEDULE_LIMIT	INTERVAL DAY (3) TO SECOND (0)		Maximum delay in running the program after the scheduled start
PRIORITY	NUMBER		Priority of the program
WEIGHT	NUMBER		Weight of the program

Column	Datatype	NULL	Description
MAX_RUNS	NUMBER		Maximum number of runs of any job based on this program
MAX_FAILURES	NUMBER		Maximum number of failures of any job based on this program
MAX_RUN_DURATION	INTERVAL DAY (3) TO SECOND (0)		Maximum amount of time this program can run
NLS_ENV	VARCHAR2 (4000)		NLS environment in which the program was created
COMMENTS	VARCHAR2 (240)		Comments on the program

See Also:

- ["DBA_SCHEDULER_PROGRAMS"](#) on page 5-93
- ["USER_SCHEDULER_PROGRAMS"](#) on page 6-97

ALL_SCHEDULER_REMOTE_DATABASES

ALL_SCHEDULER_REMOTE_DATABASES displays information about the remote databases accessible to the current user that have been registered as sources and destinations for remote database jobs.

Related View

DBA_SCHEDULER_REMOTE_DATABASES displays information about all remote databases that have been registered as sources and destinations for remote database jobs.

Column	Datatype	NULL	Description
DATABASE_NAME	VARCHAR2 (512)	NOT NULL	Global name of the remote database
REGISTERED_AS	VARCHAR2 (11)		Indicates whether the database is registered as a source (SOURCE) or as a destination (DESTINATION)
DATABASE_LINK	VARCHAR2 (512)	NOT NULL	Name of a valid database link to the remote database

See Also: ["DBA_SCHEDULER_REMOTE_DATABASES"](#) on page 5-93

ALL_SCHEDULER_REMOTE_JOBSTATE

ALL_SCHEDULER_REMOTE_JOBSTATE displays information about the state of the jobs accessible to the current user at remote databases.

Related Views

- DBA_SCHEDULER_REMOTE_JOBSTATE displays information about the state of all jobs at remote databases.
- USER_SCHEDULER_REMOTE_JOBSTATE displays information about the state of the jobs owned by the current user at remote databases. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Scheduler job
JOB_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler job

Column	Datatype	NULL	Description
DESTINATION	VARCHAR2 (512)	NOT NULL	Name of the job destination
STATE	VARCHAR2 (15)		State of the job at the destination: ■ DISABLED ■ RETRY SCHEDULED ■ SCHEDULED ■ RUNNING ■ COMPLETED ■ BROKEN ■ FAILED ■ SUCCEEDED ■ STOPPED
NEXT_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Next start date of the job at the destination
RUN_COUNT	NUMBER		Run count of the job at the destination
FAILURE_COUNT	NUMBER		Failure count of the job at the destination
RETRY_COUNT	NUMBER		Retry count of the job at the destination
LAST_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Last start date of the job at the destination
LAST_END_DATE	TIMESTAMP (6) WITH TIME ZONE		Last end date of the job at the destination

See Also:

- ["DBA_SCHEDULER_REMOTE_JOBSTATE"](#) on page 5-93
- ["USER_SCHEDULER_REMOTE_JOBSTATE"](#) on page 6-97

ALL_SCHEDULER_RUNNING_CHAINS

ALL_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of the running chains accessible to the current user (that is, those chains that the user has ALTER privileges for). In the case of nested chains, this view also enables you to traverse the hierarchy of the chain with a SQL statement that contains a CONNECT BY clause linking up the JOB_SUBNAME and STEP_JOB_SUBNAME columns.

Related Views

- DBA_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of all running chains in the database.
- USER_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of the running chains owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the job which is running the chain
JOB_NAME	VARCHAR2 (30)	NOT NULL	Name of the job which is running the chain
JOB_SUBNAME	VARCHAR2 (30)		Subname of the job which is running the chain (for a nested chain), else NULL
CHAIN_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the chain being run
CHAIN_NAME	VARCHAR2 (30)	NOT NULL	Name of the chain being run
STEP_NAME	VARCHAR2 (30)	NOT NULL	Name of the step of the running chain

Column	Datatype	NULL	Description
STATE	VARCHAR2 (15)		State of the running chain step: ■ NOT_STARTED ■ RUNNING ■ SUCCEEDED ■ STOPPED ■ FAILED ■ SCHEDULED ■ RETRY SCHEDULED ■ PAUSED ■ STALLED
ERROR_CODE	NUMBER		Error code with which the step completed (if it has completed)
COMPLETED	VARCHAR2 (5)		Indicates whether the running chain step has completed (TRUE) or not (FALSE)
START_DATE	TIMESTAMP (6) WITH TIME ZONE		Date when the running chain step started (if it has started)
END_DATE	TIMESTAMP (6) WITH TIME ZONE		Date when the running chain step stopped (if it has stopped)
DURATION	INTERVAL DAY (9) TO SECOND (6)		Amount of time it took the chain step to complete (if it has completed)
SKIP	VARCHAR2 (5)		Indicates whether the chain step should be skipped (TRUE) or not (FALSE)
PAUSE	VARCHAR2 (5)		Indicates whether the chain step should be paused after running (TRUE) or not (FALSE)
PAUSE_BEFORE ¹	VARCHAR2 (5)		Indicates whether the chain step should be paused before running (TRUE) or not (FALSE)
RESTART_ON_RECOVERY	VARCHAR2 (5)		Indicates whether the chain step will be restarted on database recovery (TRUE) or not (FALSE)
RESTART_ON_FAILURE	VARCHAR2 (5)		Indicates whether the chain step will be restarted on application failure (TRUE) or not (FALSE)
STEP_JOB_SUBNAME	VARCHAR2 (30)		Subname of the job running the step
STEP_JOB_LOG_ID	NUMBER		Log ID of the job running the step

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also:

- ["DBA_SCHEDULER_RUNNING_CHAINS"](#) on page 5-93
- ["USER_SCHEDULER_RUNNING_CHAINS"](#) on page 6-97

ALL_SCHEDULER_RUNNING_JOBS

ALL_SCHEDULER_RUNNING_JOBS displays information about the running Scheduler jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_RUNNING_JOBS displays information about all running Scheduler jobs in the database.
- USER_SCHEDULER_RUNNING_JOBS displays information about the running Scheduler jobs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the running Scheduler job
JOB_NAME	VARCHAR2 (30)		Name of the running Scheduler job
JOB_SUBNAME	VARCHAR2 (30)		Subname of the running Scheduler job (for a job running a chain step)
JOB_STYLE	VARCHAR2 (11)		Job style: - REGULAR - LIGHTWEIGHT
DETACHED	VARCHAR2 (5)		Indicates whether the detached attribute is set for the job (TRUE) or not (FALSE). If the detached attribute is set, then the job will remain running even after the job action has completed.
SESSION_ID	NUMBER		Identifier of the session running the Scheduler job
SLAVE_PROCESS_ID	NUMBER		Process number of the slave process running the Scheduler job
SLAVE_OS_PROCESS_ID	VARCHAR2 (12)		Process number of the operating system slave process running the scheduler job
RUNNING_INSTANCE	NUMBER		Database instance number of the slave process running the Scheduler job
RESOURCE_CONSUMER_GROUP	VARCHAR2 (32)		Resource consumer group of the session in which the Scheduler job is running
ELAPSED_TIME	INTERVAL DAY (3) TO SECOND (2)		Elapsed time since the Scheduler job was started
CPU_USED	INTERVAL DAY (3) TO SECOND (2)		CPU time consumed by the running Scheduler job, if available
DESTINATION_OWNER	VARCHAR2 (128)		Owner of the destination object (if used), else NULL
DESTINATION	VARCHAR2 (128)		Destination that this job is running on
CREDENTIAL_OWNER	VARCHAR2 (30)		Owner of the login credential used for this running job, if any
CREDENTIAL_NAME	VARCHAR2 (30)		Name of the login credential used for this running job, if any
LOG_ID ¹	NUMBER		Log ID used for this running job. This column maps to the LOG_ID column of the *_SCHEDULER_JOB_LOG and *_SCHEDULER_JOB_RUN_DETAILS views.

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also:

- ["DBA_SCHEDULER_RUNNING_JOBS"](#) on page 5-93
- ["USER_SCHEDULER_RUNNING_JOBS"](#) on page 6-98

ALL_SCHEDULER_SCHEDULES

ALL_SCHEDULER_SCHEDULES displays information about the Scheduler schedules accessible to the current user.

Related Views

- DBA_SCHEDULER_SCHEDULES displays information about all Scheduler schedules in the database.
- USER_SCHEDULER_SCHEDULES displays information about the Scheduler schedules owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the schedule
SCHEDULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the schedule
SCHEDULE_TYPE	VARCHAR2 (8)		Type of the schedule: - ONCE - Repeat interval is NULL - CALENDAR - Oracle calendaring expression used as schedule - EVENT - Event schedule
START_DATE	TIMESTAMP (6) WITH TIME ZONE		Start date for the repeat interval
REPEAT_INTERVAL	VARCHAR2 (4000)		Calendar syntax expression for the schedule
EVENT_QUEUE_OWNER	VARCHAR2 (30)		Owner of the source queue into which the event will be raised
EVENT_QUEUE_NAME	VARCHAR2 (30)		Name of the source queue into which the event will be raised
EVENT_QUEUE_AGENT	VARCHAR2 (30)		Name of the AQ agent used by the user on the event source queue (if it is a secure queue)
EVENT_CONDITION	VARCHAR2 (4000)		Boolean expression used as the subscription rule for the event on the source queue
FILE_WATCHER_OWNER	VARCHAR2 (65)		Owner of the file watcher on which this schedule is based
FILE_WATCHER_NAME	VARCHAR2 (65)		Name of the file watcher on which this schedule is based
END_DATE	TIMESTAMP (6) WITH TIME ZONE		Cutoff date after which the schedule will not specify any dates
COMMENTS	VARCHAR2 (240)		Comments on the schedule

See Also:

- ["DBA_SCHEDULER_SCHEDULES"](#) on page 5-94
- ["USER_SCHEDULER_SCHEDULES"](#) on page 6-98

ALL_SCHEDULER_WINDOW_DETAILS

ALL_SCHEDULER_WINDOW_DETAILS displays log details for the Scheduler windows accessible to the current user.

Related View

DBA_SCHEDULER_WINDOW_DETAILS displays log details for all Scheduler windows in the database.

Column	Datatype	NULL	Description
LOG_ID	NUMBER		Unique identifier of the log entry (foreign key of the *_SCHEDULER_WINDOW_LOG views)
LOG_DATE	TIMESTAMP (6) WITH TIME ZONE		Date of the log entry
WINDOW_NAME	VARCHAR2 (65)		Name of the Scheduler window
REQ_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Requested start date for the Scheduler window
ACTUAL_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Actual start date of the Scheduler window

Column	Datatype	NULL	Description
WINDOW_DURATION	INTERVAL DAY (3) TO SECOND (0)		Requested duration of the Scheduler window
ACTUAL_DURATION	INTERVAL DAY (3) TO SECOND (0)		Actual duration for which the Scheduler window lasted
INSTANCE_ID	NUMBER		Identifier of the instance on which the window was run
ADDITIONAL_INFO	VARCHAR2 (4000)		Additional information on the entry, if applicable

See Also: ["DBA_SCHEDULER_WINDOW_DETAILS"](#) on page 5-94

ALL_SCHEDULER_WINDOW_GROUPS

ALL_SCHEDULER_WINDOW_GROUPS displays information about the Scheduler window groups accessible to the current user.

Related View

DBA_SCHEDULER_WINDOW_GROUPS displays information about all Scheduler window groups in the database.

Column	Datatype	NULL	Description
WINDOW_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the window group
ENABLED	VARCHAR2 (5)		Indicates whether the window group is enabled (TRUE) or disabled (FALSE)
NUMBER_OF_WINDOWS	NUMBER		Number of members in the window group
NEXT_START_DATE	VARCHAR2 (64)		If a window group is disabled, then this column will be NULL. Otherwise, it will be set to the earliest NEXT_START_DATE from the enabled windows in the group.
COMMENTS	VARCHAR2 (240)		Optional comment about the window group

See Also: ["DBA_SCHEDULER_WINDOW_GROUPS"](#) on page 5-94

ALL_SCHEDULER_WINDOW_LOG

ALL_SCHEDULER_WINDOW_LOG displays log information for the Scheduler windows accessible to the current user.

Related View

DBA_SCHEDULER_WINDOW_LOG displays log information for all Scheduler windows in the database.

Column	Datatype	NULL	Description
LOG_ID	NUMBER	NOT NULL	Unique identifier of the log entry
LOG_DATE	TIMESTAMP (6) WITH TIME ZONE		Date of the log entry
WINDOW_NAME	VARCHAR2 (65)		Name of the Scheduler window
OPERATION	VARCHAR2 (30)		Operation corresponding to the log entry
STATUS	VARCHAR2 (30)		Status of the operation, if applicable
USER_NAME	VARCHAR2 (30)		Name of the user who performed the operation, if applicable

Column	Datatype	NULL	Description
CLIENT_ID	VARCHAR2 (64)		Client identifier of the user who performed the operation, if applicable
GLOBAL_UID	VARCHAR2 (32)		Global user identifier of the user who performed the operation, if applicable
ADDITIONAL_INFO	CLOB		Additional information on the entry, if applicable

See Also: ["DBA_SCHEDULER_WINDOW_LOG"](#) on page 5-94

ALL_SCHEDULER_WINDOWS

ALL_SCHEDULER_WINDOWS displays information about the Scheduler windows accessible to the current user.

Related View

DBA_SCHEDULER_WINDOWS displays information about all Scheduler windows in the database.

Column	Datatype	NULL	Description
WINDOW_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler window
RESOURCE_PLAN	VARCHAR2 (30)		Resource plan associated with the window
SCHEDULE_OWNER	VARCHAR2 (4000)		Owner of the schedule of the window
SCHEDULE_NAME	VARCHAR2 (4000)		Name of the schedule of the window
SCHEDULE_TYPE	VARCHAR2 (8)		Type of the schedule of the window: - ONCE - Repeat interval is NULL - NAMED - Named schedule - CALENDAR - Oracle calendaring expression used as schedule
START_DATE	TIMESTAMP (6) WITH TIME ZONE		Start date of the window (for an inline schedule)
REPEAT_INTERVAL	VARCHAR2 (4000)		Calendar string for the window (for an inline schedule)
END_DATE	TIMESTAMP (6) WITH TIME ZONE		Date after which the window will no longer open (for an inline schedule)
DURATION	INTERVAL DAY (3) TO SECOND (0)		Duration of the window
WINDOW_PRIORITY	VARCHAR2 (4)		Priority of the job relative to other windows: - HIGH - LOW
NEXT_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Next date on which the window is scheduled to start
LAST_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Last date on which the window opened
ENABLED	VARCHAR2 (5)		Indicates whether the window is enabled (TRUE) or disabled (FALSE)
ACTIVE	VARCHAR2 (5)		Indicates whether the window is open (TRUE) or not (FALSE)
MANUAL_OPEN_TIME	TIMESTAMP (6) WITH TIME ZONE		Open time of the window if it was manually opened, else NULL
MANUAL_DURATION	INTERVAL DAY (3) TO SECOND (0)		Duration of the window if it was manually opened, else NULL
COMMENTS	VARCHAR2 (240)		Comments on the window

See Also: ["DBA_SCHEDULER_WINDOWS"](#) on page 5-94

ALL_SCHEDULER_WINGROUP_MEMBERS

ALL_SCHEDULER_WINGROUP_MEMBERS displays the members of the Scheduler window groups accessible to the current user.

Related View

DBA_SCHEDULER_WINGROUP_MEMBERS displays the members of all Scheduler window groups in the database.

Column	Datatype	NULL	Description
WINDOW_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the window group
WINDOW_NAME	VARCHAR2 (30)	NOT NULL	Name of the window member of the window group

See Also: ["DBA_SCHEDULER_WINGROUP_MEMBERS"](#) on page 5-94

ALL_SEC_RELEVANT_COLS

ALL_SEC_RELEVANT_COLS describes the security relevant columns of the security policies for the tables and views accessible to the current user.

Related Views

- DBA_SEC_RELEVANT_COLS describes the security relevant columns of all security policies in the database.
- USER_SEC_RELEVANT_COLS describes the security relevant columns of the security policies for the tables and views owned by the current user. This view does not display the OBJECT_OWNER column.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)		Owner of the table or view
OBJECT_NAME	VARCHAR2 (30)		Name of the table or view
POLICY_GROUP	VARCHAR2 (30)		Name of the policy group
POLICY_NAME	VARCHAR2 (30)		Name of the policy
SEC_REL_COLUMN	VARCHAR2 (30)		Name of the security relevant column
COLUMN_OPTION	VARCHAR2 (8)		Option of the security relevant column: ■ NONE ■ ALL_ROWS

See Also:

- ["DBA_SEC_RELEVANT_COLS"](#) on page 5-94
- ["USER_SEC_RELEVANT_COLS"](#) on page 6-98

ALL_SECONDARY_OBJECTS

ALL_SECONDARY_OBJECTS provides information about secondary objects associated with domain indexes accessible to the user. This view is only relevant in the context of domain indexes. And currently, the secondary objects can only be tables.

Related Views

- `DBA_SECONDARY_OBJECTS` provides information about all secondary objects that are associated with domain indexes in the database.
- `USER_SECONDARY_OBJECTS` provides information about secondary objects associated with domain indexes owned by the current user.

Column	Datatype	NULL	Description
<code>INDEX_OWNER</code>	<code>VARCHAR2(30)</code>	NOT NULL	Owner of the domain index
<code>INDEX_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the domain index
<code>SECONDARY_OBJECT_OWNER</code>	<code>VARCHAR2(30)</code>	NOT NULL	Owner of the secondary object created by the domain index
<code>SECONDARY_OBJECT_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	Name of the secondary object created by the domain index
<code>SECONDARY_OBJDATA_TYPE</code>	<code>VARCHAR2(20)</code>		Type of the secondary object created by the domain index

ALL_SEQUENCES

`ALL_SEQUENCES` describes all sequences accessible to the current user.

Related Views

- `DBA_SEQUENCES` describes all sequences in the database.
- `USER_SEQUENCES` describes all sequences owned by the current user. This view does not display the `SEQUENCE_OWNER` column.

Column	Datatype	NULL	Description
<code>SEQUENCE_OWNER</code>	<code>VARCHAR2(30)</code>	NOT NULL	Owner of the sequence
<code>SEQUENCE_NAME</code>	<code>VARCHAR2(30)</code>	NOT NULL	Sequence name
<code>MIN_VALUE</code>	<code>NUMBER</code>		Minimum value of the sequence
<code>MAX_VALUE</code>	<code>NUMBER</code>		Maximum value of the sequence
<code>INCREMENT_BY</code>	<code>NUMBER</code>	NOT NULL	Value by which sequence is incremented
<code>CYCLE_FLAG</code>	<code>VARCHAR2(1)</code>		Indicates whether the sequence wraps around on reaching the limit (Y) or not (N)
<code>ORDER_FLAG</code>	<code>VARCHAR2(1)</code>		Indicates whether sequence numbers are generated in order (Y) or not (N)
<code>CACHE_SIZE</code>	<code>NUMBER</code>	NOT NULL	Number of sequence numbers to cache
<code>LAST_NUMBER</code>	<code>NUMBER</code>	NOT NULL	Last sequence number written to disk. If a sequence uses caching, the number written to disk is the last number placed in the sequence cache. This number is likely to be greater than the last sequence number that was used.

ALL_SERVICES

`ALL_SERVICES` displays all services in the database. The view excludes rows marked for deletion.

Related View

`DBA_SERVICES` displays all services in the database. The view excludes rows marked for deletion.

Column	Datatype	NULL	Description
SERVICE_ID	NUMBER		Unique ID for the service
NAME	VARCHAR2 (64)		Service name for a queue
NAME_HASH	NUMBER		Hash of the short name for the service
NETWORK_NAME	VARCHAR2 (512)		Network name used to connect to the service
CREATION_DATE	DATE		Date the service was created
CREATION_DATE_HASH	NUMBER		Hash of the creation date
FAILOVER_METHOD	VARCHAR2 (64)		Failover method (BASIC or NONE) for the service
FAILOVER_TYPE	VARCHAR2 (64)		Failover type (SESSION or SELECT) for the service
FAILOVER_RETRIES	NUMBER (10)		Number of retries when failing over the service
FAILOVER_DELAY	NUMBER (10)		Delay between retries when failing over the service
MIN_CARDINALITY	NUMBER		Reserved for internal use
MAX_CARDINALITY	NUMBER		Reserved for internal use
GOAL	VARCHAR2 (12)		Service workload management goal: - NONE - SERVICE_TIME - THROUGHPUT
DTP	VARCHAR2 (1)		Indicates whether the service is for DTP or distributed transactions including XA transactions (Y) or (N)
ENABLED	VARCHAR2 (3)		Reserved for internal use
AQ_HA_NOTIFICATIONS	VARCHAR2 (3)		Indicates whether AQ notifications are sent for HA events (YES) or not (NO)
CLB_GOAL	VARCHAR2 (5)		Connection load balancing goal. It is used with statistics that are sent to the listeners to determine how new connections are distributed. It may be either LONG or SHORT.
EDITION ¹	VARCHAR2 (30)		A non-NULL value specifies the initial session edition for subsequent database connections that use the service and do not specify an edition. A NULL value has no effect.

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

ALL_SOURCE

ALL_SOURCE describes the text source of the stored objects accessible to the current user.

Related Views

- DBA_SOURCE describes the text source of all stored objects in the database.
- USER_SOURCE describes the text source of the stored objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
NAME	VARCHAR2 (30)	NOT NULL	Name of the object
TYPE	VARCHAR2 (12)		Type of object: FUNCTION, JAVA_SOURCE, PACKAGE, PACKAGE_BODY, PROCEDURE, TRIGGER, TYPE, TYPE_BODY
LINE	NUMBER	NOT NULL	Line number of this line of source

Column	Datatype	NULL	Description
TEXT	VARCHAR2 (4000)		Text source of the stored object

ALL_SOURCE_AE

ALL_SOURCE_AE describes the text source of the stored objects (across all editions) accessible to the current user.

Related Views

- DBA_SOURCE_AE describes the text source of all stored objects (across all editions) in the database.
- USER_SOURCE_AE describes the text source of the stored objects (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the object
NAME	VARCHAR2 (30)		Name of the object
TYPE	VARCHAR2 (12)		Type of the object: ■ TYPE ■ TYPE BODY ■ PROCEDURE ■ FUNCTION ■ PACKAGE ■ PACKAGE BODY ■ LIBRARY ■ JAVA SOURCE
LINE	NUMBER		Line number of this line of source
TEXT	VARCHAR2 (4000)		Source text
EDITION_NAME	VARCHAR2 (30)		Name of the Edition

See Also:

- ["DBA_SOURCE_AE"](#) on page 5-98
- ["USER_SOURCE_AE"](#) on page 6-99

ALL_SOURCE_TABLES

ALL_SOURCE_TABLES is a synonym for USER_SOURCE_TABLES.

See Also: ["USER_SOURCE_TABLES"](#) on page 6-99

ALL_SQLJ_TYPE_ATTRS

ALL_SQLJ_TYPE_ATTRS describes the attributes of the SQLJ object types accessible to the current user.

Related Views

- DBA_SQLJ_TYPE_ATTRS describes the attributes of all SQLJ object types in the database.

- **USER_SQLJ_TYPE_ATTRS** describes the attributes of the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the type
TYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the type
ATTR_NAME	VARCHAR2 (30)	NOT NULL	Name of the attribute
EXTERNAL_ATTR_NAME	VARCHAR2 (4000)		External name of the attribute
ATTR_TYPE_MOD	VARCHAR2 (7)		Type modifier of the attribute: ■ REF ■ POINTER
ATTR_TYPE_OWNER	VARCHAR2 (30)		Owner of the type of the attribute
ATTR_TYPE_NAME	VARCHAR2 (30)		Name of the type of the attribute
LENGTH	NUMBER		Length of the CHAR attribute, or maximum length of the VARCHAR or VARCHAR2 attribute.
PRECISION	NUMBER		Decimal precision of the NUMBER or DECIMAL attribute, or binary precision of the FLOAT attribute.
SCALE	NUMBER		Scale of the NUMBER or DECIMAL attribute
CHARACTER_SET_NAME	VARCHAR2 (44)		Character set name of the attribute (CHAR_CS or NCHAR_CS)
ATTR_NO	NUMBER	NOT NULL	Syntactical order number or position of the attribute as specified in the type specification or CREATE TYPE statement (not to be used as an ID number)
INHERITED	VARCHAR2 (3)		Indicates whether the attribute is inherited from a supertype (YES) or not (NO)

See Also:

- ["DBA_SQLJ_TYPE_ATTRS"](#) on page 5-101
- ["USER_SQLJ_TYPE_ATTRS"](#) on page 6-99

ALL_SQLJ_TYPE_METHODS

ALL_SQLJ_TYPE_METHODS describes the methods of the SQLJ object types accessible to the current user.

Related Views

- **DBA_SQLJ_TYPE_METHODS** describes the methods of all SQLJ object types in the database.
- **USER_SQLJ_TYPE_METHODS** describes the methods of the SQLJ object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the type
TYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the type
METHOD_NAME	VARCHAR2 (30)	NOT NULL	Name of the method
EXTERNAL_VAR_NAME	VARCHAR2 (4000)		Name of the external variable
METHOD_NO	NUMBER	NOT NULL	Method number that distinguishes overloaded methods (not to be used as an ID number)

Column	Datatype	NULL	Description
METHOD_TYPE	VARCHAR2 (6)		Type of the method: - MAP - ORDER - PUBLIC
PARAMETERS	NUMBER	NOT NULL	Number of parameters to the method
RESULTS	NUMBER	NOT NULL	Number of results returned by the method
FINAL	VARCHAR2 (3)		Indicates whether the method is final (YES) or not (NO)
INSTANTIABLE	VARCHAR2 (3)		Indicates whether the method is instantiable (YES) or not (NO)
OVERRIDING	VARCHAR2 (3)		Indicates whether the method is overriding a supertype method (YES) or not (NO)
INHERITED	VARCHAR2 (3)		Indicates whether the method is inherited from a supertype (YES) or not (NO)

See Also:

- ["DBA_SQLJ_TYPE_METHODS"](#) on page 5-101
- ["USER_SQLJ_TYPE_METHODS"](#) on page 6-99

ALL_SQLJ_TYPES

ALL_SQLJ_TYPES describes the SQLJ object types accessible to the current user.

Related Views

- DBA_SQLJ_TYPES describes all SQLJ object types in the database.
- USER_SQLJ_TYPES describes the SQLJ object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the type
TYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the type
TYPE_OID	RAW (16)	NOT NULL	Object identifier (OID) of the type
EXTERNAL_NAME	VARCHAR2 (4000)		External class name of the type
USING	VARCHAR2 (21)		Representation of the type: - SQLData - CustomDatum - Serializable - Serializable Internal - ORADData
TYPECODE	VARCHAR2 (30)		Typecode of the type
ATTRIBUTES	NUMBER		Number of attributes (if any) in the type
METHODS	NUMBER		Number of methods (if any) in the type
PREDEFINED	VARCHAR2 (3)		Indicates whether the type is a predefined type (YES) or not (NO)
INCOMPLETE	VARCHAR2 (3)		Indicates whether the type is an incomplete type (YES) or not (NO)
FINAL	VARCHAR2 (3)		Indicates whether the type is a final type (YES) or not (NO)

Column	Datatype	NULL	Description
INSTANTIABLE	VARCHAR2 (3)		Indicates whether the type is an instantiable type (YES) or not (NO)
SUPERTYPE_OWNER	VARCHAR2 (30)		Owner of the supertype (NULL if type is not a subtype)
SUPERTYPE_NAME	VARCHAR2 (30)		Name of the supertype (NULL if type is not a subtype)
LOCAL_ATTRIBUTES	NUMBER		Number of local (not inherited) attributes (if any) in the subtype
LOCAL_METHODS	NUMBER		Number of local (not inherited) methods (if any) in the subtype

See Also:

- ["DBA_SQLJ_TYPES"](#) on page 5-101
- ["USER_SQLJ_TYPES"](#) on page 6-99

ALL_SQLSET

ALL_SQLSET displays information about all SQL tuning sets accessible to the current user.

Related Views

- DBA_SQLSET displays information about all SQL tuning sets in the database.
- USER_SQLSET displays information about the SQL tuning sets owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)	NOT NULL	Name of the SQL tuning set
ID	NUMBER	NOT NULL	SQL tuning set identifier
OWNER	VARCHAR2 (30)		Owner of the SQL tuning set
DESCRIPTION	VARCHAR2 (256)		Description of the SQL tuning set
CREATED	DATE		Date the SQL tuning set was created
LAST_MODIFIED	DATE		Date the SQL tuning set was last modified
STATEMENT_COUNT	NUMBER		Number of statements in the SQL tuning set

ALL_SQLSET_BINDS

ALL_SQLSET_BINDS displays the bind values associated with all SQL tuning sets accessible to the current user.

Related Views

- DBA_SQLSET_BINDS displays the bind values associated with all SQL tuning sets in the database.
- USER_SQLSET_BINDS displays the bind values associated with the SQL tuning sets owned by the current user. This view does not display the SQLSET_OWNER column.

Column	Datatype	NULL	Description
SQLSET_NAME	VARCHAR2 (30)	NOT NULL	Name of the SQL tuning set for the statement
SQLSET_OWNER	VARCHAR2 (30)		User name of the SQL tuning set owner

Column	Datatype	NULL	Description
SQLSET_ID	NUMBER	NOT NULL	ID of the SQL tuning set for the statement
SQL_ID	VARCHAR2 (13)	NOT NULL	SQL identifier of the parent cursor in the library cache
FORCE_MATCHING_SIGNATURE	NUMBER	NOT NULL	The signature used when the CURSOR_SHARING parameter is set to FORCE
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line-by-line).
POSITION	NUMBER	NOT NULL	Position
VALUE	ANYDATA		Value
CAPTURED	CHAR (1)		Binds captured
SQL_SEQ	NUMBER	NOT NULL	SQL sequence

ALL_SQLSET_PLANS

ALL_SQLSET_PLANS describes captured plans for statements in the SQL tuning sets accessible to the current user.

Related Views

- DBA_SQLSET_PLANS describes captured plans in the SQL tuning sets in the database.
- USER_SQLSET_PLANS describes captured plans for statements in the SQL tuning sets owned by the current user. This view does not display the SQLSET_OWNER column.

Column	Datatype	NULL	Description
SQLSET_NAME	VARCHAR2 (30)	NOT NULL	Name of SQL tuning set for the statement
SQLSET_ID	NUMBER	NOT NULL	ID of SQL tuning set for the statement
SQLSET_OWNER	VARCHAR2 (30)		User name of SQL tuning set owner
SQL_ID	VARCHAR2 (13)	NOT NULL	SQL identifier of the parent cursor in the library cache
FORCE_MATCHING_SIGNATURE	NUMBER	NOT NULL	The signature used when the CURSOR_SHARING parameter is set to FORCE
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line-by-line).
SQL_SEQ	NUMBER	NOT NULL	SQL sequence
STATEMENT_ID	VARCHAR2 (30)		Statement ID
PLAN_ID	NUMBER		Plan ID
TIMESTAMP	DATE		Date and time timestamp
REMARKS	VARCHAR2 (4000)		Remarks
OPERATION	VARCHAR2 (30)		Name of the internal operation performed in this step (for example, TABLE ACCESS)
OPTIONS	VARCHAR2 (255)		A variation on the operation described in the OPERATION column (for example, FULL)
OBJECT_NODE	VARCHAR2 (128)		Name of the database link used to reference the object (a table name or view name). For local queries that use parallel execution, this column describes the order in which output from operations is consumed.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)		Name of the user who owns the schema containing the table or index
OBJECT_NAME	VARCHAR2 (30)		Name of the table or index
OBJECT_ALIAS	VARCHAR2 (65)		Alias for the object
OBJECT_INSTANCE	NUMBER (38)		Instance number for the object
OBJECT_TYPE	VARCHAR2 (30)		Type of the object
OPTIMIZER	VARCHAR2 (255)		Current mode of the optimizer for the first row in the plan (statement line), for example, CHOOSE. When the operation is a database access (for example, TABLE ACCESS), this column indicates whether or not the object is analyzed.
SEARCH_COLUMNS	NUMBER		Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
ID	NUMBER (38)	NOT NULL	A number assigned to each step in the execution plan
PARENT_ID	NUMBER (38)		ID of the next execution step that operates on the output of the current step
DEPTH	NUMBER (38)		Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0.
POSITION	NUMBER (38)		Order of processing for all operations that have the same PARENT_ID.
COST	NUMBER (38)		Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
CARDINALITY	NUMBER (38)		Estimate, made by the cost-based optimizer, of the number of rows produced by the operation
BYTES	NUMBER (38)		Estimate, made by the cost-based optimizer, of the number of bytes produced by the operation
OTHER_TAG	VARCHAR2 (255)		Describes the contents of the OTHER column. For information about values, see EXPLAIN PLAN in <i>Oracle Database Performance Tuning Guide</i> .
PARTITION_START	VARCHAR2 (255)		Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2 (255)		Stop partition of a range of accessed partitions
PARTITION_ID	NUMBER (38)		Step that computes the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	LONG		Other information specific to the execution step that users may find useful. For information about values, see EXPLAIN_PLAN in <i>Oracle Database Performance Tuning Guide</i> .
DISTRIBUTION	VARCHAR2 (30)		Stores the method used to distribute rows from producer query servers to consumer query servers
CPU_COST	NUMBER (38)		CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
IO_COST	NUMBER (38)		I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
TEMP_SPACE	NUMBER (38)		Temporary space usage of the operation (sort or hash join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
ACCESS_PREDICATES	VARCHAR2 (4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.

Column	Datatype	NULL	Description
FILTER_PREDICATES	VARCHAR2 (4000)		Predicates used to filter rows before producing them
PROJECTION	VARCHAR2 (4000)		Expressions produced by the operation
TIME	NUMBER (38)		Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
QBLOCK_NAME	VARCHAR2 (30)		Name of the query block
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML since multiple pieces of information can be stored there. This includes: ■ Name of the schema against which the query was parsed ■ Release number of the Oracle Database that produced the explain plan ■ Hash value associated with the execution plan ■ Name (if any) of the outline or the SQL profile used to build the execution plan ■ Indication of whether or not dynamic sampling was used to produce the plan ■ The outline data, a set of optimizer hints that can be used to regenerate the same plan For further information about values, see <code>EXPLAIN PLAN</code> in <i>Oracle Database Performance Tuning Guide</i>
EXECUTIONS	NUMBER		Number of times the plan has been executed
STARTS	NUMBER		Number of times this operation has been started, accumulated over the past executions
OUTPUT_ROWS	NUMBER		Number of rows produced by the row source, accumulated over the past executions
CR_BUFFER_GETS	NUMBER		Number of buffers received in consistent mode, accumulated over the past executions. Buffers are usually retrieved in consistent mode for queries.
CU_BUFFER_GETS	NUMBER		Number of buffers retrieved in current mode, accumulated over the past executions. Buffers are retrieved in current mode for statements such as <code>INSERT</code> , <code>UPDATE</code> , and <code>DELETE</code> .
DISK_READS	NUMBER		Number of physical disk reads performed by the operation, accumulated over the past executions
DISK_WRITES	NUMBER		Number of physical disk writes performed by the operation, accumulated over the past executions
ELAPSED_TIME	NUMBER		Elapsed time (in microseconds) corresponding to this operation, accumulated over the past executions
LAST_STARTS	NUMBER		Number of times this operation has been started, during the last execution
LAST_OUTPUT_ROWS	NUMBER		Number of rows produced by the row source, during the last execution
LAST_CR_BUFFER_GETS	NUMBER		Number of buffers retrieved in consistent mode, during the last execution. Buffers are usually retrieved in consistent mode for queries.
LAST_CU_BUFFER_GETS	NUMBER		Number of buffers retrieved in current mode, during the last execution. Buffers are retrieved in current mode for statements such as <code>INSERT</code> , <code>UPDATE</code> , and <code>DELETE</code> .
LAST_DISK_READS	NUMBER		Number of physical disk reads performed by the operation, during the last execution
LAST_DISK_WRITES	NUMBER		Number of physical disk writes performed by the operation, during the last execution

Column	Datatype	NULL	Description
LAST_ELAPSED_TIME	NUMBER		Elapsed time (in microseconds) corresponding to this operation, during the last execution
POLICY	VARCHAR2 (10)		Sizing policy for this work area: - MANUAL - AUTO
ESTIMATED_OPTIMAL_SIZE	NUMBER		Estimated size (in KB) required by this work area to execute the operation completely in memory (optimal execution). This is either derived from optimizer statistics or from previous executions.
ESTIMATED_ONEPASS_SIZE	NUMBER		Estimated size (in KB) required by this work area to execute the operation in a single pass. This is either derived from optimizer statistics or from previous executions.
LAST_MEMORY_USED	NUMBER		Memory size (in KB) used by this work area during the last execution of the cursor
LAST_EXECUTION	VARCHAR2 (10)		Indicates whether this work area ran using OPTIMAL, ONE PASS, or under ONE PASS memory requirement (MULTI-PASS), during the last execution of the cursor
LAST_DEGREE	NUMBER		Degree of parallelism used, during the last execution of the cursor
TOTAL_EXECUTIONS	NUMBER		Number of times this work area was active
OPTIMAL_EXECUTIONS	NUMBER		Number of times this work area ran in optimal mode
ONEPASS_EXECUTIONS	NUMBER		Number of times this work area ran in one pass mode
MULTIPASSES_EXECUTIONS	NUMBER		Number of times this work area ran below the one pass memory requirement
ACTIVE_TIME	NUMBER		Average time this work area is active (in hundredths of a second)
MAX_TEMPSEG_SIZE	NUMBER		Maximum temporary segment size (in bytes) created by an instantiation of this work area. This column is null if this work area has never spilled to disk.
LAST_TEMPSEG_SIZE	NUMBER		Temporary segment size (in bytes) created in the last instantiation of this work area. This column is null if the last instantiation of this work area did not spill to disk.

ALL_SQLSET_REFERENCES

ALL_SQLSET_REFERENCES describes whether or not the SQL tuning sets accessible to the current user are active.

Related Views

- DBA_SQLSET_REFERENCES describes whether or not all SQL tuning sets in the database are active. A SQL tuning set cannot be dropped if it is referenced.
- USER_SQLSET_REFERENCES describes whether or not the SQL tuning sets owned by the current user are active.

Column	Datatype	NULL	Description
SQLSET_NAME	VARCHAR2 (30)	NOT NULL	Name of the SQL tuning set
SQLSET_ID	NUMBER	NOT NULL	Identifier of the SQL tuning set
SQLSET_OWNER	VARCHAR2 (30)		Owner of the SQL tuning set
ID	NUMBER	NOT NULL	Reference identifier
OWNER	VARCHAR2 (30)		User who registered to use the SQL tuning set

Column	Datatype	NULL	Description
DESCRIPTION	VARCHAR2 (256)		Description of the usage of the SQL tuning set
CREATED	DATE		Date the reference was created

ALL_SQLSET_STATEMENTS

ALL_SQLSET_STATEMENTS displays information about the SQL statements, along with their statistics, that form all SQL tuning sets accessible to the current user.

Related Views

- DBA_SQLSET_STATEMENTS displays information about the SQL statements, along with their statistics, that form all SQL tuning sets in the database. This view does not display the SQL_SEQ column.
- USER_SQLSET_STATEMENTS displays information about the SQL statements, along with their statistics, that form the SQL tuning sets owned by the current user. This view does not display the SQLSET_OWNER column.

Column	Datatype	NULL	Description
SQLSET_NAME	VARCHAR2 (30)	NOT NULL	Name of the SQL tuning set for the statement
SQLSET_ID	NUMBER	NOT NULL	ID of the SQL tuning set for the statement
SQLSET_OWNER	VARCHAR2 (30)		User name of the SQL tuning set owner
SQL_ID	VARCHAR2 (13)	NOT NULL	SQL identifier of the parent cursor in the library cache
FORCE_MATCHING_SIGNATURE	NUMBER	NOT NULL	The signature used when the CURSOR_SHARING parameter is set to FORCE
SQL_TEXT	CLOB		Full text for the SQL statement exposed as a CLOB column.
PLAN_HASH_VALUE	NUMBER	NOT NULL	Hash value for the plan corresponding to statistics in this record
PARSING_SCHEMA_NAME	VARCHAR2 (30)		Name of the user in whose schema the statement was parsed
BIND_DATA	RAW (2000)		Bind data
BINDS_CAPTURED	CHAR (1)		Binds captured
MODULE ¹	VARCHAR2 (48)		Contains the name of the module that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_MODULE
ACTION ¹	VARCHAR2 (32)		Contains the name of the action that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_ACTION
ELAPSED_TIME	NUMBER		Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching
CPU_TIME	NUMBER		CPU time (in microseconds) used by this cursor for parsing, executing, and fetching
BUFFER_GETS	NUMBER		Number of buffer gets for this child cursor
DISK_READS	NUMBER		Number of disk reads for this child cursor
DIRECT_WRITES	NUMBER		Number of direct writes for this child cursor
ROWS_PROCESSED	NUMBER		Total number of rows that the parsed SQL statement returns
FETCHES	NUMBER		Number of fetches associated with the SQL statement

Column	Datatype	NULL	Description
EXECUTIONS	NUMBER		Number of executions that took place on this object since it was brought into the library cache
END_OF_FETCH_COUNT	NUMBER		Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less than, or equal to, the value of the EXECUTIONS column.
OPTIMIZER_COST	NUMBER		Cost of this query, given by the optimizer
OPTIMIZER_ENV	RAW(1000)		Optimizer environment
PRIORITY	NUMBER		User-defined priority
COMMAND_TYPE	NUMBER		Oracle command type definition
FIRST_LOAD_TIME	VARCHAR2(19)		Timestamp of the parent creation time
STAT_PERIOD	NUMBER		Period of time (in seconds) during which the statistics of the SQL statement were collected
ACTIVE_STAT_PERIOD	NUMBER		Effective period of time (in seconds) during which the SQL statement was active
OTHER	CLOB		Client data, specified by the user, for this statement
PLAN_TIMESTAMP	DATE		Timestamp for the plan corresponding to the statistics in this record
SQL_SEQ	NUMBER	NOT NULL	SQL sequence

¹ The datatype of this column is VARCHAR2(64) starting with Oracle Database 11g Release 2 (11.2.0.2).

ALL_STAT_EXTENSIONS

ALL_STAT_EXTENSIONS displays information about the optimizer statistics extensions accessible to the current user.

Related Views

- DBA_STAT_EXTENSIONS displays information about all optimizer statistics extensions in the database.
- USER_STAT_EXTENSIONS displays information about the optimizer statistics extensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(30)	NOT NULL	Owner of the extension
TABLE_NAME	VARCHAR2(30)	NOT NULL	Name of the table to which the extension belongs
EXTENSION_NAME	VARCHAR2(30)	NOT NULL	Name of the statistics extension
EXTENSION	CLOB		Extension (the expression or column group)
CREATOR	VARCHAR2(6)		Creator of the extension: ■ USER ■ SYSTEM
DROPPABLE	VARCHAR2(3)		Indicates whether the extension is droppable using DBMS_STATS.DROP_EXTENDED_STATS (YES) or not (NO)

See Also:

- ["DBA_STAT_EXTENSIONS"](#) on page 5-107
- ["USER_STAT_EXTENSIONS"](#) on page 6-101

ALL_STORED_SETTINGS

ALL_STORED_SETTINGS provides information about the persistent parameter settings for stored PL/SQL units for which the current user has execute privileges.

Related Views

- DBA_STORED_SETTINGS lists information about the persistent parameter settings for stored PL/SQL units for which the current user has execute privileges. It also returns parameter information for all objects in the database and is accessible only to users with the SELECT_CATALOG_ROLE privilege.
- USER_STORED_SETTINGS lists information about the persistent parameter settings for stored PL/SQL units, but only shows information about PL/SQL units owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Name of the database user owning the stored PL/SQL unit
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the PL/SQL unit
OBJECT_ID	NUMBER	NOT NULL	Object number of the PL/SQL unit
OBJECT_TYPE	VARCHAR2 (12)		The type of PL/SQL unit: PROCEDURE, FUNCTION, PACKAGE, PACKAGE BODY, TRIGGER, TYPE, or TYPE BODY
PARAM_NAME	VARCHAR2 (30)		The name of the parameter stored persistently with the PL/SQL unit
PARAM_VALUE	VARCHAR2 (4000)		The TO_CHAR () representation of the value of the persistently stored parameter. The width of this column is operating system dependent; however, it is never less than 255.

Note: This view is deprecated in favor of the ALL_PLSQL_OBJECT_SETTINGS view. Oracle recommends that you use ALL_PLSQL_OBJECT_SETTINGS instead. ALL_STORED_SETTINGS is retained for backward compatibility only.

ALL_STREAMS_COLUMNS

ALL_STREAMS_COLUMNS displays information about the Streams unsupported columns accessible to the current user.

Related View

DBA_STREAMS_COLUMNS displays information about all Streams unsupported columns in the database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table

Column	Datatype	NULL	Description
COLUMN_NAME	VARCHAR2 (30)		Name of the column
SYNC_CAPTURE_VERSION	NUMBER		Version of the synchronous capture that supports this column
SYNC_CAPTURE_REASON	VARCHAR2 (39)		Reason why this column is not supported by synchronous capture
APPLY_VERSION	NUMBER		Version of apply that supports this column
APPLY_REASON	VARCHAR2 (40)		Reason why this column is not supported by apply

See Also: ["DBA_STREAMS_COLUMNS"](#) on page 6-2

ALL_STREAMS_GLOBAL_RULES

ALL_STREAMS_GLOBAL_RULES displays information about the following types of rules:

- Global rules created for the Streams capture processes that enqueue the captured changes into queues accessible to the current user
- Global rules created for the Streams propagations that have a source queue accessible to the current user
- Global rules created for the Streams apply processes that dequeue events from queues accessible to the current user

This view only contains information about rules created using the ADD_GLOBAL_RULES or ADD_GLOBAL_PROPAGATION_RULES procedures in the DBMS_STREAMS_ADM package. It does not contain information about rules created using the DBMS_RULE_ADM package.

Related View

DBA_STREAMS_GLOBAL_RULES displays information about the global rules created for all Streams capture processes, propagations, and apply processes in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2 (30)		Name of the Streams process or propagation
STREAMS_TYPE	VARCHAR2 (11)		Type of the Streams process or propagation: ■ CAPTURE ■ PROPAGATION ■ APPLY
RULE_TYPE	VARCHAR2 (7)		Type of the rule: ■ DML ■ DDL
INCLUDE_TAGGED_LCR	VARCHAR2 (3)		Indicates whether a redo entry or logical change record (LCR) with a non-NULL tag is considered for capture, propagation, or apply (YES) or not (NO)
SOURCE_DATABASE	VARCHAR2 (128)		Source database in the rule condition. The rule evaluates to true for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this source database.
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_CONDITION	VARCHAR2 (4000)		First 4000 bytes of the system-generated rule condition evaluated by the rules engine

See Also: ["DBA_STREAMS_GLOBAL_RULES"](#) on page 6-2

ALL_STREAMS_MESSAGE_CONSUMERS

ALL_STREAMS_MESSAGE_CONSUMERS displays information about the Streams messaging clients accessible to the current user.

Related View

DBA_STREAMS_MESSAGE_CONSUMERS displays information about all Streams messaging clients in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2 (30)	NOT NULL	Name of the messaging client
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue
QUEUE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the queue
RULE_SET_NAME	VARCHAR2 (30)		Name of the positive rule set
RULE_SET_OWNER	VARCHAR2 (30)		Owner of the positive rule set
NEGATIVE_RULE_SET_NAME	VARCHAR2 (30)		Name of the negative rule set
NEGATIVE_RULE_SET_OWNER	VARCHAR2 (30)		Owner of the negative rule set
NOTIFICATION_TYPE	VARCHAR2 (9)		Type of the notification action: ■ PROCEDURE ■ MAIL ■ HTTP
NOTIFICATION_ACTION	VARCHAR2 (256)		Notification action
NOTIFICATION_CONTEXT	ANYDATA		Context for the notification action

See Also: ["DBA_STREAMS_MESSAGE_CONSUMERS"](#) on page 6-3

ALL_STREAMS_MESSAGE_RULES

ALL_STREAMS_MESSAGE_RULES displays information about the Streams messaging rules accessible to the current user.

Related View

DBA_STREAMS_MESSAGE_RULES displays information about all Streams messaging rules in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2 (30)		Name of the Streams client
STREAMS_TYPE	VARCHAR2 (11)		Type of the Streams client: ■ PROPAGATION - Streams propagation ■ APPLY - Streams apply process ■ DEQUEUE - Streams messaging client
MESSAGE_TYPE_NAME	VARCHAR2 (30)		Name of the message type
MESSAGE_TYPE_OWNER	VARCHAR2 (30)		Owner of the message type
MESSAGE_RULE_VARIABLE	VARCHAR2 (30)		Name of the variable in the message rule
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_CONDITION	VARCHAR2 (4000)		Rule condition

See Also: ["DBA_STREAMS_MESSAGE_RULES"](#) on page 6-3

ALL_STREAMS_NEWLY_SUPPORTED

ALL_STREAMS_NEWLY_SUPPORTED displays information about the tables accessible to the current user that are newly supported by Streams capture processes.

Related View

DBA_STREAMS_NEWLY_SUPPORTED displays information about all tables in the database that are newly supported by Streams capture processes.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table
REASON	VARCHAR2 (39)		Reason why the table was not supported in a previous release: ▪ IOT ▪ column with user-defined type ▪ unsupported column exists ▪ object table ▪ AQ queue table ▪ temporary table ▪ sub object ▪ external table ▪ materialized view ▪ FILE column exists ▪ materialized view log ▪ materialized view container table ▪ streams unsupported object ▪ domain index
COMPATIBLE	CHAR (4)		Minimum database compatibility for capture processes to support the database object

See Also: ["DBA_STREAMS_NEWLY_SUPPORTED"](#) on page 6-3

ALL_STREAMS_RULES

ALL_STREAMS_RULES displays information about the rules used by the Streams processes accessible to the current user.

Related View

DBA_STREAMS_RULES displays information about the rules used by all Streams processes in the database.

Column	Datatype	NULL	Description
STREAMS_TYPE	VARCHAR2 (12)		Type of the Streams process: ■ CAPTURE ■ PROPAGATION ■ APPLY ■ DEQUEUE ■ SYNC_CAPTURE
STREAMS_NAME	VARCHAR2 (30)		Name of the Streams process
RULE_SET_OWNER	VARCHAR2 (30)		Owner of the rule set
RULE_SET_NAME	VARCHAR2 (30)		Name of the rule set
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule
RULE_CONDITION	CLOB		Current rule condition
RULE_SET_TYPE	CHAR (8)		Type of the rule set: ■ POSITIVE ■ NEGATIVE
STREAMS_RULE_TYPE	VARCHAR2 (6)		For global, schema, or table rules, the type of the rule: ■ TABLE ■ SCHEMA ■ GLOBAL
SCHEMA_NAME	VARCHAR2 (30)		For table and schema rules, the schema name
OBJECT_NAME	VARCHAR2 (30)		For table rules, the table name
SUBSETTING_OPERATION	VARCHAR2 (6)		For subset rules, the type of operation: ■ INSERT ■ UPDATE ■ DELETE
DML_CONDITION	VARCHAR2 (4000)		For subset rules, the row subsetting condition
INCLUDE_TAGGED_LCR	VARCHAR2 (3)		For global, schema, or table rules, indicates whether to include tagged logical change records (LCRs) (YES) or not (NO)
SOURCE_DATABASE	VARCHAR2 (128)		For global, schema, or table rules, the name of the database where the logical change records (LCRs) originated
RULE_TYPE	VARCHAR2 (3)		For global, schema, or table rules, the type of the rule: ■ DML ■ DDL
MESSAGE_TYPE_OWNER	VARCHAR2 (30)		For message rules, the owner of the message type
MESSAGE_TYPE_NAME	VARCHAR2 (30)		For message rules, the name of the message type
MESSAGE_RULE_VARIABLE	VARCHAR2 (30)		For message rules, the name of the variable in the message rule
ORIGINAL_RULE_CONDITION	VARCHAR2 (4000)		For rules created by Streams administrative APIs, the original rule condition when the rule was created
SAME_RULE_CONDITION	VARCHAR2 (3)		For rules created by Streams administrative APIs, indicates whether the current rule condition is the same as the original rule condition (YES) or not (NO)

See Also: ["DBA_STREAMS_RULES"](#) on page 6-4

ALL_STREAMS_SCHEMA_RULES

ALL_STREAMS_SCHEMA_RULES displays information about the following types of rules:

- Schema rules created for the Streams capture processes that enqueue the captured changes into queues accessible to the current user
- Schema rules created for the Streams propagations that have a source queue accessible to the current user
- Schema rules created for the Streams apply processes that dequeue events from queues accessible to the current user

This view only contains information about rules created using the ADD_SCHEMA_RULES or ADD_SCHEMA_PROPAGATION_RULES procedures in the DBMS_STREAMS_ADM package. It does not contain information about rules created using the DBMS_RULE_ADM package.

Related View

DBA_STREAMS_SCHEMA_RULES displays information about the schema rules created for all Streams capture processes, propagations, and apply processes in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2 (30)		Name of the Streams process or propagation
STREAMS_TYPE	VARCHAR2 (11)		Type of the Streams process or propagation: ■ CAPTURE ■ PROPAGATION ■ APPLY
SCHEMA_NAME	VARCHAR2 (30)		Schema name in the rule condition. The rule evaluates to true for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this schema name.
RULE_TYPE	VARCHAR2 (7)		Type of the rule: ■ DML ■ DDL
INCLUDE_TAGGED_LCR	VARCHAR2 (3)		Indicates whether a redo entry or logical change record (LCR) with a non-NULL tag is considered for capture, propagation, or apply (YES) or not (NO)
SOURCE_DATABASE	VARCHAR2 (128)		Source database in the rule condition. The rule evaluates to true for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this source database.
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_CONDITION	VARCHAR2 (4000)		First 4000 bytes of the system-generated rule condition evaluated by the rules engine

See Also: ["DBA_STREAMS_SCHEMA_RULES"](#) on page 6-4

ALL_STREAMS_STMT_HANDLERS

ALL_STREAMS_STMT_HANDLERS displays information about all statement DML handlers in the database.

Related View

DBA_STREAMS_STMT_HANDLERS displays information about all statement DML handlers in the database.

Column	Datatype	NULL	Description
HANDLER_NAME	VARCHAR2 (30)	NOT NULL	Name of the statement handler
HANDLER_COMMENT	VARCHAR2 (4000)		Comment specified with the statement handler
CREATION_TIME	TIMESTAMP (6)		Timestamp for script creation
MODIFICATION_TIME	TIMESTAMP (6)		Timestamp for script modification

See Also: ["DBA_STREAMS_STMT_HANDLERS"](#) on page 6-8

Note: The ALL_STREAMS_STMT_HANDLERS view is not available starting with Oracle Database 11g Release 2 (11.2.0.2).

ALL_STREAMS_STMTS

ALL_STREAMS_STMTS displays information about the statements in all statement DML handlers in the database.

Related View

DBA_STREAMS_STMTS displays information about the statements in all statement DML handlers in the database.

Column	Datatype	NULL	Description
HANDLER_NAME	VARCHAR2 (30)	NOT NULL	Name of the statement handler
EXECUTION_SEQUENCE	NUMBER	NOT NULL	Execution sequence of the statement
STATEMENT	CLOB		Text of the statement
CREATION_TIME	TIMESTAMP (6)		Timestamp for statement creation
MODIFICATION_TIME	TIMESTAMP (6)		Timestamp for statement modification

See Also: ["DBA_STREAMS_STMTS"](#) on page 6-8

Note: The ALL_STREAMS_STMTS view is not available starting with Oracle Database 11g Release 2 (11.2.0.2).

ALL_STREAMS_TABLE_RULES

ALL_STREAMS_TABLE_RULES displays information about the following types of rules:

- Table rules created for the Streams capture processes that enqueue the captured changes into queues accessible to the current user
- Table rules created for the Streams propagations that have a source queue accessible to the current user

- Table rules created for the Streams apply processes that dequeue events from queues accessible to the current user
- Subset rules created for the Streams apply processes that have a source queue accessible to the current user

This view only contains information about rules created using the `ADD_TABLE_RULES`, `ADD_TABLE_PROPAGATION_RULES`, or `ADD_SUBSET_RULES` procedures in the `DBMS_STREAMS_ADM` package. It does not contain information about rules created using the `DBMS_RULE_ADM` package.

Related View

`DBA_STREAMS_TABLE_RULES` displays information about the table rules created for all Streams capture processes, propagations, and apply processes in the database.

Column	Datatype	NULL	Description
<code>STREAMS_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the Streams process or propagation
<code>STREAMS_TYPE</code>	<code>VARCHAR2 (12)</code>		Type of the Streams process or propagation: ■ <code>CAPTURE</code> ■ <code>PROPAGATION</code> ■ <code>APPLY</code> ■ <code>DEQUEUE</code> ■ <code>SYNC_CAPTURE</code>
<code>TABLE_OWNER</code>	<code>VARCHAR2 (30)</code>		Table owner in the rule condition. The rule evaluates to <code>true</code> for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this table owner.
<code>TABLE_NAME</code>	<code>VARCHAR2 (30)</code>		Table name in the rule condition. The rule evaluates to <code>true</code> for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this table name.
<code>RULE_TYPE</code>	<code>VARCHAR2 (7)</code>		Type of the rule: ■ <code>DML</code> ■ <code>DDL</code>
<code>DML_CONDITION</code>	<code>VARCHAR2 (4000)</code>		Row subsetting condition, if the rule is a subset rule
<code>SUBSETTING_OPERATION</code>	<code>VARCHAR2 (6)</code>		DML operation for row subsetting in the rule condition, if the rule is a subset rule: ■ <code>INSERT</code> ■ <code>UPDATE</code> ■ <code>DELETE</code>
<code>INCLUDE_TAGGED_LCR</code>	<code>VARCHAR2 (3)</code>		The rule evaluates to <code>true</code> for a logical change record (LCR) only if the LCR contains this command type after internal transformation.
<code>SOURCE_DATABASE</code>	<code>VARCHAR2 (128)</code>		Indicates whether a redo entry or logical change record (LCR) with a non-NULL tag is considered for capture, propagation, or apply (YES) or not (NO)
<code>RULE_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Source database in the rule condition. The rule evaluates to <code>true</code> for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this source database.
<code>RULE_OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the rule
<code>RULE_CONDITION</code>	<code>VARCHAR2 (4000)</code>		Owner of the rule
			First 4000 bytes of the system-generated rule condition evaluated by the rules engine

See Also: ["DBA_STREAMS_TABLE_RULES"](#) on page 6-8

ALL_STREAMS_TRANSFORM_FUNCTION

ALL_STREAMS_TRANSFORM_FUNCTION displays information about the rule-based transformation functions accessible to the current user.

Related View

DBA_STREAMS_TRANSFORM_FUNCTION displays information about all rule-based transformation functions in the database.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule associated with the transformation function
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule associated with the transformation function
VALUE_TYPE	VARCHAR2 (4000)		Type of the transformation function name. This type must be VARCHAR2 for a rule-based transformation to work properly.
TRANSFORM_FUNCTION_NAME	VARCHAR2 (4000)		Name of the transformation function (NULL if VALUE_TYPE is not VARCHAR2)
CUSTOM_TYPE	VARCHAR2 (11)		Type of the transformation function: ■ ONE TO ONE - One-to-one transformations ■ ONE TO MANY - One-to-many transformations

See Also:

- ["DBA_STREAMS_TRANSFORM_FUNCTION"](#) on page 6-11
- *Oracle Streams Concepts and Administration* for more information about custom rule-based transformation

ALL_STREAMS_UNSUPPORTED

ALL_STREAMS_UNSUPPORTED displays information about the tables accessible to the current user that are not supported by Streams in this release of the Oracle Database.

Related View

DBA_STREAMS_UNSUPPORTED displays information about all tables in the database that are not supported by Streams in this release of the Oracle Database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table

Column	Datatype	NULL	Description
REASON	VARCHAR2 (39)		Reason why the table is not supported: ■ IOT ■ column with user-defined type ■ unsupported column exists ■ object table ■ AQ queue table ■ temporary table ■ sub object ■ external table ■ materialized view ■ FILE column exists ■ materialized view log ■ materialized view container table ■ streams unsupported object ■ domain index ■ IOT with overflow ■ IOT with LOB ■ IOT with physical Rowid mapping ■ mapping table for physical rowid of IOT ■ IOT with LOB ■ IOT with row movement ■ summary container table
AUTO_FILTERED	VARCHAR2 (3)		Indicates whether Streams automatically filters out the object (YES) or not (NO)

See Also: ["DBA_STREAMS_UNSUPPORTED"](#) on page 6-12

ALL_SUBPART_COL_STATISTICS

ALL_SUBPART_COL_STATISTICS describes column statistics and histogram information for subpartitions of partitioned objects accessible to the current user.

Related Views

- DBA_SUBPART_COL_STATISTICS provides this information for all subpartitions in the database.
- USER_SUBPART_COL_STATISTICS provides this information for subpartitions of all partitioned objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
SUBPARTITION_NAME	VARCHAR2 (30)		Table subpartition name
COLUMN_NAME	VARCHAR2 (4000)		Column name
NUM_DISTINCT	NUMBER		Number of distinct values in the column
LOW_VALUE	RAW (32)		Low value in the column
HIGH_VALUE	RAW (32)		High value in the column

Column	Datatype	NULL	Description
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in histogram for the column
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
GLOBAL_STATS	VARCHAR2 (3)		Indicates whether column statistics for the subpartition were collected by analyzing the table as a whole (YES) or estimated from statistics gathered on partitions and subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
HISTOGRAM	VARCHAR2 (15)		Indicates existence/type of histogram: - NONE - FREQUENCY - HEIGHT BALANCED

ALL_SUBPART_HISTOGRAMS

ALL_SUBPART_HISTOGRAMS displays the actual histogram data (end-points per histogram) for histograms on table subpartitions accessible to the current user.

Related Views

- DBA_SUBPART_HISTOGRAMS displays this information for all subpartitions in the database.
- USER_SUBPART_HISTOGRAMS displays this information for subpartitions of all partitioned objects owned by the current user. This view does not display the OWNER column.

Note: These views are populated only if you collect statistics on the index using the ANALYZE statement or the DBMS_STATS package.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table
SUBPARTITION_NAME	VARCHAR2 (30)		Table subpartition name
COLUMN_NAME	VARCHAR2 (4000)		Column name
BUCKET_NUMBER	NUMBER		Bucket number
ENDPOINT_VALUE	NUMBER		Normalized endpoint values for this bucket
ENDPOINT_ACTUAL_VALUE	VARCHAR2 (1000)		Actual (not normalized) string value of the endpoint for this bucket

ALL_SUBPART_KEY_COLUMNS

ALL_SUBPART_KEY_COLUMNS displays subpartitioning key columns for composite-partitioned tables (and local indexes on composite-partitioned tables) accessible to the current user.

Related Views

- DBA_SUBPART_KEY_COLUMNS displays this information for all subpartitions in the database.
- USER_SUBPART_KEY_COLUMNS displays this information for subpartitions of all partitioned objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the partitioned table or index
NAME	VARCHAR2 (30)		Name of the partitioned table or index
OBJECT_TYPE	CHAR (5)		Object type: ■ TABLE ■ INDEX
COLUMN_NAME	VARCHAR2 (4000)		Column name
COLUMN_POSITION	NUMBER		Position of the column within the subpartitioning key

See Also:

- ["DBA_SUBPART_KEY_COLUMNS"](#) on page 6-13
- ["USER_SUBPART_KEY_COLUMNS"](#) on page 6-101

ALL_SUBPARTITION_TEMPLATES

ALL_SUBPARTITION_TEMPLATES describes the subpartition templates accessible to the current user.

Related Views

- DBA_SUBPARTITION_TEMPLATES describes all subpartition templates in the database.
- USER_SUBPARTITION_TEMPLATES describes the subpartition templates owned by the current user. This view does not display the USER_NAME column.

Column	Datatype	NULL	Description
USER_NAME	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
SUBPARTITION_NAME	VARCHAR2 (34)	NOT NULL	Name of the subpartition
SUBPARTITION_POSITION	NUMBER		Position of the subpartition
TABLESPACE_NAME	VARCHAR2 (30)		Tablespace name of the subpartition
HIGH_BOUND	LONG		Literal list values of the subpartition

See Also:

- ["DBA_SUBPARTITION_TEMPLATES"](#) on page 6-13
- ["USER_SUBPARTITION_TEMPLATES"](#) on page 6-101

ALL_SUBSCRIBED_COLUMNS

ALL_SUBSCRIBED_COLUMNS is a synonym for USER_SUBSCRIBED_COLUMNS.

See Also: ["USER_SUBSCRIBED_COLUMNS"](#) on page 6-102

ALL_SUBSCRIBED_TABLES

ALL_SUBSCRIBED_TABLES is a synonym for USER_SUBSCRIBED_TABLES.

See Also: ["USER_SUBSCRIBED_TABLES"](#) on page 6-102

ALL_SUBSCRIPTIONS

ALL_SUBSCRIPTIONS is a synonym for USER_SUBSCRIPTIONS.

See Also: ["USER_SUBSCRIPTIONS"](#) on page 6-102

ALL_SUMDELTA

ALL_SUMDELTA lists direct path load entries accessible to the current user.

Column	Datatype	NULL	Description
TABLEOBJ#	NUMBER	NOT NULL	Object number of the table
PARTITIONOBJ#	NUMBER	NOT NULL	Object number of table partitions (if the table is partitioned)
DMLOPERATION	VARCHAR2 (1)		Type of DML operation applied to the table
SCN	NUMBER	NOT NULL	SCN when the bulk DML occurred
TIMESTAMP	DATE	NOT NULL	Timestamp of the log entry
LOWROWID	ROWID	NOT NULL	Start ROWID in the loaded rowid range
HIGHROWID	ROWID	NOT NULL	End ROWID in the loaded rowid range
SEQUENCE	NUMBER		Sequence number of the direct load
XID	NUMBER		Transaction ID

ALL_SYNC_CAPTURE

ALL_SYNC_CAPTURE displays information about the synchronous capture processes that store the captured changes in queues accessible to the current user.

Related View

DBA_SYNC_CAPTURE displays information about all synchronous capture processes in the database.

Column	Datatype	NULL	Description
CAPTURE_NAME	VARCHAR2 (30)	NOT NULL	Name of the capture process
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue used for holding captured changes

Column	Datatype	NULL	Description
QUEUE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the queue used for holding captured changes
RULE_SET_NAME	VARCHAR2 (30)		Rule set used by the capture process
RULE_SET_OWNER	VARCHAR2 (30)		Owner of the rule set
CAPTURE_USER	VARCHAR2 (30)		Current user who is enqueueing captured messages

See Also: ["DBA_SYNC_CAPTURE"](#) on page 6-16

ALL_SYNC_CAPTURE_PREPARED_TABS

ALL_SYNC_CAPTURE_PREPARED_TABS displays information about the tables accessible to the current user that are prepared for synchronous capture instantiation.

Related View

DBA_SYNC_CAPTURE_PREPARED_TABS displays information about all tables in the database that are prepared for synchronous capture instantiation.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table prepared for synchronous capture instantiation
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table prepared for synchronous capture instantiation
SCN	NUMBER	NOT NULL	SCN from which changes can be captured
TIMESTAMP	DATE		Time at which the table was ready to be instantiated

See Also: ["DBA_SYNC_CAPTURE_PREPARED_TABS"](#) on page 6-16

ALL_SYNC_CAPTURE_TABLES

ALL_SYNC_CAPTURE_TABLES displays information about the tables accessible to the current user that are captured by synchronous Streams captures.

Related View

DBA_SYNC_CAPTURE_TABLES displays information about all tables in the database that are captured by synchronous Streams captures.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2 (30)		Owner of the synchronous capture table
TABLE_NAME	VARCHAR2 (30)		Name of the synchronous capture table
ENABLED	VARCHAR2 (3)		Indicates whether synchronous Streams capture is enabled for the table (YES) or not (NO)

See Also: ["DBA_SYNC_CAPTURE_TABLES"](#) on page 6-16

ALL_SYNONYMS

ALL_SYNONYMS describes the synonyms accessible to the current user. The following criteria determine the list of synonyms that ALL_SYNONYMS shows:

- All private synonyms owned by the logged-in user, even if the base object pointed to is not accessible.
- All public synonyms, even if the base object pointed to is not accessible.
- All private synonyms owned by a different user, where the ultimate base object pointed to by that synonym or by any chain of nested synonyms, is known to be accessible because of a grant to the logged-in user, or a grant to a role in effect for this session.
- If the current session has any of the following privileges, then all synonyms that point directly to local objects are shown because it is assumed that the session can access those objects:
 - LOCK ANY TABLE
 - SELECT ANY TABLE
 - INSERT ANY TABLE
 - UPDATE ANY TABLE
 - DELETE ANY TABLE

Synonyms that point to remote objects are excluded because the system privileges just listed do not automatically convey access to those remote objects. Also, if the synonyms point to objects other than tables and views (such as sequences, PL/SQL procedures, and so on) then this rule may show synonyms that ultimately resolve to objects that this session cannot access.

- All private synonyms owned by a different user, where the synonym is via a database link, are excluded.

Related Views

- `DBA_SYNONYMS` describes all synonyms in the database.
- `USER_SYNONYMS` describes the synonyms owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the synonym
SYNONYM_NAME	VARCHAR2 (30)		Name of the synonym
TABLE_OWNER	VARCHAR2 (30)		Owner of the object referenced by the synonym, or creator of the referring synonym if the target is a public synonym (that is, the object referred to by <code>TABLE_NAME</code>). Although the column is called <code>TABLE_OWNER</code> , the object owned is not necessarily a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on.
TABLE_NAME	VARCHAR2 (30)		Name of the object referenced by the synonym. Although the column is called <code>TABLE_NAME</code> , the object does not necessarily have to be a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on.
DB_LINK	VARCHAR2 (128)		Name of the database link referenced, if any

See Also:

- ["DBA_SYNONYMS"](#) on page 6-16
- ["USER_SYNONYMS"](#) on page 6-102

ALL_TAB_COL_STATISTICS

ALL_TAB_COL_STATISTICS displays column statistics and histogram information extracted from "ALL_TAB_COLUMNS" on page 3-79.

Related Views

- DBA_TAB_COL_STATISTICS displays such information extracted from "DBA_TAB_COLUMNS" on page 6-17.
- USER_TAB_COL_STATISTICS displays such information extracted from "USER_TAB_COLUMNS" on page 6-103. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table
COLUMN_NAME	VARCHAR2 (30)		Column name
NUM_DISTINCT	NUMBER		Number of distinct values in the column
LOW_VALUE	RAW (32)		Low value in the column
HIGH_VALUE	RAW (32)		High value in the column
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in histogram for the column
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
GLOBAL_STATS	VARCHAR2 (3)		For partitioned tables, indicates whether column statistics were collected for the table as a whole (YES) or were estimated from statistics on underlying partitions and subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
HISTOGRAM	VARCHAR2 (15)		Indicates existence/type of histogram: ■ NONE ■ FREQUENCY ■ HEIGHT BALANCED

ALL_TAB_COLS

ALL_TAB_COLS describes the columns of the tables, views, and clusters accessible to the current user. To gather statistics for this view, use the ANALYZE SQL statement or the DBMS_STATS package.

This view differs from "ALL_TAB_COLUMNS" on page 3-79 in that hidden columns are not filtered out.

Related Views

- DBA_TAB_COLS describes the columns of all tables, views, and clusters in the database.
- USER_TAB_COLS describes the columns of the tables, views, and clusters owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table, view, or cluster
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table, view, or cluster
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Column name
DATA_TYPE	VARCHAR2 (106)		Datatype of the column
DATA_TYPE_MOD	VARCHAR2 (3)		Datatype modifier of the column
DATA_TYPE_OWNER	VARCHAR2 (30)		Owner of the datatype of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER datatype; binary precision for FLOAT datatype; NULL for all other datatypes
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
NULLABLE	VARCHAR2 (1)		Indicates whether a column allows NULLs. The value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY.
COLUMN_ID	NUMBER		Sequence number of the column as created
DEFAULT_LENGTH	NUMBER		Length of the default value for the column
DATA_DEFAULT	LONG		Default value for the column
NUM_DISTINCT	NUMBER		Number of distinct values in the column ¹
LOW_VALUE	RAW (32)		Low value in the column ¹
HIGH_VALUE	RAW (32)		High value in the column ¹
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.¹
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in the histogram for the column Note: The number of buckets in a histogram is specified in the SIZE parameter of the ANALYZE SQL statement. However, Oracle Database does not create a histogram with more buckets than the number of rows in the sample. Also, if the sample contains any values that are very repetitious, Oracle Database creates the specified number of buckets, but the value indicated by this column may be smaller because of an internal compression algorithm.
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
CHARACTER_SET_NAME	VARCHAR2 (44)		Name of the character set: ■ CHAR_CS ■ NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column

Column	Datatype	NULL	Description
GLOBAL_STATS	VARCHAR2 (3)		For partitioned tables, indicates whether column statistics were collected for the table as a whole (YES) or were estimated from statistics on underlying partitions and subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
CHAR_LENGTH	NUMBER		Displays the length of the column in characters. This value only applies to the following datatypes: - CHAR - VARCHAR2 - NCHAR - NVARCHAR
CHAR_USED	VARCHAR2 (1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the datatype is not any of the following (NULL): - CHAR - VARCHAR2 - NCHAR - NVARCHAR2
V80_FMT_IMAGE	VARCHAR2 (3)		Indicates whether the column data is in release 8.0 image format (YES) or not (NO)
DATA_UPGRADED	VARCHAR2 (3)		Indicates whether the column data has been upgraded to the latest type version format (YES) or not (NO)
HIDDEN_COLUMN	VARCHAR2 (3)		Indicates whether the column is a hidden column (YES) or not (NO)
VIRTUAL_COLUMN	VARCHAR2 (3)		Indicates whether the column is a virtual column (YES) or not (NO)
SEGMENT_COLUMN_ID	NUMBER		Sequence number of the column in the segment
INTERNAL_COLUMN_ID	NUMBER	NOT NULL	Internal sequence number of the column
HISTOGRAM	VARCHAR2 (15)		Indicates existence/type of histogram: - NONE - FREQUENCY - HEIGHT BALANCED
QUALIFIED_COL_NAME	VARCHAR2 (4000)		Qualified column name

¹ These columns remain for backward compatibility with Oracle7. This information is now in the {TAB | PART}_COL_STATISTICS views.

ALL_TAB_COLUMNS

ALL_TAB_COLUMNS describes the columns of the tables, views, and clusters accessible to the current user. To gather statistics for this view, use the ANALYZE SQL statement or the DBMS_STATS package.

Related Views

- DBA_TAB_COLUMNS describes the columns of all tables, views, and clusters in the database.
- USER_TAB_COLUMNS describes the columns of the tables, views, and clusters owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table, view, or cluster
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table, view, or cluster
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Column name
DATA_TYPE	VARCHAR2 (106)		Datatype of the column
DATA_TYPE_MOD	VARCHAR2 (3)		Datatype modifier of the column
DATA_TYPE_OWNER	VARCHAR2 (30)		Owner of the datatype of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER datatype; binary precision for FLOAT datatype; NULL for all other datatypes
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
NULLABLE	VARCHAR2 (1)		Indicates whether a column allows NULLs. The value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY. The constraint should be in an ENABLE VALIDATE state.
COLUMN_ID	NUMBER		Sequence number of the column as created
DEFAULT_LENGTH	NUMBER		Length of the default value for the column
DATA_DEFAULT	LONG		Default value for the column
NUM_DISTINCT	NUMBER		Number of distinct values in the column ¹
LOW_VALUE	RAW (32)		Low value in the column ¹
HIGH_VALUE	RAW (32)		High value in the column ¹
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT. ¹
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in the histogram for the column Note: The number of buckets in a histogram is specified in the SIZE parameter of the ANALYZE SQL statement. However, Oracle Database does not create a histogram with more buckets than the number of rows in the sample. Also, if the sample contains any values that are very repetitious, Oracle Database creates the specified number of buckets, but the value indicated by this column may be smaller because of an internal compression algorithm.
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
CHARACTER_SET_NAME	VARCHAR2 (44)		Name of the character set: ■ CHAR_CS ■ NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
GLOBAL_STATS	VARCHAR2 (3)		For partitioned tables, indicates whether column statistics were collected for the table as a whole (YES) or were estimated from statistics on underlying partitions and subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)

Column	Datatype	NULL	Description
CHAR_LENGTH	NUMBER		Displays the length of the column in characters. This value only applies to the following datatypes: - CHAR - VARCHAR2 - NCHAR - NVARCHAR
CHAR_USED	VARCHAR2 (1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the datatype is not any of the following (NULL): - CHAR - VARCHAR2 - NCHAR - NVARCHAR2
V80_FMT_IMAGE	VARCHAR2 (3)		Indicates whether the column data is in release 8.0 image format (YES) or not (NO)
DATA_UPGRADED	VARCHAR2 (3)		Indicates whether the column data has been upgraded to the latest type version format (YES) or not (NO)
HISTOGRAM	VARCHAR2 (15)		Indicates existence/type of histogram: - NONE - FREQUENCY - HEIGHT BALANCED

¹ These columns remain for backward compatibility with Oracle7. This information is now in the {TAB | PART}_COL_STATISTICS views.

ALL_TAB_COMMENTS

ALL_TAB_COMMENTS displays comments on the tables and views accessible to the current user.

Related Views

- DBA_TAB_COMMENTS displays comments on all tables and views in the database.
- USER_TAB_COMMENTS displays comments on the tables and views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
TABLE_TYPE	VARCHAR2 (11)		Type of the object
COMMENTS	VARCHAR2 (4000)		Comment on the object

See Also:

- ["DBA_TAB_COMMENTS"](#) on page 6-17
- ["USER_TAB_COMMENTS"](#) on page 6-103

ALL_TAB_HISTGRM_PENDING_STATS

ALL_TAB_HISTGRM_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions accessible to the current user.

Related Views

- `DBA_TAB_HISTGRM_PENDING_STATS` describes pending statistics for tables, partitions, and subpartitions in the database.
- `USER_TAB_HISTGRM_PENDING_STATS` describes pending statistics for tables, partitions, and subpartitions owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2(30)</code>		Owner of the table
<code>TABLE_NAME</code>	<code>VARCHAR2(30)</code>		Name of the table
<code>PARTITION_NAME</code>	<code>VARCHAR2(30)</code>		Name of the partition
<code>SUBPARTITION_NAME</code>	<code>VARCHAR2(30)</code>		Name of the subpartition
<code>COLUMN_NAME</code>	<code>VARCHAR2(30)</code>		Name of the column
<code>ENDPOINT_NUMBER</code>	<code>NUMBER</code>		Endpoint number
<code>ENDPOINT_VALUE</code>	<code>NUMBER</code>		Normalized endpoint value
<code>ENDPOINT_ACTUAL_VALUE</code>	<code>VARCHAR2(1000)</code>		Actual endpoint value

ALL_TAB_HISTOGRAMS

`ALL_TAB_HISTOGRAMS` describes histograms on tables and views accessible to the current user.

Related Views

- `DBA_TAB_HISTOGRAMS` describes histograms on all tables and views in the database.
- `USER_TAB_HISTOGRAMS` describes histograms on all tables and views owned by the current user. This view does not display the `OWNER` column.

Note: These views are populated only if you collect statistics on the index using the `ANALYZE` statement or the `DBMS_STATS` package.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2(30)</code>		Owner of the table
<code>TABLE_NAME</code>	<code>VARCHAR2(30)</code>		Name of the table
<code>COLUMN_NAME</code>	<code>VARCHAR2(4000)</code>		Column name or attribute of the object type column
<code>ENDPOINT_NUMBER</code>	<code>NUMBER</code>		Histogram bucket number
<code>ENDPOINT_VALUE</code>	<code>NUMBER</code>		Normalized endpoint value for this bucket
<code>ENDPOINT_ACTUAL_VALUE</code>	<code>VARCHAR2(1000)</code>		Actual (not normalized) string value of the endpoint for this bucket

ALL_TAB_MODIFICATIONS

`ALL_TAB_MODIFICATIONS` describes tables accessible to the current user that have been modified since the last time statistics were gathered on the tables.

Related Views

- `DBA_TAB_MODIFICATIONS` describes such information for all tables in the database.
- `USER_TAB_MODIFICATIONS` describes such information for tables owned by the current user. This view does not display the `TABLE_OWNER` column.

Note: These views are populated only for tables with the `MONITORING` attribute. They are intended for statistics collection over a long period of time. For performance reasons, the Oracle Database does not populate these views immediately when the actual modifications occur. Run the `FLUSH_DATABASE_MONITORING_INFO` procedure in the `DBMS_STATS` PL/SQL package to populate these views with the latest information. The `ANALYZE_ANY` system privilege is required to run this procedure.

Column	Datatype	NULL	Description
<code>TABLE_OWNER</code>	<code>VARCHAR2 (30)</code>		Owner of the modified table
<code>TABLE_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the modified table
<code>PARTITION_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the modified partition
<code>SUBPARTITION_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the modified subpartition
<code>INSERTS</code>	<code>NUMBER</code>		Approximate number of inserts since the last time statistics were gathered
<code>UPDATES</code>	<code>NUMBER</code>		Approximate number of updates since the last time statistics were gathered
<code>DELETES</code>	<code>NUMBER</code>		Approximate number of deletes since the last time statistics were gathered
<code>TIMESTAMP</code>	<code>DATE</code>		Indicates the last time the table was modified
<code>TRUNCATED</code>	<code>VARCHAR2 (3)</code>		Indicates whether the table has been truncated since the last analyze (YES) or not (NO)
<code>DROP_SEGMENTS</code>	<code>NUMBER</code>		Number of partition and subpartition segments dropped since the last analyze

ALL_TAB_PARTITIONS

`ALL_TAB_PARTITIONS` displays partition-level partitioning information, partition storage parameters, and partition statistics generated by the `DBMS_STATS` package or the `ANALYZE` statement for the partitions accessible to the current user.

Related Views

- `DBA_TAB_PARTITIONS` displays such information for all partitions in the database.
- `USER_TAB_PARTITIONS` displays such information for the partitions of all partitioned objects owned by the current user. This view does not display the `TABLE_OWNER` column.

Note: Columns marked with an asterisk (*) are populated only if you collect statistics on the table with the `ANALYZE` statement or the `DBMS_STATS` package.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table
COMPOSITE	VARCHAR2 (3)		Indicates whether the table is composite-partitioned (YES) or not (NO)
PARTITION_NAME	VARCHAR2 (30)		Name of the partition
SUBPARTITION_COUNT	NUMBER		If this is a Local index on a table partitioned using a Composite method, the number of subpartitions in the partition
HIGH_VALUE	LONG		Partition bound value expression
HIGH_VALUE_LENGTH	NUMBER		Length of the partition bound value expression
PARTITION_POSITION	NUMBER		Position of the partition within the table
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the partition
PCT_FREE	NUMBER		Minimum percentage of free space in a block
PCT_USED	NUMBER		Minimum percentage of used space in a block
INI_TRANS	NUMBER		Initial number of transactions
MAX_TRANS	NUMBER		Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes (for a range partition); size of the initial extent in blocks (for a composite partition)
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes (for a range partition); size of secondary extents in blocks (for a composite partition)
MIN_EXTENT	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENT	NUMBER		Maximum number of extents allowed in the segment
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment
PCT_INCREASE	NUMBER		Percentage increase in extent size
FREELISTS	NUMBER		Number of process freelists allocated in this segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated in this segment
LOGGING	VARCHAR2 (7)		Indicates whether or not changes to the table are logged: ■ NONE - Not specified See Also: the *_TAB_SUBPARTITIONS view ■ YES ■ NO
COMPRESSION	VARCHAR2 (8)		Indicates whether compression is enabled or disabled for this partition: ■ NONE - Not specified See Also: the *_TAB_SUBPARTITIONS view ■ ENABLED ■ DISABLED
COMPRESS_FOR	VARCHAR2 (12)		Default compression for what kind of operations: ■ BASIC ■ OLTP ■ QUERY LOW¹ ■ QUERY HIGH¹ ■ ARCHIVE LOW¹ ■ ARCHIVE HIGH¹ ■ NULL

Column	Datatype	NULL	Description
NUM_ROWS*	NUMBER		Number of rows in the partition
BLOCKS*	NUMBER		Number of used data blocks in the partition
EMPTY_BLOCKS	NUMBER		Number of empty (never used) data blocks in the partition. This column is populated only if you collect statistics on the table using the ANALYZE statement.
AVG_SPACE*	NUMBER		Average amount of free space, in bytes, in a data block allocated to the partition
CHAIN_CNT*	NUMBER		Number of rows in the partition that are chained from one data block to another, or which have migrated to a new block, requiring a link to preserve the old ROWID
AVG_ROW_LEN*	NUMBER		Average length of a row in the partition (in bytes)
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this partition
LAST_ANALYZED	DATE		Date on which this partition was most recently analyzed
BUFFER_POOL	VARCHAR2 (7)		Buffer pool to be used for the partition blocks: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for partition blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for partition blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
GLOBAL_STATS	VARCHAR2 (3)		Indicates whether statistics were collected for the partition as a whole (YES) or were estimated from statistics on underlying subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
IS_NESTED	VARCHAR2 (3)		Indicates whether this is a nested table partition (YES) or not (NO) See Also: the *_NESTED_TABLES view for the parent table name/column
PARENT_TABLE_PARTITION	VARCHAR2 (30)		Parent table's corresponding partition See Also: the *_NESTED_TABLES view for the parent table name/column
INTERVAL	VARCHAR2 (3)		Indicates whether the partition is in the interval section of an interval partitioned table (YES) or whether the partition is in the range section (NO)
SEGMENT_CREATED	VARCHAR2 (4)		Indicates whether the table partition segment has been created (YES) or not (NO); N/A indicates that this table is subpartitioned and no segment exists at the partition level

¹ Hybrid columnar compression is a feature of Oracle Exadata. See Oracle Exadata Storage Server Software documentation for more information.

ALL_TAB_PENDING_STATS

ALL_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions accessible to the current user.

Related Views

- DBA_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions in the database.
- USER_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table
PARTITION_NAME	VARCHAR2 (30)		Name of the partition
SUBPARTITION_NAME	VARCHAR2 (30)		Name of the subpartition
NUM_ROWS	NUMBER		Number of rows
BLOCKS	NUMBER		Number of blocks
AVG_ROW_LEN	NUMBER		Average row length
SAMPLE_SIZE	NUMBER		Sample size
LAST_ANALYZED	DATE		Time of last analyze operation

ALL_TAB_PRIVS

ALL_TAB_PRIVS describes the following types of grants:

- Object grants for which the current user is the object owner, grantor, or grantee
- Object grants for which an enabled role or PUBLIC is the grantee

Related Views

- DBA_TAB_PRIVS describes all object grants in the database.
- USER_TAB_PRIVS describes the object grants for which the current user is the object owner, grantor, or grantee.

Column	Datatype	NULL	Description
GRANTOR	VARCHAR2 (30)	NOT NULL	Name of the user who performed the grant
GRANTEE	VARCHAR2 (30)	NOT NULL	Name of the user or role to whom access was granted
TABLE_SCHEMA	VARCHAR2 (30)	NOT NULL	Schema of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Privilege on the object
GRANTABLE	VARCHAR2 (3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
HIERARCHY	VARCHAR2 (3)		Indicates whether the privilege was granted with the HIERARCHY OPTION (YES) or not (NO)

See Also:

- ["DBA_TAB_PRIVS"](#) on page 6-18
- ["USER_TAB_PRIVS"](#) on page 6-104

ALL_TAB_PRIVS_MADE

ALL_TAB_PRIVS_MADE describes the object grants for which the current user is the object owner or grantor.

Related View

USER_TAB_PRIVS_MADE describes the object grants for which the current user is the object owner. This view does not display the OWNER column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	Name of the user or role to whom access was granted
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
GRANTOR	VARCHAR2 (30)	NOT NULL	Name of the user who performed the grant
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Privilege on the object
GRANTABLE	VARCHAR2 (3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
HIERARCHY	VARCHAR2 (3)		Indicates whether the privilege was granted with the HIERARCHY OPTION (YES) or not (NO)

See Also: ["USER_TAB_PRIVS_MADE"](#) on page 6-104

ALL_TAB_PRIVS_RECD

ALL_TAB_PRIVS_RECD describes the following types of grants:

- Object grants for which the current user is the grantee
- Object grants for which an enabled role or PUBLIC is the grantee

Related View

USER_TAB_PRIVS_RECD describes the object grants for which the current user is the grantee. This view does not display the GRANTEE column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	Name of the user or role to whom access was granted
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
GRANTOR	VARCHAR2 (30)	NOT NULL	Name of the user who performed the grant
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Privilege on the object
GRANTABLE	VARCHAR2 (3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
HIERARCHY	VARCHAR2 (3)		Indicates whether the privilege was granted with the HIERARCHY OPTION (YES) or not (NO)

See Also: ["USER_TAB_PRIVS_RECD"](#) on page 6-104

ALL_TAB_STAT_PREFS

ALL_TAB_STAT_PREFS displays information about statistics preferences for the tables accessible to the current user.

Related Views

- DBA_TAB_STAT_PREFS displays information about statistics preferences for all tables in the database.
- USER_TAB_STAT_PREFS displays information about statistics preferences for the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
PREFERENCE_NAME	VARCHAR2 (30)	NOT NULL	Name of the preference
PREFERENCE_VALUE	VARCHAR2 (1000)		Value of the preference

ALL_TAB_STATISTICS

ALL_TAB_STATISTICS displays optimizer statistics for the tables accessible to the current user.

Related Views

- DBA_TAB_STATISTICS displays optimizer statistics for all tables in the database.
- USER_TAB_STATISTICS displays optimizer statistics for the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the object
TABLE_NAME	VARCHAR2 (30)		Name of the table
PARTITION_NAME	VARCHAR2 (30)		Name of the partition
PARTITION_POSITION	NUMBER		Position of the partition within the table
SUBPARTITION_NAME	VARCHAR2 (30)		Name of the subpartition
SUBPARTITION_POSITION	NUMBER		Position of the subpartition within the partition
OBJECT_TYPE	VARCHAR2 (12)		Type of the object: ■ TABLE ■ PARTITION ■ SUBPARTITION
NUM_ROWS	NUMBER		Number of rows in the object
BLOCKS	NUMBER		Number of used blocks in the object
EMPTY_BLOCKS	NUMBER		Number of empty blocks in the object
AVG_SPACE	NUMBER		Average available free space in the object
CHAIN_CNT	NUMBER		Number of chained rows in the object
AVG_ROW_LEN	NUMBER		Average row length, including row overhead
AVG_SPACE_FREELIST_BLOCKS	NUMBER		Average freespace of all blocks on a freelist
NUM_FREELIST_BLOCKS	NUMBER		Number of blocks on the freelist
AVG_CACHED_BLOCKS	NUMBER		Average number of blocks in the buffer cache

Column	Datatype	NULL	Description
AVG_CACHE_HIT_RATIO	NUMBER		Average cache hit ratio for the object
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the table
LAST_ANALYZED	DATE		Date of the most recent time the table was analyzed
GLOBAL_STATS	VARCHAR2 (3)		Indicates whether statistics were calculated without merging underlying partitions (YES) or not (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
STATTYPE_LOCKED	VARCHAR2 (5)		Type of statistics lock: - DATA - CACHE - ALL
STALE_STATS	VARCHAR2 (3)		Indicates whether statistics for the object are stale (YES) or not (NO)

See Also:

- ["DBA_TAB_STATISTICS"](#) on page 6-18
- ["USER_TAB_STATISTICS"](#) on page 6-104

ALL_TAB_STATS_HISTORY

ALL_TAB_STATS_HISTORY provides a history of table statistics modifications for all tables accessible to the current user.

Related Views

- DBA_TAB_STATS_HISTORY provides a history of table statistics modifications for all tables in the database.
- USER_TAB_STATS_HISTORY provides a history of table statistics modifications for all tables owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the object
TABLE_NAME	VARCHAR2 (30)		Name of the table
PARTITION_NAME	VARCHAR2 (30)		Name of the partition
SUBPARTITION_NAME	VARCHAR2 (30)		Name of the subpartition
STATS_UPDATE_TIME	TIMESTAMP (6) WITH TIME ZONE		Time at which the statistics were updated

See Also:

- ["DBA_TAB_STATS_HISTORY"](#) on page 6-19
- ["USER_TAB_STATS_HISTORY"](#) on page 6-104

ALL_TAB_SUBPARTITIONS

ALL_TAB_SUBPARTITIONS displays, for each table subpartition accessible to the current user, the subpartition name, name of the table and partition to which it belongs, and its storage attributes.

Related Views

- DBA_TAB_SUBPARTITIONS displays such information for all subpartitions in the database.
- USER_TAB_SUBPARTITIONS displays such information for subpartitions of all partitioned objects owned by the current user. This view does not display the TABLE_OWNER column.

Note: Statistics are not collected on a per-subpartition basis.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
PARTITION_NAME	VARCHAR2 (30)		Name of the partition
SUBPARTITION_NAME	VARCHAR2 (30)		Name of the subpartition
HIGH_VALUE	LONG		Subpartition bound value expression
HIGH_VALUE_LENGTH	NUMBER	NOT NULL	Length of the subpartition bound value expression
SUBPARTITION_POSITION	NUMBER		Position of the subpartition within the partition
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace containing the subpartition
PCT_FREE	NUMBER	NOT NULL	Minimum percentage of free space in a block
PCT_USED	NUMBER		Minimum percentage of used space in a block
INI_TRANS	NUMBER	NOT NULL	Initial number of transactions
MAX_TRANS	NUMBER	NOT NULL	Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes (for a range partition); size of the initial extent in blocks (for a composite partition)
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes (for a range partition); size of secondary extents in blocks (for a composite partition)
MIN_EXTENT	NUMBER	NOT NULL	Minimum number of extents allowed in the segment
MAX_EXTENT	NUMBER	NOT NULL	Maximum number of extents allowed in the segment
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment
PCT_INCREASE	NUMBER		Percentage increase in extent size
FREELISTS	NUMBER		Number of freelist groups allocated in this segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated in this segment
LOGGING	VARCHAR2 (3)		Indicates whether or not changes to the table are logged: ■ YES ■ NO
COMPRESSION	VARCHAR2 (8)		Indicates whether this subpartition is compressed (ENABLED) or not (DISABLED)
COMPRESS_FOR	VARCHAR2 (12)		Default compression for what kind of operations: ■ BASIC ■ OLTP ■ QUERY LOW¹ ■ QUERY HIGH¹ ■ ARCHIVE LOW¹ ■ ARCHIVE HIGH¹ ■ NULL

Column	Datatype	NULL	Description
NUM_ROWS	NUMBER		Number of rows in the subpartition
BLOCKS	NUMBER		Number of blocks in the subpartition
EMPTY_BLOCKS	NUMBER		Number of empty blocks in the subpartition
AVG_SPACE	NUMBER		Average space in the subpartition
CHAIN_CNT	NUMBER		Chain count
AVG_ROW_LEN	NUMBER		Average row length
SAMPLE_SIZE	NUMBER		Sample size
LAST_ANALYZED	DATE		Date on which this table was most recently analyzed
BUFFER_POOL	VARCHAR2 (7)		Buffer pool for this subpartition: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for subpartition blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for subpartition blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
GLOBAL_STATS	VARCHAR2 (3)		Indicates whether column statistics for the subpartition were collected by analyzing the table as a whole (YES) or estimated from statistics collected for partitions and subpartitions (NO)
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
INTERVAL	VARCHAR2 (3)		Indicates whether the partition is in the interval section of an interval partitioned table (YES) or whether the partition is in the range section (NO)
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the table subpartition segment has been created (YES) or not (NO); N/A indicates that this table is not subpartitioned

¹ Hybrid columnar compression is a feature of Oracle Exadata. See Oracle Exadata Storage Server Software documentation for more information.

ALL_TABLES

ALL_TABLES describes the relational tables accessible to the current user. To gather statistics for this view, use the ANALYZE SQL statement.

Related Views

- DBA_TABLES describes all relational tables in the database.
- USER_TABLES describes the relational tables owned by the current user. This view does not display the OWNER column.

Note: Columns marked with an asterisk (*) are populated only if you collect statistics on the table with the `ANALYZE` statement or the `DBMS_STATS` package.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the table; NULL for partitioned, temporary, and index-organized tables
CLUSTER_NAME	VARCHAR2 (30)		Name of the cluster, if any, to which the table belongs
IOT_NAME	VARCHAR2 (30)		Name of the index-organized table, if any, to which the overflow or mapping table entry belongs. If the <code>IOT_TYPE</code> column is not NULL, then this column contains the base table name.
STATUS	VARCHAR2 (8)		If a previous <code>DROP TABLE</code> operation failed, indicates whether the table is unusable (UNUSABLE) or valid (VALID)
PCT_FREE	NUMBER		Minimum percentage of free space in a block; NULL for partitioned tables
PCT_USED	NUMBER		Minimum percentage of used space in a block; NULL for partitioned tables
INI_TRANS	NUMBER		Initial number of transactions; NULL for partitioned tables
MAX_TRANS	NUMBER		Maximum number of transactions; NULL for partitioned tables
INITIAL_EXTENT	NUMBER		Size of the initial extent (in bytes); NULL for partitioned tables
NEXT_EXTENT	NUMBER		Size of secondary extents (in bytes); NULL for partitioned tables
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment; NULL for partitioned tables
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment; NULL for partitioned tables
PCT_INCREASE	NUMBER		Percentage increase in extent size; NULL for partitioned tables
FREELISTS	NUMBER		Number of process freelists allocated to the segment; NULL for partitioned tables
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to the segment; NULL for partitioned tables
LOGGING	VARCHAR2 (3)		Indicates whether or not changes to the table are logged; NULL for partitioned tables: ■ YES ■ NO
BACKED_UP	VARCHAR2 (1)		Indicates whether the table has been backed up since the last modification (Y) or not (N)
NUM_ROWS*	NUMBER		Number of rows in the table
BLOCKS*	NUMBER		Number of used data blocks in the table
EMPTY_BLOCKS	NUMBER		Number of empty (never used) data blocks in the table. This column is populated only if you collect statistics on the table using the <code>ANALYZE</code> statement.
AVG_SPACE*	NUMBER		Average amount of free space, in bytes, in a data block allocated to the table

Column	Datatype	NULL	Description
CHAIN_CNT*	NUMBER		Number of rows in the table that are chained from one data block to another, or which have migrated to a new block, requiring a link to preserve the old ROWID
AVG_ROW_LEN*	NUMBER		Average length of a row in the table (in bytes)
AVG_SPACE_FREELIST_BLOCKS	NUMBER		Average freespace of all blocks on a freelist
NUM_FREELIST_BLOCKS	NUMBER		Number of blocks on the freelist
DEGREE	VARCHAR2 (10)		Number of threads per instance for scanning the table, or DEFAULT
INSTANCES	VARCHAR2 (10)		Number of instances across which the table is to be scanned, or DEFAULT
CACHE	VARCHAR2 (5)		Indicates whether the table is to be cached in the buffer cache (Y) or not (N)
TABLE_LOCK	VARCHAR2 (8)		Indicates whether table locking is enabled (ENABLED) or disabled (DISABLED)
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this table
LAST_ANALYZED	DATE		Date on which this table was most recently analyzed
PARTITIONED	VARCHAR2 (3)		Indicates whether the table is partitioned (YES) or not (NO)
IOT_TYPE	VARCHAR2 (12)		If the table is an index-organized table, then IOT_TYPE is IOT, IOT_OVERFLOW, or IOT_MAPPING. If the table is not an index-organized table, then IOT_TYPE is NULL.
TEMPORARY	VARCHAR2 (1)		Indicates whether the table is temporary (Y) or not (N)
SECONDARY	VARCHAR2 (1)		Indicates whether the table is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)
NESTED	VARCHAR2 (3)		Indicates whether the table is a nested table (YES) or not (NO)
BUFFER_POOL	VARCHAR2 (7)		Buffer pool for the table; NULL for partitioned tables: ■ DEFAULT ■ KEEP ■ RECYCLE ■ NULL
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for table blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for table blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information
ROW_MOVEMENT	VARCHAR2 (8)		Indicates whether partitioned row movement is enabled (ENABLED) or disabled (DISABLED)
GLOBAL_STATS	VARCHAR2 (3)		For partitioned tables, indicates whether statistics for the table as a whole (global statistics) are accurate (YES) or whether they were not collected and have to be estimated from statistics on underlying partitions and subpartitions (NO)

Column	Datatype	NULL	Description
USER_STATS	VARCHAR2 (3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
DURATION	VARCHAR2 (15)		Indicates the duration of a temporary table: ■ SYS\$SESSION - Rows are preserved for the duration of the session ■ SYS\$TRANSACTION - Rows are deleted after COMMIT Null - Permanent table
SKIP_CORRUPT	VARCHAR2 (8)		Indicates whether Oracle Database ignores blocks marked corrupt during table and index scans (ENABLED) or raises an error (DISABLED). To enable this feature, run the DBMS_REPAIR.SKIP_CORRUPT_BLOCKS procedure.
MONITORING	VARCHAR2 (3)		Indicates whether the table has the MONITORING attribute set (YES) or not (NO)
CLUSTER_OWNER	VARCHAR2 (30)		Owner of the cluster, if any, to which the table belongs
DEPENDENCIES	VARCHAR2 (8)		Indicates whether row-level dependency tracking is enabled (ENABLED) or disabled (DISABLED)
COMPRESSION	VARCHAR2 (8)		Indicates whether table compression is enabled (ENABLED) or not (DISABLED); NULL for partitioned tables
COMPRESS_FOR	VARCHAR2 (12)		Default compression for what kind of operations: ■ BASIC ■ OLTP ■ QUERY LOW¹ ■ QUERY HIGH¹ ■ ARCHIVE LOW¹ ■ ARCHIVE HIGH¹ ■ NULL
DROPPED	VARCHAR2 (3)		Indicates whether the table has been dropped and is in the recycle bin (YES) or not (NO); NULL for partitioned tables
READ_ONLY	VARCHAR2 (3)		Indicates whether the table IS READ-ONLY (YES) or not (NO)
SEGMENT_CREATED	VARCHAR2 (3)		Indicates whether the table segment is created (YES) or not (NO)
RESULT_CACHE	VARCHAR2 (7)		Result cache mode annotation for the table: ■ DEFAULT - Table has not been annotated ■ FORCE ■ MANUAL

¹ Hybrid columnar compression is a feature of Oracle Exadata. See Oracle Exadata Storage Server Software documentation for more information.

See Also:

- ["DBA_TABLES"](#) on page 6-19
- ["USER_TABLES"](#) on page 6-105

ALL_TRIGGER_COLS

ALL_TRIGGER_COLS describes the use of columns in the triggers accessible to the current user and in triggers on tables accessible to the current user. If the user has the

CREATE ANY TRIGGER privilege, then this view describes the use of columns in all triggers in the database.

Related Views

- DBA_TRIGGER_COLS describes the use of columns in all triggers in the database.
- USER_TRIGGER_COLS describes the use of columns in the triggers owned by the current user and in triggers on tables owned by the current user.

Column	Datatype	NULL	Description
TRIGGER_OWNER	VARCHAR2 (30)		Owner of the trigger
TRIGGER_NAME	VARCHAR2 (30)		Name of the trigger
TABLE_OWNER	VARCHAR2 (30)		Owner of the table on which the trigger is defined
TABLE_NAME	VARCHAR2 (30)		Table on which the trigger is defined
COLUMN_NAME	VARCHAR2 (4000)		Name of the column used in the trigger
COLUMN_LIST	VARCHAR2 (3)		Indicates whether the column is specified in the UPDATE clause (YES) or not (NO)
COLUMN_USAGE	VARCHAR2 (17)		How the column is used in the trigger: ■ NEW IN ■ OLD IN ■ NEW IN OLD IN ■ NEW OUT ■ NEW IN OUT ■ NEW OUT OLD IN ■ NEW IN OUT OLD IN ■ PARENT IN

See Also:

- ["DBA_TRIGGER_COLS"](#) on page 6-24
- ["USER_TRIGGER_COLS"](#) on page 6-105

ALL_TRIGGER_ORDERING

ALL_TRIGGER_ORDERING describes the triggers accessible to the current user that have FOLLOWS or PRECEDES ordering.

Related Views

- DBA_TRIGGER_ORDERING describes all triggers in the database that have FOLLOWS or PRECEDES ordering.
- USER_TRIGGER_ORDERING describes the triggers owned by the current user that have FOLLOWS or PRECEDES ordering. This view does not display the TRIGGER_OWNER column.

Column	Datatype	NULL	Description
TRIGGER_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the trigger
TRIGGER_NAME	VARCHAR2 (30)		Name of the trigger
REFERENCED_TRIGGER_OWNER	VARCHAR2 (30)		Owner of the referenced trigger

Column	Datatype	NULL	Description
REFERENCED_TRIGGER_NAME	VARCHAR2 (30)		Name of the referenced trigger
ORDERING_TYPE	VARCHAR2 (8)		Type of the ordering between the trigger and the referenced trigger: ▪ <code>FOLLOWS</code> ▪ <code>PRECEDES</code>

See Also:

- ["DBA_TRIGGER_ORDERING"](#) on page 6-24
- ["USER_TRIGGER_ORDERING"](#) on page 6-105

ALL_TRIGGERS

`ALL_TRIGGERS` describes the triggers on tables accessible to the current user. If the user has the `CREATE ANY TRIGGER` privilege, then this view describes all triggers in the database.

Related Views

- `DBA_TRIGGERS` describes all triggers in the database.
- `USER_TRIGGERS` describes the triggers owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the trigger
TRIGGER_NAME	VARCHAR2 (30)		Name of the trigger
TRIGGER_TYPE	VARCHAR2 (16)		When the trigger fires: ▪ <code>BEFORE STATEMENT</code> ▪ <code>BEFORE EACH ROW</code> ▪ <code>AFTER STATEMENT</code> ▪ <code>AFTER EACH ROW</code> ▪ <code>INSTEAD OF</code> ▪ <code>COMPOUND</code>
TRIGGERING_EVENT	VARCHAR2 (227)		DML, DDL, or database event that fires the trigger See Also: <i>Oracle Database PL/SQL Language Reference</i> for additional information about triggers and triggering events.
TABLE_OWNER	VARCHAR2 (30)		Owner of the table on which the trigger is defined
BASE_OBJECT_TYPE	VARCHAR2 (16)		Base object on which the trigger is defined: ▪ <code>TABLE</code> ▪ <code>VIEW</code> ▪ <code>SCHEMA</code> ▪ <code>DATABASE</code>
TABLE_NAME	VARCHAR2 (30)		If the base object type of the trigger is <code>SCHEMA</code> or <code>DATABASE</code> , then this column is <code>NULL</code> ; if the base object type of the trigger is <code>TABLE</code> or <code>VIEW</code> , then this column indicates the table or view name on which the trigger is defined
COLUMN_NAME	VARCHAR2 (4000)		Name of the nested table column (if a nested table trigger), else <code>NULL</code>

Column	Datatype	NULL	Description
REFERENCING_NAMES	VARCHAR2 (128)		Names used for referencing OLD and NEW column values from within the trigger
WHEN_CLAUSE	VARCHAR2 (4000)		Must evaluate to TRUE for TRIGGER_BODY to execute
STATUS	VARCHAR2 (8)		Indicates whether the trigger is enabled (ENABLED) or disabled (DISABLED); a disabled trigger will not fire
DESCRIPTION	VARCHAR2 (4000)		Trigger description; useful for re-creating a trigger creation statement
ACTION_TYPE	VARCHAR2 (11)		Action type of the trigger body: - CALL - PL/SQL
TRIGGER_BODY	LONG		Statements executed by the trigger when it fires
CROSSEDITION	VARCHAR2 (7)		Type of crossedition trigger: - FORWARD - REVERSE - NO
BEFORE_STATEMENT	VARCHAR2 (3)		Indicates whether the trigger has a BEFORE STATEMENT section (YES) or not (NO)
BEFORE_ROW	VARCHAR2 (3)		Indicates whether the trigger has a BEFORE EACH ROW section (YES) or not (NO)
AFTER_ROW	VARCHAR2 (3)		Indicates whether the trigger has an AFTER EACH ROW section (YES) or not (NO)
AFTER_STATEMENT	VARCHAR2 (3)		Indicates whether the trigger has an AFTER STATEMENT section (YES) or not (NO)
INSTEAD_OF_ROW	VARCHAR2 (3)		Indicates whether the trigger has an INSTEAD OF section (YES) or not (NO)
FIRE_ONCE	VARCHAR2 (3)		Indicates whether the trigger will fire only in the context of user processes making changes (YES) or whether the trigger will also fire in the context of Streams Apply or SQL Apply processes (NO)
APPLY_SERVER_ONLY	VARCHAR2 (3)		Indicates whether the trigger will only fire in the context of a Streams Apply or SQL Apply process (YES) or not (NO). If set to YES, then the setting of FIRE_ONCE does not matter. See Also: the DBMS_DDL.SET_TRIGGER_FIRING_PROPERTY procedure

See Also:

- ["DBA_TRIGGERS"](#) on page 6-24
- ["USER_TRIGGERS"](#) on page 6-105

ALL_TSTZ_TAB_COLS

ALL_TSTZ_TAB_COLS displays information about the columns of the tables accessible to the current user, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types.

Related Views

- `DBA_TSTZ_TAB_COLS` displays information about the columns of all tables in the database, which have columns defined on `TIMESTAMP WITH TIME ZONE` data

types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types. This view does not display the `NESTED` column.

- `USER_TSTZ_TAB_COLS` displays information about the columns of the tables owned by the current user, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types. This view does not display the `OWNER` or `NESTED` columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
QUALIFIED_COL_NAME	VARCHAR2 (4000)		Qualified column name
NESTED	NUMBER		Indicates whether the column is a nested table (1) or not (0)

See Also:

- ["DBA_TSTZ_TAB_COLS"](#) on page 6-26
- ["USER_TSTZ_TAB_COLS"](#) on page 6-106

ALL_TSTZ_TABLES

`ALL_TSTZ_TABLES` displays information about the tables accessible to the current user, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types.

Related Views

- `DBA_TSTZ_TABLES` displays information about all tables in the database, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types.
- `USER_TSTZ_TABLES` displays information about the tables owned by the current user, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
UPGRADE_IN_PROGRESS	VARCHAR2 (3)		Indicates whether a table upgrade is in progress (YES) or not (NO)

See Also:

- ["DBA_TSTZ_TABLES"](#) on page 6-26
- ["USER_TSTZ_TABLES"](#) on page 6-106

ALL_TYPE_ATTRS

`ALL_TYPE_ATTRS` describes the attributes of the object types accessible to the current user.

Related Views

- `DBA_TYPE_ATTRS` describes the attributes of all object types in the database.
- `USER_TYPE_ATTRS` describes the attributes of the object types owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>		Owner of the type
<code>TYPE_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the type
<code>ATTR_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the attribute
<code>ATTR_TYPE_MOD</code>	<code>VARCHAR2 (7)</code>		Type modifier of the attribute: ■ <code>REF</code> ■ <code>POINTER</code>
<code>ATTR_TYPE_OWNER</code>	<code>VARCHAR2 (30)</code>		Owner of the type of the attribute
<code>ATTR_TYPE_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the type of the attribute
<code>LENGTH</code>	<code>NUMBER</code>		Length of the <code>CHAR</code> attribute, or maximum length of the <code>VARCHAR</code> or <code>VARCHAR2</code> attribute.
<code>PRECISION</code>	<code>NUMBER</code>		Decimal precision of the <code>NUMBER</code> or <code>DECIMAL</code> attribute, or binary precision of the <code>FLOAT</code> attribute.
<code>SCALE</code>	<code>NUMBER</code>		Scale of the <code>NUMBER</code> or <code>DECIMAL</code> attribute
<code>CHARACTER_SET _NAME</code>	<code>VARCHAR2 (44)</code>		Character set name of the attribute (<code>CHAR_CS</code> or <code>NCHAR_CS</code>)
<code>ATTR_NO</code>	<code>NUMBER</code>		Syntactical order number or position of the attribute as specified in the type specification or <code>CREATE TYPE</code> statement (not to be used as an ID number)
<code>INHERITED</code>	<code>VARCHAR2 (3)</code>		Indicates whether the attribute is inherited from a supertype (<code>YES</code>) or not (<code>NO</code>)
<code>CHAR_USED</code>	<code>VARCHAR2 (1)</code>		Indicates whether the attribute uses <code>BYTE</code> length semantics (<code>B</code>) or <code>CHAR</code> length semantics (<code>C</code>). For <code>NCHAR</code> and <code>NVARCHAR2</code> attribute types, this value is always <code>C</code> .

See Also:

- ["DBA_TYPE_ATTRS"](#) on page 6-27
- ["USER_TYPE_ATTRS"](#) on page 6-106

ALL_TYPE_METHODS

`ALL_TYPE_METHODS` describes the methods of the object types accessible to the current user.

Related Views

- `DBA_TYPE_METHODS` describes the methods of all object types in the database.
- `USER_TYPE_METHODS` describes the methods of the object types owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	<code>NOT NULL</code>	Owner of the type
<code>TYPE_NAME</code>	<code>VARCHAR2 (30)</code>	<code>NOT NULL</code>	Name of the type
<code>METHOD_NAME</code>	<code>VARCHAR2 (30)</code>	<code>NOT NULL</code>	Name of the method

Column	Datatype	NULL	Description
METHOD_NO	NUMBER	NOT NULL	Method number for distinguishing overloaded methods (not to be used as ID number)
METHOD_TYPE	VARCHAR2 (6)		Type of the method: - MAP - ORDER - PUBLIC
PARAMETERS	NUMBER	NOT NULL	Number of parameters to the method
RESULTS	NUMBER	NOT NULL	Number of results returned by the method
FINAL	VARCHAR2 (3)		Indicates whether the method is final (YES) or not (NO)
INSTANTIABLE	VARCHAR2 (3)		Indicates whether the method is instantiable (YES) or not (NO)
OVERRIDING	VARCHAR2 (3)		Indicates whether the method is overriding a supertype method (YES) or not (NO)
INHERITED	VARCHAR2 (3)		Indicates whether the method is inherited from a supertype (YES) or not (NO)

See Also:

- ["DBA_TYPE_METHODS"](#) on page 6-27
- ["USER_TYPE_METHODS"](#) on page 6-106

ALL_TYPE_VERSIONS

ALL_TYPE_VERSIONS describes the versions of the object types accessible to the current user.

Related Views

- DBA_TYPE_VERSIONS describes the versions of all object types in the database.
- USER_TYPE_VERSIONS describes the versions of the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the type
TYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the type
VERSION#	NUMBER	NOT NULL	Internal version number of the type
TYPECODE	VARCHAR2 (30)		Typecode of the type
STATUS	VARCHAR2 (7)		Status of the type: - N/A - VALID - INVALID
LINE	NUMBER	NOT NULL	Line number of the type's spec
TEXT	VARCHAR2 (4000)		Text of the type's spec
HASHCODE	RAW (17)		Hashcode of the type

See Also:

- ["DBA_TYPE_VERSIONS"](#) on page 6-27
- ["USER_TYPE_VERSIONS"](#) on page 6-106

ALL_TYPES

ALL_TYPES describes the object types accessible to the current user.

Related Views

- DBA_TYPES describes all object types in the database.
- USER_TYPES describes the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the type
TYPE_NAME	VARCHAR2 (30)		Name of the type
TYPE_OID	RAW (16)		Object identifier (OID) of the type
TYPECODE	VARCHAR2 (30)		Typecode of the type
ATTRIBUTES	NUMBER		Number of attributes (if any) in the type
METHODS	NUMBER		Number of methods (if any) in the type
PREDEFINED	VARCHAR2 (3)		Indicates whether the type is a predefined type (YES) or not (NO)
INCOMPLETE	VARCHAR2 (3)		Indicates whether the type is an incomplete type (YES) or not (NO)
FINAL	VARCHAR2 (3)		Indicates whether the type is a final type (YES) or not (NO)
INSTANTIABLE	VARCHAR2 (3)		Indicates whether the type is an instantiable type (YES) or not (NO)
SUPERTYPE_OWNER	VARCHAR2 (30)		Owner of the supertype (NULL if type is not a subtype)
SUPERTYPE_NAME	VARCHAR2 (30)		Name of the supertype (NULL if type is not a subtype)
LOCAL_ATTRIBUTES	NUMBER		Number of local (not inherited) attributes (if any) in the subtype
LOCAL_METHODS	NUMBER		Number of local (not inherited) methods (if any) in the subtype
TYPEID	RAW (16)		Type ID value of the type

See Also:

- ["DBA_TYPES"](#) on page 6-27
- ["USER_TYPES"](#) on page 6-107

ALL_UNUSED_COL_TABS

ALL_UNUSED_COL_TABS describes the tables accessible to the current user that contain unused columns.

Related Views

- DBA_UNUSED_COL_TABS describes all tables in the database that contain unused columns.
- USER_UNUSED_COL_TABS describes the tables owned by the current user that contain unused columns. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
COUNT	NUMBER		Number of unused columns

See Also:

- ["DBA_UNUSED_COL_TABS"](#) on page 6-28
- ["USER_UNUSED_COL_TABS"](#) on page 6-107

ALL_UPDATABLE_COLUMNS

ALL_UPDATABLE_COLUMNS describes all columns in a join view that are updatable by the current user, subject to appropriate privileges.

Related Views

- DBA_UPDATABLE_COLUMNS describes all columns in a join view that are updatable by the database administrator, subject to appropriate privileges.
- USER_UPDATABLE_COLUMNS describes all columns owned by the current user that are in a join view and are updatable by the current user, subject to appropriate privileges.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Column name
UPDATABLE	VARCHAR2 (3)		Indicates whether the column is updatable (YES) or not (NO)
INSERTABLE	VARCHAR2 (3)		Indicates whether the column is insertable (YES) or not (NO)
DELETABLE	VARCHAR2 (3)		Indicates whether the column is deletable (YES) or not (NO)

ALL_USERS

ALL_USERS lists all users of the database visible to the current user. This view does not describe the users (see the related views).

Related Views

- DBA_USERS describes all users of the database, and contains more columns than ALL_USERS.
- USER_USERS describes the current user, and contains more columns than ALL_USERS.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (30)	NOT NULL	Name of the user
USER_ID	NUMBER	NOT NULL	ID number of the user
CREATED	DATE	NOT NULL	User creation date

See Also:

- ["DBA_USERS"](#) on page 6-28
- ["USER_USERS"](#) on page 6-107

ALL_USTATS

ALL_USTATS describes the user-defined statistics collected on the tables and indexes accessible to the current user.

Related Views

- DBA_USTATS describes the user-defined statistics collected on all tables and indexes in the database.
- USER_USTATS describes the user-defined statistics collected on the tables and indexes owned by the current user.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)		Owner of the table or index for which the statistics have been collected
OBJECT_NAME	VARCHAR2 (30)		Name of the table or index for which the statistics have been collected
PARTITION_NAME	VARCHAR2 (30)		Partition name of a table; NULL if the table is either non-partitioned or the entry corresponds to the aggregate statistics for the table
OBJECT_TYPE	VARCHAR2 (6)		Type of the object for which statistics have been collected: ■ INDEX ■ COLUMN
ASSOCIATION	VARCHAR2 (8)		Statistics type association: ■ DIRECT Direct association with the object for which the statistics have been collected ■ IMPLICIT - Association for which the statistics have been collected is with the column type or index type, and the object is an instance of that column type or index type
COLUMN_NAME	VARCHAR2 (30)		Column name, if OBJECT_TYPE is COLUMN, for which statistics have been collected
STATSTYPE_SCHEMA	VARCHAR2 (30)		Schema of the statistics type which was used to collect the statistics
STATSTYPE_NAME	VARCHAR2 (30)		Name of the statistics type which was used to collect statistics
STATISTICS	RAW (2000)		User-collected statistics for the object

See Also:

- ["DBA_USTATS"](#) on page 6-29
- ["USER_USTATS"](#) on page 6-107

ALL_VARRAYS

ALL_VARRAYS describes the varrays accessible to the current user.

Related Views

- `DBA_VARRAYS` describes all varrays in the database.
- `USER_VARRAYS` describes the varrays owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>		Owner of the table containing the varray
<code>PARENT_TABLE_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the containing table
<code>PARENT_TABLE_COLUMN</code>	<code>VARCHAR2 (4000)</code>		Name of the varray column or attribute
<code>TYPE_OWNER</code>	<code>VARCHAR2 (30)</code>		Owner of the varray type
<code>TYPE_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the varray type
<code>LOB_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the LOB if the varray is stored in a LOB
<code>STORAGE_SPEC</code>	<code>VARCHAR2 (30)</code>		Indicates whether the storage was defaulted (<code>DEFAULT</code>) or user-specified (<code>USER_SPECIFIED</code>)
<code>RETURN_TYPE</code>	<code>VARCHAR2 (20)</code>		Return type of the column: ■ <code>LOCATOR</code> ■ <code>VALUE</code>
<code>ELEMENT_SUBSTITUTABLE</code>	<code>VARCHAR2 (25)</code>		Indicates whether the varray element is substitutable (Y) or not (N)

See Also:

- ["DBA_VARRAYS"](#) on page 6-29
- ["USER_VARRAYS"](#) on page 6-107

ALL_VIEWS

`ALL_VIEWS` describes the views accessible to the current user.

Related Views

- `DBA_VIEWS` describes all views in the database.
- `USER_VIEWS` describes the views owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the view
<code>VIEW_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the view
<code>TEXT_LENGTH</code>	<code>NUMBER</code>		Length of the view text
<code>TEXT</code>	<code>LONG</code>		View text
<code>TYPE_TEXT_LENGTH</code>	<code>NUMBER</code>		Length of the type clause of the typed view
<code>TYPE_TEXT</code>	<code>VARCHAR2 (4000)</code>		Type clause of the typed view
<code>OID_TEXT_LENGTH</code>	<code>NUMBER</code>		Length of the <code>WITH OID</code> clause of the typed view
<code>OID_TEXT</code>	<code>VARCHAR2 (4000)</code>		<code>WITH OID</code> clause of the typed view
<code>VIEW_TYPE_OWNER</code>	<code>VARCHAR2 (30)</code>		Owner of the type of the view if the view is a typed view
<code>VIEW_TYPE</code>	<code>VARCHAR2 (30)</code>		Type of the view if the view is a typed view
<code>SUPERVIEW_NAME</code>	<code>VARCHAR2 (30)</code>		Name of the superview
<code>EDITIONING_VIEW</code>	<code>VARCHAR2 (1)</code>		Reserved for future use

Column	Datatype	NULL	Description
READ_ONLY	VARCHAR2 (1)		Indicates whether the view is read-only (Y) or not (N)

See Also:

- ["DBA_VIEWS"](#) on page 6-29
- ["USER_VIEWS"](#) on page 6-107

ALL_VIEWS_AE

ALL_VIEWS_AE describes the views (across all editions) accessible to the current user.

Related Views

- DBA_VIEWS_AE describes all views (across all editions) in the database.
- USER_VIEWS_AE describes the views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the view
VIEW_NAME	VARCHAR2 (30)	NOT NULL	Name of the view
TEXT_LENGTH	NUMBER		Length of the view text
TEXT	LONG		View text
TYPE_TEXT_LENGTH	NUMBER		Length of the type clause of the typed view
TYPE_TEXT	VARCHAR2 (4000)		Type clause of the typed view
OID_TEXT_LENGTH	NUMBER		Length of the WITH OID clause of the typed view
OID_TEXT	VARCHAR2 (4000)		WITH OID clause of the typed view
VIEW_TYPE_OWNER	VARCHAR2 (30)		Owner of the type of the view if the view is an typed view
VIEW_TYPE	VARCHAR2 (30)		Type of the view if the view is a typed view
SUPERVIEW_NAME	VARCHAR2 (30)		Name of the superview, if the view is a subview
EDITIONING_VIEW	VARCHAR2 (1)		Indicates whether the view is an editioning view (Y) or not (N)
READ_ONLY	VARCHAR2 (1)		Indicates whether the view is read-only (Y) or not (N)
EDITION_NAME	VARCHAR2 (30)		Name of the application edition where the object is defined

See Also:

- ["DBA_VIEWS_AE"](#) on page 6-30
- ["USER_VIEWS_AE"](#) on page 6-108

ALL_WARNING_SETTINGS

ALL_WARNING_SETTINGS displays information about the warning parameter settings for the objects accessible to the current user.

Related Views

- DBA_WARNING_SETTINGS displays information about the warning parameter settings for all objects in the database.

- `USER_WARNING_SETTINGS` displays information about the warning parameter settings for the objects owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
<code>OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the object
<code>OBJECT_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the object
<code>OBJECT_ID</code>	<code>NUMBER</code>	NOT NULL	Object number of the object
<code>OBJECT_TYPE</code>	<code>VARCHAR2 (12)</code>		Type of the object: ■ <code>PROCEDURE</code> ■ <code>FUNCTION</code> ■ <code>PACKAGE</code> ■ <code>PACKAGE BODY</code> ■ <code>TRIGGER</code> ■ <code>TYPE</code> ■ <code>TYPE BODY</code>
<code>WARNING</code>	<code>VARCHAR2 (40)</code>		Warning number or category: ■ <code>INFORMATIONAL</code> ■ <code>PERFORMANCE</code> ■ <code>SEVERE</code> ■ <code>ALL</code>
<code>SETTING</code>	<code>VARCHAR2 (7)</code>		Value of the warning setting: ■ <code>DISABLE</code> ■ <code>ENABLE</code> ■ <code>ERROR</code>

See Also:

- ["DBA_WARNING_SETTINGS" on page 6-30](#)
- ["USER_WARNING_SETTINGS" on page 6-108](#)

ALL_XML_INDEXES

`ALL_XML_INDEXES` describes the XML indexes accessible to the current user.

Related Views

- `DBA_XML_INDEXES` describes all XML indexes in the database.
- `USER_XML_INDEXES` describes the XML indexes owned by the current user. This view does not display the `INDEX_OWNER` column.

Column	Datatype	NULL	Description
<code>INDEX_OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the XML index
<code>INDEX_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the XML index
<code>TABLE_OWNER</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Owner of the indexed object
<code>TABLE_NAME</code>	<code>VARCHAR2 (30)</code>	NOT NULL	Name of the indexed object

Column	Datatype	NULL	Description
TYPE	VARCHAR2 (10)		Type of the indexed column: - REPOSITORY - BINARY - CLOB in OR - CLOB
INDEX_TYPE	VARCHAR2 (27)		Type of the index: - STRUCTURED - STRUCTURED and UNSTRUCTURED - UNSTRUCTURED
PATH_TABLE_NAME	VARCHAR2 (30)		Name of the path table
PARAMETERS	XMLTYPE		Indexed paths and Scheduler job information
ASNC	VARCHAR2 (9)		Asynchronous index type: - ON-COMMIT - MANUAL - EVERY - ALWAYS
STALE	VARCHAR2 (5)		Indicates whether the index type is stale (TRUE) or not (FALSE)
PEND_TABLE_NAME	VARCHAR2 (30)		Name of the pending table
EX_OR_INCLUDE	VARCHAR2 (8)		Path subsetting: - INCLUDE - EXCLUDE - FULLY IX

See Also:

- ["DBA_XML_INDEXES"](#) on page 6-36
- ["USER_XML_INDEXES"](#) on page 6-108

ALL_XML_SCHEMAS

ALL_XML_SCHEMAS describes the registered XML schemas accessible to the current user.

Related Views

- DBA_XML_SCHEMAS describes all registered XML schemas in the database.
- USER_XML_SCHEMAS describes the registered XML schemas owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the XML schema
SCHEMA_URL	VARCHAR2 (700)		Schema URL of the XML schema
LOCAL	VARCHAR2 (3)		Indicates whether the XML schema is local (YES) or global (NO)
SCHEMA	XMLTYPE		XML schema document
INT_OBJNAME	VARCHAR2 (4000)		Internal database object name for the schema
QUAL_SCHEMA_URL	VARCHAR2 (767)		Fully qualified schema URL

Column	Datatype	NULL	Description
HIER_TYPE	VARCHAR2 (11)		Type of hierarchy for which the schema is enabled: - NONE - RESMETADATA - CONTENTS
BINARY	VARCHAR2 (3)		Indicates whether the XML Schema is registered for binary encoding usage (YES) or not (NO)
SCHEMA_ID	RAW (16)		Opaque schema identifier (16 bytes)
HIDDEN	VARCHAR2 (3)		Indicates whether the XML Schema has been deleted in hidden mode (YES) or not (NO)

See Also:

- ["DBA_XML_SCHEMAS"](#) on page 6-36
- ["USER_XML_SCHEMAS"](#) on page 6-108

ALL_XML_TAB_COLS

ALL_XML_TAB_COLS describes the columns of the XML tables accessible to the current user.

Related Views

- DBA_XML_TAB_COLS describes the columns of all XML tables in the database.
- USER_XML_TAB_COLS describes the columns of the XML tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the XML table
TABLE_NAME	VARCHAR2 (30)		Name of the XML table
COLUMN_NAME	VARCHAR2 (4000)		Name of the XML table column
XMLSCHEMA	VARCHAR2 (700)		Name of the XML Schema that is used for the table definition
SCHEMA_OWNER	VARCHAR2 (30)		Owner of the XML Schema that is used for the table definition
ELEMENT_NAME	VARCHAR2 (2000)		Name of the XML Schema element that is used for the table
STORAGE_TYPE	VARCHAR2 (17)		Storage option for the XMLtype data: - OBJECT-RELATIONAL - BINARY - CLOB
ANYSHEMA	VARCHAR2 (3)		If storage is BINARY, indicates whether the column allows ANYSCHEMA (YES) or not (NO), else NULL
NONSCHEMA	VARCHAR2 (3)		If storage is BINARY, indicates whether the column allows NONSCHEMA (YES) or not (NO), else NULL

See Also:

- ["DBA_XML_TAB_COLS"](#) on page 6-36
- ["USER_XML_TAB_COLS"](#) on page 6-108

ALL_XML_TABLES

ALL_XML_TABLES describes the XML tables accessible to the current user.

Related Views

- DBA_XML_TABLES describes all XML tables in the database.
- USER_XML_TABLES describes the XML tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the XML table
TABLE_NAME	VARCHAR2 (30)		Name of the XML table
XMLSCHEMA	VARCHAR2 (700)		Name of the XML Schema that is used for the table definition
SCHEMA_OWNER	VARCHAR2 (30)		Owner of the XML Schema that is used for the table definition
ELEMENT_NAME	VARCHAR2 (2000)		Name of the XML Schema element that is used for the table
STORAGE_TYPE	VARCHAR2 (17)		Storage option for the XMLtype data: ■ OBJECT-RELATIONAL ■ BINARY ■ CLOB
ANYSCHEMA	VARCHAR2 (3)		If storage is BINARY, indicates whether the column allows ANYSCHEMA (YES) or not (NO), else NULL
NONSCHEMA	VARCHAR2 (3)		If storage is BINARY, indicates whether the column allows NONSCHEMA (YES) or not (NO), else NULL

See Also:

- ["DBA_XML_TABLES"](#) on page 6-36
- ["USER_XML_TABLES"](#) on page 6-108

ALL_XML_VIEW_COLS

ALL_XML_VIEW_COLS describes the columns of the XML views accessible to the current user.

Related Views

- DBA_XML_VIEW_COLS describes the columns of all XML views in the database.
- USER_XML_VIEW_COLS describes the columns of the XML views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the XML view
VIEW_NAME	VARCHAR2 (30)		Name of the XML view
COLUMN_NAME	VARCHAR2 (4000)		Name of the XML view column
XMLSCHEMA	VARCHAR2 (700)		Name of the XML Schema that is used for the view definition
SCHEMA_OWNER	VARCHAR2 (30)		Owner of the XML Schema that is used for the view definition

Column	Datatype	NULL	Description
ELEMENT_NAME	VARCHAR2 (2000)		Name of the XML SSchema element that is used for the view

See Also:

- ["DBA_XML_VIEW_COLS"](#) on page 6-36
- ["USER_XML_VIEW_COLS"](#) on page 6-108

ALL_XML_VIEWS

ALL_XML_VIEWS describes the XML views accessible to the current user.

Related Views

- DBA_XML_VIEWS describes all XML views the database.
- USER_XML_VIEWS describes the XML views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the XML view
VIEW_NAME	VARCHAR2 (30)		Name of the XML view
XMLSCHEMA	VARCHAR2 (700)		Name of the XML Schema that is used for the view definition
SCHEMA_OWNER	VARCHAR2 (30)		Owner of the XML Schema that is used for the view definition
ELEMENT_NAME	VARCHAR2 (2000)		Name of the XML SSchema element that is used for the view

See Also:

- ["DBA_XML_VIEWS"](#) on page 6-37
- ["USER_XML_VIEWS"](#) on page 6-108

ALL_XSTREAM_INBOUND

ALL_XSTREAM_INBOUND displays information about the XStream inbound servers accessible to the current user.

Related View

DBA_XSTREAM_INBOUND displays information about all XStream inbound servers in the database.

Column	Datatype	NULL	Description
SERVER_NAME	VARCHAR2 (30)	NOT NULL	Name of the inbound server
QUEUE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the queue associated with the inbound server
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue associated with the inbound server
APPLY_USER	VARCHAR2 (30)		Name of the user who can connect to the inbound server and apply messages
USER_COMMENT	VARCHAR2 (4000)		User comment
CREATE_DATE	TIMESTAMP (6)		Date when the inbound server was created

Column	Datatype	NULL	Description
STATUS ¹	VARCHAR2 (8)		Status of the inbound server: - DISABLED - The inbound server is not running. - DETACHED - The inbound server is running, but the XStream client application is not attached to it. - ATTACHED - The inbound server is running, and the XStream client application is attached to it. - ABORTED - The inbound server became disabled because it encountered an error.
COMMITTED_DATA_ONLY ¹	VARCHAR2 (3)		YES if the inbound server can receive only LCRs in committed transactions from the XStream client application. A committed transaction is an assembled, noninterleaving transaction with no rollbacks. NO if the inbound server can receive LCRs in transactions that have not yet committed. This mode is for internal Oracle use only.

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also: ["DBA_XSTREAM_INBOUND"](#) on page 6-37

ALL_XSTREAM_INBOUND_PROGRESS

ALL_XSTREAM_INBOUND_PROGRESS displays information about the progress made by the XStream inbound servers accessible to the current user.

Related View

DBA_XSTREAM_INBOUND_PROGRESS displays information about the progress made by all XStream inbound servers in the database.

Column	Datatype	NULL	Description
SERVER_NAME	VARCHAR2 (30)	NOT NULL	Name of the inbound server
PROCESSED_LOW_POSITION	RAW (64)		Position of the processed low transaction
APPLIED_LOW_POSITION	RAW (64)		All messages with a commit position less than this value have been applied
APPLIED_HIGH_POSITION	RAW (64)		Highest commit position of a transaction that has been applied
SPILL_POSITION	RAW (64)		Position of the spill low watermark of the transactions currently being applied
OLDEST_POSITION ¹	RAW (64)		Earliest position of the transactions currently being applied
OLDEST_MESSAGE_NUMBER ¹	NUMBER	NOT NULL	Earliest message number of the transactions currently being applied
APPLIED_MESSAGE_NUMBER ¹	NUMBER	NOT NULL	Message number up to which all transactions have definitely been applied. This value is the low watermark for the inbound server. That is, messages with a commit message number less than or equal to this message number have definitely been applied, but some messages with a higher commit message number may also have been applied.
APPLIED_TIME ¹	DATE		Time at which the message with the message number displayed in the APPLIED_MESSAGE_NUMBER column was applied
APPLIED_MESSAGE_CREATE_TIME ¹	DATE		Time at which the message with the message number displayed in the APPLIED_MESSAGE_NUMBER column was created at its source database

Column	Datatype	NULL	Description
<code>SPILL_MESSAGE_NUMBER</code> ¹	NUMBER		Spill low watermark. Any message with a lower SCN has either been applied or spilled to disk. The XStream client application does not need to send logical change records (LCRs) with a lower SCN than the spill low watermark. Spilled messages may not have been applied yet.
<code>SOURCE_DATABASE</code> ¹	VARCHAR2 (128)	NOT NULL	Database where the transaction originated

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also: ["DBA_XSTREAM_INBOUND_PROGRESS"](#) on page 6-37

ALL_XSTREAM_OUTBOUND

`ALL_XSTREAM_OUTBOUND` displays information about the XStream outbound servers accessible to the current user.

Related View

`DBA_XSTREAM_OUTBOUND` displays information about all XStream outbound servers in the database.

Column	Datatype	NULL	Description
<code>SERVER_NAME</code>	VARCHAR2 (30)	NOT NULL	Name of the outbound server
<code>CONNECT_USER</code>	VARCHAR2 (30)		Name of the user who can connect to the outbound server and process the outbound LCRs
<code>CAPTURE_NAME</code>	VARCHAR2 (30)		Name of the Streams capture process
<code>SOURCE_DATABASE</code>	VARCHAR2 (128)		Database where the transaction originated
<code>CAPTURE_USER</code>	VARCHAR2 (30)		Current user who is enqueueing captured messages
<code>QUEUE_OWNER</code>	VARCHAR2 (30)	NOT NULL	Owner of the queue associated with the outbound server
<code>QUEUE_NAME</code>	VARCHAR2 (30)	NOT NULL	Name of the queue associated with the outbound server
<code>USER_COMMENT</code>	VARCHAR2 (4000)		User comment
<code>CREATE_DATE</code>	TIMESTAMP (6)		Date when the outbound server was created
<code>STATUS</code> ¹	VARCHAR2 (8)		Status of the inbound server: ■ DISABLED - The outbound server is not running. ■ DETACHED - The outbound server is running, but the XStream client application is not attached to it. ■ ATTACHED - The outbound server is running, and the XStream client application is attached to it. ■ ABORTED - The outbound server became disabled because it encountered an error.
<code>COMMITTED_DATA_ONLY</code> ¹	VARCHAR2 (3)		YES if the outbound server can send only LCRs in committed transactions to the XStream client application. A committed transaction is an assembled, noninterleaving transaction with no rollbacks. NO if the outbound server can send LCRs in transactions that have not yet committed to the XStream client application. This mode is for internal Oracle use only.
<code>START_SCN</code> ¹	NUMBER		The SCN from which the outbound server's capture process started capturing changes when it was last started

Column	Datatype	NULL	Description
START_TIME ¹	TIMESTAMP (6)		The time from which the outbound server's capture process started capturing changes when it was last started

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also: ["DBA_XSTREAM_OUTBOUND"](#) on page 6-38

ALL_XSTREAM_OUTBOUND_PROGRESS

ALL_XSTREAM_OUTBOUND_PROGRESS displays information about the progress made by the XStream outbound servers accessible to the current user.

Related View

DBA_XSTREAM_OUTBOUND_PROGRESS displays information about the progress made by all XStream outbound servers in the database.

Column	Datatype	NULL	Description
SERVER_NAME	VARCHAR2 (30)	NOT NULL	Name of the outbound server
SOURCE_DATABASE	VARCHAR2 (128)		Database where the transaction originated
PROCESSED_LOW_POSITION	RAW (64)		Position of the low-watermark transaction processed by the outbound server
PROCESSED_LOW_TIME	DATE		Time when the processed low position was last updated by the outbound server
OLDEST_POSITION ¹	RAW (64)		The position of the earliest LCR that is required by the XStream client application

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also: ["DBA_XSTREAM_OUTBOUND_PROGRESS"](#) on page 6-38

ALL_XSTREAM_RULES

ALL_XSTREAM_RULES displays information about the XStream rules accessible to the current user.

Related View

DBA_XSTREAM_RULES displays information about all XStream server rules in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2 (30)		Name of the Streams process
STREAMS_TYPE	VARCHAR2 (12)		Type of the Streams process: ■ CAPTURE ■ APPLY
STREAMS_RULE_TYPE	VARCHAR2 (6)		The Streams type of the rule: ■ TABLE ■ SCHEMA ■ GLOBAL
RULE_SET_OWNER	VARCHAR2 (30)		Owner of the rule set

Column	Datatype	NULL	Description
RULE_SET_NAME	VARCHAR2 (30)		Name of the rule set
RULE_SET_TYPE	CHAR (8)		Type of the rule set: ■ POSITIVE ■ NEGATIVE
RULE_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2 (30)	NOT NULL	Name of the rule
RULE_TYPE	VARCHAR2 (3)		The type of the rule: ■ DML ■ DDL
RULE_CONDITION	CLOB		Current rule condition
SCHEMA_NAME	VARCHAR2 (30)		For table and schema rules, the schema name
OBJECT_NAME	VARCHAR2 (30)		For table rules, the table name
INCLUDE_TAGGED_LCR	VARCHAR2 (3)		Indicates whether to include tagged LCRs (YES) or not (NO)
SUBSETTING_OPERATION	VARCHAR2 (6)		For subset rules, the type of operation: ■ INSERT ■ UPDATE ■ DELETE
DML_CONDITION	VARCHAR2 (4000)		For subset rules, the row subsetting condition
SOURCE_DATABASE	VARCHAR2 (128)		The name of the database where the LCRs originated
ORIGINAL_RULE_CONDITION	VARCHAR2 (4000)		For rules created by Streams administrative APIs, the original rule condition when the rule was created
SAME_RULE_CONDITION	VARCHAR2 (3)		For rules created by Streams administrative APIs, indicates whether the current rule condition is the same as the original rule condition (YES) or not (NO)

See Also: ["DBA_XSTREAM_RULES"](#) on page 6-38

AUDIT_ACTIONS

AUDIT_ACTIONS describes audit trail action type codes. This table can be used to map action type numbers to action type names.

Column	Datatype	NULL	Description
ACTION	NUMBER	NOT NULL	Numeric audit trail action type code. These values also appear in the COMMAND column of the V\$SESSION dynamic performance view, and are listed with that view. See Also: Table 9-2 on page 9-13 for a listing of the action type codes
NAME	VARCHAR2 (28)	NOT NULL	Name of the type of audit trail action

CAT

CAT is a synonym for USER_CATALOG.

See Also: ["USER_CATALOG"](#) on page 6-70

CATALOG

CATALOG is included for compatibility. Oracle recommends that you not use this view.

CHAINED_ROWS

CHAINED_ROWS stores the output for the ANALYZE statement with the LIST CHAINED ROWS clause. You must run the `utlchain.sql` or `utlchn1.sql` script to create this table.

Column	Description
OWNER_NAME	Table owner
TABLE_NAME	Table name
CLUSTER_NAME	Cluster the table is in, if any
PARTITION_NAME	The name of the partition
SUBPARTITION_NAME	The name of the subpartition
HEAD_ROWID	ROWID the chained row is accessed by
ANALYZE_TIMESTAMP	Date/time that the ANALYZE statement was issued

CHANGE_PROPAGATION_SETS

CHANGE_PROPAGATION_SETS is a synonym for ALL_CHANGE_PROPAGATION_SETS.

See Also: ["ALL_CHANGE_PROPAGATION_SETS"](#) on page 2-27

CHANGE_PROPAGATIONS

CHANGE_PROPAGATIONS is a synonym for ALL_CHANGE_PROPAGATIONS.

See Also: ["ALL_CHANGE_PROPAGATIONS"](#) on page 2-27

CHANGE_SETS

CHANGE_SETS is a synonym for ALL_CHANGE_SETS.

See Also: ["ALL_CHANGE_SETS"](#) on page 2-28

CHANGE_SOURCES

CHANGE_SOURCES is a synonym for ALL_CHANGE_SOURCES.

See Also: ["ALL_CHANGE_SOURCES"](#) on page 2-28

CHANGE_TABLES

CHANGE_TABLES is a synonym for ALL_CHANGE_TABLES.

See Also: ["ALL_CHANGE_TABLES"](#) on page 2-29

CLIENT_RESULT_CACHE_STAT\$\$

CLIENT_RESULT_CACHE_STAT\$\$ displays various Client Result Cache settings and usage statistics. Statistics are stored as name, value pairs. For each client cache ID, there will be multiple rows for each statistic.

Column	Datatype	NULL	Description
CACHE_ID	NUMBER	NOT NULL	Unique ID per client cache
STAT_ID	NUMBER	NOT NULL	Statistic ID
NAME	VARCHAR2 (128)		Name of the statistic (see Table 3-1)
VALUE	NUMBER		Value of the statistic

Table 3-1 CLIENT_RESULT_CACHE_STAT\$\$ Statistics

Statistic Name	Description
Block Size	Size (in bytes) of each memory block in the result cache.
Block Count Max	Maximum number of blocks that can be allocated in the result cache based on the cache size configuration parameters on server and on client.
Block Count Current	Current number of blocks allocated by the client result cache.
Hash Bucket Count	Size of the hash table used for query matching.
Create Count Success	Number of cached result sets that did not get invalidated prior to caching all the rows of the result set.
Create Count Failure	Number of cached result sets that did not fetch all the rows in the result set.
Find Count	Number of cache hits.
Invalidation Count	Number of cached result sets that got invalidated due to database changes that could have affected the result set.
Delete Count Invalid	Number of cached result rests not invalidated whose memory was reclaimed by result cache.
Delete Count Valid	Number of invalidated cached result rests whose memory was reclaimed by result cache.

CLU

CLU is a synonym for USER_CLUSTERS.

See Also: ["USER_CLUSTERS"](#) on page 6-71

COL

COL is included for compatibility. Oracle recommends that you not use this view.

COLS

COLS is a synonym for USER_TAB_COLUMNS.

See Also: ["USER_TAB_COLUMNS"](#) on page 6-103

DATABASE_PROPERTIES

DATABASE_PROPERTIES lists Permanent database properties.

Column	Datatype	NULL	Description
PROPERTY_NAME	VARCHAR2 (30)	NOT NULL	Property name

Column	Datatype	NULL	Description
PROPERTY_VALUE	VARCHAR2 (4000)		Property value
DESCRIPTION	VARCHAR2 (4000)		Property description

Static Data Dictionary Views: DBA_2PC_NEIGHBORS to DBA_HIST_JAVA_POOL_ADVICE

This chapter contains the static data dictionary views DBA_2PC_NEIGHBORS through DBA_HIST_JAVA_POOL_ADVICE.

DBA_2PC_NEIGHBORS

DBA_2PC_NEIGHBORS describes incoming and outgoing connections for pending transactions.

Column	Datatype	NULL	Description
LOCAL_TRAN_ID	VARCHAR2 (22)		Local identifier of a transaction
IN_OUT	VARCHAR2 (3)		IN for incoming connections, OUT for outgoing
DATABASE	VARCHAR2 (128)		IN for client database name, OUT for outgoing database link
DBUSER_OWNER	VARCHAR2 (30)		IN for name of local user, OUT for owner of database link
INTERFACE	VARCHAR2 (1)		C for request commit, otherwise N for prepare or request read only commit
DBID	VARCHAR2 (16)		Database ID at the other end of the connection
SESS#	NUMBER (38)		Session number of the connection at this database
BRANCH	VARCHAR2 (128)		Transaction branch ID of the connection at this database

DBA_2PC_PENDING

DBA_2PC_PENDING describes distributed transactions awaiting recovery.

Column	Datatype	NULL	Description
LOCAL_TRAN_ID	VARCHAR2 (22)	NOT NULL	String of form: n.n.n; n is a number
GLOBAL_TRAN_ID	VARCHAR2 (169)		Globally unique transaction ID
STATE	VARCHAR2 (16)	NOT NULL	Collecting, prepared, committed, forced commit, or forced rollback
MIXED	VARCHAR2 (3)		YES indicates part of the transaction committed and part rolled back
ADVICE	VARCHAR2 (1)		C for commit, R for rollback, else NULL
TRAN_COMMENT	VARCHAR2 (255)		Text for commit work comment text

Column	Datatype	NULL	Description
FAIL_TIME	DATE	NOT NULL	Value of SYSDATE when the row was inserted (transaction or system recovery)
FORCE_TIME	DATE		Time of manual force decision (null if not forced locally)
RETRY_TIME	DATE	NOT NULL	Time automatic recovery (RECO) last tried to recover the transaction
OS_USER	VARCHAR2 (64)		Operating system-specific name for the end-user
OS_TERMINAL	VARCHAR2 (255)		Operating system-specific name for the end-user terminal
HOST	VARCHAR2 (128)		Name of the host machine for the end-user
DB_USER	VARCHAR2 (30)		Oracle user name of the end-user at the topmost database
COMMIT#	VARCHAR2 (16)		Global commit number for committed transactions

DBA_ADDM_FDG_BREAKDOWN

DBA_ADDM_FDG_BREAKDOWN describes the contribution for each finding from the different instances. There is one row for each finding and for each instance participating in the analysis. Rows are omitted if the impact from that instance is not sufficient to register a finding in a local ADDM analysis.

Related View

USER_ADDM_FDG_BREAKDOWN describes the contribution for each finding from the different instances owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	Identifies the task to which this finding belongs (see DBA_ADVISOR_TASKS)
FINDING_ID	NUMBER	NOT NULL	Identifies the finding (see DBA_ADVISOR_FINDINGS)
INSTANCE_NUMBER	NUMBER	NOT NULL	The number of the instance contributing to the finding
DATABASE_TIME	NUMBER		The database time, in microseconds, accumulated by this instance during the analysis period
ACTIVE_SESSIONS	NUMBER		The average number of active sessions of the finding in this instance
PERC_ACTIVE_SESSIONS	NUMBER		The percentage of contribution from this instance compared to the total impact of the finding

DBA_ADDM_FINDINGS

DBA_ADDM_FINDINGS displays the ADDM findings discovered by all advisors in the database. Each row for ADDM tasks in the related DBA_ADVISOR_FINDINGS view has a corresponding row in this view.

Related View

USER_ADDM_FINDINGS displays the ADDM findings discovered by the advisors owned by the current user. Each row for ADDM tasks in the related USER_ADVISOR_FINDINGS view has a corresponding row in this view. The USER_ADDM_FINDINGS view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
EXECUTION_NAME	VARCHAR2 (30)		The name of the task execution with which this entry (row) is associated
FINDING_ID	NUMBER	NOT NULL	Identifier of the finding
FINDING_NAME	VARCHAR2 (4000)		Name of the finding
TYPE	VARCHAR2 (11)		Type of the finding: PROBLEM SYMPTOM ERROR INFORMATION
PARENT	NUMBER	NOT NULL	Identifier of the parent finding
OBJECT_ID	NUMBER		Identifier of the associated object, if any
IMPACT_TYPE	VARCHAR2 (4000)		Impact of the finding on the system
IMPACT	NUMBER		Impact value
MESSAGE	VARCHAR2 (4000)		Message describing the finding
MORE_INFO	VARCHAR2 (4000)		Additional info associated with the finding
FILTERED	CHAR (1)		A value of Y means that the row in the view was filtered out by a directive (or a combination of directives). A value of N means that the row was not filtered.
DATABASE_TIME	NUMBER		The database time, in microseconds, accumulated by this finding
ACTIVE_SESSIONS	NUMBER		The average number of active sessions for the finding
PERC_ACTIVE_SESS	NUMBER		The percentage of active sessions for this finding out of the total active sessions for the task
IS_AGGREGATE	CHAR (1)		A value of Y means that this finding is created for global/continental ADDM as an aggregate of local ADDM findings. Otherwise, the value is N.
METER_LEVEL	VARCHAR2 (6)		Reserved for future use

DBA_ADDM_INSTANCES

DBA_ADDM_INSTANCES displays instance-level information for ADDM tasks that finished executing. For each instance that was supposed to be analyzed (whether it was or not) there is one row describing information about it.

Related View

USER_ADDM_INSTANCES displays instance-level information for ADDM tasks that finished executing in all instances owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	The ID of the main ADDM task
INSTANCE_NUMBER	NUMBER	NOT NULL	The number of the instance
INSTANCE_NAME	VARCHAR2 (16)		The name of the instance
HOST_NAME	VARCHAR2 (64)		The name of the machine on which the instance was running

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (10)		How information from this instance was used by the ADDM task. A value of ANALYZED means that the instance participated fully in the analysis. For the following remaining values, the instance was not used during task execution, for the stated reason: BOUNCED - the instance was shut down or started during the analysis period NO_SNAPS - there were either begin or end snapshots missing for the instance NO_STATS - there were key statistics missing for the instance NOT_FOUND - no mention of this instance could be found in AWR during the analysis period
DATABASE_TIME	NUMBER		The database time, in microseconds, accumulated by this instance during the analysis period
ACTIVE_SESSIONS	NUMBER		The average number of active sessions for the instance during the analysis period
PERC_ACTIVE_SESS	NUMBER		The percentage of active sessions for this instance, out of the total active sessions for the task
METER_LEVEL	VARCHAR2 (6)		Reserved for future use
LOCAL_TASK_ID	NUMBER		The ID of a local ADDM task that contained an analysis of the instance for the same analysis period as that of the main task. If the main task is a local ADDM, then this value is the same as the TASK_ID value.

DBA_ADDM_SYSTEM_DIRECTIVES

DBA_ADDM_SYSTEM_DIRECTIVES displays information about global instances for ADDM system directives.

Column	Datatype	NULL	Description
INSTANCE_ID	NUMBER	NOT NULL	Unique ID for the directive instance. The directive management engine automatically generates ID numbers.
INSTANCE_NAME	VARCHAR2 (30)	NOT NULL	User-assigned name for the directive instance.
DIRECTIVE_NAME	VARCHAR2 (30)	NOT NULL	Any value that further classifies this directive within a domain. The domain and the name form a unique key for the directive.
DESCRIPTION	VARCHAR2 (4000)		Description of the ADDM system directive, shown in the language used by the current session

DBA_ADDM_TASK_DIRECTIVES

DBA_ADDM_TASK_DIRECTIVES displays information about all ADDM task directives in the database.

Related View

USER_ADDM_TASK_DIRECTIVES displays information about all ADDM task directives in the database.

Column	Datatype	NULL	Description
TASK_ID	NUMBER		An ADDM advisor task identifier to which the directive instance is associated

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2 (30)		An ADDM advisor task to which the directive instance is associated
USERNAME	VARCHAR2 (30)	NOT NULL	Database user who owns the ADDM task instance
SEQ_ID	NUMBER	NOT NULL	Unique ID for the directive instance. The directive management engine automatically generates ID numbers.
INSTANCE_NAME	VARCHAR2 (30)	NOT NULL	A user-assigned name for the ADDM task directive instance
DIRECTIVE_NAME	VARCHAR2 (30)	NOT NULL	Any value that further classifies this directive within a domain. The domain and the name form a unique key for the directive.
DESCRIPTION	VARCHAR2 (4000)		Description of the ADDM task directive, shown in the language used by the current session

DBA_ADDM_TASKS

DBA_ADDM_TASKS displays information about all ADDM tasks in the database. The view contains one row for each row in the related DBA_ADVISOR_TASKS view that has ADVISOR_NAME=ADDM and STATUS=COMPLETED.

Related View

USER_ADDM_TASKS displays information about the ADDM tasks owned by the current user. The view contains one row for each row in the related USER_ADVISOR_TASKS view that has ADVISOR_NAME=ADDM and STATUS=COMPLETED. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
DESCRIPTION	VARCHAR2 (256)		User-supplied description of the task
ADVISOR_NAME	VARCHAR2 (30)		Advisor associated with the task
CREATED	DATE	NOT NULL	Creation date of the task
LAST_MODIFIED	DATE	NOT NULL	Date on which the task was last modified
PARENT_TASK_ID	NUMBER		Identifier of the parent task (if the task was created as a result of the recommendation of another task)
PARENT_RXEC_ID	NUMBER		Identifier of the recommendation within the parent task that resulted in the creation of the task
LAST_EXECUTION	VARCHAR2 (30)		Name of the current or last task execution
EXECUTION_TYPE	VARCHAR2 (30)		Type of the last execution. This information is optional for single-execution tasks.
EXECUTION_TYPE#	NUMBER		Reserved for internal use
EXECUTION_DESCRIPTION	VARCHAR2 (256)		Optional description of the last execution
EXECUTION_START	DATE		Execution start date and time of the task
EXECUTION_END	DATE		Execution end date and time of the task

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (11)		Current operational status of the task: - INITIAL - Initial state of the task; no recommendations are present - EXECUTING - Task is currently running - INTERRUPTED - Task analysis was interrupted by the user. Recommendation data, if present, can be viewed and reported at this time. - COMPLETED - Task successfully completed the analysis operation. Recommendation data can be viewed and reported. - ERROR - An error occurred during the analysis operation. Recommendations, if present, can be viewed and reported at this time.
STATUS_MESSAGE	VARCHAR2 (4000)		Informational message provided by the advisor, regarding the status
PCT_COMPLETION_TIME	NUMBER		Percent completion, in terms of time, of the task when it is executing
PROGRESS_METRIC	NUMBER		Metric that measures the progress of the task in terms of quality. Each advisor may have its own metric.
METRIC_UNITS	VARCHAR2 (64)		Unit of the metric used to measure progress
ACTIVITY_COUNTER	NUMBER		Counter that is updated frequently by the advisor, denoting that useful work is being performed
RECOMMENDATION_COUNT	NUMBER		Number of recommendations produced
ERROR_MESSAGE	VARCHAR2 (4000)		Informational message or an error message indicating the current operation or condition
SOURCE	VARCHAR2 (30)		Optional name that identifies the creator of the task
HOW_CREATED	VARCHAR2 (30)		Optional task or template on which the object was based
READ_ONLY	VARCHAR2 (5)		Indicates whether the task is read-only (TRUE) or not (FALSE)
SYSTEM_TASK	VARCHAR2 (5)		Indicates whether the task is a system task (TRUE) or not (FALSE). The automatic SQL tuning task, SYS_AUTO_SQL_TUNING_TASK, is one example of a system task.
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
STATUS#	NUMBER		Reserved for internal use
DBID	NUMBER		The database ID that the task was using
DBNAME	VARCHAR2 (9)		The name of the database that the task was analyzing
DBVERSION	VARCHAR2 (17)		The version of the database that the task was analyzing
ANALYSIS_VERSION	VARCHAR2 (17)		The version of the database that executed the task
BEGIN_SNAP_ID	NUMBER		The snapshot ID that starts the analysis period
BEGIN_TIME	TIMESTAMP (3)		The SYSDATE at the time the BEGIN_SNAP_ID was taken
END_SNAP_ID	NUMBER		The snapshot ID that ends the analysis period
END_TIME	TIMESTAMP (3)		The SYSDATE at the time the END_SNAP_ID was taken
REQUESTED_ANALYSIS	VARCHAR2 (8)		The type of ADDM analysis that was requested before task execution, as follows: DATABASE - global ADDM INSTANCE - local ADDM PARTIAL - continental ADDM
ACTUAL_ANALYSIS	VARCHAR2 (8)		The type of ADDM analysis that was actually performed when the task was executed (either DATABASE, INSTANCE, or PARTIAL)

Column	Datatype	NULL	Description
DATABASE_TIME	NUMBER		The total database time accumulated in the analysis period (and analyzed instances) in microseconds
ACTIVE_SESSIONS	NUMBER		The average active sessions during the analysis period (and analyzed sessions)
METER_LEVEL	VARCHAR2 (6)		Reserved for future use

DBA_ADVISOR_ACTIONS

DBA_ADVISOR_ACTIONS displays information about the actions associated with all recommendations in the database. Each action is specified by the COMMAND and ATTR1 through ATTR6 columns. Each command defines how the attribute columns will be used.

Related View

USER_ADVISOR_ACTIONS displays information about the actions associated with the recommendations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
EXECUTION_NAME	VARCHAR2 (30)		The name of the task execution with which this entry (row) is associated
REC_ID	NUMBER	NOT NULL	Recommendation associated with the action
ACTION_ID	NUMBER	NOT NULL	Unique identifier for the action
OBJECT_ID	NUMBER		Object associated with the action
COMMAND	VARCHAR2 (64)		Command to be executed See Also: DBA_ADVISOR_COMMANDS for a list of commands
COMMAND_ID	NUMBER	NOT NULL	ID of the command to be executed See Also: DBA_ADVISOR_COMMANDS for a list of commands
FLAGS	NUMBER		Advisor-specific flags
ATTR1	VARCHAR2 (4000)		Parameters defining the command
ATTR2	VARCHAR2 (4000)		Parameters defining the command
ATTR3	VARCHAR2 (4000)		Parameters defining the command
ATTR4	VARCHAR2 (4000)		Parameters defining the command
ATTR5	CLOB		Parameters defining the command; to be used if the text is significantly large (for example, a SQL statement defining a materialized view)
ATTR6	CLOB		Parameters defining the command; to be used if the text is significantly large (for example, a SQL statement defining a materialized view)
NUM_ATTR1	NUMBER		General numeric attribute
NUM_ATTR2	NUMBER		General numeric attribute
NUM_ATTR3	NUMBER		General numeric attribute
NUM_ATTR4	NUMBER		General numeric attribute
NUM_ATTR5	NUMBER		General numeric attribute

Column	Datatype	NULL	Description
MESSAGE	VARCHAR2 (4000)		Message associated with the action
FILTERED	VARCHAR2 (1)		A value of Y means that the row in the view was filtered out by a directive (or a combination of directives). A value of N means that the row was not filtered.

See Also: ["USER_ADVISOR_ACTIONS"](#) on page 6-64

DBA_ADVISOR_COMMANDS

DBA_ADVISOR_COMMANDS displays information about the commands used by all advisors in the database for specifying recommendation actions. In addition to the set of commands in the COMMAND column of V\$SESSION, the following additional commands are defined:

- RUN ADVISOR
- CHECK EXECUTION PLAN
- ALTER PARAMETER
- ENABLE TRACE

Column	Datatype	NULL	Description
COMMAND_ID	NUMBER		Identifier of the command
COMMAND_NAME	VARCHAR2 (64)		Name of the command

DBA_ADVISOR_DEF_PARAMETERS

DBA_ADVISOR_DEF_PARAMETERS displays all default task parameters and their current values in the database. When a task or object is created, the parameters and their values are copied into the private parameter table.

Column	Datatype	NULL	Description
ADVISOR_NAME	VARCHAR2 (30)	NOT NULL	Name of the advisor that supports the parameter
PARAMETER_NAME	VARCHAR2 (30)	NOT NULL	Name of the parameter
PARAMETER_VALUE	VARCHAR2 (4000)	NOT NULL	Value of the parameter. Numeric parameter values are converted to a string equivalent. Possible keywords as values: ■ ALL ■ UNLIMITED ■ UNUSED

Column	Datatype	NULL	Description
PARAMETER_TYPE	VARCHAR2 (10)		Datatype of the parameter: - NUMBER - Numeric value - STRING - String value. If the string contains special characters, then it will be enclosed in single quotes. - STRINGLIST - Comma-separated list of string elements. If a string element contains a comma or other special characters, then the element will be enclosed in single quotes. - TABLE - Single table reference. A reference will contain a schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported. - TABLELIST - List of one or more comma-separated table references. A reference will contain schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported.
IS_DEFAULT	VARCHAR2 (1)		Indicates whether the parameter value is set to the advisor's default value (Y) or not (N)
IS_OUTPUT	VARCHAR2 (1)		Indicates whether the task execution process sets the parameter value (Y) or not (N)
IS_MODIFIABLE_ANYTIME	VARCHAR2 (1)		Indicates whether the parameter value can be modified when the task is not in its initial state (Y) or not (N)
IS_SYSTEM_TASK_ONLY	VARCHAR2 (1)		Indicates whether the task is a system task (Y) or not (N)
DESCRIPTION	VARCHAR2 (4000)		Optional description of the parameter
EXECUTION_TYPE	VARCHAR2 (30)		Type of the last execution. This information is optional for single-execution tasks.

DBA_ADVISOR_DEFINITIONS

DBA_ADVISOR_DEFINITIONS displays the properties of all advisors in the database. The view contains one row for each task, representing the current state of the task as well as execution-specific data such as progress monitoring and completion status.

Column	Datatype	NULL	Description
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
ADVISOR_NAME	VARCHAR2 (30)	NOT NULL	Name of the advisor
PROPERTY	NUMBER	NOT NULL	Properties: - Bit 0: - Indicates whether the advisor runs in COMPREHENSIVE mode (1) or not (0) - Bit 1: - Indicates whether the advisor runs in LIMITED mode (1) or not (0) - Bit 2: - Indicates whether the advisor is resumable (1) or not (0) - Bit 3: - Indicates whether the advisor accepts user directives (1) or not (0)

DBA_ADVISOR_DIR_DEFINITIONS

DBA_ADVISOR_DIR_DEFINITIONS provides a definition of the base directive.

Column	Datatype	NULL	Description
ID	NUMBER	NOT NULL	Unique id for directive. The directive management engine automatically generates ID numbers. The identifier is unique among all directives regardless of the domain name and directive name.
ADVISOR_ID	NUMBER	NOT NULL	Identifier number of the owner advisor.
ADVISOR_NAME	VARCHAR2 (30)	NOT NULL	The name of the advisor to which this directive belongs.
DIRECTIVE_NAME	VARCHAR2 (30)	NOT NULL	Any value that further classifies this directive within a domain. The domain and the name form a unique key for the directive.
DOMAIN_NAME	VARCHAR2 (30)	NOT NULL	Domain or namespace name.
DESCRIPTION	VARCHAR2 (256)	NOT NULL	An optional description that documents the purpose of the directive.
TYPE	NUMBER	NOT NULL	Further describes the use of the directive. Possible values are: Filter - An Xpath filter Single Value - Evaluation returns a single string value Multiple Values - Evaluation returns one to many string values Conditional - Evaluation returns a single value based on an input key, similar to a CASE or SWITCH statement
TYPE_NAME	VARCHAR2 (15)		A decoded version of the TYPE column.
TASK_STATUS	VARCHAR2 (9)		The status of the directive instances when a task is not in its initial state. Possible values are: - IMMUTABLE - MUTABLE
INSTANCES	VARCHAR2 (8)		Indicates whether a directive will permit multiple instances. Possible values are: - SINGLE - MULTIPLE
METADATA	CLOB	NOT NULL	A DTD that is used to process the directive.

DBA_ADVISOR_DIR_INSTANCES

DBA_ADVISOR_DIR_INSTANCES provides information about all global instances for a directive.

Column	Datatype	NULL	Description
DIRECTIVE_ID	NUMBER	NOT NULL	Unique id for directive. The directive management engine automatically generates ID numbers.
INSTANCE_ID	NUMBER	NOT NULL	Unique id for the directive instance. The directive management engine automatically generates ID numbers.
INSTANCE_NAME	VARCHAR2 (30)	NOT NULL	A user-assigned name for the directive instance.
DATA	CLOB	NOT NULL	An XML document that gives meaningful default values for all parts of the directive.

DBA_ADVISOR_DIR_TASK_INST

DBA_ADVISOR_DIR_TASK_INST provides information about all task directive instances.

Related View

USER_ADVISOR_DIR_TASK_INST provides information about all task directive instances owned by the current user.

Column	Datatype	NULL	Description
DIRECTIVE_ID	NUMBER	NOT NULL	Unique id for directive. The directive management engine automatically generates ID numbers.
SEQ_ID	NUMBER	NOT NULL	Unique id for the directive instance. The directive management engine automatically generates ID numbers.
INSTANCE_NAME	VARCHAR2 (30)	NOT NULL	A user-assigned name for the directive instance.
USERNAME	VARCHAR2 (30)	NOT NULL	Database user who owns the task instance.
TASK_ID	NUMBER		An advisor task identifier to which the directive instance is associated
TASK_NAME	VARCHAR2 (30)		An advisor task to which the directive instance is associated.
DATA	CLOB	NOT NULL	An XML document that gives meaningful default values for all parts of the directive.

DBA_ADVISOR_EXEC_PARAMETERS

DBA_ADVISOR_EXEC_PARAMETERS displays the parameter values used for past executions of tasks. It is more useful for advisors supporting multiple executions, such as SQL Performance Analyzer, where a parameter can have different values for different executions.

Related View

USER_ADVISOR_EXEC_PARAMETERS displays the parameter values used for past executions of tasks owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
EXECUTION_NAME	VARCHAR2 (30)	NOT NULL	Name of the task execution with which this entry (row) is associated
EXECUTION_TYPE	VARCHAR2 (30)		Type of the last execution. This information is optional for single-execution tasks.
PARAMETER_NAME	VARCHAR2 (30)	NOT NULL	Name of the parameter
PARAMETER_VALUE	VARCHAR2 (4000)		Value of the parameter. Numeric parameter values are converted to a string equivalent.
PARAMETER_TYPE	VARCHAR2 (10)		Datatype of the parameter (see DBA_ADVISOR_PARAMETERS)
IS_DEFAULT	VARCHAR2 (1)		Indicates whether the parameter value is set to the advisor's default value (Y) or not (N)
IS_OUTPUT	VARCHAR2 (1)		Indicates whether the task execution process sets the parameter value (Y) or not (N)
IS_MODIFIABLE_ANYTIME	VARCHAR2 (1)		Indicates whether the parameter value can be modified when the task is not in its initial state (Y) or not (N)
DESCRIPTION	VARCHAR2 (4000)		Optional description of the parameter
PARAMETER_FLAGS	NUMBER	NOT NULL	Reserved for internal use
PARAMETER_TYPE#	NUMBER	NOT NULL	Reserved for internal use

DBA_ADVISOR_EXECUTION_TYPES

DBA_ADVISOR_EXECUTION_TYPES displays possible execution action for a given advisor. Only advisors that support multiple executions of their tasks have entries in this view.

Column	Datatype	NULL	Description
ADVISOR_NAME	VARCHAR2 (30)	NOT NULL	Name of the advisor
EXECUTION_TYPE	VARCHAR2 (30)	NOT NULL	Execution type supported by the advisor
EXECUTION_DESCRIPTION	VARCHAR2 (4000)		Optional description of the execution type

DBA_ADVISOR_EXECUTIONS

DBA_ADVISOR_EXECUTIONS displays metadata information for task executions. For example, the SQL Performance Analyzer creates a minimum of three executions to perform a change impact analysis on a SQL workload. The first one collects performance data for the version of the workload before the change, the second one collects data for the version of the workload after the change, and the third one performs impact analysis. All of these executions belong to the same task and are grouped into this view. Similarly, the automatic SQL tuning task, SYS_AUTO_SQL_TUNING_TASK, creates a new execution for each tuning run.

Related View

USER_ADVISOR_EXECUTIONS displays metadata information for task executions owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
EXECUTION_NAME	VARCHAR2 (30)	NOT NULL	Name of the task execution with which this entry (row) is associated
EXECUTION_ID	NUMBER	NOT NULL	Execution ID
DESCRIPTION	VARCHAR2 (256)		User-supplied description of the task
EXECUTION_TYPE	VARCHAR2 (30)		Type of the last execution (optional for single-execution tasks)
EXECUTION_TYPE#	NUMBER		Reserved for internal use
EXECUTION_START	DATE		Execution start date and time
EXECUTION_LAST_MODIFIED	DATE	NOT NULL	Last modified date and time for the execution
EXECUTION_END	DATE		Execution end date and time
ADVISOR_NAME	VARCHAR2 (30)		Advisor associated with the task
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
STATUS	VARCHAR2 (11)		Current operational status of the task: - EXECUTING - COMPLETED - INTERRUPTED - CANCELLED - FATAL ERROR
STATUS#	NUMBER	NOT NULL	Reserved for internal use

Column	Datatype	NULL	Description
STATUS_MESSAGE	VARCHAR2 (4000)		Informational message provided by the advisor regarding the status
ERROR_MESSAGE	VARCHAR2 (4000)		Informational message or an error message indicating the current operation or condition

DBA_ADVISOR_FDG_BREAKDOWN

DBA_ADVISOR_FDG_BREAKDOWN describes the contribution from the different instances to the findings for each ADDM task. This view is populated only with ADDM tasks that are analyzing multiple instances (that is, the ACTUAL_ANALYSIS column in the task's row in DBA_ADDM_TASKS is set to DATABASE or PARTIAL).

Related View

USER_ADVISOR_FDG_BREAKDOWN describes the contribution from the different instances to the findings for each ADDM task owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task (see DBA_ADVISOR_TASKS and DBA_ADDM_TASKS)
FINDING_ID	NUMBER	NOT NULL	Identifier of the finding to which this breakdown applies (see DBA_ADVISOR_FINDINGS and DBA_ADDM_FINDINGS)
INSTANCE_NUMBER	NUMBER	NOT NULL	The number of the instance for the breakdown
IMPACT	NUMBER		The database time (in microseconds) of the finding in the instance
PERC_IMPACT	NUMBER		Percentage of the contribution of the instance to the overall finding's impact
EXECUTION_NAME	VARCHAR2 (30)		The name of the task execution with which this entry (row) is associated

DBA_ADVISOR_FINDING_NAMES

DBA_ADVISOR_FINDING_NAMES provides a list of all finding names registered with the Advisor Framework.

Column	Datatype	NULL	Description
ID	NUMBER		ID of the finding name
ADVISOR_NAME	VARCHAR2 (30)	NOT NULL	Advisor name
FINDING_NAME	VARCHAR2 (4000)		Finding name

DBA_ADVISOR_FINDINGS

DBA_ADVISOR_FINDINGS displays the findings discovered by all advisors in the database.

Related View

USER_ADVISOR_FINDINGS displays the findings discovered by the advisors owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
EXECUTION_NAME	VARCHAR2 (30)		The name of the task execution with which this entry (row) is associated
FINDING_ID	NUMBER	NOT NULL	Identifier of the finding
FINDING_NAME	VARCHAR2 (4000)		Name of the finding
TYPE	VARCHAR2 (11)		Type of the finding: ■ PROBLEM ■ SYMPTOM ■ ERROR ■ INFORMATION
PARENT	NUMBER	NOT NULL	Identifier of the parent finding
OBJECT_ID	NUMBER		Identifier of the associated object, if any
IMPACT_TYPE	VARCHAR2 (4000)		Impact of the finding on the system
IMPACT	NUMBER		Impact value
MESSAGE	VARCHAR2 (4000)		Message describing the finding
MORE_INFO	VARCHAR2 (4000)		Additional info associated with the finding
FILTERED	VARCHAR2 (1)		A value of Y means that the row in the view was filtered out by a directive (or a combination of directives). A value of N means that the row was not filtered.

See Also: ["USER_ADVISOR_FINDINGS"](#) on page 6-65

DBA_ADVISOR_JOURNAL

DBA_ADVISOR_JOURNAL displays the journal entries for all tasks in the database.

Related View

USER_ADVISOR_JOURNAL displays the journal entries for the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task or workload object
TASK_NAME	VARCHAR2 (30)		Name of the task or workload object
EXECUTION_NAME	VARCHAR2 (30)		The name of the task execution with which this entry (row) is associated
JOURNAL_ENTRY_SEQ	NUMBER	NOT NULL	Sequence number of the journal entry (unique for each task). This sequence number is used to order the data.
JOURNAL_ENTRY_TYPE	VARCHAR2 (12)		Type of the task: ■ FATAL ■ ERROR ■ WARNING ■ INFORMATION ■ INFORMATION[2 3 4 5 6]
JOURNAL_ENTRY	VARCHAR2 (4000)		Entry in the journal

See Also: ["USER_ADVISOR_JOURNAL"](#) on page 6-65

DBA_ADVISOR_LOG

DBA_ADVISOR_LOG displays information about the current state of all tasks in the database, as well as execution-specific data such as progress monitoring and completion status. The view contains one row for each task.

Related View

USER_ADVISOR_LOG displays information about the current state of the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
EXECUTION_START	DATE		Execution start date and time of the task
EXECUTION_END	DATE		Execution end date and time of the task
STATUS	VARCHAR2 (11)		Current operational status of the task: - INITIAL - Initial state of the task; no recommendations are present - EXECUTING - Task is currently running - COMPLETED - Task successfully completed the analysis operation. Recommendation data can be viewed and reported. - INTERRUPTED - Task analysis was interrupted by the user. Recommendation data, if present, can be viewed and reported at this time. - CANCELLED - FATAL ERROR - A fatal error occurred during the analysis operation. All recommendation data is unusable.
STATUS_MESSAGE	VARCHAR2 (4000)		Informational message provided by the advisor regarding the status
PCT_COMPLETION_TIME	NUMBER		Percent completion, in terms of time, of the task when it is executing
PROGRESS_METRIC	NUMBER		Metric that measures the progress of the task in terms of quality. Each advisor could have its own metric.
METRIC_UNITS	VARCHAR2 (64)		Unit of the metric used to measure progress
ACTIVITY_COUNTER	NUMBER		Counter that is updated frequently by the advisor, denoting that useful work is being performed
RECOMMENDATION_COUNT	NUMBER		Number of recommendations produced
ERROR_MESSAGE	VARCHAR2 (4000)		Informational message or an error message indicating the current operation or condition

See Also: ["USER_ADVISOR_LOG"](#) on page 6-65

DBA_ADVISOR_OBJECT_TYPES

DBA_ADVISOR_OBJECT_TYPES displays information about the object types used by all advisors in the database. In addition to the regular database object types (such as TABLE and INDEX), the following types are defined:

- SYSTEM
- I/O
- SGA
- PGA
- SHARED POOL
- BUFFER CACHE
- LIBRARY CACHE
- PROCESS
- SESSION
- ENQUEUE
- LATCH
- ROLLBACK SEGMENT
- FILE
- PARAMETER
- CURSOR
- SQL
- SQL WORKLOAD

Column	Datatype	NULL	Description
OBJECT_TYPE_ID	NUMBER		Type identifier
OBJECT_TYPE	VARCHAR2 (64)		Type name

DBA_ADVISOR_OBJECTS

DBA_ADVISOR_OBJECTS displays information about the objects currently referenced by all advisors in the database. Each row in the view pertains to an object instantiation.

Related View

USER_ADVISOR_OBJECTS displays information about the objects currently referenced by the advisors owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the object
OBJECT_ID	NUMBER	NOT NULL	Identifier of the object
TYPE	VARCHAR2 (64)		Name of the type
TYPE_ID	NUMBER	NOT NULL	Type identifier number
TASK_ID	NUMBER	NOT NULL	Task referencing the object
TASK_NAME	VARCHAR2 (30)		Name of the task
EXECUTION_NAME	VARCHAR2 (30)		The name of the task execution with which this entry (row) is associated
ATTR1	VARCHAR2 (4000)		Attributes and identifier of the object
ATTR2	VARCHAR2 (4000)		Attributes and identifier of the object

Column	Datatype	NULL	Description
ATTR3	VARCHAR2 (4000)		Attributes and identifier of the object
ATTR4	CLOB		Attributes and identifiers that cannot be expressed in the ATTR1, ATTR2, and ATTR3 columns
ATTR5	VARCHAR2 (4000)		Attributes and identifier of the object
ATTR6	RAW (2000)		Attributes and identifier of the object
ATTR7	NUMBER		Attributes and identifier of the object
ATTR8	NUMBER		Attributes and identifier of the object
ATTR9	NUMBER		Attributes and identifier of the object
ATTR10	NUMBER		Attributes and identifier of the object
OTHER	CLOB		Other attributes and identifiers of the object

Note: The definition of the ATTR_n columns depends on the advisors that are using the object. For example, the SQL object type defines the attribute columns as follows:

- ATTR1 contains the SQL ID
- ATTR2 contains the SQL address (in the cursor cache)
- ATTR4 contains the SQL text

See Also: ["USER_ADVISOR_OBJECTS"](#) on page 6-66

DBA_ADVISOR_PARAMETERS

DBA_ADVISOR_PARAMETERS displays all task parameters and their current values in the database. This data is accessible by all tasks.

Related View

USER_ADVISOR_PARAMETERS displays the task parameters and their current values for the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task or workload object
TASK_ID	NUMBER	NOT NULL	Unique identifier number of the task or workload object
TASK_NAME	VARCHAR2 (30)		Name of the task or workload object
PARAMETER_NAME	VARCHAR2 (30)	NOT NULL	Name of the parameter
PARAMETER_VALUE	VARCHAR2 (4000)	NOT NULL	Value of the parameter. Numeric parameter values are converted to a string equivalent. Possible keywords as values: ■ ALL ■ UNLIMITED ■ UNUSED

Column	Datatype	NULL	Description
PARAMETER_TYPE	VARCHAR2 (10)		Datatype of the parameter: - NUMBER - Numeric value - STRING - String value. If the string contains special characters, then it will be enclosed in single quotes. - STRINGLIST - Comma-separated list of string elements. If a string element contains a comma or other special characters, then the element will be enclosed in single quotes. - TABLE - Single table reference. A reference will contain a schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported. - TABLELIST - List of one or more comma-separated table references. A reference will contain schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported.
IS_DEFAULT	VARCHAR2 (1)		Indicates whether the parameter value is set to the advisor's default value (Y) or not (N)
IS_OUTPUT	VARCHAR2 (1)		Indicates whether the task execution process sets the parameter value (Y) or not (N)
IS_MODIFIABLE_ANYTIME	VARCHAR2 (1)		Indicates whether the parameter value can be modified when the task is not in its initial state (Y) or not (N)
DESCRIPTION	VARCHAR2 (4000)		Optional description of the parameter
EXECUTION_TYPE	VARCHAR2 (30)		For advisors supporting multiple executions, the type of execution this parameter pertains to

See Also: ["USER_ADVISOR_PARAMETERS"](#) on page 6-66

DBA_ADVISOR_RATIONALE

DBA_ADVISOR_RATIONALE displays information about the rationales for all recommendations in the database.

Related View

USER_ADVISOR_RATIONALE displays information about the rationales for the recommendations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
EXECUTION_NAME	VARCHAR2 (30)		The name of the task execution with which this entry (row) is associated
REC_ID	NUMBER		Recommendation associated with the rationale
RATIONALE_ID	NUMBER	NOT NULL	Unique identifier for the rationale
IMPACT_TYPE	VARCHAR2 (4000)		Impact on the system due to the problem described in the rationale. The impact can be described in terms of time, cost, or % degradation.

Column	Datatype	NULL	Description
IMPACT	NUMBER		Calculated impact value
MESSAGE	VARCHAR2 (4000)		Message containing an overview of the rationale
OBJECT_ID	NUMBER		Identifier of an object specified in the DBA_ADVISOR_OBJECTS view
TYPE	VARCHAR2 (30)		Type of the rationale; defines what data exists in the attribute columns and how to interpret it: - TEXT - Text sentence for descriptive messages. The ATTR1 column contains the text. - CHART - Chart containing data to be displayed. The ATTR1 column contains the data.
ATTR1	VARCHAR2 (4000)		Parameters defining the rationale
ATTR2	VARCHAR2 (4000)		Parameters defining the rationale
ATTR3	VARCHAR2 (4000)		Parameters defining the rationale
ATTR4	VARCHAR2 (4000)		Parameters defining the rationale
ATTR5	CLOB		Parameters defining the rationale

See Also: ["USER_ADVISOR_RATIONALE"](#) on page 6-66

DBA_ADVISOR_RECOMMENDATIONS

DBA_ADVISOR_RECOMMENDATIONS displays the results of an analysis of all recommendations in the database. A recommendation can have multiple actions associated with it. Actions are described in the DBA_ADVISOR_ACTIONS view. A recommendation also points to a set of rationales that present a justification/reasoning for that recommendation. These rationales are in the DBA_ADVISOR_RATIONALE view.

Related View

USER_ADVISOR_RECOMMENDATIONS displays the results of an analysis of the recommendations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
REC_ID	NUMBER	NOT NULL	Unique identifier of the recommendation
TASK_ID	NUMBER	NOT NULL	Task that owns the recommendation
TASK_NAME	VARCHAR2 (30)		Name of the task
EXECUTION_NAME	VARCHAR2 (30)		The name of the task execution with which this entry (row) is associated
FINDING_ID	NUMBER		Unique identifier of the finding
TYPE	VARCHAR2 (30)		Type of the recommendation
RANK	NUMBER		Ranking, in terms of importance, within the set of recommendations generated for the task
PARENT_REC_IDS	VARCHAR2 (4000)		Comma-separated list of the recommendation IDs of the parent recommendations. If this column is nonzero, then the recommendation depends on the parents, and cannot be accepted if the parents are not accepted.

Column	Datatype	NULL	Description
BENEFIT_TYPE	VARCHAR2 (4000)		Describes the benefit obtained by carrying out the recommendation If there is a set of parents for the recommendation, then the benefit is the cumulative benefit (the improvement in system performance when this and all prior parent recommendations are accepted). If there are no parents, then this is the improvement when the recommendation is accepted, independent of other recommendations.
BENEFIT	NUMBER		Calculated benefit value
ANNOTATION_STATUS	VARCHAR2 (11)		When a task is complete, the recommendations are marked ACCEPT. The status can be changed later using the MARK_RECOMMENDATION procedure: - ACCEPT - Current recommendation is ready to implement. This recommendation can also be used as advice for future analysis operations. - REJECT - Current recommendation is not acceptable to the user, and therefore will be excluded from any implementation scripts. This recommendation can also be used as advice for future analysis operations. - IGNORE - Though not rejected, the current recommendation will be ignored when generating scripts and will never be used as advice to future analysis operations.
FLAGS	NUMBER		Advisor-specific flags
FILTERED	VARCHAR2 (1)		A value of Y means that the row in the view was filtered out by a directive (or a combination of directives). A value of N means that the row was not filtered.

See Also: ["USER_ADVISOR_RECOMMENDATIONS"](#) on page 6-66

DBA_ADVISOR_SQLA_REC_SUM

DBA_ADVISOR_SQLA_REC_SUM displays recommendation rollup information for all workload objects in the database after an Access Advisor analysis operation.

Related View

USER_ADVISOR_SQLA_REC_SUM displays recommendation rollup information for the workload objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER		Unique identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
REC_ID	NUMBER		Identifier of the recommendation
TOTAL_STMTS	NUMBER		Total number of statements processed during analysis
TOTAL_PRECOST	NUMBER		Total cost of executing the statements in which the recommended object will be utilized, prior to the recommendations
TOTAL_POSTCOST	NUMBER		Total cost of executing the statements in which the recommended object will be utilized, after the recommendations have been implemented

See Also: ["USER_ADVISOR_SQLA_REC_SUM"](#) on page 6-66

DBA_ADVISOR_SQLA_TABLES

DBA_ADVISOR_SQLA_TABLES displays cross references between the workload statements and the tables referenced in the statement.

Related View

USER_ADVISOR_SQLA_TABLES displays cross references between the workload statements and the tables referenced in the statement for the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the workload object
TASK_ID	NUMBER		Unique identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
SQL_ID	VARCHAR2 (13)		SQL identifier of the parent cursor in the library cache
STMT_ID	NUMBER		Statement ID
TABLE_OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Table name

DBA_ADVISOR_SQLA_WK_MAP

DBA_ADVISOR_SQLA_WK_MAP displays the workload references for all tasks in the database. Workload references are necessary to allow the SQL Access Advisor to find required workload data.

Related View

USER_ADVISOR_SQLA_WK_MAP displays the workload references for the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER		Unique identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
WORKLOAD_ID	NUMBER		Unique identifier of the workload object
WORKLOAD_NAME	VARCHAR2 (30)		Name of the workload
IS_STS	NUMBER		Type of workload source: 0 - SQL workload object 1 - SQL Tuning Set

See Also: ["USER_ADVISOR_SQLA_WK_MAP"](#) on page 6-66

DBA_ADVISOR_SQLA_WK_STMTS

DBA_ADVISOR_SQLA_WK_STMTS displays information about all workload objects in the database after an Access Advisor analysis operation.

Related View

USER_ADVISOR_SQLA_WK_STMTS displays information about the workload objects owned by the current user after an Access Advisor analysis operation. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
SQLSET_ID	NUMBER		ID of the SQL tuning set for the statement
SQLSET_NAME	VARCHAR2 (30)		Name of the SQL tuning set for the statement
WORKLOAD_NAME	VARCHAR2 (30)		Name of the workload
SQL_ID	NUMBER	NOT NULL	Generated identifier of the statement
SQL_SEQ	NUMBER	NOT NULL	SQL sequence
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line-by-line).
PARSING_SCHEMA_NAME	VARCHAR2 (30)		Schema name that was used to originally build this child cursor
USERNAME	VARCHAR2 (30)		Name of the user executing the statement
MODULE	VARCHAR2 (64)		Name of the module issuing the statement
ACTION	VARCHAR2 (64)		Module action for the statement
CPU_TIME	NUMBER		Total CPU count (in seconds) of the executing statement
BUFFER_GETS	NUMBER		Total number of buffer gets for the statement
DISK_READS	NUMBER		Total disk-read I/O count for the statement
ELAPSED_TIME	NUMBER		Total elapsed time (in seconds) of the executing statement
ROWS_PROCESSED	NUMBER		Total number of rows processed by the statement
EXECUTIONS	NUMBER		Total number of times the statement was executed
FIRST_LOAD_TIME	DATE		Load time of parent cursor
LAST_EXECUTION_DATE	DATE		Date on which the statement was last executed
PRIORITY	NUMBER		Business importance of the statement: ■ 1 - High ■ 2 - Medium ■ 3 - Low
COMMAND_TYPE	NUMBER		Type of the command
STAT_PERIOD	NUMBER		Unused
ACTIVE_STAT_PERIOD	NUMBER		Effective period of time (in seconds) during which the SQL statement was active
SQL_TEXT	CLOB		Text of the SQL statement
PRE COST	NUMBER		Cost of executing the statement in the workload prior to the recommendations
POST COST	NUMBER		Cost of executing the statement in the workload after the recommendations
IMPORTANCE	NUMBER		Advisor-calculated importance value
REC_ID	NUMBER		Associated recommendation identifier

Column	Datatype	NULL	Description
VALIDATED	NUMBER		Indicates whether the statement is valid for analysis: 0 - Statement will not be analyzed by the EXECUTE_TASK procedure. Typically, the statement references one or more tables that do not have valid statistics. To correct this problem, ensure that the tables have valid statistics and execute the RESET_SQLWKLID procedure on the current workload. 1 - Statement is eligible for analysis by the EXECUTE_TASK procedure

See Also: ["USER_ADVISOR_SQLA_WK_STMTS"](#) on page 6-67

DBA_ADVISOR_SQLPLANS

DBA_ADVISOR_SQLPLANS displays the different SQL execution plans generated as part of an advisor analysis.

Related View

USER_ADVISOR_SQLPLANS displays the different SQL execution plans owned by the current user generated as part of an advisor analysis.

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2 (30)		Advisor task name in which the SQL plan was generated (see DBA_ADVISOR_TASKS)
TASK_ID	NUMBER (38)	NOT NULL	Advisor task ID in which the SQL plan was generated (see DBA_ADVISOR_TASKS)
EXECUTION_NAME	VARCHAR2 (30)	NOT NULL	Advisor task execution in which the SQL plan was generated (see DBA_ADVISOR_EXECUTIONS)
SQL_ID	VARCHAR2 (13)	NOT NULL	Identifier for the relevant SQL statement
OBJECT_ID	NUMBER (38)	NOT NULL	Advisor object ID identifying the relevant SQL statement (see DBA_ADVISOR_OBJECTS)
ATTRIBUTE	VARCHAR2 (27)		Text string identifying the type of the execution plan. The following values are used by the SQL Tuning Advisor: - Original - Original plan of the query - Original with adjusted cost - Same as Original but with adjusted cost - Using SQL profile - Plan with SQL profile applied - Using new indices - Plan with indexes applied
STATEMENT_ID	VARCHAR2 (30)		Optional statement identifier specified in the EXPLAIN PLAN statement
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the execution plan
PLAN_ID	NUMBER	NOT NULL	Plan identifier
TIMESTAMP	DATE		Date and time when the EXPLAIN PLAN statement was issued
REMARKS	VARCHAR2 (4000)		Place for comments that can be added to the steps of the execution plan
OPERATION	VARCHAR2 (30)		Name of the operation performed at this step
OPTIONS	VARCHAR2 (255)		Options used for the operation performed at this step
OBJECT_NODE	VARCHAR2 (128)		Name of the database link used to reference the object
OBJECT_OWNER	VARCHAR2 (30)		Owner of the object

Column	Datatype	NULL	Description
OBJECT_NAME	VARCHAR2 (30)		Name of the object
OBJECT_ALIAS	VARCHAR2 (65)		Object alias
OBJECT_INSTANCE	NUMBER (38)		Numbered position of the object name in the original SQL statement
OBJECT_TYPE	VARCHAR2 (30)		Descriptive modifier that further describes the type of object
OPTIMIZER	VARCHAR2 (255)		Current mode of the optimizer
SEARCH_COLUMNS	NUMBER		Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
ID	NUMBER (38)	NOT NULL	Identification number for this step in the execution plan
PARENT_ID	NUMBER (38)		ID of the next step that operates on the results of this step
DEPTH	NUMBER (38)		Depth
POSITION	NUMBER (38)		Order of processing for steps with the same parent ID
COST	NUMBER (38)		Cost of the current operation estimated by the cost-based optimizer (CBO)
CARDINALITY	NUMBER (38)		Number of rows returned by the current operation (estimated by the CBO)
BYTES	NUMBER (38)		Number of bytes returned by the current operation
OTHER_TAG	VARCHAR2 (255)		Describes the function of the SQL text in the OTHER column. Values for OTHER_TAG are: - SERIAL - SQL is the text of a locally-executed, serial query plan. Currently, SQL is not loaded in OTHER for this case. - SERIAL_FROM_REMOTE - SQL text shown in the OTHER column will be executed at a remote site - PARALLEL_COMBINED_WITH_PARENT - Parent of this operation is a DFO that performs both operations in the parallel execution plan - PARALLEL_COMBINED_WITH_CHILD - Child of this operation is a DFO that performs both operations in the parallel execution plan. - PARALLEL_TO_SERIAL - SQL text shown in the OTHER column is the top-level of the parallel plan. - PARALLEL_TO_PARALLEL - SQL text shown in the OTHER column is executed and output in parallel - PARALLEL_FROM_SERIAL - Operation consumes data from a serial operation and outputs it in parallel
PARTITION_START	VARCHAR2 (255)		Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2 (255)		Stop partition of a range of accessed partitions
PARTITION_ID	NUMBER (38)		Step that has computed the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	LONG		Information about parallel execution servers and parallel queries
DISTRIBUTION	VARCHAR2 (30)		Distribution method
CPU_COST	NUMBER (38)		User-defined CPU cost
IO_COST	NUMBER (38)		User-defined I/O cost
TEMP_SPACE	NUMBER (38)		Temporary space usage of the operation (sort or hash-join) as estimated by the CBO
ACCESS_PREDICATES	VARCHAR2 (4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2 (4000)		Predicates used to filter rows before producing them

Column	Datatype	NULL	Description
PROJECTION	VARCHAR2 (4000)		Expressions produced by the operation
TIME	NUMBER (38)		Elapsed time (in seconds) of the operation as estimated by the CBO
QBLOCK_NAME	VARCHAR2 (30)		Name of the query block
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML because it allows multiple pieces of information to be stored, including the following: - Name of the schema against which the query was parsed - Release number of the Oracle Database that produced the explain plan - Hash value associated with the execution plan - Name (if any) of the outline or the SQL profile used to build the execution plan - Indication of whether or not dynamic sampling was used to produce the plan - The outline data, a set of optimizer hints that can be used to regenerate the same plan

DBA_ADVISOR_SQLSTATS

DBA_ADVISOR_SQLSTATS displays execution statistics for the test-execution of different SQL plans during the advisor analysis.

Related View

USER_ADVISOR_SQLSTATS displays execution statistics owned by the current user for the test-execution of different SQL plans during the advisor analysis.

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2 (30)		Advisor task name in which the SQL statement was executed (see DBA_ADVISOR_TASKS)
TASK_ID	NUMBER (38)	NOT NULL	Advisor task ID in which the SQL statement was executed (see DBA_ADVISOR_TASKS)
EXECUTION_NAME	VARCHAR2 (30)	NOT NULL	Advisor task execution in which the SQL statement was executed (see DBA_ADVISOR_EXECUTIONS)
EXECUTION_TYPE	VARCHAR2 (30)		Type of the advisor task execution in which the SQL statement was executed (see DBA_ADVISOR_EXECUTIONS)
OBJECT_ID	NUMBER (38)	NOT NULL	Advisor object ID identifying the relevant SQL statement (see DBA_ADVISOR_OBJECTS)
PLAN_ID	NUMBER	NOT NULL	Plan ID number generated to uniquely identify a plan for a particular SQL statement (foreign key to DBA_ADVISOR_SQLPLANS)
SQL_ID	VARCHAR2 (13)	NOT NULL	Identifier for the SQL statement executed
PLAN_HASH_VALUE	NUMBER	NOT NULL	Hash value of the SQL execution plan
ATTR1	NUMBER		Reserved for internal use
PARSE_TIME	NUMBER		Parse time (in microseconds) measured for the SQL
ELAPSED_TIME	NUMBER		Elapsed time (in microseconds) to execute the SQL and fetch all of its rows, after parsing
CPU_TIME	NUMBER		CPU time (in microseconds) to execute the SQL and fetch all of its rows, after parsing

Column	Datatype	NULL	Description
USER_IO_TIME	NUMBER		I/O time (in microseconds) to execute the SQL and fetch all of its rows, after parsing
BUFFER_GETS	NUMBER		Number of buffer gets measured for executing the SQL and fetching all of its rows
DISK_READS	NUMBER		Number of disk reads measured for executing the SQL and fetching all of its rows
DIRECT_WRITES	NUMBER		Number of direct writes measured for executing the SQL and fetching all of its rows
PHYSICAL_READ_REQUESTS	NUMBER		Number of physical read I/O requests issued by the monitored SQL
PHYSICAL_WRITE_REQUESTS	NUMBER		Number of physical write I/O requests issued by the monitored SQL
PHYSICAL_READ_BYTES	NUMBER		Number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_BYTES	NUMBER		Number of bytes written to disks by the monitored SQL
ROWS_PROCESSED	NUMBER		Number of rows returned by the SQL execution
FETCHES	NUMBER		Number of fetches for the SQL execution
EXECUTIONS	NUMBER		Execution count for the SQL. This column will always have a value of 1 or 0.
END_OF_FETCH_COUNT	NUMBER		Indicates whether the SQL was executed to end-of-fetch (1) or not (0)
OPTIMIZER_COST	NUMBER		Optimizer cost for the execution plan
OTHER	CLOB		Reserved for future use
TESTEXEC_TOTAL_EXECS	NUMBER		Total number of executions during test execute
IO_INTERCONNECT_BYTES	NUMBER		Number of I/O bytes exchanged between Oracle Database and the storage system
TESTEXEC_FIRST_EXEC_IGNORED	VARCHAR2 (1)		Indicates whether the first execution in test execute is ignored (Y) or not (N)

DBA_ADVISOR_SQLW_JOURNAL

DBA_ADVISOR_SQLW_JOURNAL displays the journal entries for all workload objects in the database.

Related View

USER_ADVISOR_SQLW_JOURNAL displays the journal entries for the workload objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the workload
WORKLOAD_ID	NUMBER	NOT NULL	Identifier number of the workload object
WORKLOAD_NAME	VARCHAR2 (30)		Name of the workload object
JOURNAL_ENTRY_SEQ	NUMBER	NOT NULL	Sequence number of the journal entry (unique for each workload). The sequence number is used to order the data.
JOURNAL_ENTRY_TYPE	VARCHAR2 (12)		Type of the task: - FATAL - ERROR - WARNING - INFORMATION - INFORMATION[2 3 4 5 6]

Column	Datatype	NULL	Description
JOURNAL_ENTRY	VARCHAR2 (4000)		Entry in the journal

See Also: ["USER_ADVISOR_SQLW_JOURNAL"](#) on page 6-67

DBA_ADVISOR_SQLW_PARAMETERS

DBA_ADVISOR_SQLW_PARAMETERS displays all workload parameters and their current values in the database.

Related View

USER_ADVISOR_SQLW_PARAMETERS displays the workload parameters and their current values owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task or workload object
WORKLOAD_ID	NUMBER	NOT NULL	Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2 (30)		Name of the workload object
PARAMETER_NAME	VARCHAR2 (30)	NOT NULL	Name of the parameter
PARAMETER_VALUE	VARCHAR2 (4000)	NOT NULL	Value of the parameter. Numeric parameter values are converted to a string equivalent. Possible keywords as values: - ALL - UNLIMITED - UNUSED
PARAMETER_TYPE	VARCHAR2 (10)		Datatype of the parameter: - NUMBER - Numeric value - STRING - String value. If the string contains special characters, then it will be enclosed in single quotes. - STRINGLIST - Comma-separated list of string elements. If a string element contains a comma or other special characters, then the element will be enclosed in single quotes. - TABLE - Single table reference. A reference contains a schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported. - TABLELIST - List of one or more comma-separated table references. A reference contains a schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported.

See Also: ["USER_ADVISOR_SQLW_PARAMETERS"](#) on page 6-67

DBA_ADVISOR_SQLW_STMTS

DBA_ADVISOR_SQLW_STMTS displays rows that correspond to all statements in the workload. All columns are guaranteed to be non-null.

Related View

USER_ADVISOR_SQLW_STMTS displays rows that correspond to the statements in the workload owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the workload object
WORKLOAD_ID	NUMBER	NOT NULL	Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2 (30)		Name of the workload
SQL_ID	NUMBER	NOT NULL	Generated identifier of the statement
HASH_VALUE	NUMBER		Hash value for the parent statement in the cache
USERNAME	VARCHAR2 (30)		Name of the user executing the statement
MODULE	VARCHAR2 (64)		Name of the module issuing the statement
ACTION	VARCHAR2 (64)		Module action for the statement
CPU_TIME	NUMBER		Total CPU count (in seconds) of the executing statement
BUFFER_GETS	NUMBER		Total number of buffer gets for the statement
DISK_READS	NUMBER		Total disk-read I/O count for the statement
ELAPSED_TIME	NUMBER		Total elapsed time (in seconds) of the executing statement
ROWS_PROCESSED	NUMBER		Total number of rows processed by the statement
EXECUTIONS	NUMBER		Total number of times the statement was executed
OPTIMIZER_COST	NUMBER		Cost of executing the statement in the workload prior to the recommendations
LAST_EXECUTION_DATE	DATE		Date on which the statement was last executed
PRIORITY	NUMBER		Priority of the statement: 1 - High 2 - Medium 3 - Low
COMMAND_TYPE	NUMBER		Type of the command
STAT_PERIOD	NUMBER		Unused
SQL_TEXT	CLOB		Text of the SQL statement
VALID	NUMBER		Indicates whether the statement is valid for analysis: 0 - Statement will not be analyzed by the EXECUTE_TASK procedure. Typically, the statement references one or more tables that do not have valid statistics. To correct this problem, ensure that the tables have valid statistics and execute the RESET_SQLWKLD procedure on the current workload. 1 - Statement is eligible for analysis by the EXECUTE_TASK procedure.

See Also: ["USER_ADVISOR_SQLW_STMTS"](#) on page 6-67

DBA_ADVISOR_SQLW_SUM

DBA_ADVISOR_SQLW_SUM displays an aggregated picture of all SQLWkld workload objects in the database.

Related View

USER_ADVISOR_SQLW_SUM displays an aggregated picture of the SQLWkld workload objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the workload object
WORKLOAD_ID	NUMBER	NOT NULL	Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2 (30)		Unique name of the workload
DESCRIPTION	VARCHAR2 (256)		User-specified description of the workload
CREATE_DATE	DATE	NOT NULL	Date on which the workload object was created
MODIFY_DATE	DATE	NOT NULL	Date of last update to the current workload
NUM_SELECT_STMT	NUMBER		Number of SELECT statements in the workload
NUM_UPDATE_STMT	NUMBER		Number of UPDATE statements in the workload
NUM_DELETE_STMT	NUMBER		Number of DELETE statements in the workload
NUM_INSERT_STMT	NUMBER		Number of INSERT statements in the workload
NUM_MERGE_STMT	NUMBER		Number of MERGE statements in the workload
SOURCE	VARCHAR2 (30)		Optional name that identifies the creator of the object
HOW_CREATED	VARCHAR2 (30)		Optional object or template on which the object was based
DATA_SOURCE	VARCHAR2 (2000)		Workload data source
READ_ONLY	VARCHAR2 (5)		Indicates whether or not the workload can be modified or deleted (TRUE) or not (FALSE)

See Also: ["USER_ADVISOR_SQLW_SUM"](#) on page 6-67

DBA_ADVISOR_SQLW_TABLES

DBA_ADVISOR_SQLW_TABLES displays cross references between the workload statements and the tables referenced in the statement.

Related View

USER_ADVISOR_SQLW_TABLES displays cross references between the workload statements and the tables referenced in the statement. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the workload object
WORKLOAD_ID	NUMBER		Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2 (30)		Name of the workload
SQL_ID	NUMBER		Identifier of the statement
TABLE_OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table

See Also: ["USER_ADVISOR_SQLW_TABLES"](#) on page 6-68

DBA_ADVISOR_SQLW_TEMPLATES

DBA_ADVISOR_SQLW_TEMPLATES displays an aggregated picture of all SQLWkld template objects in the database.

Related View

USER_ADVISOR_SQLW_TEMPLATES displays an aggregated picture of the SQLWkld template objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the workload object
WORKLOAD_ID	NUMBER	NOT NULL	Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2 (30)		Unique name of the workload
DESCRIPTION	VARCHAR2 (256)		User-specified description of the workload
CREATE_DATE	DATE	NOT NULL	Date on which the workload object was created
MODIFY_DATE	DATE	NOT NULL	Date of last update to the current workload
SOURCE	VARCHAR2 (30)		Optional object or template on which the object was based
READ_ONLY	VARCHAR2 (5)		Indicates whether the workload template can be modified or deleted (TRUE) or not (FALSE)

See Also: ["USER_ADVISOR_SQLW_TEMPLATES"](#) on page 6-68

DBA_ADVISOR_TASKS

DBA_ADVISOR_TASKS displays information about all tasks in the database. The view contains one row for each task. Each task has a name that is unique to the owner. Task names are just informational and no uniqueness is enforced within any other namespace.

Related View

USER_ADVISOR_TASKS displays information about the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
DESCRIPTION	VARCHAR2 (256)		User-supplied description of the task
ADVISOR_NAME	VARCHAR2 (30)		Advisor associated with the task
CREATED	DATE	NOT NULL	Creation date of the task
LAST_MODIFIED	DATE	NOT NULL	Date on which the task was last modified
PARENT_TASK_ID	NUMBER		Identifier of the parent task (if the task was created as a result of the recommendation of another task)
PARENT_RXEC_ID	NUMBER		Identifier of the recommendation within the parent task that resulted in the creation of the task
LAST_EXECUTION	VARCHAR2 (30)		Name of the current or last task execution
EXECUTION_TYPE	VARCHAR2 (30)		Type of the last execution. This information is optional for single-execution tasks.
EXECUTION_TYPE#	NUMBER		Reserved for internal use
EXECUTION_DESCRIPTION	VARCHAR2 (256)		Optional description of the last execution
EXECUTION_START	DATE		Execution start date and time of the task
EXECUTION_END	DATE		Execution end date and time of the task

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (11)		Current operational status of the task: - INITIAL - Initial state of the task; no recommendations are present - EXECUTING - Task is currently running - INTERRUPTED - Task analysis was interrupted by the user. Recommendation data, if present, can be viewed and reported at this time. - COMPLETED - Task successfully completed the analysis operation. Recommendation data can be viewed and reported. - ERROR - An error occurred during the analysis operation. Recommendations, if present, can be viewed and reported at this time.
STATUS_MESSAGE	VARCHAR2 (4000)		Informational message provided by the advisor regarding the status
PCT_COMPLETION_TIME	NUMBER		Percent completion, in terms of time, of the task when it is executing
PROGRESS_METRIC	NUMBER		Metric that measures the progress of the task in terms of quality. Each advisor may have its own metric.
METRIC_UNITS	VARCHAR2 (64)		Unit of the metric used to measure progress
ACTIVITY_COUNTER	NUMBER		Counter that is updated frequently by the advisor, denoting that useful work is being performed
RECOMMENDATION_COUNT	NUMBER		Number of recommendations produced
ERROR_MESSAGE	VARCHAR2 (4000)		Informational message or an error message indicating the current operation or condition
SOURCE	VARCHAR2 (30)		Optional name that identifies the creator of the task
HOW_CREATED	VARCHAR2 (30)		Optional task or template on which the object was based
READ_ONLY	VARCHAR2 (5)		Indicates whether the task is read-only (TRUE) or not (FALSE)
SYSTEM_TASK	VARCHAR2 (5)		Indicates whether the task is a system task (TRUE) or not (FALSE). The automatic SQL tuning task, SYS_AUTO_SQL_TUNING_TASK, is one example of a system task.
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
STATUS#	NUMBER		Reserved for internal use

See Also: ["USER_ADVISOR_TASKS"](#) on page 6-68

DBA_ADVISOR_TEMPLATES

DBA_ADVISOR_TEMPLATES displays information about all templates in the database.

Related View

USER_ADVISOR_TEMPLATES displays information about the templates owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
DESCRIPTION	VARCHAR2 (256)		User-supplied description of the task
ADVISOR_NAME	VARCHAR2 (30)		Advisor associated with the task

Column	Datatype	NULL	Description
CREATED	DATE	NOT NULL	Creation date of the task
LAST_MODIFIED	DATE	NOT NULL	Date on which the task was last modified
SOURCE	VARCHAR2 (30)		Optional task or template on which the template was based
READ_ONLY	VARCHAR2 (5)		Indicates whether the task can be modified or deleted (TRUE) or not (FALSE)

See Also: ["USER_ADVISOR_TEMPLATES"](#) on page 6-68

DBA_ADVISOR_USAGE

DBA_ADVISOR_USAGE displays the usage information for each type of advisor in the database.

Column	Datatype	NULL	Description
ADVISOR_ID	NUMBER	NOT NULL	Type of the advisor
LAST_EXEC_TIME	DATE	NOT NULL	Date of the last execution
NUM_EXECS	NUMBER	NOT NULL	Cumulative number of executions

DBA_ALERT_HISTORY

DBA_ALERT_HISTORY describes a time-limited history of alerts which are no longer outstanding.

Column	Datatype	NULL	Description
SEQUENCE_ID	NUMBER	NOT NULL	Alert sequence number
REASON_ID	NUMBER		ID of the alert reason
OWNER	VARCHAR2 (30)		Owner of the object on which the alert was issued
OBJECT_NAME	VARCHAR2 (513)		Name of the object
SUBOBJECT_NAME	VARCHAR2 (30)		Name of the subobject
OBJECT_TYPE	VARCHAR2 (64)		Object type
REASON	VARCHAR2 (4000)		Reason for the alert
TIME_SUGGESTED	TIMESTAMP (6) WITH TIME ZONE		Time when the alert was last updated
CREATION_TIME	TIMESTAMP (6) WITH TIME ZONE		Time when the alert was first produced
SUGGESTED_ACTION	VARCHAR2 (4000)		Advice of the recommended action
ADVISOR_NAME	VARCHAR2 (30)		Name of the advisor to be invoked for more information
METRIC_VALUE	NUMBER		Value of the related metrics
MESSAGE_TYPE	VARCHAR2 (12)		Message type: ■ Notification ■ Warning
MESSAGE_GROUP	VARCHAR2 (64)		Name of the message group to which the alert belongs
MESSAGE_LEVEL	NUMBER		Severity message level (1 to 32)
HOSTING_CLIENT_ID	VARCHAR2 (64)		ID of the client or security group to which the alert relates
MODULE_ID	VARCHAR2 (64)		ID of the module that originated the alert

Column	Datatype	NULL	Description
PROCESS_ID	VARCHAR2 (128)		Process ID
HOST_ID	VARCHAR2 (256)		DNS host name of the originating host
HOST_NW_ADDR	VARCHAR2 (256)		IP or other network address of the originating host
INSTANCE_NAME	VARCHAR2 (16)		Originating instance name
INSTANCE_NUMBER	NUMBER		Originating instance number
USER_ID	VARCHAR2 (30)		User ID
EXECUTION_CONTEXT_ID	VARCHAR2 (60)		ID of the thread of execution
ERROR_INSTANCE_ID	VARCHAR2 (142)		ID of an error instance plus a sequence number
RESOLUTION	VARCHAR2 (7)		Resolution: - cleared - N/A

DBA_ALL_TABLES

DBA_ALL_TABLES describes all object tables and relational tables in the database. Its columns are the same as those in ALL_ALL_TABLES.

See Also: ["ALL_ALL_TABLES"](#) on page 2-5

DBA_APPLICATION_ROLES

DBA_APPLICATION_ROLES describes all the roles that have authentication policy functions defined.

Column	Datatype	NULL	Description
ROLE	VARCHAR2 (30)	NOT NULL	Name of the application role
SCHEMA	VARCHAR2 (30)	NOT NULL	Schema of the authorized package
PACKAGE	VARCHAR2 (30)	NOT NULL	Name of the authorized package

DBA_APPLY

DBA_APPLY displays information about all apply processes in the database. Its columns are the same as those in ALL_APPLY.

See Also: ["ALL_APPLY"](#) on page 2-8

DBA_APPLY_CHANGE_HANDLERS

DBA_APPLY_CHANGE_HANDLERS displays information about the change handlers on all tables in the database. Its columns are the same as those in ALL_APPLY_CHANGE_HANDLERS.

See Also: ["ALL_APPLY_CHANGE_HANDLERS"](#) on page 2-9

DBA_APPLY_CONFLICT_COLUMNS

DBA_APPLY_CONFLICT_COLUMNS displays information about the conflict handlers on all tables in the database. Its columns are the same as those in ALL_APPLY_CONFLICT_COLUMNS.

See Also: ["ALL_APPLY_CONFLICT_COLUMNS"](#) on page 2-10

DBA_APPLY_DML_HANDLERS

DBA_APPLY_DML_HANDLERS displays information about the DML handlers on all tables in the database. Its columns are the same as those in ALL_APPLY_DML_HANDLERS.

See Also: ["ALL_APPLY_DML_HANDLERS"](#) on page 2-10

DBA_APPLY_ENQUEUE

DBA_APPLY_ENQUEUE displays information about the apply enqueue actions for all rules in the database. Its columns are the same as those in ALL_APPLY_ENQUEUE.

See Also: ["ALL_APPLY_ENQUEUE"](#) on page 2-11

DBA_APPLY_ERROR

DBA_APPLY_ERROR displays information about the error transactions generated by all apply processes in the database. Its columns are the same as those in ALL_APPLY_ERROR.

See Also: ["ALL_APPLY_ERROR"](#) on page 2-12

DBA_APPLY_ERROR_MESSAGES

DBA_APPLY_ERROR_MESSAGES displays information about the individual messages in all of the error transactions generated by all apply processes in the database. Its columns are the same as those in ALL_APPLY_ERROR_MESSAGES.

Note: The DBA_APPLY_ERROR_MESSAGES view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also: ["ALL_APPLY_ERROR_MESSAGES"](#) on page 2-12

DBA_APPLY_EXECUTE

DBA_APPLY_EXECUTE displays information about the apply execute actions for all rules in the database. Its columns are the same as those in ALL_APPLY_EXECUTE.

See Also: ["ALL_APPLY_EXECUTE"](#) on page 2-13

DBA_APPLY_INSTANTIATED_GLOBAL

DBA_APPLY_INSTANTIATED_GLOBAL displays information about databases for which an instantiation SCN has been set.

Column	Datatype	NULL	Description
SOURCE_DATABASE	VARCHAR2 (128)	NOT NULL	Name of the database that was instantiated
INSTANTIATION_SCN	NUMBER		Instantiation SCN for the database. Only changes committed after this SCN are applied by an apply process.

Column	Datatype	NULL	Description
APPLY_DATABASE_LINK	VARCHAR2 (128)		Database link to which changes are applied. If null, then changes are applied to the local database.

DBA_APPLY_INSTANTIATED_OBJECTS

DBA_APPLY_INSTANTIATED_OBJECTS displays information about objects for which an instantiation SCN has been set.

Column	Datatype	NULL	Description
SOURCE_DATABASE	VARCHAR2 (128)	NOT NULL	Name of the database where the object originated
SOURCE_OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object at the source database
SOURCE_OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object at the source database
SOURCE_OBJECT_TYPE	VARCHAR2 (11)		Type of the object at the source database
INSTANTIATION_SCN	NUMBER		Instantiation SCN for the object. Only changes committed after this SCN are applied by an apply process.
IGNORE_SCN	NUMBER		SCN below which the instantiation SCN cannot be set. This value corresponds to the SCN value at the source database at the time when the object was prepared for instantiation.
APPLY_DATABASE_LINK	VARCHAR2 (128)		Database link to which changes are applied. If null, then changes are applied to the local database.

DBA_APPLY_INSTANTIATED_SCHEMAS

DBA_APPLY_INSTANTIATED_SCHEMAS displays information about schemas for which an instantiation SCN has been set.

Column	Datatype	NULL	Description
SOURCE_DATABASE	VARCHAR2 (128)	NOT NULL	Name of the database where the schema originated
SOURCE_SCHEMA	VARCHAR2 (30)		Name of the schema at the source database
INSTANTIATION_SCN	NUMBER		Instantiation SCN for the schema. Only changes committed after this SCN are applied by an apply process.
APPLY_DATABASE_LINK	VARCHAR2 (128)		Database link to which changes are applied. If null, then changes are applied to the local database.

DBA_APPLY_KEY_COLUMNS

DBA_APPLY_KEY_COLUMNS displays information about the substitute key columns for all tables in the database. Its columns are the same as those in ALL_APPLY_KEY_COLUMNS.

See Also: ["ALL_APPLY_KEY_COLUMNS"](#) on page 2-13

DBA_APPLY_OBJECT_DEPENDENCIES

DBA_APPLY_OBJECT_DEPENDENCIES displays information about the object dependencies for all apply processes in the database.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object

Column	Datatype	NULL	Description
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
PARENT_OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Parent of the object owner
PARENT_OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Parent of the named object

DBA_APPLY_PARAMETERS

DBA_APPLY_PARAMETERS displays information about the parameters for all apply processes in the database. Its columns are the same as those in ALL_APPLY_PARAMETERS.

See Also: ["ALL_APPLY_PARAMETERS"](#) on page 2-14

DBA_APPLY_PROGRESS

DBA_APPLY_PROGRESS displays information about the progress made by all apply processes in the database. Its columns are the same as those in ALL_APPLY_PROGRESS.

See Also: ["ALL_APPLY_PROGRESS"](#) on page 2-14

DBA_APPLY_SPILL_TXN

DBA_APPLY_SPILL_TXN displays information about the transactions spilled from memory to hard disk by all apply processes in the database.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2 (30)	NOT NULL	Name of the apply process that spilled one or more transactions
XIDUSN	NUMBER	NOT NULL	Transaction ID undo segment number
XIDSLT	NUMBER	NOT NULL	Transaction ID slot number
XIDSQN	NUMBER	NOT NULL	Transaction ID sequence number
FIRST_SCN	NUMBER	NOT NULL	SCN of the first message in the transaction
MESSAGE_COUNT	NUMBER		Number of messages spilled for the transaction
FIRST_MESSAGE_CREATE_TIME	DATE		Source creation time of the first message in the transaction
SPILL_CREATION_TIME	DATE		Time the first message was spilled
FIRST_POSITION	RAW (64)		Position of the first message in this transaction This column is populated only for an XStream inbound server.
TRANSACTION_ID	VARCHAR2 (128)		Transaction ID of the spilled transaction

DBA_APPLY_TABLE_COLUMNS

DBA_APPLY_TABLE_COLUMNS displays, for all tables in the database, information about the nonkey table columns for which Oracle Streams apply processes do not detect conflicts for updates and deletes. Its columns are the same as those in ALL_APPLY_TABLE_COLUMNS.

See Also: ["ALL_APPLY_TABLE_COLUMNS"](#) on page 2-15

DBA_APPLY_VALUE_DEPENDENCIES

DBA_APPLY_VALUE_DEPENDENCIES displays information about the value dependencies for all apply processes in the database.

Column	Datatype	NULL	Description
DEPENDENCY_NAME	VARCHAR2 (30)	NOT NULL	Name of the dependency
OBJECT_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column
COLUMN_POSITION	NUMBER		Position of the column

DBA_AQ_AGENT_PRIVS

DBA_AQ_AGENT_PRIVS displays information about the registered AQ agents that are mapped to all users in the database.

Related View

USER_AQ_AGENT_PRIVS displays information about the registered AQ agents that are mapped to the current user. This view does not display the DB_USERNAME column.

Column	Datatype	NULL	Description
AGENT_NAME	VARCHAR2 (30)	NOT NULL	Name of the AQ agent
DB_USERNAME	VARCHAR2 (30)		Name of the database user that the agent maps to
HTTP_ENABLED	VARCHAR2 (4)		Indicates whether the agent is allowed to access AQ through HTTP (YES) or not (NO)
SMTP_ENABLED	VARCHAR2 (4)		Indicates whether the agent is allowed to access AQ through SMTP (YES) or not (NO)

See Also: ["USER_AQ_AGENT_PRIVS"](#) on page 6-68

DBA_AQ_AGENTS

DBA_AQ_AGENTS displays information about all registered AQ agents in the database.

Column	Datatype	NULL	Description
AGENT_NAME	VARCHAR2 (30)	NOT NULL	Name of the AQ agent
HTTP_ENABLED	VARCHAR2 (4)		Indicates whether the agent is allowed to access AQ through HTTP (YES) or not (NO)
SMTP_ENABLED	VARCHAR2 (4)		Indicates whether the agent is allowed to access AQ through SMTP (YES) or not (NO)

DBA_ARGUMENTS

DBA_ARGUMENTS lists the arguments of the procedures and functions that are available in the database. Its columns are the same as those in ALL_ARGUMENTS.

See Also: ["ALL_ARGUMENTS"](#) on page 2-16

DBA_ASSEMBLIES

DBA_ASSEMBLIES provides information about all assemblies in the database. Its columns are the same as those in ALL_ASSEMBLIES.

See Also: ["ALL_ASSEMBLIES"](#) on page 2-17

DBA_ASSOCIATIONS

DBA_ASSOCIATIONS describes all user-defined statistics in the database. Its columns are the same as those in ALL_ASSOCIATIONS.

See Also: ["ALL_ASSOCIATIONS"](#) on page 2-18

DBA_ATTRIBUTE_TRANSFORMATIONS

DBA_ATTRIBUTE_TRANSFORMATIONS displays information about the transformation functions for all transformations in the database.

Related View

USER_ATTRIBUTE_TRANSFORMATIONS displays information about the transformation functions for the transformations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
TRANSFORMATION_ID	NUMBER	NOT NULL	Unique identifier for the transformation
OWNER	VARCHAR2 (30)	NOT NULL	Owning user of the transformation
NAME	VARCHAR2 (30)	NOT NULL	Transformation name
FROM_TYPE	VARCHAR2 (61)		Source type name
TO_TYPE	VARCHAR2 (91)		Target type name
ATTRIBUTE	NUMBER	NOT NULL	Target type attribute number
ATTRIBUTE_TRANSFORMATION	VARCHAR2 (4000)		Transformation function for the attribute

See Also: ["USER_ATTRIBUTE_TRANSFORMATIONS"](#) on page 6-69

DBA_AUDIT_EXISTS

DBA_AUDIT_EXISTS displays audit trail entries produced by AUDIT EXISTS and AUDIT NOT EXISTS.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2 (255)		Operating system login username of the user whose actions were audited
USERNAME	VARCHAR2 (30)		Name (not ID number) of the user whose actions were audited
USERHOST	VARCHAR2 (128)		Client host machine name
TERMINAL	VARCHAR2 (255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by AUDIT SESSION) in the local database session time zone
OWNER	VARCHAR2 (30)		Intended creator of the non-existent object

Column	Datatype	NULL	Description
OBJ_NAME	VARCHAR2 (128)		Name of the object affected by the action
ACTION_NAME	VARCHAR2 (28)		Name of the action type corresponding to the numeric code in the ACTION column in DBA_AUDIT_TRAIL
NEW_OWNER	VARCHAR2 (30)		Owner of the object named in the NEW_NAME column
NEW_NAME	VARCHAR2 (128)		New name of an object after a RENAME or the name of the underlying object
OBJ_PRIVILEGE	VARCHAR2 (16)		Object privileges granted or revoked by a GRANT or REVOKE statement
SYS_PRIVILEGE	VARCHAR2 (40)		System privileges granted or revoked by a GRANT or REVOKE statement
GRANTEE	VARCHAR2 (30)		Name of the grantee specified in a GRANT or REVOKE statement
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session
ENTRYID	NUMBER	NOT NULL	Numeric ID for each audit trail entry in the session
STATEMENTID	NUMBER	NOT NULL	Numeric ID for each statement run
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: 0 - Action succeeded 2004 - Security violation
CLIENT_ID	VARCHAR2 (64)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2 (64)		Application execution context identifier
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session
EXTENDED_TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2 (32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2 (16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW (8)		Transaction identifier of the transaction in which the object is accessed or modified
SCN	NUMBER		System change number (SCN) of the query
SQL_BIND	NVARCHAR2 (2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2 (2000)		SQL text of the query
OBJ_EDITION_NAME	VARCHAR2 (30)		Name of the edition containing the audited object

Note: The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to db, extended.

See Also: ["AUDIT_TRAIL"](#) on page 1-25

DBA_AUDIT_MGMT_CLEAN_EVENTS

DBA_AUDIT_MGMT_CLEAN_EVENTS displays information about the history of audit trail cleanup or purge events. Periodically, you should delete the contents of this view so that it will not grow too large.

Column	Datatype	NULL	Description
AUDIT_TRAIL	VARCHAR2 (28)		Audit trail that was cleaned at the time of the event: - STANDARD AUDIT TRAIL - FGA AUDIT TRAIL - STANDARD AND FGA AUDIT TRAIL - OS AUDIT TRAIL - XML AUDIT TRAIL - OS AND XML AUDIT TRAIL - ALL AUDIT TRAILS
RAC_INSTANCE	NUMBER	NOT NULL	Instance number indicating the Oracle RAC instance that was cleaned up at the time of the event; 0 implies not applicable
CLEANUP_TIME	TIMESTAMP (6) WITH TIME ZONE		Timestamp when the cleanup event completed
DELETE_COUNT	NUMBER		Number of audit records or audit files that were deleted at the time of the event
WAS_FORCED	VARCHAR2 (3)		Indicates whether a forced cleanup occurred (YES) or not (NO); forced cleanup bypasses the last archive timestamp set

DBA_AUDIT_MGMT_CLEANUP_JOBS

DBA_AUDIT_MGMT_CLEANUP_JOBS displays information about the configured audit trail purge jobs.

Column	Datatype	NULL	Description
JOB_NAME	VARCHAR2 (100)	NOT NULL	Name of the audit trail purge job
JOB_STATUS	VARCHAR2 (8)		Current status of the audit trail purge job (ENABLED) or (DISABLED)
AUDIT_TRAIL	VARCHAR2 (28)		Audit trail for which the audit trail purge job is configured: - STANDARD AUDIT TRAIL - FGA AUDIT TRAIL - STANDARD AND FGA AUDIT TRAIL - OS AUDIT TRAIL - XML AUDIT TRAIL - OS AND XML AUDIT TRAIL - ALL AUDIT TRAILS
JOB_FREQUENCY	VARCHAR2 (100)		Frequency at which the audit trail purge job runs

DBA_AUDIT_MGMT_CONFIG_PARAMS

DBA_AUDIT_MGMT_CONFIG_PARAMS displays information about the currently configured audit trail properties that are used by the DBMS_AUDIT_MGMT PL/SQL package.

Column	Datatype	NULL	Description
PARAMETER_NAME	VARCHAR2 (1024)	NOT NULL	Name of the property
PARAMETER_VALUE	VARCHAR2 (4000)		Value of the property
AUDIT_TRAIL	VARCHAR2 (28)		Audit trails for which the property is configured: ■ STANDARD AUDIT TRAIL ■ FGA AUDIT TRAIL ■ STANDARD AND FGA AUDIT TRAIL ■ OS AUDIT TRAIL ■ XML AUDIT TRAIL ■ OS AND XML AUDIT TRAIL ■ ALL AUDIT TRAILS

DBA_AUDIT_MGMT_LAST_ARCH_TS

DBA_AUDIT_MGMT_LAST_ARCH_TS displays information about the last archive timestamps set for audit trail cleanup or purges.

Column	Datatype	NULL	Description
AUDIT_TRAIL	VARCHAR2 (20)		Audit trail for which the last archive timestamp applies: ■ STANDARD AUDIT TRAIL ■ FGA AUDIT TRAIL ■ OS AUDIT TRAIL ■ XML AUDIT TRAIL
RAC_INSTANCE	NUMBER	NOT NULL	Oracle RAC instance number for which the last archive timestamp applies; 0 implies not applicable
LAST_ARCHIVE_TS	TIMESTAMP (6) WITH TIME ZONE		Timestamp of the last audit record or audit file that has been archived

DBA_AUDIT_OBJECT

DBA_AUDIT_OBJECT displays audit trail records for all objects in the database.

Related View

USER_AUDIT_OBJECT displays audit trail records for the objects accessible to the current user.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2 (255)		Operating system login username of the user whose actions were audited
USERNAME	VARCHAR2 (30)		Name (not ID number) of the user whose actions were audited
USERHOST	VARCHAR2 (128)		Client host machine name
TERMINAL	VARCHAR2 (255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by AUDIT SESSION) in the local database session time zone
OWNER	VARCHAR2 (30)		Creator of the object affected by the action
OBJ_NAME	VARCHAR2 (128)		Name of the object affected by the action
ACTION_NAME	VARCHAR2 (28)		Name of the action type corresponding to the numeric code in the ACTION column in DBA_AUDIT_TRAIL

Column	Datatype	NULL	Description
NEW_OWNER	VARCHAR2 (30)		Owner of the object named in the NEW_NAME column
NEW_NAME	VARCHAR2 (128)		New name of an object after a RENAME or the name of the underlying object
SES_ACTIONS	VARCHAR2 (19)		Session summary (a string of 16 characters, one for each action type in the order ALTER, AUDIT, COMMENT, DELETE, GRANT, INDEX, INSERT, LOCK, RENAME, SELECT, UPDATE, REFERENCES, and EXECUTE). Positions 14, 15, and 16 are reserved for future use. The characters are: - - None - S - Success - F - Failure - B - Both
COMMENT_TEXT	VARCHAR2 (4000)		Text comment on the audit trail
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session
ENTRYID	NUMBER	NOT NULL	Numeric ID for each audit trail entry in the session
STATEMENTID	NUMBER	NOT NULL	Numeric ID for each statement run
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: 0 - Action succeeded 2004 - Security violation
PRIV_USED	VARCHAR2 (40)		System privilege used to execute the action
CLIENT_ID	VARCHAR2 (64)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2 (64)		Application execution context identifier
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session
EXTENDED_TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2 (32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2 (16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW (8)		Transaction identifier of the transaction in which the object is accessed or modified
SCN	NUMBER		System change number (SCN) of the query
SQL_BIND	NVARCHAR2 (2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2 (2000)		SQL text of the query
OBJ_EDITION_NAME	VARCHAR2 (30)		Name of the edition containing the audited object

Note: The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to db, extended.

See Also: ["AUDIT_TRAIL"](#) on page 1-25

DBA_AUDIT_POLICIES

DBA_AUDIT_POLICIES describes all fine-grained auditing policies in the database. Its columns are the same as those in ALL_AUDIT_POLICIES.

See Also: ["ALL_AUDIT_POLICIES"](#) on page 2-18

DBA_AUDIT_POLICY_COLUMNS

DBA_AUDIT_POLICY_COLUMNS describes all fine-grained auditing policy columns in the database. Its columns are the same as those in ALL_AUDIT_POLICY_COLUMNS.

See Also: ["ALL_AUDIT_POLICY_COLUMNS"](#) on page 2-20

DBA_AUDIT_SESSION

DBA_AUDIT_SESSION displays all audit trail records concerning CONNECT and DISCONNECT.

Related View

USER_AUDIT_SESSION displays the audit trail records concerning connections and disconnections of the current user.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2 (255)		Operating system login username of the user whose actions were audited
USERNAME	VARCHAR2 (30)		Name (not ID number) of the user whose actions were audited
USERHOST	VARCHAR2 (128)		Client host machine name
TERMINAL	VARCHAR2 (255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by AUDIT SESSION) in the local database session time zone
ACTION_NAME	VARCHAR2 (28)		Name of the action type corresponding to the numeric code in the ACTION column in DBA_AUDIT_TRAIL
LOGOFF_TIME	DATE		Date and time of user log off
LOGOFF_LREAD	NUMBER		Logical reads for the session
LOGOFF_PREAD	NUMBER		Physical reads for the session
LOGOFF_LWRITE	NUMBER		Logical writes for the session
LOGOFF_DLOCK	VARCHAR2 (40)		Deadlocks detected during the session
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: 0 - Action succeeded 2004 - Security violation
CLIENT_ID	VARCHAR2 (64)		Client identifier in each Oracle session
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session
EXTENDED_TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism

Column	Datatype	NULL	Description
GLOBAL_UID	VARCHAR2 (32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2 (16)		Operating System process identifier of the Oracle process

DBA_AUDIT_STATEMENT

DBA_AUDIT_STATEMENT displays audit trail records for all GRANT, REVOKE, AUDIT, NOAUDIT, and ALTER SYSTEM statements in the database.

Related View

USER_AUDIT_STATEMENT displays audit trail records for the GRANT, REVOKE, AUDIT, NOAUDIT, and ALTER SYSTEM statements issued by the current user.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2 (255)		Operating system login username of the user whose actions were audited
USERNAME	VARCHAR2 (30)		Name (not ID number) of the user whose actions were audited
USERHOST	VARCHAR2 (128)		Client host machine name
TERMINAL	VARCHAR2 (255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by AUDIT SESSION) in the local database session time zone
OWNER	VARCHAR2 (30)		Creator of the object affected by the action
OBJ_NAME	VARCHAR2 (128)		Name of the object affected by the action
ACTION_NAME	VARCHAR2 (28)		Name of the action type corresponding to the numeric code in the ACTION column in DBA_AUDIT_TRAIL
NEW_NAME	VARCHAR2 (128)		New name of an object after a RENAME or the name of the underlying object
OBJ_PRIVILEGE	VARCHAR2 (16)		Object privileges granted or revoked by a GRANT or REVOKE statement
SYS_PRIVILEGE	VARCHAR2 (40)		System privileges granted or revoked by a GRANT or REVOKE statement
ADMIN_OPTION	VARCHAR2 (1)		Signifies the role or system privilege was granted with the ADMIN option
GRANTEE	VARCHAR2 (30)		Name of the grantee specified in a GRANT or REVOKE statement
AUDIT_OPTION	VARCHAR2 (40)		Auditing option set with the AUDIT statement
SES_ACTIONS	VARCHAR2 (19)		Session summary (a string of 16 characters, one for each action type in the order ALTER, AUDIT, COMMENT, DELETE, GRANT, INDEX, INSERT, LOCK, RENAME, SELECT, UPDATE, REFERENCES, and EXECUTE). Positions 14, 15, and 16 are reserved for future use. The characters are: ■ - - None ■ S - Success ■ F - Failure ■ B - Both

Column	Datatype	NULL	Description
COMMENT_TEXT	VARCHAR2 (4000)		Text comment on the audit trail, inserted by the application
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session
ENTRYID	NUMBER	NOT NULL	Numeric ID for each audit trail entry in the session
STATEMENTID	NUMBER	NOT NULL	Numeric ID for each statement run
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: 0 - Action succeeded 2004 - Security violation
PRIV_USED	VARCHAR2 (40)		System privilege used to execute the action
CLIENT_ID	VARCHAR2 (64)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2 (64)		Application execution context identifier
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session
EXTENDED_TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2 (32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2 (16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW (8)		Transaction identifier of the transaction in which the object is accessed or modified
SCN	NUMBER		System change number (SCN) of the query
SQL_BIND	NVARCHAR2 (2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2 (2000)		SQL text of the query
OBJ_EDITION_NAME	VARCHAR2 (30)		Name of the edition containing the audited object

Note: The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to db, extended.

See Also: ["AUDIT_TRAIL"](#) on page 1-25

DBA_AUDIT_TRAIL

DBA_AUDIT_TRAIL displays all standard audit trail entries.

Related View

USER_AUDIT_TRAIL displays the standard audit trail entries related to the current user.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2 (255)		Operating system login username of the user whose actions were audited

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (30)		Name (not ID number) of the user whose actions were audited
USERHOST	VARCHAR2 (128)		Client host machine name
TERMINAL	VARCHAR2 (255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by <code>AUDIT SESSION</code>) in the local database session time zone
OWNER	VARCHAR2 (30)		Creator of the object affected by the action
OBJ_NAME	VARCHAR2 (128)		Name of the object affected by the action
ACTION	NUMBER	NOT NULL	Numeric action type code. The corresponding name of the action type is in the <code>ACTION_NAME</code> column.
ACTION_NAME	VARCHAR2 (28)		Name of the action type corresponding to the numeric code in the <code>ACTION</code> column
NEW_OWNER	VARCHAR2 (30)		Owner of the object named in the <code>NEW_NAME</code> column
NEW_NAME	VARCHAR2 (128)		New name of the object after a <code>RENAME</code> or the name of the underlying object
OBJ_PRIVILEGE	VARCHAR2 (16)		Object privileges granted or revoked by a <code>GRANT</code> or <code>REVOKE</code> statement
SYS_PRIVILEGE	VARCHAR2 (40)		System privileges granted or revoked by a <code>GRANT</code> or <code>REVOKE</code> statement
ADMIN_OPTION	VARCHAR2 (1)		Indicates whether the role or system privilege was granted with the <code>ADMIN</code> option
GRANTEE	VARCHAR2 (30)		Name of the grantee specified in a <code>GRANT</code> or <code>REVOKE</code> statement
AUDIT_OPTION	VARCHAR2 (40)		Auditing option set with the <code>AUDIT</code> statement
SES_ACTIONS	VARCHAR2 (19)		Session summary (a string of 16 characters, one for each action type in the order <code>ALTER</code> , <code>AUDIT</code> , <code>COMMENT</code> , <code>DELETE</code> , <code>GRANT</code> , <code>INDEX</code> , <code>INSERT</code> , <code>LOCK</code> , <code>RENAME</code> , <code>SELECT</code> , <code>UPDATE</code> , <code>REFERENCES</code> , and <code>EXECUTE</code>). Positions 14, 15, and 16 are reserved for future use. The characters are: ■ - - None ■ S - Success ■ F - Failure ■ B - Both
LOGOFF_TIME	DATE		Date and time of user log off
LOGOFF_LREAD	NUMBER		Logical reads for the session
LOGOFF_PREAD	NUMBER		Physical reads for the session
LOGOFF_LWRITE	NUMBER		Logical writes for the session
LOGOFF_DLOCK	VARCHAR2 (40)		Deadlocks detected during the session
COMMENT_TEXT	VARCHAR2 (4000)		Text comment on the audit trail entry, providing more information about the statement audited Also indicates how the user was authenticated. The method can be one of the following: ■ DATABASE - Authentication was done by password ■ NETWORK - Authentication was done by Oracle Net Services or the Advanced Security option ■ PROXY - Client was authenticated by another user; the name of the proxy user follows the method type
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session
ENTRYID	NUMBER	NOT NULL	Numeric ID for each audit trail entry in the session
STATEMENTID	NUMBER	NOT NULL	Numeric ID for each statement run

Column	Datatype	NULL	Description
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: 0 - Action succeeded 2004 - Security violation
PRIV_USED	VARCHAR2 (40)		System privilege used to execute the action
CLIENT_ID	VARCHAR2 (64)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2 (64)		Application execution context identifier
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session
EXTENDED_TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2 (32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2 (16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW (8)		Transaction identifier of the transaction in which the object is accessed or modified
SCN	NUMBER		System change number (SCN) of the query
SQL_BIND	NVARCHAR2 (2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2 (2000)		SQL text of the query
OBJ_EDITION_NAME	VARCHAR2 (30)		Name of the edition containing the audited object
DBID	NUMBER		Database identifier of the audited database

Note: The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to db, extended.

See Also: ["AUDIT_TRAIL"](#) on page 1-25

DBA_AUTO_SEGADV_CTL

DBA_AUTO_SEGADV_CTL exposes the control information used by the segment advisor. This information gives the DBA an idea of what is happening in the auto advisor.

Column	Datatype	NULL	Description
AUTO_TASKID	NUMBER		Unique task ID generated by the auto advisor
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the segment
SEGMENT_OWNER	VARCHAR2 (30)		Owner of the segment
SEGMENT_NAME	VARCHAR2 (81)		Name of the segment
SEGMENT_TYPE	VARCHAR2 (18)		The type of segment (TABLE, INDEX, and so on)
PARTITION_NAME	VARCHAR2 (30)		Name of the subsegment (if partitioned)

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (40)		Status of the analysis: - NEW - the segment/tablespace has not been analyzed - BEING-PROCESSED - the segment/tablespace is being processed - COMPLETE - the segment/tablespace has been analyzed - ERROR - problem with the segment/tablespace
REASON	VARCHAR2 (40)		Reason why this segment was chosen
REASON_VALUE	NUMBER		A value associated with the reason
CREATION_TIME	TIMESTAMP (6)		Time when this entry was created
PROCESSED_TASKID	NUMBER		Auto advisor task that was used to process the segment/tablespace
END_TIME	TIMESTAMP (6)		Time at which the advisor task was completed

DBA_AUTO_SEGADV_SUMMARY

DBA_AUTO_SEGADV_SUMMARY provides a summary of the auto advisor task runs.

Column	Datatype	NULL	Description
AUTO_TASKID	NUMBER	NOT NULL	Unique auto task ID
SNAPID	NUMBER		Maximum AWR snapid used to process the segments
SEGMENTS_SELECTED	NUMBER		Number of segments chosen for analysis
SEGMENTS_PROCESSED	NUMBER		Number of segments actually processed
TABLESPACE_SELECTED	NUMBER		Number of tablespaces chosen for analysis
TABLESPACE_PROCESSED	NUMBER		Number of tablespaces actually processed
RECOMMENDATIONS_COUNT	NUMBER		Number of recommendations generated
START_TIME	TIMESTAMP (6)		Time at which the auto task was started
END_TIME	TIMESTAMP (6)		Time at which the auto task ended

DBA_AUTOTASK_CLIENT

DBA_AUTOTASK_CLIENT displays statistical data for each automated maintenance task over 7-day and 30-day periods.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2 (64)		Name of the client
STATUS	VARCHAR2 (8)		Job status: - ENABLED - DISABLED
CONSUMER_GROUP	VARCHAR2 (30)		Consumer group used for normal priority jobs for this client
CLIENT_TAG	VARCHAR2 (2)		Tag used to identify jobs for this client
PRIORITY_OVERRIDE	VARCHAR2 (7)		User-specified priority at which the task executes: - URGENT - HIGH - MEDIUM - LOW

Column	Datatype	NULL	Description
ATTRIBUTES	VARCHAR2 (4000)		Attributes of the client
WINDOW_GROUP	VARCHAR2 (64)		Window group used to schedule jobs
SERVICE_NAME	VARCHAR2 (64)		Name of the service on which jobs will execute for the client
RESOURCE_PERCENTAGE	NUMBER		Percentage of maintenance resources for high priority maintenance tasks for this client
USE_RESOURCE_ESTIMATES	VARCHAR2 (5)		Indicates whether resource estimates are used for this client (TRUE) or not (FALSE)
MEAN_JOB_DURATION	INTERVAL DAY (9) TO SECOND (9)		Average elapsed time for a job for this client (in seconds)
MEAN_JOB_CPU	INTERVAL DAY (9) TO SECOND (9)		Average CPU time for a job submitted by this client (in seconds)
MEAN_JOB_ATTEMPTS	NUMBER		Average number of attempts it takes to complete a task
MEAN_INCOMING_TASKS_7_DAYS	NUMBER		Average number of incoming tasks at the Maintenance Window Start over the last 7 days
MEAN_INCOMING_TASKS_30_DAYS	NUMBER		Average number of incoming tasks at the Maintenance Window Start over the last 30 days
TOTAL_CPU_LAST_7_DAYS	INTERVAL DAY (9) TO SECOND (9)		Cumulative CPU time used by the jobs for this client over the last 7 days (in seconds)
TOTAL_CPU_LAST_30_DAYS	INTERVAL DAY (9) TO SECOND (9)		Cumulative CPU time used by the jobs for this client over the last 30 days (in seconds)
MAX_DURATION_LAST_7_DAYS	INTERVAL DAY (3) TO SECOND (0)		Maximum elapsed time for a job over the last 7 days (in seconds)
MAX_DURATION_LAST_30_DAYS	INTERVAL DAY (3) TO SECOND (0)		Maximum elapsed time for a job over the last 30 days (in seconds)
WINDOW_DURATION_LAST_7_DAYS	INTERVAL DAY (9) TO SECOND (9)		Total time during which the client was active during the last 7 days
WINDOW_DURATION_LAST_30_DAYS	INTERVAL DAY (9) TO SECOND (9)		Total time during which the client was active during the last 30 days

DBA_AUTOTASK_CLIENT_HISTORY

DBA_AUTOTASK_CLIENT_HISTORY displays per-window history of job execution counts for each automated maintenance task. This information is viewable in the Job History page of Enterprise Manager.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2 (64)		Name of the client
WINDOW_NAME	VARCHAR2 (65)		Name of the maintenance window
WINDOW_START_TIME	TIMESTAMP (6) WITH TIME ZONE		Maintenance window start time
WINDOW_DURATION	INTERVAL DAY (9) TO SECOND (6)		Window duration (NULL for currently open window)
JOBS_CREATED	NUMBER		Number of jobs created on behalf of the client in this window
JOBS_STARTED	NUMBER		Number of jobs started on behalf of the client during the maintenance window
JOBS_COMPLETED	NUMBER		Number of jobs successfully completed on behalf of the client during the maintenance window
WINDOW_END_TIME	TIMESTAMP (6) WITH TIME ZONE		Window end time

DBA_AUTOTASK_CLIENT_JOB

DBA_AUTOTASK_CLIENT_JOB displays information about currently running Scheduler jobs created for automated maintenance tasks. It provides information about some objects targeted by those jobs, as well as some additional statistics from previous instantiations of the same task. Some of this additional data is taken from generic Scheduler views.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2 (64)		Name of the client
JOB_NAME	VARCHAR2 (65)		Name of the job
JOB_SCHEDULER_STATUS	VARCHAR2 (15)		Job status: ■ DISABLED ■ RETRY SCHEDULED ■ SCHEDULED ■ RUNNING ■ COMPLETED ■ BROKEN ■ FAILED ■ REMOTE ■ SUCCEEDED ■ CHAIN_STALLED
TASK_NAME	VARCHAR2 (64)		Name of the task being performed
TASK_TARGET_TYPE	VARCHAR2 (64)		Type of the target being processed
TASK_TARGET_NAME	VARCHAR2 (513)	NOT NULL	Name of the target
TASK_PRIORITY	VARCHAR2 (7)		Priority of the task: ■ URGENT ■ HIGH ■ MEDIUM ■ LOW
TASK_OPERATION	VARCHAR2 (64)		Operation performed on the object

DBA_AUTOTASK_JOB_HISTORY

DBA_AUTOTASK_JOB_HISTORY displays the history of automated maintenance task job runs. Jobs are added to this view after they finish executing.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2 (64)		Name of the automated maintenance client
WINDOW_NAME	VARCHAR2 (65)		Name of the maintenance window
WINDOW_START_TIME	TIMESTAMP (6) WITH TIME ZONE		Start time of the maintenance window
WINDOW_DURATION	INTERVAL DAY (9) TO SECOND (6)		Duration of the maintenance window
JOB_NAME	VARCHAR2 (65)		Name of the maintenance job
JOB_STATUS	VARCHAR2 (30)		Status of the maintenance job
JOB_START_TIME	TIMESTAMP (6) WITH TIME ZONE		Start time of the maintenance job
JOB_DURATION	INTERVAL DAY (3) TO SECOND (0)		Duration of the maintenance job

Column	Datatype	NULL	Description
JOB_ERROR	NUMBER		Error code for the job (if any)
JOB_INFO	VARCHAR2 (4000)		Additional information about the job

DBA_AUTOTASK_OPERATION

DBA_AUTOTASK_OPERATION displays all automated maintenance task operations for each client.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2 (64)		Name of the client
OPERATION_NAME	VARCHAR2 (64)		Name of the operation
OPERATION_TAG	VARCHAR2 (3)		Tag for the operation
PRIORITY_OVERRIDE	VARCHAR2 (7)		User-specified priority at which the task executes: - URGENT - HIGH - MEDIUM - LOW
ATTRIBUTES	VARCHAR2 (4000)		Attributes of the operation
USE_RESOURCE_ESTIMATES	VARCHAR2 (5)		Indicates whether resource usage estimates are used for the operation (TRUE) or not (FALSE)
STATUS	VARCHAR2 (8)		Job status: - ENABLED - DISABLED

DBA_AUTOTASK_SCHEDULE

DBA_AUTOTASK_SCHEDULE displays the schedule of maintenance windows for the next 32 days for each client.

Column	Datatype	NULL	Description
WINDOW_NAME	VARCHAR2 (30)		Name of the maintenance window
START_TIME	TIMESTAMP (6) WITH TIME ZONE		Projected start time of the window
DURATION	INTERVAL DAY (3) TO SECOND (0)		Currently defined duration of the window (NULL for the currently open window)

DBA_AUTOTASK_TASK

DBA_AUTOTASK_TASK displays information about current and past automated maintenance tasks.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2 (64)		Name of the client
TASK_NAME	VARCHAR2 (64)		Name of the task being performed
TASK_TARGET_TYPE	VARCHAR2 (64)		Target type of the task
TASK_TARGET_NAME	VARCHAR2 (513)	NOT NULL	Name of the target
OPERATION_NAME	VARCHAR2 (64)		Operation performed on the object
ATTRIBUTES	VARCHAR2 (4000)		Attributes of the task

Column	Datatype	NULL	Description
TASK_PRIORITY	NUMBER		Task priority, relative to other tasks for this Client
PRIORITY_OVERRIDE	NUMBER		Task priority as overridden by the user
STATUS	VARCHAR2 (8)		Status of the task: ■ DISABLED ■ DEFERRED ■ ENABLED
DEFERRED_WINDOW_NAME	VARCHAR2 (65)		Appropriate window for this task
CURRENT_JOB_NAME	VARCHAR2 (65)		Name of the currently scheduled job, if any
JOB_SCHEDULER_STATUS	VARCHAR2 (15)		Job status: ■ DISABLED ■ RETRY SCHEDULED ■ SCHEDULED ■ RUNNING ■ COMPLETED ■ BROKEN ■ FAILED ■ REMOTE ■ SUCCEEDED ■ CHAIN_STALLED
ESTIMATE_TYPE	VARCHAR2 (7)		Type of resource estimates applied: ■ DERIVED ■ FORCED ■ LOCKED
ESTIMATED_WEIGHT	NUMBER		Task weight indicator
ESTIMATED_DURATION	NUMBER		Estimated elapsed time for the job (in seconds)
ESTIMATED_CPU_TIME	NUMBER		Estimated CPU time for the job (in seconds)
ESTIMATED_TEMP	NUMBER		Estimated temporary space usage for the job (in KB)
ESTIMATED_DOP	NUMBER		Estimated degree of parallelism for the job
ESTIMATED_IO_RATE	NUMBER		Estimated I/O utilization for the job (in KB per second)
ESTIMATED_UNDO_RATE	NUMBER		Estimated UNDO generation rate for the job (in KB per second)
RETRY_COUNT	NUMBER		Number of attempts to perform this task since the last successful attempt
LAST_GOOD_DATE	TIMESTAMP (6) WITH TIME ZONE		Timestamp of the last successful attempt to perform this task
LAST_GOOD_PRIORITY	NUMBER		Job priority of the last successful attempt to perform this task
LAST_GOOD_DURATION	NUMBER		Elapsed time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_CPU_TIME	NUMBER		CPU time for the job (in seconds) of the last successful attempt to perform this task
LAST_GOOD_TEMP	NUMBER		Temporary space usage for the job (in KB) of the last successful attempt to perform this task
LAST_GOOD_DOP	NUMBER		Peak degree of parallelism for the job during the last successful attempt to perform this task
LAST_GOOD_IO_RATE	NUMBER		I/O utilization rate for the job (in KB per second) of the last successful attempt to perform this task
LAST_GOOD_UNDO_RATE	NUMBER		UNDO generation rate (in KB per second) of the last successful attempt to perform this task

Column	Datatype	NULL	Description
LAST_GOOD_CPU_WAIT	NUMBER		Resource Manager wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_IO_WAIT	NUMBER		Resource Manager wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_UNDO_WAIT	NUMBER		Resource Manager wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_TEMP_WAIT	NUMBER		Resource Manager wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_CONCURRENCY	NUMBER		Concurrency wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_CONTENTION	NUMBER		Contention wait time (in seconds) of the last successful attempt to perform this task
NEXT_TRY_DATE	TIMESTAMP (6) WITH TIME ZONE		Next projected start time for the deferred maintenance window
LAST_TRY_DATE	TIMESTAMP (6) WITH TIME ZONE		Time at which the task was last attempted
LAST_TRY_PRIORITY	NUMBER		Task priority at the time of the last attempt
LAST_TRY_RESULT	VARCHAR2 (36)		Result code of the last execution of the task: ■ SUCCEEDED ■ FAILED ■ STOPPED BY USER ACTION ■ STOPPED AT END OF MAINTENANCE WINDOW ■ STOPPED AT INSTANCE SHUTDOWN ■ STOPPED
LAST_TRY_DURATION	NUMBER		Elapsed time of the last run (in seconds)
LAST_TRY_CPU_TIME	NUMBER		CPU time during the last run (in seconds)
LAST_TRY_TEMP	NUMBER		Temporary space usage for the job (in KB) for the last run
LAST_TRY_DOP	NUMBER		Peak degree of parallelism for the job during the last run
LAST_TRY_IO_RATE	NUMBER		I/O rate during the last run (in seconds)
LAST_TRY_UNDO_RATE	NUMBER		UNDO generation rate during the last run (in seconds)
LAST_TRY_CPU_WAIT	NUMBER		Time spent waiting for CPU during the last run (in seconds)
LAST_TRY_IO_WAIT	NUMBER		Time spent waiting for I/O during the last run (in seconds)
LAST_TRY_UNDO_WAIT	NUMBER		Time spent waiting for UNDO during the last run (in seconds)
LAST_TRY_TEMP_WAIT	NUMBER		Time spent waiting for temporary space during the last run (in seconds)
LAST_TRY_CONCURRENCY	NUMBER		Concurrency wait time during the last run (in seconds)
LAST_TRY_CONTENTION	NUMBER		Contention wait time during the last run (in seconds)
MEAN_GOOD_DURATION	NUMBER		Average elapsed time for successful executions of this task (in seconds)
MEAN_GOOD_CPU_TIME	NUMBER		Average CPU time for successful executions of this task (in seconds)
MEAN_GOOD_TEMP	NUMBER		Average temporary space usage for successful executions of this task (in KB)
MEAN_GOOD_DOP	NUMBER		Average peak degree of parallelism for successful executions of this task
MEAN_GOOD_IO	NUMBER		Average I/O utilization for successful executions of this task (in KB per second)

Column	Datatype	NULL	Description
MEAN_GOOD_UNDO	NUMBER		Average UNDO generation rate for this task (in KB per second)
MEAN_GOOD_CPU_WAIT	NUMBER		Average time waiting for CPU for successful executions of this task (in seconds)
MEAN_GOOD_IO_WAIT	NUMBER		Average time waiting for I/O for successful executions of this task (in seconds)
MEAN_GOOD_UNDO_WAIT	NUMBER		Average time waiting for UNDO for successful executions of this task (in seconds)
MEAN_GOOD_TEMP_WAIT	NUMBER		Average time waiting for temporary space for successful executions of this task (in seconds)
MEAN_GOOD_CONCURRENCY	NUMBER		Average concurrency wait time for successful executions of this task (in seconds)
MEAN_GOOD_CONTENTION	NUMBER		Average contention wait time for successful executions of this task (in seconds)
INFO_FIELD_1	VARCHAR2 (4000)		Client-interpreted information
INFO_FIELD_2	CLOB		Client-interpreted information
INFO_FIELD_3	NUMBER		Client-interpreted information
INFO_FIELD_4	NUMBER		Client-interpreted information

DBA_AUTOTASK_WINDOW_CLIENTS

DBA_AUTOTASK_WINDOW_CLIENTS displays the windows that belong to MAINTENANCE_WINDOW_GROUP, along with the Enabled or Disabled status for the window for each maintenance task. Primarily used by Enterprise Manager.

Column	Datatype	NULL	Description
WINDOW_NAME	VARCHAR2 (30)	NOT NULL	Name of the maintenance window
WINDOW_NEXT_TIME	TIMESTAMP (6) WITH TIME ZONE		Next scheduled window open time unless the window is disabled
WINDOW_ACTIVE	VARCHAR2 (5)		Indicates whether the window is currently active (open) (TRUE) or not (FALSE)
AUTOTASK_STATUS	VARCHAR2 (8)		Status of the automated maintenance task subsystem: ■ ENABLED ■ DISABLED
OPTIMIZER_STATS	VARCHAR2 (8)		Status of optimizer statistics gathering: ■ ENABLED ■ DISABLED
SEGMENT_ADVISOR	VARCHAR2 (8)		Status of Segment Advisor: ■ ENABLED ■ DISABLED
SQL_TUNE_ADVISOR	VARCHAR2 (8)		Status of SQL Tuning Advisor: ■ ENABLED ■ DISABLED
HEALTH_MONITOR	VARCHAR2 (8)		Status of Health Monitor: ■ ENABLED ■ DISABLED

DBA_AUTOTASK_WINDOW_HISTORY

DBA_AUTOTASK_WINDOW_HISTORY displays historical information for automated maintenance task windows.

Column	Datatype	NULL	Description
WINDOW_NAME	VARCHAR2 (65)		Name of the maintenance window
WINDOW_START_TIME	TIMESTAMP (6) WITH TIME ZONE		Window start time
WINDOW_END_TIME	TIMESTAMP (6) WITH TIME ZONE		Window end time

DBA_AW_PS

DBA_AW_PS describes the page spaces in all analytic workspaces in the database. Its columns are the same as those in ALL_AW_PS.

See Also: ["ALL_AW_PS"](#) on page 2-20

DBA_AWS

DBA_AWS describes all analytic workspaces in the database. Its columns are the same as those in ALL_AWS.

See Also: ["ALL_AWS"](#) on page 2-20

DBA_BASE_TABLE_MVIEWS

DBA_BASE_TABLE_MVIEWS describes all materialized views using materialized view logs in the database. Its columns are the same as those in ALL_BASE_TABLE_MVIEWS.

See Also: ["ALL_BASE_TABLE_MVIEWS"](#) on page 2-21

DBA_BLOCKERS

DBA_BLOCKERS displays a session if it is not waiting for a locked object but is holding a lock on an object for which another session is waiting. In an Oracle RAC environment, this only applies if the blocker is on the same instance.

Column	Datatype	NULL	Description
HOLDING_SESSION	NUMBER		Session holding a lock

DBA_CAPTURE

DBA_CAPTURE displays information about all capture processes in the database. Its columns are the same as those in ALL_CAPTURE.

See Also: ["ALL_CAPTURE"](#) on page 2-22

DBA_CAPTURE_EXTRA_ATTRIBUTES

DBA_CAPTURE_EXTRA_ATTRIBUTES displays information about the extra attributes for all capture processes in the database. Its columns are the same as those in ALL_CAPTURE_EXTRA_ATTRIBUTES.

See Also: ["ALL_CAPTURE_EXTRA_ATTRIBUTES"](#) on page 2-23

DBA_CAPTURE_PARAMETERS

DBA_CAPTURE_PARAMETERS displays information about the parameters for all capture processes in the database. Its columns are the same as those in ALL_CAPTURE_PARAMETERS.

See Also: ["ALL_CAPTURE_PARAMETERS"](#) on page 2-24

DBA_CAPTURE_PREPARED_DATABASE

DBA_CAPTURE_PREPARED_DATABASE displays information about when the local database was prepared for instantiation. Its columns are the same as those in ALL_CAPTURE_PREPARED_DATABASE.

See Also:

- ["ALL_CAPTURE_PREPARED_DATABASE"](#) on page 2-24
- *Oracle Streams Concepts and Administration* for more information about the possible values for the supplemental logging columns in this view

DBA_CAPTURE_PREPARED_SCHEMAS

DBA_CAPTURE_PREPARED_SCHEMAS displays information about all schemas prepared for instantiation at the local database. Its columns are the same as those in ALL_CAPTURE_PREPARED_SCHEMAS.

See Also:

- ["ALL_CAPTURE_PREPARED_SCHEMAS"](#) on page 2-25
- *Oracle Streams Concepts and Administration* for more information about the possible values for the supplemental logging columns in this view

DBA_CAPTURE_PREPARED_TABLES

DBA_CAPTURE_PREPARED_TABLES displays information about all tables prepared for instantiation at the local database. Its columns are the same as those in ALL_CAPTURE_PREPARED_TABLES.

See Also:

- ["ALL_CAPTURE_PREPARED_TABLES"](#) on page 2-26
- *Oracle Streams Concepts and Administration* for more information about the possible values for the supplemental logging columns in this view

DBA_CATALOG

DBA_CATALOG lists all tables, views, clusters, synonyms, and sequences in the database. Its columns are the same as those in ["ALL_CATALOG"](#) on page 2-27.

DBA_CHANGE_NOTIFICATION_REGS

DBA_CHANGE_NOTIFICATION_REGS describes all change notification registrations in the database.

Related View

USER_CHANGE_NOTIFICATION_REGS describes the change notification registrations owned by the current user. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (31)		Owner of the registration
REGID	NUMBER		Internal registration ID
REGFLAGS	NUMBER		Registration flags
CALLBACK	VARCHAR2 (256)		Notification callback
OPERATIONS_FILTER	NUMBER		Operations filter (if specified)
CHANGELAG	NUMBER		Transaction lag between notifications (if specified)
TIMEOUT	NUMBER		Registration timeout (if specified)
TABLE_NAME	VARCHAR2 (63)		Name of the registered table

See Also: ["USER_CHANGE_NOTIFICATION_REGS"](#) on page 6-70

DBA_CLU_COLUMNS

DBA_CLU_COLUMNS maps all table columns to related cluster columns.

Related View

USER_CLU_COLUMNS maps all table columns owned by the current user to related cluster columns. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the cluster
CLUSTER_NAME	VARCHAR2 (30)	NOT NULL	Name of the cluster
CLU_COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Key column in the cluster
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Clustered table name
TAB_COLUMN_NAME	VARCHAR2 (4000)		Key column or attribute of the object type column

DBA_CLUSTER_HASH_EXPRESSIONS

DBA_CLUSTER_HASH_EXPRESSIONS lists hash functions for all hash clusters in the database. Its columns are the same as those in ["ALL_CLUSTER_HASH_EXPRESSIONS"](#) on page 2-29.

DBA_CLUSTERS

DBA_CLUSTERS describes all clusters in the database. Its columns are the same as those in ["ALL_CLUSTERS"](#) on page 2-30.

DBA_COL_COMMENTS

DBA_COL_COMMENTS displays comments on the columns of all tables and views in the database. Its columns are the same as those in ALL_COL_COMMENTS.

See Also: ["ALL_COL_COMMENTS"](#) on page 2-31

DBA_COL_PENDING_STATS

DBA_COL_PENDING_STATS describes the pending statistics of all columns in the database. Its columns are the same as those in ALL_COL_PENDING_STATS.

See Also: ["ALL_COL_PENDING_STATS"](#) on page 2-31

DBA_COL_PRIVS

DBA_COL_PRIVS describes all column object grants in the database.

Related View

USER_COL_PRIVS describes the column object grants for which the current user is the object owner, grantor, or grantee.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	Name of the user or role to whom access was granted
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column
GRANTOR	VARCHAR2 (30)	NOT NULL	Name of the user who performed the grant
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Privilege on the column
GRANTABLE	VARCHAR2 (3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)

See Also: ["USER_COL_PRIVS"](#) on page 6-71

DBA_COLL_TYPES

DBA_COLL_TYPES describes all named collection types (arrays, nested tables, object tables, and so on) in the database. Its columns are the same as those in ["ALL_COLL_TYPES"](#) on page 2-34.

DBA_COMMON_AUDIT_TRAIL

DBA_COMMON_AUDIT_TRAIL displays all standard and fine-grained audit trail entries, mandatory and SYS audit records written in XML format.

Column	Datatype	NULL	Description
AUDIT_TYPE	VARCHAR2 (22)		Audit trail type: - Standard Audit - Standard XML Audit - Fine Grained Audit - Fine Grained XML Audit - SYS XML Audit - Mandatory XML Audit
SESSION_ID	NUMBER		Numeric ID for the Oracle session
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
STATEMENTID	NUMBER		Numeric ID for the statement run; a statement may cause multiple audit records
ENTRYID	NUMBER		Numeric ID for the audit trail entry in the session
EXTENDED_TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Timestamp of the audited operation (timestamp of user login for entries created by AUDIT SESSION) in the session's time zone
GLOBAL_UID	VARCHAR2 (32)		Global user identifier for the user, if the user has logged in as an enterprise user
DB_USER	VARCHAR2 (30)		Database user name of the user whose actions were audited
CLIENT_ID	VARCHAR2 (64)		Client identifier in the Oracle session
ECONTEXT_ID	VARCHAR2 (64)		Application execution context identifier
EXT_NAME	VARCHAR2 (4000)		User external name
OS_USER	VARCHAR2 (255)		Operating system login user name of the user whose actions were audited
USERHOST	VARCHAR2 (128)		Client host machine name
OS_PROCESS	VARCHAR2 (16)		Operating system process identifier of the Oracle process
TERMINAL	VARCHAR2 (255)		Identifier of the user's terminal
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OBJECT_SCHEMA	VARCHAR2 (30)		Owner of the audited object
OBJECT_NAME	VARCHAR2 (128)		Name of the object affected by the action
POLICY_NAME	VARCHAR2 (30)		Name of the Fine-Grained Auditing Policy
NEW_OWNER	VARCHAR2 (30)		Owner of the object named in the NEW_NAME column
NEW_NAME	VARCHAR2 (128)		New name of the object after a RENAME or the name of the underlying object
ACTION	NUMBER		Numeric action type code. The corresponding name of the action type is in the STATEMENT_TYPE column.
STATEMENT_TYPE	VARCHAR2 (28)		Name of the action type corresponding to the numeric code in the ACTION column
AUDIT_OPTION	VARCHAR2 (40)		Auditing option set with the AUDIT statement
TRANSACTIONID	RAW (8)		Transaction identifier of the transaction in which the object was accessed or modified
RETURNCODE	NUMBER		Oracle error code generated by the action (0 if the action succeeded)
SCN	NUMBER		System change number (SCN) of the query

Column	Datatype	NULL	Description
COMMENT_TEXT	VARCHAR2 (4000)		Text comment on the audit trail entry, providing more information about the statement audited Also indicates how the user was authenticated: - DATABASE - Authentication was done by password - NETWORK - Authentication was done by Oracle Net Services or the Advanced Networking Option - PROXY - Client was authenticated by another user. The name of the proxy user follows the method type.
SQL_BIND	NVARCHAR2 (2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2 (2000)		SQL text of the query
OBJ_PRIVILEGE	VARCHAR2 (16)		Object privileges granted or revoked by a GRANT or REVOKE statement
SYS_PRIVILEGE	VARCHAR2 (40)		System privileges granted or revoked by a GRANT or REVOKE statement
ADMIN_OPTION	VARCHAR2 (1)		Indicates whether the role or system privilege was granted with the ADMIN option
OS_PRIVILEGE	VARCHAR2 (7)		Operating privilege (SYSDBA or SYSOPER), if any, used in the session. If no privilege is used, it will be NONE.
GRANTEE	VARCHAR2 (30)		Name of the grantee specified in a GRANT or REVOKE statement
PRIV_USED	VARCHAR2 (40)		System privilege used to execute the action
SES_ACTIONS	VARCHAR2 (19)		Session summary (a string of 16 characters, one for each action type in the order ALTER, AUDIT, COMMENT, DELETE, GRANT, INDEX, INSERT, LOCK, RENAME, SELECT, UPDATE, REFERENCES, and EXECUTE). Positions 14, 15, and 16 are reserved for future use. The characters are: - - None - S - Success - F - Failure - B - Both
LOGOFF_TIME	DATE		Timestamp of user log off
LOGOFF_LREAD	NUMBER		Number of logical reads in the session
LOGOFF_PREAD	NUMBER		Number of physical reads in the session
LOGOFF_LWRITE	NUMBER		Number of logical writes for the session
LOGOFF_DLOCK	VARCHAR2 (40)		Number of deadlocks detected during the session
SESSION_CPU	NUMBER		Amount of CPU time used by the Oracle session
OBJ_EDITION_NAME	VARCHAR2 (30)		Name of the edition containing the audited object
DBID	NUMBER		Database identifier of the audited database

DBA_COMPARISON

DBA_COMPARISON displays information about all comparison objects in the database.

Related View

USER_COMPARISON displays information about the comparison objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the comparison

Column	Datatype	NULL	Description
COMPARISON_NAME	VARCHAR2 (30)	NOT NULL	Name of the comparison
COMPARISON_MODE	VARCHAR2 (5)		Mode of the comparison: TABLE
SCHEMA_NAME	VARCHAR2 (30)		Schema name of the local object
OBJECT_NAME	VARCHAR2 (30)		Name of the local object
OBJECT_TYPE	VARCHAR2 (17)		Type of the local object: - TABLE - VIEW - SYNONYM - MATERIALIZED VIEW
REMOTE_SCHEMA_NAME	VARCHAR2 (30)		Schema name of the remote object
REMOTE_OBJECT_NAME	VARCHAR2 (30)		Name of the remote object
REMOTE_OBJECT_TYPE	VARCHAR2 (17)		Type of the remote object: - TABLE - VIEW - SYNONYM - MATERIALIZED VIEW
DBLINK_NAME	VARCHAR2 (128)		Database link name to the remote database
SCAN_MODE	VARCHAR2 (9)		Scan mode of the comparison: FULL - FULL - RANDOM - CYCLIC - CUSTOM
SCAN_PERCENT	NUMBER		Scan percent of the comparison; applicable to random and cyclic modes
CYCLIC_INDEX_VALUE	VARCHAR2 (4000)		Last index column value used in a cyclic scan
NULL_VALUE	VARCHAR2 (4000)		Value to use for NULL columns
LOCAL_CONVERGE_TAG	RAW (2000)		Local Streams tag used while performing converge DMLs
REMOTE_CONVERGE_TAG	RAW (2000)		Remote Streams tag used while performing converge DMLs
MAX_NUM_BUCKETS	NUMBER		Suggested maximum number of buckets in a scan
MIN_ROWS_IN_BUCKET	NUMBER		Suggested minimum number of rows in a bucket
LAST_UPDATE_TIME	TIMESTAMP (6)		Time that this row was last updated

DBA_COMPARISON_COLUMNS

DBA_COMPARISON_COLUMNS displays information about the columns for all comparison objects in the database.

Related View

USER_COMPARISON_COLUMNS displays information about the columns for the comparison objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the comparison

Column	Datatype	NULL	Description
COMPARISON_NAME	VARCHAR2 (30)	NOT NULL	Name of the comparison
COLUMN_POSITION	NUMBER	NOT NULL	Position of the column
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Name of the column
INDEX_COLUMN	VARCHAR2 (1)		Indicates whether the column is an index column (Y) or not (N)

DBA_COMPARISON_ROW_DIF

DBA_COMPARISON_ROW_DIF displays information about the differing rows in all comparison scans in the database.

Related View

USER_COMPARISON_ROW_DIF displays information about the differing rows in the comparison scans owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the comparison
COMPARISON_NAME	VARCHAR2 (30)	NOT NULL	Name of the comparison
SCAN_ID	NUMBER	NOT NULL	Scan ID for the comparison scan
LOCAL_ROWID	ROWID		Local rowid of the differing row
REMOTE_ROWID	ROWID		Remote rowid of the differing row
INDEX_VALUE	VARCHAR2 (4000)		Index column value of the differing row
STATUS	VARCHAR2 (3)		Status of the differing row: - SUC - DIF
LAST_UPDATE_TIME	TIMESTAMP (6)		Time that this row was last updated

DBA_COMPARISON_SCAN

DBA_COMPARISON_SCAN displays information about all comparison scans in the database.

Related View

USER_COMPARISON_SCAN displays information about the comparison scans owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the comparison scan
COMPARISON_NAME	VARCHAR2 (30)	NOT NULL	Name of the comparison scan
SCAN_ID	NUMBER	NOT NULL	Scan ID
PARENT_SCAN_ID	NUMBER		Scan ID of the immediate parent scan
ROOT_SCAN_ID	NUMBER		Scan ID of the root (top-most) parent

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (16)		Status of the scan: ■ SUC ■ BUCKET DIF ■ FINAL BUCKET DIF ■ ROW DIF
CURRENT_DIF_COUNT	NUMBER		Current cumulative (including children) diff count of the scan
INITIAL_DIF_COUNT	NUMBER		Initial cumulative (including children) diff count of the scan
COUNT_ROWS	NUMBER		Number of rows in the scan
SCAN_NULLS	VARCHAR2 (1)		Indicates whether NULLs are part of this scan (Y) or not (N)
LAST_UPDATE_TIME	TIMESTAMP (6)		Time that this row was last updated

DBA_COMPARISON_SCAN_VALUES

DBA_COMPARISON_SCAN_VALUES displays information about the values for all comparison scans in the database.

Related View

USER_COMPARISON_SCAN_VALUES displays information about the values for the comparison scans owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the comparison scan
COMPARISON_SCAN	VARCHAR2 (30)	NOT NULL	Name of the comparison scan
SCAN_ID	NUMBER	NOT NULL	Scan ID
COLUMN_POSITION	NUMBER	NOT NULL	Column position, as in DBA_COMPARISON_COLUMNS
MIN_VALUE	VARCHAR2 (4000)		Minimum value of the scan
MAX_VALUE	VARCHAR2 (4000)		Maximum value of the scan
LAST_UPDATE_TIME	TIMESTAMP (6)		Time that this row was last updated

DBA_CONNECT_ROLE_GRANTEES

DBA_CONNECT_ROLE_GRANTEES displays information about users who are granted the CONNECT privilege.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)		User or schema to which the CONNECT role is granted
PATH_OF_CONNECT_ROLE_GRANT	VARCHAR2 (4000)		The path of role inheritance through which the grantee is granted the CONNECT role
ADMIN_OPT	VARCHAR2 (3)		Whether or not the grantee was granted the ADMIN option for the CONNECT role

DBA_CONS_OBJ_COLUMNS

DBA_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in all tables in the database. Its columns are the same as those in ALL_CONS_OBJ_COLUMNS.

See Also: ["ALL_CONS_OBJ_COLUMNS"](#) on page 2-35

DBA_CONSTRAINTS

DBA_CONSTRAINTS describes all constraint definitions on all tables in the database. Its columns are the same as those in ["ALL_CONSTRAINTS"](#) on page 2-35.

DBA_CONTEXT

DBA_CONTEXT provides all context namespace information in the database. Its columns are the same as those in ["ALL_CONTEXT"](#) on page 2-37.

DBA_CPOOL_INFO

DBA_CPOOL_INFO displays configuration information about all Database Resident Connection Pools in the database.

Column	Datatype	NULL	Description
CONNECTION_POOL	VARCHAR2 (128)		Name of the connection pool
STATUS	VARCHAR2 (16)		Status of the pool: ■ ACTIVE ■ INACTIVE
MINSIZE	NUMBER		Minimum number of pooled servers that are always alive in the pool
MAXSIZE	NUMBER		Maximum number of pooled servers in the pool
INCRSIZE	NUMBER		Number of pooled servers by which the pool is incremented if servers are unavailable when a client application request is received
SESSION_CACHED_CURSORS	NUMBER		Number of session cursors to cache in each pooled server
INACTIVITY_TIMEOUT	NUMBER		Maximum time (in seconds) that the pooled server can stay idle in the pool. After this time, the server is terminated.
MAX_THINK_TIME	NUMBER		Maximum time of inactivity (in seconds) for a client after obtaining a pooled server from the pool. After obtaining a pooled server from the pool, if the client application does not issue a database call for the time specified by this column, then the pooled server is freed and the client connection is terminated.
MAX_USE_SESSION	NUMBER		Number of times a pooled server can be taken and released to the pool
MAX_LIFETIME_SESSION	NUMBER		Time (in seconds) for a pooled server to live in the pool

DBA_CPU_USAGE_STATISTICS

DBA_CPU_USAGE_STATISTICS displays database CPU usage statistics.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
VERSION	VARCHAR2 (17)	NOT NULL	Database version
TIMESTAMP	DATE	NOT NULL	Time at which the CPU usage changed
CPU_COUNT	NUMBER		CPU count of the database
CPU_CORE_COUNT	NUMBER		CPU core count of the database
CPU_SOCKET_COUNT	NUMBER		CPU socket count of the database

DBA_CQ_NOTIFICATION_QUERIES

DBA_CQ_NOTIFICATION_QUERIES describes the registered queries for all CQ notifications in the database.

Related View

USER_CQ_NOTIFICATION_QUERIES describes the registered queries for the CQ notifications owned by the current user. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
QUERYID	NUMBER		ID of the query
QUERYTEXT	CLOB		Text of the query
REGID	NUMBER		Registration ID that the query is registered with
USERNAME	VARCHAR2 (31)		Name of the user who registered the query

See Also: ["USER_CQ_NOTIFICATION_QUERIES"](#) on page 6-73

DBA_CUBE_ATTR_VISIBILITY

DBA_CUBE_ATTR_VISIBILITY describes all OLAP attributes visible for the dimensions, hierarchies, and levels in the database. Its columns are the same as those in ALL_CUBE_ATTR_VISIBILITY.

See Also: ["ALL_CUBE_ATTR_VISIBILITY"](#) on page 2-38

DBA_CUBE_ATTRIBUTES

DBA_CUBE_ATTRIBUTES describes the attributes for all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_ATTRIBUTES.

See Also: ["ALL_CUBE_ATTRIBUTES"](#) on page 2-38

DBA_CUBE_BUILD_PROCESSES

DBA_CUBE_BUILD_PROCESSES describes all OLAP build processes and maintenance scripts in the database. Its columns are the same as those in ALL_CUBE_BUILD_PROCESSES.

See Also: ["ALL_CUBE_BUILD_PROCESSES"](#) on page 2-39

DBA_CUBE_CALCULATED_MEMBERS

DBA_CUBE_CALCULATED_MEMBERS describes the calculated members for all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_CALCULATED_MEMBERS.

See Also: ["ALL_CUBE_CALCULATED_MEMBERS"](#) on page 2-39

DBA_CUBE_DIM_LEVELS

DBA_CUBE_DIM_LEVELS describes all OLAP dimension levels in the database. Its columns are the same as those in ALL_CUBE_DIM_LEVELS.

See Also: ["ALL_CUBE_DIM_LEVELS"](#) on page 2-40

DBA_CUBE_DIM_MODELS

DBA_CUBE_DIM_MODELS describes the models for all OLAP dimensions in the database. Its columns are the same as those in ALL_CUBE_DIM_MODELS.

See Also: ["ALL_CUBE_DIM_MODELS"](#) on page 2-40

DBA_CUBE_DIM_VIEW_COLUMNS

DBA_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_DIM_VIEW_COLUMNS.

See Also: ["ALL_CUBE_DIM_VIEW_COLUMNS"](#) on page 2-41

DBA_CUBE_DIM_VIEWS

DBA_CUBE_DIM_VIEWS describes the relational views of all OLAP dimensions in the database. Its columns are the same as those in ALL_CUBE_DIM_VIEWS.

See Also: ["ALL_CUBE_DIM_VIEWS"](#) on page 2-41

DBA_CUBE_DIMENSIONALITY

DBA_CUBE_DIMENSIONALITY describes the dimension order for all OLAP cubes in the database. Its columns are the same as those in ALL_CUBE_DIMENSIONALITY.

See Also: ["ALL_CUBE_DIMENSIONALITY"](#) on page 2-42

DBA_CUBE_DIMENSIONS

DBA_CUBE_DIMENSIONS describes all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_DIMENSIONS.

See Also: ["ALL_CUBE_DIMENSIONS"](#) on page 2-42

DBA_CUBE_HIER_LEVELS

DBA_CUBE_HIER_LEVELS describes the hierarchy levels for all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_HIER_LEVELS.

See Also: ["ALL_CUBE_HIER_LEVELS"](#) on page 2-43

DBA_CUBE_HIER_VIEW_COLUMNS

DBA_CUBE_HIER_VIEW_COLUMNS describes the columns of the relational hierarchy views of all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_HIER_VIEW_COLUMNS.

See Also: ["ALL_CUBE_HIER_VIEW_COLUMNS"](#) on page 2-43

DBA_CUBE_HIER_VIEWS

DBA_CUBE_HIER_VIEWS describes the hierarchies for all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_HIER_VIEWS.

See Also: ["ALL_CUBE_HIER_VIEWS"](#) on page 2-44

DBA_CUBE_HIERARCHIES

DBA_CUBE_HIERARCHIES describes all OLAP dimension hierarchies in the database. Its columns are the same as those in ALL_CUBE_HIERARCHIES.

See Also: ["ALL_CUBE_HIERARCHIES"](#) on page 2-45

DBA_CUBE_MEASURES

DBA_CUBE_MEASURES describes the measures for all OLAP cubes in the database. Its columns are the same as those in ALL_CUBE_MEASURES.

See Also: ["ALL_CUBE_MEASURES"](#) on page 2-46

DBA_CUBE_VIEW_COLUMNS

DBA_CUBE_VIEW_COLUMNS describes the columns of relational views of all OLAP cubes in the database. Its columns are the same as those in ALL_CUBE_VIEW_COLUMNS.

See Also: ["ALL_CUBE_VIEW_COLUMNS"](#) on page 2-46

DBA_CUBE_VIEWS

DBA_CUBE_VIEWS describes the relational views of all OLAP cubes in the database. Its columns are the same as those in ALL_CUBE_VIEWS.

See Also: ["ALL_CUBE_VIEWS"](#) on page 2-47

DBA_CUBES

DBA_CUBES describes all OLAP cubes in the database. Its columns are the same as those in ALL_CUBES.

See Also: ["ALL_CUBES"](#) on page 2-47

DBA_DATA_FILES

DBA_DATA_FILES describes database files.

Column	Datatype	NULL	Description
FILE_NAME	VARCHAR2 (513)		Name of the database file
FILE_ID	NUMBER	NOT NULL	File identifier number of the database file
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace to which the file belongs
BYTES	NUMBER		Size of the file in bytes
BLOCKS	NUMBER	NOT NULL	Size of the file in Oracle blocks
STATUS	VARCHAR2 (9)		File status: AVAILABLE or INVALID (INVALID means that the file number is not in use, for example, a file in a tablespace that was dropped)
RELATIVE_FNO	NUMBER		Relative file number
AUTOEXTENSIBLE	VARCHAR2 (3)		Autoextensible indicator
MAXBYTES	NUMBER		Maximum file size in bytes
MAXBLOCKS	NUMBER		Maximum file size in blocks
INCREMENT_BY	NUMBER		Number of Oracle blocks used as autoextension increment
USER_BYTES	NUMBER		The size of the file available for user data. The actual size of the file minus the USER_BYTES value is used to store file related metadata.
USER_BLOCKS	NUMBER		Number of blocks which can be used by the data
ONLINE_STATUS	VARCHAR2 (7)		Online status of the file: ▪ SYSOFF ▪ SYSTEM ▪ OFFLINE ▪ ONLINE ▪ RECOVER

DBA_DATAPUMP_JOBS

DBA_DATAPUMP_JOBS identifies all active Data Pump jobs in the database, regardless of their state, on an instance (or on all instances for Real Application Clusters). It also show all Data Pump master tables not currently associated with an active job.

Related View

USER_DATAPUMP_JOBS displays the Data Pump jobs owned by the current user. This view does not display the OWNER_NAME column.

Column	Datatype	NULL	Description
OWNER_NAME	VARCHAR2 (30)		User that initiated the job
JOB_NAME	VARCHAR2 (30)		User-supplied name for the job (or the default name generated by the server)
OPERATION	VARCHAR2 (30)		Type of job
JOB_MODE	VARCHAR2 (30)		Mode of job
STATE	VARCHAR2 (30)		Current job state
DEGREE	NUMBER		Number of worker processes performing the operation
ATTACHED_SESSIONS	NUMBER		Number of sessions attached to the job
DATAPUMP_SESSIONS	NUMBER		Number of Data Pump sessions participating in the job

See Also: ["USER_DATAPUMP_JOBS"](#) on page 6-75

DBA_DATAPUMP_SESSIONS

DBA_DATAPUMP_SESSIONS identifies the user sessions that are attached to a Data Pump job. The information in this view is useful for determining why a stopped Data Pump operation has not gone away.

Column	Datatype	NULL	Description
OWNER_NAME	VARCHAR2 (30)		User that initiated the job
JOB_NAME	VARCHAR2 (30)		User-supplied name for the job (or the default name generated by the server)
SADDR	RAW (4 8)		Address of the session attached to the job. Can be used with V\$SESSION view.
SESSION_TYPE	VARCHAR2 (14)		Data Pump session type: ■ DBMS_DATAPUMP - Data Pump interface process (one for each active instantiation of DBMS_DATAPUMP.OPEN and DBMS_DATAPUMP.ATTACH per job.) ■ MASTER - master control process (one per job) ■ WORKER - worker process (1 to <i>n</i> per job, depending on degree of parallelism) ■ EXTERNAL_TABLE - external table data access process (1 to <i>n</i>, depending on degree of parallelism, for jobs that use external tables as the data access method for some tables) ■ OTHER

DBA_DB_LINKS

DBA_DB_LINKS describes all database links in the database. Its columns (except for PASSWORD) are the same as those in ALL_DB_LINKS.

See Also: ["ALL_DB_LINKS"](#) on page 2-48

DBA_DDL_LOCKS

DBA_DDL_LOCKS lists all DDL locks held in the database and all outstanding requests for a DDL lock.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER		Session identifier
OWNER	VARCHAR2 (30)		Owner of the lock
NAME	VARCHAR2 (30)		Name of the lock

Column	Datatype	NULL	Description
TYPE	VARCHAR2 (40)		Lock type: ▪ Cursor ▪ Table/Procedure/Type ▪ Body ▪ Trigger ▪ Index ▪ Cluster ▪ Java Source ▪ Java Resource ▪ Java Data
MODE_HELD	VARCHAR2 (9)		Lock mode: ▪ None ▪ Null ▪ Share ▪ Exclusive
MODE_REQUESTED	VARCHAR2 (9)		Lock request type: ▪ None ▪ Null ▪ Share ▪ Exclusive

DBA_DEPENDENCIES

DBA_DEPENDENCIES describes all dependencies in the database between procedures, packages, functions, package bodies, and triggers, including dependencies on views created without any database links. Its columns are the same as those in "[ALL_DEPENDENCIES](#)" on page 2-49.

DBA_DIM_ATTRIBUTES

DBA_DIM_ATTRIBUTES describes the relationships between dimension levels and functionally dependent columns in the database. The level columns and the dependent column must be in the same table. This view's columns are the same as those in "[ALL_DIM_ATTRIBUTES](#)" on page 2-50.

DBA_DIM_CHILD_OF

DBA_DIM_CHILD_OF describes a hierarchical relationship of 1 to *n* between all the pairs of levels in the dimensions in the database. Its columns are the same as those in "[ALL_DIM_CHILD_OF](#)" on page 2-51.

DBA_DIM_HIERARCHIES

DBA_DIM_HIERARCHIES describes all the dimension hierarchies in the database. Its columns are the same as those in "[ALL_DIM_HIERARCHIES](#)" on page 2-51.

DBA_DIM_JOIN_KEY

DBA_DIM_JOIN_KEY describes all joins in the database between two dimension tables. The join is always specified between a parent dimension level column and a

child column. This view's columns are the same as those in "[ALL_DIM_JOIN_KEY](#)" on page 2-52.

DBA_DIM_LEVEL_KEY

DBA_DIM_LEVEL_KEY describes the columns of all dimension levels in the database. This view's columns are the same as those in "[ALL_DIM_LEVEL_KEY](#)" on page 2-52.

DBA_DIM_LEVELS

DBA_DIM_LEVELS describes all dimension levels in the database. All columns of a dimension level must come from the same relation. This view's columns are the same as those in "[ALL_DIM_LEVELS](#)" on page 2-52.

DBA_DIMENSIONS

DBA_DIMENSIONS represents dimension objects. Its columns are the same as those in "[ALL_DIMENSIONS](#)" on page 2-53.

DBA_DIRECTORIES

DBA_DIRECTORIES describes all directory objects in the database. Its columns are the same as those in "[ALL_DIRECTORIES](#)" on page 2-53.

DBA_DML_LOCKS

DBA_DML_LOCKS lists all DML locks held in the database and all outstanding requests for a DML lock.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER		Session holding or acquiring the lock
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the lock
NAME	VARCHAR2 (30)	NOT NULL	Name of the lock
MODE_HELD	VARCHAR2 (13)		The type of lock held. The values are: - ROWS_S (SS): row share lock - ROW-X (SX): row exclusive lock - SHARE (S): share lock - S/ROW-X (SSX): exclusive lock - NONE: lock requested but not yet obtained
MODE_REQUESTED	VARCHAR2 (13)		Lock request type. The values are: - ROWS_S (SS): row share lock - ROW-X (SX): row exclusive lock - SHARE (S): share lock - S/ROW-X (SSX): exclusive lock - NONE: Lock identifier obtained; lock not held or requested
LAST_CONVERT	NUMBER		The last convert
BLOCKING_OTHERS	VARCHAR2 (40)		Blocking others

DBA_DMT_FREE_SPACE

DBA_DMT_FREE_SPACE describes the free extents in all dictionary managed tablespaces in the database.

Column	Datatype	NULL	Description
TABLESPACE_ID	NUMBER	NOT NULL	Identifier number of the tablespace containing the extent
FILE_ID	NUMBER	NOT NULL	File identifier number of the file containing the extent
BLOCK_ID	NUMBER	NOT NULL	Starting block number of the extent
BLOCKS	NUMBER	NOT NULL	Size of the extent (in Oracle blocks)

DBA_DMT_USED_EXTENTS

DBA_DMT_USED_EXTENTS describes the extents comprising the segments in all dictionary managed tablespaces in the database.

Column	Datatype	NULL	Description
SEGMENT_FILEID	NUMBER	NOT NULL	File number of the segment header of the extent
SEGMENT_BLOCK	NUMBER	NOT NULL	Block number of the segment header of the extent
TABLESPACE_ID	NUMBER	NOT NULL	Identifier number of the tablespace containing the extent
EXTENT_ID	NUMBER	NOT NULL	Extent number in the segment
FILEID	NUMBER	NOT NULL	File identifier number of the file containing the extent
BLOCK	NUMBER	NOT NULL	Starting block number of the extent
LENGTH	NUMBER	NOT NULL	Number of blocks in the extent

DBA_EDITION_COMMENTS

DBA_EDITION_COMMENTS describes the comments on all editions in the database. Its columns are the same as those in ALL_EDITION_COMMENTS.

See Also: ["ALL_EDITION_COMMENTS"](#) on page 2-53

DBA_EDITIONING_VIEW_COLS

DBA_EDITIONING_VIEW_COLS describes the relationship between the columns of all editioning views in the database and the table columns to which they map. Its columns are the same as those in ALL_EDITIONING_VIEW_COLS.

See Also: ["ALL_EDITIONING_VIEW_COLS"](#) on page 2-54

DBA_EDITIONING_VIEW_COLS_AE

DBA_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of all editioning views (across all editions) in the database and the table columns to which they map. Its columns are the same as those in ALL_EDITIONING_VIEW_COLS_AE.

See Also: ["ALL_EDITIONING_VIEW_COLS_AE"](#) on page 2-54

DBA_EDITIONING_VIEWS

DBA_EDITIONING_VIEWS describes all editioning views in the database. Its columns are the same as those in ALL_EDITIONING_VIEWS.

See Also: ["ALL_EDITIONING_VIEWS"](#) on page 2-55

DBA_EDITIONING_VIEWS_AE

DBA_EDITIONING_VIEWS_AE describes all editioning views (across all editions) in the database. Its columns are the same as those in ALL_EDITIONING_VIEWS_AE.

See Also: ["ALL_EDITIONING_VIEWS_AE"](#) on page 2-55

DBA_EDITIONS

DBA_EDITIONS describes all editions in the database. Its columns are the same as those in ALL_EDITIONS.

See Also: ["ALL_EDITIONS"](#) on page 2-56

DBA_ENABLED_AGGREGATIONS

DBA_ENABLED_AGGREGATIONS displays information about enabled on-demand statistic aggregation.

Column	Datatype	NULL	Description
AGGREGATION_TYPE	VARCHAR2 (21)		Type of the aggregation: - CLIENT_ID - SERVICE - SERVICE_MODULE - SERVICE_MODULE_ACTION
PRIMARY_ID	VARCHAR2 (64)		Primary qualifier (specific client identifier or service name)
QUALIFIER_ID1	VARCHAR2 (48)		Secondary qualifier (specific module name)
QUALIFIER_ID2	VARCHAR2 (32)		Additional qualifier (specific action name)

DBA_ENABLED_TRACES

DBA_ENABLED_TRACES displays information about enabled SQL traces.

Column	Datatype	NULL	Description
TRACE_TYPE	VARCHAR2 (21)		Type of the trace: - CLIENT_ID - SERVICE - SERVICE_MODULE - SERVICE_MODULE_ACTION - DATABASE
PRIMARY_ID	VARCHAR2 (64)		Primary qualifier (specific client identifier or service name)
QUALIFIER_ID1	VARCHAR2 (48)		Secondary qualifier (specific module name)
QUALIFIER_ID2	VARCHAR2 (32)		Additional qualifier (specific action name)

Column	Datatype	NULL	Description
WAITS	VARCHAR2 (5)		Indicates whether waits are traced (TRUE) or not (FALSE)
BINDS	VARCHAR2 (5)		Indicates whether binds are traced (TRUE) or not (FALSE)
INSTANCE_NAME	VARCHAR2 (16)		Instance name for tracing restricted to named instances

DBA_ENCRYPTED_COLUMNS

DBA_ENCRYPTED_COLUMNS maintains encryption algorithm information for all encrypted columns in the database. Its columns are the same as those in "[ALL_ENCRYPTED_COLUMNS](#)" on page 2-56.

DBA_EPG_DAD_AUTHORIZATION

DBA_EPG_DAD_AUTHORIZATION describes the DADs that are authorized to use different user's privileges.

Related View

USER_EPG_DAD_AUTHORIZATION describes the DADs that are authorized to use the user's privileges. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
DAD_NAME	VARCHAR2 (64)	NOT NULL	Name of DAD
USERNAME	VARCHAR2 (30)	NOT NULL	Name of the user whose privileges the DAD is authorized to use

DBA_ERRORS

DBA_ERRORS describes the current errors on all stored objects in the database. Its columns are the same as those in ALL_ERRORS.

See Also: "[ALL_ERRORS](#)" on page 2-57

DBA_ERRORS_AE

DBA_ERRORS_AE describes the current errors on all stored objects (across all editions) in the database. Its columns are the same as those in ALL_ERRORS_AE.

See Also: "[ALL_ERRORS_AE](#)" on page 2-58

DBA_EVALUATION_CONTEXT_TABLES

DBA_EVALUATION_CONTEXT_TABLES describes the tables in all rule evaluation contexts in the database. Its columns are the same as those in ALL_EVALUATION_CONTEXT_TABLES.

See Also: "[ALL_EVALUATION_CONTEXT_TABLES](#)" on page 2-58

DBA_EVALUATION_CONTEXT_VARS

DBA_EVALUATION_CONTEXT_VARS describes the variables in all rule evaluation contexts in the database. Its columns are the same as those in ALL_EVALUATION_CONTEXT_VARS.

See Also: ["ALL_EVALUATION_CONTEXT_VARS"](#) on page 2-59

DBA_EVALUATION_CONTEXTS

DBA_EVALUATION_CONTEXTS describes all rule evaluation contexts in the database. Its columns are the same as those in ALL_EVALUATION_CONTEXTS.

See Also: ["ALL_EVALUATION_CONTEXTS"](#) on page 2-59

DBA_EXP_FILES

DBA_EXP_FILES describes export files.

Column	Datatype	NULL	Description
EXP_VERSION	NUMBER (3)	NOT NULL	Version number of the export session
EXP_TYPE	VARCHAR2 (11)		Type of export file: complete, cumulative, or incremental
FILE_NAME	VARCHAR2 (100)	NOT NULL	Name of the export file
USER_NAME	VARCHAR2 (30)	NOT NULL	Name of user who executed export
TIMESTAMP	DATE	NOT NULL	Timestamp of the export session

DBA_EXP_OBJECTS

DBA_EXP_OBJECTS describes objects that have been incrementally exported.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of exported object
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of exported object
OBJECT_TYPE	VARCHAR2 (12)		Type of exported object
CUMULATIVE	DATE		Timestamp of last cumulative export
INCREMENTAL	DATE	NOT NULL	Timestamp of last incremental export
EXPORT_VERSION	NUMBER (3)	NOT NULL	The ID of the export session

DBA_EXP_VERSION

DBA_EXP_VERSION displays the version number of the last export session.

Column	Datatype	NULL	Description
EXP_VERSION	NUMBER (3)	NOT NULL	Version number of the last export session

DBA_EXTENTS

DBA_EXTENTS describes the extents comprising the segments in all tablespaces in the database.

Note that if a datafile (or entire tablespace) is offline in a locally managed tablespace, you will not see any extent information. If an object has extents in an online file of the

tablespace, you will see extent information about the offline datafile. However, if the object is entirely in the offline file, a query of this view will not return any records.

Related View

USER_EXTENTS describes the extents comprising the segments owned by the current user's objects. This view does not display the OWNER, FILE_ID, BLOCK_ID, or RELATIVE_FNO columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the segment associated with the extent
SEGMENT_NAME	VARCHAR2 (81)		Name of the segment associated with the extent
PARTITION_NAME	VARCHAR2 (30)		Object Partition Name (Set to NULL for non-partitioned objects)
SEGMENT_TYPE	VARCHAR2 (18)		Type of the segment: INDEX PARTITION, TABLE PARTITION
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the extent
EXTENT_ID	NUMBER		Extent number in the segment
FILE_ID	NUMBER		File identifier number of the file containing the extent
BLOCK_ID	NUMBER		Starting block number of the extent
BYTES	NUMBER		Size of the extent in bytes
BLOCKS	NUMBER		Size of the extent in Oracle blocks
RELATIVE_FNO	NUMBER		Relative file number of the first extent block

See Also: ["USER_EXTENTS"](#) on page 6-78

DBA_EXTERNAL_LOCATIONS

DBA_EXTERNAL_LOCATIONS describes the locations (data sources) of all external tables in the database. Its columns are the same as those in ALL_EXTERNAL_LOCATIONS.

See Also: ["ALL_EXTERNAL_LOCATIONS"](#) on page 2-60

DBA_EXTERNAL_TABLES

DBA_EXTERNAL_TABLES describes all external tables in the database. Its columns are the same as those in ALL_EXTERNAL_TABLES.

See Also: ["ALL_EXTERNAL_TABLES"](#) on page 2-60

DBA_FEATURE_USAGE_STATISTICS

DBA_FEATURE_USAGE_STATISTICS displays information about database feature usage statistics.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database identifier of the database being tracked
NAME	VARCHAR2 (64)	NOT NULL	Name of the feature (see Table 4-1)
VERSION	VARCHAR2 (17)	NOT NULL	Database version in which the feature was tracked

Column	Datatype	NULL	Description
DETECTED_USAGES	NUMBER	NOT NULL	Number of times the system has detected usage for the feature
TOTAL_SAMPLES	NUMBER	NOT NULL	Number of times the system has woken up and checked for feature usage
CURRENTLY_USED	VARCHAR2 (5)		Indicates whether usage was detected the last time the system checked (TRUE) or not (FALSE)
FIRST_USAGE_DATE	DATE		First sample time the system detected usage of the feature
LAST_USAGE_DATE	DATE		Last sample time the system detected usage of the feature
AUX_COUNT	NUMBER		This column stores feature-specific usage data in number format.
FEATURE_INFO	CLOB		This column stores feature-specific usage data in character format.
LAST_SAMPLE_DATE	DATE		Amount of time (in seconds) between the last two usage sample times
LAST_SAMPLE_PERIOD	NUMBER		Amount of time (in hours) between the last two usage sample times
SAMPLE_INTERVAL	NUMBER		Sample interval
DESCRIPTION	VARCHAR2 (128)		Description of the feature and usage detection logic (see Table 4-1)

Table 4-1 DBA_FEATURE_USAGE_STATISTICS Statistics

Name	Description
Logfile Multiplexing	Multiple members are used in a single log file group
Bigfile Tablespace	Bigfile tablespace is being used
Transportable Tablespace	Transportable tablespace is being used
Read Only Tablespace	Read only tablespace is being used
Deferred Open Read Only	Deferred open read only feature is enabled
Active Data Guard - Real-Time Query on Physical Standby	Active Data Guard real-time query is enabled on a physical standby
Backup Rollforward	Backup Rollforward strategy is being used to backup the database.
Data Recovery Advisor	Data Recovery Advisor (DRA) is being used to repair the database.
Resource Manager	Oracle Database Resource Manager is being used to manage database resources.
Server Flash Cache	Database Smart Flash Cache is being used with this database.
Server Parameter File	The server parameter file (SPFILE) was used to startup the database.
Shared Server	The database is configured as Shared Server, where one server process can service multiple client programs.
Spatial	There is at least one usage of the Oracle Spatial index metadata table.
Locator	There is at least one usage of the Oracle Locator index metadata table.
ADDM	ADDM has been used.
SQL Access Advisor	SQL Access Advisor has been used.
Undo Advisor	Undo Advisor has been used.
SQL Tuning Advisor	SQL Tuning Advisor has been used.
Segment Advisor	Segment Advisor has been used.
SQL Workload Manager	SQL Workload Manager has been used.
Tune MView	Tune MView has been used.

Table 4–1 (Cont.) DBA_FEATURE_USAGE_STATISTICS Statistics

Name	Description
SQL Performance Analyzer	SQL Performance Analyzer has been used.
SQL Repair Advisor	SQL Repair Advisor has been used.
Advanced Replication	Advanced Replication has been enabled.
ASO native encryption and checksumming	ASO network native encryption and checksumming is being used.
Audit Options	Audit options in use.
Automatic Maintenance - Optimizer Statistics Gathering	Automatic initiation of Optimizer Statistics Collection
Automatic Maintenance - Space Advisor	Automatic initiation of Space Advisor
Automatic Maintenance - SQL Tuning Advisor	Automatic initiation of SQL Tuning Advisor
Automatic Segment Space Management (system)	Extents of locally managed tablespaces are managed automatically by Oracle.
Automatic Segment Space Management (user)	Extents of locally managed user tablespaces are managed automatically by Oracle.
Automatic SQL Execution Memory	Sizing of work areas for all dedicated sessions (PGA) is automatic.
Automatic Storage Management	Automatic Storage Management has been enabled
Automatic Undo Management	Oracle automatically manages undo data using an UNDO tablespace.
Automatic Workload Repository	A manual Automatic Workload Repository (AWR) snapshot was taken in the last sample period.
AWR Baseline	At least one AWR Baseline has been created by the user
AWR Baseline Template	At least one AWR Baseline Template has been created by the user
AWR Report	At least one Workload Repository Report has been created by the user
Backup Encryption	Encrypted backups are being used.
Baseline Adaptive Thresholds	Adaptive Thresholds have been configured.
Baseline Static Computations	Static baseline statistics have been computed.
Change-Aware Incremental Backup	Track blocks that have changed in the database.
Client Identifier	Application User Proxy Authentication: Client Identifier is used at this specific time.
Clusterwide Global Transactions	Clusterwide Global Transactions is being used.
Crossedition Triggers	Crossedition triggers is being used.
CSSCAN	Oracle Database has been scanned at least once for character set:CSSCAN has been run at least once.
Character Semantics	Character length semantics is used in Oracle Database
Character Set	Character set is used in Oracle Database
Data Guard	Data Guard, a set of services, is being used to create, maintain, manage, and monitor one or more standby databases.
Data Mining	There exist Oracle Data Mining models in the database.
Dynamic SGA	The Oracle SGA has been dynamically resized through an ALTER SYSTEM SET statement.
Editions	Editions is being used.
Editioning Views	Editioning views is being used.
EM Database Control	EM Database Control Home Page has been visited at least once.
EM Grid Control	EM Grid Control Database Home Page has been visited at least once.
Diagnostic Pack	Diagnostic Pack related EM page has been visited at least once.
Tuning Pack	Tuning Pack related EM page has been visited at least once.

Table 4–1 (Cont.) DBA_FEATURE_USAGE_STATISTICS Statistics

Name	Description
File Mapping	File Mapping, the mechanism that shows a complete mapping of a file to logical volumes and physical devices, is being used.
Flashback Database	Flashback Database, a rewind button for the database, is enabled
Flashback Data Archive	Flashback Data Archive, a historical repository of changes to data contained in a table, is used
Internode Parallel Execution	Internode Parallel Execution is being used.
Label Security	Oracle Label Security, that enables label-based access control Oracle applications, is being used.
Oracle Database Vault	Oracle Database Vault is being used
Locally Managed Tablespaces (system)	There exists tablespaces that are locally managed in the database.
Locally Managed Tablespaces (user)	There exists user tablespaces that are locally managed in the database.
Messaging Gateway	Messaging Gateway, that enables communication between non-Oracle messaging systems and Advanced Queuing (AQ), link configured.
Very Large Memory	Very Large Memory is enabled.
Automatic Memory Tuning	Automatic Memory Tuning is enabled.
Automatic SGA Tuning	Automatic SGA Tuning is enabled.
Encrypted Tablespaces	Encrypted Tablespaces is enabled.
MTTR Advisor	Mean Time to Recover Advisor is enabled.
Multiple Block Sizes	Multiple Block Sizes are being used with this database.
OLAP - Analytic Workspaces	OLAP - the analytic workspaces stored in the database.
OLAP - Cubes	OLAP - number of cubes in the OLAP catalog that are fully mapped and accessible by the OLAP API.
Oracle Managed Files	Database files are being managed by Oracle.
Oracle Secure Backup	Oracle Secure Backup is used for backups to tertiary storage.
Parallel SQL DDL Execution	Parallel SQL DDL Execution is being used.
Parallel SQL DML Execution	Parallel SQL DML Execution is being used.
Parallel SQL Query Execution	Parallel SQL Query Execution is being used.
Partitioning (system)	Oracle Partitioning option is being used - there is at least one partitioned object created.
Partitioning (user)	Oracle Partitioning option is being used - there is at least one user partitioned object created.
Oracle Text	Oracle Text is being used - there is at least one Oracle text index
PL/SQL Native Compilation	PL/SQL Native Compilation is being used - there is at least one natively compiled PL/SQL library unit in the database.
Real Application Clusters (RAC)	Oracle Real Application Clusters (Oracle RAC) is configured.
Recovery Area	The recovery area is configured.
Recovery Manager (RMAN)	Recovery Manager (RMAN) is being used to backup the database.
RMAN - Disk Backup	Recovery Manager (RMAN) is being used to backup the database to disk.
RMAN - Tape Backup	Recovery Manager (RMAN) is being used to backup the database to tape.
Backup ZLIB Compression	ZLIB compressed backups are being used.
Backup BZIP2 Compression	BZIP2 compressed backups are being used.
Backup BASIC Compression	BASIC compressed backups are being used.
Backup LOW Compression	LOW compressed backups are being used.
Backup MEDIUM Compression	MEDIUM compressed backups are being used.
Backup HIGH Compression	HIGH compressed backups are being used.

Table 4–1 (Cont.) DBA_FEATURE_USAGE_STATISTICS Statistics

Name	Description
Long-term Archival Backup	Long-term archival backups are being used.
Multi Section Backup	Multi section backups are being used.
Block Media Recovery	Block Media Recovery is being used to repair the database.
Restore Point	Restore Points are being used as targets for Flashback
Compression Advisor	Compression Advisor has been used.
Real-Time SQL Monitoring	Real-Time SQL Monitoring Usage.
SQL Tuning Set (user)	A SQL Tuning Set has been created in the database in a user schema.
SQL Tuning Set (system)	A SQL Tuning Set has been created in the database in the SYS schema.
Automatic SQL Tuning Advisor	Automatic SQL Tuning Advisor has been used.
SQL Profile	SQL profiles have been used.
Database Replay: Workload Capture	Database Replay: Workload was ever captured.
Database Replay: Workload Replay	Database Replay: Workload was ever replayed.
Streams (system)	Oracle Streams processes have been configured
Streams (user)	Users have configured Oracle Streams AQ
Transparent Gateway	Heterogeneous Connectivity, access to a non-Oracle system, has been configured.
Virtual Private Database (VPD)	Virtual Private Database (VPD) policies are being used.
Workspace Manager	There is at least one version enabled table.
XDB	XDB feature is being used.
Application Express	Application Express feature is being used.
LOB	Persistent LOBs are being used.
Object	Object feature is being used.
Extensibility	Extensibility feature is being used.
SQL Plan Management	SQL Plan Management has been used.
Rules Manager	Rules Manager and Expression Filter
Oracle Utility Datapump (Export)	Oracle Utility Datapump (Export) has been used.
Oracle Utility Datapump (Import)	Oracle Utility Datapump (Import) has been used.
Oracle Utility SQL Loader (Direct Path Load)	Oracle Utility SQL Loader (Direct Path Load) has been used.
Oracle Utility Metadata API	Oracle Utility (Metadata API) has been used.
Oracle Utility External Table	Oracle Utility External Table has been used.
Result Cache	The Result Cache feature has been used.
Transparent Data Encryption	Transparent Database Encryption is being used. There is at least one column or tablespace that is encrypted.
Oracle Multimedia	Oracle Multimedia has been used
Oracle Multimedia DICOM	Oracle Multimedia DICOM (Digital Imaging and COmmunications in Medicine) has been used
Materialized Views (User)	User Materialized Views exist in the database
Change Data Capture	Change Data Capture exit in the database
Services	Oracle Services.
Semantics/RDF	A semantic network has been created indicating usage of the Oracle Semantics Feature.
SecureFiles (user)	SecureFiles is being used
SecureFiles (system)	SecureFiles is being used by system users
SecureFile Encryption (user)	SecureFile Encryption is being used

Table 4–1 (Cont.) DBA_FEATURE_USAGE_STATISTICS Statistics

Name	Description
SecureFile Encryption (system)	SecureFile Encryption is being used by system users
SecureFile Compression (user)	SecureFile Compression is being used
SecureFile Compression (system)	SecureFile Compression is being used by system users
SecureFile Deduplication (user)	SecureFile Deduplication is being used
SecureFile Deduplication (system)	SecureFile Deduplication is being used by system users
Segment Advisor (user)	Segment Advisor has been used. There is at least one user task executed.
HeapCompression	Heap Compression is being used
Hybrid Columnar Compression	Hybrid Columnar Compression is used
Segment Shrink	Segment Shrink has been used.
Job Scheduler	Job Scheduler feature is being used.
Oracle Java Virtual Machine (user)	OJVM has been used by at least one non-system user
Oracle Java Virtual Machine (system)	OJVM default system users
Exadata	Exadata is being used

DBA_FGA_AUDIT_TRAIL

DBA_FGA_AUDIT_TRAIL displays all audit records for fine-grained auditing.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER	NOT NULL	Session id of the query
TIMESTAMP	DATE		Date and time of the query in the local database session time zone
DB_USER	VARCHAR2 (30)		Database username who executed the query
OS_USER	VARCHAR2 (255)		Operating system username who executed the query
USERHOST	VARCHAR2 (128)		Client host machine name
CLIENT_ID	VARCHAR2 (64)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2 (64)		Application execution context identifier
EXT_NAME	VARCHAR2 (4000)		External name
OBJECT_SCHEMA	VARCHAR2 (30)		Owner of the table or view
OBJECT_NAME	VARCHAR2 (128)		Name of the table or view
POLICY_NAME	VARCHAR2 (30)		Name of the Fine-Grained Auditing Policy
SCN	NUMBER		System change number (SCN) of the query
SQL_TEXT	NVARCHAR2 (2000)		SQL text of the query
SQL_BIND	NVARCHAR2 (2000)		Bind variable data of the query
COMMENT\$TEXT	VARCHAR2 (4000)		Comments
STATEMENT_TYPE	VARCHAR2 (7)		Statement type of the query: ■ SELECT ■ INSERT ■ UPDATE ■ DELETE
EXTENDED_TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Timestamp of the query in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism

Column	Datatype	NULL	Description
GLOBAL_UID	VARCHAR2 (32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2 (16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW (8)		Transaction identifier of the transaction in which the object is accessed or modified
STATEMENTID	NUMBER		Numeric ID for each statement run (a statement may cause many actions)
ENTRYID	NUMBER		Numeric ID for each audit trail entry in the session
OBJ_EDITION_NAME	VARCHAR2 (30)		Name of the edition containing the audited object
DBID	NUMBER		Database identifier of the audited database

Note: The SQL_BIND and SQL_TEXT columns are populated only if the policy has been created with the AUDIT_TRAIL parameter set to db, extended.

DBA_FILE_GROUP_EXPORT_INFO

DBA_FILE_GROUP_EXPORT_INFO shows export-related information for each version in the database that has a valid Data Pump dump file. Its columns are the same as those in ["ALL_FILE_GROUP_EXPORT_INFO"](#) on page 2-61.

DBA_FILE_GROUP_FILES

DBA_FILE_GROUP_FILES shows the file set for each versioned file group in the database. Its columns are the same as those in ["ALL_FILE_GROUP_FILES"](#) on page 2-62.

DBA_FILE_GROUP_TABLES

DBA_FILE_GROUP_TABLES shows information about all the tables in the database that can be imported using the file set. Its columns are the same as those in ["ALL_FILE_GROUP_TABLES"](#) on page 2-62.

DBA_FILE_GROUP_TABLESPACES

DBA_FILE_GROUP_TABLESPACES shows information about the transportable tablespaces present (partially or completely) in all file sets in the database (when the file set contains dump files). Its columns are the same as those in ["ALL_FILE_GROUP_TABLESPACES"](#) on page 2-63.

DBA_FILE_GROUP_VERSIONS

DBA_FILE_GROUP_VERSIONS shows top-level version information for all file groups in the database. Its columns are the same as those in ["ALL_FILE_GROUP_VERSIONS"](#) on page 2-63.

DBA_FILE_GROUPS

DBA_FILE_GROUPS shows top-level metadata about all file groups in the database. Its columns are the same as those for "[ALL_FILE_GROUPS](#)" on page 2-64.

DBA_FLASHBACK_ARCHIVE

DBA_FLASHBACK_ARCHIVE describes all flashback archives available in the database.

Related View

USER_FLASHBACK_ARCHIVE describes the flashback archives available to the current user.

Column	Datatype	NULL	Description
OWNER_NAME	VARCHAR2 (30)		Name of the creator of the flashback archive
FLASHBACK_ARCHIVE_NAME	VARCHAR2 (255)	NOT NULL	Name of the flashback archive
FLASHBACK_ARCHIVE#	NUMBER	NOT NULL	Number of the flashback archive
RETENTION_IN_DAYS	NUMBER	NOT NULL	Maximum duration (in days) for which data is retained in the flashback archive
CREATE_TIME	TIMESTAMP (9)		Time at which the flashback archive was created
LAST_PURGE_TIME	TIMESTAMP (9)		Time at which the data in the flashback archive was last purged by the system
STATUS	VARCHAR2 (7)		Indicates whether the flashback archive is a default flashback archive for the system (DEFAULT) or not (NULL)

See Also: "[USER_FLASHBACK_ARCHIVE](#)" on page 6-79

DBA_FLASHBACK_ARCHIVE_TABLES

DBA_FLASHBACK_ARCHIVE_TABLES displays information about all tables in the database that are enabled for Flashback Archive.

Related View

USER_FLASHBACK_ARCHIVE_TABLES displays information about the tables owned by the current user that are enabled for Flashback Archive.

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table enabled for Flashback Archive
OWNER_NAME	VARCHAR2 (30)	NOT NULL	Owner name of the table enabled for Flashback Archive
FLASHBACK_ARCHIVE_NAME	VARCHAR2 (255)	NOT NULL	Name of the flashback archive
ARCHIVE_TABLE_NAME	VARCHAR2 (53)		Name of the archive table containing the historical data for the user table

See Also: "[USER_FLASHBACK_ARCHIVE_TABLES](#)" on page 6-80

DBA_FLASHBACK_ARCHIVE_TS

DBA_FLASHBACK_ARCHIVE_TS describes all tablespaces in the flashback archives available in the database.

Column	Datatype	NULL	Description
FLASHBACK_ARCHIVE_NAME	VARCHAR2 (255)	NOT NULL	Name of the flashback archive
FLASHBACK_ARCHIVE#	NUMBER	NOT NULL	Number of the flashback archive
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of a tablespace in the flashback archive
QUOTA_IN_MB	VARCHAR2 (40)		Maximum space (in MB) that can be used for Flashback Archive from the tablespace; NULL indicates no Quota restriction

DBA_FLASHBACK_TXN_REPORT

DBA_FLASHBACK_TXN_REPORT displays information about all compensating transactions that have been committed in the database. Each row in this view is associated with one compensating transaction.

Related View

USER_FLASHBACK_TXN_REPORT displays information about the compensating transactions owned by the current user that have been committed in the database. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
COMPENSATING_XID	RAW (8)	NOT NULL	Transaction responsible for backout
COMPENSATING_TXN_NAME	VARCHAR2 (256)		Name of the compensating transaction
COMMIT_TIME	DATE		Timestamp when the compensating transaction committed
XID_REPORT	CLOB		An XML report describing the details of the transactions backed out by the compensating transaction
USERNAME	VARCHAR2 (30)	NOT NULL	User who is executing the compensating transaction

See Also: ["USER_FLASHBACK_TXN_REPORT"](#) on page 6-80

DBA_FLASHBACK_TXN_STATE

DBA_FLASHBACK_TXN_STATE displays information about the compensating status of all transactions in the database. For each compensating transaction, there could be multiple rows, where each row provides the dependency relation between the transactions that have been compensated by the compensating transaction.

Related View

USER_FLASHBACK_TXN_STATE displays information about the compensating status of the transactions owned by the current user. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
COMPENSATING_XID	RAW (8)		Transaction ID of the compensating transaction
XID	RAW (8)		A transaction that has been compensated by the compensating transaction

Column	Datatype	NULL	Description
DEPENDENT_XID	RAW (8)		A dependent transaction of XID Note: In the case of BACKOUT_MODE = CASCADE, there must be another row with XID = DEPENDENT_XID of this column.
BACKOUT_MODE	VARCHAR2 (16)		Mode in which XID was backed out: ■ NOCASCADE ■ NOCASCADE_FORCE ■ NONCONFLICT_ONLY ■ CASCADE
USERNAME	VARCHAR2 (30)	NOT NULL	User who is performing the compensating transaction

See Also: ["USER_FLASHBACK_TXN_STATE"](#) on page 6-80

DBA_FREE_SPACE

DBA_FREE_SPACE describes the free extents in all tablespaces in the database.

Note that if a datafile (or entire tablespace) is offline in a locally managed tablespace, you will not see any extent information. If an object has extents in an online file of the tablespace, you will see extent information about the offline datafile. However, if the object is entirely in the offline file, a query of this view will not return any records.

Related View

USER_FREE_SPACE describes the free extents in the tablespaces accessible to the current user.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the extent
FILE_ID	NUMBER		File identifier number of the file containing the extent
BLOCK_ID	NUMBER		Starting block number of the extent
BYTES	NUMBER		Size of the extent (in bytes)
BLOCKS	NUMBER		Size of the extent (in Oracle blocks)
RELATIVE_FNO	NUMBER		Relative file number of the file containing the extent

See Also: ["USER_FREE_SPACE"](#) on page 6-80

DBA_FREE_SPACE_COALESCED

DBA_FREE_SPACE_COALESCED describes statistics on coalesced space in all tablespaces in the database.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace
TOTAL_EXTENTS	NUMBER		Total number of free extents in the tablespace
EXTENTS_COALESCED	NUMBER		Total number of coalesced free extents in the tablespace
PERCENT_EXTENTS_COALESCED	NUMBER		Percentage of coalesced free extents in the tablespace
TOTAL_BYTES	NUMBER		Total number of free bytes in the tablespace

Column	Datatype	NULL	Description
BYTES_COALESCED	NUMBER		Total number of coalesced free bytes in the tablespace
TOTAL_BLOCKS	NUMBER		Total number of free Oracle blocks in the tablespace
BLOCKS_COALESCED	NUMBER		Total number of coalesced free Oracle blocks in the tablespace
PERCENT_BLOCKS _COALESCED	NUMBER		Percentage of coalesced free Oracle blocks in the tablespace

DBA_HIGH_WATER_MARK_STATISTICS

DBA_HIGH_WATER_MARK_STATISTICS displays information about database high-watermark statistics.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Identifier of the database for which the high-watermark statistics are tracked
NAME	VARCHAR2 (64)	NOT NULL	Name of the high-watermark statistic (see Table 4-2)
VERSION	VARCHAR2 (17)	NOT NULL	Database version in which the high watermarks were tracked
HIGHWATER	NUMBER		Highest value of the statistic seen at sampling time
LAST_VALUE	NUMBER		Value of the statistic at the last sample time
DESCRIPTION	VARCHAR2 (128)		Description of the high-watermark statistics (see Table 4-2)

Table 4-2 DBA_HIGH_WATER_MARK_STATISTICS Statistics

Name	Description
ACTIVE_SESSIONS	Maximum Number of Active Sessions seen in the system
CPU_COUNT	Maximum Number of CPUs
DATAFILES	Maximum Number of Datafiles
DB_SIZE	Maximum Size of the Database (Bytes)
EXADATA_DISKS	Number of physical disks
INSTANCES	Oracle Database instances
PART_INDEXES	Maximum Number of Partitions belonging to an User Index
PART_TABLES	Maximum Number of Partitions belonging to an User Table
QUERY_LENGTH	Maximum Query Length
SEGMENT_SIZE	Size of Largest Segment (Bytes)
SESSIONS	Maximum Number of Concurrent Sessions seen in the database
SQL_NCHAR_COLUMNS	Maximum Number of SQL NCHAR Columns
TABLESPACES	Maximum Number of Tablespaces
USER_INDEXES	Number of User Indexes
USER_MV	Maximum Number of Materialized Views (User)
USER_TABLES	Number of User Tables

DBA_HIST_ACTIVE_SESS_HISTORY

DBA_HIST_ACTIVE_SESS_HISTORY displays the history of the contents of the in-memory active session history of recent system activity. This view contains snapshots of V\$ACTIVE_SESSION_HISTORY. See "[V\\$ACTIVE_SESSION_HISTORY](#)"

on page 7-3 for further interpretation details for many of these columns (except SNAP_ID, DBID, and INSTANCE_NUMBER).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SAMPLE_ID	NUMBER	NOT NULL	ID of the sample
SAMPLE_TIME	TIMESTAMP (3)	NOT NULL	Time of the sample
SESSION_ID	NUMBER	NOT NULL	Session identifier
SESSION_SERIAL#	NUMBER		Session serial number (used to uniquely identify a session's objects)
SESSION_TYPE	VARCHAR2 (10)		Session type: ■ FOREGROUND ■ BACKGROUND
FLAGS	NUMBER		Reserved for future use
USER_ID	NUMBER		Oracle user identifier
SQL_ID	VARCHAR2 (13)		SQL identifier of the SQL statement that is currently being executed
IS_SQLID_CURRENT	VARCHAR2 (1)		Indicates whether the SQL identifier in the SQL_ID column is being executed (Y) or not (N)
SQL_CHILD_NUMBER	NUMBER		Child number of the SQL statement that is currently being executed
SQL_OPCODE	NUMBER		Indicates what phase of operation the SQL statement is in
SQL_OPNAME	VARCHAR2 (64)		SQL command name
FORCE_MATCHING_SIGNATURE	NUMBER		Signature used when the CURSOR_SHARING parameter is set to FORCE
TOP_LEVEL_SQL_ID	VARCHAR2 (13)		SQL identifier of the top level SQL statement
TOP_LEVEL_SQL_OPCODE	NUMBER		Indicates what phase of operation the top level SQL statement was in
SQL_PLAN_HASH_VALUE	NUMBER		Numerical representation of the SQL plan for the cursor
SQL_PLAN_LINE_ID	NUMBER		SQL plan line ID
SQL_PLAN_OPERATION	VARCHAR2 (64)		Plan operation name
SQL_PLAN_OPTIONS	VARCHAR2 (64)		Plan operation options
SQL_EXEC_ID	NUMBER		SQL execution identifier
SQL_EXEC_START	DATE		Time when the execution of the SQL started
PLSQL_ENTRY_OBJECT_ID	NUMBER		Object ID of the top-most PL/SQL subprogram on the stack (or NULL if there is no PL/SQL subprogram on the stack)
PLSQL_ENTRY_SUBPROGRAM_ID	NUMBER		Subprogram ID of the top-most PL/SQL subprogram on the stack (or NULL if there is no PL/SQL subprogram on the stack)
PLSQL_OBJECT_ID	NUMBER		Object ID of the currently executing PL/SQL subprogram (or NULL if executing SQL)
PLSQL_SUBPROGRAM_ID	NUMBER		Subprogram ID of the currently executing PL/SQL object (or NULL if executing SQL)
QC_INSTANCE_ID	NUMBER		Query coordinator instance ID
QC_SESSION_ID	NUMBER		Query coordinator session ID

Column	Datatype	NULL	Description
QC_SESSION_SERIAL#	NUMBER		Query coordinator session serial number
PX_FLAGS ¹	NUMBER		Reserved for internal use
EVENT	VARCHAR2 (64)		If SESSION_STATE = WAITING, then the event for which the session was waiting at the time of sampling. If SESSION_STATE = ON CPU, then this column will be NULL.
EVENT_ID	NUMBER		Identifier of the resource or event for which the session is waiting or for which the session last waited
SEQ#	NUMBER		Sequence number that uniquely identifies the wait (incremented for each wait)
P1TEXT	VARCHAR2 (64)		Text of first additional parameter
P1	NUMBER		First additional parameter
P2TEXT	VARCHAR2 (64)		Text of second additional parameter
P2	NUMBER		Second additional parameter
P3TEXT	VARCHAR2 (64)		Text of third additional parameter
P3	NUMBER		Third additional parameter
WAIT_CLASS	VARCHAR2 (64)		Wait class name of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V\$SESSION.WAIT_CLASS.
WAIT_CLASS_ID	NUMBER		Wait class identifier of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V\$SESSION.WAIT_CLASS_ID.
WAIT_TIME	NUMBER		Total wait time for the event for which the session last waited (0 if currently waiting)
SESSION_STATE	VARCHAR2 (7)		Session state: ■ WAITING ■ ON CPU
TIME_WAITED	NUMBER		Time that the current session actually spent waiting for the event. This column is set for waits that were in progress at the time the sample was taken.
BLOCKING_SESSION_STATUS	VARCHAR2 (11)		Status of the blocking session: ■ VALID ■ NO HOLDER ■ GLOBAL ■ NOT IN WAIT ■ UNKNOWN
BLOCKING_SESSION	NUMBER		Session identifier of the blocking session. Populated only when the session was waiting for enqueues or a "buffer busy" wait. Maps to V\$SESSION.BLOCKING_SESSION.
BLOCKING_SESSION_SERIAL#	NUMBER		Serial number of the blocking session
BLOCKING_INST_ID	NUMBER		Instance number of the blocker shown in BLOCKING_SESSION
BLOCKING_HANGCHAIN_INFO	VARCHAR2 (1)		Indicates whether the information about BLOCKING_SESSION comes from the hang chain (Y) or not (N)
CURRENT_OBJ#	NUMBER		Object ID of the object that the session is currently referencing. This information is only available if the session was waiting for Application, Cluster, Concurrency, and User I/O wait events. Maps to V\$SESSION.ROW_WAIT_OBJ#.

Column	Datatype	NULL	Description
CURRENT_FILE#	NUMBER		File number of the file containing the block that the session is currently referencing. This information is only available if the session was waiting for Cluster, Concurrency, and User I/O wait events. Maps to V\$SESSION.ROW_WAIT_FILE#.
CURRENT_BLOCK#	NUMBER		ID of the block that the session is currently referencing
CURRENT_ROW#	NUMBER		Row identifier that the session is referencing
TOP_LEVEL_CALL#	NUMBER		Oracle top level call number
TOP_LEVEL_CALL_NAME	VARCHAR2 (64)		Oracle top level call name
CONSUMER_GROUP_ID	NUMBER		Consumer group ID
XID	RAW (8)		Transaction ID that the session was working on at the time of sampling. V\$SESSION does not contain this information.
REMOTE_INSTANCE#	NUMBER		Remote instance identifier that will serve the block that this session is waiting for. This information is only available if the session was waiting for cluster events.
TIME_MODEL	NUMBER		Time model information
IN_CONNECTION_MGMT	VARCHAR2 (1)		Indicates whether the session was doing connection management at the time of sampling (Y) or not (N)
IN_PARSE	VARCHAR2 (1)		Indicates whether the session was parsing at the time of sampling (Y) or not (N)
IN_HARD_PARSE	VARCHAR2 (1)		Indicates whether the session was hard parsing at the time of sampling (Y) or not (N)
IN_SQL_EXECUTION	VARCHAR2 (1)		Indicates whether the session was executing SQL statements at the time of sampling (Y) or not (N)
IN_PLSQL_EXECUTION	VARCHAR2 (1)		Indicates whether the session was executing PL/SQL at the time of sampling (Y) or not (N)
IN_PLSQL_RPC	VARCHAR2 (1)		Indicates whether the session was executing inbound PL/SQL RPC calls at the time of sampling (Y) or not (N)
IN_PLSQL_COMPILATION	VARCHAR2 (1)		Indicates whether the session was compiling PL/SQL at the time of sampling (Y) or not (N)
IN_JAVA_EXECUTION	VARCHAR2 (1)		Indicates whether the session was executing Java at the time of sampling (Y) or not (N)
IN_BIND	VARCHAR2 (1)		Indicates whether the session was doing bind operations at the time of sampling (Y) or not (N)
IN_CURSOR_CLOSE	VARCHAR2 (1)		Indicates whether the session was closing a cursor at the time of sampling (Y) or not (N)
IN_SEQUENCE_LOAD	VARCHAR2 (1)		Indicates whether the session is loading in sequence (in sequence load code) (Y) or not (N)
CAPTURE_OVERHEAD	VARCHAR2 (1)		Indicates whether the session is executing capture code (Y) or not (N)
REPLAY_OVERHEAD	VARCHAR2 (1)		Indicates whether the session is executing replay code (Y) or not (N)
IS_CAPTURED	VARCHAR2 (1)		Indicates whether the session is being captured (Y) or not (N)
IS_REPLAYED	VARCHAR2 (1)		Indicates whether the session is being replayed (Y) or not (N)
SERVICE_HASH	NUMBER		Hash that identifies the Service
PROGRAM	VARCHAR2 (64)		Name of the operating system program
MODULE ²	VARCHAR2 (48)		Name of the currently executing module as set by the DBMS_APPLICATION_INFO.SET_MODULE procedure
ACTION ²	VARCHAR2 (32)		Name of the currently executing action as set by the DBMS_APPLICATION_INFO.SET_ACTION procedure

Column	Datatype	NULL	Description
CLIENT_ID	VARCHAR2 (64)		Client identifier of the session
MACHINE	VARCHAR2 (64)		Client's operating system machine name
PORT	NUMBER		Client port number
ECID	VARCHAR2 (64)		Execution context identifier (sent by Application Server)
DBREPLAY_FILE_ID ¹	NUMBER		If the session is being captured or replayed, then DBREPLAY_FILE_ID is the file ID for the workload capture or workload replay; otherwise it is NULL.
DBREPLAY_CALL_COUNTER ¹	NUMBER		If the session is being captured or replayed, then DBREPLAY_CALL_COUNTER is the call counter of the user call that is being captured or replayed; otherwise it is NULL.
TM_DELTA_TIME	NUMBER		Time interval (in microseconds) over which TM_DELTA_CPU_TIME and TM_DELTA_DB_TIME are accumulated
TM_DELTA_CPU_TIME	NUMBER		Amount of time this session spent on CPU over the last TM_DELTA_TIME microseconds
TM_DELTA_DB_TIME	NUMBER		Amount of time spent by this session in database calls over the last TM_DELTA_TIME microseconds
DELTA_TIME	NUMBER		Time interval (in microseconds) since the last time this session was sampled or created, over which the next five statistics are accumulated
DELTA_READ_IO_REQUESTS	NUMBER		Number of read I/O requests made by this session over the last DELTA_TIME microseconds
DELTA_WRITE_IO_REQUESTS	NUMBER		Number of write I/O requests made by this session over the last DELTA_TIME microseconds
DELTA_READ_IO_BYTES	NUMBER		Number of I/O bytes read by this session over the last DELTA_TIME microseconds
DELTA_WRITE_IO_BYTES	NUMBER		Number of I/O bytes written by this session over the last DELTA_TIME microseconds
DELTA_INTERCONNECT_IO_BYTES	NUMBER		Number of I/O bytes sent over the I/O interconnect over the last DELTA_TIME microseconds
PGA_ALLOCATED	NUMBER		Amount of PGA memory (in bytes) consumed by this session at the time this sample was taken
TEMP_SPACE_ALLOCATED	NUMBER		Amount of TEMP memory (in bytes) consumed by this session at the time this sample was taken

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

² The datatype of this column is VARCHAR2 (64) starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_HIST_BASELINE

DBA_HIST_BASELINE displays information on baselines taken in the system. For each baseline, this view displays the complete time range and whether the baseline is the default baseline.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
BASLINE_ID	NUMBER	NOT NULL	Internal ID for the baseline
BASLINE_NAME	VARCHAR2 (64)		User-specified name for the baseline

Column	Datatype	NULL	Description
BASELINE_TYPE	VARCHAR2 (13)		The baseline type, as follows: STATIC - baselines that are created manually by the user MOVING WINDOW - baselines that have dynamic start and end snapshot IDs GENERATED - baselines that are automatically generated by the system, using a template
START_SNAP_ID	NUMBER		Start snapshot ID for the baseline
START_SNAP_TIME	TIMESTAMP (3)		Time associated with the start snapshot ID
END_SNAP_ID	NUMBER		End snapshot ID for the baseline
END_SNAP_TIME	TIMESTAMP (3)		Time associated with the end snapshot ID
MOVING_WINDOW_SIZE	NUMBER		If BASELINE_TYPE is MOVING WINDOW, this field is the size of the moving window in number of days. If NULL, then the window size is the value of the AWR retention setting.
CREATION_TIME	DATE		Time the baseline was created
EXPIRATION	NUMBER		How long to keep the baseline, in number of days. A NULL value means that the baseline will be kept forever.
TEMPLATE_NAME	VARCHAR2 (64)		Name of the template that created this baseline, if any.
LAST_TIME_COMPUTED	DATE		Last time that statistics were computed on the baseline.

DBA_HIST_BASELINE_DETAILS

DBA_HIST_BASELINE_DETAILS displays details about the baseline.

Column	Datatype	NULL	Description
DBID	NUMBER		Database ID
INSTANCE_NUMBER	NUMBER		Instance ID for the baseline data
BASELINE_ID	NUMBER		Internal ID for the baseline
BASELINE_NAME	VARCHAR2 (64)		User-specified name for the baseline
BASELINE_TYPE	VARCHAR2 (13)		The baseline type, as follows: STATIC - baselines that are created manually by the user MOVING WINDOW - baselines that have dynamic start and end snapshot IDs GENERATED - baselines that are automatically generated by the system, using a template
START_SNAP_ID	NUMBER		Start snapshot ID for the baseline
START_SNAP_TIME	TIMESTAMP (3)		Start snapshot time for the baseline
END_SNAP_ID	NUMBER		End snapshot ID for the baseline
END_SNAP_TIME	TIMESTAMP (3)		End snapshot time for the baseline
SHUTDOWN	VARCHAR2 (3)		Whether or not there is a database startup or shutdown in this interval (YES, NO, or NULL).
ERROR_COUNT	NUMBER		Number of errors in the snapshots in the baseline snapshot range
PCT_TOTAL_TIME	NUMBER		Amount of time captured in snapshots, divided by the total possible time for this baseline
LAST_TIME_COMPUTED	DATE		Last time that statistics were computed on the baseline

Column	Datatype	NULL	Description
MOVING_WINDOW_SIZE	NUMBER		If BASELINE_TYPE is MOVING WINDOW, this field is the size of the moving window in number of days. If NULL, then the window size is the value of the AWR retention setting.
CREATION_TIME	DATE		Time the baseline was created
EXPIRATION	NUMBER		How long to keep the baseline, in number of days. A value of NULL indicates that the baseline will be kept forever.
TEMPLATE_NAME	VARCHAR2 (64)		Name of the template that created this baseline, if any.

DBA_HIST_BASELINE_METADATA

DBA_HIST_BASELINE_METADATA displays metadata information for the baseline.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
BASLINE_ID	NUMBER	NOT NULL	Internal ID for the baseline
BASLINE_NAME	VARCHAR2 (64)		User-specified name for the baseline
BASLINE_TYPE	VARCHAR2 (13)		The baseline type, as follows: STATIC - baselines that are created manually by the user MOVING WINDOW - baselines that have dynamic start and end snapshot IDs GENERATED - baselines that are automatically generated by the system, using a template
START_SNAP_ID	NUMBER		Start snapshot ID for the baseline
END_SNAP_ID	NUMBER		End snapshot ID for the baseline
MOVING_WINDOW_SIZE	NUMBER		If BASELINE_TYPE is MOVING WINDOW, this field is the size of the moving window in number of days. If NULL, then the window size is the value of the AWR retention setting.
CREATION_TIME	DATE		Time the baseline was created
EXPIRATION	NUMBER		How long to keep the baseline, in number of days. If the value is NULL, the baseline will be kept forever.
TEMPLATE_NAME	VARCHAR2 (64)		Name of the template that created this baseline, if any
LAST_TIME_COMPUTED	DATE		Last time that statistics were computed on the baseline

DBA_HIST_BASELINE_TEMPLATE

DBA_HIST_BASELINE_TEMPLATE displays the templates used by the system for baseline generation. The system uses this information to determine which baselines should be automatically created or removed.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
TEMPLATE_ID	NUMBER	NOT NULL	Internal ID for the template
TEMPLATE_NAME	VARCHAR2 (30)	NOT NULL	Name of the template
TEMPLATE_TYPE	VARCHAR2 (9)	NOT NULL	Type of the template, as follows: SINGLE - one time period REPEATING - maintain a time period

Column	Datatype	NULL	Description
BASLINE_NAME_PREFIX	VARCHAR2 (30)	NOT NULL	Name to use for the baselines that are created: For a template type of SINGLE, the BASELINE_NAME_PREFIX is the name that will be used. For a template type of REPEATING, the BASELINE_NAME will be the prefix to the name.
START_TIME	DATE	NOT NULL	For a template type of SINGLE, this is the start time for future baselines For a template type of REPEATING, this is the effective start time that baselines should start being generated.
END_TIME	DATE	NOT NULL	For a template type of SINGLE, this is the end time for future baselines. For a template type of REPEATING, this is the effective end time that baselines should stop being generated.
DAY_OF_WEEK	VARCHAR2 (9)		For a template type of REPEATING, this indicates the day of the week to create the baseline: SUNDAY, MONDAY, TUESDAY, WEDNESDAY, THURSDAY, FRIDAY, SATURDAY, ALL.
HOURL_IN_DAY	NUMBER		For a template type of REPEATING, a value from 0 - 23 to indicate the hour of the day to create the baseline for.
DURATION	NUMBER		For a template type of REPEATING, the length of time for the baseline to be created.
EXPIRATION	NUMBER		How long to keep the baseline, in number of days
REPEAT_INTERVAL	VARCHAR2 (128)		String that represents the time repeating information in the format used by the DBMS_SCHEDULER package
LAST_GENERATED	DATE		Last time a baseline was generated for this template

DBA_HIST_BG_EVENT_SUMMARY

DBA_HIST_BG_EVENT_SUMMARY displays the historical summary background event activity. This view contains snapshots from V\$SESSION_EVENT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
EVENT_ID	NUMBER	NOT NULL	Identifier of the wait event
EVENT_NAME	VARCHAR2 (64)	NOT NULL	Name of the wait event
WAIT_CLASS_ID	NUMBER		Identifier of the class of the wait event
WAIT_CLASS	VARCHAR2 (64)		Name of the class of the wait event
TOTAL_WAITS	NUMBER		Total number of waits for the event
TOTAL_TIMEOUTS	NUMBER		Total number of timeouts for the event
TIME_WAITED_MICRO	NUMBER		Total amount of time waited for the event (in microseconds)

DBA_HIST_BUFFER_POOL_STAT

DBA_HIST_BUFFER_POOL_STAT displays historical statistics about all buffer pools available for the instance. This view contains snapshots of V\$BUFFER_POOL_STATISTICS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
ID	NUMBER	NOT NULL	Buffer pool identifier number
NAME	VARCHAR2 (20)		Name of the buffer pool
BLOCK_SIZE	NUMBER		Block Size
SET_MSIZE	NUMBER		Buffer pool maximum set size
CNUM_REPL	NUMBER		Number of buffers on the replacement list
CNUM_WRITE	NUMBER		Number of buffers on the write list
CNUM_SET	NUMBER		Number of buffers in the set
BUF_GOT	NUMBER		Number of buffers gotten by the set
SUM_WRITE	NUMBER		Number of buffers written by the set
SUM_SCAN	NUMBER		Number of buffers scanned in the set
FREE_BUFFER_WAIT	NUMBER		Free buffer wait statistic
WRITE_COMPLETE_WAIT	NUMBER		Write complete wait statistic
BUFFER_BUSY_WAIT	NUMBER		Buffer busy wait statistic
FREE_BUFFER_INSPECTED	NUMBER		Free buffer inspected statistic
DIRTY_BUFFERS_INSPECTED	NUMBER		Dirty buffers inspected statistic
DB_BLOCK_CHANGE	NUMBER		Database blocks changed statistic
DB_BLOCK_GETS	NUMBER		Database blocks gotten statistic
CONSISTENT_GETS	NUMBER		Consistent gets statistic
PHYSICAL_READS	NUMBER		Physical reads statistic
PHYSICAL_WRITES	NUMBER		Physical writes statistic

DBA_HIST_BUFFERED_QUEUES

DBA_HIST_BUFFERED_QUEUES displays historical information about all buffered queues available for the instance.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_SCHEMA	VARCHAR2 (30)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue
STARTUP_TIME	DATE	NOT NULL	Startup time of the instance
QUEUE_ID	NUMBER	NOT NULL	ID of the queue
NUM_MSGS	NUMBER		Total number of outstanding messages currently enqueued in the buffered queue for the subscriber (includes the count of the messages overflowed to disk)
SPILL_MSGS	NUMBER		Current number of overflow messages spilled to disk from the buffered queue
CNUM_MSGS	NUMBER		Cumulative total number of messages enqueued into the buffered queue since the buffered queue was created.

Column	Datatype	NULL	Description
CSPILL_MSGS	NUMBER		Cumulative total number of overflow messages spilled to disk from the buffered queue since the buffered queue was created
EXPIRED_MSGS ¹	NUMBER		Number of expired messages
OLDEST_MSGID ¹	RAW (16)		Message ID of the oldest message
OLDEST_MSG_ENQTM ¹	TIMESTAMP (3)		Enqueue time of the oldest message
QUEUE_STATE ¹	VARCHAR2 (25)		Indicates whether the queue is in recovery mode (QUEUE IS IN RECOVERY MODE) or not (NORMAL)
ELAPSED_ENQUEUE_TIME ¹	NUMBER		Total time spent in enqueue (in hundredths of a second)
ELAPSED_DEQUEUE_TIME ¹	NUMBER		Total time spent in dequeue (in hundredths of a second)
ELAPSED_TRANSFORMATION_TIME ¹	NUMBER		Total time for evaluating transformations (in hundredths of a second)
ELAPSED_RULE_EVALUATION_TIME ¹	NUMBER		Total time for rule evaluations (in hundredths of a second)
ENQUEUE_CPU_TIME ¹	NUMBER		Total CPU time for enqueue (in hundredths of a second)
DEQUEUE_CPU_TIME ¹	NUMBER		Total CPU time for dequeue (in hundredths of a second)
LAST_ENQUEUE_TIME ¹	TIMESTAMP (3)		Last message enqueue time
LAST_DEQUEUE_TIME ¹	TIMESTAMP (3)		Last message dequeue time

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_HIST_BUFFERED_SUBSCRIBERS

DBA_HIST_BUFFERED_SUBSCRIBERS displays historical information about the subscribers for all buffered queues in the instance.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_SCHEMA	VARCHAR2 (30)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue
SUBSCRIBER_ID	NUMBER	NOT NULL	Internal subscriber number (for identification)
SUBSCRIBER_NAME	VARCHAR2 (30)		Name of the subscriber
SUBSCRIBER_ADDRESS	VARCHAR2 (1024)		Address of the subscribing agent
SUBSCRIBER_TYPE	VARCHAR2 (30)		Type of subscriber: ■ PROXY - Proxy subscriber ■ SUBSCRIBOR
STARTUP_TIME	DATE	NOT NULL	Startup time of the instance
LAST_BROWSED_SEQ ¹	NUMBER		Sequence number of the most recently browsed message for the subscriber (comparable to the number of messages in the V\$STREAMS_APPLY_READER view)
LAST_BROWSED_NUM ¹	NUMBER		Internal Message number for the most recently browsed message for the subscriber
LAST_DEQUEUE_SEQ ¹	NUMBER		Sequence number of the most recently dequeued message for the subscriber (comparable to the number of messages in the V\$STREAMS_APPLY_COORDINATOR view)

Column	Datatype	NULL	Description
LAST_DEQUEUED_NUM ¹	NUMBER		Internal Message number for the most recently dequeued message for the subscriber
CURRENT_ENQ_SEQ ¹	NUMBER		Current sequence number of the most recently enqueued message for the subscriber
NUM_MSGS	NUMBER		Total number of outstanding messages currently enqueued in the buffered queue for the subscriber (includes the count of the messages overflowed to disk)
CNUM_MSGS	NUMBER		Cumulative total number of messages enqueued for the subscriber since the creation of the buffered queue
TOTAL_DEQUEUED_MSG ¹	NUMBER		Total number of messages dequeued by the subscriber
TOTAL_SPILLED_MSG	NUMBER		Total number of spilled messages for the subscriber
EXPIRED_MSGS ¹	NUMBER		Number of expired messages
MESSAGE_LAG ¹	NUMBER		Message lag of the subscriber
ELAPSED_DEQUEUE_TIME ¹	NUMBER		Total time spent in dequeue (in hundredths of a second)
DEQUEUE_CPU_TIME ¹	NUMBER		Total CPU time for dequeue (in hundredths of a second)
LAST_DEQUEUE_TIME ¹	TIMESTAMP (3)		Last message dequeue time
OLDEST_MSGID ¹	RAW (16)		Message ID of the oldest message
OLDEST_MSG_ENQTM ¹	TIMESTAMP (3)		Enqueue time of the oldest message

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_HIST_CLUSTER_INTERCON

DBA_HIST_CLUSTER_INTERCON displays information about the devices used by the instance to access the interconnect (that is, communicate with other instances).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAME	VARCHAR2 (256)	NOT NULL	Operating system name of the device
IP_ADDRESS	VARCHAR2 (64)		IP address of the device
IS_PUBLIC	VARCHAR2 (3)		Indicates whether the device is a public interface (YES) or a private interface (NO) Public interfaces can be listened to by outside applications, which may be a security problem. Oracle recommends using private interfaces for interconnect.
SOURCE	VARCHAR2 (31)		Describes the type of device

DBA_HIST_COLORED_SQL

DBA_HIST_COLORED_SQL displays the SQL IDs that have been marked for AWR SQL capture. If a SQL statement is colored using the DBMS_WORKLOAD_REPOSITORY.ADD_COLORED_SQL procedure, then AWR will always capture the SQL statistics for the colored SQL ID. A SQL statement can be removed from coloring using the DBMS_WORKLOAD_REPOSITORY.REMOVE_COLORED_SQL procedure.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID

Column	Datatype	NULL	Description
SQL_ID	VARCHAR2 (13)	NOT NULL	SQL ID of colored SQL statement
CREATE_TIME	DATE	NOT NULL	Time the SQL ID was colored

DBA_HIST_COMP_IOSTAT

DBA_HIST_COMP_IOSTAT displays information about I/O statistics aggregated on the component level.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
COMPONENT	VARCHAR2 (64)	NOT NULL	Component name
FILE_TYPE	VARCHAR2 (64)	NOT NULL	File type
IO_TYPE	CHAR (5)	NOT NULL	The type of I/O performed
OPERATION	CHAR (5)	NOT NULL	Operation name
BYTES	NUMBER	NOT NULL	Number of bytes
IO_COUNT	NUMBER	NOT NULL	Number of I/Os that were performed

DBA_HIST_CR_BLOCK_SERVER

DBA_HIST_CR_BLOCK_SERVER displays historical statistics on the Global Cache Service processes (IMS) used in cache fusion. This view contains snapshots of V\$CR_BLOCK_SERVER.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
CR_REQUESTS	NUMBER		Number of CR blocks served due to remote CR block requests
CURRENT_REQUESTS	NUMBER		Number of current blocks served due to remote CR block requests CR_REQUESTS + CURRENT_REQUESTS = global cache CR blocks served (from V\$SYSTAT).
DATA_REQUESTS	NUMBER		Number of current or CR requests for data blocks
UNDO_REQUESTS	NUMBER		Number of CR requests for undo blocks
TX_REQUESTS	NUMBER		Number of CR requests for undo segment header blocks DATA_REQUESTS + UNDO_REQUESTS + TX_REQUESTS = total number of requests handled by the LMS processes
CURRENT_RESULTS	NUMBER		Number of requests for which no changes were rolled out of the block returned to the requesting instance
PRIVATE_RESULTS	NUMBER		Number of requests for which changes were rolled out of the block returned to the requesting instance, and only the requesting transaction can use the resulting CR block
ZERO_RESULTS	NUMBER		Number of requests for which changes were rolled out of the block returned to the requesting instance. Only zero-XID transactions can use the block.

Column	Datatype	NULL	Description
DISK_READ_RESULTS	NUMBER		Number of requests for which the requesting instance had to read the requested block from disk
FAIL_RESULTS	NUMBER		Number of requests that failed; the requesting transaction must reissue the request
FAIRNESS_DOWN_CONVERTS	NUMBER		Number of times an instance receiving a request has down-converted an X lock on a block because it was not modifying the block
FAIRNESS_CLEARS	NUMBER		Number of times the fairness counter was cleared. This counter tracks the number of times a block was modified after it was served.
FREE_GC_ELEMENTS	NUMBER		Number of times a request was received from another instance and the X lock had no buffers
FLUSHES	NUMBER		Number of times the log has been flushed by an LMS process
FLUSHES_QUEUED	NUMBER		Number of flushes queued by an LMS process
FLUSH_QUEUE_FULL	NUMBER		Number of times the flush queue was full
FLUSH_MAX_TIME	NUMBER		Maximum time for flush
LIGHT_WORKS	NUMBER		Number of times the light-work rule was evoked. This rule prevents the LMS processes from going to disk while responding to CR requests for data, undo, or undo segment header blocks. This rule can prevent the LMS process from completing its response to the CR request.
ERRORS	NUMBER		Number of times an error was signalled by an LMS process

DBA_HIST_CURRENT_BLOCK_SERVER

DBA_HIST_CURRENT_BLOCK_SERVER displays historical statistics on the Global Cache Service processes (IMS) used in cache fusion. This view contains snapshots of V\$CURRENT_BLOCK_SERVER.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
PIN1	NUMBER		Pins taking less than 1 millisecond
PIN10	NUMBER		Pins taking 1 to 10 milliseconds
PIN100	NUMBER		Pins taking 10 to 100 milliseconds
PIN1000	NUMBER		Pins taking 100 to 1000 milliseconds
PIN10000	NUMBER		Pins taking 1000 to 10000 milliseconds
FLUSH1	NUMBER		Flushes taking less than 1 millisecond
FLUSH10	NUMBER		Flushes taking 1 to 10 milliseconds
FLUSH100	NUMBER		Flushes taking 10 to 100 milliseconds
FLUSH1000	NUMBER		Flushes taking 100 to 1000 milliseconds
FLUSH10000	NUMBER		Flushes taking 1000 to 10000 milliseconds
WRITE1	NUMBER		Writes taking less than 1 millisecond
WRITE10	NUMBER		Writes taking 1 to 10 milliseconds
WRITE100	NUMBER		Writes taking 10 to 100 milliseconds
WRITE1000	NUMBER		Writes taking 100 to 1000 milliseconds

Column	Datatype	NULL	Description
WRITE10000	NUMBER		Writes taking 1000 to 10000 milliseconds

DBA_HIST_DATABASE_INSTANCE

DBA_HIST_DATABASE_INSTANCE displays the databases and instances in the Workload Repository.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number
STARTUP_TIME	TIMESTAMP (3)	NOT NULL	Startup time of the instance
PARALLEL	VARCHAR2 (3)	NOT NULL	Indicates whether the instance is running in an Oracle Real Application Clusters (Oracle RAC) environment (YES) or not (NO)
VERSION	VARCHAR2 (17)	NOT NULL	Database version
DB_NAME	VARCHAR2 (9)		Name of the database
INSTANCE_NAME	VARCHAR2 (16)		Name of the instance
HOST_NAME	VARCHAR2 (64)		Name of the host
LAST_ASH_SAMPLE_ID	NUMBER	NOT NULL	Last sample ID for the active session history

DBA_HIST_DATAFILE

DBA_HIST_DATAFILE displays a history of the datafile information from the control file. This view contains snapshots of V\$DATAFILE.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
FILE#	NUMBER	NOT NULL	File identification number
CREATION_CHANGE#	NUMBER	NOT NULL	Change number at which the datafile was created
FILENAME	VARCHAR2 (513)	NOT NULL	Name of the datafile
TS#	NUMBER	NOT NULL	Tablespace number
TSNAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace
BLOCK_SIZE	NUMBER		Block size of the datafile

DBA_HIST_DB_CACHE_ADVICE

DBA_HIST_DB_CACHE_ADVICE displays historical predictions of the number of physical reads for the cache size corresponding to each row. This view contains snapshots of V\$DB_CACHE_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BPID	NUMBER	NOT NULL	Buffer Pool identifier (ranges from 1 to 8)
BUFFERS_FOR_ESTIMATE	NUMBER	NOT NULL	Cache size for prediction (in terms of buffers)
NAME	VARCHAR2 (20)		Buffer pool name

Column	Datatype	NULL	Description
BLOCK_SIZE	NUMBER		Block size in bytes for buffers in the pool (the standard block size, the power of 2 non-standard block sizes, 2048, 4096, 8192, 16384, or 32768)
ADVICE_STATUS	VARCHAR2 (3)		Status of the advisory: - ON - Currently running - OFF - Disabled (the estimates are historical and calculated when last enabled)
SIZE_FOR_ESTIMATE	NUMBER		Cache size for prediction (in megabytes)
SIZE_FACTOR	NUMBER		Size factor with respect to the current cache size
PHYSICAL_READS	NUMBER		Physical reads for the cache size
BASE_PHYSICAL_READS	NUMBER		Base physical reads for the cache size
ACTUAL_PHYSICAL_READS	NUMBER		Actual physical reads for the cache size
ESTD_PHYSICAL_READ_TIME	NUMBER		Estimated physical read time for the cache size

DBA_HIST_DISPATCHER

DBA_HIST_DISPATCHER displays historical information for each dispatcher process present at the time of the snapshot. This view contains snapshots of information from V\$DISPATCHER and V\$QUEUE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAME	VARCHAR2 (4)	NOT NULL	Name of the dispatcher process
SERIAL#	NUMBER		Serial number of the dispatcher process
IDLE	NUMBER		Total idle time for the dispatcher (in hundredths of a second)
BUSY	NUMBER		Total busy time for the dispatcher (in hundredths of a second)
WAIT	NUMBER		Total time that all items in the dispatcher queue have waited (in hundredths of a second). Divide by TOTALQ for average wait per item.
TOTALQ	NUMBER		Total number of items that have ever been in the dispatcher queue
SAMPLED_TOTAL_CONN	NUMBER		Cumulative sum of total number of connections to the dispatcher over all samples. To determine the average number of connections to the dispatcher between two snapshots, divide the difference in SAMPLED_TOTAL_CONN by the difference in NUM_SAMPLES (obtained from DBA_HIST_SHARED_SERVER_SUMMARY).

DBA_HIST_DLM_MISC

DBA_HIST_DLM_MISC displays miscellaneous Oracle Real Application Clusters (Oracle RAC) statistics. This view contains snapshots of V\$DLM_MISC.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot

Column	Datatype	NULL	Description
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
STATISTIC#	NUMBER		Statistic number
NAME	VARCHAR2 (38)		Statistic name
VALUE	NUMBER		Statistic value

DBA_HIST_DYN_REMASTER_STATS

DBA_HIST_DYN_REMASTER_STATS displays historical statistical information about the dynamic remastering process. All times are given in hundredths of a second, and total values reflect what has been collected since instance startup. This view contains snapshots of V\$DYNAMIC_REMASTER_STATS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
REMASTER_OPS	NUMBER		Total number of dynamic remastering operations
REMASTER_TIME	NUMBER		Total dynamic remastering time
REMASTERED_OBJECTS	NUMBER		Total number of objects dynamically remastered due to affinity
QUIESCE_TIME	NUMBER		Total quiesce step time
FREEZE_TIME	NUMBER		Total freeze step time
CLEANUP_TIME	NUMBER		Total cleanup step time
REPLAY_TIME	NUMBER		Total replay step time
FIXWRITE_TIME	NUMBER		Total fixwrite step time
SYNC_TIME	NUMBER		Total synchronization step time
RESOURCES_CLEANED	NUMBER		Total number of resources cleaned in the cleanup steps
REPLAYED_LOCKS_SENT	NUMBER		Total number of locks replayed to other instances in the replay steps
REPLAYED_LOCKS_RECEIVED	NUMBER		Total number of locks received from other instances in the replay steps
CURRENT_OBJECTS	NUMBER		Current number of objects remastered on this instance due to affinity

DBA_HIST_ENQUEUE_STAT

DBA_HIST_ENQUEUE_STAT displays historical statistics on the number of enqueue (lock) requests for each type of lock. This view contains snapshots of V\$ENQUEUE_STATISTICS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
EQ_TYPE	VARCHAR2 (2)	NOT NULL	Type of enqueue requested
REQ_REASON	VARCHAR2 (64)	NOT NULL	Reason for the enqueue request

DBA_HIST_EVENT_HISTOGRAM

Column	Datatype	NULL	Description
TOTAL_REQ#	NUMBER		Total number of enqueue requests or enqueue conversions for this type of enqueue
TOTAL_WAIT#	NUMBER		Total number of times an enqueue request or conversion resulted in a wait
SUCC_REQ#	NUMBER		Number of times an enqueue request or conversion was granted
FAILED_REQ#	NUMBER		Number of times an enqueue request or conversion failed
CUM_WAIT_TIME	NUMBER		Total amount of time (in milliseconds) spent waiting for the enqueue or enqueue conversion
EVENT#	NUMBER		Event number

DBA_HIST_EVENT_HISTOGRAM

DBA_HIST_EVENT_HISTOGRAM displays event histogram historical statistics information. This view contains snapshots of V\$EVENT_HISTOGRAM.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
EVENT_ID	NUMBER	NOT NULL	Identifier of the wait event
EVENT_NAME	VARCHAR2 (64)	NOT NULL	Name of the wait event
WAIT_CLASS_ID	NUMBER		Identifier of the class of the wait event
WAIT_CLASS	VARCHAR2 (64)		Name of the class of the wait event
WAIT_TIME_MILLI	NUMBER	NOT NULL	Wait time (in milliseconds)
WAIT_COUNT	NUMBER		Wait count

DBA_HIST_EVENT_NAME

DBA_HIST_EVENT_NAME displays information about wait events. This view contains a snapshot of V\$EVENT_NAME.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
EVENT_ID	NUMBER	NOT NULL	Identifier of the wait event
EVENT_NAME	VARCHAR2 (64)	NOT NULL	Name of the wait event
PARAMETER1	VARCHAR2 (64)		Description of the first parameter for the wait event
PARAMETER2	VARCHAR2 (64)		Description of the second parameter for the wait event
PARAMETER3	VARCHAR2 (64)		Description of the third parameter for the wait event
WAIT_CLASS_ID	NUMBER		Identifier of the class of the wait event
WAIT_CLASS	VARCHAR2 (64)		Name of the class of the wait event

DBA_HIST_FILEMETRIC_HISTORY

DBA_HIST_FILEMETRIC_HISTORY displays the history of file metrics collected in the Workload Repository.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FILEID	NUMBER	NOT NULL	File number
CREATIONTIME	NUMBER	NOT NULL	File creation time
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	ID of the group to which the file belongs
AVGREADTIME	NUMBER	NOT NULL	Average file read time
AVGWRTETIME	NUMBER	NOT NULL	Average file write time
PHYSICALREAD	NUMBER	NOT NULL	Number of physical reads
PHYSICALWRITE	NUMBER	NOT NULL	Number of physical writes
PHYBLKREAD	NUMBER	NOT NULL	Number of physical block reads
PHYBLKWRITE	NUMBER	NOT NULL	Number of physical block writes

DBA_HIST_FILESTATXS

DBA_HIST_FILESTATXS displays information about file read/write statistics. This view contains snapshots of V\$FILESTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
FILE#	NUMBER		File identification number
CREATION_CHANGE#	NUMBER		Change number at which the datafile was created
FILENAME	VARCHAR2 (513)		Name of the datafile
TS#	NUMBER		Tablespace number
TSNAME	VARCHAR2 (30)		Name of the tablespace
BLOCK_SIZE	NUMBER		Block size of the datafile
PHYRDS	NUMBER		Number of physical reads done
PHYWRTS	NUMBER		Number of times DBWR is required to write
SINGLEBLKRDS	NUMBER		Number of single block reads
READTIM	NUMBER		Time (in hundredths of a second) spent doing reads if the TIMED_STATISTICS parameter is true; 0 if TIMED_STATISTICS is false
WRITETIM	NUMBER		Time (in hundredths of a second) spent doing writes if the TIMED_STATISTICS parameter is true; 0 if TIMED_STATISTICS is false
SINGLEBLKRDTIM	NUMBER		Cumulative single block read time (in hundredths of a second)
PHYBLKRD	NUMBER		Number of physical blocks read
PHYBLKWRT	NUMBER		Number of blocks written to disk, which may be the same as PHYWRTS if all writes are single blocks
WAIT_COUNT	NUMBER		Wait Count

Column	Datatype	NULL	Description
TIME	NUMBER		Wait Time

DBA_HIST_IC_CLIENT_STATS

DBA_HIST_IC_CLIENT_STATS displays information about the usage of an interconnect device by the instance. The information is divided into several areas of the Oracle Database, each identified by the NAME value.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAME	VARCHAR2 (9)	NOT NULL	Identifies the area of the Oracle Database: - ipq - Parallel query communications - d1m - Database lock management - cache - Global cache communications All other values are internal to Oracle and are not expected to have high usage.
BYTES_SENT	NUMBER		Number of bytes sent by the instance since instance startup for the software area identified by NAME. This information is aggregated across all devices used by the instance.
BYTES_RECEIVED	NUMBER		Number of bytes received by the instance since instance startup for the software area identified by NAME. This information is aggregated across all devices used by the instance.

DBA_HIST_IC_DEVICE_STATS

DBA_HIST_IC_DEVICE_STATS displays operating system information about the usage of interconnect devices by the machine. This usage contains Oracle usage but is not limited to it. The quality of the information depends on the operating system.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
IF_NAME	VARCHAR2 (256)	NOT NULL	Name of the device (same as NAME in DBA_HIST_CLUSTER_INTERCON)
IP_ADDR	VARCHAR2 (64)	NOT NULL	IP address of the device (same as IP_ADDRESS in DBA_HIST_CLUSTER_INTERCON)
NET_MASK	VARCHAR2 (16)		Network mask
FLAGS	VARCHAR2 (32)		Flags
MTU	NUMBER		Maximum transmission unit
BYTES_RECEIVED	NUMBER		Number of bytes received since OS start time
PACKETS_RECEIVED	NUMBER		Number of packets received since OS start time
RECEIVE_ERRORS	NUMBER		Number of receive errors since OS start time
RECEIVE_DROPPED	NUMBER		Number of receive messages that were dropped
RECEIVE_BUF_OR	NUMBER		Number of receive buffer overruns experienced

Column	Datatype	NULL	Description
RECEIVE_FRAME_ERR	NUMBER		Number of receive errors due to frame error
BYTES_SENT	NUMBER		Number of bytes sent since OS start time
PACKETS_SENT	NUMBER		Number of packets sent since OS start time
SEND_ERRORS	NUMBER		Number of send errors since OS start time
SENDS_DROPPED	NUMBER		Number of send messages that were dropped
SEND_BUF_OR	NUMBER		Number of send buffer overruns experienced
SEND_CARRIER_LOST	NUMBER		Number of send errors due to carrier lost

DBA_HIST_INST_CACHE_TRANSFER

DBA_HIST_INST_CACHE_TRANSFER displays the historical statistics on the cache blocks transferred among instances. This view contains snapshots of V\$INSTANCE_CACHE_TRANSFER.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
INSTANCE	NUMBER		Instance from which the blocks are transferred
CLASS	VARCHAR2 (18)		Class of the cache block
CR_BLOCK	NUMBER		CR block transfers not affected by remote processing delays
CR_BUSY	NUMBER		Current block transfers affected by remote contention
CR_CONGESTED	NUMBER		CR block transfers affected by remote system load
CURRENT_BLOCK	NUMBER		Current block transfers not affected by remote processing delays
CURRENT_BUSY	NUMBER		Current block transfers affected by remote contention
CURRENT_CONGESTED	NUMBER		Current block transfers affected by remote system load
LOST	NUMBER		The number of blocks that were sent by a particular instance but that never arrived in this instance
CR_2HOP	NUMBER		The count of CR blocks which were received by this instance from a particular instance after a 2-way round-trip
CR_3HOP	NUMBER		The count of CR blocks which were received by this instance from a particular instance after a 3-way round-trip
CURRENT_2HOP	NUMBER		The count of current blocks which were received by this instance from a particular instance after a 2-way roundtrip
CURRENT_3HOP	NUMBER		The count of current blocks which were received by this instance from a particular instance after a 3-way roundtrip
CR_BLOCK_TIME	NUMBER		Total time waited for CR blocks from a particular instance (includes the other times)
CR_BUSY_TIME	NUMBER		The time waited for CR blocks which were received by this instance from a particular instance and which were delayed by a log flushed on the sending instance
CR_CONGESTED_TIME	NUMBER		The time waited for CR blocks which were received by this instance from a particular instance and which were delayed because LMS was busy

Column	Datatype	NULL	Description
CURRENT_BLOCK_TIME	NUMBER		Total time waited for CR blocks from a particular instance (includes the other times)
CURRENT_BUSY_TIME	NUMBER		The time waited for current blocks which were received by this instance from a particular instance and which were delayed by a log flushed on the sending instance
CURRENT_CONGESTED_TIME	NUMBER		The time waited for current blocks which were received by this instance from a particular instance and which were delayed because LMS was busy
LOST_TIME	NUMBER		The time waited for blocks that were sent by a particular instance but that never arrived in this instance
CR_2HOP_TIME	NUMBER		The time waited for CR blocks which were received by this instance from a particular instance after a 2-way round-trip
CR_3HOP_TIME	NUMBER		The time waited for CR blocks which were received by this instance from a particular instance after a 3-way round-trip
CURRENT_2HOP_TIME	NUMBER		The time waited for current blocks which were received by this instance from a particular instance after a 2-way roundtrip
CURRENT_3HOP_TIME	NUMBER		The time waited for current blocks which were received by this instance from a particular instance after a 3-way roundtrip

DBA_HIST_INSTANCE_RECOVERY

DBA_HIST_INSTANCE_RECOVERY displays the historical monitoring of the mechanisms available to the user to limit recovery I/O. This view contains snapshots of V\$INSTANCE_RECOVERY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
RECOVERY_ESTIMATED_IOS	NUMBER		Number of dirty buffers in the buffer cache. In the Standard Edition, this column is always null.
ACTUAL_REDO_BKLS	NUMBER		Current actual number of redo blocks required for recovery
TARGET_REDO_BKLS	NUMBER		Current target number of redo blocks that must be processed for recovery. This value is the minimum value of the following 3 columns, and identifies which of the 3 user-defined limits determines checkpointing.
LOG_FILE_SIZE_REDO_BKLS	NUMBER		Maximum number of redo blocks required to guarantee that a log switch does not occur before the checkpoint completes
LOG_CHKPT_TIMEOUT_REDO_BKLS	NUMBER		Number of redo blocks that need to be processed during recovery to satisfy the LOG_CHECKPOINT_TIMEOUT parameter. The value displayed is not meaningful unless LOG_CHECKPOINT_TIMEOUT has been set.
LOG_CHKPT_INTERVAL_REDO_BKLS	NUMBER		Number of redo blocks that need to be processed during recovery to satisfy the LOG_CHECKPOINT_INTERVAL parameter. The value displayed is not meaningful unless LOG_CHECKPOINT_INTERVAL has been set.
FAST_START_IO_TARGET_REDO_BKLS	NUMBER		This column is obsolete and maintained for backward compatibility. The value of this column is always null.

Column	Datatype	NULL	Description
TARGET_MTTR	NUMBER		Effective MTTR (mean time to recover) target value in seconds. The TARGET_MTTR value is calculated based on the value of the FAST_START_MTTR_TARGET parameter (the TARGET_MTTR value is used internally), and is usually an approximation of the parameter's value. However, if the FAST_START_MTTR_TARGET parameter value is very small (for example, one second), or very large (for example, 3600 seconds), then the calculation will produce a target value dictated by system limitations. In such cases, the TARGET_MTTR value will be the shortest calculated time, or the longest calculated time that recovery is expected to take. If FAST_START_MTTR_TARGET is not specified, then the value of this field is the current estimated MTTR.
ESTIMATED_MTTR	NUMBER		Current estimated mean time to recover (MTTR) based on the number of dirty buffers and log blocks (0 if FAST_START_MTTR_TARGET is not specified). This value tells you how long you can expect recovery to take based on the work the system is doing right now.
CKPT_BLOCK_WRITES	NUMBER		Number of blocks written by checkpoint writes
OPTIMAL_LOGFILE_SIZE	NUMBER		Redo log file size (in megabytes) that is considered optimal based on the current setting of FAST_START_MTTR_TARGET. It is recommended that all online redo logs be configured to be at least this value.
ESTD_CLUSTER_AVAILABLE_TIME	NUMBER		Estimated time (in seconds) that the cluster would become partially available should the instance fail. This column is only meaningful in an Oracle Real Application Clusters (Oracle RAC) environment. In a non-Oracle RAC environment, the value of this column is null.
WRITES_MTTR	NUMBER		Number of writes driven by the FAST_START_MTTR_TARGET parameter
WRITES_LOGFILE_SIZE	NUMBER		Number of writes driven by the smallest redo log file size
WRITES_LOG_CHECKPOINT_SETTINGS	NUMBER		Number of writes driven by the LOG_CHECKPOINT_INTERVAL parameter or the LOG_CHECKPOINT_TIMEOUT parameter
WRITES_OTHER_SETTINGS	NUMBER		Number of writes driven by other reasons (such as the deprecated FAST_START_IO_TARGET parameter)
WRITES_AUTOTUNE	NUMBER		Number of writes due to auto-tune checkpointing
WRITES_FULL_THREAD_CKPT	NUMBER		Number of writes due to full thread checkpoints

DBA_HIST_INTERCONNECT_PINGS

DBA_HIST_INTERCONNECT_PINGS displays information about measured latency of interconnect messages (round-trip) from instance to instance. In Oracle Database 11g, the PING process assesses the latencies associated with communications for each pair of instances.

Every few seconds, the process in one instance (INSTANCE_NUMBER value) sends two messages to each instance (TARGET_INSTANCE value). One message has a size of 500 bytes and the other has a size of 8 KB. The message is received by the PING process on the target instance and is immediately acknowledged. The time for the round-trip is measured and collected.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
TARGET_INSTANCE	NUMBER	NOT NULL	Target instance number
CNT_500B	NUMBER		Number of pings of size 500 bytes from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER)
WAIT_500B	NUMBER		Sum of round-trip times for messages of size 500 bytes from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER). Dividing by CNT_500B gives the average latency.
WAITSQ_500B	NUMBER		Sum of squares (divided by 1000) of round-trip times for messages of size 500 bytes from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER). When used with CNT_500B and WAIT_500B, the standard deviation of the latency can be calculated.
CNT_8K	NUMBER		Number of pings of size 8 KB from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER)
WAIT_8K	NUMBER		Sum of round-trip times for messages of size 8 KB from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER). Dividing by CNT_8K gives the average latency.
WAITSQ_8K	NUMBER		Sum of squares (divided by 1000) of round-trip times for messages of size 8 KB from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER). When used with CNT_8K and WAIT_8K, the standard deviation of the latency can be calculated.

DBA_HIST_IOSTAT_DETAIL

DBA_HIST_IOSTAT_DETAIL displays I/O statistics aggregated by combination of file type and function (component). This view contains snapshots of V\$IOSTAT_FILE and V\$IOSTAT_FUNCTION.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FUNCTION_ID	NUMBER	NOT NULL	Function ID
FUNCTION_NAME	VARCHAR2 (30)	NOT NULL	Function name
FILETYPE_ID	NUMBER	NOT NULL	Type of file (for example, log file, data file, and so on)
FILETYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the file, in the case of a data file or temp file. For all other files, a corresponding string to be displayed (for example, ARCHIVELOG).
SMALL_READ_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	NOT NULL	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	NOT NULL	Number of single block write requests

Column	Datatype	NULL	Description
LARGE_READ_REQS	NUMBER	NOT NULL	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	NOT NULL	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	NOT NULL	Number of I/O waits by functionality
WAIT_TIME	NUMBER	NOT NULL	Total wait time (in milliseconds)

DBA_HIST_IOSTAT_FILETYPE

DBA_HIST_IOSTAT_FILETYPE displays historical I/O statistics by file type. This view contains snapshots of V\$IOSTAT_FILE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FILETYPE_ID	NUMBER	NOT NULL	Type of file (for example, log file, data file, and so on)
FILETYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the file, in the case of a data file or temp file. For all other files, a corresponding string to be displayed (for example, ARCHIVELOG).
SMALL_READ_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	NOT NULL	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	NOT NULL	Number of single block write requests
SMALL_SYNC_READ_REQS	NUMBER	NOT NULL	Number of synchronous single block read requests
LARGE_READ_REQS	NUMBER	NOT NULL	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	NOT NULL	Number of multiblock write requests
SMALL_READ_SERVICETIME	NUMBER	NOT NULL	Total service time (in milliseconds) for single block read requests
SMALL_WRITE_SERVICETIME	NUMBER	NOT NULL	Total service time (in milliseconds) for single block write requests
SMALL_SYNC_READ_LATENCY	NUMBER	NOT NULL	Latency for single block synchronous reads (in milliseconds)
LARGE_READ_SERVICETIME	NUMBER	NOT NULL	Total service time (in milliseconds) for multiblock read requests
LARGE_WRITE_SERVICETIME	NUMBER	NOT NULL	Total service time (in milliseconds) for multiblock write requests
RETRIES_ON_ERROR	NUMBER	NOT NULL	Number of read retries on error

DBA_HIST_IOSTAT_FILETYPE_NAME

DBA_HIST_IOSTAT_FILETYPE_NAME displays historical I/O statistics for file type names. This view contains snapshots of V\$IOSTAT_FILE.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
FILETYPE_ID	NUMBER	NOT NULL	Type of file (for example, log file, data file, and so on)

Column	Datatype	NULL	Description
FILETYPE_NAME	VARCHAR2 (30)	NOT NULL	Name of the file, in the case of a data file or temp file. For all other files, a corresponding string to be displayed (for example, ARCHIVELOG).

DBA_HIST_IOSTAT_FUNCTION

DBA_HIST_IOSTAT_FUNCTION displays historical I/O statistics by function. This view contains snapshots of V\$IOSTAT_FUNCTION.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FUNCTION_ID	NUMBER	NOT NULL	Function ID
FUNCTION_NAME	VARCHAR2 (30)	NOT NULL	Function name
SMALL_READ_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	NOT NULL	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	NOT NULL	Number of single block write requests
LARGE_READ_REQS	NUMBER	NOT NULL	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	NOT NULL	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	NOT NULL	Number of I/O waits by functionality
WAIT_TIME	NUMBER	NOT NULL	Total wait time (in milliseconds)

DBA_HIST_IOSTAT_FUNCTION_NAME

DBA_HIST_IOSTAT_FUNCTION_NAME displays historical I/O statistics by function names. This view contains snapshots of V\$IOSTAT_FUNCTION.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
FUNCTION_ID	NUMBER	NOT NULL	Function ID
FUNCTION_NAME	VARCHAR2 (30)	NOT NULL	Function name

DBA_HIST_JAVA_POOL_ADVICE

DBA_HIST_JAVA_POOL_ADVICE displays historical information about estimated parse time in the Java pool for different pool sizes. This view contains snapshots of V\$JAVA_POOL_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot

Column	Datatype	NULL	Description
JAVA_POOL_SIZE_FOR_ESTIMATE	NUMBER	NOT NULL	Java pool size for the estimate (in megabytes)
JAVA_POOL_SIZE_FACTOR	NUMBER		Size factor with respect to the current Java pool size
ESTD_LC_SIZE	NUMBER		Estimated memory in use by the library cache (in megabytes)
ESTD_LC_MEMORY_OBJECTS	NUMBER		Estimated number of library cache memory objects in the Java pool of the specified size
ESTD_LC_TIME_SAVED	NUMBER		Estimated elapsed parse time saved (in seconds), owing to library cache memory objects being found in a Java pool of the specified size. This is the time that would have been spent in reloading the required objects in the Java pool had they been aged out due to insufficient amount of available free memory.
ESTD_LC_TIME_SAVED_FACTOR	NUMBER		Estimated parse time saved factor with respect to the current Java pool size
ESTD_LC_LOAD_TIME	NUMBER		Estimated elapsed time (in seconds) for parsing in a Java pool of the specified size.
ESTD_LC_LOAD_TIME_FACTOR	NUMBER		Estimated load time factor with respect to the current Java pool size
ESTD_LC_MEMORY_OBJECT_HITS	NUMBER		Estimated number of times a library cache memory object was found in a Java pool of the specified size

Static Data Dictionary Views: DBA_HIST_LATCH to DBA_STORED_SETTINGS

This chapter contains the static data dictionary views DBA_HIST_LATCH through DBA_STORED_SETTINGS.

DBA_HIST_LATCH

DBA_HIST_LATCH displays historical aggregate latch statistics for both parent and child latches, grouped by latch name. This view contains snapshots of V\$LATCH.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
LATCH_HASH	NUMBER		Latch Hash
LATCH_NAME	VARCHAR2 (64)		Latch name
LEVEL#	NUMBER		Latch level
GETS	NUMBER		Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER		Number of times the latch was requested in willing-to-wait mode and the requestor had to wait
SLEEPS	NUMBER		Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER		Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER		Number of times a no-wait latch request did not succeed (that is, missed)
SPIN_GETS	NUMBER		Number of willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP[1 2 3 4]	NUMBER		These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero.
WAIT_TIME	NUMBER		Elapsed time spent waiting for the latch (in microseconds)

DBA_HIST_LATCH_CHILDREN

DBA_HIST_LATCH_CHILDREN displays historical statistics about child latches. This view includes all columns of DBA_HIST_LATCH plus the CHILD# column. Note that

child latches have the same parent if their LATCH# columns match each other. This view contains snapshots of V\$LATCH_CHILDREN.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
LATCH_HASH	NUMBER		Latch Hash
LATCH_NAME	VARCHAR2 (64)		Latch name
CHILD#	NUMBER		Child latch number (unique only to each parent latch)
GETS	NUMBER		Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER		Number of times the latch was requested in willing-to-wait mode and the requestor had to wait
SLEEPS	NUMBER		Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER		Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER		Number of times a no-wait latch request did not succeed (that is, missed)
SPIN_GETS	NUMBER		Number of willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP[1 2 3 4]	NUMBER		These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero.
WAIT_TIME	NUMBER		Elapsed time spent waiting for the latch (in microseconds)

DBA_HIST_LATCH_MISSES_SUMMARY

DBA_HIST_LATCH_MISSES_SUMMARY displays historical summary statistics about missed attempts to acquire a latch. This view contains snapshots of V\$LATCH_MISSES.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
PARENT_NAME	VARCHAR2 (50)		Latch name of a parent latch
WHERE_IN_CODE	VARCHAR2 (64)		Location that attempted to acquire the latch
NWFAIL_COUNT	NUMBER		Number of times that no-wait acquisition of the latch failed
SLEEP_COUNT	NUMBER		Number of times that acquisition attempts caused sleeps
WTR_SLP_COUNT	NUMBER		Number of times a waiter slept

DBA_HIST_LATCH_NAME

DBA_HIST_LATCH_NAME displays information about decoded latch names for the latches shown in DBA_HIST_LATCH. This view contains a snapshot of V\$LATCHNAME.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
LATCH_HASH	NUMBER	NOT NULL	Latch hash
LATCH_NAME	VARCHAR2 (64)	NOT NULL	Latch name

DBA_HIST_LATCH_PARENT

DBA_HIST_LATCH_PARENT displays historical statistics about parent latches. This view contains snapshots of V\$LATCH_PARENT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
LATCH_HASH	NUMBER		Latch hash
LATCH_NAME	VARCHAR2 (64)		Latch name
LEVEL#	NUMBER		Latch level
GETS	NUMBER		Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER		Number of times the latch was requested in willing-to-wait mode and the requestor had to wait
SLEEPS	NUMBER		Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER		Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER		Number of times a no-wait latch request did not succeed (that is, missed)
SPIN_GETS	NUMBER		Number of willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP[1 2 3 4]	NUMBER		These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero.
WAIT_TIME	NUMBER		Elapsed time spent waiting for the latch (in microseconds)

DBA_HIST_LIBRARYCACHE

DBA_HIST_LIBRARYCACHE displays historical statistics about library cache performance and activity. This view contains snapshots of V\$LIBRARYCACHE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAMESPACE	VARCHAR2 (15)	NOT NULL	Library cache namespace
GETS	NUMBER		Number of times a lock was requested for objects of the namespace
GETHITS	NUMBER		Number of times an object's handle was found in memory
PINS	NUMBER		Number of times a PIN was requested for objects of the namespace

Column	Datatype	NULL	Description
PINHITS	NUMBER		Number of times all of the metadata pieces of the library object were found in memory
RELOADS	NUMBER		Any PIN of an object that is not the first PIN performed since the object handle was created, and which requires loading the object from disk
INVALIDATIONS	NUMBER		Total number of times objects in the namespace were marked invalid because a dependent object was modified
DLM_LOCK_REQUESTS	NUMBER		Number of GET requests lock instance locks
DLM_PIN_REQUESTS	NUMBER		Number of PIN requests lock instance locks
DLM_PIN_RELEASES	NUMBER		Number of release requests PIN instance locks
DLM_INVALIDATION_REQUESTS	NUMBER		Number of GET requests for invalidation instance locks
DLM_INVALIDATIONS	NUMBER		Number of invalidation pings received from other instances

DBA_HIST_LOG

DBA_HIST_LOG displays historical log file information from the control file. This view contains snapshots of V\$LOG.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
GROUP#	NUMBER	NOT NULL	Log group number
THREAD#	NUMBER	NOT NULL	Log thread number
SEQUENCE#	NUMBER	NOT NULL	Log sequence number
BYTES	NUMBER		Size of the log (in bytes)
MEMBERS	NUMBER		Number of members in the log group
ARCHIVED	VARCHAR2 (3)		Archive status (YES) or NO

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (16)		Log status: ■ UNUSED - Online redo log has never been written to. This is the state of a redo log that was just added, or just after a RESETLOGS, when it is not the current redo log. ■ CURRENT - Current redo log. This implies that the redo log is active. The redo log could be open or closed. ■ ACTIVE - Log is active but is not the current log. It is needed for crash recovery. It may be in use for block recovery. It may or may not be archived. ■ CLEARING - Log is being re-created as an empty log after an ALTER DATABASE CLEAR LOGFILE statement. After the log is cleared, the status changes to UNUSED. ■ CLEARING_CURRENT - Current log is being cleared of a closed thread. The log can stay in this status if there is some failure in the switch such as an I/O error writing the new log header. ■ INACTIVE - Log is no longer needed for instance recovery. It may be in use for media recovery. It may or may not be archived. ■ INVALIDATED - Archived the current redo log without a log switch.
FIRST_CHANGE#	NUMBER		Lowest system change number (SCN) in the log
FIRST_TIME	DATE		Time of the first SCN in the log

DBA_HIST_MEM_DYNAMIC_COMP

DBA_HIST_MEM_DYNAMIC_COMP displays historical memory component sizes. This view contains snapshots of V\$MEMORY_DYNAMIC_COMPONENTS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
COMPONENT	VARCHAR2 (64)	NOT NULL	Component name
CURRENT_SIZE	NUMBER		Current size of the component
MIN_SIZE	NUMBER		Minimum size of the component since instance startup
MAX_SIZE	NUMBER		Maximum size of the component since instance startup
USER_SPECIFIED_SIZE	NUMBER		Value of the user parameter for the component
OPER_COUNT	NUMBER		Number of operations since instance startup
LAST_OPER_TYPE	VARCHAR2 (13)		Last completed operation for the component: ■ STATIC ■ INITIALIZING ■ DISABLED ■ GROW ■ SHRINK ■ SHRINK_CANCEL

Column	Datatype	NULL	Description
LAST_OPER_MODE	VARCHAR2 (9)		Mode of the last completed operation: - MANUAL - DEFERRED - IMMEDIATE
LAST_OPER_TIME	DATE		Start time of the last completed operation
GRANULE_SIZE	NUMBER		Granularity of the GROW or SHRINK operation

DBA_HIST_MEMORY_RESIZE_OPS

DBA_HIST_MEMORY_RESIZE_OPS displays memory resize operations history. This view contains snapshots of V\$MEMORY_RESIZE_OPS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
COMPONENT	VARCHAR2 (64)	NOT NULL	Component name
OPER_TYPE	VARCHAR2 (13)	NOT NULL	Operation type: - STATIC - INITIALIZING - DISABLED - GROW - SHRINK - SHRINK_CANCEL
START_TIME	DATE	NOT NULL	Start time of the operation
END_TIME	DATE	NOT NULL	End time of the operation
TARGET_SIZE	NUMBER	NOT NULL	Requested value of the parameter after the resize
OPER_MODE	VARCHAR2 (9)		Operation mode: - MANUAL - DEFERRED - IMMEDIATE
PARAMETER	VARCHAR2 (80)		Name of the parameter for the resize operation
INITIAL_SIZE	NUMBER		Parameter value at the start of the operation
FINAL_SIZE	NUMBER		Real value of the parameter after the resize
STATUS	VARCHAR2 (9)		Completion status of the operation: - INACTIVE - PENDING - COMPLETE - CANCELLED - ERROR

DBA_HIST_MEMORY_TARGET_ADVICE

DBA_HIST_MEMORY_TARGET_ADVICE displays memory target advice history. This view contains snapshots of V\$MEMORY_TARGET_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
MEMORY_SIZE	NUMBER	NOT NULL	If the MEMORY_SIZE_FACTOR column has a value of 1, then this column shows the current size of memory, as set by the MEMORY_TARGET initialization parameter. If the value of the MEMORY_SIZE_FACTOR column is less than or greater than 1, then this column shows a proposed memory size.
MEMORY_SIZE_FACTOR	NUMBER		A multiplier for the current memory size. Possible values are 0.25, 0.5, 0.75, 1, 1.5, 1.75 and 2. This multiplier times the current memory size equals the value of the MEMORY_SIZE column.
ESTD_DB_TIME	NUMBER		For current memory size (MEMORY_SIZE_FACTOR = 1), the amount of database time required to complete the current workload. For a proposed memory size, the estimated amount of database time that would be required if the MEMORY_TARGET parameter were changed to the proposed size.
ESTD_DB_TIME_FACTOR	NUMBER		For a proposed memory size, ratio of estimated database time to current database time
VERSION	NUMBER		Version number of this recommendation

DBA_HIST_METRIC_NAME

DBA_HIST_METRIC_NAME describes attributes of the set of RDBMS metrics. This view contains a snapshot of V\$METRICNAME.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
GROUP_ID	NUMBER	NOT NULL	Metric Group ID
GROUP_NAME	VARCHAR2 (64)		Metric group name
METRIC_ID	NUMBER	NOT NULL	Metric ID
METRIC_NAME	VARCHAR2 (64)	NOT NULL	Metric name
METRIC_UNIT	VARCHAR2 (64)	NOT NULL	Unit of measurement

DBA_HIST_MTTR_TARGET_ADVICE

DBA_HIST_MTTR_TARGET_ADVICE displays historical predictions of the number of physical I/O requests for the MTTR corresponding to each row. The data also includes a physical I/O factor, which is the ratio of the number of estimated I/O requests to the number of I/O requests actually performed by the current MTTR setting during the measurement interval. This view contains snapshots of V\$MTTR_TARGET_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
MTTR_TARGET_FOR_ESTIMATE	NUMBER		MTTR setting being simulated (equal to the current MTTR setting if this is the first row of the view)

Column	Datatype	NULL	Description
ADVICE_STATUS	VARCHAR2 (5)		Current status of MTTR simulation: ■ ON SET ■ READY SET ■ OFF
DIRTY_LIMIT	NUMBER		Dirty buffer limit derived from the MTTR being simulated
ESTD_CACHE_WRITES	NUMBER		Estimated number of cache physical writes under the MTTR
ESTD_CACHE_WRITE_FACTOR	NUMBER		Estimated cache physical write ratio under the MTTR. It is the ratio of the estimated number of cache writes to the number of cache writes under the current MTTR setting.
ESTD_TOTAL_WRITES	NUMBER		Estimated total number of physical writes under the MTTR
ESTD_TOTAL_WRITE_FACTOR	NUMBER		Estimated total physical write ratio under the MTTR. It is the ratio of the estimated total number of physical writes to the total number of physical writes under the current MTTR setting.
ESTD_TOTAL_IOS	NUMBER		Estimated total number of I/O requests under the MTTR
ESTD_TOTAL_IO_FACTOR	NUMBER		Estimated total I/O ratio under the MTTR. It is the ratio of the estimated total number of I/O requests to the total number of I/O requests under the current MTTR setting.

DBA_HIST_MUTEX_SLEEP

DBA_HIST_MUTEX_SLEEP displays mutex sleep summary historical statistics information.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database identifier for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
MUTEX_TYPE	VARCHAR2 (32)	NOT NULL	Mutex type
LOCATION	VARCHAR2 (40)	NOT NULL	The code location where the waiter slept for the mutex
SLEEPS	NUMBER		Number of sleeps for this MUTEX_TYPE and LOCATION
WAIT_TIME	NUMBER		Wait time in microseconds

DBA_HIST_OPTIMIZER_ENV

DBA_HIST_OPTIMIZER_ENV displays the optimizer environments that have been captured in the Workload Repository. This view is used with the DBA_HIST_SQLSTAT view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
OPTIMIZER_ENV_HASH_VALUE	NUMBER	NOT NULL	Hash value for the optimizer environment
OPTIMIZER_ENV	RAW (623)		Optimizer environment

DBA_HIST_OSSTAT

DBA_HIST_OSSTAT displays historical operating system statistics. This view contains snapshots of V\$OSSTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
STAT_ID	NUMBER		Statistic ID
STAT_NAME	VARCHAR2 (64)		Statistic name
VALUE	NUMBER		Statistic value

DBA_HIST_OSSTAT_NAME

DBA_HIST_OSSTAT_NAME displays the names of the operating system statistics. This view is used with DBA_HIST_OSSTAT.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
STAT_ID	NUMBER	NOT NULL	Statistic ID
STAT_NAME	VARCHAR2 (64)	NOT NULL	Statistic name

DBA_HIST_PARAMETER

DBA_HIST_PARAMETER displays historical information about the initialization parameters that were in effect for the instance. This view contains snapshots of V\$SYSTEM_PARAMETER.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
PARAMETER_HASH	NUMBER		Parameter hash
PARAMETER_NAME	VARCHAR2 (64)		Name of the parameter
VALUE	VARCHAR2 (512)		Parameter value for the session (if modified within the session); otherwise, the instance-wide parameter value
ISDEFAULT	VARCHAR2 (9)		Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE)
ISMODIFIED	VARCHAR2 (10)		Indicates whether the parameter has been modified after instance startup: - MODIFIED - Parameter has been modified with ALTER SESSION - SYSTEM_MOD - Parameter has been modified with ALTER SYSTEM (which causes all the currently logged in sessions' values to be modified) - FALSE - Parameter has not been modified after instance startup

DBA_HIST_PARAMETER_NAME

DBA_HIST_PARAMETER_NAME displays information about the parameter names captured in the workload repository. This view is used with the DBA_HIST_PARAMETER view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
PARAMETER_HASH	NUMBER	NOT NULL	Parameter hash
PARAMETER_NAME	VARCHAR2 (64)	NOT NULL	Name of the parameter

DBA_HIST_PERSISTENT_QMN_CACHE

DBA_HIST_PERSISTENT_QMN_CACHE displays the historical summary background queue table activity. This view contains snapshots from V\$PERSISTENT_QMN_CACHE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_TABLE_ID	NUMBER	NOT NULL	Queue table object ID
TYPE	VARCHAR2 (32)		Type of the queue table's queue monitor cache
STATUS	NUMBER		Status of the queue table's queue monitor cache
NEXT_SERVICE_TIME	TIMESTAMP (3)		Time when the queue table should be serviced by QMON servers
WINDOW_END_TIME	TIMESTAMP (3)		Time manager activity period for non-owner queue table operations
TOTAL_RUNS	NUMBER		Total number of times this queue table is served
TOTAL_LATENCY	NUMBER		Cumulative latency in serving the queue table (in hundredths of a second)
TOTAL_ELAPSED_TIME	NUMBER		Total time spent in processing this queue table (in seconds)
TOTAL_CPU_TIME	NUMBER		Cumulative CPU time for serving the queue table (in hundredths of a second)
TMGR_ROWS_PROCESSED	NUMBER		Number of time manager entries processed
TMGR_ELAPSED_TIME	NUMBER		Cumulative time for time management activities (in hundredths of a second)
TMGR_CPU_TIME	NUMBER		Cumulative CPU time for time management activities (in hundredths of a second)
LAST_TMGR_PROCESSING_TIME	TIMESTAMP (3)		Last timer manager processing time
DEQLOG_ROWS_PROCESSED	NUMBER		Number of dequeue log entries processed
DEQLOG_PROCESSING_ELAPSED_TIME	NUMBER		Total time for processing dequeue log entries (in hundredths of a second)
DEQLOG_PROCESSING_CPU_TIME	NUMBER		Total CPU time for processing dequeue log entries (in hundredths of a second)
LAST_DEQLOG_PROCESSING_TIME	TIMESTAMP (3)		Last dequeue log processing time
DEQUEUE_INDEX_BLOCKS_FREED	NUMBER		Number of dequeue index blocks freed
HISTORY_INDEX_BLOCKS_FREED	NUMBER		Number of history index blocks freed

Column	Datatype	NULL	Description
TIME_INDEX_BLOCKS_FREED	NUMBER		Number of time manager index blocks freed
INDEX_CLEANUP_COUNT	NUMBER		Number of times index block cleanup was attempted
INDEX_CLEANUP_ELAPSED_TIME	NUMBER		Total time for index block cleanup (in hundredths of a second)
INDEX_CLEANUP_CPU_TIME	NUMBER		Total CPU time for index block cleanup (in hundredths of a second)
LAST_INDEX_CLEANUP_TIME	TIMESTAMP (3)		Last index block cleanup time

Note: The DBA_HIST_PERSISTENT_QMN_CACHE view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_HIST_PERSISTENT_QUEUES

DBA_HIST_PERSISTENT_QUEUES displays STREAMS AQ persistent queues historical statistics information. This view contains snapshots of V\$PERSISTENT_QUEUES.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_SCHEMA	VARCHAR2 (30)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue
QUEUE_ID	NUMBER	NOT NULL	Identifier for the queue
FIRST_ACTIVITY_TIME	TIMESTAMP (6)		First queue activity time since database startup
ENQUEUED_MSGS	NUMBER		Number of messages enqueued
DEQUEUED_MSGS	NUMBER		Number of messages dequeued
			Note: This column will not be incremented until all the subscribers of the message have dequeued the message and its retention time has elapsed.
BROWSED_MSGS ¹	NUMBER		Number of messages that have been browsed
ELAPSED_ENQUEUE_TIME	NUMBER		Total time (in hundredths of a second) spent doing enqueue
ELAPSED_DEQUEUE_TIME	NUMBER		Total time (in hundredths of a second) spent doing dequeue
ENQUEUE_CPU_TIME ¹	NUMBER		Total CPU time for enqueue (in hundredths of a second)
DEQUEUE_CPU_TIME ¹	NUMBER		Total CPU time for dequeue (in hundredths of a second)
AVG_MSG_AGE ¹	NUMBER		Average age of messages in the queue
DEQUEUED_MSG_LATENCY ¹	NUMBER		Last dequeued message latency (in seconds)
ELAPSED_TRANSFORMATION_TIME	NUMBER		Total time (in hundredths of a second) spent doing transformation
ELAPSED_RULE_EVALUATION_TIME	NUMBER		Total time (in hundredths of a second) spent doing rule evaluation
ENQUEUED_EXPIRY_MSGS	NUMBER		Number of messages enqueued with expiry
ENQUEUED_DELAY_MSGS	NUMBER		Number of messages enqueued with delay

Column	Datatype	NULL	Description
MSGs_MADE_EXPIRED	NUMBER		Number of messages expired by time manager
MSGs_MADE_READY	NUMBER		Number of messages made ready by time manager
LAST_ENQUEUE_TIME	TIMESTAMP (6)		Last message enqueue time
LAST_DEQUEUE_TIME	TIMESTAMP (6)		Last message dequeue time
LAST_TM_EXPIRY_TIME	TIMESTAMP (6)		Last time message was expired by time manager
LAST_TM_READY_TIME	TIMESTAMP (6)		Last time message was made ready by time manager
ENQUEUE_TRANSACTIONS ¹	NUMBER		Number of enqueue transactions
DEQUEUE_TRANSACTIONS ¹	NUMBER		Number of dequeue transactions
EXECUTION_COUNT ¹	NUMBER		Number of executions of the dequeue cursor

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_HIST_PERSISTENT_SUBS

DBA_HIST_PERSISTENT_SUBS displays STREAMS AQ persistent queue subscribers historical statistics information. This view contains snapshots of V\$PERSISTENT_SUBSCRIBERS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_SCHEMA	VARCHAR2 (30)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	NOT NULL	Name of the queue
SUBSCRIBER_ID	NUMBER	NOT NULL	Internal subscriber number
SUBSCRIBER_NAME	VARCHAR2 (30)		Name of the subscriber
SUBSCRIBER_ADDRESS	VARCHAR2 (1024)		Address of the subscribing agent
SUBSCRIBER_TYPE	VARCHAR2 (30)		Type of the subscriber: ■ PROXY - Propagation subscriber ■ SUBSCRIBER - Normal subscriber ■ RECIPIENT - Recipient
FIRST_ACTIVITY_TIME	TIMESTAMP (6)		First subscriber activity time since database startup
ENQUEUED_MSGS	NUMBER		Number of messages enqueued since FIRST_ACTIVITY_TIME
DEQUEUED_MSGS	NUMBER		Number of messages dequeued since FIRST_ACTIVITY_TIME
AVG_MSG_AGE ¹	NUMBER		Average age of messages in the queue
BROWSED_MSGS ¹	NUMBER		Number of messages that have been browsed
EXPIRED_MSGS	NUMBER		Number of messages expired since FIRST_ACTIVITY_TIME
DEQUEUED_MSG_LATENCY	NUMBER		Last dequeued message latency (in seconds)
LAST_ENQUEUE_TIME	TIMESTAMP (6)		Timestamp of the last enqueued message
LAST_DEQUEUE_TIME	TIMESTAMP (6)		Timestamp of the last dequeued message
ELAPSED_DEQUEUE_TIME ¹	NUMBER		Total time spent in dequeue (in hundredths of a second)
DEQUEUE_CPU_TIME ¹	NUMBER		Total CPU time for dequeue (in hundredths of a second)
DEQUEUE_TRANSACTIONS ¹	NUMBER		Number of dequeue transactions

Column	Datatype	NULL	Description
EXECUTION_COUNT ¹	NUMBER		Number of executions of the dequeue index cursor

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_HIST_PGA_TARGET_ADVICE

DBA_HIST_PGA_TARGET_ADVICE displays historical predictions of how the cache hit percentage and over allocation count statistics displayed by the V\$PGASTAT performance view would be impacted if the value of the PGA_AGGREGATE_TARGET parameter is changed. This view contains snapshots of V\$PGA_TARGET_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
PGA_TARGET_FOR_ESTIMATE	NUMBER	NOT NULL	Value of PGA_AGGREGATE_TARGET for the prediction (in bytes)
PGA_TARGET_FACTOR	NUMBER		PGA_TARGET_FOR_ESTIMATE / the current value of the PGA_AGGREGATE_TARGET parameter
ADVICE_STATUS	VARCHAR2 (3)		Indicates whether the advice is enabled (ON) or disabled (OFF) depending on the value of the STATISTICS_LEVEL parameter
BYTES_PROCESSED	NUMBER		Total bytes processed by all the work areas considered by this advice (in bytes)
ESTD_TIME	NUMBER		Time (in seconds) required to process the bytes
ESTD_EXTRA_BYTES_RW	NUMBER		Estimated number of extra bytes which would be read or written if PGA_AGGREGATE_TARGET was set to the value of the PGA_TARGET_FOR_ESTIMATE column. This number is derived from the estimated number and size of work areas which would run in one-pass (or multi-pass) for that value of PGA_AGGREGATE_TARGET.
ESTD_PGA_CACHE_HIT_PERCENTAGE	NUMBER		Estimated value of the cache hit percentage statistic when PGA_AGGREGATE_TARGET equals PGA_TARGET_FOR_ESTIMATE. This column is derived from the above two columns and is equal to BYTES_PROCESSED / (BYTES_PROCESSED + ESTD_EXTRA_BYTES_RW)
ESTD_OVERALLOC_COUNT	NUMBER		Estimated number of PGA memory over-allocations if the value of PGA_AGGREGATE_TARGET is set to PGA_TARGET_FOR_ESTIMATE. A nonzero value means that PGA_TARGET_FOR_ESTIMATE is not large enough to run the work area workload. Hence, PGA_AGGREGATE_TARGET should not be set to PGA_TARGET_FOR_ESTIMATE since Oracle will not be able to honor that target.

DBA_HIST_PGASTAT

DBA_HIST_PGASTAT displays historical PGA memory usage statistics as well as statistics about the automatic PGA memory manager when it is enabled. This view contains snapshots of V\$PGASTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot

Column	Datatype	NULL	Description
INSTANCE_NUMBER	NUMBER	NOT NULL	Unique snapshot ID
NAME	VARCHAR2 (64)	NOT NULL	Name of the statistic: - aggregate PGA auto target - aggregate PGA target parameter - bytes processed - cache hit percentage - extra bytes read/written - global memory bound - max processes count - maximum PGA allocated - maximum PGA used for auto workareas - maximum PGA used for manual workareas - over allocation count - PGA memory freed back to OS - process count - recompute count (total) - total freeable PGA memory - total PGA allocated - total PGA inuse - total PGA used for auto workareas - total PGA used for manual workareas See Also: V\$PGASTAT for descriptions of the statistics
VALUE	NUMBER		Statistic value

DBA_HIST_PLAN_OPERATION_NAME

DBA_HIST_PLAN_OPERATION_NAME displays historical information about SQL plan operation names.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database identifier
OPERATION_ID	NUMBER	NOT NULL	Plan operation identifier
OPERATION_NAME	VARCHAR2 (64)		Plan operation name. This value also appears in the SQL_PLAN_OPERATION column of the DBA_HIST_ACTIVE_SESS_HISTORY view.

DBA_HIST_PLAN_OPTION_NAME

DBA_HIST_PLAN_OPTION_NAME displays historical information about SQL plan option names.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database identifier
OPTION_ID	NUMBER	NOT NULL	Plan option identifier
OPTION_NAME	VARCHAR2 (64)		Plan option name. This value also appears in the SQL_PLAN_OPTIONS column of the DBA_HIST_ACTIVE_SESS_HISTORY view.

DBA_HIST_PROCESS_MEM_SUMMARY

DBA_HIST_PROCESS_MEM_SUMMARY displays historical information about dynamic PGA memory usage by named component categories for each process.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
CATEGORY	VARCHAR2 (15)	NOT NULL	Category name. Categories include "SQL", "PL/SQL", "OLAP" and "JAVA". Special categories are "Freeable" and "Other". Freeable memory has been allocated to the process by the operating system, but has not been allocated to a category. "Other" memory has been allocated to a category, but not to one of the named categories
NUM_PROCESSES	NUMBER		Number of processes
NON_ZERO_ALLOCS	NUMBER		Number of processes with non-zero allocations
USED_TOTAL	NUMBER		Bytes of PGA memory used by the process for the category
ALLOCATED_TOTAL	NUMBER		Total number of bytes of PGA memory allocated by the process for the category.
ALLOCATED_AVG	NUMBER		Average number of bytes of PGA memory allocated by the process for the category
ALLOCATED_STDDEV	NUMBER		Standard deviation of the number of bytes of PGA memory allocated by the process for the category
ALLOCATED_MAX	NUMBER		Maximum bytes of PGA memory ever allocated by the process for the category
MAX_ALLOCATED_MAX	NUMBER		Maximum bytes of PGA memory that can be allocated by the process for the category

DBA_HIST_RESOURCE_LIMIT

DBA_HIST_RESOURCE_LIMIT displays historical information about global resource use for some of the system resource. This view contains snapshots of V\$RESOURCE_LIMIT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
RESOURCE_NAME	VARCHAR2 (30)	NOT NULL	Name of the resource
CURRENT_UTILIZATION	NUMBER		Number of (resources, locks, or processes) currently being used
MAX_UTILIZATION	NUMBER		Maximum consumption of the resource since the last instance start up
INITIAL_ALLOCATION	VARCHAR2 (10)		Initial allocation. This will be equal to the value specified for the resource in the initialization parameter file (UNLIMITED for infinite allocation).
LIMIT_VALUE	VARCHAR2 (10)		Unlimited for resources and locks. This can be greater than the initial allocation value (UNLIMITED for infinite limit).

DBA_HIST_ROWCACHE_SUMMARY

DBA_HIST_ROWCACHE_SUMMARY displays historical summary statistics for data dictionary activity. This view contains snapshots of V\$ROWCACHE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
PARAMETER	VARCHAR2 (32)		Name of the initialization parameter that determines the number of entries in the data dictionary cache
TOTAL_USAGE	NUMBER		Sum of the total number of entries in the cache
USAGE	NUMBER		Number of cache entries that contain valid data
GETS	NUMBER		Total number of requests for information on the data object
GETMISSES	NUMBER		Number of data requests resulting in cache misses
SCANS	NUMBER		Number of scan requests
SCANMISSES	NUMBER		Number of times a scan failed to find the data in the cache
SCANCOMPLETES	NUMBER		For a list of subordinate entries, the number of times the list was scanned completely
MODIFICATIONS	NUMBER		Number of inserts, updates, and deletions
FLUSHES	NUMBER		Number of times flushed to disk
DLM_REQUESTS	NUMBER		Number of DLM requests
DLM_CONFLICTS	NUMBER		Number of DLM conflicts
DLM_RELEASES	NUMBER		Number of DLM releases

DBA_HIST_RSRC_CONSUMER_GROUP

DBA_HIST_RSRC_CONSUMER_GROUP displays historical information about Resource Manager consumer groups. This view contains snapshots of V\$RSRC_CONS_GROUP_HISTORY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SEQUENCE#	NUMBER	NOT NULL	A sequential counter that uniquely describes the DBA_HIST_RSRC_PLAN entry to which these consumer group statistics apply. When the instance is restarted, this value is reset to zero.
CONSUMER_GROUP_ID	NUMBER	NOT NULL	Consumer group object ID (a unique number, consistent across database shutdowns and startups)
CONSUMER_GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the consumer group
REQUESTS	NUMBER	NOT NULL	Cumulative number of requests that were executed in the consumer group
CPU_WAIT_TIME	NUMBER	NOT NULL	Cumulative amount of time that sessions waited for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.

Column	Datatype	NULL	Description
CPU_WAITS	NUMBER	NOT NULL	Cumulative number of times all sessions in the consumer group had to wait for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CONSUMED_CPU_TIME	NUMBER	NOT NULL	Cumulative amount of CPU time consumed by all sessions in the consumer group (in milliseconds)
YIELDS	NUMBER	NOT NULL	Cumulative number of times that sessions in the consumer group had to yield CPU to other sessions because of quantum expiration
ACTIVE_SESS_LIMIT_HIT	NUMBER	NOT NULL	Number of times that sessions in the consumer group were queued because the consumer group reached its active session limit
UNDO_LIMIT_HIT	NUMBER	NOT NULL	Number of times that queries in the consumer group were cancelled because the consumer group reached its UNDO_POOL limit
SWITCHES_IN_CPU_TIME	NUMBER	NOT NULL	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_OUT_CPU_TIME	NUMBER	NOT NULL	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_IN_IO_MEGABYTES	NUMBER	NOT NULL	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_OUT_IO_MEGABYTES	NUMBER	NOT NULL	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_IN_IO_REQUESTS	NUMBER	NOT NULL	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SWITCHES_OUT_IO_REQUESTS	NUMBER	NOT NULL	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SQL_CANCELED	NUMBER	NOT NULL	Number of times that SQL queries running in the consumer group were aborted because they exceeded the Resource Manager plan's SWITCH_TIME limit and CANCEL_SQL was specified as the Resource Manager plan's SWITCH_GROUP
ACTIVE_SESS_KILLED	NUMBER	NOT NULL	Number of times that sessions running in the consumer group were terminated because they exceeded the Resource Manager plan's SWITCH_TIME limit and KILL_SESSION was specified as the Resource Manager plan's SWITCH_GROUP
IDLE_SESS_KILLED	NUMBER	NOT NULL	Number of times that sessions in the consumer group were killed because they were idle for too long (reached MAX_IDLE_TIME)
IDLE_BLK_R_SESS_KILLED	NUMBER	NOT NULL	Number of times that sessions in the consumer group were killed because they were idle too long (reached MAX_IDLE_BLOCKER_TIME) and were blocking other sessions
QUEUED_TIME	NUMBER	NOT NULL	Total amount of time that sessions in the consumer group have spent in the QUEUED state because of the active session limit (in milliseconds)
QUEUE_TIME_OUTS	NUMBER	NOT NULL	Number of times that requests from sessions in the consumer group timed out because they were queued for too long (reached QUEUEING_P1)
IO_SERVICE_TIME	NUMBER	NOT NULL	Cumulative I/O wait time (in milliseconds)
IO_SERVICE_WAITS	NUMBER	NOT NULL	Total number of wait requests
SMALL_READ_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes read

Column	Datatype	NULL	Description
LARGE_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes written
SMALL_READ_REQUESTS	NUMBER	NOT NULL	Number of single block read requests
SMALL_WRITE_REQUESTS	NUMBER	NOT NULL	Number of single block write requests
LARGE_READ_REQUESTS	NUMBER	NOT NULL	Number of multiblock read requests
LARGE_WRITE_REQUESTS	NUMBER	NOT NULL	Number of multiblock write requests
PQS_QUEUED ¹	NUMBER		Number of times that sessions in the consumer group were queued when trying to run parallel statements
PQ_QUEUED_TIME ¹	NUMBER		Total amount of time that sessions in the consumer group were queued when trying to run parallel statements (in milliseconds)
PQ_QUEUE_TIME_OUTS ¹	NUMBER		Number of times that parallel statements from sessions in the consumer group timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit
PQS_COMPLETED ¹	NUMBER		Total number of completed parallel statements in the consumer group
PQ_SERVERS_USED ¹	NUMBER		Total number of parallel servers used by completed parallel statements in the consumer group
PQ_ACTIVE_TIME ¹	NUMBER		Cumulative sum of the parallel active times for all completed parallel statements in the consumer group (in milliseconds)

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_HIST_RSRC_PLAN

DBA_HIST_RSRC_PLAN displays historical information about resource plans. This view contains snapshots of V\$RSRC_PLAN_HISTORY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SEQUENCE#	NUMBER	NOT NULL	A sequential counter that uniquely describes a row. When the instance is restarted, this value is reset to zero.
START_TIME	DATE	NOT NULL	Time that the resource plan was enabled
END_TIME	DATE	NOT NULL	Time that the resource plan was disabled; NULL if the row contains the current resource plan information
PLAN_ID	NUMBER	NOT NULL	Resource plan ID; NULL if the Resource Manager was disabled
PLAN_NAME	VARCHAR2 (30)	NOT NULL	Resource plan name; NULL if the Resource Manager was disabled
CPU_MANAGED	VARCHAR2 (4)	NOT NULL	Indicates whether the resource plan has parameters that specify a policy for how the Resource Manager should schedule sessions to manage CPU usage (ON) or whether Resource Manager is not managing CPU usage (OFF)

Column	Datatype	NULL	Description
PARALLEL_EXECUTION_ MANAGED ¹	VARCHAR2 (4)		State of parallel statement queuing: - OFF - Parallel statement queuing is disabled - STARTUP - Parallel statement queuing is enabled. This is a temporary state that can occur when an Oracle RAC database is undergoing configuration changes - FIFO - Parallel statement queuing is enabled. All parallel statements are managed in a single Oracle RAC FIFO queue - FULL - Parallel statement queuing is enabled. All parallel statements are managed in per-consumer group queues according to the current resource plan. This state is used when a resource plan that contains resource allocation directives (MGMT_P*) is enabled.

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_HIST_RULE_SET

DBA_HIST_RULE_SET displays historical information about rule set statistics.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the rule set
NAME	VARCHAR2 (30)	NOT NULL	Name of the rule set
STARTUP_TIME	DATE	NOT NULL	Startup time of the instance
CPU_TIME	NUMBER		Total CPU time (in hundredths of a second) spent in evaluation of the rule set
ELAPSED_TIME	NUMBER		Total elapsed time (in hundredths of a second) spent in evaluation of the rule set
EVALUATIONS	NUMBER		Number of evaluations on the rule set
SQL_FREE_EVALUATIONS	NUMBER		Number of evaluations on the rule set which did not internally issue SQL to evaluate rules
SQL_EXECUTIONS	NUMBER		Total number of SQL statements executed during evaluation of the rule set
RELOADS	NUMBER		Number of times the rule set object was reloaded in shared memory

DBA_HIST_SEG_STAT

DBA_HIST_SEG_STAT displays historical information about segment-level statistics. This view captures the top segments based on a set of criteria and captures information from V\$SEGSTAT. The total value is the value of the statistics since instance startup. The delta value is the value of the statistics from the BEGIN_INTERVAL_TIME to the END_INTERVAL_TIME in the DBA_HIST_SNAPSHOT view.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot

Column	Datatype	NULL	Description
TS#	NUMBER	NOT NULL	Tablespace number
OBJ#	NUMBER	NOT NULL	Dictionary object number
DATAOBJ#	NUMBER	NOT NULL	Data object number
LOGICAL_READS_TOTAL	NUMBER		Cumulative value for logical reads
LOGICAL_READS_DELTA	NUMBER		Delta value for logical reads
BUFFER_BUSY_WAITS_TOTAL	NUMBER		Cumulative value for buffer busy waits
BUFFER_BUSY_WAITS_DELTA	NUMBER		Delta value for buffer busy waits
DB_BLOCK_CHANGES_TOTAL	NUMBER		Cumulative value for db block changes
DB_BLOCK_CHANGES_DELTA	NUMBER		Delta value for db block changes
PHYSICAL_READS_TOTAL	NUMBER		Cumulative value for physical reads
PHYSICAL_READS_DELTA	NUMBER		Delta value for physical reads
PHYSICAL_WRITES_TOTAL	NUMBER		Cumulative value for physical writes
PHYSICAL_WRITES_DELTA	NUMBER		Delta value for physical writes
PHYSICAL_READS_DIRECT_TOTAL	NUMBER		Cumulative value for physical reads direct
PHYSICAL_READS_DIRECT_DELTA	NUMBER		Delta value for physical reads direct
PHYSICAL_WRITES_DIRECT_TOTAL	NUMBER		Cumulative value for physical writes direct
PHYSICAL_WRITES_DIRECT_DELTA	NUMBER		Delta value for physical writes direct
ITL_WAITS_TOTAL	NUMBER		Cumulative value for ITL waits
ITL_WAITS_DELTA	NUMBER		Delta value for ITL waits
ROW_LOCK_WAITS_TOTAL	NUMBER		Cumulative value for row lock waits
ROW_LOCK_WAITS_DELTA	NUMBER		Delta value for row lock waits
GC_CR_BLOCKS_SERVED_TOTAL	NUMBER		Cumulative value for global cache CR blocks served
GC_CR_BLOCKS_SERVED_DELTA	NUMBER		Delta value for global cache CR blocks served
GC_CU_BLOCKS_SERVED_TOTAL	NUMBER		Cumulative value for global cache current blocks served
GC_CU_BLOCKS_SERVED_DELTA	NUMBER		Delta value for global cache current blocks served
GC_BUFFER_BUSY_TOTAL	NUMBER		Cumulative value for global cache buffer busy
GC_BUFFER_BUSY_DELTA	NUMBER		Delta value for global cache buffer busy
GC_CR_BLOCKS_RECEIVED_TOTAL	NUMBER		Cumulative value for global cache CR blocks received
GC_CR_BLOCKS_RECEIVED_DELTA	NUMBER		Delta value for global cache CR blocks received
GC_CU_BLOCKS_RECEIVED_TOTAL	NUMBER		Cumulative value for global cache current blocks received
GC_CU_BLOCKS_RECEIVED_DELTA	NUMBER		Delta value for global cache current blocks received
SPACE_USED_TOTAL	NUMBER		Cumulative value for space used
SPACE_USED_DELTA	NUMBER		Delta value for space used

Column	Datatype	NULL	Description
SPACE_ALLOCATED_TOTAL	NUMBER		Cumulative value for space allocated
SPACE_ALLOCATED_DELTA	NUMBER		Delta value for space allocated
TABLE_SCANS_TOTAL	NUMBER		Cumulative value for table scans
TABLE_SCANS_DELTA	NUMBER		Delta value for table scans
CHAIN_ROW_EXCESS_TOTAL	NUMBER		Cumulative value of number of chained row pieces that can be eliminated by table reorganization
CHAIN_ROW_EXCESS_DELTA	NUMBER		Delta value of number of chained row pieces that can be eliminated by table reorganization
PHYSICAL_READ_REQUESTS_TOTAL	NUMBER		Cumulative value of number of physical read I/O requests issued for the monitored segment
PHYSICAL_READ_REQUESTS_DELTA	NUMBER		Delta value of number of physical read I/O requests issued for the monitored segment
PHYSICAL_WRITE_REQUESTS_TOTAL	NUMBER		Cumulative value of number of physical write I/O requests issued for the monitored segment
PHYSICAL_WRITE_REQUESTS_DELTA	NUMBER		Delta value of number of physical write I/O requests issued for the monitored segment
OPTIMIZED_PHYSICAL_READS_TOTAL	NUMBER		Cumulative value of number of physical reads from Database Smart Flash Cache for the monitored segment
OPTIMIZED_PHYSICAL_READS_DELTA	NUMBER		Delta value of number of physical reads from Database Smart Flash Cache for the monitored segment

DBA_HIST_SEG_STAT_OBJ

DBA_HIST_SEG_STAT_OBJ displays all the names of the segments captured in the workload repository. This view is used with the DBA_HIST_SEG_STAT view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
TS#	NUMBER	NOT NULL	Tablespace number
OBJ#	NUMBER	NOT NULL	Dictionary object number
DATAOBJ#	NUMBER	NOT NULL	Data object number
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
SUBOBJECT_NAME	VARCHAR2 (30)		Name of the subobject
OBJECT_TYPE	VARCHAR2 (18)		Type of the object
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Tablespace Name for the object
PARTITION_TYPE	VARCHAR2 (8)		Partition Type, if relevant

DBA_HIST_SERVICE_NAME

DBA_HIST_SERVICE_NAME displays the names of the Services tracked by the Workload Repository. This view contains information for V\$SERVICES.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
SERVICE_NAME_HASH	NUMBER	NOT NULL	Hash of the service name
SERVICE_NAME	VARCHAR2 (64)	NOT NULL	Name of the service

DBA_HIST_SERVICE_STAT

DBA_HIST_SERVICE_STAT displays the history of important service statistics tracked by the Workload Repository. The call rate statistics in this view can be used for making run-time routing decisions, for tracking service levels, and for per-instance diagnostics per call rate.

The elapsed timing for each call provides a relative value across instances for how well a node is processing SQL calls issued under a service name. When aggregation is enabled for the service name, this view provides historical data on the timing and work done for calls issued for the whole service. This view contains information from V\$SERVICE_STATS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
SERVICE_NAME_HASH	NUMBER		Hash of the service name
SERVICE_NAME	VARCHAR2 (64)		Name of the service
STAT_ID	NUMBER		Statistic identifier
STAT_NAME	VARCHAR2 (64)		Statistic name
VALUE	NUMBER		Value of the statistic

DBA_HIST_SERVICE_WAIT_CLASS

DBA_HIST_SERVICE_WAIT_CLASS displays the history of wait class information for services as tracked by the Workload Repository. This view contains information from V\$SERVICE_WAIT_CLASS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
SERVICE_NAME_HASH	NUMBER		Hash of the service name
SERVICE_NAME	VARCHAR2 (64)		Name of the service
WAIT_CLASS_ID	NUMBER		Identifier for the class of the wait event
WAIT_CLASS	VARCHAR2 (64)		Name for the class of the wait event
TOTAL_WAITS	NUMBER		Total number of waits for this event
TIME_WAITED	NUMBER		Total amount of time waited for this event (in hundredths of a second)

DBA_HIST_SESS_TIME_STATS

DBA_HIST_SESS_TIME_STATS displays information about CPU and I/O time for interesting Streams sessions.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot

Column	Datatype	NULL	Description
SESSION_TYPE	VARCHAR2 (64)	NOT NULL	Type of session
MIN_LOGON_TIME	DATE		Minimum logon time
SUM_CPU_TIME	NUMBER		Total CPU time
SUM_SYS_IO_WAIT	NUMBER		Total system I/O wait time
SUM_USER_IO_WAIT	NUMBER		Total user I/O wait time

DBA_HIST_SESSMETRIC_HISTORY

DBA_HIST_SESSMETRIC_HISTORY displays the history of several important session metrics.

Note: This view is populated only if a session metric exceeds a server metric threshold that was configured using the DBMS_SERVER_ALERT package.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
SESSID	NUMBER	NOT NULL	Session ID
SERIAL#	NUMBER	NOT NULL	Session serial number
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	Group ID
METRIC_ID	NUMBER	NOT NULL	Metric ID
METRIC_NAME	VARCHAR2 (64)	NOT NULL	Metric name
VALUE	NUMBER	NOT NULL	Metric Value
METRIC_UNIT	VARCHAR2 (64)	NOT NULL	Unit of measurement

See Also: The DBMS_SERVER_ALERT package in *Oracle Database PL/SQL Packages and Types Reference*

DBA_HIST_SGA

DBA_HIST_SGA displays historical summary information about the system global area (SGA). This view contains snapshots of V\$SGA.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAME	VARCHAR2 (64)	NOT NULL	SGA component group
VALUE	NUMBER	NOT NULL	Memory size (in bytes)

DBA_HIST_SGA_TARGET_ADVICE

DBA_HIST_SGA_TARGET_ADVICE provides historical information about the SGA_TARGET initialization parameter.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SGA_SIZE	NUMBER	NOT NULL	Size of the SGA
SGA_SIZE_FACTOR	NUMBER	NOT NULL	Ratio between the SGA_SIZE and the current size of the SGA
ESTD_DB_TIME	NUMBER	NOT NULL	Estimated DB_TIME for this SGA_SIZE
ESTD_PHYSICAL_READS	NUMBER		Estimated number of physical reads

DBA_HIST_SGASTAT

DBA_HIST_SGASTAT displays detailed historical information on the system global area (SGA). This view contains snapshots of V\$SGASTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
NAME	VARCHAR2 (64)		SGA component group
POOL	VARCHAR2 (12)		Designates the pool in which the memory in NAME resides: - shared pool - Memory is allocated from the shared pool - large pool - Memory is allocated from the large pool - java pool - Memory is allocated from the Java pool - streams pool - Memory is allocated from the Streams pool
BYTES	NUMBER		Memory size (in bytes)

DBA_HIST_SHARED_POOL_ADVICE

DBA_HIST_SHARED_POOL_ADVICE displays historical information about estimated parse time in the shared pool for different pool sizes. This view contains snapshots of V\$SHARED_POOL_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SHARED_POOL_SIZE_FOR_ESTIMATE	NUMBER	NOT NULL	Shared pool size for the estimate (in megabytes)
SHARED_POOL_SIZE_FACTOR	NUMBER		Size factor with respect to the current shared pool size

Column	Datatype	NULL	Description
ESTD_LC_SIZE	NUMBER		Estimated memory in use by the library cache (in megabytes)
ESTD_LC_MEMORY_OBJECTS	NUMBER		Estimated number of library cache memory objects in the shared pool of the specified size
ESTD_LC_TIME_SAVED	NUMBER		Estimated elapsed parse time saved (in seconds), owing to library cache memory objects being found in a shared pool of the specified size. This is the time that would have been spent in reloading the required objects in the shared pool had they been aged out due to insufficient amount of available free memory.
ESTD_LC_TIME_SAVED_FACTOR	NUMBER		Estimated parse time saved factor with respect to the current shared pool size
ESTD_LC_LOAD_TIME	NUMBER		Estimated elapsed time (in seconds) for parsing in a shared pool of the specified size.
ESTD_LC_LOAD_TIME_FACTOR	NUMBER		Estimated load time factor with respect to the current shared pool size
ESTD_LC_MEMORY_OBJECT_HITS	NUMBER		Estimated number of times a library cache memory object was found in a shared pool of the specified size

DBA_HIST_SHARED_SERVER_SUMMARY

DBA_HIST_SHARED_SERVER_SUMMARY displays historical information for shared servers. This includes information about shared server activity, the servers, common queues, and dispatcher queues. This view obtains information from V\$SHARED_SERVER, V\$DISPATCHER, V\$CIRCUIT, and V\$QUEUE, and is aggregated over all servers, dispatchers, queues, and circuits.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NUM_SAMPLES	NUMBER		Total number of samples
SAMPLE_TIME	NUMBER		Last sample timestamp
SAMPLED_TOTAL_CONN	NUMBER		Cumulative sum of total number of connections over all samples. To determine the average number of connections between two snapshots, divide the difference in SAMPLED_TOTAL_CONN by the difference in NUM_SAMPLES.
SAMPLED_ACTIVE_CONN	NUMBER		Cumulative sum of active number of connections over all samples. To determine the average number of active connections between two snapshots, divide the difference in SAMPLED_ACTIVE_CONN by the difference in NUM_SAMPLES.
SAMPLED_TOTAL_SRV	NUMBER		Cumulative sum of total number of servers over all samples. To determine the average number of servers between two snapshots, divide the difference in SAMPLED_TOTAL_SRV by the difference in NUM_SAMPLES.
SAMPLED_ACTIVE_SRV	NUMBER		Cumulative sum of active number of servers over all samples. To determine the average number of active servers between two snapshots, divide the difference in SAMPLED_ACTIVE_SRV by the difference in NUM_SAMPLES.

Column	Datatype	NULL	Description
SAMPLED_TOTAL_DISP	NUMBER		Cumulative sum of total number of dispatchers over all samples. To determine the average number of dispatchers between two snapshots, divide the difference in SAMPLED_TOTAL_DISP by the difference in NUM_SAMPLES.
SAMPLED_ACTIVE_DISP	NUMBER		Cumulative sum of active number of dispatchers over all samples. To determine the average number of active dispatchers between two snapshots, divide the difference in SAMPLED_ACTIVE_DISP by the difference in NUM_SAMPLES.
SRV_BUSY	NUMBER		Total shared server busy time (in hundredths of a second)
SRV_IDLE	NUMBER		Total shared server idle time (in hundredths of a second)
SRV_IN_NET	NUMBER		Total shared server incoming network wait time (in hundredths of a second). This includes waits for receives and resets. This time is also included in SRV_BUSY.
SRV_OUT_NET	NUMBER		Total shared server outgoing network wait time (in hundredths of a second). This includes waits for sends and outbound connection requests. This time is also included in SRV_BUSY.
SRV_MESSAGES	NUMBER		Number of messages processed
SRV_BYTES	NUMBER		Total number of bytes in all messages
CQ_WAIT	NUMBER		Total time that all items in the common queue have waited (in hundredths of a second)
CQ_TOTALQ	NUMBER		Total number of items that have ever been in the common queue
DQ_TOTALQ	NUMBER		Total number of items that have ever been in a dispatcher queue

DBA_HIST_SNAP_ERROR

DBA_HIST_SNAP_ERROR displays information about the snapshot error information in the Workload Repository.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the table in which the error occurred
ERROR_NUMBER	NUMBER	NOT NULL	Error number for the error encountered

DBA_HIST_SNAPSHOT

DBA_HIST_SNAPSHOT displays information about the snapshots in the Workload Repository.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
STARTUP_TIME	TIMESTAMP (3)	NOT NULL	Startup time of the instance
BEGIN_INTERVAL_TIME	TIMESTAMP (3)	NOT NULL	Time at the beginning of the snapshot interval

Column	Datatype	NULL	Description
END_INTERVAL_TIME	TIMESTAMP (3)	NOT NULL	Time at the end of the snapshot interval; the actual time the snapshot was taken
FLUSH_ELAPSED	INTERVAL DAY (5) TO SECOND (1)		Amount of time to perform the snapshot
SNAP_LEVEL	NUMBER		Snapshot level
ERROR_COUNT	NUMBER		Number of errors occurring in the tables for the particular snapshot
SNAP_FLAG	NUMBER		Condition under which the snapshot was inserted. Possible values are: 1 - Manual snapshot created using a PL/SQL package 2 - Imported snapshot 4 - Snapshot taken while Diagnostic Pack or Tuning Pack was not enabled
SNAP_TIMEZONE ¹	INTERVAL DAY (0) TO SECOND (0)		Snapshot time zone expressed as offset from UTC (Coordinated Universal Time) time zone

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_HIST_SQL_BIND_METADATA

DBA_HIST_SQL_BIND_METADATA displays historical information on metadata for bind variables used by SQL cursors.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
SQL_ID	VARCHAR2 (13)	NOT NULL	SQL identifier of the parent cursor in the library cache
NAME	VARCHAR2 (30)		Name of the bind variable
POSITION	NUMBER	NOT NULL	Position of the bind variable in the SQL statement
DUP_POSITION	NUMBER		If the binding is performed by name and the bind variable is duplicated, then this column gives the position of the primary bind variable
DATATYPE	NUMBER		Internal identifier for the bind datatype
DATATYPE_STRING	VARCHAR2 (15)		Textual representation of the bind datatype
CHARACTER_SID	NUMBER		National character set identifier
PRECISION	NUMBER		Precision (for numeric binds)
SCALE	NUMBER		Scale (for numeric binds)
MAX_LENGTH	NUMBER		Maximum bind length

DBA_HIST_SQL_PLAN

DBA_HIST_SQL_PLAN displays the execution plan information for each child cursor in the workload repository. This view captures information from V\$SQL_PLAN and is used with the DBA_HIST_SQLSTAT view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
SQL_ID	VARCHAR2 (13)	NOT NULL	SQL identifier of the parent cursor in the library cache
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).

Column	Datatype	NULL	Description
ID	NUMBER	NOT NULL	A number assigned to each step in the execution plan
OPERATION	VARCHAR2 (30)		Name of the internal operation performed in this step (for example, TABLE ACCESS)
OPTIONS	VARCHAR2 (30)		A variation on the operation described in the OPERATION column (for example, FULL)
OBJECT_NODE	VARCHAR2 (128)		Name of the database link used to reference the object (a table name or view name). For local queries that use parallel execution, this column describes the order in which output from operations is consumed.
OBJECT#	NUMBER		Object number of the table or the index
OBJECT_OWNER	VARCHAR2 (30)		Name of the user who owns the schema containing the table or index
OBJECT_NAME	VARCHAR2 (31)		Name of the table or index
OBJECT_ALIAS	VARCHAR2 (65)		Alias for the object
OBJECT_TYPE	VARCHAR2 (20)		Type of the object
OPTIMIZER	VARCHAR2 (20)		Current mode of the optimizer for the first row in the plan (statement line), for example, CHOOSE. When the operation is a database access (for example, TABLE ACCESS), this column indicates whether or not the object is analyzed.
PARENT_ID	NUMBER		ID of the next execution step that operates on the output of the current step
DEPTH	NUMBER		Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0.
POSITION	NUMBER		Order of processing for all operations that have the same PARENT_ID
SEARCH_COLUMNS	NUMBER		Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
COST	NUMBER		Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
CARDINALITY	NUMBER		Estimate, by the cost-based optimizer, of the number of rows produced by the operation
BYTES	NUMBER		Estimate, by the cost-based optimizer, of the number of bytes produced by the operation
OTHER_TAG	VARCHAR2 (35)		Describes the contents of the OTHER column. See EXPLAIN PLAN for values.
PARTITION_START	VARCHAR2 (5)		Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2 (5)		Stop partition of a range of accessed partitions
PARTITION_ID	NUMBER		Step that computes the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	VARCHAR2 (4000)		Other information specific to the execution step that users may find useful. See EXPLAIN PLAN for values.
DISTRIBUTION	VARCHAR2 (20)		Stores the method used to distribute rows from producer query servers to consumer query servers
CPU_COST	NUMBER		CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
IO_COST	NUMBER		I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.

Column	Datatype	NULL	Description
TEMP_SPACE	NUMBER		Temporary space usage of the operation (sort or hash-join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
ACCESS_PREDICATES	VARCHAR2 (4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2 (4000)		Predicates used to filter rows before producing them
PROJECTION	VARCHAR2 (4000)		Expressions produced by the operation
TIME	NUMBER		Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
QBLOCK_NAME	VARCHAR2 (31)		Name of the query block
REMARKS	VARCHAR2 (4000)		Remarks
TIMESTAMP	DATE		Timestamp for when the plan was produced
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML because it allows multiple pieces of information to be stored, including the following: - Name of the schema against which the query was parsed - Release number of the Oracle Database that produced the explain plan - Hash value associated with the execution plan - Name (if any) of the outline or the SQL profile used to build the execution plan - Indication of whether or not dynamic sampling was used to produce the plan - The outline data, a set of optimizer hints that can be used to regenerate the same plan

DBA_HIST_SQL_SUMMARY

DBA_HIST_SQL_SUMMARY displays historical SQL summary information.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
TOTAL_SQL	NUMBER	NOT NULL	Total number of SQL
TOTAL_SQL_MEM	NUMBER	NOT NULL	Total memory usage of SQL
SINGLE_USE_SQL	NUMBER	NOT NULL	Number of single use SQL
SINGLE_USE_SQL_MEM	NUMBER	NOT NULL	Total memory usage of single use SQL

DBA_HIST_SQL_WORKAREA_HSTGRM

DBA_HIST_SQL_WORKAREA_HSTGRM displays the historical cumulative work area execution statistics (cumulated since instance startup) for different work area groups. This view contains snapshots of V\$SQL_WORKAREA_HISTOGRAM.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
LOW_OPTIMAL_SIZE	NUMBER	NOT NULL	Lower bound for the optimal memory requirement of work areas included in the row (in bytes)
HIGH_OPTIMAL_SIZE	NUMBER	NOT NULL	Upper bound for the optimal memory requirement of work areas included in the row (in bytes)
OPTIMAL_EXECUTIONS	NUMBER		Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which have been executed in optimal mode since instance startup
ONEPASS_EXECUTIONS	NUMBER		Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which have been executed in one-pass mode since instance startup
MULTIPASSES_EXECUTIONS	NUMBER		Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which have been executed in multi-pass mode since instance startup
TOTAL_EXECUTIONS	NUMBER		Sum of OPTIMAL_EXECUTIONS, ONEPASS_EXECUTIONS, and MULTIPASSES_EXECUTIONS

DBA_HIST_SQLBIND

DBA_HIST_SQLBIND displays historical information on bind variables used by SQL cursors. This view contains snapshots of V\$SQL_BIND_CAPTURE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
SQL_ID	VARCHAR2 (13)		SQL identifier of the parent cursor in the library cache
NAME	VARCHAR2 (30)		Name of the bind variable
POSITION	NUMBER		Position of the bind variable in the SQL statement
DUP_POSITION	NUMBER		If the binding is performed by name and the bind variable is duplicated, then this column gives the position of the primary bind variable.
DATATYPE	NUMBER		Internal identifier for the bind datatype
DATATYPE_STRING	VARCHAR2 (15)		Textual representation of the bind datatype
CHARACTER_SID	NUMBER		National character set identifier
PRECISION	NUMBER		Precision (for numeric binds)
SCALE	NUMBER		Scale (for numeric binds)
MAX_LENGTH	NUMBER		Maximum bind length
WAS_CAPTURED	VARCHAR2 (3)		Indicates whether the bind value was captured (YES) or not (NO)
LAST_CAPTURED	DATE		Date when the bind value was captured. Bind values are captured when SQL statements are executed. To limit the overhead, binds are captured at most every 15 minutes for a given cursor.
VALUE_STRING	VARCHAR2 (4000)		Value of the bind represented as a string
VALUE_ANYDATA	ANYDATA		Value of the bind represented using the self-descriptive Sys.AnyData datatype. This representation is useful to programmatically decode the value of the bind variable.

DBA_HIST_SQLCOMMAND_NAME

DBA_HIST_SQLCOMMAND_NAME displays the mapping between SQL opcodes and names.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
COMMAND_TYPE	NUMBER	NOT NULL	SQL command number
COMMAND_NAME	VARCHAR2 (64)		SQL command name

DBA_HIST_SQLSTAT

DBA_HIST_SQLSTAT displays historical information about SQL statistics. This view captures the top SQL statements based on a set of criteria and captures the statistics information from V\$SQL. The total value is the value of the statistics since instance startup. The delta value is the value of the statistics from the BEGIN_INTERVAL_TIME to the END_INTERVAL_TIME in the DBA_HIST_SNAPSHOT view.

This view is used with the DBA_HIST_OPTIMIZER_ENV, DBA_HIST_SQLTEXT, and DBA_HIST_SQL_PLAN views to provide a complete picture of historical SQL statistics.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SQL_ID	VARCHAR2 (13)	NOT NULL	SQL identifier of the parent cursor in the library cache
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).
OPTIMIZER_COST	NUMBER		Cost of the query given by the optimizer
OPTIMIZER_MODE	VARCHAR2 (10)		Mode under which the SQL statement is executed
OPTIMIZER_ENV_HASH_VALUE	NUMBER		Hash Value for the optimizer environment
SHARABLE_MEM	NUMBER		Amount of shared memory used by the child cursor (in bytes)
LOADED_VERSIONS	NUMBER		Indicates whether the context heap is loaded (1) or not (0)
VERSION_COUNT	NUMBER		Number of children associated with the cursor
MODULE	VARCHAR2 (64)		Contains the name of the module that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_MODULE
ACTION	VARCHAR2 (64)		Contains the name of the action that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_ACTION
SQL_PROFILE	VARCHAR2 (64)		Name of the applied SQL Profile
FORCE_MATCHING_SIGNATURE	NUMBER		The signature used when the CURSOR_SHARING parameter is set to FORCE
PARSING_SCHEMA_ID	NUMBER		Schema ID that was used to originally build the child cursor
PARSING_SCHEMA_NAME	VARCHAR2 (30)		Schema name that was used to originally build the child cursor

Column	Datatype	NULL	Description
PARSING_USER_ID	NUMBER		User ID that was used to originally build the child cursor
FETCHES_TOTAL	NUMBER		Cumulative number of fetches associated with the SQL statement
FETCHES_DELTA	NUMBER		Delta number of fetches associated with the SQL statement
END_OF_FETCH_COUNT_TOTAL	NUMBER		Cumulative number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column.
END_OF_FETCH_COUNT_DELTA	NUMBER		Delta number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed.
SORTS_TOTAL	NUMBER		Cumulative number of sorts that were done for this child cursor
SORTS_DELTA	NUMBER		Delta number of sorts that were done for this child cursor
EXECUTIONS_TOTAL	NUMBER		Cumulative number of executions that took place on this object since it was brought into the library cache
EXECUTIONS_DELTA	NUMBER		Delta number of executions that took place on this object since it was brought into the library cache
PX_SERVERS_EXECS_TOTAL	NUMBER		Cumulative number of PX server executions
PX_SERVERS_EXECS_DELTA	NUMBER		Delta number of PX server executions
LOADS_TOTAL	NUMBER		Cumulative number of times the object was either loaded or reloaded
LOADS_DELTA	NUMBER		Delta number of times the object was either loaded or reloaded
INVALIDATIONS_TOTAL	NUMBER		Cumulative number of times this child cursor has been invalidated
INVALIDATIONS_DELTA	NUMBER		Delta number of times this child cursor has been invalidated
PARSE_CALLS_TOTAL	NUMBER		Cumulative number of parse calls for this child cursor
PARSE_CALLS_DELTA	NUMBER		Delta number of parse calls for this child cursor
DISK_READS_TOTAL	NUMBER		Cumulative number of disk reads for this child cursor
DISK_READS_DELTA	NUMBER		Delta number of disk reads for this child cursor
BUFFER_GETS_TOTAL	NUMBER		Cumulative number of buffer gets for this child cursor
BUFFER_GETS_DELTA	NUMBER		Delta number of buffer gets for this child cursor
ROWS_PROCESSED_TOTAL	NUMBER		Cumulative number of rows the parsed SQL statement returns
ROWS_PROCESSED_DELTA	NUMBER		Delta number of rows the parsed SQL statement returns
CPU_TIME_TOTAL	NUMBER		Cumulative value of CPU time (in microseconds) used by this cursor for parsing/executing/fetching
CPU_TIME_DELTA	NUMBER		Delta value of CPU time (in microseconds) used by this cursor for parsing/executing/fetching

Column	Datatype	NULL	Description
ELAPSED_TIME_TOTAL	NUMBER		Cumulative value of elapsed time (in microseconds) used by this cursor for parsing/executing/fetching
ELAPSED_TIME_DELTA	NUMBER		Delta value of elapsed time (in microseconds) used by this cursor for parsing/executing/fetching
IOWAIT_TOTAL	NUMBER		Cumulative value of user I/O wait time (in microseconds)
IOWAIT_DELTA	NUMBER		Delta value of user I/O wait time (in microseconds)
CLWAIT_TOTAL	NUMBER		Cumulative value of cluster wait time (in microseconds)
CLWAIT_DELTA	NUMBER		Delta value of cluster wait time (in microseconds)
APWAIT_TOTAL	NUMBER		Cumulative value of application wait time (in microseconds)
APWAIT_DELTA	NUMBER		Delta value of application wait time (in microseconds)
CCWAIT_TOTAL	NUMBER		Cumulative value of concurrency wait time (in microseconds)
CCWAIT_DELTA	NUMBER		Delta value of concurrency wait time (in microseconds)
DIRECT_WRITES_TOTAL	NUMBER		Cumulative value of direct writes
DIRECT_WRITES_DELTA	NUMBER		Delta value of direct writes
PLSEEXEC_TIME_TOTAL	NUMBER		Cumulative value of PL/SQL Execution Time (in microseconds)
PLSEEXEC_TIME_DELTA	NUMBER		Delta value of PL/SQL Execution Time (in microseconds)
JAVEXEC_TIME_TOTAL	NUMBER		Cumulative value of Java Execution Time (in microseconds)
JAVEXEC_TIME_DELTA	NUMBER		Delta value of Java Execution Time (in microseconds)
IO_OFFLOAD_ELIG_BYTES_TOTAL	NUMBER		Cumulative value of number of I/O bytes which can be filtered by the Exadata storage system See Also: Oracle Exadata Storage Server Software documentation for more information
IO_OFFLOAD_ELIG_BYTES_DELTA	NUMBER		Delta value of number of I/O bytes which can be filtered by the Exadata storage system See Also: Oracle Exadata Storage Server Software documentation for more information
IO_INTERCONNECT_BYTES_TOTAL	NUMBER		Cumulative value of number of I/O bytes exchanged between Oracle Database and the storage system
IO_INTERCONNECT_BYTES_DELTA	NUMBER		Delta value of number of I/O bytes exchanged between Oracle Database and the storage system
PHYSICAL_READ_REQUESTS_TOTAL	NUMBER		Cumulative value of number of physical read I/O requests issued by the monitored SQL
PHYSICAL_READ_REQUESTS_DELTA	NUMBER		Delta value of number of physical read I/O requests issued by the monitored SQL
PHYSICAL_READ_BYTES_TOTAL	NUMBER		Cumulative value of number of bytes read from disks by the monitored SQL
PHYSICAL_READ_BYTES_DELTA	NUMBER		Delta value of number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_REQUESTS_TOTAL	NUMBER		Cumulative value of number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_REQUESTS_DELTA	NUMBER		Delta value of number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_BYTES_TOTAL	NUMBER		Cumulative value of number of bytes written to disks by the monitored SQL
PHYSICAL_WRITE_BYTES_DELTA	NUMBER		Delta value of number of bytes written to disks by the monitored SQL

Column	Datatype	NULL	Description
OPTIMIZED_PHYSICAL_READS_TOTAL	NUMBER		Cumulative value of number of physical reads from Database Smart Flash Cache by the monitored SQL
OPTIMIZED_PHYSICAL_READS_DELTA	NUMBER		Delta value of number of physical reads from Database Smart Flash Cache by the monitored SQL
CELL_UNCOMPRESSED_BYTES_TOTAL	NUMBER		Cumulative value of number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells See Also: Oracle Exadata Storage Server Software documentation for more information
CELL_UNCOMPRESSED_BYTES_DELTA	NUMBER		Delta value of number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells See Also: Oracle Exadata Storage Server Software documentation for more information
IO_OFFLOAD_RETURN_BYTES_TOTAL	NUMBER		Cumulative value of number of bytes that are returned by the Exadata cell for smart scan only (that is, not including bytes for other database I/O) See Also: Oracle Exadata Storage Server Software documentation for more information
IO_OFFLOAD_RETURN_BYTES_DELTA	NUMBER		Delta value of number of bytes that are returned by the Exadata cell for smart scan only (that is, not including bytes for other database I/O) See Also: Oracle Exadata Storage Server Software documentation for more information
BIND_DATA	RAW(2000)		Bind data
FLAG	NUMBER		Reserved for internal use

DBA_HIST_SQLTEXT

DBA_HIST_SQLTEXT displays the text of SQL statements belonging to shared SQL cursors captured in the Workload Repository. This view captures information from V\$SQL and is used with the DBA_HIST_SQLSTAT view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
SQL_TEXT	CLOB		Full text for the SQL statement exposed as a CLOB column
COMMAND_TYPE	NUMBER		Oracle command type definition

DBA_HIST_STAT_NAME

DBA_HIST_STAT_NAME displays decoded statistic names for the statistics captured in the Workload Repository. This view captures information from V\$STATNAME and used with DBA_HIST_SYSSTAT and DBA_HIST_SYS_TIME_MODEL.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
STAT_ID	NUMBER	NOT NULL	Statistic identifier
STAT_NAME	VARCHAR2(64)	NOT NULL	Statistic name

DBA_HIST_STREAMS_APPLY_SUM

DBA_HIST_STREAMS_APPLY_SUM displays information about each apply process and its activities. This view contains a snapshot of V\$STREAMS_APPLY_COORDINATOR, V\$STREAMS_APPLY_READER, and V\$STREAMS_APPLY_SERVER. This view is intended for use with Automatic Workload Repository (AWR).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
APPLY_NAME	VARCHAR2(30)	NOT NULL	Name of the apply process
STARTUP_TIME	DATE	NOT NULL	Time that the apply process was last started
READER_TOTAL_MESSAGES_DEQUEUED	NUMBER		Total number of messages dequeued since the apply process was last started
READER_LAG	NUMBER		For captured messages, the delay (in seconds) between the creation of the last message and it being received by the apply process. For user enqueued messages, the delay between the message being enqueued in the local database and being received by the apply process.
COORD_TOTAL_RECEIVED	NUMBER		Total number of transactions received by the coordinator process since the apply process was last started
COORD_TOTAL_APPLIED	NUMBER		Total number of transactions applied by the apply process since the apply process was last started
COORD_TOTAL_ROLLBACKS	NUMBER		Number of transactions which were rolled back due to unexpected contention
COORD_TOTAL_WAIT_DEPS	NUMBER		Number of times since the apply process was last started that an apply server waited to apply a logical change record (LCR) in a transaction until another apply server applied a transaction because of a dependency between the transactions
COORD_TOTAL_WAIT_CMTS	NUMBER		Number of times since the apply process was last started that an apply server waited to commit a transaction until another apply server committed a transaction to serialize commits
COORD_LWM_LAG	NUMBER		For captured messages, the delay (in seconds) between the creation of the message corresponding to the low watermark and it being applied by the apply process. For user enqueued messages, the delay between the message being enqueued in the local database and being applied by the apply process.
SERVER_TOTAL_MESSAGES_APPLIED	NUMBER		Total number of messages applied by all the apply servers since the apply process was last started
SERVER_ELAPSED_DEQUEUE_TIME	NUMBER		Time elapsed (in hundredths of a second) dequeuing messages by all the apply servers since the apply process was last started
SERVER_ELAPSED_APPLY_TIME	NUMBER		Time elapsed (in hundredths of a second) applying messages by all the apply servers since the apply process was last started

DBA_HIST_STREAMS_CAPTURE

DBA_HIST_STREAMS_CAPTURE displays information about each capture process. This view contains a snapshot of V\$STREAMS_CAPTURE. This view is intended for use with Automatic Workload Repository (AWR).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
CAPTURE_NAME	VARCHAR2 (30)	NOT NULL	Name of the capture process
STARTUP_TIME	DATE	NOT NULL	Time that the capture process was last started
LAG	NUMBER		Delay (in seconds) between the creation and capture of the most recently captured message
TOTAL_MESSAGES_CAPTURED	NUMBER		Total changes captured since the capture process was last started
TOTAL_MESSAGES_ENQUEUED	NUMBER		Total number of messages enqueued since the capture process was last started
ELAPSED_RULE_TIME	NUMBER		Elapsed time (in hundredths of a second) evaluating rules since the capture process was last started
ELAPSED_ENQUEUE_TIME	NUMBER		Elapsed time (in hundredths of a second) enqueueing messages since the capture process was last started
ELAPSED_REDO_WAIT_TIME	NUMBER		Elapsed time (in hundredths of a second) spent by the capture process in the WAITING FOR REDO state
ELAPSED_PAUSE_TIME	NUMBER		Elapsed pause time

DBA_HIST_STREAMS_POOL_ADVICE

DBA_HIST_STREAMS_POOL_ADVICE displays historical information about the estimated count of spilled or unspilled messages and the associated time spent in the spill or unspill activity for different Streams pool sizes. This view is intended for use with Automatic Workload Repository (AWR).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID of the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number of the snapshot
SIZE_FOR_ESTIMATE	NUMBER	NOT NULL	Pool size for the estimate (in megabytes)
SIZE_FACTOR	NUMBER		Size factor with respect to the current pool size
ESTD_SPILL_COUNT	NUMBER		Estimated count of messages spilled from the Streams pool
ESTD_SPILL_TIME	NUMBER		Estimated elapsed time (in seconds) to spill
ESTD_UNSPILL_COUNT	NUMBER		Estimated count of unspills (read back from disk)
ESTD_UNSPILL_TIME	NUMBER		Estimated elapsed time (in seconds) to unspill

DBA_HIST_SYS_TIME_MODEL

DBA_HIST_SYS_TIME_MODEL displays historical system time model statistics. This view contains snapshots of V\$SYS_TIME_MODEL.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
STAT_ID	NUMBER		Statistic ID

Column	Datatype	NULL	Description
STAT_NAME	VARCHAR2 (64)		Statistic name
VALUE	NUMBER		Statistic value

DBA_HIST_SYSMETRIC_HISTORY

DBA_HIST_SYSMETRIC_HISTORY externalizes all available history of the system metric values for the entire set of data kept in the database. This view contains snapshots of V\$SYSMETRIC_HISTORY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	Group ID
METRIC_ID	NUMBER	NOT NULL	Metric ID
METRIC_NAME	VARCHAR2 (64)	NOT NULL	Metric name
VALUE	NUMBER	NOT NULL	Metric Value
METRIC_UNIT	VARCHAR2 (64)	NOT NULL	Unit of measurement

DBA_HIST_SYSMETRIC_SUMMARY

DBA_HIST_SYSMETRIC_SUMMARY displays a history of statistical summary of all metric values in the System Metrics Long Duration group. This view contains snapshots of V\$SYSMETRIC_SUMMARY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	Group ID
METRIC_ID	NUMBER	NOT NULL	Metric ID
METRIC_NAME	VARCHAR2 (64)	NOT NULL	Metric name
METRIC_UNIT	VARCHAR2 (64)	NOT NULL	Unit of measurement
NUM_INTERVAL	NUMBER	NOT NULL	Number of intervals observed
MINVAL	NUMBER	NOT NULL	Minimum value observed
MAXVAL	NUMBER	NOT NULL	Maximum value observed
AVERAGE	NUMBER	NOT NULL	Average over the period
STANDARD_DEVIATION	NUMBER	NOT NULL	One standard deviation
SUM_SQUARES	NUMBER		Sum of the squared deviations from the mean

DBA_HIST_SYSSTAT

DBA_HIST_SYSSTAT displays historical system statistics information. This view contains snapshots of V\$SYSSTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
STAT_ID	NUMBER		Statistic identifier
STAT_NAME	VARCHAR2 (64)		Statistic name
VALUE	NUMBER		Statistic value

DBA_HIST_SYSTEM_EVENT

DBA_HIST_SYSTEM_EVENT displays historical information on total waits for an event. This view contains snapshots of V\$SYSTEM_EVENT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
EVENT_ID	NUMBER	NOT NULL	Identifier of the wait event
EVENT_NAME	VARCHAR2 (64)	NOT NULL	Name of the wait event
WAIT_CLASS_ID	NUMBER		Identifier of the Class of the Wait Event
WAIT_CLASS	VARCHAR2 (64)		Name of the Class of the Wait Event
TOTAL_WAITS	NUMBER		Total number of waits for the event
TOTAL_TIMEOUTS	NUMBER		Total number of timeouts for the event
TIME_WAITED_MICRO	NUMBER		Total amount of time waited for the event (in microseconds)
TOTAL_WAITS_FG	NUMBER		Total number of waits for the event, from foreground sessions
TOTAL_TIMEOUTS_FG	NUMBER		Total number of timeouts for the event, from foreground sessions
TIME_WAITED_MICRO_FG	NUMBER		Amount of time waited for the event (in microseconds), from foreground sessions

DBA_HIST_TABLESPACE_STAT

DBA_HIST_TABLESPACE_STAT displays tablespace information from the control file. This view contains snapshots of V\$TABLESPACE and DBA_TABLESPACE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
TS#	NUMBER		Tablespace number
TSNAME	VARCHAR2 (30)		Tablespace name

Column	Datatype	NULL	Description
CONTENTS	VARCHAR2 (9)		Tablespace contents: - PERMANENT - TEMPORARY
STATUS	VARCHAR2 (9)		Tablespace status: - ONLINE - OFFLINE - READ ONLY
SEGMENT_SPACE_MANAGEMENT	VARCHAR2 (6)		Indicates whether the free and used segment space in the tablespace is managed using free lists (MANUAL) or bitmaps (AUTO)
EXTENT_MANAGEMENT	VARCHAR2 (10)		Indicates whether the extents in the tablespace are dictionary managed (DICTIONARY) or locally managed (LOCAL)
IS_BACKUP	VARCHAR2 (5)		Indicates whether the tablespace is part of a backup

DBA_HIST_TBSPC_SPACE_USAGE

DBA_HIST_TBSPC_SPACE_USAGE displays historical tablespace usage statistics.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
TABLESPACE_ID	NUMBER		Tablespace ID
TABLESPACE_SIZE	NUMBER		Tablespace size
TABLESPACE_MAXSIZE	NUMBER		Maximum size of the tablespace
TABLESPACE_USED_SIZE	NUMBER		Used size of the tablespace
RTIME	VARCHAR2 (25)		Runtime

DBA_HIST_TEMPFILE

DBA_HIST_TEMPFILE displays a history of the tempfile information from the control file. This view contains snapshots of V\$TEMPFILE.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
FILE#	NUMBER	NOT NULL	File identification number
CREATION_CHANGE#	NUMBER	NOT NULL	Change number at which the tempfile was created
FILENAME	VARCHAR2 (513)	NOT NULL	Name of the tempfile
TS#	NUMBER	NOT NULL	Tablespace number
TSNAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace
BLOCK_SIZE	NUMBER		Block size of the tempfile

DBA_HIST_TEMPSTATXS

DBA_HIST_TEMPSTATXS displays information about temporary file read/write statistics. This view contains snapshots of V\$TEMPSTAT.

DBA_HIST_THREAD

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FILE#	NUMBER	NOT NULL	File identification number
CREATION_CHANGE#	NUMBER	NOT NULL	Change number at which the tempfile was created
FILENAME	VARCHAR2 (513)	NOT NULL	Name of the tempfile
TS#	NUMBER	NOT NULL	Tablespace number
TSNAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace
BLOCK_SIZE	NUMBER		Block size of the tempfile
PHYRDS	NUMBER		Number of physical reads done
PHYWRTS	NUMBER		Number of times DBWR is required to write
SINGLEBLKRDS	NUMBER		Number of single block reads
READTIM	NUMBER		Time (in hundredths of a second) spent doing reads if the TIMED_STATISTICS parameter is true; 0 if false
WRITETIM	NUMBER		Time (in hundredths of a second) spent doing writes if the TIMED_STATISTICS parameter is true; 0 if false
SINGLEBLKRDTIM	NUMBER		Cumulative single block read time (in hundredths of a second)
PHYBLKRD	NUMBER		Number of physical blocks read
PHYBLKWRT	NUMBER		Number of blocks written to disk, which may be the same as PHYWRTS if all writes are single blocks
WAIT_COUNT	NUMBER		Wait Count
TIME	NUMBER		Wait time

DBA_HIST_THREAD

DBA_HIST_THREAD displays historical thread information from the control file.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
THREAD#	NUMBER	NOT NULL	Thread number
THREAD_INSTANCE_NUMBER	NUMBER		Instance number of the thread
STATUS	VARCHAR2 (6)		Thread status (OPEN) or (CLOSED)
OPEN_TIME	DATE		Last time the thread was opened
CURRENT_GROUP#	NUMBER		Current log group
SEQUENCE#	NUMBER		Sequence number of the current log

DBA_HIST_TOPLEVELCALL_NAME

DBA_HIST_TOPLEVELCALL_NAME displays the mapping between Oracle top level calls and names.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID

Column	Datatype	NULL	Description
TOP_LEVEL_CALL#	NUMBER	NOT NULL	Oracle top level call number
TOP_LEVEL_CALL_NAME	VARCHAR2 (64)		Oracle top level call name

DBA_HIST_UNDOSTAT

DBA_HIST_UNDOSTAT displays the history of histograms of statistical data to show how well the system is working. The available statistics include undo space consumption, transaction concurrency, and length of queries executed in the instance. This view contains snapshots of V\$UNDOSTAT.

Column	Datatype	NULL	Description
BEGIN_TIME	DATE	NOT NULL	Identifies the beginning of the time interval
END_TIME	DATE	NOT NULL	Identifies the end of the time interval
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
UNDOTSN	NUMBER	NOT NULL	Represents the last active undo tablespace in the duration of time. The tablespace ID of the active undo tablespace is returned in this column. If more than one undo tablespace was active in that period, the active undo tablespace that was active at the end of the period is reported.
UNDOBLKS	NUMBER		Represents the total number of undo blocks consumed. You can use this column to obtain the consumption rate of undo blocks, and thereby estimate the size of the undo tablespace needed to handle the workload on your system.
TXNCOUNT	NUMBER		Identifies the total number of transactions executed within the period
MAXQUERYLEN	NUMBER		Identifies the length of the longest query (in number of seconds) executed in the instance during the period. You can use this statistic to estimate the proper setting of the UNDO_RETENTION initialization parameter. The length of a query is measured from the cursor open time to the last fetch/execute time of the cursor. Only the length of those cursors that have been fetched/executed during the period are reflected in the view.
MAXQUERYSQLID	VARCHAR2 (13)		SQL identifier of the longest running SQL statement in the period
MAXCONCURRENCY	NUMBER		Identifies the highest number of transactions executed concurrently within the period
UNXPSTEALCNT	NUMBER		Number of attempts to obtain undo space by stealing unexpired extents from other transactions
UNXPBLKRELCNT	NUMBER		Number of unexpired blocks removed from certain undo segments so they can be used by other transactions
UNXPBLKREUCNT	NUMBER		Number of unexpired undo blocks reused by transactions
EXPSTEALCNT	NUMBER		Number of attempts to steal expired undo blocks from other undo segments
EXPBLKRELCNT	NUMBER		Number of expired undo blocks stolen from other undo segments
EXPBLKREUCNT	NUMBER		Number of expired undo blocks reused within the same undo segments

Column	Datatype	NULL	Description
SSOLDERRCNT	NUMBER		Identifies the number of times the error ORA-01555 occurred. You can use this statistic to decide whether or not the UNDO_RETENTION initialization parameter is set properly given the size of the undo tablespace. Increasing the value of UNDO_RETENTION can reduce the occurrence of this error.
NOSPACEERRCNT	NUMBER		Identifies the number of times space was requested in the undo tablespace and there was no free space available. That is, all of the space in the undo tablespace was in use by active transactions. The corrective action is to add more space to the undo tablespace.
ACTIVEBLKS	NUMBER		Total number of blocks in the active extents of the undo tablespace for the instance at the sampled time in the period
UNEXPIREDBLKS	NUMBER		Total number of blocks in the unexpired extents of the undo tablespace for the instance at the sampled time in the period
EXPIREDBLKS	NUMBER		Total number of blocks in the expired extents of the undo tablespace for the instance at the sampled time in the period
TUNED_UNDORETENTION	NUMBER		System tuned value indicating the period for which undo is being retained

DBA_HIST_WAITCLASSMET_HISTORY

DBA_HIST_WAITCLASSMET_HISTORY displays the history of the wait event class metric data kept by the Workload Repository.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID of the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number of the snapshot
WAIT_CLASS_ID	NUMBER	NOT NULL	Identifier of the class of the wait event
WAIT_CLASS	VARCHAR2 (64)		Name of the class of the wait event
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	Metric group ID
AVERAGE_WAITER_COUNT	NUMBER	NOT NULL	Average waiter count
DBTIME_IN_WAIT	NUMBER	NOT NULL	Percent of database time spent in the wait
TIME_WAITED	NUMBER	NOT NULL	Time waited during the interval (in microseconds)
WAIT_COUNT	NUMBER	NOT NULL	Number of times waited

DBA_HIST_WAITSTAT

DBA_HIST_WAITSTAT displays historical block contention statistics. This view contains snapshots of V\$WAITSTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot

Column	Datatype	NULL	Description
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
CLASS	VARCHAR2 (18)		Class of the block
WAIT_COUNT	NUMBER		Number of waits by the OPERATION for this CLASS of block
TIME	NUMBER		Sum of all wait times for all the waits by the OPERATION for this CLASS of block

DBA_HIST_WR_CONTROL

DBA_HIST_WR_CONTROL displays the control information for the Workload Repository.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
SNAP_INTERVAL	INTERVAL DAY (5) TO SECOND (1)	NOT NULL	Snapshot interval; how often to automatically take snapshots
RETENTION	INTERVAL DAY (5) TO SECOND (1)	NOT NULL	Retention setting for the snapshots; amount of time to keep the snapshots
TOPNSQL	VARCHAR2 (10)		The number of Top SQL flushed for each SQL criteria (elapsed time, CPU time, parse calls, shareable memory, version count)

DBA_HISTOGRAMS

DBA_HISTOGRAMS is a synonym for DBA_TAB_HISTOGRAMS.

See Also: ["DBA_TAB_HISTOGRAMS"](#) on page 6-17

DBA_IDENTIFIERS

DBA_IDENTIFIERS displays information about the identifiers in all stored objects in the database. Its columns are the same as those in ALL_IDENTIFIERS.

See Also: ["ALL_IDENTIFIERS"](#) on page 2-64

DBA_IND_COLUMNS

DBA_IND_COLUMNS describes the columns of all the indexes on all tables and clusters in the database. Its columns are the same as those in ["ALL_IND_COLUMNS"](#) on page 2-65.

DBA_IND_EXPRESSIONS

DBA_IND_EXPRESSIONS lists expressions of function-based indexes on all tables and clusters in the database. Its columns are the same as those in ["ALL_IND_EXPRESSIONS"](#) on page 2-66.

DBA_IND_PARTITIONS

DBA_IND_PARTITIONS describes, for each index partition in the database, the partition-level partitioning information, the storage parameters for the partition, and

various partition statistics collected by `ANALYZE` statements. Its columns are the same as those in ["ALL_IND_PARTITIONS"](#) on page 2-66.

DBA_IND_PENDING_STATS

`DBA_IND_PENDING_STATS` describes pending statistics for all tables, partitions, and subpartitions in the database. Its columns are the same as those in ["ALL_IND_PENDING_STATS"](#) on page 2-69.

DBA_IND_STATISTICS

`DBA_IND_STATISTICS` displays optimizer statistics for all indexes in the database. Its columns are the same as those in `ALL_IND_STATISTICS`.

See Also: ["ALL_IND_STATISTICS"](#) on page 2-69

DBA_IND_SUBPARTITIONS

`DBA_IND_SUBPARTITIONS` describes, for each index subpartition in the database, the partition-level partitioning information, the storage parameters for the subpartition, and various partition statistics collected by `ANALYZE` statements. Its columns are the same as those in ["ALL_IND_SUBPARTITIONS"](#) on page 2-70.

DBA_INDEXES

`DBA_INDEXES` describes all indexes in the database. To gather statistics for this view, use the SQL `ANALYZE` statement. This view supports parallel partitioned index scans. Its columns are the same as those in ["ALL_INDEXES"](#) on page 2-72.

DBA_INDEXTYPE_ARRAYTYPES

`DBA_INDEXTYPE_ARRAYTYPES` displays information about the array types specified by all indextypes in the database. Its columns are the same as those in `ALL_INDEXTYPE_ARRAYTYPES`.

See Also: ["ALL_INDEXTYPE_ARRAYTYPES"](#) on page 2-76

DBA_INDEXTYPE_COMMENTS

`DBA_INDEXTYPE_COMMENTS` displays comments for all user-defined indextypes in the database. Its columns are the same as those in `ALL_INDEXTYPE_COMMENTS`.

See Also: ["ALL_INDEXTYPE_COMMENTS"](#) on page 2-76

DBA_INDEXTYPE_OPERATORS

`DBA_INDEXTYPE_OPERATORS` lists all the operators supported by indextypes in the database. Its columns are the same as those in `ALL_INDEXTYPE_OPERATORS`.

See Also: ["ALL_INDEXTYPE_OPERATORS"](#) on page 2-77

DBA_INDEXTYPES

DBA_INDEXTYPES describes all indextypes in the database. Its columns are the same as those in ALL_INDEXTYPES.

See Also: ["ALL_INDEXTYPES"](#) on page 2-77

DBA_INTERNAL_TRIGGERS

DBA_INTERNAL_TRIGGERS describes internal triggers on all tables in the database. Its columns are the same as those in ["ALL_INTERNAL_TRIGGERS"](#) on page 2-78.

DBA_JAVA_ARGUMENTS

DBA_JAVA_ARGUMENTS displays argument information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_ARGUMENTS.

See Also: ["ALL_JAVA_ARGUMENTS"](#) on page 2-78

DBA_JAVA_CLASSES

DBA_JAVA_CLASSES displays class level information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_CLASSES.

See Also: ["ALL_JAVA_CLASSES"](#) on page 2-79

DBA_JAVA_COMPILER_OPTIONS

DBA_JAVA_COMPILER_OPTIONS displays information about all native compiler options in the database. Its columns are the same as those in ALL_JAVA_COMPILER_OPTIONS.

See Also: ["ALL_JAVA_COMPILER_OPTIONS"](#) on page 2-80

DBA_JAVA_DERIVATIONS

DBA_JAVA_DERIVATIONS displays mapping information about Java source objects and their derived Java class objects and Java resource objects for all Java classes in the database. Its columns are the same as those in ALL_JAVA_DERIVATIONS.

See Also: ["ALL_JAVA_DERIVATIONS"](#) on page 2-80

DBA_JAVA_FIELDS

DBA_JAVA_FIELDS displays field information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_FIELDS.

See Also: ["ALL_JAVA_FIELDS"](#) on page 2-81

DBA_JAVA_IMPLEMENTATIONS

DBA_JAVA_IMPLEMENTATIONS describes interfaces implemented by all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_IMPLEMENTATIONS.

See Also: ["ALL_JAVA_IMPLEMENTATIONS"](#) on page 2-82

DBA_JAVA_INNERS

DBA_JAVA_INNERS displays information about inner classes referred to by all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_INNERS.

See Also: ["ALL_JAVA_INNERS"](#) on page 2-82

DBA_JAVA_LAYOUTS

DBA_JAVA_LAYOUTS displays class layout information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_LAYOUTS.

See Also: ["ALL_JAVA_LAYOUTS"](#) on page 2-83

DBA_JAVA_METHODS

DBA_JAVA_METHODS displays method information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_METHODS.

See Also: ["ALL_JAVA_METHODS"](#) on page 2-84

DBA_JAVA_NCOMPS

DBA_JAVA_NCOMPS displays ncomp-related information about all Java classes in the database. Its columns are the same as those in ALL_JAVA_NCOMPS.

See Also: ["ALL_JAVA_NCOMPS"](#) on page 2-85

DBA_JAVA_POLICY

DBA_JAVA_POLICY describes Java security permissions for all users in the database.

Related View

USER_JAVA_POLICY describes Java security permissions for the current user.

Column	Datatype	NULL	Description
KIND	VARCHAR2 (8)		Indicates whether the permission is a positive (GRANT) or a limitation (RESTRICT)
GRANTEE	VARCHAR2 (30)	NOT NULL	Name of the user, schema, or role to which the permission object is assigned
TYPE_SCHEMA	VARCHAR2 (30)	NOT NULL	Schema in which the permission object is loaded
TYPE_NAME	VARCHAR2 (4000)		Permission class type, which is designated by a string containing the full class name, such as, <code>java.io.FilePermission</code>
NAME	VARCHAR2 (4000)		Target attribute (name) of the permission object. This name is used when defining the permission.
ACTION	VARCHAR2 (4000)		Action attribute for this permission. Many permissions expect a null value if no action is appropriate for the permission.
ENABLED	VARCHAR2 (8)		Indicates whether the permission is enabled (ENABLED) or disabled (DISABLED)
SEQ	NUMBER		Sequence number used to identify this row. This number should be supplied when disabling, enabling, or deleting the permission.

See Also: ["USER_JAVA_POLICY"](#) on page 6-83

DBA_JAVA_RESOLVERS

DBA_JAVA_RESOLVERS displays information about resolvers of all Java classes in the database. Its columns are the same as those in ALL_JAVA_RESOLVERS.

See Also: ["ALL_JAVA_RESOLVERS"](#) on page 2-85

DBA_JAVA_THROWS

DBA_JAVA_THROWS displays information about exceptions thrown from methods of all Java classes in the database. Its columns are the same as those in ALL_JAVA_THROWSa.

See Also: ["ALL_JAVA_THROWS"](#) on page 2-86

DBA_JOBS

DBA_JOBS describes all jobs in the database.

Related View

USER_JOBS describes the jobs owned by the current user.

Column	Datatype	NULL	Description
JOB	NUMBER	NOT NULL	Identifier of job. Neither import/export nor repeated executions change this value.
LOG_USER	VARCHAR2 (30)	NOT NULL	Login user when the job was submitted
PRIV_USER	VARCHAR2 (30)	NOT NULL	User whose default privileges apply to this job
SCHEMA_USER	VARCHAR2 (30)	NOT NULL	Default schema used to parse the job For example, if the SCHEMA_USER is SCOTT and you submit the procedure HIRE_EMP as a job, the Oracle Database looks for SCOTT.HIRE_EMP
LAST_DATE	DATE		Date on which this job last successfully executed
LAST_SEC	VARCHAR2 (8)		Same as LAST_DATE. This is when the last successful execution started.
THIS_DATE	DATE		Date that this job started executing (usually null if not executing)
THIS_SEC	VARCHAR2 (8)		Same as THIS_DATE. This is when the last successful execution started.
NEXT_DATE	DATE	NOT NULL	Date that this job will next be executed
NEXT_SEC	VARCHAR2 (8)		Same as NEXT_DATE. This is when the last successful execution started.
TOTAL_TIME	NUMBER		Total wall clock time spent by the system on this job (in seconds) since the first time this job executed. This value is cumulative.
BROKEN	VARCHAR2 (1)		Y: no attempt is made to run this job N: an attempt is made to run this job
INTERVAL	VARCHAR2 (200)	NOT NULL	A date function, evaluated at the start of execution, becomes next NEXT_DATE
FAILURES	NUMBER		Number of times the job has started and failed since its last success

Column	Datatype	NULL	Description
WHAT	VARCHAR2 (4000)		Body of the anonymous PL/SQL block that the job executes
NLS_ENV	VARCHAR2 (4000)		Session parameters describing the NLS environment of the job
MISC_ENV	RAW (32)		Other session parameters that apply to this job
INSTANCE	NUMBER		ID of the instance that can execute or is executing the job. The default is 0.

See Also: ["USER_JOBS"](#) on page 6-84

DBA_JOBS_RUNNING

DBA_JOBS_RUNNING lists all jobs that are currently running in the instance.

Column	Datatype	NULL	Description
SID	NUMBER		Identifier of process that is executing the job. See "V\$LOCK" on page 8-15.
JOB	NUMBER		Identifier of job. This job is currently executing.
FAILURES	NUMBER		Number of times this job started and failed since its last success.
LAST_DATE	DATE		Date that this job last successfully executed.
LAST_SEC	VARCHAR2 (8)		Same as LAST_DATE. This is when the last successful execution started.
THIS_DATE	DATE		Date that this job started executing.
THIS_SEC	VARCHAR2 (8)		Same as THIS_DATE. This is when the last successful execution started.
INSTANCE	NUMBER		Indicates which instance can execute or is executing the job; the default is 0.

DBA_JOIN_IND_COLUMNS

DBA_JOIN_IND_COLUMNS describes all join conditions in the database. Its columns are the same as those in ["ALL_JOIN_IND_COLUMNS"](#) on page 2-87.

DBA_KGLLOCK

DBA_KGLLOCK lists all the locks and pins held on KGL objects (objects in the Kernel Generic Library cache).

Column	Datatype	NULL	Description
kgllkuse	RAW (4)		Address of the user session that holds the lock or pin
kgllkhdl	RAW (4)		Address of the handle for the KGL object
kgllkmod	NUMBER		Current mode of the lock or pin
kgllkreq	NUMBER		Mode in which the lock or pin was requested
kgllktype	VARCHAR2 (4)		Whether this is a lock or a pin

DBA_LIBRARIES

DBA_LIBRARIES describes all libraries in the database. Its columns are the same as those in ALL_LIBRARIES.

See Also: ["ALL_LIBRARIES"](#) on page 2-87

DBA_LMT_FREE_SPACE

DBA_LMT_FREE_SPACE describes the free extents in all locally managed tablespaces in the database.

Column	Datatype	NULL	Description
TABLESPACE_ID	NUMBER		Identifier number of the tablespace containing the extent
FILE_ID	NUMBER		File identifier number of the file containing the extent
BLOCK_ID	NUMBER		Starting block number of the extent
BLOCKS	NUMBER		Size of the extent (in Oracle blocks)

DBA_LMT_USED_EXTENTS

DBA_LMT_USED_EXTENTS describes the extents comprising the segments in all locally managed tablespaces in the database.

Column	Datatype	NULL	Description
SEGMENT_FILEID	NUMBER		File number of the segment header of the extent
SEGMENT_BLOCK	NUMBER		Block number of the segment header of the extent
TABLESPACE_ID	NUMBER		Identifier number of the tablespace containing the extent
EXTENT_ID	NUMBER		Extent number in the segment
FILEID	NUMBER		File identifier number of the file containing the extent
BLOCK	NUMBER		Starting block number of the extent
LENGTH	NUMBER		Number of blocks in the extent

DBA_LOB_PARTITIONS

DBA_LOB_PARTITIONS displays all LOB partitions in the database. Its columns are the same as those in ["ALL_LOB_PARTITIONS"](#) on page 2-88.

DBA_LOB_SUBPARTITIONS

DBA_LOB_SUBPARTITIONS displays partition-level attributes of all LOB data subpartitions in the database. Its columns are the same as those in ["ALL_LOB_SUBPARTITIONS"](#) on page 2-90.

DBA_LOB_TEMPLATES

DBA_LOB_TEMPLATES describes all LOB subpartition templates in the database. Its columns are the same as those in [ALL_LOB_TEMPLATES](#).

See Also: ["ALL_LOB_TEMPLATES"](#) on page 2-92

DBA_LOBS

DBA_LOBS displays the BLOBs and CLOBs contained in all tables in the database. BFILEs are stored outside the database, so they are not described by this view. This view's columns are the same as those in ["ALL_LOBS"](#) on page 2-93.

DBA_LOCK

DBA_LOCK lists all locks or latches held in the database, and all outstanding requests for a lock or latch.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER		Session holding or acquiring the lock
LOCK_TYPE	VARCHAR2 (26)		Lock type See Also: For a listing of lock types, see Appendix D, "Oracle Enqueue Names"
MODE_HELD	VARCHAR2 (40)		Lock mode
MODE_REQUESTED	VARCHAR2 (40)		Lock mode requested
LOCK_ID1	VARCHAR2 (40)		Type-specific lock identifier, part 1
LOCK_ID2	VARCHAR2 (40)		Type-specific lock identifier, part 2
LAST_CONVERT	NUMBER		The last convert
BLOCKING_OTHERS	VARCHAR2 (40)		Whether the lock is currently blocking others

DBA_LOCK_INTERNAL

DBA_LOCK_INTERNAL displays a row for each lock or latch that is being held, and one row for each outstanding request for a lock or latch.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER		Session holding or acquiring the lock
LOCK_TYPE	VARCHAR2 (56)		Lock type See Also: For a listing of lock types, see Appendix D, "Oracle Enqueue Names"
MODE_HELD	VARCHAR2 (40)		Lock mode
MODE_REQUESTED	VARCHAR2 (40)		Lock mode requested
LOCK_ID1	VARCHAR2 (1130)		Type-specific lock identifier, part 1
LOCK_ID2	VARCHAR2 (40)		Type-specific lock identifier, part 2

DBA_LOCKS

DBA_LOCKS is a synonym for DBA_LOCK.

See Also: ["DBA_LOCK"](#) on page 5-50

DBA_LOG_GROUP_COLUMNS

DBA_LOG_GROUP_COLUMNS describes all columns in the database that are specified in log groups. Its columns are the same as those in ["ALL_LOG_GROUP_COLUMNS"](#) on page 2-95.

DBA_LOG_GROUPS

DBA_LOG_GROUPS describes log group definitions on all tables in the database. Its columns are the same as those in ["ALL_LOG_GROUPS"](#) on page 2-95.

DBA_LOGMNR_LOG

DBA_LOGMNR_LOG displays all archived logs registered with active LogMiner persistent sessions in the database.

A persistent LogMiner session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating Streams capture.

Column	Datatype	NULL	Description
LOGMNR_SESSION_ID	NUMBER	NOT NULL	Unique identifier of the persistent session
NAME	VARCHAR2 (513)		Name of the archived log
DBID	NUMBER	NOT NULL	Database identifier that produced the archived log
RESETLOGS_SCN	NUMBER	NOT NULL	SCN at which resetlogs operation was performed at the source database generating the archived log
RESETLOGS_TIME	NUMBER	NOT NULL	Timestamp at which resetlogs operation was performed at the source database generating the archived log
MODIFIED_TIME	DATE		Time at which the archived log was registered with LogMiner
THREAD#	NUMBER	NOT NULL	Redo thread at the source database that generated the archived log
SEQUENCE#	NUMBER	NOT NULL	Logfile sequence number
FIRST_SCN	NUMBER	NOT NULL	Lowest SCN of the redo record contained in the logfile
NEXT_SCN	NUMBER	NOT NULL	Highest possible SCN of the redo record contained in the logfile
FIRST_TIME	DATE		Time of the first redo record contained in the logfile
NEXT_TIME	DATE		Time of the last redo record contained in the logfile
DICTIONARY_BEGIN	VARCHAR2 (3)		Indicates whether the archived log contains the beginning of a LogMiner dictionary (YES) or not (NO)
DICTIONARY_END	VARCHAR2 (3)		Indicates whether the archived log contains the end of a LogMiner dictionary (YES) or not (NO)
KEEP	VARCHAR2 (3)		Indicates whether the logfile is still required for this LogMiner session (YES) or not (NO)
SUSPECT	VARCHAR2 (3)		Indicates whether the archived log content was deemed to be corrupt or the archived log is partially filled (YES) or not (NO)

DBA_LOGMNR_PURGED_LOG

DBA_LOGMNR_PURGED_LOG displays archived redo log files that have been applied to the logical standby database and can be deleted because they are no longer needed. Files in this view are refreshed as a result of executing either of the following PL/SQL procedures:

- DBMS_LOGSTDBY.PURGE_SESSION (for Oracle Data Guard SQL Apply)
- DBMS_CAPTURE.SET_FIRST_SCN (for Oracle Streams)

Column	Datatype	NULL	Description
FILE_NAME	VARCHAR2 (513)		Fully qualified names of the archived redo log files that are no longer needed by SQL Apply and can be deleted from the operating system

DBA_LOGMNR_SESSION

DBA_LOGMNR_SESSION displays all active LogMiner persistent sessions in the database.

A persistent LogMiner session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating Streams capture.

Column	Datatype	NULL	Description
ID	NUMBER	NOT NULL	Unique session identifier
NAME	VARCHAR2 (128)	NOT NULL	Unique session name
SOURCE_DATABASE	VARCHAR2 (128)		Global name of the source database whose archived logs are to be mined in this persistent LogMiner session
SOURCE_DBID	NUMBER		Database ID of the source database
SOURCE_RESETLOGS_SCN	NUMBER		Resetlogs SCN associated with the incarnation of the source database whose archived logs are mined
SOURCE_RESETLOGS_TIME	NUMBER		Resetlogs time associated with the incarnation of the source database whose archived logs are mined
FIRST_SCN	NUMBER		Only modifications that occurred on or after this SCN can be mined using this persistent session
END_SCN	NUMBER		No modifications that occurred on or after this SCN can be mined using this persistent session
BRANCH_SCN	NUMBER		SCN at which a branch will be taken in terms of the incarnation corresponding to the source database. This implies a point-in-time recovery was performed at the source database at this SCN.
WAIT_FOR_LOG	VARCHAR2 (3)		Indicates whether the persistent session waits for RFS to register new archived logs or to fill gaps (YES) or not (NO)
HOT_MINE	VARCHAR2 (3)		Indicates whether real-time mining is on (YES) or not (NO)
SAFE_PURGE_SCN	NUMBER		Persistent session can safely be purged up to this SCN
CHECKPOINT_SCN	NUMBER		SCN at which the latest checkpoint is taken by the persistent LogMiner session

DBA_LOGSTDBY_EVENTS

DBA_LOGSTDBY_EVENTS displays information about the activity of the logical standby database system. It can be used to determine the cause of failures that occur when applying redo data to logical standby databases. This view is for logical standby databases only.

Column	Datatype	NULL	Description
EVENT_TIME	DATE		Time when the event was logged
EVENT_TIMESTAMP	TIMESTAMP (6)		Timestamp when the event was logged
CURRENT_SCN	NUMBER		SCN associated with the change at the primary database. If a failure occurred, then examine this column to determine which archived log file contains the source of the failure (for example, an unsupported record).
COMMIT_SCN	NUMBER		SCN value on which the change was committed at the primary database
XIDUSN	NUMBER		Transaction ID undo segment number at the primary database of the associated transaction
XIDSLT	NUMBER		Transaction ID slot number at the primary database of the associated transaction

Column	Datatype	NULL	Description
XIDSQN	NUMBER		Transaction ID sequence number at the primary database of the associated transaction
EVENT	CLOB		Statement that was being processed when the failure occurred
STATUS_CODE	NUMBER		Status (or Oracle error code) belonging to the STATUS message
STATUS	VARCHAR2 (2000)		Description of the current activity of the process or the reason why the apply operation stopped

DBA_LOGSTDBY_HISTORY

DBA_LOGSTDBY_HISTORY displays the history of switchovers and failovers in a Data Guard configuration. It does this by showing the complete sequence of redo log streams processed or created on the local system, across all role transitions. (After a role transition, a new log stream is started and the log stream sequence number is incremented by the new primary database.) This view is for logical standby databases only.

Column	Datatype	NULL	Description
STREAM_SEQUENCE#	NUMBER		Lists the sequence numbers for all log streams created or applied on the local system. Note: A value of 0 indicates an unknown sequence order; this is reserved for future log streams.
STATUS	VARCHAR2 (16)		Description of the log stream processing: - Past - The log stream has already been processed - Immediate Past - This is the most recently processed log stream; its status is transitioning from Current to Past - Current - The log stream is currently being processed - Immediate Future - This is the next log stream to be processed; its status is transitioning from Future to Current - Future - The log stream will be processed
SOURCE	VARCHAR2 (5)		Describes how the log stream was started: - RFS - The RFS process created the log stream - User - A user registered the initial log file for the log stream - Synch - A user issued the ALTER DATABASE START LOGICAL STANDBY APPLY NEW PRIMARY DDL statement - Redo - The log stream information was recorded in the redo log
DBID	NUMBER		Database identifier of the primary database that created the log stream
FIRST_CHANGE#	NUMBER		Lowest system change number (SCN) in the current log file
LAST_CHANGE#	NUMBER		Highest system change number (SCN) in the current log file
FIRST_TIME	DATE		Time of the first SCN entry (FIRST_CHANGE#) in the current log file
LAST_TIME	DATE		Time of the last SCN entry (LAST_CHANGE#) in the current log file

Column	Datatype	NULL	Description
DGNAME	VARCHAR2 (255)		Unique database name (DB_UNIQUE_NAME) of the primary database that produced the log stream. See V\$DATAGUARD_CONFIG to display all database DB_UNIQUE_NAME values defined in the Data Guard configuration.
MERGE_CHANGE#	NUMBER		SCN that should be used to flashback a failed primary (that created the log stream) or to flashback a bystander logical standby database following a failover, in the context of the associated redo log stream. It is the SCN up to which redo for the associated log stream can be merged safely in all databases using local copies of archived logs received from the primary database. In order to apply changes beyond this following a failover, you will need to fetch and mine the redo logs from the failover target.
PROCESSED_CHANGE#	NUMBER		Strict upper bound on the SCN up to which SQL Apply has applied redo records before it switched to a new log stream (either because it was activated and became the primary database, or in the case of a bystander logical standby database where it switched to a new log stream in order to accommodate a new primary database).

DBA_LOGSTDBY_LOG

DBA_LOGSTDBY_LOG displays information about the logs registered for a logical standby database. This view is for logical standby databases only.

Column	Datatype	NULL	Description
THREAD#	NUMBER	NOT NULL	Thread ID of the archive log. The THREAD number is 1 for a single instance. For Real Application Clusters, this column will contain different numbers.
RESETLOGS_CHANGE#	NUMBER	NOT NULL	Start SCN of the branch
RESETLOGS_ID	NUMBER	NOT NULL	Resetlogs identifier (a numerical form of the timestamp of the branch)
SEQUENCE#	NUMBER	NOT NULL	Sequence number of the archive log file
FIRST_CHANGE#	NUMBER	NOT NULL	System change number (SCN) of the current archive log
NEXT_CHANGE#	NUMBER		SCN of the next archive log
FIRST_TIME	DATE		Date of the current archive log
NEXT_TIME	DATE		Date of the next archive log
FILE_NAME	VARCHAR2 (513)		Name of the archive log
TIMESTAMP	DATE		Time when the archive log was registered
DICT_BEGIN	VARCHAR2 (3)		Indicates whether the beginning of the dictionary build is in this archive log (YES) or not (NO)
DICT_END	VARCHAR2 (3)		Indicates whether the end of the dictionary build is in this archive log (YES) or not (NO)

Column	Datatype	NULL	Description
APPLIED	VARCHAR2 (8)		Indicates primarily whether a given foreign archived log has been applied fully by SQL Apply: - YES - SQL Apply has fully applied the foreign archived log and no longer needs it - CURRENT - SQL Apply is currently applying changes contained in the foreign archived log - NO - SQL Apply has not started applying any changes contained in the foreign archived log - FETCHING - SQL Apply encountered a corruption while reading redo records from this foreign archived log, and is currently using the automatic gap resolution to refetch a new copy of the log from the primary database - CORRUPT - SQL Apply encountered a corruption while reading redo records from this foreign archived log, and refetching a new copy of the archived log did not resolve the problem. SQL Apply will not refetch a new copy of this archived log automatically, and will require user intervention to manually register a new copy of the foreign archived log.
BLOCKS	NUMBER		Number of blocks in the log
BLOCK_SIZE	NUMBER		Size of each block in the log

Note: The SCN values in this view correlate to the SCN values shown in the DBA_LOGSTDBY_PROGRESS view.

DBA_LOGSTDBY_NOT_UNIQUE

DBA_LOGSTDBY_NOT_UNIQUE displays all tables that have no primary and no non-null unique indexes. Most of the tables displayed by this view are supported because their columns contain enough information to be maintained in a logical standby database. Some tables, however, cannot be supported because their columns do not contain the necessary information. Unsupported tables usually contain a column defined using an unsupported datatype.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Schema name of the non-unique table
TABLE_NAME	VARCHAR2 (30)		Table name of the non-unique table
BAD_COLUMN	VARCHAR2 (1)		- Y - Table column is defined using an unbounded data type, such as LONG or BLOB. If two rows in the table match except in their LOB columns, then the table cannot be maintained properly. Log apply services will attempt to maintain these tables, but you must ensure the application does not allow uniqueness only in the unbounded columns. - N - Enough column information is present to maintain the table in the logical standby database but the log transport services and log apply services would run more efficiently if you added a primary key. You should consider adding a disabled RELY constraint to these tables.

DBA_LOGSTDBY_PARAMETERS

DBA_LOGSTDBY_PARAMETERS displays the list of parameters used by SQL apply for logical standby databases. This view is for logical standby databases only.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)		Name of the parameter: ■ MAX_SGA - System global area (SGA) allocated for the log apply services cache (in megabytes) ■ MAX_SERVERS - Number of processes used by SQL Apply services ■ PREPARE_SERVERS - Controls the number of parallel execution servers used to prepare changes ■ APPLY_SERVERS - Controls the number of parallel execution servers used to apply changes ■ MAX_EVENTS_RECORDED - Number of events stored in the DBA_LOGSTDBY_EVENTS view ■ RECORD_SKIP_ERRORS - Indicates records that are skipped ■ RECORD_SKIP_DDL - Indicates skipped DDL statements ■ RECORD_APPLIED_DDL - Indicates applied DDL statements ■ RECORD_UNSUPPORTED_OPERATIONS - Shows whether SQL Apply will capture information about transactions that did unsupported operations at the primary database in the DBA_LOGSTDBY_EVENTS view ■ EVENT_LOG_DEST - Indicates where SQL Apply records the occurrence of an interesting event ■ LOG_AUTO_DELETE - Shows whether SQL Apply will automatically delete remote archived logs received from the primary database, once the contents of the logs are applied at the logical standby database. ■ LOG_AUTO_DEL_RETENTION_TARGET - How many minutes a remote archived log received from the primary database will be retained at the logical standby database, once the contents of the log are applied by SQL Apply. ■ PRESERVE_COMMIT_ORDER - Shows whether transactions are committed at the logical standby database in the same order that they were committed at the primary database
VALUE	VARCHAR2 (2000)		Value of the parameter
UNIT	VARCHAR2 (64)		Unit of the value, if applicable
SETTING	VARCHAR2 (64)		Possible values are as follows: ■ SYSTEM - Parameter value was not explicitly set by the user. However, the user can change it with an appropriate call to the APPLY_SET procedure. ■ USER - Parameter value was explicitly set by the user
DYNAMIC	VARCHAR2 (64)		YES if the parameter can be set dynamically (that is, without having to stop SQL Apply) NO if setting the parameter requires that SQL Apply be stopped

DBA_LOGSTDBY_PROGRESS

DBA_LOGSTDBY_PROGRESS is deprecated. The information that was provided in this view is now provided in the V\$LOGSTDBY_PROGRESS view.

DBA_LOGSTDBY_SKIP

DBA_LOGSTDBY_SKIP displays the tables that will be skipped by log apply services. This view is for logical standby databases only.

Column	Datatype	NULL	Description
ERROR	VARCHAR2 (1)		Indicates whether the statement should be skipped (Y) or just return errors for the statement (N)
STATEMENT_OPT	VARCHAR2 (30)		Specifies the type of statement that should be skipped. It must be one of the SYSTEM_AUDIT statement options.
OWNER	VARCHAR2 (30)		Name of the schema under which the skip option should be used
NAME	VARCHAR2 (65)		Name of the table that is being skipped
USE_LIKE	VARCHAR2 (1)		Indicates whether the statement should use a SQL wildcard search when matching names (Y) or not (N)
ESC	VARCHAR2 (1)		Escape character used when performing wildcard matches
PROC	VARCHAR2 (98)		Name of a stored procedure that will be executed when processing the skip option

DBA_LOGSTDBY_SKIP_TRANSACTION

DBA_LOGSTDBY_SKIP_TRANSACTION displays the skip settings chosen. This view is for logical standby databases only.

Column	Datatype	NULL	Description
XIDUSN	NUMBER		Transaction ID undo segment number
XIDSLT	NUMBER		Transaction ID slot number
XIDSQN	NUMBER		Transaction ID sequence number

DBA_LOGSTDBY_UNSUPPORTED

DBA_LOGSTDBY_UNSUPPORTED displays the schemas, tables, and columns in those tables that contain unsupported datatypes. Use this view when you are preparing to create a logical standby database. This view is for logical standby databases only.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the unsupported table
TABLE_NAME	VARCHAR2 (30)		Name of the unsupported table
COLUMN_NAME	VARCHAR2 (30)		Name of the unsupported column

Column	Datatype	NULL	Description
ATTRIBUTES	VARCHAR2 (39)		Displays the reason why the table is not supported by SQL Apply. If the structure of the table is unsupported (not just the datatype of some columns), then this view displays all columns in the table, with one of the following values displayed for each column in the table: ▪ IOT with Overflow ▪ IOT with LOB ▪ Mapping table for physical rowid of IOT ▪ IOT with row movement ▪ Table Compression ▪ Object Table ▪ AQ queue table ▪ Unsupported Virtual Column ▪ Encrypted Column If the structure of the table is supported but certain columns in the table have unsupported datatypes, the ATTRIBUTE column will be NULL.
DATA_TYPE	VARCHAR2 (32)		Datatype of the unsupported column

DBA_LOGSTDBY_UNSUPPORTED_TABLE

DBA_LOGSTDBY_UNSUPPORTED_TABLE displays the data tables that are not supported by Logical Standby. This view is for logical standby databases only.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the unsupported table
TABLE_NAME	VARCHAR2 (30)		Name of the unsupported table

DBA_MEASURE_FOLDER_CONTENTS

DBA_MEASURE_FOLDER_CONTENTS describes the contents of all OLAP measure folders in the database. Its columns are the same as those in ALL_MEASURE_FOLDER_CONTENTS.

See Also: ["ALL_MEASURE_FOLDER_CONTENTS"](#) on page 2-96

DBA_MEASURE_FOLDERS

DBA_MEASURE_FOLDERS describes all OLAP measure folders in the database. Its columns are the same as those in ALL_MEASURE_FOLDERS.

See Also: ["ALL_MEASURE_FOLDERS"](#) on page 2-96

DBA_METHOD_PARAMS

DBA_METHOD_PARAMS describes the method parameters of all object types in the database. Its columns are the same as those in ALL_METHOD_PARAMS.

See Also: ["ALL_METHOD_PARAMS"](#) on page 2-97

DBA_METHOD_RESULTS

DBA_METHOD_RESULTS describes the method results of all object types in the database. Its columns are the same as those in ALL_METHOD_RESULTS.

See Also: ["ALL_METHOD_RESULTS"](#) on page 2-98

DBA_MINING_MODEL_ATTRIBUTES

DBA_MINING_MODEL_ATTRIBUTES describes all mining model attributes in the database. Its columns are the same as those in ALL_MINING_MODEL_ATTRIBUTES.

See Also: ["ALL_MINING_MODEL_ATTRIBUTES"](#) on page 2-98

DBA_MINING_MODEL_SETTINGS

DBA_MINING_MODEL_SETTINGS describes all mining model settings in the database. Its columns are the same as those in ALL_MINING_MODEL_SETTINGS.

See Also: ["ALL_MINING_MODEL_SETTINGS"](#) on page 2-99

DBA_MINING_MODELS

DBA_MINING_MODELS describes all mining models in the database. Its columns are the same as those in ALL_MINING_MODELS.

See Also: ["ALL_MINING_MODELS"](#) on page 2-100

DBA_MVIEW_AGGREGATES

DBA_MVIEW_AGGREGATES describes the grouping functions (aggregated measures) that appear in the SELECT list of all aggregated materialized view in the database. Its columns are the same as those in ["ALL_MVIEW_AGGREGATES"](#) on page 2-101.

DBA_MVIEW_ANALYSIS

DBA_MVIEW_ANALYSIS describes all materialized views in the database that potentially support query rewrite and that provide additional information for analysis by applications. Its columns are the same as those in ["ALL_MVIEW_ANALYSIS"](#) on page 2-102.

Note: This view excludes materialized views that reference remote tables or that include references to non-static values such as SYSDATE or USER. This view also excludes materialized views that were created as snapshots prior to Oracle8i and that were never altered to enable query rewrite.

DBA_MVIEW_COMMENTS

DBA_MVIEW_COMMENTS displays comments on all materialized views in the database. Its columns are the same as those in ALL_MVIEW_COMMENTS.

See Also: ["ALL_MVIEW_COMMENTS"](#) on page 2-103

DBA_MVIEW_DETAIL_PARTITION

DBA_MVIEW_DETAIL_PARTITION displays freshness information for all materialized views in the database, with respect to a PCT detail partition. Its columns are the same as those in ["ALL_MVIEW_DETAIL_PARTITION"](#) on page 2-103.

DBA_MVIEW_DETAIL_RELATIONS

DBA_MVIEW_DETAIL_RELATIONS represents the named detail relations that are either in the FROM list of a materialized view, or that are indirectly referenced through views in the FROM list. Its columns are the same as those in ["ALL_MVIEW_DETAIL_RELATIONS"](#) on page 2-104.

DBA_MVIEW_DETAIL_SUBPARTITION

DBA_MVIEW_DETAIL_SUBPARTITION displays freshness information for all materialized views in the database, with respect to a PCT detail subpartition. Its columns are the same as those in ["ALL_MVIEW_DETAIL_SUBPARTITION"](#) on page 2-105.

DBA_MVIEW_JOINS

DBA_MVIEW_JOINS describes a join between two columns in the WHERE clause of a subquery that defines a materialized view. Its columns are the same as those in ["ALL_MVIEW_JOINS"](#) on page 2-105.

DBA_MVIEW_KEYS

DBA_MVIEW_KEYS describes the columns or expressions in the SELECT list upon which materialized views in the database are based. Its columns are the same as those in ["ALL_MVIEW_KEYS"](#) on page 2-106.

DBA_MVIEW_LOG_FILTER_COLS

DBA_MVIEW_LOG_FILTER_COLS displays all columns (excluding primary key columns) being logged in the materialized view logs.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the master table being logged
NAME	VARCHAR2 (30)		Name of the master table being logged
COLUMN_NAME	VARCHAR2 (30)		Column being logged

DBA_MVIEW_LOGS

DBA_MVIEW_LOGS describes all materialized view logs in the database. Its columns are the same as those in [ALL_MVIEW_LOGS](#).

See Also: ["ALL_MVIEW_LOGS"](#) on page 2-107

DBA_MVIEW_REFRESH_TIMES

DBA_MVIEW_REFRESH_TIMES describes refresh times of all materialized views in the database. Its columns are the same as those in [ALL_MVIEW_REFRESH_TIMES](#).

See Also: ["ALL_MVIEW_REFRESH_TIMES"](#) on page 2-107

DBA_MVIEWS

DBA_MVIEWS describes all materialized views in the database. Its columns are the same as those in ALL_MVIEWS.

See Also: ["ALL_MVIEWS"](#) on page 2-108

DBA_NESTED_TABLE_COLS

DBA_NESTED_TABLE_COLS describes the columns of all nested tables in the database. Its columns are the same as those in ["ALL_NESTED_TABLE_COLS"](#) on page 2-111. To gather statistics for this view, use the SQL ANALYZE statement.

DBA_NESTED_TABLES

DBA_NESTED_TABLES describes all nested tables contained in all tables in the database. Its columns are the same as those in ["ALL_NESTED_TABLES"](#) on page 2-113.

DBA_NETWORK_ACL_PRIVILEGES

DBA_NETWORK_ACL_PRIVILEGES describes the network privileges defined in all access control lists that are currently assigned to network hosts.

Column	Datatype	NULL	Description
ACL	VARCHAR2 (4000)		Path of the access control list
ACLID	RAW (16)	NOT NULL	Object ID of the access control list
PRINCIPAL	VARCHAR2 (4000)		Principal (database user or role) whom the privilege is granted to or denied from
PRIVILEGE	VARCHAR2 (7)		Network privilege
IS_GRANT	VARCHAR2 (5)		Indicates whether the privilege is granted (<code>true</code>) or denied (<code>false</code>)
INVERT	VARCHAR2 (5)		Indicates whether the access control entry contains invert principal (<code>true</code>) or not (<code>false</code>)
START_DATE	TIMESTAMP (9) WITH TIME ZONE		Start date of the access control entry
END_DATE	TIMESTAMP (9) WITH TIME ZONE		End date of the access control entry

DBA_NETWORK_ACLS

DBA_NETWORK_ACLS describes the access control list assignments to network hosts.

Column	Datatype	NULL	Description
HOST	VARCHAR2 (1000)	NOT NULL	Network host
LOWER_PORT	NUMBER (5)		Lower bound of the port range
UPPER_PORT	NUMBER (5)		Upper bound of the port range
ACL	VARCHAR2 (4000)		Path of the access control list
ACLID	RAW (16)	NOT NULL	Object ID of the access control list

DBA_OBJ_AUDIT_OPTS

DBA_OBJ_AUDIT_OPTS describes auditing options on all objects.

Related View

USER_OBJ_AUDIT_OPTS describes auditing options on all objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the object
OBJECT_NAME	VARCHAR2 (30)		Name of the object
OBJECT_TYPE	VARCHAR2 (23)		Type of the object
ALT	VARCHAR2 (3)		Auditing ALTER WHENEVER SUCCESSFUL / UNSUCCESSFUL
AUD	VARCHAR2 (3)		Auditing AUDIT WHENEVER SUCCESSFUL / UNSUCCESSFUL
COM	VARCHAR2 (3)		Auditing COMMENT WHENEVER SUCCESSFUL / UNSUCCESSFUL
DEL	VARCHAR2 (3)		Auditing DELETE WHENEVER SUCCESSFUL / UNSUCCESSFUL
GRA	VARCHAR2 (3)		Auditing GRANT WHENEVER SUCCESSFUL / UNSUCCESSFUL
IND	VARCHAR2 (3)		Auditing INDEX WHENEVER SUCCESSFUL / UNSUCCESSFUL
INS	VARCHAR2 (3)		Auditing INSERT WHENEVER SUCCESSFUL / UNSUCCESSFUL
LOC	VARCHAR2 (3)		Auditing LOCK WHENEVER SUCCESSFUL / UNSUCCESSFUL
REN	VARCHAR2 (3)		Auditing RENAME WHENEVER SUCCESSFUL / UNSUCCESSFUL
SEL	VARCHAR2 (3)		Auditing SELECT WHENEVER SUCCESSFUL / UNSUCCESSFUL
UPD	VARCHAR2 (3)		Auditing UPDATE WHENEVER SUCCESSFUL / UNSUCCESSFUL
REF	CHAR (3)		This column is obsolete and maintained for backward compatibility. The value of this column is always - / -
EXE	VARCHAR2 (3)		Auditing EXECUTE WHENEVER SUCCESSFUL / UNSUCCESSFUL
CRE	VARCHAR2 (3)		Auditing CREATE WHENEVER SUCCESSFUL / UNSUCCESSFUL
REA	VARCHAR2 (3)		Auditing READ WHENEVER SUCCESSFUL / UNSUCCESSFUL
WRI	VARCHAR2 (3)		Auditing WRITE WHENEVER SUCCESSFUL / UNSUCCESSFUL
FBK	VARCHAR2 (3)		Auditing FLASHBACK WHENEVER SUCCESSFUL / UNSUCCESSFUL

DBA_OBJ_COLATTRS

DBA_OBJ_COLATTRS describes object columns and attributes contained in all tables in the database. Its columns are the same as those in ALL_OBJ_COLATTRS.

See Also: ["ALL_OBJ_COLATTRS"](#) on page 2-113

DBA_OBJECT_SIZE

DBA_OBJECT_SIZE lists the sizes, in bytes, of various PL/SQL objects.

Related View

- USER_OBJECT_SIZE lists the size of PL/SQL objects owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
NAME	VARCHAR2 (30)	NOT NULL	Name of the object
TYPE	VARCHAR2 (12)		Type of the object: TYPE, TYPE BODY, TABLE, VIEW, SYNONYM, SEQUENCE, PROCEDURE, FUNCTION, PACKAGE, PACKAGE BODY, JAVA SOURCE, JAVA CLASS or JAVA RESOURCE
SOURCE_SIZE	NUMBER		Size of the source in bytes. Must be in memory during compilation, or dynamic recompilation.
PARSED_SIZE	NUMBER		Size of the parsed form of the object, in bytes. Must be in memory when an object is being compiled that references this object.
CODE_SIZE	NUMBER		Code size, in bytes. Must be in memory when this object is executing.
ERROR_SIZE	NUMBER		Size of error messages, in bytes. In memory during the compilation of the object when there are compilation errors.

DBA_OBJECT_TABLES

DBA_OBJECT_TABLES describes all object tables in the database. Its columns are the same as those in ALL_OBJECT_TABLES.

See Also: ["ALL_OBJECT_TABLES"](#) on page 2-114

DBA_OBJECTS

DBA_OBJECTS describes all objects in the database. Its columns are the same as those in ["ALL_OBJECTS"](#) on page 2-117.

DBA_OBJECTS_AE

DBA_OBJECTS_AE describes all objects (across all editions) in the database. Its columns are the same as those in ALL_OBJECTS_AE.

See Also: ["ALL_OBJECTS_AE"](#) on page 2-117

DBA_OPANCILLARY

DBA_OPANCILLARY provides ancillary information for all operator bindings in the database. Its columns are the same as those in ["ALL_OPANCILLARY"](#) on page 2-118.

DBA_OPARGUMENTS

DBA_OPARGUMENTS provides argument information for all operator bindings in the database. Its columns are the same as those in ["ALL_OPARGUMENTS"](#) on page 2-119.

DBA_OPBINDINGS

DBA_OPBINDINGS describes the binding functions and methods on all operators in the database. Its columns are the same as those in ALL_OPBINDINGS.

See Also: ["ALL_OPBINDINGS"](#) on page 2-119

DBA_OPERATOR_COMMENTS

DBA_OPERATOR_COMMENTS displays comments for all user-defined operators in the database. Its columns are the same as those in ALL_OPERATOR_COMMENTS.

See Also: ["ALL_OPERATOR_COMMENTS"](#) on page 2-120

DBA_OPERATORS

DBA_OPERATORS describes all operators in the database. Its columns are the same as those in ALL_OPERATORS.

See Also: ["ALL_OPERATORS"](#) on page 2-120

DBA_OPTSTAT_OPERATIONS

DBA_OPTSTAT_OPERATIONS contains a history of statistics operations performed at the schema and database level using the DBMS_STATS package.

Column	Datatype	NULL	Description
OPERATION	VARCHAR2 (64)		Operation name
TARGET	VARCHAR2 (64)		Target on which the operation was performed
START_TIME	TIMESTAMP (6) WITH TIME ZONE		Time at which the operation started
END_TIME	TIMESTAMP (6) WITH TIME ZONE		Time at which the operation ended

DBA_ORPHAN_KEY_TABLE

DBA_ORPHAN_KEY_TABLE reports key values from indexes where the underlying base table has block corruptions. To create the view, run the DBMS_REPAIR.ADMIN_TABLES procedure. To populate the orphan key table for an index, run the DBMS_REPAIR.DUMP_ORPHAN_KEYS procedure on the index. For each key in the index that points to a corrupt data block, Oracle inserts a row into the orphan key table.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Schema name of the index
INDEX_NAME	VARCHAR2 (30)	NOT NULL	Name of the index
IPART_NAME	VARCHAR2 (30)	NULL	Name of the index partition or subpartition
INDEX_ID	NUMBER	NOT NULL	Dictionary object ID of the index
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the base table of the index
PART_NAME	VARCHAR2 (30)	NULL	Name of the base table partition or subpartition
TABLE_ID	NUMBER	NOT NULL	Dictionary object ID of the base table
KEYDATA	UROWID	NOT NULL	Physical rowid of the corrupt data row
KEY	UROWID	NOT NULL	Key values for the index entry

Column	Datatype	NULL	Description
DUMP_TIMESTAMP	DATE	NOT NULL	Timestamp when the entry was made into the orphan key table

DBA_OUTLINE_HINTS

DBA_OUTLINE_HINTS describes the set of hints stored in all outlines in the database.

Related View

USER_OUTLINE_HINTS describes the set of hints stored in the outlines owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)		Name of the outline
OWNER	VARCHAR2 (30)		Name of the user who created the outline
NODE	NUMBER		ID of the query or subquery to which the hint applies. The top-level query is labeled 1. Subqueries are assigned sequentially numbered labels, starting with 2.
STAGE	NUMBER		Outline hints can be applied at three different stages during the compilation process. This column indicates the stage at which this hint was applied.
JOIN_POS	NUMBER		Position of the table in the join order. The value is 0 for all hints except access method hints, which identify a table to which the hint and the join position apply.
HINT	VARCHAR2 (512)		Text of the hint

See Also: ["USER_OUTLINE_HINTS"](#) on page 6-89

DBA_OUTLINES

DBA_OUTLINES describes all stored outlines in the database.

Related View

USER_OUTLINES describes the stored outlines owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)		User-specified or generated name of the stored outline. The name must be of a form that can be expressed in SQL.
OWNER	VARCHAR2 (30)		Name of the user who created the outline
CATEGORY	VARCHAR2 (30)		User-defined name of the category to which the outline belongs
USED	VARCHAR2 (6)		Indicates whether the outline has ever been used (USED) or not (UNUSED)
TIMESTAMP	DATE		Timestamp of outline creation
VERSION	VARCHAR2 (64)		Oracle version that created the outline
SQL_TEXT	LONG		SQL text of the query, including any hints that were a part of the original statement. If bind variables are included, the variable names are stored as SQL text, not the values that are assigned to the variables.

Column	Datatype	NULL	Description
			Note: This field may contain sensitive information about your database or application. Therefore, use discretion when granting <code>SELECT</code> or <code>VIEW</code> object privileges on these views.
SIGNATURE	RAW (16)		Signature uniquely identifying the outline SQL text
COMPATIBLE	VARCHAR2 (12)		Indicates whether the outline hints were compatible across a migration (COMPATIBLE) or not (INCOMPATIBLE)
ENABLED	VARCHAR2 (8)		Indicates whether the outline is enabled (ENABLED) or disabled (DISABLED)
FORMAT	VARCHAR2 (6)		Hint format: ■ NORMAL ■ LOCAL
MIGRATED	VARCHAR2 (12)		Indicates whether the outline has been migrated to a SQL plan baseline (MIGRATED) or not (NOT-MIGRATED)

See Also: ["USER_OUTLINES"](#) on page 6-89

DBA_OUTSTANDING_ALERTS

DBA_OUTSTANDING_ALERTS describes alerts which the server considers to be outstanding.

Column	Datatype	NULL	Description
SEQUENCE_ID	NUMBER		Alert sequence number
REASON_ID	NUMBER	NOT NULL	ID of the alert reason
OWNER	VARCHAR2 (30)		Owner of the object on which the alert was issued
OBJECT_NAME	VARCHAR2 (513)		Name of the object
SUBOBJECT_NAME	VARCHAR2 (30)		Name of the subobject
OBJECT_TYPE	VARCHAR2 (64)		Object type
REASON	VARCHAR2 (4000)		Reason for the alert
TIME_SUGGESTED	TIMESTAMP (6) WITH TIME ZONE		Time when the alert was last updated
CREATION_TIME	TIMESTAMP (6) WITH TIME ZONE		Time when the alert was first created
SUGGESTED_ACTION	VARCHAR2 (4000)		Advice of the recommended action
ADVISOR_NAME	VARCHAR2 (30)		Name of the advisor to be invoked for more information
METRIC_VALUE	NUMBER		Value of the related metrics
MESSAGE_TYPE	VARCHAR2 (12)		Message type: ■ Notification ■ Warning
MESSAGE_GROUP	VARCHAR2 (64)		Name of the message group to which the alert belongs
MESSAGE_LEVEL	NUMBER		Message severity level (1 to 32)
HOSTING_CLIENT_ID	VARCHAR2 (64)		ID of the client or security group to which the alert relates
MODULE_ID	VARCHAR2 (64)		ID of the module that originated the alert
PROCESS_ID	VARCHAR2 (128)		Process ID
HOST_ID	VARCHAR2 (256)		DNS host name of the originating host

Column	Datatype	NULL	Description
HOST_NW_ADDR	VARCHAR2 (256)		IP or other network address of the originating host
INSTANCE_NAME	VARCHAR2 (16)		Originating instance name
INSTANCE_NUMBER	NUMBER		Originating instance number
USER_ID	VARCHAR2 (30)		User ID
EXECUTION_CONTEXT_ID	VARCHAR2 (60)		ID of the threshold of execution
ERROR_INSTANCE_ID	VARCHAR2 (142)		ID of an error instance plus a sequence number

DBA_PARALLEL_EXECUTE_CHUNKS

DBA_PARALLEL_EXECUTE_CHUNKS displays the chunks for all tasks in the database.

Related View

USER_PARALLEL_EXECUTE_CHUNKS displays the chunks for tasks created by the current user. This view does not display the TASK_OWNER column.

Column	Datatype	NULL	Description
CHUNK_ID	NUMBER	NOT NULL	Unique ID for the chunk
TASK_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the task
TASK_NAME	VARCHAR2 (128)	NOT NULL	Name of the task
STATUS	VARCHAR2 (20)		Status of the chunk: ■ UNASSIGNED ■ ASSIGNED ■ PROCESSED ■ PROCESSED_WITH_ERROR
START_ROWID	ROWID		Rowid for the first row in the chunk
END_ROWID	ROWID		Rowid for the last row in the chunk
START_ID	NUMBER		Number column value of the first row in the chunk
END_ID	NUMBER		Number column value of the last row in the chunk
JOB_NAME	VARCHAR2 (30)		Name of the job which processed this chunk
START_TS	TIMESTAMP (6)		Processing start time for the chunk
END_TS	TIMESTAMP (6)		Processing end time for the chunk
ERROR_CODE	NUMBER		Error code returned during the execution of the chunk if the STATUS column is PROCESSED_WITH_ERROR
ERROR_MESSAGE	VARCHAR2 (4000)		Error message returned during the execution of the chunk if the STATUS column is PROCESSED_WITH_ERROR

See Also: ["USER_PARALLEL_EXECUTE_CHUNKS"](#) on page 6-90

DBA_PARALLEL_EXECUTE_TASKS

DBA_PARALLEL_EXECUTE_TASKS displays all tasks in the database.

Related View

USER_PARALLEL_EXECUTE_TASKS displays the tasks created by the current user. This view does not display the TASK_OWNER column.

Column	Datatype	NULL	Description
TASK_OWNER	VARCHAR2 (30)	NOT NULL	Owner of the task
TASK_NAME	VARCHAR2 (128)	NOT NULL	Name of the task
CHUNK_TYPE	VARCHAR2 (12)		Type of parallel update: ■ UNDELARED ■ ROWID_RANGE ■ NUMBER_RANGE
STATUS	VARCHAR2 (19)		Status of the task: ■ CREATED ■ CHUNKING ■ CHUNKING_FAILED ■ CHUNKED ■ PROCESSING ■ FINISHED ■ FINISHED_WITH_ERROR ■ CRASHED
TABLE_OWNER	VARCHAR2 (30)		Owner of the table to be chunked
TABLE_NAME	VARCHAR2 (30)		Name of the table to be chunked
NUMBER_COLUMN	VARCHAR2 (30)		Name of the column holding IDs (only applicable to NUMBER_RANGE chunking type)
TASK_COMMENT	VARCHAR2 (4000)		Comment field
JOB_PREFIX	VARCHAR2 (30)		Prefix of the job name executing this task
SQL_STMT	CLOB		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
LANGUAGE_FLAG	NUMBER		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
EDITION	VARCHAR2 (30)		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
APPLY_CROSSEDITION_TRIGGER	VARCHAR2 (30)		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
FIRE_APPLY_TRIGGER	VARCHAR2 (10)		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
PARALLEL_LEVEL	NUMBER		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
JOB_CLASS	VARCHAR2 (30)		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK

See Also: ["USER_PARALLEL_EXECUTE_TASKS"](#) on page 6-90

DBA_PART_COL_STATISTICS

DBA_PART_COL_STATISTICS displays column statistics and histogram information for all table partitions in the database. Its columns are the same as those in ALL_PART_COL_STATISTICS.

See Also: ["ALL_PART_COL_STATISTICS"](#) on page 3-1

DBA_PART_HISTOGRAMS

DBA_PART_HISTOGRAMS displays the histogram data (endpoints per histogram) for the histograms on all table partitions in the database. Its columns are the same as those in ALL_PART_HISTOGRAMS.

See Also: ["ALL_PART_HISTOGRAMS"](#) on page 3-2

DBA_PART_INDEXES

DBA_PART_INDEXES displays the object-level partitioning information for all partitioned indexes in the database. Its columns are the same as those in ALL_PART_INDEXES.

See Also: ["ALL_PART_INDEXES"](#) on page 3-3

DBA_PART_KEY_COLUMNS

DBA_PART_KEY_COLUMNS describes the partitioning key columns for all partitioned objects in the database. Its columns are the same as those in ALL_PART_KEY_COLUMNS.

See Also: ["ALL_PART_KEY_COLUMNS"](#) on page 3-5

DBA_PART_LOBS

DBA_PART_LOBS displays table-level information for all partitioned LOBs in the database, including default attributes for LOB data partitions. Its columns are the same as those in ALL_PART_LOBS.

See Also: ["ALL_PART_LOBS"](#) on page 3-5

DBA_PART_TABLES

DBA_PART_TABLES displays the object-level partitioning information for all partitioned tables in the database. Its columns are the same as those in ALL_PART_TABLES.

See Also: ["ALL_PART_TABLES"](#) on page 3-8

DBA_PARTIAL_DROP_TABS

DBA_PARTIAL_DROP_TABS describes all tables in the database that have partially completed DROP COLUMN operations. Its columns are the same as those in ["ALL_PARTIAL_DROP_TABS"](#) on page 3-11.

DBA_PENDING_CONV_TABLES

DBA_PENDING_CONV_TABLES describes all pending conversion tables in the database. Its columns are the same as those in ALL_PENDING_CONV_TABLES.

See Also: ["ALL_PENDING_CONV_TABLES"](#) on page 3-11

DBA_PENDING_TRANSACTIONS

DBA_PENDING_TRANSACTIONS describes unresolved transactions (either due to failure or if the coordinator has not sent a commit/rollback).

Column	Datatype	NULL	Description
FORMATID	NUMBER		The format identifier of the transaction identifier
GLOBALID	RAW (64)		The global part (gtrid) of the transaction identifier
BRANCHID	RAW (64)		The branch qualifier (bqual) of the transaction identifier

DBA_PLSQL_OBJECT_SETTINGS

DBA_PLSQL_OBJECT_SETTINGS displays information about the compiler settings for all stored objects in the database. Its columns are the same as those in ALL_PLSQL_OBJECT_SETTINGS.

See Also: ["ALL_PLSQL_OBJECT_SETTINGS"](#) on page 3-11

DBA_POLICIES

DBA_POLICIES describes all Oracle Virtual Private Database (VPD) security policies in the database. Its columns are the same as those in ALL_POLICIES. A security policy is a list of security requirements and rules that regulate user access to database objects.

See Also: ["ALL_POLICIES"](#) on page 3-12

DBA_POLICY_CONTEXTS

DBA_POLICY_CONTEXTS describes all driving contexts in the database. Its columns are the same as those in ALL_POLICY_CONTEXTS.

See Also: ["ALL_POLICY_CONTEXTS"](#) on page 3-13

DBA_POLICY_GROUPS

DBA_POLICY_GROUPS describes all policy groups in the database. Its columns are the same as those in ALL_POLICY_GROUPS.

See Also: ["ALL_POLICY_GROUPS"](#) on page 3-14

DBA_PRIV_AUDIT_OPTS

DBA_PRIV_AUDIT_OPTS describes current system privileges being audited across the system and by user.

Column	Datatype	NULL	Description
USER_NAME	VARCHAR2 (30)		User name if by user auditing; ANY CLIENT if access by a proxy on behalf of a client is being audited; NULL for system-wide auditing
PROXY_NAME	VARCHAR2 (30)		Name of the proxy user which is performing an operation for the client; NULL if the client is performing the operation directly
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Name of the system privilege being audited
SUCCESS	VARCHAR2 (10)		Mode for WHENEVER SUCCESSFUL system auditing

Column	Datatype	NULL	Description
FAILURE	VARCHAR2 (10)		Mode for WHENEVER NOT SUCCESSFUL system auditing

DBA_PROCEEDURES

DBA_PROCEEDURES lists all functions and procedures along with their associated properties. Its columns are the same as those in ["ALL_PROCEEDURES"](#) on page 3-14.

DBA_PROFILES

DBA_PROFILES displays all profiles and their limits.

Column	Datatype	NULL	Description
PROFILE	VARCHAR2 (30)	NOT NULL	Profile name
RESOURCE_NAME	VARCHAR2 (32)	NOT NULL	Resource name
RESOURCE_TYPE	VARCHAR2 (8)		Indicates whether the resource profile is a KERNEL or a PASSWORD parameter
LIMIT	VARCHAR2 (40)		Limit placed on this resource for this profile

DBA_PROPAGATION

DBA_PROPAGATION displays information about all Streams propagations in the database. Its columns are the same as those in [ALL_PROPAGATION](#).

See Also: ["ALL_PROPAGATION"](#) on page 3-15

DBA_PROXIES

DBA_PROXIES displays Information about all proxy connections in the database.

Related View

USER_PROXIES displays information about connections the current user is allowed to proxy. This view does not display the PROXY or PROXY_AUTHORITY columns.

Column	Datatype	NULL	Description
PROXY	VARCHAR2 (30)	NOT NULL	Name of the proxy user
CLIENT	VARCHAR2 (30)	NOT NULL	Name of the client user who the proxy user can act on behalf of
AUTHENTICATION	VARCHAR2 (3)		Indicates whether the proxy is required to supply the client's authentication credentials (YES) or not (NO)
AUTHORIZATION_ CONSTRAINT	VARCHAR2 (35)		Indicates the proxy's authority to exercise roles on the client's behalf: - PROXY MAY ACTIVATE ALL CLIENT ROLES - NO CLIENT ROLES MAY BE ACTIVATED - PROXY MAY ACTIVATE ROLE - PROXY MAY ACTIVATE ALL CLIENT ROLES - PROXY MAY NOT ACTIVATE ROLE
ROLE	VARCHAR2 (30)		Name of the role referenced in AUTHORIZATION_ CONSTRAINT

Column	Datatype	NULL	Description
PROXY_AUTHORITY	VARCHAR2 (9)		Value is either: - DIRECTORY if EUS proxy is enabled for that database user - DATABASE if this row describes a local proxy permission

See Also: ["USER_PROXIES"](#) on page 6-92

DBA_PUBLISHED_COLUMNS

DBA_PUBLISHED_COLUMNS describes all source table columns in the database which have been published for the source tables. This view is intended for use by Change Data Capture publishers.

Related View

USER_PUBLISHED_COLUMNS describes the source table columns owned by the current user which have been published for the source tables. This view does not display the CHANGE_TABLE_SCHEMA or CHANGE_TABLE_NAME columns.

Column	Datatype	NULL	Description
CHANGE_SET_NAME	VARCHAR2 (30)	NOT NULL	Name of the change set
CHANGE_TABLE_SCHEMA	VARCHAR2 (30)	NOT NULL	Associated change table owner
CHANGE_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Associated change table name
PUB_ID	NUMBER	NOT NULL	Publication identifier
SOURCE_SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Table owner in the source database
SOURCE_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Table name in the source database
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Column name
DATA_TYPE	VARCHAR2 (106)		Column datatype
DATA_LENGTH	NUMBER	NOT NULL	Column length (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER datatypes; binary precision for FLOAT datatypes; NULL for all other datatypes
DATA_SCALE	NUMBER		Digits to the right of a decimal point in a number
NULLABLE	VARCHAR2 (1)		Indicates whether NULLs are allowed (Y) or not (N)

See Also: ["USER_PUBLISHED_COLUMNS"](#) on page 6-92

DBA_QUEUE_SCHEDULES

DBA_QUEUE_SCHEDULES describes all propagation schedules in the database. Its columns are the same as those in ALL_QUEUE_SCHEDULES.

See Also: ["ALL_QUEUE_SCHEDULES"](#) on page 3-16

DBA_QUEUE_SUBSCRIBERS

DBA_QUEUE_SUBSCRIBERS displays all subscribers on all queues in the database. Its columns are the same as those in ["ALL_QUEUE_SUBSCRIBERS"](#) on page 3-18.

DBA_QUEUE_TABLES

DBA_QUEUE_TABLES contains information about the owner instance for a queue table. A queue table can contain multiple queues. In this case, each queue in a queue table has the same owner instance as the queue table. Its columns are the same as those in ALL_QUEUE_TABLES.

See Also: ["ALL_QUEUE_TABLES"](#) on page 3-18

DBA_QUEUES

DBA_QUEUES describes the operational characteristics of every queue in a database. Its columns are the same as those in ["ALL_QUEUES"](#) on page 3-19.

See Also: *Oracle Streams Advanced Queuing User's Guide* for more information about this view and Advanced Queuing

DBA_RCHILD

DBA_RCHILD displays all the children in any refresh group.

Column	Datatype	NULL	Description
REFGROUP	NUMBER		Internal identifier of the refresh group
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object in the refresh group
NAME	VARCHAR2 (30)	NOT NULL	Name of the object in the refresh group
TYPE#	VARCHAR2 (30)		Type of the object in the refresh group

DBA_RECOVERABLE_SCRIPT

DBA_RECOVERABLE_SCRIPT provides details about recoverable operations.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW (16)		Unique ID of the operation
CREATION_TIME	DATE		Time the operation was invoked
INVOKING_PACKAGE_OWNER	VARCHAR2 (30)		Invoking package owner of the operation
INVOKING_PACKAGE	VARCHAR2 (30)		Invoking package of the operation
INVOKING_PROCEDURE	VARCHAR2 (30)		Invoking procedure of the operation
INVOKING_USER	VARCHAR2 (30)		Script owner
STATUS	VARCHAR2 (12)		State of the recoverable script: GENERATING, NOT EXECUTED, EXECUTING, EXECUTED, or ERROR
TOTAL_BLOCKS	NUMBER		Total number of blocks for the recoverable script to be executed
DONE_BLOCK_NUM	NUMBER		Last block executed, thus far
SCRIPT_COMMENT	VARCHAR2 (4000)		Comment for the recoverable script

DBA_RECOVERABLE_SCRIPT_BLOCKS

DBA_RECOVERABLE_SCRIPT_BLOCKS provides details about recoverable script blocks.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW (16)		Global unique ID of the recoverable script to which this block belongs
BLOCK_NUM	NUMBER		The <i>n</i> th block in the recoverable script to be executed
FORWARD_BLOCK	CLOB		Forward block to be executed
FORWARD_BLOCK_DBLINK	VARCHAR2 (128)		Database where the forward block is executed
UNDO_BLOCK	CLOB		Block to roll back the forward operation
UNDO_BLOCK_DBLINK	VARCHAR2 (128)		Database where the undo block is executed
STATUS	VARCHAR2 (12)		Status of the block execution: GENERATING, NOT EXECUTED, EXECUTING, EXECUTED, or ERROR
BLOCK_COMMENT	VARCHAR2 (4000)		Comment for the block

DBA_RECOVERABLE_SCRIPT_ERRORS

DBA_RECOVERABLE_SCRIPT_ERRORS provides details about errors that occurred during script execution.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW (16)		Global unique ID of the recoverable script
BLOCK_NUM	NUMBER		The <i>n</i> th block that failed
ERROR_NUMBER	NUMBER		Number of the error encountered while executing the block
ERROR_MESSAGE	VARCHAR2 (4000)		Error message encountered while executing the block
ERROR_CREATION_TIME	DATE		Time that the error was created

DBA_RECOVERABLE_SCRIPT_HIST

DBA_RECOVERABLE_SCRIPT_HIST displays details about executed or purged recoverable operations.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW (16)		Unique id of the operation
CREATION_TIME	DATE		Time the operation was invoked
INVOKING_PACKAGE_OWNER	VARCHAR2 (30)		Invoking package owner of the operation
INVOKING_PACKAGE	VARCHAR2 (30)		Invoking package of the operation
INVOKING_PROCEDURE	VARCHAR2 (30)		Invoking procedure of the operation
INVOKING_USER	VARCHAR2 (30)		Script owner
STATUS	VARCHAR2 (8)		state of the recoverable script: EXECUTED, PURGED
TOTAL_BLOCKS	NUMBER		total number of blocks for the recoverable script to be executed
DONE_BLOCK_NUM	NUMBER		last block so far executed
SCRIPT_COMMENT	VARCHAR2 (4000)		comment for the recoverable script

DBA_RECOVERABLE_SCRIPT_PARAMS

DBA_RECOVERABLE_SCRIPT_PARAMS provides details about recoverable operation parameters.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW (16)		Unique ID of the operation
PARAMETER	VARCHAR2 (30)		Name of the parameter
PARAM_INDEX	NUMBER		Index for multi-valued parameter
VALUE	VARCHAR2 (4000)		Value of the parameter

DBA_RECYCLEBIN

DBA_RECYCLEBIN displays information about all recycle bins in the database.

Related View

USER_RECYCLEBIN displays information about the recycle bin owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Name of the original owner of the object
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	New name of the object
ORIGINAL_NAME	VARCHAR2 (32)		Original name of the object
OPERATION	VARCHAR2 (9)		Operation carried out on the object: ▪ DROP - Object was dropped ▪ TRUNCATE - Object was truncated Note: The Oracle Database currently only supports recovering dropped objects from the recycle bin. The truncated objects cannot be recovered.
TYPE	VARCHAR2 (25)		Type of the object: ▪ TABLE ▪ NORMAL INDEX ▪ BITMAP INDEX ▪ NESTED TABLE ▪ LOB ▪ LOB INDEX ▪ DOMAIN INDEX ▪ IOT TOP INDEX ▪ IOT OVERFLOW SEGMENT ▪ IOT MAPPING TABLE ▪ TRIGGER ▪ CONSTRAINT ▪ Table Partition ▪ Table Composite Partition ▪ Index Partition ▪ Index Composite Partition ▪ LOB Partition ▪ LOB Composite Partition
TS_NAME	VARCHAR2 (30)		Name of the tablespace to which the object belongs
CREATETIME	VARCHAR2 (19)		Timestamp for the creation of the object
DROPTIME	VARCHAR2 (19)		Timestamp for the dropping of the object
DROPSCN	NUMBER		System change number (SCN) of the transaction which moved the object to the recycle bin
PARTITION_NAME	VARCHAR2 (32)		Name of the partition which was dropped

Column	Datatype	NULL	Description
CAN_UNDROP	VARCHAR2 (3)		Indicates whether the object can be undropped (YES) or not (NO)
CAN_PURGE	VARCHAR2 (3)		Indicates whether the object can be purged (YES) or not (NO)
RELATED	NUMBER	NOT NULL	Object number of the parent object
BASE_OBJECT	NUMBER	NOT NULL	Object number of the base object
PURGE_OBJECT	NUMBER	NOT NULL	Object number for the object which gets purged
SPACE	NUMBER		Number of blocks used by the object

See Also: ["USER_RECYCLEBIN"](#) on page 6-93

DBA_REDEFINITION_ERRORS

DBA_REDEFINITION_ERRORS is an online redefinition view and displays the dependent objects for which errors were raised while attempting to create similar objects on the interim table of the redefinition.

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2 (12)		Type of the redefinition object: - TABLE - INDEX - CONSTRAINT - TRIGGER - NESTED TABLE - PARTITION - MV LOG
OBJECT_OWNER	VARCHAR2 (4000)		Owner of the redefinition object
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the redefinition object
BASE_TABLE_OWNER	VARCHAR2 (30)		Owner of the base table of the redefinition object
BASE_TABLE_NAME	VARCHAR2 (30)		Name of the base table of the redefinition object
DDL_TXT	CLOB		DDL used to create the corresponding interim redefinition object
EDITION_NAME	VARCHAR2 (30)		Reserved for future use

DBA_REDEFINITION_OBJECTS

DBA_REDEFINITION_OBJECTS is an online redefinition view and displays the objects involved in the current redefinitions.

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2 (12)		Type of the redefinition object: - TABLE - INDEX - CONSTRAINT - TRIGGER - NESTED TABLE - PARTITION - MV LOG

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2 (4000)		Owner of the redefinition object
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the redefinition object
BASE_TABLE_OWNER	VARCHAR2 (30)		Owner of the base table of the redefinition object
BASE_TABLE_NAME	VARCHAR2 (30)		Name of the base table of the redefinition object
INTERIM_OBJECT_OWNER	VARCHAR2 (4000)		Owner of the corresponding interim redefinition object
INTERIM_OBJECT_NAME	VARCHAR2 (30)		Name of the corresponding interim redefinition object
EDITION_NAME	VARCHAR2 (30)		Reserved for future use

DBA_REFRESH

DBA_REFRESH describes all refresh groups in the database. Its columns are the same as those in ["ALL_REFRESH"](#) on page 3-20.

DBA_REFRESH_CHILDREN

DBA_REFRESH_CHILDREN lists all of the objects in all refresh groups in the database. Its columns are the same as those in ["ALL_REFRESH_CHILDREN"](#) on page 3-21.

DBA_REFS

DBA_REFS describes the REF columns and REF attributes in object type columns of all the objects in the database. Its columns are the same as those in ["ALL_REFS"](#) on page 3-22.

DBA_REGISTERED_ARCHIVED_LOG

DBA_REGISTERED_ARCHIVED_LOG displays information about all registered archived logfiles in the database.

Column	Datatype	NULL	Description
CONSUMER_NAME	VARCHAR2 (30)	NOT NULL	Consumer name of the archived logs
SOURCE_DATABASE	VARCHAR2 (128)		Name of the database which generated the redo logs
THREAD#	NUMBER	NOT NULL	Thread number of the archived redo log. The thread number is 1 for a single instance. For Real Application Clusters, this column will contain different numbers.
SEQUENCE#	NUMBER	NOT NULL	Sequence number of the archived redo log file
FIRST_SCN	NUMBER	NOT NULL	System change number (SCN) of the current archived redo log
NEXT_SCN	NUMBER		System change number (SCN) of the next archived redo log
FIRST_TIME	DATE		Date and time of the current archived redo log
NEXT_TIME	DATE		Date and time of the next archived redo log
NAME	VARCHAR2 (513)		Name of the archived redo log
MODIFIED_TIME	DATE		Time when the archived redo log was registered
DICTIONARY_BEGIN	VARCHAR2 (3)		Indicates whether the beginning of the dictionary build is in the archived redo log (YES) or not (NO)
DICTIONARY_END	VARCHAR2 (3)		Indicates whether the end of the dictionary build is in the archived redo log (YES) or not (NO)

Column	Datatype	NULL	Description
PURGEABLE	VARCHAR2 (3)		Indicates whether the redo log can be permanently removed (YES) or not (NO)
RESET_LOGS_CHANGE#	NUMBER	NOT NULL	Resetlogs change number of the database when the log was written
RESET_TIMESTAMP	NUMBER	NOT NULL	Resetlogs time of the database when the log was written

DBA_REGISTERED_MVIEW_GROUPS

DBA_REGISTERED_MVIEW_GROUPS lists all the registered materialized view groups at the master site or master materialized view site.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)		Name of the materialized view replication group
MVIEW_SITE	VARCHAR2 (128)		Site of the materialized view replication group
GROUP_COMMENT	VARCHAR2 (80)		Description of the materialized view replication group
VERSION	VARCHAR2 (8)		Oracle release of the materialized view replication group: ■ ORACLE 7 ■ ORACLE 8 ■ REPAPI Note: Oracle8i and newer materialized view groups show ORACLE 8.
FNAME	VARCHAR2 (30)		Name of the flavor of the materialized view group
OWNER	VARCHAR2 (30)		Owner of the materialized view replication group

DBA_REGISTERED_MVIEWS

DBA_REGISTERED_MVIEWS describes all registered materialized views (registered at a master site or a master materialized view site) in the database. Its columns are the same as those in ALL_REGISTERED_MVIEWS.

See Also: ["ALL_REGISTERED_MVIEWS"](#) on page 3-22

DBA_REGISTRY

DBA_REGISTRY displays information about all components in the database that are loaded into the component registry. The component registry tracks components that can be separately loaded into the Oracle Database. When a SQL script loads the PL/SQL packages and other database objects for a component into the database, the script uses the DBMS_REGISTRY package to record the component name, status, and version. If scripts are used to upgrade/downgrade the dictionary elements for the component, then those scripts also use the DBMS_REGISTRY package to provide status and version information.

Related View

USER_REGISTRY displays information about the components owned by the current user that are loaded into the component registry.

Column	Datatype	NULL	Description
COMP_ID	VARCHAR2 (30)	NOT NULL	Component identifier

Column	Datatype	NULL	Description
COMP_NAME	VARCHAR2 (255)		Component name
VERSION	VARCHAR2 (30)		Component version loaded
STATUS	VARCHAR2 (11)		Component status: ■ INVALID ■ VALID ■ LOADING ■ LOADED ■ UPGRADING ■ UPGRADED ■ DOWNGRADING ■ DOWNGRADED ■ REMOVING ■ REMOVED
MODIFIED	VARCHAR2 (20)		Time when the component was last modified
NAMESPACE	VARCHAR2 (30)	NOT NULL	Component namespace
CONTROL	VARCHAR2 (30)	NOT NULL	User that created the component entry
SCHEMA	VARCHAR2 (30)	NOT NULL	User that contains the objects for the component
PROCEDURE	VARCHAR2 (61)		Validation procedure
STARTUP	VARCHAR2 (8)		Indicates whether the component requires a startup after the upgrade (REQUIRED) or not
PARENT_ID	VARCHAR2 (30)		Parent component identifier

See Also: ["USER_REGISTRY"](#) on page 6-93

DBA_REGISTRY_HIERARCHY

DBA_REGISTRY_HIERARCHY displays information about the components loaded into the database, grouped by owner and organized in the component hierarchy.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2 (30)	NOT NULL	Component namespace
COMP_ID	VARCHAR2 (4000)		Component identifier
VERSION	VARCHAR2 (30)		Component version loaded
STATUS	VARCHAR2 (11)		Component status: ■ INVALID ■ VALID ■ LOADING ■ LOADED ■ UPGRADING ■ UPGRADED ■ DOWNGRADING ■ DOWNGRADED ■ REMOVING ■ REMOVED
MODIFIED	VARCHAR2 (20)		Time when the component was last modified

DBA_REGISTRY_HISTORY

DBA_REGISTRY_HISTORY provides information about upgrades, downgrades, and critical patch updates that have been performed on the database.

Column	Datatype	NULL	Description
ACTION_TIME	TIMESTAMP (6)		The time the upgrade, downgrade, or patch action was completed
ACTION	VARCHAR2 (30)		The specific action (for example, UPGRADE or DOWNGRADE)
NAMESPACE	VARCHAR2 (30)		The namespace of the components affected (for example, SERVER)
VERSION	VARCHAR2 (30)		The version number of the server (for example, 10.2.0.1.0)
ID	NUMBER		Bundle ID
BUNDLE_SERIES ¹	VARCHAR2 (30)		Name of the bundle series (for example, CPU, PSU, or WINBUNDLE)
COMMENTS	VARCHAR2 (255)		Additional comments about the action taken

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_REGISTRY_LOG

DBA_REGISTRY_LOG displays operating information about components loaded into the database.

Column	Datatype	NULL	Description
OPTIME	VARCHAR2 (20)		Operation time
NAMESPACE	VARCHAR2 (30)		Component namespace
COMP_ID	VARCHAR2 (30)		Component identifier
OPERATION	VARCHAR2 (11)		Operation name
MESSAGE	VARCHAR2 (1000)		Message

DBA_REPAIR_TABLE

DBA_REPAIR_TABLE describes any corruptions found by the DBMS_REPAIR.CHECK_OBJECT procedure. This information is used by the DBMS_REPAIR.FIX_CORRUPT_BLOCKS procedure on execution. To create this view, first run the DBMS_REPAIR.ADMIN_TABLES procedure. To populate the resulting repair table for an object, run the DBMS_REPAIR.CHECK_OBJECT procedure on the object.

Note: The table created by the DBMS_REPAIR.ADMIN_TABLES procedure is called REPAIR_TABLE by default. If you specify a different name, this view will have the name you specify, preceded by "DBA_REPAIR_".

Column	Datatype	NULL	Description
OBJECT_ID	NUMBER	NOT NULL	Dictionary object number of the object with the corruption
TABLESPACE_ID	NUMBER	NOT NULL	Tablespace number of the corrupt object

Column	Datatype	NULL	Description
RELATIVE_FILE_ID	NUMBER	NOT NULL	Relative file number of the corrupt object
BLOCK_ID	NUMBER	NOT NULL	Block number of the corruption
CORRUPT_TYPE	NUMBER	NOT NULL	Type of corruption encountered
SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Schema of the corrupt object
OBJECT_NAME	VARCHAR2 (30)	NOT NULL	Name of the corrupt object
BASEOBJECT_NAME	VARCHAR2 (30)	NULL	If the object is an index, the name of its base table
PARTITION_NAME	VARCHAR2 (30)	NULL	Partition or subpartition name, if applicable
CORRUPT_DESCRIPTION	VARCHAR2 (200)	NULL	Description of corruption
REPAIR_DESCRIPTION	VARCHAR2 (200)	NULL	Description of repair action
MARKED_CORRUPT	VARCHAR2 (10)	NOT NULL	Whether the block is marked corrupt (TRUE FALSE)
CHECK_TIMESTAMP	DATE	NOT NULL	Date and time when this row was insert into the repair table
FIX_TIMESTAMP	DATE	NULL	Date and time when the block was modified by the FIX_CORRUPT_BLOCKS procedure, if applicable
REFORMAT_TIMESTAMP	DATE	NULL	Reserved for future use

DBA_RESOURCE_INCARNATIONS

DBA_RESOURCE_INCARNATIONS lists all resource incarnations that are running or eligible for HA status notification.

Column	Datatype	NULL	Description
RESOURCE_TYPE	VARCHAR2 (30)	NOT NULL	Type of resource
RESOURCE_NAME	VARCHAR2 (256)		Name of resource
DB_UNIQUE_NAME	VARCHAR2 (30)	NOT NULL	Database unique name
DB_DOMAIN	VARCHAR2 (128)	NOT NULL	Database domain
INSTANCE_NAME	VARCHAR2 (30)	NOT NULL	Name of instance at which resource is located
HOST_NAME	VARCHAR2 (512)		Name of host at which resource is located
STARTUP_TIME	TIMESTAMP (9) WITH TIME ZONE		Resource startup date and time

DBA_RESUMABLE

DBA_RESUMABLE displays all resumable statements executed in the system.

Related View

USER_RESUMABLE displays the resumable statements executed by the current user. This view does not display the USER_ID column.

Column	Datatype	NULL	Description
USER_ID	NUMBER		User ID Number of the Resumable Statement Owner
SESSION_ID	NUMBER		Session Identifier of the Resumable Statement
INSTANCE_ID	NUMBER		Instance Number of the Resumable Statement
COORD_INSTANCE_ID	NUMBER		Instance Number on which the Parallel Coordinator is Running
COORD_SESSION_ID	NUMBER		Session Identifier of the Parallel Coordinator

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (9)		Status of the resumable statement: ■ RUNNING ■ SUSPENDED ■ TIMEOUT ■ ERROR ■ ABORTED
TIMEOUT	NUMBER		Timeout of the resumable statement
START_TIME	VARCHAR2 (20)		Start time of the resumable statement
SUSPEND_TIME	VARCHAR2 (20)		Last time the resumable statement was suspended (initialized to NULL)
RESUME_TIME	VARCHAR2 (20)		Last time the suspended resumable statement was resumed (initialized to NULL)
NAME	VARCHAR2 (4000)		Name given in the resumable clause of the resumable statement
SQL_TEXT	VARCHAR2 (1000)		Resumable statement, selected from the V\$SQL view
ERROR_NUMBER	NUMBER		Error code of the last correctable error. When STATUS is set to RUNNING, its value will be 0.
ERROR_PARAMETER1	VARCHAR2 (80)		First parameter for the error message (NULL if no error)
ERROR_PARAMETER2	VARCHAR2 (80)		Second parameter for the error message (NULL if no error)
ERROR_PARAMETER3	VARCHAR2 (80)		Third parameter for the error message (NULL if no error)
ERROR_PARAMETER4	VARCHAR2 (80)		Forth parameter for the error message (NULL if no error)
ERROR_PARAMETER5	VARCHAR2 (80)		Fifth parameter for the error message (NULL if no error)
ERROR_MSG	VARCHAR2 (4000)		Error message corresponding to ERROR_NUMBER. It will be NULL when ERROR_NUMBER is 0.

See Also: ["USER_RESUMABLE"](#) on page 6-94

DBA_REWRITE_EQUIVALENCES

DBA_REWRITE_EQUIVALENCES describes all rewrite equivalences in the database. Its columns are the same as those in ALL_REWRITE_EQUIVALENCES.

See Also: ["ALL_REWRITE_EQUIVALENCES"](#) on page 3-23

DBA_RGROUP

DBA_RGROUP displays all refresh groups.

Column	Datatype	NULL	Description
REFGROUP	NUMBER		Internal identifier of the refresh group
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object in the refresh group
NAME	VARCHAR2 (30)	NOT NULL	Name of the object in the refresh group
IMPLICIT_DESTROY	VARCHAR2 (1)		Indicates whether the refresh group is destroyed when its last item is removed (Y) or not (N)
PUSH_DEFERRED_RPC	VARCHAR2 (1)		Indicates whether changes are pushed from the snapshot to the master before refresh (Y) or not (N)

Column	Datatype	NULL	Description
REFRESH_AFTER_ERRORS	VARCHAR2 (1)		Indicates whether to proceed with refresh despite errors when pushing deferred RPCs (Y) or not (N)
ROLLBACK_SEG	VARCHAR2 (30)		Name of the rollback segment to use while refreshing
JOB	NUMBER	NOT NULL	Identifier of the job used to refresh the group automatically
PURGE_OPTION	NUMBER (38)		Method for purging the transaction queue after each push. 1 indicates quick purge option; 2 indicates precise purge option
PARALLELISM	NUMBER (38)		Level of parallelism for transaction propagation
HEAP_SIZE	NUMBER (38)		Size of the heap

DBA_ROLE_PRIVS

DBA_ROLE_PRIVS describes the roles granted to all users and roles in the database.

Related View

USER_ROLE_PRIVS describes the roles granted to the current user.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)		Name of the user or role receiving the grant
GRANTED_ROLE	VARCHAR2 (30)	NOT NULL	Granted role name
ADMIN_OPTION	VARCHAR2 (3)		Indicates whether the grant was with the ADMIN OPTION (YES) or not (NO)
DEFAULT_ROLE	VARCHAR2 (3)		Indicates whether the role is designated as a DEFAULT ROLE for the user (YES) or not (NO)

See Also: ["USER_ROLE_PRIVS"](#) on page 6-94

DBA_ROLES

DBA_ROLES describes all roles in the database.

Column	Datatype	NULL	Description
ROLE	VARCHAR2 (30)	NOT NULL	Name of the role
PASSWORD_REQUIRED	VARCHAR2 (8)		This column is deprecated in favor of the AUTHENTICATION_TYPE column
AUTHENTICATION_TYPE	VARCHAR2 (11)		Indicates the authentication mechanism for the role: - NONE - CREATE ROLE <i>role1</i>; - EXTERNAL - CREATE ROLE <i>role2</i> IDENTIFIED EXTERNALLY; - GLOBAL - CREATE ROLE <i>role3</i> IDENTIFIED GLOBALLY; - APPLICATION - CREATE ROLE <i>role4</i> IDENTIFIED USING <i>schema.package</i>; - PASSWORD - CREATE ROLE <i>role5</i> IDENTIFIED BY <i>role5</i>;

DBA_ROLLBACK_SEGS

DBA_ROLLBACK_SEGS describes rollback segments.

Column	Datatype	NULL	Description
SEGMENT_NAME	VARCHAR2 (30)	NOT NULL	Name of the rollback segment
OWNER	VARCHAR2 (6)		Owner of the rollback segment: - PUBLIC - SYS
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace containing the rollback segment
SEGMENT_ID	NUMBER	NOT NULL	ID number of the rollback segment
FILE_ID	NUMBER	NOT NULL	File identifier number of the file containing the segment head
BLOCK_ID	NUMBER	NOT NULL	ID number of the block containing the segment header
INITIAL_EXTENT	NUMBER		Initial extent size in bytes
NEXT_EXTENT	NUMBER		Secondary extent size in bytes
MIN_EXTENTS	NUMBER	NOT NULL	Minimum number of extents
MAX_EXTENTS	NUMBER	NOT NULL	Maximum number of extent
PCT_INCREASE	NUMBER		Percent increase for extent size
STATUS	VARCHAR2 (16)		Rollback segment status: - OFFLINE - ONLINE - NEEDS RECOVERY - PARTLY AVAILABLE - UNDEFINED
INSTANCE_NUM	VARCHAR2 (40)		Rollback segment owning Real Application Clusters instance number
RELATIVE_FNO	NUMBER	NOT NULL	Relative file number of the segment header

DBA_RSRC_CATEGORIES

DBA_RSRC_CATEGORIES displays all resource consumer group categories.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)		Name of the consumer group category
COMMENTS	VARCHAR2 (2000)		Text comment on the consumer group category
STATUS	VARCHAR2 (30)		Indicates whether the consumer group category is part of the pending area (PENDING) or not (NULL)
MANDATORY	VARCHAR2 (3)		Indicates whether the consumer group category is mandatory (YES) or not (NO)

DBA_RSRC_CONSUMER_GROUP_PRIVS

DBA_RSRC_CONSUMER_GROUP_PRIVS displays information about all resource consumer groups and the users and roles assigned to them. The grant referred to in this view and the related view is the grant of the SWITCH_CONSUMER_GROUP object privilege, which is granted using the DBMS_RESOURCE_MANAGER_PRIVS package. This privilege is not granted through the GRANT SQL statement.

Related View

USER_RSRC_CONSUMER_GROUP_PRIVS displays information about the resource consumer groups to which the current user is assigned. This view does not display the GRANTEE column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	User or role receiving the grant
GRANTED_GROUP	VARCHAR2 (30)		Granted consumer group name
GRANT_OPTION	VARCHAR2 (3)		Indicates whether the grant was with the GRANT option (YES) or not (NO)
INITIAL_GROUP	VARCHAR2 (3)		Indicates whether the consumer group is designated as the default for this user or role (YES) or not (NO)

See Also:

- ["USER_RSRC_CONSUMER_GROUP_PRIVS"](#) on page 6-94
- *Oracle Database PL/SQL Packages and Types Reference* for more information on consumer group privileges

DBA_RSRC_CONSUMER_GROUPS

DBA_RSRC_CONSUMER_GROUPS displays information about all resource consumer groups in the database.

Column	Datatype	NULL	Description
CONSUMER_GROUP_ID	NUMBER	NOT NULL	ID of the consumer group
CONSUMER_GROUP	VARCHAR2 (30)		Name of the consumer group
CPU_METHOD	VARCHAR2 (30)		CPU resource allocation method for the consumer group
MGMT_METHOD	VARCHAR2 (30)		Resource allocation method for the consumer group
INTERNAL_USE	VARCHAR2 (3)		Indicates whether the consumer group is for internal use only (YES) or not (NO)
COMMENTS	VARCHAR2 (2000)		Text comment on the consumer group
CATEGORY	VARCHAR2 (30)		Category of the consumer group
STATUS	VARCHAR2 (30)		Indicates whether the consumer group is part of the pending area (PENDING) or not (NULL)
MANDATORY	VARCHAR2 (3)		Indicates whether the consumer group is mandatory (YES) or not (NO)

DBA_RSRC_GROUP_MAPPINGS

DBA_RSRC_GROUP_MAPPINGS displays the mapping between session attributes and consumer groups in the database.

Column	Datatype	NULL	Description
ATTRIBUTE	VARCHAR2 (30)		Session attribute to match
VALUE	VARCHAR2 (128)		Attribute value
CONSUMER_GROUP	VARCHAR2 (30)		Target consumer group name
STATUS	VARCHAR2 (30)		Indicates whether the consumer group is part of the pending area (PENDING) or not (NULL)

DBA_RSRC_IO_CALIBRATE

DBA_RSRC_IO_CALIBRATE displays I/O calibration results for the latest calibration run.

Column	Datatype	NULL	Description
START_TIME	TIMESTAMP (6)		Start time of the most recent I/O calibration
END_TIME	TIMESTAMP (6)		End time of the most recent I/O calibration
MAX_IOPS	NUMBER		Maximum number of data block read requests that can be sustained per second
MAX_MBPS	NUMBER		Maximum megabytes per second of maximum-sized read requests that can be sustained
MAX_PMBPS	NUMBER		Maximum megabytes per second of large I/O requests that can be sustained by a single process
LATENCY	NUMBER		Latency for data block read requests
NUM_PHYSICAL_DISKS	NUMBER		Number of physical disks in the storage subsystem (as specified by the user)

DBA_RSRC_MANAGER_SYSTEM_PRIVS

DBA_RSRC_MANAGER_SYSTEM_PRIVS displays information about all the users and roles that have been granted the ADMINISTER_RESOURCE_MANAGER system privilege, which is granted using the DBMS_RESOURCE_MANAGER_PRIVS package. This privilege is not granted through the GRANT SQL statement.

Related View

USER_RSRC_MANAGER_SYSTEM_PRIVS displays information about the users who are granted system privileges for the DBMS_RESOURCE_MANAGER package. This view does not display the GRANTEE column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	User or role receiving the grant
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Name of the system privilege
ADMIN_OPTION	VARCHAR2 (3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)

See Also:

- ["USER_RSRC_MANAGER_SYSTEM_PRIVS"](#) on page 6-94
- *Oracle Database PL/SQL Packages and Types Reference* for more information on consumer group privileges

DBA_RSRC_MAPPING_PRIORITY

DBA_RSRC_MAPPING_PRIORITY displays information about all consumer group mapping attribute priorities.

Column	Datatype	NULL	Description
ATTRIBUTE	VARCHAR2 (30)		Session attribute
PRIORITY	NUMBER		Priority (1 is the highest)
STATUS	VARCHAR2 (30)		Indicates whether the consumer group is part of the pending area (PENDING) or not (NULL)

DBA_RSRC_PLAN_DIRECTIVES

DBA_RSRC_PLAN_DIRECTIVES displays information about all resource plan directives in the database.

Column	Datatype	NULL	Description
PLAN	VARCHAR2 (30)		Name of the plan to which the directive belongs
GROUP_OR_SUBPLAN	VARCHAR2 (30)		Name of the consumer group or subplan referred to
TYPE	VARCHAR2 (14)		Indicates whether GROUP_OR_SUBPLAN refers to a consumer group (CONSUMER_GROUP) or a plan (PLAN)
CPU_P1	NUMBER		First parameter for the CPU resource allocation method
CPU_P2	NUMBER		Second parameter for the CPU resource allocation method
CPU_P3	NUMBER		Third parameter for the CPU resource allocation method
CPU_P4	NUMBER		Fourth parameter for the CPU resource allocation method
CPU_P5	NUMBER		Fifth parameter for the CPU resource allocation method
CPU_P6	NUMBER		Sixth parameter for the CPU resource allocation method
CPU_P7	NUMBER		Seventh parameter for the CPU resource allocation method
CPU_P8	NUMBER		Eighth parameter for the CPU resource allocation method
MGMT_P1	NUMBER		First parameter for the resource allocation method
MGMT_P2	NUMBER		Second parameter for the resource allocation method
MGMT_P3	NUMBER		Third parameter for the resource allocation method
MGMT_P4	NUMBER		Fourth parameter for the resource allocation method
MGMT_P5	NUMBER		Fifth parameter for the resource allocation method
MGMT_P6	NUMBER		Sixth parameter for the resource allocation method
MGMT_P7	NUMBER		Seventh parameter for the resource allocation method
MGMT_P8	NUMBER		Eighth parameter for the resource allocation method
ACTIVE_SESS_POOL_P1	NUMBER		First parameter for the active session pool resource allocation method
QUEUEING_P1	NUMBER		First parameter for the queueing resource allocation method
PARALLEL_TARGET_PERCENTAGE ¹	NUMBER		Maximum percentage of the target number of parallel servers that the consumer group can use
PARALLEL_DEGREE_LIMIT_P1	NUMBER		First parameter for the parallel degree limit resource allocation method
SWITCH_GROUP	VARCHAR2 (30)		Group to switch to once the switch time is reached
SWITCH_FOR_CALL	VARCHAR2 (5)		Indicates whether to switch back to the initial consumer group once the top call has completed (TRUE) or not (FALSE)
SWITCH_TIME	NUMBER		Amount of run time before the session is automatically switched
SWITCH_IO_MEGABYTES	NUMBER		Maximum megabytes of I/O within a group
SWITCH_IO_REQS	NUMBER		Maximum I/O requests within a group
SWITCH_ESTIMATE	VARCHAR2 (5)		Indicates whether estimated execution time should be used for switch criteria (TRUE) or not (FALSE)
MAX_EST_EXEC_TIME	NUMBER		Maximum estimated execution time
UNDO_POOL	NUMBER		Undo pool size for the consumer group

Column	Datatype	NULL	Description
MAX_IDLE_TIME	NUMBER		Maximum idle time for the session
MAX_IDLE_BLOCKER_TIME	NUMBER		Maximum idle time for the session when blocking other sessions
MAX_UTILIZATION_LIMIT	NUMBER		Maximum percentage of CPU that the consumer group or subplan can utilize
PARALLEL_QUEUE_TIMEOUT ¹	NUMBER		Time (in seconds) that a query may remain in the parallel statement queue for the consumer group before it is removed and terminated with error ORA-07454
SWITCH_TIME_IN_CALL	NUMBER		Call switch time limit for execution in a group
COMMENTS	VARCHAR2 (2000)		Text comment on the plan directive
STATUS	VARCHAR2 (30)		Indicates whether the plan directive is part of the pending area (PENDING) or not (NULL)
MANDATORY	VARCHAR2 (3)		Indicates whether the plan directive is mandatory (YES) or not (NO)

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also:

- *Oracle Database Administrator's Guide* for information on resource plans in general
- *Oracle Database PL/SQL Packages and Types Reference* for more information on creating resource plans with the DBMS_RESOURCE_MANAGER package

DBA_RSRC_PLANS

DBA_RSRC_PLANS displays information about all resource plans in the database. For a list of currently active plans, see "[V\\$RSRC_PLAN](#)" on page 8-99.

Column	Datatype	NULL	Description
PLAN_ID	NUMBER	NOT NULL	ID number of the resource plan
PLAN	VARCHAR2 (30)		Name of the resource plan
NUM_PLAN_DIRECTIVES	NUMBER		Number of plan directives for the plan
CPU_METHOD	VARCHAR2 (30)		CPU resource allocation method for the plan
MGMT_METHOD	VARCHAR2 (30)		Resource allocation method for the plan
ACTIVE_SESS_POOL_MTH	VARCHAR2 (30)		Active session pool resource allocation method for the plan
PARALLEL_DEGREE_LIMIT_MTH	VARCHAR2 (30)		Parallel degree limit resource allocation method for the plan
QUEUING_MTH	VARCHAR2 (30)		Queuing resource allocation method for the plan
SUB_PLAN	VARCHAR2 (3)		Indicates whether the plan is a subplan (YES) or not (NO)
COMMENTS	VARCHAR2 (2000)		Text comment on the plan
STATUS	VARCHAR2 (30)		Indicates whether the plan is part of the pending area (PENDING) or not (NULL)
MANDATORY	VARCHAR2 (3)		Indicates whether the plan is mandatory (YES) or not (NO)

See Also:

- *Oracle Database Administrator's Guide* for information on resource plans in general
- *Oracle Database PL/SQL Packages and Types Reference* for more information on creating resource plans with the DBMS_RESOURCE_MANAGER package

DBA_RULE_SET_RULES

DBA_RULE_SET_RULES describes the rules in all rule sets in the database. Its columns are the same as those in ALL_RULE_SET_RULES.

See Also: ["ALL_RULE_SET_RULES"](#) on page 3-24

DBA_RULE_SETS

DBA_RULE_SETS describes all rule sets in the database. Its columns are the same as those in ALL_RULE_SETS.

See Also: ["ALL_RULE_SETS"](#) on page 3-24

DBA_RULES

DBA_RULES describes all rules in the database. Its columns are the same as those in ALL_RULES.

See Also: ["ALL_RULES"](#) on page 3-25

DBA_SCHEDULER_CHAIN_RULES

DBA_SCHEDULER_CHAIN_RULES displays information about the rules for all chains in the database. Its columns are the same as those in ALL_SCHEDULER_CHAIN_RULES.

See Also: ["ALL_SCHEDULER_CHAIN_RULES"](#) on page 3-25

DBA_SCHEDULER_CHAIN_STEPS

DBA_SCHEDULER_CHAIN_STEPS displays information about the defined steps of all chains in the database. Its columns are the same as those in ALL_SCHEDULER_CHAIN_STEPS.

See Also: ["ALL_SCHEDULER_CHAIN_STEPS"](#) on page 3-26

DBA_SCHEDULER_CHAINS

DBA_SCHEDULER_CHAINS displays information about all chains in the database. Its columns are the same as those in ALL_SCHEDULER_CHAINS.

See Also: ["ALL_SCHEDULER_CHAINS"](#) on page 3-27

DBA_SCHEDULER_CREDENTIALS

DBA_SCHEDULER_CREDENTIALS displays information about all credentials in the database. Its columns are the same as those in ALL_SCHEDULER_CREDENTIALS.

See Also: ["ALL_SCHEDULER_CREDENTIALS"](#) on page 3-28

DBA_SCHEDULER_DB_DESTS

DBA_SCHEDULER_DB_DESTS displays information about all destination objects in the database pointing to remote databases. Its columns are the same as those in ALL_SCHEDULER_DB_DESTS.

See Also: ["ALL_SCHEDULER_DB_DESTS"](#) on page 3-28

DBA_SCHEDULER_DESTS

DBA_SCHEDULER_DESTS displays information about all destination objects for jobs in the database. Its columns are the same as those in ALL_SCHEDULER_DESTS.

See Also: ["ALL_SCHEDULER_DESTS"](#) on page 3-29

DBA_SCHEDULER_EXTERNAL_DESTS

DBA_SCHEDULER_EXTERNAL_DESTS displays information about all destination objects in the database pointing to remote agents. Its columns are the same as those in ALL_SCHEDULER_EXTERNAL_DESTS.

See Also: ["ALL_SCHEDULER_EXTERNAL_DESTS"](#) on page 3-29

DBA_SCHEDULER_FILE_WATCHERS

DBA_SCHEDULER_FILE_WATCHERS displays information about all scheduler file watch requests in the database. Its columns are the same as those in ALL_SCHEDULER_FILE_WATCHERS.

See Also: ["ALL_SCHEDULER_FILE_WATCHERS"](#) on page 3-30

DBA_SCHEDULER_GLOBAL_ATTRIBUTE

DBA_SCHEDULER_GLOBAL_ATTRIBUTE displays the values of all scheduler attributes in the database (for example, DEFAULT_TIMEZONE and CURRENT_OPEN_WINDOW). Its columns are the same as those in ALL_SCHEDULER_GLOBAL_ATTRIBUTE.

See Also: ["ALL_SCHEDULER_GLOBAL_ATTRIBUTE"](#) on page 3-31

DBA_SCHEDULER_GROUP_MEMBERS

DBA_SCHEDULER_GROUP_MEMBERS displays information about the members of all Scheduler object groups in the database. Its columns are the same as those in ALL_SCHEDULER_GROUP_MEMBERS.

See Also: ["ALL_SCHEDULER_GROUP_MEMBERS"](#) on page 3-31

DBA_SCHEDULER_GROUPS

DBA_SCHEDULER_GROUPS displays information about all Scheduler object groups in the database. Its columns are the same as those in ALL_SCHEDULER_GROUPS.

See Also: ["ALL_SCHEDULER_GROUPS"](#) on page 3-31

DBA_SCHEDULER_JOB_ARGS

DBA_SCHEDULER_JOB_ARGS displays information about the arguments of all Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_JOB_ARGS.

See Also: ["ALL_SCHEDULER_JOB_ARGS"](#) on page 3-32

DBA_SCHEDULER_JOB_CLASSES

DBA_SCHEDULER_JOB_CLASSES displays information about all Scheduler job classes in the database. Its columns are the same as those in ALL_SCHEDULER_JOB_CLASSES.

See Also: ["ALL_SCHEDULER_JOB_CLASSES"](#) on page 3-33

DBA_SCHEDULER_JOB_DESTS

DBA_SCHEDULER_JOB_DESTS displays information about the state of all jobs in the database at each of their destinations. Its columns are the same as those in ALL_SCHEDULER_JOB_DESTS.

See Also: ["ALL_SCHEDULER_JOB_DESTS"](#) on page 3-33

DBA_SCHEDULER_JOB_LOG

DBA_SCHEDULER_JOB_LOG displays log information for all Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_JOB_LOG.

See Also: ["ALL_SCHEDULER_JOB_LOG"](#) on page 3-34

DBA_SCHEDULER_JOB_ROLES

DBA_SCHEDULER_JOB_ROLES displays information about all Scheduler jobs in the database by database role.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the Scheduler job
JOB_NAME	VARCHAR2 (30)	NOT NULL	Name of the Scheduler job
JOB_SUBNAME	VARCHAR2 (30)		Subname of the Scheduler job (for a job running a chain step)
JOB_CREATOR	VARCHAR2 (30)		Creator of the Scheduler job
DATABASE_ROLE	VARCHAR2 (16)		Name of the database role
PROGRAM_OWNER	VARCHAR2 (4000)		Owner of the program associated with the job
PROGRAM_NAME	VARCHAR2 (4000)		Name of the program associated with the job
JOB_TYPE	VARCHAR2 (16)		Inline job action type: ▪ PLSQL_BLOCK ▪ STORED_PROCEDURE ▪ EXECUTABLE ▪ CHAIN
JOB_ACTION	VARCHAR2 (4000)		Inline job action
JOB_CLASS	VARCHAR2 (30)		Name of the job class associated with the job

Column	Datatype	NULL	Description
SCHEDULE_OWNER	VARCHAR2 (4000)		Owner of the schedule that the job uses (can be a window or a window group)
SCHEDULE_NAME	VARCHAR2 (4000)		Name of the schedule that the job uses (can be a window or a window group)
SCHEDULE_TYPE	VARCHAR2 (12)		Type of the schedule that the job uses: ■ IMMEDIATE - Start date and repeat interval are NULL ■ ONCE - Repeat interval is NULL ■ PLSQL - PL/SQL expression used as schedule ■ CALENDAR - Oracle calendaring expression used as schedule ■ EVENT - Event schedule ■ NAMED - Named schedule ■ WINDOW - Window used as schedule ■ WINDOW_GROUP - Window group used as schedule
START_DATE	TIMESTAMP (6) WITH TIME ZONE		Original scheduled start date of the job (for an inline schedule)
REPEAT_INTERVAL	VARCHAR2 (4000)		Inline schedule PL/SQL expression or calendar string
END_DATE	TIMESTAMP (6) WITH TIME ZONE		Date after which the job will no longer run (for an inline schedule)
LAST_START_DATE	TIMESTAMP (6) WITH TIME ZONE		Last date on which the job ran
ENABLED	VARCHAR2 (5)		Indicates whether the job is enabled (TRUE) or disabled (FALSE)
STATE	VARCHAR2 (15)		Current state of the job: ■ DISABLED ■ RETRY SCHEDULED ■ SCHEDULED ■ RUNNING ■ COMPLETED ■ BROKEN ■ FAILED ■ REMOTE ■ SUCCEEDED ■ CHAIN_STALLED
COMMENTS	VARCHAR2 (240)		Comments on the job

DBA_SCHEDULER_JOB_RUN_DETAILS

DBA_SCHEDULER_JOB_RUN_DETAILS displays log run details for all Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_JOB_RUN_DETAILS.

See Also: ["ALL_SCHEDULER_JOB_RUN_DETAILS"](#) on page 3-35

DBA_SCHEDULER_JOBS

DBA_SCHEDULER_JOBS displays information about all Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_JOBS.

See Also: ["ALL_SCHEDULER_JOBS"](#) on page 3-36

DBA_SCHEDULER_NOTIFICATIONS

DBA_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for all jobs in the database. Its columns are the same as those in ALL_SCHEDULER_NOTIFICATIONS.

See Also: ["ALL_SCHEDULER_NOTIFICATIONS"](#) on page 3-39

DBA_SCHEDULER_PROGRAM_ARGS

DBA_SCHEDULER_PROGRAM_ARGS displays information about the arguments of all Scheduler programs in the database. Its columns are the same as those in ALL_SCHEDULER_PROGRAM_ARGS.

See Also: ["ALL_SCHEDULER_PROGRAM_ARGS"](#) on page 3-40

DBA_SCHEDULER_PROGRAMS

DBA_SCHEDULER_PROGRAMS displays information about all Scheduler programs in the database. Its columns are the same as those in ALL_SCHEDULER_PROGRAMS.

See Also: ["ALL_SCHEDULER_PROGRAMS"](#) on page 3-41

DBA_SCHEDULER_REMOTE_DATABASES

DBA_SCHEDULER_REMOTE_DATABASES displays information about all remote databases that have been registered as sources and destinations for remote database jobs. Its columns are the same as those in ALL_SCHEDULER_REMOTE_DATABASES.

See Also: ["ALL_SCHEDULER_REMOTE_DATABASES"](#) on page 3-42

DBA_SCHEDULER_REMOTE_JOBSTATE

DBA_SCHEDULER_REMOTE_JOBSTATE displays information about the state of all jobs at remote databases. Its columns are the same as those in ALL_SCHEDULER_REMOTE_JOBSTATE.

See Also: ["ALL_SCHEDULER_REMOTE_JOBSTATE"](#) on page 3-42

DBA_SCHEDULER_RUNNING_CHAINS

DBA_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of all running chains in the database. Its columns are the same as those in ALL_SCHEDULER_RUNNING_CHAINS.

See Also: ["ALL_SCHEDULER_RUNNING_CHAINS"](#) on page 3-43

DBA_SCHEDULER_RUNNING_JOBS

DBA_SCHEDULER_RUNNING_JOBS displays information about all running Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_RUNNING_JOBS.

See Also: ["ALL_SCHEDULER_RUNNING_JOBS"](#) on page 3-44

DBA_SCHEDULER_SCHEDULES

DBA_SCHEDULER_SCHEDULES displays information about all Scheduler schedules in the database. Its columns are the same as those in ALL_SCHEDULER_SCHEDULES.

See Also: ["ALL_SCHEDULER_SCHEDULES"](#) on page 3-45

DBA_SCHEDULER_WINDOW_DETAILS

DBA_SCHEDULER_WINDOW_DETAILS displays log details for all Scheduler windows in the database. Its columns are the same as those in ALL_SCHEDULER_WINDOW_DETAILS.

See Also: ["ALL_SCHEDULER_WINDOW_DETAILS"](#) on page 3-46

DBA_SCHEDULER_WINDOW_GROUPS

DBA_SCHEDULER_WINDOW_GROUPS displays information about all Scheduler window groups in the database. Its columns are the same as those in ALL_SCHEDULER_WINDOW_GROUPS.

See Also: ["ALL_SCHEDULER_WINDOW_GROUPS"](#) on page 3-47

DBA_SCHEDULER_WINDOW_LOG

DBA_SCHEDULER_WINDOW_LOG displays log information for all Scheduler windows in the database. Its columns are the same as those in ALL_SCHEDULER_WINDOW_LOG.

See Also: ["ALL_SCHEDULER_WINDOW_LOG"](#) on page 3-47

DBA_SCHEDULER_WINDOWS

DBA_SCHEDULER_WINDOWS displays information about all Scheduler windows in the database. Its columns are the same as those in ALL_SCHEDULER_WINDOWS.

See Also: ["ALL_SCHEDULER_WINDOWS"](#) on page 3-48

DBA_SCHEDULER_WINGROUP_MEMBERS

DBA_SCHEDULER_WINGROUP_MEMBERS displays the members of all Scheduler window groups in the database. Its columns are the same as those in ALL_SCHEDULER_WINGROUP_MEMBERS.

See Also: ["ALL_SCHEDULER_WINGROUP_MEMBERS"](#) on page 3-49

DBA_SEC_RELEVANT_COLS

DBA_SEC_RELEVANT_COLS describes the security relevant columns of all security policies in the database. Its columns are the same as those in ALL_SEC_RELEVANT_COLS.

See Also: ["ALL_SEC_RELEVANT_COLS"](#) on page 3-49

DBA_SECONDARY_OBJECTS

DBA_SECONDARY_OBJECTS provides information about all secondary objects that are associated with domain indexes in the database. This view is only relevant in the context of domain indexes. Its columns are the same as those in "[ALL_SECONDARY_OBJECTS](#)" on page 3-49.

DBA_SEGMENTS

DBA_SEGMENTS describes the storage allocated for all segments in the database.

Related View

USER_SEGMENTS describes the storage allocated for the segments owned by the current user's objects. This view does not display the OWNER, HEADER_FILE, HEADER_BLOCK, or RELATIVE_FNO columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Username of the segment owner
SEGMENT_NAME	VARCHAR2 (81)		Name, if any, of the segment
PARTITION_NAME	VARCHAR2 (30)		Object Partition Name (Set to NULL for non-partitioned objects)
SEGMENT_TYPE	VARCHAR2 (18)		Type of segment: ■ NESTED TABLE ■ TABLE ■ TABLE PARTITION ■ CLUSTER ■ LOBINDEX ■ INDEX ■ INDEX PARTITION ■ LOBSEGMENT ■ TABLE SUBPARTITION ■ INDEX SUBPARTITION ■ LOB PARTITION ■ LOB SUBPARTITION ■ ROLLBACK ■ TYPE2 UNDO ■ DEFERRED ROLLBACK ■ TEMPORARY ■ CACHE ■ SPACE HEADER ■ UNDEFINED
SEGMENT_SUBTYPE	VARCHAR2 (10)		Subtype of LOB segment: SECUREFILE, ASSM, MSSM, and NULL
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the segment
HEADER_FILE	NUMBER		ID of the file containing the segment header
HEADER_BLOCK	NUMBER		ID of the block containing the segment header
BYTES	NUMBER		Size, in bytes, of the segment
BLOCKS	NUMBER		Size, in Oracle blocks, of the segment
EXTENTS	NUMBER		Number of extents allocated to the segment

Column	Datatype	NULL	Description
INITIAL_EXTENT	NUMBER		Size in bytes requested for the initial extent of the segment at create time. (Oracle rounds the extent size to multiples of 5 blocks if the requested size is greater than 5 blocks.)
NEXT_EXTENT	NUMBER		Size in bytes of the next extent to be allocated to the segment
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment
RETENTION	VARCHAR2 (7)		Retention option for SECUREFILE segment
MINRETENTION	NUMBER		Minimum retention duration for SECUREFILE segment
PCT_INCREASE	NUMBER		Percent by which to increase the size of the next extent to be allocated
FREELISTS	NUMBER		Number of process freelists allocated to this segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to this segment
RELATIVE_FNO	NUMBER		Relative file number of the segment header
BUFFER_POOL	VARCHAR2 (7)		Buffer pool to be used for segment blocks: ■ DEFAULT ■ KEEP ■ RECYCLE
FLASH_CACHE	VARCHAR2 (7)		Database Smart Flash Cache hint to be used for segment blocks: ■ DEFAULT ■ KEEP ■ NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2 (7)		Cell flash cache hint to be used for segment blocks: ■ DEFAULT ■ KEEP ■ NONE See Also: Oracle Exadata Storage Server Software documentation for more information

See Also: ["USER_SEGMENTS"](#) on page 6-98

DBA_SEGMENTS_OLD

DBA_SEGMENTS_OLD lists information about storage allocated for all database segments.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Username of the segment owner
SEGMENT_NAME	VARCHAR2 (81)		Name, if any, of the segment
PARTITION_NAME	VARCHAR2 (30)		Name of the partition
SEGMENT_TYPE	VARCHAR2 (18)		Type of segment: INDEX PARTITION, TABLE PARTITION, TABLE, CLUSTER, INDEX, ROLLBACK, DEFERRED ROLLBACK, TEMPORARY, CACHE, LOBSEGMENT and LOBINDEX
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the segment

Column	Datatype	NULL	Description
HEADER_FILE	NUMBER		ID of the file containing the segment header
HEADER_BLOCK	NUMBER		ID of the block containing the segment header
BYTES	NUMBER		Size, in bytes, of the segment
BLOCKS	NUMBER		Size, in Oracle blocks, of the segment
EXTENTS	NUMBER		Number of extents allocated to the segment
INITIAL_EXTENT	NUMBER		Size in bytes requested for the initial extent of the segment at create time. (Oracle rounds the extent size to multiples of 5 blocks if the requested size is greater than 5 blocks.)
NEXT_EXTENT	NUMBER		Size in bytes of the next extent to be allocated to the segment
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment
PCT_INCREASE	NUMBER		Percent by which to increase the size of the next extent to be allocated
FREELISTS	NUMBER		Number of process freelists allocated to the segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to this segment
RELATIVE_FNO	NUMBER		Relative file number of the segment header
BUFFER_POOL	VARCHAR2 (7)		Buffer pool for the object

DBA_SEQUENCES

DBA_SEQUENCES describes all sequences in the database. Its columns are the same as those in "[ALL_SEQUENCES](#)" on page 3-50.

DBA_SERVER_REGISTRY

DBA_SERVER_REGISTRY displays information about all server components in the database that are loaded into the component registry.

Column	Datatype	NULL	Description
COMP_ID	VARCHAR2 (30)	NOT NULL	Component identifier
COMP_NAME	VARCHAR2 (255)		Component name
VERSION	VARCHAR2 (30)		Component version loaded
STATUS	VARCHAR2 (11)		Component status: ■ INVALID ■ VALID ■ LOADING ■ LOADED ■ UPGRADING ■ UPGRADED ■ DOWNGRADING ■ DOWNGRADED ■ REMOVING ■ REMOVED
MODIFIED	VARCHAR2 (20)		Time when the component was last modified
CONTROL	VARCHAR2 (30)	NOT NULL	User that created the component entry
SCHEMA	VARCHAR2 (30)	NOT NULL	User that contains the objects for the component

Column	Datatype	NULL	Description
PROCEDURE	VARCHAR2 (61)		Validation procedure
STARTUP	VARCHAR2 (8)		Indicates whether the component requires a startup after the upgrade (REQUIRED) or not
PARENT_ID	VARCHAR2 (30)		Parent component identifier

DBA_SERVICES

DBA_SERVICES displays all services in the database. The view excludes rows marked for deletion. Its columns are the same as those in ALL_SERVICES.

DBA_SOURCE

DBA_SOURCE describes the text source of all stored objects in the database. Its columns are the same as those in ["ALL_SOURCE"](#) on page 3-51.

DBA_SOURCE_AE

DBA_SOURCE_AE describes the text source of all stored objects (across all editions) in the database. Its columns are the same as those in ALL_SOURCE_AE.

See Also: ["ALL_SOURCE_AE"](#) on page 3-52

DBA_SOURCE_TABLES

DBA_SOURCE_TABLES describes all source tables in the database for which a change table is defined. This view is intended for use by Change Data Capture publishers.

Related View

USER_SOURCE_TABLES describes the source tables owned by the current user for which a change table is defined.

Column	Datatype	NULL	Description
SOURCE_SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Table owner in the source database
SOURCE_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Table name in the source database

See Also: ["USER_SOURCE_TABLES"](#) on page 6-99

DBA_SQL_MANAGEMENT_CONFIG

DBA_SQL_MANAGEMENT_CONFIG displays the configuration parameters of the SQL management base. You must have the DBA role in order to change the configuration parameter values.

Column	Datatype	NULL	Description
PARAMETER_NAME	VARCHAR2 (30)	NOT NULL	Name of the configuration parameter: - SPACE_BUDGET_PERCENT - PLAN_RETENTION_WEEKS
PARAMETER_VALUE	NUMBER	NOT NULL	Value of the configuration parameter
LAST_MODIFIED	TIMESTAMP (6)		Time the parameter value was last updated

Column	Datatype	NULL	Description
MODIFIED_BY	VARCHAR2 (30)		User who last updated the parameter value

DBA_SQL_PATCHES

DBA_SQL_PATCHES displays the set of SQL patches.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)	NOT NULL	Name of the SQL patch
CATEGORY	VARCHAR2 (30)	NOT NULL	Category of the SQL patch
SIGNATURE	NUMBER	NOT NULL	Unique identifier generated from normalized SQL text
SQL_TEXT	CLOB	NOT NULL	Un-normalized SQL text
CREATED	TIMESTAMP (6)	NOT NULL	Timestamp when the SQL patch was created
LAST_MODIFIED	TIMESTAMP (6)		Timestamp when the SQL patch was last modified
DESCRIPTION	VARCHAR2 (500)		Text description provided for the SQL patch
STATUS	VARCHAR2 (8)		Status of the SQL patch: - ENABLED - DISABLED
FORCE_MATCHING	VARCHAR2 (3)		Indicates whether the signature is force matching (YES) or exact matching (NO)
TASK_ID	NUMBER		Advisor task ID that generated the SQL patch
TASK_EXEC_NAME	VARCHAR2 (30)		Advisor execution name for the SQL patch
TASK_OBJ_ID	NUMBER		Advisor object ID for the SQL patch
TASK_FND_ID	NUMBER		Advisor finding ID for the SQL patch
TASK_REC_ID	NUMBER		Advisor recommendation ID for the SQL patch

DBA_SQL_PLAN_BASELINES

DBA_SQL_PLAN_BASELINES displays information about the SQL plan baselines currently created for specific SQL statements.

Column	Datatype	NULL	Description
SIGNATURE	NUMBER	NOT NULL	Unique SQL identifier generated from normalized SQL text
SQL_HANDLE	VARCHAR2 (30)	NOT NULL	Unique SQL identifier in string form as a search key
SQL_TEXT	CLOB	NOT NULL	Un-normalized SQL text
PLAN_NAME	VARCHAR2 (30)	NOT NULL	Unique plan identifier in string form as a search key
CREATOR	VARCHAR2 (30)		User who created the plan baseline
ORIGIN	VARCHAR2 (14)		How the plan baseline was created: - MANUAL-LOAD - AUTO-CAPTURE - MANUAL-SQLTUNE - AUTO-SQLTUNE
PARSING_SCHEMA_NAME	VARCHAR2 (30)		Name of the parsing schema
DESCRIPTION	VARCHAR2 (500)		Text description provided for the plan baseline
VERSION	VARCHAR2 (64)		Database version at the time of plan baseline creation
CREATED	TIMESTAMP (6)	NOT NULL	Timestamp when the plan baseline was created

Column	Datatype	NULL	Description
LAST_MODIFIED	TIMESTAMP (6)		Timestamp when the plan baseline was last modified
LAST_EXECUTED	TIMESTAMP (6)		Timestamp when the plan baseline was last executed
LAST_VERIFIED	TIMESTAMP (6)		Timestamp when the plan baseline was last verified
ENABLED	VARCHAR2 (3)		Indicates whether the plan baseline is enabled (YES) or disabled (NO)
ACCEPTED	VARCHAR2 (3)		Indicates whether the plan baseline is accepted (YES) or not (NO)
FIXED	VARCHAR2 (3)		Indicates whether the plan baseline is fixed (YES) or not (NO)
REPRODUCED ¹	VARCHAR2 (3)		Indicates whether the optimizer was able to reproduce the plan (YES) or not (NO). The value of this column is set to YES when a plan is initially added to the plan baseline.
AUTOPURGE	VARCHAR2 (3)		Indicates whether the plan baseline is auto-purged (YES) or not (NO)
OPTIMIZER_COST	NUMBER		Optimizer cost at the time the plan baseline was created
MODULE ²	VARCHAR2 (48)		Application module name
ACTION ²	VARCHAR2 (32)		Application action
EXECUTIONS	NUMBER		Number of executions at the time the plan baseline was created
ELAPSED_TIME	NUMBER		Total elapsed time at the time the plan baseline was created
CPU_TIME	NUMBER		Total CPU time at the time the plan baseline was created
BUFFER_GETS	NUMBER		Total buffer gets at the time the plan baseline was created
DISK_READS	NUMBER		Total disk reads at the time the plan baseline was created
DIRECT_WRITES	NUMBER		Total direct writes at the time the plan baseline was created
ROWS_PROCESSED	NUMBER		Total rows processed at the time the plan baseline was created
FETCHES	NUMBER		Total number of fetches at the time the plan baseline was created
END_OF_FETCH_COUNT	NUMBER		Total number of full fetches at the time the plan baseline was created

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

² The datatype of this column is VARCHAR2 (64) starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also:

- The SQL Plan Management chapter in *Oracle Database Performance Tuning Guide*
- The DBMS_SQLTUNE package in *Oracle Database PL/SQL Packages and Types Reference*

DBA_SQL_PROFILES

DBA_SQL_PROFILES displays information about SQL profiles currently created for specific SQL statements.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)	NOT NULL	Name of the SQL profile
CATEGORY	VARCHAR2 (30)	NOT NULL	Category of the SQL profile
SIGNATURE	NUMBER	NOT NULL	Unique identifier generated from normalized SQL text
SQL_TEXT	CLOB	NOT NULL	Un-normalized SQL text
CREATED	DATE	NOT NULL	Timestamp when the SQL profile was created
LAST_MODIFIED	DATE	NOT NULL	Timestamp when the SQL profile was last modified
DESCRIPTION	VARCHAR2 (500)		Text description provided for the SQL profile
TYPE	VARCHAR2 (9)		Type of the SQL profile (how it was created): - MANUAL - AUTO
STATUS	VARCHAR2 (8)		Status of the SQL profile: - ENABLED - DISABLED - VOID
FORCE_MATCHING	VARCHAR2 (3)		If YES, this causes SQL Profiles to target all SQL statements which have the same text after normalizing all literal values to bind variables. If a combination of literal values and bind variables is used in the same SQL text, then no transformation occurs. This is analogous to the matching algorithm use by the FORCE option of the CURSOR_SHARING parameter. If NO, literals are not transformed. This is analogous to the matching algorithm used by the EXACT option of the CURSOR_SHARING parameter.
TASK_ID	NUMBER		Advisor task ID that generated the SQL profile
EXECUTION_NAME	VARCHAR2 (30)		Advisor execution name for the SQL profile
OBJECT_ID	NUMBER		Advisor object ID for the SQL profile
FINDING_ID	NUMBER		Advisor finding ID for the SQL profile
REC_ID	NUMBER		Advisor recommendation ID for the SQL profile

See Also: The DBMS_SQLTUNE package in *Oracle Database PL/SQL Packages and Types Reference*

DBA_SQLJ_TYPE_ATTRS

DBA_SQLJ_TYPE_ATTRS describes the attributes of all SQLJ object types in the database. Its columns are the same as those in ALL_SQLJ_TYPE_ATTRS.

See Also: ["ALL_SQLJ_TYPE_ATTRS"](#) on page 3-52

DBA_SQLJ_TYPE_METHODS

DBA_SQLJ_TYPE_METHODS describes the methods of all SQLJ object types in the database. Its columns are the same as those in ALL_SQLJ_TYPE_METHODS.

See Also: ["ALL_SQLJ_TYPE_METHODS"](#) on page 3-53

DBA_SQLJ_TYPES

DBA_SQLJ_TYPES describes all SQLJ object types in the database. Its columns are the same as those in ALL_SQLJ_TYPES.

See Also: ["ALL_SQLJ_TYPES"](#) on page 3-54

DBA_SQLSET

DBA_SQLSET displays information about all SQL tuning sets in the database. Its columns are the same as those in ["ALL_SQLSET"](#) on page 3-55.

DBA_SQLSET_BINDS

DBA_SQLSET_BINDS displays the bind values associated with all SQL tuning sets in the database. Its columns are the same as those in ["ALL_SQLSET_BINDS"](#) on page 3-55.

DBA_SQLSET_PLANS

DBA_SQLSET_PLANS describes captured plans in the SQL tuning sets in the database. Its columns are the same as those in ["ALL_SQLSET_PLANS"](#) on page 3-56.

DBA_SQLSET_REFERENCES

DBA_SQLSET_REFERENCES describes whether or not all SQL tuning sets in the database are active. A SQL tuning set cannot be dropped if it is referenced. Its columns are the same as those in ["ALL_SQLSET_REFERENCES"](#) on page 3-59.

DBA_SQLSET_STATEMENTS

DBA_SQLSET_STATEMENTS displays information about the SQL statements, along with their statistics, that form all SQL tuning sets in the database. Its columns are the same as those in ["ALL_SQLSET_STATEMENTS"](#) on page 3-60.

DBA_SQLTUNE_BINDS

DBA_SQLTUNE_BINDS displays the bind values associated with all tuned SQL statements in the database.

Related View

USER_SQLTUNE_BINDS displays the bind values associated with the tuned SQL statements owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER (38)	NOT NULL	Tuning task identifier
OBJECT_ID	NUMBER (38)	NOT NULL	Advisor framework object identifier
POSITION	NUMBER (38)	NOT NULL	Bind position
VALUE	ANYDATA		Bind value

See Also: ["USER_SQLTUNE_BINDS"](#) on page 6-100

DBA_SQLTUNE_PLANS

DBA_SQLTUNE_PLANS displays information about the execution plans generated for all SQL statements in the database during a SQL tuning session.

Related View

USER_SQLTUNE_PLANS displays information about the execution plans generated for the SQL statements owned by the current user during a SQL tuning session.

Column	Datatype	NULL	Description
TASK_ID	NUMBER (38)	NOT NULL	Advisor task ID
EXECUTION_NAME	VARCHAR2 (30)	NOT NULL	Advisor task execution
OBJECT_ID	NUMBER (38)	NOT NULL	Advisor object ID
ATTRIBUTE	VARCHAR2 (27)		Text string identifying the type of the execution plan: - Original - Original plan of the query - Original with adjusted cost - Same as Original but with adjusted cost - Using SQL profile - Plan with SQL profile applied - Using new indices - Plan with indexes applied
STATEMENT_ID	VARCHAR2 (30)		Optional statement identifier specified in the EXPLAIN PLAN statement
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the execution plan
PLAN_ID	NUMBER		Plan identifier
TIMESTAMP	DATE		Date and time when the EXPLAIN PLAN statement was issued
REMARKS	VARCHAR2 (4000)		Place for comments that can be added to the steps of the execution plan
OPERATION	VARCHAR2 (30)		Name of the operation performed at this step
OPTIONS	VARCHAR2 (255)		Options used for the operation performed at this step
OBJECT_NODE	VARCHAR2 (128)		Name of the database link used to reference the object
OBJECT_OWNER	VARCHAR2 (30)		Owner of the object
OBJECT_NAME	VARCHAR2 (30)		Name of the object
OBJECT_ALIAS	VARCHAR2 (65)		Object alias
OBJECT_INSTANCE	NUMBER (38)		Numbered position of the object name in the original SQL statement
OBJECT_TYPE	VARCHAR2 (30)		Descriptive modifier that further describes the type of object
OPTIMIZER	VARCHAR2 (255)		Current mode of the optimizer
SEARCH_COLUMNS	NUMBER		Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
ID	NUMBER (38)	NOT NULL	Identification number for this step in the execution plan
PARENT_ID	NUMBER (38)		ID of the next step that operates on the results of this step
DEPTH	NUMBER (38)		Depth
POSITION	NUMBER (38)		Order of processing for steps with the same parent ID
COST	NUMBER (38)		Cost of the current operation estimated by the cost-based optimizer (CBO)
CARDINALITY	NUMBER (38)		Number of rows returned by the current operation (estimated by the CBO)
BYTES	NUMBER (38)		Number of bytes returned by the current operation

Column	Datatype	NULL	Description
OTHER_TAG	VARCHAR2 (255)		Describes the function of the SQL text in the OTHER column. Values for OTHER_TAG are: - SERIAL - SQL is the text of a locally-executed, serial query plan. Currently, SQL is not loaded in OTHER for this case. - SERIAL_FROM_REMOTE - SQL text shown in the OTHER column will be executed at a remote site - PARALLEL_COMBINED_WITH_PARENT - Parent of this operation is a DFO that performs both operations in the parallel execution plan - PARALLEL_COMBINED_WITH_CHILD - Child of this operation is a DFO that performs both operations in the parallel execution plan. - PARALLEL_TO_SERIAL - SQL text shown in the OTHER column is the top-level of the parallel plan. - PARALLEL_TO_PARALLEL - SQL text shown in the OTHER column is executed and output in parallel - PARALLEL_FROM_SERIAL - Operation consumes data from a serial operation and outputs it in parallel
PARTITION_START	VARCHAR2 (255)		Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2 (255)		Stop partition of a range of accessed partitions
PARTITION_ID	NUMBER (38)		Step that has computed the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	LONG		Information about parallel execution servers and parallel queries
DISTRIBUTION	VARCHAR2 (30)		Distribution method
CPU_COST	NUMBER (38)		User-defined CPU cost
IO_COST	NUMBER (38)		User-defined I/O cost
TEMP_SPACE	NUMBER (38)		Temporary space usage of the operation (sort or hash-join) as estimated by the CBO
ACCESS_PREDICATES	VARCHAR2 (4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2 (4000)		Predicates used to filter rows before producing them
PROJECTION	VARCHAR2 (4000)		Expressions produced by the operation
TIME	NUMBER (38)		Elapsed time (in seconds) of the operation as estimated by the CBO
QBLOCK_NAME	VARCHAR2 (30)		Name of the query block
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML because it allows multiple pieces of information to be stored, including the following: - Name of the schema against which the query was parsed - Release number of the Oracle Database that produced the explain plan - Hash value associated with the execution plan - Name (if any) of the outline or the SQL profile used to build the execution plan - Indication of whether or not dynamic sampling was used to produce the plan - The outline data, a set of optimizer hints that can be used to regenerate the same plan

See Also: ["USER_SQLTUNE_PLANS"](#) on page 6-100

DBA_SQLTUNE_RATIONALE_PLAN

DBA_SQLTUNE_RATIONALE_PLAN displays the association between rationales and operations in the execution plan of all SQL statements in the database.

Related View

USER_SQLTUNE_RATIONALE_PLAN displays the association between rationales and operations in the execution plan of the SQL statements owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER (38)	NOT NULL	Tuning task identifier
EXECUTION_NAME	VARCHAR2 (30)	NOT NULL	The name of the task execution with which this entry (row) is associated
RATIONALE_ID	NUMBER (38)	NOT NULL	Rationale identifier
OBJECT_ID	NUMBER (38)	NOT NULL	Advisor framework object identifier
OPERATION_ID	NUMBER (38)	NOT NULL	Operation identifier
PLAN_ATTRIBUTE	VARCHAR2 (27)		Type of the execution plan: - Original - Original plan of the query - Original with adjusted cost - Same as Original but with adjusted cost - Using SQL profile - Plan with SQL profile applied - Using new indices - Plan with indexes applied

See Also: ["USER_SQLTUNE_RATIONALE_PLAN"](#) on page 6-100

DBA_SQLTUNE_STATISTICS

DBA_SQLTUNE_STATISTICS displays statistics associated with all SQL statements in the database.

Related View

USER_SQLTUNE_STATISTICS displays statistics associated with the SQL statements owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER (38)	NOT NULL	Tuning task identifier
OBJECT_ID	NUMBER (38)	NOT NULL	Advisor framework object identifier
PARSING_SCHEMA_ID	NUMBER		Schema under which the SQL is parsed
MODULE ¹	VARCHAR2 (48)		Last application module recorded for the SQL
ACTION ¹	VARCHAR2 (32)		Last application action recorded for the SQL
ELAPSED_TIME	NUMBER		Elapsed time for the SQL statement
CPU_TIME	NUMBER		CPU time for the SQL
BUFFER_GETS	NUMBER		Number of buffer gets
DISK_READS	NUMBER		Number of disk reads
DIRECT_WRITES	NUMBER		Number of disk writes
ROWS_PROCESSED	NUMBER		Number of rows processed by the SQL
FETCHES	NUMBER		Number of fetches
EXECUTIONS	NUMBER		Number of executions

Column	Datatype	NULL	Description
END_OF_FETCH_COUNT	NUMBER		End of fetch count
OPTIMIZER_COST	NUMBER		Optimizer cost for the SQL
OPTIMIZER_ENV	RAW(1000)		Optimizer environment
COMMAND_TYPE	NUMBER		Command type

¹ The datatype of this column is VARCHAR2 (64) starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also: ["USER_SQLTUNE_STATISTICS"](#) on page 6-100

DBA_SSCR_CAPTURE

DBA_SSCR_CAPTURE displays session state capture statistics.

Column	Datatype	NULL	Description
DB_NAME	VARCHAR2(4000)		Database name of captured session
INST_NAME	VARCHAR2(4000)		Instance name of captured session
INST_ID	VARCHAR2(4000)		Instance ID of captured session
SESSION_ID	NUMBER		Session ID of captured session
SESSION_SERIAL#	NUMBER		Session serial number of captured session
USER_NAME	VARCHAR2(30)	NOT NULL	User name of captured session
SCHEMA_NAME	VARCHAR2(30)	NOT NULL	Schema name of captured session
SEQUENCE#	NUMBER		Sequence number of captured session
CAPTURE_MODE	VARCHAR2(7)		Mode of capture operation
CAPTURE_SCOPE	VARCHAR2(7)		Scope of capture operation
CAPTURE_FORMAT	VARCHAR2(9)		Format of capture files
CAPTURE_DIR	VARCHAR2(30)		Directory object of capture files
CAPTURE_LOCATOR	RAW(64)		Locator of master capture file
CAPTURE_TIME	TIMESTAMP(6)		Timestamp of capture operation

DBA_SSCR_RESTORE

DBA_SSCR_RESTORE displays session state restore statistics.

Column	Datatype	NULL	Description
DB_NAME	VARCHAR2(4000)		Database name of restored session
INST_NAME	VARCHAR2(4000)		Instance name of restored session
INST_ID	VARCHAR2(4000)		Instance ID of restored session
SESSION_ID	NUMBER		Session ID of restored session
SESSION_SERIAL#	NUMBER		Session serial number of restored session
USER_NAME	VARCHAR2(30)	NOT NULL	User name of restored session
SCHEMA_NAME	VARCHAR2(30)	NOT NULL	Schema name of restored session
SEQUENCE#	NUMBER		Sequence number of restore operation
RESTORE_MODE	VARCHAR2(7)		Mode of restore operation
RESTORE_SCOPE	VARCHAR2(7)		Scope of restore operation
RESTORE_FORMAT	VARCHAR2(9)		Format of restore files

Column	Datatype	NULL	Description
RESTORE_DIR	VARCHAR2 (30)		Directory object of restore files
RESTORE_LOCATOR	RAW (64)		Locator of master restore file
RESTORE_TIME	TIMESTAMP (6)		Timestamp of restore operation

DBA_STAT_EXTENSIONS

DBA_STAT_EXTENSIONS displays information about all optimizer statistics extensions in the database.

See Also: ["ALL_STAT_EXTENSIONS"](#) on page 3-61

DBA_STMT_AUDIT_OPTS

DBA_STMT_AUDIT_OPTS describes current system auditing options across the system and by user.

Column	Datatype	NULL	Description
USER_NAME	VARCHAR2 (30)		User name if by user auditing; ANY CLIENT if access by a proxy on behalf of a client is being audited; NULL for system-wide auditing
PROXY_NAME	VARCHAR2 (30)		Name of the proxy user which is performing an operation for the client; NULL if the client is performing the operation directly
AUDIT_OPTION	VARCHAR2 (40)	NOT NULL	Name of the system auditing option
SUCCESS	VARCHAR2 (10)		Mode for WHENEVER SUCCESSFUL system auditing
FAILURE	VARCHAR2 (10)		Mode for WHENEVER NOT SUCCESSFUL system auditing

DBA_STORED_SETTINGS

DBA_STORED_SETTINGS lists information about the persistent parameter settings for stored PL/SQL units for which the current user has execute privileges. It also returns parameter information for all objects in the database and is accessible only to users with the SELECT_CATALOG_ROLE privilege. Its columns are the same as those in ["ALL_STORED_SETTINGS"](#) on page 3-62.

Static Data Dictionary Views: DBA_STREAMS_ADD_COLUMN to XS_SESSION_ROLES

This chapter contains the static data dictionary views DBA_STREAMS_ADD_COLUMN through XS_SESSION_ROLES.

DBA_STREAMS_ADD_COLUMN

DBA_STREAMS_ADD_COLUMN displays information about declarative rule-based transformations that add a column to a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)		Owner of the rule
RULE_NAME	VARCHAR2 (30)		Name of the rule
SCHEMA_NAME	VARCHAR2 (30)		Schema of the column to be added
TABLE_NAME	VARCHAR2 (30)		Table of the column to be added
COLUMN_NAME	VARCHAR2 (4000)		Name of the column to be added
COLUMN_VALUE	ANYDATA		Value of the column to be added
COLUMN_TYPE	VARCHAR2 (4000)		Type of the column to be added
COLUMN_FUNCTION	VARCHAR2 (30)		Name of the default function used to add a column
VALUE_TYPE	VARCHAR2 (3)		Indicates whether to modify the old (OLD), new (NEW), or both (*) values of the LCR
PRECEDENCE	NUMBER		3 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

DBA_STREAMS_ADMINISTRATOR

DBA_STREAMS_ADMINISTRATOR displays information about the users who have been granted privileges to be a Streams administrator by procedures in the DBMS_STREAMS_AUTH package.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (30)	NOT NULL	Name of the user who has been granted privileges to be a Streams administrator
LOCAL_PRIVILEGES	VARCHAR2 (3)		Indicates whether the user has been granted local Streams administrator privileges (YES) or not (NO)

Column	Datatype	NULL	Description
ACCESS_FROM_REMOTE	VARCHAR2 (3)		Indicates whether the user can be used for remote Streams administration through a database link (YES) or not (NO)

DBA_STREAMS_COLUMNS

DBA_STREAMS_COLUMNS displays information about all Streams unsupported columns in the database. Its columns are the same as those in ALL_STREAMS_COLUMNS.

See Also: ["ALL_STREAMS_COLUMNS"](#) on page 3-62

DBA_STREAMS_DELETE_COLUMN

DBA_STREAMS_DELETE_COLUMN displays information about declarative rule-based transformations that delete a column from a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)		Owner of the rule
RULE_NAME	VARCHAR2 (30)		Name of the rule
SCHEMA_NAME	VARCHAR2 (30)		Schema of the column to be deleted
TABLE_NAME	VARCHAR2 (30)		Table of the column to be deleted
COLUMN_NAME	VARCHAR2 (4000)		Name of the column to delete
VALUE_TYPE	VARCHAR2 (3)		Indicates whether to modify the old (OLD), new (NEW), or both (*) values of the LCR
PRECEDENCE	NUMBER		1 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

DBA_STREAMS_GLOBAL_RULES

DBA_STREAMS_GLOBAL_RULES displays information about the global rules created for all Streams capture processes, propagations, and apply processes in the database. Its columns are the same as those in ALL_STREAMS_GLOBAL_RULES.

See Also: ["ALL_STREAMS_GLOBAL_RULES"](#) on page 3-63

DBA_STREAMS_KEEP_COLUMNS

DBA_STREAMS_KEEP_COLUMNS displays information about declarative rule-based transformations that keep a list of columns in a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)		Owner of the rule which has an associated transformation
RULE_NAME	VARCHAR2 (30)		Name of the rule which has an associated transformation
SCHEMA_NAME	VARCHAR2 (30)		Schema of the column to be kept
TABLE_NAME	VARCHAR2 (30)		Table of the column to be kept
COLUMN_NAME	VARCHAR2 (4000)		Column to keep

Column	Datatype	NULL	Description
VALUE_TYPE	VARCHAR2 (3)		Indicates whether to keep the old (OLD), new (NEW), or both (*) value of the LCR
PRECEDENCE	NUMBER		0 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

DBA_STREAMS_MESSAGE_CONSUMERS

DBA_STREAMS_MESSAGE_CONSUMERS displays information about all Streams messaging clients in the database. Its columns are the same as those in ALL_STREAMS_MESSAGE_CONSUMERS.

See Also: ["ALL_STREAMS_MESSAGE_CONSUMERS"](#) on page 3-64

DBA_STREAMS_MESSAGE_RULES

DBA_STREAMS_MESSAGE_RULES displays information about all Streams messaging rules in the database. Its columns are the same as those in ALL_STREAMS_MESSAGE_RULES.

See Also: ["ALL_STREAMS_MESSAGE_RULES"](#) on page 3-64

DBA_STREAMS_NEWLY_SUPPORTED

DBA_STREAMS_NEWLY_SUPPORTED displays information about all tables in the database that are newly supported by Streams capture processes. Its columns are the same as those in ALL_STREAMS_NEWLY_SUPPORTED.

See Also: ["ALL_STREAMS_NEWLY_SUPPORTED"](#) on page 3-65

DBA_STREAMS_RENAME_COLUMN

DBA_STREAMS_RENAME_COLUMN displays information about declarative rule-based transformations that rename a column in a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)		Owner of the rule
RULE_NAME	VARCHAR2 (30)		Name of the rule
SCHEMA_NAME	VARCHAR2 (30)		Schema of the column to be renamed
TABLE_NAME	VARCHAR2 (30)		Table of the column to be renamed
FROM_COLUMN_NAME	VARCHAR2 (4000)		Column to rename
TO_COLUMN_NAME	VARCHAR2 (4000)		New column name
VALUE_TYPE	VARCHAR2 (3)		Indicates whether to modify the old (OLD), new (NEW), or both (*) values of the LCR
PRECEDENCE	NUMBER		2 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

DBA_STREAMS_RENAME_SCHEMA

DBA_STREAMS_RENAME_SCHEMA displays information about declarative rule-based transformations that rename a schema in a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)		Owner of the rule
RULE_NAME	VARCHAR2 (30)		Name of the rule
FROM_SCHEMA_NAME	VARCHAR2 (30)		Schema to be renamed
TO_SCHEMA_NAME	VARCHAR2 (30)		New schema name
PRECEDENCE	NUMBER		5 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

DBA_STREAMS_RENAME_TABLE

DBA_STREAMS_RENAME_TABLE displays information about declarative rule-based transformations that rename a table in a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)		Owner of the rule
RULE_NAME	VARCHAR2 (30)		Name of the rule
FROM_SCHEMA_NAME	VARCHAR2 (30)		Schema to be renamed
TO_SCHEMA_NAME	VARCHAR2 (30)		New schema name
FROM_TABLE_NAME	VARCHAR2 (30)		Table to be renamed
TO_TABLE_NAME	VARCHAR2 (30)		New table name
PRECEDENCE	NUMBER		4 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

DBA_STREAMS_RULES

DBA_STREAMS_RULES displays information about the rules used by all Streams processes in the database. Its columns are the same as those in ALL_STREAMS_RULES.

See Also: ["ALL_STREAMS_RULES"](#) on page 3-65

DBA_STREAMS_SCHEMA_RULES

DBA_STREAMS_SCHEMA_RULES displays information about the schema rules created for all Streams capture processes, propagations, and apply processes in the database. Its columns are the same as those in ALL_STREAMS_SCHEMA_RULES.

See Also: ["ALL_STREAMS_SCHEMA_RULES"](#) on page 3-67

DBA_STREAMS_SPLIT_MERGE

DBA_STREAMS_SPLIT_MERGE displays information about current automatic split and merge operations.

Column	Datatype	NULL	Description
ORIGINAL_CAPTURE_NAME	VARCHAR2 (30)	NOT NULL	Name of the original capture process
CLONED_CAPTURE_NAME	VARCHAR2 (30)		Name of the cloned capture process
ORIGINAL_CAPTURE_STATUS	VARCHAR2 (8)		Status of the original capture process: ■ DISABLED ■ ENABLED ■ ABORTED
CLONED_CAPTURE_STATUS	VARCHAR2 (8)		Status of the cloned capture process: ■ DISABLED ■ ENABLED ■ ABORTED
ORIGINAL_STREAMS_NAME	VARCHAR2 (30)		Name of the original Oracle Streams component that receives database changes directly from the original capture process. The component is either a propagation or a local apply process.
CLONED_STREAMS_NAME	VARCHAR2 (30)		Name of the cloned Oracle Streams component that receives database changes directly from the cloned capture process. The component is either a propagation or a local apply process.
STREAMS_TYPE	VARCHAR2 (11)		Type of the component in ORIGINAL_STREAMS_NAME and CLONED_STREAMS_NAME: ■ PROPAGATION ■ APPLY
RECOVERABLE_SCRIPT_ID	RAW (16)		Unique ID of the operation
SCRIPT_STATUS	VARCHAR2 (12)		State of the recoverable script: ■ GENERATING ■ NOT EXECUTED ■ EXECUTING ■ EXECUTED ■ ERROR
ACTION_TYPE	VARCHAR2 (7)		Type of action performed by the script: ■ SPLIT ■ MERGE ■ MONITOR
ACTION_THRESHOLD	VARCHAR2 (40)		For SPLIT actions, the threshold set by the split_threshold capture process parameter. For MERGE actions, the threshold set by the merge_threshold capture process parameter.

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (16)		Status of the action: ■ NOTHING TO SPLIT - Not ready to split or does not need to split ■ ABOUT TO SPLIT ■ SPLITTING - A split is in process ■ SPLIT DONE - A split is done ■ NOTHING TO MERGE - Not ready to merge ■ ABOUT TO MERGE ■ MERGING - A merge is in process ■ MERGE DONE - A merge is done ■ ERROR - An error was returned during a split or merge ■ NONSPLITTABLE - The original capture is not splittable either because it is disabled, it has more than one publisher to its queue, or it has only one destination for captured messages
STATUS_UPDATE_TIME	TIMESTAMP (6)		Time when status was last updated
CREATION_TIME	TIMESTAMP (6)		Time when the action started
LAG	NUMBER		Time (in seconds) that the cloned capture process lags behind the original capture process
JOB_OWNER	VARCHAR2 (30)		Owner of the job that performs the split or merge operation
JOB_NAME	VARCHAR2 (30)		Name of the job that performs the split or merge operation
JOB_STATE	VARCHAR2 (15)		Current state of the job: ■ DISABLED ■ RETRY SCHEDULED ■ SCHEDULED ■ RUNNING ■ COMPLETED ■ BROKEN ■ FAILED ■ REMOTE ■ SUCCEEDED ■ CHAIN_STALLED
JOB_NEXT_RUN_DATE	VARCHAR2 (64)		Next time the job will run
ERROR_NUMBER	NUMBER		Error number if the capture process was aborted
ERROR_MESSAGE	VARCHAR2 (4000)		Error message if the capture process was aborted

DBA_STREAMS_SPLIT_MERGE_HIST

DBA_STREAMS_SPLIT_MERGE_HIST displays information about past automatic split and merge operations.

Column	Datatype	NULL	Description
ORIGINAL_CAPTURE_NAME	VARCHAR2 (30)	NOT NULL	Name of the original capture process
CLONED_CAPTURE_NAME	VARCHAR2 (30)		Name of the cloned capture process
ORIGINAL_QUEUE_OWNER	VARCHAR2 (30)		Owner of the queue used by the original capture process
ORIGINAL_QUEUE_NAME	VARCHAR2 (30)		Name of the queue used by the original capture process
CLONED_QUEUE_OWNER	VARCHAR2 (30)		Owner of the queue used by the cloned capture process

Column	Datatype	NULL	Description
CLONED_QUEUE_NAME	VARCHAR2 (30)		Name of the queue used by the cloned capture process
ORIGINAL_CAPTURE_STATUS	VARCHAR2 (8)		Status of the original capture process: - DISABLED - ENABLED - ABORTED
CLONED_CAPTURE_STATUS	VARCHAR2 (8)		Status of the cloned capture process: - DISABLED - ENABLED - ABORTED
ORIGINAL_STREAMS_NAME	VARCHAR2 (30)		Name of the original Oracle Streams component that receives database changes directly from the original capture process. The component is either a propagation or a local apply process.
CLONED_STREAMS_NAME	VARCHAR2 (30)		Name of the cloned Oracle Streams component that receives database changes directly from the cloned capture process. The component is either a propagation or a local apply process.
STREAMS_TYPE	VARCHAR2 (11)		Type of the component in ORIGINAL_STREAMS_NAME and CLONED_STREAMS_NAME: - PROPAGATION - APPLY
RECOVERABLE_SCRIPT_ID	RAW (16)		Unique ID of the operation
SCRIPT_STATUS	VARCHAR2 (12)		State of the recoverable script: - GENERATING - NOT EXECUTED - EXECUTING - EXECUTED - ERROR
ACTION_TYPE	VARCHAR2 (7)		Type of action performed by the script: - SPLIT - MERGE - MONITOR
ACTION_THRESHOLD	VARCHAR2 (40)		For SPLIT actions, the threshold set by the split_threshold capture process parameter. For MERGE actions, the threshold set by the merge_threshold capture process parameter.
STATUS	VARCHAR2 (16)		Status of the action: - NOTHING TO SPLIT - Not ready to split or does not need to split - ABOUT TO SPLIT - SPLITTING - A split is in process - SPLIT DONE - A split is done - NOTHING TO MERGE - Not ready to merge - ABOUT TO MERGE - MERGING - A merge is in process - MERGE DONE - A merge is done - ERROR - An error was returned during a split or merge - NONSPLITTABLE - The original capture is not splittable either because it is disabled, it has more than one publisher to its queue, or it has only one destination for captured messages

Column	Datatype	NULL	Description
STATUS_UPDATE_TIME	TIMESTAMP (6)		Time when status was last updated
CREATION_TIME	TIMESTAMP (6)		Time when the action started
LAG	NUMBER		Time (in seconds) that the cloned capture process lags behind the original capture process
JOB_OWNER	VARCHAR2 (30)		Owner of the job that performs the split or merge operation
JOB_NAME	VARCHAR2 (30)		Name of the job that performs the split or merge operation
ERROR_NUMBER	NUMBER		Error number if the capture process was aborted
ERROR_MESSAGE	VARCHAR2 (4000)		Error message if the capture process was aborted

DBA_STREAMS_STMT_HANDLERS

DBA_STREAMS_STMT_HANDLERS displays information about all statement DML handlers in the database. Its columns are the same as those in ALL_STREAMS_STMT_HANDLERS.

See Also: ["ALL_STREAMS_STMT_HANDLERS"](#) on page 3-67

DBA_STREAMS_STMTS

DBA_STREAMS_STMTS displays information about the statements in all statement DML handlers in the database. Its columns are the same as those in ALL_STREAMS_STMTS.

See Also: ["ALL_STREAMS_STMTS"](#) on page 3-68

DBA_STREAMS_TABLE_RULES

DBA_STREAMS_TABLE_RULES displays information about the table rules created for all Streams capture processes, propagations, and apply processes in the database. Its columns are the same as those in ALL_STREAMS_TABLE_RULES.

See Also: ["ALL_STREAMS_TABLE_RULES"](#) on page 3-68

DBA_STREAMS_TP_COMPONENT

DBA_STREAMS_TP_COMPONENT displays information about each Oracle Streams component at each database.

Column	Datatype	NULL	Description
COMPONENT_ID	NUMBER	NOT NULL	ID of the Streams component
COMPONENT_NAME	VARCHAR2 (4000)		Name of the Streams component
COMPONENT_DB	VARCHAR2 (128)		Database where the Streams component resides
COMPONENT_TYPE	VARCHAR2 (20)		Type of the Streams component: ■ CAPTURE ■ PROPAGATION SENDER ■ PROPAGATION RECEIVER ■ APPLY ■ QUEUE

Column	Datatype	NULL	Description
COMPONENT_CHANGED_TIME	DATE		Time that the Streams component was last changed

DBA_STREAMS_TP_COMPONENT_LINK

DBA_STREAMS_TP_COMPONENT_LINK displays information about how messages flow between Oracle Streams components.

Column	Datatype	NULL	Description
SOURCE_COMPONENT_ID	NUMBER	NOT NULL	ID of the source Streams component
SOURCE_COMPONENT_NAME	VARCHAR2 (4000)		Name of the source Streams component
SOURCE_COMPONENT_DB	VARCHAR2 (128)		Database where the source Streams component resides
SOURCE_COMPONENT_TYPE	VARCHAR2 (20)		Type of the source Streams component: ■ CAPTURE ■ PROPAGATION SENDER ■ PROPAGATION RECEIVER ■ APPLY ■ QUEUE
DESTINATION_COMPONENT_ID	NUMBER	NOT NULL	ID of the destination Streams component
DESTINATION_COMPONENT_NAME	VARCHAR2 (4000)		Name of the destination Streams component
DESTINATION_COMPONENT_DB	VARCHAR2 (128)		Database where the destination Streams component resides
DESTINATION_COMPONENT_TYPE	VARCHAR2 (20)		Type of the destination Streams component: ■ CAPTURE ■ PROPAGATION SENDER ■ PROPAGATION RECEIVER ■ APPLY ■ QUEUE
PATH_ID	NUMBER	NOT NULL	ID of the stream path
POSITION	NUMBER		Position of the link within the stream path

DBA_STREAMS_TP_COMPONENT_STAT

DBA_STREAMS_TP_COMPONENT_STAT displays temporary performance statistics and session statistics about each Oracle Streams component.

Column	Datatype	NULL	Description
COMPONENT_ID	NUMBER	NOT NULL	ID of the Streams component
COMPONENT_NAME	VARCHAR2 (4000)		Name of the Streams component
COMPONENT_DB	VARCHAR2 (128)		Database where the Streams component resides
COMPONENT_TYPE	VARCHAR2 (20)		Type of the Streams component: ■ CAPTURE ■ PROPAGATION SENDER ■ PROPAGATION RECEIVER ■ APPLY ■ QUEUE

Column	Datatype	NULL	Description
SUB_COMPONENT_TYPE	VARCHAR2 (27)		Type of the Streams subcomponent: - LOGMINER READER - LOGMINER PREPARER - LOGMINER BUILDER - CAPTURE SESSION - PROPAGATION SENDER+RECEIVER - APPLY READER - APPLY COORDINATOR - APPLY SERVER
SESSION_ID	NUMBER		ID of the Streams session for the Streams component
SESSION_SERIAL#	NUMBER		Serial number of the Streams session for the Streams component
STATISTIC_TIME	DATE		Time that the statistic was taken
STATISTIC_NAME	VARCHAR2 (64)		Name of the statistic
STATISTIC_VALUE	NUMBER		Value of the statistic
STATISTIC_UNIT	VARCHAR2 (64)		Unit of the statistic
ADVISOR_RUN_ID	NUMBER		Logical number (1-based) of the Advisor run
ADVISOR_RUN_TIME	DATE		Time that the Advisor was run

DBA_STREAMS_TP_DATABASE

DBA_STREAMS_TP_DATABASE displays information about each database that contains Oracle Streams components.

Column	Datatype	NULL	Description
GLOBAL_NAME	VARCHAR2 (128)	NOT NULL	Global name of the Streams database
LAST_QUERIED	DATE	NOT NULL	Time that the Streams database was last queried
VERSION	VARCHAR2 (30)		Database version of the Streams database
COMPATIBILITY	VARCHAR2 (30)		Compatible setting of the Streams database
MANAGEMENT_PACK_ACCESS	VARCHAR2 (30)		Management pack access of the Streams database

DBA_STREAMS_TP_PATH_BOTTLENECK

DBA_STREAMS_TP_PATH_BOTTLENECK displays temporary information about Oracle Streams components that might be slowing down the flow of messages in a stream path.

Column	Datatype	NULL	Description
PATH_ID	NUMBER		ID of the stream path
COMPONENT_ID	NUMBER		ID of the bottleneck component
COMPONENT_NAME	VARCHAR2 (4000)		Name of the bottleneck component
COMPONENT_DB	VARCHAR2 (128)		Database where the bottleneck component resides

Column	Datatype	NULL	Description
COMPONENT_TYPE	VARCHAR2 (20)		Type of the bottleneck component: ■ CAPTURE ■ PROPAGATION_SENDER ■ PROPAGATION_RECEIVER ■ APPLY ■ QUEUE
TOP_SESSION_ID	NUMBER		ID of the top session for the bottleneck component
TOP_SESSION_SERIAL#	NUMBER		Serial number of the top session for the bottleneck component
ACTION_NAME	VARCHAR2 (32)		Action name for the bottleneck process
BOTTLENECK_IDENTIFIED	VARCHAR2 (30)		Indicates whether the bottleneck was identified (YES) or not (NO)
ADVISOR_RUN_ID	NUMBER		Logical number (1-based) of the Advisor run
ADVISOR_RUN_TIME	DATE		Time that the Advisor was run
ADVISOR_RUN_REASON	VARCHAR2 (4000)		Reason for the bottleneck analysis result.: ■ NULL - Bottleneck is identified ■ PRE-11.1 DATABASE EXISTS - A pre-release 11.1 database exists in the stream path ■ DIAGNOSTIC PACK REQUIRED - A database in the stream path does not have the diagnostic package installed ■ NO BOTTLENECK IDENTIFIED

DBA_STREAMS_TP_PATH_STAT

DBA_STREAMS_TP_PATH_STAT displays temporary performance statistics about each stream path that exists in the Oracle Streams topology.

Column	Datatype	NULL	Description
PATH_ID	NUMBER		ID of the stream path
STATISTIC_TIME	DATE		Time that the statistic was taken
STATISTIC_NAME	VARCHAR2 (64)		Name of the statistic
STATISTIC_VALUE	NUMBER		Value of the statistic
STATISTIC_UNIT	VARCHAR2 (64)		Unit of the statistic
ADVISOR_RUN_ID	NUMBER		Logical number (1-based) of the Advisor run
ADVISOR_RUN_TIME	DATE		Time that the Advisor was run

DBA_STREAMS_TRANSFORM_FUNCTION

DBA_STREAMS_TRANSFORM_FUNCTION displays information about all rule-based transformation functions in the database. Its columns are the same as those in ALL_STREAMS_TRANSFORM_FUNCTION.

See Also: ["ALL_STREAMS_TRANSFORM_FUNCTION"](#) on page 3-70

DBA_STREAMS_TRANSFORMATIONS

DBA_STREAMS_TRANSFORMATIONS displays information about all transformations available on a system, in order of execution.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2 (30)		Owner of the rule
RULE_NAME	VARCHAR2 (30)		Name of the rule
TRANSFORM_TYPE	VARCHAR2 (26)		Type of the transformation: ■ DECLARATIVE TRANSFORMATION ■ SUBSET RULE ■ CUSTOM TRANSFORMATION
FROM_SCHEMA_NAME	VARCHAR2 (30)		Schema to be renamed
TO_SCHEMA_NAME	VARCHAR2 (30)		New schema name
FROM_TABLE_NAME	VARCHAR2 (30)		Table to be renamed
TO_TABLE_NAME	VARCHAR2 (30)		New table name
SCHEMA_NAME	VARCHAR2 (30)		Schema of the column to be modified
TABLE_NAME	VARCHAR2 (30)		Table of the column to be modified
FROM_COLUMN_NAME	VARCHAR2 (4000)		Column to be renamed
TO_COLUMN_NAME	VARCHAR2 (4000)		New column name
COLUMN_NAME	VARCHAR2 (4000)		Column to add or delete
COLUMN_VALUE	ANYDATA		Value of the column to add
COLUMN_TYPE	VARCHAR2 (4000)		Type of the new column
COLUMN_FUNCTION	VARCHAR2 (30)		Name of the default function used to add a column
VALUE_TYPE	VARCHAR2 (3)		Indicates whether to modify the old (OLD), new (NEW), or both (*) values of the LCR
USER_FUNCTION_NAME	VARCHAR2 (4000)		Name of the user-defined transformation function to run
SUBSETTING_OPERATION	VARCHAR2 (6)		DML operation for row subsetting: ■ INSERT ■ UPDATE ■ DELETE
DML_CONDITION	VARCHAR2 (4000)		Row subsetting condition
DECLARATIVE_TYPE	VARCHAR2 (13)		Type of declarative transform: ■ KEEP COLUMNS ■ DELETE COLUMN ■ RENAME COLUMN ■ ADD COLUMN ■ RENAME TABLE ■ RENAME SCHEMA
PRECEDENCE	NUMBER		Execution order relative to other declarative transformations on the same STEP_NUMBER
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

DBA_STREAMS_UNSUPPORTED

DBA_STREAMS_UNSUPPORTED displays information about all tables in the database that are not supported by Streams in this release of the Oracle Database. Its columns are the same as those in ALL_STREAMS_UNSUPPORTED.

See Also: ["ALL_STREAMS_UNSUPPORTED"](#) on page 3-70

DBA_SUBPART_COL_STATISTICS

DBA_SUBPART_COL_STATISTICS provides column statistics and histogram information for all subpartitions in the database. Its columns are the same as those in ["ALL_STORED_SETTINGS"](#) on page 3-62.

DBA_SUBPART_HISTOGRAMS

DBA_SUBPART_HISTOGRAMS lists actual histogram data (end-points per histogram) for histograms on all table subpartitions in the database. Its columns are the same as those in ["ALL_SUBPART_HISTOGRAMS"](#) on page 3-72.

DBA_SUBPART_KEY_COLUMNS

DBA_SUBPART_KEY_COLUMNS lists subpartitioning key columns for all composite-partitioned tables (and local indexes on composite-partitioned tables) in the database. Its columns are the same as those in ALL_SUBPART_KEY_COLUMNS.

See Also: ["ALL_SUBPART_KEY_COLUMNS"](#) on page 3-73

DBA_SUBPARTITION_TEMPLATES

DBA_SUBPARTITION_TEMPLATES describes all subpartition templates in the database. Its columns are the same as those in ALL_SUBPARTITION_TEMPLATES.

See Also: ["ALL_SUBPARTITION_TEMPLATES"](#) on page 3-73

DBA_SUBSCR_REGISTRATIONS

DBA_SUBSCR_REGISTRATIONS displays information about all subscription registrations in the database.

Related View

USER_SUBSCR_REGISTRATIONS displays information about the subscription registrations owned by the current user.

Column	Datatype	NULL	Description
REG_ID	NUMBER		Registration ID
SUBSCRIPTION_NAME	VARCHAR2(128)	NOT NULL	Name of the subscription registration. The subscription name is of the form <i>schema.queue</i> if the registration is for a single consumer queue or <i>schema.queue:consumer_name</i> if the registration is for a multi-consumer queue.
LOCATION_NAME	VARCHAR2(256)	NOT NULL	Location endpoint of the registration
USER#	NUMBER	NOT NULL	Internally generated user ID
USER_CONTEXT	RAW(128)		Context the user provided during registration of PL/SQL registrations or an internally generated context for OCI registrations
CONTEXT_SIZE	NUMBER		Size of the context
NAMESPACE	VARCHAR2(9)		Namespace of the subscription registration: ▪ ANONYMOUS ▪ AQ ▪ DBCHANGE

Column	Datatype	NULL	Description
PRESENTATION	VARCHAR2 (7)		Presentation format of notifications: ■ DEFAULT - Binary ■ XML
VERSION	VARCHAR2 (5)		Database version: ■ 8.1.6 ■ 10.2 ■ 11.1
STATUS	VARCHAR2 (8)		Status of the registration: ■ DB REG - Database registration ■ LDAP REG - LDAP registration
ANY_CONTEXT	ANYDATA		AnyData user context (used for Streams replication registrations)
CONTEXT_TYPE	NUMBER		Type of the user context
QOSFLAGS	VARCHAR2 (13)		Quality of service of the registration: ■ RELIABLE - Reliable notifications persist across instance and database restarts ■ PAYLOAD - Payload delivery is required. It is only supported for client notification and only for RAW queues. ■ PURGE_ON_NTFN - Registration is to be purged automatically when the first notification is delivered to this registration location
PAYLOAD_CALLBACK	VARCHAR2 (4000)		Any callback registered to serialize the notification payload
TIMEOUT	TIMESTAMP (6)		Registration timeout
REG_TIME	TIMESTAMP (6) WITH TIME ZONE		Time of the registration
NTFN_GROUPING_CLASS	VARCHAR2 (4)		Notification grouping class
NTFN_GROUPING_VALUE	NUMBER		Notification grouping value
NTFN_GROUPING_TYPE	VARCHAR2 (7)		Notification grouping type: ■ SUMMARY ■ LAST
NTFN_GROUPING_START_TIME	TIMESTAMP (6) WITH TIME ZONE		Notification grouping start time
NTFN_GROUPING_REPEAT_COUNT	VARCHAR2 (40)		Notification grouping repeat count, or FOREVER

See Also: ["USER_SUBSCR_REGISTRATIONS"](#) on page 6-101

DBA_SUBSCRIBED_COLUMNS

DBA_SUBSCRIBED_COLUMNS describes the columns of source tables to which any subscriber has subscribed. This view is intended for use by Change Data Capture publishers.

Related View

USER_SUBSCRIBED_COLUMNS describes the columns of source tables to which the current user has subscribed.

Column	Datatype	NULL	Description
HANDLE	NUMBER	NOT NULL	Subscription handle
SOURCE_SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Source table schema identifier
SOURCE_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Source table identifier
COLUMN_NAME	VARCHAR2 (30)	NOT NULL	Source table column identifier
SUBSCRIPTION_NAME	VARCHAR2 (30)	NOT NULL	Name of the subscription
SOURCE_DB	VARCHAR2 (128)		Source database global name

See Also: ["USER_SUBSCRIBED_COLUMNS"](#) on page 6-102

DBA_SUBSCRIBED_TABLES

DBA_SUBSCRIBED_TABLES describes all source tables in the database to which any subscriber has subscribed. This view is intended for use by Change Data Capture publishers.

Related View

USER_SUBSCRIBED_TABLES describes the source tables to which the current user has subscribed.

Column	Datatype	NULL	Description
HANDLE	NUMBER	NOT NULL	Subscription handle
SOURCE_SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Source table owner
SOURCE_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Source table name
VIEW_NAME	VARCHAR2 (30)		Subscriber view name
CHANGE_SET_NAME	VARCHAR2 (30)	NOT NULL	Change set name
SUBSCRIPTION_NAME	VARCHAR2 (30)	NOT NULL	Name of the subscription

See Also: ["USER_SUBSCRIBED_TABLES"](#) on page 6-102

DBA_SUBSCRIPTIONS

DBA_SUBSCRIPTIONS describes all subscriptions in the database. This view is intended for use by Change Data Capture publishers.

Related View

USER_SUBSCRIPTIONS describes the subscriptions created by the current user.

Column	Datatype	NULL	Description
HANDLE	NUMBER	NOT NULL	Subscription handle
SET_NAME	VARCHAR2 (30)	NOT NULL	Change set name
USERNAME	VARCHAR2 (30)	NOT NULL	User name of the subscriber
CREATED	DATE	NOT NULL	Subscription creation date
STATUS	VARCHAR2 (1)	NOT NULL	Status of the subscriptions: ■ N - Not yet active ■ A - Currently active
EARLIEST_SCN	NUMBER	NOT NULL	Subscription window low boundary

Column	Datatype	NULL	Description
LATEST_SCN	NUMBER	NOT NULL	Subscription window high boundary
DESCRIPTION	VARCHAR2 (255)		Comment field for the subscriber
LAST_PURGED	DATE		Last time the subscriber called the PURGE_WINDOW for this subscription
LAST_EXTENDED	DATE		Last time the subscriber called the EXTEND_WINDOW for this subscription
SUBSCRIPTION_NAME	VARCHAR2 (30)	NOT NULL	Name of the subscription

See Also: ["USER_SUBSCRIPTIONS"](#) on page 6-102

DBA_SYNC_CAPTURE

DBA_SYNC_CAPTURE displays information about all synchronous capture processes in the database. Its columns are the same as those in ALL_SYNC_CAPTURE.

See Also: ["ALL_SYNC_CAPTURE"](#) on page 3-74

DBA_SYNC_CAPTURE_PREPARED_TABS

DBA_SYNC_CAPTURE_PREPARED_TABS displays information about all tables in the database that are prepared for synchronous capture instantiation. Its columns are the same as those in ALL_SYNC_CAPTURE_PREPARED_TABS.

See Also: ["ALL_SYNC_CAPTURE_PREPARED_TABS"](#) on page 3-75

DBA_SYNC_CAPTURE_TABLES

DBA_SYNC_CAPTURE_TABLES displays information about all tables in the database that are captured by synchronous Streams captures. Its columns are the same as those in ALL_SYNC_CAPTURE_TABLES.

See Also: ["ALL_SYNC_CAPTURE_TABLES"](#) on page 3-75

DBA_SYNONYMS

DBA_SYNONYMS describes all synonyms in the database. Its columns are the same as those in ALL_SYNONYMS.

See Also: ["ALL_SYNONYMS"](#) on page 3-75

DBA_SYS_PRIVS

DBA_SYS_PRIVS describes system privileges granted to users and roles.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	Grantee name, user, or role receiving the grant
PRIVILEGE	VARCHAR2 (40)	NOT NULL	System privilege
ADMIN_OPTION	VARCHAR2 (3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)

DBA_TAB_COL_STATISTICS

DBA_TAB_COL_STATISTICS contains column statistics and histogram information extracted from "DBA_TAB_COLUMNS" on page 6-17. Its columns are the same as those in "ALL_TAB_COL_STATISTICS" on page 3-77.

DBA_TAB_COLS

DBA_TAB_COLS describes the columns of all tables, views, and clusters in the database. This view differs from "DBA_TAB_COLUMNS" on page 6-17 in that hidden columns are not filtered out. Its columns are the same as those in "ALL_TAB_COLS" on page 3-77. To gather statistics for this view, use the SQL ANALYZE statement.

DBA_TAB_COLUMNS

DBA_TAB_COLUMNS describes the columns of all tables, views, and clusters in the database. Its columns are the same as those in "ALL_TAB_COLUMNS" on page 3-79. To gather statistics for this view, use the SQL ANALYZE statement.

DBA_TAB_COMMENTS

DBA_TAB_COMMENTS displays comments on all tables and views in the database. Its columns are the same as those in ALL_TAB_COMMENTS.

See Also: "ALL_TAB_COMMENTS" on page 3-81

DBA_TAB_HISTGRM_PENDING_STATS

DBA_TAB_HISTGRM_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions in the database. Its columns are the same as those in "ALL_TAB_HISTGRM_PENDING_STATS" on page 3-81.

DBA_TAB_HISTOGRAMS

DBA_TAB_HISTOGRAMS describes histograms on columns of all tables in the database. Its columns are the same as those in "ALL_TAB_HISTOGRAMS" on page 3-82.

DBA_TAB_MODIFICATIONS

DBA_TAB_MODIFICATIONS describes modifications to all tables in the database that have been modified since the last time statistics were gathered on the tables. Its columns are the same as those in "ALL_TAB_MODIFICATIONS" on page 3-82.

Note: This view is populated only for tables with the MONITORING attribute. It is intended for statistics collection over a long period of time. For performance reasons, the Oracle Database does not populate this view immediately when the actual modifications occur. Run the FLUSH_DATABASE_MONITORING_INFO procedure in the DBMS_STATS PL/SQL package to populate this view with the latest information. The ANALYZE_ANY system privilege is required to run this procedure.

DBA_TAB_PARTITIONS

DBA_TAB_PARTITIONS displays partition-level partitioning information, partition storage parameters, and partition statistics generated by the DBMS_STATS package or the ANALYZE statement for all partitions in the database. Its columns are the same as those in ["ALL_TAB_PARTITIONS"](#) on page 3-83.

DBA_TAB_PENDING_STATS

DBA_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions in the database. Its columns are the same as those in ["ALL_TAB_PENDING_STATS"](#) on page 3-86.

DBA_TAB_PRIVS

DBA_TAB_PRIVS describes all object grants in the database.

Related View

USER_TAB_PRIVS describes the object grants for which the current user is the object owner, grantor, or grantee.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	Name of the user or role to whom access was granted
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object. The object can be any object, including tables, packages, indexes, sequences, and so on.
GRANTOR	VARCHAR2 (30)	NOT NULL	Name of the user who performed the grant
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Privilege on the object
GRANTABLE	VARCHAR2 (3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
HIERARCHY	VARCHAR2 (3)		Indicates whether the privilege was granted with the HIERARCHY OPTION (YES) or not (NO)

See Also: ["USER_TAB_PRIVS"](#) on page 6-104

DBA_TAB_STATISTICS

DBA_TAB_STATISTICS displays optimizer statistics for all tables in the database. Its columns are the same as those in ALL_TAB_STATISTICS.

See Also: ["ALL_TAB_STATISTICS"](#) on page 3-88

DBA_TAB_STAT_PREFS

DBA_TAB_STAT_PREFS displays information about statistics preferences for all tables in the database. Its columns are the same as those in ["ALL_TAB_STAT_PREFS"](#) on page 3-88.

DBA_TAB_STATS_HISTORY

DBA_TAB_STATS_HISTORY provides a history of table statistics modifications for all tables in the database. Its columns are the same as those in "[ALL_TAB_STATS_HISTORY](#)" on page 3-89.

DBA_TAB_SUBPARTITIONS

DBA_TAB_SUBPARTITIONS describes, for each table subpartition, the subpartition name, name of the table and partition to which it belongs, and its storage attributes. Its columns are the same as those in "[ALL_TAB_SUBPARTITIONS](#)" on page 3-89.

Note: Statistics are not collected on a per-subpartition basis.

DBA_TABLES

DBA_TABLES describes all relational tables in the database. Its columns are the same as those in ALL_TABLES. To gather statistics for this view, use the ANALYZE SQL statement.

See Also: "[ALL_TABLES](#)" on page 3-91

DBA_TABLESPACE_GROUPS

DBA_TABLESPACE_GROUPS describes all tablespace groups in the database.

Column	Datatype	NULL	Description
GROUP_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace group
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace

DBA_TABLESPACE_THRESHOLDS

DBA_TABLESPACE_THRESHOLDS describes space utilization threshold settings for all tablespaces in the database.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2 (30)		Tablespace name
CONTENTS	VARCHAR2 (9)		Tablespace contents: ■ UNDO ■ PERMANENT ■ TEMPORARY
EXTENT_MANAGEMENT	VARCHAR2 (10)		Indicates whether the extents in the tablespace are dictionary managed (DICTIONARY) or locally managed (LOCAL)
THRESHOLD_TYPE	VARCHAR2 (8)		Source of the threshold: ■ EXPLICIT ■ DEFAULT ■ NONE
METRICS_NAME	VARCHAR2 (64)		Name of the metric being monitored

Column	Datatype	NULL	Description
WARNING_OPERATOR	VARCHAR2 (12)		Relational operator for warning thresholds: ▪ GT ▪ EQ ▪ LT ▪ LE ▪ GE ▪ CONTAINS ▪ NE ▪ DO NOT CHECK ▪ DO_NOT_CHECK
WARNING_VALUE	VARCHAR2 (256)		Warning threshold value
CRITICAL_OPERATOR	VARCHAR2 (12)		Relational operator for critical thresholds: ▪ GT ▪ EQ ▪ LT ▪ LE ▪ GE ▪ CONTAINS ▪ NE ▪ DO NOT CHECK ▪ DO_NOT_CHECK
CRITICAL_VALUE	VARCHAR2 (256)		Critical threshold value

DBA_TABLESPACE_USAGE_METRICS

DBA_TABLESPACE_USAGE_METRICS describes tablespace usage metrics for all types of tablespaces, including permanent, temporary, and undo tablespaces.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2 (30)		Tablespace name
USED_SPACE	NUMBER		Total space consumed by the tablespace
TABLESPACE_SIZE	NUMBER		Total size of the tablespace
USED_PERCENT	NUMBER		Percentage of used space, as a function of the maximum possible tablespace size

DBA_TABLESPACES

DBA_TABLESPACES describes all tablespaces in the database.

Related View

USER_TABLESPACES describes the tablespaces accessible to the current user. This view does not display the PLUGGED_IN column.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace
BLOCK_SIZE	NUMBER	NOT NULL	Tablespace block size
INITIAL_EXTENT	NUMBER		Default initial extent size
NEXT_EXTENT	NUMBER		Default incremental extent size

Column	Datatype	NULL	Description
MIN_EXTENTS	NUMBER	NOT NULL	Default minimum number of extents
MAX_EXTENTS	NUMBER		Default maximum number of extents
MAX_SIZE	NUMBER		Default maximum size of segments (in Oracle blocks)
PCT_INCREASE	NUMBER		Default percent increase for extent size
MIN_EXTLEN	NUMBER		Minimum extent size for this tablespace
STATUS	VARCHAR2 (9)		Tablespace status: ■ ONLINE ■ OFFLINE ■ READ ONLY
CONTENTS	VARCHAR2 (9)		Tablespace contents: ■ UNDO ■ PERMANENT ■ TEMPORARY
LOGGING	VARCHAR2 (9)		Default logging attribute: ■ LOGGING ■ NOLOGGING
FORCE_LOGGING	VARCHAR2 (3)		Indicates whether the tablespace is under force logging mode (YES) or not (NO)
EXTENT_MANAGEMENT	VARCHAR2 (10)		Indicates whether the extents in the tablespace are dictionary managed (DICTIONARY) or locally managed (LOCAL)
ALLOCATION_TYPE	VARCHAR2 (9)		Type of extent allocation in effect for the tablespace: ■ SYSTEM ■ UNIFORM ■ USER
PLUGGED_IN	VARCHAR2 (3)		Indicates whether the tablespace is plugged in (YES) or not (NO)
SEGMENT_SPACE_MANAGEMENT	VARCHAR2 (6)		Indicates whether the free and used segment space in the tablespace is managed using free lists (MANUAL) or bitmaps (AUTO)
DEF_TAB_COMPRESSION	VARCHAR2 (8)		Indicates whether default table compression is enabled (ENABLED) or not (DISABLED) Note: Enabling default table compression indicates that all tables in the tablespace will be created with table compression enabled unless otherwise specified.
RETENTION	VARCHAR2 (11)		Undo tablespace retention: ■ GUARANTEE - Tablespace is an undo tablespace with RETENTION specified as GUARANTEE A RETENTION value of GUARANTEE indicates that unexpired undo in all undo segments in the undo tablespace should be retained even if it means that forward going operations that need to generate undo in those segments fail. ■ NOGUARANTEE - Tablespace is an undo tablespace with RETENTION specified as NOGUARANTEE ■ NOT APPLY - Tablespace is not an undo tablespace
BIGFILE	VARCHAR2 (3)		Indicates whether the tablespace is a bigfile tablespace (YES) or a smallfile tablespace (NO)
PREDICATE_EVALUATION	VARCHAR2 (7)		Indicates whether predicates are evaluated by host (HOST) or by storage (STORAGE)
ENCRYPTED	VARCHAR2 (3)		Indicates whether the tablespace is encrypted (YES) or not (NO)

Column	Datatype	NULL	Description
COMPRESS_FOR	VARCHAR2 (12)		Default compression for what kind of operations: ■ BASIC ■ OLTP ■ QUERY LOW¹ ■ QUERY HIGH¹ ■ ARCHIVE LOW¹ ■ ARCHIVE HIGH¹ ■ NULL

¹ Hybrid columnar compression is a feature of Oracle Exadata. See Oracle Exadata Storage Server Software documentation for more information.

See Also: ["USER_TABLESPACES"](#) on page 6-105

DBA_TEMP_FILES

DBA_TEMP_FILES describes all temporary files (tempfiles) in the database.

Column	Datatype	NULL	Description
FILE_NAME	VARCHAR2 (513)		Name of the database temp file
FILE_ID	NUMBER		File identifier number of the database temp file
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace to which the file belongs
BYTES	NUMBER		Size of the file (in bytes)
BLOCKS	NUMBER		Size of the file (in Oracle blocks)
STATUS	CHAR (9)		File status: ■ OFFLINE ■ ONLINE ■ UNKNOWN
RELATIVE_FNO	NUMBER		Tablespace-relative file number
AUTOEXTENSIBLE	VARCHAR2 (3)		Indicates whether the file is autoextensible (YES) or not (NO)
MAXBYTES	NUMBER		maximum size of the file (in bytes)
MAXBLOCKS	NUMBER		Maximum size of the file (in Oracle blocks)
INCREMENT_BY	NUMBER		Default increment for autoextension (in Oracle blocks)
USER_BYTES	NUMBER		Size of the useful portion of the file (in bytes)
USER_BLOCKS	NUMBER		Size of the useful portion of the file (in Oracle blocks)

DBA_TEMP_FREE_SPACE

DBA_TEMP_FREE_SPACE displays temporary space usage information at tablespace level.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace
TABLESPACE_SIZE	NUMBER		Total size of the tablespace, in bytes
ALLOCATED_SPACE	NUMBER		Total allocated space, in bytes, including space that is currently allocated and used and space that is currently allocated and available for reuse

Column	Datatype	NULL	Description
FREE_SPACE	NUMBER		Total free space available, in bytes, including space that is currently allocated and available for reuse and space that is currently unallocated

DBA_THRESHOLDS

DBA_THRESHOLDS describes all thresholds.

Column	Datatype	NULL	Description
METRICS_NAME	VARCHAR2 (64)		Metrics name
WARNING_OPERATOR	VARCHAR2 (12)		Relational operator for warning thresholds: - GT - EQ - LT - LE - GE - CONTAINS - NE - DO NOT CHECK - DO_NOT_CHECK
WARNING_VALUE	VARCHAR2 (256)		Warning threshold value
CRITICAL_OPERATOR	VARCHAR2 (12)		Relational operator for critical thresholds: - GT - EQ - LT - LE - GE - CONTAINS - NE - DO NOT CHECK - DO_NOT_CHECK
CRITICAL_VALUE	VARCHAR2 (256)		Critical threshold value
OBSERVATION_PERIOD	NUMBER		Observation period length (in minutes)
CONSECUTIVE_OCCURRENCES	NUMBER		Number of occurrences before an alert is issued
INSTANCE_NAME	VARCHAR2 (16)		Instance name; NULL for database-wide alerts
OBJECT_TYPE	VARCHAR2 (64)		Object type: - SYSTEM - SERVICE - EVENT_CLASS - TABLESPACE - FILE
OBJECT_NAME	VARCHAR2 (513)		Name of the object for which the threshold is set
STATUS	VARCHAR2 (7)		Indicates whether the threshold is applicable on a valid object (VALID) or not (INVALID)

DBA_TRANSFORMATIONS

DBA_TRANSFORMATIONS displays information about all transformations in the database. These transformations can be specified with Advanced Queuing operations such as enqueue, dequeue, and subscribe to automatically integrate transformations in AQ messaging.

Related View

USER_TRANSFORMATIONS displays information about transformations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
TRANSFORMATION_ID	NUMBER	NOT NULL	Unique identifier for the transformation
OWNER	VARCHAR2 (30)	NOT NULL	Owning user of the transformation
NAME	VARCHAR2 (30)	NOT NULL	Transformation name
FROM_TYPE	VARCHAR2 (61)		Source type name
TO_TYPE	VARCHAR2 (91)		Target type name

See Also: ["USER_TRANSFORMATIONS"](#) on page 6-105

DBA_TRIGGER_COLS

DBA_TRIGGER_COLS describes the use of columns in all triggers in the database. Its columns are the same as those in ALL_TRIGGER_COLS.

See Also: ["ALL_TRIGGER_COLS"](#) on page 3-94

DBA_TRIGGER_ORDERING

DBA_TRIGGER_ORDERING describes all triggers in the database that have FOLLOWS or PRECEDES ordering. Its columns are the same as those in ALL_TRIGGER_ORDERING.

See Also: ["ALL_TRIGGER_ORDERING"](#) on page 3-95

DBA_TRIGGERS

DBA_TRIGGERS describes all triggers in the database. Its columns are the same as those in ALL_TRIGGERS.

See Also: ["ALL_TRIGGERS"](#) on page 3-96

DBA_TS_QUOTAS

DBA_TS_QUOTAS describes tablespace quotas for all users.

Related View

USER_TS_QUOTAS describes tablespace quotas for the current user. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2 (30)	NOT NULL	Tablespace name
USERNAME	VARCHAR2 (30)	NOT NULL	User with resource rights on the tablespace

Column	Datatype	NULL	Description
BYTES	NUMBER		Number of bytes charged to the user
MAX_BYTES	NUMBER		User's quota in bytes, or -1 if no limit
BLOCKS	NUMBER	NOT NULL	Number of Oracle blocks charged to the user
MAX_BLOCKS	NUMBER		User's quota in Oracle blocks, or -1 if no limit
DROPPED	VARCHAR2 (3)		Whether the tablespace has been dropped

DBA_TSM_DESTINATION

DBA_TSM_DESTINATION lists transparent session migration (TSM) destination session statistics.

Column	Datatype	NULL	Description
SOURCE_DATABASE_NAME	VARCHAR2 (4000)		Database name of source session
DESTINATION_DATABASE_NAME	VARCHAR2 (4000)		Database name of destination session
DESTINATION_INSTANCE_NAME	VARCHAR2 (4000)		Instance name of destination session
DESTINATION_INSTANCE_ID	VARCHAR2 (4000)		Instance ID of destination session
DESTINATION_INST_START_TIME	TIMESTAMP (6) WITH TIME ZONE		Instance start time of destination session
SEQUENCE#	NUMBER		Migration sequence number
DESTINATION_SID	NUMBER		Session ID of destination session
DESTINATION_SERIAL#	NUMBER		Session serial number of destination session
DESTINATION_START_TIME	TIMESTAMP (6) WITH TIME ZONE		Start time for migration on destination session
DESTINATION_END_TIME	TIMESTAMP (6) WITH TIME ZONE		End time for migration on destination session
DESTINATION_USER_NAME	VARCHAR2 (30)	NOT NULL	User associated with the destination session
DESTINATION_SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Schema associated with the destination session
DESTINATION_STATE	VARCHAR2 (24)		Migration state of destination session

DBA_TSM_SOURCE

DBA_TSM_SOURCE lists transparent session migration (TSM) source session statistics.

Column	Datatype	NULL	Description
SOURCE_DATABASE_NAME	VARCHAR2 (4000)		Database name of source session
SOURCE_INSTANCE_NAME	VARCHAR2 (4000)		Instance name of source session
SOURCE_INSTANCE_ID	VARCHAR2 (4000)		Instance ID of source session
SOURCE_INSTANCE_START_TIME	TIMESTAMP (6) WITH TIME ZONE		Instance start time of source session
SEQUENCE#	NUMBER		Migration sequence number
SOURCE_SID	NUMBER		Session ID of source session
SOURCE_SERIAL#	NUMBER		Source serial number of source session
SOURCE_STATE	VARCHAR2 (24)		Migration state of source session
CONNECT_STRING	VARCHAR2 (4000)		Connect string specified for migration

Column	Datatype	NULL	Description
SOURCE_START_TIME	TIMESTAMP (6) WITH TIME ZONE		Start time for migration on source session
COST	NUMBER		Estimate of migration cost
FAILURE_REASON	VARCHAR2 (34)		Reason for migration failure, if any
SOURCE_END_TIME	TIMESTAMP (6) WITH TIME ZONE		End time for migration on source session
ROUNDTRIPS	NUMBER		Number of client-server round trips during migration
SOURCE_USER_NAME	VARCHAR2 (30)	NOT NULL	User associated with the source session
SOURCE_SCHEMA_NAME	VARCHAR2 (30)	NOT NULL	Schema associated with the source session
DESTINATION_DATABASE_NAME	VARCHAR2 (4000)		Database name of the destination session

DBA_TSTZ_TAB_COLS

DBA_TSTZ_TAB_COLS displays information about the columns of all tables in the database, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types. Its columns (except for NESTED) are the same as those in ALL_TSTZ_TAB_COLS.

See Also: ["ALL_TSTZ_TAB_COLS"](#) on page 3-97

DBA_TSTZ_TABLES

DBA_TSTZ_TABLES displays information about all tables in the database, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types. Its columns are the same as those in ALL_TSTZ_TABLES.

See Also: ["ALL_TSTZ_TABLES"](#) on page 3-98

DBA_TUNE_MVIEW

DBA_TUNE_MVIEW displays the result of executing the `DBMS_ADVISOR.TUNE_MVIEW` procedure.

Related View

USER_TUNE_MVIEW displays the result of executing the `DBMS_ADVISOR.TUNE_MVIEW` procedure. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Owner of the task
TASK_NAME	VARCHAR2 (30)		Name of the task
ACTION_ID	NUMBER	NOT NULL	Identifier of the action
SCRIPT_TYPE	VARCHAR2 (14)		Type of the script: ■ IMPLEMENTATION ■ UNDO
STATEMENT	CLOB		Action statement

See Also: ["USER_TUNE_MVIEW"](#) on page 6-106

DBA_TYPE_ATTRS

DBA_TYPE_ATTRS describes the attributes of all object types in the database. Its columns (except for CHAR_USED) are the same as those in ALL_TYPE_ATTRS.

See Also: ["ALL_TYPE_ATTRS"](#) on page 3-98

DBA_TYPE_METHODS

DBA_TYPE_METHODS describes the methods of all object types in the database. Its columns are the same as those in ALL_TYPE_METHODS.

See Also: ["ALL_TYPE_METHODS"](#) on page 3-99

DBA_TYPE_VERSIONS

DBA_TYPE_VERSIONS describes the versions of all object types in the database. Its columns are the same as those in ALL_TYPE_VERSIONS.

See Also: ["ALL_TYPE_VERSIONS"](#) on page 3-100

DBA_TYPES

DBA_TYPES describes all object types in the database. Its columns are the same as those in ALL_TYPES.

See Also: ["ALL_TYPES"](#) on page 3-101

DBA_UNDO_EXTENTS

DBA_UNDO_EXTENTS describes the extents comprising the segments in all undo tablespaces in the database.

Column	Datatype	NULL	Description
OWNER	CHAR(3)		Owner of the undo tablespace
SEGMENT_NAME	VARCHAR2(30)	NOT NULL	Name of the undo segment
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the undo tablespace
EXTENT_ID	NUMBER		ID of the extent
FILE_ID	NUMBER	NOT NULL	File identifier number of the file containing the extent
BLOCK_ID	NUMBER		Start block number of the extent
BYTES	NUMBER		Size of the extent (in bytes)
BLOCKS	NUMBER		Size of the extent (in blocks)
RELATIVE_FNO	NUMBER		Relative number of the file containing the segment header
COMMIT_JTIME	NUMBER		Commit time of the undo in the extent expressed as Julian time. This column is deprecated, but retained for backward compatibility reasons.
COMMIT_WTIME	VARCHAR2(20)		Commit time of the undo in the extent expressed as Wallclock time. This column is deprecated, but retained for backward compatibility reasons.

Column	Datatype	NULL	Description
STATUS	VARCHAR2 (9)		Transaction Status of the undo in the extent: ■ ACTIVE ■ EXPIRED ■ UNEXPIRED

DBA_UNUSED_COL_TABS

DBA_UNUSED_COL_TABS describes all tables in the database containing unused columns. Its columns are the same as those in ALL_UNUSED_COL_TABS.

See Also: ["ALL_UNUSED_COL_TABS"](#) on page 3-101

DBA_UPDATABLE_COLUMNS

DBA_UPDATABLE_COLUMNS describes all columns in a join view that can be updated by the database administrator, subject to appropriate privileges. Its columns are the same as those in ["ALL_UPDATABLE_COLUMNS"](#) on page 3-102.

See Also: *Oracle Database Concepts* for information on updatable join views

DBA_USERS

DBA_USERS describes all users of the database.

Related View

USER_USERS describes the current user. This view does not display the PASSWORD, PROFILE, PASSWORD_VERSIONS, EDITIONS_ENABLED, or AUTHENTICATION_TYPE columns.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (30)	NOT NULL	Name of the user
USER_ID	NUMBER	NOT NULL	ID number of the user
PASSWORD	VARCHAR2 (30)		This column is deprecated in favor of the AUTHENTICATION_TYPE column
ACCOUNT_STATUS	VARCHAR2 (32)	NOT NULL	Account status: ■ OPEN ■ EXPIRED ■ EXPIRED (GRACE) ■ LOCKED (TIMED) ■ LOCKED ■ EXPIRED & LOCKED (TIMED) ■ EXPIRED (GRACE) & LOCKED (TIMED) ■ EXPIRED & LOCKED ■ EXPIRED (GRACE) & LOCKED
LOCK_DATE	DATE		Date the account was locked if account status was LOCKED
EXPIRY_DATE	DATE		Date of expiration of the account
DEFAULT_TABLESPACE	VARCHAR2 (30)	NOT NULL	Default tablespace for data

Column	Datatype	NULL	Description
TEMPORARY_TABLESPACE	VARCHAR2 (30)	NOT NULL	Name of the default tablespace for temporary tables or the name of a tablespace group
CREATED	DATE	NOT NULL	User creation date
PROFILE	VARCHAR2 (30)	NOT NULL	User resource profile name
INITIAL_RSRC_CONSUMER_GROUP	VARCHAR2 (30)		Initial resource consumer group for the user
EXTERNAL_NAME	VARCHAR2 (4000)		User external name
PASSWORD_VERSIONS	VARCHAR2 (8)		Database version in which the password was created or changed
EDITIONS_ENABLED	VARCHAR2 (1)		Indicates whether editions have been enabled for the corresponding user (Y) or not (N)
AUTHENTICATION_TYPE	VARCHAR2 (8)		Indicates the authentication mechanism for the user: - EXTERNAL - CREATE USER <i>user1</i> IDENTIFIED EXTERNALLY; - GLOBAL - CREATE USER <i>user2</i> IDENTIFIED GLOBALLY; - PASSWORD - CREATE USER <i>user3</i> IDENTIFIED BY <i>user3</i>;

See Also: ["USER_USERS"](#) on page 6-107

DBA_USERS_WITH_DEFPWD

DBA_USERS_WITH_DEFPWD displays all users in the database that are still using their default passwords.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (30)	NOT NULL	Name of the user

DBA_USTATS

DBA_USTATS describes the user-defined statistics collected on all tables and indexes in the database. Its columns are the same as those in ALL_USTATS.

See Also: ["ALL_USTATS"](#) on page 3-103

DBA_VARRAYS

DBA_VARRAYS describes all varrays in the database. Its columns are the same as those in ALL_VARRAYS.

See Also: ["ALL_VARRAYS"](#) on page 3-103

DBA_VIEWS

DBA_VIEWS describes all views in the database. Its columns are the same as those in ALL_VIEWS.

See Also: ["ALL_VIEWS"](#) on page 3-104

DBA_VIEWS_AE

DBA_VIEWS_AE describes all views (across all editions) in the database. Its columns are the same as those in ALL_VIEWS_AE.

See Also: ["ALL_VIEWS_AE"](#) on page 3-105

DBA_WAITERS

DBA_WAITERS shows all the sessions that are waiting for a lock. In an Oracle RAC environment, this only applies if the waiter is on the same instance.

Column	Datatype	NULL	Description
WAITING_SESSION	NUMBER		The waiting session
HOLDING_SESSION	NUMBER		The holding session
LOCK_TYPE	VARCHAR2 (26)		The lock type
MODE_HELD	VARCHAR2 (40)		The mode held
MODE_REQUESTED	VARCHAR2 (40)		The mode requested
LOCK_ID1	VARCHAR2 (40)		Lock ID 1
LOCK_ID2	VARCHAR2 (40)		Lock ID 2

DBA_WALLET_ACLS

DBA_WALLET_ACLS displays the access control lists assigned to restrict access to wallets through PL/SQL network utility packages.

Column	Datatype	NULL	Description
WALLET_PATH	VARCHAR2 (1000)	NOT NULL	Wallet path
ACL	VARCHAR2 (4000)		Path of the access control list
ACLID	RAW (16)	NOT NULL	Object ID of the access control list

DBA_WARNING_SETTINGS

DBA_WARNING_SETTINGS displays information about the warning parameter settings for all objects in the database. Its columns are the same as those in ALL_WARNING_SETTINGS.

See Also: ["ALL_WARNING_SETTINGS"](#) on page 3-105

DBA_WORKLOAD_CAPTURES

DBA_WORKLOAD_CAPTURES displays all the workload captures that have been performed in the current database. It also lists captures on which DBMS_WORKLOAD_CAPTURE.GET_CAPTURE_INFO () or DBMS_WORKLOAD_REPLAY.GET_REPLAY_INFO () have been called. Each row contains information about one workload capture.

Column	Datatype	NULL	Description
ID	NUMBER	NOT NULL	Internal key for the workload capture
NAME	VARCHAR2 (100)	NOT NULL	Name for the workload capture
DBID	NUMBER	NOT NULL	ID of the database in which the workload was captured

Column	Datatype	NULL	Description
DBNAME	VARCHAR2 (10)	NOT NULL	Name of the database in which the workload was captured
DBVERSION	VARCHAR2 (30)	NOT NULL	Version of the database in which the workload was captured
PARALLEL	VARCHAR2 (3)		Indicates whether the database in which the workload was captured is an Oracle RAC database (YES) or a single instance database (NO)
DIRECTORY	VARCHAR2 (30)	NOT NULL	Name of the directory object for workload capture
STATUS	VARCHAR2 (40)	NOT NULL	Current status of the workload capture: - IN PROGRESS - Workload capture is in progress - COMPLETED - Workload capture has completed successfully - FAILED - Workload capture was aborted due to errors encountered (see the COMMENT column for further details)
START_TIME	DATE	NOT NULL	Datetime when the capture began
END_TIME	DATE		Datetime when the capture completed or failed; NULL if the capture is still in progress
DURATION_SECS	NUMBER		Duration of the workload capture (in seconds)
START_SCN	NUMBER	NOT NULL	Start SCN value for this capture
END_SCN	NUMBER		End SCN value for this capture; NULL if the capture is still in progress
DEFAULT_ACTION	VARCHAR2 (30)	NOT NULL	Mode in which to apply workload capture filters: - INCLUDE - All the capture filters are treated as EXCLUSION filters, determining the workload that will not be captured. - EXCLUDE - All the capture filters are treated as INCLUSION FILTERS, determining the workload that will be captured.
FILTERS_USED	NUMBER		Number of filters that were used for this capture
CAPTURE_SIZE	NUMBER		Total size of workload capture
DBTIME	NUMBER		Total amount of database time (in microseconds) that has been recorded in this workload capture
DBTIME_TOTAL	NUMBER		Total amount of database time (in microseconds) across the entire database during the workload capture, including the part of the workload that was not captured.
USER_CALLS	NUMBER		Total number of user calls that have been recorded in this workload capture
USER_CALLS_TOTAL	NUMBER		Total number of user calls across the entire database during the workload capture, including the part of the workload that was not captured.
USER_CALLS_UNREPLAYABLE	NUMBER		Total number of user calls that will not be replayed in a subsequent replay of this workload capture
TRANSACTIONS	NUMBER		Total number of transactions that have been recorded in this workload capture
TRANSACTIONS_TOTAL	NUMBER		Total number of transactions across the entire database during the workload capture, including the part of the workload that was not captured.
CONNECTS	NUMBER		Total number of session connects that have been recorded in this workload capture
CONNECTS_TOTAL	NUMBER		Total number of session connects across the entire database during the workload capture, including the part of the workload that was not captured

Column	Datatype	NULL	Description
ERRORS	NUMBER		Total number of errors that have been recorded in this workload capture
AWR_DBID	NUMBER		Database ID of the AWR snapshots that correspond to this workload capture. For captures that were performed in the current database, this value is equal to the current database's DBID. For captures that were performed in other databases, this value will either be NULL or will be populated by <code>DBMS_WORKLOAD_CAPTURE.IMPORT_AWR()</code> .
AWR_BEGIN_SNAP	NUMBER		Begin snapshot ID of the AWR snapshots that correspond to this workload capture
AWR_END_SNAP	NUMBER		End snapshot ID of the AWR snapshots that correspond to this workload capture
AWR_EXPORTED	VARCHAR2(12)		Indicates whether the AWR snapshots that correspond to this workload capture have been exported using <code>DBMS_WORKLOAD_CAPTURE.EXPORT_AWR()</code> (YES) or not (NO), or whether AWR snapshots cannot be exported because the capture is still in progress, has run to completion successfully, or was done in a different database from which it was not exported (NOT POSSIBLE)
ERROR_CODE	NUMBER		Error code for this workload capture
ERROR_MESSAGE	VARCHAR2(300)		Error message for this workload capture
DIR_PATH	VARCHAR2(4000)	NOT NULL	Full directory path for the workload capture directory object
DIR_PATH_SHARED	VARCHAR2(10)	NOT NULL	Indicates whether the workload capture directory is shared by all the instances of the recording database (applicable only for Oracle RAC databases)
LAST_PROCESSED_VERSION	VARCHAR2(30)		Database version in which this capture was preprocessed using <code>DBMS_WORKLOAD_REPLAY.PROCESS_CAPTURE()</code> last; NULL if the capture has never been preprocessed
SQLSET_OWNER ¹	VARCHAR2(30)		User name of the SQL tuning set owner
SQLSET_NAME ¹	VARCHAR2(30)		Name of the SQL tuning set for this workload capture

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_WORKLOAD_CONNECTION_MAP

`DBA_WORKLOAD_CONNECTION_MAP` displays the connection mapping information for workload replay. Each row defines one connection mapping for a particular workload replay.

Column	Datatype	NULL	Description
REPLAY_ID	NUMBER	NOT NULL	ID of the replay (corresponds to <code>DBA_WORKLOAD_REPLAYS.ID</code>)
CONN_ID	NUMBER	NOT NULL	Key (ID) of the connection mapping table
CAPTURE_CONN	VARCHAR2(4000)	NOT NULL	Connection string that was used during capture
REPLAY_CONN	VARCHAR2(4000)		Connection string that should be used during replay

DBA_WORKLOAD_FILTERS

`DBA_WORKLOAD_FILTERS` displays all the workload filters that have been defined in the current database. In Oracle Database 11g, only workload filters of type `CAPTURE` are supported.

Column	Datatype	NULL	Description
TYPE	VARCHAR2 (30)	NOT NULL	Type of the workload filter
ID	NUMBER	NOT NULL	Sequence number of the workload filter
STATUS	VARCHAR2 (6)		Status of the workload filter: - NEW - This filter will be used by the next subsequent operation such as the next workload capture. - IN USE - This filter is currently being used by an operation that is in progress such as an active workload capture. - USED - This filter was used in the past by some operation such as a past workload capture.
SET_NAME ¹	VARCHAR2 (1000)		Name of the filter set to which the filter belongs
NAME	VARCHAR2 (100)	NOT NULL	Name of the workload filter
ATTRIBUTE	VARCHAR2 (100)	NOT NULL	Name of the attribute on which the filter is defined
VALUE	VARCHAR2 (4000)	NOT NULL	Value of the attribute on which the filter is defined. Wildcards such as % and _ are supported if the attribute is of string type.

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_WORKLOAD_REPLAY_DIVERGENCE

DBA_WORKLOAD_REPLAY_DIVERGENCE displays information about data/error divergence for a user call that has been replayed.

Column	Datatype	NULL	Description
REPLAY_ID	NUMBER	NOT NULL	ID (key) for the workload replay
TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Time that the divergence occurred
DIVERGENCE_TYPE	NUMBER	NOT NULL	Reserved for future use
IS_QUERY_DATA_DIVERGENCE	VARCHAR2 (1)		Indicates whether the data divergence is from the number of rows fetched by SELECT queries (Y) or not (N)
IS_DML_DATA_DIVERGENCE	VARCHAR2 (1)		Indicates whether the divergence is from the number of rows affected by INSERT, UPDATE, or DELETE SQL statements (Y) or not (N)
IS_ERROR_DIVERGENCE	VARCHAR2 (1)		Indicates whether the divergence is from errors seen during capture or replay (Y) or not (N)
IS_THREAD_FAILURE	VARCHAR2 (1)		Indicates whether the divergence is from sessions that failed during replay (Y) or not (N)
EXPECTED_ROW_COUNT	NUMBER		Number of rows fetched for SELECT queries or rows affected for INSERT, UPDATE, or DELETE SQL statements during capture
OBSERVED_ROW_COUNT	NUMBER		Actual number of rows fetched for SELECT queries or rows affected for INSERT, UPDATE, or DELETE SQL statements during replay
EXPECTED_ERROR#	NUMBER		Error number that was seen during capture (0 if the capture ran successfully)
OBSERVED_ERROR#	NUMBER		Actual error number seen during replay (0 if the replay ran successfully, 15566 (corresponding to ORA-15566) if the captured call could not be replayed)
STREAM_ID	NUMBER	NOT NULL	Stream ID of the session that reported the divergence
CALL_COUNTER	NUMBER	NOT NULL	Call counter of the user call that reported the divergence

Column	Datatype	NULL	Description
SQL_ID	VARCHAR2 (13)		SQL ID of the SQL that reported the divergence
SESSION_ID	NUMBER	NOT NULL	Session ID of the session that reported the divergence
SESSION_SERIAL#	NUMBER	NOT NULL	Captured session serial number of the session that reported the divergence
SERVICE	VARCHAR2 (64)		Service name of the session that reported the divergence
MODULE ¹	VARCHAR2 (48)		Module name of the session that reported the divergence
ACTION ¹	VARCHAR2 (32)		Action name of the session that reported the divergence

¹ The datatype of this column is VARCHAR2 (64) starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_WORKLOAD_REPLAYS

DBA_WORKLOAD_REPLAYS displays all the workload replays that have been performed in the current database. It also lists replays on which DBMS_WORKLOAD_REPLAY.GET_REPLAY_INFO() has been called. Each row contains information about one workload replay.

Column	Datatype	NULL	Description
ID	NUMBER	NOT NULL	Internal key for the workload replay
NAME	VARCHAR2 (100)	NOT NULL	Name of the workload replay
DBID	NUMBER	NOT NULL	ID of the database in which the workload was replayed
DBNAME	VARCHAR2 (10)	NOT NULL	Name of the database in which the workload was replayed
DBVERSION	VARCHAR2 (30)	NOT NULL	Version of the database in which the workload was replayed
PARALLEL	VARCHAR2 (3)		Indicates whether the database in which the workload was replayed was an Oracle RAC database (YES) or a single instance database (NO)
DIRECTORY	VARCHAR2 (30)	NOT NULL	Name of the directory object for the workload replay
CAPTURE_ID	NUMBER		ID of the capture (DBA_WORKLOAD_CAPTURES.ID) that was replayed
STATUS	VARCHAR2 (40)	NOT NULL	Current status of the workload replay: ■ PREPARE - Workload prepare has been started and is waiting for clients to join ■ IN PROGRESS - Workload replay is in progress ■ COMPLETED - Workload replay has successfully completed ■ CANCELLED - Workload replay or the workload prepare has been cancelled ■ FAILED - Workload replay was aborted due to errors encountered. See the COMMENTS column for further information.
PREPARE_TIME	DATE		Datetime at which the workload prepare started
START_TIME	DATE		Datetime when the replay began
END_TIME	DATE		Datetime when the replay completed or cancelled; NULL if the replay is still in progress
DURATION_SECS	NUMBER		Duration of the workload replay (in seconds)
NUM_CLIENTS	NUMBER	NOT NULL	Number of workload replay client processes that were used in this workload replay

Column	Datatype	NULL	Description
NUM_CLIENTS_DONE	NUMBER	NOT NULL	Number of workload replay client processes that have finished replay
FILTER_SET_NAME ¹	VARCHAR2 (1000)		Name of the filter set used for the replay
DEFAULT_ACTION	VARCHAR2 (30)	NOT NULL	Reserved for future use
SYNCHRONIZATION	VARCHAR2 (5)		Indicates whether recorded transaction semantics should be maintained (TRUE) or not (FALSE) When synchronization is on, the commit order observed during the original workload capture will be preserved. Every action that is replayed will be executed only after all of its dependent commits have been executed. Dependent commits are commits that were issued before the given action in the original workload capture. See Also: DBMS_WORKLOAD_REPLAY . PREPARE_REPLAY () in <i>Oracle Database PL/SQL Packages and Types Reference</i> for a detailed explanation of this replay parameter
CONNECT_TIME_SCALE	NUMBER	NOT NULL	Connection time scaling factor for captured streams during replay. The value is interpreted as a percentage. The default value of 100 means 100 percent. See Also: DBMS_WORKLOAD_REPLAY . PREPARE_REPLAY () in <i>Oracle Database PL/SQL Packages and Types Reference</i> for a detailed explanation of this replay parameter
THINK_TIME_SCALE	NUMBER	NOT NULL	Think time scaling factor for captured streams during replay. It scales the thinking time elapsed between two successive user calls from the same captured stream. The input is interpreted as a percentage. The default value of 100 means 100 percent. See Also: DBMS_WORKLOAD_REPLAY . PREPARE_REPLAY () in <i>Oracle Database PL/SQL Packages and Types Reference</i> for a detailed explanation of this replay parameter
THINK_TIME_AUTO_CORRECT	VARCHAR2 (5)		Indicates whether the think time should be automatically corrected between calls (TRUE) or not (FALSE) A value of TRUE either reduces think time if replay goes slower than capture or increases think time if replay goes faster than capture. A value of FALSE results in no action. See Also: DBMS_WORKLOAD_REPLAY . PREPARE_REPLAY () in <i>Oracle Database PL/SQL Packages and Types Reference</i> for a detailed explanation of this replay parameter
USER_CALLS	NUMBER		Total number of user calls replayed
DBTIME	NUMBER		Accumulated database time for the replay
NETWORK_TIME	NUMBER		Accumulated network time for the replay
THINK_TIME	NUMBER		Accumulated think time for the replay
ELAPSED_TIME_DIFF	NUMBER		Reserved for future use
AWR_DBID	NUMBER		Database ID of the AWR snapshots that correspond to this workload replay. For replays that were performed in the current database, this value is equal to the current database's DBID. For replays that were performed in other databases, this value will either be NULL or will be populated by DBMS_WORKLOAD_REPLAY . IMPORT_AWR () .
AWR_BEGIN_SNAP	NUMBER		Begin snapshot ID of the AWR snapshots that correspond to this workload replay
AWR_END_SNAP	NUMBER		End snapshot ID of the AWR snapshots that correspond to this workload replay

Column	Datatype	NULL	Description
AWR_EXPORTED	VARCHAR2 (12)		Indicates whether the AWR snapshots that correspond to this workload replay have been exported using DBMS_WORKLOAD_REPLAY.EXPORT_AWR () (YES) or not (NO), or whether AWR snapshots cannot be exported because the replay is still in progress, has run to completion successfully, or was done in a different database from which it was not exported (NOT POSSIBLE)
ERROR_CODE	NUMBER		Error code for this workload replay
ERROR_MESSAGE	VARCHAR2 (300)		Error message for this workload replay
DIR_PATH	VARCHAR2 (4000)	NOT NULL	Full directory path for the replay directory object
SQLSET_OWNER ¹	VARCHAR2 (30)		User name of the SQL tuning set owner
SQLSET_NAME ¹	VARCHAR2 (30)		Name of the SQL tuning set for this workload replay

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_XML_INDEXES

DBA_XML_INDEXES describes all XML indexes in the database. Its columns are the same as those in ALL_XML_INDEXES.

See Also: ["ALL_XML_INDEXES"](#) on page 3-106

DBA_XML_SCHEMAS

DBA_XML_SCHEMAS describes all registered XML schemas in the database. Its columns are the same as those in ALL_XML_SCHEMAS.

See Also: ["ALL_XML_SCHEMAS"](#) on page 3-107

DBA_XML_TAB_COLS

DBA_XML_TAB_COLS describes the columns of all XML tables in the database. Its columns are the same as those in ALL_XML_TAB_COLS.

See Also: ["ALL_XML_TAB_COLS"](#) on page 3-108

DBA_XML_TABLES

DBA_XML_TABLES describes all XML tables in the database. Its columns are the same as those in ALL_XML_TABLES.

See Also: ["ALL_XML_TABLES"](#) on page 3-109

DBA_XML_VIEW_COLS

DBA_XML_VIEW_COLS describes the columns of all XML views in the database. Its columns are the same as those in ALL_XML_VIEW_COLS.

See Also: ["ALL_XML_VIEW_COLS"](#) on page 3-109

DBA_XML_VIEWS

DBA_XML_VIEWS describes all XML views in the database. Its columns are the same as those in ALL_XML_VIEWS.

See Also: ["ALL_XML_VIEWS"](#) on page 3-110

DBA_XSTREAM_ADMINISTRATOR

DBA_XSTREAM_ADMINISTRATOR displays information about the users who have been granted privileges to be XStream administrators by procedures in the DBMS_XSTREAM_AUTH package.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (30)	NOT NULL	Name of the user who has been granted privileges to be an XStream administrator
LOCAL_PRIVILEGES	VARCHAR2 (3)		Indicates whether the user has been granted local XStream administrator privileges (YES) or not (NO)
ACCESS_FROM_REMOTE	VARCHAR2 (3)		Indicates whether the user can be used for remote XStream administration through a database link (YES) or not (NO)

Note: The DBA_XSTREAM_ADMINISTRATOR view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_XSTREAM_INBOUND

DBA_XSTREAM_INBOUND displays information about all XStream inbound servers in the database. Its columns are the same as those in ALL_XSTREAM_INBOUND.

See Also: ["ALL_XSTREAM_INBOUND"](#) on page 3-110

DBA_XSTREAM_INBOUND_PROGRESS

DBA_XSTREAM_INBOUND_PROGRESS displays information about the progress made by all XStream inbound servers in the database. Its columns are the same as those in ALL_XSTREAM_INBOUND_PROGRESS.

See Also: ["ALL_XSTREAM_INBOUND_PROGRESS"](#) on page 3-111

DBA_XSTREAM_OUT_SUPPORT_MODE

DBA_XSTREAM_OUT_SUPPORT_MODE displays information about the level of capture process support for the tables in the database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)		Table owner
OBJECT_NAME	VARCHAR2 (30)		Table name

Column	Datatype	NULL	Description
SUPPORT_MODE	VARCHAR2 (6)		Capture process support level for the table: - FULL - A capture process can capture changes made to all of the columns in the table. - ID KEY - A capture process can capture changes made to the key columns and any other columns in the table that are supported by the capture process, except for LOB, LONG, LONG RAW, and XMLType columns. - NONE - A capture process cannot capture changes made to any columns in the table.

Note: The DBA_XSTREAM_OUT_SUPPORT_MODE view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

DBA_XSTREAM_OUTBOUND

DBA_XSTREAM_OUTBOUND displays information about all XStream outbound servers in the database. Its columns are the same as those in ALL_XSTREAM_OUTBOUND.

See Also: ["ALL_XSTREAM_OUTBOUND"](#) on page 3-112

DBA_XSTREAM_OUTBOUND_PROGRESS

DBA_XSTREAM_OUTBOUND_PROGRESS displays information about the progress made by all XStream outbound servers in the database. Its columns are the same as those in ALL_XSTREAM_OUTBOUND_PROGRESS.

See Also: ["ALL_XSTREAM_OUTBOUND_PROGRESS"](#) on page 3-113

DBA_XSTREAM_RULES

DBA_XSTREAM_RULES displays information about all XStream rules in the database. Its columns are the same as those in ALL_XSTREAM_RULES.

See Also: ["ALL_XSTREAM_RULES"](#) on page 3-113

DBFS_CONTENT

DBFS_CONTENT displays all the path items from all available content stores in the system.

Column	Datatype	NULL	Description
STORE	VARCHAR2 (256)		Name of store
MOUNT	VARCHAR2 (256)		Location at which instance of store is mounted
PATHNAME	VARCHAR2 (1024)		Name of path to item
PATHTYPE	VARCHAR2 (32)		Type of path item (see DBMS_DBFS_CONTENT Constants - Path Name Types)
FILEDATA	BLOB		BLOB locator that can be used to access data in the path item
STD_ACCESS_TIME	TIMESTAMP (6)		Time of last access of a pathname's contents

Column	Datatype	NULL	Description
STD_ACL	VARCHAR2 (1024)		Access Control List (in standard ACL syntax)
STD_CHANGE_TIME	TIMESTAMP (6)		Time of last change to the path name
STD_CHILDREN	NUMBER		Number of child directories/folders a directory/folder path has (this property should be available in providers that support the FEATURE_FOLDERS feature)
STD_CONTENT_TYPE	VARCHAR2 (1024)		One or more client-supplied mime-types (in standard RFC syntax) describing the path name which is typically of TYPE_FILE. The content type is not necessarily interpreted by the store.
STD_CREATION_TIME	TIMESTAMP (6)		Time at which the item was created. Once set, this value remains the same for the lifetime of the path name.
STD_DELETED	NUMBER		Set to a nonzero number if the path name has been soft-deleted but not yet purged (see DBMS_DBFS_CONTENT Constants - Store Features)
STD_GUID	NUMBER		Store-specific unique identifier for a path name. Clients must not depend on the GUID being unique across different stores, but a given (store-name, store-specific-pathname) has a stable and unique GUID for its lifetime.
STD_MODIFICATION_TIME	TIMESTAMP (6)		Time of last change to the data associated with a path name. Changes to the content of a TYPE_FILE or TYPE_REFERENCE path, the referent of the TYPE_LINK path, and addition or deletion of immediate children in a TYPE_DIRECTORY path, all constitute data changes.
STD_OWNER	VARCHAR2 (32)		Client-supplied (or implicit) owner name for the path name
STD_PARENT_GUID	NUMBER		Store-specific unique identifier for the parent of a path name. Clients must not depend on the GUID being unique across different stores, but a given (store-name, store-specific-pathname) has a stable and unique GUID for its lifetime. The GUID of the parent of this path name (that is that std_parent_guid(pathname) == std_guid(parent(pathname))).
STD_REFERENT	VARCHAR2 (1024)		Content of the symbolic link of a TYPE_LINK path, otherwise NULL. The STD_REFERENT can be an arbitrary string and must not necessarily be interpreted as path name by clients (or such interpretation should be done with great care).
OPT_HASH_TYPE	VARCHAR2 (32)		Type of hash provided in the OPT_HASH_VALUE property (see DBMS_CRYPTO for possible options)
OPT_HASH_VALUE	VARCHAR2 (128)		Hash value of type OPT_HASH_TYPE describing the content of the path name
OPT_LOCK_COUNT	NUMBER		Number of compatible locks placed on a path name. If different principals are allowed to place compatible (read) locks on a path, the OPT_LOCKER must specify all lockers with repeats so that lock counts can be correctly maintained.
OPT_LOCK_DATA	VARCHAR2 (128)		Client-supplied user-data associated with a user-lock, uninterpreted by the store
OPT_LOCKER	VARCHAR2 (128)		One or more implicit or client-specified principals that applied a user-lock on a path name
OPT_LOCK_STATUS	NUMBER		One of the (LOCK_READ_ONLY, LOCK_WRITE_ONLY, LOCK_READ_WRITE) values describing the type of lock currently applied on a path name
OPT_VERSION	NUMBER		Sequence number for linear versioning of a path name
OPT_VERSION_PATH	VARCHAR2 (1024)		Version path name for hierarchical versioning of a path name

Column	Datatype	NULL	Description
OPT_CONTENT_ID	RAW (128)		A provider-generated store-specific unique contentID in the form of a string for a file element (that may optionally not be associated with a path (see FEATURE_CONTENT_ID and FEATURE_LAZY_PATH in DBMS_DBFS_CONTENT Constants - Store Features)

DBFS_CONTENT_PROPERTIES

DBFS_CONTENT_PROPERTIES displays all the property/value pairs for all path items in all content stores in the system.

Column	Datatype	NULL	Description
STORE	VARCHAR2 (256)		Name of store
MOUNT	VARCHAR2 (256)		Location at which instance of store is mounted
PATHNAME	VARCHAR2 (1024)		Name of path to item
PROPERTY_NAME	VARCHAR2 (32)		Name of the property
PROPERTY_VALUE	VARCHAR2 (1024)		Value of the property
PROPERTY_TYPE	NUMBER		PL/SQL typecode for the property value

DBMS_ALERT_INFO

DBMS_ALERT_INFO describes registered alerts.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)	NOT NULL	Name of the alert
SID	VARCHAR2 (30)	NOT NULL	Session ID of a session waiting for this alert
CHANGED	VARCHAR2 (1)		Boolean flag to indicate that an alert has been signaled. Y: alert signaled, N: no alert.
MESSAGE	VARCHAR2 (1800)		Optional message passed by signaler

DBMS_LOCK_ALLOCATED

DBMS_LOCK_ALLOCATED describes user-allocated locks.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (128)	NOT NULL	Name of the lock
LOCKID	NUMBER (38)		Lock identifier number
EXPIRATION	DATE		Planned lock expiration date (updates whenever the allocation procedure is run)

DEPTREE

This view, created by `utldtree.sql`, contains information on the object dependency tree. For user `SYS`, this view displays shared cursors (and only shared cursors) that depend on the object. For all other users, it displays objects other than shared cursors. Other users can access `SYS.DEPTREE` for information on shared cursors.

Column	Datatype	NULL	Description
NESTED_LEVEL	NUMBER		Nesting level in the dependency tree

Column	Datatype	NULL	Description
TYPE	VARCHAR2 (15)		Object type
OWNER	VARCHAR2 (30)		Object owner
NAME	VARCHAR2 (1002)		Object name
SEQ#	NUMBER		Sequence number in the dependency tree. Used for ordering queries. See Also: "IDEPTREE" on page 6-48

DICT

DICT is a synonym for DICTIONARY.

See Also: ["DICTIONARY"](#) on page 6-41

DICT_COLUMNS

DICT_COLUMNS contains descriptions of columns in data dictionary tables and views.

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2 (30)		Name of the object that contains the column
COLUMN_NAME	VARCHAR2 (30)		Name of the column
COMMENTS	VARCHAR2 (4000)		Text comment on the column

DICTIONARY

DICTIONARY contains descriptions of data dictionary tables and views.

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2 (30)		Name of the object
COMMENTS	VARCHAR2 (4000)		Text comment on the object

DM_USER_MODELS

DM_USER_MODELS displays information about the models in the user's schema.

Column	Datatype	NULL	Description
NAME	VARCHAR2 (30)	NOT NULL	Name of the model

Column	Datatype	NULL	Description
FUNCTION_NAME	VARCHAR2 (30)		Model function: ■ <code>association</code> - Association is a descriptive mining function. An association model identifies relationships and the probability of their occurrence within a data set. ■ <code>attribute_importance</code> - Attribute Importance is a predictive mining function. An attribute importance model identifies the relative importance of an attribute in predicting a given outcome. ■ <code>classification</code> - Classification is a predictive mining function. A classification model uses historical data to predict new discrete or categorical data. The <code>classification</code> function can also be used for anomaly detection. In this case, the SVM algorithm with a null target is used (One-Class SVM). ■ <code>clustering</code> - Clustering is a descriptive mining function. A clustering model identifies natural groupings within a data set. ■ <code>feature_extraction</code> - Feature Extraction is a descriptive mining function. A feature extraction model creates an optimized data set on which to base a model. ■ <code>regression</code> - Regression is a predictive mining function. A regression model uses historical data to predict new continuous, numerical data.
ALGORITHM_NAME	VARCHAR2 (30)		Algorithm used by the model: ■ <code>algo_name</code> - Setting that specifies the algorithm used by the model. ■ <code>asso_max_rule_length</code> - Setting that specifies the maximum length of a rule used by an association model. ■ <code>asso_min_confidence</code> - Setting that specifies the minimum confidence for an association model. ■ <code>asso_min_support</code> - Setting that specifies the minimum support for an association model. ■ <code>clas_cost_table_name</code> - Setting that specifies the name of the cost matrix table for a classification model. ■ <code>clas_priors_table_name</code> - Setting that specifies the name of the prior probability table for NB and ABN models. Decision Tree is the only classification algorithm that does not use priors. For SVM classification models, this setting specifies the name of a table of weights. ■ <code>clus_num_clusters</code> - Setting that specifies the number of clusters for a clustering model. ■ <code>feat_num_features</code> - Setting that specifies the number of features for a feature selection model.
CREATION_DATE	DATE	NOT NULL	Date on which the model was created
BUILD_DURATION	NUMBER		Duration of the model build process
TARGET_ATTRIBUTE	VARCHAR2 (30)		Attribute designated as the target of a classification model
MODEL_SIZE	NUMBER		Size of the model (in megabytes)

DOCUMENT_LINKS

DOCUMENT_LINKS provides system information about Oracle XML DB document links in Oracle XML DB Repository documents. When an XML document that includes XLink or XInclude links is added to the repository, these links can be mapped to document links, which are tracked using view DOCUMENT_LINKS.

Column	Datatype	NULL	Description
SOURCE_ID	RAW (16)		The source resource OID
TARGET_ID	RAW (16)		The target resource OID
TARGET_PATH	VARCHAR2 (4000)		This column is always NULL. It is reserved for future use.
LINK_TYPE	VARCHAR2 (8)		The document link type: Hard or Weak
LINK_FORM	VARCHAR2 (8)		Whether the original link was of form XLink or XInclude
SOURCE_TYPE	VARCHAR2 (17)		Whether the link is contained in Resource Content or Resource Metadata

See Also: *Oracle XML DB Developer's Guide* for information about using this view

ERROR_SIZE

ERROR_SIZE is accessed to create ["DBA_OBJECT_SIZE"](#) on page 5-63 and ["USER_OBJECT_SIZE"](#) on page 6-88.

EXCEPTIONS

EXCEPTIONS contains information on violations of integrity constraints. This table is created by the `utlexcpt.sql` script.

Column	Datatype	NULL	Description
ROW_ID	ROWID		Row that caused the violation
OWNER	VARCHAR2 (30)		Owner of the table
TABLE_NAME	VARCHAR2 (30)		Name of the table
CONSTRAINT	VARCHAR2 (30)		Integrity constraint that was violated

FLASHBACK_TRANSACTION_QUERY

FLASHBACK_TRANSACTION_QUERY displays information about all flashback transaction queries in the database. The database must have at least minimal supplemental logging enabled to avoid unpredictable behavior.

Column	Datatype	NULL	Description
XID	RAW (8)		Transaction identifier
START_SCN	NUMBER		Transaction start system change number (SCN)
START_TIMESTAMP	DATE		Transaction start timestamp
COMMIT_SCN	NUMBER		Transaction commit system change number; NULL for active transactions
COMMIT_TIMESTAMP	DATE		Transaction commit timestamp; NULL for active transactions

GLOBAL_NAME

Column	Datatype	NULL	Description
LOGON_USER	VARCHAR2 (30)		Logon user for the transaction
UNDO_CHANGE#	NUMBER		Undo system change number (1 or higher)
OPERATION	VARCHAR2 (32)		Forward-going DML operation performed by the transaction: ■ D - Delete ■ I - Insert ■ U - Update ■ B ■ UNKNOWN
TABLE_NAME	VARCHAR2 (256)		Name of the table to which the DML applies
TABLE_OWNER	VARCHAR2 (32)		Owner of the table to which the DML applies
ROW_ID	VARCHAR2 (19)		Rowid of the row that was modified by the DML
UNDO_SQL	VARCHAR2 (4000)		SQL to undo the DML indicated by OPERATION

See Also: *Oracle Database Utilities* for information on how to enable minimal supplemental logging

GLOBAL_NAME

GLOBAL_NAME contains one row that displays the global name of the current database.

Column	Datatype	NULL	Description
GLOBAL_NAME	VARCHAR2 (4000)		Global name of the database

HS_ALL_CAPS

HS_ALL_CAPS contains information about all of the capabilities (that is, features) associated with non-Oracle (FDS) data stores.

Column	Datatype	NULL	Description
CAP_NUMBER	NUMBER		Capability number
CONTEXT	NUMBER		Context in which this capability is applicable
TRANSLATION	VARCHAR2 (255)		Valid for functions; contains translation to FDS dialect
ADDITIONAL_INFO	NUMBER		Flag for internal use
FDS_CLASS_NAME	VARCHAR2 (30)		Name of the FDS Class
FDS_INST_NAME	VARCHAR2 (30)		Name of the FDS instance

HS_ALL_DD

HS_ALL_DD contains data dictionary information about non-Oracle (FDS) data stores.

Column	Datatype	NULL	Description
DD_TABLE_NAME	VARCHAR2 (30)		Data dictionary table name
TRANSLATION_TYPE	CHAR (1)		T = Translation, M = Mimic
TRANSLATION_TEXT	VARCHAR2 (4000)		SQL statement containing the mapping
FDS_CLASS_NAME	VARCHAR2 (30)		Name of the FDS Class
FDS_INST_NAME	VARCHAR2 (30)		Name of the FDS instance

Column	Datatype	NULL	Description
DD_TABLE_DESC	VARCHAR2 (255)		Description of the Oracle data dictionary table

HS_ALL_INITS

HS_ALL_INITS contains initialization parameter information about non-Oracle (FDS) data stores.

Column	Datatype	NULL	Description
INIT_VALUE_NAME	VARCHAR2 (64)		Name of the initialization parameter
INIT_VALUE	VARCHAR2 (255)		Value of the initialization parameter
INIT_VALUE_TYPE	VARCHAR2 (1)		Environment variable (T or F). T means this is an environment variable; F means do not set as an environment variable
FDS_CLASS_NAME	VARCHAR2 (30)		Name of the FDS Class
FDS_INST_NAME	VARCHAR2 (30)		Name of the FDS instance

HS_BASE_CAPS

HS_BASE_CAPS contains information about base capability (that is, base features) of the non-Oracle (FDS) data store.

Column	Datatype	NULL	Description
CAP_NUMBER	NUMBER	NOT NULL	Capability number
CAP_DESCRIPTION	VARCHAR2 (255)		Description of the capability

HS_BASE_DD

HS_BASE_DD displays information from the base data dictionary translation table.

Column	Datatype	NULL	Description
DD_TABLE_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
DD_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the Oracle data dictionary table
DD_TABLE_DESC	VARCHAR2 (255)		Description of the Oracle data dictionary table

HS_CLASS_CAPS

HS_CLASS_CAPS contains information about the class-specific (driver) capabilities belonging to the non-Oracle (FDS) data store.

Column	Datatype	NULL	Description
CAP_NUMBER	NUMBER	NOT NULL	Capability number
CAP_DESCRIPTION	VARCHAR2 (255)		Capability description
CONTEXT	NUMBER		Flag indicating the context in which the capability is enabled
TRANSLATION	VARCHAR2 (255)		Valid for functions; contains translation to FDS dialect
ADDITIONAL_INFO	NUMBER		Additional flags for internal use
FDS_CLASS_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS Class

Column	Datatype	NULL	Description
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

HS_CLASS_DD

HS_CLASS_DD displays information from the non-Oracle data store (FDS) class-specific data dictionary translations.

Column	Datatype	NULL	Description
DD_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the Oracle data dictionary table
DD_TABLE_DESC	VARCHAR2 (255)		Description of the Oracle data dictionary table
TRANSLATION_TYPE	CHAR (1)	NOT NULL	T = Translation, M = Mimic
TRANSLATION_TEXT	VARCHAR2 (4000)		SQL statement containing the mapping
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS Class
DD_TABLE_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

HS_CLASS_INIT

HS_CLASS_INIT displays information about the non-Oracle (FDS) class-specific initialization parameters.

Column	Datatype	NULL	Description
INIT_VALUE_NAME	VARCHAR2 (64)	NOT NULL	Name of the initialization parameter
INIT_VALUE	VARCHAR2 (255)	NOT NULL	Value of the initialization parameter
INIT_VALUE_TYPE	VARCHAR2 (1)	NOT NULL	Environment variable (T or F). T means this is an environment variable; F means do not set as an environment variable
FDS_CLASS_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS Class
FDS_CLASS_INIT_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

HS_FDS_CLASS

HS_FDS_CLASS contains information about legal non-Oracle (FDS) classes.

Column	Datatype	NULL	Description
FDS_CLASS_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS class (for example, ODBC, DB2)
FDS_CLASS_COMMENTS	VARCHAR2 (255)		Text description of the non-Oracle class
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

HS_FDS_INST

HS_FDS_INST contains information about non-Oracle (FDS) instances.

Column	Datatype	NULL	Description
FDS_INST_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS instance
FDS_INST_COMMENTS	VARCHAR2 (255)		Text description of the non-Oracle instance
FDS_CLASS_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS class
FDS_INST_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

HS_INST_CAPS

HS_INST_CAPS contains information about instance-specific capabilities (that is, features).

Column	Datatype	NULL	Description
CAP_NUMBER	NUMBER	NOT NULL	Capability number
CAP_DESCRIPTION	VARCHAR2 (255)		Capability description
CONTEXT	NUMBER		Context in which this capability is applicable
TRANSLATION	VARCHAR2 (255)		Valid for functions; contains translation to FDS dialect
ADDITIONAL_INFO	NUMBER		Additional flags for internal use
FDS_CLASS_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS class (for example, ODBC, DB2)
FDS_INST_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS instance
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_INST_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

HS_INST_DD

HS_INST_DD displays information from the non-Oracle (FDS) instance-specific data dictionary translations.

Column	Datatype	NULL	Description
DD_TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the Oracle data dictionary table
DD_TABLE_DESC	VARCHAR2 (255)		Description of the Oracle data dictionary table
TRANSLATION_TYPE	CHAR (1)	NOT NULL	T = Translation, M = Mimic
TRANSLATION_TEXT	VARCHAR2 (4000)		SQL statement containing the mapping
FDS_CLASS_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS class (for example, ODBC, DB2)
FDS_INST_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS instance
DD_TABLE_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_INST_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

HS_INST_INIT

HS_INST_INIT contains information about the non-Oracle (FDS) instance-specific initialization parameters.

IDEPTREE

Column	Datatype	NULL	Description
INIT_VALUE_NAME	VARCHAR2 (64)	NOT NULL	Name of the initialization parameter
INIT_VALUE	VARCHAR2 (255)	NOT NULL	Value of the initialization parameter
INIT_VALUE_TYPE	VARCHAR2 (1)	NOT NULL	Environment variable (T or F). T means this is an environment variable; F means do not set as an environment variable
FDS_CLASS_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS class (for example: ODBC, DB2)
FDS_INST_NAME	VARCHAR2 (30)	NOT NULL	Name of the FDS instance
FDS_INST_INIT_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_INST_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

IDEPTREE

This view, created by `utldtree.sql`, lists the indented dependency tree. It is a pre-sorted, pretty-print version of DEPTREE.

Column	Datatype	NULL	Description
NESTED_LEVEL	NUMBER		Nesting level in the dependency tree
TYPE	VARCHAR2 (15)		Object type
OWNER	VARCHAR2 (30)		Object owner
NAME	VARCHAR2 (1002)		Object name

IND

IND is a synonym for USER_INDEXES.

See Also: ["USER_INDEXES"](#) on page 6-81

INDEX_HISTOGRAM

INDEX_HISTOGRAM contains information from the `ANALYZE INDEX ... VALIDATE STRUCTURE` statement.

Note: The `ANALYZE INDEX ... VALIDATE STRUCTURE OFFLINE` statement must be used in order to collect statistics.

Column	Datatype	NULL	Description
REPEAT_COUNT	NUMBER		Number of times that one or more index keys is repeated in the table
KEYS_WITH_REPEAT_COUNT	NUMBER		Number of index keys that are repeated that many times

INDEX_STATS

INDEX_STATS stores information from the last `ANALYZE INDEX ... VALIDATE STRUCTURE` statement.

Note: The ANALYZE INDEX ... VALIDATE STRUCTURE OFFLINE statement must be used in order to collect statistics

Column	Datatype	NULL	Description
HEIGHT	NUMBER		Height of the B-Tree
BLOCKS	NUMBER	NOT NULL	Blocks allocated to the segment
NAME	VARCHAR2 (30)	NOT NULL	Name of the index
PARTITION_NAME	VARCHAR2 (30)		Name of the partition of the index which was analyzed. If the index is not partitioned, NULL is returned.
LF_ROWS	NUMBER		Number of leaf rows (values in the index)
LF_BLKs	NUMBER		Number of leaf blocks in the B-Tree
LF_ROWS_LEN	NUMBER		Sum of the lengths of all the leaf rows
LF_BLK_LEN	NUMBER		Usable space in a leaf block
BR_ROWS	NUMBER		Number of branch rows in the B-Tree
BR_BLKs	NUMBER		Number of branch blocks in the B-Tree
BR_ROWS_LEN	NUMBER		Sum of the lengths of all the branch blocks in the B-Tree
BR_BLK_LEN	NUMBER		Usable space in a branch block
DEL_LF_ROWS	NUMBER		Number of deleted leaf rows in the index
DEL_LF_ROWS_LEN	NUMBER		Total length of all deleted rows in the index
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index (may include rows that have been deleted)
MOST_REPEATED_KEY	NUMBER		How many times the most repeated key is repeated (may include rows that have been deleted)
BTREE_SPACE	NUMBER		Total space currently allocated in the B-Tree
USED_SPACE	NUMBER		Total space that is currently being used in the B-Tree
PCT_USED	NUMBER		Percent of space allocated in the B-Tree that is being used
ROWS_PER_KEY	NUMBER		Average number of rows per distinct key (this figure is calculated without consideration of deleted rows)
BLKS_GETS_PER_ACCESS	NUMBER		Expected number of consistent mode block reads per row, assuming that a randomly chosen row is accessed using the index. Used to calculate the number of consistent reads that will occur during an index scan.
PRE_ROWS	NUMBER		Number of prefix rows (values in the index)
PRE_ROWS_LEN	NUMBER		Sum of lengths of all prefix rows
OPT_CMPR_COUNT	NUMBER		Optimal key compression length
OPT_CMPR_PCTSAVE	NUMBER		Corresponding space savings after an ANALYZE

LOGSTDBY_UNSUPPORTED_TABLES

LOGSTDBY_UNSUPPORTED_TABLES is a synonym for DBA_LOGSTDBY_UNSUPPORTED_TABLE.

See Also: ["DBA_LOGSTDBY_UNSUPPORTED_TABLE"](#) on page 5-58

MAP_OBJECT

MAP_OBJECT is a global temporary table that displays the hierarchical arrangement of storage containers for objects. Each row in the table represents a level in the hierarchy.

Column	Datatype	NULL	Description
OBJECT_NAME	VARCHAR2 (2000)		Name of the object
OBJECT_OWNER	VARCHAR2 (2000)		Owner of the object
OBJECT_TYPE	VARCHAR2 (2000)		Object type
FILE_MAP_IDX	NUMBER		File index (corresponds to FILE_MAP_IDX in V\$MAP_FILE)
DEPTH	NUMBER		Element depth within the I/O stack
ELEM_IDX	NUMBER		Index corresponding to the element
CU_SIZE	NUMBER		Contiguous set of logical blocks of the file (in HKB units) that is resident contiguously on the element
STRIDE	NUMBER		Number of HKB between contiguous units (CU) in the file that are contiguous on this element. Used in RAID5 and striped files.
NUM_CU	NUMBER		Number of contiguous units that are adjacent to each other on this element that are separated by STRIDE HKB in the file. In RAID5, the number of contiguous units also include the parity stripes.
ELEM_OFFSET	NUMBER		Element offset (in HKB units)
FILE_OFFSET	NUMBER		Offset (in HKB units) from the start of the file to the first byte of the contiguous units
DATA_TYPE	VARCHAR2 (2000)		Datatype (DATA, PARITY, or DATA AND PARITY)
PARITY_POS	NUMBER		Position of the parity. Only for RAID5. This field is needed to distinguish the parity from the data part.
PARITY_PERIOD	NUMBER		Parity period. Only for RAID5.

NLS_DATABASE_PARAMETERS

NLS_DATABASE_PARAMETERS lists permanent NLS parameters of the database.

Column	Datatype	NULL	Description
PARAMETER	VARCHAR2 (30)	NOT NULL	Parameter name
VALUE	VARCHAR2 (40)		Parameter value

NLS_INSTANCE_PARAMETERS

NLS_INSTANCE_PARAMETERS lists NLS parameters of the instance.

Column	Datatype	NULL	Description
PARAMETER	VARCHAR2 (30)		Parameter name
VALUE	VARCHAR2 (40)		Parameter value

NLS_SESSION_PARAMETERS

NLS_SESSION_PARAMETERS lists NLS parameters of the user session.

Column	Datatype	NULL	Description
PARAMETER	VARCHAR2 (30)		Parameter name
VALUE	VARCHAR2 (40)		Parameter value

OBJ

OBJ is a synonym for USER_OBJECTS.

See Also: ["USER_OBJECTS"](#) on page 6-88

PATH_VIEW

PATH_VIEW contains one row for each unique path to access a resource in the Oracle XML DB repository.

Column	Datatype	NULL	Description
PATH	VARCHAR2 (1024)		An (absolute) path to repository resource RES
RES	XMLTYPE(XMLSchema "http://xmlns.oracle.com/xdb/XDBResource.xsd" Element "Resource")		The resource referred to by the PATH column
LINK	XMLTYPE		Link property
RESID	RAW (16)		Resource OID

See Also: *Oracle XML DB Developer's Guide* for information about using this view

PLAN_TABLE

PLAN_TABLE is automatically created as a global temporary table to hold the output of an EXPLAIN PLAN statement for all users. PLAN_TABLE is the default sample output table into which the EXPLAIN PLAN statement inserts rows describing execution plans.

While a PLAN_TABLE table is automatically set up for each user, you can use the SQL script `utlxpplan.sql` to manually create a local PLAN_TABLE in your schema.

Column	Datatype	NULL	Description
STATEMENT_ID	VARCHAR2 (30)		Value of the optional STATEMENT_ID parameter specified in the EXPLAIN PLAN statement
PLAN_ID	NUMBER		Unique identifier of a plan in the database
TIMESTAMP	DATE		Date and time when the EXPLAIN PLAN statement was generated
REMARKS	VARCHAR2 (4000)		Any comment (of up to 4000 bytes) you want to associate with each step of the explained plan. This column is used to indicate whether an outline or SQL Profile was used for the query. If you need to add or change a remark on any row of the PLAN_TABLE, then use the UPDATE statement to modify the rows of the PLAN_TABLE.

Column	Datatype	NULL	Description
OPERATION	VARCHAR2 (30)		Name of the internal operation performed in this step. In the first row generated for a statement, the column contains one of the following values: - DELETE STATEMENT - INSERT STATEMENT - SELECT STATEMENT - UPDATE STATEMENT
OPTIONS	VARCHAR2 (255)		A variation on the operation described in the OPERATION column
OBJECT_NODE	VARCHAR2 (128)		Name of the database link used to reference the object (a table name or view name). For local queries using parallel execution, this column describes the order in which output from operations is consumed.
OBJECT_OWNER	VARCHAR2 (30)		Owner of the table or index
OBJECT_NAME	VARCHAR2 (30)		Name of the table or index
OBJECT_ALIAS	VARCHAR2 (65)		Unique alias of a table or view in a SQL statement. For indexes, it is the object alias of the underlying table.
OBJECT_INSTANCE	NUMBER (38)		Number corresponding to the ordinal position of the object as it appears in the original statement. The numbering proceeds from left to right, outer to inner with respect to the original statement text. View expansion results in unpredictable numbers.
OBJECT_TYPE	VARCHAR2 (30)		Modifier that provides descriptive information about the object; for example, NON-UNIQUE for indexes
OPTIMIZER	VARCHAR2 (255)		Current mode of the optimizer
SEARCH_COLUMNS	NUMBER		Not currently used
ID	NUMBER (38)		A number assigned to each step in the execution plan
PARENT_ID	NUMBER (38)		ID of the next execution step that operates on the output of the ID step
DEPTH	NUMBER (38)		Depth of the operation in the row source tree that the plan represents. The value can be used for indenting the rows in a plan table report.
POSITION	NUMBER (38)		For the first row of output, this indicates the optimizer's estimated cost of executing the statement. For the other rows, it indicates the position relative to the other children of the same parent.
COST	NUMBER (38)		Cost of the operation as estimated by the optimizer's query approach. Cost is not determined for table access operations. The value of this column does not have any particular unit of measurement; it is merely a weighted value used to compare costs of execution plans. The value of this column is a function of the CPU_COST and IO_COST columns.
CARDINALITY	NUMBER (38)		Estimate by the query optimization approach of the number of rows accessed by the operation
BYTES	NUMBER (38)		Estimate by the query optimization approach of the number of bytes accessed by the operation

Column	Datatype	NULL	Description
OTHER_TAG	VARCHAR2 (255)		Describes the contents of the OTHER column: - SERIAL - Serial execution. Currently, SQL is not loaded in the OTHER column for this case. - SERIAL_FROM_REMOTE - Serial execution at a remote site. - PARALLEL_FROM_SERIAL - Serial execution. Output of step is partitioned or broadcast to parallel execution servers. - PARALLEL_TO_SERIAL - Parallel execution. Output of step is returned to serial query coordinator (QC) process. - PARALLEL_TO_PARALLEL - Parallel execution. Output of step is repartitioned to second set of parallel execution servers. - PARALLEL_COMBINED_WITH_PARENT - Parallel execution; Output of step goes to next step in same parallel process. No interprocess communication to parent. - PARALLEL_COMBINED_WITH_CHILD - Parallel execution. Input of step comes from prior step in same parallel process. No interprocess communication from child.
PARTITION_START	VARCHAR2 (255)		Start partition of a range of accessed partitions: <i>number</i> - Start partition has been identified by the SQL compiler, and its partition number is given by <i>number</i> - KEY - Start partition will be identified at run time from partitioning key values - ROW REMOVE_LOCATION - Start partition (same as the stop partition) will be computed at run time from the location of each record being retrieved. The record location is obtained by a user or from a global index. - INVALID - Range of accessed partitions is empty
PARTITION_STOP	VARCHAR2 (255)		Stop partition of a range of accessed partitions: <i>number</i> - Stop partition has been identified by the SQL compiler, and its partition number is given by <i>number</i> - KEY - Stop partition will be identified at run time from partitioning key values - ROW REMOVE_LOCATION - Stop partition (same as the start partition) will be computed at run time from the location of each record being retrieved. The record location is obtained by a user or from a global index. - INVALID - Range of accessed partitions is empty
PARTITION_ID	NUMBER (38)		Step that has computed the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	LONG		Other information that is specific to the execution step that a user might find useful (see the OTHER_TAG column)

Column	Datatype	NULL	Description
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML since multiple pieces of information can be stored there. This includes: - Name of the schema against which the query was parsed - Release number of the Oracle Database that produced the explain plan - Hash value associated with the execution plan - Name (if any) of the outline or the SQL profile used to build the execution plan - Indication of whether or not dynamic sampling was used to produce the plan - The outline data, a set of optimizer hints that can be used to regenerate the same plan
DISTRIBUTION	VARCHAR2 (30)		Method used to distribute rows from producer query servers to consumer query servers See Also: <i>Oracle Database Data Warehousing Guide</i> for more information about consumer and producer query servers
CPU_COST	NUMBER (38)		CPU cost of the operation as estimated by the query optimizer's approach. The value of this column is proportional to the number of machine cycles required for the operation. For statements that use the rule-based approach, this column is NULL.
IO_COST	NUMBER (38)		I/O cost of the operation as estimated by the query optimizer's approach. The value of this column is proportional to the number of data blocks read by the operation. For statements that use the rule-based approach, this column is NULL.
TEMP_SPACE	NUMBER (38)		Temporary space (in bytes) used by the operation as estimated by the query optimizer's approach. For statements that use the rule-based approach, or for operations that do not use any temporary space, this column is NULL.
ACCESS_PREDICATES	VARCHAR2 (4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2 (4000)		Predicates used to filter rows before producing them
PROJECTION	VARCHAR2 (4000)		Expressions produced by the operation
TIME	NUMBER (38)		Elapsed time (in seconds) of the operation as estimated by query optimization. For statements that use the rule-based approach, this column is NULL.
QBLOCK_NAME	VARCHAR2 (30)		Name of the query block (either system-generated or defined by the user with the <code>QB_NAME</code> hint)

PLUGGABLE_SET_CHECK

PLUGGABLE_SET_CHECK contains pluggable set checks.

Column	Datatype	NULL	Description
OBJ1_OWNER	VARCHAR2 (30)		Owner of the object
OBJ1_NAME	VARCHAR2 (30)		Object 1
OBJ1_SUBNAME	VARCHAR2 (30)		SubObject1Name
OBJ1_TYPE	VARCHAR2 (15)		Object Type
TS1_NAME	VARCHAR2 (30)		Tablespace containing Object 1

Column	Datatype	NULL	Description
OBJ2_NAME	VARCHAR2 (30)		Object Name
OBJ2_SUBNAME	VARCHAR2 (30)		SubObject2Name
OBJ2_TYPE	VARCHAR2 (15)		Object Type
OBJ2_OWNER	VARCHAR2 (30)		Object owner of second object
TS2_NAME	VARCHAR2 (30)		Tablespace containing Object 1
CONSTRAINT_NAME	VARCHAR2 (30)		Name of dependent constraint
REASON	VARCHAR2 (79)		Reason for Pluggable check violation
MESG_ID	NUMBER		The message ID

PRODUCT_COMPONENT_VERSION

PRODUCT_COMPONENT_VERSION contains version and status information for component products.

Column	Datatype	NULL	Description
PRODUCT	VARCHAR2 (64)		Product name
VERSION	VARCHAR2 (64)		Version number
STATUS	VARCHAR2 (64)		Status of release

PROXY_USERS

PROXY_USERS describes the list of proxy users and the clients on whose behalf they can act.

Column	Datatype	NULL	Description
PROXY	VARCHAR2 (30)	NOT NULL	Name of a proxy user
CLIENT	VARCHAR2 (30)	NOT NULL	Name of the client user who the proxy user can act as
AUTHENTICATION	VARCHAR2 (3)		Indicates whether the proxy is required to supply the client's authentication credentials (YES) or not (NO)
FLAGS	VARCHAR2 (35)		Flags associated with the proxy/client pair: ■ PROXY MAY ACTIVATE ALL CLIENT ROLES ■ NO CLIENT ROLES MAY BE ACTIVATED ■ PROXY MAY ACTIVATE ROLE ■ PROXY MAY ACTIVATE ALL CLIENT ROLES ■ PROXY MAY NOT ACTIVATE ROLE

PSTUBTBL

This table contains information on stubs generated by the PSTUB utility so that an Oracle Forms 3.0 client can call stored procedures in Oracle Database.

Note: The contents of this table are intended only for use by the PSTUB utility.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (30)		Schema part of the identifier of a stored procedure

PUBLIC_DEPENDENCY

Column	Datatype	NULL	Description
DBNAME	VARCHAR2 (128)		Database link part of the identifier of a stored procedure
LUN	VARCHAR2 (30)		Library unit name part of the identifier of a stored procedure
LUTYPE	VARCHAR2 (3)		Type of the stored procedure
LINENO	NUMBER		Line number of the stub
LINE	VARCHAR2 (1800)		Text of the stub

PUBLIC_DEPENDENCY

PUBLIC_DEPENDENCY lists dependencies to and from objects, by object number.

Column	Datatype	NULL	Description
OBJECT_ID	NUMBER	NOT NULL	Object number
REFERENCED_OBJECT_ID	NUMBER	NOT NULL	Referenced object (the parent object)

PUBLICSYN

PUBLICSYN contains information on public synonyms.

Column	Datatype	NULL	Description
SNAME	VARCHAR2 (30)		Name of the synonym
CREATOR	VARCHAR2 (30)		Owner of the synonym
TNAME	VARCHAR2 (30)		Table of which this is a synonym
DATABASE	VARCHAR2 (128)		Database in which the table resides
TABTYPE	VARCHAR2 (9)		Type of table

QUEUE_PRIVILEGES

QUEUE_PRIVILEGES shows all Advanced Queuing object privileges granted to the session.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2 (30)	NOT NULL	Name of the user or role to whom access was granted
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
NAME	VARCHAR2 (30)	NOT NULL	Name of the object
GRANTOR	VARCHAR2 (30)	NOT NULL	Name of the user who performed the grant
ENQUEUE_PRIVILEGE	NUMBER		Permission to ENQUEUE to the queue
DEQUEUE_PRIVILEGE	NUMBER		Permission to DEQUEUE from the queue

RECYCLEBIN

RECYCLEBIN is a synonym for USER_RECYCLEBIN.

See Also: ["USER_RECYCLEBIN"](#) on page 6-93

REPORT_COMPONENTS

REPORT_COMPONENTS displays metadata about different database components offering reports in XML, HTML, or Text formats. Reports are first generated in XML and can then be translated into HTML or Text formats, for supported report types. Each component generates one or more reports containing different types of content. You can request reports using the component's own PL/SQL interfaces (for example, DBMS_SQLTUNE for SQL Tuning Advisor) or using the DBMS_REPORT package.

Column	Datatype	NULL	Description
COMPONENT_ID	NUMBER	NOT NULL	ID number of the database component building the report
COMPONENT_NAME	VARCHAR2 (30)	NOT NULL	Name of the database component building the report (for example, sqltune for SQL Tuning Advisor)
COMPONENT_DESCRIPTION	VARCHAR2 (256)		Component description
REPORT_ID	NUMBER	NOT NULL	ID number of the report type
REPORT_NAME	VARCHAR2 (30)	NOT NULL	Name of the report type
REPORT_DESCRIPTION	VARCHAR2 (256)		Description of the report type
SCHEMA_FILENAME	VARCHAR2 (500)		Filename of the XML schema for the report (optional)
SCHEMA_DATA	XMLTYPE		XML schema for this report (optional)

REPORT_FILES

REPORT_FILES displays data for all of the XML schema and XSLT files associated with reports for a given component.

Column	Datatype	NULL	Description
COMPONENT_ID	NUMBER		ID number of the database component building the report
COMPONENT_NAME	VARCHAR2 (30)		Name of the database component building the report (for example, sqltune for SQL Tuning Advisor)
FILENAME	VARCHAR2 (500)	NOT NULL	Name of the XSLT/XML schema file
DATA	XMLTYPE		XSLT/XML schema data

REPORT_FORMATS

REPORT_FORMATS displays metadata about the different output formats supported for reports. Some reports are generated in XML only, in which case no data will appear in this view. When reports support HTML or Text formats (for example, the SQL Performance Analyzer reports), metadata about the format will appear in this view. XML reports can be translated to another format with the DBMS_REPORT . FORMAT_REPORT procedure.

Column	Datatype	NULL	Description
COMPONENT_ID	NUMBER	NOT NULL	ID number of the database component building the report
COMPONENT_NAME	VARCHAR2 (30)	NOT NULL	Name of the database component building the report (for example, sqltune for SQL Tuning Advisor)
REPORT_ID	NUMBER	NOT NULL	ID number of the report type
REPORT_NAME	VARCHAR2 (30)	NOT NULL	Name of the report type
FORMAT_NAME	VARCHAR2 (30)	NOT NULL	Name of the report format

RESOURCE_COST

Column	Datatype	NULL	Description
DESCRIPTION	VARCHAR2 (256)		Description of the report format
TYPE	VARCHAR2 (6)		Format type: ■ XSLT - Reports generated by applying an XSLT stylesheet to XML data (for example, HTML reports) ■ Text - Reports generated by first applying an XSLT stylesheet to convert XML data to HTML, and then converting the HTML to formatted Text using the internal report HTML-to-text translation engine. ■ Custom - Custom formats implemented natively by report clients
XSLT_FILENAME	VARCHAR2 (500)		Name of the XSLT used for this format (XSLT and Text format types only)
XSLT_DATA	XMLTYPE		XSLT data (XSLT and Text format types only)
TEXT_LINESIZE	NUMBER		Maximum line size of the formatted text report (Text format types only)

RESOURCE_COST

RESOURCE_COST lists the cost for each resource.

Column	Datatype	NULL	Description
RESOURCE_NAME	VARCHAR2 (32)	NOT NULL	Name of the resource
UNIT_COST	NUMBER	NOT NULL	Cost of the resource

RESOURCE_MAP

RESOURCE_MAP describes resources. This table can be used to map resource names to resource numbers.

Column	Datatype	NULL	Description
RESOURCE#	NUMBER	NOT NULL	Numeric resource code
TYPE#	NUMBER	NOT NULL	Numeric type code
NAME	VARCHAR2 (32)	NOT NULL	Name of the resource

RESOURCE_VIEW

RESOURCE_VIEW contains one row for each resource in the Oracle XML DB repository.

Column	Datatype	NULL	Description
RES	XMLTYPE(XMLSchema "http://xmlns.oracle.com/xdb/XDBResource.xsd" Element "Resource")		A resource in the repository
ANY_PATH	VARCHAR2 (4000)		An (absolute) path to the resource
RESID	RAW (16)		Resource OID, which is a unique handle to the resource

See Also: *Oracle XML DB Developer's Guide* for information about using this view

ROLE_ROLE_PRIVS

ROLE_ROLE_PRIVS describes the roles granted to other roles. Information is provided only about roles to which the user has access.

Column	Datatype	NULL	Description
ROLE	VARCHAR2 (30)	NOT NULL	Name of the role
GRANTED_ROLE	VARCHAR2 (30)	NOT NULL	Role that was granted
ADMIN_OPTION	VARCHAR2 (3)		Signifies that the role was granted with ADMIN option

ROLE_SYS_PRIVS

ROLE_SYS_PRIVS describes system privileges granted to roles. Information is provided only about roles to which the user has access.

Column	Datatype	NULL	Description
ROLE	VARCHAR2 (30)	NOT NULL	Name of the role
PRIVILEGE	VARCHAR2 (40)	NOT NULL	System privilege granted to the role
ADMIN_OPTION	VARCHAR2 (3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)

ROLE_TAB_PRIVS

ROLE_TAB_PRIVS describes table privileges granted to roles. Information is provided only about roles to which the user has access.

Column	Datatype	NULL	Description
ROLE	VARCHAR2 (30)	NOT NULL	Name of the role
OWNER	VARCHAR2 (30)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2 (30)	NOT NULL	Name of the object
COLUMN_NAME	VARCHAR2 (30)		Name of the column, if applicable
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Object privilege granted to the role
GRANTABLE	VARCHAR2 (3)		YES if the role was granted with ADMIN OPTION; otherwise NO

SCHEDULER_BATCH_ERRORS

SCHEDULER_BATCH_ERRORS displays the errors caused by each call in the batch after a Scheduler batch call (when the COMMIT_SEMANTICS argument has been set to ABSORB_ERRORS).

Column	Datatype	NULL	Description
ARRAY_INDEX	NUMBER		Index of the job in the batch
OBJECT_TYPE	VARCHAR2 (30)		Object type: - JOB - LIGHTWEIGHT JOB - UNKNOWN
OBJECT_NAME	VARCHAR2 (100)		Full name of the object (including schema)
ATTR_NAME	VARCHAR2 (30)		Name of the attribute being set (if this is a batch set attribute call); NULL otherwise

Column	Datatype	NULL	Description
ERROR_CODE	NUMBER		Top level error code
ERROR_MESSAGE	VARCHAR2 (4000)		Complete error stack
ADDITIONAL_INFO	VARCHAR2 (4000)		Additional information (currently unused)

SEQ

SEQ is a synonym for USER_SEQUENCES.

See Also: ["USER_SEQUENCES"](#) on page 6-98

SESSION_CONTEXT

SESSION_CONTEXT describes the context attributes and their values set for the current session.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2 (30)		Namespace that the active attribute is in
ATTRIBUTE	VARCHAR2 (30)		Name of the active attribute
VALUE	VARCHAR2 (4000)		Value of the active attribute

See Also: *Oracle Database SQL Language Reference* for information on the predefined attributes of the current session

SESSION_PRIVS

SESSION_PRIVS describes the privileges that are currently available to the user.

Column	Datatype	NULL	Description
PRIVILEGE	VARCHAR2 (40)	NOT NULL	Name of the privilege

SESSION_ROLES

SESSION_ROLES describes the roles that are currently enabled to the user.

Column	Datatype	NULL	Description
ROLE	VARCHAR2 (30)	NOT NULL	Name of the role

SOURCE_SIZE

Oracle accesses this view to create views about object size.

See Also: ["DBA_OBJECT_SIZE"](#) on page 5-63 and ["USER_OBJECT_SIZE"](#) on page 6-88

STMT_AUDIT_OPTION_MAP

STMT_AUDIT_OPTION_MAP describes auditing option type codes. This table can be used to map auditing option type numbers to type names.

Column	Datatype	NULL	Description
OPTION#	NUMBER	NOT NULL	Numeric auditing option type code
NAME	VARCHAR2 (40)	NOT NULL	Name of the type of auditing option
PROPERTY	NUMBER	NOT NULL	Property flag of the auditing option

SYN

SYN is a synonym for USER_SYNONYMS.

See Also: ["ALL_SYNONYMS"](#) on page 3-75

SYNONYMS

SYNONYMS is included for compatibility. Oracle recommends that you do not use this view.

SYS_OBJECTS

SYS_OBJECTS maps object IDs to object types and segment data block addresses.

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2 (15)		Type of the object
OBJECT_TYPE_ID	NUMBER		Type ID of the object
SEGMENT_TYPE_ID	NUMBER		Type of segment: TABLE, CLUSTER, INDEX, ROLLBACK, DEFERRED ROLLBACK, TEMPORARY, CACHE
OBJECT_ID	NUMBER		Object identifier
HEADER_FILE	NUMBER		ID of the file containing the segment header
HEADER_BLOCK	NUMBER		ID of the block containing the segment header
TS_NUMBER	NUMBER		The tablespace number

SYSCATALOG

SYSCATALOG is included for compatibility. Oracle recommends that you do not use this view.

SYSFILES

SYSFILES is included for compatibility. Oracle recommends that you do not use this view.

SYSSEGOBJ

SYSSEGOBJ is included for compatibility. Oracle recommends that you do not use this view.

SYSTEM_PRIVILEGE_MAP

SYSTEM_PRIVILEGE_MAP describes privilege type codes. This table can be used to map privilege type numbers to type names.

Column	Datatype	NULL	Description
PRIVILEGE	NUMBER	NOT NULL	Numeric privilege type code
NAME	VARCHAR2 (40)	NOT NULL	Name of the type of privilege
PROPERTY	NUMBER	NOT NULL	Property flag of the privilege

TAB

TAB is included for compatibility. Oracle recommends that you do not use this view.

TABLE_PRIVILEGE_MAP

TABLE_PRIVILEGE_MAP describes privilege (auditing option) type codes. This table can be used to map privilege (auditing option) type numbers to type names.

Column	Datatype	NULL	Description
PRIVILEGE	NUMBER	NOT NULL	Numeric privilege (auditing option) type code
NAME	VARCHAR2 (40)	NOT NULL	Name of the type of privilege (auditing option)

TABQUOTAS

TABQUOTAS is included for compatibility. Oracle recommends that you do not use this view.

TABS

TABS is a synonym for USER_TABLES.

See Also: ["USER_TABLES"](#) on page 6-105

TRUSTED_SERVERS

TRUSTED_SERVERS displays whether a server is trusted or untrusted.

Column	Datatype	NULL	Description
TRUST	VARCHAR2 (9)		Trustedness of the server listed. Values can be TRUSTED or UNTRUSTED servers which are not listed in the NAME column have opposite trustedness.
NAME	VARCHAR2 (128)		Server name. Can be a specific server name or ALL for all servers.

[Table 6–1](#) shows examples of the values returned depending on the status of the servers.

Table 6–1 TRUSTED_SERVERS Values

Condition (If . . .)	TRUSTED column	NAME column
... all servers are trusted	Trusted	ALL
... no servers are trusted	Untrusted	ALL
... all servers except DB1 are trusted	Untrusted	DB1
... all servers except DB1 are untrusted	Trusted	DB1

See Also: *Oracle Database Heterogeneous Connectivity User's Guide*

TS_PITR_CHECK

This view, created by `catpitr.sql`, provides information on any dependencies or restrictions that might prevent tablespace point-in-time recovery from proceeding. This view applies only to the tablespace point-in-time recovery feature.

Column	Datatype	NULL	Description
OBJ1_OWNER	VARCHAR2 (30)	NOT NULL	The owner of the object preventing tablespace point-in-time recovery. See the REASON column for details.
OBJ1_NAME	VARCHAR2 (30)	NOT NULL	The name of the object preventing tablespace point-in-time recovery
OBJ1_TYPE	VARCHAR2 (15)		The object type for the object preventing tablespace point-in-time recovery
OBJ1_SUBNAME	VARCHAR2 (30)		Subordinate to OBJ1_NAME
TS1_NAME	VARCHAR2 (30)	NOT NULL	Name of the tablespace containing the object preventing tablespace point-in-time recovery
OBJ2_NAME	VARCHAR2 (30)		The name of a second object which may be preventing tablespace point-in-time recovery. If NULL, object 1 is the only object preventing recovery.
OBJ2_TYPE	VARCHAR2 (15)		The object type for the second object (will be NULL if OBJ2_NAME is NULL)
OBJ2_OWNER	VARCHAR2 (30)		The owner of the second object (will be NULL if OBJ2_NAME is NULL)
OBJ2_SUBNAME	VARCHAR2 (30)		Subordinate to OBJ2_NAME
TS2_NAME	VARCHAR2 (30)		Name of the tablespace containing second object which may be preventing tablespace point-in-time recovery (-1 indicates not applicable)
CONSTRAINT_NAME	VARCHAR2 (30)		Name of the constraint
REASON	VARCHAR2 (78)		Reason why tablespace point-in-time recovery cannot proceed

See Also: *Oracle Database Backup and Recovery User's Guide*

TS_PITR_OBJECTS_TO_BE_DROPPED

TS_PITR_OBJECTS_TO_BE_DROPPED lists all objects lost as a result of performing tablespace point-in-time recovery. This view applies only to the tablespace point-in-time recovery feature.

Column	Datatype	NULL	Description
OWNER	VARCHAR2 (30)	NOT NULL	The owner of the object
NAME	VARCHAR2 (30)	NOT NULL	The name of the object that will be lost as a result of undergoing tablespace point-in-time recovery
CREATION_TIME	DATE	NOT NULL	Creation timestamp of the object
TABLESPACE_NAME	VARCHAR2 (30)		Name of the tablespace containing the object

UNI_PLUGGABLE_SET_CHECK

UNI_PLUGGABLE_SET_CHECK contains pluggable check information.

Column	Datatype	NULL	Description
OBJ1_OWNER	VARCHAR2 (30)		Owner of object
OBJ1_NAME	VARCHAR2 (30)		Object 1
OBJ1_SUBNAME	VARCHAR2 (30)		SubObject1Name
OBJ1_TYPE	VARCHAR2 (15)		Object Type
TS1_NAME	VARCHAR2 (30)		Tablespace containing Object 1
OBJ2_NAME	VARCHAR2 (30)		Object Name
OBJ2_SUBNAME	VARCHAR2 (30)		SubObject2Name
OBJ2_TYPE	VARCHAR2 (15)		Object Type
OBJ2_OWNER	VARCHAR2 (30)		Object owner of second object
TS2_NAME	VARCHAR2 (30)		Tablespace containing Object 1
CONSTRAINT_NAME	VARCHAR2 (30)		Name of dependent constraint
REASON	VARCHAR2 (79)		Reason for Pluggable check violation
MESG_ID	NUMBER		The message ID

USER_ADDM_FDG_BREAKDOWN

USER_ADDM_FDG_BREAKDOWN describes the contribution for each finding from the different instances owned by the current user. Its columns are the same as those in ["DBA_ADDM_FDG_BREAKDOWN"](#) on page 4-2.

USER_ADDM_FINDINGS

USER_ADDM_FINDINGS displays the ADDM findings discovered by the advisors owned by the current user. Each row for ADDM tasks in the related USER_ADVISOR_FINDINGS view has a corresponding row in this view. Its columns (except for OWNER) are the same as those in ["DBA_ADDM_FINDINGS"](#) on page 4-2.

USER_ADDM_INSTANCES

USER_ADDM_INSTANCES provides instance-level information for ADDM tasks that finished executing in all instances owned by the current user. Its columns are the same as those in ["DBA_ADDM_INSTANCES"](#) on page 4-3.

USER_ADDM_TASKS

USER_ADDM_TASKS displays information about the ADDM tasks owned by the current user. The view contains one row for each row in the related USER_ADVISOR_TASKS view that has ADVISOR_NAME=ADDM and STATUS=COMPLETED. Its columns (except for OWNER) are the same as those in ["DBA_ADVISOR_TASKS"](#) on page 4-30.

USER_ADVISOR_ACTIONS

USER_ADVISOR_ACTIONS displays information about the actions associated with the recommendations owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_ACTIONS.

See Also: ["DBA_ADVISOR_ACTIONS"](#) on page 4-7

USER_ADVISOR_DIR_TASK_INST

USER_ADVISOR_DIR_TASK_INST displays information about all task directive instances owned by the current user. Its columns (except for SEQ_ID and USERNAME) are the same as those in ["DBA_ADVISOR_DIR_TASK_INST"](#) on page 4-10.

USER_ADVISOR_EXEC_PARAMETERS

USER_ADVISOR_EXEC_PARAMETERS displays the parameter values used for past executions of tasks owned by the current user. Its columns (except for OWNER) are the same as those in ["DBA_ADVISOR_EXEC_PARAMETERS"](#) on page 4-11.

USER_ADVISOR_EXECUTIONS

USER_ADVISOR_EXECUTIONS displays metadata information for tasks owned by the current user. Its columns (except for OWNER) are the same as those in ["DBA_ADVISOR_EXECUTIONS"](#) on page 4-12.

USER_ADVISOR_FDG_BREAKDOWN

USER_ADVISOR_FDG_BREAKDOWN describes the contribution from the different instances to the findings for each ADDM task owned by the current user. Its columns are the same as those in DBA_ADVISOR_FDG_BREAKDOWN.

See Also: ["DBA_ADVISOR_FDG_BREAKDOWN"](#) on page 4-13

USER_ADVISOR_FINDINGS

USER_ADVISOR_FINDINGS displays the findings discovered by the advisors owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_FINDINGS.

See Also: ["DBA_ADVISOR_FINDINGS"](#) on page 4-13

USER_ADVISOR_JOURNAL

USER_ADVISOR_JOURNAL displays the journal entries for the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_JOURNAL.

See Also: ["DBA_ADVISOR_JOURNAL"](#) on page 4-14

USER_ADVISOR_LOG

USER_ADVISOR_LOG displays information about the current state of the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_LOG.

See Also: ["DBA_ADVISOR_LOG"](#) on page 4-15

USER_ADVISOR_OBJECTS

USER_ADVISOR_OBJECTS displays information about the objects currently referenced by the advisors owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_OBJECTS.

See Also: ["DBA_ADVISOR_OBJECTS"](#) on page 4-16

USER_ADVISOR_PARAMETERS

USER_ADVISOR_PARAMETERS displays the task parameters and their current values for the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_PARAMETERS.

See Also: ["DBA_ADVISOR_PARAMETERS"](#) on page 4-17

USER_ADVISOR_RATIONALE

USER_ADVISOR_RATIONALE displays information about the rationales for the recommendations owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_RATIONALE.

See Also: ["DBA_ADVISOR_RATIONALE"](#) on page 4-18

USER_ADVISOR_RECOMMENDATIONS

USER_ADVISOR_RECOMMENDATIONS displays the results of an analysis of the recommendations owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_RECOMMENDATIONS.

See Also: ["DBA_ADVISOR_RECOMMENDATIONS"](#) on page 4-19

USER_ADVISOR_SQLA_REC_SUM

USER_ADVISOR_SQLA_REC_SUM displays recommendation rollup information for the workload objects owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLA_REC_SUM.

See Also: ["DBA_ADVISOR_SQLA_REC_SUM"](#) on page 4-20

USER_ADVISOR_SQLA_TABLES

USER_ADVISOR_SQLA_TABLES displays cross references between the workload statements and the tables referenced in the statement for the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLA_TABLES.

See Also: ["DBA_ADVISOR_SQLA_TABLES"](#) on page 4-21

USER_ADVISOR_SQLA_WK_MAP

USER_ADVISOR_SQLA_WK_MAP displays the workload references for the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLA_WK_MAP.

See Also: ["DBA_ADVISOR_SQLA_WK_MAP"](#) on page 4-21

USER_ADVISOR_SQLA_WK_STMTS

USER_ADVISOR_SQLA_WK_STMTS displays information about the workload objects owned by the current user after an Access Advisor analysis operation. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLA_WK_STMTS.

See Also: ["DBA_ADVISOR_SQLA_WK_STMTS"](#) on page 4-21

USER_ADVISOR_SQLPLANS

USER_ADVISOR_SQLPLANS displays the different SQL execution plans owned by the current user generated as part of an advisor analysis. Its columns are the same as those in ["DBA_ADVISOR_SQLPLANS"](#) on page 4-23.

USER_ADVISOR_SQLSTATS

USER_ADVISOR_SQLSTATS displays execution statistics owned by the current user for the test-execution of different SQL plans during the advisor analysis. Its columns are the same as those in ["DBA_ADVISOR_SQLSTATS"](#) on page 4-25.

USER_ADVISOR_SQLW_JOURNAL

USER_ADVISOR_SQLW_JOURNAL displays the journal entries for the workload objects owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLW_JOURNAL.

See Also: ["DBA_ADVISOR_SQLW_JOURNAL"](#) on page 4-26

USER_ADVISOR_SQLW_PARAMETERS

USER_ADVISOR_SQLW_PARAMETERS displays the workload parameters and their current values owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLW_PARAMETERS.

See Also: ["DBA_ADVISOR_SQLW_PARAMETERS"](#) on page 4-27

USER_ADVISOR_SQLW_STMTS

USER_ADVISOR_SQLW_STMTS displays rows that correspond to the statements in the workload owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLW_STMTS.

See Also: ["DBA_ADVISOR_SQLW_STMTS"](#) on page 4-27

USER_ADVISOR_SQLW_SUM

USER_ADVISOR_SQLW_SUM displays an aggregated picture of the SQLWkld workload objects owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLW_SUM.

See Also: ["DBA_ADVISOR_SQLW_SUM"](#) on page 4-28

USER_ADVISOR_SQLW_TABLES

USER_ADVISOR_SQLW_TABLES displays cross references between the workload statements and the tables referenced in the statement. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLW_TABLES.

See Also: ["DBA_ADVISOR_SQLW_TABLES"](#) on page 4-29

USER_ADVISOR_SQLW_TEMPLATES

USER_ADVISOR_SQLW_TEMPLATES displays an aggregated picture of the SQLWkld template objects owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLW_TEMPLATES.

See Also: ["DBA_ADVISOR_SQLW_TEMPLATES"](#) on page 4-29

USER_ADVISOR_TASKS

USER_ADVISOR_TASKS displays information about the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_TASKS.

See Also: ["DBA_ADVISOR_TASKS"](#) on page 4-30

USER_ADVISOR_TEMPLATES

USER_ADVISOR_TEMPLATES displays information about the templates owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_TEMPLATES.

See Also: ["DBA_ADVISOR_TEMPLATES"](#) on page 4-31

USER_ALL_TABLES

USER_ALL_TABLES describes the object tables and relational tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ALL_TABLES.

See Also: ["ALL_ALL_TABLES"](#) on page 2-5

USER_AQ_AGENT_PRIVS

USER_AQ_AGENT_PRIVS displays information about the registered AQ agents that are mapped to the current user. Its columns (except for DB_USERNAME) are the same as those in DBA_AQ_AGENT_PRIVS.

See Also: ["DBA_AQ_AGENT_PRIVS"](#) on page 4-37

USER_ARGUMENTS

USER_ARGUMENTS lists the arguments of the procedures and functions that are owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ARGUMENTS.

See Also: ["ALL_ARGUMENTS"](#) on page 2-16

USER_ASSEMBLIES

USER_ASSEMBLIES provides information about all assemblies owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ASSEMBLIES.

See Also: ["ALL_ASSEMBLIES"](#) on page 2-17

USER_ASSOCIATIONS

USER_ASSOCIATIONS describes user-defined statistics associated with objects owned by the current user. Its columns are the same as those in ALL_ASSOCIATIONS.

See Also: ["ALL_ASSOCIATIONS"](#) on page 2-18

USER_ATTRIBUTE_TRANSFORMATIONS

USER_ATTRIBUTE_TRANSFORMATIONS displays information about the transformation functions for the transformations owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ATTRIBUTE_TRANSFORMATIONS.

See Also: ["DBA_ATTRIBUTE_TRANSFORMATIONS"](#) on page 4-38

USER_AUDIT_OBJECT

USER_AUDIT_OBJECT displays audit trail records for the objects accessible to the current user. Its columns are the same as those in ["DBA_AUDIT_OBJECT"](#) on page 4-41.

USER_AUDIT_POLICIES

USER_AUDIT_POLICIES describes the fine-grained auditing policies on the tables and views owned by the current user. Its columns (except for OBJECT_SCHEMA) are the same as those in ALL_AUDIT_POLICIES.

See Also: ["ALL_AUDIT_POLICIES"](#) on page 2-18

USER_AUDIT_POLICY_COLUMNS

USER_AUDIT_POLICY_COLUMNS describes the fine-grained auditing policy columns on the tables and views owned by the current user. Its columns are the same as those in ALL_AUDIT_POLICY_COLUMNS.

See Also: ["ALL_AUDIT_POLICY_COLUMNS"](#) on page 2-20

USER_AUDIT_SESSION

USER_AUDIT_SESSION displays the audit trail records concerning connections and disconnections of the current user. Its columns are the same as those in ["DBA_AUDIT_SESSION"](#) on page 4-43.

USER_AUDIT_STATEMENT

USER_AUDIT_STATEMENT displays audit trail entries for the GRANT, REVOKE, AUDIT, NOAUDIT, and ALTER SYSTEM statements issued by the current user. Its columns are the same as those in ["DBA_AUDIT_STATEMENT"](#) on page 4-44.

USER_AUDIT_TRAIL

USER_AUDIT_TRAIL displays the standard audit trail entries related to the current user. Its columns are the same as those in ["DBA_AUDIT_TRAIL"](#) on page 4-45.

USER_AW_PS

USER_AW_PS describes the page spaces in the analytic workspaces owned by the current user. Its columns (except for OWNER) are the same as those in ALL_AW_PS.

See Also: ["ALL_AW_PS"](#) on page 2-20

USER_AWS

USER_AWS describes the analytic workspaces owned by the current user. Its columns (except for OWNER) are the same as those in ALL_AWS.

See Also: ["ALL_AWS"](#) on page 2-20

USER_BASE_TABLE_MVIEWS

USER_BASE_TABLE_MVIEWS describes the materialized views using materialized view logs owned by the current user. Its columns are the same as those in ALL_BASE_TABLE_MVIEWS.

See Also: ["ALL_BASE_TABLE_MVIEWS"](#) on page 2-21

USER_CATALOG

USER_CATALOG lists tables, views, clusters, synonyms, and sequences owned by the current user. Its columns are the same as those in ["ALL_CATALOG"](#) on page 2-27.

USER_CHANGE_NOTIFICATION_REGS

USER_CHANGE_NOTIFICATION_REGS describes the change notification registrations owned by the current user. Its columns (except for USERNAME) are the same as those in DBA_CHANGE_NOTIFICATION_REGS.

See Also: ["DBA_CHANGE_NOTIFICATION_REGS"](#) on page 4-57

USER_CLU_COLUMNS

USER_CLU_COLUMNS maps columns in the current user's tables to cluster columns. Its columns are the same as those in ["DBA_CLU_COLUMNS"](#) on page 4-57.

USER_CLUSTER_HASH_EXPRESSIONS

USER_CLUSTER_HASH_EXPRESSIONS lists hash functions for the hash clusters owned by the current user. Its columns are the same as those in ["ALL_CLUSTER_HASH_EXPRESSIONS"](#) on page 2-29.

USER_CLUSTERS

USER_CLUSTERS describes all the clusters owned by the current user. Its columns are the same as those in ["ALL_CLUSTERS"](#) on page 2-30.

USER_COL_COMMENTS

USER_COL_COMMENTS displays comments on the columns of the tables and views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_COL_COMMENTS.

See Also: ["ALL_COL_COMMENTS"](#) on page 2-31

USER_COL_PENDING_STATS

USER_COL_PENDING_STATS describes the pending statistics of the columns owned by the current user. Its columns (except for OWNER) are the same as those in ALL_COL_PENDING_STATS.

See Also: ["ALL_COL_PENDING_STATS"](#) on page 2-31

USER_COL_PRIVS

USER_COL_PRIVS describes the column object grants for which the current user is the object owner, grantor, or grantee. Its columns are the same as those in DBA_COL_PRIVS.

See Also: ["DBA_COL_PRIVS"](#) on page 4-58

USER_COL_PRIVS_MADE

USER_COL_PRIVS_MADE describes the column object grants for which the current user is the object owner. Its columns (except for OWNER) are the same as those in ALL_COL_PRIVS_MADE.

See Also: ["ALL_COL_PRIVS_MADE"](#) on page 2-33

USER_COL_PRIVS_RECD

USER_COL_PRIVS_RECD describes the column object grants for which the current user is the grantee. Its columns (except for GRANTEE) are the same as those in ALL_COL_PRIVS_RECD.

See Also: ["ALL_COL_PRIVS_RECD"](#) on page 2-33

USER_COLL_TYPES

USER_COLL_TYPES describes named collection types (VARRAYs, nested tables, object tables, and so on) in the current user's schema. Its columns are the same as those in ["ALL_COLL_TYPES"](#) on page 2-34.

USER_COMPARISON

USER_COMPARISON displays information about the comparison objects owned by the current user. Its columns (except for OWNER) are the same as those in ["DBA_COMPARISON"](#) on page 4-60.

USER_COMPARISON_COLUMNS

USER_COMPARISON_COLUMNS displays information about the columns for the comparison objects owned by the current user. Its columns (except for OWNER) are the same as those in ["DBA_COMPARISON_COLUMNS"](#) on page 4-61.

USER_COMPARISON_ROW_DIF

USER_COMPARISON_ROW_DIF displays information about the differing rows in the comparison scans owned by the current user. Its columns are the same as those in ["DBA_COMPARISON_ROW_DIF"](#) on page 4-62.

USER_COMPARISON_SCAN

USER_COMPARISON_SCAN displays information about the comparison scans owned by the current user. Its columns (except for OWNER) are the same as those in ["DBA_COMPARISON_SCAN"](#) on page 4-62.

USER_COMPARISON_SCAN_VALUES

USER_COMPARISON_SCAN_VALUES displays information about the values for the comparison scans owned by the current user. Its columns (except for OWNER) are the same as those in ["DBA_COMPARISON_SCAN_VALUES"](#) on page 4-63.

USER_CONS_COLUMNS

USER_CONS_COLUMNS describes columns that are owned by the current user and that are specified in constraint definitions. Its columns are the same as those in ["ALL_CONS_COLUMNS"](#) on page 2-34.

USER_CONS_OBJ_COLUMNS

USER_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in the tables owned by the current user. Its columns (except for OWNER) are the same as those in [ALL_CONS_OBJ_COLUMNS](#).

See Also: ["ALL_CONS_OBJ_COLUMNS"](#) on page 2-35

USER_CONSTRAINTS

USER_CONSTRAINTS describes all constraint definitions on tables owned by the current user. Its columns are the same as those in ["ALL_CONSTRAINTS"](#) on page 2-35.

USER_CQ_NOTIFICATION_QUERIES

USER_CQ_NOTIFICATION_QUERIES describes the registered queries for the CQ notifications owned by the current user. Its columns (except for USERNAME) are the same as those in DBA_CQ_NOTIFICATION_QUERIES.

See Also: ["DBA_CQ_NOTIFICATION_QUERIES"](#) on page 4-65

USER_CUBE_ATTR_VISIBILITY

USER_CUBE_ATTR_VISIBILITY describes the OLAP attributes visible for the dimensions, hierarchies, and levels owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_ATTR_VISIBILITY.

USER_CUBE_ATTRIBUTES

USER_CUBE_ATTRIBUTES describes the attributes for the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_ATTRIBUTES.

USER_CUBE_BUILD_PROCESSES

USER_CUBE_BUILD_PROCESSES describes the OLAP build processes and maintenance scripts owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_BUILD_PROCESSES.

USER_CUBE_CALCULATED_MEMBERS

USER_CUBE_CALCULATED_MEMBERS describes the calculated members for the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_CALCULATED_MEMBERS.

USER_CUBE_DIM_LEVELS

USER_CUBE_DIM_LEVELS describes the OLAP dimension levels owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIM_LEVELS.

USER_CUBE_DIM_MODELS

USER_CUBE_DIM_MODELS describes the models for the OLAP dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIM_MODELS.

USER_CUBE_DIM_VIEW_COLUMNS

USER_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIM_VIEW_COLUMNS.

USER_CUBE_DIM_VIEWS

USER_CUBE_DIM_VIEWS describes the relational views of the OLAP dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIM_VIEWS.

USER_CUBE_DIMENSIONALITY

USER_CUBE_DIMENSIONALITY describes the dimension order for the OLAP cubes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIMENSIONALITY.

USER_CUBE_DIMENSIONS

USER_CUBE_DIMENSIONS describes the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIMENSIONS.

USER_CUBE_HIER_LEVELS

USER_CUBE_HIER_LEVELS describes the hierarchy levels for the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_HIER_LEVELS.

USER_CUBE_HIER_VIEW_COLUMNS

USER_CUBE_HIER_VIEW_COLUMNS describes the columns of the relational hierarchy views of the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_HIER_VIEW_COLUMNS.

USER_CUBE_HIER_VIEWS

USER_CUBE_HIER_VIEWS describes the hierarchies for the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_HIER_VIEWS.

USER_CUBE_HIERARCHIES

USER_CUBE_HIERARCHIES describes the OLAP dimension hierarchies owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_HIERARCHIES.

USER_CUBE_MEASURES

USER_CUBE_MEASURES describes the measures for the OLAP cubes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_MEASURES.

USER_CUBE_VIEW_COLUMNS

USER_CUBE_VIEW_COLUMNS describes the columns of relational views of OLAP cubes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_VIEW_COLUMNS.

USER_CUBE_VIEWS

USER_CUBE_VIEWS describes the relational views of the OLAP cubes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_VIEWS.

USER_CUBES

USER_CUBES describes the OLAP cubes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBES.

USER_DATAPUMP_JOBS

USER_DATAPUMP_JOBS displays the Data Pump jobs owned by the current user. Its columns (except for OWNER_NAME) are the same as those in DBA_DATAPUMP_JOBS.

See Also: ["DBA_DATAPUMP_JOBS"](#) on page 4-68

USER_DB_LINKS

USER_DB_LINKS describes the database links owned by the current user. Its columns are the same as those in ALL_DB_LINKS except that it does not have the OWNER column. It also displays an additional column, PASSWORD, which is no longer used and for which nothing is returned. The PASSWORD column is maintained for backward compatibility only.

See Also: ["ALL_DB_LINKS"](#) on page 2-48

USER_DBFS_HS_FILES

USER_DBFS_HS_FILES displays files in the DBFS hierarchical store owned by the current user and their location on the backend device.

Column	Datatype	NULL	Description
PATH	VARCHAR2 (1024)		Path name of the file
SEQUENCENUMBER	NUMBER		Sequence number of this piece of the file
STARTOFFSET	NUMBER		Begin offset of this piece in the tarball
ENDOFFSET	NUMBER		End offset of this piece in the tarball
TARBALLID	NUMBER		Tarball ID
BACKUPFILENAME	VARCHAR2 (256)		File on backend in which this tarball is located
TARSTARTOFFSET	NUMBER		Begin Offset of this tarball in the backup file
TARENDOFFSET	NUMBER		End Offset of this tarball in the backup file

USER_DEPENDENCIES

`USER_DEPENDENCIES` describes dependencies between procedures, packages, functions, package bodies, and triggers owned by the current user, including dependencies on views created without any database links. Its columns are the same as those in "[ALL_DEPENDENCIES](#)" on page 2-49.

USER_DIM_ATTRIBUTES

`USER_DIM_ATTRIBUTES` describes the relationship between dimension levels and functionally dependent columns in the current user's schema. The level columns and the dependent column must be in the same table. This view's columns are the same as those in "[ALL_DIM_ATTRIBUTES](#)" on page 2-50.

USER_DIM_CHILD_OF

`USER_DIM_CHILD_OF` describes a hierarchical relationship of 1 to n between pairs of levels in dimensions owned by the current user. Its columns are the same as those in "[ALL_DIM_CHILD_OF](#)" on page 2-51.

USER_DIM_HIERARCHIES

`USER_DIM_HIERARCHIES` describes the dimension hierarchies owned by the current user. Its columns are the same as those in "[ALL_DIM_HIERARCHIES](#)" on page 2-51.

USER_DIM_JOIN_KEY

`USER_DIM_JOIN_KEY` describes the join between two dimension tables owned by the current user. The join is always specified between a parent dimension level column and a child column. This view's columns are the same as those in "[ALL_DIM_JOIN_KEY](#)" on page 2-52.

USER_DIM_LEVEL_KEY

`USER_DIM_LEVEL_KEY` describes columns of dimension levels owned by the current user. This view's columns are the same as those in "[ALL_DIM_LEVEL_KEY](#)" on page 2-52.

USER_DIM_LEVELS

`USER_DIM_LEVELS` describes the levels of dimensions owned by the current user. All columns of a dimension level must come from the same relation. This view's columns are the same as those in "[ALL_DIM_LEVELS](#)" on page 2-52.

USER_DIMENSIONS

`USER_DIMENSIONS` describes dimension objects in the user's schema. Its columns are the same as those in "[ALL_DIMENSIONS](#)" on page 2-53.

USER_EDITIONING_VIEW_COLS

`USER_EDITIONING_VIEW_COLS` describes the relationship between the columns of the editioning views owned by the current user and the table columns to which they

map. Its columns (except for OWNER) are the same as those in ALL_EDITIONING_VIEW_COLS.

See Also: ["ALL_EDITIONING_VIEW_COLS"](#) on page 2-54

USER_EDITIONING_VIEW_COLS_AE

USER_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of the editioning views (across all editions) owned by the current user and the table columns to which they map. Its columns (except for OWNER) are the same as those in ALL_EDITIONING_VIEW_COLS_AE.

See Also: ["ALL_EDITIONING_VIEW_COLS_AE"](#) on page 2-54

USER_EDITIONING_VIEWS

USER_EDITIONING_VIEWS describes the editioning views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_EDITIONING_VIEWS.

See Also: ["ALL_EDITIONING_VIEWS"](#) on page 2-55

USER_EDITIONING_VIEWS_AE

USER_EDITIONING_VIEWS_AE describes the editioning views (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_EDITIONING_VIEWS_AE.

See Also: ["ALL_EDITIONING_VIEWS_AE"](#) on page 2-55

USER_ENCRYPTED_COLUMNS

USER_ENCRYPTED_COLUMNS maintains encryption algorithm information for all encrypted columns in all tables in the user's schema. Its columns (except for OWNER) are the same as those in ["ALL_ENCRYPTED_COLUMNS"](#) on page 2-56.

USER_EPG_DAD_AUTHORIZATION

USER_EPG_DAD_AUTHORIZATION describes the DADs that are authorized to use the user's privileges. Its columns (except for USERNAME) are the same as those in ["DBA_EPG_DAD_AUTHORIZATION"](#) on page 4-74.

USER_ERRORS

USER_ERRORS describes the current errors on the stored objects owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ERRORS.

See Also: ["ALL_ERRORS"](#) on page 2-57

USER_ERRORS_AE

USER_ERRORS_AE describes the current errors on the stored objects (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ERRORS_AE.

See Also: ["ALL_ERRORS_AE"](#) on page 2-58

USER_EVALUATION_CONTEXT_TABLES

USER_EVALUATION_CONTEXT_TABLES describes the tables in the rule evaluation contexts owned by the current user. Its columns (except for EVALUATION_CONTEXT_OWNER) are the same as those in ALL_EVALUATION_CONTEXT_TABLES.

See Also: ["ALL_EVALUATION_CONTEXT_TABLES"](#) on page 2-58

USER_EVALUATION_CONTEXT_VARS

USER_EVALUATION_CONTEXT_VARS describes the variables in the rule evaluation contexts owned by the current user. Its columns (except for EVALUATION_CONTEXT_OWNER) are the same as those in ALL_EVALUATION_CONTEXT_VARS.

See Also: ["ALL_EVALUATION_CONTEXT_VARS"](#) on page 2-59

USER_EVALUATION_CONTEXTS

USER_EVALUATION_CONTEXTS describes the rule evaluation contexts owned by the current user. Its columns (except for EVALUATION_CONTEXT_OWNER) are the same as those in ALL_EVALUATION_CONTEXTS.

See Also: ["ALL_EVALUATION_CONTEXTS"](#) on page 2-59

USER_EXTENTS

USER_EXTENTS describes the extents comprising the segments owned by the current user's objects. Its columns (except for OWNER, FILE_ID, BLOCK_ID, and RELATIVE_FNO) are the same as those in DBA_EXTENTS.

See Also: ["DBA_EXTENTS"](#) on page 4-75

USER_EXTERNAL_LOCATIONS

USER_EXTERNAL_LOCATIONS describes the locations (data sources) of the external tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_EXTERNAL_LOCATIONS.

See Also: ["ALL_EXTERNAL_LOCATIONS"](#) on page 2-60

USER_EXTERNAL_TABLES

USER_EXTERNAL_TABLES describes the external tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_EXTERNAL_TABLES.

See Also: ["ALL_EXTERNAL_TABLES"](#) on page 2-60

USER_FILE_GROUP_EXPORT_INFO

USER_FILE_GROUP_EXPORT_INFO shows export-related information for all file groups that the current user can manage. Its columns (except for FILE_GROUP_OWNER) are the same as those in ["ALL_FILE_GROUP_EXPORT_INFO"](#) on page 2-61.

USER_FILE_GROUP_FILES

USER_FILE_GROUP_FILES shows the file set for each versioned group owned by the current user. Its columns (except for FILE_GROUP_OWNER) are the same as those in "[ALL_FILE_GROUP_FILES](#)" on page 2-62.

USER_FILE_GROUP_TABLES

USER_FILE_GROUP_TABLES shows information about tables owned by the current user that can be imported using the file set. Its columns (except for FILE_GROUP_OWNER) are the same as those in "[ALL_FILE_GROUP_TABLES](#)" on page 2-62.

USER_FILE_GROUP_TABLESPACES

USER_FILE_GROUP_TABLESPACES shows information about the transportable tablespaces present (partially or completely) in the file set owned by the current user (when the file set contains dump files). Its columns (except for FILE_GROUP_OWNER) are the same as those in "[ALL_FILE_GROUP_TABLESPACES](#)" on page 2-63.

USER_FILE_GROUP_VERSIONS

USER_FILE_GROUP_VERSIONS shows top-level version information for all file groups owned by the current user. Its columns (except for FILE_GROUP_OWNER) are the same as those in "[ALL_FILE_GROUP_VERSIONS](#)" on page 2-63.

USER_FILE_GROUPS

USER_FILE_GROUPS shows top-level metadata about file groups owned by the current user. Its columns (except for FILE_GROUP_OWNER) are the same as those in "[ALL_FILE_GROUPS](#)" on page 2-64.

USER_FLASHBACK_ARCHIVE

USER_FLASHBACK_ARCHIVE describes flashback data archives, which consist of multiple tablespaces and historic data from all transactions against tracked tables. The content of this view depends on the privileges of the user who queries it, as follows:

- If the user has the FLASHBACK ARCHIVE ADMINISTER system privilege, then USER_FLASHBACK_ARCHIVE describes the flashback archives for all users who have been granted the FLASHBACK ARCHIVE object privilege.
- If the user does not have the FLASHBACK ARCHIVE ADMINISTER system privilege, then USER_FLASHBACK_ARCHIVE describes flashback archives for which the current user has been granted the FLASHBACK ARCHIVE object privilege.

The columns of the USER_FLASHBACK_ARCHIVE view are the same as those in DBA_FLASHBACK_ARCHIVE.

See Also: "[DBA_FLASHBACK_ARCHIVE](#)" on page 4-83

USER_FLASHBACK_ARCHIVE_TABLES

USER_FLASHBACK_ARCHIVE_TABLES displays information about the tables owned by the current user that are enabled for Flashback Archive. Its columns are the same as those in DBA_FLASHBACK_ARCHIVE_TABLES.

See Also: ["DBA_FLASHBACK_ARCHIVE_TABLES"](#) on page 4-83

USER_FLASHBACK_TXN_REPORT

USER_FLASHBACK_TXN_REPORT displays information about the compensating transactions owned by the current user that have been committed in the database. Its columns (except for USERNAME) are the same as those in DBA_FLASHBACK_TXN_REPORT.

See Also: ["DBA_FLASHBACK_TXN_REPORT"](#) on page 4-84

USER_FLASHBACK_TXN_STATE

USER_FLASHBACK_TXN_STATE displays information about the compensating status of the transactions owned by the current user. Its columns (except for USERNAME) are the same as those in DBA_FLASHBACK_TXN_STATE.

See Also: ["DBA_FLASHBACK_TXN_STATE"](#) on page 4-84

USER_FREE_SPACE

USER_FREE_SPACE describes the free extents in the tablespaces accessible to the current user. Its columns are the same as those in DBA_FREE_SPACE.

See Also: ["DBA_FREE_SPACE"](#) on page 4-85

USER_HISTOGRAMS

USER_HISTOGRAMS is a synonym for USER_TAB_HISTOGRAMS.

See Also: ["USER_TAB_HISTOGRAMS"](#) on page 6-103

USER_IDENTIFIERS

USER_IDENTIFIERS displays information about the identifiers in the stored objects owned by the current user. Its columns (except for OWNER) are the same as those in ALL_IDENTIFIERS.

See Also: ["ALL_IDENTIFIERS"](#) on page 2-64

USER_IND_COLUMNS

USER_IND_COLUMNS describes the columns of the indexes owned by the current user and columns of indexes on tables owned by the current user. Its columns (except for INDEX_OWNER and TABLE_OWNER) are the same as those in ["ALL_IND_COLUMNS"](#) on page 2-65.

USER_IND_EXPRESSIONS

USER_IND_EXPRESSIONS describes expressions of function-based indexes on tables owned by the current user. Its columns (except for INDEX_OWNER and TABLE_OWNER) are the same as those in ["ALL_IND_EXPRESSIONS"](#) on page 2-66.

USER_IND_PARTITIONS

USER_IND_PARTITIONS describes, for each index partition owned by the current user, the partition-level partitioning information, the storage parameters for the partition, and various partition statistics analyzed by ANALYZE statements. Its columns are the same as those in ["ALL_IND_PARTITIONS"](#) on page 2-66.

USER_IND_PENDING_STATS

USER_IND_PENDING_STATS describes pending statistics for all tables, partitions, and subpartitions owned by the current user. Its columns (except for OWNER) are the same as those in ["ALL_IND_PENDING_STATS"](#) on page 2-69.

USER_IND_STATISTICS

USER_IND_STATISTICS displays optimizer statistics for the indexes on the tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_IND_STATS.

See Also: ["ALL_IND_STATISTICS"](#) on page 2-69

USER_IND_SUBPARTITIONS

USER_IND_SUBPARTITIONS describes, for each index subpartition owned by the current user, the partition-level partitioning information, the storage parameters for the subpartition, and various partition statistics collected by ANALYZE statements. Its columns are the same as those in ["ALL_IND_SUBPARTITIONS"](#) on page 2-70.

USER_INDEXES

USER_INDEXES describes indexes owned by the current user. To gather statistics for this view, use the SQL ANALYZE statement. This view supports parallel partitioned index scans. Its columns (except for OWNER) are the same as those in ["ALL_INDEXES"](#) on page 2-72.

USER_INDEXTYPE_ARRAYTYPES

USER_INDEXTYPE_ARRAYTYPES displays information about the array types specified by the indextypes owned by the current user. Its columns are the same as those in ALL_INDEXTYPE_ARRAYTYPES.

See Also: ["ALL_INDEXTYPE_ARRAYTYPES"](#) on page 2-76

USER_INDEXTYPE_COMMENTS

USER_INDEXTYPE_COMMENTS displays comments for the user-defined indextypes owned by the current user. Its columns are the same as those in ALL_INDEXTYPE_COMMENTS.

See Also: ["ALL_INDEXTYPE_COMMENTS"](#) on page 2-76

USER_INDEXTYPE_OPERATORS

USER_INDEXTYPE_OPERATORS lists all the operators supported by indextypes owned by the current user. Its columns are the same as those in ALL_INDEXTYPE_OPERATORS.

See Also: ["ALL_INDEXTYPE_OPERATORS"](#) on page 2-77

USER_INDEXTYPES

USER_INDEXTYPES describes the indextypes owned by the current user. Its columns are the same as those in ALL_INDEXTYPES.

See Also: ["ALL_INDEXTYPES"](#) on page 2-77

USER_INTERNAL_TRIGGERS

USER_INTERNAL_TRIGGERS describes the internal triggers on all tables owned by the current user. Its columns are the same as those in ["ALL_INTERNAL_TRIGGERS"](#) on page 2-78.

USER_JAVA_ARGUMENTS

USER_JAVA_ARGUMENTS displays argument information about the stored Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_ARGUMENTS.

See Also: ["ALL_JAVA_ARGUMENTS"](#) on page 2-78

USER_JAVA_CLASSES

USER_JAVA_CLASSES displays class level information about the stored Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_CLASSES.

See Also: ["ALL_JAVA_CLASSES"](#) on page 2-79

USER_JAVA_COMPILER_OPTIONS

USER_JAVA_COMPILER_OPTIONS displays information about the native compiler options owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_COMPILER_OPTIONS.

See Also: ["ALL_JAVA_COMPILER_OPTIONS"](#) on page 2-80

USER_JAVA_DERIVATIONS

USER_JAVA_DERIVATIONS displays mapping information about Java source objects and their derived Java class objects and Java resource objects for the Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_DERIVATIONS.

See Also: ["ALL_JAVA_DERIVATIONS"](#) on page 2-80

USER_JAVA_FIELDS

USER_JAVA_FIELDS displays field information about the stored Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_FIELDS.

See Also: ["ALL_JAVA_FIELDS"](#) on page 2-81

USER_JAVA_IMPLEMENTES

USER_JAVA_IMPLEMENTES describes interfaces implemented by the stored Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_IMPLEMENTES.

See Also: ["ALL_JAVA_IMPLEMENTES"](#) on page 2-82

USER_JAVA_INNERS

USER_JAVA_INNERS displays information about inner classes referred to by the stored Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_INNERS.

See Also: ["ALL_JAVA_INNERS"](#) on page 2-82

USER_JAVA_LAYOUTS

USER_JAVA_LAYOUTS displays class layout information about the stored Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_LAYOUTS.

See Also: ["ALL_JAVA_LAYOUTS"](#) on page 2-83

USER_JAVA_METHODS

USER_JAVA_METHODS displays method information about the stored Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_METHODS.

See Also: ["ALL_JAVA_METHODS"](#) on page 2-84

USER_JAVA_NCOMPS

USER_JAVA_NCOMPS displays ncomp-related information about the Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_NCOMPS.

See Also: ["ALL_JAVA_NCOMPS"](#) on page 2-85

USER_JAVA_POLICY

USER_JAVA_POLICY describes Java security permissions for the current user. Its columns are the same as those in DBA_JAVA_POLICY.

See Also: ["DBA_JAVA_POLICY"](#) on page 5-46

USER_JAVA_RESOLVERS

USER_JAVA_RESOLVERS displays information about resolvers of the Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_RESOLVERS.

See Also: ["ALL_JAVA_RESOLVERS"](#) on page 2-85

USER_JAVA_THROWS

USER_JAVA_THROWS displays information about exceptions thrown from methods of the Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_THROWS.

See Also: ["ALL_JAVA_THROWS"](#) on page 2-86

USER_JOBS

USER_JOBS describes the jobs owned by the current user. Its columns are the same as those in DBA_JOBS.

See Also: ["DBA_JOBS"](#) on page 5-47

USER_JOIN_IND_COLUMNS

USER_JOIN_IND_COLUMNS describes all join conditions owned by the current user. Its columns are the same as those in ["ALL_JOIN_IND_COLUMNS"](#) on page 2-87.

USER_LIBRARIES

USER_LIBRARIES describes the libraries owned by the current user. Its columns (except for OWNER) are the same as those in ALL_LIBRARIES.

See Also: ["ALL_LIBRARIES"](#) on page 2-87

USER_LOB_PARTITIONS

USER_LOB_PARTITIONS displays the LOB partitions contained in the tables owned by the current user. Its columns are the same as those in ["ALL_LOB_PARTITIONS"](#) on page 2-88.

USER_LOB_SUBPARTITIONS

USER_LOB_SUBPARTITIONS displays partition-level attributes of the LOB data subpartitions owned by the current user. Its columns are the same as those in ["ALL_LOB_SUBPARTITIONS"](#) on page 2-90.

- DBA_LOB_TEMPLATES describes all LOB subpartition templates in the database.

USER_LOB_TEMPLATES

USER_LOB_TEMPLATES describes the LOB subpartition templates owned by the current user. Its columns (except for USER_NAME) are the same as those in ALL_LOB_TEMPLATES.

See Also: ["ALL_LOB_TEMPLATES"](#) on page 2-92

USER_LOBS

USER_LOBS displays the user's CLOBs and BLOBs contained in the user's tables. BFILEs are stored outside the database, so they are not described by this view. This view's columns are the same as those in ["ALL_LOBS"](#) on page 2-93.

USER_LOG_GROUP_COLUMNS

USER_LOG_GROUP_COLUMNS describes columns that are owned by the current user and that are specified in log groups. Its columns are the same as those in ["ALL_LOG_GROUP_COLUMNS"](#) on page 2-95.

USER_LOG_GROUPS

USER_LOG_GROUPS describes log group definitions on tables owned by the current user. Its columns are the same as those in ["ALL_LOG_GROUPS"](#) on page 2-95.

USER_MEASURE_FOLDER_CONTENTS

USER_MEASURE_FOLDER_CONTENTS describes the contents of the OLAP measure folders owned by the current user. Its columns (except for OWNER) are the same as those in ALL_MEASURE_FOLDER_CONTENTS.

USER_MEASURE_FOLDERS

USER_MEASURE_FOLDERS describes the OLAP measure folders owned by the current user. Its columns (except for OWNER) are the same as those in ALL_MEASURE_FOLDERS.

USER_METHOD_PARAMS

USER_METHOD_PARAMS describes the method parameters of the object types owned by the current user. Its columns (except for OWNER) are the same as those in ALL_METHOD_PARAMS.

See Also: ["ALL_METHOD_PARAMS"](#) on page 2-97

USER_METHOD_RESULTS

USER_METHOD_RESULTS describes the method results of the object types owned by the current user. Its columns (except for OWNER) are the same as those in ALL_METHOD_RESULTS.

See Also: ["ALL_METHOD_RESULTS"](#) on page 2-98

USER_MINING_MODEL_ATTRIBUTES

USER_MINING_MODEL_ATTRIBUTES describes the mining model attributes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_MINING_MODEL_ATTRIBUTES.

See Also: ["ALL_MINING_MODEL_ATTRIBUTES"](#) on page 2-98

USER_MINING_MODEL_SETTINGS

USER_MINING_MODEL_SETTINGS describes the mining model settings owned by the current user. Its columns (except for OWNER) are the same as those in ALL_MINING_MODEL_SETTINGS.

See Also: ["ALL_MINING_MODEL_SETTINGS"](#) on page 2-99

USER_MINING_MODELS

USER_MINING_MODELS describes the mining models owned by the current user. Its columns (except for OWNER) are the same as those in ALL_MINING_MODELS.

See Also: ["ALL_MINING_MODELS"](#) on page 2-100

USER_MVIEW_AGGREGATES

USER_MVIEW_AGGREGATES describes the grouping functions (aggregated measures) that appear in the SELECT list of aggregated materialized views owned by the current user. Its columns are the same as those in ["ALL_MVIEW_AGGREGATES"](#) on page 2-101.

USER_MVIEW_ANALYSIS

USER_MVIEW_ANALYSIS describes all materialized views owned by the current user that potentially support query rewrite and that provide additional information for analysis by applications. Its columns are the same as those in ["ALL_MVIEW_ANALYSIS"](#) on page 2-102.

Note: This view excludes materialized views that reference remote tables or that include references to non-static values such as SYSDATE or USER. This view also excludes materialized views that were created as snapshots prior to Oracle8i and that were never altered to enable query rewrite.

USER_MVIEW_COMMENTS

USER_MVIEW_COMMENTS displays comments on the materialized views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_MVIEW_COMMENTS.

See Also: ["ALL_MVIEW_COMMENTS"](#) on page 2-103

USER_MVIEW_DETAIL_PARTITION

USER_MVIEW_DETAIL_PARTITION displays freshness information for all materialized views, with respect to a PCT detail partition, owned by the current user. Its columns are the same as those in ["ALL_MVIEW_DETAIL_PARTITION"](#) on page 2-103.

USER_MVIEW_DETAIL_RELATIONS

USER_MVIEW_DETAIL_RELATIONS represents the named detail relations that are either in the FROM list of a materialized view, or that are indirectly referenced through views in the FROM list. Its columns are the same as those in "[ALL_MVIEW_DETAIL_RELATIONS](#)" on page 2-104.

USER_MVIEW_DETAIL_SUBPARTITION

USER_MVIEW_DETAIL_SUBPARTITION displays freshness information for all materialized views, with respect to a PCT detail subpartition, owned by the current user. Its columns are the same as those in "[ALL_MVIEW_DETAIL_SUBPARTITION](#)" on page 2-105.

USER_MVIEW_JOINS

USER_MVIEW_JOINS describes a join between two columns in the WHERE clause of a subquery that defines a materialized view. Its columns are the same as those in "[ALL_MVIEW_JOINS](#)" on page 2-105.

USER_MVIEW_KEYS

USER_MVIEW_KEYS describes the columns or expressions in the SELECT list upon which materialized views in the current user's schema are based. Its columns are the same as those in "[ALL_MVIEW_KEYS](#)" on page 2-106.

USER_MVIEW_LOGS

USER_MVIEW_LOGS describes all materialized view logs owned by the current user. Its columns are the same as those in [ALL_MVIEW_LOGS](#).

See Also: "[ALL_MVIEW_LOGS](#)" on page 2-107

USER_MVIEW_REFRESH_TIMES

USER_MVIEW_REFRESH_TIMES describes refresh times of the materialized views owned by the current user. Its columns are the same as those in [ALL_MVIEW_REFRESH_TIMES](#).

See Also: "[ALL_MVIEW_REFRESH_TIMES](#)" on page 2-107

USER_MVIEWS

USER_MVIEWS describes all materialized views owned by the current user. Its columns are the same as those in [ALL_MVIEWS](#).

See Also: "[ALL_MVIEWS](#)" on page 2-108

USER_NESTED_TABLE_COLS

USER_NESTED_TABLE_COLS describes the columns of the nested tables owned by the current user. Its columns (except for OWNER) are the same as those in "[ALL_NESTED_TABLE_COLS](#)" on page 2-111. To gather statistics for this view, use the [ANALYZE SQL](#) statement.

USER_NESTED_TABLES

USER_NESTED_TABLES describes the nested tables in tables owned by the current user. Its columns are the same as those in ["ALL_NESTED_TABLES"](#) on page 2-113.

USER_NETWORK_ACL_PRIVILEGES

USER_NETWORK_ACL_PRIVILEGES describes the status of the network privileges for the current user to access network hosts.

Column	Datatype	NULL	Description
HOST	VARCHAR2 (1000)		Network host
LOWER_PORT	NUMBER (5)		Lower bound of the port range
UPPER_PORT	NUMBER (5)		Upper bound of the port range
PRIVILEGE	CHAR (7)		Network privilege
STATUS	VARCHAR2 (7)		Privilege status: ■ DENIED ■ GRANTED

USER_OBJ_AUDIT_OPTS

USER_OBJ_AUDIT_OPTS describes auditing options on all objects owned by the current user. Its columns (except for OWNER) are the same as those in ["DBA_OBJ_AUDIT_OPTS"](#) on page 5-62.

USER_OBJ_COLATTRS

USER_OBJ_COLATTRS describes object columns and attributes contained in the tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_OBJ_COLATTRS.

See Also: ["ALL_OBJ_COLATTRS"](#) on page 2-113

USER_OBJECT_SIZE

USER_OBJECT_SIZE lists the sizes, in bytes, of various PL/SQL objects. Its columns are the same as those in ["DBA_OBJECT_SIZE"](#) on page 5-63.

USER_OBJECT_TABLES

USER_OBJECT_TABLES describes the object tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_OBJECT_TABLES.

See Also: ["ALL_OBJECT_TABLES"](#) on page 2-114

USER_OBJECTS

USER_OBJECTS describes all objects owned by the current user. Its columns are the same as those in ["ALL_OBJECTS"](#) on page 2-117.

USER_OBJECTS_AE

USER_OBJECTS_AE describes the objects (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_OBJECTS_AE.

See Also: ["ALL_OBJECTS_AE"](#) on page 2-117

USER_OPANCILLARY

USER_OPANCILLARY provides ancillary information for operators owned by the current user. Its columns are the same as those in ["ALL_OPANCILLARY"](#) on page 2-118.

USER_OPARGUMENTS

USER_OPARGUMENTS provides argument information for operator bindings owned by the current user. Its columns are the same as those in ["ALL_OPARGUMENTS"](#) on page 2-119.

USER_OPBINDINGS

USER_OPBINDINGS describes the binding functions and methods on the operators owned by the current user. Its columns are the same as those in ALL_OPBINDINGS.

See Also: ["ALL_OPBINDINGS"](#) on page 2-119

USER_OPERATOR_COMMENTS

USER_OPERATOR_COMMENTS displays comments for the user-defined operators owned by the current user. Its columns are the same as those in ALL_OPERATOR_COMMENTS.

See Also: ["ALL_OPERATOR_COMMENTS"](#) on page 2-120

USER_OPERATORS

USER_OPERATORS describes all operators owned by the current user. Its columns are the same as those in ALL_OPERATORS.

See Also: ["ALL_OPERATORS"](#) on page 2-120

USER_OUTLINE_HINTS

USER_OUTLINE_HINTS describes the set of hints stored in the outlines owned by the current user. Its columns (except for OWNER) are the same as those in DBA_OUTLINE_HINTS.

See Also: ["DBA_OUTLINE_HINTS"](#) on page 5-65

USER_OUTLINES

USER_OUTLINES describes the stored outlines owned by the current user. Its columns (except for OWNER) are the same as those in DBA_OUTLINES.

See Also: ["DBA_OUTLINES"](#) on page 5-65

USER_PARALLEL_EXECUTE_CHUNKS

USER_PARALLEL_EXECUTE_CHUNKS displays the chunks for tasks created by the current user. Its columns (except for TASK_OWNER) are the same as those in DBA_PARALLEL_EXECUTE_CHUNKS.

See Also: ["DBA_PARALLEL_EXECUTE_CHUNKS"](#) on page 5-67

USER_PARALLEL_EXECUTE_TASKS

USER_PARALLEL_EXECUTE_TASKS displays the tasks created by the current user. Its columns (except for TASK_OWNER) are the same as those in DBA_PARALLEL_EXECUTE_TASKS.

See Also: ["DBA_PARALLEL_EXECUTE_TASKS"](#) on page 5-67

USER_PART_COL_STATISTICS

USER_PART_COL_STATISTICS displays column statistics and histogram information for the table partitions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PART_COL_STATISTICS.

See Also: ["ALL_PART_COL_STATISTICS"](#) on page 3-1

USER_PART_HISTOGRAMS

USER_PART_HISTOGRAMS displays the histogram data (endpoints per histogram) for the histograms on the table partitions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PART_HISTOGRAMS.

See Also: ["ALL_PART_HISTOGRAMS"](#) on page 3-2

USER_PART_INDEXES

USER_PART_INDEXES displays the object-level partitioning information for the partitioned indexes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PART_INDEXES.

See Also: ["ALL_PART_INDEXES"](#) on page 3-3

USER_PART_KEY_COLUMNS

USER_PART_KEY_COLUMNS describes the partitioning key columns for the partitioned objects owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PART_KEY_COLUMNS.

See Also: ["ALL_PART_KEY_COLUMNS"](#) on page 3-5

USER_PART_LOBS

USER_PART_LOBS displays table-level information about the partitioned LOBs owned by the current user, including default attributes for LOB data partitions. Its columns (except for TABLE_OWNER) are the same as those in ALL_PART_LOBS.

See Also: ["ALL_PART_LOBS"](#) on page 3-5

USER_PART_TABLES

USER_PART_TABLES displays the object-level partitioning information for the partitioned tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PART_TABLES.

See Also: ["ALL_PART_TABLES"](#) on page 3-8

USER_PARTIAL_DROP_TABS

USER_PARTIAL_DROP_TABS describes all tables in the schema of the current user that have partially completed DROP COLUMN operations. Its columns are the same as those in ["ALL_PARTIAL_DROP_TABS"](#) on page 3-11.

USER_PASSWORD_LIMITS

USER_PASSWORD_LIMITS describes the password profile parameters that are assigned to the user.

Column	Datatype	NULL	Description
RESOURCE_NAME	VARCHAR2 (32)	NOT NULL	Name of the password resource
LIMIT	VARCHAR2 (40)		Value of the resource limit

USER_PENDING_CONV_TABLES

USER_PENDING_CONV_TABLES describes the pending conversion tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PENDING_CONV_TABLES.

See Also: ["ALL_PENDING_CONV_TABLES"](#) on page 3-11

USER_PLSQL_OBJECT_SETTINGS

USER_PLSQL_OBJECT_SETTINGS displays information about the compiler settings for the stored objects owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PLSQL_OBJECT_SETTINGS.

See Also: ["ALL_PLSQL_OBJECT_SETTINGS"](#) on page 3-11

USER_POLICIES

USER_POLICIES describes all Oracle Virtual Private Database (VPD) security policies associated with objects owned by the current user. Its columns (except for OBJECT_OWNER) are the same as those in ALL_POLICIES.

See Also: ["ALL_POLICIES"](#) on page 3-12

USER_POLICY_CONTEXTS

USER_POLICY_CONTEXTS describes the driving contexts defined for the synonyms, tables, and views owned by the current user. Its columns (except for OBJECT_OWNER) are the same as those in ALL_POLICY_CONTEXTS.

See Also: ["ALL_POLICY_CONTEXTS"](#) on page 3-13

USER_POLICY_GROUPS

USER_POLICY_GROUPS describes the policy groups defined for the synonyms, tables, and views owned by the current user. Its columns (except for OBJECT_OWNER) are the same as those in ALL_POLICY_GROUPS.

See Also: ["ALL_POLICY_GROUPS"](#) on page 3-14

USER_PROCEEDURES

USER_PROCEEDURES lists all functions and procedures, along with their associated properties. Its columns (except OWNER) are the same as those in ["ALL_PROCEEDURES"](#) on page 3-14.

USER_PROXIES

USER_PROXIES displays information about connections the current user is allowed to proxy. Its columns (except for PROXY) are the same as those in DBA_PROXIES.

See Also: ["DBA_PROXIES"](#) on page 5-71

USER_PUBLISHED_COLUMNS

USER_PUBLISHED_COLUMNS describes the source table columns owned by the current user which have been published for the source tables. This view is intended for use by Change Data Capture subscribers. Its columns (except for CHANGE_TABLE_SCHEMA and CHANGE_TABLE_NAME) are the same as those in DBA_PUBLISHED_COLUMNS.

See Also: ["DBA_PUBLISHED_COLUMNS"](#) on page 5-72

USER_QUEUE_SCHEDULES

USER_QUEUE_SCHEDULES describes the propagation schedules whose source queues are owned by the current user. Its columns (except for SCHEMA) are the same as those in ALL_QUEUE_SCHEDULES.

See Also: ["ALL_QUEUE_SCHEDULES"](#) on page 3-16

USER_QUEUE_SUBSCRIBERS

USER_QUEUE_SUBSCRIBERS displays the list of subscribers on queues that are under the current user's schema. Its columns (except for OWNER) are the same as those in ["ALL_QUEUE_SUBSCRIBERS"](#) on page 3-18.

USER_QUEUE_TABLES

USER_QUEUE_TABLES describes the queues in the queue tables created in the current user's schema. Its columns (except for OWNER) are the same as those in ALL_QUEUE_TABLES.

See Also: ["ALL_QUEUE_TABLES"](#) on page 3-18

USER_QUEUES

USER_QUEUES describes the operational characteristics of every queue in the user's schema. Its columns (except for OWNER) are the same as those in "ALL_QUEUES" on page 3-19.

See Also: *Oracle Streams Advanced Queuing User's Guide* for more information about these views and Advanced Queuing

USER_RECYCLEBIN

USER_RECYCLEBIN displays information about the recycle bin owned by the current user. Its columns (except for OWNER) are the same as those in DBA_RECYCLEBIN.

See Also: "DBA_RECYCLEBIN" on page 5-75

USER_REFRESH

USER_REFRESH describes all refresh groups owned by the current user. Its columns are the same as those in "ALL_REFRESH" on page 3-20.

USER_REFRESH_CHILDREN

USER_REFRESH_CHILDREN lists all the objects in refresh groups owned by the current user. Its columns are the same as those in "ALL_REFRESH_CHILDREN" on page 3-21.

USER_REFS

USER_REFS describes the REF columns and REF attributes in the object type columns of tables owned by the current user. Its columns are the same as those in "ALL_REFS" on page 3-22.

USER_REGISTERED_MVIEWS

USER_REGISTERED_MVIEWS describes all registered materialized views (registered at a master site or a master materialized view site) owned by the current user. Its columns are the same as those in ALL_REGISTERED_MVIEWS.

See Also: "ALL_REGISTERED_MVIEWS" on page 3-22

USER_REGISTRY

USER_REGISTRY displays information about the components owned by the current user that are loaded into the component registry. Its columns are the same as those in DBA_REGISTRY.

See Also: "DBA_REGISTRY" on page 5-78

USER_RESOURCE_LIMITS

USER_RESOURCE_LIMITS displays the resource limits for the current user.

Column	Datatype	NULL	Description
RESOURCE_NAME	VARCHAR2 (32)	NOT NULL	Name of the resource

Column	Datatype	NULL	Description
LIMIT	VARCHAR2 (40)		Limit placed on this resource

USER_RESUMABLE

USER_RESUMABLE displays the resumable statements executed by the current user. Its columns (except for USER_ID) are the same as those in DBA_RESUMABLE.

See Also: ["DBA_RESUMABLE"](#) on page 5-81

USER_REWRITE_EQUIVALENCES

USER_REWRITE_EQUIVALENCES describes the rewrite equivalences owned by the current user. Its columns are the same as those in ALL_REWRITE_EQUIVALENCES.

See Also: ["ALL_REWRITE_EQUIVALENCES"](#) on page 3-23

USER_ROLE_PRIVS

USER_ROLE_PRIVS describes the roles granted to the current user.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (30)		Name of the user, or PUBLIC
GRANTED_ROLE	VARCHAR2 (30)		Name of the role granted to the user
ADMIN_OPTION	VARCHAR2 (3)		Indicates whether the grant was with the ADMIN OPTION (YES) or not (NO)
DEFAULT_ROLE	VARCHAR2 (3)		Indicates whether the role is designated as a DEFAULT ROLE for the user (YES) or not (NO)
OS_GRANTED	VARCHAR2 (3)		Indicates whether the role was granted by the operating system (YES) or not (NO); occurs if the OS_ROLES initialization parameter is true

USER_RSRC_CONSUMER_GROUP_PRIVS

USER_RSRC_CONSUMER_GROUP_PRIVS displays information about the resource consumer groups to which the current user is assigned. Its columns (except for GRANTEE) are the same as those in DBA_RSRC_CONSUMER_GROUP_PRIVS.

See Also: ["DBA_RSRC_CONSUMER_GROUP_PRIVS"](#) on page 5-84

USER_RSRC_MANAGER_SYSTEM_PRIVS

USER_RSRC_MANAGER_SYSTEM_PRIVS displays information about the users who are granted system privileges for the DBMS_RESOURCE_MANAGER package. Its columns (except for GRANTEE) are the same as those in DBA_RSRC_MANAGER_SYSTEM_PRIVS.

See Also: ["DBA_RSRC_MANAGER_SYSTEM_PRIVS"](#) on page 5-86

USER_RULE_SET_RULES

USER_RULE_SET_RULES describes the rules in the rule sets owned by the current user. Its columns (except for RULE_SET_OWNER) are the same as those in ALL_RULE_SET_RULES.

See Also: ["ALL_RULE_SET_RULES"](#) on page 3-24

USER_RULE_SETS

USER_RULE_SETS describes the rule sets owned by the current user. Its columns (except for RULE_SET_OWNER) are the same as those in ALL_RULE_SETS.

See Also: ["ALL_RULE_SETS"](#) on page 3-24

USER_RULES

USER_RULES describes the rules owned by the current user. Its columns (except for RULE_OWNER) are the same as those in ALL_RULES.

See Also: ["ALL_RULES"](#) on page 3-25

USER_SCHEDULER_CHAIN_RULES

USER_SCHEDULER_CHAIN_RULES displays information about the rules for the chains owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_CHAIN_RULES.

See Also: ["ALL_SCHEDULER_CHAIN_RULES"](#) on page 3-25

USER_SCHEDULER_CHAIN_STEPS

USER_SCHEDULER_CHAIN_STEPS displays information about the defined steps of the chains owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_CHAIN_STEPS.

See Also: ["ALL_SCHEDULER_CHAIN_STEPS"](#) on page 3-26

USER_SCHEDULER_CHAINS

USER_SCHEDULER_CHAINS displays information about the chains owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_CHAINS.

See Also: ["ALL_SCHEDULER_CHAINS"](#) on page 3-27

USER_SCHEDULER_CREDENTIALS

USER_SCHEDULER_CREDENTIALS displays information about the credentials owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_CREDENTIALS.

See Also: ["ALL_SCHEDULER_CREDENTIALS"](#) on page 3-28

USER_SCHEDULER_DB_DESTS

USER_SCHEDULER_DB_DESTS displays information about the destination objects owned by the current user pointing to remote databases. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_DB_DESTS.

See Also: ["ALL_SCHEDULER_DB_DESTS"](#) on page 3-28

USER_SCHEDULER_DESTS

USER_SCHEDULER_DESTS displays information about the destination objects for jobs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_DESTS.

See Also: ["ALL_SCHEDULER_DESTS"](#) on page 3-29

USER_SCHEDULER_FILE_WATCHERS

USER_SCHEDULER_FILE_WATCHERS displays information about the Scheduler file watch requests owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_FILE_WATCHERS.

See Also: ["ALL_SCHEDULER_FILE_WATCHERS"](#) on page 3-30

USER_SCHEDULER_GROUP_MEMBERS

USER_SCHEDULER_GROUP_MEMBERS displays information about the members of the Scheduler object groups owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_GROUP_MEMBERS.

See Also: ["ALL_SCHEDULER_GROUP_MEMBERS"](#) on page 3-31

USER_SCHEDULER_GROUPS

USER_SCHEDULER_GROUPS displays information about the Scheduler object groups owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_GROUPS.

See Also: ["ALL_SCHEDULER_GROUPS"](#) on page 3-31

USER_SCHEDULER_JOB_ARGS

USER_SCHEDULER_JOB_ARGS displays information about the arguments of the Scheduler jobs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_JOB_ARGS.

See Also: ["ALL_SCHEDULER_JOB_ARGS"](#) on page 3-32

USER_SCHEDULER_JOB_DESTS

USER_SCHEDULER_JOB_DESTS displays information about the state of the jobs owned by the current user at each of their destinations. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_JOB_DESTS.

See Also: ["ALL_SCHEDULER_JOB_DESTS"](#) on page 3-33

USER_SCHEDULER_JOB_LOG

USER_SCHEDULER_JOB_LOG displays log information for the Scheduler jobs owned by the current user. Its columns are the same as those in ALL_SCHEDULER_JOB_LOG.

See Also: ["ALL_SCHEDULER_JOB_LOG"](#) on page 3-34

USER_SCHEDULER_JOB_RUN_DETAILS

USER_SCHEDULER_JOB_RUN_DETAILS displays log run details for the Scheduler jobs owned by the current user. Its columns are the same as those in ALL_SCHEDULER_JOB_RUN_DETAILS.

See Also: ["ALL_SCHEDULER_JOB_RUN_DETAILS"](#) on page 3-35

USER_SCHEDULER_JOBS

USER_SCHEDULER_JOBS displays information about the Scheduler jobs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_JOBS.

See Also: ["ALL_SCHEDULER_JOBS"](#) on page 3-36

USER_SCHEDULER_NOTIFICATIONS

USER_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for the jobs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_NOTIFICATIONS.

See Also: ["ALL_SCHEDULER_NOTIFICATIONS"](#) on page 3-39

USER_SCHEDULER_PROGRAM_ARGS

USER_SCHEDULER_PROGRAM_ARGS displays information about the arguments of the Scheduler programs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_PROGRAM_ARGS.

See Also: ["ALL_SCHEDULER_PROGRAM_ARGS"](#) on page 3-40

USER_SCHEDULER_PROGRAMS

USER_SCHEDULER_PROGRAMS displays information about the Scheduler programs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_PROGRAMS.

See Also: ["ALL_SCHEDULER_PROGRAMS"](#) on page 3-41

USER_SCHEDULER_REMOTE_JOBSTATE

USER_SCHEDULER_REMOTE_JOBSTATE displays information about the state of the jobs owned by the current user at remote databases. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_REMOTE_JOBSTATE.

See Also: ["ALL_SCHEDULER_REMOTE_JOBSTATE"](#) on page 3-42

USER_SCHEDULER_RUNNING_CHAINS

USER_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of the running chains owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_RUNNING_CHAINS.

See Also: ["ALL_SCHEDULER_RUNNING_CHAINS"](#) on page 3-43

USER_SCHEDULER_RUNNING_JOBS

USER_SCHEDULER_RUNNING_JOBS displays information about the running Scheduler jobs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_RUNNING_JOBS.

See Also: ["ALL_SCHEDULER_RUNNING_JOBS"](#) on page 3-44

USER_SCHEDULER_SCHEDULES

USER_SCHEDULER_SCHEDULES displays information about the Scheduler schedules owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_SCHEDULES.

See Also: ["ALL_SCHEDULER_SCHEDULES"](#) on page 3-45

USER_SEC_RELEVANT_COLS

USER_SEC_RELEVANT_COLS describes the security relevant columns of the security policies for the tables and views owned by the current user. Its columns (except for OBJECT_OWNER) are the same as those in ALL_SEC_RELEVANT_COLS.

See Also: ["ALL_SEC_RELEVANT_COLS"](#) on page 3-49

USER_SECONDARY_OBJECTS

USER_SECONDARY_OBJECTS provides information about secondary objects associated with domain indexes owned by the current user. This view is only relevant in the context of domain indexes. Its columns are the same as those in ["ALL_SECONDARY_OBJECTS"](#) on page 3-49.

USER_SEGMENTS

USER_SEGMENTS describes the storage allocated for the segments owned by the current user's objects. Its columns (except for OWNER, HEADER_FILE, HEADER_BLOCK, and RELATIVE_FNO) are the same as those in DBA_SEGMENTS.

See Also: ["DBA_SEGMENTS"](#) on page 5-95

USER_SEQUENCES

USER_SEQUENCES describes all sequences owned by the current user. Its columns are the same as those in ["ALL_SEQUENCES"](#) on page 3-50.

USER_SOURCE

USER_SOURCE describes the text source of the stored objects owned by the current user. Its columns (except for OWNER) are the same as those in ["ALL_SOURCE"](#) on page 3-51.

USER_SOURCE_AE

USER_SOURCE_AE describes the text source of the stored objects (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SOURCE_AE.

See Also: ["ALL_SOURCE_AE"](#) on page 3-52

USER_SOURCE_TABLES

USER_SOURCE_TABLES describes the source tables owned by the current user for which a change table is defined. This view is intended for use by Change Data Capture subscribers. Its columns are the same as those in DBA_SOURCE_TABLES.

See Also: ["DBA_SOURCE_TABLES"](#) on page 5-98

USER_SQLJ_TYPE_ATTRS

USER_SQLJ_TYPE_ATTRS describes the attributes of the SQLJ object types owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SQLJ_TYPE_ATTRS.

See Also: ["ALL_SQLJ_TYPE_ATTRS"](#) on page 3-52

USER_SQLJ_TYPE_METHODS

USER_SQLJ_TYPE_METHODS describes the methods of the SQLJ object types owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SQLJ_TYPE_METHODS.

See Also: ["ALL_SQLJ_TYPE_METHODS"](#) on page 3-53

USER_SQLJ_TYPES

USER_SQLJ_TYPES describes the SQLJ object types owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SQLJ_TYPES.

See Also: ["ALL_SQLJ_TYPES"](#) on page 3-54

USER_SQLSET

USER_SQLSET displays information about the SQL tuning sets owned by the current user. Its columns (except for OWNER) are the same as those in ["ALL_SQLSET"](#) on page 3-55.

USER_SQLSET_BINDS

USER_SQLSET_BINDS displays the bind values associated with the SQL tuning sets owned by the current user. Its columns (except for SQLSET_OWNER) are the same as those in ["ALL_SQLSET_BINDS"](#) on page 3-55.

USER_SQLSET_PLANS

USER_SQLSET_PLANS describes captured plans for statements in the SQL tuning sets owned by the current user. Its columns (except for SQLSET_OWNER) are the same as those in ["ALL_SQLSET_PLANS"](#) on page 3-56.

USER_SQLSET_REFERENCES

USER_SQLSET_REFERENCES describes whether or not the SQL tuning sets owned by the current user are active. Its columns (except for SQLSET_OWNER) are the same as those in ["ALL_SQLSET_REFERENCES"](#) on page 3-59.

USER_SQLSET_STATEMENTS

USER_SQLSET_STATEMENTS displays information about the SQL statements, along with their statistics, that form the SQL tuning sets owned by the current user. Its columns (except for SQLSET_OWNER) are the same as those in ["ALL_SQLSET_STATEMENTS"](#) on page 3-60.

USER_SQLTUNE_BINDS

USER_SQLTUNE_BINDS displays the bind values associated with the tuned SQL statements owned by the current user. Its columns are the same as those in DBA_SQLTUNE_BINDS.

See Also: ["DBA_SQLTUNE_BINDS"](#) on page 5-102

USER_SQLTUNE_PLANS

USER_SQLTUNE_PLANS displays information about the execution plans generated for the SQL statements owned by the current user during a SQL tuning session. Its columns are the same as those in DBA_SQLTUNE_PLANS.

See Also: ["DBA_SQLTUNE_PLANS"](#) on page 5-102

USER_SQLTUNE_RATIONALE_PLAN

USER_SQLTUNE_RATIONALE_PLAN displays the association between rationales and operations in the execution plan of the SQL statements owned by the current user. Its columns are the same as those in DBA_SQLTUNE_RATIONALE_PLAN.

See Also: ["DBA_SQLTUNE_RATIONALE_PLAN"](#) on page 5-105

USER_SQLTUNE_STATISTICS

USER_SQLTUNE_STATISTICS displays statistics associated with the SQL statements owned by the current user. Its columns are the same as those in DBA_SQLTUNE_STATISTICS.

See Also: ["DBA_SQLTUNE_STATISTICS"](#) on page 5-105

USER_STAT_EXTENSIONS

USER_STAT_EXTENSIONS displays information about the optimizer statistics extensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_STAT_EXTENSIONS.

See Also: ["ALL_STAT_EXTENSIONS"](#) on page 3-61

USER_STORED_SETTINGS

USER_STORED_SETTINGS lists information about the persistent parameter settings for stored PL/SQL units, but only shows information about PL/SQL units owned by the current user. USER_STORED_SETTINGS does not display the OWNER column. The rest of its columns are the same as those in ["ALL_STORED_SETTINGS"](#) on page 3-62.

USER_SUBPART_COL_STATISTICS

USER_SUBPART_COL_STATISTICS provides column statistics and histogram information for subpartitions of subpartitioned objects owned by the current user. Its columns are the same as those in ["ALL_STORED_SETTINGS"](#) on page 3-62.

USER_SUBPART_HISTOGRAMS

USER_SUBPART_HISTOGRAMS lists actual histogram data (end-points per histogram) for histograms on table subpartitions owned by the current user. Its columns are the same as those in ["ALL_SUBPART_HISTOGRAMS"](#) on page 3-72.

USER_SUBPART_KEY_COLUMNS

USER_SUBPART_KEY_COLUMNS lists subpartitioning key columns for composite-partitioned tables (and local indexes on composite-partitioned tables) owned by the current user. Its columns are the same as those in ALL_SUBPART_KEY_COLUMNS.

See Also: ["ALL_SUBPART_KEY_COLUMNS"](#) on page 3-73

USER_SUBPARTITION_TEMPLATES

USER_SUBPARTITION_TEMPLATES describes the subpartition templates owned by the current user. Its columns (except for USER_NAME) are the same as those in ALL_SUBPARTITION_TEMPLATES.

See Also: ["ALL_SUBPARTITION_TEMPLATES"](#) on page 3-73

USER_SUBSCR_REGISTRATIONS

USER_SUBSCR_REGISTRATIONS displays information about the subscription registrations owned by the current user. Its columns are the same as those in DBA_SUBSCR_REGISTRATIONS.

See Also: ["DBA_SUBSCR_REGISTRATIONS"](#) on page 6-13

USER_SUBSCRIBED_COLUMNS

USER_SUBSCRIBED_COLUMNS describes the columns of source tables to which the current user has subscribed. This view is intended for use by Change Data Capture subscribers. Its columns are the same as those in DBA_SUBSCRIBED_COLUMNS.

See Also: ["DBA_SUBSCRIBED_COLUMNS"](#) on page 6-14

USER_SUBSCRIBED_TABLES

USER_SUBSCRIBED_TABLES describes the source tables to which the current user has subscribed. This view is intended for use by Change Data Capture subscribers. Its columns are the same as those in DBA_SUBSCRIBED_TABLES.

See Also: ["DBA_SUBSCRIBED_TABLES"](#) on page 6-15

USER_SUBSCRIPTIONS

USER_SUBSCRIPTIONS describes the subscriptions created by the current user. This view is intended for use by Change Data Capture subscribers. Its columns are the same as those in DBA_SUBSCRIPTIONS.

See Also: ["DBA_SUBSCRIPTIONS"](#) on page 6-15

USER_SYNONYMS

USER_SYNONYMS describes the private synonyms (synonyms owned by the current user). Its columns (except for OWNER) are the same as those in ALL_SYNONYMS.

See Also: ["ALL_SYNONYMS"](#) on page 3-75

USER_SYS_PRIVS

USER_SYS_PRIVS describes system privileges granted to the current user.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2 (30)		Name of the user, or PUBLIC
PRIVILEGE	VARCHAR2 (40)	NOT NULL	System privilege
ADMIN_OPTION	VARCHAR2 (3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)

USER_TAB_COL_STATISTICS

USER_TAB_COL_STATISTICS contains column statistics and histogram information extracted from ["USER_TAB_COLUMNS"](#) on page 6-103. Its columns are the same as those in ["ALL_TAB_COL_STATISTICS"](#) on page 3-77.

USER_TAB_COLS

USER_TAB_COLS describes the columns of the tables, views, and clusters owned by the current user. This view differs from ["USER_TAB_COLUMNS"](#) on page 6-103 in that hidden columns are not filtered out. Its columns (except for OWNER) are the same as those in ["ALL_TAB_COLS"](#) on page 3-77. To gather statistics for this view, use the ANALYZE SQL statement.

USER_TAB_COLUMNS

USER_TAB_COLUMNS describes the columns of the tables, views, and clusters owned by the current user. Its columns (except for OWNER) are the same as those in "[ALL_TAB_COLUMNS](#)" on page 3-79. To gather statistics for this view, use the ANALYZE SQL statement.

USER_TAB_COMMENTS

USER_TAB_COMMENTS displays comments on the tables and views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_COMMENTS.

See Also: "[ALL_TAB_COMMENTS](#)" on page 3-81

USER_TAB_HISTGRM_PENDING_STATS

USER_TAB_HISTGRM_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions owned by the current user. Its columns (except for OWNER) are the same as those in "[ALL_TAB_HISTGRM_PENDING_STATS](#)" on page 3-81.

USER_TAB_HISTOGRAMS

USER_TAB_HISTOGRAMS describes histograms on columns of tables owned by the current user. Its columns are the same as those in "[ALL_TAB_HISTOGRAMS](#)" on page 3-82.

USER_TAB_MODIFICATIONS

USER_TAB_MODIFICATIONS describes modifications to all tables owned by the current user that have been modified since the last time statistics were gathered on the tables. Its columns are the same as those in "[ALL_TAB_MODIFICATIONS](#)" on page 3-82.

Note: This view is populated only for tables with the MONITORING attribute. It is intended for statistics collection over a long period of time. For performance reasons, the Oracle Database does not populate this view immediately when the actual modifications occur. Run the FLUSH_DATABASE_MONITORING_INFO procedure in the DBMS_STATS PL/SQL package to populate this view with the latest information. The ANALYZE_ANY system privilege is required to run this procedure.

USER_TAB_PARTITIONS

USER_TAB_PARTITIONS describes partition-level partitioning information, partition storage parameters, and partition statistics generated by the DBMS_STATS package or the ANALYZE statement for all partitions owned by the current user. Its columns are the same as those in "[ALL_TAB_PARTITIONS](#)" on page 3-83.

USER_TAB_PENDING_STATS

USER_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions owned by the current user. Its columns (except for OWNER) are the same as those in ["ALL_TAB_PENDING_STATS"](#) on page 3-86.

USER_TAB_PRIVS

USER_TAB_PRIVS describes the object grants for which the current user is the object owner, grantor, or grantee. Its columns are the same as those in DBA_TAB_PRIVS.

See Also: ["DBA_TAB_PRIVS"](#) on page 6-18

USER_TAB_PRIVS_MADE

USER_TAB_PRIVS_MADE describes the object grants for which the current user is the object owner. Its columns (except for OWNER) are the same as those in ALL_TAB_PRIVS_MADE.

See Also: ["ALL_TAB_PRIVS_MADE"](#) on page 3-87

USER_TAB_PRIVS_RECD

USER_TAB_PRIVS_RECD describes the object grants for which the current user is the grantee. Its columns (except for GRANTEE) are the same as those in ALL_TAB_PRIVS_RECD.

See Also: ["ALL_TAB_PRIVS_RECD"](#) on page 3-87

USER_TAB_STAT_PREFS

USER_TAB_STAT_PREFS displays information about statistics preferences for the tables owned by the current user. Its columns (except for OWNER) are the same as those in ["ALL_TAB_STAT_PREFS"](#) on page 3-88.

USER_TAB_STATISTICS

USER_TAB_STATISTICS displays optimizer statistics for the tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_STATISTICS.

See Also: ["ALL_TAB_STATISTICS"](#) on page 3-88

USER_TAB_STATS_HISTORY

USER_TAB_STATS_HISTORY provides a history of table statistics modifications for all tables owned by the current user. Its columns (except for OWNER) are the same as those in ["ALL_TAB_STATS_HISTORY"](#) on page 3-89.

USER_TAB_SUBPARTITIONS

USER_TAB_SUBPARTITIONS describes, for each table subpartition owned by the current user, the subpartition name, name of the table and partition to which it

belongs, and its storage attributes. Its columns are the same as those in "[ALL_TAB_SUBPARTITIONS](#)" on page 3-89.

Note: Statistics are not collected on a per-subpartition basis.

USER_TABLES

USER_TABLES describes the relational tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TABLES. To gather statistics for this view, use the ANALYZE SQL statement.

See Also: "[ALL_TABLES](#)" on page 3-91

USER_TABLESPACES

USER_TABLESPACES describes the tablespaces accessible to the current user. Its columns (except for PLUGGED_IN) are the same as those in DBA_TABLESPACES.

See Also: "[DBA_TABLESPACES](#)" on page 6-20

USER_TRANSFORMATIONS

USER_TRANSFORMATIONS displays information about the transformations owned by the current user. Its columns (except for OWNER) are the same as those in DBA_TRANSFORMATIONS.

See Also: "[DBA_TRANSFORMATIONS](#)" on page 6-24

USER_TRIGGER_COLS

USER_TRIGGER_COLS describes the use of columns in the triggers owned by the current user and in triggers on tables owned by the current user. Its columns are the same as those in ALL_TRIGGER_COLS.

See Also: "[ALL_TRIGGER_COLS](#)" on page 3-94

USER_TRIGGER_ORDERING

USER_TRIGGER_ORDERING describes the triggers owned by the current user that have FOLLOWS or PRECEDES ordering. Its columns (except for TRIGGER_OWNER) are the same as those in ALL_TRIGGER_ORDERING.

See Also: "[ALL_TRIGGER_ORDERING](#)" on page 3-95

USER_TRIGGERS

USER_TRIGGERS describes the triggers owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TRIGGERS.

See Also: "[ALL_TRIGGERS](#)" on page 3-96

USER_TS_QUOTAS

USER_TS_QUOTAS contains information about tablespace quotas for the current user. Its columns (except for USERNAME) the same as those in ["DBA_TS_QUOTAS"](#) on page 6-24.

USER_TSTZ_TAB_COLS

USER_TSTZ_TAB_COLS displays information about the columns of the tables owned by the current user, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types. Its columns (except for OWNER and NESTED) are the same as those in `ALL_TSTZ_TAB_COLS`.

See Also: ["ALL_TSTZ_TAB_COLS"](#) on page 3-97

USER_TSTZ_TABLES

USER_TSTZ_TABLES displays information about the tables owned by the current user, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types. Its columns (except for OWNER) are the same as those in `ALL_TSTZ_TABLES`.

See Also: ["ALL_TSTZ_TABLES"](#) on page 3-98

USER_TUNE_MVIEW

USER_TUNE_MVIEW displays the result of executing the `DBMS_ADVISOR.TUNE_MVIEW` procedure. Its columns (except for OWNER) are the same as those in `DBA_TUNE_MVIEW`.

See Also: ["DBA_TUNE_MVIEW"](#) on page 6-26

USER_TYPE_ATTRS

USER_TYPE_ATTRS describes the attributes of the object types owned by the current user. Its columns (except for OWNER and CHAR_USED) are the same as those in `ALL_TYPE_ATTRS`.

See Also: ["ALL_TYPE_ATTRS"](#) on page 3-98

USER_TYPE_METHODS

USER_TYPE_METHODS describes the methods of the object types owned by the current user. Its columns (except for OWNER) are the same as those in `ALL_TYPE_METHODS`.

See Also: ["ALL_TYPE_METHODS"](#) on page 3-99

USER_TYPE_VERSIONS

USER_TYPE_VERSIONS describes the versions of the object types owned by the current user. Its columns (except for OWNER) are the same as those in `ALL_TYPE_VERSIONS`.

See Also: ["ALL_TYPE_VERSIONS"](#) on page 3-100

USER_TYPES

USER_TYPES describes the object types owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TYPES.

See Also: ["ALL_TYPES"](#) on page 3-101

USER_UNUSED_COL_TABS

USER_UNUSED_COL_TABS describes the tables owned by the current user that contain unused columns. Its columns (except for OWNER) are the same as those in ALL_UNUSED_COL_TABS.

See Also: ["ALL_UNUSED_COL_TABS"](#) on page 3-101

USER_UPDATABLE_COLUMNS

USER_UPDATABLE_COLUMNS describes columns in a join view that can be updated by the current user, subject to appropriate privileges. Its columns are the same as those in ["ALL_UPDATABLE_COLUMNS"](#) on page 3-102.

See Also: *Oracle Database Concepts* for information on updatable join views

USER_USERS

USER_USERS describes the current user. Its columns (except for PASSWORD, PROFILE, PASSWORD_VERSIONS, EDITIONS_ENABLED, AUTHENTICATION_TYPE, and EDITIONS_ENABLED) are the same as those in DBA_USERS.

See Also: ["DBA_USERS"](#) on page 6-28

USER_USTATS

USER_USTATS describes the user-defined statistics collected on the tables and indexes owned by the current user. Its columns are the same as those in ALL_USTATS.

See Also: ["ALL_USTATS"](#) on page 3-103

USER_VARRAYS

USER_VARRAYS describes the varrays owned by the current user. Its columns (except for OWNER) are the same as those in ALL_VARRAYS.

See Also: ["ALL_VARRAYS"](#) on page 3-103

USER_VIEWS

USER_VIEWS describes the views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_VIEWS.

See Also: ["ALL_VIEWS"](#) on page 3-104

USER_VIEWS_AE

USER_VIEWS_AE describes the views (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_VIEWS_AE.

See Also: ["ALL_VIEWS_AE"](#) on page 3-105

USER_WARNING_SETTINGS

USER_WARNING_SETTINGS displays information about the warning parameter settings for the objects owned by the current user. Its columns (except for OWNER) are the same as those in ALL_WARNING_SETTINGS.

See Also: ["ALL_WARNING_SETTINGS"](#) on page 3-105

USER_XML_INDEXES

USER_XML_INDEXES describes the XML indexes owned by the current user. Its columns (except for INDEX_OWNER) are the same as those in ALL_XML_INDEXES.

See Also: ["ALL_XML_INDEXES"](#) on page 3-106

USER_XML_SCHEMAS

USER_XML_SCHEMAS describes the registered XML schemas owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_SCHEMAS.

See Also: ["ALL_XML_SCHEMAS"](#) on page 3-107

USER_XML_TAB_COLS

USER_XML_TAB_COLS describes the columns of the XML tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_TAB_COLS.

See Also: ["ALL_XML_TAB_COLS"](#) on page 3-108

USER_XML_TABLES

USER_XML_TABLES describes the XML tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_TABLES.

See Also: ["ALL_XML_TABLES"](#) on page 3-109

USER_XML_VIEW_COLS

USER_XML_VIEW_COLS describes the columns of the XML views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_VIEW_COLS.

See Also: ["ALL_XML_VIEW_COLS"](#) on page 3-109

USER_XML_VIEWS

USER_XML_VIEWS describes the XML views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_VIEWS.

See Also: ["ALL_XML_VIEWS"](#) on page 3-110

XS_SESSION_ROLES

XS_SESSION_ROLES describes the enabled roles in the current lightweight user session for the current request.

Column	Datatype	NULL	Description
ROLE	VARCHAR2 (1025)		Name of the role
UUID	VARCHAR2 (33)		UUID of the role
DBID	NUMBER		Database ID of the role
FLAGS	NUMBER		Status flags

Part III

Dynamic Performance Views

This part describes the dynamic performance views, which are often referred to as V\$ views. This part contains the following chapters:

- [Chapter 7, "Dynamic Performance \(V\\$\) Views: V\\$ACCESS to V\\$HVMaster_INFO"](#)
- [Chapter 8, "Dynamic Performance \(V\\$\) Views: V\\$INDEXED_FIXED_COLUMN to V\\$RULE_SET_AGGREGATE_STATS"](#)
- [Chapter 9, "Dynamic Performance \(V\\$\) Views: V\\$SCHEDULER_RUNNING_JOBS to V\\$XSTREAM_TRANSACTION"](#)

Dynamic Performance (V\$) Views: V\$ACCESS to V\$HVMMASTER_INFO

This chapter describes the first set (in alphabetical order) of dynamic performance views. The remaining dynamic performance views appear in alphabetical order in [Chapter 8](#) through [Chapter 9](#).

This chapter contains the following topics:

- [About Dynamic Performance Views](#)
- [Dynamic Performance View Descriptions](#)

About Dynamic Performance Views

Oracle contains a set of underlying views that are maintained by the database server and accessible to the database administrator user SYS. These views are called **dynamic performance views** because they are continuously updated while a database is open and in use, and their contents relate primarily to performance.

Although these views appear to be regular database tables, they are not. These views provide data on internal disk structures and memory structures. You can select from these views, but you can never update or alter them.

Note:

- You can query the dynamic performance views to extract information from them. However, only simple queries are supported. If sorts, joins, GROUP BY clauses and the like are needed, then you should copy the information from each V\$ view into a table (for example, using a CREATE TABLE . . . AS SELECT statement), and then query from those tables.
 - Because the information in the V\$ views is dynamic, read consistency is not guaranteed for SELECT operations on these views.
-

The `catalog.sql` script contains definitions of the views and public synonyms for the dynamic performance views. You must run `catalog.sql` to create these views and synonyms. After installation, only user SYS or anyone with SYSDBA role has access to the dynamic performance tables. See *Oracle Database Administrator's Guide* for more information about running `catalog.sql`.

V\$ Views

The actual dynamic performance views are identified by the prefix V_\$. Public synonyms for these views have the prefix V\$. Database administrators and other users should access only the V\$ objects, not the V_\$ objects.

The dynamic performance views are used by Oracle Enterprise Manager, which is the primary interface for accessing information about system performance. After an instance is started, the V\$ views that read from memory are accessible. Views that read data from disk require that the database be mounted, and some require that the database be open.

GV\$ Views

For almost every V\$ view described in this chapter, Oracle has a corresponding GV\$ (global V\$) view. In Real Application Clusters, querying a GV\$ view retrieves the V\$ view information from all qualified instances. In addition to the V\$ information, each GV\$ view contains an extra column named INST_ID of datatype NUMBER. The INST_ID column displays the instance number from which the associated V\$ view information was obtained. The INST_ID column can be used as a filter to retrieve V\$ information from a subset of available instances. For example, the following query retrieves the information from the V\$LOCK view on instances 2 and 5:

```
SQL> SELECT * FROM GV$LOCK WHERE INST_ID = 2 OR INST_ID = 5;
```

See Also: *Oracle Real Application Clusters Installation and Configuration Guide* for your operating system

Dynamic Performance View Descriptions

The remainder of this chapter describes the dynamic performance views in alphabetical order.

V\$ACCESS

V\$ACCESS displays information about locks that are currently imposed on library cache objects. The locks are imposed to ensure that they are not aged out of the library cache while they are required for SQL execution.

Column	Datatype	Description
SID	NUMBER	Session number that is accessing an object
OWNER	VARCHAR2 (64)	Owner of the object
OBJECT	VARCHAR2 (1000)	Name of the object
TYPE	VARCHAR2 (64)	Type identifier for the object

V\$ACTIVE_INSTANCES

V\$ACTIVE_INSTANCES displays the mapping between instance names and instance numbers for all instances that have the database currently mounted.

Column	Datatype	Description
INST_NUMBER	NUMBER	Instance number
INST_NAME	VARCHAR2 (60)	Instance name

V\$ACTIVE_SERVICES

V\$ACTIVE_SERVICES displays information about the active services in the database.

Column	Datatype	Description
SERVICE_ID	NUMBER	Service ID
NAME	VARCHAR2 (64)	Name of the service
NAME_HASH	NUMBER	Service name hash
NETWORK_NAME	VARCHAR2 (512)	Network name
CREATION_DATE	DATE	Creation date
CREATION_DATE_HASH	NUMBER	Creation date hash
GOAL	VARCHAR2 (12)	Service workload management goal: ■ NONE ■ SERVICE_TIME ■ THROUGHPUT
DTP	VARCHAR2 (1)	Indicates whether the service is for DTP or distributed transactions including XA transactions (Y) or not (N)
BLOCKED	VARCHAR2 (3)	Indicates whether a service on the specified instance is blocked from accepting new connections altogether (YES) or not (NO). If a service is blocked, then all connections will be directed to other instances (if any) that are hosting the desired service.
AQ_HA_NOTIFICATION	VARCHAR2 (3)	Indicates whether AQ notifications are sent for HA events (YES) or not (NO)
CLB_GOAL	VARCHAR2 (5)	Connection load balancing goal used with statistics that are sent to the listeners to determine how new connections are distributed: ■ LONG ■ SHORT

V\$ACTIVE_SESS_POOL_MTH

V\$ACTIVE_SESS_POOL_MTH displays available active session pool resource allocation methods.

Column	Datatype	Description
NAME	VARCHAR2 (40)	Name of the active session pool resource allocation method

V\$ACTIVE_SESSION_HISTORY

V\$ACTIVE_SESSION_HISTORY displays sampled session activity in the database. It contains snapshots of active database sessions taken once a second. A database session is considered active if it was on the CPU or was waiting for an event that didn't belong to the `Idle` wait class. Refer to the V\$EVENT_NAME view for more information on wait classes.

This view contains one row for each active session per sample and returns the latest session sample rows first. A majority of the columns describing the session in the active session history are present in the V\$SESSION view.

Column	Datatype	Description
SAMPLE_ID	NUMBER	ID of the sample
SAMPLE_TIME	TIMESTAMP (3)	Time at which the sample was taken

Column	Datatype	Description
IS_AWR_SAMPLE	VARCHAR2 (1)	Indicates whether this sample has been flushed or will be flushed to the Automatic Workload Repository (DBA_HIST_ACTIVE_SESS_HISTORY) (Y) or not (N)
SESSION_ID	NUMBER	Session identifier; maps to V\$SESSION.SID
SESSION_SERIAL#	NUMBER	Session serial number (used to uniquely identify a session's objects); maps to V\$SESSION.SERIAL#
SESSION_TYPE	VARCHAR2 (10)	Session type: ■ FOREGROUND ■ BACKGROUND
FLAGS	NUMBER	Reserved for future use
USER_ID	NUMBER	Oracle user identifier; maps to V\$SESSION.USER#
SQL_ID	VARCHAR2 (13)	SQL identifier of the SQL statement that the session was executing at the time of sampling
IS_SQLID_CURRENT	VARCHAR2 (1)	Indicates whether the SQL identifier in the SQL_ID column is being executed (Y) or not (N)
SQL_CHILD_NUMBER	NUMBER	Child number of the SQL statement that the session was executing at the time of sampling
SQL_OPCODE	NUMBER	Indicates what phase of operation the SQL statement was in; maps to V\$SESSION.COMMAND See Also: "V\$SESSION" on page 9-8 for information on interpreting this column
SQL_OPNAME	VARCHAR2 (64)	SQL command name
FORCE_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to FORCE
TOP_LEVEL_SQL_ID	VARCHAR2 (13)	SQL identifier of the top level SQL statement
TOP_LEVEL_SQL_OPCODE	NUMBER	Indicates what phase of operation the top level SQL statement was in
SQL_PLAN_HASH_VALUE	NUMBER	Numerical representation of the SQL plan for the cursor. This information might not be available for all session samples. V\$SESSION does not contain this information.
SQL_PLAN_LINE_ID	NUMBER	SQL plan line ID
SQL_PLAN_OPERATION	VARCHAR2 (30)	Plan operation name
SQL_PLAN_OPTIONS	VARCHAR2 (30)	Plan operation options
SQL_EXEC_ID	NUMBER	SQL execution identifier
SQL_EXEC_START	DATE	Time when the execution of the SQL started
PLSQL_ENTRY_OBJECT_ID	NUMBER	Object ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack. Maps to DBA_OBJECTS.OBJECT_ID.
PLSQL_ENTRY_SUBPROGRAM_ID	NUMBER	Subprogram ID of the top-most PL/SQL subprogram on the stack. Maps to DBA_OBJECTS.DATA_OBJECT_ID.
PLSQL_OBJECT_ID	NUMBER	Object ID of the currently executing PL/SQL subprogram. Maps to DBA_OBJECTS.OBJECT_ID.
PLSQL_SUBPROGRAM_ID	NUMBER	Subprogram ID of the currently executing PL/SQL object; NULL if executing SQL. Maps to DBA_OBJECTS.DATA_OBJECT_ID.
QC_INSTANCE_ID	NUMBER	Query coordinator instance ID. This information is only available if the sampled session is a parallel query slave. For all other sessions, the value is 0.
QC_SESSION_ID	NUMBER	Query coordinator session ID. This information is only available if the sampled session is a parallel query slave. For all other sessions, the value is 0.
QC_SESSION_SERIAL#	NUMBER	Query coordinator session serial number. This information is only available if the sampled session is a parallel query slave. For all other sessions, the value is 0.

Column	Datatype	Description
PX_FLAGS ¹	NUMBER	Reserved for internal use
EVENT	VARCHAR2 (64)	If SESSION_STATE = WAITING, then the event for which the session was waiting for at the time of sampling. If SESSION_STATE = ON CPU, then this column is NULL. See Also: Appendix C, "Oracle Wait Events"
EVENT_ID	NUMBER	Identifier of the resource or event for which the session is waiting or for which the session last waited. Interpretation is similar to that of the EVENT column.
EVENT#	NUMBER	Number of the resource or event for which the session is waiting or for which the session last waited. Interpretation is similar to that of the EVENT column.
SEQ#	NUMBER	Sequence number that uniquely identifies the wait (incremented for each wait)
P1TEXT	VARCHAR2 (64)	Text of the first additional parameter
P1	NUMBER	First additional parameter
P2TEXT	VARCHAR2 (64)	Text of the second additional parameter
P2	NUMBER	Second additional parameter
P3TEXT	VARCHAR2 (64)	Text of the third additional parameter
P3	NUMBER	Third additional parameter
WAIT_CLASS	VARCHAR2 (64)	Wait class name of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V\$SESSION.WAIT_CLASS.
WAIT_CLASS_ID	NUMBER	Wait class identifier of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V\$SESSION.WAIT_CLASS_ID.
WAIT_TIME	NUMBER	Total wait time for the event for which the session last waited if the session was on the CPU when sampled; 0 if the session was waiting at the time of sampling Note: Whether or not WAIT_TIME = 0 is what is useful to find the SESSION_STATE at the time of sampling, rather than the actual value of WAIT_TIME itself. Maps to V\$SESSION.WAIT_TIME.
SESSION_STATE	VARCHAR2 (7)	Session state: ■ WAITING ■ ON CPU
TIME_WAITED	NUMBER	If SESSION_STATE = WAITING, then the time that the session actually spent waiting for that event (in microseconds). This column is set for waits that were in progress at the time the sample was taken. If a wait event lasted for more than a second and was caught waiting in more than one session sample row, then the actual time spent waiting for that wait event will be populated in the last of those session sample rows. At any given time, this information will not be available for the latest session sample.
BLOCKING_SESSION_STATUS	VARCHAR2 (11)	Status of the blocking session: ■ VALID ■ NO HOLDER ■ GLOBAL ■ NOT IN WAIT ■ UNKNOWN
BLOCKING_SESSION	NUMBER	Session identifier of the blocking session. Populated only if the blocker is on the same instance and the session was waiting for enqueue or a "buffer busy" wait. Maps to V\$SESSION.BLOCKING_SESSION.
BLOCKING_SESSION_SERIAL#	NUMBER	Serial number of the blocking session

Column	Datatype	Description
BLOCKING_INST_ID	NUMBER	Instance number of the blocker shown in BLOCKING_SESSION
BLOCKING_HANGCHAIN_INFO	VARCHAR2 (1)	Indicates whether the information about BLOCKING_SESSION comes from the hang chain (Y) or not (N)
CURRENT_OBJ#	NUMBER	Object ID of the object that the session is referencing. This information is only available if the session was waiting for application, cluster, concurrency, and user I/O wait events. Maps to V\$SESSION.ROW_WAIT_OBJ#.
CURRENT_FILE#	NUMBER	File number of the file containing the block that the session is referencing. This information is only available if the session was waiting for cluster, concurrency, and user I/O wait events. Maps to V\$SESSION.ROW_WAIT_FILE#.
CURRENT_BLOCK#	NUMBER	ID of the block that the session is referencing. This information is only available if the session was waiting for cluster, concurrency, and user I/O wait events. Maps to V\$SESSION.ROW_WAIT_BLOCK#.
CURRENT_ROW#	NUMBER	Row identifier that the session is referencing. This information is only available if the session was waiting for cluster, concurrency, and user I/O wait events. Maps to V\$SESSION.ROW_WAIT_ROW#.
TOP_LEVEL_CALL#	NUMBER	Oracle top level call number
TOP_LEVEL_CALL_NAME	VARCHAR2 (64)	Oracle top level call name
CONSUMER_GROUP_ID	NUMBER	Consumer group ID
XID	RAW (8)	Transaction ID that the session was working on at the time of sampling. V\$SESSION does not contain this information.
REMOTE_INSTANCE#	NUMBER	Remote instance identifier that will serve the block that this session is waiting for. This information is only available if the session was waiting for cluster events.
TIME_MODEL	NUMBER	Time model information
IN_CONNECTION_MGMT	VARCHAR2 (1)	Indicates whether the session was doing connection management at the time of sampling (Y) or not (N)
IN_PARSE	VARCHAR2 (1)	Indicates whether the session was parsing at the time of sampling (Y) or not (N)
IN_HARD_PARSE	VARCHAR2 (1)	Indicates whether the session was hard parsing at the time of sampling (Y) or not (N)
IN_SQL_EXECUTION	VARCHAR2 (1)	Indicates whether the session was executing SQL statements at the time of sampling (Y) or not (N)
IN_PLSQL_EXECUTION	VARCHAR2 (1)	Indicates whether the session was executing PL/SQL at the time of sampling (Y) or not (N)
IN_PLSQL_RPC	VARCHAR2 (1)	Indicates whether the session was executing inbound PL/SQL RPC calls at the time of sampling (Y) or not (N)
IN_PLSQL_COMPILATION	VARCHAR2 (1)	Indicates whether the session was compiling PL/SQL at the time of sampling (Y) or not (N)
IN_JAVA_EXECUTION	VARCHAR2 (1)	Indicates whether the session was executing Java at the time of sampling (Y) or not (N)
IN_BIND	VARCHAR2 (1)	Indicates whether the session was doing bind operations at the time of sampling (Y) or not (N)
IN_CURSOR_CLOSE	VARCHAR2 (1)	Indicates whether the session was closing a cursor at the time of sampling (Y) or not (N)
IN_SEQUENCE_LOAD	VARCHAR2 (1)	Indicates whether the session is loading in sequence (in sequence load code) (Y) or not (N)
CAPTURE_OVERHEAD	VARCHAR2 (1)	Indicates whether the session is executing capture code (Y) or not (N)
REPLAY_OVERHEAD	VARCHAR2 (1)	Indicates whether the session is executing replay code (Y) or not (N)
IS_CAPTURED	VARCHAR2 (1)	Indicates whether the session is being captured (Y) or not (N)
IS_REPLAYED	VARCHAR2 (1)	Indicates whether the session is being replayed (Y) or not (N)

Column	Datatype	Description
SERVICE_HASH	NUMBER	Hash that identifies the Service; maps to V\$ACTIVE_SERVICES.NAME_HASH
PROGRAM	VARCHAR2 (48)	Name of the operating system program
MODULE ²	VARCHAR2 (48)	Name of the executing module when sampled, as set by the DBMS_APPLICATION_INFO.SET_MODULE procedure
ACTION ²	VARCHAR2 (32)	Name of the executing module when sampled, as set by the DBMS_APPLICATION_INFO.SET_ACTION procedure
CLIENT_ID	VARCHAR2 (64)	Client identifier of the session; maps to V\$SESSION.CLIENT_IDENTIFIER
MACHINE	VARCHAR2 (64)	Client's operating system machine name
PORT	NUMBER	Client port number
ECID	VARCHAR2 (64)	Execution context identifier (sent by Application Server)
DBREPLAY_FILE_ID ¹	NUMBER	If the session is being captured or replayed, then DBREPLAY_FILE_ID is the file ID for the workload capture or workload replay; otherwise it is NULL.
DBREPLAY_CALL_COUNTER ¹	NUMBER	If the session is being captured or replayed, then DBREPLAY_CALL_COUNTER is the call counter of the user call that is being captured or replayed; otherwise it is NULL.
TM_DELTA_TIME	NUMBER	Time interval (in microseconds) over which TM_DELTA_CPU_TIME and TM_DELTA_DB_TIME are accumulated
TM_DELTA_CPU_TIME	NUMBER	Amount of time this session spent on CPU over the last TM_DELTA_TIME microseconds
TM_DELTA_DB_TIME	NUMBER	Amount of time spent by this session in database calls over the last TM_DELTA_TIME microseconds
DELTA_TIME	NUMBER	Time interval (in microseconds) since the last time this session was sampled or created, over which the next five statistics are accumulated
DELTA_READ_IO_REQUESTS	NUMBER	Number of read I/O requests made by this session over the last DELTA_TIME microseconds
DELTA_WRITE_IO_REQUESTS	NUMBER	Number of write I/O requests made by this session over the last DELTA_TIME microseconds
DELTA_READ_IO_BYTES	NUMBER	Number of I/O bytes read by this session over the last DELTA_TIME microseconds
DELTA_WRITE_IO_BYTES	NUMBER	Number of I/O bytes written by this session over the last DELTA_TIME microseconds
DELTA_INTERCONNECT_IO_BYTES	NUMBER	Number of I/O bytes sent over the I/O interconnect over the last DELTA_TIME microseconds
PGA_ALLOCATED	NUMBER	Amount of PGA memory (in bytes) consumed by this session at the time this sample was taken
TEMP_SPACE_ALLOCATED	NUMBER	Amount of TEMP memory (in bytes) consumed by this session at the time this sample was taken

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

² The datatype of this column is VARCHAR2 (64) starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$ADVISOR_PROGRESS

V\$ADVISOR_PROGRESS displays information about the progress of advisor execution.

Column	Datatype	Description
SID	NUMBER	Session ID
SERIAL#	NUMBER	Session serial number
USERNAME	VARCHAR2 (30)	Oracle user name

V\$ALERT_TYPES

Column	Datatype	Description
OPNAME	VARCHAR2 (64)	Operation name
ADVISOR_NAME	VARCHAR2 (64)	Advisor name
TASK_ID	NUMBER	Task ID
TARGET_DESC	VARCHAR2 (32)	Description of the target of the advisor
SOFAR	NUMBER	Amount of work done so far
TOTALWORK	NUMBER	Total work to be done
UNITS	VARCHAR2 (32)	Units that the work is measured in
BENEFIT_SOFAR	NUMBER	Benefit obtained so far
BENEFIT_MAX	NUMBER	Estimate of maximum benefit that could be obtained
FINDINGS	NUMBER	Number of findings so far
RECOMMENDATIONS	NUMBER	Number of recommendations so far
TIME_REMAINING	NUMBER	Estimate of time remaining for the completion of the task (in seconds)
START_TIME	DATE	Start time of the task
LAST_UPDATE_TIME	DATE	Last time progress was posted
ELAPSED_SECONDS	NUMBER	Elapsed time so far
ADVISOR_METRIC1	NUMBER	Value of the advisor-specific metric
METRIC1_DESC	VARCHAR2 (64)	Description of the advisor-specific metric
EXECUTION_TYPE	VARCHAR2 (64)	Type of the last execution. This information is optional for single-execution tasks.

V\$ALERT_TYPES

V\$ALERT_TYPES displays information about server alert types.

Column	Datatype	Description
REASON_ID	NUMBER	ID of the alert reason
OBJECT_TYPE	VARCHAR2 (64)	Object type
TYPE	VARCHAR2 (9)	Alert type: - Stateful - Stateless
GROUP_NAME	VARCHAR2 (64)	Group name
SCOPE	VARCHAR2 (8)	Scope: - Database - Instance
INTERNAL_METRIC_CATEGORY	VARCHAR2 (64)	Internal metric category
INTERNAL_METRIC_NAME	VARCHAR2 (64)	Internal metric name

V\$AQ

V\$AQ displays statistics for the queues in the database.

Column	Datatype	Description
QID	NUMBER	Unique queue identifier
WAITING	NUMBER	Number of messages in the queue in the state 'WAITING'
READY	NUMBER	Number of messages in the queue in the state 'READY'

Column	Datatype	Description
EXPIRED	NUMBER	Number of messages in the queue the state 'EXPIRED'
TOTAL_WAIT	NUMBER	Total wait time of all 'READY' messages in the queue
AVERAGE_WAIT	NUMBER	Average wait time of 'READY' messages in the queue

V\$ARCHIVE

V\$ARCHIVE displays information about redo log files in need of archiving. Each row displays information for one thread. This information is also available in V\$LOG. Oracle recommends that you use V\$LOG.

See Also: ["V\\$LOG"](#) on page 8-17

Column	Datatype	Description
GROUP#	NUMBER	Log file group number
THREAD#	NUMBER	Log file thread number
SEQUENCE#	NUMBER	Log file sequence number
ISCURRENT	VARCHAR2 (3)	This is the current online redo log
CURRENT	VARCHAR2 (3)	This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in ISCURRENT.
FIRST_CHANGE#	NUMBER	First SCN stored in the current log

V\$ARCHIVE_DEST

V\$ARCHIVE_DEST displays, for the current instance, all of the destinations in the Data Guard configuration, including each destination's current value, mode, and status.

Column	Datatype	Description
DEST_ID	NUMBER	Log archive destination parameter identifier (1 to 31)
DEST_NAME	VARCHAR2 (256)	Log archive destination parameter name
STATUS	VARCHAR2 (9)	Identifies the current status of the destination: - VALID - Initialized and available - INACTIVE - No destination information - DEFERRED - Manually disabled by the user - ERROR - Error during open or copy - DISABLED - Disabled after error - BAD PARAM - Parameter has errors - ALTERNATE - Destination is in an alternate state - FULL - Exceeded quota size for the destination
BINDING	VARCHAR2 (9)	Specifies how failure will affect the archival operation: - MANDATORY - Successful archival is required - OPTIONAL - Successful archival is not required (depends on LOG_ARCHIVE_MIN_SUCCEED_DEST)
NAME_SPACE	VARCHAR2 (7)	Identifies the scope of parameter setting: - SYSTEM - System definition - SESSION - Session definition

Column	Datatype	Description
TARGET	VARCHAR2 (7)	Specifies whether the archive destination is local or remote to the primary database: - PRIMARY - local - STANDBY - remote
ARCHIVER	VARCHAR2 (10)	Identifies the archiver process relative to the database where the query is issued: - ARCn - FOREGROUND - LGWR - RFS
SCHEDULE	VARCHAR2 (8)	Indicates whether the archival of this destination is INACTIVE, PENDING, ACTIVE, or LATENT
DESTINATION	VARCHAR2 (256)	Specifies the location where the archived redo logs are to be archived
LOG_SEQUENCE	NUMBER	Identifies the sequence number of the last archived redo log to be archived
REOPEN_SECS	NUMBER	Identifies the retry time (in seconds) after error
DELAY_MINS	NUMBER	Identifies the delay interval (in minutes) before the archived redo log is automatically applied to a standby database
MAX_CONNECTIONS	NUMBER	Maximum number of connections
NET_TIMEOUT	NUMBER	Number of seconds the log writer process will wait for status from the network server of a network operation issued by the log writer process
PROCESS	VARCHAR2 (10)	Identifies the archiver process relative to the primary database, even if the query is issued on the standby database: - ARCn - FOREGROUND - LGWR
REGISTER	VARCHAR2 (3)	Indicates whether the archived redo log is registered in the remote destination control file (YES) or not (NO). If the archived redo log is registered, it is available to log apply services.
FAIL_DATE	DATE	Date and time of last error
FAIL_SEQUENCE	NUMBER	Sequence number of the archived redo log being archived when the last error occurred
FAIL_BLOCK	NUMBER	Block number of the archived redo log being archived when the last error occurred
FAILURE_COUNT	NUMBER	Current number of contiguous archival operation failures that have occurred for the destination
MAX_FAILURE	NUMBER	Allows you to control the number of times log transport services will attempt to reestablish communication and resume archival operations with a failed destination
ERROR	VARCHAR2 (256)	Displays the error text
ALTERNATE	VARCHAR2 (256)	Alternate destination, if any
DEPENDENCY	VARCHAR2 (256)	Reserved for future use
REMOTE_TEMPLATE	VARCHAR2 (256)	Specifies the template to be used to derive the location to be recorded
QUOTA_SIZE	NUMBER	Destination quotas, expressed in bytes
QUOTA_USED	NUMBER	Size of all the archived redo logs currently residing on the specified destination
MOUNTID	NUMBER	Instance mount identifier
TRANSMIT_MODE	VARCHAR2 (12)	Specifies network transmission mode: - SYNCHRONOUS - PARALLELSYNC - ASYNCHRONOUS

Column	Datatype	Description
ASYNC_BLOCKS	NUMBER	Number of blocks specified for the ASYNC attribute
AFFIRM	VARCHAR2 (3)	Specifies disk I/O mode
TYPE	VARCHAR2 (7)	Indicates whether the archived log destination definition is PUBLIC or PRIVATE. Only PUBLIC destinations can be modified at runtime using the ALTER SYSTEM SET or ALTER SESSION SET statements. By default, all archived log destinations are PUBLIC.
VALID_NOW	VARCHAR2 (16)	Indicates whether the destination is valid right now for archival operations: ■ YES - Redo log type and database role for this destination are valid for the current database ■ WRONG VALID_TYPE - Redo log type specified for this destination is not valid for the current database role. For example, WRONG VALID_TYPE would be returned if a destination specified with the VALID_FOR= (STANDBY_LOGFILE, STANDBY_ROLE) attribute is running in the standby database role but does not have standby redo logs implemented. ■ WRONG VALID_ROLE - Database role specified for this destination is not the role in which the database is currently running. For example, the WRONG VALID_ROLE would be returned when a destination defined with the VALID_FOR= (ONLINE_LOGFILE, STANDBY_ROLE) attribute is running in the primary database role. ■ INACTIVE - Destination is inactive, probably due to an error
VALID_TYPE	VARCHAR2 (15)	Redo log type or types that are valid for the destination: ■ ONLINE_LOGFILE ■ STANDBY_LOGFILE ■ ALL_LOGFILES
VALID_ROLE	VARCHAR2 (12)	Database role or roles that are valid for the destination: ■ PRIMARY_ROLE ■ STANDBY_ROLE ■ ALL_ROLES
DB_UNIQUE_NAME	VARCHAR2 (30)	Unique database name
VERIFY	VARCHAR2 (3)	Indicates whether the value of the VERIFY attribute on the LOG_ARCHIVE_DEST_n parameter is verified (YES) or not verified (NO)
COMPRESSION	VARCHAR2 (7)	Indicates whether network compression is ENABLED or DISABLED.
APPLIED_SCN ¹	NUMBER	For a destination that corresponds to a physical or logical standby database, the SCN of the last applied redo. For a destination that corresponds to a snapshot standby database, the SCN of the last redo applied before conversion to a snapshot standby database. This column is only valid for enabled and active standby database destinations on a primary or cascading standby database.

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also:

- ["LOG_ARCHIVE_DEST"](#) on page 1-87 and ["LOG_ARCHIVE_DEST_n"](#) on page 1-88
- ["LOG_ARCHIVE_DUPLEX_DEST"](#) on page 1-92 and ["LOG_ARCHIVE_DEST_STATE_n"](#) on page 1-91
- ["STANDBY_ARCHIVE_DEST"](#) on page 1-168
- ["LOG_ARCHIVE_MIN_SUCCEED_DEST"](#) on page 1-95

V\$ARCHIVE_DEST_STATUS

V\$ARCHIVE_DEST_STATUS displays runtime and configuration information for the archived redo log destinations. The information in this view does not persist across an instance shutdown.

Column	Datatype	Description
DEST_ID	NUMBER	Identifies the log archive destination parameter (1 to 31)
DEST_NAME	VARCHAR2 (256)	Log archive destination parameter name
STATUS	VARCHAR2 (9)	Current status of the destination: - VALID - Initialized and available - INACTIVE - No destination information - DEFERRED - Manually disabled by the user - ERROR - Error during open or copy - DISABLED - Disabled after error - BAD PARAM - Parameter has errors - ALTERNATE - Destination is in an alternate state - FULL - Exceeded quota size for the destination
TYPE	VARCHAR2 (14)	Type of archival destination database: - LOCAL - Local to primary database - PHYSICAL - Physical standby - CROSS-INSTANCE - An instance of the primary - LOGICAL - Logical standby - SNAPSHOT - Snapshot standby database - DOWNSTREAM - Streams downstream capture database
DATABASE_MODE	VARCHAR2 (15)	Current mode of the archival destination database: - STARTED - Instance started, not mounted - MOUNTED - Mounted - MOUNTED-STANDBY - Mounted standby - OPEN - Open read/write - OPEN_READ-ONLY - Open read-only
RECOVERY_MODE	VARCHAR2 (23)	Current apply mode at the archival destination: - IDLE - Managed recovery is not active - MANAGED - Managed recovery is active - MANAGED REAL TIME APPLY - Log apply services recover redo data from standby redo logs at the same time the logs are being written to, as opposed to recovering redo from archived redo logs when a log switch occurs - LOGICAL REAL TIME APPLY - Real time SQL Apply - LOGICAL APPLY - SQL Apply
PROTECTION_MODE	VARCHAR2 (20)	Indicates whether the database is protected: - MAXIMUM PROTECTION - MAXIMUM AVAILABILITY - RESYNCHRONIZATION - MAXIMUM PERFORMANCE - UNPROTECTED
DESTINATION	VARCHAR2 (256)	Specifies the location where the redo data is to be archived
STANDBY_LOGFILE_COUNT	NUMBER	Indicates the total number of standby redo logs created on the standby database
STANDBY_LOGFILE_ACTIVE	NUMBER	Indicates the total number of standby redo logs on the standby database that are active and contain primary database online redo log information

Column	Datatype	Description
ARCHIVED_THREAD#	NUMBER	Identifies the thread number of the most recent archived redo log received at the destination
ARCHIVED_SEQ#	NUMBER	Identifies the log sequence number of the most recent archived redo log received at the destination
APPLIED_THREAD#	NUMBER	Identifies the thread number of the most recent applied redo log received at the destination
APPLIED_SEQ#	NUMBER	Identifies the log sequence number of the most recent applied redo log received at the destination
ERROR	VARCHAR2 (256)	Displays the error text
SRL	VARCHAR2 (3)	Indicates whether standby redo logfiles are used on the standby database (YES) or not (NO)
DB_UNIQUE_NAME	VARCHAR2 (30)	Specifies the unique database name of the current instance that was defined with the DB_UNIQUE_NAME attribute on the LOG_ARCHIVE_DEST_n parameter
SYNCHRONIZATION_STATUS	VARCHAR2 (22)	Possible values for this column are as follows: - CHECK CONFIGURATION - Synchronization with this destination is not possible because this database is either not in MAXIMUM PROTECTION or MAXIMUM PERFORMANCE data protection mode, or the LOG_ARCHIVE_DEST_n parameter associated with this destination has not been configured with the SYNC and AFFIRM attributes. - CHECK STANDBY REDO LOG - The standby redo log at this destination is configured improperly. - CHECK NETWORK - One or more instances of this database cannot send redo data to this destination. - DESTINATION HAS A GAP - This destination is missing redo data needed for synchronization with this database. - OK - This destination is synchronized with this database. - NOT AVAILABLE - Synchronization status is not available. See Also: <i>Oracle Data Guard Concepts and Administration</i> for more information about redo transport configuration
SYNCHRONIZED	VARCHAR2 (3)	Possible values are: - YES - This destination is synchronized with the primary database. - NO - The destination is not synchronized with the primary database. - UNKNOWN - The synchronization status of this destination cannot be determined.
GAP_STATUS	VARCHAR2 (24)	Redo gap status: - NO GAP - Destination does not have a redo gap. - LOG SWITCH GAP - Destination has not yet received all of the redo from the previous log file. - RESOLVABLE GAP - Destination has a redo gap that can be automatically resolved by fetching the missing redo from this database. - UNRESOLVABLE GAP - Destination has a redo gap that cannot be automatically resolved by fetching the missing redo from this database and there are no other destinations from which redo can be fetched. - LOCALLY UNRESOLVABLE GAP - Destination has a redo gap that cannot be automatically resolved by fetching the missing redo from this database. It may be possible to resolve the gap by fetching the missing redo from another destination.

V\$ARCHIVE_GAP

V\$ARCHIVE_GAP displays information about archive gaps on a standby database. This view can be used to find out the current archive gap that is blocking recovery for the current recovery incarnation.

Column	Datatype	Description
THREAD#	NUMBER	Thread number of the missing archived redo log files. The number is 1 for a single instance. For Real Application Clusters, this column will contain different numbers.
LOW_SEQUENCE#	NUMBER	Lowest sequence number of the log files received on the standby system
HIGH_SEQUENCE#	NUMBER	Highest sequence number of the log files received on the standby system

V\$ARCHIVE_PROCESSES

V\$ARCHIVE_PROCESSES displays the state of the various ARCH processes for the instance.

Column	Datatype	Description
PROCESS	NUMBER	Identifier for the ARCH process for the instance, numbered from 0-9
STATUS	VARCHAR2 (10)	Status of the ARCH process, displayed as a keyword. Possible values are: STOPPED, SCHEDULED, STARTING, ACTIVE, STOPPING, and TERMINATED.
LOG_SEQUENCE	NUMBER	This is the online redo log sequence number currently being archived, if STATE="BUSY"
STATE	VARCHAR2 (4)	This is the current state of the ARCH process, displayed as a keyword. Possible keywords are IDLE or BUSY.

V\$ARCHIVED_LOG

V\$ARCHIVED_LOG displays archived log information from the control file, including archive log names. An archive log record is inserted after the online redo log is successfully archived or cleared (name column is NULL if the log was cleared). If the log is archived twice, there will be two archived log records with the same THREAD#, SEQUENCE#, and FIRST_CHANGE#, but with a different name. An archive log record is also inserted when an archive log is restored from a backup set or a copy and whenever a copy of a log is made with the RMAN COPY command.

Column	Datatype	Description
RECID	NUMBER	Archived log record ID
STAMP	NUMBER	Archived log record stamp
NAME	VARCHAR2 (513)	Archived log file name. If set to NULL, either the log file was cleared before it was archived or an RMAN backup command with the "delete input" option was executed to back up archivelog all (RMAN> backup archivelog all delete input;).
DEST_ID	NUMBER	Original destination from which the archive log was generated. The value is 0 if the destination identifier is not available.
THREAD#	NUMBER	Redo thread number
SEQUENCE#	NUMBER	Redo log sequence number
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the database when the log was written
RESETLOGS_TIME	DATE	Resetlogs time of the database when the log was written
RESETLOGS_ID	NUMBER	Resetlogs identifier associated with the archived redo log

Column	Datatype	Description
FIRST_CHANGE#	NUMBER	First change number in the archived log
FIRST_TIME	DATE	Timestamp of the first change
NEXT_CHANGE#	NUMBER	First change in the next log
NEXT_TIME	DATE	Timestamp of the next change
BLOCKS	NUMBER	Size of the archived log (in blocks)
BLOCK_SIZE	NUMBER	Redo log block size. This is the logical block size of the archived log, which is the same as the logical block size of the online log from which the archived log was copied. The online log logical block size is a platform-specific value that is not adjustable by the user.
CREATOR	VARCHAR2 (7)	Creator of the archivelog: - ARCH - Archiver process - FGRD - Foreground process - RMAN - Recovery Manager - SRMN - RMAN at standby - LGWR - Logwriter process
REGISTRAR	VARCHAR2 (7)	Registrar of the entry: - RFS - Remote File Server process - ARCH - Archiver process - FGRD - Foreground process - RMAN - Recovery manager - SRMN - RMAN at standby - LGWR - Logwriter process
STANDBY_DEST	VARCHAR2 (3)	Indicates whether the entry is an archivelog destination (YES) or not (NO)
ARCHIVED	VARCHAR2 (3)	Indicates whether the online redo log was archived (YES) or whether RMAN only inspected the log and created a record for future application of redo logs during recovery (NO). See Also: <i>Oracle Database Backup and Recovery User's Guide.</i>
APPLIED	VARCHAR2 (9)	Indicates whether an archived redo log file has been applied to the corresponding physical standby database. The value is always NO for local destinations. This column is meaningful on a physical standby database for rows where REGISTRAR = RFS: - If REGISTRAR = RFS and APPLIED = NO, then the log file has been received but has not yet been applied. - If REGISTRAR = RFS and APPLIED = IN-MEMORY, then the log file has been applied in memory, but the datafiles have not yet been updated. - If REGISTRAR = RFS and APPLIED = YES, then the log file has been applied and the datafiles have been updated. This column can be used to identify log files that can be backed up and deleted. When used for this purpose, the value IN-MEMORY should be treated as if it were NO.
DELETED	VARCHAR2 (3)	Indicates whether an RMAN DELETE command has physically deleted the archived log file from disk, as well as logically removing it from the control file of the target database and from the recovery catalog (YES) or not (NO)
STATUS	VARCHAR2 (1)	Status of the archived log: - A - Available - D - Deleted - U - Unavailable - X - Expired
COMPLETION_TIME	DATE	Time when the archiving completed

Column	Datatype	Description
DICTIONARY_BEGIN	VARCHAR2 (3)	Indicates whether the log contains the start of a LogMiner dictionary (YES) or not (NO)
DICTIONARY_END	VARCHAR2 (3)	Indicates whether the log contains the end of a LogMiner dictionary (YES) or not (NO)
END_OF_REDO	VARCHAR2 (3)	Indicates whether the archived redo log contains the end of all redo information from the primary database (YES) or not (NO)
BACKUP_COUNT	NUMBER	Indicates the number of times this file has been backed up. Values range from 0-15. If the file has been backed up more than 15 times, the value remains 15.
ARCHIVAL_THREAD#	NUMBER	Redo thread number of the instance that performed the archival operation. This column differs from the THREAD# column only when a closed thread is archived by another instance.
ACTIVATION#	NUMBER	Number assigned to the database instantiation
IS_RECOVERY_DEST_FILE	VARCHAR2 (3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
COMPRESSED	VARCHAR2 (3)	Reserved for internal use
FAL	VARCHAR2 (3)	Indicates whether the archive log was generated as the result of a FAL request (YES) or not (NO)
END_OF_REDO_TYPE	VARCHAR2 (10)	Possible values are as follows: - SWITCHOVER - Shows archived redo log files that are produced at the end of a switchover - TERMINAL - Shows archived redo log files produced after a failover - RESETLOGS - Shows online redo log files archived on the primary database after an ALTER DATABASE OPEN RESETLOGS statement is issued - ACTIVATION - Shows any log files archived on a physical standby database after an ALTER DATABASE ACTIVATE STANDBY DATABASE statement is issued "empty string" - Any empty string implies that the log is just a normal archival and was not archived due to any of the other events
BACKED_BY_VSS	VARCHAR2 (3)	Whether or not the file has been backed up by Volume Shadow Copy Service (VSS). This column is reserved for internal use.

V\$ASM_ACFS_ENCRYPTION_INFO

V\$ASM_ACFS_ENCRYPTION_INFO displays encryption information for every mounted Oracle ACFS.

Column	Datatype	Description
FS_NAME	VARCHAR2 (1024)	File system mount point (foreign key to V\$ASM_FILESYSTEM)
VOL_DEVICE	VARCHAR2 (256)	Name of the Oracle ADVM device
SET_STATUS	VARCHAR2 (7)	Indicates whether encryption parameters have been set on the file system (YES) or not (NO); otherwise UNKNOWN.
ENABLED_STATUS	VARCHAR2 (8)	Indicates whether file system level encryption is enabled (ENABLED) or not (DISABLED); otherwise UNKNOWN.
ALGORITHM	VARCHAR2 (7)	Encryption algorithm used. AES is the only supported algorithm.
KEY_LENGTH	VARCHAR2 (7)	Key length used for the encryption key
LAST_REKEY_TIME	DATE	Time that the volume was last rekeyed

Note: The V\$ASM_ACFS_ENCRYPTION_INFO view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$ASM_ACFS_SECURITY_INFO

V\$ASM_ACFS_SECURITY_INFO displays security information for every mounted Oracle ACFS.

Column	Datatype	Description
FS_NAME	VARCHAR2 (1024)	File system mount point (foreign key to V\$ASM_FILESYSTEM)
VOL_DEVICE	VARCHAR2 (256)	Name of the Oracle ADVM device
PREPARED_STATUS	VARCHAR2 (7)	Indicates whether the file system is prepared for security (YES) or not (NO); otherwise UNKNOWN.
ENABLED_STATUS	VARCHAR2 (8)	Indicates whether security is enabled for the file system (ENABLED) or not (DISABLED); otherwise UNKNOWN.

Note: The V\$ASM_ACFS_SECURITY_INFO view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$ASM_ACFSSNAPSHOTS

V\$ASM_ACFSSNAPSHOTS displays snapshot information for every mounted Oracle ACFS.

Column	Datatype	Description
FS_NAME	VARCHAR2 (1024)	File system mount point (foreign key to V\$ASM_FILESYSTEM)
VOL_DEVICE	VARCHAR2 (256)	Name of the Oracle ADVM device
SNAP_NAME	VARCHAR2 (1024)	Name of the snapshot
CREATE_TIME	DATE	Time when the snapshot was created

V\$ASM_ACFSVOLUMES

V\$ASM_ACFSVOLUMES displays information about mounted Oracle ACFS volumes, correlated with V\$ASM_FILESYSTEM.

Column	Datatype	Description
FS_NAME	VARCHAR2 (1024)	File system mount point (foreign key to V\$ASM_FILESYSTEM)
VOL_DEVICE	VARCHAR2 (256)	Name of the Oracle ADVM device
VOL_LABEL	VARCHAR2 (64)	Volume label (optional name) assigned through mkfs/acfsformat; NULL if no name exists
PRIMARY_VOL	VARCHAR2 (5)	Indicates whether the volume is the primary volume for the file system (TRUE) or not (FALSE)
TOTAL_MB	NUMBER	Size of the volume device (in megabytes)
FREE_MB	NUMBER	Available space on the volume device (in megabytes)

V\$ASM_ALIAS

In an Automatic Storage Management instance, V\$ASM_ALIAS displays one row for every alias present in every disk group mounted by the Automatic Storage Management instance. In a database instance, V\$ASM_ALIAS displays no rows.

Column	Datatype	Description
NAME	VARCHAR2 (70)	Automatic Storage Management alias or alias directory name
GROUP_NUMBER	NUMBER	Owning disk group number of the alias (foreign key to the V\$ASM_DISKGROUP view)
FILE_NUMBER	NUMBER	Automatic Storage Management file number of the alias (foreign key to the V\$ASM_FILE view)
FILE_INCARNATION	NUMBER	Automatic Storage Management file incarnation number for the alias
ALIAS_INDEX	NUMBER	Alias entry number for the alias
ALIAS_INCARNATION	NUMBER	Incarnation number for the parent of the alias
PARENT_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and an alias entry number in the low-order 24 bits (number of the directory containing the alias)
REFERENCE_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and an alias entry number in the low-order 24 bits (number of the directory describing the current entry)
ALIAS_DIRECTORY	VARCHAR2 (1)	Indicates whether the alias is to a directory (Y) or to an Automatic Storage Management file (N)
SYSTEM_CREATED	VARCHAR2 (1)	Indicates whether the alias is system created (Y) or user created (N)

V\$ASM_ATTRIBUTE

V\$ASM_ATTRIBUTE displays one row for each attribute defined. In addition to attributes specified by CREATE DISKGROUP and ALTER DISKGROUP statements, the view may show other attributes that are created automatically. Note that attributes are only displayed for disk groups where COMPATIBLE . ASM is set to 11.1 or higher.

Column	Datatype	Description
NAME	VARCHAR2 (256)	Full name of the attribute
VALUE	VARCHAR2 (256)	Value of the attribute
GROUP_NUMBER	NUMBER	Number of the disk group in which this attribute exists (composite primary key)
ATTRIBUTE_INDEX	NUMBER	Number of this attribute in the disk group (composite primary key)
ATTRIBUTE_INCARNATION	NUMBER	Incarnation number for this attribute (composite primary key)
READ_ONLY	VARCHAR2 (7)	Indicates whether the attribute is read-only (Y) or not (N)
SYSTEM_CREATED	VARCHAR2 (7)	Indicates whether this is a system-created attribute (Y) or not (N)

See Also: *Oracle Automatic Storage Management Administrator's Guide* for more information about viewing ASM disk group attributes using this view

V\$ASM_CLIENT

In an Automatic Storage Management instance, V\$ASM_CLIENT identifies databases using disk groups managed by the ASM instance. In a database instance, V\$ASM_CLIENT displays information about the ASM instance if the database has any open ASM files.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the disk group being used by the client database instance (foreign key to the V\$ASM_DISKGROUP view)
INSTANCE_NAME	VARCHAR2 (64)	Identifier for the database instance client

Column	Datatype	Description
DB_NAME	VARCHAR2 (8)	Unique database name of the database client instance
STATUS	VARCHAR2 (12)	Status of the client connection: ■ CONNECTED - Database instance client has an active connection to the Automatic Storage Management instance ■ DISCONNECTED - Database instance client normally ended its connection to the Automatic Storage Management instance ■ BROKEN - Connection with the database instance client terminated abnormally
SOFTWARE_VERSION	VARCHAR2 (60)	Software version number of the database or Automatic Storage Management instance for the selected disk group connection
COMPATIBLE_VERSION	VARCHAR2 (60)	Compatibility setting of the database or Automatic Storage Management instance for the selected disk group connection

V\$ASM_DISK

V\$ASM_DISK displays one row for every disk discovered by the Automatic Storage Management instance, including disks that are not part of any disk group.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the disk group containing the disk (foreign key to the V\$ASM_DISKGROUP view)
DISK_NUMBER	NUMBER	Number assigned to the disk within its disk group
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a disk number in the low-order 24 bits (for efficient access to the view)
INCARNATION	NUMBER	Incarnation number for the disk
MOUNT_STATUS	VARCHAR2 (7)	Per-instance status of the disk relative to group mounts: ■ MISSING - Automatic Storage Management metadata indicates that the disk is known to be part of the Automatic Storage Management disk group but no disk in the storage system was found with the indicated name ■ CLOSED - Disk is present in the storage system but is not being accessed by Automatic Storage Management ■ OPENED - Disk is present in the storage system and is being accessed by Automatic Storage Management. This is the normal state for disks in a database instance which are part of a Disk Group being actively used by the instance. ■ CACHED - Disk is present in the storage system and is part of a disk group being accessed by the Automatic Storage Management instance. This is the normal state for disks in an Automatic Storage Management instance which are part of a mounted disk group. ■ IGNORED - Disk is present in the system but is ignored by ASM because of one of the following: – The disk is detected by the system library but is ignored because an ASM library discovered the same disk – ASM has determined that the membership claimed by the disk header is no longer valid ■ CLOSING - ASM is in the process of closing this disk

Column	Datatype	Description
HEADER_STATUS	VARCHAR2 (12)	Per-instance status of the disk as seen by discovery: - UNKNOWN - Automatic Storage Management disk header has not been read - CANDIDATE - Disk is not part of a disk group and may be added to a disk group with the ALTER DISKGROUP statement - INCOMPATIBLE - Version number in the disk header is not compatible with the Automatic Storage Management software version - PROVISIONED - Disk is not part of a disk group and may be added to a disk group with the ALTER DISKGROUP statement. The PROVISIONED header status is different from the CANDIDATE header status in that PROVISIONED implies that an additional platform-specific action has been taken by an administrator to make the disk available for Automatic Storage Management. - MEMBER - Disk is a member of an existing disk group. No attempt should be made to add the disk to a different disk group. The ALTER DISKGROUP statement will reject such an addition unless overridden with the FORCE option. - FORMER - Disk was once part of a disk group but has been dropped cleanly from the group. It may be added to a new disk group with the ALTER DISKGROUP statement. - CONFLICT - Automatic Storage Management disk was not mounted due to a conflict - FOREIGN - Disk contains data created by an Oracle product other than ASM. This includes datafiles, logfiles, and OCR disks.
MODE_STATUS	VARCHAR2 (7)	Global status about which kinds of I/O requests are allowed to the disk: - ONLINE - Disk is online and operating normally. Reads and writes are attempted when the disk is mounted. Reads are attempted as part of disk discovery. - OFFLINE - Disk is offline and access to data is not permitted. Reads and writes are not attempted. An offline disk remains logically part of its disk group.
STATE	VARCHAR2 (8)	Global state of the disk with respect to the disk group: - UNKNOWN - Automatic Storage Management disk state is not known (typically the disk is not mounted) - NORMAL - Disk is online and operating normally - ADDING - Disk is being added to a disk group, and is pending validation by all instances that have the disk group mounted - DROPPING - Disk has been manually taken offline and space allocation or data access for the disk halts. Rebalancing will commence to relocate data off the disks to other disks in the disk group. Upon completion of the rebalance, the disk is expelled from the group. - HUNG - Disk drop operation cannot continue because there is insufficient space to relocate the data from the disk being dropped - FORCING - Disk is being removed from the disk group without attempting to offload its data. The data will be recovered from redundant copies, where possible. - DROPPED - Disk has been fully expelled from the disk group
REDUNDANCY	VARCHAR2 (7)	Hardware redundancy of the disk: - UNKNOWN - UNPROT - MIRROR - PARITY Note: This column is valid only if an ASMLIB is present that supports returning hardware redundancy information. This column is not related to the redundancy of the disk group of which the disk is a member.
LIBRARY	VARCHAR2 (64)	Name of the library that discovered the disk

Column	Datatype	Description
OS_MB	NUMBER	Size of the disk (in megabytes) as reported by the host operating system
TOTAL_MB	NUMBER	Total capacity of the disk (in megabytes)
FREE_MB	NUMBER	Unused capacity of the disk (in megabytes)
HOT_USED_MB	NUMBER	Number of used megabytes in the hot region
COLD_USED_MB	NUMBER	Number of used megabytes in the cold region
NAME	VARCHAR2 (30)	Name of the disk
FAILGROUP	VARCHAR2 (30)	Name of the failure group containing the disk
LABEL	VARCHAR2 (31)	Disk label portion of the name returned by discovery
PATH	VARCHAR2 (256)	Operating system pathname portion of the name returned by discovery
UDID	VARCHAR2 (64)	Unique Device ID portion of the name returned by discovery
PRODUCT	VARCHAR2 (32)	Name of the manufacturer and the name of the product. All disks with the same product id will have the same performance and reliability characteristics.
CREATE_DATE	DATE	Date and time when the disk was added to the disk group
MOUNT_DATE	DATE	Date and time when the disk was mounted by the first instance
REPAIR_TIMER	NUMBER	Seconds remaining until the disk is automatically dropped (0 if not failed)
READS	NUMBER	Total number of I/O read requests for the disk
WRITES	NUMBER	Total number of I/O write requests for the disk
READ_ERRS	NUMBER	Total number of failed I/O read requests for the disk
WRITE_ERRS	NUMBER	Total number of failed I/O write requests for the disk
READ_TIME	NUMBER	Total I/O time (in seconds) for read requests for the disk if the TIMED_STATISTICS initialization parameter is set to true (0 if set to false)
WRITE_TIME	NUMBER	Total I/O time (in seconds) for write requests for the disk if the TIMED_STATISTICS initialization parameter is set to true (0 if set to false)
BYTES_READ	NUMBER	Total number of bytes read from the disk
BYTES_WRITTEN	NUMBER	Total number of bytes written to the disk
PREFERRED_READ	VARCHAR2 (1)	Status of the preferred read failure group: ■ U - Disk group has no preferred read failure group ■ Y - Disk is a preferred read disk ■ N - Disk is not a preferred read disk For a disk group with one or more preferred read failure groups, if the disk is in one of the preferred read failure groups, the value of this column is Y; otherwise it is N.
HASH_VALUE	NUMBER	A unique hash value for an ASM disk, computed using the ASM disk name (as specified by NAME column in v\$asm_disk) and the ASM disk group name (as specified by NAME column in v\$asm_diskgroup).
HOT_READS	NUMBER	Number of reads from the hot region on disk
HOT_WRITES	NUMBER	Number of writes to the hot region on disk
HOT_BYTES_READ	NUMBER	Number of bytes read from the hot region on disk
HOT_BYTES_WRITTEN	NUMBER	Number of bytes written to the hot region on disk
COLD_READS	NUMBER	Number of reads from the cold region on disk
COLD_WRITES	NUMBER	Number of writes to the cold region on disk
COLD_BYTES_READ	NUMBER	Number of bytes read from the cold region on disk
COLD_BYTES_WRITTEN	NUMBER	Number of bytes written to the cold region on disk
VOTING_FILE	VARCHAR2 (1)	Indicates whether the disk contains a voting file (Y) or not (N)
SECTOR_SIZE	NUMBER	Physical block size (in bytes)

Column	Datatype	Description
FAILGROUP_TYPE	VARCHAR2 (7)	Type of the failure group: - REGULAR - QUORUM

Note: The GROUP_NUMBER and DISK_NUMBER columns will only be valid if the disk is part of a disk group which is currently mounted by the instance. Otherwise, GROUP_NUMBER will be 0, and DISK_NUMBER will be a unique value with respect to the other disks that also have a group number of 0.

V\$ASM_DISK_IOSTAT

V\$ASM_DISK_IOSTAT displays information about disk I/O statistics for each ASM client. If this view is queried from the database instance, only the rows for that instance are shown.

Column	Datatype	Description
INSTNAME	VARCHAR2 (64)	Identifier for the DB/ADVM instance client
DBNAME	VARCHAR2 (8)	Unique database name (DB_UNIQUE_NAME)
GROUP_NUMBER	NUMBER	Number of the disk group containing the disk
DISK_NUMBER	NUMBER	Number assigned to the disk within its disk group
FAILGROUP	VARCHAR2 (30)	Name of the failure group to which the disk belongs
READS	NUMBER	Total number of I/O read requests for the disk
WRITES	NUMBER	Total number of I/O write requests for the disk
READ_ERRS	NUMBER	Total number of failed I/O read requests for the disk
WRITE_ERRS	NUMBER	Total number of failed I/O write requests for the disk
READ_TIME	NUMBER	Total I/O time (in seconds) for read requests for the disk if the TIMED_STATISTICS initialization parameter is set to TRUE (0 if set to FALSE).
WRITE_TIME	NUMBER	Total I/O time (in seconds) for write requests for the disk if the TIMED_STATISTICS initialization parameter is set to TRUE (0 if set to FALSE)
BYTES_READ	NUMBER	Total number of bytes read from the disk
BYTES_WRITTEN	NUMBER	Total number of bytes written from the disk
HOT_READS	NUMBER	Number of reads from the hot region on disk
HOT_WRITES	NUMBER	Number of writes to the hot region on disk
HOT_BYTES_READ	NUMBER	Number of bytes read from the hot region on disk
HOT_BYTES_WRITTEN	NUMBER	Number of bytes written to the hot region on disk
COLD_READS	NUMBER	Number of reads from the cold region on disk
COLD_WRITES	NUMBER	Number of writes to the cold region on disk
COLD_BYTES_READ	NUMBER	Number of bytes read from the cold region on disk
COLD_BYTES_WRITTEN	NUMBER	Number of bytes written to the cold region on disk

V\$ASM_DISK_STAT

V\$ASM_DISK_STAT displays performance statistics in the same way that V\$ASM_DISK does, but without performing discovery of new disks. This results in a less

expensive operation. However, since discovery is not performed, the output of this view does not include any data about disks that are new to the system.

The columns for V\$ASM_DISK_STAT are the same as those for V\$ASM_DISK.

See Also: ["V\\$ASM_DISK"](#) on page 7-19

V\$ASM_DISKGROUP

V\$ASM_DISKGROUP displays one row for every ASM disk group discovered by the ASM instance on the node.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Cluster-wide number assigned to the disk group (primary key)
NAME	VARCHAR2 (30)	Name of the disk group
SECTOR_SIZE	NUMBER	Physical block size (in bytes)
BLOCK_SIZE	NUMBER	Automatic Storage Management metadata block size (in bytes)
ALLOCATION_UNIT_SIZE	NUMBER	Size of the allocation unit (in bytes)
STATE	VARCHAR2 (11)	State of the disk group relative to the instance: ■ CONNECTED - Disk group is in use by the database instance ■ BROKEN - Database instance lost connectivity to the Automatic Storage Management instance that mounted the disk group ■ UNKNOWN - Automatic Storage Management instance has never attempted to mount the disk group ■ DISMOUNTED - Disk group was cleanly dismounted by the Automatic Storage Management instance following a successful mount ■ MOUNTED - Instance is successfully serving the disk group to its database clients ■ QUIESCING - CRSCCTL utility attempted to dismount a disk group that contains the Oracle Cluster Registry (OCR). The disk group cannot be dismounted until Cluster Ready Services (CRS) exits, because the disk group contains the OCR.
TYPE	VARCHAR2 (6)	Redundancy type for the disk group: ■ EXTERN ■ NORMAL ■ HIGH
TOTAL_MB	NUMBER	Total capacity of the disk group (in megabytes)
FREE_MB	NUMBER	Unused capacity of the disk group (in megabytes)
HOT_USED_MB	NUMBER	Number of used megabytes in the hot region
COLD_USED_MB	NUMBER	Number of used megabytes in the cold region
REQUIRED_MIRROR_FREE_MB	NUMBER	Amount of space that is required to be available in a given disk group in order to restore redundancy after one or more disk failures. The amount of space displayed in this column takes mirroring effects into account.
USABLE_FILE_MB	NUMBER	Amount of free space that can be safely utilized taking mirroring into account and yet be able to restore redundancy after a disk failure
OFFLINE_DISKS	NUMBER	Number of disks in the disk group that are currently offline
COMPATIBILITY	VARCHAR2 (60)	Minimum software version required for an ASM instance to mount this disk group
DATABASE_COMPATIBILITY	VARCHAR2 (60)	Minimum software version required for a database instance to use files in this disk group
VOTING_FILES	VARCHAR2 (1)	Indicates whether the disk contains voting files (Y) or not (N)

Note: The GROUP_NUMBER, TOTAL_MB, and FREE_MB columns are only meaningful if the disk group is mounted by the instance. Otherwise, their values will be 0.

V\$ASM_DISKGROUP_STAT

V\$ASM_DISKGROUP_STAT displays performance statistics in the same way that V\$ASM_DISKGROUP does, but without performing discovery of new disk groups. This results in a less expensive operation. However, since discovery is not performed, the output of this view does not include any data about disk groups that are new to the system.

The columns for V\$ASM_DISKGROUP_STAT are the same as those for V\$ASM_DISKGROUP.

See Also: ["V\\$ASM_DISKGROUP"](#) on page 7-23

V\$ASM_FILE

In an Automatic Storage Management instance, V\$ASM_FILE displays one row for every Automatic Storage Management file in every disk group mounted by the Automatic Storage Management instance. In a database instance, V\$ASM_FILE displays no rows.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the disk group containing the file (composite primary key)
FILE_NUMBER	NUMBER	Number of the file within the disk group (composite primary key)
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a file number in the low-order 24 bits (for efficient access to the view)
INCARNATION	NUMBER	Incarnation number for the file (composite primary key)
BLOCK_SIZE	NUMBER	Block size of the file (in bytes)
BLOCKS	NUMBER	Number of blocks in the file
BYTES	NUMBER	Number of bytes in the file
SPACE	NUMBER	Number of bytes allocated to the file
TYPE	VARCHAR2 (64)	Type of the file. Possible values are as follows: ■ CONTROLFILE ■ DATAFILE ■ ONLINELOG ■ ARCHIVELOG ■ TEMPFILE ■ BACKUPSET ■ XTRANSPORT ■ PARAMETERFILE ■ DATAGUARDCONFIG ■ FLASHBACK ■ CHANGETRACKING ■ DUMPSET ■ AUTOBACKUP

Column	Datatype	Description
REDUNDANCY	VARCHAR2 (6)	Redundancy of the file: ■ UNPROT ■ MIRROR ■ HIGH
STRIPED	VARCHAR2 (6)	Indicates how the file is striped: ■ FINE ■ COARSE
CREATION_DATE	DATE	Date on which the file was created
MODIFICATION_DATE	DATE	Date of the last open/close for writing, rounded back to the nearest hour
REDUNDANCY_LOWERED	VARCHAR2 (1)	Indicates whether a file has lower redundancy than what was expected (Y) or not (N). Redundancy is said to have been lowered for a file when one or more data extents in that file are not mirrored at the level specified by the administrator. In case of unprotected files, data extents could be missing altogether. Another possible value for this column is (U), which means that it is unknown.
PERMISSIONS	VARCHAR2 (16)	Access permissions of the file, in order of user, group, and other
USER_NUMBER	NUMBER	User number
USER_INCARNATION	NUMBER	Incarnation number of the user
USERGROUP_NUMBER	NUMBER	User group number
USERGROUP_INCARNATION	NUMBER	Incarnation number of the user group
PRIMARY_REGION	VARCHAR2 (4)	Region used for allocating primary extents: ■ HOT ■ COLD
MIRROR_REGION	VARCHAR2 (4)	Region for allocating mirrored extents: ■ HOT ■ COLD
HOT_READS	NUMBER	Number of reads from the hot region for the file
HOT_WRITES	NUMBER	Number of writes to the hot region for the file
HOT_BYTES_READ	NUMBER	Number of bytes read from the hot region for the file
HOT_BYTES_WRITTEN	NUMBER	Number of bytes written to the hot region for the file
COLD_READS	NUMBER	Number of reads from the cold region for the file
COLD_WRITES	NUMBER	Number of writes to the cold region for the file
COLD_BYTES_READ	NUMBER	Number of bytes read from the cold region for the file
COLD_BYTES_WRITTEN	NUMBER	Number of bytes written to the cold region for the file

V\$ASM_FILESYSTEM

V\$ASM_FILESYSTEM displays information for every mounted Oracle ACFS.

Column	Datatype	Description
FS_NAME	VARCHAR2 (1024)	Mount point (primary key)
AVAILABLE_TIME	DATE	Mount time or the time that the file system became available again; NULL if the file system is not available
BLOCK_SIZE	NUMBER	File system block size (in kilobytes)

Column	Datatype	Description
STATE	VARCHAR2 (13)	File system status:: ■ NOT AVAILABLE ■ AVAILABLE ■ OFFLINE - Either the ASM instance is down, the disk group has been forced dismounted, or less commonly, a metadata I/O failure occurred or serious metadata corruption was detected. In the case of a metadata I/O failure, the file system is also marked as corrupt. An offline file system can only be unmounted; other attempts at access result in errors.
CORRUPT	VARCHAR2 (5)	Indicates whether the file system needs the fixer (fsck, acfschkdsk) to be run (TRUE) or not (FALSE)
NUM_VOL	NUMBER	Number of volumes in the file system
TOTAL_SIZE	NUMBER	Total capacity of the file system (in megabytes)
TOTAL_FREE	NUMBER	Total free space in the file system (in megabytes)
TOTAL_SNAP_SPACE_USAGE	NUMBER	Total space used by snapshots (in megabytes)

V\$ASM_OPERATION

In an Automatic Storage Management instance, V\$ASM_OPERATION displays one row for every active Automatic Storage Management long running operation executing in the Automatic Storage Management instance. In a database instance, V\$ASM_OPERATION displays no rows.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Disk group number (primary key). This is the foreign key to the V\$ASM_DISKGROUP view.
OPERATION	CHAR (5)	Type of the operation: ■ REBAL - Rebalance pending for this group. The disk group needs rebalance to complete. ■ ONLIN - Online disks operation in progress for the disk group
STATE	VARCHAR2 (4)	State of the operation: ■ WAIT - No operations running for the group ■ RUN - Operation running for the group ■ REAP - Operation is being run down ■ HALT - Operation halted by admin ■ ERRS - Operation halted by errors
POWER	NUMBER	Power requested for the operation as specified by the ASM_POWER_LIMIT initialization parameter or command syntax
ACTUAL	NUMBER	Power allocated to the operation
SO FAR	NUMBER	Number of Allocation Units that have been moved so far by the operation
EST_WORK	NUMBER	Estimated number of Allocation Units that have to be moved by the operation
EST_RATE	NUMBER	Estimated number of Allocation Units that are being moved per minute by the operation
EST_MINUTES	NUMBER	Estimated amount of time (in minutes) that the remainder of the operation is expected to take
ERROR_CODE	VARCHAR2 (44)	Oracle external error code; NULL if no error

V\$ASM_TEMPLATE

In an Automatic Storage Management instance, V\$ASM_TEMPLATE displays one row for every template present in every disk group mounted by the Automatic Storage Management instance. In a database instance, V\$ASM_TEMPLATE displays one row for every template present in every disk group mounted by the Automatic Storage Management instance with which the database instance communicates.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Owning disk group number (foreign key to the V\$ASM_DISKGROUP view)
ENTRY_NUMBER	NUMBER	Template number (primary key)
REDUNDANCY	VARCHAR2 (6)	Redundancy of the template: ■ UNPROT ■ MIRROR ■ HIGH
STRIPE	VARCHAR2 (6)	Indicates how the template is striped: ■ FINE ■ COARSE
SYSTEM	VARCHAR2 (1)	Indicates whether the template is a system template (Y) or not (N)
NAME	VARCHAR2 (30)	Name of the template
PRIMARY_REGION	VARCHAR2 (4)	Region used for allocating primary extents: ■ HOT ■ COLD
MIRROR_REGION	VARCHAR2 (4)	Region for allocating mirrored extents: ■ HOT ■ COLD

V\$ASM_USER

V\$ASM_USER displays the effective operating system user names of connected database instances and of file owners.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	ASM disk group number
USER_NUMBER	NUMBER	ASM internal unique user number
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a user number in the low-order 24 bits (for efficient access to the view)
INCARNATION	NUMBER	Incarnation number of the user
OS_ID	VARCHAR2 (128)	Operating system user ID
OS_NAME	VARCHAR2 (64)	Operating system user name

V\$ASM_USERGROUP

V\$ASM_USERGROUP displays the creator for each ASM File Access Control group.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	ASM disk group number
USERGROUP_NUMBER	NUMBER	Number of the user group

Column	Datatype	Description
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a user group number in the low-order 24 bits (for efficient access to the view)
INCARNATION	NUMBER	Incarnation number of the user group
OWNER_NUMBER	NUMBER	User group owner identified by a unique number
OWNER_INCARNATION	NUMBER	Incarnation number of the user group owner
NAME	VARCHAR2 (64)	User group name

V\$ASM_USERGROUP_MEMBER

V\$ASM_USERGROUP_MEMBER displays the members for each ASM File Access Control group.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	ASM disk group number
MEMBER_NUMBER	NUMBER	Number of the user group member
MEMBER_INCARNATION	NUMBER	Incarnation number of the user group member
USERGROUP_NUMBER	NUMBER	User group number
USERGROUP_INCARNATION	NUMBER	Incarnation number of the user group

V\$ASM_VOLUME

In an Automatic Storage Management instance, V\$ASM_VOLUME displays information about each Oracle ADVM volume. In a database instance, V\$ASM_VOLUME displays no rows.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Cluster-wide number assigned to the disk group (composite primary key)
VOLUME_NAME	VARCHAR2 (30)	Name of the volume
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a volume number in the low-order 24 bits (for efficient access to the view)
SIZE_MB	NUMBER	Size of the volume (in megabytes)
VOLUME_NUMBER	NUMBER	Number of the Volume within the disk group (composite primary key)
REDUNDANCY	VARCHAR2 (6)	Redundancy type for the volume: ■ UNPROT ■ HIGH ■ MIRROR
STRIPE_COLUMNS	NUMBER	Number of columns in a stripe set
STRIPE_WIDTH_K	NUMBER	Stripe width of the volume (in kilobytes)
STATE	VARCHAR2 (8)	Indicates whether the volume is enabled (ENABLED) or disabled (DISABLED)
FILE_NUMBER	NUMBER	Volume file number
INCARNATION	NUMBER	Volume file incarnation number
DRL_FILE_NUMBER	NUMBER	volume Dirty Region Logging (DRL) file used for mirrored volumes
RESIZE_UNIT_MB	NUMBER	Volume allocation unit (in megabytes) that a volume can be created
USAGE	VARCHAR2 (30)	Optional usage string for the volume

Column	Datatype	Description
VOLUME_DEVICE	VARCHAR2 (256)	OSD path for the volume device
MOUNTPATH	VARCHAR2 (1024)	Optional mount path string for the volume

V\$ASM_VOLUME_STAT

In an Automatic Storage Management instance, V\$ASM_VOLUME_STAT displays information about statistics for each Oracle ADVM volume. In a database instance, V\$ASM_VOLUME_STAT displays no rows.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Cluster-wide number assigned to the disk group (composite primary key)
VOLUME_NAME	VARCHAR2 (30)	Name of the volume
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a volume number in the low-order 24 bits (for efficient access to the view)
VOLUME_NUMBER	NUMBER	Number of the Volume within the disk group (composite primary key)
READS	NUMBER	Total number of read requests for this volume
WRITES	NUMBER	Total number of write requests for this volume
READ_ERRS	NUMBER	Total number of failed read I/O operations for this volume
WRITE_ERRS	NUMBER	Total number of failed write I/O operations for this volume
READ_TIME	NUMBER	Total I/O time (in seconds) for read requests for this volume
WRITE_TIME	NUMBER	Total I/O time (in seconds) for write requests for this volume
BYTES_READ	NUMBER	Total number of bytes read for this volume
BYTES_WRITTEN	NUMBER	Total number of bytes written for this volume

V\$AW_AGGREGATE_OP

V\$AW_AGGREGATE_OP displays the aggregation operators available in analytic workspaces. You can use this view in an application to provide a list of choices.

Column	Datatype	Description
NAME	VARCHAR2 (14)	Keyword for the aggregation operator
LONGNAME	VARCHAR2 (30)	Descriptive name for the operator
DEFAULT_WEIGHT	NUMBER	Default weight factor for weighted operators

V\$AW_ALLOCATE_OP

V\$AW_ALLOCATE_OP displays the allocation operators available in analytic workspaces. You can use this view in an application to provide a list of choices.

Column	Datatype	Description
NAME	VARCHAR2 (14)	Keyword for the allocation operator
LONGNAME	VARCHAR2 (30)	Descriptive name for the operator

V\$AW_CALC

V\$AW_CALC reports on the effectiveness of various caches used by Oracle OLAP during dynamic aggregation.

Column	Datatype	Description
SESSION_ID	NUMBER	A unique numeric identifier for the session.
AGGREGATE_CACHE_HITS	NUMBER	The number of times a dimension member is found in the aggregate cache (a hit). The number of hits for run-time aggregation can be increased by fetching data across the dense dimension
AGGREGATE_CACHE_MISSES	NUMBER	The number of times a dimension member is not found in the aggregate cache and must be read from disk (a miss).
SESSION_CACHE_HITS	NUMBER	The number of times the data is found in the session cache (a hit).
SESSION_CACHE_MISSES	NUMBER	The number of times the data is not found in the session cache (a miss).
POOL_HITS	NUMBER	The number of times the data is found in a page in the OLAP page pool (a hit).
POOL_MISSES	NUMBER	The number of times the data is not found in the OLAP page pool (a miss).
POOL_NEW_PAGES	NUMBER	The number of newly created pages in the OLAP page pool that have not yet been written to the workspace LOB.
POOL_RECLAIMED_PAGES	NUMBER	The number of previously unused pages that have been recycled with new data.
CACHE_WRITES	NUMBER	The number of times the data from the OLAP page pool has been written to the database cache.
POOL_SIZE	NUMBER	The number of kilobytes in the OLAP page pool.
CURR_DML_COMMAND	VARCHAR2 (64)	The command currently being executed.
PREV_DML_COMMAND	VARCHAR2 (64)	The command most recently completed.
AGGR_FUNC_LOGICAL_NA	NUMBER	The number of times the aggregation engine returns a logical NA because the AGGINDEX option is on and the composite tuple does not exist.
AGGR_FUNC_PRECOMPUTE	NUMBER	The number of times the aggregation engine finds a value in a position that it was called to calculate.
AGGR_FUNC_CALCS	NUMBER	The number of times the aggregation engine calculates a parent value based on the values of its children.

V\$AW_LONGOPS

V\$AW_LONGOPS displays status information about active SQL cursors initiated in an analytic workspace.

Column	Datatype	Description
SESSION_ID	NUMBER	Identifier for the session in which the fetch is executing. This table can be joined with V\$SESSION to obtain the user name.
CURSOR_NAME	VARCHAR2 (64)	Name assigned to the cursor

Column	Datatype	Description
COMMAND	VARCHAR2 (17)	Command that is actively fetching data from relational tables: ■ QUERY ■ FETCH ■ IMPORT ■ EXECUTE ■ UPDATE ■ SOLVE ■ CLEAR ■ LOAD CUBE ■ LOAD DIMENSION ■ DIMENSION COMPILE
STATUS	VARCHAR2 (9)	Status of the current operation: ■ EXECUTING - Command has begun executing ■ FETCHING - Data is being fetched into the analytic workspace ■ FINISHED - Command has finished executing. This status appears very briefly before the record disappears from the table.
ROWS_PROCESSED	NUMBER	Number of rows already inserted, updated, or deleted
SEQ_NUMBER	NUMBER	Sequence number in the Cube Build log
SQL_ID	VARCHAR2 (13)	SQL ID of the statement
TARGET	VARCHAR2 (64)	Operated object name
TARGET_DESC	VARCHAR2 (64)	A brief description of the operated object
START_TIME	DATE	Time the command started executing
LAST_UPDATE_TIME	DATE	Last updated time
ELAPSED_SECONDS	NUMBER	Number of seconds between START_TIME and LAST_UPDATE_TIME
SO FAR	NUMBER	Number of units so far
TOTALWORK	NUMBER	Total number of units
UNITS	VARCHAR2 (6)	Units description: ■ ROWS ■ NODES ■ VALUES
MESSAGE	VARCHAR2 (512)	Message for the user
USERNAME	VARCHAR2 (32)	User name

V\$AW_OLAP

V\$AW_OLAP provides a record of active sessions and their use with analytic workspaces. A row is generated whenever an analytic workspace is created or attached. The first row for a session is created when the first command is issued. It identifies the SYS . EXPRESS workspace, which is attached automatically to each session. Rows related to a particular analytic workspace are deleted when the workspace is detached from the session or the session ends.

Column	Datatype	Description
SESSION_ID	NUMBER	A unique numeric identifier for a session
AW_NUMBER	NUMBER	A unique numeric identifier for an analytic workspace. To get the name of the analytic workspace, join this column to the AW_NUMBER column of the USER_AWS view or to the AWSEQ# column of the AW\$ table.
ATTACH_MODE	VARCHAR2 (10)	READ ONLY or READ WRITE

Column	Datatype	Description
GENERATION	NUMBER	The generation of an analytic workspace. Each UPDATE creates a new generation. Sessions attaching the same workspace between UPDATE commands share the same generation.
TEMP_SPACE_PAGES	NUMBER	The number of pages stored in temporary segments for the analytic workspace.
TEMP_SPACE_READS	NUMBER	The number of times data has been read from a temporary segment and not from the page pool.
LOB_READS	NUMBER	The number of times data has been read from the table where the analytic workspace is stored (the permanent LOB).
POOL_CHANGED_PAGES	NUMBER	The number of pages in the page pool that have been modified in this analytic workspace.
POOL_UNCHANGED_PAGES	NUMBER	The number of pages in the page pool that have not been modified in this analytic workspace.

V\$AW_SESSION_INFO

V\$AW_SESSION_INFO provides information about each active session. A transaction is a single exchange between a client session and Oracle OLAP. Multiple commands can execute within a single transaction.

Column	Datatype	Description
SESSION_ID	NUMBER	A unique numeric identifier for a session
CLIENT_TYPE	VARCHAR2 (64)	OLAP
SESSION_STATE	VARCHAR2 (64)	TRANSACTIONING, NOT_TRANSACTIONING, EXCEPTION_HANDLING, CONSTRUCTING, CONSTRUCTED, DECONSTRUCTING, or DECONSTRUCTED
SESSION_HANDLE	NUMBER	The session identifier
USERID	VARCHAR2 (64)	The database user name under which the session opened
TOTAL_TRANSACTION	NUMBER	The total number of transactions executed within the session; this number provides a general indication of the level of activity in the session
TRANSACTION_TIME	NUMBER	The elapsed time in milliseconds of the mostly recently completed transaction
TOTAL_TRANSACTION_TIME	NUMBER	The total elapsed time in milliseconds in which transactions were being executed
AVERAGE_TRANSACTION_TIME	NUMBER	The average elapsed time in milliseconds to complete a transaction
TRANSACTION_CPU_TIME	NUMBER	The total CPU time in milliseconds used to complete the most recent transaction
TOTAL_TRANSACTION_CPU_TIME	NUMBER	The total CPU time used to execute all transactions in this session; this total does not include transactions that are currently in progress
AVERAGE_TRANSACTION_CPU_TIME	NUMBER	The average CPU time to complete a transaction; this average does not include transactions that are currently in progress

V\$BACKUP

V\$BACKUP displays the backup status of all online datafiles.

Column	Datatype	Description
FILE#	NUMBER	File identifier

Column	Datatype	Description
STATUS	VARCHAR2 (18)	File status: NOT ACTIVE, ACTIVE (backup in progress), OFFLINE NORMAL, or description of an error. NOT ACTIVE indicates that the file is not currently in backup mode (that is, an ALTER TABLESPACE ... BEGIN BACKUP or ALTER DATABASE BEGIN BACKUP statement has not been issued), whereas ACTIVE indicates that the file is currently in backup mode.
CHANGE#	NUMBER	System change number when backup started
TIME	DATE	Time the backup started

V\$BACKUP_ARCHIVELOG_DETAILS

V\$BACKUP_ARCHIVELOG_DETAILS contains information about all restorable archive logs. It will include all archived logs backed up in a backup set or proxy copies.

Column	Datatype	Description
BTYPE	CHAR (9)	Backup type container, either BACKUPSET or PROXYCOPY
BTYPE_KEY	NUMBER	Unique identifier for the backup type. For BACKUPSET, it is BS_KEY.
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
ID1	NUMBER	If BACKUPSET, it contains SET_STAMP If PROXYCOPY, it is RECID from the control file
ID2	NUMBER	If BACKUPSET, it contains SET_COUNT If PROXYCOPY, it is STAMP
THREAD#	NUMBER	Thread number
SEQUENCE#	NUMBER	Sequence number
RESETLOGS_CHANGE#	NUMBER	Resetlogs change SCN
RESETLOGS_TIME	DATE	Resetlogs change time
FIRST_CHANGE#	NUMBER	First change SCN
FIRST_TIME	DATE	First change time
NEXT_CHANGE#	NUMBER	Next change SCN
NEXT_TIME	DATE	Next change time
FILESIZE	NUMBER	File size
COMPRESSION_RATIO	NUMBER	Compression ratio
FILESIZE_DISPLAY	VARCHAR2 (4000)	Same value as the FILESIZE column, but converted to a user-displayable format, for example nM, nG, nT, nP, and so on

V\$BACKUP_ARCHIVELOG_SUMMARY

V\$BACKUP_ARCHIVELOG_SUMMARY provides archive log summary information based on archive logs in the backup set or on proxy copies.

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of files backed up
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct archive log files backed up
MIN_FIRST_CHANGE#	NUMBER	Lowest SCN range value
MAX_NEXT_CHANGE#	NUMBER	Highest SCN range value

Column	Datatype	Description
MIN_FIRST_TIME	DATE	Lowest SCN range time
MAX_NEXT_TIME	DATE	Highest SCH range time
INPUT_BYTES	NUMBER	Total input bytes read
OUTPUT_BYTES	NUMBER	Output size of backups
COMPRESSION_RATIO	NUMBER	Compression ratio
INPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for input bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output bytes

V\$BACKUP_ASYNC_IO

V\$BACKUP_ASYNC_IO displays performance information about ongoing and recently completed RMAN backups and restores. For each backup, it contains one row for each input datafile, one row for the aggregate total performance of all datafiles, and one row for the output backup piece. This data is not stored persistently, and is not preserved when the instance is re-started.

See Also: *Oracle Database Performance Tuning Guide* for information on how to use this table to tune backup performance

Column	Datatype	Description
SID	NUMBER	Oracle SID of the session doing the backup or restore
SERIAL	NUMBER	Use count for the SID doing the backup or restore
USE_COUNT	NUMBER	A counter that can be used to identify rows from different backup sets
RMAN_STATUS_RECID	NUMBER	Owning V\$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V\$RMAN_STATUS record stamp
DEVICE_TYPE	VARCHAR2 (17)	Device type where the file is located
TYPE	VARCHAR2 (9)	INPUT, OUTPUT, or AGGREGATE
STATUS	VARCHAR2 (11)	NOT STARTED, IN PROGRESS, or FINISHED
FILENAME	VARCHAR2 (513)	Name of the backup file being read or written
SET_COUNT	NUMBER	Set count of the backup set being read or written
SET_STAMP	NUMBER	Set stamp of the backup set being read or written
BUFFER_SIZE	NUMBER	Size of the buffers being used to read/write the file, in bytes
BUFFER_COUNT	NUMBER	Number of buffers being used to read/write the file
TOTAL_BYTES	NUMBER	Total number of bytes that will be read or written for the file, if known. If not known, this column will be null
OPEN_TIME	DATE	Time the file was opened. If TYPE='AGGREGATE', then this is the time that the first file in the aggregate was opened
CLOSE_TIME	DATE	Time the file was closed. If TYPE='AGGREGATE', then this is the time that the last file in the aggregate was closed
ELAPSED_TIME	NUMBER	Time, in hundredths of a second, that the file was open
MAXOPENFILES	NUMBER	Number of concurrently open DISK files. This value is only present in rows where TYPE='AGGREGATE'.
BYTES	NUMBER	Number of bytes read or written so far
EFFECTIVE_BYTES_PER_SECOND	NUMBER	I/O rate that was achieved with this device during this backup
IO_COUNT	NUMBER	Number of I/Os that were performed to this file

Column	Datatype	Description
READY	NUMBER	Number of asynchronous requests for which a buffer was immediately ready for use
SHORT_WAITS	NUMBER	Number of times that a buffer was not immediately available, but a buffer became available after doing a nonblocking poll for I/O completion
SHORT_WAIT_TIME_TOTAL	NUMBER	Total time, in hundredths of a second, taken by nonblocking polls for I/O completion
SHORT_WAIT_TIME_MAX	NUMBER	Maximum time taken for a nonblocking poll for I/O completion, in hundredths of a second
LONG_WAITS	NUMBER	The number of times that a buffer was not immediately available, and only became available after a blocking wait was issued
LONG_WAIT_TIME_TOTAL	NUMBER	The total time, in hundredths of a second, taken by blocking waits for I/O completion
LONG_WAIT_TIME_MAX	NUMBER	The maximum time taken for a blocking wait for I/O completion, in hundredths of a second

V\$BACKUP_CONTROLFILE_DETAILS

V\$BACKUP_CONTROLFILE_DETAILS contains information about restorable control files. It will include all the control files backed up in the backup set, image copies, and proxy copies.

Column	Datatype	Description
BTYPE	CHAR (9)	Backup type container. Possible values are BACKUPSET, IMAGECOPY, PROXYCOPY.
BTYPE_KEY	NUMBER	Unique identifier for the backup type, either BS_KEY or COPY_KEY.
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
ID1	NUMBER	If BACKUPSET, it contains SET_STAMP If IMAGECOPY or PROXYCOPY, it is RECID from the control file
ID2	NUMBER	If BACKUPSET, it contains SET_COUNT If IMAGECOPY or PROXYCOPY, it is STAMP
CREATION_TIME	DATE	File creation time
RESETLOGS_CHANGE#	NUMBER	Resetlogs change SCN
RESETLOGS_TIME	DATE	Resetlogs change time
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change SCN
CHECKPOINT_TIME	DATE	Checkpoint change time
FILESIZE	NUMBER	File size, in bytes, for the output of backing up this control file
COMPRESSION_RATIO	NUMBER	Compression ratio for this backup
FILESIZE_DISPLAY	VARCHAR2 (4000)	Same value as the FILESIZE column, but converted to a user-displayable format, for example nM, nG, nT, nP, and so on

V\$BACKUP_CONTROLFILE_SUMMARY

V\$BACKUP_CONTROLFILE_SUMMARY provides control file summary information, based on either a backup set of files, image copies, or proxy copies.

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of files backed up for specific criteria

Column	Datatype	Description
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct files backed up
MIN_CHECKPOINT_CHANGE#	NUMBER	Minimum checkpoint change number of the datafile for specified criteria
MAX_CHECKPOINT_CHANGE#	NUMBER	Maximum checkpoint change number of the datafile for specified criteria
MIN_CHECKPOINT_TIME	DATE	Minimum checkpoint time of the datafile for specified criteria
MAX_CHECKPOINT_TIME	DATE	Maximum checkpoint time of the datafile for specified criteria
INPUT_BYTES	NUMBER	Total input bytes of files read
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPRESSION_RATIO	NUMBER	Compression ratio
INPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for input bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output bytes

V\$BACKUP_COPY_DETAILS

V\$BACKUP_COPY_DETAILS contains information about all available control file and datafile copies.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
COPY_KEY	NUMBER	Unique identifier for this datafile or control file copy
FILE#	NUMBER	Absolute datafile number
NAME	VARCHAR2 (513)	File name of the datafile copy. The maximum length of the name is dependent on your operating system.
TAG	VARCHAR2 (32)	Datafile copy tag
CREATION_CHANGE#	NUMBER	Datafile creation change number
CREATION_TIME	DATE	Datafile creation timestamp
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change number of the datafile when the copy was made
CHECKPOINT_TIME	DATE	Checkpoint timestamp of the datafile when the copy was made
MARKED_CORRUPT	NUMBER	Number of blocks marked corrupt by this copy operation. That is, blocks that were not marked corrupted in the source datafile, but were detected and marked as corrupted during the copy operation.
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPLETION_TIME	DATE	Time when the copy was completed
CONTROLFILE_TYPE	VARCHAR2 (1)	Type of control file. B indicates normal copies. S indicates standby copies.
KEEP	VARCHAR2 (3)	(YES NO) Indicates whether or not this backup set has a retention policy that is different than the value for the configure retention policy
KEEP_UNTIL	DATE	If specified, this is the date after which the backup becomes obsolete. If this column is null, then the backup never expires.
KEEP_OPTIONS	VARCHAR2 (10)	Lists additional retention options for this backup set. Possible values are: - LOGS - The logs needed to recover this backup set are kept - NOLOGS - The logs needed to recover this backup set are not kept
IS_RECOVERY_DEST_FILE	VARCHAR2 (3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Size of backup set to display

V\$BACKUP_COPY_SUMMARY

V\$BACKUP_COPY_SUMMARY provides summary information for the output datafile and control file copy.

Column	Datatype	Description
NUM_COPIES	NUMBER	Number of copies created
NUM_DISTINCT_COPIES	NUMBER	Number of distinct copies (that contain datafiles with different checkpoints)
MIN_CHECKPOINT_CHANGE#	NUMBER	Minimum checkpoint change SCN
MAX_CHECKPOINT_CHANGE#	NUMBER	Maximum checkpoint change SCN
MIN_CHECKPOINT_TIME	DATE	Minimum checkpoint change time
MAX_CHECKPOINT_TIME	DATE	Maximum checkpoint change time
OUTPUT_BYTES	NUMBER	Total number of output bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output bytes

V\$BACKUP_CORRUPTION

V\$BACKUP_CORRUPTION displays information about corrupt block ranges in datafile backups from the control file. Note that corruptions are not tolerated in the control file and archived redo log backups.

Column	Datatype	Description
RECID	NUMBER	Backup corruption record ID
STAMP	NUMBER	Backup corruption record stamp
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
PIECE#	NUMBER	backup piece that contains this corrupt block
FILE#	NUMBER	Absolute file number of the datafile that contains the corrupt blocks
BLOCK#	NUMBER	Block number of the first corrupt block in the range of corrupted blocks
BLOCKS	NUMBER	Number of corrupted blocks found starting with BLOCK#
CORRUPTION_CHANGE#	NUMBER	Change number at which the logical corruption was detected. Set to 0 to indicate media corruption.
MARKED_CORRUPT	VARCHAR2 (3)	Indicates whether this corruption was not previously detected by the Oracle Database (YES) or the Oracle Database had already discovered this corrupt block and marked it as corrupt (NO). Note that when a corrupt block is encountered in a backup, and was not already marked corrupt by the Oracle Database, then the backup process does not mark the block as corrupt in the production datafile. Thus, this field may be YES for the same block in more than one backup set.

Column	Datatype	Description
CORRUPTION_TYPE	VARCHAR2 (9)	Type of block corruption in the datafile: - ALL ZERO - Block header on disk contained only zeros. The block may be valid if it was never filled and if it is in an Oracle7 file. The buffer will be reformatted to the Oracle8 standard for an empty block. - FRACTURED - Block header looks reasonable, but the front and back of the block are different versions. - CHECKSUM - optional check value shows that the block is not self-consistent. It is impossible to determine exactly why the check value fails, but it probably fails because sectors in the middle of the block are from different versions. - CORRUPT - Block is wrongly identified or is not a data block (for example, the data block address is missing) - LOGICAL - Block is logically corrupt - NOLOGGING - Block does not have redo log entries (for example, NOLOGGING operations on primary database can introduce this type of corruption on a physical standby)

V\$BACKUP_DATAFILE

V\$BACKUP_DATAFILE displays information about control files and datafiles in backup sets from the control file.

Column	Datatype	Description
RECID	NUMBER	Backup datafile record ID
STAMP	NUMBER	Backup datafile record stamp
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
FILE#	NUMBER	Datafile number; set to 0 for control file
CREATION_CHANGE#	NUMBER	Creation system change number (SCN) of the datafile
CREATION_TIME	DATE	Creation timestamp of the datafile
RESETLOGS_CHANGE#	NUMBER	Resetlogs system change number (SCN) of the datafile when it was backed up
RESETLOGS_TIME	DATE	Resetlogs timestamp of the datafile when it was backed up
INCREMENTAL_LEVEL	NUMBER	(0-4) incremental backup level
INCREMENTAL_CHANGE#	NUMBER	All blocks changed after the incremental change number is included in this backup; set to 0 for a full backup
CHECKPOINT_CHANGE#	NUMBER	All changes up to the checkpoint change number are included in this backup
CHECKPOINT_TIME	DATE	Timestamp of the checkpoint
ABSOLUTE_FUZZY_CHANGE#	NUMBER	Highest change number in this backup
MARKED_CORRUPT	NUMBER	Number of blocks marked corrupt
MEDIA_CORRUPT	NUMBER	Number of blocks media corrupt
LOGICALLY_CORRUPT	NUMBER	Number of blocks logically corrupt
DATAFILE_BLOCKS	NUMBER	Size of the datafile in blocks at backup time. This value is also the number of blocks taken by the datafile restarted from this backup.
BLOCKS	NUMBER	Size of the backup datafile (in blocks). Unused blocks are not copied to the backup.
BLOCK_SIZE	NUMBER	Block size

Column	Datatype	Description
OLDEST_OFFLINE_RANGE	NUMBER	RECID of the oldest offline range record in this backup control file. 0 for datafile backups.
COMPLETION_TIME	DATE	Time completed
CONTROLFILE_TYPE	VARCHAR2 (1)	B - Normal copies S - Standby copies
USED_CHANGE_TRACKING	VARCHAR2 (3)	Indicates whether change tracking data was used to accelerate this incremental backup (YES) or whether change tracking data was not used (NO)
BLOCKS_READ	NUMBER	Number of blocks that were scanned while taking this backup. If this was an incremental backup, and change tracking was used to optimize the backup, then the value of this column will be smaller than DATAFILE_BLOCKS. Otherwise, the value of this column will be the same as DATAFILE_BLOCKS. Even when change tracking data is used, the value of this column may be larger than BLOCKS, because the data read by change tracking is further refined during the process of creating an incremental backup.
USED_OPTIMIZATION	VARCHAR2 (3)	Indicates whether backup optimization was applied (YES) or not (NO)
FOREIGN_DBID	NUMBER	Foreign DBID of the database from which this datafile was transported. The value is 0 if the file backed up is not a foreign database file.
PLUGGED_READONLY	VARCHAR2 (3)	YES if this is a backup of a transported read-only foreign file; otherwise NO.
PLUGIN_CHANGE#	NUMBER	SCN at which the foreign datafile was transported into the database. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_CHANGE#	NUMBER	The SCN of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_TIME	DATE	The time of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
SECTION_SIZE	NUMBER	Specifies the number of blocks in each section of a multisection backup. Value is 0 for whole file backups.
UNDO_OPTIMIZED	VARCHAR2 (3)	Indicates whether undo blocks were ignored when creating the backup datafile (YES) or not (NO)
BLOCKS_SKIPPED_IN_CELL	NUMBER	Number of blocks that were not backed up because they were skipped by the Exadata cell See Also: Oracle Exadata Storage Server Software documentation for more information

V\$BACKUP_DATAFILE_DETAILS

V\$BACKUP_DATAFILE_DETAILS contains information about restorable datafiles. It will include all datafiles backed in the backup set, image copies, and proxy copies.

Column	Datatype	Description
BTYPE	CHAR (9)	Backup type container. Possible values are: BACKUPSET, IMAGECOPY, PROXYCOPY.
BTYPE_KEY	NUMBER	Unique identifier for the backup type. For BACKUPSET, it is BS_KEY.
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session record ID
SESSION_STAMP	NUMBER	Session stamp
ID1	NUMBER	If BACKUPSET, it contains SET_STAMP. If IMAGECOPY or PROXYCOPY, it is RECID from the control file.

Column	Datatype	Description
ID2	NUMBER	If BACKUPSET, it contains SET_COUNT. If IMAGECOPY or PROXYCOPY, it is STAMP.
FILE#	NUMBER	File number
CREATION_CHANGE#	NUMBER	File creation change SCN
CREATION_TIME	DATE	File creation time
RESETLOGS_CHANGE#	NUMBER	Resetlogs change SCN
RESETLOGS_TIME	DATE	Resetlogs change time
INCREMENTAL_LEVEL	NUMBER	Incremental level
INCREMENTAL_CHANGE#	NUMBER	Incremental change SCN
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change SCN
CHECKPOINT_TIME	DATE	Checkpoint change time
MARKED_CORRUPT	NUMBER	Number of blocks marked corrupt
FILESIZE	NUMBER	File size, in bytes
COMPRESSION_RATIO	NUMBER	Compression ratio
TS#	NUMBER	Tablespace number
TSNAME	VARCHAR2 (30)	Tablespace name
FILESIZE_DISPLAY	VARCHAR2 (4000)	Same value as the FILESIZE column, but converted to a user-displayable format, for example nM, nG, nT, nP, and so on

V\$BACKUP_DATAFILE_SUMMARY

V\$BACKUP_DATAFILE_SUMMARY provides summary information for a specific criteria set, based on a backup job, a time range applicable to jobs, or a specific datafile).

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of files backed up for specified criteria
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct files backed up
NUM_DISTINCT_TS_BACKED	NUMBER	Number of distinct tablespaces backed up
MIN_CHECKPOINT_CHANGE#	NUMBER	Minimum checkpoint change number of the datafile for specified criteria
MAX_CHECKPOINT_CHANGE#	NUMBER	Maximum checkpoint change number of the datafile for specified criteria
MIN_CHECKPOINT_TIME	DATE	Minimum checkpoint time of the datafile for specified criteria
MAX_CHECKPOINT_TIME	DATE	Maximum checkpoint time of the datafile for specified criteria
INPUT_BYTES	NUMBER	Total input bytes of files read
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPRESSION_RATIO	NUMBER	Compression ratio
INPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for input bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output bytes

V\$BACKUP_DEVICE

V\$BACKUP_DEVICE displays information about supported backup devices. If a device type does not support named devices, then one row with the device type and a null device name is returned for that device type. If a device type supports named devices

then one row is returned for each available device of that type. The special device type DISK is not returned by this view because it is always available.

Column	Datatype	Description
DEVICE_TYPE	VARCHAR2 (17)	Type of the backup device
DEVICE_NAME	VARCHAR2 (513)	Name of the backup device

V\$BACKUP_FILES

V\$BACKUP_FILES displays information about all RMAN backups (both image copies and backup sets) and archived logs.

This view simulates the LIST BACKUP and LIST COPY RMAN commands. This view requires that the database be set using the DBMS_RCVMAN.SETDATABASE procedure.

Column	Datatype	Description
PKEY	NUMBER	Primary key for the backup
BACKUP_TYPE	VARCHAR2 (32)	Type of the backup: ■ BACKUP SET ■ COPY ■ PROXY COPY
FILE_TYPE	VARCHAR2 (32)	Type of the file: ■ DATAFILE ■ CONTROLFILE ■ SPFILE ■ REDO LOG ■ ARCHIVED LOG ■ COPY (for an image copy backup) ■ PIECE (for a backup piece)
KEEP	VARCHAR2 (3)	Indicates whether the backup has a retention policy different from the value for CONFIGURE RETENTION POLICY (YES) or not (NO)
KEEP_UNTIL	DATE	If the KEEP UNTIL TIME clause of the BACKUP command was specified, then this column shows the date after which the backup becomes obsolete. If the column is null and KEEP_OPTIONS is not null, the backup never becomes obsolete.
KEEP_OPTIONS	VARCHAR2 (13)	KEEP options for the backup: ■ LOGS - RMAN keeps the logs needed to recover the backup ■ NOLOGS - RMAN does not keep the logs needed to recover the backup If this column is null, then the backup has no KEEP options and will be made obsolete based on the retention policy.
STATUS	VARCHAR2 (16)	Status of the backup: ■ AVAILABLE ■ UNAVAILABLE ■ EXPIRED ■ OTHER
FNAME	VARCHAR2 (1024)	Name of the file
TAG	VARCHAR2 (32)	Tag of the piece, copy, or proxy copy
MEDIA	VARCHAR2 (80)	Media ID of the piece or proxy copy
RECID	NUMBER	Recid of the record in the control file
STAMP	NUMBER	Stamp of the record in the control file

Column	Datatype	Description
DEVICE_TYPE	VARCHAR2 (255)	Type of media device that stores the backup
BLOCK_SIZE	NUMBER	Block size for the backup (in bytes)
COMPLETION_TIME	DATE	Time when the backup completed
COMPRESSED	VARCHAR2 (3)	Indicates whether the backup piece is compressed (YES) or not (NO); valid only if FILE_TYPE is PIECE. Image copies cannot be compressed.
OBSOLETE	VARCHAR2 (3)	Indicates whether the backup piece or copy is obsolete (YES) or not (NO); valid only if FILE_TYPE is PIECE or COPY
BYTES	NUMBER	Size of the file (in bytes)
BS_KEY	NUMBER	Primary key of the backup set (valid only if BACKUP_TYPE is BACKUP SET)
BS_COUNT	NUMBER	Count of the backup set from the control file record (valid only if BACKUP_TYPE is BACKUP SET)
BS_STAMP	NUMBER	Stamp of the backup set from the control file record (valid only if BACKUP_TYPE is BACKUP SET)
BS_TYPE	VARCHAR2 (32)	Type of the backup set (valid only if BACKUP_TYPE is BACKUP SET): - DATAFILE - ARCHIVED LOG
BS_INCR_TYPE	VARCHAR2 (32)	Incremental type of the backup set (valid only if BACKUP_TYPE is BACKUP SET)
BS_PIECES	NUMBER	Number of backup pieces in the backup set (valid only if BACKUP_TYPE is BACKUP SET)
BS_COPIES	NUMBER	Number of copies of the backup set (valid only if FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)
BS_COMPLETION_TIME	DATE	Completion time of the backup set (valid only if BACKUP_TYPE is BACKUP SET)
BS_STATUS	VARCHAR2 (16)	Status of the backup set (valid only if BACKUP_TYPE is BACKUP SET): - AVAILABLE - UNAVAILABLE - EXPIRED - OTHER - Pieces which are part of the backup set do not have uniform status (that is, some of them are available, some not)
BS_BYTES	NUMBER	Sum of all backup piece sizes in the backup set (valid only if BACKUP_TYPE is BACKUP SET)
BS_COMPRESSED	VARCHAR2 (3)	Indicates whether the backup pieces of the backup set are compressed (YES) or not (NO); valid only if BACKUP_TYPE is BACKUP SET
BS_TAG	VARCHAR2 (1024)	Tags of the backup set. If pieces have different tags, then all piece tags are concatenated and separated by commas. Valid only if BACKUP_TYPE is BACKUP SET)
BS_DEVICE_TYPE	VARCHAR2 (255)	Device type of the backup set. If there is more than one device type, then they are separated by commas. Valid only if BACKUP_TYPE is BACKUP SET
BP_PIECE#	NUMBER	Number of pieces inside the backup set (valid only if FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)
BP_COPY#	NUMBER	Number of copies of the backup set (valid only if FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)
DF_FILE#	NUMBER	Absolute file number of the datafile (valid only if FILE_TYPE is DATAFILE)
DF_TABLESPACE	VARCHAR2 (30)	Tablespace name of the datafile (valid only if FILE_TYPE is DATAFILE)
DF_RESETLOGS_CHANGE#	NUMBER	System change number (SCN) of the most recent RESETLOGS when the control file or datafile was created (valid only if FILE_TYPE is DATAFILE)
DF_CREATION_CHANGE#	NUMBER	Creation SCN of the control file or datafile (valid only if FILE_TYPE is CONTROLFILE or DATAFILE)

Column	Datatype	Description
DF_CHECKPOINT_CHANGE#	NUMBER	System change number (SCN) of the most recent control file or datafile checkpoint (valid only if FILE_TYPE is CONTROLFILE or DATAFILE)
DF_CKP_MOD_TIME	DATE	Modification time in case of SPFILE, otherwise time when the control file or datafile was checkpointed (valid only if FILE_TYPE is SPFILE, CONTROLFILE, or DATAFILE)
RL_THREAD#	NUMBER	Redo log thread number of the archived log (valid only if FILE_TYPE is REDO LOG)
RL_SEQUENCE#	NUMBER	Redo log sequence number of the archived log (valid only if FILE_TYPE is REDO LOG)
RL_RESETLOGS_CHANGE#	NUMBER	System change number (SCN) of the most recent RESETLOGS when the record was created (valid only if FILE_TYPE is REDO LOG)
RL_FIRST_CHANGE#	NUMBER	First SCN of the redo log (valid only if FILE_TYPE is REDO LOG)
RL_FIRST_TIME	DATE	Time when the Oracle Database switched into the redo log (valid only if FILE_TYPE is REDO LOG)
RL_NEXT_CHANGE#	NUMBER	First SCN of the next redo log in the thread (valid only if FILE_TYPE is REDO LOG)
RL_NEXT_TIME	DATE	First timestamp of the next redo log in the thread (valid only if FILE_TYPE is REDO LOG)

V\$BACKUP_PIECE

V\$BACKUP_PIECE displays information about backup pieces from the control file. Each backup set consists of one or more backup pieces.

Column	Datatype	Description
RECID	NUMBER	Backup piece record ID
STAMP	NUMBER	Backup piece record stamp
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
PIECE#	NUMBER	Backup piece number (1-N)
COPY#	NUMBER	Indicates the copy number for backup pieces created with duplex enabled. 1 if the backup piece is not duplexed.
DEVICE_TYPE	VARCHAR2 (17)	Type of the device on which the backup piece resides. Set to DISK for backup sets on disk. See Also: V\$BACKUP_DEVICE
HANDLE	VARCHAR2 (513)	Backup piece handle identifies the backup piece on restore
COMMENTS	VARCHAR2 (64)	Comment returned by the operating system or storage subsystem. Set to NULL for backup pieces on disk. This value is informational only; not needed for restore.
MEDIA	VARCHAR2 (65)	Name of the media on which the backup piece resides. This value is informational only; not needed for restore.
MEDIA_POOL	NUMBER	The media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command.
CONCUR	VARCHAR2 (3)	(YES NO) Indicates whether the piece on a media that can be accessed concurrently
TAG	VARCHAR2 (32)	Backup piece tag. The tag is specified at backup set level, but stored at piece level.
STATUS	VARCHAR2 (1)	Indicates the status of the piece: A (available), D (deleted), or X (expired)
START_TIME	DATE	Starting time
COMPLETION_TIME	DATE	Completion time

Column	Datatype	Description
ELAPSED_SECONDS	NUMBER	Number of elapsed seconds
DELETED	VARCHAR2 (3)	(YES/NO) NO indicates that the file still exists. YES indicates the file no longer exists because it has been deleted.
BYTES	NUMBER	Size of the backup piece (in bytes)
IS_RECOVERY_DEST_FILE	VARCHAR2 (3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
RMAN_STATUS_RECID	NUMBER	Owning V\$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V\$RMAN_STATUS record stamp
COMPRESSED	VARCHAR2 (3)	Indicates whether the backup piece is compressed (YES) or not (NO)
BACKED_BY_VSS	VARCHAR2 (3)	Whether or not the file has been backed up by Volume Shadow Copy Service (VSS). This column is reserved for internal use.
ENCRYPTED	VARCHAR2 (3)	A value of YES means an encrypted backup, otherwise not an encrypted backup.
BACKED_BY_OSB	VARCHAR2 (3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.

V\$BACKUP_PIECE_DETAILS

V\$BACKUP_PIECE_DETAILS displays information about all available backup pieces.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
BS_KEY	NUMBER	Backup set identifier
BP_KEY	NUMBER	Backup piece key
RECID	NUMBER	Backup piece record ID
STAMP	NUMBER	Backup piece record stamp
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
PIECE#	NUMBER	Backup piece number (1-N)
COPY#	NUMBER	Indicates the copy number for backup pieces created with duplex enabled. The value is 1 if the backup piece is not duplexed.
DEVICE_TYPE	VARCHAR2 (17)	Type of device on which the backup piece resides. Set to DISK for backup sets on disk.
HANDLE	VARCHAR2 (513)	Backup piece handle identifies the backup piece on restore
COMMENTS	VARCHAR2 (64)	Comments returned by the operating system or storage subsystem. Set to NULL for backup pieces on disk. This value is informational only. It is not needed for restore.
MEDIA	VARCHAR2 (65)	Name of the media on which the backup piece resides. This value is informational only. It is not needed for restore.
MEDIA_POOL	NUMBER	The media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command.
CONCUR	VARCHAR2 (3)	(YES NO) indicates whether or not the piece is on a media that can be accessed concurrently
TAG	VARCHAR2 (32)	Backup piece tag. The tag is specified at backup set level, but stored at piece level.
STATUS	VARCHAR2 (1)	Indicates the status of the piece: A (available), D (deleted), or X (expired)

Column	Datatype	Description
START_TIME	DATE	Starting time
COMPLETION_TIME	DATE	Completion time
ELAPSED_SECONDS	NUMBER	Number of elapsed seconds
DELETED	VARCHAR2 (3)	NO indicates that the file still exists. YES indicates that the file no longer exists because it has been deleted.
BYTES	NUMBER	Size of the backup piece, in bytes
IS_RECOVERY_DEST_FILE	VARCHAR2 (3)	Indicates whether or not the file was created in the fast recovery area (YES) or not (NO)
RMAN_STATUS_RECID	NUMBER	Owning V\$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V\$RMAN_STATUS record stamp
COMPRESSED	VARCHAR2 (3)	Indicates whether the backup piece is compressed (YES) or not (NO)
BACKED_BY_VSS	VARCHAR2 (3)	Whether or not the file has been backed up by Volume Shadow Copy Service (VSS). This column is reserved for internal use.
ENCRYPTED	VARCHAR2 (3)	A value of YES means an encrypted backup, otherwise not an encrypted backup.
BACKED_BY_OSB	VARCHAR2 (3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.
PIECES_PER_SET	NUMBER	Number of backup pieces per set
SIZE_BYTES_DISPLAY	VARCHAR2 (4000)	Size (in bytes) of the backup piece to display

V\$BACKUP_REDOLOG

V\$BACKUP_REDOLOG displays information about archived logs in backup sets from the control file. Note that online redo logs cannot be backed up directly; they must be archived first to disk and then backed up. An archive log backup set can contain one or more archived logs.

Column	Datatype	Description
RECID	NUMBER	Record ID for this row; it is an integer that identifies this row
STAMP	NUMBER	Timestamp used with RECID to uniquely identify this row
SET_STAMP	NUMBER	One of the foreign keys for the row of the V\$BACKUP_SET table that identifies this backup set
SET_COUNT	NUMBER	One of the foreign keys for the row of the V\$BACKUP_SET table that identifies this backup set
THREAD#	NUMBER	Thread number for the log
SEQUENCE#	NUMBER	Log sequence number
RESETLOGS_CHANGE#	NUMBER	Change number of the last resetlogs before the log was written
RESETLOGS_TIME	DATE	Change time of the last resetlogs before the log was written. These will be the same for all logs in a backup set.
FIRST_CHANGE#	NUMBER	SCN when the log was switched into. The redo in the log is at this SCN and greater.
FIRST_TIME	DATE	Time allocated when the log was switched into
NEXT_CHANGE#	NUMBER	SCN when the next log in this thread was switched into. The redo in the log is below this SCN.
NEXT_TIME	DATE	Time when the next log in this thread was switched into
BLOCKS	NUMBER	Size of the log in logical blocks including the header block
BLOCK_SIZE	NUMBER	Size of the log blocks in bytes
TERMINAL	VARCHAR2 (3)	Indicates whether this record corresponds to a terminal archived redo log, as defined in V\$ARCHIVED_LOG (YES) or not (NO)

V\$BACKUP_SET

V\$BACKUP_SET displays information about backup sets from the control file. A backup set record is inserted after the backup set is successfully completed.

Column	Datatype	Description
RECID	NUMBER	Backup set record ID
STAMP	NUMBER	Backup set record stamp
SET_STAMP	NUMBER	Backup set stamp. The backup set stamp and count uniquely identify the backup set.
SET_COUNT	NUMBER	Primary key for the V\$BACKUP_SET table, and the foreign key for the following tables: V\$BACKUP_PIECE, V\$BACKUP_DATAFILE, V\$BACKUP_REDOLOG, V\$BACKUP_CORRUPTION. Backup set count. The backup set count is incremented by one every time a new backup set is started (if the backup set is never completed the number is "lost"). If the control file is re-created then the count is reset to 1. Therefore the count must be used with the stamp to uniquely identify a backup set. Primary key for the V\$BACKUP_SET table, and the foreign key for the following tables: V\$BACKUP_PIECE, V\$BACKUP_DATAFILE, V\$BACKUP_REDOLOG, V\$BACKUP_CORRUPTION
BACKUP_TYPE	VARCHAR2 (1)	Type of files that are in this backup. If the backup contains archived redo logs, the value is L. If this is a datafile full backup, the value is D. If this is an incremental backup, the value is I.
CONTROLFILE_INCLUDED	VARCHAR2 (3)	Set to YES if there is a control file included in this backup set, otherwise set to NO
INCREMENTAL_LEVEL	NUMBER	Location where this backup set fits into the database's backup strategy. Set to zero for full datafile backups, nonzero for incremental datafile backups, and NULL for archive log backups.
PIECES	NUMBER	Number of distinct backup pieces in the backup set
START_TIME	DATE	Starting time
COMPLETION_TIME	DATE	Time that this backup set completed
ELAPSED_SECONDS	NUMBER	The number of elapsed seconds
BLOCK_SIZE	NUMBER	Block size of the backup set
INPUT_FILE_SCAN_ONLY	VARCHAR2 (3)	YES indicates no actual backup is performed, but the datafiles are read. NO indicates a normal backup is performed.
KEEP	VARCHAR2 (3)	(YES/NO) Indicates whether or not this backup set has a retention policy that is different than the value for the configure retention policy
KEEP_UNTIL	DATE	If KEEP_UNTIL_TIME is specified, this is the date after which the backup becomes obsolete. If this column is null, then the backup never expires.
KEEP_OPTIONS	VARCHAR2 (10)	Lists additional retention options for this backup set. Possible values are: LOGS - The logs need to recover this backup are kept NOLOGS - The logs needed to recover this backup will not be kept BACKUP_LOGS - An archive log backup exists to support this backup set
MULTI_SECTION	VARCHAR2 (3)	Indicates whether or not this backup set is a multi-section backup. Valid values are YES and NO. A multi-section backup is a backup in which multiple backup pieces are produced independently in parallel by multiple channels.

V\$BACKUP_SET_DETAILS

V\$BACKUP_SET_DETAILS provides detailed information about the backup set. This view will contain an extra row for each backup session that invokes BACKUP BACKUPSET (that is, creates new copies for the same backup set or copies backup set

information from disk to tape). However, the remaining values of other columns belong to the complete backup set.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Identifies the job, together with SESSION_STAMP.
SESSION_STAMP	NUMBER	Identifies the job, together with SESSION_RECID
BS_KEY	NUMBER	Backup set identifier
RECID	NUMBER	RECID from V\$BACKUP_SET record
STAMP	NUMBER	Stamp from V\$BACKUP_SET record
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup count number
BACKUP_TYPE	VARCHAR2 (1)	Type of backup (same as in V\$BACKUP_SET)
CONTROLFILE_INCLUDED	VARCHAR2 (3)	Control file included in backup set (same as in V\$BACKUP_SET)
INCREMENTAL_LEVEL	NUMBER	Incremental level (same as in V\$BACKUP_SET)
PIECES	NUMBER	Number of pieces (same as in V\$BACKUP_SET)
START_TIME	DATE	Start time of the backup set (same as in V\$BACKUP_SET)
COMPLETION_TIME	DATE	Completion time of the backup set (same as in V\$BACKUP_SET)
ELAPSED_SECONDS	NUMBER	Time taken for backup set creation (same as in V\$BACKUP_SET)
BLOCK_SIZE	NUMBER	Block size (same as in V\$BACKUP_SET)
KEEP	VARCHAR2 (3)	Keep value (same as in V\$BACKUP_SET)
KEEP_UNTIL	DATE	Keep Until time (same as in V\$BACKUP_SET)
KEEP_OPTIONS	VARCHAR2 (10)	Keep options (same as in V\$BACKUP_SET)
DEVICE_TYPE	VARCHAR2 (17)	Type of device. If the backup set exists on more than one device type, an * is indicated here.
COMPRESSED	VARCHAR2 (3)	YES, if backup is compressed
NUM_COPIES	NUMBER	Number of identical copies
OUTPUT_BYTES	NUMBER	Size of the backup set
ORIGINAL_INPUT_BYTES	NUMBER	Amount of data backed up when the backup set was created
COMPRESSION_RATIO	NUMBER	Compression ratio (input size/output size)
STATUS	CHAR (1)	The status of the backup set. It is always A (all backup pieces available), because this view only reflects available backup sets.
ORIGINAL_INPRATE_BYTES	NUMBER	Number of bytes read per second when backup set was initially created
OUTPUT_RATE_BYTES	NUMBER	Number of bytes written per second when the backup set was initially created
ORIGINAL_INPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Input rate to display
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Size of backup set to display
ORIGINAL_INPRATE_BYTES_DISPLAY	VARCHAR2 (4000)	Input rate per second for display
OUTPUT_RATE_BYTES_DISPLAY	VARCHAR2 (4000)	Output rate per second for display
TIME_TAKEN_DISPLAY	VARCHAR2 (4000)	Elapsed time in hh:mm:ss format
ENCRYPTED	VARCHAR2 (3)	A value of YES means an encrypted backup, otherwise not an encrypted backup.
BACKED_BY_OSB	VARCHAR2 (3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.

V\$BACKUP_SET_SUMMARY

V\$BACKUP_SET_SUMMARY provides summary information for a backup set.

Column	Datatype	Description
NUM_BACKUPSETS	NUMBER	Total number of backup sets created
OLDEST_BACKUP_TIME	DATE	Oldest backup start time
NEWEST_BACKUP_TIME	DATE	Newest backup start time
OUTPUT_BYTES	NUMBER	Number of output bytes (not including multiple copies)
ORIGINAL_INPUT_BYTES	NUMBER	Number of input bytes when backup sets were created
ORIGINAL_INPRATE_BYTES	NUMBER	Average input rate
OUTPUT_RATE_BYTES	NUMBER	Average output rate
COMPRESSION_RATIO	NUMBER	Compression ratio
ORIGINAL_INPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for input bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output bytes
ORIGINAL_INPRATE_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for input rate
OUTPUT_RATE_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output rate

V\$BACKUP_SPFILE

V\$BACKUP_SPFILE displays information about server parameter files in backup sets from the control file.

Column	Datatype	Description
RECID	NUMBER	Backup SPFILE record ID
STAMP	NUMBER	Backup SPFILE record stamp
SET_STAMP	NUMBER	Backup set stamp (of the set which contains this SPFILE backup)
SET_COUNT	NUMBER	Backup set count (of the set which contains this SPFILE backup)
MODIFICATION_TIME	DATE	Time when the SPFILE was last modified (this also includes creation time)
BYTES	NUMBER	Size of the SPFILE (in bytes)
COMPLETION_TIME	DATE	Time when the backup of the SPFILE completed
DB_UNIQUE_NAME	VARCHAR2 (30)	Unique database name

V\$BACKUP_SPFILE_DETAILS

V\$BACKUP_SPFILE_DETAILS displays information about all restorable SP files backed up in the backup set.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
BS_KEY	NUMBER	Unique backup set identifier
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count

Column	Datatype	Description
MODIFICATION_TIME	DATE	Time the backup set was modified
FILESIZE	NUMBER	Size, in bytes, of the SPFILE that was backed up
FILESIZE_DISPLAY	VARCHAR2 (4000)	Same value as the FILESIZE column, but converted to a user-displayable format, for example <i>nM</i> , <i>nG</i> , <i>nT</i> , <i>nP</i> , and so on

V\$BACKUP_SPFILE_SUMMARY

V\$BACKUP_SPFILE_SUMMARY provides summary information for input SP file, based on either a backup job or time range applicable to jobs.

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of files backed up
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct SP files backed up (with modification timestamp)
MIN_MODIFICATION_TIME	DATE	Minimum modification time
MAX_MODIFICATION_TIME	DATE	Maximum modification time
INPUT_BYTES	NUMBER	Total input bytes for all SP files backed up
INPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for all input bytes

V\$BACKUP_SYNC_IO

V\$BACKUP_SYNC_IO displays performance information about ongoing and recently completed RMAN backups and restores. For each backup, it contains one row for each input datafile, one row for the aggregate total performance of all datafiles, and one row for the output backup piece. This data is not stored persistently, and is not preserved when the instance is re-started.

See Also: *Oracle Database Performance Tuning Guide* for information on how to use this table to tune backup performance

Column	Datatype	Description
SID	NUMBER	The Oracle SID of the session doing the backup or restore
SERIAL	NUMBER	The use count for the SID doing the backup or restore
USE_COUNT	NUMBER	A counter that can be used to identify rows from different backup sets
RMAN_STATUS_RECID	NUMBER	Owning V\$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V\$RMAN_STATUS record stamp
DEVICE_TYPE	VARCHAR2 (17)	The device type where the file is located
TYPE	VARCHAR2 (9)	INPUT, OUTPUT, or AGGREGATE
STATUS	VARCHAR2 (11)	NOT STARTED, IN PROGRESS, or FINISHED
FILENAME	VARCHAR2 (513)	The name of the backup file being read or written
SET_COUNT	NUMBER	The set count of the backup set being read or written
SET_STAMP	NUMBER	The set stamp of the backup set being read or written
BUFFER_SIZE	NUMBER	The size of the buffers being used to read/write this file, in bytes
BUFFER_COUNT	NUMBER	The number of buffers being used to read/write this file
TOTAL_BYTES	NUMBER	The total number of bytes that will be read or written for this file, if known. If not known, this column will be null.

Column	Datatype	Description
OPEN_TIME	DATE	The time this file was opened. If TYPE='AGGREGATE', then this is the time that the first file in the aggregate was opened.
CLOSE_TIME	DATE	The time this file was closed. If TYPE='AGGREGATE', then this is the time that the last file in the aggregate was closed.
ELAPSED_TIME	NUMBER	The time, in hundredths of a second, that the file was open
MAXOPENFILES	NUMBER	The number of concurrently open DISK files. This value is only present in rows where TYPE='AGGREGATE'.
BYTES	NUMBER	The number of bytes read or written so far
EFFECTIVE_BYTES_PER_SECOND	NUMBER	The I/O rate that was achieved with this device during this backup
IO_COUNT	NUMBER	The number of I/Os that were performed to this file
IO_TIME_TOTAL	NUMBER	The total time, in hundredths of a second, taken to do I/O for this file
IO_TIME_MAX	NUMBER	The maximum time taken for a single I/O request
DISCRETE_BYTES_PER_SECOND	NUMBER	The average transfer rate for this file

V\$BGPROCESS

V\$BGPROCESS displays information about the background processes.

Column	Datatype	Description
PADDR	RAW (4 8)	Address of the process state object
PSERIAL#	NUMBER	Process state object serial number
NAME	VARCHAR2 (5)	Name of this background process
DESCRIPTION	VARCHAR2 (64)	Description of the background process
ERROR	NUMBER	Error encountered

V\$BH

V\$BH displays the status and number of pings for every buffer in the SGA. This is a Real Application Clusters view.

Column	Datatype	Description
FILE#	NUMBER	Datafile identifier number (to find the filename, query DBA_DATA_FILES or V\$DBFILE)
BLOCK#	NUMBER	Block number
CLASS#	NUMBER	Class number
STATUS	VARCHAR2 (6)	Status of the buffer: ■ free - Not currently in use ■ xcur - Exclusive ■ scur - Shared current ■ cr - Consistent read ■ read - Being read from disk ■ mrec - In media recovery mode ■ irec - In instance recovery mode
XNC	NUMBER	This column is obsolete. Its value is hard-coded to 0.
FORCED_READS	NUMBER	This column is obsolete. Its value is hard-coded to 0.

Column	Datatype	Description
FORCED_WRITES	NUMBER	This column is obsolete. Its value is hard-coded to 0.
LOCK_ELEMENT_ADDR	RAW (4 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_NAME	NUMBER	The address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_CLASS	NUMBER	The address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
DIRTY	VARCHAR2 (1)	Y - block modified
TEMP	VARCHAR2 (1)	Y - temporary block
PING	VARCHAR2 (1)	Y - block pinged
STALE	VARCHAR2 (1)	Y - block is stale
DIRECT	VARCHAR2 (1)	Y - direct block
NEW	VARCHAR2 (1)	Always set to N. This column is obsolete and maintained for backward compatibility.
OBJD	NUMBER	Database object number of the block that the buffer represents
TS#	NUMBER	Tablespace number of block
LOBID	NUMBER	If the buffer belongs to a SecureFiles object, the value in this column is the unique identifier for the SecureFiles object. For other buffer types, the value in this column is meaningless.

See Also: The *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Installation Guide* for your operating system.

V\$BLOCK_CHANGE_TRACKING

V\$BLOCK_CHANGE_TRACKING displays the status of block change tracking for the database.

Column	Datatype	Description
STATUS	VARCHAR2 (10)	Status of block change tracking in the database: - DISABLED - Block change tracking is disabled - TRANSITION - Block change tracking is in the process of transitioning between the enabled and disabled states. The TRANSITION state should usually never be observed, because it only exists while enabling or disabling block change tracking. This state might be observed if the instance crashed while enabling or disabling block change tracking, in which case it will be cleaned up automatically the next time that the database is opened. - ENABLED - Block change tracking is enabled
FILENAME	VARCHAR2 (513)	Name of the block change tracking file for the database
BYTES	NUMBER	Size of the block change tracking file (in bytes)

See Also: *Oracle Database Backup and Recovery User's Guide* for information on setting up block change tracking

V\$BLOCKING_QUIESCE

V\$BLOCKING_QUIESCE indicates if a session is blocking, or would block, a quiesce operation.

Column	Datatype	Description
SID	NUMBER	Session identifier

V\$BUFFER_POOL

V\$BUFFER_POOL displays information about all buffer pools available for the instance.

Column	Datatype	Description
ID	NUMBER	Buffer pool identifier number
NAME	VARCHAR2 (20)	Name of the buffer pool: ■ DEFAULT ■ KEEP ■ RECYCLE Note: Currently, KEEP and RECYCLE pools only exist for the standard block size. All non-standard block size pools are DEFAULT.
BLOCK_SIZE	NUMBER	Block size (in bytes) for buffers in this pool. Possible values: the standard block size, the power of 2 non-standard block sizes, 2048, 4096, 8192, 16384, 32768.
RESIZE_STATE	VARCHAR2 (10)	Current state of the resize operation: STATIC - Not being resized ALLOCATING - Memory is being allocated (can be cancelled by the user) ACTIVATING - New buffers are being created (user cannot cancel) SHRINKING - Buffers are being deleted (can be cancelled by the user)
CURRENT_SIZE	NUMBER	Present size of the sub-cache (in megabytes)
BUFFERS	NUMBER	Current instantaneous number of buffers
TARGET_SIZE	NUMBER	If a resize is in progress (state is not STATIC), records new target size (in megabytes). If the pool is STATIC, the value in this column is the same as the current size of the pool.
TARGET_BUFFERS	NUMBER	If a resize is in progress, records new target size in terms of buffers. Otherwise, the value in this column is the same as the current number of buffers.
PREV_SIZE	NUMBER	Previous buffer pool size. If the buffer pool has never been resized, the previous size is zero.
PREV_BUFFERS	NUMBER	Previous number of buffers in the buffer pool. Value is zero if the buffer pool has never been resized.
LO_BNUM	NUMBER	Obsolete column
HI_BNUM	NUMBER	Obsolete column
LO_SETID	NUMBER	Obsolete column
HI_SETID	NUMBER	Obsolete column
SET_COUNT	NUMBER	Obsolete column

See Also: ["DB_BLOCK_SIZE"](#) on page 1-45

V\$BUFFER_POOL_STATISTICS

V\$BUFFER_POOL_STATISTICS displays statistics about all buffer pools available for the instance.

Column	Datatype	Description
ID	NUMBER	Buffer pool identifier number
NAME	VARCHAR2 (20)	Name of the buffer pool
SET_MSIZE	NUMBER	Buffer pool maximum set size
CNUM_REPL	NUMBER	Number of buffers on replacement list
CNUM_WRITE	NUMBER	Number of buffers on write list
CNUM_SET	NUMBER	Number of buffers in set
BUF_GOT	NUMBER	Number of buffers gotten by the set
SUM_WRITE	NUMBER	Number of buffers written by the set
SUM_SCAN	NUMBER	Number of buffers scanned in the set
FREE_BUFFER_WAIT	NUMBER	Free buffer wait statistic
WRITE_COMPLETE_WAIT	NUMBER	Write complete wait statistic
BUFFER_BUSY_WAIT	NUMBER	Buffer busy wait statistic
FREE_BUFFER_INSPECTED	NUMBER	Free buffer inspected statistic
DIRTY_BUFFERS_INSPECTED	NUMBER	Dirty buffers inspected statistic
DB_BLOCK_CHANGE	NUMBER	Database blocks changed statistic
DB_BLOCK_GETS	NUMBER	Database blocks gotten statistic
CONSISTENT_GETS	NUMBER	Consistent gets statistic
PHYSICAL_READS	NUMBER	Physical reads statistic
PHYSICAL_WRITES	NUMBER	Physical writes statistic

See Also: ["DB_CACHE_SIZE"](#) on page 1-47

V\$BUFFERED_PUBLISHERS

V\$BUFFERED_PUBLISHERS displays information about all buffered publishers in the instance. There is one row per queue per sender. The values are reset to zero when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2 (30)	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	Name of the queue
SENDER_NAME	VARCHAR2 (30)	Name of the agent enqueueing the message (the Streams name assigned for a capture process)
SENDER_ADDRESS	VARCHAR2 (1024)	Queue name and database name of the source (last propagating) queue; database name is not specified if the source queue is in the local database
SENDER_PROTOCOL	NUMBER	Protocol used by the sender's address
NUM_MSGS	NUMBER	Current number of messages that have yet to be dequeued from the buffer queue
CNUM_MSGS	NUMBER	Cumulative total number of messages enqueued into the buffered queue since the database last started (comparable to V\$STREAMS_CAPTURE.TOTAL_ENQUEUED_MESSAGES)
LAST_ENQUEUED_MSG	NUMBER	Most recently enqueued message identifier
UNBROWSED_MSGS	NUMBER	Number of messages that have been enqueued but not browsed
OVERSPILLED_MSGS	NUMBER	Number of messages that have been spilled but not browsed

Column	Datatype	Description
MEMORY_USAGE	NUMBER	Percentage of the Streams pool that is being used (or 0 if there is no Streams pool)
ELAPSED_ENQUEUE_TIME	NUMBER	Total time spent in enqueue (in hundredths of a second)
ENQUEUE_CPU_TIME	NUMBER	Total CPU time for enqueue (in hundredths of a second)
LAST_ENQUEUE_TIME	TIMESTAMP (3) WITH TIME ZONE	Last message enqueue time
PUBLISHER_STATE	VARCHAR2 (59)	State of the publisher: - IN FLOW CONTROL: TOO MANY UNBROWSED MESSAGES - IN FLOW CONTROL: OVERSPILLED MESSAGES - IN FLOW CONTROL: INSUFFICIENT MEMORY AND UNBROWSED MESSAGES - PUBLISHING MESSAGES - Normal

V\$BUFFERED_QUEUES

V\$BUFFERED_QUEUES displays information about all buffered queues in the instance. There is one row per queue.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2 (30)	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	Name of the queue
STARTUP_TIME	DATE	Startup time
NUM_MSGS	NUMBER	Total number of messages currently in the buffered queue
SPILL_MSGS	NUMBER	Current number of overflow messages spilled to disk from the buffered queue
CNUM_MSGS	NUMBER	Cumulative total number of messages enqueued into the buffered queue since the database last started
CSPILL_MSGS	NUMBER	Cumulative total number of overflow messages spilled to disk from the buffered queue since the database last started
EXPIRED_MSGS	NUMBER	Number of expired messages
OLDEST_MSGID	RAW (16)	Message ID of the oldest message
OLDEST_MSG_ENQTM	TIMESTAMP (3)	Enqueue time of the oldest message
QUEUE_STATE	VARCHAR2 (25)	Indicates whether the queue is in recovery mode (QUEUE IS IN RECOVERY MODE) or not (NORMAL)
ELAPSED_ENQUEUE_TIME	NUMBER	Total time spent in enqueue (in hundredths of a second)
ELAPSED_DEQUEUE_TIME	NUMBER	Total time spent in dequeue (in hundredths of a second)
ELAPSED_TRANSFORMATION_TIME	NUMBER	Total time for evaluating transformations (in hundredths of a second)
ELAPSED_RULE_EVALUATION_TIME	NUMBER	Total time for rule evaluations (in hundredths of a second)
ENQUEUE_CPU_TIME	NUMBER	Total CPU time for enqueue (in hundredths of a second)
DEQUEUE_CPU_TIME	NUMBER	Total CPU time for dequeue (in hundredths of a second)
AVG_MSG_AGE ¹	NUMBER	Average age of messages in the queue
LAST_ENQUEUE_TIME	TIMESTAMP (3) WITH TIME ZONE	Last message enqueue time
LAST_DEQUEUE_TIME	TIMESTAMP (3) WITH TIME ZONE	Last message dequeue time

Column	Datatype	Description
QUEUE_SIZE ¹	NUMBER	Size of queue, which is the total number of bytes allocated for all messages and metadata

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$BUFFERED_SUBSCRIBERS

V\$BUFFERED_SUBSCRIBERS displays information about the subscribers for all buffered queues in the instance. There is one row per subscriber per queue.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2 (30)	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	Name of the queue
SUBSCRIBER_ID	NUMBER	Internal subscriber number (for identification)
SUBSCRIBER_NAME	VARCHAR2 (30)	Name of the subscriber (comparable to the Streams name for the Streams process)
SUBSCRIBER_ADDRESS	VARCHAR2 (1024)	Address of the subscribing agent
PROTOCOL	NUMBER	Protocol of the subscribing agent
SUBSCRIBER_TYPE	VARCHAR2 (30)	Type of the subscriber: ■ PROXY - Proxy subscriber ■ SUBSCRIBER
STARTUP_TIME	DATE	Startup time
LAST_BROWSED_SEQ	NUMBER	Sequence number of the most recently browsed message for the subscriber (comparable to the number of messages in the V\$STREAMS_APPLY_READER view)
LAST_BROWSED_NUM	NUMBER	Internal Message number for the most recently browsed message for the subscriber
LAST_DEQUEUED_SEQ	NUMBER	Sequence number of the most recently dequeued message for the subscriber (comparable to the number of messages in the V\$STREAMS_APPLY_COORDINATOR view)
LAST_DEQUEUED_NUM	NUMBER	Internal Message number for the most recently dequeued message for the subscriber
CURRENT_ENQ_SEQ	NUMBER	Current sequence number of the most recently enqueued message for the subscriber
NUM_MSGS	NUMBER	Total number of outstanding messages currently enqueued in the buffered queue for the subscriber (includes the count of the messages overflowed to disk)
CNUM_MSGS	NUMBER	Cumulative total number of messages enqueued for the subscriber since the database last started
TOTAL_DEQUEUED_MSG	NUMBER	Total number of messages dequeued by the subscriber
TOTAL_SPILLED_MSG	NUMBER	Total number of spilled messages for the subscriber
EXPIRED_MSGS	NUMBER	Number of expired messages
MESSAGE_LAG	NUMBER	Message lag of the subscriber
ELAPSED_DEQUEUE_TIME	NUMBER	Total time spent in dequeue (in hundredths of a second)
DEQUEUE_CPU_TIME	NUMBER	Total CPU time for dequeue (in hundredths of a second)
AVG_MSG_AGE ¹	NUMBER	Average age of messages currently enqueued in the buffered queue for the subscriber
LAST_DEQUEUE_TIME	TIMESTAMP (3) WITH TIME ZONE	Last message dequeue time
OLDEST_MSGID	RAW (16)	Message ID of the oldest message

Column	Datatype	Description
OLDEST_MSG_ENQTM	TIMESTAMP (3)	Enqueue time of the oldest message

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$CACHE

V\$CACHE displays information from the block header of each block in the SGA of the current instance as related to particular database objects. This is a Real Application Clusters view.

Column	Datatype	Description
FILE#	NUMBER	Datafile identifier number (to find the filename, query DBA_DATA_FILES or V\$DBFILE)
BLOCK#	NUMBER	Block number
CLASS#	NUMBER	Class number
STATUS	VARCHAR2 (6)	Status of the block: ■ free - Not currently in use ■ xcur - Exclusive ■ scur - Shared current ■ cr - Consistent read ■ read - Being read from disk ■ mrec - In media recovery mode ■ irec - In instance recovery mode
XNC	NUMBER	Number of PCM x to null lock conversions due to contention with another instance. This column is obsolete and maintained for backward compatibility.
FORCED_READS	NUMBER	Number of times the block had to be reread from the cache because another instance has forced it out of this instance's cache by requesting the lock on the block in exclusive mode
FORCED_WRITES	NUMBER	Number of times GCS had to write this block to cache because this instance had used the block and another instance had requested the lock on the block in a conflicting mode
NAME	VARCHAR2 (30)	Name of the database object containing the block
PARTITION_NAME	VARCHAR2 (30)	Name of the partition (null for non-partitioned objects)

Column	Datatype	Description
KIND	VARCHAR2 (15)	Type of the database object: ■ INDEX ■ TABLE ■ CLUSTER ■ VIEW ■ SYNONYM ■ SEQUENCE ■ PROCEDURE ■ FUNCTION ■ PACKAGE ■ NON-EXISTENT ■ PACKAGE BODY ■ TRIGGER ■ TYPE ■ TYPE BODY ■ TABLE PARTITION ■ INDEX PARTITION ■ LOB ■ LIBRARY ■ JAVA SOURCE ■ JAVA CLASS ■ JAVA RESOURCE ■ JAVA DATA ■ UNDO
OWNER#	NUMBER	Owner number
LOCK_ELEMENT_ADDR	RAW (4 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_NAME	NUMBER	Name of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.

See Also: The *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Installation Guide* for your operating system.

V\$CACHE_LOCK

V\$CACHE_LOCK is deprecated. The information that was provided in this view is now provided in the V\$INSTANCE_CACHE_TRANSFER and V\$SEGMENT_STATISTICS views.

Column	Datatype	Description
FILE#	NUMBER	Datafile identifier number (to find filename, query DBA_DATA_FILES or V\$DBFILE)
BLOCK#	NUMBER	Block number

Column	Datatype	Description
STATUS	VARCHAR2 (6)	Status of the block: ■ free - Not currently in use ■ xcur - Exclusive ■ scur - Shared current ■ cr - Consistent read ■ read - Being read from disk ■ mrec - In media recovery mode ■ irec - In instance recovery mode
XNC	NUMBER	Number of parallel cache management (PCM) lock conversions due to contention with another instance
NAME	VARCHAR2 (30)	Name of the database object containing the block
KIND	VARCHAR2 (12)	Type of database object: ■ 1 - Index ■ 2 - Table ■ 3 - Cluster ■ 4 - View ■ 5 - Synonym ■ 6 - Sequence ■ 7 - Procedure ■ 8 - Function ■ 9 - Package ■ 10 - Nonexistent ■ 11 - Package body ■ 12 - Trigger ■ 13 - Type ■ 14 - Type body ■ 19 - Table partition ■ 20 - Index partition ■ 21 - LOB ■ 22 - Library ■ Null - Unknown
OWNER#	NUMBER	Owner number
LOCK_ELEMENT_ADDR	RAW (4 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_NAME	NUMBER	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
FORCED_READS	NUMBER	Number of times the block had to be reread from the cache because another instance has forced it out of this instance's cache by requesting the lock on the block in exclusive mode
FORCED_WRITES	NUMBER	Number of times GCS had to write this block to cache because this instance had used the block and another instance had requested the lock on the block in a conflicting mode
INDX	NUMBER	Platform-specific lock manager identifier
CLASS	NUMBER	Platform-specific lock manager identifier

See Also: The *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Installation Guide* for your operating system.

V\$CACHE_TRANSFER

V\$CACHE_TRANSFER is identical to the V\$CACHE view but only displays blocks that have been pinged at least once. This view contains information from the block header of each block in the SGA of the current instance as related to particular database objects. This is a Real Application Clusters view.

Column	Datatype	Description
FILE#	NUMBER	Datafile identifier number (to find the filename, query DBA_DATA_FILES or V\$DBFILE)
BLOCK#	NUMBER	Block number
CLASS#	NUMBER	Class number
STATUS	VARCHAR2 (6)	Status of the block: ■ free - Not currently in use ■ xcur - Exclusive ■ scur - Shared current ■ cr - Consistent read ■ read - Being read from disk ■ mrec - In media recovery mode ■ irec - In instance recovery mode
XNC	NUMBER	Number of PCM lock conversions due to contention with another instance. This column is obsolete and maintained for backward compatibility.
FORCED_READS	NUMBER	Number of times the block had to be reread from the cache because another instance has forced it out of this instance's cache by requesting the lock on the block in exclusive mode
FORCED_WRITES	NUMBER	Number of times GCS had to write this block to cache because this instance had used the block and another instance had requested the lock on the block in a conflicting mode
NAME	VARCHAR2 (30)	Name of the database object containing the block
PARTITION_NAME	VARCHAR2 (30)	NULL for non-partitioned objects
KIND	VARCHAR2 (15)	Type of database object See Also: Table 8-1 on page 8-16
OWNER#	NUMBER	Owner number
GC_ELEMENT_ADDR	RAW (4 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
GC_ELEMENT_NAME	NUMBER	The name of the lock that contains the PCM lock that is covering the buffer

See Also: The *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Installation Guide* for your operating system.

V\$CIRCUIT

V\$CIRCUIT contains information about virtual circuits, which are user connections to the database through dispatchers and servers.

Column	Datatype	Description
CIRCUIT	RAW (4 8)	Circuit address
DISPATCHER	RAW (4 8)	Current dispatcher process address
SERVER	RAW (4 8)	Current server process address

Column	Datatype	Description
WAITER	RAW (4 8)	Address of the server process that is waiting for the (currently busy) circuit to become available
SADDR	RAW (4 8)	Address of the session bound to the circuit
STATUS	VARCHAR2 (16)	Status of the circuit: ■ BREAK - currently interrupted ■ EOF - about to be removed ■ OUTBOUND - an outward link to a remote database ■ NORMAL - normal circuit into the local database
QUEUE	VARCHAR2 (16)	Queue the circuit is currently on: ■ COMMON - on the common queue, waiting to be picked up by a server process ■ DISPATCHER - waiting for the dispatcher ■ SERVER - currently being serviced ■ NONE - idle circuit
MESSAGE0	NUMBER	Size in bytes of the messages in the first message buffer
MESSAGE1	NUMBER	Size in bytes of the messages in the second message buffer
MESSAGE2	NUMBER	Size in bytes of the messages in the third message buffer
MESSAGE3	NUMBER	Size in bytes of the messages in the fourth message buffer
MESSAGES	NUMBER	Total number of messages that have gone through this circuit
BYTES	NUMBER	Total number of bytes that have gone through this circuit
BREAKS	NUMBER	Total number of breaks (interruptions) for this circuit
PRESENTATION	VARCHAR2 (257)	Presentation protocol used by the client and server
PCIRCUIT	RAW (4 8)	Address of the parent circuit

V\$CLASS_CACHE_TRANSFER

V\$CLASS_CACHE_TRANSFER is deprecated. The information that was provided in this view is now provided in the V\$INSTANCE_CACHE_TRANSFER and V\$SEGMENT_STATISTICS views.

Column	Datatype	Description
CLASS	CHAR (10)	Block class; always data block
X_2_NULL	NUMBER	Number of blocks with Exclusive-to-NULL conversions; always 0
X_2_NULL_FORCED_WRITE	NUMBER	Number of Exclusive-to-NULL forced writes; always 0
X_2_NULL_FORCED_STALE	NUMBER	Number of Exclusive-to-NULL blocks converted to CR; always 0
X_2_S	NUMBER	Number of blocks with Exclusive-to-Shared conversions; always 0
X_2_S_FORCED_WRITE	NUMBER	Number of Exclusive-to-Shared forced writes; always 0
S_2_NULL	NUMBER	Number of blocks with Shared-to-NULL conversions; always 0
S_2_NULL_FORCED_STALE	NUMBER	Number of Shared-to-NULL blocks converted to CR; always 0
NULL_2_X	NUMBER	Number of blocks with NULL-to-Exclusive conversions; always 0
S_2_X	NUMBER	Number of blocks with Shared-to-Exclusive conversions; always 0
NULL_2_S	NUMBER	Number of blocks with NULL-to-Shared conversions; always 0
CR_TRANSFER	NUMBER	Number of CR blocks transferred; always 0
CURRENT_TRANSFER	NUMBER	Number of current blocks transferred; always 0

V\$CLIENT_STATS

V\$CLIENT_STATS displays measures for all sessions that are active for the client identifier per instance. The statistics available in this view are a subset of those available in V\$SESSTAT and V\$SESS_TIME_MODEL.

Column	Datatype	Description
CLIENT_IDENTIFIER	VARCHAR2 (64)	Client identifier
STAT_ID	NUMBER	Statistic identifier
STAT_NAME	VARCHAR2 (64)	Derived statistic name from V\$STATNAME and V\$SESS_TIME_MODEL
VALUE	NUMBER	Cumulative value (in microseconds)

V\$CLUSTER_INTERCONNECTS

V\$CLUSTER_INTERCONNECTS displays one or more interconnects that are being used for cluster communication.

Column	Datatype	Description
NAME	VARCHAR2 (15)	Name of the interconnect (such as eth0)
IP_ADDRESS	VARCHAR2 (16)	IP address of the interconnect
IS_PUBLIC	VARCHAR2 (4)	If the value is YES, the interface is known to the public. If the value is NO, the interface is known to be private. Note that if the CLUSTER_INTERCONNECTS initialization parameter is also specified, then it is expected that the interconnect is private. Oracle expects cluster traffic to be run on private interconnects only. If the value is empty, it is unknown whether the interface is public or private. Oracle Corporation recommends that you set the interface for Oracle Real Application Clusters (Oracle RAC) communication in the Oracle Cluster Repository (OCR).
SOURCE	VARCHAR2 (31)	Indicates where this interface was picked up from: - Oracle Cluster Registry - Interface was configured in the OCR and Oracle Database found the interface in the OCR - Operating-system dependent software - Oracle Database automatically detects this - CLUSTER_INTERCONNECTS parameter - This initialization parameter was set

V\$CONFIGURED_INTERCONNECTS

V\$CONFIGURED_INTERCONNECTS displays all the interconnects that Oracle is aware of. This view attempts to answer the question of where Oracle found the information about a specific interconnect.

Column	Datatype	Description
NAME	VARCHAR2 (15)	Name of the interconnect (such as eth0)
IP_ADDRESS	VARCHAR2 (16)	IP address of the interconnect

Column	Datatype	Description
IS_PUBLIC	VARCHAR2 (4)	If the value is YES, the interface is known to the public. If the value is NO, the interface is known to be private. Note that if the CLUSTER_INTERCONNECTS initialization parameter is also specified, then it is expected that the interconnect is private. Oracle expects cluster traffic to be run on private interconnects only. If the value is empty, it is unknown whether the interface is public or private. Oracle Corporation recommends that you set the interface for Oracle Real Application Clusters (Oracle RAC) communication in the Oracle Cluster Repository (OCR).
SOURCE	VARCHAR2 (31)	Indicates where this interface was picked up from: - Oracle Cluster Registry - Interface was configured in the OCR and Oracle Database found the interface in the OCR - Operating-system dependent software - Oracle Database automatically detects this - CLUSTER_INTERCONNECTS parameter - This initialization parameter was set

V\$CONTEXT

V\$CONTEXT displays set attributes in the current session.

Column	Datatype	Description
NAMESPACE	VARCHAR2 (31)	Namespace that the attribute is in
ATTRIBUTE	VARCHAR2 (31)	Name of the attribute
VALUE	VARCHAR2 (4000)	Value of the attribute

V\$CONTROLFILE

V\$CONTROLFILE displays the names of the control files.

Column	Datatype	Description
STATUS	VARCHAR2 (7)	INVALID if the name cannot be determined (which should not occur); NULL if the name can be determined
NAME	VARCHAR2 (513)	Name of the control file
IS_RECOVERY_DEST_FILE	VARCHAR2 (3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
BLOCK_SIZE	NUMBER	Control file block size
FILE_SIZE_BKLS	NUMBER	Control file size (in blocks)

V\$CONTROLFILE_RECORD_SECTION

V\$CONTROLFILE_RECORD_SECTION displays information about the control file record sections.

Column	Datatype	Description
TYPE	VARCHAR2 (28)	Identifies the type of record section: ■ DATABASE ■ CKPT PROGRESS ■ REDO THREAD ■ REDO LOG ■ DATAFILE ■ FILENAME ■ TABLESPACE ■ TEMPORARY FILENAME ■ RMAN CONFIGURATION ■ LOG HISTORY ■ OFFLINE RANGE ■ ARCHIVED LOG ■ BACKUP SET ■ BACKUP PIECE ■ BACKUP DATAFILE ■ BACKUP REDOLOG ■ DATAFILE COPY ■ BACKUP CORRUPTION ■ COPY CORRUPTION ■ DELETED OBJECT ■ PROXY COPY ■ BACKUP SPFILE ■ DATABASE INCARNATION ■ FLASHBACK LOG ■ RECOVERY DESTINATION ■ INSTANCE SPACE RESERVATION ■ REMOVABLE RECOVERY FILES ■ RMAN STATUS ■ THREAD INSTANCE NAME MAPPING ■ MTTR ■ DATAFILE HISTORY ■ PLUGGED IN DATAFILE
RECORD_SIZE	NUMBER	Record size in bytes
RECORDS_TOTAL	NUMBER	Number of records allocated for the section
RECORDS_USED	NUMBER	Number of records used in the section
FIRST_INDEX	NUMBER	Index (position) of the first record
LAST_INDEX	NUMBER	Index of the last record
LAST_RECID	NUMBER	Record ID of the last record

V\$COPY_CORRUPTION

V\$COPY_CORRUPTION displays information about datafile copy corruptions from the control file.

Column	Datatype	Description
RECID	NUMBER	Copy corruption record ID

V\$CORRUPT_XID_LIST

Column	Datatype	Description
STAMP	NUMBER	Copy corruption record stamp
COPY_RECID	NUMBER	Datafile copy record ID
COPY_STAMP	NUMBER	Datafile copy record stamp
FILE#	NUMBER	Datafile number
BLOCK#	NUMBER	First block of the corrupted range
BLOCKS	NUMBER	Number of contiguous blocks in the corrupted range
CORRUPTION_CHANGE#	NUMBER	Change number at which the logical corruption was detected. Set to 0 to indicate media corruption.
MARKED_CORRUPT	VARCHAR2 (3)	(YES NO) If set to YES the blocks were not marked corrupted in the datafile, but were detected and marked as corrupted while making the datafile copy
CORRUPTION_TYPE	VARCHAR2 (9)	Type of block corruption in the datafile: ■ ALL ZERO - Block header on disk contained only zeros. The block may be valid if it was never filled and if it is in an Oracle7 file. The buffer will be reformatted to the Oracle8 standard for an empty block. ■ FRACTURED - Block header looks reasonable, but the front and back of the block are different versions. ■ CHECKSUM - optional check value shows that the block is not self-consistent. It is impossible to determine exactly why the check value fails, but it probably fails because sectors in the middle of the block are from different versions. ■ CORRUPT - Block is wrongly identified or is not a data block (for example, the data block address is missing) ■ LOGICAL - Block is logically corrupt ■ NOLOGGING - Block does not have redo log entries (for example, NOLOGGING operations on primary database can introduce this type of corruption on a physical standby)

V\$CORRUPT_XID_LIST

V\$CORRUPT_XID_LIST displays all corrupted XIDs.

Column	Datatype	Description
CORRUPT_XID	VARCHAR2 (256)	Name of corrupt XID

V\$CPool_CC_INFO

V\$CPool_CC_INFO displays information about the pool-to-connection class mapping for the Database Resident Connection Pool per instance.

Column	Datatype	Description
POOL_NAME	VARCHAR2 (1024)	Name of the Database Resident Connection Pool
CCLASS_NAME	VARCHAR2 (1024)	Name of the connection class

V\$CPool_CC_STATS

V\$CPool_CC_STATS displays information about the connection class level statistics for the Database Resident Connection Pool per instance.

Column	Datatype	Description
CCLASS_NAME	VARCHAR2 (1024)	Name of the connection class

Column	Datatype	Description
NUM_REQUESTS	NUMBER	Number of session requests
NUM_HITS	NUMBER	Total number of times a session that matches with the request was found in the pool
NUM_MISSES	NUMBER	Total number of times an exact match to the request was not found in the pool and a new session had to be created
NUM_WAITS	NUMBER	Total number of times session requests had to wait before getting served
WAIT_TIME	NUMBER	Reserved for future use
CLIENT_REQ_TIMEOUTS	NUMBER	Reserved for future use
NUM_AUTHENTICATIONS	NUMBER	Total number of authentications of clients done by the pool

V\$CPool_CONN_INFO

V\$CPool_CONN_INFO displays connection information about each connection to the connection broker.

Column	Datatype	Description
CMON_ADDR	RAW (4 8)	Address of the connection broker
SESSION_ADDR	RAW (4 8)	Address of the session associated with the connection; NULL if the connection does not have an associated session
CONNECTION_ADDR	RAW (4 8)	Address of the connection
USERNAME	VARCHAR2 (1024)	Name of the user associated with the connection
PROXY_USER	VARCHAR2 (1024)	Name of the proxy user
CCLASS_NAME	VARCHAR2 (1024)	Connection class associated with the connection
PURITY	VARCHAR2 (1024)	Purity used to create the connection (can be SELF or NEW)
TAG	VARCHAR2 (1024)	Tag, if specified, at connection creation time
SERVICE	VARCHAR2 (64)	TNS service name for the connection
PROCESS_ID	VARCHAR2 (24)	Client process ID of the process which created the connection
PROGRAM	VARCHAR2 (48)	Program name of the client process which created the connection
MACHINE	VARCHAR2 (64)	Machine name of the client process which created the connection
TERMINAL	VARCHAR2 (30)	Terminal identifier of the client process which created the connection
CONNECTION_MODE	VARCHAR2 (1024)	Reserved for internal use
CONNECTION_STATUS	VARCHAR2 (10)	Status of the connection: ■ NONE ■ CONNECTING ■ ACTIVE ■ WAITING ■ IDLE ■ CLOSING
CLIENT_REGID ¹	NUMBER	Query cache registration ID sent by the client

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$CPool_STATS

V\$CPool_STATS displays information about the Database Resident Connection Pool statistics for an instance.

Column	Datatype	Description
POOL_NAME	VARCHAR2 (1024)	Name of the Database Resident Connection Pool
NUM_OPEN_SERVERS	NUMBER	Total number of busy and free servers in the pool (including the authentication servers)
NUM_BUSY_SERVERS	NUMBER	Total number of busy servers in the pool (not including the authentication servers)
NUM_AUTH_SERVERS	NUMBER	Number of authentication servers in the pool
NUM_REQUESTS	NUMBER	Number of client requests
NUM_HITS	NUMBER	Total number of times client requests found matching pooled servers in the pool
NUM_MISSES	NUMBER	Total number of times client requests could not find a matching pooled server in the pool
NUM_WAITS	NUMBER	Total number of client requests that had to wait due to non-availability of free pooled servers
WAIT_TIME	NUMBER	Reserved for future use
CLIENT_REQ_TIMEOUTS	NUMBER	Reserved for future use
NUM_AUTHENTICATIONS	NUMBER	Total number of authentications of clients done by the pool
NUM_PURGED	NUMBER	Total number of sessions purged by the pool
HISTORIC_MAX	NUMBER	Maximum size that the pool has ever reached

V\$CR_BLOCK_SERVER

V\$CR_BLOCK_SERVER displays statistics on the Global Cache Service processes (LMS) used in cache fusion.

Column	Datatype	Description
CR_REQUESTS	NUMBER	Number of CR blocks served due to remote CR block requests
CURRENT_REQUESTS	NUMBER	Number of current blocks served due to remote CR block requests CR_REQUESTS + CURRENT_REQUESTS = global cache CR clocks served (from V\$SYSTAT).
DATA_REQUESTS	NUMBER	Number of current or CR requests for data blocks
UNDO_REQUESTS	NUMBER	Number of CR requests for undo blocks
TX_REQUESTS	NUMBER	Number of CR requests for undo segment header blocks
OTHER_REQUESTS	NUMBER	Number of CR requests for other types of blocks DATA_REQUESTS + UNDO_REQUESTS + TX_REQUESTS + OTHER_REQUESTS = total number of requests handled by the LMS processes
CURRENT_RESULTS	NUMBER	Number of requests for which no changes were rolled out of the block returned to the requesting instance
PRIVATE_RESULTS	NUMBER	Number of requests for which changes were rolled out of the block returned to the requesting instance, and only the requesting transaction can use the resulting CR block
ZERO_RESULTS	NUMBER	Number of requests for which changes were rolled out of the block returned to the requesting instance. Only zero-XID transactions can use the block.
DISK_READ_RESULTS	NUMBER	Number of requests for which the requesting instance had to read the requested block from disk
FAIL_RESULTS	NUMBER	Number of requests that failed; the requesting transaction must reissue the request
STALE	NUMBER	Number of requests for which the disk read of the requested block was stale

Column	Datatype	Description
FAIRNESS_DOWN_CONVERTS	NUMBER	Number of times an instance receiving a request has down-converted an X lock on a block because it was not modifying the block
FAIRNESS_CLEARS	NUMBER	Number of times the "fairness counter" was cleared. This counter tracks the number of times a block was modified after it was served.
FREE_GC_ELEMENTS	NUMBER	Number of times a request was received from another instance and the X lock had no buffers
FLUSHES	NUMBER	Number of times the log has been flushed by an LMS process
FLUSHES_QUEUED	NUMBER	Number of flushes queued by an LMS process
FLUSH_QUEUE_FULL	NUMBER	Number of times the flush queue was full
FLUSH_MAX_TIME	NUMBER	Maximum time for flush
LIGHT_WORKS	NUMBER	Number of times the light-work rule was evoked. This rule prevents the LMS processes from going to disk while responding to CR requests for data, undo, or undo segment header blocks. This rule can prevent the LMS process from completing its response to the CR request.
ERRORS	NUMBER	Number of times an error was signalled by an LMS process

See Also: The *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Installation Guide* for your operating system for more information on these processes and on cache fusion

Note: This view contains internal diagnostic information for use by Oracle Support Services. It is subject to change without notice.

V\$CURRENT_BLOCK_SERVER

V\$CURRENT_BLOCK_SERVER displays statistics on the Global Cache Service processes (IMS) used in cache fusion.

Column	Datatype	Description
PIN1	NUMBER	Pins taking less than 1 millisecond
PIN10	NUMBER	Pins taking 1 to 10 milliseconds
PIN100	NUMBER	Pins taking 10 to 100 milliseconds
PIN1000	NUMBER	Pins taking 100 to 1000 milliseconds
PIN10000	NUMBER	Pins taking 1000 to 10000 milliseconds
FLUSH1	NUMBER	Flushes taking less than 1 millisecond
FLUSH10	NUMBER	Flushes taking 1 to 10 milliseconds
FLUSH100	NUMBER	Flushes taking 10 to 100 milliseconds
FLUSH1000	NUMBER	Flushes taking 100 to 1000 milliseconds
FLUSH10000	NUMBER	Flushes taking 1000 to 10000 milliseconds
WRITE1	NUMBER	Writes taking less than 1 millisecond
WRITE10	NUMBER	Writes taking 1 to 10 milliseconds
WRITE100	NUMBER	Writes taking 10 to 100 milliseconds
WRITE1000	NUMBER	Writes taking 100 to 1000 milliseconds
WRITE10000	NUMBER	Writes taking 1000 to 10000 milliseconds
CLEANDC	NUMBER	Reserved for internal use
RCVDC	NUMBER	Number of lock down-converts to S (shared) caused by instance recovery

Column	Datatype	Description
QUEUEDC	NUMBER	Number of queued lock down-converts to NULL
EVICTDC	NUMBER	Number of lock down-converts to NULL caused by an SGA shrink
WRITEDC	NUMBER	Number of dirty blocks in read-mostly objects which were written and the X (exclusive) lock down-converted to S (shared) locks

V\$DATABASE

V\$DATABASE displays information about the database from the control file.

Column	Datatype	Description
DBID	NUMBER	Database identifier calculated when the database is created and stored in all file headers
NAME	VARCHAR2 (9)	Name of the database
CREATED	DATE	Creation date of the database. If the control file was re-created using the CREATE CONTROLFILE statement, then this column displays the date that the control file was re-created.
RESETLOGS_CHANGE#	NUMBER	System change number (SCN) at open resetlogs
RESETLOGS_TIME	DATE	Timestamp of open resetlogs
PRIOR_RESETLOGS_CHANGE#	NUMBER	SCN at prior resetlogs
PRIOR_RESETLOGS_TIME	DATE	Timestamp of prior resetlogs
LOG_MODE	VARCHAR2 (12)	Archive log mode: ■ NOARCHIVELOG ■ ARCHIVELOG ■ MANUAL
CHECKPOINT_CHANGE#	NUMBER	Last SCN checkpointed
ARCHIVE_CHANGE#	NUMBER	Database force archiving SCN. Any redo log with a start SCN below this will be forced to archive out.
CONTROLFILE_TYPE	VARCHAR2 (7)	Type of control file: ■ STANDBY - Indicates that the database is in standby mode ■ CLONE - Indicates a clone database ■ BACKUP CREATED - Indicates the database is being recovered using a backup or created control file ■ CURRENT - database is available for general use
CONTROLFILE_CREATED	DATE	Creation date of the control file
CONTROLFILE_SEQUENCE#	NUMBER	Control file sequence number incremented by control file transactions
CONTROLFILE_CHANGE#	NUMBER	Last SCN in backup control file; null if the control file is not a backup
CONTROLFILE_TIME	DATE	Last timestamp in backup control file; null if the control file is not a backup
OPEN_RESETLOGS	VARCHAR2 (11)	(NOT ALLOWED ALLOWED REQUIRED) Indicates whether the next database open allows or requires the resetlogs option
VERSION_TIME	DATE	Version time
OPEN_MODE	VARCHAR2 (20)	Open mode information: ■ MOUNTED ■ READ WRITE ■ READ ONLY ■ READ ONLY WITH APPLY - A physical standby database is open in real-time query mode

Column	Datatype	Description
PROTECTION_MODE	VARCHAR2 (20)	Protection mode currently in effect for the database: ■ MAXIMUM PROTECTION - Database is running in maximized protection mode ■ MAXIMUM AVAILABILITY - Database is running in maximized availability mode ■ RESYNCHRONIZATION - Database is running in resynchronization mode ■ MAXIMUM PERFORMANCE - Database is running in maximized protection mode ■ UNPROTECTED - Database is unprotected (this normally occurs when the primary database is mounted and not open)
PROTECTION_LEVEL	VARCHAR2 (20)	Aggregated protection mode currently in effect for the database: ■ MAXIMUM PROTECTION - Database is running in maximized protection mode ■ MAXIMUM AVAILABILITY - Database is running in maximized availability mode ■ RESYNCHRONIZATION - Database is running in resynchronization mode ■ MAXIMUM PERFORMANCE - Database is running in maximized protection mode ■ UNPROTECTED - Database is unprotected (this normally occurs when the primary database is mounted and not open) Note: This column is an aggregation of the PROTECTION_MODE of all standby archive log destinations.
REMOTE_ARCHIVE	VARCHAR2 (8)	Value of the REMOTE_ARCHIVE_ENABLE initialization parameter
ACTIVATION#	NUMBER	Number assigned to the database instantiation
SWITCHOVER#	NUMBER	Number assigned to the database switchover
DATABASE_ROLE	VARCHAR2 (16)	Current role of the database: ■ SNAPSHOT STANDBY ■ LOGICAL STANDBY ■ PHYSICAL STANDBY ■ PRIMARY
ARCHIVELOG_CHANGE#	NUMBER	Highest NEXT_CHANGE# (from the V\$ARCHIVED_LOG view) for an archive log
ARCHIVELOG_COMPRESSION	VARCHAR2 (8)	Status of the archive log compression (ENABLED) or (DISABLED)

Column	Datatype	Description
SWITCHOVER_STATUS	VARCHAR2 (20)	Indicates whether switchover is allowed: ■ NOT ALLOWED - On a primary database, this status indicates that there are no valid and enabled standby databases. On a standby database, this status indicates that a switchover request has not been received from the primary database. ■ SESSIONS ACTIVE - The database has active sessions. On a physical standby database, the WITH SESSION SHUTDOWN SQL clause must be specified to perform a role transition while in this state. On a logical standby database, a role transition can be performed while in this state, but the role transition will not complete until all current transactions have committed. ■ SWITCHOVER PENDING - On a physical standby database, this status indicates that a switchover request has been received from the primary database and is being processed. A physical standby database cannot switch to the primary role while in this transient state. ■ SWITCHOVER LATENT - On a physical standby database, this status indicates that a switchover request was pending, but the original primary database has been switched back to the primary role. ■ TO PRIMARY - The database is ready to switch to the primary role. ■ TO STANDBY - The database is ready to switch to either the physical or logical standby role. ■ TO LOGICAL STANDBY - The database has received a data dictionary from a logical standby database and is ready to switch to the logical standby role. ■ RECOVERY NEEDED - On a physical standby database, this status indicates that additional redo must be applied before the database can switch to the primary role. ■ PREPARING SWITCHOVER - On a primary database, this status indicates that a data dictionary is being received from a logical standby database in preparation for switching to the logical standby role. On a logical standby database, this status indicates that the data dictionary has been sent to the primary database and other standby databases. ■ PREPARING DICTIONARY - On a logical standby database, this status indicates that the data dictionary is being sent to the primary database and other standby databases in preparation for switching to the primary role. ■ FAILED DESTINATION - On a primary database, this status indicates that one or more standby destinations are in an error state. ■ RESOLVABLE GAP - On a primary database, this status indicates that one or more standby databases have a redo gap that can be automatically resolved by fetching the missing redo from the primary database or from another standby database. ■ UNRESOLVABLE GAP - On a primary database, this status indicates that one or more standby databases have a redo gap that cannot be automatically resolved by fetching the missing redo from the primary database or from another standby database. ■ LOG SWITCH GAP - On a primary database, this status indicates that one or more standby databases are missing redo due to a recent log switch.
DATAGUARD_BROKER	VARCHAR2 (8)	Data Guard broker information: ■ ENABLED - Database is part of a broker configuration and broker management of the database is enabled ■ DISABLED - Database is part of a broker configuration and broker management of the database is disabled. This value is displayed if the user disabled broker management of the database or configuration, or if broker management was disabled due to a role change (for example, the old primary was disabled after a failover operation). the database is not part of a broker configuration. the broker is not running on the database.

Column	Datatype	Description
GUARD_STATUS	VARCHAR2 (7)	Protects data from being changed: ■ ALL - Indicates all users other than SYS are prevented from making changes to any data in the database. ■ STANDBY - Indicates all users other than SYS are prevented from making changes to any database object being maintained by logical standby. ■ NONE - Indicates normal security for all data in the database.
SUPPLEMENTAL_LOG_DATA_MIN	VARCHAR2 (8)	Ensures that LogMiner (and any products building on LogMiner technology) will have sufficient information to support chained rows and various storage arrangements such as cluster tables: ■ NO - None of the database-wide supplemental logging directives are enabled ■ IMPLICIT - Minimal supplemental logging is enabled because all or a combination of primary key, unique key, and foreign key supplemental logging is enabled ■ YES - Minimal supplemental logging is enabled through an ALTER DATABASE ADD SUPPLEMENTAL LOG DATA statement See Also: <i>Oracle Database SQL Language Reference</i> for additional information about the ALTER DATABASE ADD SUPPLEMENTAL LOG DATA statement
SUPPLEMENTAL_LOG_DATA_PK	VARCHAR2 (3)	For all tables with a primary key, indicates whether all columns of the primary key are placed into the redo log whenever an update is performed (YES) or not (NO) See Also: <i>Oracle Database SQL Language Reference</i> for more information about the ALTER DATABASE ADD SUPPLEMENTAL LOG supplemental_id_key_clause statement
SUPPLEMENTAL_LOG_DATA_UI	VARCHAR2 (3)	For all tables with a unique key, indicates whether all other columns belonging to the unique key are placed into the redo log if any of the unique key columns are modified (YES) or not (NO) See Also: <i>Oracle Database SQL Language Reference</i> for more information about the ALTER DATABASE ADD SUPPLEMENTAL LOG supplemental_id_key_clause statement
FORCE_LOGGING	VARCHAR2 (3)	Indicates whether the database is under force logging mode (YES) or not (NO)
PLATFORM_ID	NUMBER	Platform identification number of the database
PLATFORM_NAME	VARCHAR2 (101)	Platform name of the database
RECOVERY_TARGET_INCARNATION#	NUMBER	Incarnation number where all datafiles are recovered by the RECOVER DATABASE command
LAST_OPEN_INCARNATION#	NUMBER	Record number of the incarnation in V\$DATABASE_INCARNATION that was last opened successfully
CURRENT_SCN	NUMBER	Current SCN; null if the database is not currently open. For a standby database, the checkpoint SCN of the mounted physical standby database during media recovery and is always less than the last applied SCN tracked in V\$RECOVERY_PROGRESS.
FLASHBACK_ON	VARCHAR2 (18)	Possible values are as follows: ■ YES - Flashback is on ■ NO - Flashback is off ■ RESTORE POINT ONLY - Flashback is on but one can only flashback to guaranteed restore points
SUPPLEMENTAL_LOG_DATA_FK	VARCHAR2 (3)	For all tables with a foreign key, indicates whether all other columns belonging to the foreign key are placed into the redo log if any foreign key columns are modified (YES) or not (NO) See Also: <i>Oracle Database SQL Language Reference</i> for more information about the ALTER DATABASE ADD SUPPLEMENTAL LOG supplemental_id_key_clause statement

Column	Datatype	Description
SUPPLEMENTAL_LOG_DATA_ALL	VARCHAR2 (3)	For all columns, indicates whether all the fixed-length maximum size columns of that row are placed into the redo log (YES) or not (NO) See Also: <i>Oracle Database SQL Language Reference</i> for more information about the ALTER DATABASE ADD SUPPLEMENTAL LOG supplemental_id_key_clause statement
DB_UNIQUE_NAME	VARCHAR2 (30)	Unique database name
STANDBY_BECAME_PRIMARY_SCN	NUMBER	SCN at which a physical standby database became a primary database. This SCN is useful for converting a failed primary database into a physical standby database after a forced failover. See Also: <i>Oracle Data Guard Concepts and Administration</i>
FS_FAILOVER_STATUS	VARCHAR2 (22)	Fast-start failover status: ■ DISABLED ■ BYSTANDER ■ SYNCHRONIZED ■ UNSYNCHRONIZED ■ SUSPENDED ■ STALLED ■ LOADING DICTIONARY ■ PRIMARY UNOBSERVED ■ REINSTATE REQUIRED ■ REINSTATE FAILED ■ TARGET OVER LAG LIMIT ■ TARGET UNDER LAG LIMIT See Also: <i>Oracle Data Guard Broker</i> for detailed descriptions of these values Note: If the value of this column is DISABLED, then the values for the FS_FAILOVER_CURRENT_TARGET, FS_FAILOVER_THRESHOLD, FS_FAILOVER_OBSERVER_PRESENT, and FS_FAILOVER_OBSERVER_HOST columns in this table are not meaningful.
FS_FAILOVER_CURRENT_TARGET	VARCHAR2 (30)	DB_UNIQUE_NAME of the standby that is the current FSFO target standby for the Data Guard configuration
FS_FAILOVER_THRESHOLD	NUMBER	Time (in seconds) that the observer will attempt to reconnect with a disconnected primary before attempting FSFO with the target standby
FS_FAILOVER_OBSERVER_PRESENT	VARCHAR2 (7)	Indicates whether the observer is currently connected to the local database (YES) or not (NO) Note: This column is consistent throughout an Oracle RAC environment; that is, if the observer is connected to any instance, then all instances will show a value of YES.
FS_FAILOVER_OBSERVER_HOST	VARCHAR2 (512)	Machine name that is currently hosting the observer process
CONTROLFILE_CONVERTED	VARCHAR2 (3)	Indicates whether the control file was implicitly converted from its original type during restore (YES) or not (NO) This column will be set to YES when RMAN restores a standby control file from a backup of the control file taken at the primary database or restores a backup control file from a backup taken at the physical standby database. This column will change to NO when the file names are fixed using information in the recovery catalog schema.

Column	Datatype	Description
PRIMARY_DB_UNIQUE_NAME	VARCHAR2 (30)	For any Standby database (Physical, Logical, or Snapshot), this column will contain the DB_UNIQUE_NAME of the Primary database that this Standby last received current redo from. If this standby has not received any current redo since last being started, then this column will be null. For a Primary database that had previously been a Standby, this column will contain the DB_UNIQUE_NAME of the last Primary that this database received current redo from while acting as a Standby. For a Primary database that has never been a Standby, this column will be null.
SUPPLEMENTAL_LOG_DATA_PL	VARCHAR2 (3)	Indicates whether additional information is logged in the redo log (YES) or not (NO) during invocation of procedures in Oracle-supplied packages for which procedural replication is supported. See Also: <i>Oracle Data Guard Concepts and Administration</i> for a list of Oracle-supplied packages that are procedurally replicated to a logical standby database
MIN_REQUIRED_CAPTURE_CHANGE#	NUMBER	Minimum REQUIRED_CHECKPOINT_SCN for all local capture processes on the database

V\$DATABASE_BLOCK_CORRUPTION

V\$DATABASE_BLOCK_CORRUPTION displays information about database blocks that were corrupted after the last backup.

Column	Datatype	Description
FILE#	NUMBER	Absolute file number of the datafile that contains the corrupt blocks
BLOCK#	NUMBER	Block number of the first corrupt block in the range of corrupted blocks
BLOCKS	NUMBER	Number of corrupted blocks found starting with BLOCK#
CORRUPTION_CHANGE#	NUMBER	Change number at which the logical corruption was detected. Set to 0 to indicate media corruption.
CORRUPTION_TYPE	VARCHAR2 (9)	Type of block corruption in the datafile: ■ ALL ZERO - Block header on disk contained only zeros. The block may be valid if it was never filled and if it is in an Oracle7 file. The buffer will be reformatted to the Oracle8 standard for an empty block. ■ FRACTURED - Block header looks reasonable, but the front and back of the block are different versions. ■ CHECKSUM - optional check value shows that the block is not self-consistent. It is impossible to determine exactly why the check value fails, but it probably fails because sectors in the middle of the block are from different versions. ■ CORRUPT - Block is wrongly identified or is not a data block (for example, the data block address is missing) ■ LOGICAL - Block is logically corrupt ■ NOLOGGING - Block does not have redo log entries (for example, NOLOGGING operations on primary database can introduce this type of corruption on a physical standby)

V\$DATABASE_INCARNATION

V\$DATABASE_INCARNATION displays information about all database incarnations. Oracle creates a new incarnation whenever a database is opened with the RESETLOGS option. Records about the current and immediately previous incarnation are also contained in the V\$DATABASE view.

Column	Datatype	Description
INCARNATION#	NUMBER	Record ID for the branch record in the control file
RESETLOGS_CHANGE#	NUMBER	Resetlogs system change number (SCN) for the incarnation of the current row
RESETLOGS_TIME	DATE	Resetlogs timestamp for the incarnation of the current row
PRIOR_RESETLOGS_CHANGE#	NUMBER	Resetlogs SCN for the previous incarnation
PRIOR_RESETLOGS_TIME	DATE	Resetlogs timestamp for the previous incarnation
STATUS	VARCHAR2 (7)	Incarnation status: ■ ORPHAN - Orphan incarnation ■ CURRENT - Current incarnation of the database ■ PARENT - Parent of the current incarnation
RESETLOGS_ID	NUMBER	Branch ID for the incarnation of the current row (used by user-managed recovery/RMAN restore to get unique names for archived logs across incarnations)
PRIOR_INCARNATION#	NUMBER	Parent incarnation record ID if nonzero
FLASHBACK_DATABASE_ALLOWED	VARCHAR2 (26)	Indicate whether or not Flashback Database can be performed into SCNs or timestamps in the incarnation. A value of YES means that you can flashback to some point in that incarnation. A value of NO indicates that you cannot flashback into the incarnation.

V\$DATAFILE

V\$DATAFILE displays datafile information from the control file.

See Also: ["V\\$DATAFILE_HEADER"](#) on page 7-77, which displays information from datafile headers

Column	Datatype	Description
FILE#	NUMBER	File identification number
CREATION_CHANGE#	NUMBER	Change number at which the datafile was created
CREATION_TIME	DATE	Timestamp of the datafile creation
TS#	NUMBER	Tablespace number
RFILE#	NUMBER	Tablespace relative datafile number
STATUS	VARCHAR2 (7)	Type of file (system or user) and its status. Values: OFFLINE, ONLINE, SYSTEM, RECOVER, SYSOFF (an offline file from the SYSTEM tablespace)
ENABLED	VARCHAR2 (10)	Describes how accessible the file is from SQL: ■ DISABLED - No SQL access allowed ■ READ ONLY - No SQL updates allowed ■ READ WRITE - Full access allowed ■ UNKNOWN - should not occur unless the control file is corrupted
CHECKPOINT_CHANGE#	NUMBER	SCN at last checkpoint
CHECKPOINT_TIME	DATE	Timestamp of the checkpoint#
UNRECOVERABLE_CHANGE#	NUMBER	Last unrecoverable change number made to this datafile. If the database is in ARCHIVELOG mode, then this column is updated when an unrecoverable operation completes. If the database is not in ARCHIVELOG mode, this column does not get updated.
UNRECOVERABLE_TIME	DATE	Timestamp of the last unrecoverable change. This column is updated only if the database is in ARCHIVELOG mode.

Column	Datatype	Description
LAST_CHANGE#	NUMBER	Last change number made to this datafile (null if the datafile is being changed)
LAST_TIME	DATE	Timestamp of the last change
OFFLINE_CHANGE#	NUMBER	Offline change number of the last offline range. This column is updated only when the datafile is brought online.
ONLINE_CHANGE#	NUMBER	Online change number of the last offline range
ONLINE_TIME	DATE	Online timestamp of the last offline range
BYTES	NUMBER	Current datafile size (in bytes); 0 if inaccessible
BLOCKS	NUMBER	Current datafile size (in blocks); 0 if inaccessible
CREATE_BYTES	NUMBER	Size when created (in bytes)
BLOCK_SIZE	NUMBER	Block size of the datafile
NAME	VARCHAR2 (513)	Name of the datafile
PLUGGED_IN	NUMBER	Describes whether the tablespace is plugged in. The value is 1 if the tablespace is plugged in and has not been made read/write, 0 if not.
BLOCK1_OFFSET	NUMBER	Offset from the beginning of the file to where the Oracle generic information begins. The exact length of the file can be computed as follows: BYTES + BLOCK1_OFFSET.
AUX_NAME	VARCHAR2 (513)	Auxiliary name that has been set for this file via CONFIGURE AUXNAME
FIRST_NONLOGGED_SCN	NUMBER	First nonlogged SCN
FIRST_NONLOGGED_TIME	DATE	First nonlogged time
FOREIGN_DBID	NUMBER	Foreign DBID from which this data file came from. The value is 0 if this file is not a foreign database file.
FOREIGN_CREATION_CHANGE#	NUMBER	Creation SCN of a foreign datafile. The value is 0 if this file is not a foreign database file.
FOREIGN_CREATION_TIME	DATE	Creation time of a foreign datafile. The value is 0 if this file is not a foreign database file.
PLUGGED_READONLY	VARCHAR2 (3)	YES if this is a transported read-only foreign file; otherwise NO.
PLUGIN_CHANGE#	NUMBER	SCN at which the foreign datafile was transported into the database. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_CHANGE#	NUMBER	The SCN of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_TIME	DATE	The time of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.

V\$DATAFILE_COPY

V\$DATAFILE_COPY displays datafile copy information from the control file.

Column	Datatype	Description
RECID	NUMBER	Datafile copy record ID
STAMP	NUMBER	Datafile copy record stamp
NAME	VARCHAR2 (513)	Filename of the datafile copy. The maximum length of the name is OS dependent.
TAG	VARCHAR2 (32)	Datafile copy tag
FILE#	NUMBER	Absolute datafile number
RFILE#	NUMBER	Tablespace relative datafile number
CREATION_CHANGE#	NUMBER	Datafile creation change#

Column	Datatype	Description
CREATION_TIME	DATE	Datafile creation timestamp
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the datafile when the copy was made
RESETLOGS_TIME	DATE	Resetlogs timestamp of the datafile when the copy was made
INCREMENTAL_LEVEL	NUMBER	The incremental level
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change number of the datafile when the copy was made
CHECKPOINT_TIME	DATE	Checkpoint timestamp of the datafile when the copy was made
ABSOLUTE_FUZZY_CHANGE#	NUMBER	Highest change seen when the datafile was copied
RECOVERY_FUZZY_CHANGE#	NUMBER	Highest change written to the file by media recovery
RECOVERY_FUZZY_TIME	DATE	Timestamp of the highest change written to the file by media recovery
ONLINE_FUZZY	VARCHAR2 (3)	(YES NO) If set to YES, this is a copy taken using an operating system utility after a crash or offline immediate (or an invalid copy taken while datafile was online and the database open). Recovery will need to apply all redo up to the next crash recovery marker to make the file consistent.
BACKUP_FUZZY	VARCHAR2 (3)	(YES NO) If set to YES, this is a copy taken using the BEGIN BACKUP/END BACKUP technique. Recovery will need to apply all redo up to the end backup marker to make this copy consistent.
MARKED_CORRUPT	NUMBER	Number of blocks marked corrupt by this copy operation. That is, blocks that were not marked corrupted in the source datafile, but were detected and marked as corrupted during the copy operation.
MEDIA_CORRUPT	NUMBER	Total number of media corrupt blocks. For example, blocks with checksum errors are marked media corrupt.
LOGICALLY_CORRUPT	NUMBER	Total number of logically corrupt blocks. For example, applying redo for unrecoverable operations will mark affected blocks logically corrupt.
BLOCKS	NUMBER	Size of the datafile copy in blocks (also the size of the datafile when the copy was made)
BLOCK_SIZE	NUMBER	Block size of the datafile
OLDEST_OFFLINE_RANGE	NUMBER	RECID of the oldest offline range record in this control file copy; 0 for datafile copies
DELETED	VARCHAR2 (3)	(YES NO) If set to YES the datafile copy has been deleted or overwritten
STATUS	VARCHAR2 (1)	Identifies the status of this datafile copy. Possible values are: A - Available D - Deleted U - Unavailable X - Expired
COMPLETION_TIME	DATE	Time when the copy was completed
CONTROLFILE_TYPE	VARCHAR2 (1)	B indicates normal copies S indicates standby copies
KEEP	VARCHAR2 (3)	(YES/NO) Indicates whether or not this backup set has a retention policy that is different than the value for the configure retention policy
KEEP_UNTIL	DATE	If KEEP_UNTIL is specified, this is the date after which the backup becomes obsolete. If this column is null, then the backup never expires.
KEEP_OPTIONS	VARCHAR2 (10)	Lists additional retention options for this backup set. Possible values are: LOGS - The logs need to recover this backup are kept NOLOGS - The logs needed to recover this backup will not be kept
SCANNED	VARCHAR2 (3)	Indicates whether RMAN scanned the file (YES) or not (NO)
IS_RECOVERY_DEST_FILE	VARCHAR2 (3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
RMAN_STATUS_RECID	NUMBER	Owning V\$RMAN_STATUS record ID

Column	Datatype	Description
RMAN_STATUS_STAMP	NUMBER	Owning V\$RMAN_STATUS record stamp
CONVERTED_FILE	VARCHAR2 (3)	(YES/NO) Indicates whether or not the datafile copy was created using the RMAN CONVERT command
SAME_ENDIAN	VARCHAR2 (3)	If the value of the CONVERTED_FILE column is YES, then this column indicates whether the datafile copy has the same endianness as the source datafile (YES) or not (NO); otherwise NULL
FOREIGN_DBID	NUMBER	Foreign DBID from which this data file came from. The value is 0 if this file is not a foreign database file.
PLUGGED_READONLY	VARCHAR2 (3)	YES if this is a transported read-only foreign file; otherwise NO.
PLUGIN_CHANGE#	NUMBER	SCN at which the foreign datafile was transported into the database. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_CHANGE#	NUMBER	The SCN of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_TIME	DATE	The time of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
BACKED_BY_VSS	VARCHAR2 (3)	Whether or not the file has been backed up by Volume Shadow Copy Service (VSS). This column is reserved for internal use.

V\$DATAFILE_HEADER

V\$DATAFILE_HEADER displays datafile information from the datafile headers.

Column	Datatype	Description
FILE#	NUMBER	Datafile number (from control file)
STATUS	VARCHAR2 (7)	ONLINE OFFLINE (from control file)
ERROR	VARCHAR2 (18)	NULL if the datafile header read and validation were successful. If the read failed then the rest of the columns are NULL. If the validation failed then the rest of columns may display invalid data. If there is an error then usually the datafile must be restored from a backup before it can be recovered or used.
FORMAT	NUMBER	Indicates the format for the header block. The possible values are 6, 7, 8, 10 or 0. 6 - indicates Oracle Version 6 7 - indicates Oracle Version 7 8 - indicates Oracle Version 8 10 - indicates Oracle Version 10 0 - indicates the format could not be determined (for example, the header could not be read)
RECOVER	VARCHAR2 (3)	File needs media recovery (YES NO)
FUZZY	VARCHAR2 (3)	File is fuzzy (YES NO)
CREATION_CHANGE#	NUMBER	Datafile creation change#
CREATION_TIME	DATE	Datafile creation timestamp
TABLESPACE_NAME	VARCHAR2 (30)	Tablespace name
TS#	NUMBER	Tablespace number
RFILE#	NUMBER	Tablespace relative datafile number
RESETLOGS_CHANGE#	NUMBER	Resetlogs change#
RESETLOGS_TIME	DATE	Resetlogs timestamp
CHECKPOINT_CHANGE#	NUMBER	Datafile checkpoint change#

Column	Datatype	Description
CHECKPOINT_TIME	DATE	Datafile checkpoint timestamp
CHECKPOINT_COUNT	NUMBER	Datafile checkpoint count
BYTES	NUMBER	Current datafile size in bytes
BLOCKS	NUMBER	Current datafile size in blocks
NAME	VARCHAR2 (513)	Datafile name
SPACE_HEADER	VARCHAR2 (40)	The amount of space currently being used and the amount that is free, as identified in the space header
LAST_DEALLOC_SCN	VARCHAR2 (16)	Last deallocated SCN
UNDO_OPT_CURRENT_CHANGE#	VARCHAR2 (40)	For internal use only

V\$DATAGUARD_CONFIG

V\$DATAGUARD_CONFIG displays the unique database names defined with the DB_UNIQUE_NAME and LOG_ARCHIVE_CONFIG initialization parameters, providing a view of the Data Guard environment from any database in the configuration.

The first row of the view lists the unique database name of the current database that was specified with the DB_UNIQUE_NAME initialization parameter. Additional rows reflect the unique database names of the other databases in the configuration that were specified with the DG_CONFIG keyword of the LOG_ARCHIVE_CONFIG initialization parameter.

Column	Datatype	Description
DB_UNIQUE_NAME	VARCHAR2 (30)	Unique database name

V\$DATAGUARD_STATS

V\$DATAGUARD_STATS displays information about Data Guard metrics when queried on a standby database. No rows are returned when queried on a primary database.

Column	Datatype	Description
NAME	VARCHAR2 (32)	Name of the metric: - APPLY FINISH TIME - An estimate of the time needed to apply all received, but unapplied redo from the primary database. If there are one or more redo gaps on the standby database, an estimate of the time needed to apply all received, but unapplied redo up to the end of the last archived redo log before the beginning of the earliest redo gap. - APPLY LAG - Apply lag is a measure of the degree to which the data in a standby database lags behind the data in the primary database, due to delays in propagating and applying redo to the standby database. - TRANSPORT LAG - Transport lag is a measure of the degree to which the transport of redo to the standby database lags behind the generation of redo on the primary database. If there are one or more redo gaps on the standby database, the transport lag is calculated as if no redo has been received after the beginning of the earliest redo gap. - ESTIMATED STARTUP TIME - An estimate of the time needed to start and open the database.
VALUE	VARCHAR2 (64)	Value of the metric
UNIT	VARCHAR2 (30)	Unit of measurement
TIME_COMPUTED	VARCHAR2 (30)	Local time at the standby database when the metric was computed

Column	Datatype	Description
DATUM_TIME	VARCHAR2 (30)	Local time at the standby database when the datum used to compute the metric was received The APPLY LAG and TRANSPORT LAG metrics are computed based on data that is periodically received from the primary database. An unchanging value in this column across multiple queries indicates that the standby database is not receiving data from the primary database.

V\$DATAGUARD_STATUS

V\$DATAGUARD_STATUS displays messages recently written to the alert log or server process trace files that concern physical standby databases or redo transport services for all standby database types.

Column	Datatype	Description
FACILITY	VARCHAR2 (24)	Facility that encountered the event: - Crash Recovery - Log Transport Services - Log Apply Services - Role Management Services - Remote File Server - Fetch Archive Log - Data Guard - Network Services
SEVERITY	VARCHAR2 (13)	Severity of the event: - Informational - Informational message - Warning - Warning message - Error - Indicates the process has failed - Fatal - Control - An expected change in state such as the start or completion of an archival, log recovery, or switchover operation
DEST_ID	NUMBER	Destination ID number to which the event pertains. If the event does not pertain to a particular destination, then the value is 0.
MESSAGE_NUM	NUMBER	A chronologically increasing number giving each event a unique number
ERROR_CODE	NUMBER	Error ID pertaining to the event
CALLOUT	VARCHAR2 (3)	Reserved for future use
TIMESTAMP	DATE	Message date
MESSAGE	VARCHAR2 (256)	A text message describing the event

V\$DB_CACHE_ADVICE

V\$DB_CACHE_ADVICE contains rows that predict the number of physical reads for the cache size corresponding to each row. The rows also compute a "physical read factor," which is the ratio of the number of estimated reads to the number of reads actually performed by the real buffer cache during the measurement interval.

See Also: ["DB_CACHE_ADVICE"](#) on page 1-46

Column	Datatype	Description
ID	NUMBER	Buffer pool identifier (ranges from 1 to 8)
NAME	VARCHAR2 (20)	Buffer pool name

Column	Datatype	Description
BLOCK_SIZE	NUMBER	Block size in bytes for buffers in this pool. Possible values: the standard block size, the power of 2 non-standard block sizes, 2048, 4096, 8192, 16384, 32768.
ADVICE_STATUS	VARCHAR2 (3)	Status of the advisory. ON indicates it is currently running; OFF indicates it is disabled (in this case the estimates are historical and calculated when last enabled).
SIZE_FOR_ESTIMATE	NUMBER	Cache size for prediction (in megabytes)
SIZE_FACTOR	NUMBER	Size factor with respect to the current cache size
BUFFERS_FOR_ESTIMATE	NUMBER	Cache size for prediction (in terms of buffers)
ESTD_PHYSICAL_READ_FACTOR	NUMBER	Physical read factor for this cache size, which is the ratio of the number of estimated physical reads to the number of reads in the real cache. If there are no physical reads in the real cache, the value of this column is null.
ESTD_PHYSICAL_READS	NUMBER	Estimated number of physical reads for this cache size
ESTD_PHYSICAL_READ_TIME	NUMBER	Estimated disk read time
ESTD_PCT_OF_DB_TIME_FOR_READS	NUMBER	Estimated disk time as a percentage of the total time
ESTD_CLUSTER_READS	NUMBER	Estimated total number of blocks foreground processes read from the global cache (Real Application Clusters only)
ESTD_CLUSTER_READ_TIME	NUMBER	Estimated total amount of time, in seconds, foreground processes read from global cache (Real Application Clusters only)

V\$DB_OBJECT_CACHE

V\$DB_OBJECT_CACHE displays database objects that are cached in the library cache. Objects include tables, indexes, clusters, synonym definitions, PL/SQL procedures and packages, and triggers.

Column	Datatype	Description
OWNER	VARCHAR2 (64)	Owner of the object
NAME	VARCHAR2 (1000)	Name of the object
DB_LINK	VARCHAR2 (64)	Database link name, if any
NAMESPACE	VARCHAR2 (64)	Library cache namespace of the object: TABLE/PROCEDURE, BODY, TRIGGER, INDEX, CLUSTER, OBJECT
TYPE	VARCHAR2 (64)	Type of the object: INDEX, TABLE, CLUSTER, VIEW, SET, SYNONYM, SEQUENCE, PROCEDURE, FUNCTION, PACKAGE, PACKAGE BODY, TRIGGER, CLASS, OBJECT, USER, DBLINK
SHARABLE_MEM	NUMBER	Amount of sharable memory in the shared pool consumed by the object
LOADS	NUMBER	Number of times the object has been loaded. This count also increases when an object has been invalidated.
EXECUTIONS	NUMBER	Not used See Also: "V\$SQLAREA" on page 9-52 to see actual execution counts
LOCKS	NUMBER	Number of users currently locking this object
PINS	NUMBER	Number of users currently pinning this object
KEPT	VARCHAR2 (3)	(YES NO) Depends on whether this object has been "kept" (permanently pinned in memory) with the PL/SQL procedure DBMS_SHARED_POOL.KEEP
CHILD_LATCH	NUMBER	Child latch number that is protecting the object. This column is obsolete and maintained for backward compatibility.
INVALIDATIONS	NUMBER	Total number of times objects in the namespace were marked invalid because a dependent object was modified

Column	Datatype	Description
HASH_VALUE	NUMBER	Hash value of the object
LOCK_MODE	VARCHAR2 (9)	Current lock mode of the object
PIN_MODE	VARCHAR2 (9)	Current pin mode of the object
STATUS	VARCHAR2 (19)	Status of the object
TIMESTAMP	VARCHAR2 (19)	Timestamp for the specification of the objec
PREVIOUS_TIMESTAMP	VARCHAR2 (19)	Previous timestamp for the specification of the object
LOCKED_TOTAL	NUMBER	Total number of times the object has been locked
PINNED_TOTAL	NUMBER	Total number of times the object has been pinned

V\$DB_PIPES

V\$DB_PIPES displays the pipes that are currently represented in the shared pool for this instance.

Column	Datatype	Description
OWNERID	NUMBER	Owner ID of the owner (if this is a private pipe), else NULL
NAME	VARCHAR2 (1000)	Name of the pipe (for example, SCOTT.PIPE)
TYPE	VARCHAR2 (7)	Type of the pipe: - PUBLIC - PRIVATE
PIPE_SIZE	NUMBER	Amount of memory the pipe uses Note: The value of this column may be larger than maxpipesize because of an internal algorithm.

V\$DB_TRANSPORTABLE_PLATFORM

V\$DB_TRANSPORTABLE_PLATFORM displays all platforms to which the database can be transported using the RMAN CONVERT DATABASE command. The transportable database feature only supports transports of the same endian platform. Therefore, V\$DB_TRANSPORTABLE_PLATFORM displays fewer rows than V\$TRANSPORTABLE_PLATFORM.

Column	Datatype	Description
PLATFORM_ID	NUMBER	Platform identification number
PLATFORM_NAME	VARCHAR2 (101)	Platform name
ENDIAN_FORMAT	VARCHAR2 (14)	Platform endian format: - Big - Little - UNKNOWN FORMAT

V\$DBFILE

V\$DBFILE displays all datafiles making up the database. This view is retained for historical compatibility. Use of V\$DATAFILE is recommended instead.

Column	Datatype	Description
FILE#	NUMBER	File identifier

Column	Datatype	Description
NAME	VARCHAR2 (513)	Name of the file

See Also: ["V\\$DATAFILE"](#) on page 7-74

V\$DBLINK

V\$DBLINK describes all database links (links with IN_TRANSACTION = YES) opened by the session issuing the query on V\$DBLINK. These database links must be committed or rolled back before being closed.

Column	Datatype	Description
DB_LINK	VARCHAR2 (128)	Name of the database link
OWNER_ID	NUMBER	Owner of the database link UID
LOGGED_ON	VARCHAR2 (3)	Whether the database link is currently logged on
HETEROGENEOUS	VARCHAR2 (3)	Whether the database link is heterogeneous
PROTOCOL	VARCHAR2 (6)	Communication protocol for the database link
OPEN_CURSORS	NUMBER	Whether there are open cursors for the database link
IN_TRANSACTION	VARCHAR2 (3)	Whether the database link is currently in a transaction
UPDATE_SENT	VARCHAR2 (3)	Whether there has been an update on the database link
COMMIT_POINT_STRENGTH	NUMBER	Commit point strength of the transactions on the database link

V\$DELETED_OBJECT

V\$DELETED_OBJECT displays information about deleted archived logs, datafile copies and backup pieces from the control file. The only purpose of this view is to optimize the recovery catalog resync operation. When an archived log, datafile copy, or backup piece is deleted, the corresponding record is marked deleted.

Column	Datatype	Description
RECID	NUMBER	Deleted object record ID
STAMP	NUMBER	Deleted object record stamp

Column	Datatype	Description
TYPE	VARCHAR2 (26)	Identifies the type of deleted object: ■ ARCHIVED LOG ■ BACKUP PIECE ■ DATAFILE COPY ■ PROXY COPY ■ BACKUP PIECE AVAILABLE ■ BACKUP PIECE EXPIRED ■ PROXY COPY AVAILABLE ■ PROXY COPY EXPIRED ■ BACKUP PIECE UNAVAILABLE ■ PROXY COPY UNAVAILABLE ■ DATAFILE COPY AVAILABLE ■ DATAFILE COPY EXPIRED ■ DATAFILE COPY UNAVAILABLE ■ ARCHIVED LOG AVAILABLE ■ ARCHIVED LOG EXPIRED ■ ARCHIVED LOG UNAVAILABLE ■ BACKUP SET KEEP OPTIONS ■ BACKUP SET KEEP UNTIL ■ PROXY COPY KEEP OPTIONS ■ PROXY COPY KEEP UNTIL ■ DATAFILE COPY KEEP OPTIONS ■ DATAFILE COPY KEEP UNTIL ■ DATAFILE RENAME ON RESTORE
OBJECT_RECID	NUMBER	Record ID of the deleted object
OBJECT_STAMP	NUMBER	Record timestamp of the deleted object
OBJECT_DATA	NUMBER	Displays additional internal information related to this deleted object. For internal Oracle use only.
SET_STAMP	NUMBER	Set stamp of the deleted object
SET_COUNT	NUMBER	Set count of the deleted object

V\$DISPATCHER

V\$DISPATCHER displays information about the dispatcher processes.

Column	Datatype	Description
NAME	VARCHAR2 (4)	Name of the dispatcher process
NETWORK	VARCHAR2 (1024)	Network address of the dispatcher
PADDR	RAW (4 8)	Process address

Column	Datatype	Description
STATUS	VARCHAR2 (16)	Status of the dispatcher: ■ WAIT - Idle ■ SEND - Sending a message ■ RECEIVE - Receiving a message ■ CONNECT - Establishing a connection ■ DISCONNECT - Handling a disconnect request ■ BREAK - Handling a break ■ TERMINATE - In the process of terminating ■ ACCEPT - Accepting connections (no further information available) ■ REFUSE - Rejecting connections (no further information available)
ACCEPT	VARCHAR2 (3)	Indicates whether the dispatcher is accepting new connections (YES) or not (NO)
MESSAGES	NUMBER	Number of messages processed by the dispatcher
BYTES	NUMBER	Size (in bytes) of messages processed by the dispatcher
BREAKS	NUMBER	Number of breaks occurring in the connection
OWNED	NUMBER	Number of circuits owned by the dispatcher
CREATED	NUMBER	Number of circuits created by the dispatcher
IDLE	NUMBER	Total idle time for the dispatcher (in hundredths of a second)
BUSY	NUMBER	Total busy time for the dispatcher (in hundredths of a second)
LISTENER	NUMBER	Most recent Oracle error number the dispatcher received from the listener
CONF_INDX	NUMBER	Zero-based index of the DISPATCHERS configuration used by the dispatcher

V\$DISPATCHER_CONFIG

V\$DISPATCHER_CONFIG displays information about the dispatcher configurations and their attributes.

Column	Datatype	Description
CONF_INDX	NUMBER	Zero-based index of the DISPATCHERS configuration
NETWORK	VARCHAR2 (1024)	Network protocol or listening address of dispatchers (may be truncated)
DISPATCHERS	NUMBER	Number of dispatchers to maintain for the configuration
CONNECTIONS	NUMBER	Maximum number of concurrent connections per dispatcher
SESSIONS	NUMBER	Maximum number of concurrent sessions per dispatcher
POOL	VARCHAR2 (4)	Indicates whether Connection Pooling is on: ■ IN ■ OUT ■ BOTH ■ OFF
TICKS	NUMBER	Tick size (in seconds) for Connection Pooling timeout
INBD_TIMEOUT	NUMBER	Timeout duration (in ticks) for pooled inbound connections
OUTBD_TIMEOUT	NUMBER	Timeout duration (in ticks) for pooled outbound connections
MULTIPLEX	VARCHAR2 (4)	Indicates whether Session Multiplexing is on: ■ IN ■ OUT ■ BOTH ■ OFF

Column	Datatype	Description
LISTENER	VARCHAR2 (1200)	Listeners to register dispatchers with (may be truncated)
SERVICE	VARCHAR2 (128)	Service names supported (may be truncated)

V\$DISPATCHER_RATE

V\$DISPATCHER_RATE displays rate statistics for a number of activities performed by the dispatcher processes. Collected samples have an activity-specific "time-to-live" (TTL_* columns). Statistics are reported over the following two types of time intervals:

- Current statistics (CUR_ columns)
Current statistics use samples collected over the most recent time-to-live interval.
- Historical statistics (AVG_ and most of the MAX_ columns)
Historical statistics make use of all samples that are no longer current.

At the time of collection, a sample is current. After the time-to-live has elapsed, the sample becomes historical. Each type of activity has a specific scale (represented by the SCALE_* columns) at which the statistics are reported.

Column	Datatype	Description
NAME	VARCHAR2 (4)	Name of the dispatcher process
PADDR	RAW (4 8)	Address of the dispatcher process
CUR_LOOP_RATE	NUMBER	Rate at which the dispatcher has been iterating through its dispatching loop, reported over the past TTL_LOOPS, in iterations/SCALE_LOOPS
CUR_EVENT_RATE	NUMBER	Rate at which the dispatcher has been processing dispatcher events, reported over the past TTL_LOOPS, in events/SCALE_LOOPS. Such dispatcher events include network events and shared server requests.
CUR_EVENTS_PER_LOOP	NUMBER	Average number of events the dispatcher has been processing in each iteration through its dispatching loop, reported over the past TTL_LOOPS, in events/iteration
CUR_MSG_RATE	NUMBER	Rate at which the dispatcher has been relaying messages between clients and shared servers, reported over the past TTL_MSG, in messages/SCALE_MSG
CUR_SVR_BUF_RATE	NUMBER	Rate at which the dispatcher has been relaying buffers to shared servers, reported over the past TTL_SVR_BUF, in messages/SCALE_SVR_BUF
CUR_SVR_BYTE_RATE	NUMBER	Rate at which the dispatcher has been relaying data to shared servers, reported over the past TTL_SVR_BUF, in bytes/SCALE_SVR_BUF
CUR_SVR_BYTE_PER_BUF	NUMBER	Average number of data types in each buffer relayed to shared servers, reported over the past TTL_SVR_BUF, in bytes/buffer
CUR_CLT_BUF_RATE	NUMBER	Rate at which the dispatcher has been relaying buffers to clients, reported over the past TTL_CLT_BUF, in buffers/SCALE_CLT_BUF
CUR_CLT_BYTE_RATE	NUMBER	Rate at which the dispatcher has been relaying data to clients, reported over the past TTL_CLT_BUF, in bytes/SCALE_CLT_BUF
CUR_CLT_BYTE_PER_BUF	NUMBER	Average number of data bytes in each buffer relayed to clients, reported over the past TTL_CLT_BUF, in bytes/buffer
CUR_BUF_RATE	NUMBER	Rate at which the dispatcher has been relaying buffers to either clients or shared servers, reported over the past TTL_BUF, in bytes/SCALE_BUF
CUR_BYTE_RATE	NUMBER	Rate at which the dispatcher has been relaying data to either clients or shared servers, reported over the past TTL_BUF, in bytes/SCALE_BUF
CUR_BYTE_PER_BUF	NUMBER	Average number of data bytes in each buffer relayed to either clients or shared servers, reported over the past TTL_BUF, in bytes/buffer

Column	Datatype	Description
CUR_IN_CONNECT_RATE	NUMBER	Rate at which the dispatcher has been accepting incoming client connections, reported over the past TTL_IN_CONNECT, in connections/SCALE_IN_CONNECT
CUR_OUT_CONNECT_RATE	NUMBER	Rate at which the dispatcher has been establishing outbound connections, reported over the past TTL_OUT_CONNECT, in connections/SCALE_OUT_CONNECT
CUR_RECONNECT_RATE	NUMBER	In a connection pooling setup, the rate at which clients have been reconnecting to the dispatcher, reported over the past TTL_RECONNECT, in reconnections/SCALE_RECONNECT
MAX_LOOP_RATE	NUMBER	Maximum rate at which the dispatcher has ever iterated through its dispatching loop, reported in iterations/SCALE_LOOPS, over the dispatcher's lifetime excluding the past TTL_LOOPS
MAX_EVENT_RATE	NUMBER	Maximum rate at which the dispatcher has ever processed dispatcher events, reported in events/SCALE_LOOPS, over the dispatcher's lifetime excluding the past TTL_LOOPS
MAX_EVENTS_PER_LOOP	NUMBER	Maximum number of events the dispatcher has ever processed in one iteration through its dispatching loop, reported in events/iteration, over the dispatcher's lifetime
MAX_MSG_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed messages between clients and shared servers, reported in messages/SCALE_MSG, over the dispatcher's lifetime excluding the past TTL_MSG
MAX_SVR_BUF_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed buffers to shared servers, reported in buffers/SCALE_SVR_BUF, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
MAX_SVR_BYTE_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed data to shared servers, reported in bytes/SCALE_SVR_BUF, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
MAX_SVR_BYTE_PER_BUF	NUMBER	Maximum number of data bytes the dispatcher has ever relayed in one buffer to a client, reported in bytes/buffer, over the dispatcher's lifetime
MAX_CLT_BUF_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed buffers to either clients or shared servers, reported in buffers/SCALE_CLT_BUF, over the dispatcher's life time excluding the past TTL_CLT_BUF
MAX_CLT_BYTE_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed buffers to clients, reported in bytes/SCALE_CLT_BUF, over the dispatcher's lifetime excluding the last TTL_CLT_BUF
MAX_CLT_BYTE_PER_BUF	NUMBER	Maximum number of data bytes the dispatcher has ever relayed in one buffer to a client, reported in bytes/buffer, over the dispatcher's lifetime
MAX_BUF_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed buffers to either clients or shared servers, reported in buffers/SCALE_BUF, over the dispatcher's lifetime, excluding the past TTL_BUF
MAX_BYTE_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed data to either clients or shared servers, reported in bytes/SCALE_BUF, over the dispatcher's lifetime excluding the past TTL_BUF
MAX_BYTE_PER_BUF	NUMBER	Maximum number of data bytes the dispatcher has ever relayed in one buffer to either a client or a shared server, reported in bytes/buffer, over the dispatcher's lifetime
MAX_IN_CONNECT_RATE	NUMBER	Maximum rate at which the dispatcher has ever accepted incoming client connections, reported in connections/SCALE_IN_CONNECT, over the dispatcher's lifetime excluding the past TTL_IN_CONNECT
MAX_OUT_CONNECT_RATE	NUMBER	Maximum rate at which the dispatcher has ever established outbound connections, reported in connections/SCALE_OUT_CONNECT, over the dispatcher's lifetime excluding the past TTL_OUT_CONNECT
MAX_RECONNECT_RATE	NUMBER	In a connection pooling setup, the maximum rate at which clients have ever reconnected to this dispatcher, reported in reconnections/SCALE_RECONNECT, over the dispatcher's lifetime excluding the past TTL_RECONNECT
AVG_LOOP_RATE	NUMBER	Historical average rate at which the dispatcher has iterated through its dispatching loop, reported in iterations/SCALE_LOOPS, over the dispatcher's lifetime excluding the past TTL_LOOPS

Column	Datatype	Description
AVG_EVENT_RATE	NUMBER	Historical average rate at which the dispatcher has processed dispatcher events, reported in events/SCALE_LOOPS, over the dispatcher's lifetime excluding the past TTL_LOOPS
AVG_EVENTS_PER_LOOP	NUMBER	Historical average number of events the dispatcher has processed in one iteration through its dispatching loop, reported in events/iteration, over the dispatcher's lifetime excluding the past TTL_LOOPS
AVG_MSG_RATE	NUMBER	Historical average rate at which the dispatcher has relayed messages between clients and shared servers, reported in messages/SCALE_MSG, over the dispatcher's lifetime excluding the past TTL_MSG
AVG_SVR_BUF_RATE	NUMBER	Historical average rate at which the dispatcher has relayed buffers to shared servers, reported in buffers/SCALE_SVR_BUF, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
AVG_SVR_BYTE_RATE	NUMBER	Historical average rate at which the dispatcher has relayed data to shared servers, reported in bytes/SCALE_SVR_BUF, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
AVG_SVR_BYTE_PER_BUF	NUMBER	Historical average number of data bytes per buffer the dispatcher has relayed to shared servers, reported in bytes/buffer, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
AVG_CLT_BUF_RATE	NUMBER	Historical average rate at which the dispatcher has relayed buffers to clients, reported in buffers/SCALE_CLT_BUF, over the dispatcher's lifetime excluding the past TTL_CLT_BUF
AVG_CLT_BYTE_RATE	NUMBER	Historical average rate at which the dispatcher has relayed data to clients, reported in bytes/SCALE_CLT_BUF, over the dispatcher's lifetime excluding the past TTL_CLT_BUF
AVG_CLT_BYTE_PER_BUF	NUMBER	Historical average number of data bytes per buffer the dispatcher has relayed to clients, reported in bytes/buffer, over the dispatcher's lifetime excluding the past TTL_CLT_BUF
AVG_BUF_RATE	NUMBER	Historical average rate at which the dispatcher has relayed buffers to either clients or shared servers, reported in buffers/SCALE_BUF, over the dispatcher's lifetime excluding the past TTL_BUF
AVG_BYTE_RATE	NUMBER	Historical average rate at which the dispatcher has relayed data to either clients or shared servers, reported in bytes/SCALE_BUF, over the dispatcher's lifetime excluding the past TTL_BUF
AVG_BYTE_PER_BUF	NUMBER	Historical average number of data bytes per buffer the dispatcher has relayed to either clients or shared servers, reported in bytes/buffer, over the dispatcher's lifetime excluding the past TTL_BUF
AVG_IN_CONNECT_RATE	NUMBER	Historical average rate at which the dispatcher has accepted incoming client connections, reported in connections/SCALE_IN_CONNECT, over the dispatcher's lifetime excluding the past TTL_IN_CONNECT
AVG_OUT_CONNECT_RATE	NUMBER	Historical average rate at which the dispatcher has established outbound connections, reported in connections/SCALE_OUT_CONNECT, over the dispatcher's lifetime excluding the past TTL_OUT_CONNECT
AVG_RECONNECT_RATE	NUMBER	In a connection pooling setup, the historical average rate at which clients have reconnected to this dispatcher, reported in reconnections/SCALE_RECONNECT, over the dispatcher's lifetime excluding the past TTL_RECONNECT
TTL_LOOPS	NUMBER	Time-to-live for "loops" samples, reported in hundredths of a second. Default is 10 minutes.
TTL_MSG	NUMBER	Time-to-live for "messages" samples, reported in hundredths of a second. Default is 10 seconds.
TTL_SVR_BUF	NUMBER	Time-to-live for "buffers to servers" samples, reported in hundredths of a second. Default is 1 second.
TTL_CLT_BUF	NUMBER	Time-to-live for "buffers to clients" samples, reported in hundredths of a second. Default is 1 second.
TTL_BUF	NUMBER	Time-to-live for "buffers to clients/servers" samples, reported in hundredths of a second. Default is 1 second.
TTL_IN_CONNECT	NUMBER	Time-to-live for "inbound connections" samples, reported in hundredths of a second. Default is 10 minutes.

Column	Datatype	Description
TTL_OUT_CONNECT	NUMBER	Time-to-live for "outbound connections" samples, reported in hundredths of a second. Default is 10 minutes.
TTL_RECONNECT	NUMBER	Time-to-live for "reconnections" samples, reported in hundredths of a second. Default is 10 minutes.
SCALE_LOOPS	NUMBER	Scale for "loops" statistics, reported in hundredths of a second. Default is 1 minute.
SCALE_MSG	NUMBER	Scale for "messages" statistics, reported in hundredths of a second. Default is 1 second.
SCALE_SVR_BUF	NUMBER	Scale for "buffers to servers" statistics, reported in hundredths of a second. Default is 1/10 second.
SCALE_CLT_BUF	NUMBER	Scale for "buffers to clients" statistics, reported in hundredths of a second. Default is 1/10 second.
SCALE_BUF	NUMBER	Scale for "buffers to clients/servers" statistics, reported in hundredths of a second. Default is 1/10 second.
SCALE_IN_CONNECT	NUMBER	Scale for "inbound connections" statistics, reported in hundredths of a second. Default is 1 minute.
SCALE_OUT_CONNECT	NUMBER	Scale for "outbound connections" statistics, reported in hundredths of a second. Default is 1 minute.
SCALE_RECONNECT	NUMBER	Scale for "reconnections" statistics, reported in hundredths of a second. Default is 1 minute.

V\$DNFS_CHANNELS

V\$DNFS_CHANNELS displays information about the Oracle process connections (channels) open to NFS servers.

Column	Datatype	Description
PNUM	NUMBER	Oracle process number
SVRNAME	VARCHAR2 (255)	NFS server name
PATH	VARCHAR2 (255)	Network path to the NFS server specified by IP address or by name
LOCAL	VARCHAR2 (255)	Local path on the database host specified by IP address or by name
CH_ID	NUMBER	Direct NFS channel identifier
SVR_ID	NUMBER	Direct NFS server identifier
SENDS	NUMBER	Send operations over the channel since the last select
RECVS	NUMBER	Receive operations over the channel since the last select
PINGS	NUMBER	Ping operations over the channel since the last select

V\$DNFS_FILES

V\$DNFS_FILES displays information about the Oracle process files open through Direct NFS.

Column	Datatype	Description
FILENAME	VARCHAR2 (513)	File name
FILESIZE	NUMBER	File Size
PNUM	NUMBER	Oracle process number which opened the file
SVR_ID	NUMBER	Direct NFS server identifier which identifies the server the file is open on

V\$DNFS_SERVERS

V\$DNFS_SERVERS displays information about the Direct NFS servers accessed by Direct NFS.

Column	Datatype	Description
ID	NUMBER	Direct NFS server identifier
SVRNAME	VARCHAR2 (255)	NFS server name
DIRNAME	VARCHAR2 (1024)	Mounted directory
MNTPORT	NUMBER	NFS mount port
NFSPORT	NUMBER	NFS port
WTMAX	NUMBER	WTMAX exported by the NFS server
RTMAX	NUMBER	RTMAX exported by the NFS server

V\$DNFS_STATS

V\$DNFS_STATS displays information about the Oracle process NFS operation statistics issued by Direct NFS.

Column	Datatype	Description
PNUM	NUMBER	Oracle process number that statistics are relevant to
NFS_NULL	NUMBER	Null
NFS_GETATTR	NUMBER	Get attributes
NFS_SETATTR	NUMBER	Set attributes
NFS_LOOKUP	NUMBER	Lookup object
NFS_ACCESS	NUMBER	Access object
NFS_READLINK	NUMBER	Read link
NFS_READ	NUMBER	Read file
NFS_WRITE	NUMBER	Write file
NFS_CREATE	NUMBER	Create file
NFS_MKDIR	NUMBER	Make directory
NFS_SYMLINK	NUMBER	Symbolic link
NFS_MKNOD	NUMBER	Make node
NFS_REMOVE	NUMBER	Remove file
NFS_RMDIR	NUMBER	Remove directory
NFS_RENAME	NUMBER	Rename
NFS_LINK	NUMBER	Link
NFS_READDIR	NUMBER	Read directory
NFS_READDIRPLUS	NUMBER	Read directory plus
NFS_FSSTAT	NUMBER	File system status
NFS_FSINFO	NUMBER	File system information
NFS_PATHCONF	NUMBER	Path configuration
NFS_COMMIT	NUMBER	Commit
NFS_MOUNT	NUMBER	Mount

V\$DYNAMIC_REMASTER_STATS

V\$DYNAMIC_REMASTER_STATS displays statistical information about the dynamic remastering process. All times are given in hundredths of a second, and total values reflect what has been collected since instance startup.

Column	Datatype	Description
REMASTER_OPS	NUMBER	Total number of dynamic remastering operations
REMASTER_TIME	NUMBER	Total dynamic remastering time
REMASTERED_OBJECTS	NUMBER	Total number of objects dynamically remastered due to affinity
QUIESCE_TIME	NUMBER	Total quiesce step time
FREEZE_TIME	NUMBER	Total freeze step time
CLEANUP_TIME	NUMBER	Total cleanup step time
REPLAY_TIME	NUMBER	Total replay step time
FIXWRITE_TIME	NUMBER	Total fixwrite step time
SYNC_TIME	NUMBER	Total synchronization step time
RESOURCES_CLEANED	NUMBER	Total number of resources cleaned in the cleanup steps
REPLAYED_LOCKS_SENT	NUMBER	Total number of locks replayed to other instances in the replay steps
REPLAYED_LOCKS_RECEIVED	NUMBER	Total number of locks received from other instances in the replay steps
CURRENT_OBJECTS	NUMBER	Current number of objects remastered on this instance due to affinity

V\$EMON

V\$EMON displays performance statistics per event monitor (EMON) slave for diagnosability of notifications. All processing time and latency is in seconds.

Column	Datatype	Description
EMON#	NUMBER	EMON identifier (0 - 9)
SID	NUMBER	Session identifier
STARTUP_TIME	TIMESTAMP (3) WITH TIME ZONE	Time when this EMON slave was started
SERVER_TYPE	VARCHAR2 (8)	Notification quality of the service provided by EMON: - REGULAR - RELIABLE
STATUS	VARCHAR2 (6)	EMON status: - IDLE - ACTIVE
STATUS_CHANGE_TIME	TIMESTAMP (3) WITH TIME ZONE	Time at which EMON switched to the current STATUS
NUM_NTFNS	NUMBER	Total number of notifications (including grouping notifications)
NUM_GROUPING_NTFNS	NUMBER	Number of grouping notifications
NUM_NTFNS_ALL_GROUPS	NUMBER	Total number of events in all notification groups
NUM_OCI_NTFNS	NUMBER	Number of OCI notifications
NUM_PLSQL_NTFNS	NUMBER	Number of PL/SQL notifications
NUM_EMAIL_NTFNS	NUMBER	Number of E-mail notifications
NUM_HTTP_NTFNS	NUMBER	Number of HTTP notifications

Column	Datatype	Description
NUM_EVENTS_PROCESSED	NUMBER	Number of events posted by a publisher for which notifications have been delivered
NUM_EVENTS_PENDING	NUMBER	Number of events posted by a publisher for which notifications are not yet delivered
NUM_ANONYMOUS_NTFNS	NUMBER	Number of anonymous notifications
NUM_AQ_NTFNS	NUMBER	Number of AQ notifications
NUM_DBCHANGE_NTFNS	NUMBER	Number of DBChange notifications
TOTAL_ANONYMOUS_NTFN_TIME	NUMBER	Total time to process Anonymous notifications
TOTAL_AQ_NTFN_TIME	NUMBER	Total time to process AQ notifications
TOTAL_DBCHANGE_NTFN_TIME	NUMBER	Total time to process dbchange notifications
TOTAL_PLSQL_NTFN_TIME	NUMBER	Total time to process PL/SQL notifications
TOTAL_OCI_NTFN_TIME	NUMBER	Total time to process OCI notifications
TOTAL_EMAIL_NTFN_TIME	NUMBER	Total time to process E-mail notifications
TOTAL_HTTP_NTFN_TIME	NUMBER	Total time to process HTTP notifications
TOTAL_EMON_LATENCY	NUMBER	Total latency in processing events
REGISTRATIONS_EXPIRED	NUMBER	Number of expired registrations
REGISTRATIONS_PURGED	NUMBER	Number of purged registrations
REGISTRATIONS_INVALID	NUMBER	Number of registrations invalidated due to notification delivery failure
LAST_UPDATE_TIME	TIMESTAMP (3) WITH TIME ZONE	Time when statistics were last updated

V\$ENABLEDPRIVS

V\$ENABLEDPRIVS displays which privileges are enabled. These privileges can be found in the table SYSTEM_PRIVILEGE_MAP.

Column	Datatype	Description
PRIV_NUMBER	NUMBER	Numeric identifier of enabled privileges

See Also: ["SYSTEM_PRIVILEGE_MAP"](#) on page 6-61

V\$ENCRYPTED_TABLESPACES

V\$ENCRYPTED_TABLESPACES displays information about the tablespaces that are encrypted.

Column	Datatype	Description
TS#	NUMBER	Tablespace number
ENCRYPTIONALG	VARCHAR2 (7)	Encryption algorithm: - NONE 3DES168 - AES128 - AES192 - AES256
ENCRYPTEDTS	VARCHAR2 (3)	Indicates whether the tablespace is encrypted (YES) or not (NO)

Column	Datatype	Description
ENCRYPTEDKEY ¹	RAW (32)	Encrypted version of the tablespace key for the encrypted tablespace
MASTERKEYID ¹	RAW (16)	ID of the master key that was used to encrypt the tablespace key
BLOCKS_ENCRYPTED ¹	NUMBER	Number of tablespace blocks that have been encrypted during the lifetime of this instance
BLOCKS_DECRYPTED ¹	NUMBER	Number of tablespace blocks that have been decrypted during the lifetime of this instance

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$ENCRYPTION_WALLET

V\$ENCRYPTION_WALLET displays information on the status of the wallet and the wallet location for transparent data encryption.

Column	Datatype	Description
WRL_TYPE	VARCHAR2 (20)	Type of the wallet resource locator (for example, FILE)
WRL_PARAMETER	VARCHAR2 (4000)	Parameter of the wallet resource locator (for example, absolute filename if WRL_TYPE = FILE)
STATUS	VARCHAR2 (9)	Status of the wallet: ■ OPEN ■ CLOSED ■ UNDEFINED

V\$ENQUEUE_LOCK

V\$ENQUEUE_LOCK displays all locks owned by enqueue state objects. The columns in this view are identical to the columns in V\$LOCK.

See Also: ["V\\$LOCK"](#) on page 8-15

Column	Datatype	Description
ADDR	RAW (4 8)	Address of lock state object
KADDR	RAW (4 8)	Address of lock
SID	NUMBER	Identifier for session holding or acquiring the lock
TYPE	VARCHAR2 (2)	Type of lock. Lists user and system types that can have locks.
ID1	NUMBER	Lock identifier #1 (depends on type)
ID2	NUMBER	Lock identifier #2 (depends on type)
LMODE	NUMBER	Lock mode in which the session holds the lock: ■ 0 - none ■ 1 - null (NULL) ■ 2 - row-S (SS) ■ 3 - row-X (SX) ■ 4 - share (S) ■ 5 - S/Row-X (SSX) ■ 6 - exclusive (X)

Column	Datatype	Description
REQUEST	NUMBER	Lock mode in which the process requests the lock: 0 - none 1 - null (NULL) 2 - row-S (SS) 3 - row-X (SX) 4 - share (S) 5 - S/Row-X (SSX) 6 - exclusive (X)
CTIME	NUMBER	Time since current mode was granted
BLOCK	NUMBER	The lock is blocking another lock

V\$ENQUEUE_STAT

V\$ENQUEUE_STAT displays statistics on the number of enqueue (lock) requests for each type of lock.

Column	Datatype	Description
INST_ID	NUMBER	ID of the instance
EQ_TYPE	VARCHAR2 (2)	Type of enqueue requested
TOTAL_REQ#	NUMBER	Total number of enqueue requests or enqueue conversions for this type of enqueue
TOTAL_WAIT#	NUMBER	Total number of times an enqueue request or conversion resulted in a wait
SUCC_REQ#	NUMBER	Number of times an enqueue request or conversion was granted
FAILED_REQ#	NUMBER	Number of times an enqueue request or conversion failed
CUM_WAIT_TIME	NUMBER	Total amount of time (in milliseconds) spent waiting for the enqueue or enqueue conversion

V\$ENQUEUE_STATISTICS

V\$ENQUEUE_STATISTICS displays statistics on the number of enqueue (lock) requests for each type of lock. V\$ENQUEUE_STATISTICS encompasses V\$ENQUEUE_STAT and gives more detailed information (several rows for same enqueues with different reasons).

Column	Datatype	Description
EQ_NAME	VARCHAR2 (64)	Name of the enqueue request
EQ_TYPE	VARCHAR2 (2)	Type of enqueue requested
REQ_REASON	VARCHAR2 (64)	Reason for the enqueue request
TOTAL_REQ#	NUMBER	Total number of enqueue requests or enqueue conversions for this type of enqueue
TOTAL_WAIT#	NUMBER	Total number of times an enqueue request or conversion resulted in a wait
SUCC_REQ#	NUMBER	Number of times an enqueue request or conversion was granted
FAILED_REQ#	NUMBER	Number of times an enqueue request or conversion failed
CUM_WAIT_TIME	NUMBER	Total amount of time (in milliseconds) spent waiting for the enqueue or enqueue conversion
REQ_DESCRIPTION	VARCHAR2 (4000)	Description of the enqueue request
EVENT#	NUMBER	Event number

V\$EVENT_HISTOGRAM

V\$EVENT_HISTOGRAM displays a histogram of the number of waits, the maximum wait, and total wait time on an event basis. The histogram has buckets of time intervals from < 1 ms, < 2 ms, < 4 ms, < 8 ms, ... < 2²¹ ms, < 2²² ms, and >= 2²² ms.

The histogram will not be filled unless the TIMED_STATISTICS initialization parameter is set to true.

Column	Datatype	Description
EVENT#	NUMBER	Event number
EVENT	VARCHAR2 (64)	Name of the Event
WAIT_TIME_MILLI	NUMBER	Amount of time the bucket represents (in milliseconds). If the duration = <i>num</i> , then this column represents waits of duration < <i>num</i> that are not included in any smaller bucket.
WAIT_COUNT	NUMBER	Number of waits of the duration belonging to the bucket of the histogram
LAST_UPDATE_TIME	VARCHAR2 (64)	Indicates the last time the bucket was updated (the ending timestamp of the last wait falling into the bucket's duration)

V\$EVENT_NAME

V\$EVENT_NAME displays information about wait events.

Column	Datatype	Description
EVENT#	NUMBER	Number of the wait event
EVENT_ID	NUMBER	Identifier of the wait event
NAME	VARCHAR2 (64)	Name of the wait event
PARAMETER1	VARCHAR2 (64)	Description of the first parameter for the wait event
PARAMETER2	VARCHAR2 (64)	Description of the second parameter for the wait event
PARAMETER3	VARCHAR2 (64)	Description of the third parameter for the wait event
WAIT_CLASS_ID	NUMBER	Identifier of the class of the wait event
WAIT_CLASS#	NUMBER	Number of the class of the wait event
WAIT_CLASS	VARCHAR2 (64)	Name of the class of the wait event See Also: "Classes of Wait Events" on page C-1 for a description of the different wait event classes

V\$EVENTMETRIC

V\$EVENTMETRIC displays values of wait event metrics for the most recent 60-second interval.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
EVENT#	NUMBER	Number of the event
EVENT_ID	NUMBER	Identifier of the event
NUM_SESS_WAITING	NUMBER	Number of sessions waiting at the end of the interval
TIME_WAITED	NUMBER	Time waited (in hundredths of a second)

Column	Datatype	Description
WAIT_COUNT	NUMBER	Number of times waited
TIME_WAITED_FG	NUMBER	Time waited (in hundredths of a second), from foreground sessions
WAIT_COUNT_FG	NUMBER	Number of times waited, from foreground sessions

V\$EXECUTION

V\$EXECUTION displays information on parallel execution.

Column	Datatype	Description
PID	NUMBER	Session ID
DEPTH	NUMBER	The depth
FUNCTION	VARCHAR2 (10)	Session serial number
TYPE	VARCHAR2 (7)	Name of the OBJECT_NODE in plan table
NVALS	NUMBER	Elapsed time for OBJECT_NODE
VAL1	NUMBER	The value for number 1
VAL2	NUMBER	The value for number 2
SEQH	NUMBER	A sequence
SEQL	NUMBER	A sequence

V\$FALSE_PING

V\$FALSE_PING is deprecated. The information that was provided in this view is now provided in the V\$INSTANCE_CACHE_TRANSFER and V\$SEGMENT_STATISTICS views.

Column	Datatype	Description
FILE#	NUMBER	Datafile identifier number (to find the filename, query DBA_DATA_FILES or V\$DBFILE)
BLOCK#	NUMBER	Block number
STATUS	VARCHAR2 (6)	Status of the block: - free - Not currently in use - xcur - Exclusive - scur - Shared current - cr - Consistent read - read - Being read from disk - mrec - In media recovery mode - irec - In instance recovery mode
XNC	NUMBER	Number of PCM lock conversions from Exclusive mode due to contention with another instance. This column is obsolete and maintained for backward compatibility.
FORCED_READS	NUMBER	Number of times the block had to be reread from the cache because another instance has forced it out of this instance's cache by requesting the lock on the block in exclusive mode
FORCED_WRITES	NUMBER	Number of times GCS had to write this block to cache because this instance had used the block and another instance had requested the lock on the block in a conflicting mode
NAME	VARCHAR2 (30)	Name of the database object containing the block
PARTITION_NAME	VARCHAR2 (30)	NULL for non-partitioned objects
KIND	VARCHAR2 (15)	Type of database object

Column	Datatype	Description
OWNER#	NUMBER	Owner number
LOCK_ELEMENT_ADDR	RAW (4 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_NAME	NUMBER	Name of the lock that contains the PCM lock that is covering the buffer
LOCK_ELEMENT_CLASS	NUMBER	Lock element class

See Also: The *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Installation Guide* for your operating system.

V\$FAST_START_SERVERS

V\$FAST_START_SERVERS provides information about all the recovery slaves performing parallel transaction recovery.

Column	Datatype	Description
STATE	VARCHAR2 (11)	State of the server (IDLE or RECOVERING)
UNDOBLOCKSDONE	NUMBER	Number of undo blocks done so far
PID	NUMBER	Process ID
XID	RAW (8)	Transaction ID

See Also: *Oracle Database Performance Tuning Guide*

V\$FAST_START_TRANSACTIONS

V\$FAST_START_TRANSACTIONS displays information about the progress of the transactions that Oracle is recovering.

Column	Datatype	Description
USN	NUMBER	Undo segment number of the transaction
SLT	NUMBER	Slot within the rollback segment
SEQ	NUMBER	Incarnation number of the slot
STATE	VARCHAR2 (16)	State of the transaction (may be TO BE RECOVERED, RECOVERED, or RECOVERING)
UNDOBLOCKSDONE	NUMBER	Number of undo blocks completed on the transaction
UNDOBLOCKSTOTAL	NUMBER	Total number of undo blocks that need recovery
PID	NUMBER	ID of the current server it has been assigned to
CPUTIME	NUMBER	Time for which recovery has progressed (in seconds)
PARENTUSN	NUMBER	Undo segment number of the parent transaction in PDML
PARENTSLT	NUMBER	Slot of the parent transaction in PDML
PARENTSEQ	NUMBER	Sequence number of the parent transaction in PDML
XID	RAW (8)	Transaction ID
PXID	RAW (8)	Parent transaction ID
RCVSERVERS	NUMBER	Number of servers used in the last recovery

See Also: *Oracle Database Performance Tuning Guide*

V\$FILE_CACHE_TRANSFER

V\$FILE_CACHE_TRANSFER is deprecated. The information that was provided in this view is now provided in the V\$INSTANCE_CACHE_TRANSFER and V\$SEGMENT_STATISTICS views.

Column	Datatype	Description
FILE_NUMBER	NUMBER	Number of the datafile
X_2_NULL	NUMBER	Number of blocks with Exclusive-to-NULL conversions; always 0
X_2_NULL_FORCED_WRITE	NUMBER	Number of Exclusive-to-NULL forced writes; always 0
X_2_NULL_FORCED_STALE	NUMBER	Number of Exclusive-to-NULL blocks converted to CR; always 0
X_2_S	NUMBER	Number of blocks with Exclusive-to-Shared conversions; always 0
X_2_S_FORCED_WRITE	NUMBER	Number of Exclusive-to-Shared forced writes; always 0
S_2_NULL	NUMBER	Number of blocks with Shared-to-NULL conversions; always 0
S_2_NULL_FORCED_STALE	NUMBER	Number of Shared-to-NULL blocks converted to CR; always 0
RBR	NUMBER	Number of reuse blocks cross-instance calls; always 0
RBR_FORCED_WRITE	NUMBER	Number of blocks written due to reuse blocks cross-instance calls; always 0
RBR_FORCED_STALE	NUMBER	Number of blocks marked as flushed due to reuse blocks cross-instance calls; always 0
NULL_2_X	NUMBER	Number of blocks with NULL-to-Exclusive conversions; always 0
S_2_X	NUMBER	Number of blocks with Shared-to-Exclusive conversions; always 0
NULL_2_S	NUMBER	Number of blocks with NULL-to-Shared conversions; always 0
CR_TRANSFERS	NUMBER	Number of CR blocks received; always 0
CUR_TRANSFERS	NUMBER	Number of current blocks received; always 0

V\$FILE_HISTOGRAM

V\$FILE_HISTOGRAM displays a histogram of all synchronous single block reads on a per-file basis (for data files). The histogram has buckets of time intervals from < 1 ms, < 2 ms, < 4 ms, < 8 ms, ... < 2²¹ ms, < 2²² ms, and >= 2²² ms.

The histogram will not be filled unless the STATISTICS_LEVEL initialization parameter is set to ALL.

Column	Datatype	Description
FILE#	NUMBER	File number
SINGLEBLKRDTIM_MILLI	NUMBER	Amount of time the bucket represents (in milliseconds). If the duration = <i>num</i> , then this column represents waits of duration < <i>num</i> that are not included in any smaller bucket.
SINGLEBLKRDS	NUMBER	Number of waits of the duration belonging to the bucket of the histogram

V\$FILEMETRIC

V\$FILEMETRIC displays values of file metrics for the most recent 10-minute interval. A history of the last one hour will be kept in the system.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval

Column	Datatype	Description
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
FILE_ID	NUMBER	File number
CREATION_TIME	NUMBER	Timestamp of the file creation
AVERAGE_READ_TIME	NUMBER	Average file read time (in hundredths of a second)
AVERAGE_WRITE_TIME	NUMBER	Average file write time (in hundredths of a second)
PHYSICAL_READS	NUMBER	Number of physical reads
PHYSICAL_WRITES	NUMBER	Number of physical writes
PHYSICAL_BLOCK_READS	NUMBER	Number of physical block reads
PHYSICAL_BLOCK_WRITES	NUMBER	Number of physical block writes

V\$FILEMETRIC_HISTORY

V\$FILEMETRIC_HISTORY displays values of file metrics for all intervals in the last one hour.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
FILE_ID	NUMBER	File number
CREATION_TIME	NUMBER	Timestamp of the file creation
AVERAGE_READ_TIME	NUMBER	Average file read time (in hundredths of a second)
AVERAGE_WRITE_TIME	NUMBER	Average file write time (in hundredths of a second)
PHYSICAL_READS	NUMBER	Number of physical reads
PHYSICAL_WRITES	NUMBER	Number of physical writes
PHYSICAL_BLOCK_READS	NUMBER	Number of physical block reads
PHYSICAL_BLOCK_WRITES	NUMBER	Number of physical block writes

V\$FILESPACE_USAGE

V\$FILESPACE_USAGE summarizes space allocation information of each datafile and tempfile.

Column	Datatype	Description
TABLESPACE_ID	NUMBER	ID of the tablespace to which the file belongs
RFNO	NUMBER	Relative file number of the file
ALLOCATED_SPACE	NUMBER	Total allocated space in the file
FILE_SIZE	NUMBER	Current file size
FILE_MAXSIZE	NUMBER	Maximum file size
CHANGESCN_BASE	NUMBER	SCN base of the last change to the file
CHANGESCN_WRAP	NUMBER	SCN wrap of the last change to the file
FLAG	NUMBER	Flags for file attributes

V\$FILESTAT

V\$FILESTAT displays the number of physical reads and writes done and the total number of single-block and multiblock I/Os done at file level. As of Oracle Database 10g Release 2 (10.2), this view also includes reads done by RMAN processes for backup operations.

Column	Datatype	Description
FILE#	NUMBER	Number of the file
PHYRDS	NUMBER	Number of physical reads done
PHYWRTS	NUMBER	Number of times DBWR is required to write
PHYBLKRD	NUMBER	Number of physical blocks read
OPTIMIZED_PHYBLKRD	NUMBER	Number of physical reads from Database Smart Flash Cache blocks
PHYBLKWRT	NUMBER	Number of blocks written to disk, which may be the same as PHYWRTS if all writes are single blocks
SINGLEBLKRDS	NUMBER	Number of single block reads
READTIM	NUMBER	Time (in hundredths of a second) spent doing reads if the TIMED_STATISTICS parameter is true; 0 if false
WRITETIM	NUMBER	Time (in hundredths of a second) spent doing writes if the TIMED_STATISTICS parameter is true; 0 if false
SINGLEBLKRDTIM	NUMBER	Cumulative single block read time (in hundredths of a second)
AVGIOTIM	NUMBER	Average time (in hundredths of a second) spent on I/O, if the TIMED_STATISTICS parameter is true; 0 if false
LSTIOTIM	NUMBER	Time (in hundredths of a second) spent doing the last I/O, if the TIMED_STATISTICS parameter is true; 0 if false
MINIOTIM	NUMBER	Minimum time (in hundredths of a second) spent on a single I/O, if the TIMED_STATISTICS parameter is true; 0 if false
MAXIORTM	NUMBER	Maximum time (in hundredths of a second) spent doing a single read, if the TIMED_STATISTICS parameter is true; 0 if false
MAXIOWTM	NUMBER	Maximum time (in hundredths of a second) spent doing a single write, if the TIMED_STATISTICS parameter is true; 0 if false

V\$FIXED_TABLE

V\$FIXED_TABLE displays all dynamic performance tables, views, and derived tables in the database. Some V\$ tables (for example, V\$ROLLNAME) refer to real tables and are therefore not listed.

Column	Datatype	Description
NAME	VARCHAR2 (30)	Name of the object
OBJECT_ID	NUMBER	Identifier of the fixed object
TYPE	VARCHAR2 (5)	Object type (TABLE VIEW)
TABLE_NUM	NUMBER	Number that identifies the dynamic performance table if it is of type TABLE

V\$FIXED_VIEW_DEFINITION

V\$FIXED_VIEW_DEFINITION contains the definitions of all the fixed views (views beginning with V\$). Use this table with caution. Oracle tries to keep the behavior of fixed views the same from release to release, but the definitions of the fixed views can change without notice. Use these definitions to optimize your queries by using indexed columns of the dynamic performance tables.

Column	Datatype	Description
VIEW_NAME	VARCHAR2 (30)	Name of the fixed view
VIEW_DEFINITION	VARCHAR2 (4000)	Definition of the fixed view

V\$FLASHBACK_DATABASE_LOG

V\$FLASHBACK_DATABASE_LOG displays information about the flashback data. Use this view to help estimate the amount of flashback space required for the current workload.

Column	Datatype	Description
OLDEST_FLASHBACK_SCN	NUMBER	Lowest system change number (SCN) in the flashback data, for any incarnation
OLDEST_FLASHBACK_TIME	DATE	Time of the lowest SCN in the flashback data, for any incarnation
RETENTION_TARGET	NUMBER	Target retention time (in minutes)
FLASHBACK_SIZE	NUMBER	Current size (in bytes) of the flashback data
ESTIMATED_FLASHBACK_SIZE	NUMBER	Estimated size of flashback data needed for the current target retention

V\$FLASHBACK_DATABASE_LOGFILE

V\$FLASHBACK_DATABASE_LOGFILE displays information about the flashback log files.

Column	Datatype	Description
NAME	VARCHAR2 (513)	Name of the log file
LOG#	NUMBER	Log file number
THREAD#	NUMBER	Log file thread number
SEQUENCE#	NUMBER	Log file sequence number
BYTES	NUMBER	Log file size (in bytes)
FIRST_CHANGE#	NUMBER	Lowest system change number (SCN) in the log file
FIRST_TIME	DATE	Time of the first SCN in the log file
TYPE ¹	VARCHAR2 (9)	Log type: ■ NORMAL ■ RESERVED ■ FREE ■ TO DELETE

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$FLASHBACK_DATABASE_STAT

V\$FLASHBACK_DATABASE_STAT displays statistics for monitoring the I/O overhead of logging flashback data. This view also displays the estimated flashback space needed based on previous workloads.

Column	Datatype	Description
BEGIN_TIME	DATE	Beginning of the time interval
END_TIME	DATE	End of the time interval
FLASHBACK_DATA	NUMBER	Number of bytes of flashback data written during the interval

Column	Datatype	Description
DB_DATA	NUMBER	Number of bytes of database data read and written during the interval
REDO_DATA	NUMBER	Number of bytes of redo data written during the interval
ESTIMATED_FLASHBACK_SIZE	NUMBER	Value of ESTIMATED_FLASHBACK_SIZE in V\$FLASHBACK_DATABASE_LOG at the end of the time interval

V\$FLASHBACK_TXN_GRAPH

V\$FLASHBACK_TXN_GRAPH displays a tabular representation of the transaction dependency graph. For each dependency edge, there could be multiple rows, one for each conflicting operation..

This view is relevant AFTER a compensating transaction has been started through the DBMS_FLASHBACK.TRANSACTION_BACKOUT () set of functions, and is no longer relevant once the compensating transaction is either committed or rolled back. It also provides a tabular representation of the undo SQL that is not available through the CLOB XML construct in the DBA_FLASHBACK_TXN_REPORT view.

Column	Datatype	Description
COMPENSATING_XID	RAW (8)	Transaction ID of the compensating transaction
COMPENSATING_TXN_NAME	VARCHAR2 (255)	Name of the compensating transaction
XID	RAW (8)	Transaction ID of a relevant transaction found in memory
TXN_NAME	VARCHAR2 (255)	Name of the transaction with XID as the transaction ID; NULL if none
PARENT_XID	RAW (8)	Parent transaction ID (for a PDML transaction)
INTERESTING	NUMBER	If the transaction is in the transaction dependency graph
ORIGINAL	NUMBER	If the transaction is part of the input set provided
BACKOUT_SEQ	NUMBER	Order in which the transaction has been backed out
NUM_PREDS	NUMBER	Number of predecessors of the transaction specified by XID in the transaction graph
NUM_SUCCS	NUMBER	Number of successors of the transaction specified by XID in the transaction graph
DEP_XID	RAW (8)	One dependent transaction ID of the transaction specified by XID. This is a particular child of XID.
DEP_TXN_NAME	VARCHAR2 (255)	Transaction name, if any, for the transaction specified by DEP_XID
TXN_CONF_SQL_ID	NUMBER	SQL ID of undo SQL executed in the context of XID which conflicts with the dependent transaction
DEP_TXN_CONF_SQL_ID	NUMBER	SQL ID of undo SQL executed in the context of DEP_XID which conflicts with XID
CONFLICT_TYPE	VARCHAR2 (32)	The type of conflict that the conflict resolution method is used to resolve: delete, uniqueness, or update

V\$FLASHBACK_TXN_MODS

V\$FLASHBACK_TXN_MODS displays the individual modifications of all the transactions in memory.

This view is relevant AFTER a compensating transaction has been started through the DBMS_FLASHBACK.TRANSACTION_BACKOUT () set of functions, and is no longer relevant once the compensating transaction is either committed or rolled back. It also provides a tabular representation of the undo SQL that is not available through the CLOB XML construct in the DBA_FLASHBACK_TXN_REPORT view.

Column	Datatype	Description
COMPENSATING_XID	RAW (8)	Transaction ID of the compensating transaction
COMPENSATING_TXN_NAME	VARCHAR2 (255)	Name of the compensating transaction
XID	RAW (8)	Transaction ID of a relevant transaction found in memory
TXN_NAME	VARCHAR2 (255)	Name of the transaction with XID as the transaction ID; NULL if none
PARENT_XID	RAW (8)	Parent transaction ID (for a PDML transaction)
INTERESTING	NUMBER	If the transaction is in the transaction dependency graph
ORIGINAL	NUMBER	If the transaction is part of the input set provided
BACKOUT_SEQ	NUMBER	Order in which the transaction has been backed out
UNDO_SQL	VARCHAR2 (4000)	Undo SQL for the modification
UNDO_SQL_SQN	NUMBER	Order in which the given SQL has been executed to back out this transaction
UNDO_SQL_SUB_SQN	NUMBER	If the undo SQL is greater than 4000 bytes, then a sequence number, starting from 1, of a 4000-byte division of the undo SQL
BACKOUT_SQL_ID	NUMBER	SQL ID of the undo SQL (used only for this compensating transaction)
OPERATION	VARCHAR2 (30)	Operation (such as insert/update/delete) performed by the forward-going operation
BACKEDOUT	NUMBER	Indicates whether the transaction has been backed out as of now
CONFLICT_MOD	NUMBER	If the concerned modification is causing a conflict
MODS_PER_LCR	NUMBER	Sometimes an LCR could cause multiple modifications (for example, an update of an IOT could actually be a delete followed by an insert)

V\$FOREIGN_ARCHIVED_LOG

V\$FOREIGN_ARCHIVED_LOG can be queried on a logical standby database to find out the list of foreign archived logs received by a database.

Column	Datatype	Description
RECID	NUMBER	Archived log record ID
STAMP	NUMBER	Archived log record stamp
NAME	VARCHAR2 (513)	Archived log file name. If set to NULL, either the log file was cleared before it was archived or an RMAN BACKUP command with the delete input option was executed to back up archivelog all (RMAN> backup archivelog all delete input;).
DEST_ID	NUMBER	Original destination from which the archive log was generated. The value is 0 if the destination identifier is not available
THREAD#	NUMBER	Redo thread number
SEQUENCE#	NUMBER	Redo log sequence number
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the database when the log was written
RESETLOGS_TIME	DATE	Resetlogs time of the database when the log was written
RESETLOGS_ID	NUMBER	Resetlogs identifier associated with the archived redo log
FIRST_CHANGE#	NUMBER	First change number in the archived log
FIRST_TIME	DATE	Timestamp of the first change
NEXT_CHANGE#	NUMBER	First change in the next log
NEXT_TIME	DATE	Timestamp of the next change
BLOCKS	NUMBER	Size of the archived log (in blocks)

Column	Datatype	Description
BLOCK_SIZE	NUMBER	Redo log block size. This is the logical block size of the archived log, which is the same as the logical block size of the online log from which the archived log was copied. The online log logical block size is a platform-specific value that is not adjustable by the user.
CREATOR	VARCHAR2 (7)	Creator of the archive log: ARCH - Archiver process FGRD - Foreground process RMAN - Recovery Manager SRMN - RMAN at standby LGWR - Logwriter process
REGISTRAR	VARCHAR2 (7)	Registrar of the entry: RFS - Remote File Server process ARCH - Archiver process FGRD - Foreground process RMAN - Recovery Manager SRMN - RMAN at standby LGWR - Logwriter process
ARCHIVED	VARCHAR2 (3)	Indicates whether the online redo log was archived (YES) or whether RMAN only inspected the log and created a record for future application of redo logs during recovery (NO). <i>See Oracle Database Backup and Recovery User's Guide for more information.</i>
APPLIED	VARCHAR2 (3)	Indicates whether the archivelog has been applied to its corresponding standby database (YES) or not (NO). The value is always NO for local destinations. This column is meaningful at the physical standby site for the ARCHIVED_LOG entries with REGISTRAR= 'RFS' (which means this log is shipped from the primary to the standby database). If REGISTRAR= 'RFS' and APPLIED is NO, then the log has arrived at the standby but has not yet been applied. If REGISTRAR= 'RFS' and APPLIED is YES, the log has arrived and been applied at the standby database. You can use this field to identify archivelogs that can be backed up and removed from disk.
DELETED	VARCHAR2 (3)	Indicates whether an RMAN DELETE command has physically deleted the archived log file from disk, as well as logically removing it from the control file of the target database and from the recovery catalog (YES) or not (NO)
STATUS	VARCHAR2 (1)	Status of the archived log: A - Available D - Deleted U - Unavailable X - Expired
COMPLETION_TIME	DATE	Time when the archiving completed
DICTIONARY_BEGIN	VARCHAR2 (3)	Indicates whether the log contains the start of a LogMiner dictionary (YES) or not (NO)
DICTIONARY_END	VARCHAR2 (3)	Indicates whether the log contains the end of a LogMiner dictionary (YES) or not (NO)
END_OF_REDO	VARCHAR2 (3)	Indicates whether the archived redo log contains the end of all redo information from the primary database () or not ()
ARCHIVAL_THREAD#	NUMBER	Redo thread number of the instance that performed the archival operation. This column differs from the THREAD# column only when a closed thread is archived by another instance.
IS_RECOVERY_DEST_FILE	VARCHAR2 (3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
COMPRESSED	VARCHAR2 (3)	Reserved for internal use

Column	Datatype	Description
FAL	VARCHAR2 (3)	Indicates whether the archive log was generated as the result of a FAL request (YES) or not (NO)
END_OF_REDO_TYPE	VARCHAR2 (10)	Possible values are as follows: SWITCHOVER - Shows archived redo log files that are produced at the end of a switchover TERMINAL - Shows archived redo log files produced after a failover RESETLOGS - Shows online redo log files archived on the primary database after an ALTER DATABASE OPEN RESETLOGS statement is issued ACTIVATION - Shows any log files archived on a physical standby database after an ALTER DATABASE ACTIVATE STANDBY DATABASE statement is issued "empty string" - Any empty string implies that the log is just a normal archival and was not archived due to any of the other events
SOURCE_DBID	NUMBER	Database ID of the source database that generated this archived log

V\$FS_FAILOVER_STATS

V\$FS_FAILOVER_STATS displays statistics about Fast-Start Failovers (FSFOs) occurring on the system.

Column	Datatype	Description
LAST_FAILOVER_TIME	VARCHAR2 (20)	Timestamp of the last Fast-Start Failover
LAST_FAILOVER_REASON	VARCHAR2 (255)	Reason for the last Fast-Start Failover

V\$GC_ELEMENT

V\$GC_ELEMENT displays one entry for each global cache resource that is used by the buffer cache. The name of the global cache resource that corresponds to a lock element is {'BL', indx, class}. This is a Real Application Clusters view.

See Also: The *Oracle Database Oracle Clusterware and Oracle Real Application Clusters Installation Guide* for your operating system.

Column	Datatype	Description
GC_ELEMENT_ADDR	RAW (4 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
INDX	NUMBER	Platform specific lock manager identifier
CLASS	NUMBER	Platform specific lock manager identifier
GC_ELEMENT_NAME	NUMBER	Name of the lock that contains the PCM lock that is covering the buffer
MODE_HELD	NUMBER	Platform dependent value for lock mode held; often: 3 = share; 5 = exclusive
BLOCK_COUNT	NUMBER	Number of blocks covered by PCM lock
RELEASING	NUMBER	Nonzero if PCM lock is being downgraded
ACQUIRING	NUMBER	Nonzero if PCM lock is being upgraded
WRITING	NUMBER	If the GC_ELEMENT is being written, the write status
RECOVERING	NUMBER	If the GC_ELEMENT is being recovered, the recovery status
LOCAL	NUMBER	Zero if the GC_ELEMENT is local, one if it is global
FLAGS	NUMBER	Process level flags for the lock element

V\$GC_ELEMENTS_WITH_COLLISIONS

V\$GC_ELEMENTS_WITH_COLLISIONS is deprecated. The information that was provided in this view is now provided in the V\$INSTANCE_CACHE_TRANSFER and V\$SEGMENT_STATISTICS views.

Column	Datatype	Description
GC_ELEMENT_ADDR	RAW (4 8)	Address of the lock element that contains the PCM lock covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.

V\$GCSHVMMASTER_INFO

V\$GCSHVMMASTER_INFO describes the current and previous master instances and the number of re-masterings of Global Cache Service resources except those belonging to files mapped to a particular master.

Column	Datatype	Description
HV_ID	NUMBER	PCM hash value ID
CURRENT_MASTER	NUMBER	Master instance of this PCM hash value ID
PREVIOUS_MASTER	NUMBER	Previous master instance of this PCM hash value ID
REMASTER_CNT	NUMBER	Number of times this has been remastered

V\$GCSPFMASTER_INFO

V\$GCSPFMASTER_INFO describes the current and previous master instances and the number of re-masterings of Global Cache Service resources belonging to files mapped to instances.

Column	Datatype	Description
FILE_ID	NUMBER	File number
DATA_OBJECT_ID	NUMBER	Data object ID
GC_MASTERING_POLICY	VARCHAR2 (11)	Data object type. The possible values are Affinity or Read mostly.
CURRENT_MASTER	NUMBER	Master instance of this file
PREVIOUS_MASTER	NUMBER	Previous master instance of this file
REMASTER_CNT	NUMBER	Number of times this has been remastered

V\$GES_BLOCKING_ENQUEUE

V\$GES_BLOCKING_ENQUEUE describes all locks currently known to lock manager that are being blocked or blocking others. The output of this view is a subset of the output from V\$GES_ENQUEUE. This is a Real Application Clusters view.

See Also: ["V\\$GES_ENQUEUE"](#) on page 7-108 for a description of all locks known to the lock manager

Column	Datatype	Description
HANDLE	RAW (4 8)	Lock pointer
GRANT_LEVEL	VARCHAR2 (9)	Granted level of the lock

Column	Datatype	Description
REQUEST_LEVEL	VARCHAR2 (9)	Requested level of the lock
RESOURCE_NAME1	VARCHAR2 (30)	Resource name for the lock
RESOURCE_NAME2	VARCHAR2 (30)	Resource name for the lock
PID	NUMBER	Process identifier which holds the lock
TRANSACTION_ID0	NUMBER	Lower 4 bytes of the transaction identifier where the lock belongs to
TRANSACTION_ID1	NUMBER	Upper 4 bytes of the transaction identifier where the lock belongs to
GROUP_ID	NUMBER	Group identifier for the lock
OPEN_OPT_DEADLOCK	NUMBER	1 if DEADLOCK open option is set, otherwise 0
OPEN_OPT_PERSISTENT	NUMBER	1 if PERSISTENT open option is set, otherwise 0
OPEN_OPT_PROCESS_OWNED	NUMBER	1 if PROCESS_OWNED open option is set, otherwise 0
OPEN_OPT_NO_XID	NUMBER	1 if NO_XID open option is set, otherwise 0
CONVERT_OPT_GETVALUE	NUMBER	1 if GETVALUE convert option is set, otherwise 0
CONVERT_OPT_PUTVALUE	NUMBER	1 if PUTVALUE convert option is set, otherwise 0
CONVERT_OPT_NOVALUE	NUMBER	1 if NOVALUE convert option is set, otherwise 0
CONVERT_OPT_DUBVALUE	NUMBER	1 if DUBVALUE convert option is set, otherwise 0
CONVERT_OPT_NOQUEUE	NUMBER	1 if NOQUEUE convert option is set, otherwise 0
CONVERT_OPT_EXPRESS	NUMBER	1 if EXPRESS convert option is set, otherwise 0
CONVERT_OPT_NODEADLOCKWAIT	NUMBER	1 if NODEADLOCKWAIT convert option is set, otherwise 0
CONVERT_OPT_NODEADLOCKBLOCK	NUMBER	1 if NODEADLOCKBLOCK convert option is set, otherwise 0
WHICH_QUEUE	NUMBER	Which queue the lock is currently located. 0 for NULL queue; 1 for GRANTED queue; 2 for CONVERT queue.
STATE	VARCHAR2 (64)	State of lock as owner sees it
AST_EVENT0	NUMBER	Last AST event
OWNER_NODE	NUMBER	Node identifier
BLOCKED	NUMBER	1 if this lock request is blocked by others, otherwise 0
BLOCKER	NUMBER	1 if this lock is blocking others, otherwise 0

V\$GES_CONVERT_LOCAL

V\$GES_CONVERT_LOCAL displays statistics for local GES enqueue operations. This view records average convert times, count information, and timed statistics for global enqueue requests.

Column	Datatype	Description
INST_ID	NUMBER	ID of the instance

Column	Datatype	Description
CONVERT_TYPE	VARCHAR2 (16)	Conversion type: ■ NULL -> SS - NULL mode to subshared mode ■ NULL -> SX - NULL mode to shared exclusive mode ■ NULL -> S - NULL mode to shared mode ■ NULL -> SSX - NULL mode to subshared exclusive mode ■ NULL -> X - NULL mode to exclusive mode ■ SS -> SX - Subshared mode to shared exclusive mode ■ SS -> S - Subshared mode to shared mode ■ SS -> SSX - Subshared mode to subshared exclusive mode ■ SS -> X - Subshared mode to exclusive mode ■ SX -> S - Shared exclusive mode to shared mode ■ SX -> SSX - Shared exclusive mode to subshared exclusive mode ■ SX -> X - Shared exclusive mode to exclusive mode ■ S -> SX - Shared mode to shared exclusive mode ■ S -> SSX - Shared mode to subshared exclusive mode ■ S -> X - Shared mode to exclusive mode ■ SSX -> X - Sub-shared exclusive mode to exclusive mode
AVERAGE_CONVERT_TIME	NUMBER	Average conversion time for each type of lock operation (in hundredths of a second)
CONVERT_COUNT	NUMBER	Number of operations

V\$GES_CONVERT_REMOTE

V\$GES_CONVERT_REMOTE displays values for remote GES enqueue conversions. This view records average convert times, count information, and timed statistics for global enqueue requests.

Column	Datatype	Description
INST_ID	NUMBER	ID of the instance
CONVERT_TYPE	VARCHAR2 (16)	Conversion type: ■ NULL -> SS - NULL mode to subshared mode ■ NULL -> SX - NULL mode to shared exclusive mode ■ NULL -> S - NULL mode to shared mode ■ NULL -> SSX - NULL mode to subshared exclusive mode ■ NULL -> X - NULL mode to exclusive mode ■ SS -> SX - Subshared mode to shared exclusive mode ■ SS -> S - Subshared mode to shared mode ■ SS -> SSX - Subshared mode to subshared exclusive mode ■ SS -> X - Subshared mode to exclusive mode ■ SX -> S - Shared exclusive mode to shared mode ■ SX -> SSX - Shared exclusive mode to subshared exclusive mode ■ SX -> X - Shared exclusive mode to exclusive mode ■ S -> SX - Shared mode to shared exclusive mode ■ S -> SSX - Shared mode to subshared exclusive mode ■ S -> X - Shared mode to exclusive mode ■ SSX -> X - Sub-shared exclusive mode to exclusive mode
AVERAGE_CONVERT_TIME	NUMBER	Average conversion time for each type of lock operation (in hundredths of a second)
CONVERT_COUNT	NUMBER	Number of operations

V\$GES_ENQUEUE

V\$GES_ENQUEUE describes all locks currently known to lock manager. This is a Real Application Clusters view.

See Also: ["V\\$GES_BLOCKING_ENQUEUE"](#) on page 7-105 for a description of all such locks that are currently blocking or being blocked

Column	Datatype	Description
HANDLE	RAW(4 8)	Lock pointer
GRANT_LEVEL	VARCHAR2(9)	Granted level of the lock
REQUEST_LEVEL	VARCHAR2(9)	Requested level of the lock
RESOURCE_NAME1	VARCHAR2(30)	Resource name for the lock
RESOURCE_NAME2	VARCHAR2(30)	Resource name for the lock
PID	NUMBER	Process identifier which holds the lock
TRANSACTION_ID0	NUMBER	Lower 4 bytes of the transaction identifier to which the lock belongs
TRANSACTION_ID1	NUMBER	Upper 4 bytes of the transaction identifier to which the lock belongs
GROUP_ID	NUMBER	Group identifier for the lock
OPEN_OPT_DEADLOCK	NUMBER	1 if DEADLOCK open option is set, otherwise 0
OPEN_OPT_PERSISTENT	NUMBER	1 if PERSISTENT open option is set, otherwise 0
OPEN_OPT_PROCESS_OWNED	NUMBER	1 if PROCESS_OWNED open option is set, otherwise 0
OPEN_OPT_NO_XID	NUMBER	1 if NO_XID open option is set, otherwise 0
CONVERT_OPT_GETVALUE	NUMBER	1 if GETVALUE convert option is set, otherwise 0
CONVERT_OPT_PUTVALUE	NUMBER	1 if PUTVALUE convert option is set, otherwise 0
CONVERT_OPT_NOVALUE	NUMBER	1 if NOVALUE convert option is set, otherwise 0
CONVERT_OPT_DUBVALUE	NUMBER	1 if DUBVALUE convert option is set, otherwise 0
CONVERT_OPT_NOQUEUE	NUMBER	1 if NOQUEUE convert option is set, otherwise 0
CONVERT_OPT_EXPRESS	NUMBER	1 if EXPRESS convert option is set, otherwise 0
CONVERT_OPT_NODEADLOCKWAIT	NUMBER	1 if NODEADLOCKWAIT convert option is set, otherwise 0
CONVERT_OPT_NODEADLOCKBLOCK	NUMBER	1 if NODEADLOCKBLOCK convert option is set, otherwise 0
WHICH_QUEUE	NUMBER	Which queue the lock is currently located. 0 for NULL queue; 1 for GRANTED queue; 2 for CONVERT queue.
STATE	VARCHAR2(64)	State of the lock as the owner sees it
AST_EVENT0	NUMBER	Last AST event
OWNER_NODE	NUMBER	Node identifier
BLOCKED	NUMBER	1 if this lock request is blocked by others, otherwise 0
BLOCKER	NUMBER	1 if this lock is blocking others, otherwise 0

V\$GES_LATCH

V\$GES_LATCH is deprecated.

See Also: ["V\\$LATCH"](#) on page 8-10 for statistics about GES latch performance

V\$GES_RESOURCE

V\$GES_RESOURCE is a Real Application Clusters view. It displays information of all resources currently known to the lock manager.

Column	Datatype	Description
RESP	RAW (4 8)	Resource pointer
RESOURCE_NAME	VARCHAR2 (30)	Resource name in hexadecimal for the lock
ON_CONVERT_Q	NUMBER	1 if on convert queue, 0 otherwise
ON_GRANT_Q	NUMBER	1 if on granted queue, 0 otherwise
PERSISTENT_RES	NUMBER	1 if it is a persistent resource, 0 otherwise
MASTER_NODE	NUMBER	Master node ID
NEXT_CVT_LEVEL	VARCHAR2 (9)	Next lock level to convert on global convert queue
VALUE_BLK_STATE	VARCHAR2 (32)	State of the value block
VALUE_BLK	VARCHAR2 (64)	First 64 bytes of the value block

V\$GES_STATISTICS

V\$GES_STATISTICS displays miscellaneous GES statistics.

Column	Datatype	Description
STATISTIC#	NUMBER	Statistic number
NAME	VARCHAR2 (64)	Name of the statistic
VALUE	NUMBER	Value associated with the statistic

V\$GLOBAL_BLOCKED_LOCKS

V\$GLOBAL_BLOCKED_LOCKS displays global blocked locks.

Column	Datatype	Description
ADDR	RAW (4 8)	Address of lock state object
KADDR	RAW (4 8)	Address of lock
SID	NUMBER	Identifier of session holding the lock (number)
TYPE	VARCHAR2 (2)	Resource type (char)
ID1	NUMBER	Resource identifier #1 (number)
ID2	NUMBER	Resource identifier #2 (number)
LMODE	NUMBER	Lock mode held (number)
REQUEST	NUMBER	Lock mode requested (number)
CTIME	NUMBER	Time since current mode was granted

V\$GLOBAL_TRANSACTION

V\$GLOBAL_TRANSACTION displays information on the currently active global transactions.

Column	Datatype	Description
FORMATID	NUMBER	Format identifier of the global transaction

Column	Datatype	Description
GLOBALID	RAW (64)	Global transaction identifier of the global transaction
BRANCHID	RAW (64)	Branch qualifier of the global transaction
BRANCHES	NUMBER	Total number of branches in the global transaction
REFCOUNT	NUMBER	Number of siblings for the global transaction (must be the same as branches)
PREPARECOUNT	NUMBER	Number of branches of the global transaction that have prepared
STATE	VARCHAR2 (38)	State of the branch of the global transaction: - ACTIVE - COLLECTING - FINALIZED - FAILED - RECOVERING - UNASSOCIATED - FORGOTTEN - READY FOR RECOVERY - NO-READONLY FAILED - SIBLING INFO WRITTEN [ORACLE COORDINATED] ACTIVE [ORACLE COORDINATED] COLLECTING [ORACLE COORDINATED] FINALIZED [ORACLE COORDINATED] FAILED [ORACLE COORDINATED] RECOVERING [ORACLE COORDINATED] UNASSOCIATED [ORACLE COORDINATED] FORGOTTEN [ORACLE COORDINATED] READY FOR RECOVERY [ORACLE COORDINATED] NO-READONLY FAILED [MULTINODE] ACTIVE [MULTINODE] COLLECTING [MULTINODE] FINALIZED [MULTINODE] FAILED [MULTINODE] RECOVERING [MULTINODE] UNASSOCIATED [MULTINODE] FORGOTTEN [MULTINODE] READY FOR RECOVERY [MULTINODE] NO-READONLY FAILED [MULTINODE] SIBLING INFO WRITTEN - COMBINATION
FLAGS	NUMBER	The numerical representation of the state
COUPLING	VARCHAR2 (15)	Indicates whether the branches are free (FREE), loosely coupled (LOOSELY COUPLED), or tightly coupled (TIGHTLY COUPLED)

V\$HM_CHECK

V\$HM_CHECK displays information about all the checks registered with Health Monitor. Each check is uniquely identified by a name or an ID.

Column	Datatype	Description
ID	NUMBER	Health check ID

Column	Datatype	Description
NAME	VARCHAR2 (64)	Health check name
NAME_NLS	VARCHAR2 (1024)	Internationalized names of the health checks
CLSID	NUMBER	Class ID to which this check belongs
CLS_NAME	VARCHAR2 (15)	Class name of the check: ■ GENERIC ■ PERSISTENT_DATA
FLAGS	NUMBER	Reserved for internal use
INTERNAL_CHECK	VARCHAR2 (1)	Internal check
OFFLINE_CAPABLE	VARCHAR2 (1)	Ability to run when database is not open yet (Y or N)
DESCRIPTION	VARCHAR2 (64)	Description of what the check does

V\$HM_CHECK_PARAM

V\$HM_CHECK_PARAM displays information about the input parameters of all Health Monitor checks.

Column	Datatype	Description
ID	NUMBER	Parameter ID
NAME	VARCHAR2 (64)	Parameter name
CHECK_ID	NUMBER	ID of the check to which this parameter belongs
TYPE	VARCHAR2 (20)	Data type of the input parameter: ■ DBKH_PARAM_UB4 ■ DBKH_PARAM_UB8 ■ DBKH_PARAM_TEXT ■ DBKH_PARAM_DATE ■ DBKH_PARAM_UB4_LIST ■ DBKH_PARAM_UB8_LIST ■ DBKH_PARAM_TEXT_LIST ■ DBKH_PARAM_DATE_LIST
DEFAULT_VALUE	VARCHAR2 (64)	Default value for this parameter
FLAGS	NUMBER	Reserved for internal use
DESCRIPTION	VARCHAR2 (64)	Description of the parameter

V\$HM_FINDING

V\$HM_FINDING displays information about all the findings of various Health Monitor runs.

Column	Datatype	Description
FINDING_ID	NUMBER	Unique ID to represent the finding
RUN_ID	NUMBER	ID of the run that created this finding
NAME	VARCHAR2 (32)	Name of the finding
PARENT_ID	NUMBER	Parent finding ID for this finding
CHILD_COUNT	NUMBER	Number of active (open) child findings, if this finding is a parent finding type
CLASS_NAME	VARCHAR2 (32)	Name of the class to which this finding belongs
TIME_DETECTED	TIMESTAMP (6)	Time this finding was detected

Column	Datatype	Description
MODIFIED	TIMESTAMP (6)	Time that this finding was last modified
PRIORITY	VARCHAR2 (8)	Priority of the finding: ■ LOW, ■ HIGH ■ CRITICAL
STATUS	VARCHAR2 (12)	Status of the finding: ■ OPEN ■ CLOSED
TYPE	VARCHAR2 (13)	Type of the finding: ■ INFORMATIONAL ■ FAILURE
DESCRIPTION	VARCHAR2 (1024)	Description of the finding
DAMAGE_DESCRIPTION	VARCHAR2 (1024)	Possible damage description of the finding

V\$HM_INFO

V\$HM_INFO displays information about Health Monitor runs, findings, and recommendations. The information for a run/finding/recommendation is organized as a name, value pair.

If the type of information is RUN, then the data represents the input parameters for that run. If the type of information is FINDING or RECOMMENDATION, then the data represents the information about that particular finding/recommendation.

Column	Datatype	Description
ID	NUMBER	Unique identifier of the information
TYPE	VARCHAR2 (14)	Type of the information: ■ RUN ■ RUN-RESUME ■ FINDING ■ RECOMMENDATION
NAME	VARCHAR2 (32)	Information parameter name
VALUE	VARCHAR2 (513)	Information parameter value

V\$HM_RECOMMENDATION

V\$HM_RECOMMENDATION displays information about all the recommendations made to various Health Monitor findings.

Column	Datatype	Description
RECOMMENDATION_ID	NUMBER	Unique ID to represent the recommendation
FDG_ID	NUMBER	Unique ID to represent either the finding ID or the finding set ID for which the recommendation was made
RUN_ID	NUMBER	ID of the run that may have generated the recommendation If the ID is 0, then the recommendations were generated by RMAN.
NAME	VARCHAR2 (32)	Name of the recommendation
TYPE	VARCHAR2 (7)	Type of the recommendation: ■ MANUAL ■ REPAIR

Column	Datatype	Description
RANK	NUMBER	Rank of the recommendation
TIME_DETECTED	TIMESTAMP (6)	Time that the recommendation was made
EXECUTED	TIMESTAMP (6)	Time that the recommendation (repair) was implemented
STATUS	VARCHAR2 (7)	Status of the recommendation (repair) execution: ■ NOT RUN ■ RUNNING ■ SUCCESS ■ FAILED
DESCRIPTION	VARCHAR2 (1024)	Description of the recommendation
REPAIR_SCRIPT	VARCHAR2 (512)	Location of the repair script file

V\$HM_RUN

V\$HM_RUN displays information about all Health Monitor checks and their status.

Column	Datatype	Description
RUN_ID	NUMBER	Unique ID to represent the run
NAME	VARCHAR2 (32)	Unique name used to identify the run
CHECK_NAME	VARCHAR2 (32)	Name of the check
RUN_MODE	VARCHAR2 (8)	Mode of the run: ■ MANUAL ■ REACTIVE ■ AUTO
TIMEOUT	NUMBER	Number of seconds allowed for this run to complete before it is aborted
START_TIME	TIMESTAMP (6)	Start time of the run
LAST_RESUME_TIME	TIMESTAMP (6)	Last resumed time for the run
END_TIME	TIMESTAMP (6)	End time of the run
MODIFIED_TIME	TIMESTAMP (6)	Last modified time of the run record
STATUS	VARCHAR2 (11)	Status of the run: ■ INITIAL ■ EXECUTING ■ INTERRUPTED ■ TIMEDOUT ■ CANCELLED ■ COMPLETED ■ ERROR
SRC_INCIDENT	NUMBER	Source incident ID that activated this run
NUM_INCIDENT	NUMBER	Number of incidents created by this run
ERROR_NUMBER	NUMBER	Error number if the run failed to complete because of an error
PROBLEM_ID	NUMBER	Problem ID of the source incident ID that may have activated this Run

V\$HS_AGENT

V\$HS_AGENT displays the set of HS agents currently running on a given host. There is one row per agent process.

V\$HS_PARAMETER

Column	Datatype	Description
AGENT_ID	NUMBER	Oracle Net session identifier used for connections to the agent (the identifier used in the LISTENER.ORA file)
MACHINE	VARCHAR2 (64)	Operating system machine name
PROCESS	VARCHAR2 (9)	Operating system process identifier of the agent
PROGRAM	VARCHAR2 (48)	Program name of the agent
OSUSER	VARCHAR2 (30)	Operating system user
STARTTIME	DATE	Starting time
AGENT_TYPE	NUMBER	Type of the agent
FDS_CLASS_ID	NUMBER	ID of the Foreign Data Store class
FDS_INST_ID	NUMBER	Instance name of the Foreign Data Store

V\$HS_PARAMETER

V\$HS_PARAMETER describes the initialization parameters in use by the server and agent.

Column	Datatype	Description
HS_SESSION_ID	NUMBER	Unique HS session identifier (maps to the HS_SESSION_ID column of V\$HS_SESSION)
PARAMETER	VARCHAR2 (30)	Name of the parameter
VALUE	VARCHAR2 (64)	Value of the parameter
SOURCE	VARCHAR2 (1)	Indicates whether the parameter was defined in the agent (A) or server (S)
ENV	VARCHAR2 (1)	Indicates whether the parameter was set as an environment variable in the agent (T) or elsewhere (F)

V\$HS_SESSION

V\$HS_SESSION describes the current HS session.

Column	Datatype	Description
HS_SESSION_ID	NUMBER	Unique HS session identifier
AGENT_ID	NUMBER	Oracle Net session identifier used for connections to the agent (maps to the AGENT_ID column of V\$HS_AGENT)
SID	NUMBER	User session identifier (maps to the SID column of V\$SESSION)
DB_LINK	VARCHAR2 (128)	Server database link name used to access the agent; blank if no database link is used (for example, when using external procedures)
DB_LINK_OWNER	NUMBER	Owner of the database link in DB_LINK
STARTTIME	DATE	Time the connection was initiated

V\$HVMASTER_INFO

V\$HVMASTER_INFO describes the current and previous master instances and the number of re-masterings of Global Enqueue Service resources.

Column	Datatype	Description
HV_ID	NUMBER	Hash value ID
CURRENT_MASTER	NUMBER	Master instance of this hash value ID
PREVIOUS_MASTER	NUMBER	Previous master instance of this hash value ID

Column	Datatype	Description
REMASTER_CNT	NUMBER	Number of times this has been remastered

Dynamic Performance (V\$) Views: V\$INDEXED_FIXED_COLUMN to V\$RULE_ SET_AGGREGATE_STATS

This chapter contains the dynamic performance views V\$INDEXED_FIXED_COLUMN to V\$RULE_SET_AGGREGATE_STATS.

V\$INDEXED_FIXED_COLUMN

V\$INDEXED_FIXED_COLUMN displays the columns in dynamic performance tables that are indexed (X\$ tables). The X\$ tables can change without notice. Use this view only to write queries against fixed views (V\$ views) more efficiently.

Column	Datatype	Description
TABLE_NAME	VARCHAR2 (30)	Name of the dynamic performance table that is indexed
INDEX_NUMBER	NUMBER	Number that distinguishes to which index a column belongs
COLUMN_NAME	VARCHAR2 (30)	Name of the column that is being indexed
COLUMN_POSITION	NUMBER	Position of the column in the index key (this is mostly relevant for multicolumn indexes)

V\$INSTANCE

V\$INSTANCE displays the state of the current instance.

Column	Datatype	Description
INSTANCE_NUMBER	NUMBER	Instance number used for instance registration (corresponds to the INSTANCE_NUMBER initialization parameter) See Also: "INSTANCE_NUMBER" on page 1-77
INSTANCE_NAME	VARCHAR2 (16)	Name of the instance
HOST_NAME	VARCHAR2 (64)	Name of the host machine
VERSION	VARCHAR2 (17)	Database version
STARTUP_TIME	DATE	Time when the instance was started
STATUS	VARCHAR2 (12)	Status of the instance: - STARTED - After STARTUP NOMOUNT - MOUNTED - After STARTUP MOUNT or ALTER DATABASE CLOSE - OPEN - After STARTUP or ALTER DATABASE OPEN - OPEN MIGRATE - After ALTER DATABASE OPEN { UPGRADE DOWNGRADE }

Column	Datatype	Description
PARALLEL	VARCHAR2 (3)	Indicates whether the instance is mounted in cluster database mode (YES) or not (NO)
THREAD#	NUMBER	Redo thread opened by the instance
ARCHIVER	VARCHAR2 (7)	Automatic archiving status: ■ STOPPED ■ STARTED ■ FAILED - Archiver failed to archive a log last time but will try again within 5 minutes
LOG_SWITCH_WAIT	VARCHAR2 (15)	Event that log switching is waiting for: ■ ARCHIVE LOG ■ CLEAR LOG ■ CHECKPOINT ■ NULL - ALTER SYSTEM SWITCH LOGFILE is hung but there is room in the current online redo log
LOGINS	VARCHAR2 (10)	Indicates whether the instance is in unrestricted mode, allowing logins by all users (ALLOWED), or in restricted mode, allowing logins by database administrators only (RESTRICTED)
SHUTDOWN_PENDING	VARCHAR2 (3)	Indicates whether a shutdown is pending (YES) or not (NO)
DATABASE_STATUS	VARCHAR2 (17)	Status of the database: ■ ACTIVE ■ SUSPENDED ■ INSTANCE RECOVERY
INSTANCE_ROLE	VARCHAR2 (18)	Indicates whether the instance is an active instance (PRIMARY_INSTANCE) or an inactive secondary instance (SECONDARY_INSTANCE), or UNKNOWN if the instance has been started but not mounted
ACTIVE_STATE	VARCHAR2 (9)	Quiesce state of the instance: ■ NORMAL - Database is in a normal state. ■ QUIESCING - ALTER SYSTEM QUIESCE RESTRICTED has been issued: no new user transactions, queries, or PL/SQL statements are processed in this instance. User transactions, queries, or PL/SQL statements issued before the ALTER SYSTEM QUIESCE RESTRICTED statement are unaffected. DBA transactions, queries, or PL/SQL statements are also unaffected. ■ QUIESCED - ALTER SYSTEM QUIESCE RESTRICTED has been issued: no user transactions, queries, or PL/SQL statements are processed. DBA transactions, queries, or PL/SQL statements are unaffected. User transactions, queries, or PL/SQL statements issued after the ALTER SYSTEM QUIESCE RESTRICTED statement are not processed. A single ALTER SYSTEM QUIESCE RESTRICTED statement quiesces all instances in an Oracle RAC environment. After this statement has been issued, some instances may enter into a quiesced state before other instances; the system is quiesced when all instances enter the quiesced state.
BLOCKED	VARCHAR2 (3)	Indicates whether all services are blocked (YES) or not (NO)

V\$INSTANCE_CACHE_TRANSFER

V\$INSTANCE_CACHE_TRANSFER displays statistics for the cache blocks transferred among instances.

Oracle keeps multiple versions of data buffered in the buffer cache. The current buffer (or block), CURRENT_BLOCK, is the most up-to-date copy, containing all recent modifications. A consistent read buffer (or block), CR_BLOCK, contains the version of the data at a particular time prior to the current buffer. It is read-consistent (that is, all the data shown in that buffer are consistent for the start time of a query).

Therefore, for the same data block there can be multiple copies in the buffer cache: one current copy, and one or more consistent read copies with data consistent as of different snapshot times.

Column	Datatype	Description
INSTANCE	NUMBER	Instance from which the blocks are transferred
CLASS	VARCHAR2 (18)	Class of the cache block
LOST	NUMBER	The number of blocks that were sent by a particular instance but that never arrived in this instance
LOST_TIME	NUMBER	The time waited for blocks that were sent by a particular instance but that never arrived in this instance
CR_BLOCK	NUMBER	CR Block transfers not affected by remote processing delays
CR_BLOCK_TIME	NUMBER	Total time waited for CR blocks from a particular instance (includes the other times)
CR_2HOP	NUMBER	The count of CR blocks which were received by this instance from a particular instance after a 2-way round-trip
CR_2HOP_TIME	NUMBER	The time waited for CR blocks which were received by this instance from a particular instance after a 2-way round-trip
CR_3HOP	NUMBER	The count of CR blocks which were received by this instance from a particular instance after a 3-way round-trip
CR_3HOP_TIME	NUMBER	The time waited for CR blocks which were received by this instance from a particular instance after a 3-way round-trip
CR_BUSY	NUMBER	CR Block transfers affected by remote contention
CR_BUSY_TIME	NUMBER	The time waited for CR blocks which were received by this instance from a particular instance and which were delayed by a log flushed on the sending instance
CR_CONGESTED	NUMBER	CR Block transfers affected by remote system load
CR_CONGESTED_TIME	NUMBER	The time waited for CR blocks which were received by this instance from a particular instance and which were delayed because LMS was busy
CURRENT_BLOCK	NUMBER	Current block transfers not affected by remote processing delays
CURRENT_BLOCK_TIME	NUMBER	Total time waited for current blocks from a particular instance (includes the other times)
CURRENT_2HOP	NUMBER	The count of current blocks which were received by this instance from a particular instance after a 2-way roundtrip
CURRENT_2HOP_TIME	NUMBER	The time waited for current blocks which were received by this instance from a particular instance after a 2-way roundtrip
CURRENT_3HOP	NUMBER	The count of current blocks which were received by this instance from a particular instance after a 3-way roundtrip
CURRENT_3HOP_TIME	NUMBER	The time waited for current blocks which were received by this instance from a particular instance after a 3-way roundtrip
CURRENT_BUSY	NUMBER	Current block transfers affected by remote contention
CURRENT_BUSY_TIME	NUMBER	The time waited for current blocks which were received by this instance from a particular instance and which were delayed by a log flushed on the sending instance
CURRENT_CONGESTED	NUMBER	Current block transfers affected by remote system load
CURRENT_CONGESTED_TIME	NUMBER	The time waited for current blocks which were received by this instance from a particular instance and which were delayed because LMS was busy

V\$INSTANCE_RECOVERY

V\$INSTANCE_RECOVERY monitors the mechanisms available to users to limit recovery I/O. Those mechanisms are:

- Set the LOG_CHECKPOINT_TIMEOUT initialization parameter

- Set the LOG_CHECKPOINT_INTERVAL initialization parameter
- Set the FAST_START_MTTR_TARGET initialization parameter
- Set the size of the smallest redo log

Column	Datatype	Description
RECOVERY_ESTIMATED_IOS	NUMBER	Number of dirty buffers in the buffer cache. In the Standard Edition, this column is always null.
ACTUAL_REDO_BKLS	NUMBER	Current actual number of redo blocks required for recovery
TARGET_REDO_BKLS	NUMBER	Current target number of redo blocks that must be processed for recovery. This value is the minimum value of the following 3 columns, and identifies which of the 3 user-defined limits determines checkpointing.
LOG_FILE_SIZE_REDO_BKLS	NUMBER	Maximum number of redo blocks required to guarantee that a log switch does not occur before the checkpoint completes.
LOG_CHKPT_TIMEOUT_REDO_BKLS	NUMBER	Number of redo blocks that need to be processed during recovery to satisfy the LOG_CHECKPOINT_TIMEOUT parameter. The value displayed is not meaningful unless that parameter has been set.
LOG_CHKPT_INTERVAL_REDO_BKLS	NUMBER	Number of redo blocks that need to be processed during recovery to satisfy the LOG_CHECKPOINT_INTERVAL parameter. The value displayed is not meaningful unless that parameter has been set.
FAST_START_IO_TARGET_REDO_BKLS	NUMBER	This column is obsolete and maintained for backward compatibility. The value of this column is always null.
TARGET_MTTR	NUMBER	Effective MTTR (mean time to recover) target value in seconds. The TARGET_MTTR value is calculated based on the value of the FAST_START_MTTR_TARGET parameter (the TARGET_MTTR value is used internally), and is usually an approximation of the parameter's value. However, if the FAST_START_MTTR_TARGET parameter value is very small (for example, one second), or very large (for example, 3600 seconds), the calculation will produce a target value dictated by system limitations. In such cases, the TARGET_MTTR value will be the shortest calculated time, or the longest calculated time that recovery is expected to take. If FAST_START_MTTR_TARGET is not specified, the value of this field is the current estimated MTTR.
ESTIMATED_MTTR	NUMBER	Current estimated mean time to recover (MTTR) based on the number of dirty buffers and log blocks (0 if FAST_START_MTTR_TARGET is not specified). Basically, this value tells you how long you could expect recovery to take based on the work your system is doing right now.
CKPT_BLOCK_WRITES	NUMBER	Number of blocks written by checkpoint writes
OPTIMAL_LOGFILE_SIZE	NUMBER	Redo log file size (in megabytes) that is considered optimal based on the current setting of FAST_START_MTTR_TARGET. It is recommended that the user configure all online redo logs to be at least this value. Note that redo log files must be at least 4 megabytes in size; otherwise an error is generated.
ESTD_CLUSTER_AVAILABLE_TIME	NUMBER	Estimated time (in seconds) that the cluster would become partially available should this instance fail. This column is only meaningful in an Oracle Real Application Clusters (Oracle RAC) environment. In a non-Oracle RAC environment, the value of this column is null.
WRITES_MTTR	NUMBER	Number of writes driven by the FAST_START_MTTR_TARGET initialization parameter
WRITES_LOGFILE_SIZE	NUMBER	Number of writes driven by the smallest redo log file size
WRITES_LOG_CHECKPOINT_SETTINGS	NUMBER	Number of writes driven by the LOG_CHECKPOINT_INTERVAL or LOG_CHECKPOINT_TIMEOUT initialization parameter
WRITES_OTHER_SETTINGS	NUMBER	Number of writes driven by other reasons (such as the deprecated FAST_START_IO_TARGET initialization parameter)
WRITES_AUTOTUNE	NUMBER	Number of writes due to auto-tune checkpointing
WRITES_FULL_THREAD_CKPT	NUMBER	Number of writes due to full thread checkpoints

See Also:

- *Oracle Database Performance Tuning Guide* for more information on limiting recovery I/O, and how Oracle determines MTTR recovery times
- [LOG_CHECKPOINT_INTERVAL](#) on page 1-98
- [FAST_START_MTTR_TARGET](#) on page 1-69

V\$IO_CALIBRATION_STATUS

V\$IO_CALIBRATION_STATUS displays the status of I/O calibration in the instance.

Column	Datatype	Description
STATUS	VARCHAR2 (13)	Calibration status: ■ IN_PROGRESS - Calibration in Progress (Results from a previous calibration run are displayed, if available) ■ READY Results are ready and available from an earlier run ■ NOT_AVAILABLE Calibration results are not available
CALIBRATION_TIME	TIMESTAMP (3)	End time of the last calibration run

V\$IOFUNKMETRIC

V\$IOFUNKMETRIC displays I/O statistics information by database function for the most recent time interval period.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time for the metric value
END_TIME	DATE	End time for the metric value
INTSIZE_CSEC	NUMBER	Size of the time period
FUNCTION_ID	NUMBER	Function ID
FUNCTION_NAME	VARCHAR2 (18)	Function name
SMALL_READ_MBPS	NUMBER	Single block megabytes read per second
SMALL_WRITE_MBPS	NUMBER	Single block megabytes written per second
LARGE_READ_MBPS	NUMBER	Multiblock megabytes read per second
LARGE_WRITE_MBPS	NUMBER	Multiblock megabytes written per second
SMALL_READ_IOPS	NUMBER	Single block read requests per second
SMALL_WRITE_IOPS	NUMBER	Single block write requests per second
LARGE_READ_IOPS	NUMBER	Multiblock read requests per second
LARGE_WRITE_IOPS	NUMBER	Multiblock write requests per second
AVG_WAIT_TIME	NUMBER	Average wait time (in milliseconds)

V\$IOFUNKMETRIC_HISTORY

V\$IOFUNKMETRIC_HISTORY displays a recent history of the I/O statistics information by database function for the most recent time interval period.

The columns for V\$IOFUNKMETRIC_HISTORY are the same as those for V\$IOFUNKMETRIC.

See Also: ["V\\$IOFUNKMETRIC"](#) on page 8-5

V\$IOSTAT_CONSUMER_GROUP

V\$IOSTAT_CONSUMER_GROUP displays disk I/O statistics for consumer groups. If the resource manager is enabled, then I/O statistics for all consumer groups that are part of the currently enabled resource plan are captured.

Column	Datatype	Description
CONSUMER_GROUP_ID	NUMBER	Consumer Group ID
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	Number of single block write requests
LARGE_READ_REQS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	Number of I/O waits by consumer group
WAIT_TIME	NUMBER	Total wait time (in milliseconds)

V\$IOSTAT_FILE

V\$IOSTAT_FILE displays information about disk I/O statistics of database files (including data files, temp files, and other types of database files). I/O statistics for Data files and Temp files are provided for each file. All other file types (for example, control files, log files, archive logs, and so on) have their statistics consolidated into one entry in the view.

Column	Datatype	Description
FILE_NO	NUMBER	File identification number
FILETYPE_ID	VARCHAR2 (25)	Type of file (for example, log file, data file, and so on)
FILETYPE_NAME	VARCHAR2 (28)	Name of the file, in the case of a data file or temp file. For all other files, a corresponding string to be displayed (for example, ARCHIVELOG).
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	Number of single block write requests
SMALL_SYNC_READ_REQS	NUMBER	Number of synchronous single block read requests
LARGE_READ_REQS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	Number of multiblock write requests
SMALL_READ_SERVICETIME	NUMBER	Total service time (in milliseconds) for single block read requests
SMALL_WRITE_SERVICETIME	NUMBER	Total service time (in milliseconds) for single block write requests
SMALL_SYNC_READ_LATENCY	NUMBER	Latency for single block synchronous reads (in milliseconds)

Column	Datatype	Description
LARGE_READ_SERVICETIME	NUMBER	Total service time (in milliseconds) for multiblock read requests
LARGE_WRITE_SERVICETIME	NUMBER	Total service time (in milliseconds) for multiblock write requests
ASYNCH_IO	VARCHAR2 (9)	Indicates whether asynchronous I/O is available for the file (ASYNC_ON) or not (ASYNC_OFF)
ACCESS_METHOD	VARCHAR2 (11)	I/O library used to access the file. Possible values include: ■ OS_LIB - OS system calls are used to access the file ■ ODM_LIB - Oracle Disk Manager library is used to access the file ■ ASM_MANAGED - The file is managed and accessed through ASM ■ DNFS_LIB - The file is accessed through direct NFS library
RETRIES_ON_ERROR	NUMBER	Number of read retries on error

V\$IOSTAT_FUNCTION

V\$IOSTAT_FUNCTION displays disk I/O statistics for database functions (such as the LGWR and DBWR).

Column	Datatype	Description
FUNCTION_ID	NUMBER	Function ID
FUNCTION_NAME	VARCHAR2 (18)	Function name: ■ RMAN ■ DBWR ■ LGWR ■ ARCH ■ XDB ■ Streams AQ ■ Data Pump ■ Recovery ■ Buffer Cache Reads ■ Direct Reads ■ Direct Writes ■ Smart Scan ■ Archive Manager ■ Others
SMALL_READ_MEGABYTES	NUMBER	Number of megabytes read via single block read requests
SMALL_WRITE_MEGABYTES	NUMBER	Number of megabytes written via single block write requests
LARGE_READ_MEGABYTES	NUMBER	Number of megabytes read via multiblock read requests
LARGE_WRITE_MEGABYTES	NUMBER	Number of megabytes written via multiblock write requests
SMALL_READ_REQS	NUMBER	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	Number of single block write requests
LARGE_READ_REQS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	Number of synchronous I/O waits by functionality
WAIT_TIME	NUMBER	Total synchronous I/O wait time (in milliseconds)

V\$IOSTAT_FUNCTION_DETAIL

V\$IOSTAT_FUNCTION_DETAIL displays disk I/O statistics for database functions (such as the LGWR and DBWR), broken down by file type.

Column	Datatype	Description
FUNCTION_ID	NUMBER	Function ID
FUNCTION_NAME	VARCHAR2 (18)	Function name: ■ RMAN ■ DBWR ■ LGWR ■ ARCH ■ XDB ■ Streams AQ ■ Data Pump ■ Recovery ■ Buffer Cache Reads ■ Direct Reads ■ Direct Writes ■ Smart Scan ■ Archive Manager ■ Others
FILETYPE_ID	NUMBER	File type ID
FILETYPE_NAME	VARCHAR2 (28)	File type name: ■ Control File ■ Data File ■ Log File ■ Archive Log ■ Temp File ■ Data File Backup ■ Data File Incremental Backup ■ Archive Log Backup ■ Data File Copy ■ Flashback Log ■ Data Pump Dump File ■ Other
SMALL_READ_MEGABYTES	NUMBER	Number of megabytes read via single block read requests
SMALL_WRITE_MEGABYTES	NUMBER	Number of megabytes written via single block write requests
LARGE_READ_MEGABYTES	NUMBER	Number of megabytes read via multiblock read requests
LARGE_WRITE_MEGABYTES	NUMBER	Number of megabytes written via multiblock write requests
SMALL_READ_REQS	NUMBER	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	Number of single block write requests
LARGE_READ_REQS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	Number of synchronous I/O waits by functionality
WAIT_TIME	NUMBER	Total synchronous I/O wait time (in milliseconds)

V\$IOSTAT_NETWORK

V\$IOSTAT_NETWORK displays information about network I/O statistics that were caused by accessing files on a remote database instance.

Column	Datatype	Description
CLIENT	VARCHAR2 (32)	Database client name initiating the network I/O (for example, RMAN or PL/SQL)
READS#	NUMBER	Number of read operations issued
WRITES#	NUMBER	Number of write operations issued
KBYTES_READ	NUMBER	Total number of kilobytes read
KBYTES_WRITTEN	NUMBER	Total number of kilobytes written
READ_LATENCY	NUMBER	Total read wait time (in milliseconds)
WRITE_LATENCY	NUMBER	Total write wait time (in milliseconds)

V\$JAVA_LIBRARY_CACHE_MEMORY

V\$JAVA_LIBRARY_CACHE_MEMORY displays information about memory allocated to library cache memory objects in different namespaces for Java objects. A memory object is an internal grouping of memory for efficient management. A library cache object may consist of one or more memory objects.

Column	Datatype	Description
LC_NAMESPACE	VARCHAR2 (15)	Library cache namespace
LC_INUSE_MEMORY_OBJECTS	NUMBER	Number of library cache memory objects currently in use in the Java pool
LC_INUSE_MEMORY_SIZE	NUMBER	Total size of library cache in-use memory objects (in megabytes)
LC_FREEABLE_MEMORY_OBJECTS	NUMBER	Number of freeable library cache memory objects in the Java pool
LC_FREEABLE_MEMORY_SIZE	NUMBER	Size of library cache freeable memory objects (in megabytes)

V\$JAVA_POOL_ADVICE

V\$JAVA_POOL_ADVICE displays information about estimated parse time in the Java pool for different pool sizes. The sizes range from 10% of the current Java pool size or the amount of pinned Java library cache memory (whichever is higher) to 200% of the current Java pool size, in equal intervals. The value of the interval depends on the current size of the Java pool.

Parse time saved refers to the amount of time saved by keeping library cache memory objects in the Java pool, as opposed to having to reload these objects.

Column	Datatype	Description
JAVA_POOL_SIZE_FOR_ESTIMATE	NUMBER	Java pool size for the estimate (in megabytes)
JAVA_POOL_SIZE_FACTOR	NUMBER	Size factor with respect to the current Java pool size
ESTD_LC_SIZE	NUMBER	Estimated memory in use by the library cache (in megabytes)
ESTD_LC_MEMORY_OBJECTS	NUMBER	Estimated number of library cache memory objects in the Java pool of the specified size

Column	Datatype	Description
ESTD_LC_TIME_SAVED	NUMBER	Estimated elapsed parse time saved (in seconds), owing to library cache memory objects being found in a Java pool of the specified size. This is the time that would have been spent in reloading the required objects in the Java pool had they been aged out due to insufficient amount of available free memory.
ESTD_LC_TIME_SAVED_FACTOR	NUMBER	Estimated parse time saved factor with respect to the current Java pool size
ESTD_LC_LOAD_TIME	NUMBER	Estimated elapsed time (in seconds) for parsing in a Java pool of the specified size
ESTD_LC_LOAD_TIME_FACTOR	NUMBER	Estimated load time factor with respect to the current Java pool size
ESTD_LC_MEMORY_OBJECT_HITS	NUMBER	Estimated number of times a library cache memory object was found in a Java pool of the specified size

V\$LATCH

V\$LATCH displays aggregate latch statistics for both parent and child latches, grouped by latch name. Individual parent and child latch statistics are broken down in the views V\$LATCH_PARENT and V\$LATCH_CHILDREN.

Column	Datatype	Description
ADDR	RAW (4 8)	Address of the latch object
LATCH#	NUMBER	Latch number
LEVEL#	NUMBER	Latch level
NAME	VARCHAR2 (64)	Latch name
HASH	NUMBER	Latch hash
GETS	NUMBER	Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER	Number of times the latch was requested in willing-to-wait mode and the requestor had to wait
SLEEPS	NUMBER	Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER	Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER	Number of times a no-wait latch request did not succeed (that is, missed)
WAITERS_WOKEN	NUMBER	This column has been deprecated and is present only for compatibility with previous releases of Oracle. No data is accumulated for this column; it will always have a value of zero.
WAITS_HOLDING_LATCH	NUMBER	This column has been deprecated and is present only for compatibility with previous releases of Oracle. No data is accumulated for this column; it will always have a value of zero.
SPIN_GETS	NUMBER	Willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP [1 2 3 4 5 6 7 8 9 10 11]	NUMBER	These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero. As a substitute for these columns you can query the appropriate rows of the V\$EVENT_HISTOGRAM view where the EVENT column has a value of latch_free or latch: %.
WAIT_TIME	NUMBER	Elapsed time spent waiting for the latch (in microseconds)

See Also:

- ["V\\$LATCH_CHILDREN"](#) on page 8-11
- ["V\\$LATCH_PARENT"](#) on page 8-12

V\$LATCH_CHILDREN

V\$LATCH_CHILDREN displays statistics about child latches. This view includes all columns of V\$LATCH plus the CHILD# column. Note that child latches have the same parent if their LATCH# columns match each other.

Column	Datatype	Description
ADDR	RAW (4 8)	Address of the latch object
LATCH#	NUMBER	Latch number of the parent latch
CHILD#	NUMBER	Child latch number (unique only to each parent latch)
LEVEL#	NUMBER	Latch level
NAME	VARCHAR2 (64)	Latch name
HASH	NUMBER	Latch hash
GETS	NUMBER	Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER	Number of times the latch was requested in willing-to-wait mode and the requestor had to wait
SLEEPS	NUMBER	Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER	Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER	Number of times a no-wait latch request did not succeed (that is, missed)
WAITERS_WOKEN	NUMBER	This column has been deprecated and is present only for compatibility with previous releases of Oracle. No data is accumulated for this column; it will always have a value of zero.
WAITS_HOLDING_LATCH	NUMBER	This column has been deprecated and is present only for compatibility with previous releases of Oracle. No data is accumulated for this column; it will always have a value of zero.
SPIN_GETS	NUMBER	Willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP [1 2 3 4 5 6 7 8 9 10 11]	NUMBER	These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero. As a substitute for these columns you can query the appropriate rows of the V\$EVENT_HISTOGRAM view where the EVENT column has a value of latch_free or latch: %.
WAIT_TIME	NUMBER	Elapsed time spent waiting for the latch (in microseconds)

See Also: "V\$LATCH" on page 8-10

V\$LATCH_MISSES

V\$LATCH_MISSES displays statistics about missed attempts to acquire a latch.

Column	Datatype	Description
PARENT_NAME	VARCHAR2 (64)	Latch name of a parent latch
WHERE	VARCHAR2 (80)	This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in LOCATION.
NWFAIL_COUNT	NUMBER	Number of times that no-wait acquisition of the latch failed
SLEEP_COUNT	NUMBER	Number of times that acquisition attempts caused sleeps
WTR_SLP_COUNT	NUMBER	Number of times a waiter slept
LONGHOLD_COUNT	NUMBER	Number of times someone held a latch for the entire duration of someone else's sleep
LOCATION	VARCHAR2 (80)	Location that attempted to acquire the latch

V\$LATCH_PARENT

V\$LATCH_PARENT displays statistics about parent latches. The columns for V\$LATCH_PARENT are the same as those for V\$LATCH.

See Also: ["V\\$LATCH"](#) on page 8-10

V\$LATCHHOLDER

V\$LATCHHOLDER displays information about the current latch holders.

Column	Datatype	Description
PID	NUMBER	Identifier of the process holding the latch
SID	NUMBER	Identifier of the session that owns the latch
LADDR	RAW (4 8)	Latch address
NAME	VARCHAR2 (64)	Name of the latch being held
GETS	NUMBER	Number of times that the latch was obtained in either wait mode or no-wait mode

V\$LATCHNAME

V\$LATCHNAME displays information about decoded latch names for the latches shown in V\$LATCH. The rows of V\$LATCHNAME have a one-to-one correspondence to the rows of V\$LATCH.

Column	Datatype	Description
LATCH#	NUMBER	Latch number
NAME	VARCHAR2 (64)	Latch name
HASH	NUMBER	Latch hash

See Also: ["V\\$LATCH"](#) on page 8-10

V\$LIBCACHE_LOCKS

V\$LIBCACHE_LOCKS displays information about the library cache locks and pins. Locks and pins are distinguished based on the value of the TYPE column.

Column	Datatype	Description
TYPE	VARCHAR2 (4)	LOCK or PIN
ADDR	RAW (4 8)	Address of the lock/pin
HOLDING_USER_SESSION	RAW (4 8)	User session holding this lock/pin
HOLDING_SESSION	RAW (4 8)	Session holding this lock/pin
OBJECT_HANDLE	RAW (4 8)	Handle address for which the lock/pin is acquired
LOCK_HELD	RAW (4 8)	If the type is LOCK, then LOCK_HELD represents the pin that is pinning the object. If the type is PIN, then LOCK_HELD represents the lock that is locking the object.
REFCOUNT	NUMBER	Reference count for this lock/pin

Column	Datatype	Description
MODE_HELD	NUMBER	Lock/pin mode held: 0 - No lock/pin held 1 - Null mode 2 - Share mode 3 - Exclusive mode
MODE_REQUESTED	NUMBER	Lock/pin mode requested: 0 - No lock/pin requested 1 - Null mode 2 - Share mode 3 - Exclusive mode
SAVEPOINT_NUMBER	NUMBER	Kernel transaction savepoint number at the time the lock/pin was acquired

V\$LIBRARY_CACHE_MEMORY

V\$LIBRARY_CACHE_MEMORY displays information about memory allocated to library cache memory objects in different namespaces. A memory object is an internal grouping of memory for efficient management. A library cache object may consist of one or more memory objects.

Column	Datatype	Description
LC_NAMESPACE	VARCHAR2 (15)	Library cache namespace
LC_INUSE_MEMORY_OBJECTS	NUMBER	Number of library cache memory objects currently in use in the shared pool
LC_INUSE_MEMORY_SIZE	NUMBER	Total size of library cache in-use memory objects (in megabytes)
LC_FREEABLE_MEMORY_OBJECTS	NUMBER	Number of freeable library cache memory objects in the shared pool
LC_FREEABLE_MEMORY_SIZE	NUMBER	Size of library cache freeable memory objects (in megabytes)

V\$LIBRARYCACHE

V\$LIBRARYCACHE contains statistics about library cache performance and activity.

Column	Datatype	Description
NAMESPACE	VARCHAR2 (15)	Library cache namespace
GETS	NUMBER	Number of times a lock was requested for objects of this namespace
GETHITS	NUMBER	Number of times an object's handle was found in memory
GETHITRATIO	NUMBER	Ratio of GETHITS to GETS
PINS	NUMBER	Number of times a PIN was requested for objects of this namespace
PINHITS	NUMBER	Number of times all of the metadata pieces of the library object were found in memory
PINHITRATIO	NUMBER	Ratio of PINHITS to PINS
RELOADS	NUMBER	Any PIN of an object that is not the first PIN performed since the object handle was created, and which requires loading the object from disk
INVALIDATIONS	NUMBER	Total number of times objects in this namespace were marked invalid because a dependent object was modified
DLM_LOCK_REQUESTS	NUMBER	Number of GET requests lock instance locks
DLM_PIN_REQUESTS	NUMBER	Number of PIN requests lock instance locks

Column	Datatype	Description
DLM_PIN_RELEASES	NUMBER	Number of release requests PIN instance locks
DLM_INVALIDATION_REQUESTS	NUMBER	Number of GET requests for invalidation instance locks
DLM_INVALIDATIONS	NUMBER	Number of invalidation pings received from other instances

V\$LICENSE

V\$LICENSE displays information about license limits.

Column	Datatype	Description
SESSIONS_MAX	NUMBER	Maximum number of concurrent user sessions allowed for the instance
SESSIONS_WARNING	NUMBER	Warning limit for concurrent user sessions for the instance
SESSIONS_CURRENT	NUMBER	Current number of concurrent user sessions
SESSIONS_HIGHWATER	NUMBER	Highest number of concurrent user sessions since the instance started
USERS_MAX	NUMBER	Maximum number of named users allowed for the database
CPU_COUNT_CURRENT	NUMBER	Current number of logical CPUs or processors on the system
CPU_CORE_COUNT_CURRENT	NUMBER	Current number of CPU cores on the system (includes subcores of multicore CPUs, as well as single-core CPUs)
CPU_SOCKET_COUNT_CURRENT	NUMBER	Current number of CPU sockets on the system (represents an absolute count of CPU chips on the system, regardless of multithreading or multicore architectures)
CPU_COUNT_HIGHWATER	NUMBER	Highest number of logical CPUs or processors on the system since the instance started
CPU_CORE_COUNT_HIGHWATER	NUMBER	Highest number of CPU cores on the system since the instance started (includes subcores of multicore CPUs, as well as single-core CPUs)
CPU_SOCKET_COUNT_HIGHWATER	NUMBER	Highest number of CPU sockets on the system since the instance started (represents an absolute count of CPU chips on the system, regardless of multithreading or multicore architectures)

Note: The availability of the CPU core count and CPU socket count statistics is subject to the operating system platform on which the Oracle Database is running. If a statistic is unavailable, the view will return NULL for the statistic value.

V\$LOADISTAT

V\$LOADISTAT contains errors that occurred when updating indexes on a table during a load using the Direct Path API.

Column	Datatype	Description
OWNER	VARCHAR2 (31)	Schema name
TABNAME	VARCHAR2 (31)	Table name
INDEXNAME	VARCHAR2 (31)	Index name
SUBNAME	VARCHAR2 (31)	Index sub name
MESSAGE_NUM	NUMBER	Error message number
MESSAGE	VARCHAR2 (4000)	Error message

V\$LOADPSTAT

V\$LOADPSTAT contains statistics about the number of rows loaded into a partition, or subpartition, during a load using the Direct Path API.

Column	Datatype	Description
OWNER	VARCHAR2 (31)	Schema name
TABNAME	VARCHAR2 (31)	Table name
PARTNAME	VARCHAR2 (31)	Partition name
LOADED	NUMBER	Number of rows loaded

V\$LOCK

V\$LOCK lists the locks currently held by the Oracle Database and outstanding requests for a lock or latch.

Column	Datatype	Description
ADDR	RAW (4 8)	Address of lock state object
KADDR	RAW (4 8)	Address of lock
SID	NUMBER	Identifier for session holding or acquiring the lock
TYPE	VARCHAR2 (2)	Type of user or system lock The locks on the user types are obtained by user applications. Any process that is blocking others is likely to be holding one of these locks. The user type locks are: TM - DML enqueue TX - Transaction enqueue UL - User supplied The system type locks are listed in Table 8–1 . Be aware that not all types of locks are documented. To find a complete list of locks for the current release, query the V\$LOCK_TYPE data dictionary view, described on " V\$LOCK_TYPE " on page 8-16.
ID1	NUMBER	Lock identifier #1 (depends on type)
ID2	NUMBER	Lock identifier #2 (depends on type)
LMODE	NUMBER	Lock mode in which the session holds the lock: ■ 0 - none ■ 1 - null (NULL) ■ 2 - row-S (SS) ■ 3 - row-X (SX) ■ 4 - share (S) ■ 5 - S/Row-X (SSX) ■ 6 - exclusive (X)
REQUEST	NUMBER	Lock mode in which the process requests the lock: ■ 0 - none ■ 1 - null (NULL) ■ 2 - row-S (SS) ■ 3 - row-X (SX) ■ 4 - share (S) ■ 5 - S/Row-X (SSX) ■ 6 - exclusive (X)
CTIME	NUMBER	Time since current mode was granted

Column	Datatype	Description
BLOCK	NUMBER	A value of either 0 or 1, depending on whether or not the lock in question is the blocker.

Table 8–1 Values for the TYPE Column: System Types

System Type	Description	System Type	Description
AE	Edition enqueue	MR	Media recovery
AT	Lock held for the ALTER TABLE statement	NA . . NZ	Library cache pin instance (A . . Z = namespace)
BL	Buffer hash table instance	PF	Password File
CF	Control file schema global enqueue	PI , PS	Parallel operation
CI	Cross-instance function invocation instance	PR	Process startup
CU	Cursor bind	QA . . QZ	Row cache instance (A . . Z = cache)
DF	datafile instance	RT	Redo thread global enqueue
DL	Direct loader parallel index create	SC	System change number instance
DM	Mount/startup db primary/secondary instance	SM	SMON
DR	Distributed recovery process	SN	Sequence number instance
DX	Distributed transaction entry	SQ	Sequence number enqueue
FS	File set	SS	Sort segment
HW	Space management operations on a specific segment	ST	Space transaction enqueue
IN	Instance number	SV	Sequence number value
IR	Instance recovery serialization global enqueue	TA	Generic enqueue
IS	Instance state	TS	Temporary segment enqueue (ID2=0)
IV	Library cache invalidation instance	TS	New block allocation enqueue (ID2=1)
JQ	Job queue	TT	Temporary table enqueue
KK	Thread kick	UN	User name
LA . . LP	Library cache lock instance lock (A..P = namespace)	US	Undo segment DDL
MM	Mount definition global enqueue	WL	Being-written redo log instance

V\$LOCK_ACTIVITY

V\$LOCK_ACTIVITY is deprecated. The information that was provided in this view is now provided in the V\$INSTANCE_CACHE_TRANSFER and V\$SEGMENT_STATISTICS views.

Column	Datatype	Description
FROM_VAL	CHAR (4)	Global Cache Resource initial state; always NULL
TO_VAL	CHAR (1)	Global Cache Resource initial state; always S
ACTION_VAL	CHAR (21)	Description of the conversion; always Lock buffers for read
COUNTER	NUMBER	Number of times the lock operation executed

V\$LOCK_TYPE

V\$LOCK_TYPE describes the type of locks available.

Column	Datatype	Description
TYPE	VARCHAR2 (64)	A two-letter internal resource identifier
NAME	VARCHAR2 (64)	Resource type name. This is a short (less than 32 characters) enqueue type name.
ID1_TAG	VARCHAR2 (64)	Description of the enqueue type.
ID2_TAG	VARCHAR2 (64)	Further description of the enqueue type.
IS_USER	VARCHAR2 (3)	User enqueue. These are enqueues that are acquired as a direct result of a SQL statement. Applications may get deadlocks on these enqueues. Such deadlocks are considered application errors.
DESCRIPTION	VARCHAR2 (4000)	Explanation of how or for what purpose the enqueue is used.

V\$LOCKED_OBJECT

V\$LOCKED_OBJECT lists all locks acquired by every transaction on the system. It shows which sessions are holding DML locks (that is, TM-type enqueues) on what objects and in what mode.

Column	Datatype	Description
XIDUSN	NUMBER	Undo segment number
XIDSLOT	NUMBER	Slot number
XIDSQN	NUMBER	Sequence number
OBJECT_ID	NUMBER	Object ID being locked
SESSION_ID	NUMBER	Session ID
ORACLE_USERNAME	VARCHAR2 (30)	Oracle user name
OS_USER_NAME	VARCHAR2 (30)	OS user name
PROCESS	VARCHAR2 (12)	OS process ID
LOCKED_MODE	NUMBER	Lock mode

V\$LOG

V\$LOG displays log file information from the control file.

Column	Datatype	Description
GROUP#	NUMBER	Log group number
THREAD#	NUMBER	Log thread number
SEQUENCE#	NUMBER	Log sequence number
BYTES	NUMBER	Size of the log (in bytes)
BLOCKSIZE	NUMBER	Block size of the logfile (512 or 4096)
MEMBERS	NUMBER	Number of members in the log group
ARCHIVED	VARCHAR2 (3)	Archive status (YES) or (NO)

Column	Datatype	Description
STATUS	VARCHAR2 (16)	Log status: ■ UNUSED - Online redo log has never been written to. This is the state of a redo log that was just added, or just after a RESETLOGS, when it is not the current redo log. ■ CURRENT - Current redo log. This implies that the redo log is active. The redo log could be open or closed. ■ ACTIVE - Log is active but is not the current log. It is needed for crash recovery. It may be in use for block recovery. It may or may not be archived. ■ CLEARING - Log is being re-created as an empty log after an ALTER DATABASE CLEAR LOGFILE statement. After the log is cleared, the status changes to UNUSED. ■ CLEARING_CURRENT - Current log is being cleared of a closed thread. The log can stay in this status if there is some failure in the switch such as an I/O error writing the new log header. ■ INACTIVE - Log is no longer needed for instance recovery. It may be in use for media recovery. It may or may not be archived.
FIRST_CHANGE#	NUMBER	Lowest system change number (SCN) in the log
FIRST_TIME	DATE	Time of the first SCN in the log

V\$LOG_HISTORY

V\$LOG_HISTORY displays log history information from the control file.

Column	Datatype	Description
RECID	NUMBER	Control file record ID
STAMP	NUMBER	Control file record stamp
THREAD#	NUMBER	Thread number of the archived log
SEQUENCE#	NUMBER	Sequence number of the archived log
FIRST_CHANGE#	NUMBER	Lowest system change number (SCN) in the log
FIRST_TIME	DATE	Time of the first entry (lowest SCN) in the log
NEXT_CHANGE#	NUMBER	Highest SCN in the log
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the database when the log was written
RESETLOGS_TIME	DATE	Resetlogs time of the database when the log was written

V\$LOGFILE

V\$LOGFILE contains information about redo log files.

Column	Datatype	Description
GROUP#	NUMBER	Redo log group identifier number
STATUS	VARCHAR2 (7)	Status of the log member: ■ INVALID - File is inaccessible ■ STALE - File's contents are incomplete ■ DELETED - File is no longer used ■ null - File is in use
TYPE	VARCHAR2 (7)	Type of the logfile: ■ ONLINE ■ STANDBY
MEMBER	VARCHAR2 (513)	Redo log member name

Column	Datatype	Description
IS_RECOVERY_DEST_FILE	VARCHAR2 (3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)

V\$LOGHIST

V\$LOGHIST contains log history information from the control file. This view is retained for historical compatibility. Oracle recommends that you use V\$LOG_HISTORY instead.

See Also: ["V\\$LOG_HISTORY"](#) on page 8-18

Column	Datatype	Description
THREAD#	NUMBER	Log thread number
SEQUENCE#	NUMBER	Log sequence number
FIRST_CHANGE#	NUMBER	Lowest SCN in the log
FIRST_TIME	DATE	Time of first SCN in the log
SWITCH_CHANGE#	NUMBER	SCN at which the log switch occurred; one more than highest SCN in the log

V\$LOGMNR_CONTENTS

V\$LOGMNR_CONTENTS contains log history information. To query this view, you must have the SELECT ANY TRANSACTION privilege.

When a SELECT statement is executed against the V\$LOGMNR_CONTENTS view, the archive redo log files are read sequentially. Translated records from the redo log files are returned as rows in the V\$LOGMNR_CONTENTS view. This continues until either the filter criteria specified at startup (EndTime or endScn) are met or the end of the archive log file is reached.

Column	Datatype	Description
SCN	NUMBER	System change number (SCN) when the database change was made
START_SCN	NUMBER	System change number (SCN) when the transaction that contains this change started; only meaningful if the COMMITTED_DATA_ONLY option was chosen in a DBMS_LOGMNR.START_LOGMNR () invocation, NULL otherwise. This column may also be NULL if the query is run over a time/SCN range that does not contain the start of the transaction.
COMMIT_SCN	NUMBER	System change number (SCN) when the transaction committed; only meaningful if the COMMITTED_DATA_ONLY option was chosen in a DBMS_LOGMNR.START_LOGMNR () invocation
TIMESTAMP	DATE	Timestamp when the database change was made
START_TIMESTAMP	DATE	Timestamp when the transaction that contains this change started; only meaningful if the COMMITTED_DATA_ONLY option was chosen in a DBMS_LOGMNR.START_LOGMNR () invocation, NULL otherwise. This column may also be NULL if the query is run over a time/SCN range that does not contain the start of the transaction.
COMMIT_TIMESTAMP	DATE	Timestamp when the transaction committed; only meaningful if the COMMITTED_DATA_ONLY option was chosen in a DBMS_LOGMNR.START_LOGMNR () invocation
XIDUSN	NUMBER	Transaction ID undo segment number of the transaction that generated the change
XIDSLT	NUMBER	Transaction ID slot number of the transaction that generated the change

Column	Datatype	Description
XIDSQN	NUMBER	Transaction ID sequence number of the transaction that generated the change
XID	RAW (8)	Raw representation of the transaction identifier
PXIDUSN	NUMBER	Parent transaction ID undo segment number of a parallel transaction
PXIDSLT	NUMBER	Parent transaction ID slot number of a parallel transaction
PXIDSQN	NUMBER	Parent transaction ID sequence number of a parallel transaction
PXID	RAW (8)	Raw representation of the parent transaction identifier
TX_NAME	VARCHAR2 (256)	Name of the transaction that made the change; only meaningful if the transaction is a named transaction
OPERATION	VARCHAR2 (32)	User level SQL operation that made the change: ■ INSERT - Change was caused by an insert statement ■ UPDATE - Change was caused by an update statement ■ DELETE - Change was caused by a delete statement ■ DDL - Change was caused by a DDL statement ■ START - Change was caused by the start of a transaction ■ COMMIT - Change was caused by the commit of a transaction ■ ROLLBACK - Change was caused by a full rollback of a transaction ■ LOB_WRITE - Change was caused by an invocation of DBMS_LOB.WRITE ■ LOB_TRIM - Change was caused by an invocation of DBMS_LOB.TRIM ■ LOB_ERASE - Change was caused by an invocation of DBMS_LOB.ERASE ■ SELECT_FOR_UPDATE - Operation was a SELECT FOR UPDATE statement ■ SEL_LOB_LOCATOR - Operation was a SELECT statement that returned a LOB locator ■ MISSING_SCN - LogMiner encountered a gap in the redo records. This is most likely because not all redo logs were registered with LogMiner. ■ INTERNAL - Change was caused by internal operations initiated by the database ■ XML DOC BEGIN - Beginning of a change to an XMLType column or table ■ XML DOC WRITE - Data for an XML document ■ XML DOC END - End of the Data for an XML document ■ UNSUPPORTED - Change was caused by operations not currently supported by LogMiner (for example, changes made to tables with ADT columns)

Column	Datatype	Description
OPERATION_CODE	NUMBER	Number of the operation code: 0 - INTERNAL 1 - INSERT 2 - DELETE 3 - UPDATE 5 - DDL 6 - START 7 - COMMIT 9 - SELECT_LOB_LOCATOR 10 - LOB_WRITE 11 - LOB_TRIM 25 - SELECT_FOR_UPDATE 28 - LOB_ERASE 34 - MISSING_SCN 68 - XML DOC BEGIN 70 = XML DOC WRITE 71 = XML DOC END 36 - ROLLBACK 255 - UNSUPPORTED
ROLLBACK	NUMBER	1 = if the redo record was generated because of a partial or a full rollback of the associated transaction 0 = otherwise
SEG_OWNER	VARCHAR2 (32)	Owner of the modified data segment
SEG_NAME	VARCHAR2 (256)	Name of the modified data segment
TABLE_NAME	VARCHAR2 (32)	Name of the modified table (in case the redo pertains to a table modification)
SEG_TYPE	NUMBER	Type of the modified data segment: 0 - UNKNOWN 1 - INDEX 2 - TABLE 19 - TABLE PARTITION 20 - INDEX PARTITION 34 - TABLE SUBPARTITION - All other values - UNSUPPORTED
SEG_TYPE_NAME	VARCHAR2 (32)	Segment type name: - UNKNOWN - INDEX - TABLE - TABLE PARTITION - INDEX PARTITION - TABLE SUBPARTITION - UNSUPPORTED
TABLE_SPACE	VARCHAR2 (32)	Name of the tablespace containing the modified data segment. This column is not populated for rows where the value of the OPERATION column is DDL. This is because DDL may operate on more than one tablespace.
ROW_ID	VARCHAR2 (18)	Row ID of the row modified by the change (only meaningful if the change pertains to a DML). This will be NULL if the redo record is not associated with a DML.
USERNAME	VARCHAR2 (30)	Name of the user who executed the transaction

Column	Datatype	Description
OS_USERNAME	VARCHAR2 (4000)	Name of the operating system user
MACHINE_NAME	VARCHAR2 (4000)	Machine from which the user connected to the database
AUDIT_SESSIONID	NUMBER	Audit session ID associated with the user session making the change
SESSION#	NUMBER	Session number of the session that made the change
SERIAL#	NUMBER	Serial number of the session that made the change
SESSION_INFO	VARCHAR2 (4000)	Information about the database session that executed the transaction. Contains process information, machine name from which the user logged in, and so on. A possible SESSION_INFO column may contain the following: - login_username = HR - client_info = - OS_username = jkundu - Machine_name = nirvan - OS_terminal = pts/31 - OS_program_name = sqlplus@nirvan (TNS V1-V3)
THREAD#	NUMBER	Number of the thread that made the change to the database
SEQUENCE#	NUMBER	Sequence number of the SQL statement within the transaction. If you are mining without the COMMITTED_DATA_ONLY option set, then this value is 1.
RBASQN	NUMBER	Sequence# associated with the Redo Block Address (RBA) of the redo record associated with the change
RBABLK	NUMBER	RBA block number within the log file
RBABYTE	NUMBER	RBA byte offset within the block
UBAFIL	NUMBER	Undo Block Address (UBA) file number identifying the file containing the undo block
UBABLK	NUMBER	UBA block number for the undo block
UBAREC	NUMBER	UBA record index within the undo block
UBASQN	NUMBER	UBA undo block sequence number
ABS_FILE#	NUMBER	Data block absolute file number of the block changed by the transaction
REL_FILE#	NUMBER	Data block relative file number. The file number is relative to the tablespace of the object.
DATA_BLK#	NUMBER	Data block number within the file
DATA_OBJ#	NUMBER	Data block object number identifying the object
DATA_OBJV#	NUMBER	Version number of the table being modified
DATA_OBJD#	NUMBER	Data block data object number identifying the object within the tablespace
SQL_REDO	VARCHAR2 (4000)	Reconstructed SQL statement that is equivalent to the original SQL statement that made the change. Refer to <i>Oracle Database Utilities</i> before executing SQL_REDO to your database. LogMiner does not generate SQL redo for temporary tables. In such a case, this column will contain the string "/* No SQL_REDO for temporary tables */".
SQL_UNDO	VARCHAR2 (4000)	Reconstructed SQL statement that can be used to undo the effect of the original statement that made the change. DDL statements have no corresponding SQL_UNDO. Refer to <i>Oracle Database Utilities</i> before executing SQL_UNDO to your database. LogMiner does not generate SQL undo for temporary tables. In such a case, this column will contain the string "/* No SQL_UNDO for temporary tables */".

Column	Datatype	Description
RS_ID	VARCHAR2 (32)	Record set ID. The tuple (RS_ID, SSN) together uniquely identifies a logical row change. This will usually mean one row from V\$LOGMNR_CONTENTS, but could be more than one row if a single SQL statement for either the Redo or Undo would be too large to fit within the respective columns SQL_UNDO or SQL_REDO. RS_ID uniquely identifies the redo record that generated the row.
SSN	NUMBER	SQL sequence number. Used in conjunction with RS_ID, this uniquely identifies a logical row change, shown as one or more rows from the V\$LOGMNR_CONTENTS view.
CSF	NUMBER	Continuation SQL flag. Possible values are: 0 - Indicates SQL_REDO and SQL_UNDO is contained within the same row 1 - Indicates that either SQL_REDO or SQL_UNDO is greater than 4000 bytes in size and is continued in the next row returned by the view
INFO	VARCHAR2 (32)	Informational message about the row. For instance, the string "USER DDL" indicates that the DDL statement returned in the SQL_REDO column was the top-level DDL executed by the user and the string "INTERNAL DDL" indicates that the DDL statement returned in the SQL_REDO column was executed internally by the RDBMS.
STATUS	NUMBER	A value of 0 indicates that the reconstructed SQL statements as shown in the SQL_REDO and SQL_UNDO columns are valid executable SQL statements. Otherwise, the reconstructed SQL statements are not executable. This may be due to the fact that no data dictionary was provided to LogMiner for the analysis, or that the data dictionary provided did not have the definition of the object being mined. A value of 5 indicates that this row is part of a change to an XMLType column or table and the XML document must be assembled before being applied.
REDO_VALUE	NUMBER	Used as input to the DBMS_LOGMNR.MINE_VALUE() and DBMS_LOGMNR.COLUMN_PRESENT() functions
UNDO_VALUE	NUMBER	Used as input to the DBMS_LOGMNR.MINE_VALUE() and DBMS_LOGMNR.COLUMN_PRESENT() functions
SAFE_RESUME_SCN	NUMBER	Reserved for future use
CSCN	NUMBER	This column is deprecated in favor of the COMMIT_SCN column
OBJECT_ID	RAW (16)	Object identifier for DMLs to XMLType tables. For changes to non-typed tables, this column is NULL.
EDITION_NAME	VARCHAR2 (30)	Identifies the edition in which a DDL statement was executed
CLIENT_ID	VARCHAR2 (64)	Client identifier in the session that performed the operation, if available.

V\$LOGMNR_DICTIONARY

V\$LOGMNR_DICTIONARY contains log history information.

Column	Datatype	Description
DB_NAME	VARCHAR2 (9)	Name of the database
DB_ID	NUMBER	Database ID
DB_CREATED	DATE	Creation date of the source database (corresponds to the CREATED column in the V\$DATABASE view)
TIMESTAMP	DATE	Date when the dictionary was created
RESET_SCN	NUMBER	Reset log SCN when the dictionary was created
RESET_SCN_TIME	DATE	Timestamp of the reset log SCN when the dictionary was created
DB_VERSION_TIME	DATE	Version time for the source database (corresponds to the VERSION_TIME column in the V\$DATABASE view)
DB_CHARACTER_SET	VARCHAR2 (30)	Character set of the source database

Column	Datatype	Description
DB_VERSION	VARCHAR2 (64)	This column is deprecated.
DB_STATUS	VARCHAR2 (64)	This column is deprecated.
DICTIONARY_SCN	NUMBER	Database checkpoint SCN at which the dictionary was created
ENABLED_THREAD_MAP	RAW (16)	This column is deprecated.
DB_TXN_SCN	NUMBER	SCN at which the dictionary was created
FILENAME	VARCHAR2 (512)	Dictionary file name
INFO	VARCHAR2 (32)	Informational/Status message BAD_DATE indicates that the SCN of the dictionary file does not match the SCN range of the log files
STATUS	NUMBER	A NULL indicates a valid dictionary file for the list of log files. A non-NULL value indicates further information is contained in the INFO column as a text string.

V\$LOGMNR_DICTIONARY_LOAD

V\$LOGMNR_DICTIONARY_LOAD displays information about LogMiner dictionaries for all active LogMiner sessions on the system. Each query of this view will return one row for each attached LogMiner session. This view will not show valid information for LogMiner adhoc query clients.

Column	Datatype	Description
SESSION_ID	NUMBER	LogMiner session ID
LOGMNR_UID	NUMBER	LogMiner dictionary UID
ACTION#	NUMBER	Reserved for internal use
OPCODE	NUMBER	Reserved for internal use
COMMAND	VARCHAR2 (161)	Current command being executed
CURRENT_STATE	VARCHAR2 (32)	Summary information if LOADED=ACTIVE
COMPLETED_ACTIONS	NUMBER	The steps completed so far
TOTAL_ACTIONS	NUMBER	Total steps to complete
LOADED	VARCHAR2 (7)	Status of the dictionary load: ■ YES - dictionary has been loaded ■ NO - dictionary has not been loaded ■ ACTIVE - dictionary is in the process of being loaded
PERCENT_DONE	NUMBER	Percentage of the dictionary that has been loaded

V\$LOGMNR_LATCH

V\$LOGMNR_LATCH can be joined with the V\$LATCH and the V\$LATCH_CHILDREN views to obtain statistics about different latches used by active LogMiner persistent sessions. A persistent LogMiner session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating a Streams capture.

Column	Datatype	Description
SESSION_ID	NUMBER	Unique identifier of the LogMiner persistent session

Column	Datatype	Description
NAME	VARCHAR2 (32)	Name of the Latch: - LogMiner internal state - Identifies the latch that protects communications between the LogMiner READER, PREPARER, and BUILDER processes - LogMiner memory allocation - Identifies the latch that protects all memory allocation and deallocation inside LogMiner - LogMiner transaction list - Identifies the latch that protects interaction between the LogMiner layer and its clients (Data Guard SQL Apply on a logical standby database or Oracle Streams)
CHILD_ADDR	RAW (4)	Address of the child latch object. This column matches the corresponding ADDR column in the V\$LATCH_CHLDREN view
STATE	VARCHAR2 (6)	State of the Latch: - UNINIT - The latch structure is uninitialized; that is, it is not currently assigned to any LogMiner persistent session - READY - The latch structure is being used by a persistent LogMiner session

V\$LOGMNR_LOGS

V\$LOGMNR_LOGS contains log information.

Column	Datatype	Description
LOG_ID	NUMBER	This column is deprecated.
FILENAME	VARCHAR2 (512)	Name of the log file
LOW_TIME	DATE	Oldest date of any records in the file
HIGH_TIME	DATE	Most recent date of any records in the file
DB_ID	NUMBER	Database ID
DB_NAME	VARCHAR2 (8)	Name of the database
RESET_SCN	NUMBER	Resetlogs SCN of the database incarnation that generated the log file
RESET_SCN_TIME	DATE	Resetlogs timestamp of the database incarnation that generated the log file
COMPATIBLE	VARCHAR2 (17)	The setting of the database COMPATIBLE initialization parameter at the time the log file was generated
THREAD_ID	NUMBER	Thread number
THREAD_SEQN	NUMBER	Thread sequence number
LOW_SCN	NUMBER	SCN allocated when log switched into
NEXT_SCN	NUMBER	SCN after this log. Low SCN of the next log.
DICTIONARY_BEGIN	VARCHAR2 (3)	Indicates whether dictionary dumped to redo logs starts in this redo log (YES) or not (NO)
DICTIONARY_END	VARCHAR2 (3)	Indicates whether dictionary dumped to redo logs ends in this redo log (YES) or not (NO)
TYPE	VARCHAR2 (7)	Redo log file type: - ARCHIVED - ONLINE
BLOCKSIZE	NUMBER	Database block size
FILESIZE	NUMBER	Size of the redo file (in bytes)
INFO	VARCHAR2 (32)	Informational message. A value of MISSING_LOGFILE will be assigned to a row entry where a needed log file is missing from the list of log files.

Column	Datatype	Description
STATUS	NUMBER	Status of the redo log file: 0 - Will be read 1 - First to be read 2 - Not needed 4 - Missing log file

V\$LOGMNR_PARAMETERS

V\$LOGMNR_PARAMETERS contains log information.

Column	Datatype	Description
START_DATE	DATE	Date to start the search
REQUIRED_START_DATE	DATE	Required date to start the search if DDL tracking is enabled
END_DATE	DATE	Date to end the search
START_SCN	NUMBER	System change number to start the search
REQUIRED_START_SCN	NUMBER	Required system change number to start the search if DDL tracking is enabled
END_SCN	NUMBER	System change number to end the search
OPTIONS	NUMBER	Options specified for the current LogMiner session
INFO	VARCHAR2 (32)	This column is always null.
STATUS	NUMBER	This column is always 0.

V\$LOGMNR_PROCESS

V\$LOGMNR_PROCESS identifies all processes attached to an active LogMiner persistent session. (A persistent LogMiner session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating Streams capture.) This view can be joined with either the V\$SESSION view or the V\$PROCESS view to gather process-specific information.

Column	Datatype	Description
SESSION_ID	NUMBER	Unique identifier for the LogMiner persistent session
PID	NUMBER	Oracle process identifier for the SQL Apply or Streams capture process (same as the V\$PROCESS . PID)
SPID	VARCHAR2 (12)	Operating system process identifier (same as the V\$PROCESS . SPID)
ROLE	VARCHAR2 (32)	Identifies the role of the active LogMiner process: READER, PREPARER, BUILDER, COORDINATOR, or APPLY SERVER
USERNAME	VARCHAR2 (15)	Operating system process user name that is connected to the database
SID	NUMBER	Session identifier for the V\$SESSION . SID process
SERIAL#	NUMBER	Session serial number associated with the V\$SESSION . SERIAL process
LATCHWAIT	VARCHAR2 (8)	Address of the latch the process is waiting for; NULL if none
LATCHSPIN	VARCHAR2 (8)	Address of the latch the process is spinning on; NULL if none
WORK_MICROSEC	VARCHAR2 (21)	Microseconds spent by the process doing useful work
OVERHEAD_MICROSEC	VARCHAR2 (21)	Microseconds spent by the process doing overhead tasks or simply waiting/idling

V\$LOGMNR_SESSION

V\$LOGMNR_SESSION displays information about active LogMiner persistent sessions. (A LogMiner persistent session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating Streams Capture.) Transient LogMiner sessions (those created as a result of querying the V\$LOGMNR_CONTENTS view) do not show up in the V\$LOGMNR_SESSION view. The statistics shown in this view correspond to snapshots of the system and are not cumulative in nature.

Column	Datatype	Description
SESSION_ID	NUMBER	Unique identifier for the LogMiner persistent session
SESSION_NAME	VARCHAR2 (32)	Unique session name
SESSION_STATE	VARCHAR2 (9)	Current state of the LogMiner persistent session: - READY - Client has created the LogMiner persistent session and added the relevant archived redo log files, but has not loaded the initial LogMiner dictionary - STARTED - The LogMiner dictionary has been loaded - ACTIVE - The LogMiner persistent session is mining the redo stream - DETACHED - The LogMiner persistent session is not currently active, and it is in the process of becoming inactive - DISCARDED - Client is about to destroy the LogMiner persistent session
DB_NAME	VARCHAR2 (128)	Global database name for the source database
DB_ID	NUMBER	Database identifier of the source database
RESET_SCN	NUMBER	System change number (SCN) when the session started
RESET_TIMESTAMP	NUMBER	Time of the RESETLOGS when the LogMiner persistent session started
NUM_PROCESS	NUMBER	Number of processes allocated to this session
CHUNK_SIZE	NUMBER	Amount of memory allocated for this chunk
START_SCN	NUMBER	System change number (SCN) at start of the session
END_SCN	NUMBER	System change number (SCN) at end of the session
SPILL_SCN	NUMBER	In the event of a restart, redo records with an SCN lower than this will not be read from the archived redo log files
PROCESSED_SCN	NUMBER	The BUILDER process has successfully mined redo records up to this SCN
PREPARED_SCN	NUMBER	The PREPARER processes have successfully transformed all redo records below this SCN into logical change records (LCRs). However the LCRs may not have been grouped into transactions or merged in case they pertain to chained rows or LOB updates.
READ_SCN	NUMBER	The READER process has read all redo records below this SCN
LOW_MARK_SCN	NUMBER	LogMiner has delivered all transactions that committed below this SCN to the client
CONSUMED_SCN	NUMBER	Client has consumed and released all transactions that committed below this SCN.
MAX_MEMORY_SIZE	NUMBER	Maximum amount of shared memory (in bytes) that LogMiner is allowed to consume
USED_MEMORY_SIZE	NUMBER	Amount of shared memory (in bytes) actually consumed by LogMiner
BUILDER_WORK_SIZE	NUMBER	Amount of redo (in bytes) in the current work unit being processed by the BUILDER process.
PREPARED_WORK_SIZE	NUMBER	Amount of redo (in bytes) that has been prepared by LogMiner
AVAILABLE_WORK_SIZE	NUMBER	Amount of redo records (in bytes) that are ready, but are yet to be consumed by the client
AVAILABLE_TXN	NUMBER	Number of transaction chunks ready for consumption

V\$LOGMNR_STATS

Column	Datatype	Description
AVAILABLE_COMMITTED_TXN	NUMBER	Number of committed transactions ready for consumption. This is less than, or equal to, AVAILABLE_TXN.
DELIVERED_TXN	NUMBER	Number of transaction chunks that the client currently has in its possession
DELIVERED_COMMITTED_TXN	NUMBER	Number of committed transaction chunks that the client is currently working on. This is less than, or equal to, the value of the DELIVERED_TXN column.
PINNED_TXN	NUMBER	Number of transactions pinned (the client is actively working on)
PINNED_COMMITTED_TXN	NUMBER	Number of committed transactions pinned (the client is actively working on)
CHECKPOINT_INTERVAL	NUMBER	Checkpoint interval

V\$LOGMNR_STATS

V\$LOGMNR_STATS displays the activity currently being performed by the active LogMiner persistent sessions.

Column	Datatype	Description
SESSION_ID	NUMBER	Unique identifier for the LogMiner persistent sessions

Column	Datatype	Description
NAME	VARCHAR2 (64)	Name of the LogMiner statistic, state, or status, including: - Bytes of Redo Processed - Cumulative count of bytes processed by SQL Apply - Redo Records Processed - Count of redo records processed by SQL Apply - Txns Delivered to Client - Count of SQL transactions processed by SQL Apply - DML txns delivered - Count of DML transactions processed by SQL Apply - DDL txns delivered - Count of DDL transactions processed by SQL Apply - CTAS txns delivered - Count of CREATE TABLE AS SELECT (CTAS) transactions processed by SQL Apply - Recursive txns delivered - Count of recursive transactions processed by SQL Apply - Rolled back txns seen - LCRs delivered to client - Number of logical change records (LCRs) processed by SQL Apply - Bytes paged out - Cumulative count of bytes that have been paged out. LogMiner pages out memory from the LCR cache to accommodate certain ill-behaved workloads or under-configured systems. The ratio of bytes paged out to bytes of redo processed should be low. If this ratio is high (10% or higher), try increasing the MAX_SGA allocated to SQL Apply. - Microsecs spent in pageout - Time spent by LogMiner paging out memory from the LCR cache - Bytes checkpointed - Keeps track of the amount of bytes checkpointed. The mining engine takes periodic checkpoints, whereby it writes out logical change records (LCRs) pertaining to long-running transactions. The ratio of Bytes Checkpointed to Bytes of Redo Processed should be low. A high ratio (10% or higher) indicates an ill-behaved workload. - Microsecs spent in checkpoint - Time spent by the mining engine taking checkpoints, whereby it writes out logical change records (LCRs) pertaining to long-running transactions. - Bytes rolled back - Cumulative value of the number of bytes rolled back by LogMiner. There are times that LogMiner needs to backtrack and reprocess a section of the redo stream. In this case, it will roll back work it has already done. The ratio of Bytes Rolled Back to Bytes of Redo Processed should be low. If this ratio is high (10% or higher), reduce the number of PREPARER processes allocated to SQL Apply. - Microsecs spent in rollback - Time spent rolling back transactions already applied to the logical standby database
VALUE	VARCHAR2 (64)	The corresponding metric value

V\$LOGSTDBY

V\$LOGSTDBY is deprecated.

Column	Datatype	Description
SERIAL#	NUMBER	SQL Session serial number. This data is used when joining this view with the V\$SESSION and V\$PX_SESSION views.
LOGSTDBY_ID	NUMBER	Parallel query slave ID
PID	VARCHAR2 (12)	Process ID of the SQL apply process
TYPE	VARCHAR2 (30)	Indicates the task being performed by the process (COORDINATOR, APPLIER, ANALYZER, READER, PREPARER, or BUILDER)
STATUS_CODE	NUMBER	Status number (or Oracle error code) belonging to the STATUS message

Column	Datatype	Description
STATUS	VARCHAR2 (256)	Description of the current activity of the process
HIGH_SCN	NUMBER	Highest system change number (SCN) seen by the process. This column is used to confirm the progress of the individual process.

V\$LOGSTDBY_PROCESS

V\$LOGSTDBY_PROCESS displays dynamic information about what is happening to the Data Guard log apply services. This view is helpful when diagnosing performance problems during the logical application of archived redo logs to the standby database, and it can be helpful for other problems. This view is for logical standby databases only.

Column	Datatype	Description
SID	NUMBER	Session id of the associated session. This matches the SID column of the corresponding row in the V\$SESSION view.
SERIAL#	NUMBER	Serial number of the associated session. Together, (SID,SERIAL#) uniquely identify the session in the current database instance.
LOGSTDBY_ID	NUMBER	Parallel query slave ID
SPID	VARCHAR2 (12)	This corresponds to the SPID value of the row corresponding to this process in the V\$PROCESS view
TYPE	VARCHAR2 (30)	Role that the process plays in the context of SQL Apply: - COORDINATOR - APPLIER - ANALYZER - READER - PREPARER - BUILDER
STATUS_CODE	NUMBER	Operation code identifying the current action of the process: 16111 - SQL Apply process is initializing 16112 - SQL Apply process is cleaning up as apply and mining processes are stopping based on a user command 16116 - SQL Apply process is idle 16117 - SQL Apply process is busy and is not waiting on any interesting event 16110 - APPLIER process has invoked a user-provided stored procedure in order to inspect a DDL statement prior to it being processed 16113 - APPLIER process is applying DML changes to some user object or to a sequence 16114 - APPLIER process is applying a DDL change 16115 - COORDINATOR process is loading the LogMiner dictionary from the redo stream 16243 - BUILDER process is paging out memory to free up space in lcr cache 16240 - READER process idle waiting for additional logfile to be available 16241 - READER process is idle waiting for the logfile to fill the log sequence gap 16242 - READER process is processing a logfile
STATUS	VARCHAR2 (256)	Description of the current action of the process
HIGH_SCN	NUMBER	Identifies the highest redo record/LCR processed by this process

V\$LOGSTDBY_PROGRESS

V\$LOGSTDBY_PROGRESS displays the progress of log apply services on the logical standby database. This view is for logical standby databases only.

Column	Datatype	Description
APPLIED_SCN	NUMBER	All the transactions with COMMIT SCN lower than or equal to this SCN have been applied
APPLIED_TIME	DATE	The time and date of APPLIED_SCN
RESTART_SCN	NUMBER	During an apply restart, LogMiner does not read any log file with a NEXT_CHANGE# lower than this SCN.
RESTART_TIME	DATE	The time and date of RESTART_SCN
LATEST_SCN	NUMBER	The highest SCN of all redo records that Logical Standby has encountered
LATEST_TIME	DATE	The time and date of LATEST_SCN
MINING_SCN	NUMBER	The SCN of the latest redo record processed by the builder process
MINING_TIME	DATE	The time and date of MINING_SCN
RESETLOGS_ID	NUMBER	A redo branch is identified by resetlogs SCN and resetlogs timestamp. The RESETLOGS_ID column contents are the same as resetlogs timestamp converted to a number.

V\$LOGSTDBY_STATE

V\$LOGSTDBY_STATE provides consolidated information from V\$LOGSTDBY and V\$LOGSTDBY_STATS about the running state of Logical Standby.

Column	Datatype	Description
PRIMARY_DBID	NUMBER	Database ID (DBID) of the primary database
SESSION_ID	NUMBER	LogMiner session ID allocated to SQL Apply.
REALTIME_APPLY	VARCHAR2 (64)	Y indicates that SQL Apply is running in real-time apply mode. If a standby redo log is configured, SQL Apply applies changes as they are written to the standby redo log files. N indicates that SQL Apply applies changes as each archived redo log file is received.
STATE	VARCHAR2 (64)	■ INITIALIZING: LogMiner session has been created and coordinator has attached to it ■ LOADING DICTIONARY: SQL Apply is loading the LogMiner dictionary ■ WAITING ON GAP: SQL Apply is waiting for a log file to be sent from the primary database ■ APPLYING: SQL Apply is actively mining or applying transactions ■ WAITING FOR DICTIONARY LOGS: SQL Apply is waiting for the archived logs containing the LogMiner dictionary to be shipped from the primary database ■ IDLE: SQL Apply has applied all changes available at the logical standby, and is caught up with the primary database

V\$LOGSTDBY_STATS

V\$LOGSTDBY_STATS displays statistics, current state, and status information related to SQL Apply. No rows are returned from this view when SQL Apply is not running. This view is only meaningful in the context of a logical standby database.

All statistics shown in this view are reinitialized at each SQL Apply start.

Column	Datatype	Description
NAME	VARCHAR2 (64)	Name of the statistic, state, or status: Note: Many of the following statistics are subject to change or deletion; programmers should write application code to tolerate missing or extra statistics. ▪ id of the logminer session used by SQL Apply to mine the redo logs. ▪ number of preparers ▪ number of appliers ▪ server processes in use for SQL Apply ▪ maximum SGA (in MBytes) for LCR cache ▪ whether SQL Apply is preserving the commit order seen at the primary database while applying changes ▪ maximum events recorded in the DBA_LOGSTDBY_EVENTS table ▪ whether SQL Apply is logging errors that are skipped in the DBA_LOGSTDBY_EVENTS table ▪ whether SQL Apply is logging DDLs that are skipped in the DBA_LOGSTDBY_EVENTS table ▪ whether SQL Apply is logging DDLs that are applied in the DBA_LOGSTDBY_EVENTS table ▪ whether SQL Apply is logging unsupported operations that are encountered in the DBA_LOGSTDBY_EVENTS table ▪ whether or not real time apply is on ▪ value of apply delay (in minutes) ▪ coordinator state ▪ coordinator uptime in seconds ▪ time of the most recent start of SQL Apply ▪ number of transactions mined and made available for apply ▪ number of transactions applied ▪ number of rolled back transactions mined ▪ number of DDL txns mined ▪ number of CTAS (Create Table as Select) txns mined ▪ number of thread enable events encountered in the redo stream ▪ number of thread disable events encountered in the redo stream ▪ bytes of redo records mined ▪ bytes paged out ▪ seconds spent in pageout activity ▪ bytes checkpointed ▪ seconds spent in checkpointing activity ▪ seconds SQL Apply is idle ▪ number of times a complete standby redo logs are mined without having to mine the corresponding archived log ▪ number of times SQL Apply had to switch from a standby redo log to the corresponding archived log ▪ number of times SQL Apply mined redo from the archived logs ▪ number of archived logs that arrived at the standby via gap fetch mechanism (gap fetched logs mined) ▪ number of failed attempts to open a logfile ▪ amount of time spent in waiting for the current gap to resolve if SQL Apply is running in real time mode (current logfile wait)¹ ▪ time spent in waiting for gap to resolve if SQL Apply is running in real time mode (total logfile wait)²
VALUE	VARCHAR2 (64)	Value of the statistic or state information

¹ In case SQL Apply is not running in real time mode, this may not reflect time spent in gap resolution, but simply the time spent waiting for the most recent archived log to show up at the logical standby.

- ² In case SQL Apply is not running in real time mode, this will include time that SQL Apply spent every time it finished processing all archived logs registered with it, and waited for the next log to be archived.

V\$LOGSTDBY_TRANSACTION

V\$LOGSTDBY_TRANSACTION displays all transactions that are actively being processed by SQL Apply. The transaction identifiers shown in this view are those mined from the redo stream and correspond to transaction identifiers assigned at the primary database, and do not correspond to the transactions that are active at the logical standby database. For information regarding transactions active in the logical standby database, including those created as part of SQL Apply, query the V\$TRANSACTION view at the logical standby database.

Column	Datatype	Description
PRIMARY_XIDUSN	NUMBER	Undo segment number of the transaction
PRIMARY_XIDSLT	NUMBER	Slot number of the transaction
PRIMARY_XIDSQN	NUMBER	Sequence number of the transaction
PRIMARY_XID	RAW (8)	Transaction ID
PRIMARY_START_SCN	NUMBER	Start system change number (SCN) base
PRIMARY_START_TIME	DATE	Start time
PRIMARY_PARENT_XIDUSN	NUMBER	Undo segment number of the parent transaction
PRIMARY_PARENT_XIDSLT	NUMBER	Slot number of the parent transaction
PRIMARY_PARENT_XIDSQN	NUMBER	Sequence number of the parent transaction
PRIMARY_PARENT_XID	RAW (8)	Transaction ID of the parent transaction (PDML)
TYPE	VARCHAR2 (32)	Type: ■ PL/SQL - Transaction was done as part of a supported PL/SQL procedure ■ Direct Path Load - Transaction is a direct path load ■ CTAS - Transaction contains at least one CREATE TABLE ... AS SELECT operation ■ DDL - Transaction contains one or more DDL operations ■ PDML Child - Transaction is a child transaction ■ DML - Transaction contains only DML operations
MINING_STATUS	VARCHAR2 (32)	Mining status: ■ ACTIVE - Transaction is still being mined by LogMiner. At least part of this transaction is ready to be applied or has already been applied. ■ COMPLETE - Transaction is complete and ready to be applied. LogMiner has finished mining.
APPLY_STATUS	VARCHAR2 (6)	■ ACTIVE - Transaction has been assigned to an apply server. It is in one of the following states: - The transaction is being actively applied - The transaction is being held by an apply server waiting for certain events to occur - The transaction is being held by an apply server waiting for subsequent parts of this transaction ■ NONE - Transaction has not yet been assigned to an apply server
SID	NUMBER	Session ID of the apply server's session; Null if APPLY_STATUS is NONE
SERIAL#	NUMBER	Serial number of the apply server's session; Null if APPLY_STATUS is NONE

V\$MANAGED_STANDBY

V\$MANAGED_STANDBY displays current status information for some Oracle Database processes related to physical standby databases in the Data Guard environment. This view does not persist after an instance shutdown.

Column	Datatype	Description
PROCESS	VARCHAR2 (9)	Type of the process whose information is being reported: ■ RFS - Remote file server ■ MRP0 - Detached recovery server process ■ MR (fg) - Foreground recovery session ■ ARCH - Archiver process ■ FGRD ■ LGWR ■ RFS (FAL) ■ RFS (NEXP) ■ LNS - Network server process
PID	NUMBER	Operating system process identifier of the process
STATUS	VARCHAR2 (12)	Current process status: ■ UNUSED - No active process ■ ALLOCATED - Process is active but not currently connected to a primary database ■ CONNECTED - Network connection established to a primary database ■ ATTACHED - Process is actively attached and communicating to a primary database ■ IDLE - Process is not performing any activities ■ ERROR - Process has failed ■ OPENING - Process is opening the archived redo log ■ CLOSING - Process has completed archival and is closing the archived redo log ■ WRITING - Process is actively writing redo data to the archived redo log ■ RECEIVING - Process is receiving network communication ■ ANNOUNCING - Process is announcing the existence of a potential dependent archived redo log ■ REGISTERING - Process is registering the existence of a completed dependent archived redo log ■ WAIT_FOR_LOG - Process is waiting for the archived redo log to be completed ■ WAIT_FOR_GAP - Process is waiting for the archive gap to be resolved ■ APPLYING_LOG - Process is actively applying the archived redo log to the standby database
CLIENT_PROCESS	VARCHAR2 (8)	Identifies the corresponding primary database process: ■ Archival - Foreground (manual) archival process (SQL) ■ ARCH - Background ARCH_n process ■ LGWR - Background LGWR process
CLIENT_PID	VARCHAR2 (40)	Operating system process identifier of the client process
CLIENT_DBID	VARCHAR2 (40)	Database identifier of the primary database
GROUP#	VARCHAR2 (40)	Standby redo log group
RESETLOG_ID	NUMBER	Resetlogs identifier of the archived redo log
THREAD#	NUMBER	Archived redo log thread number
SEQUENCE#	NUMBER	Archived redo log sequence number

Column	Datatype	Description
BLOCK#	NUMBER	Last processed archived redo log block number
BLOCKS	NUMBER	Count (in 512-byte blocks) of the last write to a redo log, or for a recovery process, the expected final read count
DELAY_MINS	NUMBER	Archived redo log delay interval in minutes
KNOWN_AGENTS	NUMBER	Total number of standby database agents processing an archived redo log
ACTIVE_AGENTS	NUMBER	Number of standby database agents actively processing an archived redo log

V\$MAP_COMP_LIST

V\$MAP_COMP_LIST displays supplementary information for all element mapping structures.

Column	Datatype	Description
ELEM_IDX	NUMBER	Index corresponding to the element
NUM_COMP	NUMBER	Number of components (maximum is 5)
COMP1_NAME	VARCHAR2 (256)	Name of the first component
COMP1_VAL	VARCHAR2 (256)	Value of the first component
COMP2_NAME	VARCHAR2 (256)	Name of the second component
COMP2_VAL	VARCHAR2 (256)	Value of the second component
COMP3_NAME	VARCHAR2 (256)	Name of the third component
COMP3_VAL	VARCHAR2 (256)	Value of the third component
COMP4_NAME	VARCHAR2 (256)	Name of the fourth component
COMP4_VAL	VARCHAR2 (256)	Value of the fourth component
COMP5_NAME	VARCHAR2 (256)	Name of the fifth component
COMP5_VAL	VARCHAR2 (256)	Value of the fifth component

V\$MAP_ELEMENT

V\$MAP_ELEMENT displays a list of all element mapping structures in the SGA of the instance.

Column	Datatype	Description
ELEM_NAME	VARCHAR2 (256)	Element name
ELEM_IDX	NUMBER	Index corresponding to the element
ELEM_CFGID	VARCHAR2 (256)	Configuration ID (N/A if configuration ID is not supported)
ELEM_TYPE	VARCHAR2 (12)	Element type: ■ MIRROR ■ STRIPE ■ RAID5 ■ CONCATENATED ■ PARTITION ■ DISK ■ NONE
ELEM_SIZE	NUMBER	Element Size in HKB
ELEM_NSUBELEM	NUMBER	Number of Subelements
ELEM_DESCR	VARCHAR2 (256)	Element Description

Column	Datatype	Description
STRIPE_SIZE	NUMBER	Stripe Size in HKB for RAID-5 and STRIPE elements, 0 for the remaining types
LIB_IDX	NUMBER	Index of the library which claims ownership of the element

V\$MAP_EXT_ELEMENT

V\$MAP_EXT_ELEMENT displays supplementary information for all element mapping structures.

Column	Datatype	Description
ELEM_IDX	NUMBER	Index corresponding to the element
NUM_ATTRB	NUMBER	Number of Attributes (maximum is 5)
ATTRB1_NAME	VARCHAR2 (256)	Name of the first Attribute
ATTRB1_VAL	VARCHAR2 (256)	Value of the first attribute
ATTRB2_NAME	VARCHAR2 (256)	Name of the second attribute
ATTRB2_VAL	VARCHAR2 (256)	Value of the second attribute
ATTRB3_NAME	VARCHAR2 (256)	Name of the third attribute
ATTRB3_VAL	VARCHAR2 (256)	Value of the third attribute
ATTRB4_NAME	VARCHAR2 (256)	Name of the fourth attribute
ATTRB4_VAL	VARCHAR2 (256)	Value of the fourth attribute
ATTRB5_NAME	VARCHAR2 (256)	Name of the fifth attribute
ATTRB5_VAL	VARCHAR2 (256)	Value of the fifth attribute

V\$MAP_FILE

V\$MAP_FILE displays a list of all file mapping structures in the shared memory of the instance.

Column	Datatype	Description
FILE_MAP_IDX	NUMBER	Index corresponding to the file
FILE_CFGID	VARCHAR2 (256)	Configuration ID (N/A if configuration ID is not supported)
FILE_STATUS	VARCHAR2 (7)	Status of the mapping information: - VALID - File mapping information is latest - INVALID - Mapping needs to be refreshed
FILE_NAME	VARCHAR2 (256)	Absolute file name
FILE_TYPE	VARCHAR2 (11)	File type: - DATAFILE - SPFILE - TEMPFILE - CONTROLFILE - LOGFILE - ARCHIVEFILE
FILE_STRUCTURE	VARCHAR2 (9)	File structure: - FILE - RAWVOLUME - RAWDEVICE - NONE

Column	Datatype	Description
FILE_SIZE	NUMBER	File size in HKB (half KB)
FILE_NEXTS	NUMBER	Number of file extents in the file (not necessarily the same as the number of file extents mapped)
LIB_IDX	NUMBER	Index of mapping library claiming ownership of the file

V\$MAP_FILE_EXTENT

V\$MAP_FILE_EXTENT displays a list of all file extent mapping structures in the shared memory of the instance.

Column	Datatype	Description
FILE_MAP_IDX	NUMBER	File index (corresponds to FILE_MAP_IDX in V\$MAP_FILE)
EXT_NUM	NUMBER	File extent number
EXT_ELEM_OFF	NUMBER	Element offset in HKB
EXT_SIZE	NUMBER	File extent size in HKB
EXT_FILE_OFF	NUMBER	File Offset in HKB
EXT_TYPE	VARCHAR2 (6)	File Extent Type: - DATA - PARITY - NONE
ELEM_IDX	NUMBER	Index in V\$MAP_ELEMENT corresponding to the element where the file extent resides

V\$MAP_FILE_IO_STACK

V\$MAP_FILE_IO_STACK displays the hierarchical arrangement of storage containers for files. Each row in the view represents a level in the hierarchy.

Column	Datatype	Description
FILE_MAP_IDX	NUMBER	File index (corresponds to FILE_MAP_IDX in V\$MAP_FILE)
DEPTH	NUMBER	Element depth within the I/O stack
ELEM_IDX	NUMBER	Index corresponding to the element
CU_SIZE	NUMBER	Contiguous set of logical blocks of the file (in HKB units) that is resident contiguously on the element
STRIDE	NUMBER	Number of HKB between contiguous units (CU) in the file that are contiguous on this element. Used in RAID5 and striped files.
NUM_CU	NUMBER	Number of contiguous units that are adjacent to each other on this element that are separated by STRIDE HKB in the file. In RAID5, the number of contiguous units also include the parity stripes.
ELEM_OFFSET	NUMBER	Element offset in HKB units
FILE_OFFSET	NUMBER	Offset in HKB units from the start of the file to the first byte of the contiguous units
DATA_TYPE	VARCHAR2 (15)	Datatype: - DATA - PARITY - DATA AND PARITY
PARITY_POS	NUMBER	Position of the parity. Only for RAID5. This column is needed to distinguish the parity from the data part.
PARITY_PERIOD	NUMBER	Parity period. Only for RAID5.

Column	Datatype	Description
ID	NUMBER	Unique identifier
PARENT_ID	NUMBER	Parent identifier

V\$MAP_LIBRARY

V\$MAP_LIBRARY displays a list of all mapping libraries dynamically loaded by the external process.

Column	Datatype	Description
LIB_IDX	NUMBER	Index corresponding to the library
LIB_NAME	VARCHAR2 (256)	Absolute library name
VENDOR_NAME	VARCHAR2 (64)	Name of the vendor implementing the library
PROTOCOL_NUM	NUMBER	Mapping protocol that the library supports
VERSION_NUM	VARCHAR2 (32)	Version number
PATH_NAME	VARCHAR2 (4000)	Path name
MAP_FILE	VARCHAR2 (1)	Indicates whether the library supports mapping files (Y) or not (N)
FILE_CFGID	VARCHAR2 (13)	Type of configuration ID supported for files: - NONE - Not supported - PERSISTENT - NONPERSISTENT
MAP_ELEM	VARCHAR2 (1)	Indicates whether the library supports mapping elements (Y) or not (N)
ELEM_CFGID	VARCHAR2 (13)	Type of configuration id supported for elements: - NONE - Not supported - PERSISTENT - NONPERSISTENT
MAP_SYNC	VARCHAR2 (1)	Indicates whether the library needs to be explicitly synced so that future mappings reflect the most recent changes (Y) or not (N). Note that configuration IDs cannot be supported if the library needs to be explicitly synced.

V\$MAP_SUBELEMENT

V\$MAP_SUBELEMENT displays a list of all subelement mapping structures in the shared memory of the instance.

Column	Datatype	Description
CHILD_IDX	NUMBER	Index in V\$MAP_ELEMENT corresponding to the child element
PARENT_IDX	NUMBER	Index in V\$MAP_ELEMENT corresponding to the parent element
SUB_NUM	NUMBER	Subelement number
SUB_SIZE	NUMBER	Subelement size in HKB
ELEM_OFFSET	NUMBER	Offset in HKB on the child element
SUB_FLAGS	NUMBER	Subelement flags (currently unused)

V\$MEMORY_CURRENT_RESIZE_OPS

V\$MEMORY_CURRENT_RESIZE_OPS displays information about memory resize operations (both automatic and manual) which are currently in progress. An operation

can be a grow or a shrink of a dynamic memory component. All sizes are expressed in bytes.

Column	Datatype	Description
COMPONENT	VARCHAR2 (64)	Component name
OPER_TYPE	VARCHAR2 (13)	Operation type: ■ STATIC ■ INITIALIZING ■ DISABLED ■ GROW ■ SHRINK ■ SHRINK_CANCEL
OPER_MODE	VARCHAR2 (9)	Operation mode: ■ MANUAL ■ DEFERRED ■ IMMEDIATE
PARAMETER	VARCHAR2 (80)	Name of the parameter for the resize operation
INITIAL_SIZE	NUMBER	Parameter value at the start of the operation
TARGET_SIZE	NUMBER	Desired value of the parameter after the resize
CURRENT_SIZE	NUMBER	Current value of the parameter
START_TIME	DATE	Start time of the operation
LAST_UPDATE_TIME	DATE	Last time progress was made for the operation

V\$MEMORY_DYNAMIC_COMPONENTS

V\$MEMORY_DYNAMIC_COMPONENTS displays information about the dynamic SGA components. This view summarizes information based on all completed SGA resize operations since instance startup. All sizes are expressed in bytes.

Column	Datatype	Description
COMPONENT	VARCHAR2 (64)	Component name
CURRENT_SIZE	NUMBER	Current size of the component
MIN_SIZE	NUMBER	Minimum size of the component since instance startup
MAX_SIZE	NUMBER	Maximum size of the component since instance startup
USER_SPECIFIED_SIZE	NUMBER	Value of the user parameter for the component
OPER_COUNT	NUMBER	Number of operations since instance startup
LAST_OPER_TYPE	VARCHAR2 (13)	Last completed operation for the component: ■ STATIC ■ INITIALIZING ■ DISABLED ■ GROW ■ SHRINK ■ SHRINK_CANCEL
LAST_OPER_MODE	VARCHAR2 (9)	Mode of the last completed operation: ■ MANUAL ■ DEFERRED ■ IMMEDIATE
LAST_OPER_TIME	DATE	Start time of the last completed operation

Column	Datatype	Description
GRANULE_SIZE	NUMBER	Granularity of the GROW or SHRINK operation

V\$MEMORY_RESIZE_OPS

V\$MEMORY_RESIZE_OPS displays information about the last 800 completed memory resize operations (both automatic and manual). This does not include in-progress operations. All sizes are expressed in bytes.

Column	Datatype	Description
COMPONENT	VARCHAR2 (64)	Component name
OPER_TYPE	VARCHAR2 (13)	Operation type: ■ STATIC ■ INITIALIZING ■ DISABLED ■ GROW ■ SHRINK ■ SHRINK_CANCEL
OPER_MODE	VARCHAR2 (9)	Operation mode: ■ MANUAL ■ DEFERRED ■ IMMEDIATE
PARAMETER	VARCHAR2 (80)	Name of the parameter for the resize operation
INITIAL_SIZE	NUMBER	Parameter value at the start of the operation
TARGET_SIZE	NUMBER	Requested value of the parameter after the resize
FINAL_SIZE	NUMBER	Real value of the parameter after the resize
STATUS	VARCHAR2 (9)	Completion status of the operation: ■ INACTIVE ■ PENDING ■ COMPLETE ■ CANCELLED ■ ERROR
START_TIME	DATE	Start time of the operation
END_TIME	DATE	End time of the operation

V\$MEMORY_TARGET_ADVICE

V\$MEMORY_TARGET_ADVICE provides information about how the MEMORY_TARGET parameter should be sized based on current sizing and satisfaction metrics.

Column	Datatype	Description
MEMORY_SIZE	NUMBER	If the MEMORY_SIZE_FACTOR column has a value of 1, then this column shows the current size of memory, as set by the MEMORY_TARGET initialization parameter. If the value of the MEMORY_SIZE_FACTOR column is less than or greater than 1, then this column shows a proposed memory size.
MEMORY_SIZE_FACTOR	NUMBER	A multiplier for the current memory size. Possible values are 0.25, 0.5, 0.75, 1, 1.5, 1.75, and 2. This multiplier times the current memory size equals the value of the MEMORY_SIZE column.

Column	Datatype	Description
ESTD_DB_TIME	NUMBER	For current memory size (MEMORY_SIZE_FACTOR = 1), the amount of database time required to complete the current workload. For a proposed memory size, the estimated amount of database time that would be required if the MEMORY_TARGET parameter were changed to the proposed size.
ESTD_DB_TIME_FACTOR	NUMBER	For a proposed memory size, ratio of estimated database time to current database time
VERSION	NUMBER	Version number of this recommendation (this snapshot of the V\$MEMORY_TARGET_ADVICE view)

Table 8–2 shows how the information provided in V\$MEMORY_TARGET_ADVICE could be used to improve performance. The data indicates that if current memory size is 380M, and you were to increase it to 760M (2x), the current workload would take 80525 units of DBtime as opposed to 115475 units of DBtime, which is a significant improvement in performance.

Table 8–2 Example of Using V\$MEMORY_TARGET_ADVICE

MEMORY_SIZE	MEMORY_SIZE_FACTOR	ESTD_DB_TIME	ESTD_DB_TIME_FACTOR	VERSION
380	1	115475	1	3
95	.25	200500	1.7	3
190	.5	125600	1.1	3
760	2	80525	0.7	3

V\$METRIC

V\$METRIC displays the most recent statistic values for the complete set of metrics captured by the AWR infrastructure.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time for the metric value
END_TIME	DATE	End time for the metric value
INTSIZE_CSEC	NUMBER	Size of the time period
GROUP_ID	NUMBER	Metric Group ID. Refer to the V\$METRICNAME view for the name of the group.
ENTITY_ID	NUMBER	Entity ID for the metric in question. The value of the Entity ID depends upon the metric group. (See the following table for an explanation of possible values.)
ENTITY_SEQUENCE	NUMBER	Entity Sequence number for the metric in question. The value of the Entity Sequence depends upon the metric group. (See the following table for an explanation of possible values.)
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2 (64)	Metric Name. This is the statistic that is captured for the entity.
VALUE	NUMBER	Value of the statistic between BEGIN_TIME and END_TIME
METRIC_UNIT	VARCHAR2 (64)	Unit for the VALUE

The following table describes what the ENTITY_ID and ENTITY_SEQUENCE are for each metric group:

GID	Group NAME	Entity ID	Entity Sequence
0	Event Metrics	Event#	N/A
1	Event Class Metrics	Wait Class ID	N/A
2	System Metrics Long Duration	N/A	N/A
3	System Metrics Short Duration	N/A	N/A
4	Session Metrics Long Duration	Session ID	Serial#
5	Session Metrics Short Duration	Session ID	Serial#
6	Service Metrics	N/A	Service Hash
7	File Metrics Long Duration	File#	Creation Change#
9	Tablespace Metrics Long Duration	Tablespace#	N/A
10	Service Metrics (Short)	N/A	Service Hash

V\$METRICGROUP

V\$METRICGROUP displays information about the metric group for each of the four major Streams components: capture, propagation, apply, and queue.

Column	Datatype	Description
GROUP_ID	NUMBER	Internal ID associated with each group
NAME	VARCHAR2 (64)	External name of the group
INTERVAL_SIZE	NUMBER	How often to collect statistics
MAX_INTERVAL	NUMBER	Total number of intervals over which statistics should be collected

V\$METRIC_HISTORY

V\$METRIC_HISTORY displays all the available statistic values for the complete set of metrics captured by the AWR infrastructure.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time for the metric value
END_TIME	DATE	End time for the metric value
INTSIZE_CSEC	NUMBER	Size of the time period
GROUP_ID	NUMBER	Metric Group ID. Refer to the V\$METRICNAME view for the name of the group.
ENTITY_ID	NUMBER	Entity ID for the metric in question. The value of the Entity ID depends upon the metric group. (See the table in the description of V\$METRIC for an explanation of possible values.)
ENTITY_SEQUENCE	NUMBER	Entity Sequence number for the metric in question. The value of the Entity Sequence depends upon the metric group. (See the table in the description of V\$METRIC for an explanation of possible values.)
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2 (64)	Metric Name. This is the statistic that is captured for the entity.
VALUE	NUMBER	Value of the statistic between BEGIN_TIME and END_TIME
METRIC_UNIT	VARCHAR2 (64)	Unit for the VALUE

V\$METRICNAME

V\$METRICNAME displays the mapping of the name of metrics to their metric ID.

Column	Datatype	Description
GROUP_ID	NUMBER	Metric group ID
GROUP_NAME	VARCHAR2 (64)	Metric group name
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2 (64)	Metric name
METRIC_UNIT	VARCHAR2 (64)	Unit of measurement

V\$MTTR_TARGET_ADVICE

V\$MTTR_TARGET_ADVICE displays rows that predict the number of physical I/Os for the MTTR corresponding to each row. The rows also compute a physical I/O factor, which is the ratio of the number of estimated I/Os to the number of I/Os actually performed by the current MTTR setting during the measurement interval.

The content of the view is empty if MTTR advisory has not been turned on since database startup. Otherwise, it returns the advisory information collected. If advisory is currently off, then this information comes from the last time MTTR advisory was on. FAST_START_MTTR_TARGET must be set to a nonzero value if the STATISTICS_LEVEL parameter is dynamically modified to turn MTTR advisory on.

If the FAST_START_MTTR_TARGET parameter is changed while MTTR advisory is on, then MTTR advisory is temporarily turned off until the new FAST_START_MTTR_TARGET setting takes effect. During this transition period, the contents of V\$MTTR_TARGET_ADVICE reflect the simulation result for the old MTTR setting.

Column	Datatype	Description
MTTR_TARGET_FOR_ESTIMATE	NUMBER	MTTR setting being simulated. Equal to the current MTTR setting if this is the first row of the view.
ADVICE_STATUS	VARCHAR2 (5)	Current status of MTTR simulation: ■ ON ■ READY ■ OFF
DIRTY_LIMIT	NUMBER	Dirty buffer limit derived from the MTTR being simulated
ESTD_CACHE_WRITES	NUMBER	Estimated number of cache physical writes under this MTTR
ESTD_CACHE_WRITE_FACTOR	NUMBER	Estimated cache physical write ratio under this MTTR. It is the ratio of the estimated number of cache writes to the number of cache writes under the current MTTR setting.
ESTD_TOTAL_WRITES	NUMBER	Estimated total number of physical writes under this MTTR
ESTD_TOTAL_WRITE_FACTOR	NUMBER	Estimated total physical write ratio under this MTTR. It is the ratio of the estimated total number of physical writes to the total number of physical writes under the current MTTR setting.
ESTD_TOTAL_IOS	NUMBER	Estimated total number of I/Os under this MTTR
ESTD_TOTAL_IO_FACTOR	NUMBER	Estimated total I/O ratio under this MTTR. It is the ratio of the estimated total number of I/Os to the total number of I/Os under the current MTTR setting.

V\$MUTEX_SLEEP

V\$MUTEX_SLEEP shows the wait time, and the number of sleeps for each combination of mutex type and location.

Column	Datatype	Description
MUTEX_TYPE	VARCHAR2 (32)	Type of action/object the mutex protects
LOCATION	VARCHAR2 (40)	The code location where the waiter slept for the mutex
SLEEPS	NUMBER	Number of sleeps for this MUTEX_TYPE and LOCATION
WAIT_TIME	NUMBER	Wait time in microseconds

V\$MUTEX_SLEEP_HISTORY

V\$MUTEX_SLEEP_HISTORY displays time-series data. Each row in this view is for a specific time, mutex type, location, requesting session and blocking session combination. That is, it shows data related to a specific session (requesting session) that slept while requesting a specific mutex type and location, because it was being held by a specific blocking session. The data in this view is contained within a circular buffer, with the most recent sleeps shown.

Column	Datatype	Description
MUTEX_IDENTIFIER	NUMBER	Mutex ID
SLEEP_TIMESTAMP	TIMESTAMP (6)	The last date/time this MUTEX_TYPE and LOCATION was slept for by the REQUESTING_SESSION, while being held by the BLOCKING_SESSION.
MUTEX_TYPE	VARCHAR2 (32)	Type of action/object the mutex protects
GETS	NUMBER	The number of times the mutex/location was requested by the requesting session while being held by the blocking session. GETS is only incremented once per request, irrespective of the number of sleeps required to obtain the mutex.
SLEEPS	NUMBER	The number of times the requestor had to sleep before obtaining the mutex
REQUESTING_SESSION	NUMBER	The SID of a session requesting the mutex
BLOCKING_SESSION	NUMBER	The SID of a session holding the mutex
LOCATION	VARCHAR2 (40)	The code location where the waiter slept for the mutex
MUTEX_VALUE	RAW (4)	If the mutex is held in exclusive (X) mode, this column shows the SID of the blocking session, else it shows the number of sessions referencing the mutex in S mode.
P1	NUMBER	Reserved for internal use
P1RAW	RAW (4)	Reserved for internal use
P2	NUMBER	Reserved for internal use
P3	NUMBER	Reserved for internal use
P4	NUMBER	Reserved for internal use
P5	VARCHAR2 (64)	Reserved for internal use

V\$MVREFRESH

V\$MVREFRESH displays information about the materialized views currently being refreshed.

Column	Datatype	Description
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Session serial number, which is used to uniquely identify a session's objects. Guarantees that session-level commands are applied to the correct session objects if the session ends with, and another session begins with, the same session ID.

Column	Datatype	Description
CURRMVOWNER	VARCHAR2 (31)	Owner of the materialized view currently being refreshed. The materialized view resides in this user's schema.
CURRMVNAME	VARCHAR2 (31)	Name of the materialized view currently being refreshed

V\$MYSTAT

V\$MYSTAT contains statistics on the current session.

Column	Datatype	Description
SID	NUMBER	ID of the current session
STATISTIC#	NUMBER	Number of the statistic
VALUE	NUMBER	Value of the statistic

V\$NFS_CLIENTS

V\$NFS_CLIENTS displays information about NFS clients currently connected to the XML DB NFS Server.

Column	Datatype	Description
CLIENTID	NUMBER	A number identifying the client
PRINCIPAL	VARCHAR2 (2000)	User string denoting the principal that set the client ID (SetClientId)
CLIENTOPAQUEIDENTIFIER	VARCHAR2 (1000)	Opaque string presented as identification by the client to the NFS server
VERIFIER	RAW (8)	Verifier presented by the client
LEASEEXPIRY	NUMBER	Number of seconds in which the lease expires for the client
CLIENTADDR	VARCHAR2 (2000)	Address of the client
CONFIRMED	VARCHAR2 (5)	TRUE if the client is confirmed; otherwise FALSE

V\$NFS_LOCKS

V\$NFS_LOCKS displays information about byte range locks held on different files by NFS clients.

Column	Datatype	Description
OPENSTATEID	RAW (16)	Open state ID of the open owner
OPENSEQUENCEID	NUMBER	Open Sequence ID of the open owner
LOCKSTATEID	RAW (16)	Lock state ID of the lock owner
LOCKSEQUENCEID	NUMBER	Lock sequence ID of the lock owner
LOCKOWNER	VARCHAR2 (2000)	Opaque string presented as identification by the lock owner to the NFS server
OFFSET	NUMBER	Byte Offset from which lock starts
LENGTH	NUMBER	Length of the lock
LOCKTYPE	VARCHAR2 (20)	Type of the lock

V\$NFS_OPEN_FILES

V\$NFS_OPEN_FILES displays information about all the files currently opened by clients at the NFS server.

Column	Datatype	Description
CLIENTID	NUMBER	Number identifying the client
OPENOWNEROPAQUE	VARCHAR2 (2000)	All the files currently opened by clients at the NFS server
OPENSTATEID	RAW (16)	Open state ID of the open owner
FILEHANDLE	RAW (32)	FileHandle of the file that has been opened
OPENSEQUENCEID	NUMBER	Open sequence ID of open owner
OPENREAD	VARCHAR2 (5)	TRUE if the file is open for READ operations; otherwise FALSE
OPENWRITE	VARCHAR2 (5)	TRUE if the file is open for WRITE operations; otherwise FALSE
SHAREACCESS	VARCHAR2 (15)	Sharing mode of the file (SharedReadWrite, SharedRead, SharedWrite)
SHAREDENY	VARCHAR2 (13)	Deny mode of the file (DenyReadWrite, DenyRead, DenyWrite)
CONFIRMED	VARCHAR2 (5)	TRUE if open is confirmed; otherwise FALSE

V\$NLS_PARAMETERS

V\$NLS_PARAMETERS contains current values of NLS parameters.

Column	Datatype	Description
PARAMETER	VARCHAR2 (64)	Parameter names are as follows: NLS_CALENDAR, NLS_CHARACTERSET, NLS_COMP, NLS_CURRENCY, NLS_DATE_FORMAT, NLS_DATE_LANGUAGE, NLS_DUAL_CURRENCY, NLS_ISO_CURRENCY, NLS_LANGUAGE, NLS_LENGTH_SEMANTICS, NLS_NCHAR_CHARACTERSET, NLS_NCHAR_CONV_EXCP, NLS_NUMERIC_CHARACTERS, NLS_SORT, NLS_TERRITORY, NLS_TIMESTAMP_FORMAT, NLS_TIMESTAMP_TZ_FORMAT Two additional parameters, NLS_TIME_FORMAT and NLS_TIME_TZ_FORMAT, are currently used for internal purposes only.
VALUE	VARCHAR2 (64)	NLS parameter value

V\$NLS_VALID_VALUES

V\$NLS_VALID_VALUES lists all valid values for NLS parameters.

Column	Datatype	Description
PARAMETER	VARCHAR2 (64)	Parameter name (LANGUAGE SORT TERRITORY CHARACTERSET)
VALUE	VARCHAR2 (64)	NLS parameter value
ISDEPRECATED	VARCHAR2 (5)	Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)

V\$OBJECT_DEPENDENCY

V\$OBJECT_DEPENDENCY displays the objects depended on by a package, procedure, or cursor that is currently loaded in the shared pool. For example, together with V\$SESSION and V\$SQL, this view can be used to determine which tables are used in the SQL statement that a user is currently executing.

See Also: ["V\\$SESSION"](#) on page 9-8 and ["V\\$SQL"](#) on page 9-28

Column	Datatype	Description
FROM_ADDRESS	RAW (4 8)	Address of a procedure, package, or cursor that is currently loaded in the shared pool

Column	Datatype	Description
FROM_HASH	NUMBER	Hash value of a procedure, package, or cursor that is currently loaded in the shared pool
TO_OWNER	VARCHAR2 (64)	Owner of the object that is depended on
TO_NAME	VARCHAR2 (1000)	Name of the object that is depended on
TO_ADDRESS	RAW (4 8)	Address of the object that is depended on. These can be used to look up more information on the object in V\$DB_OBJECT_CACHE.
TO_HASH	NUMBER	Hash value of the object that is depended on. These can be used to look up more information on the object in V\$DB_OBJECT_CACHE.
TO_TYPE	NUMBER	Type of the object that is depended on

V\$OBJECT_PRIVILEGE

V\$OBJECT_PRIVILEGE displays information about privileges associated with an object.

Column	Datatype	Description
OBJECT_TYPE_NAME	VARCHAR2 (64)	Name of the object type
OBJECT_TYPE_ID	NUMBER	ID of the object type
PRIVILEGE_ID	NUMBER	ID of the privilege
PRIVILEGE_NAME	VARCHAR2 (64)	Name of the privilege

V\$OBJECT_USAGE

V\$OBJECT_USAGE displays statistics about index usage gathered from the database for the indexes owned by the current user. You can use this view to monitor index usage. All indexes that have been used at least once can be monitored and displayed in this view.

Column	Datatype	Description
INDEX_NAME	VARCHAR2 (30)	Index name in sys.obj\$.name
TABLE_NAME	VARCHAR2 (30)	Table name in sys.obj\$.name
MONITORING	VARCHAR2 (3)	YES NO
USED	VARCHAR2 (3)	YES NO
START_MONITORING	VARCHAR2 (19)	Start monitoring time in sys.object_stats.start_monitoring
END_MONITORING	VARCHAR2 (19)	End monitoring time in sys.object_stats.end_monitoring

V\$OBSOLETE_BACKUP_FILES

V\$OBSOLETE_BACKUP_FILES displays all obsolete backups, copies, and archived logs according to the current retention policy. This view requires that the database is set using the DBMS_RCVMAN.SETDATABASE procedure.

Column	Datatype	Description
PKEY	NUMBER	Primary key for the backup
BACKUP_TYPE	VARCHAR2 (32)	Type of the backup: ■ BACKUP SET ■ COPY ■ PROXY COPY

Column	Datatype	Description
FILE_TYPE	VARCHAR2 (32)	Type of the file: - DATAFILE - CONTROLFILE - SPFILE - REDO LOG - PIECE
KEEP	VARCHAR2 (3)	Indicates whether the backup has a retention policy different from the value for CONFIGURE RETENTION POLICY (YES) or not (NO)
KEEP_UNTIL	DATE	If the KEEP UNTIL TIME clause of the BACKUP command was specified, then this column shows the date after which the backup becomes obsolete. If the column is null and KEEP_OPTIONS is not null, the backup never becomes obsolete.
KEEP_OPTIONS	VARCHAR2 (13)	KEEP options for the backup: - LOGS - RMAN keeps the logs needed to recover the backup - NOLOGS - RMAN does not keep the logs needed to recover the backup If this column is null, then the backup has no KEEP options and will be made obsolete based on the retention policy.
STATUS	VARCHAR2 (16)	Status of the backup: - AVAILABLE - UNAVAILABLE - EXPIRED - OTHER
FNAME	VARCHAR2 (1024)	Name of the file
TAG	VARCHAR2 (32)	Tag of the piece, copy, or proxy copy
MEDIA	VARCHAR2 (80)	Media ID of the piece or proxy copy
RECID	NUMBER	Recid of the record in the controlfile
STAMP	NUMBER	Stamp of the record in the controlfile
DEVICE_TYPE	VARCHAR2 (255)	Type of media device that stores the backup
BLOCK_SIZE	NUMBER	Block size for the backup (in bytes)
COMPLETION_TIME	DATE	Time when the backup completed
BS_KEY	NUMBER	Primary key of the backup set (valid only when BACKUP_TYPE is BACKUP SET)
BS_COUNT	NUMBER	Count of the backup set from the controlfile record (valid only when BACKUP_TYPE is BACKUP SET)
BS_STAMP	NUMBER	Stamp of the backup set from the controlfile record (valid only when BACKUP_TYPE is BACKUP SET)
BS_TYPE	VARCHAR2 (32)	Type of the backup set (valid only when BACKUP_TYPE is BACKUP SET): - DATAFILE - ARCHIVED LOG
BS_INCR_TYPE	VARCHAR2 (32)	Incremental level of the backup set (valid only when BACKUP_TYPE is BACKUP SET)
BS_PIECES	NUMBER	Number of backup pieces in the backup set (valid only when BACKUP_TYPE is BACKUP SET)
BS_COMPLETION_TIME	DATE	Completion time of the backup set (valid only when BACKUP_TYPE is BACKUP SET)
BP_PIECE#	NUMBER	Number of the backup piece (valid only when FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)
BP_COPY#	NUMBER	Copy number of the backup piece (valid only when FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)

Column	Datatype	Description
DF_FILE#	NUMBER	Absolute file number of the datafile (valid only when FILE_TYPE is DATAFILE)
DF_RESETLOGS_CHANGE#	NUMBER	System change number (SCN) of the most recent RESETLOGS when the control file or datafile was created (valid only when FILE_TYPE is DATAFILE)
DF_CREATION_CHANGE#	NUMBER	Creation SCN of the control file or datafile (valid only when FILE_TYPE is DATAFILE)
DF_CHECKPOINT_CHANGE#	NUMBER	System change number (SCN) of the most recent control file or datafile checkpoint (valid only when FILE_TYPE is DATAFILE)
DF_CKP_MOD_TIME	DATE	Modification time in case of SPFILE, otherwise time when the control file or datafile was checkpointed (valid only when FILE_TYPE is DATAFILE)
RL_THREAD#	NUMBER	Number of the redo thread (valid only when FILE_TYPE is REDO LOG)
RL_SEQUENCE#	NUMBER	Log sequence number (valid only when FILE_TYPE is REDO LOG)
RL_RESETLOGS_CHANGE#	NUMBER	System change number (SCN) of the most recent RESETLOGS when the record was created (valid only when FILE_TYPE is REDO LOG)
RL_FIRST_CHANGE#	NUMBER	First SCN of the redo log (valid only when FILE_TYPE is REDO LOG)
RL_FIRST_TIME	DATE	Time when Oracle switched into the redo log (valid only when FILE_TYPE is REDO LOG)
RL_NEXT_CHANGE#	NUMBER	First SCN of the next redo log in the thread (valid only when FILE_TYPE is REDO LOG)
RL_NEXT_TIME	DATE	First timestamp of the next redo log in the thread (valid only when FILE_TYPE is REDO LOG)

V\$OBSOLETE_PARAMETER

V\$OBSOLETE_PARAMETER displays information about obsolete initialization parameters. If any row of the view contains TRUE in the ISSPECIFIED column, then you should examine why.

Column	Datatype	Description
NAME	VARCHAR2 (64)	Name of the parameter
ISSPECIFIED	VARCHAR2 (5)	Indicates whether the parameter was specified in the parameter file (TRUE) or not (FALSE)

V\$OFFLINE_RANGE

V\$OFFLINE_RANGE displays datafile offline information from the control file. Note that the last offline range of each datafile is kept in the DATAFILE record.

An offline range is created for a datafile when its tablespace is first altered to be OFFLINE NORMAL or READ ONLY, and then subsequently altered to be ONLINE or read/write. Note that no offline range is created if the datafile itself is altered to be OFFLINE or if the tablespace is altered to be OFFLINE IMMEDIATE.

See Also: "[V\\$DATAFILE](#)" on page 7-74

Column	Datatype	Description
RECID	NUMBER	Record ID
STAMP	NUMBER	Record stamp
FILE#	NUMBER	Datafile number
OFFLINE_CHANGE#	NUMBER	SCN at which offlined

Column	Datatype	Description
ONLINE_CHANGE#	NUMBER	SCN at which onlined
ONLINE_TIME	DATE	Time of offline SCN
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the record
RESETLOGS_TIME	DATE	Resetlogs timestamp of the record

V\$OPEN_CURSOR

V\$OPEN_CURSOR lists cursors that each user session currently has opened and parsed, or cached.

Column	Datatype	Description
SADDR	RAW (4 8)	Session address
SID	NUMBER	Session identifier
USER_NAME	VARCHAR2 (30)	User that is logged in to the session
ADDRESS	RAW (4 8)	Used with HASH_VALUE to uniquely identify the SQL statement being executed in the session
HASH_VALUE	NUMBER	Used with ADDRESS to uniquely identify the SQL statement being executed in the session
SQL_ID	VARCHAR2 (13)	SQL identifier of the SQL statement being executed in the session
SQL_TEXT	VARCHAR2 (60)	First 60 characters of the SQL statement that is parsed into the open cursor
LAST_SQL_ACTIVE_TIME	DATE	Time when this cursor was last executed
SQL_EXEC_ID	NUMBER	If the open cursor is executing, then the SQL execution identifier for that execution (see V\$SQL_MONITOR)
CURSOR_TYPE	VARCHAR2 (64)	Type of cursor: ■ BUNDLE DICTIONARY LOOKUP CACHED ■ CONSTRAINTS CURSOR CACHED ■ DICTIONARY LOOKUP CURSOR CACHED ■ OPEN ■ OPEN-PL/SQL ■ OPEN-RECURSIVE ■ PL/SQL CURSOR CACHED ■ REPLICATION TRIGGER CURSOR CACHED ■ SESSION CURSOR CACHED

V\$OPTION

V\$OPTION displays Oracle Database options and features. Typically, although not always, options must be separately licensed, whereas features come with the product and are enabled based on the product that is running (Standard Edition, Enterprise Edition, and so on).

Column	Datatype	Description
PARAMETER	VARCHAR2 (64)	Name of the option (or feature)
VALUE	VARCHAR2 (64)	Indicates whether the option (or feature) is installed (TRUE) or not (FALSE)

See Also: *Oracle Database Licensing Information*

V\$OSSTAT

V\$OSSTAT displays system utilization statistics from the operating system. One row is returned for each system statistic.

Column	Datatype	Description
STAT_NAME	VARCHAR2 (64)	Name of the statistic (see Table 8–3)
VALUE	NUMBER	Instantaneous statistic value
OSSTAT_ID	NUMBER	Statistic ID
COMMENTS	VARCHAR2 (64)	Any additional OS-specific clarifications for the statistic
CUMULATIVE	VARCHAR2 (3)	Indicates whether the statistic is cumulative (that is, accumulates over time) (YES) or not (NO)

Table 8–3 V\$OSSTAT Statistics

Statistic Name	Description
NUM_CPUS	Number of CPUs or processors available
IDLE_TIME	Number of hundredths of a second that a processor has been idle, totalled over all processors
BUSY_TIME	Number of hundredths of a second that a processor has been busy executing user or kernel code, totalled over all processors
USER_TIME	Number of hundredths of a second that a processor has been busy executing user code, totalled over all processors
SYS_TIME	Number of hundredths of a second that a processor has been busy executing kernel code, totalled over all processors
IOWAIT_TIME	Number of hundredths of a second that a processor has been waiting for I/O to complete, totalled over all processors
NICE_TIME	Number of hundredths of a second that a processor has been busy executing low-priority user code, totalled over all processors
AVG_IDLE_TIME	Number of hundredths of a second that a processor has been idle, averaged over all processors
AVG_BUSY_TIME	Number of hundredths of a second that a processor has been busy executing user or kernel code, averaged over all processors
AVG_USER_TIME	Number of hundredths of a second that a processor has been busy executing user code, averaged over all processors
AVG_SYS_TIME	Number of hundredths of a second that a processor has been busy executing kernel code, averaged over all processors
AVG_IOWAIT_TIME	Number of hundredths of a second that a processor has been waiting for I/O to complete, averaged over all processors
AVG_NICE_TIME	Number of hundredths of a second that a processor has been busy executing low-priority user code, averaged over all processors
OS_CPU_WAIT_TIME	Total number of hundredths of a second that processes have been in a ready state, waiting to be selected by the operating system scheduler to run
RSRC_MGR_CPU_WAIT_TIME	Total number of hundredths of a second that Oracle processes have been in a ready state, waiting for CPU to be available for their consumer group in the currently active resource plan
VM_PAGE_IN_BYTES	Total number of bytes of data that have been paged in due to virtual memory paging
VM_PAGE_OUT_BYTES	Total number of bytes of data that have been paged out due to virtual memory paging
PHYSICAL_MEMORY_BYTES	Total number of bytes of physical memory
LOAD	Current number of processes that are either running or in the ready state, waiting to be selected by the operating-system scheduler to run. On many platforms, this statistic reflects the average load over the past minute.
NUM_CPU_CORES	Number of CPU cores available (includes subcores of multicore CPUs as well as single-core CPUs)

Table 8–3 (Cont.) V\$OSSTAT Statistics

Statistic Name	Description
NUM_CPU_SOCKETS	Number of CPU sockets available (represents an absolute count of CPU chips on the system, regardless of multithreading or multi-core architectures)
NUM_VCPUS	Number of virtual CPUs available
NUM_LCPUS	Number of logical CPUs available (includes hardware threads if hardware threading is turned on)
TCP_SEND_SIZE_MIN	Minimum size of the TCP send buffer
TCP_SEND_SIZE_DEFAULT	Default size of the TCP send buffer
TCP_SEND_SIZE_MAX	Maximum size of the TCP send buffer
TCP_RECEIVE_SIZE_MIN	Minimum size of the TCP receive buffer
TCP_RECEIVE_SIZE_DEFAULT	Default size of the TCP receive buffer
TCP_RECEIVE_SIZE_MAX	Maximum size of the TCP receive buffer
GLOBAL_SEND_SIZE_MAX	Maximum size of the global send buffer
GLOBAL_RECEIVE_SIZE_MAX	Maximum size of the global receive buffer

Note: The availability of all statistics except for NUM_CPUS and RSRC_MGR_CPU_WAIT_TIME is subject to the operating system platform on which the Oracle Database is running.

V\$PARALLEL_DEGREE_LIMIT_MTH

V\$PARALLEL_DEGREE_LIMIT_MTH displays all available parallel degree limit resource allocation methods.

Column	Datatype	Description
NAME	VARCHAR2 (40)	Name of the parallel degree limit resource allocation method

V\$PARAMETER

V\$PARAMETER displays information about the initialization parameters that are currently in effect for the session. A new session inherits parameter values from the instance-wide values displayed by the V\$SYSTEM_PARAMETER view.

Column	Datatype	Description
NUM	NUMBER	Parameter number
NAME	VARCHAR2 (80)	Name of the parameter
TYPE	NUMBER	Parameter type: 1 - Boolean 2 - String 3 - Integer 4 - Parameter file 5 - Reserved 6 - Big integer
VALUE	VARCHAR2 (4000)	Parameter value for the session (if modified within the session); otherwise, the instance-wide parameter value
DISPLAY_VALUE	VARCHAR2 (4000)	Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K.

Column	Datatype	Description
ISDEFAULT	VARCHAR2 (9)	Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE)
ISSES_MODIFIABLE	VARCHAR2 (5)	Indicates whether the parameter can be changed with ALTER SESSION (TRUE) or not (FALSE)
ISSYS_MODIFIABLE	VARCHAR2 (9)	Indicates whether the parameter can be changed with ALTER SYSTEM and when the change takes effect: - IMMEDIATE - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect immediately. - DEFERRED - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect in subsequent sessions. - FALSE - Parameter cannot be changed with ALTER SYSTEM unless a server parameter file was used to start the instance. The change takes effect in subsequent instances.
ISINSTANCE_MODIFIABLE	VARCHAR2 (5)	For parameters that can be changed with ALTER SYSTEM, indicates whether the value of the parameter can be different for every instance (TRUE) or whether the parameter must have the same value for all Real Application Clusters instances (FALSE). If the ISSYS_MODIFIABLE column is FALSE, then this column is always FALSE.
ISMODIFIED	VARCHAR2 (10)	Indicates whether the parameter has been modified after instance startup: - MODIFIED - Parameter has been modified with ALTER SESSION - SYSTEM_MOD - Parameter has been modified with ALTER SYSTEM (which causes all the currently logged in sessions' values to be modified) - FALSE - Parameter has not been modified after instance startup
ISADJUSTED	VARCHAR2 (5)	Indicates whether Oracle adjusted the input value to a more suitable value (for example, the parameter value should be prime, but the user input a non-prime number, so Oracle adjusted the value to the next prime number)
ISDEPRECATED	VARCHAR2 (5)	Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)
ISBASIC	VARCHAR2 (5)	Indicates whether the parameter is a basic parameter (TRUE) or not (FALSE)
DESCRIPTION	VARCHAR2 (255)	Description of the parameter
UPDATE_COMMENT	VARCHAR2 (255)	Comments associated with the most recent update
HASH	NUMBER	Hash value for the parameter name

V\$PARAMETER_VALID_VALUES

V\$PARAMETER_VALID_VALUES displays a list of valid values for list parameters.

Column	Datatype	Description
NUM	NUMBER	Parameter number
NAME	VARCHAR2 (64)	Parameter name
ORDINAL	NUMBER	Ordinal number in the list (1-based)
VALUE	VARCHAR2 (255)	Parameter value at ordinal
ISDEFAULT	VARCHAR2 (64)	Indicates whether the given ordinal value is the default value for the parameter

V\$PARAMETER2

V\$PARAMETER2 displays information about the initialization parameters that are currently in effect for the session, with each list parameter value appearing as a row in

the view. A new session inherits parameter values from the instance-wide values displayed in the V\$SYSTEM_PARAMETER2 view.

Presenting the list parameter values in this format enables you to quickly determine the values for a list parameter. For example, if a parameter value is a, b, then the V\$PARAMETER view does not tell you if the parameter has two values (both a and b) or one value (a, b). V\$PARAMETER2 makes the distinction between the list parameter values clear.

Column	Datatype	Description
NUM	NUMBER	Parameter number
NAME	VARCHAR2 (80)	Name of the parameter
TYPE	NUMBER	Parameter type: 1 - Boolean 2 - String 3 - Integer 4 - Parameter file 5 - Reserved 6 - Big integer
VALUE	VARCHAR2 (4000)	Parameter value for the session (if modified within the session); otherwise, the instance-wide parameter value
DISPLAY_VALUE	VARCHAR2 (4000)	Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K.
ISDEFAULT	VARCHAR2 (6)	Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE)
ISSES_MODIFIABLE	VARCHAR2 (5)	Indicates whether the parameter can be changed with ALTER SESSION (TRUE) or not (FALSE)
ISSYS_MODIFIABLE	VARCHAR2 (9)	Indicates whether the parameter can be changed with ALTER SYSTEM and when the change takes effect: - IMMEDIATE - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect immediately. - DEFERRED - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect in subsequent sessions. - FALSE - Parameter cannot be changed with ALTER SYSTEM unless a server parameter file was used to start the instance. The change takes effect in subsequent instances.
ISINSTANCE_MODIFIABLE	VARCHAR2 (5)	For parameters that can be changed with ALTER SYSTEM, indicates whether the value of the parameter can be different for every instance (TRUE) or whether the parameter must have the same value for all Real Application Clusters instances (FALSE). If the ISSYS_MODIFIABLE column is FALSE, then this column is always FALSE.
ISMODIFIED	VARCHAR2 (10)	Indicates whether the parameter has been modified after instance startup: - MODIFIED - Parameter has been modified with ALTER SESSION - SYSTEM_MOD - Parameter has been modified with ALTER SYSTEM (which causes all the currently logged in sessions' values to be modified) - FALSE - Parameter has not been modified after instance startup
ISADJUSTED	VARCHAR2 (5)	Indicates whether Oracle adjusted the input value to a more suitable value (for example, the parameter value should be prime, but the user input a non-prime number, so Oracle adjusted the value to the next prime number)
ISDEPRECATED	VARCHAR2 (5)	Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)

Column	Datatype	Description
ISBASIC	VARCHAR2 (5)	Indicates whether the parameter is a basic parameter (TRUE) or not (FALSE)
DESCRIPTION	VARCHAR2 (255)	Description of the parameter
ORDINAL	NUMBER	Position (ordinal number) of the parameter value. Useful only for parameters whose values are lists of strings.
UPDATE_COMMENT	VARCHAR2 (255)	Comments associated with the most recent update

V\$PERSISTENT_PUBLISHERS

V\$PERSISTENT_PUBLISHERS displays information about all active publishers of the persistent queues in the database. There is one row per instance per queue per publisher. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2 (30)	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	Name of the queue
PUBLISHER_NAME	VARCHAR2 (30)	Name of the agent enqueueing the message
PUBLISHER_ADDRESS	VARCHAR2 (1024)	Address of the publisher agent
PROTOCOL	NUMBER	Protocol used by the publisher's address
ENQUEUED_MSGS	NUMBER	Number of messages that have been enqueued
ELAPSED_ENQUEUE_TIME	NUMBER	Total time spent doing enqueue (in hundredths of a second)
ENQUEUE_CPU_TIME	NUMBER	Total CPU time for enqueue (in hundredths of a second)
LAST_ENQUEUE_TIME	TIMESTAMP (6)	Last enqueue message timestamp
ENQUEUE_TRANSACTIONS	NUMBER	Number of enqueue transactions

V\$PERSISTENT_QMN_CACHE

V\$PERSISTENT_QMN_CACHE displays detailed information and statistics about the background activities for all queue tables in the system. There is one row per queue table. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QUEUE_TABLE_ID	NUMBER	Queue table object ID
TYPE	VARCHAR2 (32)	Type of the queue table's queue monitor cache
STATUS	NUMBER	Status of the queue table's queue monitor cache
NEXT_SERVICE_TIME	TIMESTAMP (3) WITH TIME ZONE	Time when the queue table should be serviced by QMON servers
WINDOW_END_TIME	TIMESTAMP (3) WITH TIME ZONE	Time manager activity period for non-owner queue table operations
TOTAL_RUNS	NUMBER	Total number of times this queue table is served
TOTAL_LATENCY	NUMBER	Cumulative latency in serving the queue table (in hundredths of a second)
TOTAL_ELAPSED_TIME	NUMBER	Total time spent in processing this queue table (in seconds)
TOTAL_CPU_TIME	NUMBER	Cumulative CPU time for serving the queue table (in hundredths of a second)
TMGR_ROWS_PROCESSED	NUMBER	Number of time manager entries processed

Column	Datatype	Description
TMGR_ELAPSED_TIME	NUMBER	Cumulative time for time management activities (in hundredths of a second)
TMGR_CPU_TIME	NUMBER	Cumulative CPU time for time management activities (in hundredths of a second)
LAST_TMGR_PROCESSING_TIME	TIMESTAMP (3) WITH TIME ZONE	Last timer manager processing time
DEQLOG_ROWS_PROCESSED	NUMBER	Number of dequeue log entries processed
DEQLOG_PROCESSING_ELAPSED_TIME	NUMBER	Total time for processing dequeue log entries (in hundredths of a second)
DEQLOG_PROCESSING_CPU_TIME	NUMBER	Total CPU time for processing dequeue log entries (in hundredths of a second)
LAST_DEQLOG_PROCESSING_TIME	TIMESTAMP (3) WITH TIME ZONE	Last dequeue log processing time
DEQUEUE_INDEX_BLOCKS_FREED	NUMBER	Number of dequeue index blocks freed
HISTORY_INDEX_BLOCKS_FREED	NUMBER	Number of history index blocks freed
TIME_INDEX_BLOCKS_FREED	NUMBER	Number of time manager index blocks freed
INDEX_CLEANUP_COUNT	NUMBER	Number of times index block cleanup was attempted
INDEX_CLEANUP_ELAPSED_TIME	NUMBER	Total time for index block cleanup (in hundredths of a second)
INDEX_CLEANUP_CPU_TIME	NUMBER	Total CPU time for index block cleanup (in hundredths of a second)
LAST_INDEX_CLEANUP_TIME	TIMESTAMP (3) WITH TIME ZONE	Last index block cleanup time

V\$PERSISTENT_QUEUES

V\$PERSISTENT_QUEUES displays information about all active persistent queues in the database since the queues' first activity time. There is one row per queue. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_TABLE_ID	NUMBER	Queue table identifier
QUEUE_SCHEMA	VARCHAR2 (30)	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	Name of the queue
FIRST_ACTIVITY_TIME	TIMESTAMP (6)	First queue activity time since database startup
ENQUEUED_MSGS	NUMBER	Number of messages enqueued
DEQUEUED_MSGS	NUMBER	Number of messages dequeued Note: This column will not be incremented until all the subscribers of the message have dequeued the message and its retention time has elapsed.
BROWSED_MSGS	NUMBER	Number of messages that have been browsed
ELAPSED_ENQUEUE_TIME	NUMBER	Total time (in hundredths of a second) spent doing enqueue
ELAPSED_DEQUEUE_TIME	NUMBER	Total time (in hundredths of a second) spent doing dequeue
ENQUEUE_CPU_TIME	NUMBER	Total CPU time for enqueue (in hundredths of a second)
DEQUEUE_CPU_TIME	NUMBER	Total CPU time for dequeue (in hundredths of a second)
AVG_MSG_AGE	NUMBER	Average age of messages in the queue

Column	Datatype	Description
DEQUEUED_MSG_LATENCY	NUMBER	Last dequeued message latency (in seconds)
ELAPSED_TRANSFORMATION_TIME	NUMBER	Total time (in hundredths of a second) spent doing transformation
ELAPSED_RULE_EVALUATION_TIME	NUMBER	Total time (in hundredths of a second) spent doing rule evaluation
ENQUEUED_EXPIRY_MSGS	NUMBER	Number of messages enqueued with expiry
ENQUEUED_DELAY_MSGS	NUMBER	Number of messages enqueued with delay
MSGS_MADE_EXPIRED	NUMBER	Number of messages expired by time manager
MSGS_MADE_READY	NUMBER	Number of messages made ready by time manager
LAST_ENQUEUE_TIME	TIMESTAMP (6)	Last message enqueue time
LAST_DEQUEUE_TIME	TIMESTAMP (6)	Last message dequeue time
LAST_TM_EXPIRY_TIME	TIMESTAMP (6)	Last time message was expired by time manager
LAST_TM_READY_TIME	TIMESTAMP (6)	Last time message was made ready by time manager
ENQUEUE_TRANSACTIONS	NUMBER	Number of enqueue transactions
DEQUEUE_TRANSACTIONS	NUMBER	Number of dequeue transactions
EXECUTION_COUNT	NUMBER	Number of executions of the dequeue cursor
OLDEST_MSGID ¹	RAW (16)	Message ID of the oldest message in the queue
OLDEST_MSG_ENQTM ¹	TIMESTAMP (6)	Enqueue time of the oldest message in the queue

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$PERSISTENT_SUBSCRIBERS

V\$PERSISTENT_SUBSCRIBERS displays information about all active subscribers of the persistent queues in the database. There is one row per instance per queue per subscriber. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2 (30)	Owner of the queue
QUEUE_NAME	VARCHAR2 (30)	Name of the queue
SUBSCRIBER_ID	NUMBER	Internal subscriber number
SUBSCRIBER_NAME	VARCHAR2 (30)	Name of the subscriber
SUBSCRIBER_ADDRESS	VARCHAR2 (1024)	Address of the subscribing agent
PROTOCOL	NUMBER	Protocol of the subscribing agent
SUBSCRIBER_TYPE	VARCHAR2 (30)	Type of the subscriber: ■ PROXY - Propagation subscriber ■ SUBSCRIBER - Normal subscriber ■ RECIPIENT - Recipient
FIRST_ACTIVITY_TIME	TIMESTAMP (6)	First subscriber activity time since database startup
ENQUEUED_MSGS	NUMBER	Number of messages enqueued since FIRST_ACTIVITY_TIME
DEQUEUED_MSGS	NUMBER	Number of messages dequeued since FIRST_ACTIVITY_TIME
AVG_MSG_AGE	NUMBER	Average age of messages in the queue
BROWSED_MSGS	NUMBER	Number of messages that have been browsed
EXPIRED_MSGS	NUMBER	Number of messages expired since FIRST_ACTIVITY_TIME

Column	Datatype	Description
DEQUEUED_MSG_LATENCY	NUMBER	Last dequeued message latency (in seconds)
LAST_ENQUEUE_TIME	TIMESTAMP (6)	Timestamp of the last enqueued message
LAST_DEQUEUE_TIME	TIMESTAMP (6)	Timestamp of the last dequeued message
ELAPSED_DEQUEUE_TIME	NUMBER	Total time spent in dequeue (in hundredths of a second)
DEQUEUE_CPU_TIME	NUMBER	Total CPU time for dequeue (in hundredths of a second)
DEQUEUE_TRANSACTIONS	NUMBER	Number of dequeue transactions
EXECUTION_COUNT	NUMBER	Number of executions of the dequeue index cursor
DEQUEUE_MEMORY_LOCKS ¹	NUMBER	Number of dequeue transactions that obtained memory locks
DEQUEUE_DISK_LOCKS ¹	NUMBER	Number of dequeue transactions that obtained disk locks
DEQUEUE_DISK_DELETES ¹	NUMBER	Number of dequeue transactions that deleted index-organized table entries
OLDEST_MSGID ¹	RAW (16)	Message ID of the oldest message
OLDEST_MSG_ENQTM ¹	TIMESTAMP (6)	Enqueue time of the oldest message

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$PGA_TARGET_ADVICE

V\$PGA_TARGET_ADVICE predicts how the cache hit percentage and over allocation count statistics displayed by the V\$PGASTAT performance view would be impacted if the value of the PGA_AGGREGATE_TARGET parameter is changed. The prediction is performed for various values of the PGA_AGGREGATE_TARGET parameter, selected around its current value. The advice statistic is generated by simulating the past workload run by the instance.

The content of the view is empty if PGA_AGGREGATE_TARGET is not set. In addition, the content of this view is not updated if the STATISTICS_LEVEL parameter is set to BASIC. Base statistics for this view are reset at instance startup and when the value of the PGA_AGGREGATE_TARGET initialization parameter is dynamically modified.

Column	Datatype	Description
PGA_TARGET_FOR_ESTIMATE	NUMBER	Value of PGA_AGGREGATE_TARGET for this prediction (in bytes)
PGA_TARGET_FACTOR	NUMBER	PGA_TARGET_FOR_ESTIMATE / the current value of the PGA_AGGREGATE_TARGET parameter
ADVICE_STATUS	VARCHAR2 (3)	Indicates whether the advice is enabled (ON) or disabled (OFF) depending on the value of the STATISTICS_LEVEL parameter
BYTES_PROCESSED	NUMBER	Total bytes processed by all the work areas considered by this advice (in bytes)
ESTD_TIME	NUMBER	Time (in seconds) required to process the bytes
ESTD_EXTRA_BYTES_RW	NUMBER	Estimated number of extra bytes which would be read or written if PGA_AGGREGATE_TARGET was set to the value of the PGA_TARGET_FOR_ESTIMATE column. This number is derived from the estimated number and size of work areas which would run in one-pass (or multi-pass) for that value of PGA_AGGREGATE_TARGET.
ESTD_PGA_CACHE_HIT_PERCENTAGE	NUMBER	Estimated value of the cache hit percentage statistic when PGA_AGGREGATE_TARGET equals PGA_TARGET_FOR_ESTIMATE. This column is derived from the above two columns and is equal to BYTES_PROCESSED / (BYTES_PROCESSED + ESTD_EXTRA_BYTES_RW)

Column	Datatype	Description
ESTD_OVERALLOC_COUNT	NUMBER	Estimated number of PGA memory over-allocations if the value of PGA_AGGREGATE_TARGET is set to PGA_TARGET_FOR_ESTIMATE. A nonzero value means that PGA_TARGET_FOR_ESTIMATE is not large enough to run the work area workload. Hence, the DBA should not set PGA_AGGREGATE_TARGET to PGA_TARGET_FOR_ESTIMATE since Oracle will not be able to honor that target.

See Also: *Oracle Database Performance Tuning Guide* for information on tuning the PGA_AGGREGATE_TARGET initialization parameter using the PGA advice views

V\$PGA_TARGET_ADVICE_HISTOGRAM

V\$PGA_TARGET_ADVICE_HISTOGRAM predicts how statistics displayed by the V\$SQL_WORKAREA_HISTOGRAM dynamic view would be impacted if the value of the PGA_AGGREGATE_TARGET parameter is changed. This prediction is performed for various values of the PGA_AGGREGATE_TARGET parameter, selected around its current value. The advice statistic is generated by simulating the past workload run by the instance.

The content of the view is empty if PGA_AGGREGATE_TARGET is not set. In addition, the content of this view is not updated when the STATISTICS_LEVEL initialization parameter is set to BASIC. Base statistics for this view are reset at instance startup or when the value of the PGA_AGGREGATE_TARGET initialization parameter is dynamically modified.

Column	Datatype	Description
PGA_TARGET_FOR_ESTIMATE	NUMBER	Value of PGA_AGGREGATE_TARGET for this prediction (in bytes)
PGA_TARGET_FACTOR	NUMBER	PGA_TARGET_FOR_ESTIMATE / the current value of the PGA_AGGREGATE_TARGET parameter
ADVICE_STATUS	VARCHAR2 (3)	Indicates whether the advice is enabled (ON) or disabled (OFF) depending on the value of the STATISTICS_LEVEL parameter
LOW_OPTIMAL_SIZE	NUMBER	Lower bound for the optimal memory requirement of work areas included in this row (in bytes)
HIGH_OPTIMAL_SIZE	NUMBER	Upper bound for the optimal memory requirement of work areas included in this row (in bytes)
ESTD_OPTIMAL_EXECUTIONS	NUMBER	Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which are predicted to run optimal given a value of PGA_AGGREGATE_TARGET equal to PGA_TARGET_FOR_ESTIMATE
ESTD_ONEPASS_EXECUTIONS	NUMBER	Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which are predicted to run one-pass given a value of PGA_AGGREGATE_TARGET equal to PGA_TARGET_FOR_ESTIMATE
ESTD_MULTIPASSES_EXECUTIONS	NUMBER	Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which are predicted to run multi-pass given a value of PGA_AGGREGATE_TARGET equal to PGA_TARGET_FOR_ESTIMATE
ESTD_TOTAL_EXECUTIONS	NUMBER	Sum of ESTD_OPTIMAL_EXECUTIONS, ESTD_ONEPASS_EXECUTIONS, and ESTD_MULTIPASSES_EXECUTIONS
IGNORED_WORKAREAS_COUNT	NUMBER	Number of work areas with optimal memory requirement between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE ignored in the advice generation due to memory and CPU constraints

See Also: *Oracle Database Performance Tuning Guide* for information on tuning the PGA_AGGREGATE_TARGET initialization parameter using the PGA advice views

V\$PGASTAT

V\$PGASTAT displays PGA memory usage statistics as well as statistics about the automatic PGA memory manager when it is enabled (that is, when PGA_AGGREGATE_TARGET is set). Cumulative values in V\$PGASTAT are accumulated since instance startup.

Column	Datatype	Description
NAME	VARCHAR2 (64)	Name of the statistic (see Table 8–4)
VALUE	NUMBER	Statistic value
UNIT	VARCHAR2 (12)	Unit for the value: - bytes - microseconds - percent

Table 8–4 V\$PGASTAT Statistics

Statistic Name	Description
aggregate PGA auto target	Amount of PGA memory the Oracle Database can use for work areas running in automatic mode. This amount is dynamically derived from the value of the PGA_AGGREGATE_TARGET initialization parameter and the current work area workload, and continuously adjusted by the Oracle Database. If this value is small compared to the value of PGA_AGGREGATE_TARGET, then a large amount of PGA memory is used by other components of the system (for example, PL/SQL or Java memory) and little is left for work areas. The DBA must ensure that enough PGA memory is left for work areas running in automatic mode.
aggregate PGA target parameter	Current value of the PGA_AGGREGATE_TARGET initialization parameter. If this parameter is not set, then its value is 0 and automatic management of PGA memory is disabled.
bytes processed	Number of bytes processed by memory intensive SQL operators, cumulated since instance startup.
cache hit percentage	A metric computed by the Oracle Database to reflect the performance of the PGA memory component, cumulative since instance startup. A value of 100% means that all work areas executed by the system since instance startup have used an optimal amount of PGA memory. When a work area cannot run optimal, one or more extra passes is performed over the input data. This will reduce the cache hit percentage in proportion to the size of the input data and the number of extra passes performed.
extra bytes read/written	Number of bytes processed during extra passes of the input data, cumulated since instance startup. When a work area cannot run optimal, one or more of these extra passes is performed.
global memory bound	Maximum size of a work area executed in automatic mode. This value is continuously adjusted by the Oracle Database to reflect the current state of the work area workload. The global memory bound generally decreases when the number of active work areas is increasing in the system. If the value of the global bound decreases below 1 MB, then the value of PGA_AGGREGATE_TARGET should be increased.
max processes count	Maximum number of processes active at any one time since instance startup.
maximum PGA allocated	Maximum number of bytes of PGA memory allocated at one time since instance startup.
maximum PGA used for auto workareas	Maximum amount of PGA memory consumed at one time by work areas running under the automatic memory management mode since instance startup.

Table 8–4 (Cont.) V\$PGASTAT Statistics

Statistic Name	Description
maximum PGA used for manual workareas	Maximum amount of PGA memory consumed at one time by work areas running under the manual memory management mode since instance startup.
over allocation count	This statistic is cumulative since instance startup. Over allocating PGA memory can happen if the value of PGA_AGGREGATE_TARGET is too small. When this happens, the Oracle Database cannot honor the value of PGA_AGGREGATE_TARGET and extra PGA memory needs to be allocated. If over allocation occurs, then increase the value of PGA_AGGREGATE_TARGET using the information provided by the V\$PGA_TARGET_ADVICE view.
PGA memory freed back to OS	Number of bytes of PGA memory freed back to the operating system, cumulated since instance startup.
process count	Number of processes active within up to the last 3 seconds.
recompute count (total)	Number of times the instance bound, which is a cap on the maximum size of each active work area, has been recomputed since instance startup. Generally, the instance bound is recomputed in the background every 3 seconds, but it could be recomputed by a foreground process when the number of work areas changes rapidly in a short period of time.
total freeable PGA memory	Number of bytes of PGA memory in all processes that could be freed back to the operating system.
total PGA allocated	Current amount of PGA memory allocated by the instance. The Oracle Database attempts to keep this number below the value of the PGA_AGGREGATE_TARGET initialization parameter. However, it is possible for the PGA allocated to exceed that value by a small percentage and for a short period of time when the work area workload is increasing very rapidly or when PGA_AGGREGATE_TARGET is set to a small value.
total PGA inuse	Indicates how much PGA memory is currently consumed by work areas. This number can be used to determine how much memory is consumed by other consumers of the PGA memory (for example, PL/SQL or Java).
total PGA used for auto workareas	Indicates how much PGA memory is currently consumed by work areas running under the automatic memory management mode. This number can be used to determine how much memory is consumed by other consumers of the PGA memory (for example, PL/SQL or Java).
total PGA used for manual workareas	Indicates how much PGA memory is currently consumed by work areas running under the manual memory management mode. This number can be used to determine how much memory is consumed by other consumers of the PGA memory (for example, PL/SQL or Java).

V\$PQ_SESSTAT

V\$PQ_SESSTAT lists session statistics for parallel queries. After you have run a query or DML operation, you can use the information derived from V\$PQ_SESSTAT to view the number of slave processes used, and other information for the session and system.

Column	Datatype	Description
STATISTIC	VARCHAR2 (30)	Name of the statistic: ■ Queries Parallelized - Number of queries run in parallel ■ DDL Parallelized - Number of DDL operations run in parallel ■ DML Parallelized - Number of DML operations run in parallel ■ DFO Trees - Number of executed DFO trees ■ Server Threads - Number of PX servers used ■ Allocation Height - Requested number of servers per instance ■ Allocation Width - Requested number of instances ■ Local Msgs Sent - Number of local (intra-instance) messages sent ■ Distr Msgs Sent - Number of remote (inter-instance) messages sent ■ Local Msgs Recv'd - Number of local (intra-instance) messages received ■ Distr Msgs Recv'd - Number of remote (inter-instance) messages received
LAST_QUERY	NUMBER	Value of the statistic for the last operation
SESSION_TOTAL	NUMBER	Value of the statistic for the entire session to this point in time

V\$PQ_SLAVE

V\$PQ_SLAVE lists statistics for each of the active parallel execution servers on an instance.

Column	Datatype	Description
SLAVE_NAME	VARCHAR2 (4)	Name of the parallel execution server
STATUS	VARCHAR2 (4)	Current status of the parallel execution server: ■ BUSY ■ IDLE
SESSIONS	NUMBER	Number of sessions that have used this parallel execution server
IDLE_TIME_CUR	NUMBER	Amount of time spent idle while processing statements in the current session
BUSY_TIME_CUR	NUMBER	Amount of time spent busy while processing statements in the current session
CPU_SECS_CUR	NUMBER	Amount of CPU time spent on the current session
MSGSENT_CUR	NUMBER	Number of messages sent while processing statements for the current session
MSGRCVD_CUR	NUMBER	Number of messages received while processing statements for the current session
IDLE_TIME_TOTAL	NUMBER	Total amount of time this query server has been idle
BUSY_TIME_TOTAL	NUMBER	Total amount of time this query server has been active
CPU_SECS_TOTAL	NUMBER	Total amount of CPU time this query server has used to process statements
MSGSENT_TOTAL	NUMBER	Total number of messages this query server has sent
MSGRCVD_TOTAL	NUMBER	Total number of messages this query server has received

V\$PQ_SYSSTAT

V\$PQ_SYSSTAT lists system statistics for parallel queries. After you have run a query or DML operation, you can use the information derived from V\$PQ_SYSSTAT to view the number of slave processes used, and other information for the system.

Column	Datatype	Description
STATISTIC	VARCHAR2 (30)	Name of the statistic: ■ Servers Busy - Number of currently busy servers on this instance ■ Servers Idle - Number of currently idle servers on this instance ■ Servers Highwater - Number of active servers on this instance that have partaken in >= 1 operation so far ■ Server Sessions - Total number of operations executed in all servers on this instance ■ Servers Started - Total number of servers started on this instance ■ Servers Shutdown - Total number of servers shutdown on this instance ■ Servers Cleaned Up - Total number of servers on this instance cleaned up due to process death ■ Queries Initiated - Total number of parallel queries initiated on this instance ■ DDL Initiated - Total number of parallel DDL operations that were initiated ■ DML Initiated - Total number of parallel DML operations that were initiated ■ DFO Trees - Total number of DFO trees executed on this instance ■ Local Msgs Sent - Total number of local (intra-instance) messages sent on this instance ■ Distr Msgs Sent - Total number of remote (inter-instance) messages sent on this instance ■ Local Msgs Recv'd - Total number of remote (inter-instance) messages received on this instance ■ Distr Msgs Recv'd - Total number of remote (inter-instance) messages received on this instance
VALUE	NUMBER	Value of the statistic

V\$PQ_TQSTAT

V\$PQ_TQSTAT contains statistics on parallel execution operations. The statistics are compiled after the query completes and only remain for the duration of the session. It displays the number of rows processed through each parallel execution server at each stage of the execution tree. This view can help determine skew problems in a query's execution. (Note that for PDML, information from V\$PQ_TQSTAT is available only after a commit or rollback operation.)

Column	Datatype	Description
DFO_NUMBER	NUMBER	Data flow operator (DFO) tree number to differentiate queries
TQ_ID	NUMBER	Table queue ID within the query, which represents the connection between two DFO nodes in the query execution tree
SERVER_TYPE	VARCHAR2 (10)	The role in table queue - producer/consumer/ranger
NUM_ROWS	NUMBER	The number of rows produced/consumed
BYTES	NUMBER	The number of bytes produced/consumed
OPEN_TIME	NUMBER	Time (seconds) the table queue remained open
AVG_LATENCY	NUMBER	Time (minutes) for a message to be dequeued after it enters the queue
WAITS	NUMBER	The number of waits encountered during dequeue
TIMEOUTS	NUMBER	The number of timeouts when waiting for a message
PROCESS	VARCHAR2 (10)	Process ID
INSTANCE	NUMBER	Instance ID

V\$PROCESS

V\$PROCESS displays information about the currently active processes. While the LATCHWAIT column indicates what latch a process is waiting for, the LATCHSPIN column indicates what latch a process is spinning on. On multi-processor machines, Oracle processes will spin on a latch before waiting on it.

Column	Datatype	Description
ADDR	RAW (4 8)	Address of the process state object
PID	NUMBER	Oracle process identifier
SPID	VARCHAR2 (24)	Operating system process identifier
PNAME	VARCHAR2 (5)	Name of this process
USERNAME	VARCHAR2 (15)	Operating system process username Note: Any two-task user coming across the network has "-T" appended to the username.
SERIAL#	NUMBER	Process serial number
TERMINAL	VARCHAR2 (30)	Operating system terminal identifier
PROGRAM	VARCHAR2 (48)	Program in progress
TRACEID	VARCHAR2 (255)	Trace file identifier
TRACEFILE	VARCHAR2 (513)	Trace file name of the process
BACKGROUND	VARCHAR2 (1)	1 for a background process; NULL for a normal process
LATCHWAIT	VARCHAR2 (8)	Address of the latch the process is waiting for; NULL if none
LATCHSPIN	VARCHAR2 (8)	Address of the latch the process is spinning on; NULL if none
PGA_USED_MEM	NUMBER	PGA memory currently used by the process
PGA_ALLOC_MEM	NUMBER	PGA memory currently allocated by the process (including free PGA memory not yet released to the operating system by the server process)
PGA_FREEABLE_MEM	NUMBER	Allocated PGA memory which can be freed
PGA_MAX_MEM	NUMBER	Maximum PGA memory ever allocated by the process

V\$PROCESS_MEMORY

V\$PROCESS_MEMORY displays dynamic PGA memory usage by named component categories for each process.

Column	Datatype	Description
PID	NUMBER	Oracle process identifier
SERIAL#	NUMBER	Oracle process serial number
CATEGORY	VARCHAR2 (15)	Category name. Categories include "SQL", "PL/SQL", "OLAP" and "JAVA". Special categories are "Freeable" and "Other". Freeable memory has been allocated to the process by the operating system, but has not been allocated to a category. "Other" memory has been allocated to a category, but not to one of the named categories.
ALLOCATED	NUMBER	Bytes of PGA memory allocated by the process for the category. For the "Freeable" category, it is the amount of free PGA memory eligible to be released to the operating system.
USED	NUMBER	Bytes of PGA memory used by the process for the category. For "Freeable", the value is zero. For "Other", the value is NULL for performance reasons.
MAX_ALLOCATED	NUMBER	Maximum bytes of PGA memory ever allocated by the process for the category.

V\$PROPAGATION_RECEIVER

V\$PROPAGATION_RECEIVER displays information about buffer queue propagation schedules on the receiving (destination) side. The values are reset to zero when the database (or instance in an Oracle Real Application Clusters (Oracle RAC) environment) restarts, when propagation migrates to another instance, or when an unscheduled propagation is attempted.

Column	Datatype	Description
SRC_QUEUE_SCHEMA	VARCHAR2 (30)	Name of the source schema
SRC_QUEUE_NAME	VARCHAR2 (30)	Name of the source queue
SRC_DBNAME	VARCHAR2 (128)	Name of the source database
DST_QUEUE_SCHEMA	VARCHAR2 (30)	Name of the destination schema
DST_QUEUE_NAME	VARCHAR2 (30)	Name of the destination queue
STARTUP_TIME	DATE	Startup time of this schedule. This time changes when the source/destination database gets restarted.
HIGH_WATER_MARK	NUMBER	High watermark of the messages received
ACKNOWLEDGEMENT	NUMBER	Acknowledgement of the messages received by the receiver
LAST_RECEIVED_MSG	NUMBER	Last received message
TOTAL_MSGS	NUMBER	Total number of messages
ELAPSED_UNPICKLE_TIME	NUMBER	Elapsed unpickle time
ELAPSED_RULE_TIME	NUMBER	Elapsed rule time
ELAPSED_ENQUEUE_TIME	NUMBER	Elapsed enqueue time
SESSION_ID	NUMBER	Session ID of the propagation receiver
SERIAL#	NUMBER	Serial number of the propagation receiver
SPID	VARCHAR2 (24)	Process identification number of the propagation receiver
PROPAGATION_NAME	VARCHAR2 (30)	Name of the Streams propagation on the source database
STATE	VARCHAR2 (43)	State of the propagation receiver: ■ Initializing ■ Sending unapplied txns ■ Waiting for message from client ■ Receiving LCRs ■ Evaluating rules ■ Enqueueing LCRS ■ Waiting for memory ■ Waiting for apply to read ■ Waiting for message from propagation sender When the propagation schedule is not optimized, the state is Normal.
LAST_RECEIVED_MSG_POSITION	RAW (64)	Last received message position. Corresponds to LAST_RECEIVED_MSG, except the value is in position rather than SCN. Position is used by XStream to determine ordering.
ACKNOWLEDGEMENT_POSITION	RAW (64)	Acknowledgement position of the messages received by the receiver. Corresponds to ACKNOWLEDGEMENT, except the value is in position rather than SCN. Position is used by XStream to determine ordering.

V\$PROPAGATION_SENDER

V\$PROPAGATION_SENDER displays information about buffer queue propagation schedules on the sending (source) side. The values are reset to zero when the database (or instance in an Oracle Real Application Clusters (Oracle RAC) environment)

restarts, when propagation migrates to another instance, or when an unscheduled propagation is attempted.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue identifier of the queue
QUEUE_SCHEMA	VARCHAR2 (30)	Schema of the queue
QUEUE_NAME	VARCHAR2 (30)	Name of the queue
DST_QUEUE_SCHEMA	VARCHAR2 (30)	Destination schema of the queue
DST_QUEUE_NAME	VARCHAR2 (30)	Name of the destination queue
STARTUP_TIME	DATE	Time at which the propagation started
DBLINK	VARCHAR2 (128)	Name of the destination database link
HIGH_WATER_MARK	NUMBER	High watermark of the messages sent
ACKNOWLEDGEMENT	NUMBER	Acknowledgement of the messages received by the receiver
SCHEDULE_STATUS	VARCHAR2 (30)	Status of the propagation schedule
TOTAL_MSGS	NUMBER	Total messages propagated
TOTAL_BYTES	NUMBER	Total bytes propagated
ELAPSED_DEQUEUE_TIME	NUMBER	Elapsed dequeue time (in hundredths of a second)
ELAPSED_PICKLE_TIME	NUMBER	Elapsed pickle time (time taken to linearize a logical change record (LCR) into a stream of bytes that can be sent over the network) (in hundredths of a second)
ELAPSED_PROPAGATION_TIME	NUMBER	Elapsed propagation time (in hundredths of a second)
ELAPSED_RULE_TIME	NUMBER	Elapsed rule time (in hundredths of a second)
MAX_NUM_PER_WIN	NUMBER	Maximum bytes per window
MAX_SIZE	NUMBER	Maximum bytes sent per window
LAST_MSG_LATENCY	NUMBER	Last propagated message latency
LAST_MSG_ENQUEUE_TIME	TIMESTAMP (6)	Last propagated message enqueue time
LAST_MSG_PROPAGATION_TIME	TIMESTAMP (6)	Last time when the message was propagated
LAST_LCR_LATENCY	NUMBER	Last propagated LCR latency
LAST_LCR_CREATION_TIME	DATE	Last propagated LCR timestamp
LAST_LCR_PROPAGATION_TIME	DATE	Last time when the LCR was propagated
DST_DATABASE_NAME	VARCHAR2 (128)	Global name of the destination database
SESSION_ID	NUMBER	Session ID of the propagation sender process
SERIAL#	NUMBER	Serial number of the propagation sender process
SPID	VARCHAR2 (24)	Process identification number of the propagation sender process
PROPAGATION_NAME	VARCHAR2 (30)	Name of the Streams propagation

Column	Datatype	Description
STATE	VARCHAR2 (53)	State of the propagation sender process: ■ Initializing ■ Initializing propagation receiver ■ Browsing LCRs ■ Evaluating rules ■ Dequeueing LCRs ■ Sending LCRs ■ Waiting for apply to be enabled ■ Waiting for apply database to start ■ Waiting for propagation to be enabled ■ Waiting for capture to terminate ■ Waiting for a subscriber to be added ■ Suspended due to a dropped subscriber ■ Suspended for auto split/merge ■ Waiting on empty queue When the SCHEDULE_STATUS column is not SCHEDULE OPTIMIZED, the state is the value of the SCHEDULE_STATUS column.

V\$PROXY_ARCHIVEDLOG

V\$PROXY_ARCHIVEDLOG contains descriptions of archived log backups that were taken using the proxy copy functionality.

In a proxy copy, the media manager takes over the operations of backing up and restoring data. Each row represents a backup of one control file.

Column	Datatype	Description
RECID	NUMBER	Proxy copy record identifier
STAMP	NUMBER	Proxy copy stamp
DEVICE_TYPE	VARCHAR2 (17)	Type of media device that stores the proxy copy
HANDLE	VARCHAR2 (513)	Name or "handle" for the proxy copy
COMMENTS	VARCHAR2 (81)	Comments about the proxy copy
MEDIA	VARCHAR2 (65)	A comment that contains further information about the media manager that created this backup
MEDIA_POOL	NUMBER	Number of the media pool in which the proxy copy is stored
TAG	VARCHAR2 (32)	Tag for the proxy copy
STATUS	VARCHAR2 (1)	Status of the backup set: ■ A - Available ■ U - Unavailable ■ X - Expired ■ D - Deleted
DELETED	VARCHAR2 (3)	Indicates whether this record has been deleted (YES) or not (NO)
THREAD#	NUMBER	Number of the redo thread
SEQUENCE#	NUMBER	Log sequence number
RESETLOGS_CHANGE#	NUMBER	RESETLOGS SCN of the database incarnation to which this archived log belongs
RESETLOGS_TIME	DATE	RESETLOGS time stamp of the database incarnation to which this archived log belongs
FIRST_CHANGE#	NUMBER	First SCN of this redo log

Column	Datatype	Description
FIRST_TIME	DATE	Time when Oracle switched into the redo log
NEXT_CHANGE#	NUMBER	First SCN of the next redo log in the thread
NEXT_TIME	DATE	First time stamp of the next redo log in the thread
BLOCKS	NUMBER	Size of this archived redo log (in operating system blocks)
BLOCK_SIZE	NUMBER	Block size for the copy (in bytes)
START_TIME	DATE	Time when the proxy copy was initiated
COMPLETION_TIME	DATE	Time when the proxy copy was completed
ELAPSED_SECONDS	NUMBER	Duration of the proxy copy
RMAN_STATUS_RECID	NUMBER	Owning V\$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V\$RMAN_STATUS stamp
TERMINAL	VARCHAR2 (3)	Indicates whether this record corresponds to a terminal archived redo log, as defined in V\$ARCHIVED_LOG (YES) or not (NO)

V\$PROXY_ARCHIVELOG_DETAILS

V\$PROXY_ARCHIVELOG_DETAILS contains information about all available archive log proxy copies.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
COPY_KEY	NUMBER	Copy identifier
THREAD#	NUMBER	Redo thread number
SEQUENCE#	NUMBER	Redo log sequence number
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the database when this log was written
RESETLOGS_TIME	DATE	Resetlogs time of the database when this log was written
HANDLE	VARCHAR2 (513)	Proxy copy handle identifies the copy for restore
MEDIA	VARCHAR2 (65)	Name of the media on which the copy resides. This value is informational only. It is not needed for restore.
MEDIA_POOL	NUMBER	Media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command.
TAG	VARCHAR2 (32)	Proxy copy tag
FIRST_CHANGE#	NUMBER	First change number in the archived log
NEXT_CHANGE#	NUMBER	First change number in the next log
FIRST_TIME	DATE	Timestamp of the first change
NEXT_TIME	DATE	Timestamp of the next change
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPLETION_TIME	DATE	Completion time
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output bytes

V\$PROXY_ARCHIVELOG_SUMMARY

V\$PROXY_ARCHIVELOG_SUMMARY provides summary information about the output proxy archive log file.

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of archived log files backed up
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct archived log files backed up
MIN_FIRST_CHANGE#	NUMBER	Minimum first change SCN
MAX_NEXT_CHANGE#	NUMBER	Maximum first change SCN
MIN_FIRST_TIME	DATE	Minimum first change time. Forms the redo range, along with MAX_NEXT_TIME.
MAX_NEXT_TIME	DATE	Maximum next change time
OUTPUT_BYTES	NUMBER	Total output size, in bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output bytes

V\$PROXY_COPY_DETAILS

V\$PROXY_COPY_DETAILS contains information about all available control file and datafile proxy copies.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
COPY_KEY	NUMBER	Copy identifier
FILE#	NUMBER	Absolute datafile number, or 0 if this is a control file backup
HANDLE	VARCHAR2 (513)	Proxy copy handle identifies the copy for restore
MEDIA	VARCHAR2 (65)	Name of the media on which the copy resides. This value is informational only. It is not needed for restore.
MEDIA_POOL	NUMBER	Media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command.
TAG	VARCHAR2 (32)	Proxy copy tag
CREATION_CHANGE#	NUMBER	Datafile creation change number
CREATION_TIME	DATE	Datafile creation timestamp
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change number of the datafile when the copy was made
CHECKPOINT_TIME	DATE	Checkpoint timestamp of the datafile when the copy was made
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPLETION_TIME	DATE	Completion time
CONTROLFILE_TYPE	VARCHAR2 (1)	Type of control file: ■ B - Normal control file ■ S - Standby control file
KEEP	VARCHAR2 (3)	Indicates whether this backup set has a retention policy that is different than the value for the configure retention policy (YES) or not (NO)
KEEP_UNTIL	DATE	If specified, then this is the date after which the backup becomes obsolete. If this column is NULL, then the backup never expires.

Column	Datatype	Description
KEEP_OPTIONS	VARCHAR2 (11)	Additional retention options for this backup set: - LOGS - Indicates a long-term backup made with the LOGS keyword, which is now deprecated - BACKUP_LOGS - Indicates that the backup was made in open mode, so archived log backups must be applied to make it consistent - NOLOGS - Indicates a consistent backup made when the database was mounted. - NULL - Indicates that this backup has no KEEP options and becomes obsolete based on the retention policy
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output bytes

V\$PROXY_COPY_SUMMARY

V\$PROXY_COPY_SUMMARY provides summary information about the output proxy datafile and control file.

Column	Datatype	Description
NUM_COPIES	NUMBER	Number of copies created
NUM_DISTINCT_COPIES	NUMBER	Number of distinct copies (that contain datafiles with different checkpoints)
MIN_CHECKPOINT_CHANGE#	NUMBER	Minimum checkpoint change SCN
MAX_CHECKPOINT_CHANGE#	NUMBER	Maximum checkpoint change SCN
MIN_CHECKPOINT_TIME	DATE	Minimum checkpoint change time
MAX_CHECKPOINT_TIME	DATE	Maximum checkpoint change time
OUTPUT_BYTES	NUMBER	Total output bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Displayable format for output bytes

V\$PROXY_DATAFILE

V\$PROXY_DATAFILE contains descriptions of datafile and control file backups that are taken with Proxy Copy. Each row represents a backup of one database file.

Column	Datatype	Description
RECID	NUMBER	Proxy copy record ID
STAMP	NUMBER	Proxy copy record stamp
DEVICE_TYPE	VARCHAR2 (17)	Type of the device on which the copy resides
HANDLE	VARCHAR2 (513)	Proxy copy handle identifies the copy for restore
COMMENTS	VARCHAR2 (81)	Comment returned by the operating system or storage subsystem. This value is informational only. It is not needed for restore.
MEDIA	VARCHAR2 (65)	Name of the media on which the copy resides. This value is informational only. It is not needed for restore.
MEDIA_POOL	NUMBER	Media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command
TAG	VARCHAR2 (32)	Proxy copy tag

Column	Datatype	Description
STATUS	VARCHAR2 (1)	Status of the backup set: ■ A - Available ■ U - Unavailable ■ X - Expired ■ D - Deleted
DELETED	VARCHAR2 (3)	Indicates whether this record has been deleted (YES) or not (NO)
FILE#	NUMBER	Absolute datafile number, or 0 if this is a control file backup
CREATION_CHANGE#	NUMBER	Datafile creation change number
CREATION_TIME	DATE	Datafile creation Timestamp
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the datafile when the copy was made
RESETLOGS_TIME	DATE	Resetlogs timestamp of the datafile when the copy was made
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change number of the datafile when the copy was made
CHECKPOINT_TIME	DATE	Checkpoint timestamp of the datafile when the copy was made
ABSOLUTE_FUZZY_CHANGE#	NUMBER	Highest change in any block of the file, if known
RECOVERY_FUZZY_CHANGE#	NUMBER	Highest change written to the file by media recovery
RECOVERY_FUZZY_TIME	DATE	Timestamp of the highest change written to the file by media recovery
INCREMENTAL_LEVEL	NUMBER	If this backup is part of an incremental backup strategy, then 0. Otherwise null.
ONLINE_FUZZY	VARCHAR2 (3)	Indicates whether this copy was made after a crash or offline immediate (or is a copy of a copy which was taken improperly while the database was open) (YES) or not (NO). Recovery will need to apply all redo up to the next crash recovery marker to make the file consistent.
BACKUP_FUZZY	VARCHAR2 (3)	Indicates whether this is a copy taken using the BEGIN BACKUP END BACKUP technique (YES) or not (NO). The BEGIN BACKUP END BACKUP technique is used internally when proxy copies of open files are created. Recovery will need to apply all redo up to the end backup marker to make this copy consistent.
BLOCKS	NUMBER	Size of the copy (in blocks). Also the size of the datafile when the copy was made.
BLOCK_SIZE	NUMBER	Block size of the datafile
OLDEST_OFFLINE_RANGE	NUMBER	If the file number is 0 (that is, this is a control file backup), the RECID of the oldest offline range record in this control file copy. 0 for datafile copies.
START_TIME	DATE	Starting time
COMPLETION_TIME	DATE	Completion time
ELAPSED_SECONDS	NUMBER	Number of elapsed seconds
CONTROLFILE_TYPE	VARCHAR2 (1)	Type of control file: ■ B - Normal control file ■ S - Standby control file
KEEP	VARCHAR2 (3)	Indicates whether this backup set has a retention policy that is different than the value for the configure retention policy (YES) or not (NO)
KEEP_UNTIL	DATE	If specified, then this is the date after which the backup becomes obsolete. If this column is NULL, then the backup never expires.

Column	Datatype	Description
KEEP_OPTIONS	VARCHAR2 (11)	Additional retention options for this backup set: - LOGS - Indicates a long-term backup made with the LOGS keyword, which is now deprecated - BACKUP_LOGS - Indicates that the backup was made in open mode, so archived log backups must be applied to make it consistent - NOLOGS - Indicates a consistent backup made when the database was mounted. - NULL - Indicates that this backup has no KEEP options and becomes obsolete based on the retention policy
RMAN_STATUS_RECID	NUMBER	Owning V\$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V\$RMAN_STATUS stamp
FOREIGN_DBID	NUMBER	Foreign DBID of the database from which this datafile was transported. The value is 0 if the file backed up is not a foreign database file.
PLUGGED_READONLY	VARCHAR2 (3)	Indicates whether this is a proxy copy of a transported read-only foreign file (YES) or not (NO)
PLUGIN_CHANGE#	NUMBER	SCN at which the foreign datafile was transported into the database. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_CHANGE#	NUMBER	SCN of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_TIME	DATE	Time of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.

V\$PWFILERS

V\$PWFILERS lists all users in the password file, and indicates whether the user has been granted the SYSDBA, SYSOPER, and SYSASM privileges.

Column	Datatype	Description
USERNAME	VARCHAR2 (30)	Name of the user that is contained in the password file
SYSDBA	VARCHAR2 (5)	Indicates whether the user can connect with SYSDBA privileges (TRUE) or not (FALSE)
SYSOPER	VARCHAR2 (5)	Indicates whether the user can connect with SYSOPER privileges (TRUE) or not (FALSE)
SYSASM	VARCHAR2 (5)	Indicates whether the user can connect with SYSASM privileges (TRUE) or not (FALSE)

V\$PX_INSTANCE_GROUP

V\$PX_INSTANCE_GROUP provides information about the instance groups being used for parallel operations by the current session.

Column	Datatype	Description
QC_INSTANCE_GROUP	VARCHAR2 (64)	The instance group being used by this session for parallel operations. This value repeats for every row returned.
WHY	VARCHAR2 (23)	Where the current instance group name comes from, as follows: SERVICE - the instance group being used is from the session's service name PARALLEL_INSTANCE_GROUP - the instance group being used is being used because the PARALLEL_INSTANCE_GROUP initialization parameter has been set. The value repeats for every row returned.

Column	Datatype	Description
INSTANCE_NUMBER	NUMBER	Instance number of the instance providing this instance group. There will be one row for each instance in the instance group that the Query Coordinator is using.

V\$PX_PROCESS

V\$PX_PROCESS contains information about the sessions running parallel execution.

Column	Datatype	Description
SERVER_NAME	VARCHAR2 (4)	The name of the PX server (P000, P001, and so on)
STATUS	VARCHAR2 (9)	The state of the PX server (IN USE AVAILABLE)
PID	NUMBER	The process identifier
SPID	VARCHAR2 (12)	OS process ID
SID	NUMBER	The session ID of the PX server, if in use
SERIAL#	NUMBER	The session serial number of the PX server, if in use

V\$PX_PROCESS_SYSSTAT

V\$PX_PROCESS_SYSSTAT contains information about the sessions running parallel execution.

Column	Datatype	Description
STATISTIC	VARCHAR2 (30)	Name of the statistic: <code>Servers In Use</code> - Number of PX servers currently performing parallel operations <code>Servers Available</code> - Number of PX servers available to perform parallel operations <code>Servers Started</code> - Number of times the system has had to create a PX server process <code>Servers Shutdown</code> - Number of times a PX server process has been shut down. A PX server process will be shut down if it has not been used recently. If this value is large, then consider increasing the parameter. This will improve performance by avoiding the latency of PX server process creation. <code>Servers HWM</code> - Maximum number of concurrent PX server processes If this number is equal to the <code>PARALLEL_MAX_SERVERS</code> initialization parameter, then consider increasing the parameter. This could allow you to increase your throughput, especially if your system is under-utilized and the <code>V\$SYSSTAT</code> statistic "Parallel operations downgraded to serial" is large. <code>Servers Cleaned Up</code> - Number of times PMON had to clean up a PX server. This should only happen during abnormal termination of a parallel operation. If this number is large, then you should determine the cause. <code>Server Sessions</code> - Total number of sessions created by all PX servers <code>Memory Chunks Allocated</code> - Number of large memory chunks allocated by PX servers <code>Memory Chunks Freed</code> - Number of large memory chunks freed <code>Memory Chunks Current</code> - Number of large memory chunks currently being used <code>Memory Chunks HWM</code> - Maximum number of concurrently allocated chunks <code>Buffers allocated</code> - Number of times a message buffer has been allocated <code>Buffers freed</code> - Number of times a message buffer has been freed <code>Buffers Current</code> - Number of message buffers currently being used <code>Buffers HWM</code> - Maximum number of concurrently allocated message buffers
VALUE	NUMBER	Value of the statistic

V\$PX_SESSION

V\$PX_SESSION contains information about the sessions running parallel execution.

Column	Datatype	Description
SADDR	RAW (4 8)	Session address
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Session serial number
QCSID	NUMBER	Session identifier of the parallel coordinator
QCSERIAL#	NUMBER	Session serial number of the parallel coordinator
QCINST_ID	NUMBER	Instance number on which the parallel coordinator is running
SERVER_GROUP	NUMBER	The logical group of servers to which this cluster database process belongs

Column	Datatype	Description
SERVER_SET	NUMBER	The logical set of servers to which this cluster database process belongs. A single server group will have at most two server sets.
SERVER#	NUMBER	The logical number of the cluster database process within a server set
DEGREE	NUMBER	The degree of parallelism being used by the server set
REQ_DEGREE	NUMBER	The degree of parallelism that was requested by the user when the statement was issued and prior to any resource, multi-user, or load balancing reductions

V\$PX_SESSTAT

V\$PX_SESSTAT contains information about the sessions running parallel execution.

Column	Datatype	Description
SADDR	RAW (4 8)	Session address
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Session serial number
QCSID	NUMBER	Session identifier of the parallel coordinator
QCSERIAL#	NUMBER	Session serial number of the parallel coordinator
QCINST_ID	NUMBER	Instance number on which the parallel coordinator is running
SERVER_GROUP	NUMBER	The logical group of servers to which this cluster database process belongs
SERVER_SET	NUMBER	The logical set of servers that this cluster database process belongs to. A single server group will have at most two server sets.
SERVER#	NUMBER	The logical number of the cluster database process within a server set
DEGREE	NUMBER	The degree of parallelism being used by the server set
REQ_DEGREE	NUMBER	The degree of parallelism that was requested by the user when the statement was issued and prior to any resource, multi-user, or load balancing reductions
STATISTIC#	NUMBER	Statistic number
VALUE	NUMBER	Statistic value

V\$QMON_COORDINATOR_STATS

V\$QMON_COORDINATOR_STATS displays information and statistics about the Queue Monitor Coordinator process (QMNC). There is one row per instance. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QMNC_PID	VARCHAR2 (24)	Queue Monitor Coordinator process ID
STATUS	VARCHAR2 (24)	Current status of the coordinator: - DEAD - INITIALIZING - RUNNING TASK COORDINATOR - WAITING - ADDING SERVER
NUM_SERVERS	NUMBER	Number of QMON servers currently running
LAST_SERVER_START_TIME	TIMESTAMP (3) WITH TIME ZONE	Last server startup time
LAST_SERVER_PID	VARCHAR2 (24)	Process ID of the last server process (Qnnn) created

Column	Datatype	Description
NEXT_WAKEUP_TIME	TIMESTAMP (3) WITH TIME ZONE	Next wakeup time of the coordinator
NEXT_READY_TIME	TIMESTAMP (3) WITH TIME ZONE	Ready time of the first delayed task
NEXT_EXPIRY_TIME	TIMESTAMP (3) WITH TIME ZONE	Expiry time of the next ready task
LAST_WAIT_TIME	TIMESTAMP (3) WITH TIME ZONE	Time when the coordinator went to sleep
LAST_FAILURE	VARCHAR2 (32)	Last failure encountered
LAST_FAILURE_TIME	TIMESTAMP (3) WITH TIME ZONE	Last failure time
MAX_TASK_LATENCY	VARCHAR2 (40)	Maximum task latency across all the servers (in seconds)
MIN_TASK_LATENCY	VARCHAR2 (40)	Minimum task latency across all the servers (in seconds)
TOTAL_TASK_LATENCY	NUMBER	Cumulative latency across all the tasks (in seconds)
TOTAL_TASKS_EXECUTED	NUMBER	Cumulative number of tasks serviced by all the servers
MAX_SERVERS	NUMBER	Maximum number of servers present at any point of time

V\$QMON_SERVER_STATS

V\$QMON_SERVER_STATS displays information and statistics about the active queue monitor server processes. There is one row per live queue monitor server process. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QMNC_PID	VARCHAR2 (24)	Process ID of the Queue Monitor Coordinator for this server
SERVER_PID	VARCHAR2 (24)	Process ID of the server
SERVER_NAME	VARCHAR2 (48)	Name of the server
STATUS	VARCHAR2 (40)	Current state of the server: ■ UNUSED ■ RUNNING ■ IDLE WAIT ■ EXITING ■ NOT ACTIVE
SERVER_START_TIME	TIMESTAMP (3) WITH TIME ZONE	Start time of the server
TASK_NAME	VARCHAR2 (32)	Current executing task
TASK_NUMBER	NUMBER	Unique task number of the running task
TASK_START_TIME	TIMESTAMP (3) WITH TIME ZONE	Start time of the running task
LAST_WAIT_TIME	TIMESTAMP (3) WITH TIME ZONE	Time when the server last waited
MAX_LATENCY	NUMBER	Maximum task latency for this server (in seconds)
MIN_LATENCY	NUMBER	Minimum task latency for this server (in seconds)
TOTAL_LATENCY	NUMBER	Cumulative task latency for this server (in seconds)
NUM_TASKS	NUMBER	Number of tasks processed by the server
LAST_FAILURE	VARCHAR2 (32)	Last failure encountered by the server
LAST_FAILURE_TIME	TIMESTAMP (3) WITH TIME ZONE	Last failure time

Column	Datatype	Description
LAST_FAILURE_TASK	VARCHAR2 (32)	Task being run at the time of the last failure
LAST_FAILURE_TASKNUM	NUMBER	Unique task number of the failed task

V\$QMON_TASK_STATS

V\$QMON_TASK_STATS displays information and statistics based on different queue monitor tasks in the system (spilling, time manager activity, and so on). There is one row per kind of task. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
TASK_NAME	VARCHAR2 (32)	Name of the task
TASK_TYPE	VARCHAR2 (40)	Type of the task
LAST_CREATED_TASKNUM	NUMBER	Unique task number last created for this task
NUM_TASKS	NUMBER	Number of tasks currently present
TOTAL_TASK_RUN_TIME	NUMBER	Cumulative task run time
TOTAL_TASK_RUNS	NUMBER	Cumulative task runs
TOTAL_TASK_FAILURES	NUMBER	Cumulative failures
METRIC_TYPE	VARCHAR2 (50)	Type of metric gathered for this task type
METRIC_VALUE	NUMBER	Value of this metric
LAST_FAILURE	VARCHAR2 (32)	Last failure encountered while executing this type of task
LAST_FAILURE_TIME	TIMESTAMP (3) WITH TIME ZONE	Time when the last failure occurred
LAST_FAILURE_TASKNUM	NUMBER	Task number of the last failed task for this task
REMARK	VARCHAR2 (64)	Remarks about the task

V\$QMON_TASKS

V\$QMON_TASKS displays information and statistics about all queue background tasks in the system, which would be served by queue monitor servers. There is one row per task. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
TASK_NAME	VARCHAR2 (32)	Task name
TASK_NUMBER	NUMBER	Unique task number
TASK_TYPE	VARCHAR2 (40)	Task type
TASK_SUBMIT_TIME	TIMESTAMP (3) WITH TIME ZONE	Task submit time
TASK_READY_TIME	TIMESTAMP (3) WITH TIME ZONE	Task ready time
TASK_EXPIRY_TIME	TIMESTAMP (3) WITH TIME ZONE	Time when this task expires
TASK_START_TIME	TIMESTAMP (3) WITH TIME ZONE	Last actual start time for the task
TASK_STATUS	VARCHAR2 (32)	Status of the task
SERVER_NAME	VARCHAR2 (48)	Name of the QMON server running this task
MAX_RETRIES	NUMBER	Maximum retry count for the task

V\$QUEUE

Column	Datatype	Description
NUM_RUNS	NUMBER	Number of runs of the task if repeatable
NUM_FAILURES	NUMBER	Number of failures encountered while running the task

V\$QUEUE

V\$QUEUE contains information on the shared server message queues.

Column	Datatype	Description
PADDR	RAW (4 8)	Address of the process that owns the queue
TYPE	VARCHAR2 (10)	Type of queue: ■ COMMON - Processed by servers ■ DISPATCHER
QUEUED	NUMBER	Number of items in the queue
WAIT	NUMBER	Total time that all items in this queue have waited (in hundredths of a second). Divide by TOTALQ for average wait per item.
TOTALQ	NUMBER	Total number of items that have ever been in the queue

V\$QUEUEING_MTH

V\$QUEUEING_MTH displays all available queuing resource allocation methods.

Column	Datatype	Description
NAME	VARCHAR2 (40)	Name of the queuing resource allocation method

V\$RECOVER_FILE

V\$RECOVER_FILE displays the status of files needing media recovery.

Column	Datatype	Description
FILE#	NUMBER	File identifier number
ONLINE	VARCHAR2 (7)	This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in ONLINE_STATUS.
ONLINE_STATUS	VARCHAR2 (7)	Online status (ONLINE, OFFLINE)
ERROR	VARCHAR2 (18)	Why the file needs to be recovered: NULL if reason unknown, or OFFLINE NORMAL if recovery not needed
CHANGE#	NUMBER	SCN where recovery must start
TIME	DATE	Time of SCN when recovery must start

V\$RECOVERY_AREA_USAGE

V\$RECOVERY_AREA_USAGE displays usage information about recovery areas.

Column	Datatype	Description
FILE_TYPE	VARCHAR2 (20)	File type: ■ CONTROL FILE ■ REDO LOG ■ ARCHIVED LOG ■ BACKUP PIECE ■ IMAGE COPY ■ FLASHBACK LOG ■ REMOTE ARCHIVED LOG
PERCENT_SPACE_USED	NUMBER	Percent of the recovery area that is in use
PERCENT_SPACE_RECLAIMABLE	NUMBER	Percent of the recovery area that is reclaimable
NUMBER_OF_FILES	NUMBER	Number of files in the recovery area

V\$RECOVERY_FILE_DEST

V\$RECOVERY_FILE_DEST displays information about the disk quota and current disk usage in the fast recovery area.

Column	Datatype	Description
NAME	VARCHAR2 (513)	Location name. This is the value specified in the DB_RECOVERY_FILE_DEST initialization parameter.
SPACE_LIMIT	NUMBER	Maximum amount of disk space (in bytes) that the database can use for the fast recovery area. This is the value specified in the DB_RECOVERY_FILE_DEST_SIZE initialization parameter.
SPACE_USED	NUMBER	Amount of disk space (in bytes) used by fast recovery area files created in current and all previous fast recovery areas. Changing fast recovery areas does not reset SPACE_USED to 0.
SPACE_RECLAIMABLE	NUMBER	Total amount of disk space (in bytes) that can be created by deleting obsolete, redundant, and other low priority files from the fast recovery area
NUMBER_OF_FILES	NUMBER	Number of files in the fast recovery area

V\$RECOVERY_FILE_STATUS

V\$RECOVERY_FILE_STATUS contains one row for each datafile for each RECOVER statement. This view contains useful information only for the Oracle process doing the recovery. When Recovery Manager directs a server process to perform recovery, only Recovery Manager is able to view the relevant information in this view. V\$RECOVERY_FILE_STATUS will be empty to all other Oracle users.

Column	Datatype	Description
FILENUM	NUMBER	Number of the file being recovered
FILENAME	VARCHAR2 (513)	Filename of the datafile being recovered
STATUS	VARCHAR2 (13)	Status of the recovery: ■ IN RECOVERY ■ CURRENT ■ NOT RECOVERED

See Also: *Oracle Database Backup and Recovery User's Guide*

V\$RECOVERY_LOG

V\$RECOVERY_LOG lists information about archived logs that are needed to complete media recovery. This information is derived from the log history view, V\$LOG_HISTORY.

V\$RECOVERY_LOG contains useful information only for the Oracle process doing the recovery. When Recovery Manager directs a server process to perform recovery, only Recovery Manager is able to view the relevant information in this view. V\$RECOVERY_LOG will be empty to all other Oracle users.

Column	Datatype	Description
THREAD#	NUMBER	Thread number of the archived log
SEQUENCE#	NUMBER	Sequence number of the archived log
TIME	DATE	Time of the first entry (lowest SCN) in the log
ARCHIVE_NAME	VARCHAR2 (513)	Name of the file when archived, using the naming convention specified by the LOG_ARCHIVE_FORMAT initialization parameter See Also: "LOG_ARCHIVE_FORMAT" on page 1-93

See Also: "V\$LOG_HISTORY" on page 8-18 and *Oracle Database Backup and Recovery User's Guide*

V\$RECOVERY_PROGRESS

V\$RECOVERY_PROGRESS can be used to track database recovery operations to ensure that they are not stalled, and also to estimate the time required to complete the operation in progress.

V\$RECOVERY_PROGRESS is a subview of V\$SESSION_LONGOPS.

Column	Datatype	Description
START_TIME	DATE	Start time of the recovery operation
TYPE	VARCHAR2 (64)	Type of recovery operation being performed
ITEM	VARCHAR2 (32)	Item being measured
UNITS	VARCHAR2 (32)	The units of measurement for each item
SOFAR	NUMBER	Amount of work done so far
TOTAL	NUMBER	Total amount of work expected
TIMESTAMP	DATE	Timestamp of the last redo record applied
COMMENTS	VARCHAR2 (208)	Miscellaneous notes; currently displays the SCN for the last applied redo

See Also: *Oracle Database Backup and Recovery User's Guide*

V\$RECOVERY_STATUS

V\$RECOVERY_STATUS contains statistics of the current recovery process. This view contains useful information only for the Oracle process doing the recovery. When Recovery Manager directs a server process to perform recovery, only Recovery Manager is able to view the relevant information in this view. V\$RECOVERY_STATUS will be empty to all other Oracle users.

Column	Datatype	Description
RECOVERY_CHECKPOINT	DATE	Point in time to which the recovery has occurred. If no logs have been applied, this is the point in time the recovery starts.
THREAD	NUMBER	Number of the redo thread currently being processed
SEQUENCE_NEEDED	NUMBER	Log sequence number of the log needed by the recovery process. The value is 0 if no log is needed.
SCN_NEEDED	VARCHAR2 (16)	Low SCN of the log needed by recovery. The value is 0 if unknown or no log is needed.
TIME_NEEDED	DATE	Time when the log was created. The value is midnight on 1/1/88 if the time is unknown or if no log is needed.
PREVIOUS_LOG_NAME	VARCHAR2 (513)	Filename of the log
PREVIOUS_LOG_STATUS	VARCHAR2 (13)	Status of the previous log. Contains one of the following values: RELEASE; WRONG NAME; MISSING NAME; UNNEEDED NAME; NONE
REASON	VARCHAR2 (13)	Reason recovery is returning control to the user (NEED LOG LOG REUSED THREAD DISABLED)

See Also: *Oracle Database Backup and Recovery User's Guide*

V\$REDO_DEST_RESP_HISTOGRAM

V\$REDO_DEST_RESP_HISTOGRAM provides statistical information for each redo transport destination.

Column	Datatype	Description
DEST_ID	NUMBER	A non-negative integer value from 1 - 10 for each possible LGWR SYNC standby destination
TIME	VARCHAR2 (20)	A text string that shows the last wall-clock time that a bucket was hit
DURATION	NUMBER	A positive integer value that represents a bucket of seconds, 1, 2, 3, up to 300 seconds, followed by 5 additional buckets that represent 600, 1200, 2400, 4800, and 9600 (>= 4801) seconds
FREQUENCY	NUMBER	A non-negative integer that shows the number of times a particular bucket was hit by the SYNC LNS process

V\$REPLPROP

V\$REPLPROP displays information about the parallel propagation currently in progress at the replication site. Use this view to determine which transactions are currently being propagated, the number of calls propagated in each transaction, and the current activity of the parallel propagation slave processes or parallel propagation coordinator process.

Column	Datatype	Description
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Session serial number. Used to identify uniquely a session's objects. Guarantees that session-level commands are applied to the correct session objects if the session ends with, and another session begins with, the same session ID.

Column	Datatype	Description
NAME	VARCHAR2 (71)	Name of the propagation session: - Replication Parallel Prop Slaven - Slave process <i>n</i> is active, either waiting, pushing deferred transactions, purging metadata, or creating an error transaction - Replication Parallel Prop Coordinator - Coordinator process is active, and either waiting, sleeping, or scheduling slaves to perform operations The coordinator process reads transactions from the deferred transaction queue and assigns them to the slave processes. Then, the slaves propagate the transactions to the destination site. When the slaves push transactions in a push session, the slaves remain active until the push session completes, even if there are no more transactions to push.
DBLINK	VARCHAR2 (128)	Database link on which this replication session is propagating
STATE	VARCHAR2 (12)	State of the propagation session: - WAIT - Slave processes or the coordinator process is waiting for an event (that is, a message) - SLEEP - Coordinator process is sleeping for the duration of the <code>delay_seconds</code> setting. Note: <code>delay_seconds</code> is set with the <code>DBMS_DEFER_SYS.SCHEDULE_PUSH</code> procedure. - PUSH - Slave processes are pushing transactions from the deferred transaction queue to the remote site - PURGE - Slave processes are purging metadata related to successfully applied transactions from the remote site - CREATE_ERROR - Slave processes are creating an error transaction. In this case, an error or a conflict occurred while the slaves were pushing deferred transactions to the remote site. - SCHEDULE_TXN - Coordinator process is determining the order that transactions are applied and assigning slave processes to execute the transactions
XID	VARCHAR2 (22)	If the session is a slave session, then indicates the transaction id of the transaction that the slave is currently propagating.
SEQUENCE	NUMBER	If the process is a slave process, then indicates the sequence number of the calls propagated in the current operation, if relevant. Each transaction must process one or more calls, and the value of <code>SEQUENCE</code> starts at zero and increases as each call is processed. The <code>SEQUENCE</code> value shows the call that is currently being processed in each transaction. This value increases until the slave has processed all of the calls in a transaction.

Note: This view only contains data when deferred transactions are being pushed using parallel propagation at the current site. The `parallelism` parameter must be set to 1 or higher in the `DBMS_DEFER_SYS.SCHEDULE_PUSH` function for a push to use parallel propagation. Otherwise, the push uses serial propagation, and no data appears in this view during the push.

V\$REPLQUEUE

V\$REPLQUEUE displays statistics about the replication deferred transactions queue. All values are stored since the start of the current database instance.

Column	Datatype	Description
TXNS_ENQUEUED	NUMBER	Number of transactions enqueued in the deferred transactions queue
CALLS_ENQUEUED	NUMBER	Number of calls enqueued into the deferred transactions queue
TXNS_PURGED	NUMBER	Number of transactions purged from the deferred transactions queue

Column	Datatype	Description
LAST_ENQUEUE_TIME	DATE	Date when the last transaction was enqueued into the deferred transaction queue (null if no transactions have been enqueued into the deferred transaction queue since the instance started)
LAST_PURGE_TIME	DATE	Date when the last transaction was purged from the deferred transaction queue (null if no transactions have been purged from the deferred transaction queue since the instance started)

V\$REQDIST

V\$REQDIST lists statistics for the histogram of shared server dispatcher request times, divided into 12 buckets, or ranges of time. The time ranges grow exponentially as a function of the bucket number.

Column	Datatype	Description
BUCKET	NUMBER	Bucket number: 0 – 11; the maximum time for each bucket is $(4 * 2^N) / 100$ seconds
COUNT	NUMBER	Count of requests whose total time to complete (excluding wait time) falls in this range

V\$RESERVED_WORDS

V\$RESERVED_WORDS displays a list of all SQL keywords. To determine whether a particular keyword is reserved in any way, check the RESERVED, RES_TYPE, RES_ATTR, and RES_SEMI columns.

Column	Datatype	Description
KEYWORD	VARCHAR2 (30)	Name of the keyword
LENGTH	NUMBER	Length of the keyword
RESERVED	VARCHAR2 (1)	Indicates whether the keyword cannot be used as an identifier (Y) or whether the keyword is not reserved (N)
RES_TYPE	VARCHAR2 (1)	Indicates whether the keyword cannot be used as a type name (Y) or whether the keyword is not reserved (N)
RES_ATTR	VARCHAR2 (1)	Indicates whether the keyword cannot be used as an attribute name (Y) or whether the keyword is not reserved (N)
RES_SEMI	VARCHAR2 (1)	Indicates whether the keyword is not allowed as an identifier in certain situations, such as in DML (Y) or whether the keyword is not reserved (N)
DUPLICATE	VARCHAR2 (1)	Indicates whether the keyword is a duplicate of another keyword (Y) or whether the keyword is not a duplicate (N)

V\$RESOURCE

V\$RESOURCE contains resource name and address information.

Column	Datatype	Description
ADDR	RAW (4 8)	Address of the resource object
TYPE	VARCHAR2 (2)	Resource type; the resource types are listed in Table 8–1 on page 8-16
ID1	NUMBER	Resource identifier #1
ID2	NUMBER	Resource identifier #2

V\$RESOURCE_LIMIT

V\$RESOURCE_LIMIT displays information about global resource use for some of the system resources. Use this view to monitor the consumption of resources so that you can take corrective action, if necessary. Many of the resources correspond to initialization parameters listed in [Table 8–5](#).

Some resources, those used by DLM for example, have an initial allocation (soft limit), and the hard limit, which is theoretically infinite (although in practice it is limited by SGA size). During SGA reservation/initialization, a place is reserved in SGA for the INITIAL_ALLOCATION of resources, but if this allocation is exceeded, additional resources are allocated up to the value indicated by LIMIT_VALUE. The CURRENT_UTILIZATION column indicates whether the initial allocation has been exceeded. When the initial allocation value is exceeded, the additional required resources are allocated from the shared pool, where they must compete for space with other resources.

A good choice for the value of INITIAL_ALLOCATION will avoid the contention for space. For most resources, the value for INITIAL_ALLOCATION is the same as the LIMIT_VALUE. Exceeding LIMIT_VALUE results in an error.

Column	Datatype	Description
RESOURCE_NAME	VARCHAR2 (30)	Name of the resource (see Table 8–5)
CURRENT_UTILIZATION	NUMBER	Number of (resources, locks, or processes) currently being used
MAX_UTILIZATION	NUMBER	Maximum consumption of this resource since the last instance start-up
INITIAL_ALLOCATION	VARCHAR2 (10)	Initial allocation. This will be equal to the value specified for the resource in the initialization parameter file (UNLIMITED for infinite allocation).
LIMIT_VALUE	VARCHAR2 (10)	Unlimited for resources and locks. This can be greater than the initial allocation value (UNLIMITED for infinite limit).

Table 8–5 Values for the RESOURCE_NAME Column

Resource Name	Corresponds to
DML_LOCKS	See " DML_LOCKS " on page 1-66
ENQUEUE_LOCKS	This value is computed by the Oracle Database. See V\$ENQUEUE_LOCK on page 7-92 to obtain more information about the enqueue locks.
GES_LOCKS	Global Enqueue Service locks
GES_PROCS	Global Enqueue Service processes
GES_RESS	Global Enqueue Service resources
MAX_SHARED_SERVERS	See " MAX_SHARED_SERVERS " on page 1-102
PARALLEL_MAX_SERVERS	See " PARALLEL_MAX_SERVERS " on page 1-130
PROCESSES	See " PROCESSES " on page 1-140
SESSIONS	See " SESSIONS " on page 1-157
SORT_SEGMENT_LOCKS	This value is computed by the Oracle Database
TEMPORARY_LOCKS	This value is computed by the Oracle Database
TRANSACTIONS	See " TRANSACTIONS " on page 1-175

V\$RESTORE_POINT

V\$RESTORE_POINT displays information about restore points.

Column	Datatype	Description
SCN	NUMBER	Database SCN when the restore point was created
DATABASE_INCARNATION#	NUMBER	Database incarnation number when the restore point was created
GUARANTEE_FLASHBACK_DATABASE	VARCHAR2 (3)	Indicates whether flashback log files will be kept to ensure a flashback to this point (YES) or not (NO)
STORAGE_SIZE	NUMBER	Approximate number of bytes of disk space currently tied up supporting this restore point. This will only be nonzero for guaranteed restore points.
TIME	TIMESTAMP (9)	Wall-clock time when the restore point was created
RESTORE_POINT_TIME	TIMESTAMP (9)	Time that was specified when the restore point was created. If a time was not specified, this value is NULL.
PRESERVED	VARCHAR2 (3)	Indicates whether the restore point must be explicitly deleted (YES) or not (NO)
NAME	VARCHAR2 (128)	Name of the restore point

V\$RESULT_CACHE_DEPENDENCY

V\$RESULT_CACHE_DEPENDENCY displays the depends-on relationship between cached results and dependencies.

Column	Datatype	Description
RESULT_ID	NUMBER	Cached result
DEPEND_ID	NUMBER	Dependency object
OBJECT_NO	NUMBER	Dictionary object number of the dependency object

V\$RESULT_CACHE_MEMORY

V\$RESULT_CACHE_MEMORY displays all the memory blocks and their status.

Column	Datatype	Description
ID	NUMBER	Unique block identifier (that is, the block number)
CHUNK	NUMBER	Chunk to which the block belongs (the upper 27 bits of the ID)
OFFSET	NUMBER	Offset of the block within its chunk (the lower 5 bits of the ID)
FREE	VARCHAR2 (3)	Indicates whether the block is free (YES) or not (NO)
OBJECT_ID	NUMBER	Cache object to which the memory block belongs; NULL unless the memory block is allocated to a cache object (FREE = NO)
POSITION	NUMBER	Position of the block in the cached object; NULL unless the memory block is allocated to a cache object (FREE = NO)

V\$RESULT_CACHE_OBJECTS

V\$RESULT_CACHE_OBJECTS displays all the objects (both cached results and dependencies) and their attributes.

Column	Datatype	Description
ID	NUMBER	Identifier for the cache object (also the ID of the first block)
TYPE	VARCHAR2 (10)	Type of the cache object: - Result - Dependency

Column	Datatype	Description
STATUS	VARCHAR2 (9)	Status of the object: ■ New - Result is still under construction ■ Published - Result is available for use ■ Bypass - Result will be bypassed from use ■ Expired - Result has exceeded expiration time ■ Invalid - Result is no longer available for use
BUCKET_NO	NUMBER	Internal hash bucket for the object
HASH	NUMBER	Hash value for the object
NAME	VARCHAR2 (128)	Name (for example, SQL prefix or PL/SQL function name)
NAMESPACE	VARCHAR2 (5)	Namespace: ■ SQL ■ PLSQL
CREATION_TIMESTAMP	DATE	Time when the object was created
CREATOR_UID	NUMBER	UID that created the object
DEPEND_COUNT	NUMBER	Number of dependencies (TYPE = Result) or dependents (TYPE = Dependency)
BLOCK_COUNT	NUMBER	Total number of blocks in the cached object
SCN	NUMBER	Build SCN (TYPE = Result) or invalidation SCN (TYPE = Dependency)
COLUMN_COUNT	NUMBER	Number of columns in the cached result ¹
PIN_COUNT	NUMBER	Number of active scans on this result ¹
SCAN_COUNT	NUMBER	Total number of scans initiated on the cached result ¹
ROW_COUNT	NUMBER	Total number of rows in the cached result ¹
ROW_SIZE_MAX	NUMBER	Size of the largest row (in bytes) ¹
ROW_SIZE_MIN	NUMBER	Size of the smallest row (in bytes) ¹
ROW_SIZE_AVG	NUMBER	Average size of a row (in bytes) ¹
BUILD_TIME	NUMBER	Amount of time (in hundredths of a second) it took to build the cached result ¹
LRU_NUMBER	NUMBER	LRU list position (the smaller the value, the more recent the usage) ¹
OBJECT_NO	NUMBER	Dictionary object number of the dependency object ²
INVALIDATIONS	NUMBER	Number of times the object has invalidated its dependents ²
SPACE_OVERHEAD	NUMBER	Overhead (in bytes) for the result ¹
SPACE_UNUSED	NUMBER	Unused space (in bytes) for the result ¹
CACHE_ID	VARCHAR2 (93)	CacheId for the result (object name if it's a dependency)
CACHE_KEY	VARCHAR2 (93)	CacheKey for the result (object name if it's a dependency)

¹ These columns are only valid for TYPE = Result; otherwise, they are NULL.

² These columns are only valid for TYPE = Dependency; otherwise, they are NULL.

V\$RESULT_CACHE_STATISTICS

V\$RESULT_CACHE_STATISTICS displays various Result Cache settings and usage statistics.

Column	Datatype	Description
ID	NUMBER	Statistic number

Column	Datatype	Description
NAME	VARCHAR2 (128)	Name of the statistic (see Table 8–6)
VALUE	NUMBER	Value of the statistic

Table 8–6 V\$RESULT_CACHE_STATISTICS Statistics

Statistic Name	Description
Block Size (Bytes)	Size of each memory block
Block Count Maximum	Maximum number of memory blocks allowed
Block Count Current	Number of memory blocks currently allocated
Result Size Maximum (Blocks)	Maximum number of blocks allowed for a single result
Create Count Success	Number of cache results successfully created
Create Count Failure	Number of cache results that failed to create
Find Count	Number of cached results that were successfully found
Invalidation Count	Total number of invalidations
Delete Count Invalid	Number of invalid cached results deleted
Delete Count Valid	Number of valid cached results deleted
Hash Chain Length	Average length of items in the hash chain
Find Copy Count ¹	Number of results copied directly out of the cache

¹ This statistic is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$RMAN_BACKUP_JOB_DETAILS

V\$RMAN_BACKUP_JOB_DETAILS displays details about backup jobs.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Together, with SESSION_KEY and SESSION_STAMP, used to uniquely identify job output from V\$RMAN_OUTPUT
SESSION_STAMP	NUMBER	Together, with SESSION_KEY and SESSION_RECID, used to uniquely identify job output from V\$RMAN_OUTPUT
COMMAND_ID	VARCHAR2 (33)	Either a user-specified SET COMMAND ID or a unique command ID generated by RMAN
START_TIME	DATE	Start time of the first BACKUP command in the job
END_TIME	DATE	End time of the last BACKUP command in the job
INPUT_BYTES	NUMBER	Sum of all input file sizes backed up by this job
OUTPUT_BYTES	NUMBER	Output size of all pieces generated by this job
STATUS_WEIGHT	NUMBER	Used internally by Enterprise Manager
OPTIMIZED_WEIGHT	NUMBER	Used internally by Enterprise Manager
OBJECT_TYPE_WEIGHT	NUMBER	Used internally by Enterprise Manager
OUTPUT_DEVICE_TYPE	VARCHAR2 (17)	Can be DISK, SBT, or *. An * indicates more than one device (in most cases, it will be DISK or SBT).
AUTOBACKUP_COUNT	NUMBER	Number of autobackups performed by this job
BACKED_BY_OSB	VARCHAR2 (3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.
AUTOBACKUP_DONE	VARCHAR2 (3)	YES or NO, depending upon whether or not a control file autobackup was done as part of this backup job

Column	Datatype	Description
STATUS	VARCHAR2 (23)	One of the following values: ■ RUNNING WITH WARNINGS ■ RUNNING WITH ERRORS ■ COMPLETED ■ COMPLETED WITH WARNINGS ■ COMPLETED WITH ERRORS ■ FAILED
INPUT_TYPE	VARCHAR2 (13)	Contains one of the following values. If the user command does not satisfy one of them, then preference is given in order, from top to bottom of the list. ■ DB FULL ■ RECVR AREA ■ DB INCR ■ DATAFILE FULL ■ DATAFILE INCR ■ ARCHIVELOG ■ CONTROLFILE ■ SPFILE
OPTIMIZED	VARCHAR2 (3)	YES or NO, depending on whether optimization was applied. Applicable to backup jobs only.
ELAPSED_SECONDS	NUMBER	Number of elapsed seconds
COMPRESSION_RATIO	NUMBER	Compression ratio
INPUT_BYTES_PER_SEC	NUMBER	Input read-rate-per-second
OUTPUT_BYTES_PER_SEC	NUMBER	Output write-rate-per-second
INPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Values in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Values in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on
INPUT_BYTES_PER_SEC_DISPLAY	VARCHAR2 (4000)	Input read-rate-per-second. These values are in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.
OUTPUT_BYTES_PER_SEC_DISPLAY	VARCHAR2 (4000)	Output write-rate-per-second. These values are in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.
TIME_TAKEN_DISPLAY	VARCHAR2 (4000)	Time taken, shown in user-displayable format <nn>h:<nn>m:<nn>s

V\$RMAN_BACKUP_SUBJOB_DETAILS

V\$RMAN_BACKUP_SUBJOB_DETAILS merges similar operations within an RMAN session into a single row. For example, if there are four BACKUP DATAFILE <n> commands, three RECOVERY COPY OF DATAFILE commands, and one BACKUP RECOVERY AREA command, this view will contain three rows - one each for BACKUP, ROLLFORWARD, and COPY_DISK_TO_TAPE operation.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Together with SESSION_KEY and SESSION_STAMP, used to uniquely identify job output from V\$RMAN_OUTPUT
SESSION_STAMP	NUMBER	Together with SESSION_KEY and SESSION_RECID, used to uniquely identify job output from V\$RMAN_OUTPUT

Column	Datatype	Description
OPERATION	VARCHAR2 (33)	Can be BACKUP, ROLLFORWARD, VALIDATE, or COPY_DISK_TO_TAPE. A row for each suboperation type for the session will be in the output view.
COMMAND_ID	VARCHAR2 (33)	Either a user-specified SET COMMAND ID or a unique command ID generated by RMAN
START_TIME	DATE	Start time of the first BACKUP command in the job
END_TIME	DATE	End time of the last BACKUP command in the job
INPUT_BYTES	NUMBER	Sum of all input file sizes backed up by this job
OUTPUT_BYTES	NUMBER	Output size of all pieces generated by this job
STATUS_WEIGHT	NUMBER	Used internally by Enterprise Manager
OBJECT_TYPE_WEIGHT	NUMBER	Used internally by Enterprise Manager
OPTIMIZED_WEIGHT	NUMBER	Used internally by Enterprise Manager
OUTPUT_DEVICE_TYPE	VARCHAR2 (17)	Can be DISK, SBT, or *. An * indicates more than one device (in most cases, it will be DISK or SBT).
BACKED_BY_OSB	VARCHAR2 (3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.
AUTOBACKUP_DONE	VARCHAR2 (3)	YES or NO, depending upon whether or not a control file autobackup was done as part of this job
STATUS	VARCHAR2 (23)	One of the following values: ■ RUNNING WITH WARNINGS ■ RUNNING WITH ERRORS ■ COMPLETED ■ COMPLETED WITH WARNINGS ■ COMPLETED WITH ERRORS ■ FAILED
INPUT_TYPE	VARCHAR2 (13)	Contains one of the following values. If the user command does not satisfy one of them, then preference is given in order, from top to bottom of the list. ■ DB FULL ■ RECV AREA ■ DB INCR ■ DATAFILE FULL ■ DATAFILE INCR ■ ARCHIVELOG ■ CONTROLFILE ■ SPFILE
OPTIMIZED	VARCHAR2 (3)	YES or NO, depending on whether optimization was applied. Applicable to backup jobs only.
AUTOBACKUP_COUNT	NUMBER	Number of autobackups performed by this job
COMPRESSION_RATIO	NUMBER	Compression ratio
INPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Values in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.
OUTPUT_BYTES_DISPLAY	VARCHAR2 (4000)	Values in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.

V\$RMAN_BACKUP_TYPE

V\$RMAN_BACKUP_TYPE displays information about RMAN backup types.

Column	Datatype	Description
WEIGHT	NUMBER	Used to set precedence order of different backup types in reports.
INPUT_TYPE	VARCHAR2 (13)	Used to represent possible filters used in creating various reporting screens.

V\$RMAN_COMPRESSION_ALGORITHM

V\$RMAN_COMPRESSION_ALGORITHM provides descriptions of supported compression algorithms. It is used by the RMAN client.

Column	Datatype	Description
ALGORITHM_ID ¹	NUMBER	Algorithm ID
ALGORITHM_NAME	VARCHAR2 (64)	Name of the algorithm (for example, LOW, MEDIUM, DEFAULT, or HIGH)
INITIAL_RELEASE	VARCHAR2 (18)	First Oracle Database release when this compression algorithm was available
TERMINAL_RELEASE	VARCHAR2 (18)	Last Oracle Database release that supported using this compression algorithm to create new backups. Existing backups can always be restored, even if they use a deprecated compression algorithm.
ALGORITHM_DESCRIPTION	VARCHAR2 (64)	Description of the algorithm
ALGORITHM_COMPATIBILITY	VARCHAR2 (18)	Required database compatibility level for the algorithm (for example, 11.2.0 for DEFAULT)
IS_VALID	VARCHAR2 (3)	Indicates whether the algorithm is valid with regard to the compatibility setting (YES) or not (NO). The value is YES if ALGORITHM_COMPATIBILITY <= DATABASE_COMPATIBILITY.
REQUIRES_ACO	VARCHAR2 (3)	Indicates whether the algorithm requires the Advanced Compression Option (YES) or not (NO)
IS_DEFAULT ¹	VARCHAR2 (3)	Indicates whether the algorithm is the default compression algorithm that RMAN uses to create compressed backup sets (YES) or not (NO)

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$RMAN_CONFIGURATION

V\$RMAN_CONFIGURATION lists information about RMAN persistent configuration settings.

Column	Datatype	Description
CONF#	NUMBER	A unique key identifying this configuration record within the target database that owns it.
NAME	VARCHAR2 (65)	The type of configuration. All options of the CONFIGURE command are valid types except: ■ CONFIGURE EXCLUDE (described in RC_TABLESPACE) ■ CONFIGURE AUXNAME (described in RC_DATAFILE) ■ CONFIGURE SNAPSHOT CONTROLFILE (stored only in control file)
VALUE	VARCHAR2 (1025)	The CONFIGURE command setting. Example: RETENTION POLICY TO RECOVERY WINDOW OF 10 DAYS

V\$RMAN_ENCRYPTION_ALGORITHMS

V\$RMAN_ENCRYPTION_ALGORITHMS displays supported encryption algorithms. It is used by the RMAN client to validate user-requested algorithms. This view will list AES128, AES192, and AES256 encryption algorithms for the current release. The default algorithm is AES128.

Column	Datatype	Description
ALGORITHM_ID	NUMBER	Number to identify the algorithm
ALGORITHM_NAME	VARCHAR2 (64)	Name of the algorithm (for example, AES128, AES192, or AES256)
ALGORITHM_DESCRIPTION	VARCHAR2 (64)	Description of the algorithm
IS_DEFAULT	VARCHAR2 (3)	Indicates whether this is the default encryption algorithm (YES) or not (NO). This value is set by Oracle Database and may vary for each Release (that is, it is not dependent on user-specified RMAN configuration).
RESTORE_ONLY	VARCHAR2 (3)	Indicates whether this algorithm can be used for restore only (YES) or not (NO). If the value is NO, then the algorithm is also allowed for backup. This column is useful in determining whether an encryption algorithm is deprecated for backup purpose.

V\$RMAN_OUTPUT

V\$RMAN_OUTPUT displays messages reported by RMAN. This is an in-memory view and is not recorded in the controlfile. The view can hold 32768 rows.

Column	Datatype	Description
SID	NUMBER	Session ID of the session which is running this RMAN operation
RECID	NUMBER	Record ID of the corresponding V\$RMAN_STATUS row
STAMP	NUMBER	Timestamp of the corresponding V\$RMAN_STATUS row
SESSION_RECID	NUMBER	Record ID of the session (corresponding V\$RMAN_STATUS row with ROW_LEVEL = 0)
SESSION_STAMP	NUMBER	Timestamp of the session (corresponding V\$RMAN_STATUS row with ROW_LEVEL = 0)
OUTPUT	VARCHAR2 (129)	Output text reported by RMAN
RMAN_STATUS_RECID	NUMBER	Owning V\$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V\$RMAN_STATUS record stamp
SESSION_KEY	NUMBER	Session identifier

V\$RMAN_STATUS

V\$RMAN_STATUS displays the finished and on-going RMAN jobs. For on-going jobs, this view displays progress and status. The jobs which are in progress are stored only in memory while the finished jobs are stored in the controlfile.

Column	Datatype	Description
SID	NUMBER	Session ID of the session which is running this RMAN operation
RECID	NUMBER	Record ID of the row in the controlfile
STAMP	NUMBER	Timestamp of the row (RECID + STAMP is unique)
PARENT_RECID	NUMBER	Record ID of the parent row of this row (corresponding V\$RMAN_STATUS row with ROW_LEVEL = ROW_LEVEL - 1)
PARENT_STAMP	NUMBER	Timestamp of the parent row of this row (corresponding V\$RMAN_STATUS row with ROW_LEVEL = ROW_LEVEL - 1)

V\$ROLLNAME

Column	Datatype	Description
SESSION_RECID	NUMBER	Record ID of the session (corresponding V\$RMAN_STATUS row with ROW_LEVEL = 0)
SESSION_STAMP	NUMBER	Timestamp of the session (corresponding V\$RMAN_STATUS row with ROW_LEVEL = 0)
ROW_LEVEL	NUMBER	Level of the row. The session has level 0.
ROW_TYPE	VARCHAR2 (19)	Type of the row: ■ SESSION ■ COMMAND ■ RECURSIVE OPERATION
COMMAND_ID	VARCHAR2 (33)	Command ID set by the RMAN SET COMMAND ID command. If not set, then RMAN will create a unique number.
OPERATION	VARCHAR2 (33)	Name of the command in the execution explained by this row
STATUS	VARCHAR2 (23)	Status of the operation: ■ RUNNING ■ RUNNING WITH WARNINGS ■ RUNNING WITH ERRORS ■ COMPLETED ■ COMPLETED WITH WARNINGS ■ COMPLETED WITH ERRORS ■ FAILED
MBYTES_PROCESSED	NUMBER	Percentage of the job completed; null if not applicable for the operation
START_TIME	DATE	Start time of the job
END_TIME	DATE	End time of the job
INPUT_BYTES	NUMBER	Number of input bytes read
OUTPUT_BYTES	NUMBER	Number of output bytes written
OPTIMIZED	VARCHAR2 (3)	YES, if backup optimization was applied during the backup job. Otherwise, NO.
OBJECT_TYPE	VARCHAR2 (13)	Identifies types of objects backed up
OUTPUT_DEVICE_TYPE	VARCHAR2 (17)	DISK, SBT_TAPE, or *. An * indicates that output was written to more than one device type.
OSB_ALLOCATED	VARCHAR2 (3)	A value of YES means an Oracle Secure Backup channel was allocated during the specified operation identified by the V\$RMAN_STATUS view.

V\$ROLLNAME

V\$ROLLNAME lists the names of all online rollback segments. It can only be accessed when the database is open.

Column	Datatype	NULL	Description
USN	NUMBER		Rollback (undo) segment number
NAME	VARCHAR2 (30)	NOT NULL	Rollback segment name

V\$ROLLSTAT

V\$ROLLSTAT contains rollback segment statistics.

Column	Datatype	Description
USN	NUMBER	Rollback segment number

Column	Datatype	Description
LATCH	NUMBER	Latch for the rollback segment
EXTENTS	NUMBER	Number of extents in the rollback segment
RSSIZE	NUMBER	Size (in bytes) of the rollback segment. This value differs by the number of bytes in one database block from the value of the BYTES column of the *_SEGMENTS view. See Also: <i>Oracle Database Administrator's Guide</i>
WRITES	NUMBER	Number of bytes written to the rollback segment
XACTS	NUMBER	Number of active transactions
GETS	NUMBER	Number of header gets
WAITS	NUMBER	Number of header waits
OPTSIZE	NUMBER	Optimal size of the rollback segment
HWMSIZE	NUMBER	High watermark of the rollback segment size
SHRINKS	NUMBER	Number of times the size of a rollback segment decreases
WRAPS	NUMBER	Number of times rollback segment is wrapped
EXTENDS	NUMBER	Number of times rollback segment size is extended
AVESHRINK	NUMBER	Average shrink size
AVEACTIVE	NUMBER	Current size of active extents, averaged over time.
STATUS	VARCHAR2 (15)	Rollback segment status: ■ ONLINE ■ PENDING OFFLINE ■ OFFLINE ■ FULL
CUREXT	NUMBER	Current extent
CURBLK	NUMBER	Current block

V\$ROWCACHE

V\$ROWCACHE displays statistics for data dictionary activity. Each row contains statistics for one data dictionary cache.

Column	Datatype	Description
CACHE#	NUMBER	Row cache ID number
TYPE	VARCHAR2 (11)	Parent or subordinate row cache type
SUBORDINATE#	NUMBER	Subordinate set number
PARAMETER	VARCHAR2 (32)	Name of the initialization parameter that determines the number of entries in the data dictionary cache
COUNT	NUMBER	Total number of entries in the cache
USAGE	NUMBER	Number of cache entries that contain valid data
FIXED	NUMBER	Number of fixed entries in the cache
GETS	NUMBER	Total number of requests for information on the data object
GETMISSES	NUMBER	Number of data requests resulting in cache misses
SCANS	NUMBER	Number of scan requests
SCANMISSES	NUMBER	Number of times a scan failed to find the data in the cache
SCANCOMPLETES	NUMBER	For a list of subordinate entries, the number of times the list was scanned completely
MODIFICATIONS	NUMBER	Number of inserts, updates, and deletions

Column	Datatype	Description
FLUSHES	NUMBER	Number of times flushed to disk
DLM_REQUESTS	NUMBER	Number of DLM requests
DLM_CONFLICTS	NUMBER	Number of DLM conflicts
DLM_RELEASES	NUMBER	Number of DLM releases

V\$ROWCACHE_PARENT

V\$ROWCACHE_PARENT displays information for parent objects in the data dictionary. There is one row per lock owner, and one waiter for each object. This row shows the mode held or requested. For objects with no owners or waiters, a single row is displayed.

Column	Datatype	Description
INDX	NUMBER	Index of the row
HASH	NUMBER	Hash value
ADDRESS	RAW (4 8)	Address of the parent object
CACHE#	NUMBER	Parent cache ID
CACHE_NAME	VARCHAR2 (64)	Parent cache name
EXISTENT	VARCHAR2 (1)	Indicates whether the object is an existing object
LOCK_MODE	NUMBER	Mode the lock is held in
LOCK_REQUEST	NUMBER	Mode the lock is requested in
TXN	RAW (4)	Transaction currently locking the object
SADDR	RAW (4 8)	Address of the session
INST_LOCK_REQUEST	NUMBER	Mode in which instance lock is being requested. This column is only relevant for Real Application Clusters.
INST_LOCK_RELEASE	NUMBER	Whether the instance lock needs to be released. This column is only relevant for Real Application Clusters.
INST_LOCK_TYPE	VARCHAR2 (2)	Type of instance lock. This column is only relevant for Real Application Clusters.
INST_LOCK_ID1	RAW (4)	ID associated with the instance lock. This column is only relevant for Real Application Clusters.
INST_LOCK_ID2	RAW (4)	ID associated with the instance lock. This column is only relevant for Real Application Clusters.
KEY	RAW (100)	Contents of the key. This column is only relevant for Real Application Clusters.

V\$ROWCACHE_SUBORDINATE

V\$ROWCACHE_SUBORDINATE displays information for subordinate objects in the data dictionary.

Column	Datatype	Description
INDX	NUMBER	The index
HASH	NUMBER	The hash value
ADDRESS	RAW (4 8)	Address of the subordinate object
CACHE#	NUMBER	The parent cache ID
SUBCACHE#	NUMBER	The subcache ID
SUBCACHE_NAME	VARCHAR2 (64)	The subcache name

Column	Datatype	Description
EXISTENT	VARCHAR2 (1)	Whether the object is an existing object
PARENT	RAW (4 8)	Address of the parent object
KEY	RAW (100)	The contents of the key

V\$RSRC_CONS_GROUP_HISTORY

V\$RSRC_CONS_GROUP_HISTORY displays a history of consumer group statistics for each entry in V\$RSRC_PLAN_HISTORY that has a non-NULL plan.

Column	Datatype	Description
SEQUENCE#	NUMBER	A sequential counter that uniquely describes the V\$RSRC_PLAN_HISTORY entry to which these consumer group statistics apply. When the instance is restarted, this value is reset to zero.
ID	NUMBER	Consumer group object ID (a unique number, consistent across database shutdowns and startups)
NAME	VARCHAR2 (30)	Name of the consumer group
REQUESTS	NUMBER	Cumulative number of requests that were executed in the consumer group
CPU_WAIT_TIME	NUMBER	Cumulative amount of time that sessions waited for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CPU_WAITS	NUMBER	Cumulative number of times all sessions in the consumer group had to wait for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CONSUMED_CPU_TIME	NUMBER	Cumulative amount of CPU time consumed by all sessions in the consumer group (in milliseconds)
YIELDS	NUMBER	Cumulative number of times that sessions in the consumer group had to yield CPU to other sessions because of quantum expiration
CPU_DECISIONS	NUMBER	Percentage of CPU decisions for which the consumer group was present
CPU_DECISIONS_EXCLUSIVE	NUMBER	Percentage of the CPU decisions for which the consumer group was present and was the only consumer group present
CPU_DECISIONS_WON	NUMBER	Percentage of the CPU decisions that the consumer group won
ACTIVE_SESS_LIMIT_HIT	NUMBER	Number of times that sessions in the consumer group were queued because the consumer group reached its active session limit
UNDO_LIMIT_HIT	NUMBER	Number of times that queries in the consumer group were cancelled because the consumer group reached its UNDO_POOL limit
SWITCHES_IN_CPU_TIME	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_OUT_CPU_TIME	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_IN_IO_MEGABYTES	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_OUT_IO_MEGABYTES	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_IN_IO_REQUESTS	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SWITCHES_OUT_IO_REQUESTS	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SQL_CANCELED	NUMBER	Number of times that SQL queries running in the consumer group were aborted because they exceeded the Resource Manager plan's SWITCH_TIME limit and CANCEL_SQL was specified as the Resource Manager plan's SWITCH_GROUP

Column	Datatype	Description
ACTIVE_SESS_KILLED	NUMBER	Number of times that sessions running in the consumer group were terminated because they exceeded the Resource Manager plan's SWITCH_TIME limit and KILL_SESSION was specified as the Resource Manager plan's SWITCH_GROUP
IDLE_SESS_KILLED	NUMBER	Number of times that sessions in the consumer group were killed because they were idle for too long (reached MAX_IDLE_TIME)
IDLE_BLK_R_SESS_KILLED	NUMBER	Number of times that sessions in the consumer group were killed because they were idle too long (reached MAX_IDLE_BLOCKER_TIME) and were blocking other sessions
QUEUED_TIME	NUMBER	Total amount of time that sessions in the consumer group have spent in the QUEUED state because of the active session limit (in milliseconds)
QUEUE_TIME_OUTS	NUMBER	Number of times that requests from sessions in the consumer group timed out because they were queued for too long (reached QUEUEING_P1)
IO_SERVICE_TIME	NUMBER	Cumulative I/O wait time (in milliseconds)
IO_SERVICE_WAITS	NUMBER	Total number of wait requests
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQUESTS	NUMBER	Number of single block read requests
SMALL_WRITE_REQUESTS	NUMBER	Number of single block write requests
LARGE_READ_REQUESTS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQUESTS	NUMBER	Number of multiblock write requests
PQS_COMPLETED ¹	NUMBER	Total number of completed parallel statements in the consumer group
PQ_SERVERS_USED ¹	NUMBER	Total number of parallel servers used by completed parallel statements in the consumer group
PQS_QUEUED ¹	NUMBER	Number of times that sessions in the consumer group were queued when trying to run parallel statements
PQ_ACTIVE_TIME ¹	NUMBER	Cumulative sum of the parallel active times for all completed parallel statements in the consumer group (in milliseconds)
PQ_QUEUED_TIME ¹	NUMBER	Total amount of time that sessions in the consumer group were queued when trying to run parallel statements (in milliseconds)
PQ_QUEUE_TIME_OUTS ¹	NUMBER	Number of times that parallel statements from sessions in the consumer group timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$RSRC_CONSUMER_GROUP

V\$RSRC_CONSUMER_GROUP displays data related to currently active resource consumer groups.

Column	Datatype	Description
ID	NUMBER	Consumer group object ID (a unique number, consistent across database shutdowns and startups)
NAME	VARCHAR2 (32)	Name of the consumer group
ACTIVE_SESSIONS	NUMBER	Number of currently active sessions in the consumer group
EXECUTION_WAITERS	NUMBER	Number of currently active sessions waiting for an execution time slice in which they will be able to use CPU
REQUESTS	NUMBER	Cumulative number of requests that were executed in the consumer group

Column	Datatype	Description
CPU_WAIT_TIME	NUMBER	Cumulative amount of time that sessions waited for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CPU_WAITS	NUMBER	Cumulative number of times all sessions in the consumer group had to wait for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CONSUMED_CPU_TIME	NUMBER	Cumulative amount of CPU time consumed by all sessions in the consumer group (in milliseconds)
YIELDS	NUMBER	Cumulative number of times that sessions in the consumer group had to yield CPU to other sessions because of quantum expiration
CPU_DECISIONS	NUMBER	Percentage of CPU decisions for which the consumer group was present
CPU_DECISIONS_EXCLUSIVE	NUMBER	Percentage of the CPU decisions for which the consumer group was present and was the only consumer group present
CPU_DECISIONS_WON	NUMBER	Percentage of the CPU decisions that the consumer group won
QUEUE_LENGTH	NUMBER	Number of sessions waiting in the queue
CURRENT_UNDO_CONSUMPTION	NUMBER	Current amount (in KB) of undo consumed by the consumer group
ACTIVE_SESSION_LIMIT_HIT	NUMBER	Number of times that sessions in the consumer group were queued because the consumer group reached its active session limit
UNDO_LIMIT_HIT	NUMBER	Number of times that queries in the consumer group were cancelled because the consumer group reached its UNDO_POOL limit
SWITCHES_IN_CPU_TIME	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_OUT_CPU_TIME	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_IN_IO_MEGABYTES	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_OUT_IO_MEGABYTES	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_IN_IO_REQUESTS	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SWITCHES_OUT_IO_REQUESTS	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SQL_CANCELED	NUMBER	Number of times that SQL queries running in the consumer group were aborted because they exceeded the Resource Manager plan's SWITCH_TIME limit and CANCEL_SQL was specified as the Resource Manager plan's SWITCH_GROUP
ACTIVE_SESSIONS_KILLED	NUMBER	Number of times that sessions running in the consumer group were terminated because they exceeded the Resource Manager plan's SWITCH_TIME limit and KILL_SESSION was specified as the Resource Manager plan's SWITCH_GROUP
IDLE_SESSIONS_KILLED	NUMBER	Number of times that sessions in the consumer group were killed because they were idle for too long (reached MAX_IDLE_TIME)
IDLE_BLK_SESSIONS_KILLED	NUMBER	Number of times that sessions in the consumer group were killed because they were idle too long (reached MAX_IDLE_BLOCKER_TIME) and were blocking other sessions
QUEUED_TIME	NUMBER	Total amount of time that sessions in the consumer group have spent in the QUEUED state because of the active session limit (in milliseconds)
QUEUE_TIME_OUTS	NUMBER	Number of times that requests from sessions in the consumer group timed out because they were queued for too long (reached QUEUEING_P1)
IO_SERVICE_TIME	NUMBER	Cumulative I/O wait time (in milliseconds)
IO_SERVICE_WAITS	NUMBER	Total number of wait requests
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written

Column	Datatype	Description
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQUESTS	NUMBER	Number of single block read requests
SMALL_WRITE_REQUESTS	NUMBER	Number of single block write requests
LARGE_READ_REQUESTS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQUESTS	NUMBER	Number of multiblock write requests
CURRENT_PQS_ACTIVE ¹	NUMBER	Number of active parallel statements in the consumer group. This value does not include parallel statements that are never queued, such as GV\$ queries.
CURRENT_PQ_SERVERS_ACTIVE ¹	NUMBER	Number of active parallel servers in the consumer group. This value does not include servers running parallel statements that are never queued, such as GV\$ queries.
PQS_QUEUED ¹	NUMBER	Number of times that sessions in the consumer group were queued when trying to run parallel statements
PQS_COMPLETED ¹	NUMBER	Total number of completed parallel statements in the consumer group
PQ_SERVERS_USED ¹	NUMBER	Total number of parallel servers used by completed parallel statements in the consumer group
PQ_ACTIVE_TIME ¹	NUMBER	Cumulative sum of the parallel active times for all completed parallel statements in the consumer group (in milliseconds)
CURRENT_PQS_QUEUED ¹	NUMBER	Number of sessions in the consumer group that are waiting in the parallel statement queue trying to run parallel statements
PQ_QUEUED_TIME ¹	NUMBER	Total amount of time that sessions in the consumer group were queued when trying to run parallel statements (in milliseconds)
PQ_QUEUE_TIME_OUTS ¹	NUMBER	Number of times that parallel statements from sessions in the consumer group timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also:

- *Oracle Database Administrator's Guide* for information on resource groups
- *Oracle Database PL/SQL Packages and Types Reference* for information on creating resource groups with the DBMS_RESOURCE_MANAGER package

V\$RSRC_CONSUMER_GROUP_CPU_MTH

V\$RSRC_CONSUMER_GROUP_CPU_MTH displays all resource allocation methods defined for resource consumer groups.

Column	Datatype	Description
NAME	VARCHAR2 (40)	Name of the CPU resource allocation method

See Also:

- *Oracle Database Administrator's Guide* for information on resource allocation methods
- *Oracle Database PL/SQL Packages and Types Reference* on defining resource allocation methods for consumer groups with the DBMS_RESOURCE_MANAGER package
- "[V\\$RSRC_PLAN_CPU_MTH](#)" on page 8-100 for a listing of all resource allocation methods defined for resource plans

V\$RSRC_PLAN

V\$RSRC_PLAN displays the names of all currently active resource plans.

Column	Datatype	Description
ID	NUMBER	Resource plan ID (a unique number, consistent across database shutdowns and startups). This is also the data dictionary object ID.
NAME	VARCHAR2 (32)	Name of the resource plan
IS_TOP_PLAN	VARCHAR2 (5)	Indicates whether the resource plan is the current top plan (TRUE) or whether the resource plan is a subplan of the current top plan (FALSE)
CPU_MANAGED	VARCHAR2 (3)	Indicates whether the resource plan has parameters that specify a policy for how the Resource Manager should schedule sessions to manage CPU usage (ON) or whether Resource Manager is not managing CPU usage (OFF)
INSTANCE_CAGING ¹	VARCHAR2 (3)	Indicates whether instance caging is enabled (ON) or disabled (OFF). Instance caging is enabled if the CPU_COUNT initialization parameter is set to a value other than 0 and Resource Manager is enabled.
PARALLEL_SERVERS_ACTIVE ¹	NUMBER	Total number of active parallel servers on the instance
PARALLEL_SERVERS_TOTAL ¹	NUMBER	The value of PARALLEL_SERVERS_TARGET for the instance. Parallel statements are queued if the total number of active parallel servers exceeds this value.
PARALLEL_EXECUTION_MANAGED ¹	VARCHAR2 (32)	State of parallel statement queuing: ■ OFF - Parallel statement queuing is disabled ■ STARTUP - Parallel statement queuing is enabled. This is a temporary state that can occur when an Oracle RAC database is undergoing configuration changes ■ FIFO - Parallel statement queuing is enabled. All parallel statements are managed in a single Oracle RAC FIFO queue ■ FULL - Parallel statement queuing is enabled. All parallel statements are managed in per-consumer group queues according to the current resource plan. This state is used when a resource plan that contains resource allocation directives (MGMT_P*) is enabled.

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

See Also:

- "[DBA_RSRC_PLANS](#)" on page 5-88 for a listing of all plans in the database
- *Oracle Database Administrator's Guide* for information on resource plans
- *Oracle Database PL/SQL Packages and Types Reference* for information on defining resource allocation methods for consumer groups with the DBMS_RESOURCE_MANAGER package

V\$RSRC_PLAN_CPU_MTH

V\$RSRC_PLAN_CPU_MTH displays all available CPU resource allocation methods defined for resource plans.

Column	Datatype	Description
NAME	VARCHAR2 (40)	Name of the resource allocation method

See Also:

- ["V\\$RSRC_CONSUMER_GROUP_CPU_MTH"](#) on page 8-98 for a listing of resource allocation methods defined for consumer groups
- *Oracle Database Administrator's Guide* for information on resource plans
- *Oracle Database PL/SQL Packages and Types Reference* for information on defining resource allocation methods for consumer plans with the DBMS_RESOURCE_MANAGER package

V\$RSRC_PLAN_HISTORY

V\$RSRC_PLAN_HISTORY displays a history of when a resource plan was enabled, disabled, or modified on the instance. Up to 15 of the most recent entries are shown. Once the database is opened, this view shows at least one row. The row with the most recent START_TIME and with END_TIME equal to NULL gives information about the current resource plan.

Column	Datatype	Description
SEQUENCE#	NUMBER	A sequential counter that uniquely describes a row. When the instance is restarted, this value is reset to zero.
ID	NUMBER	Resource plan ID; NULL if the Resource Manager was disabled
NAME	VARCHAR2 (30)	Resource plan name; NULL if the Resource Manager was disabled
START_TIME	DATE	Time that the resource plan was enabled
END_TIME	DATE	Time that the resource plan was disabled; NULL if the row contains the current resource plan information
ENABLED_BY_SCHEDULER	VARCHAR2 (5)	Indicates whether the plan was enabled by a Job Scheduler window (TRUE) or not (FALSE)
WINDOW_NAME	VARCHAR2 (30)	Job Scheduler window that triggered the resource plan event; NULL if a user triggered the resource plan event
ALLOWED_AUTOMATED_SWITCHES	VARCHAR2 (5)	Indicates whether automated plan switches were allowed after this resource plan event (TRUE) or whether automated plan switches were disabled after this resource plan event (FALSE) See Also: the SWITCH_PLAN procedure
CPU_MANAGED	VARCHAR2 (3)	Indicates whether the resource plan has parameters that specify a policy for how the Resource Manager should schedule sessions to manage CPU usage (ON) or whether Resource Manager is not managing CPU usage (OFF)
INSTANCE_CAGING ¹	VARCHAR2 (3)	Indicates whether instance caging is enabled (ON) or disabled (OFF). Instance caging is enabled if the CPU_COUNT initialization parameter is set to a value other than 0 and Resource Manager is enabled.

Column	Datatype	Description
PARALLEL_EXECUTION_ MANAGED ¹	VARCHAR2 (32)	State of parallel statement queuing: ■ OFF - Parallel statement queuing is disabled ■ STARTUP - Parallel statement queuing is enabled. This is a temporary state that can occur when an Oracle RAC database is undergoing configuration changes ■ FIFO - Parallel statement queuing is enabled. All parallel statements are managed in a single Oracle RAC FIFO queue ■ FULL - Parallel statement queuing is enabled. All parallel statements are managed in per-consumer group queues according to the current resource plan. This state is used when a resource plan that contains resource allocation directives (MGMT_P*) is enabled.

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$RSRC_SESSION_INFO

V\$RSRC_SESSION_INFO displays Resource Manager statistics per session.

Column	Datatype	Description
SID	NUMBER	Session identifier
CURRENT_CONSUMER_ GROUP_ID	NUMBER	Object ID of the consumer group in which the session currently belongs; NULL if the session has not yet logged in
ORIG_CONSUMER_GROUP_ ID	NUMBER	Object ID of the consumer group in which the session was placed by the consumer group mappings; NULL if the session has not yet logged in This group may not be the current group because the SWITCH_GROUP directive in the current plan may have changed the session's current group. This group may not equal the MAPPED_CONSUMER_GROUP because the MAPPED_CONSUMER_GROUP may not be part of the current plan.
MAPPING_ATTRIBUTE	VARCHAR2 (32)	Session attribute that was used to map the session into its original consumer group; NULL if no mapping was used See Also: "DBA_RSRC_GROUP_MAPPINGS" on page 5-85 for more details
MAPPED_CONSUMER_GROUP	VARCHAR2 (32)	Consumer group to which the session was originally mapped; NULL if no mapping was used This may not correspond to the original consumer group, because the mapped group may not be part of the current plan. See Also: "DBA_RSRC_GROUP_MAPPINGS" on page 5-85 for more details
STATE	VARCHAR2 (32)	Current state of the session: ■ NOT MANAGED - Session has not logged in or the current Resource Manager plan does not require the session to be managed at this point in time ■ RUNNING - Session is currently running on the CPU ■ WAITING FOR CPU - Session is ready to run. It is waiting for a CPU quantum to run. ■ QUEUED - Session is queued because the active session limit was reached ■ IDLE - Session is idle ■ IDLE BLKR - Session is idle and blocking another session ■ WAITING - Session is currently in a wait See Also: "V\$SESSION_WAIT" on page 9-19 for the wait type ■ WAITING_FOR_IO - Session is waiting to submit an I/O request ■ UNBOUND - Session is not bound to any process ■ EXITING - Session is about to terminate

Column	Datatype	Description
ACTIVE	VARCHAR2 (5)	Indicates whether the session is currently active (TRUE) or not (FALSE). This includes when one of the following conditions is true: - Session is in the top call - Session has a transaction in progress - Session is using temporary space objects - Session holds user enqueues
CURRENT_IDLE_TIME	NUMBER	Number of seconds the session has been idle (in states IDLE or IDLE BLKR) while in this consumer group; NULL if the current Resource Manager plan does not require updating this statistic. This value is reset to zero when the session becomes active.
CURRENT_CPU_WAIT_TIME	NUMBER	Amount of time (in milliseconds) the session has waited for CPU because of resource management (in state WAIT FOR CPU) while in the current consumer group; NULL if the current Resource Manager plan does not require updating this statistic. This does not include waits due to latch or enqueue contention, I/O waits, and so on. If SWITCH_TIME_IN_CALL is used, then this will be reset at the end of every call.
CPU_WAIT_TIME	NUMBER	Cumulative amount of time (in milliseconds) the session has waited for CPU (in its lifetime) because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CURRENT_CPU_WAITS	NUMBER	Number of times the session had to wait for CPU because of resource management while in this consumer group; NULL if the current Resource Manager plan does not require updating this statistic. This does not include waits due to latch or enqueue contention, I/O waits, and so on. If SWITCH_TIME_IN_CALL is used, then this will be reset at the end of every call.
CPU_WAITS	NUMBER	Cumulative number of times the session had to wait for CPU (in its lifetime) because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CURRENT_CONSUMED_CPU_TIME	NUMBER	Amount of CPU time (in milliseconds) consumed by the session while in the current consumer group; NULL if the current Resource Manager plan does not require updating this statistic. If SWITCH_TIME_IN_CALL is used, then this will be reset at the end of every call.
CONSUMED_CPU_TIME	NUMBER	Cumulative amount of CPU time consumed by the session (in its lifetime) (in milliseconds)
CURRENT_ACTIVE_TIME	NUMBER	Amount of time (in milliseconds) the session has been active while in the current consumer group; NULL if the current Resource Manager plan does not require updating this statistic. Active time is time spent running and waiting while executing a call. It does not include the time a session waited for CPU resources. If SWITCH_TIME_IN_CALL is used, then this is reset at the end of every call.
ACTIVE_TIME	NUMBER	Cumulative amount of active time (in milliseconds) consumed by the session (in its lifetime)
CURRENT_QUEUED_TIME	NUMBER	Amount of time (in milliseconds) the current request from the session has been queued (in state QUEUED). If the session does not have a request currently queued up, then this number will be zero.
QUEUED_TIME	NUMBER	Total amount of time (in milliseconds) the session has spent in the QUEUED state (in its lifetime)
CURRENT_YIELDS	NUMBER	Number of times the session had to yield the CPU to other sessions (due to quantum expiration) while in the current consumer group; NULL if the current Resource Manager plan does not require updating this statistic. If SWITCH_TIME_IN_CALL is used, then this is reset at the end of every call.
YIELDS	NUMBER	Cumulative number of times the session had to yield CPU to other sessions due to quantum expiration (in its lifetime)
CURRENT_UNDO_CONSUMPTION	NUMBER	Current amount (in KB) of undo consumed by the session; NULL if the current Resource Manager plan does not have an UNDO_POOL directive
MAX_UNDO_CONSUMPTION	NUMBER	Maximum amount of undo consumed (in KB) during the session's lifetime. This value may not be updated because the current Resource Manager plan may not have an UNDO_POOL directive.

Column	Datatype	Description
SQL_CANCELED	NUMBER	Number of times SQL queries running in the session were canceled due to exceeding the Resource Manager plan's SWITCH_TIME limit.
QUEUE_TIME_OUTS	NUMBER	Number of times requests from the session timed out because they queued longer than the Resource Manager plan's limit
ESTIMATED_EXECUTION_LIMIT_HIT	NUMBER	Number of times requests from the session were not run because the optimizer's estimated time to execute the query exceeded the MAX_EST_EXEC_TIME limit
CURRENT_IO_SERVICE_TIME	NUMBER	Current I/O wait time of the session (in milliseconds)
IO_SERVICE_TIME	NUMBER	Cumulative amount of I/O wait time by the session (in its lifetime) (in milliseconds)
CURRENT_IO_SERVICE_WAITS	NUMBER	Current I/O waits by session
IO_SERVICE_WAITS	NUMBER	Cumulative I/O waits by session (in its lifetime)
CURRENT_SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read by the session
SMALL_READ_MEGABYTES	NUMBER	Total number of single block megabytes read by the session (in its lifetime)
CURRENT_LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read by the session
LARGE_READ_MEGABYTES	NUMBER	Total number of multiblock megabytes read by the session (in its lifetime)
CURRENT_SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written by the session
SMALL_WRITE_MEGABYTES	NUMBER	Total number of single block megabytes written by the session (in its lifetime)
CURRENT_LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written by the session
LARGE_WRITE_MEGABYTES	NUMBER	Total number of multiblock megabytes written by the session (in its lifetime)
CURRENT_SMALL_READ_REQUESTS	NUMBER	Number of single block read requests by the session
SMALL_READ_REQUESTS	NUMBER	Total number of single block read requests by the session (in its lifetime)
CURRENT_SMALL_WRITE_REQUESTS	NUMBER	Number of single block write requests by the session
SMALL_WRITE_REQUESTS	NUMBER	Total number of single block write requests by the session (in its lifetime)
CURRENT_LARGE_READ_REQUESTS	NUMBER	Number of multiblock read requests by the session
LARGE_READ_REQUESTS	NUMBER	Total number of multiblock read requests by the session (in its lifetime)
CURRENT_LARGE_WRITE_REQUESTS	NUMBER	Number of multiblock write requests by the session
LARGE_WRITE_REQUESTS	NUMBER	Total number of multiblock write requests by the session (in its lifetime)
CURRENT_PQ_ACTIVE_TIME ¹	NUMBER	Amount of time that the current active parallel statement has been executing, not including the amount of time that the statement has been queued (in milliseconds). If the parallel statement is queued, then the value is 0.
PQ_ACTIVE_TIME ¹	NUMBER	Cumulative amount of time that parallel statements have been executed over the lifetime of the session (in milliseconds)
DOP ¹		Degree of parallelism for the active or queued parallel statement
ESTIMATED_EXECUTION_TIME ¹	NUMBER	Estimated execution time for the parallel statement, as estimated by the optimizer (in milliseconds). You can compare this value to CURRENT_PQ_ACTIVE_TIME to estimate how much longer the parallel statement will run.

Column	Datatype	Description
CURRENT_PQ_QUEUED_TIME ¹	NUMBER	Amount of time that the current parallel statement in the session has been queued (in milliseconds). If the session does not have a queued parallel statement, then the value is 0.
PQ_QUEUED_TIME ¹	NUMBER	Total amount of time that the session has spent in the PQ_QUEUED state in its lifetime (in milliseconds)
PQ_QUEUED ¹	NUMBER	Number of times that parallel statements in the session have been queued
PQ_QUEUE_TIME_OUTS ¹	NUMBER	Number of times that parallel statements in the session timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit
PQ_ACTIVE ¹	VARCHAR2 (5)	Indicates whether the session is actively running a parallel statement (TRUE) or not (FALSE).

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$RSRCMGRMETRIC

V\$RSRCMGRMETRIC displays information about resources consumed and wait times per consumer group.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time for the metric value
END_TIME	DATE	End time for the metric value
INTSIZE_CSEC	NUMBER	Size of the time period
SEQUENCE#	NUMBER	A sequential counter that uniquely describes the V\$RSRC_PLAN_HISTORY entry to which these consumer group statistics apply. When the instance is restarted, this value is reset to zero.
CONSUMER_GROUP_ID	NUMBER	Consumer group object ID (a unique number, consistent across database shutdowns and startups)
CONSUMER_GROUP_NAME	VARCHAR2 (30)	Name of the consumer group
CPU_CONSUMED_TIME	NUMBER	Cumulative amount of CPU time consumed by all sessions in the consumer group
CPU_WAIT_TIME	NUMBER	Cumulative amount of time that sessions waited for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
NUM_CPUS ¹	NUMBER	Number of CPUs that the Resource Manager is utilizing. If instance caging is enabled, then this column is equal to the value of the CPU_COUNT initialization parameter. If instance caging is not enabled, then this column is equal to the total number of CPUs in the system.
RUNNING_SESSIONS_LIMIT ¹	NUMBER	Maximum number of sessions in the consumer group that can run simultaneously. The value of this column is set by the Resource Manager plan's MAX_UTILIZATION_LIMIT directive.
AVG_RUNNING_SESSIONS ¹	NUMBER	Average number of sessions in the consumer group that are currently running
AVE_WAITING_SESSIONS ¹	NUMBER	Average number of sessions in the consumer group that are waiting for CPU due to resource management
CPU_UTILIZATION_LIMIT ¹	NUMBER	Maximum percentage of CPU that the consumer group can utilize at any time. The value of this column is set by the Resource Manager plan's MAX_UTILIZATION_LIMIT directive. If instance caging is enabled, then this value is derived using the CPU_COUNT initialization parameter.
AVG_CPU_UTILIZATION ¹	NUMBER	Average percentage CPU consumed by the consumer group
CPU_DECISIONS	NUMBER	Percentage of CPU decisions for which the consumer group was present. This column is deprecated.

Column	Datatype	Description
CPU_DECISIONS_EXCLUSIVE	NUMBER	Percentage of the CPU decisions for which the consumer group was present and was the only consumer group present. This column is deprecated.
CPU_DECISIONS_WON	NUMBER	Percentage of the CPU decisions that the consumer group won. This column is deprecated.
IO_REQUESTS	NUMBER	I/O requests
IO_MEGABYTES	NUMBER	I/O megabytes

¹ This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$RSRCMGRMETRIC_HISTORY

V\$RSRCMGRMETRIC_HISTORY displays a history (the last one hour) of resource manager metrics, taken from V\$RSRCMGRMETRIC. When a resource plan is set, this history is cleared and restarted. This view provides information about resources consumed and wait times per consumer group.

The columns for V\$RSRCMGRMETRIC_HISTORY are the same as those for V\$RSRCMGRMETRIC.

See Also: ["V\\$RSRCMGRMETRIC"](#) on page 8-104

V\$RULE

V\$RULE displays rule statistics. This view has a row for every rule loaded into shared memory.

Column	Datatype	Description
RULE_SET_OBJECT_ID	NUMBER	Rule set object ID
EVALUATION_CONTEXT_OBJECT_ID	NUMBER	Evaluation context object ID
RULE_OWNER	VARCHAR2 (30)	Owner of the rule
RULE_NAME	VARCHAR2 (30)	Name of the rule
RULE_CONDITION	VARCHAR2 (200)	Rule condition
TRUE_HITS	NUMBER	Number of times the rule evaluated to TRUE
MAYBE_HITS	NUMBER	Number of times the rule evaluated to MAYBE
SQL_EVALUATIONS	NUMBER	Number of evaluations of the rule that were performed by issuing SQL

V\$RULE_SET

V\$RULE_SET displays rule set statistics. This view has a row for every rule set loaded into shared memory.

Note: Querying the V\$RULE_SET view may have a negative impact on performance if a database has a large library cache.

Column	Datatype	Description
OWNER	VARCHAR2 (30)	Owner of the rule set
NAME	VARCHAR2 (30)	Name of the rule set

Column	Datatype	Description
CPU_TIME	NUMBER	Total CPU time (in hundredths of a second) spent in evaluation of the rule set
ELAPSED_TIME	NUMBER	Total elapsed time (in hundredths of a second) spent in evaluation of the rule set
FIRST_LOAD_TIME	DATE	First time the current cached copy of the rule set was loaded
LAST_LOAD_TIME	DATE	Last time the current cached copy of the rule set was loaded
LAST_LOADING_TIME	NUMBER	Total elapsed time (in hundredths of a second) spent to load the rule set the last time it was loaded
SHARABLE_MEM	NUMBER	Shared memory (in bytes) used by the rule set
RELOADS	NUMBER	Number of times the rule set object was reloaded in shared memory
INVALIDATIONS	NUMBER	Number of times the rule set object was invalidated
EVALUATIONS	NUMBER	Number of evaluations on the rule set
FIRST_HIT_EVALUATIONS	NUMBER	Number of evaluations on the rule set, with stop_on_first_hit set to TRUE
SIMPLE_RULES_ONLY_EVALUATIONS	NUMBER	Number of evaluations on the rule set, with simple_rules_only set to TRUE
SQL_FREE_EVALUATIONS	NUMBER	Number of evaluations on the rule set which did not internally issue SQL to evaluate rules
SQL_EXECUTIONS	NUMBER	Total number of SQL statements executed during evaluation of the rule set
CONDITIONS_PROCESSED	NUMBER	Total number of fast (indexed) conditions processed during evaluation of the rule set
TRUE_RULES	NUMBER	Total number of TRUE rules returned during evaluation of the rule set
MAYBE_RULES	NUMBER	Total number of MAYBE rules returned during evaluation of the rule set
VARIABLE_VALUE_FUNCTION_CALLS	NUMBER	Total number of calls made to user-defined functions to retrieve variable values (specified by the variable_value_function field in RE\$VARIABLE_TYPE) made during evaluation of the rule set
VARIABLE_METHOD_FUNCTION_CALLS	NUMBER	Total number of calls made to user-defined functions to retrieve variable method values (specified by the variable_method_function field in RE\$VARIABLE_TYPE) made during evaluation of the rule set
EVALUATION_FUNCTION_CALLS	NUMBER	Total number of calls made to user-defined evaluation functions (specified as the evaluation_function argument to the DBMS_RULE_ADM.CREATE_EVALUATION_CONTEXT procedure) made during evaluation of the rule set

V\$RULE_SET_AGGREGATE_STATS

V\$RULE_SET_AGGREGATE_STATS displays statistics aggregated over all evaluations on all rule sets. This view has a row for each type of statistic.

Column	Datatype	Description
NAME	VARCHAR2 (80)	Name of the statistic: - rule set evaluations (all) - Total number of evaluations on all rule sets - rule set evaluations (first_hit) - Total number of evaluations on rule sets with stop_on_first_hit set to TRUE - rule set evaluations (simple_rules_only) - Total number of evaluations on rule sets with simple_rules_only set to TRUE - rule set evaluations (SQL free) - Total number of evaluations on rule sets which did not internally issue SQL to evaluate rules - rule set evaluation time (CPU) - Total CPU time (in hundredths of a second) spent in evaluations on rule sets - rule set evaluation time (elapsed) - Total elapsed time (in hundredths of a second) spent in evaluations on rule sets - rule set SQL executions - Total number of SQL statements executed during evaluations on rule sets - rule set conditions processed - Total number of fast (indexed) conditions processed during evaluations on rule sets - rule set true rules - Total number of TRUE rules returned during evaluations on rule sets - rule set maybe rules - Total number of MAYBE rules returned during evaluations on rule sets - rule set user function calls (variable value function) - Total number of calls made to user-defined functions to retrieve variable values (specified by the variable_value_function field in RE\$VARIABLE_TYPE) made during evaluations on rule sets - rule set user function calls (variable method function) - Total number of calls made to user-defined functions to retrieve variable method values (specified by the variable_method_function field in RE\$VARIABLE_TYPE) made during evaluations on rule sets - rule set user function calls (evaluation function) - Total number of calls made to user-defined evaluation functions (specified as the evaluation_function argument to the DBMS_RULE_ADM.CREATE_EVALUATION_CONTEXT procedure) made during evaluations on rule sets
VALUE	NUMBER	Statistic value

Dynamic Performance (V\$) Views: V\$SCHEDULER_RUNNING_JOBS to V\$XSTREAM_TRANSACTION

This chapter contains the dynamic performance views V\$SCHEDULER_RUNNING_JOBS to V\$XSTREAM_TRANSACTION.

V\$SCHEDULER_RUNNING_JOBS

V\$SCHEDULER_RUNNING_JOBS displays information about running Scheduler jobs.

Column	Datatype	Description
SESSION_ID	NUMBER	Identifier of the session running the Scheduler job
SESSION_SERIAL_NUM	NUMBER	Session serial number
JOB_ID	NUMBER	ID of the running Scheduler job
PADDR	RAW (4 8)	Process address
OS_PROCESS_ID	VARCHAR2 (12)	Operating system process ID
SESSION_STAT_CPU	INTERVAL DAY (2) TO SECOND (3)	CPU statistics for the session

V\$SECUREFILE_TIMER

V\$SECUREFILE_TIMER displays information about time taken (in microseconds) by functions of SecureFiles. These timer values are collected per session.

Column	Datatype	Description
NAME	VARCHAR2 (50)	Name of the function
LAYER_ID	NUMBER	ID of the layer that the function belongs to: 0 - Entire Subtree 1 - Delta Updates 2 - Write gather cache 3 - Deduplication 4 - Compression & Encryption 5 - Inode 6 - Space 7 - Utilities 8 - Row-Column Intersection
OWNTIME	NUMBER	Total time taken by the function

V\$SEGMENT_STATISTICS

Column	Datatype	Description
MAXTIME	NUMBER	Maximum time taken by a single call
MINTIME	NUMBER	Minimum time taken by a single call
INVOCATIONS	NUMBER	Number of times the function was invoked
LAYER_NAME	VARCHAR2 (50)	Name of the layer to which the function belongs

V\$SEGMENT_STATISTICS

V\$SEGMENT_STATISTICS displays information about segment-level statistics.

Column	Datatype	Description
OWNER	VARCHAR2 (30)	Owner of the object
OBJECT_NAME	VARCHAR2 (30)	Name of the object
SUBOBJECT_NAME	VARCHAR2 (30)	Name of the subobject
TABLESPACE_NAME	VARCHAR2 (30)	Name of the table space to which the object belongs
TS#	NUMBER	Tablespace number
OBJ#	NUMBER	Dictionary object number of the object
DATAOBJ#	NUMBER	Data object number of the object
OBJECT_TYPE	VARCHAR2 (18)	Type of the object
STATISTIC_NAME	VARCHAR2 (64)	Name of the statistic
STATISTIC#	NUMBER	Statistic number
VALUE	NUMBER	Statistic value

V\$SEGSTAT

V\$SEGSTAT displays information about segment-level statistics.

Column	Datatype	Description
TS#	NUMBER	Tablespace number
OBJ#	NUMBER	Dictionary object number
DATAOBJ#	NUMBER	Data object number
STATISTIC_NAME	VARCHAR2 (64)	Name of the statistic
STATISTIC#	NUMBER	Statistic number
VALUE	NUMBER	Statistic value

V\$SEGSTAT_NAME

V\$SEGSTAT_NAME displays information about segment-level statistics properties.

Column	Datatype	Description
STATISTIC#	NUMBER	Statistic number
NAME	VARCHAR2 (64)	Name of the statistic
SAMPLED	VARCHAR2 (3)	Indicates whether the statistic was collected by sampling (YES) or not (NO)

V\$SERV_MOD_ACT_STATS

V\$SERV_MOD_ACT_STATS displays the same set of performance statistics as V\$SERVICE_STATS except for a specific combination of service/module/action names.

When aggregation is enabled for the service name, module, and action name, then this view provides the timing and work done for calls issued for the business transaction.

Column	Datatype	Description
AGGREGATION_TYPE	VARCHAR2 (21)	Aggregation statistic type: - SERVICE_MODULE - Action value is NULL and the entry is an aggregate for all actions within a given module - SERVICE_MODULE_ACTION - Action value is NULL only for an empty action, and the aggregation is on the level of service/module/action
SERVICE_NAME	VARCHAR2 (64)	Service name from V\$SERVICES
MODULE ¹	VARCHAR2 (49)	Module name from DBA_ENABLED_AGGREGATIONS
ACTION ¹	VARCHAR2 (33)	Action name from DBA_ENABLED_AGGREGATIONS
STAT_ID	NUMBER	Statistic identifier
STAT_NAME	VARCHAR2 (64)	Derived statistic name from V\$STATNAME and V\$SESS_TIME_MODEL
VALUE	NUMBER	Cumulative value (in microseconds)

¹ The datatype of this column is VARCHAR2 (65) starting with Oracle Database 11g Release 2 (11.2.0.2).

V\$SERVICE_EVENT

V\$SERVICE_EVENT displays aggregated wait counts and wait times for each wait statistic.

Column	Datatype	Description
SERVICE_NAME	VARCHAR2 (64)	Service name from V\$SERVICES
SERVICE_NAME_HASH	NUMBER	Service name hash from V\$SERVICES
EVENT	VARCHAR2 (64)	Name of the wait event; derived statistic name from V\$EVENT_NAME
EVENT_ID	NUMBER	Identifier of the event
TOTAL_WAITS	NUMBER	Total amount of time waited for the event by this service (in hundredths of a second)
TOTAL_TIMEOUTS	NUMBER	Total number of timeouts for the event by this service
TIME_WAITED	NUMBER	Time waited for the event (in hundredths of a second)
AVERAGE_WAIT	NUMBER	Average amount of time waited for the event by this service (in hundredths of a second)
MAX_WAIT	NUMBER	Maximum time (in hundredths of a second) waited for the event by this service
TIME_WAITED_MICRO	NUMBER	Total time waited for the event (in microseconds)

V\$SERVICE_STATS

V\$SERVICE_STATS displays a minimal set of performance statistics. These call rate statistics are used for making run-time routing decisions, for tracking service levels, and for per-instance diagnostics per call rate. The elapsed timing for each call provides a relative value across instances for how well a node is processing SQL calls issued under a service name.

When aggregation is enabled for the Service Name, then this view provides the timing and work done for calls issued for the whole service.

Column	Datatype	Description
SERVICE_NAME_HASH	NUMBER	Service name hash from V\$SERVICES
SERVICE_NAME	VARCHAR2 (64)	Service name from V\$SERVICES
STAT_ID	NUMBER	Statistic identifier
STAT_NAME	VARCHAR2 (64)	Derived statistic name from V\$STATNAME and V\$SESS_TIME_MODEL
VALUE	NUMBER	Cumulative value (in microseconds)

V\$SERVICE_WAIT_CLASS

V\$SERVICE_WAIT_CLASS displays aggregated wait counts and wait times for each wait statistic. An aggregation of these wait classes is used when thresholds are imported.

Column	Datatype	Description
SERVICE_NAME	VARCHAR2 (64)	Service name from V\$SERVICES
SERVICE_NAME_HASH	NUMBER	Service name hash from V\$SERVICES
WAIT_CLASS_ID	NUMBER	Identifier of the wait class
WAIT_CLASS#	NUMBER	Number of the wait class
WAIT_CLASS	VARCHAR2 (64)	Name of the wait class
TOTAL_WAITS	NUMBER	Number of times waits of the class occurred for this client
TIME_WAITED	NUMBER	Amount of time (in hundredths of a second) spent in the class by this session

V\$SERVICEMETRIC

V\$SERVICEMETRIC displays metric values measured on the most recent time interval period for services executing inside the database. Service metrics are measured in 5-second and 1-minute intervals.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin timestamp for the interval period
END_TIME	DATE	End timestamp for the interval period
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	Group ID for the service metric group
SERVICE_NAME_HASH	NUMBER	Service name hash
SERVICE_NAME	VARCHAR2 (64)	Service name
CTMHASH	NUMBER	Service create timestamp hash value
ELAPSEDPERCALL	NUMBER	Elapsed time per call (in microseconds). This column is deprecated in favor of the DBTIMEPERCALL column.
CPUPERCALL	NUMBER	CPU time per call (in microseconds)
DBTIMEPERCALL	NUMBER	Elapsed time per call (in microseconds)
CALLSPERSEC	NUMBER	Number of user calls per second
DBTIMEPERSEC	NUMBER	Database time per second

Column	Datatype	Description
GOODNESS	NUMBER	Indicates how attractive a given instance is with respect to processing the workload that is presented to the service. A lower number is better. This number is internally computed based on the GOAL (LONG or SHORT) that is specified for the particular service.
DELTA	NUMBER	Indicates the predicted increase in the goodness for every additional session that is routed to this instance
FLAGS	NUMBER	Flags that can be any of the following values: 0x01 - Service is BLOCKED from accepting new connections 0x02 - Service is VIOLATING the set threshold on some metric 0x04 - Goodness is UNKNOWN

V\$SERVICEMETRIC_HISTORY

V\$SERVICEMETRIC_HISTORY displays a recent history of the metric values measured in predefined time interval periods for services executing inside the database. Service metrics are measured in 5-second and 1-minute intervals.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin timestamp for the interval period
END_TIME	DATE	End timestamp for the interval period
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	Group ID for the service metric group
SERVICE_NAME_HASH	NUMBER	Service name hash
SERVICE_NAME	VARCHAR2 (64)	Service name
CTMHASH	NUMBER	Service create timestamp hash value
ELAPSEDPERCALL	NUMBER	Elapsed time per call (in microseconds). This column is deprecated in favor of the DBTIMEPERCALL column.
CPUPERCALL	NUMBER	CPU time per call (in microseconds)
DBTIMEPERCALL	NUMBER	Elapsed time per call (in microseconds)
CALLSPERSEC	NUMBER	Number of user calls per second
DBTIMEPERSEC	NUMBER	Database time per second

V\$SERVICES

V\$SERVICES displays information about the services in the database.

Column	Datatype	Description
SERVICE_ID	NUMBER	Service ID
NAME	VARCHAR2 (64)	Name of the service
NAME_HASH	NUMBER	Service name hash
NETWORK_NAME	VARCHAR2 (512)	Network name
CREATION_DATE	DATE	Creation date
CREATION_DATE_HASH	NUMBER	Creation date hash
GOAL	VARCHAR2 (12)	Service workload management goal: - NONE - SERVICE_TIME - THROUGHPUT

Column	Datatype	Description
DTP	VARCHAR2 (1)	Indicates whether the service is for DTP or distributed transactions including XA transactions (Y) or not (N)
AQ_HA_NOTIFICATION	VARCHAR2 (3)	Indicates whether AQ notifications are sent for HA events (YES) or not (NO)
CLB_GOAL	VARCHAR2 (5)	Connection load balancing goal used with statistics that are sent to the listeners to determine how new connections are distributed: - LONG - SHORT

V\$SES_OPTIMIZER_ENV

V\$SES_OPTIMIZER_ENV displays the contents of the optimizer environment used by each session. When a new session is first created, it automatically inherits its optimizer environment from the optimizer environment defined at the instance level by V\$SYS_OPTIMIZER_ENV. The value of certain parameters can be dynamically modified by issuing an ALTER SESSION statement.

Column	Datatype	Description
SID	NUMBER	Session identifier. This column can be used to join with V\$SESSION on the SID column.
ID	NUMBER	Unique identifier of the parameter in the optimizer environment
NAME	VARCHAR2 (40)	Name of the parameter
SQL_FEATURE	VARCHAR2 (64)	Associated feature control ID
ISDEFAULT	VARCHAR2 (3)	Indicates whether the parameter is set to the default value (YES) or not (NO)
VALUE	VARCHAR2 (25)	Value of the parameter for the session

See Also: ["V\\$SYS_OPTIMIZER_ENV"](#) on page 9-75

V\$SESS_IO

V\$SESS_IO displays I/O statistics for each user session.

Column	Datatype	Description
SID	NUMBER	Session identifier
BLOCK_GETS	NUMBER	Block gets for this session
CONSISTENT_GETS	NUMBER	Consistent gets for this session
PHYSICAL_READS	NUMBER	Physical reads for this session
BLOCK_CHANGES	NUMBER	Block changes for this session
CONSISTENT_CHANGES	NUMBER	Consistent changes for this session
OPTIMIZED_PHYSICAL_READS	NUMBER	Number of physical reads from Database Smart Flash Cache for this session

V\$SESS_TIME_MODEL

V\$SESS_TIME_MODEL displays the session-accumulated time for various operations. The time reported is the total elapsed or CPU time (in microseconds). Any timed operation will buffer at most 5 seconds of time data. Specifically, this means that if a timed operation (such as SQL execution) takes a long period of time to perform, the

data published to this view is at most missing 5 seconds of the time accumulated for the operation.

The time values are 8-byte integers and can therefore hold approximately 580,000 years of time before wrapping. Background process time is not included in a statistic value unless the statistic is specifically for background processes.

Column	Datatype	Description
SID	NUMBER	Session ID (same as in V\$SESSION)
STAT_ID	NUMBER	Statistic identifier for the time statistic
STAT_NAME	VARCHAR2 (64)	Name of the statistic (see Table 9-1)
VALUE	NUMBER	Amount of time (in microseconds) that the session has spent in this operation

Table 9-1 V\$SESS_TIME_MODEL and V\$SYS_TIME_MODEL Statistics

Statistic Name	Description
DB Time	Amount of elapsed time (in microseconds) spent performing Database user-level calls. This does not include the elapsed time spent on instance background processes such as PMON.
DB CPU	Amount of CPU time (in microseconds) spent on database user-level calls. This does not include the CPU time spent on instance background processes such as PMON.
background elapsed time	Amount of elapsed time (in microseconds) consumed by database background processes.
background CPU time	Amount of CPU time (in microseconds) consumed by database background processes.
sequence load elapsed time	Amount of elapsed time spent getting the next sequence number from the data dictionary. If a sequence is cached, then this is the amount of time spent replenishing the cache when it runs out. No time is charged when a sequence number is found in the cache. For non-cached sequences, some time will be charged for every nextval call.
parse time elapsed	Amount of elapsed time spent parsing SQL statements. It includes both soft and hard parse time.
hard parse elapsed time	Amount of elapsed time spent hard parsing SQL statements.
SQL execute elapsed time	Amount of elapsed time SQL statements are executing. Note that for select statements this also includes the amount of time spent performing fetches of query results.
connection management call elapsed time	Amount of elapsed time spent performing session connect and disconnect calls.
failed parse elapsed time	Amount of time spent performing SQL parses which ultimately fail with some parse error.
failed parse (out of shared memory) elapsed time	Amount of time spent performing SQL parses which ultimately fail with error ORA-04031.
hard parse (sharing criteria) elapsed time	Amount of elapsed time spent performing SQL hard parses when the hard parse resulted from not being able to share an existing cursor in the SQL cache.
hard parse (bind mismatch) elapsed time	Amount of elapsed time spent performing SQL hard parses when the hard parse resulted from bind type or bind size mismatch with an existing cursor in the SQL cache.
PL/SQL execution elapsed time	Amount of elapsed time spent running the PL/SQL interpreter. This does not include time spent recursively executing/parsing SQL statements or time spent recursively executing the Java VM.
PL/SQL compilation elapsed time	Amount of elapsed time spent running the PL/SQL compiler.
inbound PL/SQL rpc elapsed time	Time inbound PL/SQL remote procedure calls have spent executing. It includes all time spent recursively executing SQL and JAVA, and therefore is not easily related to "PL/SQL execution elapsed time".

Table 9–1 (Cont.) V\$SESS_TIME_MODEL and V\$SYS_TIME_MODEL Statistics

Statistic Name	Description
Java execution elapsed time	Amount of elapsed time spent running the Java VM. This does not include time spent recursively executing/parsing SQL statements or time spent recursively executing PL/SQL.
RMAN cpu time (backup/restore)	Amount of CPU time (in microseconds) spent in RMAN backup and restore operations.
repeated bind elapsed time	Amount of elapsed time spent giving new values to bind variables (rebinding).

The relationships between the statistics listed in [Table 9–1](#) form two trees in which all the time reported by a child in the tree is contained within the parent in the tree. The following are the relationship trees; the number is the level in the given tree.

- ```

1) background elapsed time
 2) background cpu time
 3) RMAN cpu time (backup/restore)
1) DB time
 2) DB CPU
 2) connection management call elapsed time
 2) sequence load elapsed time
 2) sql execute elapsed time
 2) parse time elapsed
 3) hard parse elapsed time
 4) hard parse (sharing criteria) elapsed time
 5) hard parse (bind mismatch) elapsed time
 3) failed parse elapsed time
 4) failed parse (out of shared memory) elapsed time
 2) PL/SQL execution elapsed time
 2) inbound PL/SQL rpc elapsed time
 2) PL/SQL compilation elapsed time
 2) Java execution elapsed time
 2) repeated bind elapsed time

```

The relationship between a parent and a child in the tree indicates containment only. Keep the following in mind with regard to the tree:

- Children do not necessarily add up to the parent.
- Children are not necessarily exclusive (that is, it is possible that they overlap).
- The union of children does not necessarily cover the whole of the parent.

## V\$SESSION

V\$SESSION displays session information for each current session.

| Column  | Datatype    | Description                                                                                                                                                                                                                      |
|---------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SADDR   | RAW (4   8) | Session address                                                                                                                                                                                                                  |
| SID     | NUMBER      | Session identifier                                                                                                                                                                                                               |
| SERIAL# | NUMBER      | Session serial number. Used to uniquely identify a session's objects. Guarantees that session-level commands are applied to the correct session objects if the session ends and another session begins with the same session ID. |
| AUDSID  | NUMBER      | Auditing session ID                                                                                                                                                                                                              |
| PADDR   | RAW (4   8) | Address of the process that owns the session                                                                                                                                                                                     |
| USER#   | NUMBER      | Oracle user identifier                                                                                                                                                                                                           |

| Column            | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| USERNAME          | VARCHAR2 (30) | Oracle username                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| COMMAND           | NUMBER        | Command in progress (last statement parsed); for a list of values, see <a href="#">Table 9–2</a> . These values also appear in the AUDIT_ACTIONS table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| OWNERID           | NUMBER        | Identifier of the user who owns the migratable session; the column contents are invalid if the value is 2147483644<br><br>For operations using Parallel Slaves, interpret this value as a 4-byte value. The low-order 2 bytes represent the session number and the high-order bytes represent the instance ID of the query coordinator.                                                                                                                                                                                                                                                                                                             |
| TADDR             | VARCHAR2 (8)  | Address of the transaction state object                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| LOCKWAIT          | VARCHAR2 (8)  | Address of the lock the session is waiting for; NULL if none                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| STATUS            | VARCHAR2 (8)  | Status of the session: <ul style="list-style-type: none"> <li>■ ACTIVE - Session currently executing SQL</li> <li>■ INACTIVE - Session which is inactive and either has no configured limits or has not yet exceeded the configured limits</li> <li>■ KILLED - Session marked to be killed</li> <li>■ CACHED - Session temporarily cached for use by Oracle*XA</li> <li>■ SNIPED - An inactive session that has exceeded some configured limits (for example, resource limits specified for the resource manager consumer group or idle_time specified in the user's profile). Such sessions will not be allowed to become active again.</li> </ul> |
| SERVER            | VARCHAR2 (9)  | Server type: <ul style="list-style-type: none"> <li>■ DEDICATED</li> <li>■ SHARED</li> <li>■ PSEUDO</li> <li>■ POOLED</li> <li>■ NONE</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| SCHEMA#           | NUMBER        | Schema user identifier                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| SCHEMANAME        | VARCHAR2 (30) | Schema user name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| OSUSER            | VARCHAR2 (30) | Operating system client user name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| PROCESS           | VARCHAR2 (24) | Operating system client process ID                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| MACHINE           | VARCHAR2 (64) | Operating system machine name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| PORT              | NUMBER        | Client port number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| TERMINAL          | VARCHAR2 (30) | Operating system terminal name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| PROGRAM           | VARCHAR2 (48) | Operating system program name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| TYPE              | VARCHAR2 (10) | Session type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| SQL_ADDRESS       | RAW (4   8)   | Used with SQL_HASH_VALUE to identify the SQL statement that is currently being executed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| SQL_HASH_VALUE    | NUMBER        | Used with SQL_ADDRESS to identify the SQL statement that is currently being executed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| SQL_ID            | VARCHAR2 (13) | SQL identifier of the SQL statement that is currently being executed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| SQL_CHILD_NUMBER  | NUMBER        | Child number of the SQL statement that is currently being executed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| SQL_EXEC_START    | DATE          | Time when the execution of the SQL currently executed by this session started; NULL if SQL_ID is NULL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| SQL_EXEC_ID       | NUMBER        | SQL execution identifier; NULL if SQL_ID is NULL or if the execution of that SQL has not yet started (see V\$SQL_MONITOR)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| PREV_SQL_ADDR     | RAW (4   8)   | Used with PREV_HASH_VALUE to identify the last SQL statement executed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| PREV_HASH_VALUE   | NUMBER        | Used with SQL_HASH_VALUE to identify the last SQL statement executed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| PREV_SQL_ID       | VARCHAR2 (13) | SQL identifier of the last SQL statement executed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| PREV_CHILD_NUMBER | NUMBER        | Child number of the last SQL statement executed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

| Column                    | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PREV_EXEC_START           | DATE          | SQL execution start of the last executed SQL statement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| PREV_EXEC_ID              | NUMBER        | SQL execution identifier of the last executed SQL statement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| PLSQL_ENTRY_OBJECT_ID     | NUMBER        | Object ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| PLSQL_ENTRY_SUBPROGRAM_ID | NUMBER        | Subprogram ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| PLSQL_OBJECT_ID           | NUMBER        | Object ID of the currently executing PL/SQL subprogram; NULL if executing SQL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| PLSQL_SUBPROGRAM_ID       | NUMBER        | Subprogram ID of the currently executing PL/SQL object; NULL if executing SQL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| MODULE <sup>1</sup>       | VARCHAR2 (48) | Name of the currently executing module as set by calling the DBMS_APPLICATION_INFO.SET_MODULE procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| MODULE_HASH               | NUMBER        | Hash value of the MODULE column                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| ACTION <sup>1</sup>       | VARCHAR2 (32) | Name of the currently executing action as set by calling the DBMS_APPLICATION_INFO.SET_ACTION procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| ACTION_HASH               | NUMBER        | Hash value of the ACTION column                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CLIENT_INFO               | VARCHAR2 (64) | Information set by the DBMS_APPLICATION_INFO.SET_CLIENT_INFO procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| FIXED_TABLE_SEQUENCE      | NUMBER        | This contains a number that increases every time the session completes a call to the database and there has been an intervening select from a dynamic performance table. This column can be used by performance monitors to monitor statistics in the database. Each time the performance monitor looks at the database, it only needs to look at sessions that are currently active or have a higher value in this column than the highest value that the performance monitor saw the last time. All the other sessions have been idle since the last time the performance monitor looked at the database. |
| ROW_WAIT_OBJ#             | NUMBER        | Object ID for the table containing the row specified in ROW_WAIT_ROW#                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| ROW_WAIT_FILE#            | NUMBER        | Identifier for the datafile containing the row specified in ROW_WAIT_ROW#. This column is valid only if the session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.                                                                                                                                                                                                                                                                                                                                                                                        |
| ROW_WAIT_BLOCK#           | NUMBER        | Identifier for the block containing the row specified in ROW_WAIT_ROW#. This column is valid only if the session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.                                                                                                                                                                                                                                                                                                                                                                                           |
| ROW_WAIT_ROW#             | NUMBER        | Current row being locked. This column is valid only if the session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| TOP_LEVEL_CALL#           | NUMBER        | Oracle top level call number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| LOGON_TIME                | DATE          | Time of logon                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| LAST_CALL_ET              | NUMBER        | If the session STATUS is currently ACTIVE, then the value represents the elapsed time (in seconds) since the session has become active.<br><br>If the session STATUS is currently INACTIVE, then the value represents the elapsed time (in seconds) since the session has become inactive.                                                                                                                                                                                                                                                                                                                  |
| PDML_ENABLED              | VARCHAR2 (3)  | This column has been replaced by the PDML_STATUS column                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| FAILOVER_TYPE             | VARCHAR2 (13) | Indicates whether and to what extent transparent application failover (TAF) is enabled for the session: <ul style="list-style-type: none"> <li>NONE - Failover is disabled for this session</li> <li>SESSION - Client is able to fail over its session following a disconnect</li> <li>SELECT - Client is able to fail over queries in progress as well</li> </ul> <b>See Also:</b> <ul style="list-style-type: none"> <li>Oracle Database Concepts for more information on TAF</li> <li>Oracle Database Net Services Administrator's Guide for information on configuring TAF</li> </ul>                   |



| Column                        | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FAILOVER_METHOD               | VARCHAR2 (10) | Indicates the transparent application failover method for the session: <ul style="list-style-type: none"> <li>NONE - Failover is disabled for this session</li> <li>BASIC - Client itself reconnects following a disconnect</li> <li>PRECONNECT - Backup instance can support all connections from every instance for which it is backed up</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                 |
| FAILED_OVER                   | VARCHAR2 (3)  | Indicates whether the session is running in failover mode and failover has occurred (YES) or not (NO)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| RESOURCE_CONSUMER_GROUP       | VARCHAR2 (32) | Name of the session's current resource consumer group                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| PDML_STATUS                   | VARCHAR2 (8)  | If ENABLED, the session is in a PARALLEL DML enabled mode. If DISABLED, PARALLEL DML enabled mode is not supported for the session. If FORCED, the session has been altered to force PARALLEL DML.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| PDDL_STATUS                   | VARCHAR2 (8)  | If ENABLED, the session is in a PARALLEL DDL enabled mode. If DISABLED, PARALLEL DDL enabled mode is not supported for the session. If FORCED, the session has been altered to force PARALLEL DDL.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| PQ_STATUS                     | VARCHAR2 (8)  | If ENABLED, the session is in a PARALLEL QUERY enabled mode. If DISABLED, PARALLEL QUERY enabled mode is not supported for the session. If FORCED, the session has been altered to force PARALLEL QUERY.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| CURRENT_QUEUE_DURATION        | NUMBER        | If queued (1), the current amount of time the session has been queued. If not currently queued, the value is 0.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| CLIENT_IDENTIFIER             | VARCHAR2 (64) | Client identifier of the session                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| BLOCKING_SESSION_STATUS       | VARCHAR2 (11) | This column provides details on whether there is a blocking session: <ul style="list-style-type: none"> <li>VALID - there is a blocking session, and it is identified in the BLOCKING_INSTANCE and BLOCKING_SESSION columns</li> <li>NO HOLDER - there is no session blocking this session</li> <li>NOT IN WAIT - this session is not in a wait</li> <li>UNKNOWN - the blocking session is unknown</li> </ul>                                                                                                                                                                                                                                                                                                                          |
| BLOCKING_INSTANCE             | NUMBER        | Instance identifier of the blocking session. This column is valid only if BLOCKING_SESSION_STATUS has the value VALID.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| BLOCKING_SESSION              | NUMBER        | Session identifier of the blocking session. This column is valid only if BLOCKING_SESSION_STATUS has the value VALID.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| FINAL_BLOCKING_SESSION_STATUS | VARCHAR2 (11) | The final blocking session is the final element in the wait chain constructed by following the sessions that are blocked by one another starting with this session. In the case of a cyclical wait chain, one of the sessions in the wait chain will be chosen as the final blocker.<br><br>This column provides details on whether there is a final blocking session: <ul style="list-style-type: none"> <li>VALID - there is a final blocking session and it is identified in the FINAL_BLOCKING_INSTANCE and FINAL_BLOCKING_SESSION columns</li> <li>NO HOLDER - there is no session blocking this session</li> <li>NOT IN WAIT - this session is not in a wait</li> <li>UNKNOWN - the final blocking session is unknown</li> </ul> |
| FINAL_BLOCKING_INSTANCE       | NUMBER        | Instance identifier of the final blocking session. This column is valid only if FINAL_BLOCKING_SESSION_STATUS has the value VALID.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| FINAL_BLOCKING_SESSION        | NUMBER        | Session identifier of the blocking session. This column is valid only if FINAL_BLOCKING_SESSION_STATUS has the value VALID.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| SEQ#                          | NUMBER        | A number that uniquely identifies the current or last wait (incremented for each wait)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| EVENT#                        | NUMBER        | Event number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| EVENT                         | VARCHAR2 (64) | Resource or event for which the session is waiting<br><b>See Also:</b> <a href="#">Appendix C, "Oracle Wait Events"</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| P1TEXT                        | VARCHAR2 (64) | Description of the first wait event parameter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| P1                            | NUMBER        | First wait event parameter (in decimal)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

| Column                     | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| P1RAW                      | RAW (8)       | First wait event parameter (in hexadecimal) <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| P2TEXT                     | VARCHAR2 (64) | Description of the second wait event parameter                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| P2                         | NUMBER        | Second wait event parameter (in decimal)                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| P2RAW                      | RAW (8)       | Second wait event parameter (in hexadecimal) <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| P3TEXT                     | VARCHAR2 (64) | Description of the third wait event parameter                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| P3                         | NUMBER        | Third wait event parameter (in decimal)                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| P3RAW                      | RAW (8)       | Third wait event parameter (in hexadecimal) <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| WAIT_CLASS_ID              | NUMBER        | Identifier of the class of the wait event                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| WAIT_CLASS#                | NUMBER        | Number of the class of the wait event                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| WAIT_CLASS                 | VARCHAR2 (64) | Name of the class of the wait event                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| WAIT_TIME                  | NUMBER        | <p>If the session is currently waiting, then the value is 0. If the session is not in a wait, then the value is as follows:</p> <ul style="list-style-type: none"> <li>■ &gt; 0 - Value is the duration of the last wait in hundredths of a second</li> <li>■ -1 - Duration of the last wait was less than a hundredth of a second</li> <li>■ -2 - Parameter TIMED_STATISTICS was set to false</li> </ul> <p>This column has been deprecated in favor of the columns WAIT_TIME_MICRO and STATE.</p> |
| SECONDS_IN_WAIT            | NUMBER        | <p>If the session is currently waiting, then the value is the amount of time waited for the current wait. If the session is not in a wait, then the value is the amount of time since the start of the last wait.</p> <p>This column has been deprecated in favor of the columns WAIT_TIME_MICRO and TIME_SINCE_LAST_WAIT_MICRO.</p>                                                                                                                                                                |
| STATE                      | VARCHAR2 (19) | <p>Wait state:</p> <ul style="list-style-type: none"> <li>■ WAITING - Session is currently waiting</li> <li>■ WAITED UNKNOWN TIME - Duration of the last wait is unknown; this is the value when the parameter TIMED_STATISTICS is set to false</li> <li>■ WAITED SHORT TIME - Last wait was less than a hundredth of a second</li> <li>■ WAITED KNOWN TIME - Duration of the last wait is specified in the WAIT_TIME column</li> </ul>                                                             |
| WAIT_TIME_MICRO            | NUMBER        | Amount of time waited (in microseconds). If the session is currently waiting, then the value is the time spent in the current wait. If the session is currently not in a wait, then the value is the amount of time waited in the last wait.                                                                                                                                                                                                                                                        |
| TIME_REMAINING_MICRO       | NUMBER        | <p>Value is interpreted as follows:</p> <ul style="list-style-type: none"> <li>■ &gt; 0 - Amount of time remaining for the current wait (in microseconds)</li> <li>■ 0 - Current wait has timed out</li> <li>■ -1 - Session can indefinitely wait in the current wait</li> <li>■ NULL - Session is not currently waiting</li> </ul>                                                                                                                                                                 |
| TIME_SINCE_LAST_WAIT_MICRO | NUMBER        | Time elapsed since the end of the last wait (in microseconds). If the session is currently in a wait, then the value is 0.                                                                                                                                                                                                                                                                                                                                                                          |
| SERVICE_NAME               | VARCHAR2 (64) | Service name of the session                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| SQL_TRACE                  | VARCHAR2 (8)  | Indicates whether SQL tracing is enabled (ENABLED) or disabled (DISABLED)                                                                                                                                                                                                                                                                                                                                                                                                                           |
| SQL_TRACE_WAITS            | VARCHAR2 (5)  | Indicates whether wait tracing is enabled (TRUE) or not (FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| SQL_TRACE_BINDS            | VARCHAR2 (5)  | Indicates whether bind tracing is enabled (TRUE) or not (FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                     |

| Column               | Datatype      | Description                                                                                                                                                                                            |
|----------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SQL_TRACE_PLAN_STATS | VARCHAR2 (10) | Frequency at which row source statistics are dumped in the trace files for each cursor: <ul style="list-style-type: none"> <li>■ never</li> <li>■ first_execution</li> <li>■ all_executions</li> </ul> |
| SESSION_EDITION_ID   | NUMBER        | Shows the value that, in the session, would be reported by sys_context('USERENV', 'SESSION_EDITION_ID')                                                                                                |
| CREATOR_ADDR         | RAW (4   8)   | Address of the creating process or circuit                                                                                                                                                             |
| CREATOR_SERIAL#      | NUMBER        | Serial number of the creating process or circuit                                                                                                                                                       |
| ECID                 | VARCHAR2 (64) | Execution context identifier (sent by Application Server)                                                                                                                                              |

<sup>1</sup> The datatype of this column is VARCHAR2 (64) starting with Oracle Database 11g Release 2 (11.2.0.2).

<sup>2</sup> The P1RAW, P2RAW, and P3RAW columns display the same values as the P1, P2, and P3 columns, except that the numbers are displayed in hexadecimal.

**Table 9–2 COMMAND Column of V\$SESSION and Corresponding Commands**

| Number | Command            | Number | Command              |
|--------|--------------------|--------|----------------------|
| 1      | CREATE TABLE       | 2      | INSERT               |
| 3      | SELECT             | 4      | CREATE CLUSTER       |
| 5      | ALTER CLUSTER      | 6      | UPDATE               |
| 7      | DELETE             | 8      | DROP CLUSTER         |
| 9      | CREATE INDEX       | 10     | DROP INDEX           |
| 11     | ALTER INDEX        | 12     | DROP TABLE           |
| 13     | CREATE SEQUENCE    | 14     | ALTER SEQUENCE       |
| 15     | ALTER TABLE        | 16     | DROP SEQUENCE        |
| 17     | GRANT OBJECT       | 18     | REVOKE OBJECT        |
| 19     | CREATE SYNONYM     | 20     | DROP SYNONYM         |
| 21     | CREATE VIEW        | 22     | DROP VIEW            |
| 23     | VALIDATE INDEX     | 24     | CREATE PROCEDURE     |
| 25     | ALTER PROCEDURE    | 26     | LOCK                 |
| 27     | NO-OP              | 28     | RENAME               |
| 29     | COMMENT            | 30     | AUDIT OBJECT         |
| 31     | NOAUDIT OBJECT     | 32     | CREATE DATABASE LINK |
| 33     | DROP DATABASE LINK | 34     | CREATE DATABASE      |
| 35     | ALTER DATABASE     | 36     | CREATE ROLLBACK SEG  |
| 37     | ALTER ROLLBACK SEG | 38     | DROP ROLLBACK SEG    |
| 39     | CREATE TABLESPACE  | 40     | ALTER TABLESPACE     |
| 41     | DROP TABLESPACE    | 42     | ALTER SESSION        |
| 43     | ALTER USER         | 44     | COMMIT               |
| 45     | ROLLBACK           | 46     | SAVEPOINT            |
| 47     | PL/SQL EXECUTE     | 48     | SET TRANSACTION      |
| 49     | ALTER SYSTEM       | 50     | EXPLAIN              |
| 51     | CREATE USER        | 52     | CREATE ROLE          |
| 53     | DROP USER          | 54     | DROP ROLE            |
| 55     | SET ROLE           | 56     | CREATE SCHEMA        |

**Table 9–2 (Cont.) COMMAND Column of V\$SESSION and Corresponding Commands**

| Number | Command                      | Number | Command                     |
|--------|------------------------------|--------|-----------------------------|
| 57     | CREATE CONTROL FILE          | 59     | CREATE TRIGGER              |
| 60     | ALTER TRIGGER                | 61     | DROP TRIGGER                |
| 62     | ANALYZE TABLE                | 63     | ANALYZE INDEX               |
| 64     | ANALYZE CLUSTER              | 65     | CREATE PROFILE              |
| 66     | DROP PROFILE                 | 67     | ALTER PROFILE               |
| 68     | DROP PROCEDURE               | 70     | ALTER RESOURCE COST         |
| 71     | CREATE MATERIALIZED VIEW LOG | 72     | ALTER MATERIALIZED VIEW LOG |
| 73     | DROP MATERIALIZED VIEW LOG   | 74     | CREATE MATERIALIZED VIEW    |
| 75     | ALTER MATERIALIZED VIEW      | 76     | DROP MATERIALIZED VIEW      |
| 77     | CREATE TYPE                  | 78     | DROP TYPE                   |
| 79     | ALTER ROLE                   | 80     | ALTER TYPE                  |
| 81     | CREATE TYPE BODY             | 82     | ALTER TYPE BODY             |
| 83     | DROP TYPE BODY               | 84     | DROP LIBRARY                |
| 85     | TRUNCATE TABLE               | 86     | TRUNCATE CLUSTER            |
| 91     | CREATE FUNCTION              | 92     | ALTER FUNCTION              |
| 93     | DROP FUNCTION                | 94     | CREATE PACKAGE              |
| 95     | ALTER PACKAGE                | 96     | DROP PACKAGE                |
| 97     | CREATE PACKAGE BODY          | 98     | ALTER PACKAGE BODY          |
| 99     | DROP PACKAGE BODY            | 100    | LOGON                       |
| 101    | LOGOFF                       | 102    | LOGOFF BY CLEANUP           |
| 108    | SYSTEM GRANT                 | 109    | SYSTEM REVOKE               |
| 110    | CREATE PUBLIC SYNONYM        | 111    | DROP PUBLIC SYNONYM         |
| 112    | CREATE PUBLIC DATABASE LINK  | 113    | DROP PUBLIC DATABASE LINK   |
| 114    | GRANT ROLE                   | 115    | REVOKE ROLE                 |
| 116    | EXECUTE PROCEDURE            | 117    | USER COMMENT                |
| 118    | ENABLE TRIGGER               | 119    | DISABLE TRIGGER             |
| 120    | ENABLE ALL TRIGGERS          | 121    | DISABLE ALL TRIGGERS        |
| 122    | NETWORK ERROR                | 123    | EXECUTE TYPE                |
| 157    | CREATE DIRECTORY             | 158    | DROP DIRECTORY              |
| 159    | CREATE LIBRARY               | 160    | CREATE JAVA                 |
| 161    | ALTER JAVA                   | 162    | DROP JAVA                   |
| 163    | CREATE OPERATOR              | 164    | CREATE INDEXTYPE            |
| 165    | DROP INDEXTYPE               | 167    | DROP OPERATOR               |
| 168    | ASSOCIATE STATISTICS         | 169    | DISASSOCIATE STATISTICS     |
| 170    | CALL METHOD                  | 171    | CREATE SUMMARY              |
| 172    | ALTER SUMMARY                | 173    | DROP SUMMARY                |
| 174    | CREATE DIMENSION             | 175    | ALTER DIMENSION             |
| 176    | DROP DIMENSION               | 177    | CREATE CONTEXT              |
| 178    | DROP CONTEXT                 | 179    | ALTER OUTLINE               |
| 180    | CREATE OUTLINE               | 181    | DROP OUTLINE                |
| 182    | UPDATE INDEXES               | 183    | ALTER OPERATOR              |

## V\$SESSION\_BLOCKERS

V\$SESSION\_BLOCKERS displays the blocker sessions for each blocked session. Each row represents a blocked and blocker session pair. If a session is blocked by multiple sessions there will be multiple rows for that blocked session. The maximum number of blocker sessions displayed for a single blocked session is 30. If a session is not blocked by other sessions, then there will be no row in this view for that session.

| Column               | Datatype      | Description                                                       |
|----------------------|---------------|-------------------------------------------------------------------|
| SID                  | NUMBER        | Blocked session's Oracle session identifier                       |
| SESS_SERIAL#         | NUMBER        | Blocked session's Oracle session serial number                    |
| WAIT_ID              | NUMBER        | A number identifying the wait for the blocked session             |
| WAIT_EVENT           | NUMBER        | Resource or event number for which the blocked session is waiting |
| WAIT_EVENT_TEXT      | VARCHAR2 (64) | Resource or event for which the blocked session is waiting        |
| BLOCKER_INSTANCE_ID  | NUMBER        | Blocker session's instance identifier                             |
| BLOCKER_SID          | NUMBER        | Blocker session's Oracle session identifier                       |
| BLOCKER_SESS_SERIAL# | NUMBER        | Blocker session's Oracle session serial number                    |

## V\$SESSION\_CONNECT\_INFO

V\$SESSION\_CONNECT\_INFO displays information about network connections for all currently logged in sessions.

| Column                 | Datatype        | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SID                    | NUMBER          | Session identifier (can be used to join this view with V\$SESSION)                                                                                                                                                                                                                                                                                                                                                                                                                  |
| SERIAL#                | NUMBER          | Session serial number. Used to uniquely identify a session's objects. Guarantees that session-level commands are applied to the correct session objects if the session ends and another session begins with the same session ID. (Can be used to join this view with V\$SESSION.)                                                                                                                                                                                                   |
| AUTHENTICATION_TYPE    | VARCHAR2 (26)   | How the user was authenticated: <ul style="list-style-type: none"> <li>■ DATABASE - Username/password authentication</li> <li>■ OS - Operating system external user authentication</li> <li>■ NETWORK - Network protocol or ANO authentication</li> <li>■ PROXY - OCI proxy connection authentication</li> <li>■ SERVER</li> <li>■ PASSWORD</li> <li>■ EXTERNAL ADAPTERS</li> <li>■ INTERNAL</li> <li>■ GLOBAL</li> <li>■ EXTERNAL</li> <li>■ PASSWORD BASED GLOBAL USER</li> </ul> |
| OSUSER                 | VARCHAR2 (30)   | External username for this database user                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| NETWORK_SERVICE_BANNER | VARCHAR2 (4000) | Product banners for each Oracle Net service used for this connection (one row per banner)                                                                                                                                                                                                                                                                                                                                                                                           |
| CLIENT_CHARSET         | VARCHAR2 (40)   | Client character set as specified in the NLS_LANG environment variable or in the OCIEnvNlsCreate () call; Unknown if the Oracle client is older than release 11.1 or the connection is through the JDBC thin driver                                                                                                                                                                                                                                                                 |
| CLIENT_CONNECTION      | VARCHAR2 (13)   | Client server connection flags: <ul style="list-style-type: none"> <li>■ Heterogeneous</li> <li>■ Homogeneous</li> </ul>                                                                                                                                                                                                                                                                                                                                                            |

| Column             | Datatype      | Description                                                                                                                                                                                                             |
|--------------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CLIENT_OCI_LIBRARY | VARCHAR2 (27) | OCI client library: <ul style="list-style-type: none"> <li>■ Home-based</li> <li>■ Full Instant Client</li> <li>■ XE Instant Client</li> <li>■ Light Weight Instant Client</li> <li>■ OCI</li> <li>■ Unknown</li> </ul> |
| CLIENT_VERSION     | VARCHAR2 (40) | Client library version number                                                                                                                                                                                           |
| CLIENT_DRIVER      | VARCHAR2 (9)  | Client driver name                                                                                                                                                                                                      |
| CLIENT_LOBATTR     | VARCHAR2 (23) | Client LOB flags: <ul style="list-style-type: none"> <li>■ Client Temp Lob Rfc On</li> <li>■ Client Temp Lob Rfc Off</li> </ul>                                                                                         |
| CLIENT_REGID       | NUMBER        | Query cache registration ID sent by the client                                                                                                                                                                          |

## V\$SESSION\_CURSOR\_CACHE

V\$SESSION\_CURSOR\_CACHE displays information on cursor usage for the current session.

---

**Note:** The V\$SESSION\_CURSOR\_CACHE view is not a measure of the effectiveness of the SESSION\_CACHED\_CURSORS initialization parameter.

---

| Column    | Datatype | Description                                                                                                                                                                                                            |
|-----------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MAXIMUM   | NUMBER   | Maximum number of cursors to cache. Once you hit this number, some cursors will need to be closed in order to open more. The value in this column is derived from the initialization parameter SESSION_CACHED_CURSORS. |
| COUNT     | NUMBER   | Current number of cursors (whether they are in use or not)                                                                                                                                                             |
| OPENS     | NUMBER   | Cumulative total of cursor opens minus one. This is because the cursor that is currently open and being used for this query is not counted in the OPENS statistic.                                                     |
| HITS      | NUMBER   | Cumulative total of cursor open hits                                                                                                                                                                                   |
| HIT_RATIO | NUMBER   | Ratio of the number of times an open cursor was found divided by the number of times a cursor was sought                                                                                                               |

## V\$SESSION\_EVENT

V\$SESSION\_EVENT displays information on waits for an event by a session. Note that the TIME\_WAITED and AVERAGE\_WAIT columns will contain a value of zero on those platforms that do not support a fast timing mechanism. If you are running on one of these platforms and you want this column to reflect true wait times, then you must set TIMED\_STATISTICS to true in the parameter file; doing this will have a small negative effect on system performance.

**See Also:** ["TIMED\\_STATISTICS"](#) on page 1-173

| Column | Datatype | Description       |
|--------|----------|-------------------|
| SID    | NUMBER   | ID of the session |

| Column            | Datatype      | Description                                                                                 |
|-------------------|---------------|---------------------------------------------------------------------------------------------|
| EVENT             | VARCHAR2 (64) | Name of the wait event<br><b>See Also:</b> <a href="#">Appendix C, "Oracle Wait Events"</a> |
| TOTAL_WAITS       | NUMBER        | Total number of waits for the event by the session                                          |
| TOTAL_TIMEOUTS    | NUMBER        | Total number of timeouts for the event by the session                                       |
| TIME_WAITED       | NUMBER        | Total amount of time waited for the event by the session (in hundredths of a second)        |
| AVERAGE_WAIT      | NUMBER        | Average amount of time waited for the event by the session (in hundredths of a second)      |
| MAX_WAIT          | NUMBER        | Maximum time waited for the event by the session (in hundredths of a second)                |
| TIME_WAITED_MICRO | NUMBER        | Total amount of time waited for the event by the session (in microseconds)                  |
| EVENT_ID          | NUMBER        | Identifier of the wait event                                                                |
| WAIT_CLASS_ID     | NUMBER        | Identifier of the class of the wait event                                                   |
| WAIT_CLASS#       | NUMBER        | Number of the class of the wait event                                                       |
| WAIT_CLASS        | VARCHAR2 (64) | Name of the class of the wait event                                                         |

## V\$SESSION\_FIX\_CONTROL

V\$SESSION\_FIX\_CONTROL displays information about Fix Control (enabled/disabled) for the current session.

| Column                   | Datatype      | Description                                                                   |
|--------------------------|---------------|-------------------------------------------------------------------------------|
| SESSION_ID               | NUMBER        | Session identifier (can be used to join this view with V\$SESSION)            |
| BUGNO                    | NUMBER        | Bug number (as fix control identifier)                                        |
| VALUE                    | NUMBER        | Current value set for the fix control                                         |
| SQL_FEATURE              | VARCHAR2 (64) | Feature control ID                                                            |
| DESCRIPTION              | VARCHAR2 (64) | Description of the fix control                                                |
| OPTIMIZER_FEATURE_ENABLE | VARCHAR2 (25) | Version on (and after) which the fix is enabled by default                    |
| EVENT                    | NUMBER        | Event formerly used to control the fix                                        |
| IS_DEFAULT               | NUMBER        | Indicates whether the current value is the same as the default (1) or not (0) |

## V\$SESSION\_LONGOPS

V\$SESSION\_LONGOPS displays the status of various operations that run for longer than 6 seconds (in absolute time). These operations currently include many backup and recovery functions, statistics gathering, and query execution, and more operations are added for every Oracle release.

To monitor query execution progress, you must be using the cost-based optimizer and you must:

- Set the TIMED\_STATISTICS or SQL\_TRACE parameters to true
- Gather statistics for your objects with the ANALYZE statement or the DBMS\_STATS package

You can add information to this view about application-specific long-running operations by using the DBMS\_APPLICATION\_INFO.SET\_SESSION\_LONGOPS procedure.

| Column              | Datatype       | Description                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SID                 | NUMBER         | Identifier of the session processing the long-running operation. If multiple sessions are cooperating in the long-running operation, then SID corresponds to the main or master session.                                                                                                                                                                                                                             |
| SERIAL#             | NUMBER         | Serial number of the session processing the long-running operation. If multiple sessions are cooperating in the long-running operation, then SERIAL# corresponds to the main or master session. SERIAL# is used to uniquely identify a session's objects. Guarantees that session-level commands are applied to the correct session objects if the session ends and another session begins with the same session ID. |
| OPNAME              | VARCHAR2 (64)  | Brief description of the operation                                                                                                                                                                                                                                                                                                                                                                                   |
| TARGET              | VARCHAR2 (64)  | Object on which the operation is carried out                                                                                                                                                                                                                                                                                                                                                                         |
| TARGET_DESC         | VARCHAR2 (32)  | Description of the target                                                                                                                                                                                                                                                                                                                                                                                            |
| SOFAR               | NUMBER         | Units of work done so far                                                                                                                                                                                                                                                                                                                                                                                            |
| TOTALWORK           | NUMBER         | Total units of work                                                                                                                                                                                                                                                                                                                                                                                                  |
| UNITS               | VARCHAR2 (32)  | Units of measurement                                                                                                                                                                                                                                                                                                                                                                                                 |
| START_TIME          | DATE           | Starting time of the operation                                                                                                                                                                                                                                                                                                                                                                                       |
| LAST_UPDATE_TIME    | DATE           | Time when statistics were last updated for the operation                                                                                                                                                                                                                                                                                                                                                             |
| TIMESTAMP           | DATE           | Timestamp specific to the operation                                                                                                                                                                                                                                                                                                                                                                                  |
| TIME_REMAINING      | NUMBER         | Estimate (in seconds) of time remaining for the operation to complete                                                                                                                                                                                                                                                                                                                                                |
| ELAPSED_SECONDS     | NUMBER         | Number of elapsed seconds from the start of the operations                                                                                                                                                                                                                                                                                                                                                           |
| CONTEXT             | NUMBER         | Context                                                                                                                                                                                                                                                                                                                                                                                                              |
| MESSAGE             | VARCHAR2 (512) | Statistics summary message                                                                                                                                                                                                                                                                                                                                                                                           |
| USERNAME            | VARCHAR2 (30)  | User ID of the user performing the operation                                                                                                                                                                                                                                                                                                                                                                         |
| SQL_ADDRESS         | RAW (4   8)    | Used with the value of the SQL_HASH_VALUE column to identify the SQL statement associated with the operation                                                                                                                                                                                                                                                                                                         |
| SQL_HASH_VALUE      | NUMBER         | Used with the value of the SQL_ADDRESS column to identify the SQL statement associated with the operation                                                                                                                                                                                                                                                                                                            |
| SQL_ID              | VARCHAR2 (13)  | SQL identifier of the SQL statement associated with the long operation, if any                                                                                                                                                                                                                                                                                                                                       |
| SQL_PLAN_HASH_VALUE | NUMBER         | SQL plan hash value; NULL if SQL_ID is NULL                                                                                                                                                                                                                                                                                                                                                                          |
| SQL_EXEC_START      | DATE           | Time when the execution of the SQL started; NULL if SQL_ID is NULL                                                                                                                                                                                                                                                                                                                                                   |
| SQL_EXEC_ID         | NUMBER         | SQL execution identifier (see V\$SQL_MONITOR)                                                                                                                                                                                                                                                                                                                                                                        |
| SQL_PLAN_LINE_ID    | NUMBER         | SQL plan line ID corresponding to the long operation; NULL if the long operation is not associated with a line of the execution plan                                                                                                                                                                                                                                                                                 |
| SQL_PLAN_OPERATION  | VARCHAR2 (30)  | Plan operation name; NULL if SQL_PLAN_LINE_ID is NULL                                                                                                                                                                                                                                                                                                                                                                |
| SQL_PLAN_OPTIONS    | VARCHAR2 (30)  | Plan operation options; NULL if SQL_PLAN_LINE_ID is NULL                                                                                                                                                                                                                                                                                                                                                             |
| QCSID               | NUMBER         | Session identifier of the parallel coordinator                                                                                                                                                                                                                                                                                                                                                                       |

**See Also:** *Oracle Database PL/SQL Packages and Types Reference* for more information on `DBMS_APPLICATION_INFO.SET_SESSION_LONGOPS`

## V\$SESSION\_OBJECT\_CACHE

V\$SESSION\_OBJECT\_CACHE displays object cache statistics for the current user session on the local server (instance).

| Column | Datatype | Description                                    |
|--------|----------|------------------------------------------------|
| PINS   | NUMBER   | Number of object pins or look-ups in the cache |



| Column           | Datatype | Description                                                                                                                               |
|------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------|
| HITS             | NUMBER   | Number of object pins that found the object already in the cache                                                                          |
| TRUE_HITS        | NUMBER   | Number of object pins that found the object already in the cache and in the desired state (thus, not requiring refresh from the database) |
| HIT_RATIO        | NUMBER   | Ratio of HITS / PINS                                                                                                                      |
| TRUE_HIT_RATIO   | NUMBER   | Ratio of TRUE_HITS/PINS                                                                                                                   |
| OBJECT_REFRESHES | NUMBER   | Number of objects in the cache that were refreshed with a new value from the database                                                     |
| CACHE_REFRESHES  | NUMBER   | Number of times the whole cache (all objects) were refreshed                                                                              |
| OBJECT_FLUSHES   | NUMBER   | Number of objects in the cache that were flushed to the database                                                                          |
| CACHE_FLUSHES    | NUMBER   | Number of times the whole cache (all objects) were flushed to the database                                                                |
| CACHE_SHRINKS    | NUMBER   | Number of times the cache was shrunk to the optimal size                                                                                  |
| CACHED_OBJECTS   | NUMBER   | Number of objects currently cached                                                                                                        |
| PINNED_OBJECTS   | NUMBER   | Number of objects currently pinned                                                                                                        |
| CACHE_SIZE       | NUMBER   | Current size of the cache (in bytes)                                                                                                      |
| OPTIMAL_SIZE     | NUMBER   | Optimal size of the cache (in bytes)                                                                                                      |
| MAXIMUM_SIZE     | NUMBER   | Maximum size of the cache (in bytes)                                                                                                      |

## V\$SESSION\_WAIT

V\$SESSION\_WAIT displays the current or last wait for each session.

| Column        | Datatype      | Description                                                                                                             |
|---------------|---------------|-------------------------------------------------------------------------------------------------------------------------|
| SID           | NUMBER        | Session identifier; maps to V\$SESSION.SID                                                                              |
| SEQ#          | NUMBER        | A number that uniquely identifies the current or last wait (incremented for each wait)                                  |
| WAIT_ID       | NUMBER        | Wait identifier                                                                                                         |
| EVENT         | VARCHAR2 (64) | Resource or event for which the session is waiting<br><b>See Also:</b> <a href="#">Appendix C, "Oracle Wait Events"</a> |
| P1TEXT        | VARCHAR2 (64) | Description of the first wait event parameter                                                                           |
| P1            | NUMBER        | First wait event parameter (in decimal)                                                                                 |
| P1RAW         | RAW (8)       | First wait event parameter (in hexadecimal) <sup>1</sup>                                                                |
| P2TEXT        | VARCHAR2 (64) | Description of the second wait event parameter                                                                          |
| P2            | NUMBER        | Second wait event parameter (in decimal)                                                                                |
| P2RAW         | RAW (8)       | Second wait event parameter (in hexadecimal) <sup>1</sup>                                                               |
| P3TEXT        | VARCHAR2 (64) | Description of the third wait event parameter                                                                           |
| P3            | NUMBER        | Third wait event parameter (in decimal)                                                                                 |
| P3RAW         | RAW (8)       | Third wait event parameter (in hexadecimal) <sup>1</sup>                                                                |
| WAIT_CLASS_ID | NUMBER        | Identifier of the class of the wait event                                                                               |
| WAIT_CLASS#   | NUMBER        | Number of the class of the wait event                                                                                   |
| WAIT_CLASS    | VARCHAR2 (64) | Name of the class of the wait event                                                                                     |

| Column                     | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WAIT_TIME                  | NUMBER        | <p>If the session is currently waiting, then the value is 0. If the session is not in a wait, then the value is as follows:</p> <ul style="list-style-type: none"> <li>■ &gt; 0 - Value is the duration of the last wait in hundredths of a second</li> <li>■ -1 - Duration of the last wait was less than a hundredth of a second</li> <li>■ -2 - Parameter TIMED_STATISTICS was set to false</li> </ul> <p>This column has been deprecated in favor of the columns WAIT_TIME_MICRO and STATE.</p> |
| SECONDS_IN_WAIT            | NUMBER        | <p>If the session is currently waiting, then the value is the amount of time waited for the current wait. If the session is not in a wait, then the value is the amount of time since the start of the last wait.</p> <p>This column has been deprecated in favor of the columns WAIT_TIME_MICRO and TIME_SINCE_LAST_WAIT_MICRO.</p>                                                                                                                                                                |
| STATE                      | VARCHAR2 (19) | <p>Wait state:</p> <ul style="list-style-type: none"> <li>■ WAITING - Session is currently waiting</li> <li>■ WAITED UNKNOWN TIME - Duration of the last wait is unknown; this is the value when the parameter TIMED_STATISTICS is set to false</li> <li>■ WAITED SHORT TIME - Last wait was less than a hundredth of a second</li> <li>■ WAITED KNOWN TIME - Duration of the last wait is specified in the WAIT_TIME column</li> </ul>                                                             |
| WAIT_TIME_MICRO            | NUMBER        | Amount of time waited (in microseconds). If the session is currently waiting, then the value is the time spent in the current wait. If the session is currently not in a wait, then the value is the amount of time waited in the last wait.                                                                                                                                                                                                                                                        |
| TIME_REMAINING_MICRO       | NUMBER        | <p>Value is interpreted as follows:</p> <ul style="list-style-type: none"> <li>■ &gt; 0 - Amount of time remaining for the current wait (in microseconds)</li> <li>■ 0 - Current wait has timed out</li> <li>■ -1 - Session can indefinitely wait in the current wait</li> <li>■ NULL - Session is not currently waiting</li> </ul>                                                                                                                                                                 |
| TIME_SINCE_LAST_WAIT_MICRO | NUMBER        | Time elapsed since the end of the last wait (in microseconds). If the session is currently in a wait, then the value is 0.                                                                                                                                                                                                                                                                                                                                                                          |

<sup>1</sup> The P1RAW, P2RAW, and P3RAW columns display the same values as the P1, P2, and P3 columns, except that the numbers are displayed in hexadecimal.

**See Also:** ["TIMED\\_STATISTICS"](#) on page 1-173 and [Appendix C, "Oracle Wait Events"](#)

## V\$SESSION\_WAIT\_CLASS

V\$SESSION\_WAIT\_CLASS displays the time spent in various wait event operations on a per-session basis.

| Column        | Datatype      | Description                                                 |
|---------------|---------------|-------------------------------------------------------------|
| SID           | NUMBER        | Session identifier                                          |
| SERIAL#       | NUMBER        | Serial number                                               |
| WAIT_CLASS_ID | NUMBER        | Identifier of the wait class                                |
| WAIT_CLASS#   | NUMBER        | Number of the wait class                                    |
| WAIT_CLASS    | VARCHAR2 (64) | Name of the wait class                                      |
| TOTAL_WAITS   | NUMBER        | Number of times waits of the class occurred for the session |
| TIME_WAITED   | NUMBER        | Amount of time spent in the wait class by the session       |

## V\$SESSION\_WAIT\_HISTORY

V\$SESSION\_WAIT\_HISTORY displays the last 10 wait events for each active session.

| Column                     | Datatype      | Description                                                                           |
|----------------------------|---------------|---------------------------------------------------------------------------------------|
| SID                        | NUMBER        | Session identifier                                                                    |
| SEQ#                       | NUMBER        | Sequence of wait events; 1 is the most recent                                         |
| EVENT#                     | NUMBER        | Event number                                                                          |
| EVENT                      | VARCHAR2 (64) | Resource or event for which the session is waiting                                    |
| P1TEXT                     | VARCHAR2 (64) | Description of the first wait event parameter                                         |
| P1                         | NUMBER        | First wait event parameter (in decimal)                                               |
| P2TEXT                     | VARCHAR2 (64) | Description of the second wait event parameter                                        |
| P2                         | NUMBER        | Second wait event parameter (in decimal)                                              |
| P3TEXT                     | VARCHAR2 (64) | Description of the third wait event parameter                                         |
| P3                         | NUMBER        | Third wait event parameter (in decimal)                                               |
| WAIT_TIME                  | NUMBER        | Amount of time waited (in hundredths of a second)                                     |
| WAIT_TIME_MICRO            | NUMBER        | Amount of time waited (in microseconds)                                               |
| TIME_SINCE_LAST_WAIT_MICRO | NUMBER        | Time elapsed (in microseconds) since the end of the previous wait in the wait history |

## V\$SESSMETRIC

V\$SESSMETRIC displays the metric values for all sessions.

| Column             | Datatype | Description                               |
|--------------------|----------|-------------------------------------------|
| BEGIN_TIME         | DATE     | Begin time of the interval                |
| END_TIME           | DATE     | End time of the interval                  |
| INTSIZE_CSEC       | NUMBER   | Interval size (in hundredths of a second) |
| SESSION_ID         | NUMBER   | Session ID                                |
| SESSION_SERIAL_NUM | NUMBER   | Session serial number                     |
| CPU                | NUMBER   | CPU usage                                 |
| PHYSICAL_READS     | NUMBER   | Number of physical reads                  |
| LOGICAL_READS      | NUMBER   | Number of logical reads                   |
| PGA_MEMORY         | NUMBER   | PGA size at the end of the interval       |
| HARD_PARSSES       | NUMBER   | Number of hard parses                     |
| SOFT_PARSSES       | NUMBER   | Number of soft parses                     |
| PHYSICAL_READ_PCT  | NUMBER   | Physical read ratio                       |
| LOGICAL_READ_PCT   | NUMBER   | Logical read ratio                        |

## V\$SESSTAT

V\$SESSTAT displays user session statistics. To find the name of the statistic associated with each statistic number (STATISTIC#), query the V\$STATNAME view.

| Column | Datatype | Description        |
|--------|----------|--------------------|
| SID    | NUMBER   | Session identifier |

| Column     | Datatype | Description                                                                                                                                                                                                               |
|------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STATISTIC# | NUMBER   | Statistic number<br><br><b>Note:</b> Statistics numbers are not guaranteed to remain constant from one release to another. Therefore, you should rely on the statistics name rather than its number in your applications. |
| VALUE      | NUMBER   | Statistic value                                                                                                                                                                                                           |

**See Also:** ["V\\$STATNAME"](#) on page 9-63 and [Appendix E, "Statistics Descriptions"](#)

## V\$SGA

V\$SGA displays summary information about the system global area (SGA).

| Column | Datatype      | Description            |
|--------|---------------|------------------------|
| NAME   | VARCHAR2 (20) | SGA component group    |
| VALUE  | NUMBER        | Memory size (in bytes) |

## V\$SGA\_CURRENT\_RESIZE\_OPS

V\$SGA\_CURRENT\_RESIZE\_OPS displays information about SGA resize operations which are currently in progress. An operation can be a grow or a shrink of a dynamic SGA component. All sizes are expressed in bytes.

| Column           | Datatype      | Description                                                                                                                                                                       |
|------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| COMPONENT        | VARCHAR2 (64) | Component name                                                                                                                                                                    |
| OPER_TYPE        | VARCHAR2 (13) | Operation type: <ul style="list-style-type: none"> <li>■ STATIC</li> <li>■ INITIALIZING</li> <li>■ DISABLED</li> <li>■ GROW</li> <li>■ SHRINK</li> <li>■ SHRINK_CANCEL</li> </ul> |
| OPER_MODE        | VARCHAR2 (9)  | Operation mode: <ul style="list-style-type: none"> <li>■ MANUAL</li> <li>■ DEFERRED</li> <li>■ IMMEDIATE</li> </ul>                                                               |
| PARAMETER        | VARCHAR2 (80) | Name of the parameter for the resize operation                                                                                                                                    |
| INITIAL_SIZE     | NUMBER        | Parameter value at the start of the operation                                                                                                                                     |
| TARGET_SIZE      | NUMBER        | Desired value of the parameter after the resize                                                                                                                                   |
| CURRENT_SIZE     | NUMBER        | Current value of the parameter                                                                                                                                                    |
| START_TIME       | DATE          | Start time of the operation                                                                                                                                                       |
| LAST_UPDATE_TIME | DATE          | Last time progress was made for the operation                                                                                                                                     |

## V\$SGA\_DYNAMIC\_COMPONENTS

V\$SGA\_DYNAMIC\_COMPONENTS displays information about the dynamic SGA components. This view summarizes information based on all completed SGA resize operations since instance startup. All sizes are expressed in bytes.

| Column              | Datatype      | Description                                                                                                                                                                                                   |
|---------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| COMPONENT           | VARCHAR2 (64) | Component name                                                                                                                                                                                                |
| CURRENT_SIZE        | NUMBER        | Current size of the component                                                                                                                                                                                 |
| MIN_SIZE            | NUMBER        | Minimum size of the component since instance startup                                                                                                                                                          |
| MAX_SIZE            | NUMBER        | Maximum size of the component since instance startup                                                                                                                                                          |
| USER_SPECIFIED_SIZE | NUMBER        | Value of the user parameter for the component                                                                                                                                                                 |
| OPER_COUNT          | NUMBER        | Number of operations since instance startup                                                                                                                                                                   |
| LAST_OPER_TYPE      | VARCHAR2 (13) | Last completed operation for the component: <ul style="list-style-type: none"> <li>■ STATIC</li> <li>■ INITIALIZING</li> <li>■ DISABLED</li> <li>■ GROW</li> <li>■ SHRINK</li> <li>■ SHRINK_CANCEL</li> </ul> |
| LAST_OPER_MODE      | VARCHAR2 (9)  | Mode of the last completed operation: <ul style="list-style-type: none"> <li>■ MANUAL</li> <li>■ DEFERRED</li> <li>■ IMMEDIATE</li> </ul>                                                                     |
| LAST_OPER_TIME      | DATE          | Start time of the last completed operation                                                                                                                                                                    |
| GRANULE_SIZE        | NUMBER        | Granularity of the grow or the shrink operation                                                                                                                                                               |

## V\$SGA\_DYNAMIC\_FREE\_MEMORY

V\$SGA\_DYNAMIC\_FREE\_MEMORY displays information about the amount of SGA memory available for future dynamic SGA resize operations.

| Column       | Datatype | Description                           |
|--------------|----------|---------------------------------------|
| CURRENT_SIZE | NUMBER   | Amount of available memory (in bytes) |

## V\$SGA\_RESIZE\_OPS

V\$SGA\_RESIZE\_OPS displays information about the last 800 completed SGA resize operations. This does not include in-progress operations. All sizes are expressed in bytes.

| Column    | Datatype      | Description                                                                                                                                                                       |
|-----------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| COMPONENT | VARCHAR2 (64) | Component name                                                                                                                                                                    |
| OPER_TYPE | VARCHAR2 (13) | Operation type: <ul style="list-style-type: none"> <li>■ STATIC</li> <li>■ INITIALIZING</li> <li>■ DISABLED</li> <li>■ GROW</li> <li>■ SHRINK</li> <li>■ SHRINK_CANCEL</li> </ul> |
| OPER_MODE | VARCHAR2 (9)  | Operation mode: <ul style="list-style-type: none"> <li>■ MANUAL</li> <li>■ DEFERRED</li> <li>■ IMMEDIATE</li> </ul>                                                               |

| Column       | Datatype      | Description                                                                                                                                                                   |
|--------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PARAMETER    | VARCHAR2 (80) | Name of the parameter for the resize operation                                                                                                                                |
| INITIAL_SIZE | NUMBER        | Parameter value at the start of the operation                                                                                                                                 |
| TARGET_SIZE  | NUMBER        | Requested value of the parameter after the resize                                                                                                                             |
| FINAL_SIZE   | NUMBER        | Real value of the parameter after the resize                                                                                                                                  |
| STATUS       | VARCHAR2 (9)  | Completion status of the operation: <ul style="list-style-type: none"> <li>■ INACTIVE</li> <li>■ PENDING</li> <li>■ COMPLETE</li> <li>■ CANCELLED</li> <li>■ ERROR</li> </ul> |
| START_TIME   | DATE          | Start time of the operation                                                                                                                                                   |
| END_TIME     | DATE          | End time of the operation                                                                                                                                                     |

## V\$SGA\_TARGET\_ADVICE

V\$SGA\_TARGET\_ADVICE displays information about the SGA\_TARGET initialization parameter.

| Column              | Datatype | Description                                                            |
|---------------------|----------|------------------------------------------------------------------------|
| SGA_SIZE            | NUMBER   | Size of the SGA                                                        |
| SGA_SIZE_FACTOR     | NUMBER   | Ratio between the SGA_SIZE and the current size of the SGA             |
| ESTD_DB_TIME        | NUMBER   | Estimated DB_TIME for this SGA_SIZE                                    |
| ESTD_DB_TIME_FACTOR | NUMBER   | Ratio between ESTD_DB_TIME and DB_TIME for the current size of the SGA |
| ESTD_PHYSICAL_READS | NUMBER   | Estimated number of physical reads                                     |

## V\$SGAINFO

V\$SGAINFO displays size information about the SGA, including the sizes of different SGA components, the granule size, and free memory.

| Column     | Datatype      | Description                                                     |
|------------|---------------|-----------------------------------------------------------------|
| NAME       | VARCHAR2 (32) | Name of the SGA statistic                                       |
| BYTES      | NUMBER        | Size of the statistic (in bytes)                                |
| RESIZEABLE | VARCHAR2 (3)  | Indicates whether the statistic is resizeable (YES) or not (NO) |

## V\$SGASTAT

V\$SGASTAT displays detailed information on the system global area (SGA).

| Column | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                           |
|--------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| POOL   | VARCHAR2 (12) | Designates the pool in which the memory in NAME resides: <ul style="list-style-type: none"> <li>■ shared pool - Memory is allocated from the shared pool</li> <li>■ large pool - Memory is allocated from the large pool</li> <li>■ java pool - Memory is allocated from the Java pool</li> <li>■ streams pool - Memory is allocated from the Streams pool</li> </ul> |
| NAME   | VARCHAR2 (26) | SGA component name                                                                                                                                                                                                                                                                                                                                                    |

| Column | Datatype | Description            |
|--------|----------|------------------------|
| BYTES  | NUMBER   | Memory size (in bytes) |

## V\$SHARED\_POOL\_ADVICE

V\$SHARED\_POOL\_ADVICE displays information about estimated parse time in the shared pool for different pool sizes. The sizes range from 10% of the current shared pool size or the amount of pinned library cache memory (whichever is higher) to 200% of the current shared pool size, in equal intervals. The value of the interval depends on the current size of the shared pool.

| Column                        | Datatype | Description                                                                                                                                                                                                                                                                                                             |
|-------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SHARED_POOL_SIZE_FOR_ESTIMATE | NUMBER   | Shared pool size for the estimate (in megabytes)                                                                                                                                                                                                                                                                        |
| SHARED_POOL_SIZE_FACTOR       | NUMBER   | Size factor with respect to the current shared pool size                                                                                                                                                                                                                                                                |
| ESTD_LC_SIZE                  | NUMBER   | Estimated memory in use by the library cache (in megabytes)                                                                                                                                                                                                                                                             |
| ESTD_LC_MEMORY_OBJECTS        | NUMBER   | Estimated number of library cache memory objects in the shared pool of the specified size                                                                                                                                                                                                                               |
| ESTD_LC_TIME_SAVED            | NUMBER   | Estimated elapsed parse time saved (in seconds), owing to library cache memory objects being found in a shared pool of the specified size. This is the time that would have been spent in reloading the required objects in the shared pool had they been aged out due to insufficient amount of available free memory. |
| ESTD_LC_TIME_SAVED_FACTOR     | NUMBER   | Estimated parse time saved factor with respect to the current shared pool size                                                                                                                                                                                                                                          |
| ESTD_LC_LOAD_TIME             | NUMBER   | Estimated elapsed time (in seconds) for parsing in a shared pool of the specified size                                                                                                                                                                                                                                  |
| ESTD_LC_LOAD_TIME_FACTOR      | NUMBER   | Estimated load time factor with respect to the current shared pool size                                                                                                                                                                                                                                                 |
| ESTD_LC_MEMORY_OBJECT_HITS    | NUMBER   | Estimated number of times a library cache memory object was found in a shared pool of the specified size                                                                                                                                                                                                                |

## V\$SHARED\_POOL\_RESERVED

V\$SHARED\_POOL\_RESERVED displays statistics that help you tune the reserved pool and space within the shared pool.

| Column         | Datatype | Description                                                                                                                                               |
|----------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| FREE_SPACE     | NUMBER   | Total amount of free space on the reserved list <sup>1</sup>                                                                                              |
| AVG_FREE_SIZE  | NUMBER   | Average size of the free memory on the reserved list <sup>1</sup>                                                                                         |
| FREE_COUNT     | NUMBER   | Number of free pieces of memory on the reserved list <sup>1</sup>                                                                                         |
| MAX_FREE_SIZE  | NUMBER   | Size of the largest free piece of memory on the reserved list <sup>1</sup>                                                                                |
| USED_SPACE     | NUMBER   | Total amount of used memory on the reserved list <sup>1</sup>                                                                                             |
| AVG_USED_SIZE  | NUMBER   | Average size of the used memory on the reserved list <sup>1</sup>                                                                                         |
| USED_COUNT     | NUMBER   | Number of used pieces of memory on the reserved list <sup>1</sup>                                                                                         |
| MAX_USED_SIZE  | NUMBER   | Size of the largest used piece of memory on the reserved list <sup>1</sup>                                                                                |
| REQUESTS       | NUMBER   | Number of times that the reserved list was searched for a free piece of memory <sup>1</sup>                                                               |
| REQUEST_MISSES | NUMBER   | Number of times the reserved list did not have a free piece of memory to satisfy the request, and started flushing objects from the LRU list <sup>1</sup> |

| Column                    | Datatype | Description                                                                                                                                                                             |
|---------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAST_MISS_SIZE            | NUMBER   | Request size of the last request miss, when the reserved list did not have a free piece of memory to satisfy the request and started flushing objects from the LRU list <sup>1</sup>    |
| MAX_MISS_SIZE             | NUMBER   | Request size of the largest request miss, when the reserved list did not have a free piece of memory to satisfy the request and started flushing objects from the LRU list <sup>1</sup> |
| REQUEST_FAILURES          | NUMBER   | Number of times that no memory was found to satisfy a request. If an internal flush (used to free up memory) does not meet a memory need, then the error ORA-04031 occurs. <sup>2</sup> |
| LAST_FAILURE_SIZE         | NUMBER   | Request size of the last failed request. If an internal flush (used to free up memory) does not meet a memory need, then the error ORA-04031 occurs. <sup>2</sup>                       |
| ABORTED_REQUEST_THRESHOLD | NUMBER   | Minimum size of a request which signals an ORA-04031 error without flushing objects <sup>2</sup>                                                                                        |
| ABORTED_REQUESTS          | NUMBER   | Number of requests that signalled an ORA-04031 error without flushing objects <sup>2</sup>                                                                                              |
| LAST_ABORTED_SIZE         | NUMBER   | Last size of the request that returned an ORA-04031 error without flushing objects from the LRU list <sup>2</sup>                                                                       |

<sup>1</sup> These columns are valid only if the initialization parameter SHARED\_POOL\_RESERVED\_SIZE is set to a valid value.

<sup>2</sup> These columns contain values which are valid even if SHARED\_POOL\_RESERVED\_SIZE is not set.

## V\$SHARED\_SERVER

V\$SHARED\_SERVER displays information on the shared server processes.

| Column   | Datatype      | Description                                                                                                                                                                                                                                                      |
|----------|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME     | VARCHAR2 (4)  | Name of the server                                                                                                                                                                                                                                               |
| PADDR    | RAW (4   8)   | Server's process address                                                                                                                                                                                                                                         |
| STATUS   | VARCHAR2 (16) | Server status:<br>EXEC - Executing SQL<br>WAIT (ENQ) - Waiting for a lock<br>WAIT (SEND) - Waiting to send data to user<br>WAIT (COMMON) - Idle; waiting for a user request<br>WAIT (RESET) - Waiting for a circuit to reset after a break<br>QUIT - Terminating |
| MESSAGES | NUMBER        | Number of messages processed                                                                                                                                                                                                                                     |
| BYTES    | NUMBER        | Total number of bytes in all messages                                                                                                                                                                                                                            |
| BREAKS   | NUMBER        | Number of breaks                                                                                                                                                                                                                                                 |
| CIRCUIT  | RAW (4   8)   | Address of the circuit currently being serviced                                                                                                                                                                                                                  |
| IDLE     | NUMBER        | Total idle time (in hundredths of a second)                                                                                                                                                                                                                      |
| BUSY     | NUMBER        | Total busy time (in hundredths of a second)                                                                                                                                                                                                                      |
| IN_NET   | NUMBER        | Total incoming network wait time (in hundredths of a second)                                                                                                                                                                                                     |
| OUT_NET  | NUMBER        | Total outgoing network wait time (in hundredths of a second)                                                                                                                                                                                                     |
| REQUESTS | NUMBER        | Total number of requests taken from the common queue in this server's lifetime                                                                                                                                                                                   |

## V\$SHARED\_SERVER\_MONITOR

V\$SHARED\_SERVER\_MONITOR displays information for tuning the shared server.



| Column              | Datatype | Description                                                                                                                                                                                                                                                                                                                                       |
|---------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MAXIMUM_CONNECTIONS | NUMBER   | Highest number of virtual circuits in use at one time since the instance started. If this value reaches the value set for the <code>CIRCUITS</code> initialization parameter, then consider raising the value of <code>CIRCUITS</code> .<br><b>See Also:</b> " <a href="#">CIRCUITS</a> " on page 1-30                                            |
| MAXIMUM_SESSIONS    | NUMBER   | Highest number of shared server sessions in use at one time since the instance started. If this reaches the value set for the <code>SHARED_SERVER_SESSIONS</code> initialization parameter, then consider raising the value of <code>SHARED_SERVER_SESSIONS</code> .<br><b>See Also:</b> " <a href="#">SHARED_SERVER_SESSIONS</a> " on page 1-162 |
| SERVERS_STARTED     | NUMBER   | Total number of shared servers started since the instance started (but not including those started during startup)                                                                                                                                                                                                                                |
| SERVERS_TERMINATED  | NUMBER   | Total number of shared servers stopped by Oracle since the instance started                                                                                                                                                                                                                                                                       |
| SERVERS_HIGHWATER   | NUMBER   | Highest number of servers running at one time since the instance started. If this value reaches the value set for the <code>MAX_SHARED_SERVERS</code> initialization parameter, then consider raising the value of <code>SHARED_SERVERS</code> .<br><b>See Also:</b> " <a href="#">SHARED_SERVERS</a> " on page 1-162                             |

## V\$SORT\_SEGMENT

`V$SORT_SEGMENT` displays information about every sort segment in a given instance. The view is only updated when the tablespace is of the `TEMPORARY` type.

| Column          | Datatype      | Description                                            |
|-----------------|---------------|--------------------------------------------------------|
| TABLESPACE_NAME | VARCHAR2 (31) | Name of the tablespace                                 |
| SEGMENT_FILE    | NUMBER        | File number of the first extent                        |
| SEGMENT_BLOCK   | NUMBER        | Block number of the first extent                       |
| EXTENT_SIZE     | NUMBER        | Extent size                                            |
| CURRENT_USERS   | NUMBER        | Number of active users of the segment                  |
| TOTAL_EXTENTS   | NUMBER        | Total number of extents in the segment                 |
| TOTAL_BLOCKS    | NUMBER        | Total number of blocks in the segment                  |
| USED_EXTENTS    | NUMBER        | Extents allocated to active sorts                      |
| USED_BLOCKS     | NUMBER        | Blocks allocated to active sorts                       |
| FREE_EXTENTS    | NUMBER        | Extents not allocated to any sort                      |
| FREE_BLOCKS     | NUMBER        | Blocks not allocated to any sort                       |
| ADDED_EXTENTS   | NUMBER        | Number of extent allocations                           |
| EXTENT_HITS     | NUMBER        | Number of times an unused extent was found in the pool |
| FREED_EXTENTS   | NUMBER        | Number of deallocated extents                          |
| FREE_REQUESTS   | NUMBER        | Number of requests to deallocate                       |
| MAX_SIZE        | NUMBER        | Maximum number of extents ever used                    |
| MAX_BLOCKS      | NUMBER        | Maximum number of blocks ever used                     |
| MAX_USED_SIZE   | NUMBER        | Maximum number of extents used by all sorts            |
| MAX_USED_BLOCKS | NUMBER        | Maximum number of blocks used by all sorts             |
| MAX_SORT_SIZE   | NUMBER        | Maximum number of extents used by an individual sort   |
| MAX_SORT_BLOCKS | NUMBER        | Maximum number of blocks used by an individual sort    |
| RELATIVE_FNO    | NUMBER        | Relative file number of the sort segment header        |

## V\$SPPARAMETER

V\$SPPARAMETER displays information about the contents of the server parameter file. If a server parameter file was not used to start the instance, then each row of the view will contain FALSE in the ISSPECIFIED column.

| Column         | Datatype       | Description                                                                                                                                                                             |
|----------------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SID            | VARCHAR2 (80)  | SID for which the parameter is defined                                                                                                                                                  |
| NAME           | VARCHAR2 (80)  | Name of the parameter                                                                                                                                                                   |
| TYPE           | VARCHAR2 (11)  | Parameter type                                                                                                                                                                          |
| VALUE          | VARCHAR2 (255) | Parameter value (null if a server parameter file was not used to start the instance)                                                                                                    |
| DISPLAY_VALUE  | VARCHAR2 (255) | Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K. |
| ISSPECIFIED    | VARCHAR2 (6)   | Indicates whether the parameter was specified in the server parameter file (TRUE) or not (FALSE)                                                                                        |
| ORDINAL        | NUMBER         | Position (ordinal number) of the parameter value (0 if a server parameter file was not used to start the instance). Useful only for parameters whose values are lists of strings.       |
| UPDATE_COMMENT | VARCHAR2 (255) | Comments associated with the most recent update (null if a server parameter file was not used to start the instance)                                                                    |

## V\$SQL

V\$SQL lists statistics on shared SQL areas without the GROUP BY clause and contains one row for each child of the original SQL text entered. Statistics displayed in V\$SQL are normally updated at the end of query execution. However, for long running queries, they are updated every 5 seconds. This makes it easy to see the impact of long running SQL statements while they are still in progress.

| Column                | Datatype        | Description                                                                                                                                                                                    |
|-----------------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SQL_TEXT              | VARCHAR2 (1000) | First thousand characters of the SQL text for the current cursor                                                                                                                               |
| SQL_FULLTEXT          | CLOB            | Full text for the SQL statement exposed as a CLOB column. The full text of a SQL statement can be retrieved using this column instead of joining with the V\$SQLTEXT dynamic performance view. |
| SQL_ID                | VARCHAR2 (13)   | SQL identifier of the parent cursor in the library cache                                                                                                                                       |
| SHARABLE_MEM          | NUMBER          | Amount of shared memory used by the child cursor (in bytes)                                                                                                                                    |
| PERSISTENT_MEM        | NUMBER          | Fixed amount of memory used for the lifetime of the child cursor (in bytes)                                                                                                                    |
| RUNTIME_MEM           | NUMBER          | Fixed amount of memory required during the execution of the child cursor                                                                                                                       |
| SORTS                 | NUMBER          | Number of sorts that were done for the child cursor                                                                                                                                            |
| LOADED_VERSIONS       | NUMBER          | Indicates whether the context heap is loaded (1) or not (0)                                                                                                                                    |
| OPEN_VERSIONS         | NUMBER          | Indicates whether the child cursor is locked (1) or not (0)                                                                                                                                    |
| USERS_OPENING         | NUMBER          | Number of users executing the statement                                                                                                                                                        |
| FETCHES               | NUMBER          | Number of fetches associated with the SQL statement                                                                                                                                            |
| EXECUTIONS            | NUMBER          | Number of executions that took place on this object since it was brought into the library cache                                                                                                |
| PX_SERVERS_EXECUTIONS | NUMBER          | Total number of executions performed by parallel execution servers (0 when the statement has never been executed in parallel)                                                                  |

| Column                   | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| END_OF_FETCH_COUNT       | NUMBER        | Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column. |
| USERS_EXECUTING          | NUMBER        | Number of users executing the statement                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| LOADS                    | NUMBER        | Number of times the object was either loaded or reloaded                                                                                                                                                                                                                                                                                                                                                                                                                            |
| FIRST_LOAD_TIME          | VARCHAR2 (19) | Timestamp of the parent creation time                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| INVALIDATIONS            | NUMBER        | Number of times this child cursor has been invalidated                                                                                                                                                                                                                                                                                                                                                                                                                              |
| PARSE_CALLS              | NUMBER        | Number of parse calls for this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| DISK_READS               | NUMBER        | Number of disk reads for this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| DIRECT_WRITES            | NUMBER        | Number of direct writes for this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| BUFFER_GETS              | NUMBER        | Number of buffer gets for this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| APPLICATION_WAIT_TIME    | NUMBER        | Application wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CONCURRENCY_WAIT_TIME    | NUMBER        | Concurrency wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CLUSTER_WAIT_TIME        | NUMBER        | Cluster wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| USER_IO_WAIT_TIME        | NUMBER        | User I/O Wait Time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| PLSQL_EXEC_TIME          | NUMBER        | PL/SQL execution time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| JAVA_EXEC_TIME           | NUMBER        | Java execution time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| ROWS_PROCESSED           | NUMBER        | Total number of rows the parsed SQL statement returns                                                                                                                                                                                                                                                                                                                                                                                                                               |
| COMMAND_TYPE             | NUMBER        | Oracle command type definition                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| OPTIMIZER_MODE           | VARCHAR2 (10) | Mode under which the SQL statement was executed                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| OPTIMIZER_COST           | NUMBER        | Cost of this query given by the optimizer                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| OPTIMIZER_ENV            | RAW (2000)    | Optimizer environment                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| OPTIMIZER_ENV_HASH_VALUE | NUMBER        | Hash value for the optimizer environment                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| PARSING_USER_ID          | NUMBER        | User ID of the user who originally built this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                          |
| PARSING_SCHEMA_ID        | NUMBER        | Schema ID that was used to originally build this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                       |
| PARSING_SCHEMA_NAME      | VARCHAR2 (30) | Schema name that was used to originally build this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                     |
| KEPT_VERSIONS            | NUMBER        | Indicates whether this child cursor has been marked to be kept pinned in the cache using the DBMS_SHARED_POOL package                                                                                                                                                                                                                                                                                                                                                               |
| ADDRESS                  | RAW (4   8)   | Address of the handle to the parent for this cursor                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| TYPE_CHK_HEAP            | RAW (4)       | Descriptor of the type check heap for this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                             |
| HASH_VALUE               | NUMBER        | Hash value of the parent statement in the library cache                                                                                                                                                                                                                                                                                                                                                                                                                             |
| OLD_HASH_VALUE           | NUMBER        | Old SQL hash value                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| PLAN_HASH_VALUE          | NUMBER        | Numeric representation of the SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).                                                                                                                                                                                                                                                                        |
| CHILD_NUMBER             | NUMBER        | Number of this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| SERVICE                  | VARCHAR2 (64) | Service name                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| SERVICE_HASH             | NUMBER        | Hash value for the name listed in the SERVICE column                                                                                                                                                                                                                                                                                                                                                                                                                                |
| MODULE                   | VARCHAR2 (64) | Contains the name of the module that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_MODULE                                                                                                                                                                                                                                                                                                                    |
| MODULE_HASH              | NUMBER        | Hash value of the module listed in the MODULE column                                                                                                                                                                                                                                                                                                                                                                                                                                |

| Column                   | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ACTION                   | VARCHAR2 (64) | Contains the name of the action that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_ACTION                                                                                                                                                                                                                                                              |
| ACTION_HASH              | NUMBER        | Hash value of the action listed in the ACTION column                                                                                                                                                                                                                                                                                                                                                                          |
| SERIALIZABLE_ABORTS      | NUMBER        | Number of times the transaction failed to serialize, producing ORA-08177 errors, per cursor                                                                                                                                                                                                                                                                                                                                   |
| OUTLINE_CATEGORY         | VARCHAR2 (64) | If an outline was applied during construction of the cursor, then this column displays the category of that outline. Otherwise the column is left blank.                                                                                                                                                                                                                                                                      |
| CPU_TIME                 | NUMBER        | CPU time (in microseconds) used by this cursor for parsing, executing, and fetching                                                                                                                                                                                                                                                                                                                                           |
| ELAPSED_TIME             | NUMBER        | Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching                                                                                                                                                                                                                                                                                                                                       |
| OUTLINE_SID              | NUMBER        | Outline session identifier                                                                                                                                                                                                                                                                                                                                                                                                    |
| CHILD_ADDRESS            | RAW (4   8)   | Address of the child cursor                                                                                                                                                                                                                                                                                                                                                                                                   |
| SQLTYPE                  | NUMBER        | Denotes the version of the SQL language used for this statement                                                                                                                                                                                                                                                                                                                                                               |
| REMOTE                   | VARCHAR2 (1)  | Indicates whether the cursor is remote mapped (Y) or not (N)                                                                                                                                                                                                                                                                                                                                                                  |
| OBJECT_STATUS            | VARCHAR2 (19) | Status of the cursor: <ul style="list-style-type: none"> <li>VALID - Valid, authorized without errors</li> <li>VALID_AUTH_ERROR - Valid, authorized with authorization errors</li> <li>VALID_COMPILE_ERROR - Valid, authorized with compilation errors</li> <li>VALID_UNAUTH - Valid, unauthorized</li> <li>INVALID_UNAUTH - Invalid, unauthorized</li> <li>INVALID - Invalid, unauthorized but keep the timestamp</li> </ul> |
| LITERAL_HASH_VALUE       | NUMBER        | Hash value of the literals which are replaced with system-generated bind variables and are to be matched, when CURSOR_SHARING is used. This is not the hash value for the SQL statement. If CURSOR_SHARING is not used, then the value is 0.                                                                                                                                                                                  |
| LAST_LOAD_TIME           | VARCHAR2 (19) | Time at which the query plan was loaded into the library cache                                                                                                                                                                                                                                                                                                                                                                |
| IS_OBSOLETE              | VARCHAR2 (1)  | Indicates whether the cursor has become obsolete (Y) or not (N). This can happen if the number of child cursors is too large.                                                                                                                                                                                                                                                                                                 |
| IS_BIND_SENSITIVE        | VARCHAR2 (1)  | Indicates whether the cursor is bind sensitive (Y) or not (N). A query is considered bind-sensitive if the optimizer peeked at one of its bind variable values when computing predicate selectivities and where a change in a bind variable value may cause the optimizer to generate a different plan.                                                                                                                       |
| IS_BIND_AWARE            | VARCHAR2 (1)  | Indicates whether the cursor is bind aware (Y) or not (N). A query is considered bind-aware if it has been marked to use extended cursor sharing. The query would already have been marked as bind-sensitive.                                                                                                                                                                                                                 |
| IS_SHAREABLE             | VARCHAR2 (1)  | Indicates whether the cursor can be shared (Y) or not (N)                                                                                                                                                                                                                                                                                                                                                                     |
| CHILD_LATCH              | NUMBER        | Child latch number that is protecting the cursor. This column is obsolete and maintained for backward compatibility.                                                                                                                                                                                                                                                                                                          |
| SQL_PROFILE              | VARCHAR2 (64) | SQL profile used for this statement, if any                                                                                                                                                                                                                                                                                                                                                                                   |
| SQL_PATCH                | VARCHAR2 (30) | SQL patch used for this statement, if any                                                                                                                                                                                                                                                                                                                                                                                     |
| SQL_PLAN_BASELINE        | VARCHAR2 (30) | SQL plan baseline used for this statement, if any                                                                                                                                                                                                                                                                                                                                                                             |
| PROGRAM_ID               | NUMBER        | Program identifier                                                                                                                                                                                                                                                                                                                                                                                                            |
| PROGRAM_LINE#            | NUMBER        | Program line number                                                                                                                                                                                                                                                                                                                                                                                                           |
| EXACT_MATCHING_SIGNATURE | NUMBER        | Signature calculated on the normalized SQL text. The normalization includes the removal of white space and the uppercasing of all non-literal strings.                                                                                                                                                                                                                                                                        |
| FORCE_MATCHING_SIGNATURE | NUMBER        | Signature used when the CURSOR_SHARING parameter is set to FORCE                                                                                                                                                                                                                                                                                                                                                              |

| Column                         | Datatype  | Description                                                                                                                                                                                            |
|--------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAST_ACTIVE_TIME               | DATE      | Time at which the query plan was last active                                                                                                                                                           |
| BIND_DATA                      | RAW(2000) | Bind data                                                                                                                                                                                              |
| TYPECHECK_MEM                  | NUMBER    | Typecheck memory                                                                                                                                                                                       |
| IO_CELL_OFFLOAD_ELIGIBLE_BYTES | NUMBER    | Number of I/O bytes which can be filtered by the Exadata storage system<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information                                  |
| IO_INTERCONNECT_BYTES          | NUMBER    | Number of I/O bytes exchanged between Oracle Database and the storage system                                                                                                                           |
| PHYSICAL_READ_REQUESTS         | NUMBER    | Number of physical read I/O requests issued by the monitored SQL                                                                                                                                       |
| PHYSICAL_READ_BYTES            | NUMBER    | Number of bytes read from disks by the monitored SQL                                                                                                                                                   |
| PHYSICAL_WRITE_REQUESTS        | NUMBER    | Number of physical write I/O requests issued by the monitored SQL                                                                                                                                      |
| PHYSICAL_WRITE_BYTES           | NUMBER    | Number of bytes written to disks by the monitored SQL                                                                                                                                                  |
| OPTIMIZED_PHY_READ_REQUESTS    | NUMBER    | Number of physical read I/O requests from Database Smart Flash Cache issued by the monitored SQL                                                                                                       |
| LOCKED_TOTAL                   | NUMBER    | Total number of times the child cursor has been locked                                                                                                                                                 |
| PINNED_TOTAL                   | NUMBER    | Total number of times the child cursor has been pinned                                                                                                                                                 |
| IO_CELL_UNCOMPRESSED_BYTES     | NUMBER    | Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information |
| IO_CELL_OFFLOAD_RETURNED_BYTES | NUMBER    | Number of bytes that are returned by Exadata cell through the regular I/O path<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information                           |

## V\$SQL\_BIND\_CAPTURE

V\$SQL\_BIND\_CAPTURE displays information on bind variables used by SQL cursors. Each row in the view contains information for one bind variable defined in a cursor. This includes:

- Reference to the cursor defining the bind variable  
(hash\_value, address) for the parent cursor and (hash\_value, child\_address) for the child cursor.
- Bind metadata  
Name, position, datatype, character set ID, precision, scale, and maximum length of the bind variable.
- Bind data  
One of the bind values used for the bind variable during a past execution of its associated SQL statement. Bind values are not always captured for this view. Bind values are displayed by this view only when the type of the bind variable is simple (this excludes LONG, LOB, and ADT datatypes) and when the bind variable is used in the WHERE or HAVING clauses of the SQL statement.

Bind capture is disabled when the STATISTICS\_LEVEL initialization parameter is set to BASIC. This view can be joined with V\$SQLAREA on (HASH\_VALUE, ADDRESS) and with V\$SQL on (HASH\_VALUE, CHILD\_ADDRESS).

| Column          | Datatype        | Description                                                                                                                                                                              |
|-----------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADDRESS         | RAW (4   8)     | Address of the parent cursor                                                                                                                                                             |
| HASH_VALUE      | NUMBER          | Hash value of the parent cursor in the library cache. The hash value is a fixed index for the view and should always be used to speed up access to the view.                             |
| SQL_ID          | VARCHAR2 (13)   | SQL identifier of the parent cursor in the library cache                                                                                                                                 |
| CHILD_ADDRESS   | RAW (4   8)     | Address of the child cursor                                                                                                                                                              |
| CHILD_NUMBER    | NUMBER          | Child cursor number                                                                                                                                                                      |
| NAME            | VARCHAR2 (30)   | Name of the bind variable                                                                                                                                                                |
| POSITION        | NUMBER          | Position of the bind variable in the SQL statement                                                                                                                                       |
| DUP_POSITION    | NUMBER          | If the binding is performed by name and the bind variable is duplicated, then this column gives the position of the primary bind variable.                                               |
| DATATYPE        | NUMBER          | Internal identifier for the bind datatype                                                                                                                                                |
| DATATYPE_STRING | VARCHAR2 (15)   | Textual representation of the bind datatype                                                                                                                                              |
| CHARACTER_SID   | NUMBER          | National character set identifier                                                                                                                                                        |
| PRECISION       | NUMBER          | Precision (for numeric binds)                                                                                                                                                            |
| SCALE           | NUMBER          | Scale (for numeric binds)                                                                                                                                                                |
| MAX_LENGTH      | NUMBER          | Maximum bind length                                                                                                                                                                      |
| WAS_CAPTURED    | VARCHAR2 (3)    | Indicates whether the bind value was captured (YES) or not (NO)                                                                                                                          |
| LAST_CAPTURED   | DATE            | Date when the bind value was captured. Bind values are captured when SQL statements are executed. To limit the overhead, binds are captured at most every 15 minutes for a given cursor. |
| VALUE_STRING    | VARCHAR2 (4000) | Value of the bind represented as a string                                                                                                                                                |
| VALUE_ANYDATA   | ANYDATA         | Value of the bind represented using the ANYDATA datatype. This representation is useful to programmatically decode the value of the bind variable.                                       |

## V\$SQL\_BIND\_DATA

V\$SQL\_BIND\_DATA describes, for each distinct bind variable in each cursor owned by the session querying this view:

- Actual bind data, if the bind variable is user defined
- The underlying literal, if the CURSOR\_SHARING parameter is set to FORCE and the bind variable is system generated. (System-generated binds have a value of 256 in the SHARED\_FLAG2 column.)

| Column          | Datatype | Description                                                                                 |
|-----------------|----------|---------------------------------------------------------------------------------------------|
| CURSOR_NUM      | NUMBER   | Cursor number for this bind                                                                 |
| POSITION        | NUMBER   | Bind position                                                                               |
| DATATYPE        | NUMBER   | Bind datatype                                                                               |
| SHARED_MAX_LEN  | NUMBER   | Shared maximum length for this bind from the shared cursor object associated with this bind |
| PRIVATE_MAX_LEN | NUMBER   | Private maximum length for this bind sent from the client                                   |
| ARRAY_SIZE      | NUMBER   | Maximum number of array elements (for array binds only)                                     |
| PRECISION       | NUMBER   | Precision (for numeric binds)                                                               |
| SCALE           | NUMBER   | Scale (for numeric binds)                                                                   |
| SHARED_FLAG     | NUMBER   | Shared bind data flags                                                                      |
| SHARED_FLAG2    | NUMBER   | Shared bind data flags (continued)                                                          |

| Column      | Datatype        | Description                 |
|-------------|-----------------|-----------------------------|
| BUF_ADDRESS | RAW (4   8)     | Bind buffer memory address  |
| BUF_LENGTH  | NUMBER          | Bind buffer length          |
| VAL_LENGTH  | NUMBER          | Actual bind value length    |
| BUF_FLAG    | NUMBER          | Bind buffer flags           |
| INDICATOR   | NUMBER          | Bind indicator              |
| VALUE       | VARCHAR2 (4000) | Contents of the bind buffer |

## V\$SQL\_BIND\_METADATA

V\$SQL\_BIND\_METADATA describes, for each distinct bind variable in each cursor owned by the session querying this view:

- Bind metadata provided by the client, if the bind variable is user defined
- Metadata based on the underlying literal, if the CURSOR\_SHARING parameter is set to FORCE and the bind variable is system-generated.

| Column     | Datatype      | Description                                                     |
|------------|---------------|-----------------------------------------------------------------|
| ADDRESS    | RAW (4   8)   | Memory address of the child cursor that owns this bind variable |
| POSITION   | NUMBER        | Bind position                                                   |
| DATATYPE   | NUMBER        | Bind datatype                                                   |
| MAX_LENGTH | NUMBER        | Maximum length of the bind value                                |
| ARRAY_LEN  | NUMBER        | Maximum number of array elements (for array binds only)         |
| BIND_NAME  | VARCHAR2 (30) | User-defined or system-generated bind variable name (if used)   |

## V\$SQL\_CS\_HISTOGRAM

V\$SQL\_CS\_HISTOGRAM summarizes the monitoring information stored by adaptive cursor sharing. This information is used to decide whether to enable extended cursor sharing for a query. It is stored in a histogram, whose bucket's contents are exposed by this view.

| Column       | Datatype      | Description                                              |
|--------------|---------------|----------------------------------------------------------|
| ADDRESS      | RAW (4)       | Address of the handle to the parent for this cursor      |
| HASH_VALUE   | NUMBER        | Hash value of the parent statement in the library cache  |
| SQL_ID       | VARCHAR2 (13) | SQL identifier of the parent cursor in the library cache |
| CHILD_NUMBER | NUMBER        | Number of the child cursor being monitored               |
| BUCKET_ID    | NUMBER        | Bucket number of the monitoring histogram                |
| COUNT        | NUMBER        | Value in this bucket of the histogram                    |

## V\$SQL\_CS\_SELECTIVITY

V\$SQL\_CS\_SELECTIVITY exposes the valid selectivity ranges for a child cursor in extended cursor sharing mode. A valid range consists of a low and high value for each predicate containing binds. Each predicate's selectivity (with the current bind value) must fall between the corresponding low and high values in order for the child cursor to be shared.

| Column       | Datatype      | Description                                                                               |
|--------------|---------------|-------------------------------------------------------------------------------------------|
| ADDRESS      | RAW (4)       | Address of the handle to the parent for this cursor                                       |
| HASH_VALUE   | NUMBER        | Hash value of the parent statement in the library cache                                   |
| SQL_ID       | VARCHAR2 (13) | SQL identifier of the parent cursor in the library cache                                  |
| CHILD_NUMBER | NUMBER        | Number of the child cursor                                                                |
| PREDICATE    | VARCHAR2 (40) | Predicate whose selectivity must fall between low and high values                         |
| RANGE_ID     | NUMBER        | Identifier for the range used to match up the low and high values for multiple predicates |
| LOW          | VARCHAR2 (10) | Lower bound for allowable selectivity                                                     |
| HIGH         | VARCHAR2 (10) | Upper bound for allowable selectivity                                                     |

## V\$SQL\_CS\_STATISTICS

V\$SQL\_CS\_STATISTICS contains the raw execution statistics used by the monitoring component of adaptive cursor sharing. A sample of the executions is monitored. This view exposes which executions were sampled, and what the statistics were for those executions. The statistics are cumulative for each distinct set of bind values.

| Column              | Datatype      | Description                                                                                                         |
|---------------------|---------------|---------------------------------------------------------------------------------------------------------------------|
| ADDRESS             | RAW (4)       | Address of the handle to the parent for this cursor                                                                 |
| HASH_VALUE          | NUMBER        | Hash value of the parent statement in the library cache                                                             |
| SQL_ID              | VARCHAR2 (13) | SQL identifier of the parent cursor in the library cache                                                            |
| CHILD_NUMBER        | NUMBER        | Number of the child cursor being monitored                                                                          |
| BIND_SET_HASH_VALUE | NUMBER        | Hash of the values of the binds                                                                                     |
| PEEKED              | VARCHAR2 (1)  | Indicates if this is the bind set used to build the cursor (Y) or not (N)                                           |
| EXECUTIONS          | NUMBER        | Number of times this bind set has been executed and monitored                                                       |
| ROWS_PROCESSED      | NUMBER        | Cumulative number of rows processed by all row sources in the plan over all monitored executions with this bind set |
| BUFFER_GETS         | NUMBER        | Cumulative number of buffer gets over all monitored executions with this bind set                                   |
| CPU_TIME            | NUMBER        | Cumulative CPU time (in microseconds) used by this cursor for monitored executions with this bind set               |

## V\$SQL\_CURSOR

V\$SQL\_CURSOR displays debugging information for each cursor associated with the session querying this view.

| Column        | Datatype     | Description                                                           |
|---------------|--------------|-----------------------------------------------------------------------|
| CURNO         | NUMBER       | Cursor number                                                         |
| FLAG          | NUMBER       | Flags set in the cursor                                               |
| STATUS        | VARCHAR2 (9) | Status of the cursor; that is, what state the cursor is in            |
| PARENT_HANDLE | RAW (4   8)  | Pointer to the parent cursor handle                                   |
| PARENT_LOCK   | RAW (4   8)  | Pointer to the parent cursor lock                                     |
| CHILD_LOCK    | RAW (4   8)  | Pointer to the child cursor lock                                      |
| CHILD_PIN     | RAW (4   8)  | Pointer to the child cursor pin                                       |
| PERS_HEAP_MEM | NUMBER       | Total amount of memory allocated from persistent heap for this cursor |
| WORK_HEAP_MEM | NUMBER       | Total amount of memory allocated from the work heap for this cursor   |



| Column       | Datatype      | Description                                                                     |
|--------------|---------------|---------------------------------------------------------------------------------|
| BIND_VARS    | NUMBER        | Total number of bind positions in the query currently parsed into this cursor   |
| DEFINE_VARS  | NUMBER        | Total number of define variables in the query currently parsed into this cursor |
| BIND_MEM_LOC | VARCHAR2 (64) | Which memory heap the bind variables are stored in: either the UGA or the CGA   |
| INST_FLAG    | VARCHAR2 (64) | Instantiation object flags                                                      |
| INST_FLAG2   | VARCHAR2 (64) | Instantiation object flags (continued)                                          |

## V\$SQL\_JOIN\_FILTER

V\$SQL\_JOIN\_FILTER displays performance information about the characteristics of join filters when they are used for a parallel cursor. (A join filter is a bitmap filter applied to table rows prior to a join operation in order to avoid parallel communication.)

| Column              | Datatype | Description                                                                                                                                         |
|---------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| QC_SESSION_ID       | NUMBER   | QC (Query Coordinator) session ID of the given cursor for the given parallel query                                                                  |
| QC_INSTANCE_ID      | NUMBER   | QC (Query Coordinator) instance ID of the given cursor for the given parallel query                                                                 |
| SQL_PLAN_HASH_VALUE | NUMBER   | SQL plan hash value of the given cursor for the given parallel query                                                                                |
| LENGTH              | NUMBER   | Total size of the join filter field                                                                                                                 |
| BITS_SET            | NUMBER   | Number of bits set in this filter                                                                                                                   |
| FILTERED            | NUMBER   | Number of rows seen by the join filter                                                                                                              |
| PROBED              | NUMBER   | Number of rows of the right table that have been tested against the bitmap filter. This is the sum of the filtered rows plus the non-filtered rows. |
| ACTIVE              | NUMBER   | Whether the filter is active (Yes) or not (No)                                                                                                      |

## V\$SQL\_MONITOR

V\$SQL\_MONITOR displays SQL statements whose execution have been (or are being) monitored by Oracle. An entry is created in V\$SQL\_MONITOR every time the execution of a SQL statement is being monitored. SQL monitoring is automatically started when a SQL statement runs parallel or when it has consumed at least 5 seconds of CPU or I/O time.

When the SQL statement being monitored is executing, statistics in V\$SQL\_MONITOR are generally refreshed in near real time, once every second. Once the execution ends, monitoring information is not deleted immediately. Instead, it is kept in V\$SQL\_MONITOR for at least one minute. The entry will eventually be deleted to reclaim its space as new statements are monitored.

| Column | Datatype | Description                                                                                                                                  |
|--------|----------|----------------------------------------------------------------------------------------------------------------------------------------------|
| KEY    | NUMBER   | Artificial join key to efficiently join V\$SQL_MONITOR with its corresponding plan level monitoring statistics stored in V\$SQL_PLAN_MONITOR |

| Column                    | Datatype        | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STATUS                    | VARCHAR2 (19)   | SQL execution status: <ul style="list-style-type: none"> <li>■ QUEUED - SQL statement is queued</li> <li>■ EXECUTING - SQL statement is still executing</li> <li>■ DONE (ERROR) - Execution terminated with an error</li> <li>■ DONE (FIRST N ROWS) - Execution terminated by the application before all rows were fetched</li> <li>■ DONE (ALL ROWS) - Execution terminated and all rows were fetched</li> <li>■ DONE - Execution terminated (parallel execution)</li> </ul> |
| USER#                     | NUMBER          | User ID of the database user who issued the SQL being monitored                                                                                                                                                                                                                                                                                                                                                                                                               |
| USERNAME                  | VARCHAR2 (30)   | User name of the database user who issued the SQL being monitored                                                                                                                                                                                                                                                                                                                                                                                                             |
| MODULE <sup>1</sup>       | VARCHAR2 (48)   | Name of the executing module when sampled, as set by the DBMS_APPLICATION_INFO.SET_MODULE procedure                                                                                                                                                                                                                                                                                                                                                                           |
| ACTION <sup>1</sup>       | VARCHAR2 (32)   | Name of the executing action when sampled, as set by the DBMS_APPLICATION_INFO.SET_ACTION procedure                                                                                                                                                                                                                                                                                                                                                                           |
| SERVICE_NAME              | VARCHAR2 (64)   | Service name of the user session                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| CLIENT_IDENTIFIER         | VARCHAR2 (64)   | Client identifier from the user session                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| CLIENT_INFO               | VARCHAR2 (64)   | Client information for the user session                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| PROGRAM                   | VARCHAR2 (48)   | Name of the OS program that issued the monitored SQL                                                                                                                                                                                                                                                                                                                                                                                                                          |
| PLSQL_ENTRY_OBJECT_ID     | NUMBER          | Object ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack                                                                                                                                                                                                                                                                                                                                                                  |
| PLSQL_ENTRY_SUBPROGRAM_ID | NUMBER          | Subprogram ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack                                                                                                                                                                                                                                                                                                                                                              |
| PLSQL_OBJECT_ID           | NUMBER          | Object ID of the currently executing PL/SQL subprogram; NULL if executing SQL                                                                                                                                                                                                                                                                                                                                                                                                 |
| PLSQL_SUBPROGRAM_ID       | NUMBER          | Subprogram ID of the currently executing PL/SQL object; NULL if executing SQL                                                                                                                                                                                                                                                                                                                                                                                                 |
| FIRST_REFRESH_TIME        | DATE            | Time when monitoring of the SQL statement started, generally a few seconds after execution start time                                                                                                                                                                                                                                                                                                                                                                         |
| LAST_REFRESH_TIME         | DATE            | Time when statistics in V\$SQL_MONITOR were last updated for the SQL statement. Statistics are generally refreshed every second when the statement executes.                                                                                                                                                                                                                                                                                                                  |
| REFRESH_COUNT             | NUMBER          | Number of times V\$SQL_MONITOR statistics have been refreshed (generally once every second when the SQL statement executes)                                                                                                                                                                                                                                                                                                                                                   |
| SID                       | NUMBER          | Session identifier executing (or having executed) the SQL statement being monitored                                                                                                                                                                                                                                                                                                                                                                                           |
| PROCESS_NAME              | VARCHAR2 (5)    | Process name identifier executing (or having executed) the statement; ora if the process is foreground, else the background process name (for example, p001 for PX server p001)                                                                                                                                                                                                                                                                                               |
| SQL_ID                    | VARCHAR2 (13)   | SQL identifier of the statement being monitored                                                                                                                                                                                                                                                                                                                                                                                                                               |
| SQL_TEXT                  | VARCHAR2 (2000) | Up to the first 2000 characters of the text of the SQL being monitored                                                                                                                                                                                                                                                                                                                                                                                                        |
| IS_FULL_SQLTEXT           | VARCHAR2 (1)    | Indicates whether the SQL_TEXT column has the entire SQL text (Y) or not (N)                                                                                                                                                                                                                                                                                                                                                                                                  |
| SQL_EXEC_START            | DATE            | Time when the execution started                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| SQL_EXEC_ID               | NUMBER          | Execution identifier. Together, the three columns SQL_ID, SQL_EXEC_START, and SQL_EXEC_ID represent the execution key. The execution key is used to uniquely identify one execution of the SQL statement.                                                                                                                                                                                                                                                                     |
| SQL_PLAN_HASH_VALUE       | NUMBER          | SQL Plan hash value                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| EXACT_MATCHING_SIGNATURE  | NUMBER          | Signature calculated on the normalized SQL text. The normalization includes the removal of white space and the uppcasing of all non-literal strings.                                                                                                                                                                                                                                                                                                                          |

| Column                   | Datatype       | Description                                                                                                                                                                                                                                                                                |
|--------------------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FORCE_MATCHING_SIGNATURE | NUMBER         | Same as EXACT_MATCHING_SIGNATURE but literals in the SQL text are replaced by binds                                                                                                                                                                                                        |
| SQL_CHILD_ADDRESS        | RAW (4   8)    | Address of the child cursor (can be used with SQL_ID to join with V\$SQL)                                                                                                                                                                                                                  |
| SESSION_SERIAL#          | NUMBER         | Session serial number executing the statement being monitored                                                                                                                                                                                                                              |
| PX_IS_CROSS_INSTANCE     | VARCHAR2 (1)   | Indicates whether the SQL statement ran parallel across multiple instances (Y) or not (N)                                                                                                                                                                                                  |
| PX_MAXDOP                | NUMBER         | Maximum degree of parallelism for any plan operation executed on behalf of the monitored SQL                                                                                                                                                                                               |
| PX_MAXDOP_INSTANCES      | NUMBER         | Number of database instances touched at the maximum degree of parallelism                                                                                                                                                                                                                  |
| PX_SERVERS_REQUESTED     | NUMBER         | Total number of parallel execution servers requested to execute the monitored SQL                                                                                                                                                                                                          |
| PX_SERVERS_ALLOCATED     | NUMBER         | Actual number of parallel execution servers allocated to execute the query                                                                                                                                                                                                                 |
| PX_SERVER#               | NUMBER         | Logical parallel execution server process number executing (or having executed) the statement being monitored; NULL if this monitoring entry is not associated with an execution server. This is a logical number within the parallel server set (see SERVER# in V\$PX_SESSION).           |
| PX_SERVER_GROUP          | NUMBER         | Logical parallel execution server group number to which PX_SERVER# belongs (see SERVER_GROUP in V\$PX_SESSION); NULL if this monitoring entry is not associated with a parallel execution server. This value is generally 1 unless the SQL statement has one or more parallel sub-queries. |
| PX_SERVER_SET            | NUMBER         | Number (1 or 2) of the logical set of parallel execution servers to which PX_SERVER# belongs (see SERVER_SET in V\$PX_SESSION); NULL if this monitoring entry is not associated with a parallel execution server                                                                           |
| PX_QCINST_ID             | NUMBER         | Instance identifier where the parallel execution coordinator runs; NULL if PX_SERVER# is NULL                                                                                                                                                                                              |
| PX_QCSID                 | NUMBER         | Session identifier for the parallel execution coordinator; NULL if PX_SERVER# is NULL                                                                                                                                                                                                      |
| ERROR_NUMBER             | VARCHAR2 (40)  | Error number encountered in case a SQL fails to execute successfully (for example, 932 in case of ORA-00932)                                                                                                                                                                               |
| ERROR_FACILITY           | VARCHAR2 (4)   | Error facility in case a SQL fails to execute successfully (for example, ORA in case of ORA-00932)                                                                                                                                                                                         |
| ERROR_MESSAGE            | VARCHAR2 (256) | Detailed error message displayed corresponding to the error number and error facility when a SQL fails to execute successfully                                                                                                                                                             |
| BINDS_XML                | CLOB           | Information about bind variables used with the SQL, such as name, position, value, data type, and so on (stored in XML format)                                                                                                                                                             |
| OTHER_XML                | CLOB           | Additional information about SQL execution stored in XML format                                                                                                                                                                                                                            |
| ELAPSED_TIME             | NUMBER         | Elapsed time (in microseconds); updated as the statement executes                                                                                                                                                                                                                          |
| QUEUEING_TIME            | NUMBER         | Duration of time (in microseconds) spent by SQL in the statement queue                                                                                                                                                                                                                     |
| CPU_TIME                 | NUMBER         | CPU time (in microseconds); updated as the statement executes                                                                                                                                                                                                                              |
| FETCHES                  | NUMBER         | Number of fetches associated with the SQL statement; updated as the statement executes                                                                                                                                                                                                     |
| BUFFER_GETS              | NUMBER         | Number of buffer get operations; updated as the statement executes                                                                                                                                                                                                                         |
| DISK_READS               | NUMBER         | Number of disk reads; updated as the statement executes                                                                                                                                                                                                                                    |
| DIRECT_WRITES            | NUMBER         | Number of direct writes; updated as the statement executes                                                                                                                                                                                                                                 |
| IO_INTERCONNECT_BYTES    | NUMBER         | Number of I/O bytes exchanged between Oracle Database and the storage system                                                                                                                                                                                                               |
| PHYSICAL_READ_REQUESTS   | NUMBER         | Number of physical read I/O requests issued by the monitored SQL                                                                                                                                                                                                                           |
| PHYSICAL_READ_BYTES      | NUMBER         | Number of bytes read from disks by the monitored SQL                                                                                                                                                                                                                                       |
| PHYSICAL_WRITE_REQUESTS  | NUMBER         | Number of physical write I/O requests issued by the monitored SQL                                                                                                                                                                                                                          |

| Column                | Datatype | Description                                                                |
|-----------------------|----------|----------------------------------------------------------------------------|
| PHYSICAL_WRITE_BYTES  | NUMBER   | Number of bytes written to disks by the monitored SQL                      |
| APPLICATION_WAIT_TIME | NUMBER   | Application wait time (in microseconds); updated as the statement executes |
| CONCURRENCY_WAIT_TIME | NUMBER   | Concurrency wait time (in microseconds); updated as the statement executes |
| CLUSTER_WAIT_TIME     | NUMBER   | Cluster wait time (in microseconds); updated as the statement executes     |
| USER_IO_WAIT_TIME     | NUMBER   | User I/O Wait Time (in microseconds); updated as the statement executes    |
| PLSQL_EXEC_TIME       | NUMBER   | PL/SQL execution time (in microseconds); updated as the statement executes |
| JAVA_EXEC_TIME        | NUMBER   | Java execution time (in microseconds); updated as the statement executes   |

<sup>1</sup> The datatype of this column is VARCHAR2 (64) starting with Oracle Database 11g Release 2 (11.2.0.2).

## V\$SQL\_OPTIMIZER\_ENV

V\$SQL\_OPTIMIZER\_ENV displays the contents of the optimizer environment used to build the execution plan of a SQL cursor. This view can be joined with V\$SQLAREA on (HASH\_VALUE, ADDRESS) and with V\$SQL on (HASH\_VALUE, CHILD\_ADDRESS).

| Column        | Datatype      | Description                                                                                                                                                                                            |
|---------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADDRESS       | RAW (4   8)   | Address of the parent cursor                                                                                                                                                                           |
| HASH_VALUE    | NUMBER        | Hash value of the parent cursor in the library cache. The hash value is the fixed index for the view and should be used when querying V\$SQL_OPTIMIZER_ENV to avoid scanning the entire library cache. |
| SQL_ID        | VARCHAR2 (13) | SQL identifier                                                                                                                                                                                         |
| CHILD_ADDRESS | RAW (4   8)   | Address of the child cursor                                                                                                                                                                            |
| CHILD_NUMBER  | NUMBER        | Child cursor number                                                                                                                                                                                    |
| ID            | NUMBER        | Unique identifier of the parameter in the optimizer environment                                                                                                                                        |
| NAME          | VARCHAR2 (40) | Name of the parameter                                                                                                                                                                                  |
| ISDEFAULT     | VARCHAR2 (3)  | Indicates whether the parameter is set to the default value (YES) or not (NO)                                                                                                                          |
| VALUE         | VARCHAR2 (25) | Value of the parameter                                                                                                                                                                                 |

## V\$SQL\_PLAN

V\$SQL\_PLAN contains the execution plan information for each child cursor loaded in the library cache.

| Column          | Datatype      | Description                                                                                                                                                                                                   |
|-----------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADDRESS         | RAW (4   8)   | Address of the handle to the parent for this cursor                                                                                                                                                           |
| HASH_VALUE      | NUMBER        | Hash value of the parent statement in the library cache. The two columns ADDRESS and HASH_VALUE can be used to join with V\$SQLAREA to add the cursor-specific information.                                   |
| SQL_ID          | VARCHAR2 (13) | SQL identifier of the parent cursor in the library cache                                                                                                                                                      |
| PLAN_HASH_VALUE | NUMBER        | Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). |
| CHILD_ADDRESS   | RAW (4   8)   | Address of the child cursor                                                                                                                                                                                   |
| CHILD_NUMBER    | NUMBER        | Number of the child cursor that uses this execution plan. The columns ADDRESS, HASH_VALUE, and CHILD_NUMBER can be used to join with V\$SQL to add the child cursor-specific information.                     |

| Column          | Datatype        | Description                                                                                                                                                                                                                                       |
|-----------------|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TIMESTAMP       | DATE            | Date and time when the execution plan was generated                                                                                                                                                                                               |
| OPERATION       | VARCHAR2 (30)   | Name of the internal operation performed in this step (for example, TABLE ACCESS)                                                                                                                                                                 |
| OPTIONS         | VARCHAR2 (30)   | A variation on the operation described in the OPERATION column (for example, FULL)                                                                                                                                                                |
| OBJECT_NODE     | VARCHAR2 (40)   | Name of the database link used to reference the object (a table name or view name). For local queries that use parallel execution, this column describes the order in which output from operations is consumed.                                   |
| OBJECT#         | NUMBER          | Object number of the table or the index                                                                                                                                                                                                           |
| OBJECT_OWNER    | VARCHAR2 (30)   | Name of the user who owns the schema containing the table or index                                                                                                                                                                                |
| OBJECT_NAME     | VARCHAR2 (30)   | Name of the table or index                                                                                                                                                                                                                        |
| OBJECT_ALIAS    | VARCHAR2 (65)   | Alias for the object                                                                                                                                                                                                                              |
| OBJECT_TYPE     | VARCHAR2 (20)   | Type of the object                                                                                                                                                                                                                                |
| OPTIMIZER       | VARCHAR2 (20)   | Current mode of the optimizer for the first row in the plan (statement line), for example, CHOOSE. When the operation is a database access (for example, TABLE ACCESS), this column indicates whether or not the object is analyzed.              |
| ID              | NUMBER          | A number assigned to each step in the execution plan                                                                                                                                                                                              |
| PARENT_ID       | NUMBER          | ID of the next execution step that operates on the output of the current step                                                                                                                                                                     |
| DEPTH           | NUMBER          | Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0. |
| POSITION        | NUMBER          | Order of processing for all operations that have the same PARENT_ID                                                                                                                                                                               |
| SEARCH_COLUMNS  | NUMBER          | Number of index columns with start and stop keys (that is, the number of columns with matching predicates)                                                                                                                                        |
| COST            | NUMBER          | Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                                                                  |
| CARDINALITY     | NUMBER          | Estimate, by the cost-based optimizer, of the number of rows produced by the operation                                                                                                                                                            |
| BYTES           | NUMBER          | Estimate, by the cost-based optimizer, of the number of bytes produced by the operation                                                                                                                                                           |
| OTHER_TAG       | VARCHAR2 (35)   | Describes the contents of the OTHER column. See EXPLAIN PLAN for values.                                                                                                                                                                          |
| PARTITION_START | VARCHAR2 (64)   | Start partition of a range of accessed partitions                                                                                                                                                                                                 |
| PARTITION_STOP  | VARCHAR2 (64)   | Stop partition of a range of accessed partitions                                                                                                                                                                                                  |
| PARTITION_ID    | NUMBER          | Step that computes the pair of values of the PARTITION_START and PARTITION_STOP columns                                                                                                                                                           |
| OTHER           | VARCHAR2 (4000) | Other information specific to the execution step that users may find useful. See EXPLAIN PLAN for values.                                                                                                                                         |
| DISTRIBUTION    | VARCHAR2 (20)   | Stores the method used to distribute rows from producer query servers to consumer query servers                                                                                                                                                   |
| CPU_COST        | NUMBER          | CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                                                              |
| IO_COST         | NUMBER          | I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                                                              |
| TEMP_SPACE      | NUMBER          | Temporary space usage of the operation (sort or hash-join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                             |

| Column            | Datatype        | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ACCESS_PREDICATES | VARCHAR2 (4000) | Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| FILTER_PREDICATES | VARCHAR2 (4000) | Predicates used to filter rows before producing them                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| PROJECTION        | VARCHAR2 (4000) | Expressions produced by the operation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| TIME              | NUMBER          | Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| QBLOCK_NAME       | VARCHAR2 (30)   | Name of the query block                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| REMARKS           | VARCHAR2 (4000) | Remarks                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| OTHER_XML         | CLOB            | Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML since multiple pieces of information can be stored there. This includes: <ul style="list-style-type: none"> <li>■ Name of the schema against which the query was parsed</li> <li>■ Release number of the Oracle Database that produced the explain plan</li> <li>■ Hash value associated with the execution plan</li> <li>■ Name (if any) of the outline or the SQL profile used to build the execution plan</li> <li>■ Indication of whether or not dynamic sampling was used to produce the plan</li> <li>■ The outline data, a set of optimizer hints that can be used to regenerate the same plan</li> </ul> |

## V\$SQL\_PLAN\_MONITOR

V\$SQL\_PLAN\_MONITOR displays plan level monitoring statistics for each SQL statement found in V\$SQL\_MONITOR. Each row in V\$SQL\_PLAN\_MONITOR corresponds to an operation of the execution plan being monitored. As with V\$SQL\_MONITOR, statistics exposed in V\$SQL\_PLAN\_MONITOR are generally updated every second when the statement executes. These statistics are recycled on the same basis as V\$SQL\_MONITOR.

To eliminate the overhead of SQL plan monitoring, statistics collected for each operation of the plan don't record timing information such as elapsed time, CPU time, or I/O time. Instead, this timing information can be estimated quite accurately by joining V\$SQL\_PLAN\_MONITOR with V\$ACTIVE\_SESSION\_HISTORY on SQL\_ID, SQL\_EXEC\_START, SQL\_EXEC\_ID, and SQL\_PLAN\_LINE\_ID (simply named PLAN\_LINE\_ID in V\$SQL\_PLAN\_MONITOR). The result of that join is a sample of the activity performed by each operation in the plan, from which an estimate of CPU time and wait time can be derived. This can be achieved by breaking statement level monitoring time statistics found in V\$SQL\_MONITOR in proportion to the number of samples found in V\$ACTIVE\_SESSION\_HISTORY for the corresponding activity type.

| Column | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| KEY    | NUMBER        | Foreign key to efficiently join V\$SQL_PLAN_MONITOR with V\$SQL_MONITOR (see V\$SQL_MONITOR)                                                                                                                                                                                                                                                                                                                                      |
| STATUS | VARCHAR2 (19) | SQL execution status: <ul style="list-style-type: none"> <li>■ EXECUTING - SQL statement is still executing</li> <li>■ DONE (ERROR) - Execution terminated with an error</li> <li>■ DONE (FIRST N ROWS) - Execution terminated by the application before all rows were fetched</li> <li>■ DONE (ALL ROWS) - Execution terminated and all rows were fetched</li> <li>■ DONE - Execution terminated (parallel execution)</li> </ul> |

| Column               | Datatype      | Description                                                                                                                                                                                                                                       |
|----------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FIRST_REFRESH_TIME   | DATE          | Time when monitoring of the SQL statement started                                                                                                                                                                                                 |
| LAST_REFRESH_TIME    | DATE          | Time when statistics were last updated for the SQL statement                                                                                                                                                                                      |
| FIRST_CHANGE_TIME    | DATE          | First time a row was produced by this operation                                                                                                                                                                                                   |
| LAST_CHANGE_TIME     | DATE          | Last time a row was produced by this operation                                                                                                                                                                                                    |
| REFRESH_COUNT        | NUMBER        | Number of times statistics have been refreshed                                                                                                                                                                                                    |
| SID                  | NUMBER        | Session identifier executing (or having executed) the SQL statement being monitored                                                                                                                                                               |
| PROCESS_NAME         | VARCHAR2 (5)  | Process name identifier                                                                                                                                                                                                                           |
| SQL_ID               | VARCHAR2 (13) | SQL identifier                                                                                                                                                                                                                                    |
| SQL_EXEC_START       | DATE          | Time when the execution started                                                                                                                                                                                                                   |
| SQL_EXEC_ID          | NUMBER        | Execution identifier                                                                                                                                                                                                                              |
| SQL_PLAN_HASH_VALUE  | NUMBER        | SQL plan hash value                                                                                                                                                                                                                               |
| SQL_CHILD_ADDRESS    | RAW (4   8)   | Address of the child cursor                                                                                                                                                                                                                       |
| PLAN_PARENT_ID       | NUMBER        | ID of the next execution step that operates on the output of the current step                                                                                                                                                                     |
| PLAN_LINE_ID         | NUMBER        | Plan line number for the entry                                                                                                                                                                                                                    |
| PLAN_OPERATION       | VARCHAR2 (30) | Plan operation name (from V\$SQL_PLAN)                                                                                                                                                                                                            |
| PLAN_OPTIONS         | VARCHAR2 (30) | Plan option name (from V\$SQL_PLAN)                                                                                                                                                                                                               |
| PLAN_OBJECT_OWNER    | VARCHAR2 (30) | Name of the user who owns the schema containing the table or index                                                                                                                                                                                |
| PLAN_OBJECT_NAME     | VARCHAR2 (30) | Name of the table or index                                                                                                                                                                                                                        |
| PLAN_OBJECT_TYPE     | VARCHAR2 (20) | Type of the object                                                                                                                                                                                                                                |
| PLAN_DEPTH           | NUMBER        | Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0. |
| PLAN_POSITION        | NUMBER        | Order of processing for all operations that have the same PARENT_ID                                                                                                                                                                               |
| PLAN_COST            | NUMBER        | Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.                                                                                                  |
| PLAN_CARDINALITY     | NUMBER        | Estimate, by the cost-based optimizer, of the number of rows produced by the operation                                                                                                                                                            |
| PLAN_BYTES           | NUMBER        | Estimate, by the cost-based optimizer, of the number of bytes produced by the operation                                                                                                                                                           |
| PLAN_TIME            | NUMBER        | Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.                                                                             |
| PLAN_PARTITION_START | VARCHAR2 (64) | Start partition of a range of accessed partitions                                                                                                                                                                                                 |
| PLAN_PARTITION_STOP  | VARCHAR2 (64) | Stop partition of a range of accessed partitions                                                                                                                                                                                                  |
| PLAN_CPU_COST        | NUMBER        | CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.                                                                                              |
| PLAN_IO_COST         | NUMBER        | I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.                                                                                              |
| PLAN_TEMP_SPACE      | NUMBER        | Temporary space usage of the operation (sort or hash-join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.                                                             |
| STARTS               | NUMBER        | Number of times this operation was executed. For example, an operation is executed multiple times when it is on the right side of a nested-loop join (once for each row of the left input of that nested-loop join).                              |

| Column                  | Datatype | Description                                                                                                                                                                                                                                          |
|-------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OUTPUT_ROWS             | NUMBER   | Number of rows produced by this operation since the execution started. This number is cumulated for all executions of this operation. Divide by the value of the STARTS column to compute the average number of rows per execution of the operation. |
| IO_INTERCONNECT_BYTES   | NUMBER   | Number of I/O bytes exchanged between Oracle Database and the storage system. Maintained only after Oracle starts to monitor the execution.                                                                                                          |
| PHYSICAL_READ_REQUESTS  | NUMBER   | Number of physical read I/O requests issued by the monitored SQL. Maintained only after Oracle starts to monitor the execution.                                                                                                                      |
| PHYSICAL_READ_BYTES     | NUMBER   | Number of bytes read from disks by the monitored SQL. Maintained only after Oracle starts to monitor the execution.                                                                                                                                  |
| PHYSICAL_WRITE_REQUESTS | NUMBER   | Number of physical write I/O requests issued by the monitored SQL. Maintained only after Oracle starts to monitor the execution.                                                                                                                     |
| PHYSICAL_WRITE_BYTES    | NUMBER   | Number of bytes written to disks by the monitored SQL. Maintained only after Oracle starts to monitor the execution.                                                                                                                                 |
| WORKAREA_MEM            | NUMBER   | Amount of memory (in bytes) used by the operation when the query is executing; NULL if the execution is done. This applies only to operations using a work area, such as sort, hash-join, group-by, and so on.                                       |
| WORKAREA_MAX_MEM        | NUMBER   | Maximum value (in bytes) for WORKAREA_MEM; NULL if the operation is not using a work area. When the execution is finished, this value will hold the maximum amount of memory consumed by this operation during the execution of the statement.       |
| WORKAREA_TEMPSEG        | NUMBER   | Amount of temporary space (in bytes) used by the operation when the query is executing; NULL if the operation has not spilled to disk or if the execution is finished                                                                                |
| WORKAREA_MAX_TEMPSEG    | NUMBER   | Maximum value (in bytes) for WORKAREA_TEMPSEG; NULL if this operation never spilled to disk. When the execution is done, this value will hold the maximum amount of temporary space consumed by this operation during the entire execution.          |

## V\$SQL\_PLAN\_STATISTICS

V\$SQL\_PLAN\_STATISTICS provides execution statistics at the row source level for each child cursor.

| Column           | Datatype      | Description                                                                                                                                                                                                   |
|------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADDRESS          | RAW (4   8)   | Address of the handle to the parent for this cursor                                                                                                                                                           |
| HASH_VALUE       | NUMBER        | Hash value of the parent statement in the library cache. The two columns ADDRESS and HASH_VALUE can be used to join with V\$SQLAREA to locate the parent cursor.                                              |
| SQL_ID           | VARCHAR2 (13) | SQL identifier of the parent statement in the library cache                                                                                                                                                   |
| PLAN_HASH_VALUE  | NUMBER        | Numerical representation of the SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line) |
| CHILD_ADDRESS    | RAW (4   8)   | Address of the child cursor                                                                                                                                                                                   |
| CHILD_NUMBER     | NUMBER        | Number of the child cursor that uses this work area. The columns ADDRESS, HASH_VALUE, and CHILD_NUMBER can be used to join with V\$SQL to locate the child cursor using this area.                            |
| OPERATION_ID     | NUMBER        | A number assigned to each step in the execution plan                                                                                                                                                          |
| EXECUTIONS       | NUMBER        | Number of times this cursor has been executed                                                                                                                                                                 |
| LAST_STARTS      | NUMBER        | Number of times this operation has been started, during the last execution                                                                                                                                    |
| STARTS           | NUMBER        | Number of times this operation has been started, accumulated over the past executions                                                                                                                         |
| LAST_OUTPUT_ROWS | NUMBER        | Number of rows produced by the row source, during the last execution                                                                                                                                          |



| Column              | Datatype | Description                                                                                                                                                                 |
|---------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OUTPUT_ROWS         | NUMBER   | Number of rows produced by the row source, accumulated over the past executions                                                                                             |
| LAST_CR_BUFFER_GETS | NUMBER   | Number of buffers retrieved in consistent mode, during the last execution. Buffers are usually retrieved in consistent mode for queries.                                    |
| CR_BUFFER_GETS      | NUMBER   | Number of buffers retrieved in consistent mode, accumulated over the past executions. Buffers are usually retrieved in consistent mode for queries.                         |
| LAST_CU_BUFFER_GETS | NUMBER   | Number of buffers retrieved in current mode, during the last execution. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE.            |
| CU_BUFFER_GETS      | NUMBER   | Number of buffers retrieved in current mode, accumulated over the past executions. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE. |
| LAST_DISK_READS     | NUMBER   | Number of physical disk reads performed by the operation, during the last execution                                                                                         |
| DISK_READS          | NUMBER   | Number of physical disk reads performed by the operation, accumulated over the past executions                                                                              |
| LAST_DISK_WRITES    | NUMBER   | Number of physical disk writes performed by the operation, during the last execution                                                                                        |
| DISK_WRITES         | NUMBER   | Number of physical disk writes performed by the operation, accumulated over the past executions                                                                             |
| LAST_ELAPSED_TIME   | NUMBER   | Elapsed time (in microseconds) corresponding to this operation, during the last execution                                                                                   |
| ELAPSED_TIME        | NUMBER   | Elapsed time (in microseconds) corresponding to this operation, accumulated over the past executions                                                                        |

## V\$SQL\_PLAN\_STATISTICS\_ALL

V\$SQL\_PLAN\_STATISTICS\_ALL contains memory usage statistics for row sources that use SQL memory (sort or hash-join). This view concatenates information in V\$SQL\_PLAN with execution statistics from V\$SQL\_PLAN\_STATISTICS and V\$SQL\_WORKAREA.

| Column          | Datatype      | Description                                                                                                                                                                                                     |
|-----------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADDRESS         | RAW (4   8)   | Address of the handle to the parent for this cursor                                                                                                                                                             |
| HASH_VALUE      | NUMBER        | Hash value of the parent statement in the library cache. The two columns ADDRESS and HASH_VALUE can be used to join with V\$SQLAREA to add the cursor-specific information.                                     |
| SQL_ID          | VARCHAR2 (13) | SQL identifier of the parent statement in the library cache                                                                                                                                                     |
| PLAN_HASH_VALUE | NUMBER        | Numerical representation of the SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line)   |
| CHILD_ADDRESS   | RAW (4   8)   | Address of the child cursor                                                                                                                                                                                     |
| CHILD_NUMBER    | NUMBER        | Number of the child cursor that uses this execution plan. The columns ADDRESS, HASH_VALUE, and CHILD_NUMBER can be used to join with V\$SQL to add the child cursor-specific information.                       |
| TIMESTAMP       | DATE          | Date and time when the execution plan was generated                                                                                                                                                             |
| OPERATION       | VARCHAR2 (30) | Name of the internal operation performed in this step (for example, TABLE ACCESS)                                                                                                                               |
| OPTIONS         | VARCHAR2 (30) | A variation on the operation described in the OPERATION column (for example, FULL)                                                                                                                              |
| OBJECT_NODE     | VARCHAR2 (40) | Name of the database link used to reference the object (a table name or view name). For local queries that use parallel execution, this column describes the order in which output from operations is consumed. |

| Column            | Datatype        | Description                                                                                                                                                                                                                                       |
|-------------------|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT#           | NUMBER          | Object number of the table or the index                                                                                                                                                                                                           |
| OBJECT_OWNER      | VARCHAR2 (30)   | Name of the user who owns the schema containing the table or index                                                                                                                                                                                |
| OBJECT_NAME       | VARCHAR2 (30)   | Name of the table or index                                                                                                                                                                                                                        |
| OBJECT_ALIAS      | VARCHAR2 (65)   | Alias for the object                                                                                                                                                                                                                              |
| OBJECT_TYPE       | VARCHAR2 (20)   | Type of the object                                                                                                                                                                                                                                |
| OPTIMIZER         | VARCHAR2 (20)   | Current mode of the optimizer for the first row in the plan (statement line), for example, CHOOSE. When the operation is a database access (for example, TABLE ACCESS), this column indicates whether or not the object is analyzed.              |
| ID                | NUMBER          | A number assigned to each step in the execution plan                                                                                                                                                                                              |
| PARENT_ID         | NUMBER          | ID of the next execution step that operates on the output of the current step                                                                                                                                                                     |
| DEPTH             | NUMBER          | Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0. |
| POSITION          | NUMBER          | Order of processing for all operations that have the same PARENT_ID                                                                                                                                                                               |
| SEARCH_COLUMNS    | NUMBER          | Number of index columns with start and stop keys (that is, the number of columns with matching predicates)                                                                                                                                        |
| COST              | NUMBER          | Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                                                                  |
| CARDINALITY       | NUMBER          | Estimate, by the cost-based optimizer, of the number of rows produced by the operation                                                                                                                                                            |
| BYTES             | NUMBER          | Estimate, by the cost-based optimizer, of the number of bytes produced by the operation                                                                                                                                                           |
| OTHER_TAG         | VARCHAR2 (35)   | Describes the contents of the OTHER column. See EXPLAIN PLAN for values.                                                                                                                                                                          |
| PARTITION_START   | VARCHAR2 (64)   | Start partition of a range of accessed partitions                                                                                                                                                                                                 |
| PARTITION_STOP    | VARCHAR2 (64)   | Stop partition of a range of accessed partitions                                                                                                                                                                                                  |
| PARTITION_ID      | NUMBER          | Step that computes the pair of values of the PARTITION_START and PARTITION_STOP columns                                                                                                                                                           |
| OTHER             | VARCHAR2 (4000) | Other information specific to the execution step that users may find useful. See EXPLAIN PLAN for values.                                                                                                                                         |
| DISTRIBUTION      | VARCHAR2 (20)   | Stores the method used to distribute rows from producer query servers to consumer query servers                                                                                                                                                   |
| CPU_COST          | NUMBER          | CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                                                              |
| IO_COST           | NUMBER          | I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                                                              |
| TEMP_SPACE        | NUMBER          | Temporary space usage of the operation (sort or hash-join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                             |
| ACCESS_PREDICATES | VARCHAR2 (4000) | Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.                                                                                                                             |
| FILTER_PREDICATES | VARCHAR2 (4000) | Predicates used to filter rows before producing them                                                                                                                                                                                              |
| PROJECTION        | VARCHAR2 (4000) | Expressions produced by the operation                                                                                                                                                                                                             |
| TIME              | NUMBER          | Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.                                                                             |
| QBLOCK_NAME       | VARCHAR2 (30)   | Name of the query block                                                                                                                                                                                                                           |
| REMARKS           | VARCHAR2 (4000) | Remarks                                                                                                                                                                                                                                           |

| Column                 | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OTHER_XML              | CLOB          | Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML since multiple pieces of information can be stored there. This includes: <ul style="list-style-type: none"> <li>■ Name of the schema against which the query was parsed</li> <li>■ Release number of the Oracle Database that produced the explain plan</li> <li>■ Hash value associated with the execution plan</li> <li>■ Name (if any) of the outline or the SQL profile used to build the execution plan</li> <li>■ Indication of whether or not dynamic sampling was used to produce the plan</li> <li>■ The outline data, a set of optimizer hints that can be used to regenerate the same plan</li> </ul> |
| EXECUTIONS             | NUMBER        | Number of times this cursor has been executed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| LAST_STARTS            | NUMBER        | Number of times this operation has been started, during the last execution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| STARTS                 | NUMBER        | Number of times this operation has been started, accumulated over the past executions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| LAST_OUTPUT_ROWS       | NUMBER        | Number of rows produced by the row source, during the last execution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| OUTPUT_ROWS            | NUMBER        | Number of rows produced by the row source, accumulated over the past executions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| LAST_CR_BUFFER_GETS    | NUMBER        | Number of buffers retrieved in consistent mode, during the last execution. Buffers are usually retrieved in consistent mode for queries.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| CR_BUFFER_GETS         | NUMBER        | Number of buffers retrieved in consistent mode, accumulated over the past executions. Buffers are usually retrieved in consistent mode for queries.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| LAST_CU_BUFFER_GETS    | NUMBER        | Number of buffers retrieved in current mode, during the last execution. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| CU_BUFFER_GETS         | NUMBER        | Number of buffers retrieved in current mode, accumulated over the past executions. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| LAST_DISK_READS        | NUMBER        | Number of physical disk reads performed by the operation, during the last execution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| DISK_READS             | NUMBER        | Number of physical disk reads performed by the operation, accumulated over the past executions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| LAST_DISK_WRITES       | NUMBER        | Number of physical disk writes performed by the operation, during the last execution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| DISK_WRITES            | NUMBER        | Number of physical disk writes performed by the operation, accumulated over the past executions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| LAST_ELAPSED_TIME      | NUMBER        | Elapsed time (in microseconds) corresponding to this operation, during the last execution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| ELAPSED_TIME           | NUMBER        | Elapsed time (in microseconds) corresponding to this operation, accumulated over the past executions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| POLICY                 | VARCHAR2 (10) | Sizing policy for this work area: <ul style="list-style-type: none"> <li>■ MANUAL</li> <li>■ AUTO</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| ESTIMATED_OPTIMAL_SIZE | NUMBER        | Estimated size (in KB) required by this work area to execute the operation completely in memory (optimal execution). This is either derived from optimizer statistics or from previous executions.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ESTIMATED_ONEPASS_SIZE | NUMBER        | Estimated size (in KB) required by this work area to execute the operation in a single pass. This is either derived from optimizer statistics or from previous executions.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| LAST_MEMORY_USED       | NUMBER        | Memory size (in KB) used by this work area during the last execution of the cursor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

| Column                 | Datatype      | Description                                                                                                                                                                   |
|------------------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAST_EXECUTION         | VARCHAR2 (10) | Indicates whether this work area ran using OPTIMAL, ONE PASS, or under ONE PASS memory requirement (MULTI-PASS), during the last execution of the cursor                      |
| LAST_DEGREE            | NUMBER        | Degree of parallelism used, during the last execution of the cursor                                                                                                           |
| TOTAL_EXECUTIONS       | NUMBER        | Number of times this work area was active                                                                                                                                     |
| OPTIMAL_EXECUTIONS     | NUMBER        | Number of times this work area ran in optimal mode                                                                                                                            |
| ONEPASS_EXECUTIONS     | NUMBER        | Number of times this work area ran in one pass mode                                                                                                                           |
| MULTIPASSES_EXECUTIONS | NUMBER        | Number of times this work area ran below the one pass memory requirement                                                                                                      |
| ACTIVE_TIME            | NUMBER        | Average time this work area is active (in hundredths of a second)                                                                                                             |
| MAX_TEMPSEG_SIZE       | NUMBER        | Maximum temporary segment size (in bytes) created by an instantiation of this work area. This column is null if this work area has never spilled to disk.                     |
| LAST_TEMPSEG_SIZE      | NUMBER        | Temporary segment size (in bytes) created in the last instantiation of this work area. This column is null if the last instantiation of this work area did not spill to disk. |

## V\$SQL\_REDIRECTION

V\$SQL\_REDIRECTION displays SQL statements that are redirected.

| Column            | Datatype        | Description                                                                                       |
|-------------------|-----------------|---------------------------------------------------------------------------------------------------|
| ADDRESS           | RAW (4   8)     | Address of the cursor handle                                                                      |
| PARENT_HANDLE     | RAW (4   8)     | Address of the parent cursor handle                                                               |
| HASH_VALUE        | NUMBER          | Hash value of the SQL statement                                                                   |
| SQL_ID            | VARCHAR2 (13)   | SQL identifier of the SQL statement                                                               |
| CHILD_NUMBER      | NUMBER          | Number of the child (instance) for the hash                                                       |
| PARSING_USER_ID   | NUMBER          | Parsing user ID                                                                                   |
| PARSING_SCHEMA_ID | NUMBER          | Parsing schema ID                                                                                 |
| COMMAND_TYPE      | NUMBER          | SELECT, UPDATE, INSERT, MERGE                                                                     |
| REASON            | VARCHAR2 (14)   | Reason for redirection ('INVALID OBJECT', 'ROWID', 'QUERY REWRITE', 'READ ONLY')                  |
| ERROR_CODE        | NUMBER          | Error code for local parse                                                                        |
| POSITION          | NUMBER          | Error position, 0 if unknown                                                                      |
| SQL_TEXT_PIECE    | VARCHAR2 (1000) | SQL Text containing position, usually a (qualified) identifier                                    |
| ERROR_MESSAGE     | VARCHAR2 (1000) | Error code's corresponding error message resolved in the database language, no arguments resolved |

## V\$SQL\_SHARED\_CURSOR

V\$SQL\_SHARED\_CURSOR explains why a particular child cursor is not shared with existing child cursors. Each column identifies a specific reason why the cursor cannot be shared.

| Column        | Datatype      | Description                  |
|---------------|---------------|------------------------------|
| SQL_ID        | VARCHAR2 (13) | SQL identifier               |
| ADDRESS       | RAW (4   8)   | Address of the parent cursor |
| CHILD_ADDRESS | RAW (4   8)   | Address of the child cursor  |

| Column                         | Datatype     | Description                                                                                                                                                                                       |
|--------------------------------|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CHILD_NUMBER                   | NUMBER       | Child number                                                                                                                                                                                      |
| UNBOUND_CURSOR                 | VARCHAR2 (1) | (Y   N) The existing child cursor was not fully built (in other words, it was not optimized)                                                                                                      |
| SQL_TYPE_MISMATCH              | VARCHAR2 (1) | (Y   N) The SQL type does not match the existing child cursor                                                                                                                                     |
| OPTIMIZER_MISMATCH             | VARCHAR2 (1) | (Y   N) The optimizer environment does not match the existing child cursor                                                                                                                        |
| OUTLINE_MISMATCH               | VARCHAR2 (1) | (Y   N) The outlines do not match the existing child cursor                                                                                                                                       |
| STATS_ROW_MISMATCH             | VARCHAR2 (1) | (Y   N) The existing statistics do not match the existing child cursor                                                                                                                            |
| LITERAL_MISMATCH               | VARCHAR2 (1) | (Y   N) Non-data literal values do not match the existing child cursor                                                                                                                            |
| FORCE_HARD_PARSE               | VARCHAR2 (1) | (Y   N) For internal use                                                                                                                                                                          |
| EXPLAIN_PLAN_CURSOR            | VARCHAR2 (1) | (Y   N) The child cursor is an explain plan cursor and should not be shared                                                                                                                       |
| BUFFERED_DML_MISMATCH          | VARCHAR2 (1) | (Y   N) Buffered DML does not match the existing child cursor                                                                                                                                     |
| PDML_ENV_MISMATCH              | VARCHAR2 (1) | (Y   N) PDML environment does not match the existing child cursor                                                                                                                                 |
| INST_DRTLD_MISMATCH            | VARCHAR2 (1) | (Y   N) Insert direct load does not match the existing child cursor                                                                                                                               |
| SLAVE_QC_MISMATCH              | VARCHAR2 (1) | (Y   N) The existing child cursor is a slave cursor and the new one was issued by the coordinator (or, the existing child cursor was issued by the coordinator and the new one is a slave cursor) |
| TYPECHECK_MISMATCH             | VARCHAR2 (1) | (Y   N) The existing child cursor is not fully optimized                                                                                                                                          |
| AUTH_CHECK_MISMATCH            | VARCHAR2 (1) | (Y   N) Authorization/translation check failed for the existing child cursor                                                                                                                      |
| BIND_MISMATCH                  | VARCHAR2 (1) | (Y   N) The bind metadata does not match the existing child cursor                                                                                                                                |
| DESCRIBE_MISMATCH              | VARCHAR2 (1) | (Y   N) The typecheck heap is not present during the describe for the child cursor                                                                                                                |
| LANGUAGE_MISMATCH              | VARCHAR2 (1) | (Y   N) The language handle does not match the existing child cursor                                                                                                                              |
| TRANSLATION_MISMATCH           | VARCHAR2 (1) | (Y   N) The base objects of the existing child cursor do not match                                                                                                                                |
| BIND_EQUIV_FAILURE             | VARCHAR2 (1) | (Y   N) The bind value's selectivity does not match that used to optimize the existing child cursor                                                                                               |
| INSUFF_PRIVS                   | VARCHAR2 (1) | (Y   N) Insufficient privileges on objects referenced by the existing child cursor                                                                                                                |
| INSUFF_PRIVS_REM               | VARCHAR2 (1) | (Y   N) Insufficient privileges on remote objects referenced by the existing child cursor                                                                                                         |
| REMOTE_TRANS_MISMATCH          | VARCHAR2 (1) | (Y   N) The remote base objects of the existing child cursor do not match                                                                                                                         |
| LOGMINER_SESSION_MISMATCH      | VARCHAR2 (1) | (Y   N) LogMiner Session parameters mismatch                                                                                                                                                      |
| INCOMP_LTRL_MISMATCH           | VARCHAR2 (1) | (Y   N) Cursor might have some binds (literals) which may be unsafe/non-data. Value mismatch.                                                                                                     |
| OVERLAP_TIME_MISMATCH          | VARCHAR2 (1) | (Y   N) Mismatch caused by setting session parameter ERROR_ON_OVERLAP_TIME                                                                                                                        |
| EDITION_MISMATCH               | VARCHAR2 (1) | (Y   N) Cursor edition mismatch                                                                                                                                                                   |
| MV_QUERY_GEN_MISMATCH          | VARCHAR2 (1) | (Y   N) Internal, used to force a hard-parse when analyzing materialized view queries                                                                                                             |
| USER_BIND_PEEK_MISMATCH        | VARCHAR2 (1) | (Y   N) Cursor is not shared because value of one or more user binds is different and this has a potential to change the execution plan                                                           |
| TPCHK_DEP_MISMATCH             | VARCHAR2 (1) | (Y   N) Cursor has typecheck dependencies                                                                                                                                                         |
| NO_TRIGGER_MISMATCH            | VARCHAR2 (1) | (Y   N) Cursor and child have no trigger mismatch                                                                                                                                                 |
| FLASHBACK_CURSOR               | VARCHAR2 (1) | (Y   N) Cursor non-shareability due to flashback                                                                                                                                                  |
| ANYDATA_TRANSFORMATION         | VARCHAR2 (1) | (Y   N) Is criteria for opaque type transformation and does not match                                                                                                                             |
| INCOMPLETE_CURSOR <sup>1</sup> | VARCHAR2 (1) | (Y   N) Cursor is incomplete: typecheck heap came from call memory                                                                                                                                |

| Column                         | Datatype     | Description                                                                                                                                                                                                                                     |
|--------------------------------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PDDL_ENV_MISMATCH <sup>2</sup> | VARCHAR2 (1) | (Y   N) Environment setting mismatch for parallel DDL cursor (that is, one or more of the following parameter values have changed: PARALLEL_EXECUTION_ENABLED, PARALLEL_DDL_MODE, PARALLEL_DDL_FORCED_DEGREE, or PARALLEL_DDL_FORCED_INSTANCES) |
| TOP_LEVEL_RPI_CURSOR           | VARCHAR2 (1) | (Y   N) Is top level RPI cursor                                                                                                                                                                                                                 |
| DIFFERENT_LONG_LENGTH          | VARCHAR2 (1) | (Y   N) Value of LONG does not match                                                                                                                                                                                                            |
| LOGICAL_STANDBY_APPLY          | VARCHAR2 (1) | (Y   N) Logical standby apply context does not match                                                                                                                                                                                            |
| DIFF_CALL_DURN                 | VARCHAR2 (1) | (Y   N) If Slave SQL cursor/single call                                                                                                                                                                                                         |
| BIND_UACS_DIFF                 | VARCHAR2 (1) | (Y   N) One cursor has bind UACs and one does not                                                                                                                                                                                               |
| PLSQL_CMP_SWITCHS_DIFF         | VARCHAR2 (1) | (Y   N) PL/SQL anonymous block compiled with different PL/SQL compiler switches                                                                                                                                                                 |
| CURSOR_PARTS_MISMATCH          | VARCHAR2 (1) | (Y   N) Cursor was compiled with subexecution (cursor parts were executed)                                                                                                                                                                      |
| STB_OBJECT_MISMATCH            | VARCHAR2 (1) | (Y   N) STB has come into existence since cursor was compiled                                                                                                                                                                                   |
| CROSSEDITION_TRIGGER_MISMATCH  | VARCHAR2(1)  | (Y   N) The set of crossedition triggers to execute might differ                                                                                                                                                                                |
| PQ_SLAVE_MISMATCH              | VARCHAR2 (1) | (Y   N) Top-level slave decides not to share cursor                                                                                                                                                                                             |
| TOP_LEVEL_DDL_MISMATCH         | VARCHAR2 (1) | (Y   N) Is top-level DDL cursor                                                                                                                                                                                                                 |
| MULTI_PX_MISMATCH              | VARCHAR2 (1) | (Y   N) Cursor has multiple parallelizers and is slave-compiled                                                                                                                                                                                 |
| BIND_PEEKED_PQ_MISMATCH        | VARCHAR2 (1) | (Y   N) Cursor based around bind peeked values                                                                                                                                                                                                  |
| MV_REWRITE_MISMATCH            | VARCHAR2 (1) | (Y   N) Cursor needs recompilation because an SCN was used during compile time due to being rewritten by materialized view                                                                                                                      |
| ROLL_INVALID_MISMATCH          | VARCHAR2 (1) | (Y   N) Marked for rolling invalidation and invalidation window exceeded                                                                                                                                                                        |
| OPTIMIZER_MODE_MISMATCH        | VARCHAR2 (1) | (Y   N) Parameter OPTIMIZER_MODE mismatch (for example, all_rows versus first_rows_1)                                                                                                                                                           |
| PX_MISMATCH                    | VARCHAR2 (1) | (Y   N) Mismatch in one parameter affecting the parallelization of a SQL statement. For example, one cursor was compiled with parallel DML enabled while the other was not.                                                                     |
| MV_STALEOBJ_MISMATCH           | VARCHAR2 (1) | (Y   N) Cursor cannot be shared because there is a mismatch in the list of materialized views which were stale at the time the cursor was built                                                                                                 |
| FLASHBACK_TABLE_MISMATCH       | VARCHAR2 (1) | (Y   N) Cursor cannot be shared because there is a mismatch with triggers being enabled and/or referential integrity constraints being deferred                                                                                                 |
| LITREP_COMP_MISMATCH           | VARCHAR2 (1) | (Y   N) Mismatch in use of literal replacement                                                                                                                                                                                                  |
| PLSQL_DEBUG                    | VARCHAR2 (1) | (Y   N) Value of the PLSQL_DEBUG parameter for the current session does not match the value used to build the cursor                                                                                                                            |
| LOAD_OPTIMIZER_STATS           | VARCHAR2 (1) | (Y   N) A hard parse is forced in order to initialize extended cursor sharing                                                                                                                                                                   |
| ACL_MISMATCH                   | VARCHAR2 (1) | (Y   N) Cached ACL evaluation result stored in the child cursor is not valid for the current session or user                                                                                                                                    |
| FLASHBACK_ARCHIVE_MISMATCH     | VARCHAR2 (1) | (Y   N) Value of the FLASHBACK_DATA_ARCHIVE_INTERNAL_CURSOR parameter for the current session does not match the value used to build the cursor                                                                                                 |
| LOCK_USER_SCHEMA_FAILED        | VARCHAR2 (1) | (Y   N) User or schema used to build the cursor no longer exists<br><b>Note:</b> This sharing criterion is deprecated                                                                                                                           |
| REMOTE_MAPPING_MISMATCH        | VARCHAR2 (1) | (Y   N) Reloaded cursor was previously remote-mapped and is currently not remote-mapped. Therefore, the cursor needs to be reparsed.                                                                                                            |
| LOAD_RUNTIME_HEAP_FAILED       | VARCHAR2 (1) | (Y   N) Loading of runtime heap for the new cursor (or reload of aged out cursor) failed                                                                                                                                                        |
| HASH_MATCH_FAILED              | VARCHAR2 (1) | (Y   N) No existing child cursors have the unsafe literal bind hash values required by the current cursor                                                                                                                                       |

| Column                          | Datatype     | Description                                                                                                              |
|---------------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------|
| PURGED_CURSOR                   | VARCHAR2 (1) | (Y   N) Child cursor is marked for purging                                                                               |
| BIND_LENGTH_UPGRADEABLE         | VARCHAR2 (1) | (Y   N) Bind length(s) required for the current cursor are longer than the bind length(s) used to build the child cursor |
| USE_FEEDBACK_STATS <sup>2</sup> | VARCHAR2 (1) | (Y   N) A hard parse is forced so that the optimizer can reoptimize the query with improved cardinality estimates        |
| REASON <sup>2</sup>             | CLOB         | Child number, id, and reason the cursor is not shared. The content of this column is structured using XML.               |

<sup>1</sup> This column is not available starting with Oracle Database 11g Release 2 (11.2.0.2).

<sup>2</sup> This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

## V\$SQL\_SHARED\_MEMORY

V\$SQL\_SHARED\_MEMORY displays information about the cursor shared memory snapshot. Each SQL statement stored in the shared pool has one or more child objects associated with it. Each child object has a number of parts, one of which is the context heap, which holds, among other things, the query plan.

| Column       | Datatype        | Description                                                                                                                                                                                    |
|--------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SQL_TEXT     | VARCHAR2 (1000) | SQL text of the shared cursor child object for which this row is displaying information                                                                                                        |
| SQL_FULLTEXT | CLOB            | Full text for the SQL statement exposed as a CLOB column. The full text of a SQL statement can be retrieved using this column instead of joining with the V\$SQLTEXT dynamic performance view. |
| HASH_VALUE   | NUMBER          | Hash value of the above SQL text in the shared pool                                                                                                                                            |
| SQL_ID       | VARCHAR2 (13)   | SQL identifier of the above SQL text in the shared pool                                                                                                                                        |
| HEAP_DESC    | RAW (4   8)     | Address of the descriptor for the context heap of the child cursor described in this row                                                                                                       |
| STRUCTURE    | VARCHAR2 (16)   | If the memory chunk described in this row was allocated using a comment of the form "X : Y", then this is the "X" part of the comment                                                          |
| FUNCTION     | VARCHAR2 (16)   | Similar to the STRUCTURE column, this is the "Y" field of the comment                                                                                                                          |
| CHUNK_COM    | VARCHAR2 (16)   | Whole comment field that was supplied when this memory chunk was allocated                                                                                                                     |
| CHUNK_PTR    | RAW (4   8)     | Starting address of the allocated memory chunk                                                                                                                                                 |
| CHUNK_SIZE   | NUMBER          | Amount of memory allocated for this chunk                                                                                                                                                      |
| ALLOC_CLASS  | VARCHAR2 (8)    | Class of memory that this chunk of memory belongs to. It will usually be either FREEABLE or PERMANENT.                                                                                         |
| CHUNK_TYPE   | NUMBER          | An index into a table of callback functions that tell the server how to re-create this chunk of memory should it need to be removed from the shared pool based on an LRU algorithm             |
| SUBHEAP_DESC | RAW (4   8)     | If the parent heap of this context heap is itself a subheap, then this is the address of the descriptor of the parent heap                                                                     |

## V\$SQL\_WORKAREA

V\$SQL\_WORKAREA displays information about work areas used by SQL cursors. Each SQL statement stored in the shared pool has one or more child cursors that are listed in the V\$SQL view. V\$SQL\_WORKAREA lists all work areas needed by these child cursors; V\$SQL\_WORKAREA can be joined with V\$SQLAREA on (ADDRESS, HASH\_VALUE) and with V\$SQL on (ADDRESS, HASH\_VALUE, CHILD\_NUMBER).

You can use this view to find out answers to the following questions:

- What are the top 10 work areas that require the most cache area?

- For work areas allocated in AUTO mode, what percentage of work areas are running using maximum memory?

| Column                 | Datatype      | Description                                                                                                                                                                              |
|------------------------|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADDRESS                | RAW (4   8)   | Address of the parent cursor handle                                                                                                                                                      |
| HASH_VALUE             | NUMBER        | Hash value of the parent statement in the library cache. Two columns PARENT_HANDLE and HASH_VALUE can be used to join with V\$SQLAREA to locate the parent cursor.                       |
| SQL_ID                 | VARCHAR2 (13) | SQL identifier of the parent statement in the library cache                                                                                                                              |
| CHILD_NUMBER           | NUMBER        | Number of the child cursor that uses this work area. The columns PARENT_HANDLE, HASH_VALUE, and CHILD_NUMBER can be used to join with V\$SQL to locate the child cursor using this area. |
| WORKAREA_ADDRESS       | RAW (4   8)   | Address of the work area handle. This is the primary key for the view.                                                                                                                   |
| OPERATION_TYPE         | VARCHAR2 (20) | Type of operation using the work area (SORT, HASH JOIN, GROUP BY, BUFFERING, BITMAP MERGE, or BITMAP CREATE)                                                                             |
| OPERATION_ID           | NUMBER        | A unique number used to identify the operation in the execution plan. This identifier can be joined to V\$SQL_PLAN to locate the operation that uses this work area.                     |
| POLICY                 | VARCHAR2 (10) | Sizing policy for this work area (MANUAL or AUTO)                                                                                                                                        |
| ESTIMATED_OPTIMAL_SIZE | NUMBER        | Estimated size (in bytes) required by this work area to execute the operation completely in memory (optimal execution). Derived from either optimizer statistics or previous executions. |
| ESTIMATED_ONEPASS_SIZE | NUMBER        | Estimated size (in bytes) required by this work area to execute the operation in a single pass. Derived from either optimizer statistics or previous executions.                         |
| LAST_MEMORY_USED       | NUMBER        | Memory (in bytes) used by this work area during the last execution of the cursor                                                                                                         |
| LAST_EXECUTION         | VARCHAR2 (10) | Indicates whether this work area runs using OPTIMAL, ONE PASS, or ONE PASS memory requirement (or MULTI-PASS), during the last execution of the cursor                                   |
| LAST_DEGREE            | NUMBER        | Degree of parallelism used during the last execution of this operation                                                                                                                   |
| TOTAL_EXECUTIONS       | NUMBER        | Number of times this work area was active                                                                                                                                                |
| OPTIMAL_EXECUTIONS     | NUMBER        | Number of times this work area ran in optimal mode                                                                                                                                       |
| ONEPASS_EXECUTIONS     | NUMBER        | Number of times this work area ran in one-pass mode                                                                                                                                      |
| MULTIPASSES_EXECUTIONS | NUMBER        | Number of times this work area ran below the one-pass memory requirement                                                                                                                 |
| ACTIVE_TIME            | NUMBER        | Average time this work area is active (in hundredths of a second)                                                                                                                        |
| MAX_TEMPSEG_SIZE       | NUMBER        | Maximum temporary segment size (in bytes) created by an instantiation of this work area. This column is NULL if this work area has never spilled to disk.                                |
| LAST_TEMPSEG_SIZE      | NUMBER        | Temporary segment size (in bytes) created in the last instantiation of this work area. This column is NULL if the last instantiation of this work area did not spill to disk.            |

## V\$SQL\_WORKAREA\_ACTIVE

V\$SQL\_WORKAREA\_ACTIVE contains an instantaneous view of the work areas currently allocated by the system. You can join this view against V\$SQL\_WORKAREA on WORKAREA\_ADDRESS to access the definition of that work area. If a work area spills to disk, then this view contains information for the temporary segment created on behalf of this work area.

The last three columns are included to enable joining V\$SQL\_WORKAREA\_ACTIVE with V\$TEMPSEG\_USAGE to retrieve more information on this temporary segment.



You can use this view to answer the following:

- What are the top 10 largest work areas currently allocated in the system?
- What percentage of memory is over-allocated (`EXPECTED_SIZE < ACTUAL_MEM_USED`) and under-allocated (`EXPECTED_SIZE > ACTUAL_MEM_USED`)?
- What are the active work areas using more memory than what is expected by the memory manager?
- What are the active work areas that have spilled to disk?

| Column           | Datatype      | Description                                                                                                                                                                                                                                                                                        |
|------------------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SQL_HASH_VALUE   | NUMBER        | Hash value of the SQL statement that is currently being executed                                                                                                                                                                                                                                   |
| SQL_ID           | VARCHAR2 (13) | SQL identifier of the SQL statement that is currently being executed                                                                                                                                                                                                                               |
| SQL_EXEC_START   | DATE          | Time when the execution of the SQL currently executed by this session started                                                                                                                                                                                                                      |
| SQL_EXEC_ID      | NUMBER        | SQL execution identifier (see V\$SQL_MONITOR)                                                                                                                                                                                                                                                      |
| WORKAREA_ADDRESS | RAW (4   8)   | Address of the work area handle. This is the primary key for the view.                                                                                                                                                                                                                             |
| OPERATION_TYPE   | VARCHAR2 (20) | Type of operation using the work area (SORT, HASH JOIN, GROUP BY, BUFFERING, BITMAP MERGE, or BITMAP CREATE)                                                                                                                                                                                       |
| OPERATION_ID     | NUMBER        | A unique number used to identify the operation in the execution plan. This identifier can be joined to V\$SQL_PLAN to locate the operation that uses this work area.                                                                                                                               |
| POLICY           | VARCHAR2 (6)  | Sizing policy for this work area (MANUAL or AUTO)                                                                                                                                                                                                                                                  |
| SID              | NUMBER        | Session identifier                                                                                                                                                                                                                                                                                 |
| QCINST_ID        | NUMBER        | Query coordinator instance identifier. Along with QCSID, enables you to uniquely identify the query coordinator.                                                                                                                                                                                   |
| QCSID            | NUMBER        | Query coordinator session identifier. This is the same as the SID if the work area is allocated by a serial cursor.                                                                                                                                                                                |
| ACTIVE_TIME      | NUMBER        | Average time this work area is active (in hundredths of a second)                                                                                                                                                                                                                                  |
| WORK_AREA_SIZE   | NUMBER        | Maximum size (in bytes) of the work area as it is currently used by the operation                                                                                                                                                                                                                  |
| EXPECTED_SIZE    | NUMBER        | Expected size (in bytes) for this work area. EXPECTED_SIZE is set on behalf of the operation by the memory manager. Memory can be over-allocated when WORK_AREA_SIZE has a higher value than EXPECTED_SIZE. This can occur when the operation using this work area takes a long time to resize it. |
| ACTUAL_MEM_USED  | NUMBER        | Amount of PGA memory (in bytes) currently allocated on behalf of this work area. This value should range between 0 and WORK_AREA_SIZE.                                                                                                                                                             |
| MAX_MEM_USED     | NUMBER        | Maximum memory amount (in bytes) used by this work area                                                                                                                                                                                                                                            |
| NUMBER_PASSES    | NUMBER        | Number of passes corresponding to this work area (0 if running in OPTIMAL mode)                                                                                                                                                                                                                    |
| TEMPSEG_SIZE     | NUMBER        | Size (in bytes) of the temporary segment used on behalf of this work area. This column is NULL if this work area has not (yet) spilled to disk.                                                                                                                                                    |
| TABLESPACE       | VARCHAR2 (30) | Tablespace name for the temporary segment created on behalf of this work area. This column is NULL if this work area has not (yet) spilled to disk.                                                                                                                                                |
| SEGRFNO#         | NUMBER        | Relative file number within the tablespace for the temporary segment created on behalf of this work area. This column is NULL if this work area has not (yet) spilled to disk.                                                                                                                     |
| SEGBLK#          | NUMBER        | Block number for the temporary segment created on behalf of this work area. This column is NULL if this work area has not (yet) spilled to disk.                                                                                                                                                   |

**See Also:** *Oracle Database Performance Tuning Guide* for more information on how to monitor SQL work areas

## V\$SQL\_WORKAREA\_HISTOGRAM

V\$SQL\_WORKAREA\_HISTOGRAM displays the cumulative work area execution statistics (cumulated since instance startup) for different work area groups. The work areas are split into 33 groups based on their optimal memory requirements with the requirements increasing in powers of two. That is, work areas whose optimal requirement varies from 0 KB to 1 KB, 1 KB to 2 KB, 2 KB to 4 KB, ... and 2 TB to 4 TB.

For each work area group, the V\$SQL\_WORKAREA\_HISTOGRAM view shows how many work areas in that group were able to run in optimal mode, how many were able to run in one-pass mode, and finally how many ran in multi-pass mode. The DBA can take a snapshot at the beginning and the end of a desired time interval to derive the same statistics for that interval.

| Column                 | Datatype | Description                                                                                                                                                                         |
|------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOW_OPTIMAL_SIZE       | NUMBER   | Lower bound for the optimal memory requirement of work areas included in this row (bytes)                                                                                           |
| HIGH_OPTIMAL_SIZE      | NUMBER   | Upper bound for the optimal memory requirement of work areas included in this row (bytes)                                                                                           |
| OPTIMAL_EXECUTIONS     | NUMBER   | Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which have been executed in optimal mode since instance startup    |
| ONEPASS_EXECUTIONS     | NUMBER   | Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which have been executed in one-pass mode since instance startup   |
| MULTIPASSES_EXECUTIONS | NUMBER   | Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which have been executed in multi-pass mode since instance startup |
| TOTAL_EXECUTIONS       | NUMBER   | Sum of OPTIMAL_EXECUTIONS, ONEPASS_EXECUTIONS, and MULTIPASSES_EXECUTIONS                                                                                                           |

**See Also:** *Oracle Database Performance Tuning Guide* for detailed information on how to monitor automatic PGA memory performance using this view

## V\$SQLAREA

V\$SQLAREA displays statistics on shared SQL areas and contains one row per SQL string. It provides statistics on SQL statements that are in memory, parsed, and ready for execution.

| Column         | Datatype       | Description                                                                                                                                                                         |
|----------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SQL_TEXT       | VARCHAR2(1000) | First thousand characters of the SQL text for the current cursor                                                                                                                    |
| SQL_FULLTEXT   | CLOB           | All characters of the SQL text for the current cursor                                                                                                                               |
| SQL_ID         | VARCHAR2(13)   | SQL identifier of the parent cursor in the library cache                                                                                                                            |
| SHARABLE_MEM   | NUMBER         | Amount of shared memory used by a cursor. If multiple child cursors exist, then the sum of all shared memory used by all child cursors.                                             |
| PERSISTENT_MEM | NUMBER         | Fixed amount of memory used for the lifetime of an open cursor. If multiple child cursors exist, then the fixed sum of memory used for the lifetime of all the child cursors.       |
| RUNTIME_MEM    | NUMBER         | Fixed amount of memory required during execution of a cursor. If multiple child cursors exist, then the fixed sum of all memory required during execution of all the child cursors. |
| SORTS          | NUMBER         | Sum of the number of sorts that were done for all the child cursors                                                                                                                 |
| VERSION_COUNT  | NUMBER         | Number of child cursors that are present in the cache under this parent                                                                                                             |

| Column                   | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOADED_VERSIONS          | NUMBER        | Number of child cursors that are present in the cache and have their context heap loaded                                                                                                                                                                                                                                                                                                                                                                                            |
| OPEN_VERSIONS            | NUMBER        | Number of child cursors that are currently open under this current parent                                                                                                                                                                                                                                                                                                                                                                                                           |
| USERS_OPENING            | NUMBER        | Number of users that have any of the child cursors open                                                                                                                                                                                                                                                                                                                                                                                                                             |
| FETCHES                  | NUMBER        | Number of fetches associated with the SQL statement                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| EXECUTIONS               | NUMBER        | Total number of executions, totalled over all the child cursors                                                                                                                                                                                                                                                                                                                                                                                                                     |
| PX_SERVERS_EXECUTIONS    | NUMBER        | Total number of executions performed by parallel execution servers (0 when the statement has never been executed in parallel)                                                                                                                                                                                                                                                                                                                                                       |
| END_OF_FETCH_COUNT       | NUMBER        | Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column. |
| USERS_EXECUTING          | NUMBER        | Total number of users executing the statement over all child cursors                                                                                                                                                                                                                                                                                                                                                                                                                |
| LOADS                    | NUMBER        | Number of times the object was loaded or reloaded                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| FIRST_LOAD_TIME          | VARCHAR2 (19) | Timestamp of the parent creation time                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| INVALIDATIONS            | NUMBER        | Total number of invalidations over all the child cursors                                                                                                                                                                                                                                                                                                                                                                                                                            |
| PARSE_CALLS              | NUMBER        | Sum of all parse calls to all the child cursors under this parent                                                                                                                                                                                                                                                                                                                                                                                                                   |
| DISK_READS               | NUMBER        | Sum of the number of disk reads over all child cursors                                                                                                                                                                                                                                                                                                                                                                                                                              |
| DIRECT_WRITES            | NUMBER        | Sum of the number of direct writes over all child cursors                                                                                                                                                                                                                                                                                                                                                                                                                           |
| BUFFER_GETS              | NUMBER        | Sum of buffer gets over all child cursors                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| APPLICATION_WAIT_TIME    | NUMBER        | Application wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CONCURRENCY_WAIT_TIME    | NUMBER        | Concurrency wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CLUSTER_WAIT_TIME        | NUMBER        | Cluster wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| USER_IO_WAIT_TIME        | NUMBER        | User I/O Wait Time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| PLSQL_EXEC_TIME          | NUMBER        | PL/SQL execution time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| JAVA_EXEC_TIME           | NUMBER        | Java execution time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| ROWS_PROCESSED           | NUMBER        | Total number of rows processed on behalf of this SQL statement                                                                                                                                                                                                                                                                                                                                                                                                                      |
| COMMAND_TYPE             | NUMBER        | Oracle command type definition                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| OPTIMIZER_MODE           | VARCHAR2 (10) | Mode under which the SQL statement was executed                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| OPTIMIZER_COST           | NUMBER        | Cost of this query given by the optimizer                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| OPTIMIZER_ENV            | RAW (2000)    | Optimizer environment                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| OPTIMIZER_ENV_HASH_VALUE | NUMBER        | Hash value for the optimizer environment                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| PARSING_USER_ID          | NUMBER        | User ID of the user that has parsed the very first cursor under this parent                                                                                                                                                                                                                                                                                                                                                                                                         |
| PARSING_SCHEMA_ID        | NUMBER        | Schema ID that was used to parse this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| PARSING_SCHEMA_NAME      | VARCHAR2 (30) | Schema name that was used to parse this child cursor                                                                                                                                                                                                                                                                                                                                                                                                                                |
| KEPT_VERSIONS            | NUMBER        | Number of child cursors that have been marked to be kept using the DBMS_SHARED_POOL package                                                                                                                                                                                                                                                                                                                                                                                         |
| ADDRESS                  | RAW (4   8)   | Address of the handle to the parent for this cursor                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| HASH_VALUE               | NUMBER        | Hash value of the parent statement in the library cache                                                                                                                                                                                                                                                                                                                                                                                                                             |
| OLD_HASH_VALUE           | NUMBER        | Old SQL hash value                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| PLAN_HASH_VALUE          | NUMBER        | Numeric representation of the SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).                                                                                                                                                                                                                                                                        |

| Column                    | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MODULE                    | VARCHAR2 (64) | Contains the name of the module that was executing at the time that the SQL statement was first parsed as set by calling DBMS_APPLICATION_INFO.SET_MODULE                                                                                                                                                                                                                                                                     |
| MODULE_HASH               | NUMBER        | Hash value of the module that is named in the MODULE column                                                                                                                                                                                                                                                                                                                                                                   |
| ACTION                    | VARCHAR2 (64) | Contains the name of the action that was executing at the time that the SQL statement was first parsed as set by calling DBMS_APPLICATION_INFO.SET_ACTION                                                                                                                                                                                                                                                                     |
| ACTION_HASH               | NUMBER        | Hash value of the action that is named in the ACTION column                                                                                                                                                                                                                                                                                                                                                                   |
| SERIALIZABLE_ABORTS       | NUMBER        | Number of times the transaction failed to serialize, producing ORA-08177 errors, totalled over all the child cursors                                                                                                                                                                                                                                                                                                          |
| OUTLINE_CATEGORY          | VARCHAR2 (64) | If an outline was applied during construction of the cursor, then this column displays the category of that outline. Otherwise the column is left blank.                                                                                                                                                                                                                                                                      |
| CPU_TIME                  | NUMBER        | CPU time (in microseconds) used by this cursor for parsing, executing, and fetching                                                                                                                                                                                                                                                                                                                                           |
| ELAPSED_TIME              | NUMBER        | Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching                                                                                                                                                                                                                                                                                                                                       |
| OUTLINE_SID               | VARCHAR2 (40) | Outline session identifier                                                                                                                                                                                                                                                                                                                                                                                                    |
| LAST_ACTIVE_CHILD_ADDRESS | RAW (4   8)   | Address (identifier) of the child cursor that was the last to be active in the group (that is, the child cursor on behalf of which statistics in V\$SQL were updated)                                                                                                                                                                                                                                                         |
| REMOTE                    | VARCHAR2 (1)  | Indicates whether the cursor is remote mapped (Y) or not (N)                                                                                                                                                                                                                                                                                                                                                                  |
| OBJECT_STATUS             | VARCHAR2 (19) | Status of the cursor: <ul style="list-style-type: none"> <li>VALID - Valid, authorized without errors</li> <li>VALID_AUTH_ERROR - Valid, authorized with authorization errors</li> <li>VALID_COMPILE_ERROR - Valid, authorized with compilation errors</li> <li>VALID_UNAUTH - Valid, unauthorized</li> <li>INVALID_UNAUTH - Invalid, unauthorized</li> <li>INVALID - Invalid, unauthorized but keep the timestamp</li> </ul> |
| LITERAL_HASH_VALUE        | NUMBER        | Hash value of the literals which are replaced with system-generated bind variables and are to be matched, when CURSOR_SHARING is used. This is not the hash value for the SQL statement. If CURSOR_SHARING is not used, then the value is 0.                                                                                                                                                                                  |
| LAST_LOAD_TIME            | DATE          | Time at which the query plan was loaded into the library cache                                                                                                                                                                                                                                                                                                                                                                |
| IS_OBSOLETE               | VARCHAR2 (1)  | Indicates whether the cursor has become obsolete (Y) or not (N). This can happen if the number of child cursors is too large.                                                                                                                                                                                                                                                                                                 |
| IS_BIND_SENSITIVE         | VARCHAR2 (1)  | Indicates whether the cursor is bind sensitive (Y) or not (N). A query is considered bind-sensitive if the optimizer peeked at one of its bind variable values when computing predicate selectivities and where a change in a bind variable value may cause the optimizer to generate a different plan.                                                                                                                       |
| IS_BIND_AWARE             | VARCHAR2 (1)  | Indicates whether the cursor is bind aware (Y) or not (N). A query is considered bind-aware if it has been marked to use extended cursor sharing. The query would already have been marked as bind-sensitive.                                                                                                                                                                                                                 |
| CHILD_LATCH               | NUMBER        | Child latch number that is protecting the cursor. This column is obsolete and maintained for backward compatibility.                                                                                                                                                                                                                                                                                                          |
| SQL_PROFILE               | VARCHAR2 (64) | SQL profile used for this statement, if any                                                                                                                                                                                                                                                                                                                                                                                   |
| SQL_PATCH                 | VARCHAR2 (30) | SQL patch used for this statement, if any                                                                                                                                                                                                                                                                                                                                                                                     |
| SQL_PLAN_BASELINE         | VARCHAR2 (30) | SQL plan baseline used for this statement, if any                                                                                                                                                                                                                                                                                                                                                                             |
| PROGRAM_ID                | NUMBER        | Program identifier                                                                                                                                                                                                                                                                                                                                                                                                            |
| PROGRAM_LINE#             | NUMBER        | Program line number                                                                                                                                                                                                                                                                                                                                                                                                           |
| EXACT_MATCHING_SIGNATURE  | NUMBER        | Signature used when the CURSOR_SHARING parameter is set to EXACT                                                                                                                                                                                                                                                                                                                                                              |

| Column                         | Datatype  | Description                                                                                                                                                                                            |
|--------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FORCE_MATCHING_SIGNATURE       | NUMBER    | Signature used when the CURSOR_SHARING parameter is set to FORCE                                                                                                                                       |
| LAST_ACTIVE_TIME               | DATE      | Time at which the query plan was last active                                                                                                                                                           |
| BIND_DATA                      | RAW(2000) | Bind data                                                                                                                                                                                              |
| TYPECHECK_MEM                  | NUMBER    | Typecheck memory                                                                                                                                                                                       |
| IO_CELL_OFFLOAD_ELIGIBLE_BYTES | NUMBER    | Number of I/O bytes which can be filtered by the Exadata storage system<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information                                  |
| IO_INTERCONNECT_BYTES          | NUMBER    | Number of I/O bytes exchanged between Oracle Database and the storage system                                                                                                                           |
| PHYSICAL_READ_REQUESTS         | NUMBER    | Number of physical read I/O requests issued by the monitored SQL                                                                                                                                       |
| PHYSICAL_READ_BYTES            | NUMBER    | Number of bytes read from disks by the monitored SQL                                                                                                                                                   |
| PHYSICAL_WRITE_REQUESTS        | NUMBER    | Number of physical write I/O requests issued by the monitored SQL                                                                                                                                      |
| PHYSICAL_WRITE_BYTES           | NUMBER    | Number of bytes written to disks by the monitored SQL                                                                                                                                                  |
| OPTIMIZED_PHY_READ_REQUESTS    | NUMBER    | Number of physical read I/O requests from Database Smart Flash Cache issued by the monitored SQL                                                                                                       |
| LOCKED_TOTAL                   | NUMBER    | Total number of times the child cursor has been locked                                                                                                                                                 |
| PINNED_TOTAL                   | NUMBER    | Total number of times the child cursor has been pinned                                                                                                                                                 |
| IO_CELL_UNCOMPRESSED_BYTES     | NUMBER    | Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information |
| IO_CELL_OFFLOAD_RETURNED_BYTES | NUMBER    | Number of bytes that are returned by Exadata cell through the regular I/O path<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information                           |

## V\$SQLAREA\_PLAN\_HASH

V\$SQLAREA\_PLAN\_HASH displays statistics on shared SQL areas (V\$SQL) by grouping on the SQL\_ID and PLAN\_HASH\_VALUE columns. It can potentially create several rows for one parent cursor, one for each distinct value of the column PLAN\_HASH\_VALUE.

| Column                    | Datatype       | Description                                                                                                                                                                                                  |
|---------------------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SQL_TEXT                  | VARCHAR2(1000) | First thousand characters of the SQL text for the current cursor                                                                                                                                             |
| SQL_FULLTEXT              | CLOB           | All characters of the SQL text for the current cursor                                                                                                                                                        |
| ADDRESS                   | RAW(4   8)     | Address of the handle to the parent for this cursor                                                                                                                                                          |
| HASH_VALUE                | NUMBER         | Hash value of the parent statement in the library cache                                                                                                                                                      |
| SQL_ID                    | VARCHAR2(13)   | SQL identifier of the parent cursor in the library cache                                                                                                                                                     |
| PLAN_HASH_VALUE           | NUMBER         | Numeric representation of the SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). |
| VERSION_COUNT             | NUMBER         | Number of child cursors that are present in the cache under this parent                                                                                                                                      |
| LAST_ACTIVE_CHILD_ADDRESS | RAW(4   8)     | Address (identifier) of the child cursor that was the last to be active in the group (that is, the child cursor on behalf of which statistics in V\$SQL were updated)                                        |
| SHARABLE_MEM              | NUMBER         | Amount of shared memory used by a cursor. If multiple child cursors exist, then it is the sum of all shared memory used by all child cursors.                                                                |

| Column                   | Datatype     | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PERSISTENT_MEM           | NUMBER       | Fixed amount of memory used for the lifetime of an open cursor. If multiple child cursors exist, then it is the fixed sum of memory used for the lifetime of all the child cursors.                                                                                                                                                                                                                                                                                                 |
| RUNTIME_MEM              | NUMBER       | Fixed amount of memory required during execution of a cursor. If multiple child cursors exist, then the fixed sum of all memory required during execution of all the child cursors.                                                                                                                                                                                                                                                                                                 |
| SORTS                    | NUMBER       | Sum of the number of sorts that were done for all the child cursors                                                                                                                                                                                                                                                                                                                                                                                                                 |
| LOADED_VERSIONS          | NUMBER       | Number of child cursors that are present in the cache and that have their context heap loaded                                                                                                                                                                                                                                                                                                                                                                                       |
| OPEN_VERSIONS            | NUMBER       | Number of child cursors that are currently open under this parent                                                                                                                                                                                                                                                                                                                                                                                                                   |
| USERS_OPENING            | NUMBER       | Number of users that have any of the child cursors open                                                                                                                                                                                                                                                                                                                                                                                                                             |
| USERS_EXECUTING          | NUMBER       | Total number of users executing the statement over all child cursors                                                                                                                                                                                                                                                                                                                                                                                                                |
| FETCHES                  | NUMBER       | Number of fetches associated with the SQL statement                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| EXECUTIONS               | NUMBER       | Total number of executions, totalled over all the child cursors                                                                                                                                                                                                                                                                                                                                                                                                                     |
| PX_SERVERS_EXECUTIONS    | NUMBER       | Total number of executions performed by parallel execution servers (0 when the statement has never been executed in parallel)                                                                                                                                                                                                                                                                                                                                                       |
| END_OF_FETCH_COUNT       | NUMBER       | Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column. |
| LOADS                    | NUMBER       | Number of times the object was loaded or reloaded                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| FIRST_LOAD_TIME          | DATE         | Timestamp of the parent creation time                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| LAST_LOAD_TIME           | DATE         | Time at which the query plan was loaded into the library cache                                                                                                                                                                                                                                                                                                                                                                                                                      |
| LAST_ACTIVE_TIME         | DATE         | Time at which the query plan was last active                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| INVALIDATIONS            | NUMBER       | Total number of invalidations over all the child cursors                                                                                                                                                                                                                                                                                                                                                                                                                            |
| PARSE_CALLS              | NUMBER       | Sum of all parse calls to all the child cursors under this parent                                                                                                                                                                                                                                                                                                                                                                                                                   |
| DISK_READS               | NUMBER       | Sum of the number of disk reads over all child cursors                                                                                                                                                                                                                                                                                                                                                                                                                              |
| DIRECT_WRITES            | NUMBER       | Sum of the number of direct writes over all child cursors                                                                                                                                                                                                                                                                                                                                                                                                                           |
| BUFFER_GETS              | NUMBER       | Sum of buffer gets over all child cursors                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| CPU_TIME                 | NUMBER       | CPU time (in microseconds) used by this cursor for parsing, executing, and fetching                                                                                                                                                                                                                                                                                                                                                                                                 |
| ELAPSED_TIME             | NUMBER       | Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching                                                                                                                                                                                                                                                                                                                                                                                             |
| APPLICATION_WAIT_TIME    | NUMBER       | Application wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CONCURRENCY_WAIT_TIME    | NUMBER       | Concurrency wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CLUSTER_WAIT_TIME        | NUMBER       | Cluster wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| USER_IO_WAIT_TIME        | NUMBER       | User I/O wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| PLSQL_EXEC_TIME          | NUMBER       | PL/SQL execution time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| JAVA_EXEC_TIME           | NUMBER       | Java execution time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| ROWS_PROCESSED           | NUMBER       | Total number of rows processed on behalf of this SQL statement                                                                                                                                                                                                                                                                                                                                                                                                                      |
| COMMAND_TYPE             | NUMBER       | Oracle command type definition                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| OPTIMIZER_MODE           | VARCHAR2(10) | Mode under which the SQL statement was executed                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| OPTIMIZER_COST           | NUMBER       | Cost of this query given by the optimizer                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| OPTIMIZER_ENV            | RAW(2000)    | Optimizer environment                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| OPTIMIZER_ENV_HASH_VALUE | NUMBER       | Hash value for the optimizer environment                                                                                                                                                                                                                                                                                                                                                                                                                                            |

| Column                         | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PARSING_USER_ID                | NUMBER        | User ID of the user that has parsed the very first cursor under this parent                                                                                                                                                                                                                                                                                                                                                               |
| PARSING_SCHEMA_ID              | NUMBER        | Schema ID that was used to parse this child cursor                                                                                                                                                                                                                                                                                                                                                                                        |
| PARSING_SCHEMA_NAME            | VARCHAR2 (30) | Schema name that was used to parse this child cursor                                                                                                                                                                                                                                                                                                                                                                                      |
| KEPT_VERSIONS                  | NUMBER        | Number of child cursors that have been marked to be kept using the DBMS_SHARED_POOL package                                                                                                                                                                                                                                                                                                                                               |
| MODULE                         | VARCHAR2 (64) | Contains the name of the module that was executing at the time that the SQL statement was first parsed as set by calling DBMS_APPLICATION_INFO.SET_MODULE                                                                                                                                                                                                                                                                                 |
| MODULE_HASH                    | NUMBER        | Hash value of the module that is named in the MODULE column                                                                                                                                                                                                                                                                                                                                                                               |
| ACTION                         | VARCHAR2 (64) | Contains the name of the action that was executing at the time that the SQL statement was first parsed as set by calling DBMS_APPLICATION_INFO.SET_ACTION                                                                                                                                                                                                                                                                                 |
| ACTION_HASH                    | NUMBER        | Hash value of the action that is named in the ACTION column                                                                                                                                                                                                                                                                                                                                                                               |
| SERIALIZABLE_ABORTS            | NUMBER        | Number of times the transaction failed to serialize, producing ORA-08177 errors, totalled over all the child cursors                                                                                                                                                                                                                                                                                                                      |
| OUTLINE_CATEGORY               | VARCHAR2 (64) | If an outline was applied during construction of the cursor, then this column displays the category of that outline. Otherwise, the column is left blank.                                                                                                                                                                                                                                                                                 |
| OUTLINE_SID                    | VARCHAR2 (40) | Outline session identifier                                                                                                                                                                                                                                                                                                                                                                                                                |
| REMOTE                         | VARCHAR2 (1)  | Indicates whether the cursor is remote mapped (Y) or not (N)                                                                                                                                                                                                                                                                                                                                                                              |
| OBJECT_STATUS                  | VARCHAR2 (19) | Status of the cursor: <ul style="list-style-type: none"> <li>■ VALID - Valid, authorized without errors</li> <li>■ VALID_AUTH_ERROR - Valid, authorized with authorization errors</li> <li>■ VALID_COMPILE_ERROR - Valid, authorized with compilation errors</li> <li>■ VALID_UNAUTH - Valid, unauthorized</li> <li>■ INVALID_UNAUTH - Invalid, unauthorized</li> <li>■ INVALID - Invalid, unauthorized but keep the timestamp</li> </ul> |
| LITERAL_HASH_VALUE             | NUMBER        | Hash value of the literals which are replaced with system-generated bind variables and are to be matched, when CURSOR_SHARING is used. This is not the hash value for the SQL statement. If CURSOR_SHARING is not used, then the value is 0.                                                                                                                                                                                              |
| SQL_PROFILE                    | VARCHAR2 (64) | SQL profile used for this statement, if any                                                                                                                                                                                                                                                                                                                                                                                               |
| PROGRAM_ID                     | NUMBER        | Program identifier                                                                                                                                                                                                                                                                                                                                                                                                                        |
| PROGRAM_LINE#                  | NUMBER        | Program line number                                                                                                                                                                                                                                                                                                                                                                                                                       |
| EXACT_MATCHING_SIGNATURE       | NUMBER        | Signature used when the CURSOR_SHARING parameter is set to EXACT                                                                                                                                                                                                                                                                                                                                                                          |
| FORCE_MATCHING_SIGNATURE       | NUMBER        | Signature used when the CURSOR_SHARING parameter is set to FORCE                                                                                                                                                                                                                                                                                                                                                                          |
| BIND_DATA                      | RAW (2000)    | Bind data                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| TYPECHECK_MEM                  | NUMBER        | Typecheck memory                                                                                                                                                                                                                                                                                                                                                                                                                          |
| IO_CELL_OFFLOAD_ELIGIBLE_BYTES | NUMBER        | Number of I/O bytes which can be filtered by the Exadata storage system<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information                                                                                                                                                                                                                                                                     |
| IO_INTERCONNECT_BYTES          | NUMBER        | Number of I/O bytes exchanged between Oracle Database and the storage system                                                                                                                                                                                                                                                                                                                                                              |
| PHYSICAL_READ_REQUESTS         | NUMBER        | Number of physical read I/O requests issued by the monitored SQL                                                                                                                                                                                                                                                                                                                                                                          |
| PHYSICAL_READ_BYTES            | NUMBER        | Number of bytes read from disks by the monitored SQL                                                                                                                                                                                                                                                                                                                                                                                      |
| PHYSICAL_WRITE_REQUESTS        | NUMBER        | Number of physical write I/O requests issued by the monitored SQL                                                                                                                                                                                                                                                                                                                                                                         |
| PHYSICAL_WRITE_BYTES           | NUMBER        | Number of bytes written to disks by the monitored SQL                                                                                                                                                                                                                                                                                                                                                                                     |

| Column                         | Datatype | Description                                                                                                                                                                                            |
|--------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OPTIMIZED_PHY_READ_REQUESTS    | NUMBER   | Number of physical read I/O requests from Database Smart Flash Cache issued by the monitored SQL                                                                                                       |
| IO_CELL_UNCOMPRESSED_BYTES     | NUMBER   | Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information |
| IO_CELL_OFFLOAD_RETURNED_BYTES | NUMBER   | Number of bytes that are returned by Exadata cell through the regular I/O path<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information                           |

## V\$SQLCOMMAND

V\$SQLCOMMAND displays the mapping between SQL opcodes and names.

| Column       | Datatype      | Description        |
|--------------|---------------|--------------------|
| COMMAND_TYPE | NUMBER        | SQL command number |
| COMMAND_NAME | VARCHAR2 (64) | SQL command name   |

## V\$SQLFN\_ARG\_METADATA

V\$SQLFN\_ARG\_METADATA contains metadata about function arguments. There is one row for each argument of every function found in V\$SQLFN\_METADATA. There are no rows for functions that do not have any arguments.

| Column   | Datatype      | Description                                                                                                                                                        |
|----------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FUNC_ID  | NUMBER        | Internal function identification number. This column can be used to join with the V\$SQLFN_METADATA view.                                                          |
| ARGNUM   | NUMBER        | Argument number                                                                                                                                                    |
| DATATYPE | VARCHAR2 (8)  | Datatype of the argument. The value is NULL if this argument is not used. Otherwise, it can take values of any Oracle datatype, family datatype, or EXPR datatype. |
| DESCR    | VARCHAR2 (30) | This column is reserved for future use.                                                                                                                            |

## V\$SQLFN\_METADATA

V\$SQLFN\_METADATA contains metadata about operators and built-in functions. Note that this view does not contain information about arguments because the number of arguments will be different for various functions. Information about arguments is contained in V\$SQLFN\_ARG\_METADATA, which can be joined with V\$SQLFN\_METADATA to get information about any function and its arguments.

| Column   | Datatype      | Description                                                                                             |
|----------|---------------|---------------------------------------------------------------------------------------------------------|
| FUNC_ID  | NUMBER        | Internal function identification number                                                                 |
| NAME     | VARCHAR2 (30) | Name of the built-in function                                                                           |
| MINARGS  | NUMBER        | Minimum number of arguments for the function                                                            |
| MAXARGS  | NUMBER        | Maximum number of arguments for the function                                                            |
| DATATYPE | VARCHAR2 (8)  | Return datatype, which can take any Oracle datatype values, datatype family values, or ARG[n] datatypes |
| VERSION  | VARCHAR2 (12) | Minimum version of the database that has this function                                                  |



| Column      | Datatype        | Description                                                                                                                                                                                                           |
|-------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANALYTIC    | VARCHAR2 (3)    | Indicates whether the function is an analytic function (YES) or not (NO)                                                                                                                                              |
| AGGREGATE   | VARCHAR2 (3)    | Indicates whether the function is an aggregate function (YES) or not (NO)                                                                                                                                             |
| OFFLOADABLE | VARCHAR2 (3)    | Indicates whether execution of the function can be offloaded to the Oracle Exadata Storage Server (YES) or not (NO)<br><br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information |
| DISP_TYPE   | VARCHAR2 (13)   | Function display type: <ul style="list-style-type: none"> <li>■ NORMAL</li> <li>■ ARITHMETIC</li> <li>■ PARENTHESIS</li> <li>■ REL-OP</li> <li>■ CASELIKE</li> <li>■ NOPARENTHESIS</li> </ul>                         |
| USAGE       | VARCHAR2 (30)   | A text explanation of how to use this function. The text is based on the syntax diagram for the function in the <i>Oracle Database SQL Language Reference</i> .                                                       |
| DESCR       | VARCHAR2 (4000) | Description of the function                                                                                                                                                                                           |

## V\$SQLSTATS

V\$SQLSTATS displays basic performance statistics for SQL cursors and contains one row per SQL statement (that is, one row per unique value of SQL\_ID). The column definitions for columns in V\$SQLSTATS are identical to those in the V\$SQL and V\$SQLAREA views. However, the V\$SQLSTATS view differs from V\$SQL and V\$SQLAREA in that it is faster, more scalable, and has a greater data retention (the statistics may still appear in this view, even after the cursor has been aged out of the shared pool). Note that V\$SQLSTATS contains a subset of columns that appear in V\$SQL and V\$SQLAREA.

| Column                    | Datatype        | Description                                                                                                                                                                                                  |
|---------------------------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SQL_TEXT                  | VARCHAR2 (1000) | First thousand characters of the SQL text for the current cursor                                                                                                                                             |
| SQL_FULLTEXT              | CLOB            | Full text for the SQL statement exposed as a CLOB column. The full text of a SQL statement can be retrieved using this column instead of joining with the V\$SQLTEXT view.                                   |
| SQL_ID                    | VARCHAR2 (13)   | SQL identifier of the parent cursor in the library cache                                                                                                                                                     |
| LAST_ACTIVE_TIME          | DATE            | Last time the statistics of a contributing cursor were updated                                                                                                                                               |
| LAST_ACTIVE_CHILD_ADDRESS | RAW (4   8)     | Address of the contributing cursor that last updated these statistics                                                                                                                                        |
| PLAN_HASH_VALUE           | NUMBER          | Numeric representation of the SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). |
| PARSE_CALLS               | NUMBER          | Number of parse calls for all cursors with this SQL text and plan                                                                                                                                            |
| DISK_READS                | NUMBER          | Number of disk reads for all cursors with this SQL text and plan                                                                                                                                             |
| DIRECT_WRITES             | NUMBER          | Number of direct writes for all cursors with this SQL text and plan                                                                                                                                          |
| BUFFER_GETS               | NUMBER          | Number of buffer gets for all cursors with this SQL text and plan                                                                                                                                            |
| ROWS_PROCESSED            | NUMBER          | Total number of rows the parsed SQL statement returns                                                                                                                                                        |
| SERIALIZABLE_ABORTS       | NUMBER          | Number of times the transaction failed to serialize, producing ORA-08177 errors, per cursor                                                                                                                  |
| FETCHES                   | NUMBER          | Number of fetches associated with the SQL statement                                                                                                                                                          |

| Column                         | Datatype | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EXECUTIONS                     | NUMBER   | Number of executions that took place on this object since it was brought into the library cache                                                                                                                                                                                                                                                                                                                                                                                     |
| END_OF_FETCH_COUNT             | NUMBER   | Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column. |
| LOADS                          | NUMBER   | Number of times the object was either loaded or reloaded                                                                                                                                                                                                                                                                                                                                                                                                                            |
| VERSION_COUNT                  | NUMBER   | number of cursors present in the cache with this SQL text and plan                                                                                                                                                                                                                                                                                                                                                                                                                  |
| INVALIDATIONS                  | NUMBER   | Number of times this child cursor has been invalidated                                                                                                                                                                                                                                                                                                                                                                                                                              |
| PX_SERVERS_EXECUTIONS          | NUMBER   | Total number of executions performed by parallel execution servers (0 when the statement has never been executed in parallel)                                                                                                                                                                                                                                                                                                                                                       |
| CPU_TIME                       | NUMBER   | CPU time (in microseconds) used by this cursor for parsing, executing, and fetching                                                                                                                                                                                                                                                                                                                                                                                                 |
| ELAPSED_TIME                   | NUMBER   | Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching                                                                                                                                                                                                                                                                                                                                                                                             |
| AVG_HARD_PARSE_TIME            | NUMBER   | Average hard parse time (in microseconds) used by this cursor for parsing, executing, and fetching                                                                                                                                                                                                                                                                                                                                                                                  |
| APPLICATION_WAIT_TIME          | NUMBER   | Application wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CONCURRENCY_WAIT_TIME          | NUMBER   | Concurrency wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CLUSTER_WAIT_TIME              | NUMBER   | Cluster wait time (in microseconds). This value is specific to Oracle RAC. It shows the total time spent waiting for all waits that are categorized under the cluster class of wait events. The value in this column is an accumulated wait time spent waiting for Oracle RAC cluster resources.                                                                                                                                                                                    |
| USER_IO_WAIT_TIME              | NUMBER   | User I/O wait time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| PLSQL_EXEC_TIME                | NUMBER   | PL/SQL execution time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| JAVA_EXEC_TIME                 | NUMBER   | Java execution time (in microseconds)                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| SORTS                          | NUMBER   | Number of sorts that were done for the child cursor                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| SHARABLE_MEM                   | NUMBER   | Total shared memory (in bytes) currently occupied by all cursors with this SQL text and plan                                                                                                                                                                                                                                                                                                                                                                                        |
| TOTAL_SHARABLE_MEM             | NUMBER   | Total shared memory (in bytes) occupied by all cursors with this SQL text and plan if they were to be fully loaded in the shared pool (that is, cursor size)                                                                                                                                                                                                                                                                                                                        |
| TYPECHECK_MEM                  | NUMBER   | Typecheck memory                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| IO_CELL_OFFLOAD_ELIGIBLE_BYTES | NUMBER   | Number of I/O bytes which can be filtered by the Exadata storage system<br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information                                                                                                                                                                                                                                                                                                               |
| IO_INTERCONNECT_BYTES          | NUMBER   | Number of I/O bytes exchanged between Oracle Database and the storage system                                                                                                                                                                                                                                                                                                                                                                                                        |
| PHYSICAL_READ_REQUESTS         | NUMBER   | Number of physical read I/O requests issued by the monitored SQL                                                                                                                                                                                                                                                                                                                                                                                                                    |
| PHYSICAL_READ_BYTES            | NUMBER   | Number of bytes read from disks by the monitored SQL                                                                                                                                                                                                                                                                                                                                                                                                                                |
| PHYSICAL_WRITE_REQUESTS        | NUMBER   | Number of physical write I/O requests issued by the monitored SQL                                                                                                                                                                                                                                                                                                                                                                                                                   |
| PHYSICAL_WRITE_BYTES           | NUMBER   | Number of bytes written to disks by the monitored SQL                                                                                                                                                                                                                                                                                                                                                                                                                               |
| EXACT_MATCHING_SIGNATURE       | NUMBER   | Signature used when the CURSOR_SHARING parameter is set to EXACT                                                                                                                                                                                                                                                                                                                                                                                                                    |
| FORCE_MATCHING_SIGNATURE       | NUMBER   | Signature used when the CURSOR_SHARING parameter is set to FORCE                                                                                                                                                                                                                                                                                                                                                                                                                    |

| Column                         | Datatype | Description                                                                                                                                                                                                |
|--------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IO_CELL_UNCOMPRESSED_BYTES     | NUMBER   | Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells<br><br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information |
| IO_CELL_OFFLOAD_RETURNED_BYTES | NUMBER   | Number of bytes that are returned by Exadata cell through the regular I/O path<br><br><b>See Also:</b> Oracle Exadata Storage Server Software documentation for more information                           |

## V\$SQLSTATS\_PLAN\_HASH

V\$SQLSTATS\_PLAN\_HASH displays basic performance statistics for SQL cursors and contains one row per execution plan of a SQL statement (that is, one row per unique combination of SQL\_ID and PLAN\_HASH\_VALUE).

The columns for V\$SQLSTATS\_PLAN\_HASH are the same as those for V\$SQLSTATS.

**See Also:** ["V\\$SQLSTATS"](#) on page 9-59

## V\$SQLTEXT

V\$SQLTEXT displays the text of SQL statements belonging to shared SQL cursors in the SGA.

| Column       | Datatype      | Description                                                    |
|--------------|---------------|----------------------------------------------------------------|
| ADDRESS      | RAW (4   8)   | Used with HASH_VALUE to uniquely identify a cached cursor      |
| HASH_VALUE   | NUMBER        | Used with ADDRESS to uniquely identify a cached cursor         |
| SQL_ID       | VARCHAR2 (13) | SQL identifier of a cached cursor                              |
| COMMAND_TYPE | NUMBER        | Code for the type of SQL statement (SELECT, INSERT, and so on) |
| PIECE        | NUMBER        | Number used to order the pieces of SQL text                    |
| SQL_TEXT     | VARCHAR2 (64) | A column containing one piece of the SQL text                  |

## V\$SQLTEXT\_WITH\_NEWLINES

V\$SQLTEXT\_WITH\_NEWLINES is identical to the V\$SQLTEXT view except that, to improve legibility, V\$SQLTEXT\_WITH\_NEWLINES does not replace newlines and tabs in the SQL statement with spaces.

| Column       | Datatype      | Description                                                    |
|--------------|---------------|----------------------------------------------------------------|
| ADDRESS      | RAW (4   8)   | Used with HASH_VALUE to uniquely identify a cached cursor      |
| HASH_VALUE   | NUMBER        | Used with ADDRESS to uniquely identify a cached cursor         |
| SQL_ID       | VARCHAR2 (13) | SQL identifier of a cached cursor                              |
| COMMAND_TYPE | NUMBER        | Code for the type of SQL statement (SELECT, INSERT, and so on) |
| PIECE        | NUMBER        | Number used to order the pieces of SQL text                    |
| SQL_TEXT     | VARCHAR2 (64) | A column containing one piece of the SQL text                  |

**See Also:** ["V\\$SQLTEXT"](#) on page 9-61

## V\$STANDBY\_EVENT\_HISTOGRAM

V\$STANDBY\_EVENT\_HISTOGRAM displays the histogram of apply lag on the physical standby. Each distinct value of apply lag has its own bucket and the count in the corresponding bucket represents the number of occurrences so far. The physical standby samples the apply lag every second and increments the corresponding bucket in the histogram.

| Column            | Datatype      | Description                                                                  |
|-------------------|---------------|------------------------------------------------------------------------------|
| NAME              | VARCHAR2 (64) | Name of the event (currently APPLY_LAG is the only valid value)              |
| TIME              | NUMBER        | Time duration that the bucket represents                                     |
| UNIT              | VARCHAR2 (16) | Time unit (seconds, minutes, hours, or days)                                 |
| COUNT             | NUMBER        | Count of occurrences falling into this bucket                                |
| LAST_TIME_UPDATED | VARCHAR2 (20) | Last time the bucket was updated by an event falling into that time duration |

## V\$STANDBY\_LOG

V\$STANDBY\_LOG displays information about standby redo logs. Standby redo logs are similar to online redo logs, but standby redo logs are only used on a standby database that is receiving redo data from the primary database.

| Column        | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GROUP#        | NUMBER        | Log group number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| DBID          | VARCHAR2 (40) | Database ID of the primary database to which the standby redo logfile is assigned. If the standby redo logfile is unassigned, the value UNASSIGNED will be displayed.                                                                                                                                                                                                                                                                                                                                                                      |
| THREAD#       | NUMBER        | Log thread number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| SEQUENCE#     | NUMBER        | Log sequence number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| BYTES         | NUMBER        | Size of the log (in bytes)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| BLOCKSIZE     | NUMBER        | Block size of the logfile (512 or 4096)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| USED          | NUMBER        | Number of bytes used in the log                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| ARCHIVED      | VARCHAR2 (3)  | Archive status (YES) or (NO). See the STATUS column for further details.                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| STATUS        | VARCHAR2 (10) | Log status: <ul style="list-style-type: none"> <li>UNASSIGNED - If ARCHIVED is NO, then the standby redo log has been archived and is again available. If ARCHIVED is YES, then the standby redo log has never been used and is available.</li> <li>ACTIVE - If ARCHIVED is NO, then the standby redo log is complete and waiting to be archived. If ARCHIVED is YES, then the standby redo log is currently being written to and is therefore not ready to be archived. For a given thread, there should be only one such log.</li> </ul> |
| FIRST_CHANGE# | NUMBER        | Lowest SCN in the log                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| FIRST_TIME    | DATE          | Time of the first SCN in the log                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| NEXT_CHANGE#  | NUMBER        | All redo records contained within this log will have an SCN lower than NEXT_CHANGE#. Only filled in once the log is complete. Also the lowest SCN of any redo record in the next log.                                                                                                                                                                                                                                                                                                                                                      |
| NEXT_TIME     | DATE          | All redo records contained within this log will have a timestamp lower than NEXT_TIME. Only filled in once the log is complete. Also the lowest timestamp of any redo record in the next log.                                                                                                                                                                                                                                                                                                                                              |
| LAST_CHANGE#  | NUMBER        | Last change number made to this datafile. Set to NULL if the datafile is being changed.                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| LAST_TIME     | DATE          | Timestamp of the last change                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## V\$STATISTICS\_LEVEL

V\$STATISTICS\_LEVEL displays the status of the statistics/advisories controlled by STATISTICS\_LEVEL.

| Column               | Datatype        | Description                                                                                                                                                                                                                                                     |
|----------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STATISTICS_NAME      | VARCHAR2 (64)   | Name of the statistic/advisory                                                                                                                                                                                                                                  |
| DESCRIPTION          | VARCHAR2 (4000) | Description of the statistic/advisory                                                                                                                                                                                                                           |
| SESSION_STATUS       | VARCHAR2 (8)    | Status of the statistic/advisory for the session: <ul style="list-style-type: none"> <li>■ ENABLED</li> <li>■ DISABLED</li> </ul>                                                                                                                               |
| SYSTEM_STATUS        | VARCHAR2 (8)    | System-wide status of the statistic/advisory: <ul style="list-style-type: none"> <li>■ ENABLED</li> <li>■ DISABLED</li> </ul>                                                                                                                                   |
| ACTIVATION_LEVEL     | VARCHAR2 (7)    | Indicates the level of STATISTICS_LEVEL that enables the statistic/advisory: <ul style="list-style-type: none"> <li>■ BASIC</li> <li>■ TYPICAL</li> <li>■ ALL</li> </ul>                                                                                        |
| STATISTICS_VIEW_NAME | VARCHAR2 (64)   | If there is a single view externalizing the statistic/advisory, then this column contains the name of that view. If there is no such view, then this column is null. If there are multiple views involved, then the DESCRIPTION column mentions the view names. |
| SESSION_SETTABLE     | VARCHAR2 (3)    | Indicates whether the statistic/advisory can be set at the session level (YES) or not (NO)                                                                                                                                                                      |

**See Also:** ["STATISTICS\\_LEVEL"](#) on page 1-170

## V\$STATNAME

V\$STATNAME displays decoded statistic names for the statistics shown in the V\$SESSTAT and V\$SYSSTAT tables.

On some platforms, the NAME and CLASS columns contain additional operating system-specific statistics.

| Column     | Datatype      | Description                                                                                                                                                                                                                                                                                                                          |
|------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STATISTIC# | NUMBER        | Statistic number<br><br><b>Note:</b> Statistics numbers are not guaranteed to remain constant from one release to another. Therefore, you should rely on the statistics name rather than its number in your applications.                                                                                                            |
| NAME       | VARCHAR2 (64) | Statistic name                                                                                                                                                                                                                                                                                                                       |
| CLASS      | NUMBER        | A number representing one or more statistics classes. The following class numbers are additive: <ul style="list-style-type: none"> <li>■ 1 - User</li> <li>■ 2 - Redo</li> <li>■ 4 - Enqueue</li> <li>■ 8 - Cache</li> <li>■ 16 - OS</li> <li>■ 32 - Real Application Clusters</li> <li>■ 64 - SQL</li> <li>■ 128 - Debug</li> </ul> |
| STAT_ID    | NUMBER        | Identifier of the statistic                                                                                                                                                                                                                                                                                                          |

**See Also:**

- ["V\\$SESSTAT"](#) on page 9-21 and ["V\\$SYSSTAT"](#) on page 9-77
- [Appendix E, "Statistics Descriptions"](#) for a description of each statistic
- Your operating system-specific Oracle documentation

## V\$STREAMS\_APPLY\_COORDINATOR

V\$STREAMS\_APPLY\_COORDINATOR displays information about each apply process coordinator. The coordinator for an apply process gets transactions from the apply process reader and passes them to apply servers. An apply process coordinator is a subcomponent of an apply process, outbound server, or inbound server.

| Column                   | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SID                      | NUMBER        | Session ID of the coordinator's session                                                                                                                                                                                                                                                                                                                                                    |
| SERIAL#                  | NUMBER        | Serial number of the coordinator's session                                                                                                                                                                                                                                                                                                                                                 |
| STATE                    | VARCHAR2 (21) | State of the coordinator: <ul style="list-style-type: none"><li>■ <code>INITIALIZING</code> - Starting up</li><li>■ <code>IDLE</code> - Performing no work</li><li>■ <code>APPLYING</code> - Passing transactions to apply servers</li><li>■ <code>SHUTTING DOWN CLEANLY</code> - Stopping without an error</li><li>■ <code>ABORTING</code> - Stopping because of an apply error</li></ul> |
| APPLY#                   | NUMBER        | Apply process number. An apply process coordinator is an Oracle background process, prefixed by <code>ap</code> .                                                                                                                                                                                                                                                                          |
| APPLY_NAME               | VARCHAR2 (30) | Name of the apply process                                                                                                                                                                                                                                                                                                                                                                  |
| TOTAL_APPLIED            | NUMBER        | Total number of transactions applied by the apply process since the apply process was last started                                                                                                                                                                                                                                                                                         |
| TOTAL_WAIT_DEPS          | NUMBER        | Number of times since the apply process was last started that an apply server waited to apply a logical change record (LCR) in a transaction until another apply server applied a transaction because of a dependency between the transactions                                                                                                                                             |
| TOTAL_WAIT_COMMITS       | NUMBER        | Number of times since the apply process was last started that an apply server waited to commit a transaction until another apply server committed a transaction to serialize commits                                                                                                                                                                                                       |
| TOTAL_ADMIN              | NUMBER        | Number of administrative jobs issued since the apply process was last started                                                                                                                                                                                                                                                                                                              |
| TOTAL_ASSIGNED           | NUMBER        | Number of transactions assigned to apply servers since the apply process was last started                                                                                                                                                                                                                                                                                                  |
| TOTAL_RECEIVED           | NUMBER        | Total number of transactions received by the coordinator process since the apply process was last started                                                                                                                                                                                                                                                                                  |
| TOTAL_IGNORED            | NUMBER        | Number of transactions which were received by the coordinator but were ignored because they had been previously applied                                                                                                                                                                                                                                                                    |
| TOTAL_ROLLBACKS          | NUMBER        | Number of transactions which were rolled back due to unexpected contention                                                                                                                                                                                                                                                                                                                 |
| TOTAL_ERRORS             | NUMBER        | Number of transactions applied by the apply process that resulted in an apply error since the apply process was last started                                                                                                                                                                                                                                                               |
| UNASSIGNED_COMPLETE_TXNS | NUMBER        | Total number of complete transactions that the coordinator has not assigned to any apply servers                                                                                                                                                                                                                                                                                           |
| AUTO_TXN_BUFFER_SIZE     | NUMBER        | Current value of transaction buffer size. Transaction buffer size refers to the number of transactions that the apply reader can assemble ahead of apply servers. The apply process periodically adjusts the transaction buffer size.                                                                                                                                                      |

| Column                   | Datatype | Description                                                                                                                                                                                                                                                        |
|--------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LWM_TIME                 | DATE     | Time when the message with the lowest message number was recorded. The creation time of the message with the lowest message number was also recorded at this time.                                                                                                 |
| LWM_MESSAGE_NUMBER       | NUMBER   | Number of the message corresponding to the low watermark. That is, messages with a commit message number less than or equal to this message number have definitely been applied, but some messages with a higher commit message number also may have been applied. |
| LWM_MESSAGE_CREATE_TIME  | DATE     | For captured messages, creation time at the source database of the message corresponding to the low watermark. For user-enqueued messages, time when the message corresponding to the low watermark was enqueued into the queue at the local database.             |
| HWM_TIME                 | DATE     | Time when the message with the highest message number was recorded. The creation time of the message with the highest message number was also recorded at this time.                                                                                               |
| HWM_MESSAGE_NUMBER       | NUMBER   | Number of the message corresponding to the high watermark. That is, no messages with a commit message number greater than this message number have been applied.                                                                                                   |
| HWM_MESSAGE_CREATE_TIME  | DATE     | For captured messages, creation time at the source database of the message corresponding to the high watermark. For user-enqueued messages, time when the message corresponding to the high watermark was enqueued into the queue at the local database.           |
| STARTUP_TIME             | DATE     | Time when the apply process was last started                                                                                                                                                                                                                       |
| ELAPSED_SCHEDULE_TIME    | NUMBER   | Time elapsed (in hundredths of a second) scheduling messages since the apply process was last started                                                                                                                                                              |
| ELAPSED_IDLE_TIME        | NUMBER   | Elapsed idle time                                                                                                                                                                                                                                                  |
| LWM_POSITION             | RAW (64) | Position of the low-watermark LCR                                                                                                                                                                                                                                  |
| HWM_POSITION             | RAW (64) | Position of the high-watermark LCR                                                                                                                                                                                                                                 |
| PROCESSED_MESSAGE_NUMBER | NUMBER   | Message number currently processed by the apply coordinator                                                                                                                                                                                                        |

---

**Note:** The ELAPSED\_SCHEDULE\_TIME column is only populated if the TIMED\_STATISTICS initialization parameter is set to true, or if the STATISTICS\_LEVEL initialization parameter is set to TYPICAL or ALL.

---

## V\$STREAMS\_APPLY\_READER

V\$STREAMS\_APPLY\_READER displays information about each apply reader. The apply reader is a process which reads (dequeues) messages from the queue, computes message dependencies, and builds transactions. It passes the transactions on to the coordinator in commit order for assignment to the apply servers. An apply reader is a subcomponent of an apply process, outbound server, or inbound server.

| Column     | Datatype      | Description                                                                             |
|------------|---------------|-----------------------------------------------------------------------------------------|
| SID        | NUMBER        | Session ID of the reader's session                                                      |
| SERIAL#    | NUMBER        | Serial number of the reader's session                                                   |
| APPLY#     | NUMBER        | Apply process number. An apply process is an Oracle background process, prefixed by ap. |
| APPLY_NAME | VARCHAR2 (30) | Name of the apply process                                                               |

| Column                       | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STATE                        | VARCHAR2 (36) | State of the reader: <ul style="list-style-type: none"> <li>INITIALIZING - Starting up</li> <li>IDLE - Performing no work</li> <li>DEQUEUE MESSAGES - Dequeuing messages from the queue</li> <li>SCHEDULE MESSAGES - Computing dependencies between messages and assembling messages into transactions</li> <li>SPILLING - Spilling unapplied messages from memory to hard disk</li> <li>PAUSED - WAITING FOR DDL TO COMPLETE - Waiting for a DDL LCR to be applied</li> </ul> |
| TOTAL_MESSAGES_DEQUEUED      | NUMBER        | Total number of messages dequeued since the apply process was last started                                                                                                                                                                                                                                                                                                                                                                                                     |
| TOTAL_MESSAGES_SPILLED       | NUMBER        | Number of messages spilled by the reader since the apply process was last started                                                                                                                                                                                                                                                                                                                                                                                              |
| DEQUEUE_TIME                 | DATE          | Time when the last message was received                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| DEQUEUED_MESSAGE_NUMBER      | NUMBER        | Number of the last message received                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| DEQUEUED_MESSAGE_CREATE_TIME | DATE          | For captured messages, creation time at the source database of the last message received. For user-enqueued messages, time when the message was enqueued into the queue at the local database.                                                                                                                                                                                                                                                                                 |
| SGA_USED                     | NUMBER        | Amount (in bytes) of SGA memory used by the apply process since it was last started                                                                                                                                                                                                                                                                                                                                                                                            |
| ELAPSED_DEQUEUE_TIME         | NUMBER        | Time elapsed (in hundredths of a second) dequeuing messages since the apply process was last started                                                                                                                                                                                                                                                                                                                                                                           |
| ELAPSED_SCHEDULE_TIME        | NUMBER        | Time elapsed (in hundredths of a second) scheduling messages since the apply process was last started. Scheduling includes computing dependencies between messages and assembling messages into transactions.                                                                                                                                                                                                                                                                  |
| ELAPSED_SPILL_TIME           | NUMBER        | Elapsed time (in hundredths of a second) spent spilling messages since the apply process was last started                                                                                                                                                                                                                                                                                                                                                                      |
| LAST_BROWSE_NUM              | NUMBER        | Reserved for internal use                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| OLDEST_SCN_NUM               | NUMBER        | Oldest SCN                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| LAST_BROWSE_SEQ              | NUMBER        | Reserved for internal use                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| LAST_DEQ_SEQ                 | NUMBER        | Last dequeue sequence number                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| OLDEST_XIDUSN                | NUMBER        | Transaction ID undo segment number of the oldest transaction that either has been applied or is being applied                                                                                                                                                                                                                                                                                                                                                                  |
| OLDEST_XIDSLT                | NUMBER        | Transaction ID slot number of the oldest transaction that either has been applied or is being applied                                                                                                                                                                                                                                                                                                                                                                          |
| OLDEST_XIDSQN                | NUMBER        | Transaction ID sequence number of the oldest transaction that either has been applied or is being applied                                                                                                                                                                                                                                                                                                                                                                      |
| SPILL_LWM_SCN                | NUMBER        | Spill low-watermark SCN                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| PROXY_SID                    | NUMBER        | When the apply process uses combined capture and apply, the session ID of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is 0.                                                                                                                                                                                                                |
| PROXY_SERIAL                 | NUMBER        | When the apply process uses combined capture and apply, the serial number of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is 0.                                                                                                                                                                                                             |
| PROXY_SPID                   | VARCHAR2 (12) | When the apply process uses combined capture and apply, the process identification number of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is 0.                                                                                                                                                                                             |



| Column                             | Datatype       | Description                                                                                                                                                                                                                                                               |
|------------------------------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAPTURE_BYTES_RECEIVED             | NUMBER         | When the apply process uses combined capture and apply, the number of bytes received by the apply process from the capture process since the apply process last started. If the apply process does not use combined capture and apply, then this column is not populated. |
| DEQUEUED_POSITION                  | RAW (64)       | Dequeued position<br>This column is populated only for an apply process that is functioning as an XStream inbound server.                                                                                                                                                 |
| LAST_BROWSE_POSITION               | RAW (64)       | Reserved for internal use                                                                                                                                                                                                                                                 |
| OLDEST_POSITION                    | RAW (64)       | The earliest position of the transactions currently being dequeued and applied<br>This column is populated only for an apply process that is functioning as an XStream inbound server.                                                                                    |
| SPILL_LWM_POSITION                 | RAW (64)       | Spill low-watermark position<br>This column is populated only for an apply process that is functioning as an XStream inbound server.                                                                                                                                      |
| OLDEST_TRANSACTION_ID              | VARCHAR2 (128) | Oldest transaction ID                                                                                                                                                                                                                                                     |
| TOTAL_LCRS_WITH_DEP <sup>1</sup>   | NUMBER         | Total number of LCRs with row-level dependencies since the apply process last started                                                                                                                                                                                     |
| TOTAL_LCRS_WITH_WMDEP <sup>1</sup> | NUMBER         | Total number of LCRs with watermark dependencies since the apply process last started<br>A watermark dependency occurs when an apply process must wait until the apply process's low watermark reaches a particular threshold.                                            |
| TOTAL_IN_MEMORY_LCRS <sup>1</sup>  | NUMBER         | Total number of LCRs currently in memory                                                                                                                                                                                                                                  |
| SGA_ALLOCATED <sup>1</sup>         | NUMBER         | The total amount of shared memory (in bytes) allocated from the Streams pool for the apply process since the apply process last started                                                                                                                                   |

<sup>1</sup> This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

---

**Note:** The ELAPSED\_DEQUEUE\_TIME and ELAPSED\_SCHEDULE\_TIME columns are only populated if the TIMED\_STATISTICS initialization parameter is set to true, or if the STATISTICS\_LEVEL initialization parameter is set to TYPICAL or ALL.

---

## V\$STREAMS\_APPLY\_SERVER

V\$STREAMS\_APPLY\_SERVER displays information about each apply server and its activities. An apply server receives messages from the apply coordinator for an apply process. For each message received, an apply server either applies the message or sends the message to the appropriate apply handler. An apply server is a subcomponent of an apply process, outbound server, or inbound server.

| Column     | Datatype      | Description                                                                             |
|------------|---------------|-----------------------------------------------------------------------------------------|
| SID        | NUMBER        | Session ID of the apply server's session                                                |
| SERIAL#    | NUMBER        | Serial number of the apply server's session                                             |
| APPLY#     | NUMBER        | Apply process number. An apply process is an Oracle background process, prefixed by ap. |
| APPLY_NAME | VARCHAR2 (30) | Name of the apply process                                                               |
| SERVER_ID  | NUMBER        | Parallel execution server number of the apply server                                    |

| Column                 | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STATE                  | VARCHAR2 (20) | <p>State of the apply server:</p> <ul style="list-style-type: none"> <li>INITIALIZING - Starting up</li> <li>IDLE - Performing no work</li> <li>RECORD LOW-WATERMARK - Performing an administrative job that maintains information about the apply progress, which is used in the ALL_APPLY_PROGRESS and DBA_APPLY_PROGRESS data dictionary views</li> <li>ADD PARTITION - Performing an administrative job that adds a partition that is used for recording information about in-progress transactions</li> <li>DROP PARTITION - Performing an administrative job that purges rows that were used to record information about in-progress transactions</li> <li>EXECUTE TRANSACTION - Applying a transaction</li> <li>WAIT COMMIT - Waiting to commit a transaction until all other transactions with a lower commit SCN are applied. This state is possible only if the COMMIT_SERIALIZATION apply process parameter is set to a value other than DEPENDENT_TRANSACTIONS and the PARALLELISM apply process parameter is set to a value greater than 1.</li> <li>WAIT DEPENDENCY - Waiting to apply a logical change record (LCR) in a transaction until another transaction, on which it has a dependency, is applied. This state is possible only if the PARALLELISM apply process parameter is set to a value greater than 1.</li> <li>ROLLBACK TRANSACTION - Rolling back a transaction</li> <li>TRANSACTION CLEANUP - Cleaning up an applied transaction, which includes removing LCRs from the apply process's queue</li> <li>WAIT FOR CLIENT - Waiting for an XStream client application to request more LCRs</li> <li>WAIT FOR NEXT CHUNK<sup>1</sup> - Waiting for the next set of LCRs for a large transaction</li> </ul> |
| XIDUSN                 | NUMBER        | Transaction ID undo segment number of the transaction currently being applied                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| XIDSLT                 | NUMBER        | Transaction ID slot number of the transaction currently being applied                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| XIDSQN                 | NUMBER        | Transaction ID sequence number of the transaction currently being applied                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| COMMITSCN              | NUMBER        | Commit system change number (SCN) of the transaction currently being applied                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| DEP_XIDUSN             | NUMBER        | Transaction ID undo segment number of a transaction on which the transaction being applied by this apply server depends                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| DEP_XIDSLT             | NUMBER        | Transaction ID slot number of a transaction on which the transaction being applied by this apply server depends                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| DEP_XIDSQN             | NUMBER        | Transaction ID sequence number of a transaction on which the transaction being applied by this apply server depends                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| DEP_COMMITSCN          | NUMBER        | Commit system change number (SCN) of the transaction on which this apply server depends                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| MESSAGE_SEQUENCE       | NUMBER        | Number of the current message being applied by the apply server. This value is reset to 1 at the beginning of each transaction.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| TOTAL_ASSIGNED         | NUMBER        | Total number of transactions assigned to the apply server since the apply process was last started                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| TOTAL_ADMIN            | NUMBER        | Total number of administrative jobs done by the apply server since the apply process was last started. See the STATE information in this view for the types of administrative jobs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| TOTAL_ROLLBACKS        | NUMBER        | Number of transactions assigned to this server which were rolled back                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| TOTAL_MESSAGES_APPLIED | NUMBER        | Total number of messages applied by this apply server since the apply process was last started                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

| Column                      | Datatype       | Description                                                                                                                                                                                                                                                                             |
|-----------------------------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| APPLY_TIME                  | DATE           | Time the last message was applied                                                                                                                                                                                                                                                       |
| APPLIED_MESSAGE_NUMBER      | NUMBER         | Number of the last message applied                                                                                                                                                                                                                                                      |
| APPLIED_MESSAGE_CREATE_TIME | DATE           | Creation time at the source database of the last captured message applied. No information about user-enqueued messages is recorded in this column.                                                                                                                                      |
| ELAPSED_DEQUEUE_TIME        | NUMBER         | Time elapsed (in hundredths of a second) dequeuing messages since the apply process was last started                                                                                                                                                                                    |
| ELAPSED_APPLY_TIME          | NUMBER         | Time elapsed (in hundredths of a second) applying messages since the apply process was last started                                                                                                                                                                                     |
| COMMIT_POSITION             | RAW (64)       | Commit position of the transaction.<br>This column is populated only for an apply process that is functioning as an XStream outbound server or inbound server.                                                                                                                          |
| DEP_COMMIT_POSITION         | RAW (64)       | Commit position of the transaction the slave depends on<br>This column is populated only for an apply process that is functioning as an XStream inbound server.                                                                                                                         |
| LAST_APPLY_POSITION         | RAW (64)       | For inbound servers, the position of the last message applied; for outbound servers, the position of the last message sent to the XStream client application<br>This column is populated only for an apply process that is functioning as an XStream outbound server or inbound server. |
| TRANSACTION_ID              | VARCHAR2 (128) | Transaction ID that the slave is applying<br>This column is populated only for an apply process that is functioning as an XStream inbound server.                                                                                                                                       |
| DEP_TRANSACTION_ID          | VARCHAR2 (128) | Transaction ID of the transaction the slave depends on<br>This column is populated only for an apply process that is functioning as an XStream inbound server.                                                                                                                          |

<sup>1</sup> This state is available starting with Oracle Database 11g Release 2 (11.2.0.2).

**Note:** The ELAPSED\_DEQUEUE\_TIME and ELAPSED\_APPLY\_TIME columns are only populated if the TIMED\_STATISTICS initialization parameter is set to true, or if the STATISTICS\_LEVEL initialization parameter is set to TYPICAL or ALL.

## V\$STREAMS\_CAPTURE

V\$STREAMS\_CAPTURE displays information about each capture process that sends LCRs to an XStream outbound server.

| Column       | Datatype      | Description                                                                                |
|--------------|---------------|--------------------------------------------------------------------------------------------|
| SID          | NUMBER        | Session identifier of the capture process                                                  |
| SERIAL#      | NUMBER        | Session serial number of the capture process session                                       |
| CAPTURE#     | NUMBER        | Capture process number. A capture process is an Oracle background process, prefixed by cp. |
| CAPTURE_NAME | VARCHAR2 (30) | Name of the capture process                                                                |
| LOGMINER_ID  | NUMBER        | Session ID of the LogMiner session associated with the capture process                     |
| STARTUP_TIME | DATE          | Time when the capture process was last started                                             |

| Column                        | Datatype       | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STATE                         | VARCHAR2 (551) | <p>State of the capture process:</p> <ul style="list-style-type: none"> <li>INITIALIZING</li> <li>CAPTURING CHANGES</li> <li>EVALUATING RULE</li> <li>ENQUEUEING MESSAGE</li> <li>SHUTTING DOWN</li> <li>ABORTING</li> <li>CREATING LCR</li> <li>WAITING FOR DICTIONARY REDO</li> <li>WAITING FOR REDO</li> <li>PAUSED FOR FLOW CONTROL</li> <li>DICTIONARY INITIALIZATION</li> <li>WAITING FOR SUBSCRIBER TO BE ADDED</li> <li>WAITING FOR BUFFERED QUEUE TO SHRINK</li> <li>SUSPENDED FOR AUTO SPLIT/MERGE</li> <li>WAITING FOR TRANSACTION<sup>1</sup></li> <li>WAITING FOR INACTIVE DEQUEUEUS<sup>1</sup></li> </ul> <p><b>See Also:</b> <i>Oracle Database XStream Guide</i> for detailed descriptions of these values</p> |
| TOTAL_PREFILTER_DISCARDED     | NUMBER         | Total number of prefiltered messages discarded                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| TOTAL_PREFILTER_KEPT          | NUMBER         | Total number of prefiltered messages kept                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| TOTAL_PREFILTER_EVALUATIONS   | NUMBER         | Total number of prefilter evaluations                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| TOTAL_MESSAGES_CAPTURED       | NUMBER         | Total number of redo entries passed by LogMiner to the capture process for detailed rule evaluation since the capture process last started. A capture process converts a redo entry into a message and performs detailed rule evaluation on the message when capture process prefiltering cannot discard the change.                                                                                                                                                                                                                                                                                                                                                                                                            |
| CAPTURE_TIME                  | DATE           | Time when the most recent message was captured                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| CAPTURE_MESSAGE_NUMBER        | NUMBER         | Number of the most recently captured message                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| CAPTURE_MESSAGE_CREATE_TIME   | DATE           | Creation time of the most recently captured message                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| TOTAL_MESSAGES_CREATED        | NUMBER         | Count associated with ELAPSED_LCR_TIME to calculate rate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| TOTAL_FULL_EVALUATIONS        | NUMBER         | Count associated with ELAPSED_RULE_TIME to calculate rate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| TOTAL_MESSAGES_ENQUEUED       | NUMBER         | Total number of messages enqueued since the capture process was last started                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| ENQUEUE_TIME                  | DATE           | Time when the last message was enqueued                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| ENQUEUE_MESSAGE_NUMBER        | NUMBER         | Number of the last enqueued message                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| ENQUEUE_MESSAGE_CREATE_TIME   | DATE           | Creation time of the last enqueued message                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| AVAILABLE_MESSAGE_NUMBER      | NUMBER         | For local capture, the last redo SCN flushed to the logfiles. For downstream capture, the last SCN added to LogMiner via the archive logs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| AVAILABLE_MESSAGE_CREATE_TIME | DATE           | For local capture, the time the SCN was written to the logfile. For downstream capture, the time the most recent archive log (containing the most recent SCN) was added to LogMiner.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| ELAPSED_CAPTURE_TIME          | NUMBER         | Elapsed time (in hundredths of a second) scanning for changes in the redo log since the capture process was last started                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

| Column                           | Datatype       | Description                                                                                                                                                                                                                           |
|----------------------------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ELAPSED_RULE_TIME                | NUMBER         | Elapsed time (in hundredths of a second) evaluating rules since the capture process was last started                                                                                                                                  |
| ELAPSED_ENQUEUE_TIME             | NUMBER         | Elapsed time (in hundredths of a second) enqueueing messages since the capture process was last started                                                                                                                               |
| ELAPSED_LCR_TIME                 | NUMBER         | Elapsed time (in hundredths of a second) creating logical change records (LCRs) since the capture process was last started                                                                                                            |
| ELAPSED_REDO_WAIT_TIME           | NUMBER         | Elapsed time (in hundredths of a second) spent by the capture process in the WAITING FOR REDO state                                                                                                                                   |
| ELAPSED_PAUSE_TIME               | NUMBER         | Elapsed flow control pause time (in hundredths of a second)                                                                                                                                                                           |
| STATE_CHANGED_TIME               | DATE           | Time at which the state of the capture process changed                                                                                                                                                                                |
| APPLY_NAME                       | VARCHAR2 (30)  | Reserved for internal use                                                                                                                                                                                                             |
| APPLY_DBLINK                     | VARCHAR2 (128) | Reserved for internal use                                                                                                                                                                                                             |
| APPLY_MESSAGES_SENT              | NUMBER         | Reserved for internal use                                                                                                                                                                                                             |
| APPLY_BYTES_SENT                 | NUMBER         | Reserved for internal use                                                                                                                                                                                                             |
| OPTIMIZATION                     | NUMBER         | Indicates whether a capture process uses combined capture and apply (greater than zero) or a capture process does not use combined capture and apply (0)                                                                              |
| PURPOSE <sup>2</sup>             | VARCHAR2 (10)  | Purpose of the capture process: <ul style="list-style-type: none"> <li>Streams - The capture process is part of an Oracle Streams configuration</li> <li>XStream - The capture process is part of an XStream configuration</li> </ul> |
| SGA_USED <sup>2</sup>            | NUMBER         | The total amount of shared memory (in bytes) currently used by the capture process out of the amount allocated (SGA_ALLOCATED)                                                                                                        |
| SGA_ALLOCATED <sup>2</sup>       | NUMBER         | The total amount of shared memory (in bytes) allocated from the Streams pool for the capture process                                                                                                                                  |
| BYTES_OF_REDO_MINED <sup>2</sup> | VARCHAR2 (64)  | The total amount of redo data mined (in bytes) since the capture process last started                                                                                                                                                 |
| SESSION_RESTART_SCN <sup>2</sup> | VARCHAR2 (64)  | The SCN from which the capture process started mining redo data when it was last started                                                                                                                                              |

<sup>1</sup> This state is available starting with Oracle Database 11g Release 2 (11.2.0.2).

<sup>2</sup> This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

---

**Note:** The ELAPSED\_CAPTURE\_TIME, ELAPSED\_RULE\_TIME, ELAPSED\_ENQUEUE\_TIME, ELAPSED\_LCR\_TIME, and ELAPSED\_REDO\_WAIT\_TIME columns are only populated if the TIMED\_STATISTICS initialization parameter is set to true, or if the STATISTICS\_LEVEL initialization parameter is set to TYPICAL or ALL.

---

## V\$STREAMS\_MESSAGE\_TRACKING

V\$STREAMS\_MESSAGE\_TRACKING displays information about LCRs tracked through the stream that are processed by each Streams client. Use the DBMS\_STREAMS\_ADM.SET\_MESSAGE\_TRACKING procedure to specify a tracking label that becomes part of each LCR generated by the current session.

When the actions parameter in the DBMS\_STREAMS\_ADM.SET\_MESSAGE\_TRACKING procedure is set to DBMS\_STREAMS\_ADM.ACTION\_MEMORY, information about the LCRs is tracked in memory, and this view is populated with information about the LCRs. Currently, DBMS\_STREAMS\_ADM.ACTION\_MEMORY is the only valid setting for the actions parameter in the procedure.

| Column                | Datatype                        | Description                                                                                                                                                                                                                  |
|-----------------------|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TRACKING_LABEL        | VARCHAR2 (30)                   | User-specified tracking label                                                                                                                                                                                                |
| TAG                   | RAW (30)                        | First 30 bytes of the tag of the LCR                                                                                                                                                                                         |
| COMPONENT_NAME        | VARCHAR2 (30)                   | Name of the component that processed the LCR                                                                                                                                                                                 |
| COMPONENT_TYPE        | VARCHAR2 (30)                   | Type of the component that processed the LCR                                                                                                                                                                                 |
| ACTION                | VARCHAR2 (50)                   | Action performed on the LCR                                                                                                                                                                                                  |
| ACTION_DETAILS        | VARCHAR2 (100)                  | Details of the action                                                                                                                                                                                                        |
| TIMESTAMP             | TIMESTAMP (9)<br>WITH TIME ZONE | Time when the action was performed                                                                                                                                                                                           |
| MESSAGE_CREATION_TIME | DATE                            | Time when the message was created                                                                                                                                                                                            |
| MESSAGE_NUMBER        | NUMBER                          | SCN of the message                                                                                                                                                                                                           |
| TRACKING_ID           | RAW (16)                        | Globally unique OID of the LCR                                                                                                                                                                                               |
| SOURCE_DATABASE_NAME  | VARCHAR2 (128)                  | Name of the source database                                                                                                                                                                                                  |
| OBJECT_OWNER          | VARCHAR2 (30)                   | Owner of the object                                                                                                                                                                                                          |
| OBJECT_NAME           | VARCHAR2 (30)                   | Name of the object                                                                                                                                                                                                           |
| XID                   | VARCHAR2 (128)                  | Transaction ID                                                                                                                                                                                                               |
| COMMAND_TYPE          | VARCHAR2 (30)                   | Command type of the LCR                                                                                                                                                                                                      |
| MESSAGE_POSITION      | RAW (64)                        | Reserved for internal use                                                                                                                                                                                                    |
| PURPOSE <sup>1</sup>  | VARCHAR2 (10)                   | Purpose of the LCR stream: <ul style="list-style-type: none"> <li>Streams - The LCR stream flows through an Oracle Streams configuration</li> <li>XStream - The LCR stream flows through an XStream configuration</li> </ul> |

<sup>1</sup> This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

## V\$STREAMS\_POOL\_ADVICE

V\$STREAMS\_POOL\_ADVICE displays information about the estimated count of spilled or unspilled messages and the associated time spent in the spill or unspill activity for different Streams pool sizes. The sizes range from 10% to 200% of the current Streams pool size, in equal intervals. The value of the interval depends on the current size of the Streams pool.

| Column                         | Datatype | Description                                                                                                                                                                                                                                                                                                                                                                                                                    |
|--------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STREAMS_POOL_SIZE_FOR_ESTIMATE | NUMBER   | Streams pool size (in megabytes) for the estimate. The size ranges from values smaller than the current Streams pool size to values larger than the current Streams pool size, and there is a separate row for each increment. There is always an entry that shows the current Streams pool size, and there are always 20 increments. The range and the size of the increments depend on the current size of the Streams pool. |
| STREAMS_POOL_SIZE_FACTOR       | NUMBER   | Size factor with respect to the current Streams pool size                                                                                                                                                                                                                                                                                                                                                                      |
| ESTD_SPILL_COUNT               | NUMBER   | Estimated count of messages spilled from the Streams pool                                                                                                                                                                                                                                                                                                                                                                      |
| ESTD_SPILL_TIME                | NUMBER   | Estimated elapsed time (in seconds) to spill                                                                                                                                                                                                                                                                                                                                                                                   |
| ESTD_UNSPILL_COUNT             | NUMBER   | Estimated count of unspills (read back from disk)                                                                                                                                                                                                                                                                                                                                                                              |
| ESTD_UNSPILL_TIME              | NUMBER   | Estimated elapsed time (in seconds) to unspill                                                                                                                                                                                                                                                                                                                                                                                 |

**See Also:** *Oracle Streams Concepts and Administration* for more information about this view

## V\$STREAMS\_POOL\_STATISTICS

V\$STREAMS\_POOL\_STATISTICS displays information about the current Streams pool usage percentage.

| Column                 | Datatype | Description                                                                                                                                                                                                                                                                                                                           |
|------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TOTAL_MEMORY_ALLOCATED | NUMBER   | Total memory allocated to the Streams pool (in bytes). It should always be less than the current size of the Streams pool. You can get the percentage of the Streams pool used by dividing TOTAL_MEMORY_ALLOCATED by CURRENT_SIZE.                                                                                                    |
| CURRENT_SIZE           | NUMBER   | Current size of the Streams pool (in bytes)                                                                                                                                                                                                                                                                                           |
| SGA_TARGET_VALUE       | NUMBER   | Value of SGA_TARGET. Used to determine whether or not streams pool automatic tuning is enabled. This should be set even if MEMORY_TARGET is set and SGA_TARGET is not set.                                                                                                                                                            |
| SHRINK_PHASE           | NUMBER   | This only pertains to the Streams pool in an automatic tuning environment (SGA_TARGET and MEMORY_TARGET set). In this case, this shows whether or not the Streams pool is being asked to shrink. During the shrink phase, enqueues are blocked, flow control is enabled for all components, and cached memory is returned to the SGA. |
| ADVICE_DISABLED        | NUMBER   | This determines whether or not Streams pool advice in V\$STREAMS_POOL_ADVICE as well as all statistics gathering related to auto-tuning the Streams pool have been disabled.                                                                                                                                                          |

## V\$STREAMS\_TRANSACTION

V\$STREAMS\_TRANSACTION displays information about transactions that are being processed by capture processes or apply processes. This view can be used to identify long running transactions and to determine how many logical change records (LCRs) are being processed in each transaction. This view only contains information about captured LCRs. It does not contain information about user-enqueued LCRs or user messages.

This view only shows information about LCRs that are being processed because they satisfied the rule sets for the Streams process at the time of the query. For capture processes, this view only shows information about changes in transactions that the capture process has converted to LCRs. It does not show information about all the active transactions present in the redo log. For apply processes, this view only shows information about LCRs that the apply process has dequeued. It does not show information about LCRs in the apply process's queue.

Information about a transaction remains in the view until the transaction commits or until the entire transaction is rolled back.

| Column       | Datatype      | Description                                                                                                                             |
|--------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| STREAMS_NAME | VARCHAR2 (30) | Name of the Streams process                                                                                                             |
| STREAMS_TYPE | VARCHAR2 (10) | Type of the Streams process: <ul style="list-style-type: none"> <li>■ CAPTURE</li> <li>■ APPLY</li> <li>■ PROPAGATION_SENDER</li> </ul> |
| XIDUSN       | NUMBER        | Transaction ID undo segment number of the transaction                                                                                   |
| XIDSLT       | NUMBER        | Transaction ID slot number of the transaction                                                                                           |
| XIDSQN       | NUMBER        | Transaction ID sequence number of the transaction                                                                                       |

| Column                   | Datatype       | Description                                                                                                                                                                                                                                                                        |
|--------------------------|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CUMULATIVE_MESSAGE_COUNT | NUMBER         | Number of LCRs processed in the transaction. If the Streams process is restarted while the transaction is being processed, then this column shows the number of LCRs processed in the transaction since the Streams process was started.                                           |
| TOTAL_MESSAGE_COUNT      | NUMBER         | Total Number of LCRs processed in the transaction by an apply process. This column does not pertain to capture processes.                                                                                                                                                          |
| FIRST_MESSAGE_TIME       | DATE           | Timestamp of the first LCR processed in the transaction. If a capture process is restarted while the transaction is being processed, then this column shows the timestamp of the first LCR processed after the capture process was started.                                        |
| FIRST_MESSAGE_NUMBER     | NUMBER         | System change number (SCN) of the first message in the transaction. If a capture process is restarted while the transaction is being processed, then this column shows the SCN of the first message processed after the capture process was started.                               |
| LAST_MESSAGE_TIME        | DATE           | Timestamp of the last LCR processed in the transaction                                                                                                                                                                                                                             |
| LAST_MESSAGE_NUMBER      | NUMBER         | SCN of the most recent message encountered for the transaction                                                                                                                                                                                                                     |
| FIRST_MESSAGE_POSITION   | RAW (64)       | Reserved for internal use                                                                                                                                                                                                                                                          |
| LAST_MESSAGE_POSITION    | RAW (64)       | Reserved for internal use                                                                                                                                                                                                                                                          |
| TRANSACTION_ID           | VARCHAR2 (128) | Transaction ID                                                                                                                                                                                                                                                                     |
| PURPOSE <sup>1</sup>     | VARCHAR2 (10)  | Purpose of the components that are processing the transaction: <ul style="list-style-type: none"> <li>Streams - The transaction is being processed in an Oracle Streams configuration</li> <li>XStream - The transaction is being processed in an XStream configuration</li> </ul> |

<sup>1</sup> This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

## V\$SUBCACHE

V\$SUBCACHE displays information about the subordinate caches currently loaded into library cache memory. The view walks through the library cache, printing out a row for each loaded subordinate cache per library cache object.

| Column     | Datatype        | Description                                        |
|------------|-----------------|----------------------------------------------------|
| OWNER_NAME | VARCHAR2 (64)   | Owner of the object containing these cache entries |
| NAME       | VARCHAR2 (1000) | Object Name                                        |
| TYPE       | NUMBER          | Object Type                                        |
| HEAP_NUM   | NUMBER          | Heap number containing this subordinate cache      |
| CACHE_ID   | NUMBER          | Subordinate cache ID                               |
| CACHE_CNT  | NUMBER          | Number of entries for this cache in this object    |
| HEAP_SZ    | NUMBER          | Amount of extent space allocated to this heap      |
| HEAP_ALOC  | NUMBER          | Amount of extent space allocated from this heap    |
| HEAP_USED  | NUMBER          | Amount of space utilized in this heap              |

## V\$SUBSCR\_REGISTRATION\_STATS

V\$SUBSCR\_REGISTRATION\_STATS displays information for diagnosability of notifications.

| Column | Datatype | Description             |
|--------|----------|-------------------------|
| REG_ID | NUMBER   | Registration identifier |



| Column                                | Datatype                        | Description                                                                   |
|---------------------------------------|---------------------------------|-------------------------------------------------------------------------------|
| NUM_NTFNS                             | NUMBER                          | Number of notifications                                                       |
| NUM_GROUPING_NTFNS                    | NUMBER                          | Number of grouping notifications                                              |
| NUM_NTFNS_CURRENT_GROUP               | NUMBER                          | Number of events received in the current group                                |
| LAST_NTFN_START_TIME                  | TIMESTAMP (3)<br>WITH TIME ZONE | Time when the last notification was started                                   |
| LAST_NTFN_SENT_TIME                   | TIMESTAMP (3)<br>WITH TIME ZONE | Time when the last notification was sent                                      |
| TOTAL_EMON_LATENCY                    | NUMBER                          | Total EMON latency (time taken by the EMON slave to process notifications)    |
| EMON#                                 | NUMBER                          | Active EMON slave serving the registration                                    |
| ALL_EMON_SERVERS                      | RAW (2000)                      | EMON slaves that served the registration                                      |
| TOTAL_PAYLOAD_BYTES_SENT              | NUMBER                          | Total payload bytes sent                                                      |
| NUM_RETRIES                           | NUMBER                          | Number of retries in sending notifications                                    |
| TOTAL_PLSQL_EXEC_TIME                 | NUMBER                          | Total PL/SQL callback execution time (relevant only for PL/SQL notifications) |
| LAST_ERR                              | VARCHAR2 (90)                   | Last error message                                                            |
| LAST_ERR_TIME                         | TIMESTAMP (3)<br>WITH TIME ZONE | Time of the last error                                                        |
| LAST_UPDATE_TIME                      | TIMESTAMP (3)<br>WITH TIME ZONE | Time of the last update                                                       |
| NUM_PENDING_NTFNS                     | NUMBER                          | Number of notifications pending to be sent                                    |
| TOTAL_PENDING_NTFN_BYTES <sup>1</sup> | NUMBER                          | Total number of bytes for notifications pending to be sent                    |

<sup>1</sup> This column is available starting with Oracle Database 11g Release 2 (11.2.0.2).

## V\$SYS\_OPTIMIZER\_ENV

V\$SYS\_OPTIMIZER\_ENV displays the contents of the optimizer environment for the instance. The optimizer environment stores the value of the main parameters used by the Oracle optimizer when building the execution plan of a SQL statement. Hence, modifying the value of one or more of these parameters (for example, by issuing an ALTER SYSTEM statement) could lead to plan changes.

The parameters displayed by this view are either regular initialization parameters (such as OPTIMIZER\_FEATURES\_ENABLE) or pseudo parameters (such as ACTIVE\_INSTANCE\_COUNT).

| Column        | Datatype      | Description                                                                   |
|---------------|---------------|-------------------------------------------------------------------------------|
| ID            | NUMBER        | Unique identifier of the parameter in the optimizer environment               |
| NAME          | VARCHAR2 (40) | Name of the parameter                                                         |
| SQL_FEATURE   | VARCHAR2 (64) | Associated feature control ID                                                 |
| ISDEFAULT     | VARCHAR2 (3)  | Indicates whether the parameter is set to the default value (YES) or not (NO) |
| VALUE         | VARCHAR2 (25) | Value of the parameter                                                        |
| DEFAULT_VALUE | VARCHAR2 (25) | Default value of the parameter                                                |

## V\$SYS\_TIME\_MODEL

V\$SYS\_TIME\_MODEL displays the system-wide accumulated times for various operations. The time reported is the total elapsed or CPU time (in microseconds). Any timed operation will buffer at most 5 seconds of time data. Specifically, this means that if a timed operation (such as SQL execution) takes a long period of time to perform, the data published to this view is at most missing 5 seconds of the time accumulated for the operation.

The time values are 8-byte integers and can therefore hold approximately 580,000 years worth of time before wrapping. Background process time is not included in a statistic value unless the statistic is specifically for background processes.

| Column    | Datatype      | Description                                                                  |
|-----------|---------------|------------------------------------------------------------------------------|
| STAT_ID   | NUMBER        | Statistic identifier for the time statistic                                  |
| STAT_NAME | VARCHAR2 (64) | Name of the statistic (see <a href="#">Table 9-1</a> on page 9-7)            |
| VALUE     | NUMBER        | Amount of time (in microseconds) that the system has spent in this operation |

## V\$SYSAUX\_OCCUPANTS

V\$SYSAUX\_OCCUPANTS displays SYSAUX tablespace occupant information.

| Column              | Datatype      | Description                                        |
|---------------------|---------------|----------------------------------------------------|
| OCCUPANT_NAME       | VARCHAR2 (64) | Occupant name                                      |
| OCCUPANT_DESC       | VARCHAR2 (64) | Occupant description                               |
| SCHEMA_NAME         | VARCHAR2 (64) | Schema name for the occupant                       |
| MOVE_PROCEDURE      | VARCHAR2 (64) | Name of the move procedure; null if not applicable |
| MOVE_PROCEDURE_DESC | VARCHAR2 (64) | Description of the move procedure                  |
| SPACE_USAGE_KBYTES  | NUMBER        | Current space usage of the occupant (in KB)        |

## V\$SYSMETRIC

V\$SYSMETRIC displays the system metric values captured for the most current time interval for both the long duration (60-second) and short duration (15-second) system metrics.

| Column       | Datatype      | Description                               |
|--------------|---------------|-------------------------------------------|
| BEGIN_TIME   | DATE          | Begin time of the interval                |
| END_TIME     | DATE          | End time of the interval                  |
| INTSIZE_CSEC | NUMBER        | Interval size (in hundredths of a second) |
| GROUP_ID     | NUMBER        | Metric group ID                           |
| METRIC_ID    | NUMBER        | Metric ID                                 |
| METRIC_NAME  | VARCHAR2 (64) | Metric name                               |
| VALUE        | NUMBER        | Metric value                              |
| METRIC_UNIT  | VARCHAR2 (64) | Metric unit description                   |

## V\$SYSMETRIC\_HISTORY

V\$SYSMETRIC\_HISTORY displays all system metric values available in the database. Both long duration (60-second with 1 hour history) and short duration (15-second with one-interval only) metrics are displayed by this view.

| Column       | Datatype      | Description                               |
|--------------|---------------|-------------------------------------------|
| BEGIN_TIME   | DATE          | Begin time of the interval                |
| END_TIME     | DATE          | End time of the interval                  |
| INTSIZE_CSEC | NUMBER        | Interval size (in hundredths of a second) |
| GROUP_ID     | NUMBER        | Metric group ID                           |
| METRIC_ID    | NUMBER        | Metric ID                                 |
| METRIC_NAME  | VARCHAR2 (64) | Metric name                               |
| VALUE        | NUMBER        | Metric value                              |
| METRIC_UNIT  | VARCHAR2 (64) | Metric unit description                   |

## V\$SYSMETRIC\_SUMMARY

V\$SYSMETRIC\_SUMMARY displays a summary of all system Metric values for the long-duration system metrics. The average, maximum value, minimum value, and the value of one standard deviation for the last hour are displayed for each metric item.

| Column             | Datatype      | Description                               |
|--------------------|---------------|-------------------------------------------|
| BEGIN_TIME         | DATE          | Begin time of the interval                |
| END_TIME           | DATE          | End time of the interval                  |
| INTSIZE_CSEC       | NUMBER        | Interval size (in hundredths of a second) |
| GROUP_ID           | NUMBER        | Metric group ID                           |
| METRIC_ID          | NUMBER        | Metric ID                                 |
| METRIC_NAME        | VARCHAR2 (64) | Metric name                               |
| NUM_INTERVAL       | NUMBER        | Number of intervals observed              |
| MAXVAL             | NUMBER        | Maximum value observed                    |
| MINVAL             | NUMBER        | Minimum value observed                    |
| AVERAGE            | NUMBER        | Average value over the period             |
| STANDARD_DEVIATION | NUMBER        | One standard deviation                    |
| METRIC_UNIT        | VARCHAR2 (64) | Metric unit description                   |

## V\$SYSSTAT

V\$SYSSTAT displays system statistics. To find the name of the statistic associated with each statistic number (STATISTIC#), query the V\$STATNAME view.

| Column     | Datatype      | Description                                                                                                                                                                                                               |
|------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STATISTIC# | NUMBER        | Statistic number<br><br><b>Note:</b> Statistics numbers are not guaranteed to remain constant from one release to another. Therefore, you should rely on the statistics name rather than its number in your applications. |
| NAME       | VARCHAR2 (64) | Statistic name. You can get a complete listing of statistic names by querying the V\$STATNAME view.                                                                                                                       |

| Column  | Datatype | Description                                                                                                                                                                                                                                                                                                        |
|---------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CLASS   | NUMBER   | A number representing one or more statistics class. The following class numbers are additive: <ul style="list-style-type: none"> <li>1 - User</li> <li>2 - Redo</li> <li>4 - Enqueue</li> <li>8 - Cache</li> <li>16 - OS</li> <li>32 - Real Application Clusters</li> <li>64 - SQL</li> <li>128 - Debug</li> </ul> |
| VALUE   | NUMBER   | Statistic value                                                                                                                                                                                                                                                                                                    |
| STAT_ID | NUMBER   | Identifier of the statistic                                                                                                                                                                                                                                                                                        |

**See Also:** ["V\\$STATNAME"](#) on page 9-63 and [Appendix E, "Statistics Descriptions"](#)

## V\$SYSTEM\_CURSOR\_CACHE

V\$SYSTEM\_CURSOR\_CACHE displays system wide information on cursor usage.

**See Also:** ["V\\$SESSION\\_CURSOR\\_CACHE"](#) on page 9-16

| Column    | Datatype | Description                                                                                              |
|-----------|----------|----------------------------------------------------------------------------------------------------------|
| OPENS     | NUMBER   | Cumulative total of cursor opens                                                                         |
| HITS      | NUMBER   | Cumulative total of cursor open hits                                                                     |
| HIT_RATIO | NUMBER   | Ratio of the number of times an open cursor was found divided by the number of times a cursor was sought |

## V\$SYSTEM\_EVENT

V\$SYSTEM\_EVENT displays information on total waits for an event. Note that the TIME\_WAITED and AVERAGE\_WAIT columns will contain a value of zero on those platforms that do not support a fast timing mechanism. If you are running on one of these platforms and you want this column to reflect true wait times, then you must set TIMED\_STATISTICS to TRUE in the parameter file; doing this will have a small negative effect on system performance.

**See Also:** ["TIMED\\_STATISTICS"](#) on page 1-173

| Column            | Datatype      | Description                                                             |
|-------------------|---------------|-------------------------------------------------------------------------|
| EVENT             | VARCHAR2 (64) | Name of the wait event                                                  |
| TOTAL_WAITS       | NUMBER        | Total number of waits for the event                                     |
| TOTAL_TIMEOUTS    | NUMBER        | Total number of timeouts for the event                                  |
| TIME_WAITED       | NUMBER        | Total amount of time waited for the event (in hundredths of a second)   |
| AVERAGE_WAIT      | NUMBER        | Average amount of time waited for the event (in hundredths of a second) |
| TIME_WAITED_MICRO | NUMBER        | Total amount of time waited for the event (in microseconds)             |
| TOTAL_WAITS_FG    | NUMBER        | Total number of waits for the event, from foreground sessions           |
| TOTAL_TIMEOUTS_FG | NUMBER        | Total number of timeouts for the event, from foreground sessions        |

| Column               | Datatype      | Description                                                                                       |
|----------------------|---------------|---------------------------------------------------------------------------------------------------|
| TIME_WAITED_FG       | NUMBER        | Amount of time waited for the event (in hundredths of a second), from foreground sessions         |
| AVERAGE_WAIT_FG      | NUMBER        | Average amount of time waited for the event (in hundredths of a second), from foreground sessions |
| TIME_WAITED_MICRO_FG | NUMBER        | Amount of time waited for the event (in microseconds), from foreground sessions                   |
| EVENT_ID             | NUMBER        | Identifier of the wait event                                                                      |
| WAIT_CLASS_ID        | NUMBER        | Identifier of the class of the wait event                                                         |
| WAIT_CLASS#          | NUMBER        | Number of the class of the wait event                                                             |
| WAIT_CLASS           | VARCHAR2 (64) | Name of the class of the wait event                                                               |

## V\$SYSTEM\_FIX\_CONTROL

V\$SYSTEM\_FIX\_CONTROL displays information about Fix Control (enabled/disabled) at the system level.

| Column                   | Datatype      | Description                                                                   |
|--------------------------|---------------|-------------------------------------------------------------------------------|
| BUGNO                    | NUMBER        | Bug number (as fix control identifier)                                        |
| VALUE                    | NUMBER        | Current value set for the fix control                                         |
| SQL_FEATURE              | VARCHAR2 (64) | Feature control ID                                                            |
| DESCRIPTION              | VARCHAR2 (64) | Description of the fix control                                                |
| OPTIMIZER_FEATURE_ENABLE | VARCHAR2 (25) | Version on (and after) which the fix is enabled by default                    |
| EVENT                    | NUMBER        | Event formerly used to control this fix                                       |
| IS_DEFAULT               | NUMBER        | Indicates whether the current value is the same as the default (1) or not (0) |

## V\$SYSTEM\_PARAMETER

V\$SYSTEM\_PARAMETER displays information about the initialization parameters that are currently in effect for the instance. A new session inherits parameter values from the instance-wide values.

| Column        | Datatype        | Description                                                                                                                                                                                                   |
|---------------|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NUM           | NUMBER          | Parameter number                                                                                                                                                                                              |
| NAME          | VARCHAR2 (80)   | Name of the parameter                                                                                                                                                                                         |
| TYPE          | NUMBER          | Parameter type: <ul style="list-style-type: none"> <li>■ 1 - Boolean</li> <li>■ 2 - String</li> <li>■ 3 - Integer</li> <li>■ 4 - Parameter file</li> <li>■ 5 - Reserved</li> <li>■ 6 - Big integer</li> </ul> |
| VALUE         | VARCHAR2 (4000) | Instance-wide parameter value                                                                                                                                                                                 |
| DISPLAY_VALUE | VARCHAR2 (4000) | Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K.                       |
| ISDEFAULT     | VARCHAR2 (9)    | Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE)                                                                         |

| Column                | Datatype       | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ISSES_MODIFIABLE      | VARCHAR2 (5)   | Indicates whether the parameter can be changed with ALTER SESSION (TRUE) or not (FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| ISSYS_MODIFIABLE      | VARCHAR2 (9)   | Indicates whether the parameter can be changed with ALTER SYSTEM and when the change takes effect: <ul style="list-style-type: none"> <li>■ IMMEDIATE - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect immediately.</li> <li>■ DEFERRED - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect in subsequent sessions.</li> <li>■ FALSE - Parameter cannot be changed with ALTER SYSTEM unless a server parameter file was used to start the instance. The change takes effect in subsequent instances.</li> </ul> |
| ISINSTANCE_MODIFIABLE | VARCHAR2 (5)   | For parameters that can be changed with ALTER SYSTEM, indicates whether the value of the parameter can be different for every instance (TRUE) or whether the parameter must have the same value for all Real Application Clusters instances (FALSE). If the ISSYS_MODIFIABLE column is FALSE, then this column is always FALSE.                                                                                                                                                                                                                                                                                                                                                                |
| ISMODIFIED            | VARCHAR2 (8)   | Indicates how the parameter was modified. If an ALTER SYSTEM was performed, the value will be MODIFIED.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| ISADJUSTED            | VARCHAR2 (5)   | Indicates whether Oracle adjusted the input value to a more suitable value (for example, the parameter value should be prime, but the user input a non-prime number, so Oracle adjusted the value to the next prime number)                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| ISDEPRECATED          | VARCHAR2 (5)   | Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| ISBASIC               | VARCHAR2 (5)   | Indicates whether the parameter is a basic parameter (TRUE) or not (FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| DESCRIPTION           | VARCHAR2 (255) | Description of the parameter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| UPDATE_COMMENT        | VARCHAR2 (255) | Comments associated with the most recent update                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| HASH                  | NUMBER         | Hash value for the parameter name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## V\$SYSTEM\_PARAMETER2

V\$SYSTEM\_PARAMETER2 displays information about the initialization parameters that are currently in effect for the instance, with each list parameter value appearing as a row in the view. A new session inherits parameter values from the instance-wide values.

Presenting the list parameter values in this format enables you to quickly determine the values for a list parameter. For example, if a parameter value is a, b, then the V\$SYSTEM\_PARAMETER view does not tell you if the parameter has two values (both a and b) or one value (a, b). V\$SYSTEM\_PARAMETER2 makes the distinction between the list parameter values clear.

| Column | Datatype      | Description           |
|--------|---------------|-----------------------|
| NUM    | NUMBER        | Parameter number      |
| NAME   | VARCHAR2 (80) | Name of the parameter |

| Column                | Datatype        | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TYPE                  | NUMBER          | Parameter type: <ul style="list-style-type: none"> <li>1 - Boolean</li> <li>2 - String</li> <li>3 - Integer</li> <li>4 - Parameter file</li> <li>5 - Reserved</li> <li>6 - Big integer</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| VALUE                 | VARCHAR2 (4000) | Parameter value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| DISPLAY_VALUE         | VARCHAR2 (4000) | Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ISDEFAULT             | VARCHAR2 (6)    | Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| ISSES_MODIFIABLE      | VARCHAR2 (5)    | Indicates whether the parameter can be changed with ALTER SESSION (TRUE) or not (FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ISSYS_MODIFIABLE      | VARCHAR2 (9)    | Indicates whether the parameter can be changed with ALTER SYSTEM and when the change takes effect: <ul style="list-style-type: none"> <li>IMMEDIATE - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect immediately.</li> <li>DEFERRED - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect in subsequent sessions.</li> <li>FALSE - Parameter cannot be changed with ALTER SYSTEM unless a server parameter file was used to start the instance. The change takes effect in subsequent instances.</li> </ul> |
| ISINSTANCE_MODIFIABLE | VARCHAR2 (5)    | For parameters that can be changed with ALTER SYSTEM, indicates whether the value of the parameter can be different for every instance (TRUE) or whether the parameter must have the same value for all Real Application Clusters instances (FALSE). If the ISSYS_MODIFIABLE column is FALSE, then this column is always FALSE.                                                                                                                                                                                                                                                                                                                                                          |
| ISMODIFIED            | VARCHAR2 (8)    | Indicates how the parameter was modified. If an ALTER SYSTEM was performed, the value will be MODIFIED.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ISADJUSTED            | VARCHAR2 (5)    | Indicates whether Oracle adjusted the input value to a more suitable value (for example, the parameter value should be prime, but the user input a non-prime number, so Oracle adjusted the value to the next prime number)                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| ISDEPRECATED          | VARCHAR2 (5)    | Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| ISBASIC               | VARCHAR2 (5)    | Indicates whether the parameter is a basic parameter (TRUE) or not (FALSE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| DESCRIPTION           | VARCHAR2 (255)  | Description of the parameter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| ORDINAL               | NUMBER          | Position (ordinal number) of the parameter value. Useful only for parameters whose values are lists of strings.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| UPDATE_COMMENT        | VARCHAR2 (255)  | Comments associated with the most recent update                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

## V\$SYSTEM\_WAIT\_CLASS

V\$SYSTEM\_WAIT\_CLASS displays the instance-wide time totals for each registered wait class.

| Column        | Datatype | Description                  |
|---------------|----------|------------------------------|
| WAIT_CLASS_ID | NUMBER   | Identifier of the wait class |

| Column         | Datatype      | Description                                                                                           |
|----------------|---------------|-------------------------------------------------------------------------------------------------------|
| WAIT_CLASS#    | NUMBER        | Number of the wait class                                                                              |
| WAIT_CLASS     | VARCHAR2 (64) | Name of the wait class                                                                                |
| TOTAL_WAITS    | NUMBER        | Number of times waits of the class occurred                                                           |
| TIME_WAITED    | NUMBER        | Amount of time (in hundredths of a second) spent in the wait by all sessions in the instance          |
| TOTAL_WAITS_FG | NUMBER        | Number of times waits from this wait class occurred in foreground sessions                            |
| TIME_WAITED_FG | NUMBER        | Amount of time (in hundredths of a second) spent in waits from this wait class in foreground sessions |

## V\$TABLESPACE

V\$TABLESPACE displays tablespace information from the control file.

| Column                      | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TS#                         | NUMBER        | Tablespace number                                                                                                                                                                                                                                                                                                                                                     |
| NAME                        | VARCHAR2 (30) | Tablespace name                                                                                                                                                                                                                                                                                                                                                       |
| INCLUDED_IN_DATABASE_BACKUP | VARCHAR2 (3)  | Indicates whether the tablespace is included in full database backups using the BACKUP DATABASE RMAN command (YES) or not (NO); NO only if the CONFIGURE EXCLUDE RMAN command was used for this tablespace                                                                                                                                                            |
| BIGFILE                     | VARCHAR2 (3)  | Indicates whether the tablespace is a bigfile tablespace (YES) or a smallfile tablespace (NO)                                                                                                                                                                                                                                                                         |
| FLASHBACK_ON                | VARCHAR2 (3)  | Indicates whether the tablespace participates in FLASHBACK DATABASE operations (YES) or not (NO)                                                                                                                                                                                                                                                                      |
| ENCRYPT_IN_BACKUP           | VARCHAR2 (3)  | Indicates whether encryption is turned ON or off at the tablespace level: <ul style="list-style-type: none"> <li>ON - Encryption is turned ON at the tablespace level</li> <li>OFF - Encryption is turned OFF at the tablespace level</li> <li>NULL - Encryption is neither explicitly turned on nor off at the tablespace level (default or when cleared)</li> </ul> |

## V\$TEMP\_CACHE\_TRANSFER

V\$TEMP\_CACHE\_TRANSFER is deprecated. The information that was provided in this view is now provided in the V\$INSTANCE\_CACHE\_TRANSFER and V\$SEGMENT\_STATISTICS views.

| Column                | Datatype | Description                                                                 |
|-----------------------|----------|-----------------------------------------------------------------------------|
| FILE_NUMBER           | NUMBER   | Number of the tempfile                                                      |
| X_2_NULL              | NUMBER   | Number of blocks with Exclusive-to-NULL conversions; always 0               |
| X_2_NULL_FORCED_WRITE | NUMBER   | Number of Exclusive-to-NULL forced writes; always 0                         |
| X_2_NULL_FORCED_STALE | NUMBER   | Number of Exclusive-to-NULL blocks converted to CR; always 0                |
| X_2_S                 | NUMBER   | Number of blocks with Exclusive-to-Shared conversions; always 0             |
| X_2_S_FORCED_WRITE    | NUMBER   | Number of Exclusive-to-Shared forced writes; always 0                       |
| S_2_NULL              | NUMBER   | Number of blocks with Shared-to-NULL conversions; always 0                  |
| S_2_NULL_FORCED_STALE | NUMBER   | Number of Shared-to-NULL blocks converted to CR; always 0                   |
| RBR                   | NUMBER   | Number of reuse blocks cross-instance calls; always 0                       |
| RBR_FORCED_WRITE      | NUMBER   | Number of blocks written due to reuse blocks cross-instance calls; always 0 |



| Column   | Datatype | Description                                                     |
|----------|----------|-----------------------------------------------------------------|
| NULL_2_X | NUMBER   | Number of blocks with NULL-to-Exclusive conversions; always 0   |
| S_2_X    | NUMBER   | Number of blocks with Shared-to-Exclusive conversions; always 0 |
| NULL_2_S | NUMBER   | Number of blocks with NULL-to-Shared conversions; always 0      |

## V\$TEMP\_EXTENT\_MAP

V\$TEMP\_EXTENT\_MAP displays the status of each unit for all LOCALLY MANAGED temporary tablespaces.

| Column        | Datatype      | Description                                 |
|---------------|---------------|---------------------------------------------|
| TABSPACE_NAME | VARCHAR2 (30) | Name of the tablespace this unit belongs to |
| FILE_ID       | NUMBER        | Absolute file number                        |
| BLOCK_ID      | NUMBER        | Begin block number for this unit            |
| BYTES         | NUMBER        | Bytes in the extent                         |
| BLOCKS        | NUMBER        | Blocks in the extent                        |
| OWNER         | NUMBER        | Instance which owns this unit               |
| RELATIVE_FNO  | NUMBER        | Relative file number                        |

## V\$TEMP\_EXTENT\_POOL

V\$TEMP\_EXTENT\_POOL displays the state of temporary space cached and used for the instance. Note that loading of the temporary space cache is lazy and that instances can be dormant.

| Column         | Datatype      | Description                                    |
|----------------|---------------|------------------------------------------------|
| TABSPACE_NAME  | VARCHAR2 (30) | Name of the tablespace                         |
| FILE_ID        | NUMBER        | Absolute file number                           |
| EXTENTS_CACHED | NUMBER        | Number of extents that have been cached        |
| EXTENTS_USED   | NUMBER        | Number of extents that are actually being used |
| BLOCKS_CACHED  | NUMBER        | Number of blocks that are cached               |
| BLOCKS_USED    | NUMBER        | Number of blocks that are used                 |
| BYTES_CACHED   | NUMBER        | Number of bytes that are cached                |
| BYTES_USED     | NUMBER        | Number of bytes that are used                  |
| RELATIVE_FNO   | NUMBER        | Relative file number                           |

## V\$TEMP\_SPACE\_HEADER

V\$TEMP\_SPACE\_HEADER displays aggregate information per file per LOCALLY MANAGED temporary tablespace regarding how much space is currently being used and how much is free as identified in the space header.

| Column        | Datatype      | Description                      |
|---------------|---------------|----------------------------------|
| TABSPACE_NAME | VARCHAR2 (30) | Name of the temporary tablespace |
| FILE_ID       | NUMBER        | Absolute file number             |
| BYTES_USED    | NUMBER        | How many bytes are in use        |
| BLOCKS_USED   | NUMBER        | How many blocks are in use       |

| Column       | Datatype | Description                           |
|--------------|----------|---------------------------------------|
| BYTES_FREE   | NUMBER   | How many bytes are free               |
| BLOCKS_FREE  | NUMBER   | How many blocks are free              |
| RELATIVE_FNO | NUMBER   | The relative file number for the file |

## V\$TEMPFILE

V\$TEMPFILE displays tempfile information.

| Column           | Datatype       | Description                                       |
|------------------|----------------|---------------------------------------------------|
| FILE#            | NUMBER         | Absolute file number                              |
| CREATION_CHANGE# | NUMBER         | Creation System Change Number (SCN)               |
| CREATION_TIME    | DATE           | Creation time                                     |
| TS#              | NUMBER         | Tablespace number                                 |
| RFILE#           | NUMBER         | Relative file number in the tablespace            |
| STATUS           | VARCHAR2 (7)   | Status of the file (OFFLINE   ONLINE)             |
| ENABLED          | VARCHAR2 (10)  | Enabled for read and/or write                     |
| BYTES            | NUMBER         | Size of the file in bytes (from the file header)  |
| BLOCKS           | NUMBER         | Size of the file in blocks (from the file header) |
| CREATE_BYTES     | NUMBER         | Creation size of the file (in bytes)              |
| BLOCK_SIZE       | NUMBER         | Block size for the file                           |
| NAME             | VARCHAR2 (513) | Name of the file                                  |

## V\$TEMPORARY\_LOBS

V\$TEMPORARY\_LOBS displays temporary LOBs.

| Column        | Datatype | Description                 |
|---------------|----------|-----------------------------|
| SID           | NUMBER   | Session ID                  |
| CACHE_LOBS    | NUMBER   | Number of cache temp LOBs   |
| NOCACHE_LOBS  | NUMBER   | Number of nocache temp LOBs |
| ABSTRACT_LOBS | NUMBER   | Number of abstract LOBs     |

## V\$TEMPSEG\_USAGE

V\$TEMPSEG\_USAGE describes temporary segment usage.

| Column       | Datatype      | Description                                                                                                                           |
|--------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------|
| USERNAME     | VARCHAR2 (30) | User who requested temporary space                                                                                                    |
| USER         | VARCHAR2 (30) | This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in USERNAME. |
| SESSION_ADDR | RAW (4   8)   | Address of shared SQL cursor                                                                                                          |
| SESSION_NUM  | NUMBER        | Serial number of session                                                                                                              |
| SQLADDR      | RAW (4   8)   | Address of SQL statement                                                                                                              |
| SQLHASH      | NUMBER        | Hash value of SQL statement                                                                                                           |
| SQL_ID       | VARCHAR2 (13) | SQL identifier of SQL statement                                                                                                       |
| TABLESPACE   | VARCHAR2 (31) | Tablespace in which space is allocated                                                                                                |

| Column   | Datatype     | Description                                                                                                                                                              |
|----------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CONTENTS | VARCHAR2 (9) | Indicates whether tablespace is TEMPORARY or PERMANENT                                                                                                                   |
| SEGTYPE  | VARCHAR2 (9) | Type of sort segment: <ul style="list-style-type: none"> <li>■ SORT</li> <li>■ HASH</li> <li>■ DATA</li> <li>■ INDEX</li> <li>■ LOB_DATA</li> <li>■ LOB_INDEX</li> </ul> |
| SEGFILE# | NUMBER       | File number of initial extent                                                                                                                                            |
| SEGBLK#  | NUMBER       | Block number of the initial extent                                                                                                                                       |
| EXTENTS  | NUMBER       | Extents allocated to the sort                                                                                                                                            |
| BLOCKS   | NUMBER       | Extents in blocks allocated to the sort                                                                                                                                  |
| SEGRFNO# | NUMBER       | Relative file number of initial extent                                                                                                                                   |

## V\$TEMPSTAT

V\$TEMPSTAT displays information about file read/write statistics.

| Column         | Datatype | Description                                                                                                                |
|----------------|----------|----------------------------------------------------------------------------------------------------------------------------|
| FILE#          | NUMBER   | Number of the file                                                                                                         |
| PHYRDS         | NUMBER   | Number of physical reads done                                                                                              |
| PHYWRTS        | NUMBER   | Number of times DBWR is required to write                                                                                  |
| PHYBLKRD       | NUMBER   | Number of physical blocks read                                                                                             |
| PHYBLKWRT      | NUMBER   | Number of blocks written to disk, which may be the same as PHYWRTS if all writes are single blocks                         |
| SINGLEBLKRDS   | NUMBER   | Number of single block reads                                                                                               |
| READTIM        | NUMBER   | Time (in hundredths of a second) spent doing reads if the TIMED_STATISTICS parameter is true; 0 if false                   |
| WRITETIM       | NUMBER   | Time (in hundredths of a second) spent doing writes if the TIMED_STATISTICS parameter is true; 0 if false                  |
| SINGLEBLKRDTIM | NUMBER   | Cumulative single block read time (in hundredths of a second)                                                              |
| AVGIOTIM       | NUMBER   | Average time (in hundredths of a second) spent on I/O, if the TIMED_STATISTICS parameter is true; 0 if false               |
| LSTIOTIM       | NUMBER   | Time (in hundredths of a second) spent doing the last I/O, if the TIMED_STATISTICS parameter is true; 0 if false           |
| MINIOTIM       | NUMBER   | Minimum time (in hundredths of a second) spent on a single I/O, if the TIMED_STATISTICS parameter is true; 0 if false      |
| MAXIORTM       | NUMBER   | Maximum time (in hundredths of a second) spent doing a single read, if the TIMED_STATISTICS parameter is true; 0 if false  |
| MAXIOWTM       | NUMBER   | Maximum time (in hundredths of a second) spent doing a single write, if the TIMED_STATISTICS parameter is true; 0 if false |

## V\$THREAD

V\$THREAD displays thread information from the control file. This view does not return meaningful results on a physical standby database.

| Column  | Datatype | Description   |
|---------|----------|---------------|
| THREAD# | NUMBER   | Thread number |

## V\$THRESHOLD\_TYPES

| Column              | Datatype      | Description                                                      |
|---------------------|---------------|------------------------------------------------------------------|
| STATUS              | VARCHAR2 (6)  | Thread status (OPEN   CLOSED)                                    |
| ENABLED             | VARCHAR2 (8)  | Enabled status: DISABLED, (enabled) PRIVATE, or (enabled) PUBLIC |
| GROUPS              | NUMBER        | Number of log groups assigned to this thread                     |
| INSTANCE            | VARCHAR2 (16) | Instance name, if available                                      |
| OPEN_TIME           | DATE          | Last time the thread was opened                                  |
| CURRENT_GROUP#      | NUMBER        | Current log group                                                |
| SEQUENCE#           | NUMBER        | Sequence number of current log                                   |
| CHECKPOINT_CHANGE#  | NUMBER        | SCN at last checkpoint                                           |
| CHECKPOINT_TIME     | DATE          | Time of last checkpoint                                          |
| ENABLE_CHANGE#      | NUMBER        | SCN at which thread was enabled                                  |
| ENABLE_TIME         | DATE          | Time of enable SCN                                               |
| DISABLE_CHANGE#     | NUMBER        | SCN at which thread was disabled                                 |
| DISABLE_TIME        | DATE          | Time of disable SCN                                              |
| LAST_REDO_SEQUENCE# | NUMBER        | Last redo sequence number written by LGWR                        |
| LAST_REDO_BLOCK     | NUMBER        | Last redo block written by LGWR                                  |
| LAST_REDO_CHANGE#   | NUMBER        | SCN of last redo for the thread                                  |
| LAST_REDO_TIME      | DATE          | Time of last redo for the thread                                 |

## V\$THRESHOLD\_TYPES

V\$THRESHOLD\_TYPES displays information about threshold types.

| Column            | Datatype      | Description                                                                                                                                                         |
|-------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| METRICS_ID        | NUMBER        | Metrics ID                                                                                                                                                          |
| METRICS_GROUP_ID  | NUMBER        | Metrics group ID                                                                                                                                                    |
| OPERATOR_MASK     | NUMBER        | Operator mask                                                                                                                                                       |
| OBJECT_TYPE       | VARCHAR2 (64) | Object type: <ul style="list-style-type: none"><li>■ SYSTEM</li><li>■ FILE</li><li>■ SERVICE</li><li>■ EVENT_CLASS</li><li>■ TABLESPACE</li><li>■ SESSION</li></ul> |
| ALERT_REASON_ID   | NUMBER        | ID of the alert reason                                                                                                                                              |
| METRIC_VALUE_TYPE | NUMBER        | Metric value type                                                                                                                                                   |

## V\$TIMER

V\$TIMER displays the elapsed time in hundredths of a second. Time is measured since the beginning of the epoch, which is operating system specific, and wraps around to 0 again whenever the value overflows four bytes (roughly 497 days).

| Column | Datatype | Description                              |
|--------|----------|------------------------------------------|
| HSECS  | NUMBER   | Elapsed time (in hundredths of a second) |

## V\$TIMEZONE\_NAMES

V\$TIMEZONE\_NAMES displays valid time zone names.

| Column   | Datatype      | Description                                            |
|----------|---------------|--------------------------------------------------------|
| TZNAME   | VARCHAR2 (64) | Time zone region (for example, US/Pacific)             |
| TZABBREV | VARCHAR2 (64) | Corresponding daylight abbreviation (for example, PDT) |

## V\$TOPLEVELCALL

V\$TOPLEVELCALL displays the mapping between Oracle top level calls and names.

| Column              | Datatype      | Description                  |
|---------------------|---------------|------------------------------|
| TOP_LEVEL_CALL#     | NUMBER        | Oracle top level call number |
| TOP_LEVEL_CALL_NAME | VARCHAR2 (64) | Oracle top level call name   |

## V\$TRANSACTION

V\$TRANSACTION lists the active transactions in the system.

| Column       | Datatype       | Description                              |
|--------------|----------------|------------------------------------------|
| ADDR         | RAW (4   8)    | Address of the transaction state object  |
| XIDUSN       | NUMBER         | Undo segment number                      |
| XIDSLOT      | NUMBER         | Slot number                              |
| XIDSQN       | NUMBER         | Sequence number                          |
| UBAFIL       | NUMBER         | Undo block address (UBA) filenum         |
| UBABLK       | NUMBER         | UBA block number                         |
| UBASQN       | NUMBER         | UBA sequence number                      |
| UBAREC       | NUMBER         | UBA record number                        |
| STATUS       | VARCHAR2 (16)  | Status                                   |
| START_TIME   | VARCHAR2 (20)  | Start time (wall clock)                  |
| START_SCNB   | NUMBER         | Start system change number (SCN) base    |
| START_SCNW   | NUMBER         | Start SCN wrap                           |
| START_UEXT   | NUMBER         | Start extent number                      |
| START_UBAFIL | NUMBER         | Start UBA file number                    |
| START_UBABLK | NUMBER         | Start UBA block number                   |
| START_UBASQN | NUMBER         | Start UBA sequence number                |
| START_UBAREC | NUMBER         | Start UBA record number                  |
| SES_ADDR     | RAW (4   8)    | User session object address              |
| FLAG         | NUMBER         | Flag                                     |
| SPACE        | VARCHAR2 (3)   | YES if a space transaction               |
| RECURSIVE    | VARCHAR2 (3)   | YES if a recursive transaction           |
| NOUNDO       | VARCHAR2 (3)   | YES if a no undo transaction             |
| PTX          | VARCHAR2 (3)   | YES if parallel transaction              |
| NAME         | VARCHAR2 (256) | Name of a named transaction              |
| PRV_XIDUSN   | NUMBER         | Previous transaction undo segment number |
| PRV_XIDSLT   | NUMBER         | Previous transaction slot number         |

## V\$TRANSACTION\_ENQUEUE

| Column        | Datatype | Description                                                                                                                            |
|---------------|----------|----------------------------------------------------------------------------------------------------------------------------------------|
| PRV_XIDSQN    | NUMBER   | Previous transaction sequence number                                                                                                   |
| PTX_XIDUSN    | NUMBER   | Rollback segment number of the parent XID                                                                                              |
| PTX_XIDSLT    | NUMBER   | Slot number of the parent XID                                                                                                          |
| PTX_XIDSQN    | NUMBER   | Sequence number of the parent XID                                                                                                      |
| DSCN-B        | NUMBER   | This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in DSCN_BASE. |
| DSCN-W        | NUMBER   | This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in DSCN_WRAP. |
| USED_UBLK     | NUMBER   | Number of undo blocks used                                                                                                             |
| USED_UREC     | NUMBER   | Number of undo records used                                                                                                            |
| LOG_IO        | NUMBER   | Logical I/O                                                                                                                            |
| PHY_IO        | NUMBER   | Physical I/O                                                                                                                           |
| CR_GET        | NUMBER   | Consistent gets                                                                                                                        |
| CR_CHANGE     | NUMBER   | Consistent changes                                                                                                                     |
| START_DATE    | DATE     | Start time (wall clock)                                                                                                                |
| DSCN_BASE     | NUMBER   | Dependent SCN base                                                                                                                     |
| DSCN_WRAP     | NUMBER   | Dependent SCN wrap                                                                                                                     |
| START_SCN     | NUMBER   | Start SCN                                                                                                                              |
| DEPENDENT_SCN | NUMBER   | Dependent SCN                                                                                                                          |
| XID           | RAW (8)  | Transaction XID                                                                                                                        |
| PRV_XID       | RAW (8)  | Previous transaction XID                                                                                                               |
| PTX_XID       | RAW (8)  | Parent transaction XID                                                                                                                 |

## V\$TRANSACTION\_ENQUEUE

V\$TRANSACTION\_ENQUEUE displays locks owned by transaction state objects.

| Column | Datatype     | Description                                                                                                                                                                                                                                             |
|--------|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADDR   | RAW (4   8)  | Address of lock state object                                                                                                                                                                                                                            |
| KADDR  | RAW (4   8)  | Address of lock                                                                                                                                                                                                                                         |
| SID    | NUMBER       | Identifier for session holding or acquiring the lock                                                                                                                                                                                                    |
| TYPE   | VARCHAR2 (2) | Type of lock. TX indicates transaction enqueue.                                                                                                                                                                                                         |
| ID1    | NUMBER       | Lock identifier #1 (depends on type)                                                                                                                                                                                                                    |
| ID2    | NUMBER       | Lock identifier #2 (depends on type)                                                                                                                                                                                                                    |
| LMODE  | NUMBER       | Lock mode in which the session holds the lock: <ul style="list-style-type: none"><li>0 - none</li><li>1 - null (NULL)</li><li>2 - row-S (SS)</li><li>3 - row-X (SX)</li><li>4 - share (S)</li><li>5 - S/Row-X (SSX)</li><li>6 - exclusive (X)</li></ul> |

| Column  | Datatype | Description                                                                                                                                                                                                                                                        |
|---------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REQUEST | NUMBER   | Lock mode in which the process requests the lock: <ul style="list-style-type: none"> <li>0 - none</li> <li>1 - null (NULL)</li> <li>2 - row-S (SS)</li> <li>3 - row-X (SX)</li> <li>4 - share (S)</li> <li>5 - S/Row-X (SSX)</li> <li>6 - exclusive (X)</li> </ul> |
| CTIME   | NUMBER   | Time since current mode was granted                                                                                                                                                                                                                                |
| BLOCK   | NUMBER   | The lock is blocking another lock                                                                                                                                                                                                                                  |

## V\$TRANSPORTABLE\_PLATFORM

V\$TRANSPORTABLE\_PLATFORM displays all platforms that support cross-platform tablespace transport. Specifically, it lists all platforms supported by the RMAN CONVERT TABLESPACE command, along with the endianness of each platform.

| Column        | Datatype       | Description                                                                                                           |
|---------------|----------------|-----------------------------------------------------------------------------------------------------------------------|
| PLATFORM_ID   | NUMBER         | Platform identification number                                                                                        |
| PLATFORM_NAME | VARCHAR2 (101) | Platform name                                                                                                         |
| ENDIAN_FORMAT | VARCHAR2 (14)  | Platform endian format: <ul style="list-style-type: none"> <li>Big</li> <li>Little</li> <li>UNKNOWN FORMAT</li> </ul> |

## V\$TYPE\_SIZE

V\$TYPE\_SIZE displays the sizes of various database components for use in estimating data block capacity.

| Column      | Datatype      | Description                                      |
|-------------|---------------|--------------------------------------------------|
| COMPONENT   | VARCHAR2 (8)  | Component name, such as segment or buffer header |
| TYPE        | VARCHAR2 (8)  | Component type                                   |
| DESCRIPTION | VARCHAR2 (32) | Description of the component                     |
| TYPE_SIZE   | NUMBER        | Size of the component                            |

## V\$UNDOSTAT

V\$UNDOSTAT displays a histogram of statistical data to show how well the system is working. The available statistics include undo space consumption, transaction concurrency, and length of queries executed in the instance. You can use this view to estimate the amount of undo space required for the current workload. Oracle uses this view to tune undo usage in the system. The view returns NULL values if the system is in manual undo management mode.

Each row in the view keeps statistics collected in the instance for a 10-minute interval. The rows are in descending order by the BEGIN\_TIME column value. Each row belongs to the time interval marked by (BEGIN\_TIME, END\_TIME). Each column represents the data collected for the particular statistic in that time interval. The first

row of the view contains statistics for the (partial) current time period. The view contains a total of 576 rows, spanning a 4 day cycle.

| Column              | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BEGIN_TIME          | DATE          | Identifies the beginning of the time interval                                                                                                                                                                                                                                                                                                                                                                                         |
| END_TIME            | DATE          | Identifies the end of the time interval                                                                                                                                                                                                                                                                                                                                                                                               |
| UNDOTSN             | NUMBER        | Represents the last active undo tablespace in the duration of time. The tablespace ID of the active undo tablespace is returned in this column. If more than one undo tablespace was active in that period, the active undo tablespace that was active at the end of the period is reported.                                                                                                                                          |
| UNDOBLKS            | NUMBER        | Represents the total number of undo blocks consumed. You can use this column to obtain the consumption rate of undo blocks, and thereby estimate the size of the undo tablespace needed to handle the workload on your system.                                                                                                                                                                                                        |
| TXNCOUNT            | NUMBER        | Identifies the total number of transactions executed within the period                                                                                                                                                                                                                                                                                                                                                                |
| MAXQUERYLEN         | NUMBER        | Identifies the length of the longest query (in seconds) executed in the instance during the period. You can use this statistic to estimate the proper setting of the UNDO_RETENTION initialization parameter. The length of a query is measured from the cursor open time to the last fetch/execute time of the cursor. Only the length of those cursors that have been fetched/executed during the period are reflected in the view. |
| MAXQUERYID          | VARCHAR2 (13) | SQL identifier of the longest running SQL statement in the period                                                                                                                                                                                                                                                                                                                                                                     |
| MAXCONCURRENCY      | NUMBER        | Identifies the highest number of transactions executed concurrently within the period                                                                                                                                                                                                                                                                                                                                                 |
| UNXPSTEALCNT        | NUMBER        | Number of attempts to obtain undo space by stealing unexpired extents from other transactions                                                                                                                                                                                                                                                                                                                                         |
| UNXPBLKRELCNT       | NUMBER        | Number of unexpired blocks removed from certain undo segments so they can be used by other transactions                                                                                                                                                                                                                                                                                                                               |
| UNXPBLKREUCNT       | NUMBER        | Number of unexpired undo blocks reused by transactions                                                                                                                                                                                                                                                                                                                                                                                |
| EXPSTEALCNT         | NUMBER        | Number of attempts to steal expired undo blocks from other undo segments                                                                                                                                                                                                                                                                                                                                                              |
| EXPBLKRELCNT        | NUMBER        | Number of expired undo blocks stolen from other undo segments                                                                                                                                                                                                                                                                                                                                                                         |
| EXPBLKREUCNT        | NUMBER        | Number of expired undo blocks reused within the same undo segments                                                                                                                                                                                                                                                                                                                                                                    |
| SSOLDERRCNT         | NUMBER        | Identifies the number of times the error ORA-01555 occurred. You can use this statistic to decide whether or not the UNDO_RETENTION initialization parameter is set properly given the size of the undo tablespace. Increasing the value of UNDO_RETENTION can reduce the occurrence of this error.                                                                                                                                   |
| NOSPACEERRCNT       | NUMBER        | Identifies the number of times space was requested in the undo tablespace and there was no free space available. That is, all of the space in the undo tablespace was in use by active transactions. The corrective action is to add more space to the undo tablespace.                                                                                                                                                               |
| ACTIVEBLKS          | NUMBER        | Total number of blocks in the active extents of the undo tablespace for the instance at the sampled time in the period                                                                                                                                                                                                                                                                                                                |
| UNEXPIREDBLKS       | NUMBER        | Total number of blocks in the unexpired extents of the undo tablespace for the instance at the sampled time in the period                                                                                                                                                                                                                                                                                                             |
| EXPIREDBLKS         | NUMBER        | Total number of blocks in the expired extents of the undo tablespace for the instance at the sampled time in the period                                                                                                                                                                                                                                                                                                               |
| TUNED_UNDORETENTION | NUMBER        | Amount of time (in seconds) for which undo will not be recycled from the time it was committed. At any point in time, the latest value of TUNED_UNDORETENTION is used to determine whether data committed at a particular time in the past can be recycled.                                                                                                                                                                           |

## V\$UNUSABLE\_BACKUPFILE\_DETAILS

V\$UNUSABLE\_BACKUPFILE\_DETAILS displays information about all backup files (backup pieces, proxy copies, or copies) that are marked unavailable and expired. You



can select one of the rows and use BTYPE\_KEY or FILETYPE\_KEY to change the status of a backup file set or a specific file to available.

| Column            | Datatype       | Description                                                                                                                               |
|-------------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| SESSION_KEY       | NUMBER         | Session identifier                                                                                                                        |
| SESSION_RECID     | NUMBER         | Session record ID                                                                                                                         |
| SESSION_STAMP     | NUMBER         | Session stamp                                                                                                                             |
| RMAN_STATUS_RECID | NUMBER         | Record ID of the corresponding row in the control file                                                                                    |
| RMAN_STATUS_STAMP | NUMBER         | Timestamp of the row in the controlfile                                                                                                   |
| BTYPE             | CHAR (9)       | Backup type container. Possible values are: BACKUPSET, IMAGECOPY, PROXYCOPY.                                                              |
| BTYPE_KEY         | NUMBER         | Unique identifier for the backup type, either BS_KEY or COPY_KEY.                                                                         |
| ID1               | NUMBER         | If BACKUPSET, it contains SET_STAMP.<br>If IMAGECOPY or PROXYCOPY, it is RECID from the control file.                                     |
| ID2               | NUMBER         | If BACKUPSET, it contains SET_COUNT.<br>If IMAGECOPY or PROXYCOPY, it is STAMP.                                                           |
| FILETYPE          | VARCHAR2 (15)  | Type of file. Possible values are: BACKUPPIECE, COPY, PROXYCOPY.                                                                          |
| FILETYPE_KEY      | NUMBER         | Backup piece key if the file is a backup piece; otherwise COPY_KEY.                                                                       |
| STATUS            | VARCHAR2 (1)   | Status of the backup file, either U (unavailable) or X (expired)                                                                          |
| FILESIZE          | NUMBER         | Size of the file                                                                                                                          |
| DEVICE_TYPE       | VARCHAR2 (17)  | Type of device on which the file resides                                                                                                  |
| FILENAME          | VARCHAR2 (513) | Name of the file                                                                                                                          |
| MEDIA             | VARCHAR2 (65)  | Name of the media on which the copy resides. This value is informational only. It is not needed for restore.                              |
| MEDIA_POOL        | NUMBER         | Media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command. |

## V\$VERSION

V\$VERSION displays version numbers of core library components in the Oracle Database. There is one row for each component.

| Column | Datatype      | Description                       |
|--------|---------------|-----------------------------------|
| BANNER | VARCHAR2 (80) | Component name and version number |

## V\$VPD\_POLICY

V\$VPD\_POLICY displays all the fine-grained security policies and predicates associated with the cursors currently in the library cache.

| Column       | Datatype      | Description                            |
|--------------|---------------|----------------------------------------|
| ADDRESS      | RAW (4   8)   | Cursor address                         |
| PARADDR      | RAW (4   8)   | Parent cursor address                  |
| SQL_HASH     | NUMBER        | SQL hash number                        |
| SQL_ID       | VARCHAR2 (13) | SQL identifier                         |
| CHILD_NUMBER | NUMBER        | Cursor's child number under the parent |
| OBJECT_OWNER | VARCHAR2 (30) | Owner of the object with the policy    |
| OBJECT_NAME  | VARCHAR2 (30) | Name of the object with the policy     |

| Column                | Datatype        | Description                                                  |
|-----------------------|-----------------|--------------------------------------------------------------|
| POLICY_GROUP          | VARCHAR2 (30)   | Name of the policy group                                     |
| POLICY                | VARCHAR2 (30)   | Name of the policy                                           |
| POLICY_FUNCTION_OWNER | VARCHAR2 (30)   | Owner of the policy function                                 |
| PREDICATE             | VARCHAR2 (4000) | Predicate for the policy (truncated to 4000 bytes in length) |

## V\$WAIT\_CHAINS

V\$WAIT\_CHAINS displays information about blocked sessions. A wait chain is comprised of sessions that are blocked by one another. Each row represents a blocked and blocker session pair. If a wait chain is not a cyclical wait chain, then the last row for the chain does not have a blocker.

| Column                    | Datatype       | Description                                                                                                                                                                                      |
|---------------------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CHAIN_ID                  | NUMBER         | A number identifying the wait chain                                                                                                                                                              |
| CHAIN_IS_CYCLE            | VARCHAR2 (5)   | Indicates whether the final blocked session in the wait chain is blocked by the initial blocked session (TRUE) or not (FALSE)                                                                    |
| CHAIN_SIGNATURE           | VARCHAR2 (801) | An Oracle-specific text signature of the wait chain. This signature can be used to identify similar wait chains.                                                                                 |
| CHAIN_SIGNATURE_HASH      | NUMBER         | A numeric representation of CHAIN_SIGNATURE                                                                                                                                                      |
| INSTANCE                  | NUMBER         | Blocked session's instance identifier                                                                                                                                                            |
| OSID                      | VARCHAR2 (25)  | Blocked session's operating system process identifier                                                                                                                                            |
| PID                       | NUMBER         | Blocked session's Oracle process identifier                                                                                                                                                      |
| SID                       | NUMBER         | Blocked session's Oracle session identifier                                                                                                                                                      |
| SESS_SERIAL#              | NUMBER         | Blocked session's Oracle session serial number                                                                                                                                                   |
| BLOCKER_IS_VALID          | VARCHAR2 (5)   | Indicates whether the blocked session has a blocker (TRUE) or not (FALSE)                                                                                                                        |
| BLOCKER_INSTANCE          | NUMBER         | Blocker session's instance identifier; NULL if BLOCKER_IS_VALID is FALSE                                                                                                                         |
| BLOCKER_OSID              | VARCHAR2 (25)  | Blocker session's operating system process identifier; NULL if BLOCKER_IS_VALID is FALSE                                                                                                         |
| BLOCKER_PID               | NUMBER         | Blocker session's Oracle process identifier; NULL if BLOCKER_IS_VALID is FALSE                                                                                                                   |
| BLOCKER_SID               | NUMBER         | Blocker session's Oracle session identifier; NULL if BLOCKER_IS_VALID is FALSE                                                                                                                   |
| BLOCKER_SESS_SERIAL#      | NUMBER         | Blocker session's Oracle session serial number; NULL if BLOCKER_IS_VALID is FALSE                                                                                                                |
| BLOCKER_CHAIN_ID          | NUMBER         | If not NULL, then the blocker session is a member of another chain specified by this chain identifier. For the remaining wait chain information, see the wait chain with the specified CHAIN_ID. |
| IN_WAIT                   | VARCHAR2 (5)   | Indicates whether the blocked session is in a wait (TRUE) or not (FALSE)                                                                                                                         |
| TIME_SINCE_LAST_WAIT_SECS | NUMBER         | Number of seconds since the last time the blocked session waited; NULL if IN_WAIT is TRUE                                                                                                        |
| WAIT_ID                   | NUMBER         | A number identifying the wait; NULL if IN_WAIT is FALSE                                                                                                                                          |
| WAIT_EVENT                | NUMBER         | Resource or event number for which the blocked session is waiting; NULL if IN_WAIT is FALSE                                                                                                      |
| WAIT_EVENT_TEXT           | VARCHAR2 (64)  | Resource or event for which the blocked session is waiting; NULL if IN_WAIT is FALSE                                                                                                             |
| P1                        | NUMBER         | First additional wait parameter; NULL if IN_WAIT is FALSE                                                                                                                                        |
| P1_TEXT                   | VARCHAR2 (64)  | Description of the first additional wait parameter; NULL if IN_WAIT is FALSE                                                                                                                     |

| Column              | Datatype      | Description                                                                                                                                                                                                                                            |
|---------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| P2                  | NUMBER        | Second additional wait parameter; NULL if IN_WAIT is FALSE                                                                                                                                                                                             |
| P2_TEXT             | VARCHAR2 (64) | Description of the second additional wait parameter; NULL if IN_WAIT is FALSE                                                                                                                                                                          |
| P3                  | NUMBER        | Third additional wait parameter; NULL if IN_WAIT is FALSE                                                                                                                                                                                              |
| P3_TEXT             | VARCHAR2 (64) | Description of the third additional wait parameter; NULL if IN_WAIT is FALSE                                                                                                                                                                           |
| IN_WAIT_SECS        | NUMBER        | Seconds the blocked session has been in the current wait; NULL if IN_WAIT is FALSE                                                                                                                                                                     |
| TIME_REMAINING_SECS | NUMBER        | Seconds remaining until the blocked session ends its wait (-1 if the blocked session can indefinitely wait); NULL if IN_WAIT is FALSE                                                                                                                  |
| NUM_WAITERS         | NUMBER        | Number of sessions waiting for the blocked session                                                                                                                                                                                                     |
| ROW_WAIT_OBJ#       | NUMBER        | Object ID for the table containing the row specified in ROW_WAIT_ROW#; NULL if IN_WAIT is FALSE                                                                                                                                                        |
| ROW_WAIT_FILE#      | NUMBER        | Identifier for the datafile containing the row specified in ROW_WAIT_ROW#; NULL if IN_WAIT is FALSE. This column is valid only if the blocked session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1. |
| ROW_WAIT_BLOCK#     | NUMBER        | Identifier for the block containing the row specified in ROW_WAIT_ROW#; NULL if IN_WAIT is FALSE. This column is valid only if the blocked session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.    |
| ROW_WAIT_ROW#       | NUMBER        | Current row being locked; NULL if IN_WAIT is FALSE. This column is valid only if the blocked session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.                                                  |

## V\$WAITCLASSMETRIC

V\$WAITCLASSMETRIC displays metric values of wait classes for the most recent 60-second interval. A history of the last one hour will be kept in the system.

| Column               | Datatype | Description                                                                                           |
|----------------------|----------|-------------------------------------------------------------------------------------------------------|
| BEGIN_TIME           | DATE     | Begin time of the interval                                                                            |
| END_TIME             | DATE     | End time of the interval                                                                              |
| INTSIZE_CSEC         | NUMBER   | Interval size (in hundredths of a second)                                                             |
| WAIT_CLASS#          | NUMBER   | Number of the class of the wait event                                                                 |
| WAIT_CLASS_ID        | NUMBER   | Identifier of the class of the wait event                                                             |
| AVERAGE_WAITER_COUNT | NUMBER   | Average waiter count                                                                                  |
| DBTIME_IN_WAIT       | NUMBER   | Percent of database time spent in the wait                                                            |
| TIME_WAITED          | NUMBER   | Time waited during the interval (in microseconds)                                                     |
| WAIT_COUNT           | NUMBER   | Number of times waited                                                                                |
| TIME_WAITED_FG       | NUMBER   | Amount of time (in hundredths of a second) spent in waits from this wait class in foreground sessions |
| WAIT_COUNT_FG        | NUMBER   | Number of times foreground processes waited                                                           |

## V\$WAITCLASSMETRIC\_HISTORY

V\$WAITCLASSMETRIC\_HISTORY displays metric values of wait classes for all intervals in the last one hour.

The columns for V\$WAITCLASSMETRIC\_HISTORY are the same as those for V\$WAITCLASSMETRIC.

**See Also:** ["V\\$WAITCLASSMETRIC"](#) on page 9-93

## V\$WAITSTAT

V\$WAITSTAT displays block contention statistics. This table is only updated when timed statistics are enabled.

| Column | Datatype      | Description                                                                       |
|--------|---------------|-----------------------------------------------------------------------------------|
| CLASS  | VARCHAR2 (18) | Class of the block                                                                |
| COUNT  | NUMBER        | Number of waits by this OPERATION for this CLASS of block                         |
| TIME   | NUMBER        | Sum of all wait times for all the waits by this OPERATION for this CLASS of block |

## V\$WALLET

V\$WALLET displays metadata of certificates that may be used as a master key for transparent data encryption.

| Column     | Datatype       | Description                                                                                                                                                                                                                                                                 |
|------------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CERT_ID    | VARCHAR2 (52)  | A unique certificate identifier value used to specify a particular PKI certificate for use as the master key                                                                                                                                                                |
| DN         | VARCHAR2 (255) | Distinguished name of a particular PKI certificate                                                                                                                                                                                                                          |
| SERIAL_NUM | VARCHAR2 (40)  | Unique serial number assigned to a certificate by the issuer or signer                                                                                                                                                                                                      |
| ISSUER     | VARCHAR2 (255) | Distinguished name of the Certificate Authority or issuer that issued and signed the certificate                                                                                                                                                                            |
| KEYSIZE    | NUMBER         | Size of the PKI key associated with the certificate                                                                                                                                                                                                                         |
| STATUS     | VARCHAR2 (16)  | Current status of the certificate: <ul style="list-style-type: none"><li>■ UNUSED</li><li>■ IN USE</li><li>■ USED</li></ul> This column allows the user to identify whether a certificate is currently in use or has already been used for transparent database encryption. |

## V\$WORKLOAD\_REPLAY\_THREAD

V\$WORKLOAD\_REPLAY\_THREAD displays information for all the different types of replay sessions.

| Column      | Datatype      | Description                                                        |
|-------------|---------------|--------------------------------------------------------------------|
| CLOCK       | NUMBER        | Current simulated SCN based on the SCN recorded at capture time    |
| NEXT_TICKER | NUMBER        | Next stream ID that will increment the CLOCK after a commit action |
| SID         | NUMBER        | Session ID of the replay session                                   |
| SERIAL#     | NUMBER        | Session serial number of the replay session                        |
| SPID        | VARCHAR2 (24) | The server process ID of the replay session                        |
| LOGON_USER  | VARCHAR2 (30) | Logon username of the replay session                               |
| LOGON_TIME  | DATE          | Logon time of the replay session                                   |
| EVENT       | VARCHAR2 (64) | Event name                                                         |
| EVENT_ID    | NUMBER        | Event identifier                                                   |
| EVENT#      | NUMBER        | Event operation code                                               |

| Column          | Datatype      | Description                                                                                                                                 |
|-----------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| P1TEXT          | VARCHAR2 (64) | Text for event parameter 1                                                                                                                  |
| P1              | NUMBER        | Value of event parameter 1                                                                                                                  |
| P2TEXT          | VARCHAR2 (64) | Text for event parameter 2                                                                                                                  |
| P2              | NUMBER        | Value of event parameter 2                                                                                                                  |
| P3TEXT          | VARCHAR2 (64) | Text for event parameter 3                                                                                                                  |
| P3              | NUMBER        | Value of event parameter 3                                                                                                                  |
| WAIT_FOR_SCN    | NUMBER        | The captured SCN for which the current user call should wait                                                                                |
| FILE_ID         | NUMBER        | The stream ID that is being replayed                                                                                                        |
| CALL_COUNTER    | NUMBER        | The call counter of the user call that is being replayed                                                                                    |
| DEPENDENT_SCN   | NUMBER        | The dependent SCN, captured to order the commit actions using block-level dependencies                                                      |
| STATEMENT_SCN   | NUMBER        | Statement SCN                                                                                                                               |
| COMMIT_WAIT_SCN | NUMBER        | The (maximum) SCN that the current commit should wait for                                                                                   |
| POST_COMMIT_SCN | NUMBER        | The next SCN after the current commit                                                                                                       |
| ACTION_TYPE     | NUMBER        | The type of commits. The possible values are: COMMIT, ROLLBACK, FAKED_COMMIT, and NULL. A value of NULL means it is not a commit operation. |
| SESSION_TYPE    | VARCHAR2 (13) | The type of replay session:<br>LOGON<br>ADMIN<br>DISPATCHER<br>REPLAY                                                                       |
| WRC_ID          | NUMBER        | Unique replay client ID assigned by the server to all participating replay clients when replay starts                                       |
| FILE_NAME       | VARCHAR2 (31) | File name of the captured stream                                                                                                            |
| SKIP_IT         | VARCHAR2 (1)  | Whether or not the current replayed user call is skipped or not                                                                             |
| DIRTY_BUFFERS   | VARCHAR2 (1)  | Reserved for internal use                                                                                                                   |
| DBTIME          | NUMBER        | Accumulated database time for the replay session                                                                                            |
| NETWORK_TIME    | NUMBER        | Accumulated network time for the replay session                                                                                             |
| THINK_TIME      | NUMBER        | Accumulated think time for the replay session                                                                                               |
| TIME_GAIN       | NUMBER        | If nonzero, the accumulated time in macro seconds indicating how fast the replay is                                                         |
| TIME_LOSS       | NUMBER        | If nonzero, the accumulated time in macro seconds indicating how slow the replay is                                                         |
| USER_CALLS      | NUMBER        | Total number of user calls                                                                                                                  |
| CLIENT_OS_USER  | VARCHAR2 (15) | Operating system username of the replay client                                                                                              |
| CLIENT_HOST     | VARCHAR2 (64) | Host name of the replay client                                                                                                              |
| CLIENT_PID      | VARCHAR2 (24) | Process ID of the replay client                                                                                                             |
| PROGRAM         | VARCHAR2 (48) | Program name of the replay client                                                                                                           |

## V\$XML\_AUDIT\_TRAIL

V\$XML\_AUDIT\_TRAIL shows standard, fine-grained, SYS, and mandatory audit records written in XML format files.

| Column             | Datatype                        | Description                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------------------|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AUDIT_TYPE         | NUMBER                          | Type of audit row: <ul style="list-style-type: none"> <li>1 = Standard XML Audit</li> <li>2 = Fine Grained XML Audit</li> <li>4 = SYS XML Audit</li> <li>8 = Mandatory XML Audit</li> </ul>                                                                                                                                                                                                                                                              |
| SESSION_ID         | NUMBER                          | Numeric ID for the Oracle session                                                                                                                                                                                                                                                                                                                                                                                                                        |
| PROXY_SESSIONID    | NUMBER                          | Proxy session serial number, if an enterprise user has logged in through a proxy mechanism                                                                                                                                                                                                                                                                                                                                                               |
| STATEMENTID        | NUMBER                          | Numeric ID for the statement run (a statement may cause multiple audit records)                                                                                                                                                                                                                                                                                                                                                                          |
| ENTRYID            | NUMBER                          | Numeric ID for the audit trail entry in the session                                                                                                                                                                                                                                                                                                                                                                                                      |
| EXTENDED_TIMESTAMP | TIMESTAMP (6)<br>WITH TIME ZONE | Timestamp of the audited operation (the timestamp of the user's logon for entries is created by AUDIT SESSION)                                                                                                                                                                                                                                                                                                                                           |
| GLOBAL_UID         | VARCHAR2 (32)                   | Global user identifier for the user, if the user has logged in as an enterprise user                                                                                                                                                                                                                                                                                                                                                                     |
| DB_USER            | VARCHAR2 (30)                   | Database username of the user whose actions were audited                                                                                                                                                                                                                                                                                                                                                                                                 |
| CLIENTIDENTIFIER   | VARCHAR2 (64)                   | Client identifier in the Oracle session                                                                                                                                                                                                                                                                                                                                                                                                                  |
| EXT_NAME           | VARCHAR2 (1024)                 | User's external name                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| OS_USER            | VARCHAR2 (30)                   | Operating system logon user name of the user whose actions were audited                                                                                                                                                                                                                                                                                                                                                                                  |
| OS_HOST            | VARCHAR2 (128)                  | Client host machine name                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| OS_PROCESS         | VARCHAR2 (16)                   | Operating system process identifier of the Oracle server process                                                                                                                                                                                                                                                                                                                                                                                         |
| TERMINAL           | VARCHAR2 (30)                   | Identifier for the user's terminal                                                                                                                                                                                                                                                                                                                                                                                                                       |
| INSTANCE_NUMBER    | NUMBER                          | Instance number as specified by the INSTANCE_NUMBER initialization parameter                                                                                                                                                                                                                                                                                                                                                                             |
| OBJECT_SCHEMA      | VARCHAR2 (30)                   | Owner of the audited object                                                                                                                                                                                                                                                                                                                                                                                                                              |
| OBJECT_NAME        | VARCHAR2 (30)                   | Name of the object affected by the action                                                                                                                                                                                                                                                                                                                                                                                                                |
| POLICY_NAME        | VARCHAR2 (30)                   | Name of the fine-grained auditing policy                                                                                                                                                                                                                                                                                                                                                                                                                 |
| NEW_OWNER          | VARCHAR2 (30)                   | Owner of the object named in the NEW_NAME column                                                                                                                                                                                                                                                                                                                                                                                                         |
| NEW_NAME           | VARCHAR2 (30)                   | New name of object after renaming, or the name of an underlying object (for example, CREATE INDEX owner.obj_name ON new_owner.new_name)                                                                                                                                                                                                                                                                                                                  |
| ACTION             | NUMBER                          | Numeric code for the action type                                                                                                                                                                                                                                                                                                                                                                                                                         |
| STATEMENT_TYPE     | NUMBER                          | Description of the action                                                                                                                                                                                                                                                                                                                                                                                                                                |
| TRANSACTIONID      | RAW (8)                         | Identifier of the transaction in which the object is accessed or modified                                                                                                                                                                                                                                                                                                                                                                                |
| RETURNCODE         | NUMBER                          | Oracle error code generated by the action. Zero if the action succeeded.                                                                                                                                                                                                                                                                                                                                                                                 |
| SCN                | NUMBER                          | System change number (SCN) of the query                                                                                                                                                                                                                                                                                                                                                                                                                  |
| COMMENT_TEXT       | VARCHAR2 (4000)                 | Text comments on standard audit entries. Also indicates how the user was authenticated - the method can be one of the following: <ul style="list-style-type: none"> <li>DATABASE - authentication was done by password</li> <li>NETWORK - authentication was done by Oracle Net Services or the Advanced Networking Option</li> <li>PROXY - the client was authenticated by another user. The name of the proxy user follows the method type.</li> </ul> |
| AUTH_PRIVILEGES    | VARCHAR2 (16)                   | Privileges granted and revoked in GRANT and REVOKE statements recorded for standard audit trail entry                                                                                                                                                                                                                                                                                                                                                    |
| GRANTEE            | VARCHAR2 (30)                   | User who granted or revoked the privilege                                                                                                                                                                                                                                                                                                                                                                                                                |
| PRIV_USED          | NUMBER                          | Numerical code of privileges, if any, used in the action                                                                                                                                                                                                                                                                                                                                                                                                 |

| Column           | Datatype        | Description                                                                                                                                                                                                                                                              |
|------------------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SES_ACTIONS      | VARCHAR2 (16)   | Session summary for standard audit records. A string of 12 characters, one for each action type, in the following order: Alter, Audit, Comment, Delete, Grant, Index, Insert, Lock, Rename, Select, Update, Flashback.<br>Values: - = None, S=Success, F=Failure, B=Both |
| OS_PRIVILEGE     | VARCHAR2 (7)    | Operating system privilege (SYSDBA or SYSOPER), if any, used in the session. If no privilege is used, it will be NONE.                                                                                                                                                   |
| ECONTEXT_ID      | VARCHAR2 (64)   | Application execution context identifier                                                                                                                                                                                                                                 |
| SQL_BIND         | VARCHAR2 (4000) | List of bind variables used in the statement                                                                                                                                                                                                                             |
| SQL_TEXT         | VARCHAR2 (4000) | The statement or command that triggered the audit event                                                                                                                                                                                                                  |
| OBJ_EDITION_NAME | VARCHAR2 (30)   | Name of the edition containing the audited object                                                                                                                                                                                                                        |
| DBID             | NUMBER          | Database identifier of the audited database                                                                                                                                                                                                                              |

## V\$XSTREAM\_CAPTURE

V\$XSTREAM\_CAPTURE displays information about each capture process that sends LCRs to an XStream outbound server.

**Note:** This view does not display information about capture processes that send LCRs to Oracle Streams apply processes. To view information about such capture processes, query the V\$STREAMS\_CAPTURE view.

| Column       | Datatype      | Description                                                                              |
|--------------|---------------|------------------------------------------------------------------------------------------|
| SID          | NUMBER        | Session identifier of the capture process                                                |
| SERIAL#      | NUMBER        | Session serial number of the capture process session                                     |
| CAPTURE#     | NUMBER        | Capture process number. A capture process is an Oracle background process prefixed by cp |
| CAPTURE_NAME | VARCHAR2 (30) | Name of the capture process                                                              |
| LOGMINER_ID  | NUMBER        | Session ID of the Oracle LogMiner session associated with the capture process            |
| STARTUP_TIME | DATE          | Time when the capture process was last started                                           |

| Column                      | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STATE                       | VARCHAR2 (51) | <p>State of the capture process:</p> <ul style="list-style-type: none"> <li>INITIALIZING - Starting up.</li> <li>WAITING FOR DICTIONARY REDO - Waiting for redo log files containing the dictionary build related to the first SCN to be added to the capture process session. A capture process cannot begin to scan the redo log files until all of the log files containing the dictionary build have been added.</li> <li>DICTIONARY INITIALIZATION - Processing a dictionary build.</li> <li>MINING (PROCESSED SCN = <i>scn_value</i>) - Mining a dictionary build at the SCN <i>scn_value</i>.</li> <li>LOADING (step <i>X</i> of <i>Y</i>) - Processing information from a dictionary build and currently at step <i>X</i> in a process that involves <i>Y</i> steps, where <i>X</i> and <i>Y</i> are numbers.</li> <li>CAPTURING CHANGES - Scanning the redo log for changes that satisfy the capture process rule sets.</li> <li>WAITING FOR REDO - Waiting for new redo log files to be added to the capture process session. The capture process has finished processing all of the redo log files added to its session. This state is possible if there is no activity at a source database. For a downstream capture process, this state is possible if the capture process is waiting for new log files to be added to its session.</li> <li>EVALUATING RULE - Evaluating a change against a capture process rule set.</li> <li>CREATING LCR - Converting a change into an LCR.</li> <li>ENQUEUEING MESSAGE - Enqueueing an LCR that satisfies the capture process rule sets into the capture process queue.</li> <li>PAUSED FOR FLOW CONTROL - Unable to enqueue LCRs either because of low memory or because propagations and outbound servers are consuming messages slower than the capture process is creating them. This state indicates flow control that is used to reduce spilling of captured LCRs when propagation or apply has fallen behind or is unavailable.</li> <li>WAITING FOR THE BUFFERED QUEUE TO SHRINK - Waiting for the buffered queue to change to a smaller size. The buffered queue shrinks when there is a memory limitation or when an administrator reduces its size.</li> <li>WAITING FOR <i>n</i> SUBSCRIBER(S) INITIALIZING - Waiting for outbound servers that receive LCRs from the capture process to start, where <i>n</i> is the number of apply processes.</li> <li>WAITING FOR TRANSACTION - Waiting for LogMiner to provide more transactions.</li> <li>WAITING FOR INACTIVE DEQUEUEUS - Waiting for the capture process's queue subscribers to start. The capture process stops enqueueing LCRs if there are no active subscribers to the queue.</li> <li>SUSPENDED FOR AUTO SPLIT/MERGE - Waiting for a merge operation to complete.</li> <li>SHUTTING DOWN - Stopping.</li> <li>ABORTING - Aborting.</li> </ul> |
| TOTAL_PREFILTER_DISCARDED   | NUMBER        | Total number of prefiltered messages discarded                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| TOTAL_PREFILTER_KEPT        | NUMBER        | Total number of prefiltered messages kept                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| TOTAL_PREFILTER_EVALUATIONS | NUMBER        | Total number of prefilter evaluations                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| TOTAL_MESSAGES_CAPTURED     | NUMBER        | Total number of redo entries passed by LogMiner to the capture process for detailed rule evaluation since the capture process last started. A capture process converts a redo entry into a message and performs detailed rule evaluation on the message when capture process prefiltering cannot discard the change.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| CAPTURE_TIME                | DATE          | Time when the most recent message was captured                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |



| Column                        | Datatype      | Description                                                                                                                                                                                      |
|-------------------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAPTURE_MESSAGE_NUMBER        | NUMBER        | Number of the most recently captured message                                                                                                                                                     |
| CAPTURE_MESSAGE_CREATE_TIME   | DATE          | Creation time of the most recently captured message                                                                                                                                              |
| TOTAL_MESSAGES_CREATED        | NUMBER        | Count associated with ELAPSED_LCR_TIME to calculate rate                                                                                                                                         |
| TOTAL_FULL_EVALUATIONS        | NUMBER        | Count associated with ELAPSED_RULE_TIME to calculate rate                                                                                                                                        |
| TOTAL_MESSAGES_ENQUEUED       | NUMBER        | Total number of messages enqueued since the capture process was last started                                                                                                                     |
| ENQUEUE_TIME                  | DATE          | Time when the last message was enqueued                                                                                                                                                          |
| ENQUEUE_MESSAGE_NUMBER        | NUMBER        | Number of the last enqueued message                                                                                                                                                              |
| ENQUEUE_MESSAGE_CREATE_TIME   | DATE          | Creation time of the last enqueued message                                                                                                                                                       |
| AVAILABLE_MESSAGE_NUMBER      | NUMBER        | For local capture, the last redo SCN flushed to the log files. For downstream capture, the last SCN added to LogMiner through the archived redo log files.                                       |
| AVAILABLE_MESSAGE_CREATE_TIME | DATE          | For local capture, the time the SCN was written to the log file. For downstream capture, the time the most recent archived redo log file (containing the most recent SCN) was added to LogMiner. |
| ELAPSED_CAPTURE_TIME          | NUMBER        | Elapsed time (in hundredths of a second) scanning for changes in the redo log since the capture process was last started                                                                         |
| ELAPSED_RULE_TIME             | NUMBER        | Elapsed time (in hundredths of a second) evaluating rules since the capture process was last started                                                                                             |
| ELAPSED_ENQUEUE_TIME          | NUMBER        | Elapsed time (in hundredths of a second) enqueueing messages since the capture process was last started                                                                                          |
| ELAPSED_LCR_TIME              | NUMBER        | Elapsed time (in hundredths of a second) creating LCRs since the capture process was last started                                                                                                |
| ELAPSED_REDO_WAIT_TIME        | NUMBER        | Elapsed time (in hundredths of a second) spent by the capture process in the WAITING FOR REDO state                                                                                              |
| ELAPSED_PAUSE_TIME            | NUMBER        | Elapsed flow control pause time (in hundredths of a second)                                                                                                                                      |
| STATE_CHANGED_TIME            | DATE          | Time at which the state of the capture process changed                                                                                                                                           |
| SGA_USED                      | NUMBER        | The total amount of shared memory (in bytes) currently used by the capture process out of the amount allocated (SGA_ALLOCATED)                                                                   |
| SGA_ALLOCATED                 | NUMBER        | The total amount of shared memory (in bytes) allocated from the Streams pool for the capture process                                                                                             |
| BYTES_OF_REDO_MINED           | VARCHAR2 (64) | The total amount of redo data mined (in bytes) since the capture process last started                                                                                                            |
| SESSION_RESTART_SCN           | VARCHAR2 (64) | The SCN from which the capture process started mining redo data when it was last started                                                                                                         |

---

**Note:** The ELAPSED\_CAPTURE\_TIME, ELAPSED\_RULE\_TIME, ELAPSED\_ENQUEUE\_TIME, ELAPSED\_LCR\_TIME, and ELAPSED\_REDO\_WAIT\_TIME columns are only populated if the TIMED\_STATISTICS initialization parameter is set to true, or if the STATISTICS\_LEVEL initialization parameter is set to TYPICAL or ALL.

---

---

**Note:** The V\$XSTREAM\_CAPTURE view is available starting with Oracle Database 11g Release 2 (11.2.0.2)

---

## V\$XSTREAM\_MESSAGE\_TRACKING

V\$XSTREAM\_MESSAGE\_TRACKING displays information about LCRs tracked through the stream that are processed by XStream components.

| Column                | Datatype                        | Description                                  |
|-----------------------|---------------------------------|----------------------------------------------|
| TRACKING_LABEL        | VARCHAR2 (30)                   | User-specified tracking label                |
| TAG                   | RAW (30)                        | First 30 bytes of the tag of the LCR         |
| COMPONENT_NAME        | VARCHAR2 (30)                   | Name of the component that processed the LCR |
| COMPONENT_TYPE        | VARCHAR2 (30)                   | Type of the component that processed the LCR |
| ACTION                | VARCHAR2 (50)                   | Action performed on the LCR                  |
| ACTION_DETAILS        | VARCHAR2 (100)                  | Details of the action                        |
| TIMESTAMP             | TIMESTAMP (9)<br>WITH TIME ZONE | Time when the action was performed           |
| MESSAGE_CREATION_TIME | DATE                            | Time when the message was created            |
| MESSAGE_NUMBER        | NUMBER                          | SCN of the message                           |
| TRACKING_ID           | RAW (16)                        | Globally unique OID of the LCR               |
| SOURCE_DATABASE_NAME  | VARCHAR2 (128)                  | Name of the source database                  |
| OBJECT_OWNER          | VARCHAR2 (30)                   | Owner of the object                          |
| OBJECT_NAME           | VARCHAR2 (30)                   | Name of the object                           |
| XID                   | VARCHAR2 (128)                  | Transaction ID                               |
| COMMAND_TYPE          | VARCHAR2 (30)                   | Command type of the LCR                      |
| MESSAGE_POSITION      | RAW (64)                        | Position of the message                      |

---

**Note:** The V\$XSTREAM\_MESSAGE\_TRACKING view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

---

## V\$XSTREAM\_OUTBOUND\_SERVER

V\$XSTREAM\_OUTBOUND\_SERVER displays statistics about an outbound server. An outbound server sends LCRs to the XStream client application.

---

**Note:** When the COMMITTED\_DATA\_ONLY column is YES in the V\$XSTREAM\_OUTBOUND\_SERVER view, the V\$STREAMS\_APPLY\_SERVER view provides additional information about the outbound server process, and information about the apply server background processes used by the outbound server.

---

| Column  | Datatype      | Description                                                                                             |
|---------|---------------|---------------------------------------------------------------------------------------------------------|
| SID     | NUMBER        | Session ID of the outbound server's session                                                             |
| SERIAL# | NUMBER        | Serial number of the outbound server's session                                                          |
| SPID    | VARCHAR2 (12) | Process identification number of the operating-system process that sends LCRs to the client application |

| Column       | Datatype      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SERVER_NAME  | VARCHAR2 (30) | Name of the outbound server                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| STARTUP_TIME | DATE          | Time when the client application attached to the outbound server                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| STATE        | VARCHAR2 (37) | <p>State of the outbound server</p> <p>When the COMMITTED_DATA_ONLY column shows YES, the following states are possible:</p> <ul style="list-style-type: none"> <li>INITIALIZING - Starting up the outbound server.</li> <li>IDLE - Performing no work because there are no LCRs to send to the XStream client application.</li> <li>GET TRANSACTIONS - Receiving transactions from the outbound server's apply coordinator.</li> <li>SEND TRANSACTION - Sending a transaction to an XStream client application.</li> <li>WAIT FOR NEXT CHUNK - Waiting for the next set of LCRs for a large transaction.</li> <li>TRANSACTION CLEANUP - Cleaning up an applied transaction, which includes removing LCRs from the outbound server's queue.</li> <li>WAIT FOR CLIENT - Waiting for an XStream client application to request more LCRs.</li> </ul> <p>When the COMMITTED_DATA_ONLY column shows NO, the following states are possible:</p> <ul style="list-style-type: none"> <li>INITIALIZING - Starting up the outbound server.</li> <li>INITIALIZING RULE EVALUATION CONTEXT - Initializing the context to evaluate the outbound server's rules.</li> <li>IDLE - Performing no work because there is no LCR to send to the XStream client application.</li> <li>BROWSING LCR - Browsing the outbound server's queue for next LCR.</li> <li>EVALUATING RULES - Evaluating an LCR against a rule set.</li> <li>DEQUEUEING LCR - Dequeueing an LCR from the outbound server's queue.</li> <li>SENDING LCR - Sending an LCR to an XStream client application.</li> <li>WAITING FOR CAPTURE TO TERMINATE - Waiting for the capture process to become disabled.</li> <li>SUSPENDED DUE TO A DROPPED SUBSCRIBER - Suspended because a connected subscriber was dropped. For example, a subscriber can be dropped during a split or merge operation.</li> <li>SUSPENDED FOR AUTO SPLIT/MERGE - Suspended because an automatic split or merge operation is being performed.</li> <li>WAITING ON EMPTY QUEUE - Waiting for more LCRs from the capture process.</li> <li>WAITING FOR CLIENT - Waiting for the XStream client application to request more LCRs.</li> <li>WAITING FOR CAPTURE TO INITIALIZE - Waiting for the capture process to finish the data dictionary build.</li> <li>WAITING TO ATTACH TO CAPTURE - Waiting for the outbound server to attach to the capture process.</li> </ul> <p>When a state refers to a capture process, it is the capture process that captures changes for the outbound server. When a state refers to a propagation, it is the outbound server that sends LCRs to the XStream client application.</p> |
| XIDUSN       | NUMBER        | <p>Transaction ID undo segment number of the transaction currently being processed</p> <p>This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

| Column                        | Datatype     | Description                                                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| XIDSLT                        | NUMBER       | Transaction ID slot number of the transaction currently being processed<br><br>This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.                                                                                                                                                |
| XIDSQN                        | NUMBER       | Transaction ID sequence number of the transaction currently being processed<br><br>This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.                                                                                                                                            |
| COMMITSCN                     | NUMBER       | Commit SCN of the transaction currently being processed<br><br>This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.                                                                                                                                                                |
| TOTAL_TRANSACTIONS_SENT       | NUMBER       | Total number of transactions sent by the outbound server to the XStream client application since the last time the client application attached to the outbound server<br><br>This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.                                                  |
| MESSAGE_SEQUENCE              | NUMBER       | Number of the current LCR being processed by the outbound server. This value is reset to 1 at the beginning of each transaction.<br><br>This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.                                                                                       |
| TOTAL_MESSAGES_SENT           | NUMBER       | Total number of LCRs sent by the outbound server to the XStream client application since the last time the client application attached to the outbound server                                                                                                                                                                                                               |
| SEND_TIME                     | DATE         | Time the last LCR was sent by the outbound server to the XStream client application                                                                                                                                                                                                                                                                                         |
| LAST_SENT_MESSAGE_NUMBER      | NUMBER       | Message number of the last LCR sent by the outbound server to the XStream client application                                                                                                                                                                                                                                                                                |
| LAST_SENT_MESSAGE_CREATE_TIME | DATE         | Creation time at the source database of the last LCR sent by the outbound server to the client application                                                                                                                                                                                                                                                                  |
| ELAPSED_SEND_TIME             | NUMBER       | Time elapsed (in hundredths of a second) sending LCRs to the XStream client application since the last time the client application attached to the outbound server                                                                                                                                                                                                          |
| COMMIT_POSITION               | RAW (64)     | Commit position of the transaction currently being processed<br><br>This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.                                                                                                                                                           |
| LAST_SENT_POSITION            | RAW (64)     | Position of the last LCR sent to the XStream client application<br><br>This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.                                                                                                                                                        |
| BYTES_SENT                    | NUMBER       | Total number of bytes sent by the outbound server to the XStream client application since the last time the client application attached to the outbound server                                                                                                                                                                                                              |
| COMMITTED_DATA_ONLY           | VARCHAR2 (3) | YES if the outbound server can send only LCRs in committed transactions to the XStream client application. A committed transaction is an assembled, noninterleaving transaction with no rollbacks.<br><br>NO if the outbound server can send LCRs in transactions that have not yet committed to the XStream client application. This mode is for internal Oracle use only. |

**Note:** The V\$XSTREAM\_OUTBOUND\_SERVER view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

## V\$XSTREAM\_TRANSACTION

V\$XSTREAM\_TRANSACTION displays information about transactions that are being processed by capture processes, outbound servers, and inbound servers. This view can identify long running transactions and to determine how many LCRs are being processed in each transaction. This view only contains information about captured LCRs. It does not contain information about user-enqueued LCRs or user messages.

This view only shows information about LCRs that are being processed because they satisfied the rule sets for the component at the time of the query. For capture processes, this view only shows information about changes in transactions that the capture process has converted into LCRs. It does not show information about all the active transactions present in the redo log.

For outbound servers, this view only shows information about LCRs that the outbound server has dequeued. It does not show information about LCRs in the outbound server's queue. For outbound servers, information about a transaction remains in the view until the transaction is sent to the XStream client application.

For inbound servers, information about a transaction remains in the view until the transaction commits or until the entire transaction is rolled back.

| Column                   | Datatype      | Description                                                                                                                                                                                                                                                                                          |
|--------------------------|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| COMPONENT_NAME           | VARCHAR2 (30) | Name of the component                                                                                                                                                                                                                                                                                |
| COMPONENT_TYPE           | VARCHAR2 (10) | Type of component <ul style="list-style-type: none"> <li>■ CAPTURE - Capture process</li> <li>■ APPLY - Apply reader subcomponent in an outbound server or inbound server</li> <li>■ PROPAGATION_SENDER - Propagation sender that sends LCRs from a capture process to an outbound server</li> </ul> |
| XIDUSN                   | NUMBER        | Transaction ID undo segment number of the transaction                                                                                                                                                                                                                                                |
| XIDSLT                   | NUMBER        | Transaction ID slot number of the transaction                                                                                                                                                                                                                                                        |
| XIDSQN                   | NUMBER        | Transaction ID sequence number of the transaction                                                                                                                                                                                                                                                    |
| CUMULATIVE_MESSAGE_COUNT | NUMBER        | Number of LCRs processed in the transaction. If a component is restarted while the transaction is being processed, then this column shows the number of LCRs processed in the transaction since the component was started.                                                                           |
| TOTAL_MESSAGE_COUNT      | NUMBER        | Total number of LCRs processed in the transaction by an outbound server or inbound server. This column does not pertain to capture processes.                                                                                                                                                        |
| FIRST_MESSAGE_TIME       | DATE          | Time stamp of the first LCR processed in the transaction. If a capture process is restarted while the transaction is being processed, then this column shows the time stamp of the first LCR processed after the capture process was started.                                                        |
| FIRST_MESSAGE_NUMBER     | NUMBER        | SCN of the first message in the transaction. If a capture process is restarted while the transaction is being processed, then this column shows the SCN of the first message processed after the capture process was started.                                                                        |
| LAST_MESSAGE_TIME        | DATE          | Time stamp of the last LCR processed in the transaction                                                                                                                                                                                                                                              |
| LAST_MESSAGE_NUMBER      | NUMBER        | SCN of the most recent message encountered for the transaction                                                                                                                                                                                                                                       |
| FIRST_MESSAGE_POSITION   | RAW (64)      | Position of the first message seen by an XStream inbound server<br>This column is populated only for an apply process that is functioning as an XStream inbound server.                                                                                                                              |
| LAST_MESSAGE_POSITION    | RAW (64)      | Position of the last message seen by an XStream inbound server<br>This column is populated only for an apply process that is functioning as an XStream inbound server.                                                                                                                               |

| Column         | Datatype       | Description                                                                                                                                          |
|----------------|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| TRANSACTION_ID | VARCHAR2 (128) | Transaction ID for an XStream inbound server<br>This column is populated only for an apply process that is functioning as an XStream inbound server. |

---

**Note:** The V\$XSTREAM\_TRANSACTION view is available starting with Oracle Database 11g Release 2 (11.2.0.2).

---

## Database Limits

This appendix lists the limits of values associated with database functions and objects. Limits exist on several levels in the database. There is usually a hard-coded limit in the database that cannot be exceeded. This value may be further restricted for any given operating system.

Database limits are divided into four categories:

- [Datatype Limits](#)
- [Physical Database Limits](#)
- [Logical Database Limits](#)
- [Process and Runtime Limits](#)

**See Also:** Your operating system-specific Oracle documentation

### Datatype Limits

| Datatypes                                         | Limit                                                                                                                                                               | Comments                                                                                                                                                                                                               |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BFILE                                             | Maximum size: 4 GB<br>Maximum size of a file name: 255 characters<br>Maximum size of a directory name: 30 characters<br>Maximum number of open BFILEs: see Comments | The maximum number of BFILEs is limited by the value of the <code>SESSION_MAX_OPEN_FILES</code> initialization parameter, which is itself limited by the maximum number of open files the operating system will allow. |
| BLOB                                              | Maximum size: (4 GB - 1) * DB_BLOCK_SIZE initialization parameter (8 TB to 128 TB)                                                                                  | The number of LOB columns per table is limited only by the maximum number of columns per table (that is, 1000 <sup>1</sup> ).                                                                                          |
| CHAR                                              | Maximum size: 2000 bytes                                                                                                                                            | None                                                                                                                                                                                                                   |
| CHAR VARYING                                      | Maximum size: 4000 bytes                                                                                                                                            | None                                                                                                                                                                                                                   |
| CLOB                                              | Maximum size: (4 GB - 1) * DB_BLOCK_SIZE initialization parameter (8 TB to 128 TB)                                                                                  | The number of LOB columns per table is limited only by the maximum number of columns per table (that is, 1000 <sup>1</sup> ).                                                                                          |
| Literals (characters or numbers in SQL or PL/SQL) | Maximum size: 4000 characters                                                                                                                                       | None                                                                                                                                                                                                                   |
| LONG                                              | Maximum size: 2 GB - 1                                                                                                                                              | Only one LONG column is allowed per table.                                                                                                                                                                             |
| NCHAR                                             | Maximum size: 2000 bytes                                                                                                                                            | None                                                                                                                                                                                                                   |

| Datatypes     | Limit                                                                              | Comments                                                                                                                      |
|---------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| NCHAR VARYING | Maximum size: 4000 bytes                                                           | None                                                                                                                          |
| NCLOB         | Maximum size: (4 GB - 1) * DB_BLOCK_SIZE initialization parameter (8 TB to 128 TB) | The number of LOB columns per table is limited only by the maximum number of columns per table (that is, 1000 <sup>1</sup> ). |
| NUMBER        | 999...(38 9's) x10 <sup>125</sup> maximum value                                    | Can be represented to full 38-digit precision (the mantissa)                                                                  |
|               | -999...(38 9's) x10 <sup>125</sup> minimum value                                   | Can be represented to full 38-digit precision (the mantissa)                                                                  |
| Precision     | 38 significant digits                                                              | None                                                                                                                          |
| RAW           | Maximum size: 2000 bytes                                                           | None                                                                                                                          |
| VARCHAR       | Maximum size: 4000 bytes                                                           | None                                                                                                                          |
| VARCHAR2      | Maximum size: 4000 bytes                                                           | None                                                                                                                          |

<sup>1</sup> The absolute maximum number of columns in a table is 1000. However, when you create an object table (or a relational table with columns of object, nested table, varray, or REF type), Oracle maps the columns of the user-defined types to relational columns, creating in effect hidden columns that count toward the 1000-column limit. For details on how Oracle calculates the total number of columns in such a table, refer to *Oracle Database Administrator's Guide*.

**See Also:** *Oracle Database SQL Language Reference* for information on the rules and limitations governing the use of datatypes and naming database objects

## Physical Database Limits

| Item                | Type of Limit                                    | Limit Value                                                                                                                                                      |
|---------------------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Database Block Size | Minimum                                          | 2048 bytes; must be a multiple of operating system physical block size                                                                                           |
| Database Block Size | Maximum                                          | Operating system dependent; never more than 32 KB                                                                                                                |
| Database Blocks     | Minimum in initial extent of a segment           | 2 blocks                                                                                                                                                         |
| Database Blocks     | Maximum per datafile                             | Platform dependent; typically 2 <sup>22</sup> - 1 blocks                                                                                                         |
| Controlfiles        | Number of control files                          | 1 minimum; 2 or more (on separate devices) strongly recommended                                                                                                  |
| Controlfiles        | Size of a control file                           | Dependent on operating system and database creation options; maximum of 25,000 x (database block size)                                                           |
| Database files      | Maximum per tablespace                           | Operating system dependent; usually 1022                                                                                                                         |
| Database files      | Maximum per database                             | 65533<br>May be less on some operating systems<br>Limited also by size of database blocks and by the DB_FILES initialization parameter for a particular instance |
| Database extents    | Maximum per dictionary managed tablespace        | 4 GB * physical block size (with K/M modifier); 4 GB (without K/M modifier)                                                                                      |
| Database extents    | Maximum per locally managed (uniform) tablespace | 2 GB * physical block size (with K/M modifier); 2 GB (without K/M modifier)                                                                                      |



| Item                                | Type of Limit                        | Limit Value                                                                                                                                                                                                                                                                               |
|-------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Database file size                  | Maximum                              | Operating system dependent. Limited by maximum operating system file size; typically $2^{22}$ or 4 MB blocks                                                                                                                                                                              |
| MAXEXTENTS                          | Default value                        | Derived from tablespace default storage or DB_BLOCK_SIZE initialization parameter                                                                                                                                                                                                         |
| MAXEXTENTS                          | Maximum                              | Unlimited                                                                                                                                                                                                                                                                                 |
| Redo Log Files                      | Maximum number of logfiles           | Limited by value of MAXLOGFILES parameter in the CREATE DATABASE statement<br><br>Control file can be resized to allow more entries; ultimately an operating system limit                                                                                                                 |
| Redo Log Files                      | Maximum number of logfiles per group | Unlimited                                                                                                                                                                                                                                                                                 |
| Redo Log File Size                  | Minimum size                         | 4 MB                                                                                                                                                                                                                                                                                      |
| Redo Log File Size                  | Maximum Size                         | Operating system limit; typically 2 GB                                                                                                                                                                                                                                                    |
| Tablespaces                         | Maximum number per database          | 64 K<br><br>Number of tablespaces cannot exceed the number of database files because each tablespace must include at least one file                                                                                                                                                       |
| Bigfile Tablespaces                 | Number of blocks                     | A bigfile tablespace contains only one datafile or tempfile, which can contain up to approximately 4 billion ( $2^{32}$ ) blocks. The maximum size of the single datafile or tempfile is 128 terabytes (TB) for a tablespace with 32 K blocks and 32 TB for a tablespace with 8 K blocks. |
| Smallfile (traditional) Tablespaces | Number of blocks                     | A smallfile tablespace is a traditional Oracle tablespace, which can contain 1022 datafiles or tempfiles, each of which can contain up to approximately 4 million ( $2^{22}$ ) blocks.                                                                                                    |
| External Tables file                | Maximum size                         | Dependent on the operating system.<br><br>An external table can be composed of multiple files.                                                                                                                                                                                            |

## Logical Database Limits

| Item            | Type of Limit                                   | Limit Value                                                                                                                             |
|-----------------|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| GROUP BY clause | Maximum length                                  | The GROUP BY expression and all of the nondistinct aggregate functions (for example, SUM, AVG) must fit within a single database block. |
| Indexes         | Maximum per table                               | Unlimited                                                                                                                               |
| Indexes         | Total size of indexed column                    | 75% of the database block size minus some overhead                                                                                      |
| Columns         | Per table                                       | 1000 columns maximum                                                                                                                    |
| Columns         | Per index (or clustered index)                  | 32 columns maximum                                                                                                                      |
| Columns         | Per bitmapped index                             | 30 columns maximum                                                                                                                      |
| Constraints     | Maximum per column                              | Unlimited                                                                                                                               |
| Subqueries      | Maximum levels of subqueries in a SQL statement | Unlimited in the FROM clause of the top-level query<br><br>255 subqueries in the WHERE clause                                           |

| Item                  | Type of Limit                                           | Limit Value                                                                                                                                                                                                                           |
|-----------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Partitions            | Maximum length of linear partitioning key               | 4 KB - overhead                                                                                                                                                                                                                       |
| Partitions            | Maximum number of columns in partition key              | 16 columns                                                                                                                                                                                                                            |
| Partitions            | Maximum number of partitions allowed per table or index | 1024K - 1                                                                                                                                                                                                                             |
| Rows                  | Maximum number per table                                | Unlimited                                                                                                                                                                                                                             |
| Stored Packages       | Maximum size                                            | PL/SQL and Developer/2000 may have limits on the size of stored procedures they can call. The limits typically range from 2000 to 3000 lines of code.<br><br><b>See Also:</b> Your PL/SQL or Developer/2000 documentation for details |
| Trigger Cascade Limit | Maximum value                                           | Operating system-dependent, typically 32                                                                                                                                                                                              |
| Users and Roles       | Maximum                                                 | 2,147,483,638                                                                                                                                                                                                                         |
| Tables                | Maximum per clustered table                             | 32 tables                                                                                                                                                                                                                             |
| Tables                | Maximum per database                                    | Unlimited                                                                                                                                                                                                                             |

---

**Note:** The limit on how long a SQL statement can be depends on many factors, including database configuration, disk space, and memory

---



---

**Note:** When an object instance exists in memory, there is no fixed limit on the number of attributes in the object. But the maximum total amount of memory consumed by an object instance is 4 GB.

When an object instance is inserted into a table, the attributes are exploded into separate columns in the table, and the Oracle 1000-column limit applies.

---

## Process and Runtime Limits

| Item                       | Type of Limit                                             | Limit Value                                                                                                           |
|----------------------------|-----------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Instances per database     | Maximum number of cluster database instances per database | Operating system-dependent                                                                                            |
| Locks                      | Row-level                                                 | Unlimited                                                                                                             |
| Locks                      | Distributed Lock Manager                                  | Operating system dependent                                                                                            |
| SGA size                   | Maximum value                                             | Operating system-dependent; typically 2 to 4 GB for 32-bit operating systems, and > 4 GB for 64-bit operating systems |
| Advanced Queuing Processes | Maximum per instance                                      | 10                                                                                                                    |
| Job Queue Processes        | Maximum per instance                                      | 1000                                                                                                                  |
| I/O Slave Processes        | Maximum per background process (DBWR, LGWR, etc.)         | 15                                                                                                                    |
| I/O Slave Processes        | Maximum per Backup session                                | 15                                                                                                                    |

| Item                           | Type of Limit        | Limit Value                                                                                            |
|--------------------------------|----------------------|--------------------------------------------------------------------------------------------------------|
| Sessions                       | Maximum per instance | 2 <sup>31</sup> ; limited by the PROCESSES and SESSIONS initialization parameters                      |
| Global Cache Service Processes | Maximum per instance | 10                                                                                                     |
| Shared Servers                 | Maximum per instance | Unlimited within constraints set by the PROCESSES and SESSIONS initialization parameters, for instance |
| Dispatchers                    | Maximum per instance | Unlimited within constraints set by PROCESSES and SESSIONS initialization parameters, for instance     |
| Parallel Execution Slaves      | Maximum per instance | Unlimited within constraints set by PROCESSES and SESSIONS initialization parameters, for instance     |
| Backup Sessions                | Maximum per instance | Unlimited within constraints set by PROCESSES and SESSIONS initialization parameters, for instance     |
| Services                       | Maximum per instance | 115                                                                                                    |



---

## SQL Scripts

This appendix describes SQL scripts that are required for optimal operation of the Oracle Database.

The SQL scripts are described in the following sections:

- [Creating the Data Dictionary](#)
- [Creating Additional Data Dictionary Structures](#)
- [The "NO" Scripts](#)
- [Upgrade and Downgrade Scripts](#)
- [Java Scripts](#)

---

**Note:** Comments within the SQL scripts themselves contain more detailed information and examples.

---

### Creating the Data Dictionary

When you use the Database Configuration Assistant to create a database, Oracle automatically creates the data dictionary. Thereafter, whenever the database is in operation, Oracle updates the data dictionary in response to every DDL statement.

The data dictionary base tables are the first objects created in any Oracle database. They are created in the `SYSTEM` tablespace and must remain there. The data dictionary base tables store information about all user-defined objects in the database.

[Table B-1](#) lists required scripts, which are run automatically when you create a database using the Database Configuration Assistant. They are described here because you might need to run them if you create a database manually. To run these scripts, you must be connected to Oracle as a user with `SYSDBA` privileges.

**Table B-1** *Creating the Data Dictionary Scripts*

| Script Name  | Needed For                | Description                                                                                                                |
|--------------|---------------------------|----------------------------------------------------------------------------------------------------------------------------|
| catalog.sql  | All databases             | Creates the data dictionary and public synonyms for many of its views<br>Grants <code>PUBLIC</code> access to the synonyms |
| catproc.sql  | All databases             | Runs all scripts required for, or used with, PL/SQL                                                                        |
| catclust.sql | Real Application Clusters | Creates Real Application Clusters data dictionary views                                                                    |

**See Also:**

- Your operating system-specific Oracle documentation for the exact names and locations of these scripts on your operating system
- *Oracle Database Administrator's Guide* for more information about creating a database
- Your release notes and *Oracle Database Upgrade Guide* to learn when it is necessary to run these scripts

## Creating Additional Data Dictionary Structures

Oracle supplies other scripts that create additional structures you can use in managing your database and creating database applications. These scripts are listed in [Table B–2](#).

**See Also:** Your operating system-specific Oracle documentation for the exact names and locations of these scripts on your operating system

**Table B–2** Creating Additional Data Dictionary Structures

| Script Name                      | Needed For                | Run By        | Description                                                                                                                              |
|----------------------------------|---------------------------|---------------|------------------------------------------------------------------------------------------------------------------------------------------|
| catblock.sql                     | Performance management    | SYS           | Creates views that can dynamically display lock dependency graphs                                                                        |
| catexp7.sql                      | Exporting data to Oracle7 | SYS           | Creates the dictionary views needed for the Oracle7 Export utility to export data from the Oracle Database in Oracle7 Export file format |
| caths.sql                        | Heterogeneous Services    | SYS           | Installs packages for administering heterogeneous services                                                                               |
| catio.sql                        | Performance management    | SYS           | Allows I/O to be traced on a table-by-table basis                                                                                        |
| catockt.sql                      | Security                  | SYS           | Creates the Oracle Cryptographic Toolkit package                                                                                         |
| catqueue.sql                     | Advanced Queuing          |               | Creates the dictionary objects required for Advanced Queuing                                                                             |
| catrep.sql                       | Oracle Replication        | SYS           | Runs all SQL scripts for enabling database replication                                                                                   |
| dbmsiotc.sql                     | Storage management        | Any user      | Analyzes chained rows in index-organized tables                                                                                          |
| dbmspool.sql                     | Performance management    | SYS or SYSDBA | Enables DBA to lock PL/SQL packages, SQL statements, and triggers into the shared pool                                                   |
| userlock.sql                     | Concurrency control       | SYS or SYSDBA | Provides a facility for user-named locks that can be used in a local or clustered environment to aid in sequencing application actions   |
| utlbstat.sql and<br>utlestat.sql | Performance monitoring    | SYS           | Respectively start and stop collecting performance tuning statistics                                                                     |

**Table B–2 (Cont.) Creating Additional Data Dictionary Structures**

| Script Name  | Needed For             | Run By                        | Description                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------|------------------------|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| utlchn1.sql  | Storage management     | Any user                      | For use with the Oracle Database. Creates tables for storing the output of the ANALYZE command with the CHAINED ROWS option. Can handle both physical and logical rowids.                                                                                                                                                                                                                                 |
| utlconst.sql | Year 2000 compliance   | Any user                      | Provides functions to validate that CHECK constraints on date columns are year 2000 compliant                                                                                                                                                                                                                                                                                                             |
| utldtree.sql | Metadata management    | Any user                      | Creates tables and views that show dependencies between objects                                                                                                                                                                                                                                                                                                                                           |
| utlexpt1.sql | Constraints            | Any user                      | For use with the Oracle Database. Creates the default table (EXCEPTIONS) for storing exceptions from enabling constraints. Can handle both physical and logical rowids.                                                                                                                                                                                                                                   |
| utlip.sql    | PL/SQL                 | SYS                           | Used primarily for upgrade and downgrade operations. It invalidates all existing PL/SQL modules by altering certain dictionary tables so that subsequent recompilations will occur in the format required by the database. It also reloads the packages STANDARD and DBMS_STANDARD, which are necessary for any PL/SQL compilations.                                                                      |
| utlirp.sql   | PL/SQL                 | SYS                           | Used to change from 32-bit to 64-bit word size or vice versa. This script recompiles existing PL/SQL modules in the format required by the new database. It first alters some data dictionary tables. Then it reloads the packages STANDARD and DBMS_STANDARD, which are necessary for using PL/SQL. Finally, it triggers a recompilation of all PL/SQL modules, such as packages, procedures, and types. |
| utllockt.sql | Performance monitoring | SYS or SYSDBA                 | Displays a lock wait-for graph, in tree structure format                                                                                                                                                                                                                                                                                                                                                  |
| utlpwdmg.sql | Security               | SYS or SYSDBA                 | Creates PL/SQL functions for default password complexity verification. Sets the default password profile parameters and enables password management features.                                                                                                                                                                                                                                             |
| utlrp.sql    | PL/SQL                 | SYS                           | Recompiles all existing PL/SQL modules that were previously in an INVALID state, such as packages, procedures, and types.                                                                                                                                                                                                                                                                                 |
| utlsampl.sql | Examples               | SYS or any user with DBA role | Creates sample tables, such as emp and dept, and users, such as scott                                                                                                                                                                                                                                                                                                                                     |
| utlsc1n.sql  | Oracle Replication     | Any user                      | Copies a snapshot schema from another snapshot site                                                                                                                                                                                                                                                                                                                                                       |

**Table B–2 (Cont.) Creating Additional Data Dictionary Structures**

| Script Name  | Needed For             | Run By   | Description                                                                                               |
|--------------|------------------------|----------|-----------------------------------------------------------------------------------------------------------|
| utltkprf.sql | Performance management | SYS      | Creates the TKPROF role to allow the TKPROF profiling utility to be run by non-DBA users                  |
| utlvalid.sql | Partitioned tables     | Any user | Creates tables required for storing output of ANALYZE TABLE ... VALIDATE STRUCTURE of a partitioned table |
| utlxplan.sql | Performance management | Any user | Creates the table PLAN_TABLE, which holds output from the EXPLAIN PLAN statement                          |

## The "NO" Scripts

The scripts in [Table B–3](#) are used to remove dictionary information for various optional services or components.

**See Also:** *Oracle Database Upgrade Guide* for more information about these scripts

**Table B–3 The NO Scripts**

| Script Name  | Needed For             | Run By | Description                                                                                   |
|--------------|------------------------|--------|-----------------------------------------------------------------------------------------------|
| catnoadt.sql | Objects                | SYS    | Drops views and synonyms on dictionary metadata that relate to object types                   |
| catnoaud.sql | Security               | SYS    | Drops views and synonyms on auditing metadata                                                 |
| catnohs.sql  | Heterogeneous Services | SYS    | Removes Heterogeneous Services dictionary metadata                                            |
| catnoprt.sql | Partitioning           | SYS    | Drops views and synonyms on dictionary metadata that relate to partitioned tables and indexes |
| catnosvm.sql | Server Manager         | SYS    | Removes Oracle7 Server Manager views and synonyms                                             |
| catnsnmp.sql | Distributed management | SYS    | Drops the DBSNMP user and SNMPAGENT role                                                      |

## Upgrade and Downgrade Scripts

The scripts in [Table B–4](#) are used when upgrading or downgrading to another release of Oracle. To run these scripts, you must be connected to Oracle as a user with SYSDBA privileges.

**Table B–4 Upgrade and Downgrade Scripts**

| Script Name  | Needed For  | Description                                                               |
|--------------|-------------|---------------------------------------------------------------------------|
| catdwgrd.sql | Downgrading | Provides a direct downgrade path from the new Oracle Database 11g release |



**Table B–4 (Cont.) Upgrade and Downgrade Scripts**

| Script Name  | Needed For              | Description                                                                                                                     |
|--------------|-------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| catupgrd.sql | Upgrading               | Provides a direct upgrade path to the new Oracle Database 11g release                                                           |
| utlul12i.SQL | Pre-Upgrade Information | Analyzes the database to be upgraded, detailing requirements and issues for the upgrade to Oracle Database 11g Release 2 (11.2) |
| utlul12s.SQL | Post-Upgrade Status     | Displays the component upgrade status after an upgrade to Oracle Database 11g Release 2 (11.2)                                  |

**See Also:** *Oracle Database Upgrade Guide* for more information about these scripts

## Java Scripts

The scripts in [Table B–5](#) are useful only if the JServer option is installed.

**Table B–5 Java Scripts**

| Script Name | Description                                                                                  |
|-------------|----------------------------------------------------------------------------------------------|
| initjvm.sql | Initializes JServer by installing core Java class libraries and Oracle-specific Java classes |
| rmjvm.sql   | Removes all elements of the JServer                                                          |
| catjava.sql | Installs Java-related packages and classes                                                   |

**See Also:** *Oracle Database Java Developer's Guide*



---

# Oracle Wait Events

This appendix contains the following topics:

- [Classes of Wait Events](#)
- [Descriptions of Common Wait Event Parameters](#)
- [Descriptions of Wait Events](#)

Information about wait events is displayed in three dynamic performance views:

- `V$SESSION_WAIT` displays the events for which sessions have just completed waiting or are currently waiting.
- `V$SYSTEM_EVENT` displays the total number of times all the sessions have waited for the events in that view.
- `V$SESSION_EVENT` is similar to `V$SYSTEM_EVENT`, but displays all waits for each session.

**See Also:** ["V\\$SESSION\\_EVENT"](#) on page 9-16, ["V\\$SESSION\\_WAIT"](#) on page 9-19, and ["V\\$SYSTEM\\_EVENT"](#) on page 9-78

Many of these wait events are tied to the internal implementation of Oracle and therefore are subject to change or deletion without notice. Application developers should be aware of this and write their code to tolerate missing or extra wait events.

The following SQL statement displays an alphabetical list of all Oracle wait events and the wait class to which they belong:

```
SQL> SELECT name, wait_class FROM V$EVENT_NAME ORDER BY name;
```

## Classes of Wait Events

Every wait event belongs to a class of wait event. The following list describes each of the wait classes.

### Administrative

Waits resulting from DBA commands that cause users to wait (for example, an index rebuild)

### Application

Waits resulting from user application code (for example, lock waits caused by row level locking or explicit lock commands)

**Cluster**

Waits related to Real Application Clusters resources (for example, global cache resources such as 'gc cr block busy')

**Commit**

This wait class only comprises one wait event - wait for redo log write confirmation after a commit (that is, 'log file sync')

**Concurrency**

Waits for internal database resources (for example, latches)

**Configuration**

Waits caused by inadequate configuration of database or instance resources (for example, undersized log file sizes, shared pool size)

**Idle**

Waits that signify the session is inactive, waiting for work (for example, 'SQL\*Net message from client')

**Network**

Waits related to network messaging (for example, 'SQL\*Net more data to dblink')

**Other**

Waits which should not typically occur on a system (for example, 'wait for EMON to spawn')

**Queue**

Contains events that signify delays in obtaining additional data in a pipelined environment. The time spent on these wait events indicates inefficiency or other problems in the pipeline. It affects features such as Oracle Streams, parallel queries, or DBMS\_PIPE PL/SQL packages.

**Scheduler**

Resource Manager related waits (for example, 'resmgr: become active')

**System I/O**

Waits for background process I/O (for example, DBWR wait for 'db file parallel write')

**User I/O**

Waits for user I/O (for example 'db file sequential read')

## Descriptions of Common Wait Event Parameters

This section provides descriptions of some of the more common wait event parameters.

**block#**

This is the block number of the block for which Oracle needs to wait. The block number is relative to the start of the file. To find the object to which this block belongs, issue the following SQL statement:

```
select segment_name, segment_type, owner, tablespace_name
```

```
from dba_extents
where file_id = file#
 and block#
 between block_id and block_id + blocks - 1;
```

**blocks**

The number of blocks that is being either read from or written to the file. The block size is dependent on the file type:

- Database files have a block size of DB\_BLOCK\_SIZE
- Logfiles and control files have a block size that is equivalent to the physical block size of the platform

**break?**

If the value for this parameter equals 0, a reset was sent to the client. A nonzero value indicates that a break was sent to the client.

**class**

The class of the block describes how the contents of the block are used. For example, class 1 represents data block, and class 4 represents segment header.

**dba**

The initials "dba" represents the data block address, which consists of a file number and a block number.

**driver id**

The address of the disconnect function of the driver that is currently being used.

**file#**

The following query returns the name of the database file:

```
select *
from v$datafile
where file# = file#;
```

**id1**

The first identifier (*id1*) of the enqueue or global lock takes its value from P2 or P2RAW. The meaning of the identifier depends on the name (P1).

**id2**

The second identifier (*id2*) of the enqueue or global lock takes its value from P3 or P3RAW. The meaning of the identifier depends on the name (P1).

**le**

The relative index number into V\$GC\_ELEMENT.

**mode**

The *mode* is usually stored in the low order bytes of P1 or P1RAW and indicates the mode of the enqueue or global lock request. This parameter has one of the following values:

**Table C-1 Lock Mode Values**

| Mode Value | Description         |
|------------|---------------------|
| 1          | Null mode           |
| 2          | Sub-Share           |
| 3          | Sub-Exclusive       |
| 4          | Share               |
| 5          | Share/Sub-Exclusive |
| 6          | Exclusive           |

Use the following SQL statement to retrieve the name of the lock and the mode of the lock request:

```
select chr(bitand(p1,-16777216)/16777215)||
 chr(bitand(p1, 16711680)/65535) "Lock",
 bitand(p1, 65535) "Mode"
from v$session_wait
where event = 'DFS enqueue lock acquisition';
```

### name and type

The name or "type" of the enqueue or global lock can be determined by looking at the two high order bytes of P1 or P1RAW. The name is always two characters. Use the following SQL statement to retrieve the lock name.

```
select chr(bitand(p1,-16777216)/16777215)||
 chr(bitand(p1,16711680)/65535) "Lock"
from v$session_wait
where event = 'DFS enqueue lock acquisition';
```

### namespace

The name of the object namespace as it is displayed in V\$DB\_OBJECT\_CACHE view.

### requests

The number of I/Os that are "requested." This differs from the number of blocks in that one request could potentially contain multiple blocks.

### session#

The number of the inactive session. Use the following SQL statement to find more information about the session:

```
select *
from v$session
where sid = session#;
```

### waited

This is the total amount of time the session has waited for this session to terminate.

## Descriptions of Wait Events

This section provides detailed descriptions for those wait events of greatest interest. Where appropriate, pointers are provided to further information elsewhere in Oracle Database documentation. For a complete listing of wait events, in alphabetical order, you can issue the following SQL statement:

```
SQL> SELECT name FROM V$EVENT_NAME ORDER BY name;
```

### alter system set dispatcher

A session has issued a statement `ALTER SYSTEM SET DISPATCHER = string` and is waiting for the dispatchers to get started.

**Wait Time:** The session will wait 1 / 100 of a second and check to see if the new dispatchers have started else the session will wait again

| Parameter     | Description                                                     |
|---------------|-----------------------------------------------------------------|
| <i>waited</i> | Number of times that the session has waited 1 / 100 of a second |

### batched allocate scn lock request

A session is waiting on another process to allocate a system change number (SCN). If the foreground timed out waiting on a process to get the SCN, the foreground will get the SCN.

**Wait Time:** The wait time is 1 second on the assumption that an SCN allocation should normally need much less than that

**Parameters:** None

### BFILE check if exists

The session waits to check if an external large object (LOB) exists.

**Wait Time:** The total elapsed time for the **exists** call

| Parameter       | Description                                  |
|-----------------|----------------------------------------------|
| <i>session#</i> | See " <a href="#">session#</a> " on page C-4 |
| <i>waited</i>   | See " <a href="#">waited</a> " on page C-4   |

### BFILE check if open

The session waits for an external large object (LOB) to open.

**Wait Time:** The total elapsed time for the **isopen** call

| Parameter       | Description                                  |
|-----------------|----------------------------------------------|
| <i>session#</i> | See " <a href="#">session#</a> " on page C-4 |
| <i>waited</i>   | See " <a href="#">waited</a> " on page C-4   |

### BFILE closure

The session waits for an external large object (LOB) to close.

**Wait Time:** The total elapsed time for the **close** call

| Parameter       | Description                                  |
|-----------------|----------------------------------------------|
| <i>session#</i> | See " <a href="#">session#</a> " on page C-4 |
| <i>waited</i>   | See " <a href="#">waited</a> " on page C-4   |

## BFILE get length

The session waits on a call to check the size of an external large object (LOB).

**Wait Time:** The total elapsed time for the call to check the LOB size

| Parameter       | Description                                  |
|-----------------|----------------------------------------------|
| <i>session#</i> | See " <a href="#">session#</a> " on page C-4 |
| <i>waited</i>   | See " <a href="#">waited</a> " on page C-4   |

## BFILE get name object

The session waits on a call to find or generate the external name of a external large object.

**Wait Time:** The total elapsed time for **make external file name** to complete

| Parameter       | Description                                  |
|-----------------|----------------------------------------------|
| <i>session#</i> | See " <a href="#">session#</a> " on page C-4 |
| <i>waited</i>   | See " <a href="#">waited</a> " on page C-4   |

## BFILE get path object

The session is waiting on a call to find or generate the external path name of an external large object (LOB).

**Wait Time:** The total elapsed time for **make external path** to complete

| Parameter       | Description                                  |
|-----------------|----------------------------------------------|
| <i>session#</i> | See " <a href="#">session#</a> " on page C-4 |
| <i>waited</i>   | See " <a href="#">waited</a> " on page C-4   |

## BFILE internal seek

The session waits for a positioning call within the external large object (LOB) to complete.

**Wait Time:** The total elapsed time for the **seek** to complete

| Parameter       | Description                                  |
|-----------------|----------------------------------------------|
| <i>session#</i> | See " <a href="#">session#</a> " on page C-4 |
| <i>waited</i>   | See " <a href="#">waited</a> " on page C-4   |

## BFILE open

The session waits for an external large object (LOB) to open.

**Wait Time:** The total elapsed time for the **isopen** call



| Parameter       | Description                                  |
|-----------------|----------------------------------------------|
| <i>session#</i> | See " <a href="#">session#</a> " on page C-4 |
| <i>waited</i>   | See " <a href="#">waited</a> " on page C-4   |

## BFILE read

The session waits for a read from a external large object (LOB) to complete.

**Wait Time:** The total elapsed time for the **read** to complete

| Parameter       | Description                                  |
|-----------------|----------------------------------------------|
| <i>session#</i> | See " <a href="#">session#</a> " on page C-4 |
| <i>waited</i>   | See " <a href="#">waited</a> " on page C-4   |

## broadcast mesg queue transition

Processes enter "wait for broadcast mesg queue transition" when cleaning up a publisher channel handle to a RELIABLE broadcast channel. The publisher is responsible for moving the message to the free queue, but it cannot do so until the message is in the done queue. If the message is still not in the done queue, process enters this wait. This wait event will most likely show up when an Oracle process is about to exit normally, or when PMON cleans up a dead process.

**Wait Time:** Varies

| Parameter             | Description                                                          |
|-----------------------|----------------------------------------------------------------------|
| <i>channel handle</i> | publisher channel handle pointer                                     |
| <i>message</i>        | broadcast message pointer                                            |
| <i>location</i>       | A number indicating the function in KSR where the process is waiting |

## broadcast mesg recovery queue transition

Processes enter "wait for broadcast mesg recovery queue transition" when cleaning up a publisher channel handle to a RELIABLE broadcast channel. The broadcasted message is in the recovery queue of another channel handle (for example, ch2). Process enters this wait, if the message is yet to be removed from the recovery queue of the ch2 channel handle. This wait event will most likely show up when an Oracle process is about to exit normally, or when PMON cleans up a dead process.

**Wait Time:** Varies

| Parameter             | Description                                                          |
|-----------------------|----------------------------------------------------------------------|
| <i>channel handle</i> | Publisher channel handle pointer                                     |
| <i>message</i>        | Broadcast message pointer                                            |
| <i>location</i>       | A number indicating the function in KSR where the process is waiting |

## buffer busy waits

Wait until a buffer becomes available. This event happens because a buffer is either being read into the buffer cache by another session (and the session is waiting for that

read to complete) or the buffer is the buffer cache, but in a incompatible mode (that is, some other session is changing the buffer).

**Wait Time:** Normal wait time is 1 second. If the session was waiting for a buffer during the last wait, then the next wait will be 3 seconds.

| Parameter     | Description                                                               |
|---------------|---------------------------------------------------------------------------|
| <i>file#</i>  | See " <a href="#">file#</a> " on page C-3                                 |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2                                |
| <i>id</i>     | The buffer busy wait event is called from different places in the session |

## buffer deadlock

Oracle does not really wait on this event; the foreground only yields the CPU. Thus, the chances of catching this event are very low. This is not an application induced deadlock, but an assumed deadlock by the cache layer. The cache layer cannot get a buffer in a certain mode within a certain amount of time.

**Wait Time:** 0 seconds. The foreground process only yields the CPU and will usually be placed at the end of the CPU run queue.

| Parameter    | Description                                                                 |
|--------------|-----------------------------------------------------------------------------|
| <i>class</i> | See " <a href="#">class</a> " on page C-3                                   |
| <i>mode</i>  | See " <a href="#">mode</a> " on page C-3                                    |
| <i>flag</i>  | The flag points to the internal flags used by the session to get this block |
| <i>dba</i>   | See " <a href="#">dba</a> " on page C-3                                     |

## buffer latch

The session waits on the buffer hash chain latch. Primarily used in the dump routines.

**Wait Time:** 1 second

| Parameter         | Description                                                                                                                                                                                                                                |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>latch addr</i> | The virtual address in the SGA where this latch is located. Use the following statement to find the name of this latch:<br><br><pre>select * from v\$latch a, v\$latchname b where addr = <i>latch addr</i> and a.latch# = b.latch#;</pre> |
| <i>chain#</i>     | The index into array of buffer hash chains. When the chain is 0xffffffff, the foreground waits on the LRU latch.                                                                                                                           |

## buffer read retry

This event occurs only if the instance is mounted in shared mode (Oracle Real Application Cluster). During the read of the buffer, the contents changed. This means that either:

- The version number, dba, or the incarnation and sequence number stored in the block no longer match
- The checksum on the block does not match the checksum in the block

The block will be re-read (this may fail up to 3 times), then corruption is assumed and the corrupt block is dumped in the trace file.

**Wait Time:** The wait time is the elapsed time of the read

| Parameter     | Description              |
|---------------|--------------------------|
| <i>file#</i>  | See "file#" on page C-3  |
| <i>block#</i> | See "block#" on page C-2 |

## checkpoint completed

A session waits for a checkpoint to complete. This could happen, for example, during a close database or a local checkpoint.

**Wait Time:** 5 seconds

**Parameters:** None

## cleanup of aborted processes

When a process spawn is aborted while the process spawning background is in the middle of spawning, the current session must wait until the pid of the new process is filled in. Once the pid is filled in, then the process spawn can be actually aborted.

**Wait Time:** Usually 3 seconds

| Parameter       | Description          |
|-----------------|----------------------|
| <i>location</i> | Location of the wait |

## control file parallel write

This event occurs while the session is writing physical blocks to all control files. This happens when:

- The session starts a control file transaction (to make sure that the control files are up to date in case the session crashes before committing the control file transaction)
- The session commits a transaction to a control file
- Changing a generic entry in the control file, the new value is being written to all control files

**Wait Time:** The wait time is the time it takes to finish all writes to all control files

| Parameter       | Description                                                          |
|-----------------|----------------------------------------------------------------------|
| <i>files</i>    | The number of control files to which the session is writing          |
| <i>blocks</i>   | The number of blocks that the session is writing to the control file |
| <i>requests</i> | The number of I/O requests which the session wants to write          |

## control file sequential read

Reading from the control file. This happens in many cases. For example, while:

- Making a backup of the control files
- Sharing information (between instances) from the control file

- Reading other blocks from the control files
- Reading the header block

**Wait Time:** The wait time is the elapsed time of the read

| Parameter     | Description                                                                                                                                                                               |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>file#</i>  | The control file from which the session is reading                                                                                                                                        |
| <i>block#</i> | Block number in the control file from where the session starts to read. The block size is the physical block size of the port (usually 512 bytes, some UNIX ports have 1 or 2 Kilobytes). |
| <i>blocks</i> | The number of blocks that the session is trying to read                                                                                                                                   |

## control file single write

This wait is signaled while the control file's shared information is written to disk. This is an atomic operation protected by an enqueue (CF), so that only one session at a time can write to the entire database.

**Wait Time:** The wait time is the elapsed time of the write

| Parameter     | Description                                                                                                                                                                       |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>file#</i>  | This identifies the control file to which the session is currently writing                                                                                                        |
| <i>block#</i> | Block number in the control file where the write begins. The block size is the as the physical block size of the port (usually 512 bytes, some UNIX ports have 1 or 2 Kilobytes). |
| <i>blocks</i> | The number of blocks that the session is trying to read                                                                                                                           |

## cursor: mutex S

A session waits on this event when it is requesting a mutex in shared mode, when another session is currently holding a this mutex in exclusive mode on the same cursor object.

| Parameter | Description                                                                                                          |
|-----------|----------------------------------------------------------------------------------------------------------------------|
| <i>P1</i> | Hash value of cursor                                                                                                 |
| <i>P2</i> | Mutex value (top 2 bytes contain SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0) |
| <i>P3</i> | Mutex where (an internal code locator) OR'd with Mutex Sleeps                                                        |

## cursor: mutex X

The session requests the mutex for a cursor object in exclusive mode, and it must wait because the resource is busy. The mutex is busy because either the mutex is being held in exclusive mode by another session or the mutex is being held shared by one or more sessions. The existing mutex holder(s) must release the mutex before the mutex can be granted exclusively.

| Parameter | Description                                                                                                          |
|-----------|----------------------------------------------------------------------------------------------------------------------|
| <i>P1</i> | Hash value of cursor                                                                                                 |
| <i>P2</i> | Mutex value (top 2 bytes contain SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0) |

| Parameter | Description                                                   |
|-----------|---------------------------------------------------------------|
| <i>P3</i> | Mutex where (an internal code locator) OR'd with Mutex Sleeps |

### cursor: pin S

A session waits on this event when it wants to update a shared mutex pin and another session is currently in the process of updating a shared mutex pin for the same cursor object. This wait event should rarely be seen because a shared mutex pin update is very fast.

**Wait Time:** Microseconds

| Parameter | Description                                                                                                           |
|-----------|-----------------------------------------------------------------------------------------------------------------------|
| <i>P1</i> | Hash value of cursor                                                                                                  |
| <i>P2</i> | Mutex value (top 2 bytes contains SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0) |
| <i>P3</i> | Mutex where (an internal code locator) OR'd with Mutex Sleeps                                                         |

### cursor: pin S wait on X

A session waits for this event when it is requesting a shared mutex pin and another session is holding an exclusive mutex pin on the same cursor object.

**Wait Time:** Microseconds

| Parameter | Description                                                                                                           |
|-----------|-----------------------------------------------------------------------------------------------------------------------|
| <i>P1</i> | Hash value of cursor                                                                                                  |
| <i>P2</i> | Mutex value (top 2 bytes contains SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0) |
| <i>P3</i> | Mutex where (an internal code locator) OR'd with Mutex Sleeps                                                         |

### cursor: pin X

A session waits on this event when it is requesting an exclusive mutex pin for a cursor object and it must wait because the resource is busy. The mutex pin for a cursor object can be busy either because a session is already holding it exclusive, or there are one or more sessions which are holding shared mutex pin(s). The exclusive waiter must wait until all holders of the pin for that cursor object have released it, before it can be granted.

**Wait Time:** Microseconds

| Parameter | Description                                                                                                           |
|-----------|-----------------------------------------------------------------------------------------------------------------------|
| <i>P1</i> | Hash value of cursor                                                                                                  |
| <i>P2</i> | Mutex value (top 2 bytes contains SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0) |
| <i>P3</i> | Mutex where (an internal code locator) OR'd with Mutex Sleeps                                                         |

### Data Guard: process clean up

During Data Guard process termination, Data Guard will wait for one second for process cleanup to complete.

## Data Guard: process exit

During Data Guard process termination, Data Guard will wait for a process to exit before attempting any process cleanup that may be required. It will sleep for one second between each check for process exit.

## Data Guard Broker: single instance

The Data Guard Broker (DMON) process waits for the other instances in this cluster to complete shutdown before continuing with the broker operation.

**Wait Time:** Depends on the number of instances, but not exceeding 30 seconds times the number of instances

## db file parallel read

This happens during recovery. It can also happen during buffer prefetching, as an optimization (rather than performing multiple single-block reads). Database blocks that need to be changed as part of recovery are read in parallel from the database.

**Wait Time:** Wait until all of the I/Os are completed

| Parameter       | Description                                                                       |
|-----------------|-----------------------------------------------------------------------------------|
| <i>files</i>    | This indicates the number of files to which the session is reading                |
| <i>blocks</i>   | This indicates the total number of blocks to be read                              |
| <i>requests</i> | This indicates the total number of I/O requests, which will be the same as blocks |

## db file parallel write

This event occurs in the DBWR. It indicates that the DBWR is performing a parallel write to files and blocks. When the last I/O has gone to disk, the wait ends.

**Wait Time:** Wait until all of the I/Os are completed

| Parameter        | Description                                                                                |
|------------------|--------------------------------------------------------------------------------------------|
| <i>requests</i>  | This indicates the total number of I/O requests, which will be the same as blocks          |
| <i>interrupt</i> |                                                                                            |
| <i>timeout</i>   | This indicates the timeout value in hundredths of a second to wait for the I/O completion. |

## db file scattered read

Similar to **db file sequential read**, except that the session is reading multiple data blocks.

**Wait Time:** The wait time is the actual time it takes to do all of the I/Os

| Parameter     | Description                                                                                             |
|---------------|---------------------------------------------------------------------------------------------------------|
| <i>file#</i>  | See "file#" on page C-3                                                                                 |
| <i>block#</i> | See "block#" on page C-2                                                                                |
| <i>blocks</i> | The number of blocks that the session is trying to read from the <i>file#</i> starting at <i>block#</i> |

## db file sequential read

The session waits while a sequential read from the database is performed. This event is also used for rebuilding the control file, dumping datafile headers, and getting the database file headers.

**Wait Time:** The wait time is the actual time it takes to do the I/O

| Parameter     | Description                                                                   |
|---------------|-------------------------------------------------------------------------------|
| <i>file#</i>  | See " <a href="#">file#</a> " on page C-3                                     |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2                                    |
| <i>blocks</i> | This is the number of blocks that the session is trying to read (should be 1) |

## db file single write

This event is used to wait for the writing of the file headers.

**Wait Time:** The wait time is the actual time it takes to do the I/O

| Parameter     | Description                                                                                                |
|---------------|------------------------------------------------------------------------------------------------------------|
| <i>file#</i>  | See " <a href="#">file#</a> " on page C-3                                                                  |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2                                                                 |
| <i>blocks</i> | This is the number of blocks that the session is trying to write in <i>file#</i> starting at <i>block#</i> |

## DFS db file lock

This event occurs only for the DBWR in Real Application Clusters. Each DBWR of every instance holds a global lock on each file in shared mode. The instance that is trying to offline the file will escalate the global lock from shared to exclusive. This signals the other instances to synchronize their SGAs with the control file before the file can be taken offline. The name of this lock is **DF** (see [Appendix D, "Oracle Enqueue Names"](#) for more information).

**Wait Time:** 1 second in loop. The DBWR is waiting in a loop (sleep, check) for the other instances to downgrade to NULL mode. During this time, the DBWR cannot perform other tasks such as writing buffers.

| Parameter   | Description                               |
|-------------|-------------------------------------------|
| <i>file</i> | See " <a href="#">file#</a> " on page C-3 |

## DFS lock handle

The session waits for the lock handle of a global lock request. The lock handle identifies a global lock. With this lock handle, other operations can be performed on this global lock (to identify the global lock in future operations such as conversions or release). The global lock is maintained by the DLM.

**Wait Time:** The session waits in a loop until it has obtained the lock handle from the DLM. Inside the loop there is a wait of 0.5 seconds.

| Parameter   | Description                                       |
|-------------|---------------------------------------------------|
| <i>name</i> | See " <a href="#">name and type</a> " on page C-4 |
| <i>mode</i> | See " <a href="#">mode</a> " on page C-3          |
| <i>id1</i>  | See " <a href="#">id1</a> " on page C-3           |
| <i>id2</i>  | See " <a href="#">id2</a> " on page C-3           |

The session needs to get the lock handle.

## direct path read

During Direct Path operations the data is asynchronously read from the database files. At some stage the session needs to make sure that all outstanding asynchronous I/O have been completed to disk. This can also happen if during a direct read no more slots are available to store outstanding load requests (a load request could consist of multiple I/Os).

**Wait Time:** 10 seconds. The session will be posted by the completing asynchronous I/O. It will never wait the entire 10 seconds. The session waits in a tight loop until all outstanding I/Os have completed.

| Parameter                 | Description                                                                                               |
|---------------------------|-----------------------------------------------------------------------------------------------------------|
| <i>descriptor address</i> | This is a pointer to the I/O context of outstanding direct I/Os on which the session is currently waiting |
| <i>first dba</i>          | The dba of the oldest I/O in the context referenced by the descriptor address                             |
| <i>block cnt</i>          | Number of valid buffers in the context referenced by the descriptor address                               |

## direct path sync

During Direct Path write operations the data is asynchronously written to the database files. At some point the session needs to ensure that all outstanding asynchronous I/O have been completed to disk. On Unix the fsync command, which synchronizes data to disk, is issued to confirm that all the writes have completed and the data is all on disk.

**Wait Time:** The time taken for the fsync operation to complete, which normally is the time taken to complete the outstanding I/Os.

| Parameters   | Description                               |
|--------------|-------------------------------------------|
| <i>file#</i> | See " <a href="#">file#</a> " on page C-3 |
| <i>flags</i> | Flags used for debugging purposes         |

## direct path write

During Direct Path operations, the data is asynchronously written to the database files. At some stage the session needs to make sure that all outstanding asynchronous I/O have been completed to disk. This can also happen if, during a direct write, no more slots are available to store outstanding load requests (a load request could consist of multiple I/Os).



**Wait Time:** 10 seconds. The session will be posted by the completing asynchronous I/O. It will never wait the entire 10 seconds. The session waits in a tight loop until all outstanding I/Os have completed.

| Parameter                 | Description                                                                                               |
|---------------------------|-----------------------------------------------------------------------------------------------------------|
| <i>descriptor address</i> | This is a pointer to the I/O context of outstanding direct I/Os on which the session is currently waiting |
| <i>first dba</i>          | The dba of the oldest I/O in the context referenced by the descriptor address                             |
| <i>block cnt</i>          | Number of valid buffers in the context referenced by the descriptor address                               |

## Disk file operations I/O

This event is used to wait for disk file operations (for example, open, close, seek, and resize). It is also used for miscellaneous I/O operations such as block dumps and password file accesses.

**Wait Time:** The wait time is the actual time it takes to do the I/O

| Parameter            | Description                                                |
|----------------------|------------------------------------------------------------|
| <i>FileOperation</i> | Type of file operation                                     |
| <i>fileno</i>        | File identification number                                 |
| <i>filetype</i>      | Type of file (for example, log file, data file, and so on) |

## dispatcher shutdown

During shutdown immediate or normal, the shutdown process must wait for all the dispatchers to shutdown. As each dispatcher is signaled, the session that causes the shutdown is waits on this event until the requested dispatcher is no longer alive.

**Wait Time:** 1 second

| Parameter     | Description                                                                                                                                     |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>waited</i> | Indicates the cumulative wait time. After 5 minutes, the session writes to the alert and trace files to indicate that there might be a problem. |

## dispatcher timer

This basically means that the dispatcher is idle and waiting for some work to arrive.

**Wait Time:** 60 seconds

| Parameter         | Description                                                                                                                                                                                          |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sleep time</i> | The intended sleep time. The dispatcher will return to work sooner if it is posted by either data arriving on the network or by a post from a shared server process to send data back to the client. |

## duplicate cluster key

It is possible for a race condition to occur when creating a new cluster key. If it is found that another process has put the cluster key into the data/index block, then the session waits and retries. The retry should then find a valid cluster key.

**Wait Time:** 0.01 seconds

| Parameter  | Description                                                                   |
|------------|-------------------------------------------------------------------------------|
| <i>dba</i> | The dba of the block into which the session is trying to insert a cluster key |

### enq: OW - initialization

A session will wait on this event if it is trying to initialize the database wallet, and another session has already begun an initialization.

**Wait Time:** Total time necessary to initialize the wallet context

**Parameters:** None

### enq: OW - termination

A session will wait on this event if it is trying to terminate the database wallet, and another session has already begun a termination.

**Wait Time:** Total time necessary to deallocate memory used by the wallet context and terminate the context.

**Parameters:** None

### enqueue

The session is waiting for a local enqueue. The wait is dependent on the name of the enqueue (see [Appendix D, "Oracle Enqueue Names"](#)).

**Wait Time:** Depends on the enqueue name

| Parameter   | Description                                       |
|-------------|---------------------------------------------------|
| <i>name</i> | See " <a href="#">name and type</a> " on page C-4 |
| <i>mode</i> | See " <a href="#">mode</a> " on page C-3          |

### flashback buf free by RVWR

This wait event only occurs when Flashback Database is turned on. A session waits for recovery writer (RVWR) to write flashback data to the flashback logs on disk because the buffers are full. Until RVWR can free up the buffers, the session may need to wait.

If this event becomes a top wait event for the database, it is typically because the file system or storage system for the Fast Recovery Area does not support enough bandwidth for Oracle to write the flashback database logs. Refer to the Flashback Database section in *Oracle Database Backup and Recovery User's Guide* for tuning considerations.

**Wait Time:** 1 second

**Parameters:** None

### flashback logfile sync

Waits for flashback database data to be written to disk.

**Wait Time:** Includes RVWR writing the flashback database data and posting this process

**Parameters:** None

## free buffer waits

This will happen if:

- All buffer gets have been suspended. This could happen when a file was read-only and is now read-write. All the existing buffers need to be invalidated since they are not linked to lock elements (needed when mounted parallel (shared)). So cache buffers are not assigned to data block addresses until the invalidation is finished.
- The session moved some dirty buffers to the dirty queue and now this dirty queue is full. The dirty queue needs to be written first. The session will wait on this event and try again to find a free buffer
- This also happens after inspecting **free buffer inspected** buffers. If no free buffer is found, Oracle waits for one second, and then tries to get the buffer again (depends on the context). For more information, see [free buffer inspected](#) on page E-6.

**Wait Time:** 1 second

| Parameter     | Description                                |
|---------------|--------------------------------------------|
| <i>file#</i>  | See " <a href="#">file#</a> " on page C-3  |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2 |

## free global transaction table entry

The session is waiting for a free slot in the global transaction table (used by the Distributed Database option). It will wait for 1 second and try again.

**Wait Time:** 1 second

| Parameter    | Description                                                                               |
|--------------|-------------------------------------------------------------------------------------------|
| <i>tries</i> | The number of times the session tried to find a free slot in the global transaction table |

## free process state object

Used during the creation of a process. The session will scan the process table and look for a free process slot. If none can be found, PMON is posted to check if all the processes currently in the process table are still alive. If there are dead processes, then PMON will clean them and make the process slot available to new processes. The waiting process will then rescan the process table to find the new slot.

**Wait Time:** 1 second

**Parameters:** None

## gc recovery quiesce

Instance recovery is waiting for a global cache operation to complete.

**Wait Time:** The total elapsed time for the global cache operation to complete

| Parameter    | Description                               |
|--------------|-------------------------------------------|
| <i>file#</i> | See " <a href="#">file#</a> " on page C-3 |

| Parameter     | Description                                |
|---------------|--------------------------------------------|
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2 |
| <i>class</i>  | See " <a href="#">class</a> " on page C-3  |

## GCS lock open S

The session waits for a resource get in SHARED mode on the block identified by file# and block#.

**Wait Time:** 1 second

| Parameter     | Description                                |
|---------------|--------------------------------------------|
| <i>file#</i>  | See " <a href="#">file#</a> " on page C-3  |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2 |
| <i>class</i>  | See " <a href="#">class</a> " on page C-3  |

## GCS lock open X

The session waits for a resource get in EXCLUSIVE mode on the block identified by file# and block#.

**Wait Time:** 1 second

| Parameter     | Description                                |
|---------------|--------------------------------------------|
| <i>file#</i>  | See " <a href="#">file#</a> " on page C-3  |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2 |
| <i>lenum</i>  | See " <a href="#">le</a> " on page C-3     |

## gcs remastering wait for drop pkey

A session dropping an object waits on the lock manager daemon (LMD) to remove the object's affinity to an instance.

**Wait Time:** 20 hundredths of a second

| Parameter   | Description                                        |
|-------------|----------------------------------------------------|
| <i>pkey</i> | The object id of the database object being dropped |

## global cache busy

The session waits to convert a buffer from Shared Current to Exclusive Current status.

**Wait Time:** 1 second

| Parameter     | Description                                |
|---------------|--------------------------------------------|
| <i>file#</i>  | See " <a href="#">file#</a> " on page C-3  |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2 |
| <i>le</i>     | See " <a href="#">lenum</a> " on page A-8  |

## global cache lock cleanup

PMON is waiting for an LCK process to cleanup the lock context after a foreground process died while doing a global cache lock operation.

**Wait Time:** 1 second

| Parameter     | Description              |
|---------------|--------------------------|
| <i>file#</i>  | See "file#" on page C-3  |
| <i>block#</i> | See "block#" on page C-2 |
| <i>lenum</i>  | See "lenum" on page A-8  |

## global cache freelist

All releasable locks are used and a new one has been requested. To make a resource element available, a resource element is pinged.

**Wait Time:** The duration of the resource get operation to ping the resource element

**Parameters:** None

## inactive session

This event is used for two purposes:

- Switching sessions  
If a time-out period has been specified, then wait that amount of time for the session to be detached.
- Killing sessions  
From either KILL SESSION or internal request. Having posted a session that it should kill itself, wait for up to 1 minute for the session to terminate.

**Wait Time:** 1 second

| Parameter       | Description                |
|-----------------|----------------------------|
| <i>session#</i> | See "session#" on page C-4 |
| <i>waited</i>   | See "waited" on page C-4   |

## inactive transaction branch

The session waits for a transaction branch that is currently used by another session.

**Wait Time:** 1 second

| Parameter      | Description                                                           |
|----------------|-----------------------------------------------------------------------|
| <i>branch#</i> | The serial number of the transaction for which the session is waiting |
| <i>waited</i>  | See "waited" on page C-4                                              |

## index block split

While trying to find an index key in an index block, Oracle noticed that the index block was being split. Oracle will wait for the split to finish and try to find the key again.

**Wait Time:** The session will yield the CPU, so there is no actual waiting time

| Parameter      | Description                                                                                                                                                                                                         |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>rootdba</i> | The root of the index                                                                                                                                                                                               |
| <i>level</i>   | This is the level of the block that the session is trying to split in the index. The leaf blocks are level 0. If the level is > 0, it is a branch block. (The root block can be considered a special branch block). |
| <i>childdb</i> | The block that the session is trying to split                                                                                                                                                                       |

## instance state change

The session waits for SMON to enable or disable cache or transaction recovery. This usually happens during `ALTER DATABASE OPEN` or `CLOSE`.

**Wait Time:** Wait time depends on the amount of time the action takes (that is, the amount of recovery needed)

| Parameter     | Description                                                                                                                                                           |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>layer</i>  | This value can be 1 or 2. If 1, it means that the transaction layer wants transaction recovery to be performed. If 2, it means that cache recovery will be performed. |
| <i>value</i>  | This value can be 0 (disable) or 1 (enable)                                                                                                                           |
| <i>waited</i> | The number of seconds waited so far                                                                                                                                   |

## io done

The session waits for an I/O to complete or it waits for a slave process to become available to submit the I/O request. This event occurs on platforms that do not support asynchronous I/O.

**Wait Time:** 50 milliseconds

| Parameter      | Description                  |
|----------------|------------------------------|
| <i>msg ptr</i> | A pointer to the I/O request |

## kcl bg acks

The session waits for the background LCK process(es) to finish what they are doing. For example:

- Lock recovery
- Initializing the locks (start up)
- Finalizing the locks (shut down)

**Wait Time:** 10 seconds

| Parameter    | Description                                                                                   |
|--------------|-----------------------------------------------------------------------------------------------|
| <i>count</i> | The number of LCK processes that have finished                                                |
| <i>loops</i> | The number times the process had to wait for the LCK processes to finish what they were doing |

## ksxr wait for mount shared

The cross instance broadcast facility of this Oracle instance is waiting for the database mount in shared mode to complete.

**Wait Time:** The time taken for the instance to mount. An indefinite wait on this event implies that the instance startup is hanging.

## ktm: instance recovery

The session waits for SMON to finish the instance, transaction recovery, or sort segment cleanup.

**Wait Time:** The wait time can vary and depends on the amount of recovery needed

| Parameter            | Description                                                                                                                                                                                     |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>undo segment#</i> | <p>If the value is 0, SMON is probably performing instance recovery. If P1 &gt; 0, use this query to find the undo segment:</p> <pre>select * from v\$rollstat where usn = undo segment#;</pre> |

## latch activity

This event is used as part of the process of determining whether a latch needs to be cleaned.

**Wait Time:** 0.05 to 0.1 seconds

| Parameter       | Description                                                                                                                                                                                  |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>address</i>  | The address of the latch that is being checked                                                                                                                                               |
| <i>number</i>   | <p>The latch number of the latch that has activity. To find more information on the latch, use the following SQL statement:</p> <pre>select * from v\$latchname where latch# = number;</pre> |
| <i>process#</i> | If this is 0, it is the first phase of the in-flux tests                                                                                                                                     |

## latch free

The process waits for a latch that is currently busy (held by another process).

**Wait Time:** The wait time increases exponentially and does not include spinning on the latch (active waiting). The maximum wait time also depends on the number of latches that the process is holding. There is an incremental wait of up to 2 seconds.

| Parameter      | Description                                                                                                                                                                                         |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>address</i> | The address of the latch for which the process is waiting                                                                                                                                           |
| <i>number</i>  | <p>The latch number that indexes in the V\$LATCHNAME view. To find more information on the latch, use the following SQL statement:</p> <pre>select * from v\$latchname where latch# = number;</pre> |

| Parameter    | Description                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------------------|
| <i>tries</i> | A count of the number of times the process tried to get the latch (slow with spinning) and the process has to sleep |

## library cache load lock

The session tries to find the load lock for the database object so that it can load the object. The load lock is always obtained in Exclusive mode, so that no other process can load the same object. If the load lock is busy the session will wait on this event until the lock becomes available.

**Wait Time:** 3 seconds (1 second for PMON)

| Parameter             | Description                                                       |
|-----------------------|-------------------------------------------------------------------|
| <i>object address</i> | Address of the object being loaded                                |
| <i>lock address</i>   | Address of load lock being used                                   |
| <i>mask</i>           | Indicates which data pieces of the object that needs to be loaded |

## library cache lock

This event controls the concurrency between clients of the library cache. It acquires a lock on the object handle so that either:

- One client can prevent other clients from accessing the same object
- The client can maintain a dependency for a long time (for example, no other client can change the object)

This lock is also obtained to locate an object in the library cache.

**Wait Time:** 3 seconds (1 second for PMON)

| Parameter             | Description                                                                                                     |
|-----------------------|-----------------------------------------------------------------------------------------------------------------|
| <i>handle address</i> | Address of the object being loaded                                                                              |
| <i>lock address</i>   | Address of the load lock being used. This is not the same thing as a latch or an enqueue, it is a State Object. |
| <i>mode</i>           | Indicates the data pieces of the object which need to be loaded                                                 |
| <i>namespace</i>      | See " <a href="#">namespace</a> " on page C-4                                                                   |

## library cache pin

This event manages library cache concurrency. Pinning an object causes the heaps to be loaded into memory. If a client wants to modify or examine the object, the client must acquire a pin after the lock.

**Wait Time:** 3 seconds (1 second for PMON)

| Parameter             | Description                                                                                                               |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| <i>handle address</i> | Address of the object being loaded                                                                                        |
| <i>pin address</i>    | Address of the load lock being used. This is not the same thing as a latch or an enqueue, it is basically a State Object. |
| <i>mode</i>           | Indicates which data pieces of the object that needs to be loaded                                                         |



| Parameter        | Description                                   |
|------------------|-----------------------------------------------|
| <i>namespace</i> | See " <a href="#">namespace</a> " on page C-4 |

## library cache shutdown

The process shutting down the instance waits for sessions to complete before proceeding with library cache shutdown.

## LMON global data update

The rolling migration operation is waiting for a response from LMON to acknowledge the global data was updated.

**Wait Time:** The time it takes for LMON to publish/retrieve the global data associated with a

**Parameters:** None

## lock manager wait for remote message

The lock manager waits for a message from a remote lock manager in the same configuration.

**Wait Time:** The elapsed time of the wait

| Parameter       | Description                         |
|-----------------|-------------------------------------|
| <i>waittime</i> | The elapsed time of the actual wait |

## Log archive I/O

Used local archiving of online redo logs (for a production database) or standby redo logs (for a standby database). When the archiving process exhausts its I/O buffers because all of them are being used for on-going I/O's, the wait for an available I/O buffer is captured in this system wait event.

**Wait Time:** Depends on the speed of the disks

**Parameters:** None

## log buffer space

Waiting for space in the log buffer because the session is writing data into the log buffer faster than LGWR can write it out. Consider making the log buffer bigger if it is small, or moving the log files to faster disks such as striped disks.

**Wait Time:** Usually 1 second, but 5 seconds if it is waiting for a Switch Logfile to complete

**Parameters:** None

## log file parallel write

Writing redo records to the redo log files from the log buffer.

**Wait Time:** Time it takes for the I/Os to complete. Even though redo records are written in parallel, the parallel write is not complete until the last I/O is on disk.

| Parameter       | Description                    |
|-----------------|--------------------------------|
| <i>files</i>    | Number of files to be written  |
| <i>blocks</i>   | Number of blocks to be written |
| <i>requests</i> | Number of I/O requests         |

## log file sequential read

Waiting for the read from this logfile to return. This is used to read redo records from the log file.

**Wait Time:** Time it takes to complete the physical I/O (read)

| Parameter     | Description                                                                                           |
|---------------|-------------------------------------------------------------------------------------------------------|
| <i>log#</i>   | The relative sequence number of the logfiles within a log group (used only when dumping the logfiles) |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2                                                            |
| <i>blocks</i> | The number of blocks to read                                                                          |

## log file single write

Waiting for the write to this logfile to complete. This event is used while updating the header of the logfile. It is signaled when adding a log file member and when incrementing sequence numbers.

**Wait Time:** Time it takes for the physical I/O (write) to complete

| Parameter     | Description                                                                   |
|---------------|-------------------------------------------------------------------------------|
| <i>log#</i>   | This is the number of the group/log to which the session is currently writing |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2                                    |
| <i>blocks</i> | The number of blocks to write                                                 |

## log file switch (archiving needed)

Waiting for a log switch because the log that the LGWR will be switching into has not been archived yet. Check the alert file to make sure that archiving has not stopped due to a failed archive write. To speed archiving, consider adding more archive processes or putting the archive files on striped disks.

**Wait Time:** 1 second

**Parameters:** None

## log file switch (checkpoint incomplete)

Waiting for a log switch because the session cannot wrap into the next log. Wrapping cannot be performed because the checkpoint for that log has not completed.

**Wait Time:** 1 second

**Parameters:** None

## log file switch (clearing log file)

Waiting for a log switch because the log is being cleared due to a `CLEAR LOGFILE` command or implicit clear logfile executed by recovery.

**Wait Time:** 1 second

**Parameters:** None

## log file switch (private strand flush incomplete)

User sessions trying to generate redo, wait on this event when LGWR waits for DBWR to complete flushing redo from IMU buffers into the log buffer; when DBWR is complete LGWR can then finish writing the current log, and then switch log files.

**Wait Time:** 1 second

**Parameters:** None

## log file switch completion

Waiting for a log switch to complete.

**Wait Time:** 1 second

**Parameters:** None

## log file sync

When a user session commits, the session's redo information needs to be flushed to the redo logfile. The user session will post the LGWR to write the log buffer to the redo log file. When the LGWR has finished writing, it will post the user session.

**Wait Time:** The wait time includes the writing of the log buffer and the post.

| Parameter      | Description                                                                            |
|----------------|----------------------------------------------------------------------------------------|
| <i>buffer#</i> | The number of the physical buffer in the redo log buffer that needs to be synchronized |

## log switch/archive

Used as part of the `ALTER SYSTEM ARCHIVE LOG CHANGE scn` statement. The session waits for the current log from all open threads to be archived.

**Wait Time:** Wait for up to 10 seconds

| Parameter      | Description                                                                 |
|----------------|-----------------------------------------------------------------------------|
| <i>thread#</i> | The thread number of the thread that is currently archiving its current log |

## optimizer stats update retry

When concurrent sessions try to update optimizer statistics for the same object, all of them except the one that successfully acquired all necessary locks/pins on the library/row cache entries, wait on this wait event and then retry locking after a short period of time. In addition to explicit statistics gathering and maintenance operations using the DBMS\_STATS package, Oracle database itself may try to update statistics for some objects, either on behalf of the user or for its own maintenance purposes.

**Wait Time:** 10 ms

**Parameters:** None

### **parallel recovery change buffer free**

The parallel recovery coordinator is waiting for a change mapping buffer to be released by one of the recovery slaves.

**Wait Time:** 100ms

**Parameters:** None

### **parallel recovery control message reply**

The parallel recovery coordinator is waiting for all recovery slaves to respond to a synchronous control message.

**Wait Time:** 100ms

**Parameters:** None

### **parallel recovery coord send blocked**

The parallel recovery coordinator is unable to send a redo change message because the recovery slave is still actively applying redo that it has already received and has not yet released the channel.

**Wait Time:** 100ms

**Parameters:** None

### **parallel recovery coord wait for reply**

The parallel recovery coordinator is waiting for all recovery slaves to exit.

**Wait Time:** 100ms

**Parameters:** None

### **parallel recovery coordinator waits for slave cleanup**

The parallel recovery coordinator is waiting for all recovery slaves to exit gracefully.

**Wait Time:** 10ms

**Parameters:** None

### **parallel recovery read buffer free**

The parallel recovery coordinator is waiting for a log read buffer to be released by all recovery slaves. Only after every recovery slave finishes applying redo from a log read buffer, can the buffer be used by the coordinator to issue the next log read.

**Wait Time:** 100ms

**Parameters:** None

### **parallel recovery slave next change**

A parallel recovery slave is idle and waiting for the next change message from the coordinator.

**Wait Time:** 100ms

**Parameters:** None

## pending global transaction(s)

This event should happen only during testing. The session waits for pending transactions to clear.

**Wait Time:** 30 seconds

| Parameter    | Description                                                       |
|--------------|-------------------------------------------------------------------|
| <i>scans</i> | Number of times the session has scanned the PENDING_TRANS\$ table |

## pipe get

The session waits for a message to be received on the pipe or for the pipe timer to expire.

**Wait Time:** There is a 5 second wake up (check) and the pipe timer set by the user

| Parameter             | Description                                   |
|-----------------------|-----------------------------------------------|
| <i>handle address</i> | The library cache object handle for this pipe |
| <i>buffer length</i>  | The length of the buffer                      |
| <i>timeout</i>        | The pipe timer set by the user                |

## pipe put

The session waits for the pipe send timer to expire or for space to be made available in the pipe.

**Wait Time:** There is the 5 second wakeup (check) and the user-supplied timeout value

| Parameter             | Description                                                        |
|-----------------------|--------------------------------------------------------------------|
| <i>handle address</i> | The library cache object handle for this pipe                      |
| <i>record length</i>  | The length of the record or buffer that has been put into the pipe |
| <i>timeout</i>        | The pipe timer set by the user                                     |

## PL/SQL lock timer

This event is called through the DBMS\_LOCK.SLEEP procedure. This event will most likely originate from procedures written by a user.

**Wait Time:** The wait time is in hundredths of seconds and is dependent on the user context

| Parameter       | Description                                                           |
|-----------------|-----------------------------------------------------------------------|
| <i>duration</i> | The duration that the user specified in the DBMS_LOCK.SLEEP procedure |

## pmon timer

This is the main wait event for PMON. When PMON is idle, it is waiting on this event.

**Wait Time:** Up to 3 seconds, if not posted before

| Parameter       | Description                                                |
|-----------------|------------------------------------------------------------|
| <i>duration</i> | The actual amount of time that the PMON is trying to sleep |

## prewarm transfer retry

Release a hash latch, then wait under this event before attempting to re-acquire the hash latch.

**Wait Time:** 10ms

**Parameters:** None

## prior process spawner to be cleaned up

When a prior process has died while spawning a background, the current process which is trying to spawn new a background must wait until the prior process state is cleaned up.

**Wait Time:** Usually 3 - 10 seconds

| Parameter          | Description                                                                                                       |
|--------------------|-------------------------------------------------------------------------------------------------------------------|
| <i>process_pid</i> | process identifier (see <code>V\$PROCESS . PID</code> ) of the process whose state needs to be cleaned up.        |
| <i>process_sno</i> | process serial number (see <code>V\$PROCESS . SERIAL#</code> ) of the process whose state needs to be cleaned up. |

## process startup

Wait for a shared server, Dispatcher, or other background process to start.

**Wait Time:** Wait up to 1 second for a background process to start. If timed out, then re-wait until 5 minutes have passed and signal an error. If the process has started, the event will acknowledge this.

| Parameter       | Description                                     |
|-----------------|-------------------------------------------------|
| <i>type</i>     | The process type that was started               |
| <i>process#</i> | The process number of the process being started |
| <i>waited</i>   | Cumulative time waited for the process to start |

## PX Deque wait

The process is waiting for a message during a parallel execute.

**Wait Time:** The wait time depends on how quickly the message arrives. Wait times can vary, but it will normally be a short period of time.

| Parameter        | Description                                          |
|------------------|------------------------------------------------------|
| <i>reason</i>    | The reason for dequeuing                             |
| <i>sleeptime</i> | The amount of time that the session slept            |
| <i>loop</i>      | The total number of times that the session has slept |

## PX qref latch

Each parallel execution process has a parallel execution qref latch, which needs to be acquired before the queue buffers can be manipulated.

**Wait Time:** Wait up to 1 second

| Parameter        | Description                                                           |
|------------------|-----------------------------------------------------------------------|
| <i>function</i>  | Indicates the type of wait that the session is doing                  |
| <i>sleeptime</i> | The amount of time that the session waits (in hundredths of a second) |
| <i>qref</i>      | The address of the process queue for which the session is waits       |

## PX server shutdown

During normal or immediate shutdown the parallel execution slaves are posted to shutdown cleanly. If any parallel execution slaves are still alive after 10 seconds, they are killed.

**Wait Time:** Wait up to 0.5 seconds

| Parameter        | Description                                                         |
|------------------|---------------------------------------------------------------------|
| <i>nalive</i>    | The number of parallel execution slaves that are still running      |
| <i>sleeptime</i> | The total sleeptime since the session started to wait on this event |
| <i>loop</i>      | The number of times the session waited for this event               |

## PX signal server

This event occurs only in Exclusive mode. The query coordinator is signalling the Query Slaves that an error has occurred.

**Wait Time:** 0.5 seconds

| Parameter     | Description                                       |
|---------------|---------------------------------------------------|
| <i>serial</i> | The serial number of the slave process queue      |
| <i>error</i>  | The error that has occurred                       |
| <i>nbusy</i>  | The number of slave processes that are still busy |

## rdbms ipc message

The background processes (LGWR, DBWR, LMS0) use this event to indicate that they are idle and are waiting for the foreground processes to send them an IPC message to do some work.

**Wait Time:** Up to 3 seconds. The parameter *timeout* shows the true sleep time.

| Parameter      | Description                                                  |
|----------------|--------------------------------------------------------------|
| <i>timeout</i> | The amount of time that the session waits for an IPC message |

## rdbms ipc message block

This event indicates that all message blocks are in use and that the session had to wait for a message block to become available.

**Wait Time:** Wait up to 60 seconds

**Parameters:** None

## rdbms ipc reply

This event is used to wait for a reply from one of the background processes.

**Wait Time:** The wait time is specified by the user and is indicated by the parameter *timeout*.

| Parameter           | Description                                                                                                             |
|---------------------|-------------------------------------------------------------------------------------------------------------------------|
| <i>from_process</i> | The background process for which the session is waiting. The wait is for a reply to an IPC message sent by the session. |
| <i>timeout</i>      | The amount of time in seconds that this process will wait for a reply                                                   |

## read by other session

This event occurs when a session requests a buffer that is currently being read into the buffer cache by another session. Prior to release 10.1, waits for this event were grouped with the other reasons for waiting for buffers under the 'buffer busy wait' event

**Wait Time:** Time waited for the buffer to be read by the other session (in microseconds)

| Parameter     | Description                                |
|---------------|--------------------------------------------|
| <i>file#</i>  | See " <a href="#">file#</a> " on page C-3  |
| <i>block#</i> | See " <a href="#">block#</a> " on page C-2 |
| <i>class#</i> | See " <a href="#">class</a> " on page C-3  |

## recovery read

A parallel recovery slave (or serial recovery process) is waiting for a batch of data block reads to complete.

**Wait Time:** Time it takes to complete the physical I/O (read)

**Parameters:** None

## resmgr:become active

The session is waiting for a resource manager active session slot. This event occurs when the resource manager is enabled and the number of active sessions in the session's current consumer group exceeds the current resource plan's active session limit for the consumer group. To reduce the occurrence of this wait event, increase the active session limit for the session's current consumer group.

**Wait Time:** The time the session waited to be allocated an active session slot

| Parameter       | Description          |
|-----------------|----------------------|
| <i>location</i> | location of the wait |



## resmgr:cpu quantum

The session is waiting to be allocated a quantum of cpu. This event occurs when the resource manager is enabled and is throttling CPU consumption. To reduce the occurrence of this wait event, increase the CPU allocation for the sessions's current consumer group.

Wait Time: The time the session waited to acquire a CPU quantum

| Parameter       | Description          |
|-----------------|----------------------|
| <i>location</i> | Location of the wait |

## resmgr:pq queued

The session is waiting in the parallel statement queue.

Wait Time: The time the session waited for sufficient parallel query processes to become available to run this session with the requested degree of parallelism

| Parameter       | Description          |
|-----------------|----------------------|
| <i>location</i> | Location of the wait |

---

**Note:** The `resmgr:pq queued` wait event is available starting with Oracle Database 11g Release 2 (11.2.0.2).

---

## rolling migration: cluster quiesce

This is the wait event that instances wait on when cluster is about to start a rolling migration. The instances are waiting for any privileged operations that blocks rolling migration to complete before allowing rolling migration.

Wait Time: 1 second

| Parameter       | Description                                                                                                                                                                                                                                       |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>location</i> | Its value will be 1 if the wait is for completion of the privileged operations so that a rolling upgrade/downgrade can start. Its value will be 2 if the wait is for completion of the rolling upgrade/downgrade on all the nodes in the cluster. |
| <i>waits</i>    | The number of seconds spent waiting at the current location.                                                                                                                                                                                      |

## row cache lock

The session is trying to get a data dictionary lock.

**Wait Time:** Wait up to 60 seconds.

| Parameter       | Description                                                               |
|-----------------|---------------------------------------------------------------------------|
| <i>cache id</i> | The <code>CACHE#</code> column value in the <code>V\$ROWCACHE</code> view |
| <i>mode</i>     | See <a href="#">"mode"</a> on page C-3                                    |
| <i>request</i>  | The pipe timer set by the user                                            |

## RVWR wait for flashback copy

Waits for a process to copy flashback database data into the flashback buffer, in order to write out the requested flashback data.

**Wait Time:** 10 milliseconds

| Parameter           | Description                                           |
|---------------------|-------------------------------------------------------|
| <i>copy latch #</i> | The number of flashback copy latch RVWR is waiting on |

## sbtbufinfo

This function is called when Oracle needs to discover the size, and number, of I/O buffers that have been allocated by the SBT layer. It should be very fast and never block.

**Wait Time:** Less than one millisecond

**Parameters:** None

## sbtgetbuf

This function obtains one I/O buffer that Oracle will use for I/O during a backup job.

**Wait Time:** Less than one millisecond

**Parameters:** None

## sbtmapbuf

This is an internal function used to facilitate multi-process buffer management. It should be very fast and never block.

**Wait Time:** Less than one millisecond

**Parameters:** None

## sbtrelbuf

This function releases an I/O buffer that has been already processed during a restore job, so that the SBT layer can fill it with more data. It should be very fast and never block.

**Wait Time:** Less than one millisecond

**Parameters:** None

## scginq AST call

Called by the session to find the highest lock mode that is held on a resource.

**Wait Time:** Wait up to 0.2 seconds, but the wait will continue until the NULL mode Acquisition AST has fired.

**Parameters:** None

## SGA: allocation forcing component growth

Process waiting on an immediate mode memory transfer with auto-tune SGA after a 4031 for MMAN to get the memory and post it.

**Wait Time:** 10 msec

**Parameters:** None

### SGA: MMAN sleep for component shrink

MMAN to wait and post itself for satisfying an auto-tuned memory request while trying to fully free a component's quiesced granules. In Release 10.1, the name of this event was 'wait for SGA component shrink'.

**Wait Time:** 10 msec

| Parameter | Description                                     |
|-----------|-------------------------------------------------|
| <i>P1</i> | component_id (corresponding to the memory pool) |
| <i>P2</i> | Current size in granules                        |
| <i>P3</i> | Target size in granules                         |

### SGA: sga\_target resize

Memory resize requests wait while sga target is being resized. In Release 10.1, the name of this event was 'wait for sga\_target resize'.

**Wait Time:** 10 msec

**Parameters:** None

### Shared IO Pool Memory

Wait until a shared I/O pool buffer becomes available. This happens when processes are using these buffers for I/O and the current process needs to wait for the release of any one of the buffers to the shared I/O pool.

**Wait Time:** 10msec

**Parameters:** None

### single-task message

When running single task, this event indicates that the session waits for the client side of the executable.

**Wait Time:** Total elapsed time that this session spent in the user application

**Parameters:** None

### shared server idle wait

Idle wait event for a shared server. The server waits on the common queue for a virtual circuit. (See also "[virtual circuit wait](#)" on page C-38.)

**Wait Time:** 30 seconds

**Parameters:** None

### smon timer

This is the main idle event for SMON. SMON will be waiting on this event most of the time until it times out or is posted by another process.

**Wait Time:** 5 minutes (300 seconds)

| Parameter        | Description                                                         |
|------------------|---------------------------------------------------------------------|
| <i>sleeptime</i> | The amount of time that SMON tries to wait on this event in seconds |
| <i>failed</i>    | The number of times SMON was posted when there some kind of error   |

### SQL\*Net break/reset to client

The server sends a break or reset message to the client. The session running on the server waits for a reply from the client.

**Wait Time:** The actual time it takes for the break or reset message to return from the client

| Parameter        | Description                                   |
|------------------|-----------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3 |
| <i>break?</i>    | See " <a href="#">break?</a> " on page C-3    |

### SQL\*Net break/reset to dblink

Same as **SQL\*Net break/reset to client**, but in this case, the break/reset message is sent to another server process over a database link.

**Wait Time:** The actual time it takes for the break or reset message to return from the other server process

| Parameter        | Description                                   |
|------------------|-----------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3 |
| <i>break?</i>    | See " <a href="#">break?</a> " on page C-3    |

### SQL\*Net message from client

The server process (foreground process) waits for a message from the client process to arrive.

**Wait Time:** The time it took for a message to arrive from the client since the last message was sent to the client

| Parameter        | Description                                                                      |
|------------------|----------------------------------------------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3                                    |
| <i>#bytes</i>    | The number of bytes received by the server (foreground process) from the client. |

### SQL\*Net message from dblink

The session waits while the server process (foreground process) receives messages over a database link from another server process.

**Wait Time:** The time it took for a message to arrive from another server (foreground process) since a message was sent to the other foreground process.

| Parameter        | Description                                   |
|------------------|-----------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3 |

| Parameter     | Description                                                                                                           |
|---------------|-----------------------------------------------------------------------------------------------------------------------|
| <i>#bytes</i> | The number of bytes received by the server (foreground process) from another foreground process over a database link. |

### SQL\*Net message to client

The server (foreground process) is sending a message to the client.

**Wait Time:** The actual time the **send** takes

| Parameter        | Description                                                  |
|------------------|--------------------------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3                |
| <i>#bytes</i>    | The number of bytes sent by the server process to the client |

### SQL\*Net message to dblink

The server process (foreground process) is sending a message over a database link to another server process.

**Wait Time:** The actual time the **send** takes

| Parameter        | Description                                                                                   |
|------------------|-----------------------------------------------------------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3                                                 |
| <i>#bytes</i>    | The number of bytes sent by the server process to another server process over a database link |

### SQL\*Net more data from client

The server is waiting on the client to send more data to its client shadow process, in an already initiated operation.

**Wait Time:** The time waited depends on the time it took to receive the data (including the waiting time)

| Parameter        | Description                                   |
|------------------|-----------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3 |
| <i>#bytes</i>    | The number of bytes received from the client  |

### SQL\*Net more data from dblink

The foreground process is expecting more data from a data base link.

**Wait Time:** The total time it takes to read the data from the database link (including the waiting time for the data to arrive)

| Parameter        | Description                                   |
|------------------|-----------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3 |
| <i>#bytes</i>    | The number of bytes received                  |

## SQL\*Net more data to client

The server process is sending more data/messages to the client. The previous operation to the client was also a **send**.

**Wait Time:** The actual time it took for the **send** to complete

| Parameter        | Description                                           |
|------------------|-------------------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3         |
| <i>#bytes</i>    | The number of bytes that are being sent to the client |

## SQL\*Net more data to dblink

The event indicates that the server is sending data over a database link again. The previous operation over this database link was also a **send**.

**Wait Time:** The actual time it takes to send the data to the other server

| Parameter        | Description                                                                          |
|------------------|--------------------------------------------------------------------------------------|
| <i>driver id</i> | See " <a href="#">driver id</a> " on page C-3                                        |
| <i>#bytes</i>    | The number of bytes that are sent over the database link to the other server process |

## Streams AQ: waiting for messages in the queue

The session is waiting on an empty OLTP queue (Advanced Queuing) for a message to arrive so that the session can dequeue that message.

**Wait Time:** The amount of time that the session wants to wait is determined by the parameter *wait time*

| Parameter        | Description                                                  |
|------------------|--------------------------------------------------------------|
| <i>queue id</i>  | The ID of the OLTP queue for which this session is waiting   |
| <i>process#</i>  | The process number of the process in which this session runs |
| <i>wait time</i> | The intended wait time for this session                      |

## switch logfile command

The session waits on the user command `SWITCH LOGFILE` to complete.

**Wait Time:** 5 seconds

**Parameters:** None

## TCP Socket (KGAS)

A session is waiting for an external host to provide requested data over a network socket. The time that this wait event tracks does not indicate a problem, and even a long wait time is not a reason to contact Oracle Support. It naturally takes time for data to flow between hosts over a network, and for the remote aspect of an application to process any request made to it. An application that communicates with a remote host must wait until the data it will read has arrived. In addition, on Microsoft Windows, a separate thread monitors the arrival of traffic. This thread spends most of its life in waits tracked by the TCP Socket (KGAS) wait event.

**Wait Time:** The total elapsed time for the network connection to be established or for data to arrive from over the network

| Parameter | Description                                                                                                                                                    |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>P0</i> | For Oracle internal use only. Values 8, 9, and 10 occur within the special thread present on Microsoft Windows; other P0 values occur in normal user sessions. |
| <i>P1</i> | For Oracle internal use only                                                                                                                                   |

## timer in sksawat

The session waits for the Archiver (ARCH) asynchronous I/O to complete.

**Wait Time:** 0.01 seconds

**Parameters:** None

## transaction

Wait for a blocking transaction to be rolled back. Continue waiting until the transaction has been rolled back.

**Wait Time:** 1 second

| Parameter        | Description                                                         |
|------------------|---------------------------------------------------------------------|
| <i>undo seg#</i> | The rollback segment ID                                             |
| <i>slot#</i>     | The slot ID inside the rollback segment                             |
| <i>wrap#</i>     | The sequence number that is incremented for each transaction        |
| <i>count</i>     | The number of times that the session has waited on this transaction |

## unbound tx

The session waits to see if there are any transactions that have been started but do not have a Rollback Segment associated with them.

**Wait Time:** 1 second

**Parameters:** None

## undo\_retention publish retry

This wait can occur for two reasons. A session issuing an ALTER SYSTEM SET UNDO\_RETENTION may wait on this event wait while a cluster reconfiguration takes place. Or the background process MMNL may wait for cluster reconfiguration while attempting to determine the max UNDO\_RETENTION.

**Wait time:** 1 second

| Parameter | Description                                                                                                                                                                          |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>P1</i> | Identifies where the retry is happening. Id = 1 retry while publishing into the max undo_retention namespace. Id = 2 retry while iterator accessing the max undo_retention namespace |
| <i>P2</i> | Retry count (maximum number of retries is 5)                                                                                                                                         |

## undo segment extension

The undo segment is being extended or shrunk. The session must wait until the operation on the undo segment has finished.

**Wait Time:** 0.01 seconds

| Parameter       | Description                                                     |
|-----------------|-----------------------------------------------------------------|
| <i>segment#</i> | The ID of the rollback segment that is being extended or shrunk |

## undo segment recovery

PMON is rolling back a dead transaction. The wait continues until rollback finishes.

**Wait Time:** 3 seconds

| Parameter       | Description                                                                            |
|-----------------|----------------------------------------------------------------------------------------|
| <i>segment#</i> | The ID of the rollback segment that contains the transaction that is being rolled back |
| <i>tx flags</i> | The transaction flags (options) set for the transaction that is being rolled back      |

## undo segment tx slot

Wait for a transaction slot to become available within the selected rollback segment. Continue waiting until the slot is available.

**Wait Time:** 1 second

| Parameter       | Description                                                                            |
|-----------------|----------------------------------------------------------------------------------------|
| <i>segment#</i> | The ID of the rollback segment that contains the transaction that is being rolled back |

## virtual circuit status

The session waits for a virtual circuit to return a message type indicated by status.

**Wait Time:** 30 seconds

| Parameter       | Description                                    |
|-----------------|------------------------------------------------|
| <i>circuit#</i> | Indicates the virtual circuit# being waited on |
| <i>status</i>   | Indicates what the session is waiting for      |

---

**Note:** The virtual circuit status wait event has been deprecated. It is replaced by the virtual circuit wait event.

---

## virtual circuit wait

The session waits for a virtual circuit operation to complete.

**Wait Time:** 30 seconds



| Parameter       | Description                                                |
|-----------------|------------------------------------------------------------|
| <i>circuit#</i> | Indicates the virtual circuit# being waited on             |
| <i>type</i>     | Indicates the type of operation the session is waiting for |

### WCR: replay client notify

During replay, the Workload Replay Client always keeps an open connection to the database to detect some special errors. This session will normally be in the wait state until some specific replay-related exception occurs.

**Wait Time:** Waits until notified. Times out every 30 seconds.

| Parameter       | Description                                                                                                                                                                              |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>who am I</i> | Identifies the reason for wait for the admin thread.<br>1 - waiting for REPLAY.START() to be issued.<br>2 - waiting for the replay to run to completion or REPLAY.CANCEL() to be issued. |

### WCR: replay clock

A session will wait on this event during replay if it has some logical dependencies on another session that has not yet committed its work.

**Wait Time:** Depends upon the amount of row lock contention in the original capture

| Parameter                        | Description                                                          |
|----------------------------------|----------------------------------------------------------------------|
| <i>wait for scn's hi 4 bytes</i> | High 4 bytes of the 8-byte replay SCN that the session is waiting on |
| <i>wait for scn's lo 4 bytes</i> | Low 4 bytes of the 8-byte replay SCN that the session is waiting on  |

### WCR: replay lock order

A session will wait on this event during replay if it saw some lock contention during capture.

**Wait Time:** Depends upon the amount of row lock contention in the original capture

| Parameter                        | Description                                                          |
|----------------------------------|----------------------------------------------------------------------|
| <i>wait for scn's hi 4 bytes</i> | High 4 bytes of the 8-byte replay SCN that the session is waiting on |
| <i>wait for scn's lo 4 bytes</i> | Low 4 bytes of the 8-byte replay SCN that the session is waiting on  |

### WCR: replay paused

When the user issues a DBMS\_WORKLOAD\_REPLAY.PAUSE\_REPLAY command, all the replayed sessions are waiting on this wait event until replay is resumed.

**Parameters:** None

### WCR: Sync context busy

In the default replay mode, commits during replay are synchronized to follow the same order as capture. All commits are serialized using the Sync context. A replayed session will wait on this event if it is trying to commit at the same time as another replayed session.

**Parameters:** None

## WMON goes to sleep

WMON is the UNIX-specific Wait Monitor, that can be used to reduce the number of system calls related to setting timers for posting or waiting in Oracle. You need to set an initialization parameter that enables the WMON process.

**Wait Time:** Depends on the next timeout

**Parameters:** None

## write complete waits

The session waits for a buffer to be written. The write is caused by normal aging or by a cross-instance call.

**Wait Time:** 1 second

| Parameter     | Description                                                                       |
|---------------|-----------------------------------------------------------------------------------|
| <i>file#</i>  | The rollback segment id that contains the transaction that is being rolled back   |
| <i>block#</i> | The transaction flags (options) set for the transaction that is being rolled back |
| <i>id</i>     | Identifies the reason for waiting                                                 |

## writes stopped by instance recovery or database suspension

The session is blocked until the instance that started Instance Recovery is finished.

**Wait Time:** 5 seconds

| Parameter         | Description                                                                     |
|-------------------|---------------------------------------------------------------------------------|
| <i>bythread#</i>  | The rollback segment id that contains the transaction that is being rolled back |
| <i>ourthread#</i> | The current instance thread number                                              |

---

## Oracle Enqueue Names

This appendix lists Oracle enqueues. **Enqueues** are shared memory structures (locks) that serialize access to database resources. They can be associated with a session or transaction. Enqueue names are displayed in the `LOCK_TYPE` column of the `DBA_LOCK` and `DBA_LOCK_INTERNAL` data dictionary views.

A **resource** uniquely identifies an object that can be locked by different sessions within an instance (local resource) or between instances (global resource). Each session that tries to lock the resource will have an **enqueue** on the resource.

---

**Note:** The names of enqueues and their definitions may change from release to release.

---

**See Also:** ["DBA\\_LOCK\\_INTERNAL"](#) on page 5-50 and ["DBA\\_LOCK"](#) on page 5-50

The Oracle enqueues are:

- BL, Buffer Cache Management
- BR, Backup/Restore
- CF, Controlfile Transaction
- CI, Cross-instance Call Invocation
- CU, Bind Enqueue
- DF, Datafile
- DL, Direct Loader Index Creation
- DM, Database Mount
- DR, Distributed Recovery Process
- DW, SecureFiles
- DX, Distributed Transaction
- FP, File Object
- FS, File Set
- HW, High-Water Lock
- IN, Instance Number
- IR, Instance Recovery

- 
- IS, Instance State
  - IV, Library Cache Invalidation
  - JI, Enqueue used during AJV snapshot refresh
  - JQ, Job Queue
  - KK, Redo Log "Kick"
  - KP, contention in Oracle Data Pump startup and shutdown processes
  - KO, Multiple Object Checkpoint
  - L[A-P], Library Cache Lock
  - LS, Log Start or Switch
  - MM, Mount Definition
  - MR, Media Recovery
  - N[A-Z], Library Cache Pin
  - PE, ALTER SYSTEM SET PARAMETER = VALUE
  - PF, Password File
  - PI, Parallel Slaves
  - PR, Process Startup
  - PS, Parallel Slave Synchronization
  - Q[A-Z], Row Cache
  - RO, Object Reuse
  - RT, Redo Thread
  - RW, Row Wait
  - SC, System Commit Number
  - SM, SMON
  - SN, Sequence Number
  - SQ, Sequence Number Enqueue
  - SR, Synchronized Replication
  - SS, Sort Segment
  - ST, Space Management Transaction
  - SV, Sequence Number Value
  - TA, Transaction Recovery
  - TC, Thread Checkpoint
  - TE, Extend Table
  - TM, DML Enqueue
  - TO, Temporary Table Object Enqueue
  - TS, Temporary Segment (also TableSpace)
  - TT, Temporary Table
  - TX, Transaction

- 
- UL, User-defined Locks
  - UN, User Name
  - US, Undo Segment, Serialization
  - WL, Being Written Redo Log
  - XA, Instance Attribute Lock
  - XI, Instance Registration Lock



---

## Statistics Descriptions

This appendix describes the statistics stored in the V\$SESSTAT and V\$SYSSTAT dynamic performance tables. These statistics are useful in identifying and correcting performance problems.

This appendix contains the following topics:

- [Displaying Statistics](#)
- [Statistics Descriptions](#)

### Displaying Statistics

The V\$SESSTAT view displays statistics on a per-session basis and is valid only for the session currently connected. When a session disconnects, all statistics for the session are updated in V\$SYSSTAT. The values for the statistics are cleared until the next session uses them.

The V\$STATNAME view contains all of the statistics for an Oracle release.

Many of these statistics are tied to the internal implementation of Oracle and therefore are subject to change or deletion without notice, even between patch releases.

Application developers should be aware of this and write their code to tolerate missing or extra statistics.

**See Also:** ["V\\$SESSTAT"](#) on page 9-21, ["V\\$STATNAME"](#) on page 9-63, and ["V\\$SYSSTAT"](#) on page 9-77 for more information on these views

### Statistics Descriptions

This section describes the statistics stored in the V\$SESSTAT and V\$SYSSTAT views. The statistics are listed here in alphabetical order.

The CLASS column contains a number representing one or more statistics classes. The following class numbers are additive:

- 1, User
- 2, Redo
- 4, Enqueue
- 8, Cache

- 16, OS
- 32, Real Application Clusters
- 64, SQL
- 128, Debug

For example, a class value of 72 represents a statistic that relates to SQL statements and caching.

Some statistics are populated only if the `TIMED_STATISTICS` initialization parameter is set to `true`. Those statistics are flagged in the right-hand column.

**Table E-1 Database Statistics Descriptions**

| Name                                   | Class | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | TIMED_STATISTICS |
|----------------------------------------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| background checkpoints completed       | 8     | Number of checkpoints completed by the background process. This statistic is incremented when the background process successfully advances the thread checkpoint.                                                                                                                                                                                                                                                                                                                                                                                                                     |                  |
| background checkpoints started         | 8     | Number of checkpoints started by the background process. This statistic can be larger than "background checkpoints completed" if a new checkpoint overrides an incomplete checkpoint or if a checkpoint is currently under way. This statistic includes only checkpoints of the redo thread. It does not include: <ul style="list-style-type: none"> <li>■ Individual file checkpoints for operations such as offline or begin backup</li> <li>■ Foreground (user-requested) checkpoints (for example, performed by <code>ALTER SYSTEM CHECKPOINT LOCAL</code> statements)</li> </ul> |                  |
| background timeouts                    | 128   | This is a count of the times where a background process has set an alarm for itself and the alarm has timed out rather than the background process being posted by another process to do some work.                                                                                                                                                                                                                                                                                                                                                                                   |                  |
| branch node splits                     | 128   | Number of times an index branch block was split because of the insertion of an additional value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                  |
| buffer is not pinned count             | 72    | Number of times a buffer was free when visited. Useful only for internal debugging purposes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                  |
| buffer is pinned count                 | 72    | Number of times a buffer was pinned when visited. Useful only for internal debugging purposes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                  |
| bytes received via SQL*Net from client | 1     | Total number of bytes received from the client over Oracle Net Services                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                  |
| bytes received via SQL*Net from dblink | 1     | Total number of bytes received from a database link over Oracle Net Services                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                  |
| bytes sent via SQL*Net to client       | 1     | Total number of bytes sent to the client from the foreground processes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                  |
| bytes sent via SQL*Net to dblink       | 1     | Total number of bytes sent over a database link                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                  |
| Cached Commit SCN referenced           | 128   | Useful only for internal debugging purposes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                  |
| calls to get snapshot scn: kcmgss      | 32    | Number of times a snapshot system change number (SCN) was allocated. The SCN is allocated at the start of a transaction.                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                  |



**Table E-1 (Cont.) Database Statistics Descriptions**

| Name                                             | Class | Description                                                                                                                                                                                                                                                                                                | TIMED_<br>STATISTICS |
|--------------------------------------------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| calls to kcmgas                                  | 128   | Number of calls to routine kcmgas to get a new SCN                                                                                                                                                                                                                                                         |                      |
| calls to kcmgcs                                  | 128   | Number of calls to routine kcmgcs to get a current SCN                                                                                                                                                                                                                                                     |                      |
| calls to kcmgrs                                  | 128   | Number of calls to routine kcmgrs to get a recent SCN                                                                                                                                                                                                                                                      |                      |
| change write time                                | 8     | Elapsed redo write time for changes made to CURRENT blocks in 10s of milliseconds.                                                                                                                                                                                                                         | 3                    |
| cleanouts and rollbacks - consistent read gets   | 128   | Number of consistent gets that require both block rollbacks and block cleanouts.<br><br><b>See Also:</b> <a href="#">"consistent gets"</a>                                                                                                                                                                 |                      |
| cleanouts only - consistent read gets            | 128   | Number of consistent gets that require only block cleanouts, no rollbacks.<br><br><b>See Also:</b> <a href="#">"consistent gets"</a>                                                                                                                                                                       |                      |
| cluster key scan block gets                      | 64    | Number of blocks obtained in a cluster scan                                                                                                                                                                                                                                                                |                      |
| cluster key scans                                | 64    | Number of cluster scans that were started                                                                                                                                                                                                                                                                  |                      |
| cold recycle reads                               | 8     | Number of buffers that were read through the least recently used end of the recycle cache with fast aging strategy                                                                                                                                                                                         |                      |
| commit cleanout failures: block lost             | 8     | Number of times Oracle attempted a cleanout at commit but could not find the correct block due to forced write, replacement, or switch CURRENT                                                                                                                                                             |                      |
| commit cleanout failures: buffer being written   | 8     | Number of times Oracle attempted a cleanout at commit, but the buffer was currently being written                                                                                                                                                                                                          |                      |
| commit cleanout failures: callback failure       | 8     | Number of times the cleanout callback function returns FALSE                                                                                                                                                                                                                                               |                      |
| commit cleanout failures: cannot pin             | 8     | Total number of times a commit cleanout was performed but failed because the block could not be pinned                                                                                                                                                                                                     |                      |
| commit cleanout failures: hot backup in progress | 8     | Number of times Oracle attempted block cleanout at commit during hot backup. The image of the block needs to be logged before the buffer can be made dirty.                                                                                                                                                |                      |
| commit cleanout failures: write disabled         | 8     | Number of times a cleanout block at commit was performed but the writes to the database had been temporarily disabled                                                                                                                                                                                      |                      |
| commit cleanouts                                 | 8     | Total number of times the cleanout block at commit function was performed                                                                                                                                                                                                                                  |                      |
| commit cleanouts successfully completed          | 8     | Number of times the cleanout block at commit function completed successfully                                                                                                                                                                                                                               |                      |
| Commit SCN cached                                | 128   | Number of times the system change number of a commit operation was cached                                                                                                                                                                                                                                  |                      |
| consistent changes                               | 8     | Number of times a user process has applied rollback entries to perform a consistent read on the block<br><br>Work loads that produce a great deal of consistent changes can consume a great deal of resources. The value of this statistic should be small in relation to the "consistent gets" statistic. |                      |

**Table E–1 (Cont.) Database Statistics Descriptions**

| Name                                                | Class | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | TIMED_STATISTICS |
|-----------------------------------------------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| consistent gets                                     | 8     | Number of times a consistent read was requested for a block.<br><br><b>See Also:</b> " <a href="#">consistent changes</a> " and " <a href="#">session logical reads</a> " statistics                                                                                                                                                                                                                                                                                                                       |                  |
| consistent gets direct                              | 8     | Number of times a consistent read was requested for a block bypassing the buffer cache (for example, direct load operation). This is a subset of "consistent gets" statistics value.                                                                                                                                                                                                                                                                                                                       |                  |
| consistent gets from cache                          | 8     | Number of times a consistent read was requested for a block from buffer cache. This is a subset of "consistent gets" statistics value.                                                                                                                                                                                                                                                                                                                                                                     |                  |
| CPU used by this session                            | 1     | Amount of CPU time (in 10s of milliseconds) used by a session from the time a user call starts until it ends. If a user call completes within 10 milliseconds, the start and end user-call time are the same for purposes of this statistics, and 0 milliseconds are added.<br><br>A similar problem can exist in the reporting by the operating system, especially on systems that suffer from many context switches.                                                                                     | 3                |
| CPU used when call started                          | 128   | The CPU time used when the call is started<br><br><b>See Also:</b> " <a href="#">CPU used by this session</a> "                                                                                                                                                                                                                                                                                                                                                                                            | 3                |
| CR blocks created                                   | 8     | Number of CURRENT blocks cloned to create CR (consistent read) blocks. The most common reason for cloning is that the buffer is held in a incompatible mode.                                                                                                                                                                                                                                                                                                                                               |                  |
| current blocks converted for CR                     | 8     | Number CURRENT blocks converted to CR state                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                  |
| cursor authentications                              | 128   | Number of privilege checks conducted during execution of an operation                                                                                                                                                                                                                                                                                                                                                                                                                                      |                  |
| data blocks consistent reads - undo records applied | 128   | Number of undo records applied to data blocks that have been rolled back for consistent read purposes                                                                                                                                                                                                                                                                                                                                                                                                      |                  |
| db block changes                                    | 8     | Closely related to " <a href="#">consistent changes</a> ", this statistic counts the total number of changes that were part of an update or delete operation that were made to all blocks in the SGA. Such changes generate redo log entries and hence become permanent changes to the database if the transaction is committed.<br><br>This approximates total database work. It statistic indicates the rate at which buffers are being dirtied (on a per-transaction or per-second basis, for example). |                  |
| db block gets                                       | 8     | Number of times a CURRENT block was requested<br><br><b>See Also:</b> " <a href="#">consistent gets</a> "                                                                                                                                                                                                                                                                                                                                                                                                  |                  |
| db block gets direct                                | 8     | Number of times a CURRENT block was requested bypassing the buffer cache (for example, a direct load operation). This is a subset of "db block gets" statistics value.                                                                                                                                                                                                                                                                                                                                     |                  |
| db block gets from cache                            | 8     | Number of times a CURRENT block was requested from the buffer cache. This is a subset of "db block gets" statistics value.                                                                                                                                                                                                                                                                                                                                                                                 |                  |

**Table E-1 (Cont.) Database Statistics Descriptions**

| Name                                           | Class | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | TIMED_STATISTICS |
|------------------------------------------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| DBWR buffers scanned                           | 8     | Total number of dirty and clean buffers Oracle looks at when scanning LRU sets for dirty buffers to clean. Divide by "DBWR lru scans" to find the average number of buffers scanned.                                                                                                                                                                                                                                                                                        |                  |
| DBWR checkpoint buffers written                | 8     | Number of buffers that were written for checkpoints                                                                                                                                                                                                                                                                                                                                                                                                                         |                  |
| DBWR checkpoints                               | 8     | Number of times the DBWR was asked to scan the cache and write all blocks marked for a checkpoint or the end of recovery. This statistic is always larger than "background checkpoints completed".                                                                                                                                                                                                                                                                          |                  |
| DBWR cross instance writes                     | 40    | Real Application Clusters only: Number of blocks written to satisfy a lock request from another instance                                                                                                                                                                                                                                                                                                                                                                    |                  |
| DBWR free buffers found                        | 8     | Number of clean buffers that DBWR found when it was requested to make free buffers. Divide by "DBWR make free requests" to find the average number of reusable buffers at the end of each LRU.                                                                                                                                                                                                                                                                              |                  |
| DBWR lru scans                                 | 8     | Number of times that DBWR scans the LRU queue looking for buffers to write. This count includes scans to fill a batch being written for another purpose (such as a checkpoint). This statistic is always greater than or equal to "DBWR make free requests".                                                                                                                                                                                                                |                  |
| DBWR make free requests                        | 8     | Number of requests to DBWR to make some free buffers for the LRU                                                                                                                                                                                                                                                                                                                                                                                                            |                  |
| DBWR revisited being-written buffer            | 8     | <p>Number of times that DBWR tried to save a buffer for writing and found that it was already in the write batch. This statistic measures the amount of "useless" work that DBWR had to do in trying to fill the batch.</p> <p>Many sources contribute to a write batch. If the same buffer from different sources is considered for adding to the write batch, then all but the first attempt will be "useless" because the buffer is already marked as being written.</p> |                  |
| DBWR summed scan depth                         | 8     | The current <b>scan depth</b> (number of buffers examined by DBWR) is added to this statistic every time DBWR scans the LRU for dirty buffers. Divide by "DBWR lru scans" to find the average scan depth.                                                                                                                                                                                                                                                                   |                  |
| DBWR transaction table writes                  | 8     | Number of rollback segment headers written by DBWR. This statistic indicates how many "hot" buffers were written, causing a user process to wait while the write completed.                                                                                                                                                                                                                                                                                                 |                  |
| DBWR undo block writes                         | 8     | Number of rollback segment blocks written by DBWR                                                                                                                                                                                                                                                                                                                                                                                                                           |                  |
| DDL statements parallelized                    | 32    | Number of DDL statements that were executed in parallel                                                                                                                                                                                                                                                                                                                                                                                                                     |                  |
| deferred (CURRENT) block cleanout applications | 128   | Number of times cleanout records are deferred, piggyback with changes, always current get                                                                                                                                                                                                                                                                                                                                                                                   |                  |
| DFO trees parallelized                         | 32    | Number of times a serial execution plan was converted to a parallel plan                                                                                                                                                                                                                                                                                                                                                                                                    |                  |
| dirty buffers inspected                        | 8     | Number of dirty buffers found by the user process while it is looking for a buffer to reuse                                                                                                                                                                                                                                                                                                                                                                                 |                  |
| DML statements parallelized                    | 32    | Number of DML statements that were executed in parallel                                                                                                                                                                                                                                                                                                                                                                                                                     |                  |

**Table E-1 (Cont.) Database Statistics Descriptions**

| Name                                     | Class | Description                                                                                                                                                                                                                                                                                                                                                                      | TIMED_STATISTICS |
|------------------------------------------|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| enqueue conversions                      | 4     | Total number of conversions of the state of table or row lock                                                                                                                                                                                                                                                                                                                    |                  |
| enqueue deadlocks                        | 4     | Total number of deadlocks between table or row locks in different sessions                                                                                                                                                                                                                                                                                                       |                  |
| enqueue releases                         | 4     | Total number of table or row locks released                                                                                                                                                                                                                                                                                                                                      |                  |
| enqueue requests                         | 4     | Total number of table or row locks acquired                                                                                                                                                                                                                                                                                                                                      |                  |
| enqueue timeouts                         | 4     | Total number of table and row locks (acquired and converted) that timed out before they could complete                                                                                                                                                                                                                                                                           |                  |
| enqueue waits                            | 4     | Total number of waits that occurred during an enqueue convert or get because the enqueue get was deferred                                                                                                                                                                                                                                                                        |                  |
| exchange deadlocks                       | 8     | Number of times that a process detected a potential deadlock when exchanging two buffers and raised an internal, restartable error. Index scans are the only operations that perform exchanges.                                                                                                                                                                                  |                  |
| execute count                            | 64    | Total number of calls (user and recursive) that executed SQL statements                                                                                                                                                                                                                                                                                                          |                  |
| flash cache eviction: aged out           | 8     | Flash cache buffer is aged out of the flash cache                                                                                                                                                                                                                                                                                                                                |                  |
| flash cache eviction: buffer pinned      | 8     | Flash cache buffer is invalidated due to object or range reuse, and so on. The flash cache buffer was in use at the time of eviction.                                                                                                                                                                                                                                            |                  |
| flash cache eviction: invalidated        | 8     | Flash cache buffer is invalidated due to object or range reuse, and so on. The flash cache buffer was not in use at the time of eviction.                                                                                                                                                                                                                                        |                  |
| flash cache insert skip: corrupt         | 8     | In-memory buffer was skipped for insertion into flash cache because the buffer was corrupted                                                                                                                                                                                                                                                                                     |                  |
| flash cache insert skip: DBWR overloaded | 8     | In-memory buffer was skipped for insertion into flash cache because DBWR was busy writing other buffers                                                                                                                                                                                                                                                                          |                  |
| flash cache insert skip: exists          | 8     | In-memory buffer was skipped for insertion into flash cache because it was already in the flash cache                                                                                                                                                                                                                                                                            |                  |
| flash cache insert skip: modification    | 8     | In-memory buffer was skipped for insertion into flash cache because it was being modified                                                                                                                                                                                                                                                                                        |                  |
| flash cache insert skip: not current     | 8     | In-memory buffer was skipped for insertion into flash cache because it was not current                                                                                                                                                                                                                                                                                           |                  |
| flash cache insert skip: not useful      | 8     | In-memory buffer was skipped for insertion into flash cache because the type of buffer was not useful to keep                                                                                                                                                                                                                                                                    |                  |
| flash cache inserts                      | 8     | Total number of in-memory buffers inserted into flash cache                                                                                                                                                                                                                                                                                                                      |                  |
| flashback log write bytes                | 2     | Total size in bytes of flashback database data written by RVWR to flashback database logs                                                                                                                                                                                                                                                                                        |                  |
| flashback log writes                     | 2     | Total number of writes by RVWR to flashback database logs                                                                                                                                                                                                                                                                                                                        |                  |
| free buffer inspected                    | 8     | Number of buffers skipped over from the end of an LRU queue in order to find a reusable buffer. The difference between this statistic and " <a href="#">dirty buffers inspected</a> " is the number of buffers that could not be used because they had a user, a waiter, or were being read or written, or because they were busy or needed to be written after rapid aging out. |                  |

**Table E-1 (Cont.) Database Statistics Descriptions**

| Name                                 | Class | Description                                                                                                                                                                                         | TIMED_STATISTICS |
|--------------------------------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| free buffer requested                | 8     | Number of times a reusable buffer or a free buffer was requested to create or load a block                                                                                                          |                  |
| global cache blocks corrupt          | 40    | Real Application Clusters only: Number of blocks that encountered a corruption or checksum failure during interconnect                                                                              |                  |
| global cache convert time            | 40    | Real Application Clusters only: Total time elapsed during lock converts                                                                                                                             |                  |
| global cache convert timeouts        | 40    | Number of times lock converts in the global cache timed out                                                                                                                                         |                  |
| global cache converts                | 40    | Number of lock converts in the global cache                                                                                                                                                         |                  |
| global cache cr block log flushes    | 40    | Number of log flushes of the consistent-read block                                                                                                                                                  |                  |
| global cache cr block log flush time | 40    | Total time spent by the BSP process in log flushes after sending a constructed consistent-read (CR) block. This statistic divided by "global cache cr blocks served" = log flush time per CR block. |                  |
| global cache cr block receive time   | 40    | Total amount of time foreground processes waited for a CR block to be sent through the interconnect. This statistic divided by "global cache cr blocks received" = time waited per block.           |                  |
| global cache cr block send time      | 40    | Total time spent by the BSP process in sending constructed consistent-read (CR) blocks. This statistic divided by "global cache cr blocks served" = send time per CR block.                         |                  |
| global cache cr block serve time     | 40    | Total amount of time the BSP process took to construct consistent-read (CR) blocks. This statistic divided by "global cache cr blocks served" = construction time per CR block.                     |                  |
| global cache cr blocks received      | 40    | Total number of blocks received                                                                                                                                                                     |                  |
| global cache cr blocks served        | 40    | Total number of blocks constructed by the BSP process                                                                                                                                               |                  |
| global cache cr requests blocked     | 40    | Number of times foreground attempt to request a cr block and failed                                                                                                                                 |                  |
| global cache cr timeouts             | 40    | Number of times a foreground process requested a consistent-read (CR) block when the request timed out                                                                                              |                  |
| global cache defers                  | 40    | Number of times a lock was requested and the holder of the lock deferred the release                                                                                                                |                  |
| global cache freelist waits          | 40    | System configured with fewer lock elements than buffers. Number of times foreground has to wait for a lock element.                                                                                 |                  |
| global cache get time                | 40    | Total time spent waiting. This divided by global cache gets = time waited per request.                                                                                                              |                  |
| global cache gets                    | 40    | Number of locks acquired                                                                                                                                                                            |                  |
| global cache prepare failures        | 40    | Number of times a failure occurred during preparation for interconnect transfer                                                                                                                     |                  |
| global lock async converts           | 32    | Total number of asynchronous global lock converts                                                                                                                                                   |                  |
| global lock async gets               | 32    | Total number of asynchronous global lock gets                                                                                                                                                       |                  |

**Table E–1 (Cont.) Database Statistics Descriptions**

| Name                                            | Class | Description                                                                                                                                                                                                                                                                                                                    | TIMED_STATISTICS |
|-------------------------------------------------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| global lock convert time                        | 32    | Total elapsed time in 10s of milliseconds of all synchronous and asynchronous global lock converts                                                                                                                                                                                                                             |                  |
| global lock get time                            | 32    | Total elapsed time in 10s of milliseconds of all synchronous and asynchronous global lock gets                                                                                                                                                                                                                                 |                  |
| global lock releases                            | 32    | Total number of synchronous global lock releases                                                                                                                                                                                                                                                                               |                  |
| global lock sync converts                       | 32    | Total number of synchronous global lock converts                                                                                                                                                                                                                                                                               |                  |
| global lock sync gets                           | 32    | Total number of synchronous global lock gets                                                                                                                                                                                                                                                                                   |                  |
| hot buffers moved to head of LRU                | 8     | When a hot buffer reaches the tail of its replacement list, Oracle moves it back to the head of the list to keep it from being reused. This statistic counts such moves.                                                                                                                                                       |                  |
| immediate (CR) block cleanout applications      | 128   | Number of times cleanout records are applied immediately during consistent-read requests                                                                                                                                                                                                                                       |                  |
| immediate (CURRENT) block cleanout applications | 128   | Number of times cleanout records are applied immediately during current gets. Compare this statistic with <a href="#">"deferred (CURRENT) block cleanout applications"</a>                                                                                                                                                     |                  |
| index fast full scans (direct read)             | 64    | Number of fast full scans initiated using direct read                                                                                                                                                                                                                                                                          |                  |
| index fast full scans (full)                    | 64    | Number of fast full scans initiated for full segments                                                                                                                                                                                                                                                                          |                  |
| index fast full scans (rowid ranges)            | 64    | Number of fast full scans initiated with rowid endpoints specified                                                                                                                                                                                                                                                             |                  |
| instance recovery database freeze count         | 32    | Number of times the database is frozen during instance recovery                                                                                                                                                                                                                                                                |                  |
| kcmccs called get current scn                   | 32    | Number of times the kernel got the CURRENT SCN when there was a need to casually confirm the SCN                                                                                                                                                                                                                               |                  |
| kcmgss read scn without going to DLM            | 32    | Number of times the kernel got a snapshot SCN without going to the distributed lock manager (DLM)                                                                                                                                                                                                                              |                  |
| kcmgss waited for batching                      | 32    | Number of times a database process is blocked waiting for a snapshot SCN                                                                                                                                                                                                                                                       |                  |
| leaf node splits                                | 128   | Number of times an index leaf node was split because of the insertion of an additional value                                                                                                                                                                                                                                   |                  |
| lob reads                                       | 8     | Number of LOB API read operations performed in the session/system. A single LOB API read may correspond to multiple physical/logical disk block reads.                                                                                                                                                                         |                  |
| lob writes                                      | 8     | Number of LOB API write operations performed in the session/system. A single LOB API write may correspond to multiple physical/logical disk block writes.                                                                                                                                                                      |                  |
| lob writes unaligned                            | 8     | Number of LOB API write operations whose start offset or buffer size is not aligned to the internal chunk size of the LOB. Writes aligned to chunk boundaries are the most efficient write operations. The internal chunk size of a LOB is available through the LOB API (for example, <code>DBMS_LOB.GETCHUNKSIZE()</code> ). |                  |
| logons cumulative                               | 1     | Total number of logons since the instance started. Useful only in <code>V\$SYSSTAT</code> . It gives an instance overview of all processes that logged on.                                                                                                                                                                     |                  |
| logons current                                  | 1     | Total number of current logons. Useful only in <code>V\$SYSSTAT</code> .                                                                                                                                                                                                                                                       |                  |

**Table E-1 (Cont.) Database Statistics Descriptions**

| Name                                  | Class | Description                                                                                                                                                                                                                                                                                                                                                                                                                                   | TIMED_STATISTICS |
|---------------------------------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| messages received                     | 128   | Number of messages sent and received between background processes                                                                                                                                                                                                                                                                                                                                                                             |                  |
| messages sent                         | 128   | Number of messages sent and received between background processes                                                                                                                                                                                                                                                                                                                                                                             |                  |
| native hash arithmetic execute        | 64    | Number of hash operations performed using native arithmetic rather than Oracle NUMBERS                                                                                                                                                                                                                                                                                                                                                        |                  |
| native hash arithmetic fail           | 64    | Number of has operations performed using native arithmetic that failed, requiring the hash operation to be performed with Oracle NUMBERS                                                                                                                                                                                                                                                                                                      |                  |
| next scns gotten without going to DLM | 32    | Number of system change numbers obtained without going to the distributed lock manager or server                                                                                                                                                                                                                                                                                                                                              |                  |
| no buffer to keep pinned count        | 72    | Number of times a visit to a buffer attempted, but the buffer was not found where expected. Like <a href="#">"buffer is not pinned count"</a> and <a href="#">"buffer is pinned count"</a> , this statistic is useful only for internal debugging purposes.                                                                                                                                                                                   |                  |
| no work - consistent read gets        | 128   | Number consistent gets that require neither block cleanouts nor rollbacks.<br><b>See Also:</b> <a href="#">"consistent gets"</a>                                                                                                                                                                                                                                                                                                              |                  |
| opened cursors cumulative             | 1     | In V\$SYSSTAT: Total number of cursors opened since the instance started.<br><br>In V\$SESSTAT: Total number of cursors opened since the start of the session.                                                                                                                                                                                                                                                                                |                  |
| opened cursors current                | 1     | Total number of current open cursors                                                                                                                                                                                                                                                                                                                                                                                                          |                  |
| opens of replaced files               | 8     | Total number of files that had to be reopened because they were no longer in the process file cache                                                                                                                                                                                                                                                                                                                                           |                  |
| opens requiring cache replacement     | 8     | Total number of file opens that caused a current file in the process file cache to be closed                                                                                                                                                                                                                                                                                                                                                  |                  |
| OS All other sleep time               | 16    | Time spent sleeping for reasons other than misses in the data segment (see <a href="#">"OS Data page fault sleep time"</a> ), kernel page faults (see <a href="#">"OS Kernel page fault sleep time"</a> ), misses in the text segment (see <a href="#">"OS Text page fault sleep time"</a> ), or waiting for an OS locking object (see <a href="#">"OS User lock wait sleep time"</a> ). An example of such a reason is expiration of quanta. |                  |
| OS Chars read and written             | 16    | Number of bytes read and written                                                                                                                                                                                                                                                                                                                                                                                                              |                  |
| OS Data page fault sleep time         | 16    | Time spent sleeping due to misses in the data segment                                                                                                                                                                                                                                                                                                                                                                                         |                  |
| OS Input blocks                       | 16    | Number of read I/Os                                                                                                                                                                                                                                                                                                                                                                                                                           |                  |
| OS Involuntary context switches       | 16    | Number of context switches that were enforced by the operating system                                                                                                                                                                                                                                                                                                                                                                         |                  |
| OS Kernel page fault sleep time       | 16    | Time spent sleeping due to OS kernel page faults                                                                                                                                                                                                                                                                                                                                                                                              |                  |
| OS Major page faults                  | 16    | Number of page faults that resulted in I/O                                                                                                                                                                                                                                                                                                                                                                                                    |                  |
| OS Messages received                  | 16    | Number of messages received                                                                                                                                                                                                                                                                                                                                                                                                                   |                  |
| OS Messages sent                      | 16    | Number of messages sent                                                                                                                                                                                                                                                                                                                                                                                                                       |                  |
| OS Minor page faults                  | 16    | Number of page faults that did not result in an actual I/O                                                                                                                                                                                                                                                                                                                                                                                    |                  |

**Table E-1 (Cont.) Database Statistics Descriptions**

| <b>Name</b>                                 | <b>Class</b> | <b>Description</b>                                                                                                                                                                                                       | <b>TIMED_<br/>STATISTICS</b> |
|---------------------------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| OS Other system trap CPU time               | 16           | Total amount of time to process system traps (as distinct from system calls)                                                                                                                                             |                              |
| OS Output blocks                            | 16           | Number of write I/Os                                                                                                                                                                                                     |                              |
| OS Process heap size                        | 16           | Size of area in memory allocated by the process. Typically this represents memory obtained by way of malloc().                                                                                                           |                              |
| OS Process stack size                       | 16           | Size of the process stack segment                                                                                                                                                                                        |                              |
| OS Signals received                         | 16           | Number of signals received                                                                                                                                                                                               |                              |
| OS Swaps                                    | 16           | Number of swap pages                                                                                                                                                                                                     |                              |
| OS System call CPU time                     | 16           | Total amount of time spent executing in system mode                                                                                                                                                                      |                              |
| OS System calls                             | 16           | Number of system calls                                                                                                                                                                                                   |                              |
| OS Text page fault sleep time               | 16           | Time spent sleeping due to misses in the text segment                                                                                                                                                                    |                              |
| OS User level CPU time                      | 16           | Total amount of time spent executing in user mode                                                                                                                                                                        |                              |
| OS User lock wait sleep time                | 16           | Total amount of time sleeping while waiting for an OS locking object                                                                                                                                                     |                              |
| OS Voluntary context switches               | 16           | Number of voluntary context switches (for example, when a process gives up the CPU by a SLEEP() system call)                                                                                                             |                              |
| OS Wait-cpu (latency) time                  | 16           | Time spent sleeping while waiting for a CPU to become available                                                                                                                                                          |                              |
| Parallel operations downgraded 1 to 25 pct  | 32           | Number of times parallel execution was requested and the degree of parallelism was reduced because of insufficient parallel execution servers                                                                            |                              |
| Parallel operations downgraded 25 to 50 pct | 32           | Number of times parallel execution was requested and the degree of parallelism was reduced because of insufficient parallel execution servers                                                                            |                              |
| Parallel operations downgraded 50 to 75 pct | 32           | Number of times parallel execution was requested and the degree of parallelism was reduced because of insufficient parallel execution servers                                                                            |                              |
| Parallel operations downgraded 75 to 99 pct | 32           | Number of times parallel execution was requested and the degree of parallelism was reduced because of insufficient parallel execution servers                                                                            |                              |
| Parallel operations downgraded to serial    | 32           | Number of times parallel execution was requested but execution was serial because of insufficient parallel execution servers                                                                                             |                              |
| Parallel operations not downgraded          | 32           | Number of times parallel execution was executed at the requested degree of parallelism                                                                                                                                   |                              |
| parse count (hard)                          | 64           | Total number of parse calls (real parses). A hard parse is a very expensive operation in terms of memory use, because it requires Oracle to allocate a workheap and other memory structures and then build a parse tree. |                              |
| parse count (describe)                      | 64           | Total number of parse calls on a describe cursor. This operation is a less expensive than a hard parse and more expensive than a soft parse.                                                                             |                              |



**Table E–1 (Cont.) Database Statistics Descriptions**

| Name                                       | Class | Description                                                                                                                                                                                                                                                                                                      | TIMED_ STATISTICS |
|--------------------------------------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| parse count (total)                        | 64    | Total number of parse calls (hard, soft, and describe). A soft parse is a check on an object already in the shared pool, to verify that the permissions on the underlying object have not changed.                                                                                                               |                   |
| parse time cpu                             | 64    | Total CPU time used for parsing (hard and soft) in 10s of milliseconds                                                                                                                                                                                                                                           | 3                 |
| parse time elapsed                         | 64    | Total elapsed time for parsing, in 10s of milliseconds. Subtract " <a href="#">parse time cpu</a> " from the this statistic to determine the total waiting time for parse resources.                                                                                                                             | 3                 |
| physical read bytes                        | 8     | Total size in bytes of all disk reads by application activity (and not other instance activity) only.                                                                                                                                                                                                            |                   |
| physical read flash cache hits             | 8     | Total number of reads from flash cache instead of disk                                                                                                                                                                                                                                                           |                   |
| physical read IO requests                  | 8     | Number of read requests for application activity (mainly buffer cache and direct load operation) which read one or more database blocks per request. This is a subset of "physical read total IO requests" statistic.                                                                                            |                   |
| physical read requests optimized           | 8     | Number of read requests that read one or more database blocks from the Database Smart Flash Cache.                                                                                                                                                                                                               |                   |
| physical read total bytes                  | 8     | Total size in bytes of disk reads by all database instance activity including application reads, backup and recovery, and other utilities. The difference between this value and "physical read bytes" gives the total read size in bytes by non-application workload.                                           |                   |
| physical read total IO requests            | 8     | Number of read requests which read one or more database blocks for all instance activity including application, backup and recovery, and other utilities. The difference between this value and "physical read total multi block requests" gives the total number of single block read requests.                 |                   |
| physical read total multi block requests   | 8     | Total number of Oracle instance read requests which read in two or more database blocks per request for all instance activity including application, backup and recovery, and other utilities.                                                                                                                   |                   |
| physical reads                             | 8     | Total number of data blocks read from disk. This value can be greater than the value of "physical reads direct" plus "physical reads cache" as reads into process private buffers also included in this statistic.                                                                                               |                   |
| physical reads cache                       | 8     | Total number of data blocks read from disk into the buffer cache. This is a subset of "physical reads" statistic.                                                                                                                                                                                                |                   |
| physical reads cache prefetch              | 8     | Number of contiguous and noncontiguous blocks that were prefetched.                                                                                                                                                                                                                                              |                   |
| physical reads direct                      | 8     | Number of reads directly from disk, bypassing the buffer cache. For example, in high bandwidth, data-intensive operations such as parallel query, reads of disk blocks bypass the buffer cache to maximize transfer rates and to prevent the premature aging of shared data blocks resident in the buffer cache. |                   |
| physical reads direct (lob)                | 8     | Number of buffers that were read directly for LOBs                                                                                                                                                                                                                                                               |                   |
| physical reads direct temporary tablespace | 8     | Number of buffers that were read directly from temporary tablespaces                                                                                                                                                                                                                                             |                   |

**Table E-1 (Cont.) Database Statistics Descriptions**

| Name                                        | Class | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | TIMED_STATISTICS |
|---------------------------------------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| physical reads for flashback new            | 8     | Number of blocks read for newing (that is, preparing a data block for a completely new change) blocks while flashback database is enabled                                                                                                                                                                                                                                                                                                                                                     |                  |
| physical reads prefetch warmup              | 8     | Number of data blocks that were read from the disk during the automatic prewarming of the buffer cache.                                                                                                                                                                                                                                                                                                                                                                                       |                  |
| physical write bytes                        | 8     | Total size in bytes of all disk writes from the database application activity (and not other kinds of instance activity).                                                                                                                                                                                                                                                                                                                                                                     |                  |
| physical write IO requests                  | 8     | Number of write requests for application activity (mainly buffer cache and direct load operation) which wrote one or more database blocks per request.                                                                                                                                                                                                                                                                                                                                        |                  |
| physical write total bytes                  | 8     | Total size in bytes of all disk writes for the database instance including application activity, backup and recovery, and other utilities. The difference between this value and "physical write bytes" gives the total write size in bytes by non-application workload.                                                                                                                                                                                                                      |                  |
| physical write total IO requests            | 8     | Number of write requests which wrote one or more database blocks from all instance activity including application activity, backup and recovery, and other utilities. The difference between this stat and "physical write total multi block requests" gives the number of single block write requests.                                                                                                                                                                                       |                  |
| physical write total multi block requests   | 8     | Total number of Oracle instance write requests which wrote two or more blocks per request to the disk for all instance activity including application activity, recovery and backup, and other utilities.                                                                                                                                                                                                                                                                                     |                  |
| physical writes                             | 8     | Total number of data blocks written to disk. This statistics value equals the sum of "physical writes direct" and "physical writes from cache" values.                                                                                                                                                                                                                                                                                                                                        |                  |
| physical writes direct                      | 8     | Number of writes directly to disk, bypassing the buffer cache (as in a direct load operation)                                                                                                                                                                                                                                                                                                                                                                                                 |                  |
| physical writes direct (lob)                | 8     | Number of buffers that were directly written for LOBs                                                                                                                                                                                                                                                                                                                                                                                                                                         |                  |
| physical writes direct temporary tablespace | 8     | Number of buffers that were directly written for temporary tablespaces                                                                                                                                                                                                                                                                                                                                                                                                                        |                  |
| physical writes from cache                  | 8     | Total number of data blocks written to disk from the buffer cache. This is a subset of "physical writes" statistic.                                                                                                                                                                                                                                                                                                                                                                           |                  |
| physical writes non checkpoint              | 8     | Number of times a buffer is written for reasons other than advancement of the checkpoint. Used as a metric for determining the I/O overhead imposed by setting the FAST_START_IO_TARGET parameter to limit recovery I/Os. (Note that FAST_START_IO_TARGET is a deprecated parameter.) Essentially this statistic measures the number of writes that would have occurred had there been no checkpointing. Subtracting this value from "physical writes" gives the extra I/O for checkpointing. |                  |

**Table E–1 (Cont.) Database Statistics Descriptions**

| Name                                          | Class | Description                                                                                                                                                                                                                                                                           | TIMED_STATISTICS |
|-----------------------------------------------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| pinned buffers inspected                      | 8     | Number of times a user process, when scanning the tail of the replacement list looking for a buffer to reuse, encountered a cold buffer that was pinned or had a waiter that was about to pin it. This occurrence is uncommon, because a cold buffer should not be pinned very often. |                  |
| prefetched blocks aged out before use         | 8     | Number of contiguous and noncontiguous blocks that were prefetched but aged out before use                                                                                                                                                                                            |                  |
| process last non-idle time                    | 128   | The last time this process executed                                                                                                                                                                                                                                                   | 3                |
| PX local messages rcv'd                       | 32    | Number of local messages received for parallel execution within the instance local to the current session                                                                                                                                                                             |                  |
| PX local messages sent                        | 32    | Number of local messages sent for parallel execution within the instance local to the current session                                                                                                                                                                                 |                  |
| PX remote messages rcv'd                      | 32    | Number of remote messages received for parallel execution within the instance local to the current session                                                                                                                                                                            |                  |
| PX remote messages sent                       | 32    | Number of remote messages sent for parallel execution within the instance local to the current session                                                                                                                                                                                |                  |
| queries parallelized                          | 32    | Number of SELECT statements executed in parallel                                                                                                                                                                                                                                      |                  |
| recovery array read time                      | 8     | Elapsed time of I/O during recovery                                                                                                                                                                                                                                                   |                  |
| recovery array reads                          | 8     | Number of reads performed during recovery                                                                                                                                                                                                                                             |                  |
| recovery blocks read                          | 8     | Number of blocks read during recovery                                                                                                                                                                                                                                                 |                  |
| recovery blocks read for lost write detection | 8     | Number of blocks read for lost write checks during recovery.                                                                                                                                                                                                                          |                  |
| recovery blocks skipped lost write checks     | 8     | Number of Block Read Records that skipped the lost write check during recovery.                                                                                                                                                                                                       |                  |
| recursive calls                               | 1     | Number of recursive calls generated at both the user and system level. Oracle maintains tables used for internal processing. When Oracle needs to make a change to these tables, it internally generates an internal SQL statement, which in turn generates a recursive call.         |                  |
| recursive cpu usage                           | 1     | Total CPU time used by non-user calls (recursive calls). Subtract this value from "CPU used by this session" to determine how much CPU time was used by the user calls.                                                                                                               |                  |
| redo blocks checksummed by FG (exclusive)     | 2     | Number of exclusive redo blocks that were checksummed by the generating foreground processes. An exclusive redo block is the one whose entire redo content belongs to a single redo entry.                                                                                            |                  |
| redo blocks checksummed by LGWR               | 2     | Number of redo blocks that were checksummed by the LGWR.                                                                                                                                                                                                                              |                  |
| redo blocks written                           | 2     | Total number of redo blocks written. This statistic divided by "redo writes" equals number of blocks per write.                                                                                                                                                                       |                  |
| redo buffer allocation retries                | 2     | Total number of retries necessary to allocate space in the redo buffer. Retries are needed either because the redo writer has fallen behind or because an event such as a log switch is occurring.                                                                                    |                  |

**Table E-1 (Cont.) Database Statistics Descriptions**

| Name                                  | Class | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | TIMED_STATISTICS |
|---------------------------------------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| redo entries                          | 2     | Number of times a redo entry is copied into the redo log buffer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                  |
| redo entries for lost write detection | 2     | Number of times a Block Read Record is copied into the log buffer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                  |
| redo log space requests               | 2     | <p>Number of times the active log file is full and Oracle must wait for disk space to be allocated for the redo log entries. Such space is created by performing a log switch.</p> <p>Log files that are small in relation to the size of the SGA or the commit rate of the work load can cause problems. When the log switch occurs, Oracle must ensure that all committed dirty buffers are written to disk before switching to a new log file. If you have a large SGA full of dirty buffers and small redo log files, a log switch must wait for DBWR to write dirty buffers to disk before continuing.</p> <p>Also examine the <b>log file space</b> and <b>log file space switch</b> wait events in V\$SESSION_WAIT</p> |                  |
| redo log space wait time              | 2     | Total elapsed waiting time for "redo log space requests" in 10s of milliseconds                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 3                |
| redo ordering marks                   | 2     | Number of times that a system change number was allocated to force a redo record to have a higher SCN than a record generated in another thread using the same block                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                  |
| redo size                             | 2     | Total amount of redo generated in bytes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                  |
| redo size for lost write detection    | 2     | Total amount of Block Read Records generated in bytes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                  |
| redo synch time                       | 8     | Elapsed time of all "redo synch writes" calls in 10s of milliseconds                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 3                |
| redo synch writes                     | 8     | Number of times the redo is forced to disk, usually for a transaction commit. The log buffer is a circular buffer that LGWR periodically flushes. Usually, redo that is generated and copied into the log buffer need not be flushed out to disk immediately.                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                  |
| redo wastage                          | 2     | Number of bytes wasted because redo blocks needed to be written before they are completely full. Early writing may be needed to commit transactions, to be able to write a database buffer, or to switch logs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                  |
| redo write broadcast ack count        | 2     | Number of times a commit broadcast acknowledgment has not been received by the time when the corresponding log write is completed. This is only for Oracle RAC.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                  |
| redo write broadcast ack time         | 2     | Total amount of the latency associated with broadcast on commit beyond the latency of the log write (in microseconds). This is only for Oracle RAC.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 3                |
| redo write time                       | 2     | Total elapsed time of the write from the redo log buffer to the current redo log file in 10s of milliseconds                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 3                |
| redo writes                           | 2     | Total number of writes by LGWR to the redo log files. "redo blocks written" divided by this statistic equals the number of blocks per write                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                  |

**Table E-1 (Cont.) Database Statistics Descriptions**

| Name                                    | Class | Description                                                                                                                                                                                                                                                                                                       | TIMED_STATISTICS |
|-----------------------------------------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| remote instance undo block writes       | 40    | Number of times this instance wrote a rollback segment so that another instance could read it                                                                                                                                                                                                                     |                  |
| remote instance undo header writes      | 40    | Number of times this instance wrote a undo header block so that another instance could read it                                                                                                                                                                                                                    |                  |
| rollback changes - undo records applied | 128   | Number of undo records applied to user-requested rollback changes (not consistent-read rollbacks)                                                                                                                                                                                                                 |                  |
| rollbacks only - consistent read gets   | 128   | Number of consistent gets that require only block rollbacks, no block cleanouts.<br><b>See Also:</b> <a href="#">"consistent gets"</a>                                                                                                                                                                            |                  |
| rows fetched via callback               | 64    | Rows fetched via callback. Useful primarily for internal debugging purposes.                                                                                                                                                                                                                                      |                  |
| serializable aborts                     | 1     | Number of times a SQL statement in a serializable isolation level had to abort                                                                                                                                                                                                                                    |                  |
| session connect time                    | 1     | The connect time for the session in 10s of milliseconds. This value is useful only in V\$SESSTAT. It is the wall clock time since the logon to this session occurred.                                                                                                                                             | 3                |
| session cursor cache count              | 64    | Total number of cursors cached. This statistic is incremented only if SESSION_CACHED_CURSORS > 0. This statistic is the most useful in V\$SESSTAT. If the value for this statistic in V\$SESSTAT is close to the setting of the SESSION_CACHED_CURSORS parameter, the value of the parameter should be increased. |                  |
| session cursor cache hits               | 64    | Number of hits in the session cursor cache. A hit means that the SQL (including recursive SQL) or PL/SQL statement did not have to be reparsed. Subtract this statistic from <a href="#">"parse count (total)"</a> to determine the real number of parses that occurred.                                          |                  |
| session logical reads                   | 1     | The sum of "db block gets" plus "consistent gets". This includes logical reads of database blocks from either the buffer cache or process private memory.                                                                                                                                                         |                  |
| session pga memory                      | 1     | Current PGA size for the session. Useful only in V\$SESSTAT; it has no meaning in V\$SYSSTAT.                                                                                                                                                                                                                     |                  |
| session pga memory max                  | 1     | Peak PGA size for the session. Useful only in V\$SESSTAT; it has no meaning in V\$SYSSTAT.                                                                                                                                                                                                                        |                  |
| session stored procedure space          | 1     | Amount of memory this session is using for stored procedures                                                                                                                                                                                                                                                      |                  |
| session uga memory                      | 1     | Current UGA size for the session. Useful only in V\$SESSTAT; it has no meaning in V\$SYSSTAT.                                                                                                                                                                                                                     |                  |
| session uga memory max                  | 1     | Peak UGA size for a session. Useful only in V\$SESSTAT; it has no meaning in V\$SYSSTAT.                                                                                                                                                                                                                          |                  |
| shared io pool buffer get failure       | 128   | Number of unsuccessful buffer gets from the shared I/O pool from instance startup time.                                                                                                                                                                                                                           |                  |
| shared io pool buffer get success       | 128   | Number of successful buffer gets from the shared I/O pool from instance startup time.                                                                                                                                                                                                                             |                  |

**Table E-1 (Cont.) Database Statistics Descriptions**

| Name                              | Class | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | TIMED_STATISTICS |
|-----------------------------------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| sorts (disk)                      | 64    | <p>Number of sort operations that required at least one disk write</p> <p>Sorts that require I/O to disk are quite resource intensive. Try increasing the size of the initialization parameter <code>SORT_AREA_SIZE</code>. For more information, see "<a href="#">SORT_AREA_SIZE</a>" on page 1-165.</p>                                                                                                                                                                                                                                                           |                  |
| sorts (memory)                    | 64    | <p>Number of sort operations that were performed completely in memory and did not require any disk writes</p> <p>You cannot do much better than memory sorts, except maybe no sorts at all. Sorting is usually caused by selection criteria specifications within table join SQL operations.</p>                                                                                                                                                                                                                                                                    |                  |
| sorts (rows)                      | 64    | Total number of rows sorted                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                  |
| SQL*Net roundtrips to/from client | 1     | Total number of Oracle Net Services messages sent to and received from the client                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                  |
| SQL*Net roundtrips to/from dblink | 1     | Total number of Oracle Net Services messages sent over and received from a database link                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                  |
| summed dirty queue length         | 8     | The sum of the dirty LRU queue length after every write request. Divide by <b>write requests</b> to get the average queue length after write completion.                                                                                                                                                                                                                                                                                                                                                                                                            |                  |
| switch current to new buffer      | 8     | Number of times the CURRENT block moved to a different buffer, leaving a CR block in the original buffer                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                  |
| table fetch by rowid              | 64    | <p>Number of rows that are fetched using a ROWID (usually recovered from an index)</p> <p>This occurrence of table scans usually indicates either non-optimal queries or tables without indexes. Therefore, this statistic should increase as you optimize queries and provide indexes in the application.</p>                                                                                                                                                                                                                                                      |                  |
| table fetch continued row         | 64    | <p>Number of times a chained or migrated row is encountered during a fetch</p> <p>Retrieving rows that span more than one block increases the logical I/O by a factor that corresponds to the number of blocks that need to be accessed. Exporting and re-importing may eliminate this problem. Evaluate the settings for the storage parameters <code>PCTFREE</code> and <code>PCTUSED</code>. This problem cannot be fixed if rows are larger than database blocks (for example, if the <code>LONG</code> datatype is used and the rows are extremely large).</p> |                  |
| table scan blocks gotten          | 64    | <p>During scanning operations, each row is retrieved sequentially by Oracle. This statistic counts the number of blocks encountered during the scan.</p> <p>This statistic tells you the number of database blocks that you had to get from the buffer cache for the purpose of scanning. Compare this value with the value of "<a href="#">consistent gets</a>" to determine how much of the consistent read activity can be attributed to scanning.</p>                                                                                                           |                  |
| table scan rows gotten            | 64    | Number of rows that are processed during scanning operations                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                  |
| table scans (cache partitions)    | 64    | Number of range scans performed on tables that have the <code>CACHE</code> option enabled                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                  |

**Table E–1 (Cont.) Database Statistics Descriptions**

| Name                                                       | Class | Description                                                                                                                                                                                                                                                             | TIMED_<br>STATISTICS |
|------------------------------------------------------------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| table scans (direct read)                                  | 64    | Number of table scans performed with direct read (bypassing the buffer cache)                                                                                                                                                                                           |                      |
| table scans (long tables)                                  | 64    | Long (or conversely short) tables can be defined as tables that do not meet the short table criteria as described in <a href="#">table scans (short tables)</a>                                                                                                         |                      |
| table scans (rowid ranges)                                 | 64    | During parallel query, the number of table scans conducted with specified ROWID ranges                                                                                                                                                                                  |                      |
| table scans (short tables)                                 | 64    | Long (or conversely short) tables can be defined by optimizer hints coming down into the row source access layer of Oracle. The table must have the CACHE option set.                                                                                                   |                      |
| total file opens                                           | 8     | Total number of file opens performed by the instance. Each process needs a number of files (control file, log file, database file) in order to work against the database.                                                                                               |                      |
| transaction lock background get time                       | 128   | Useful only for internal debugging purposes                                                                                                                                                                                                                             |                      |
| transaction lock background gets                           | 128   | Useful only for internal debugging purposes                                                                                                                                                                                                                             |                      |
| transaction lock foreground requests                       | 128   | Useful only for internal debugging purposes                                                                                                                                                                                                                             |                      |
| transaction lock foreground wait time                      | 128   | Useful only for internal debugging purposes                                                                                                                                                                                                                             |                      |
| transaction rollbacks                                      | 128   | Number of transactions being successfully rolled back                                                                                                                                                                                                                   |                      |
| transaction tables consistent read rollbacks               | 128   | Number of times rollback segment headers are rolled back to create consistent read blocks                                                                                                                                                                               |                      |
| transaction tables consistent reads - undo records applied | 128   | Number of undo records applied to transaction tables that have been rolled back for consistent read purposes                                                                                                                                                            |                      |
| Unnecessary process cleanup for SCN batching               | 32    | Total number of times that the process cleanup was performed unnecessarily because the session or process did not get the next batched SCN. The next batched SCN went to another session instead.                                                                       |                      |
| user calls                                                 | 1     | Number of user calls such as login, parse, fetch, or execute<br><br>When determining activity, the ratio of user calls to RPI calls, give you an indication of how much internal work gets generated as a result of the type of requests the user is sending to Oracle. |                      |
| user commits                                               | 1     | Number of user commits. When a user commits a transaction, the redo generated that reflects the changes made to database blocks must be written to disk. Commits often represent the closest thing to a user transaction rate.                                          |                      |

**Table E-1 (Cont.) Database Statistics Descriptions**

| <b>Name</b>                        | <b>Class</b> | <b>Description</b>                                                                                                                                                                                                                                 | <b>TIMED_<br/>STATISTICS</b> |
|------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| user rollbacks                     | 1            | Number of times users manually issue the <code>ROLLBACK</code> statement or an error occurs during a user's transactions                                                                                                                           |                              |
| write clones created in background | 8            | Number of times a background or foreground process clones a <code>CURRENT</code> buffer that is being written. The clone becomes the new, accessible <code>CURRENT</code> buffer, leaving the original buffer (now the clone) to complete writing. |                              |
| write clones created in foreground | 8            | Number of times a background or foreground process clones a <code>CURRENT</code> buffer that is being written. The clone becomes the new, accessible <code>CURRENT</code> buffer, leaving the original buffer (now the clone) to complete writing. |                              |



## Background Processes

[Table F-1](#) describes Oracle Database background processes. In this context, a **background process** is defined as any process that is listed in `V$PROCESS` and has a non-null value in the `pname` column.

The External Properties column lists the type of instance in which the process runs. If the process is specific to a particular feature, then the column names the feature.

**Table F-1 Background Processes**

| Name              | Expanded Name                                               | Short Description                                                                                                                | Long Description                                                                                                                                                                                                                                                                                                                                                                          | External Properties                           |
|-------------------|-------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| ABMR              | Auto BMR Background Process                                 | Coordinates execution of tasks such as filtering duplicate block media recovery requests and performing flood control            | When a process submits a block media recovery request to ABMR, it dynamically spawns slave processes ( <code>BMRn</code> ) to perform the recovery. ABMR and <code>BMRn</code> terminate after being idle for a long time.<br><br><b>See Also:</b> <i>Oracle Database Backup and Recovery User's Guide</i>                                                                                | Database instance                             |
| ACFS              | ASM Cluster File System CSS Process                         | Tracks the cluster membership in CSS and informs the file system driver of membership changes                                    | ACFS delivers CSS membership changes to the Oracle cluster file system. These membership changes are required for the file system to maintain file system consistency within the cluster.                                                                                                                                                                                                 | ASM instance, Oracle RAC                      |
| ACMS              | Atomic Control File to Memory Service Process               | Coordinates consistent updates to a control file resource with its SGA counterpart on all instances in an Oracle RAC environment | The ACMS process works with a coordinating caller to ensure that an operation is executed on every instance in Oracle RAC despite failures. ACMS is the process in which a distributed operation is called. As a result, this process can exhibit a variety of behaviors. In general, ACMS is limited to small, nonblocking state changes for a limited set of cross-instance operations. | Database instance, Oracle RAC                 |
| <code>APnn</code> | Logical Standby / Streams Apply Process Coordinator Process | Obtains transactions from the reader server and passes them to apply servers                                                     | The coordinator process name is <code>APnn</code> , where <i>nn</i> can include letters and numbers.<br><br><b>See Also:</b> <i>Oracle Streams Concepts and Administration</i>                                                                                                                                                                                                            | Database instance, Data Guard, Oracle Streams |
| <code>ARBn</code> | ASM Rebalance Process                                       | Rebalances data extents within an ASM disk group                                                                                 | Possible processes are ARB0-ARB9 and ARBA.                                                                                                                                                                                                                                                                                                                                                | ASM instance                                  |

**Table F–1 (Cont.) Background Processes**

| Name         | Expanded Name                                                         | Short Description                                                                                                                                                                                                                                                                                    | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | External Properties        |
|--------------|-----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| ARC <i>n</i> | Archiver Process                                                      | Copies the redo log files to archival storage when they are full or an online redo log switch occurs                                                                                                                                                                                                 | <p>ARC<i>n</i> processes exist only when the database is in ARCHIVELOG mode and automatic archiving is enabled, in which case ARC<i>n</i> automatically archives online redo log files. LGWR cannot reuse and overwrite an online redo log group until it has been archived.</p> <p>The database starts multiple archiver processes as needed to ensure that the archiving of filled online redo logs does not fall behind. Possible processes include ARC0-ARC9 and ARCa-ARCt.</p> <p>The LOG_ARCHIVE_MAX_PROCESSES initialization parameter specifies the number of ARC<i>n</i> processes that the database initially invokes.</p> <p><b>See Also:</b> <i>Oracle Database Concepts</i> and <i>Oracle Database Administrator's Guide</i></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Database instance          |
| ASMB         | ASM Background Process                                                | Communicates with the ASM instance, managing storage and providing statistics                                                                                                                                                                                                                        | ASMB runs in ASM instances when the ASMCMD cp command runs or when the database instance first starts if the server parameter file is stored in ASM. ASMB also runs with Oracle Cluster Registry on ASM.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Database and ASM instances |
| AS <i>nn</i> | Logical Standby / Streams Apply Process Reader Server or Apply Server | <ul style="list-style-type: none"> <li>Computes dependencies between logical change records (LCRs) and assembles messages into transactions (Reader Server)</li> <li>Applies LCRs to database objects or passes LCRs and user messages to their appropriate apply handlers (Apply Server)</li> </ul> | <p>When the reader server finishes computing dependencies between LCRs and assembling transactions, it returns the assembled transactions to the coordinator process. Query V\$STREAMS_APPLY_READER for information about the reader server background process.</p> <p>An apply server receives the transactions from the coordinator background process, and either applies database changes in LCRs or sends LCRs or messages to apply handlers. Apply servers can also enqueue a queue. If an apply server encounters an error, then it then tries to resolve the error with a user-specified conflict handler or error handler. If an apply server cannot resolve an error, then it rolls back the transaction and places the entire transaction, including all of its messages, in the error queue. When an apply server commits a completed transaction, this transaction has been applied. When an apply server places a transaction in the error queue and commits, this transaction also has been applied. Query V\$STREAMS_APPLY_SERVER for information about the apply server background process.</p> <p>The coordinator process name is AS<i>nn</i>, where <i>nn</i> can include letters and numbers.</p> | Database instance          |
| BMR <i>n</i> | Automatic Block Media Recovery Slave Pool Process                     | Fetches blocks from a real-time readable standby database                                                                                                                                                                                                                                            | <p>When a process submits a block media recovery request to ABMR, it dynamically spawns slave processes (BMR<i>n</i>) to perform the recovery. BMR<i>n</i> processes fetch blocks from a real-time readable standby database. ABMR and BMR<i>n</i> terminate after being idle for a long time.</p> <p><b>See Also:</b> <i>Oracle Database Backup and Recovery User's Guide</i></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Database instance          |
| B <i>nnn</i> | ASM Blocking Slave Process for GMON                                   | Performs maintenance actions on ASM disk groups                                                                                                                                                                                                                                                      | <p>B<i>nnn</i> performs actions that require waiting for resources on behalf of GMON. GMON must be highly available and cannot wait.</p> <p>A B<i>nnn</i> slave is spawned when a disk is taken offline in an ASM disk group. Offline timer processing and drop of the disk are performed in this slave. Up to five process (B000 to B004) can exist depending on the load.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | ASM instance               |

**Table F–1 (Cont.) Background Processes**

| Name         | Expanded Name                      | Short Description                                                                                                                           | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | External Properties               |
|--------------|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| CJQ0         | Job Queue Coordinator Process      | Selects jobs that need to be run from the data dictionary and spawns job queue slave processes ( <i>Jnnn</i> ) to run the jobs              | CJQ0 is automatically started and stopped as needed by Oracle Scheduler.<br><br>The <code>JOB_QUEUE_PROCESSES</code> initialization parameter specifies the maximum number of processes that can be created for the execution of jobs. CJQ0 starts only as many job queue processes as required by the number of jobs to run and available resources.<br><br><b>See Also:</b> <i>Oracle Database Concepts</i> and <i>Oracle Database Administrator's Guide</i>                                                                                                                                                                                                                        | Database instance                 |
| CKPT         | Checkpoint Process                 | Signals DBW <i>n</i> at checkpoints and updates all the data files and control files of the database to indicate the most recent checkpoint | At specific times CKPT starts a checkpoint request by messaging DBW <i>n</i> to begin writing dirty buffers. On completion of individual checkpoint requests, CKPT updates data file headers and control files to record most recent checkpoint.<br><br><b>See Also:</b> <i>Oracle Database Concepts</i>                                                                                                                                                                                                                                                                                                                                                                              | Database and ASM instances        |
| CP <i>nn</i> | Streams Capture Process            | Captures database changes from the redo log by using the infrastructure of LogMiner                                                         | The capture process name is CP <i>nn</i> , where <i>nn</i> can include letters and numbers. The underlying LogMiner process name is MS <i>nn</i> , where <i>nn</i> can include letters and numbers. The capture process includes one reader server that reads the redo log and divides it into regions, one or more preparer servers that scan the redo log, and one builder server that merges redo records from the preparer servers. Each reader server, preparer server, and builder server is a process. Query the <code>V\$STREAMS_CAPTURE</code> view for information about this background process.<br><br><b>See Also:</b> <i>Oracle Streams Concepts and Administration</i> | Database instance, Oracle Streams |
| CS <i>nn</i> | Streams Propagation Sender Process | Sends LCRs to a propagation receiver                                                                                                        | The propagation sender process name is CS <i>nn</i> , where <i>nn</i> can include letters and numbers. In an Oracle Streams combined capture and apply optimization, the propagation sender sends LCRs directly to the propagation receiver to improve performance. The propagation receiver passes the LCRs to an apply process. Query <code>V\$PROPAGATION_SENDER</code> for information about a propagation sender.                                                                                                                                                                                                                                                                | Database instance, Oracle Streams |
| CS <i>nn</i> | I/O Calibration Process            | Issues I/Os to storage as part of storage calibration.                                                                                      | CS <i>nn</i> slave processes are started on execution of the <code>DBMS_RESOURCE_MANAGER.CALIBRATE_IO()</code> procedure. There is one slave process per CPU on each node of the database.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Database instance, Oracle RAC     |
| CTWR         | Change Tracking Writer Process     | Tracks changed data blocks as part of the Recovery Manager block change tracking feature                                                    | CTWR tracks changed blocks as redo is generated at a primary database and as redo is applied at a standby database. The process is slightly different depending on the type of database.<br><br><b>See Also:</b> <i>Oracle Database Backup and Recovery User's Guide</i>                                                                                                                                                                                                                                                                                                                                                                                                              | Database instance                 |
| DBRM         | Database Resource Manager Process  | Sets resource plans and performs other tasks related to the Database Resource Manager                                                       | If a resource plan is not enabled, then this process is idle.<br><br><b>See Also:</b> <i>Oracle Database Administrator's Guide</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Database instance                 |

**Table F–1 (Cont.) Background Processes**

| Name         | Expanded Name                     | Short Description                                                                                           | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | External Properties           |
|--------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| DBW <i>n</i> | Database Writer Process           | Writes modified blocks from the database buffer cache to the data files                                     | <p>The primary responsibility of DBW<i>n</i> is to write data blocks to disk. DBW<i>n</i> also handles checkpoints, file open synchronization, and logging of Block Written records.</p> <p>In many cases the blocks that DBW<i>n</i> writes are scattered throughout the disk. Thus, the writes tend to be slower than the sequential writes performed by LGWR. DBW<i>n</i> performs multiblock writes when possible to improve efficiency. The number of blocks written in a multiblock write varies by operating system.</p> <p>The DB_WRITER_PROCESSES initialization parameter specifies the number of DBW<i>n</i> processes (DBW0-DBW9 and DBWa-DBWz). The database selects an appropriate default setting for this parameter or adjusts a user-specified setting based on the number of CPUs and processor groups.</p> <p><b>See Also:</b> <i>Oracle Database Concepts</i> and <i>Oracle Database Performance Tuning Guide</i></p> | Database instance             |
| DIA0         | Diagnostic Process                | Detects and resolves hangs and deadlocks                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | ASM and Database instances    |
| DIAG         | Diagnostic Capture Process        | Performs diagnostic dumps                                                                                   | DIAG performs diagnostic dumps requested by other processes and dumps triggered by process or instance termination. In Oracle RAC, DIAG performs global diagnostic dumps requested by remote instances.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | ASM and Database instances    |
| DM <i>nn</i> | Data Pump Master Process          | Coordinates the Data Pump job tasks performed by Data Pump worker processes and handles client interactions | The Data Pump master (control) process is started during job creation and coordinates all tasks performed by the Data Pump job. It handles all client interactions and communication, establishes all job contexts, and coordinates all worker process activities on behalf of the job.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Database instance, Data Pump  |
| DMON         | Data Guard Broker Monitor Process | Manages and monitors a database that is part of a Data Guard broker configuration                           | <p>When you start the Data Guard broker, a DMON process is created. DMON runs for every database instance that is managed by the broker. DMON interacts with the local database and the DMON processes of the other databases to perform the requested function. DMON also monitors the health of the broker configuration and ensures that every database has a consistent description of the configuration.</p> <p>DMON maintains profiles about all database objects in the broker configuration in a binary configuration file. A copy of this file is maintained by the DMON process for each of the databases that belong to the broker configuration. The process is created when the DG_BROKER_START initialization parameter is set to true.</p> <p><b>See Also:</b> <i>Oracle Data Guard Broker</i></p>                                                                                                                         | Database instance, Data Guard |

**Table F–1 (Cont.) Background Processes**

| Name        | Expanded Name                             | Short Description                                                                                                                    | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | External Properties               |
|-------------|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| <i>Dnnm</i> | Dispatcher Process                        | Performs network communication in the shared server architecture                                                                     | <p>In the shared server architecture, clients connect to a dispatcher process, which creates a virtual circuit for each connection. When the client sends data to the server, the dispatcher receives the data into the virtual circuit and places the active circuit on the common queue to be picked up by an idle shared server. The shared server then reads the data from the virtual circuit and performs the database work necessary to complete the request. When the shared server must send data to the client, the server writes the data back into the virtual circuit and the dispatcher sends the data to the client. After the shared server completes the client request, the server releases the virtual circuit back to the dispatcher and is free to handle other clients.</p> <p>Several initialization parameters relate to shared servers. The principal parameters are: <code>DISPATCHERS</code>, <code>SHARED_SERVERS</code>, <code>MAX_SHARED_SERVERS</code>, <code>LOCAL_LISTENER</code>, <code>REMOTE_LISTENER</code>.</p> <p><b>See Also:</b> <i>Oracle Database Concepts</i></p> | Database instance, shared servers |
| <i>DRnn</i> | ASM Disk Resynchronizati on Slave Process | Resynchronizes the contents of an offline disk                                                                                       | When a disk online SQL command is issued on a disk or disks that are offline, ASM spawns <i>DRnn</i> . Depending on the load, more than one slave may be spawned.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | ASM Instance                      |
| <i>DSKM</i> | Slave Diskmon Process                     | Acts as the conduit between the database, ASM instances, and the Master Diskmon daemon to communicate information to Exadata storage | This process is active only if Exadata Storage is used. DSKM performs operations related to Exadata I/O fencing and Exadata cell failure handling.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | ASM instance, Exadata             |
| <i>DWnn</i> | Data Pump Worker Process                  | Performs Data Pump tasks as assigned by the Data Pump master process                                                                 | The Data Pump worker process is responsible for performing tasks that are assigned by the Data Pump master process, such as the loading and unloading of metadata and data.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Database instance                 |
| <i>EMNC</i> | EMON Coordinator Process                  | Coordinates database event management and notifications                                                                              | EMNC coordinates event management and notification activity in the database, including Streams Event Notifications, Continuous Query Notifications, and Fast Application Notifications.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Database and ASM instances        |
| <i>Ennn</i> | EMON Slave Process                        | Performs database event management and notifications                                                                                 | The database event management and notification load is distributed among the EMON slave processes. These processes work on the system notifications in parallel, offering a capability to process a larger volume of notifications, a faster response time, and a lower shared memory use for staging notifications.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Database and ASM instances        |
| <i>FBDA</i> | Flashback Data Archiver Process           | Archives historical rows for tracked tables into flashback data archives and manages archive space, organization, and retention      | <p>When a transaction that modifies a tracked table commits, FBDA stores the pre-image of the rows in the archive. FBDA maintains metadata on the current rows and tracks how much data has been archived.</p> <p>FBDA is also responsible for automatically managing the flashback data archive for space, organization (partitioning tablespaces), and retention. FBDA also keeps track of how far the archiving of tracked transactions has progressed.</p> <p><b>See Also:</b> <i>Oracle Database Advanced Application Developer's Guide</i></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Database and ASM instances        |

**Table F–1 (Cont.) Background Processes**

| Name                 | Expanded Name                                        | Short Description                                                                         | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | External Properties                    |
|----------------------|------------------------------------------------------|-------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| FMON                 | File Mapping Monitor Process                         | Manages mapping information for the Oracle Database file mapping interface                | <p>The DBMS_STORAGE_MAP package enables you to control the mapping operations. When instructed by the user, FMON builds mapping information and stores it in the SGA, refreshes the information when a change occurs, saves the information to the data dictionary, and restores it to the SGA at instance startup.</p> <p>FMON is started by the database whenever the FILE_MAPPING initialization parameter is set to <code>true</code>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                        | Database and ASM instances             |
| FSFP                 | Data Guard Broker Fast Start Failover Pinger Process | Maintains fast-start failover state between the primary and target standby databases      | FSFP is created when fast-start failover is enabled.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Database instance, Data Guard          |
| GCR $n$ <sup>1</sup> | Global Conflict Resolution Slave Process             | Performs synchronous tasks on behalf of LMHB                                              | GCR $n$ processes are transient slaves that are started and stopped as required by LMHB to perform synchronous or resource intensive tasks.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Database and ASM instances, Oracle RAC |
| GEN0                 | General Task Execution Process                       | Performs required tasks including SQL and DML                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Database and ASM instances             |
| GMON                 | ASM Disk Group Monitor Process                       | Monitors all mounted ASM disk groups                                                      | GMON monitors all the disk groups mounted in an ASM instance and is responsible for maintaining consistent disk membership and status information. Membership changes result from adding and dropping disks, whereas disk status changes result from taking disks offline or bringing them online.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | ASM instance                           |
| GTX $n$              | Global Transaction Process                           | Provides transparent support for XA global transactions in an Oracle RAC environment      | <p>These processes help maintain the global information about XA global transactions throughout the cluster. Also, the processes help perform two-phase commit for global transactions anywhere in the cluster so that an Oracle RAC database behaves as a single system to the externally coordinated distributed transactions.</p> <p>The GLOBAL_TXN_PROCESSES initialization parameter specifies the number of GTX<math>n</math> processes, where <math>n</math> is 0-9 or a-j. The database automatically tunes the number of these processes based on the workload of XA global transactions. You can disable these processes by setting the parameter to 0. If you try to run XA global transactions with these process disabled, an error is returned.</p> <p><b>See Also:</b> <i>Oracle Real Application Clusters Administration and Deployment Guide</i></p> | Database instance, Oracle RAC          |
| Innn                 | Disk and Tape I/O Slave Process                      | Serves as an I/O slave process spawned on behalf of DBWR, LGWR, or an RMAN backup session | I/O slave process can be configured on platforms where asynchronous I/O support is not available. These slaves are started by setting the corresponding slave enable parameter in the server parameter file. The I/O slaves simulate the asynchronous I/O behavior when the underlying platform does not have native support for asynchronous I/O.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Database instance                      |
| INSV                 | Data Guard Broker Instance Slave Process             | Performs Data Guard broker communication among instances in an Oracle RAC environment     | INSV is created when the DG_BROKER_START initialization parameter is set to <code>true</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Database instance, Data Guard          |
| Jnnn                 | Job Queue Slave Process                              | Executes jobs assigned by the job coordinator                                             | <p>Job slave processes are created or awakened by the job coordinator when it is time for a job to be executed.</p> <p>Job slaves gather all the metadata required to run the job from the data dictionary. The slave processes start a database session as the owner of the job, execute triggers, and then execute the job. After the job is complete, the slave processes commit and then execute appropriate triggers and close the session. The slave can repeat this operation in case additional jobs need to be run.</p>                                                                                                                                                                                                                                                                                                                                      | Database instance                      |

**Table F–1 (Cont.) Background Processes**

| Name             | Expanded Name                                  | Short Description                                                          | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | External Properties                                     |
|------------------|------------------------------------------------|----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|
| LCK0             | Instance Enqueue Background Process            | Manages global enqueue requests and cross-instance broadcasts              | The process handles all requests for resources other than data blocks. For examples, LCK0 manages library and row cache requests.                                                                                                                                                                                                                                                                                                                                                                                                                                | Database and ASM instances, Oracle RAC                  |
| LGWR             | Log Writer Process                             | Writes redo entries to the online redo log                                 | Redo log entries are generated in the redo log buffer of the system global area (SGA). LGWR writes the redo log entries sequentially into a redo log file. If the database has a multiplexed redo log, then LGWR writes the redo log entries to a group of redo log files.<br><br><b>See Also:</b> <i>Oracle Database Concepts</i> and <i>Oracle Database Administrator's Guide</i>                                                                                                                                                                              | Database and ASM instances                              |
| LMD0             | Global Enqueue Service Daemon 0 Process        | Manages incoming remote resource requests from other instances             | LMD0 processes enqueue resources managed under Global Enqueue Service. In particular, LMD0 processes incoming enqueue request messages and controls access to global enqueues. It also performs distributed deadlock detections.                                                                                                                                                                                                                                                                                                                                 | Database and ASM instances, Oracle RAC                  |
| LMHB             | Global Cache/Enqueue Service Heartbeat Monitor | Monitor the heartbeat of LMON, LMD, and LMS <sub>n</sub> processes         | LMHB monitors LMON, LMD, and LMS <sub>n</sub> processes to ensure they are running normally without blocking or spinning.                                                                                                                                                                                                                                                                                                                                                                                                                                        | Database and ASM instances, Oracle RAC                  |
| LMON             | Global Enqueue Service Monitor Process         | Monitors an Oracle RAC cluster to manage global resources                  | LMON maintains instance membership within Oracle RAC. The process detects instance transitions and performs reconfiguration of GES and GCS resources.<br><br><b>See Also:</b> <i>Oracle Real Application Clusters Administration and Deployment Guide</i>                                                                                                                                                                                                                                                                                                        | Database and ASM instances, Oracle RAC                  |
| LMS <sub>n</sub> | Global Cache Service Process                   | Manages resources and provides resource control among Oracle RAC instances | LMS, where <i>n</i> is 0-9 or a-z, maintains a lock database for Global Cache Service (GCS) and buffer cache resources. This process receives, processes, and sends GCS requests, block transfers, and other GCS-related messages.<br><br><b>See Also:</b> <i>Oracle Real Application Clusters Administration and Deployment Guide</i>                                                                                                                                                                                                                           | Database and ASM instances, Oracle RAC                  |
| LSP0             | Logical Standby Coordinator Process            | Schedules transactions for Data Guard SQL Apply                            | LSP0 is the initial process created upon startup of Data Guard SQL Apply. In addition to managing LogMiner and Apply processes, LSP0 is responsible for maintaining inter-transaction dependencies and appropriately scheduling transactions with applier processes. LSP0 is also responsible for detecting and enabling runtime parameter changes for the SQL Apply product as a whole.                                                                                                                                                                         | Database instance, Data Guard                           |
| LSP1             | Logical Standby Dictionary Build Process       | Performs a logical standby dictionary build on a primary database          | The LSP1 process is spawned on a logical standby database that is intended to become the new primary database. A logical standby database becomes a primary database by means of switchover or failover. The dictionary is necessary for logical standby databases to interpret the redo of the new primary database.                                                                                                                                                                                                                                            | Database instance, Data Guard                           |
| LSP2             | Logical Standby Set Guard Process              | Determines which database objects will be protected by the database guard  | The LSP2 process is created as needed during startup of SQL Apply to update the list of objects that are protected by the database guard.                                                                                                                                                                                                                                                                                                                                                                                                                        | Database instance, Data Guard                           |
| Lmn              | Pooled Server Process                          | Handles client requests in Database Resident Connection Pooling            | In Database Resident Connection Pooling, clients connect to a connection broker process. When a connection becomes active, the connection broker hands off the connection to a compatible pooled server process. The pooled server process performs network communication directly on the client connection and processes requests until the client releases the server. After being released, the connection is returned to the broker for monitoring, leaving the server free to handle other clients.<br><br><b>See Also:</b> <i>Oracle Database Concepts</i> | Database instance, Database Resident Connection Pooling |

**Table F–1 (Cont.) Background Processes**

| Name | Expanded Name                                        | Short Description                                                                                           | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | External Properties                                     |
|------|------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|
| MARK | Mark AU for Resynchronization on Coordinator Process | Marks ASM allocation units as stale following a missed write to an offline disk                             | MARK essentially tracks which extents require resynchronization for offline disks. This process runs in the database instance and is started when the database instance first begins using the ASM instance. If required, MARK can also be started on demand when disks go offline in the ASM redundancy disk group.                                                                                                                                                                                                                                         | Database and ASM instances                              |
| MMAN | Memory Manager Process                               | Serves as the instance memory manager                                                                       | This process performs the resizing of memory components on the instance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Database and ASM instances                              |
| MMNL | Manageability Monitor Lite Process                   | Performs tasks relating to manageability, including active session history sampling and metrics computation | MMNL performs many tasks relating to manageability, including session history capture and metrics computation.                                                                                                                                                                                                                                                                                                                                                                                                                                               | Database and ASM instances                              |
| MMON | Manageability Monitor Process                        | Performs or schedules many manageability tasks                                                              | MMON performs many tasks related to manageability, including taking Automatic Workload Repository snapshots and performing Automatic Database Diagnostic Monitor analysis.                                                                                                                                                                                                                                                                                                                                                                                   | Database and ASM instances                              |
| Mnnn | MMON Slave Process                                   | Performs manageability tasks on behalf of MMON                                                              | Mnnn performs manageability tasks dispatched to them by MMON. Tasks performed include taking Automatic Workload Repository snapshots and Automatic Database Diagnostic Monitor analysis.                                                                                                                                                                                                                                                                                                                                                                     | Database and ASM instances                              |
| MRP0 | Managed Standby Recovery Process                     | Coordinates the application of redo on a physical standby database                                          | MRP0 is spawned at the start of redo apply on a physical standby database. This process handles the extraction of redo and coordinates the application of that redo on a physical standby database.<br><b>See Also:</b> <i>Oracle Data Guard Concepts and Administration</i>                                                                                                                                                                                                                                                                                 | Database instance, Data Guard                           |
| MSnn | LogMiner Worker Process                              | Reads redo log files and translates and assembles into transactions                                         | Multiple MSnn processes can exist, where <i>n</i> is 0-9 or A-Z. A minimum of three MSnn processes work as a group to provide transactions to a LogMiner client, for example, a logical standby database. There may be more than one such group, for example, Downstream Capture sessions.                                                                                                                                                                                                                                                                   | Database instance, Logical Standby, Oracle Streams      |
| Nnnn | Connection Broker Process                            | Monitors idle connections and hands off active connections in Database Resident Connection Pooling          | In Database Resident Connection Pooling, clients connect to a connection broker process. When a connection becomes active, the connection broker hands off the connection to a compatible pooled server process. The pooled server process performs network communication directly on the client connection and processes requests until the client releases the server. After being released, the connection is returned to the broker for monitoring, leaving the server free to handle other clients.<br><b>See Also:</b> <i>Oracle Database Concepts</i> | Database instance, Database Resident Connection Pooling |
| NSAn | Redo Transport NSA1 Process                          | Ships redo from current online redo logs to remote standby destinations configured for ASYNC transport      | NSAn can run as multiple processes, where <i>n</i> is 1-9 or A-V.<br><b>See Also:</b> <i>Oracle Data Guard Concepts and Administration</i>                                                                                                                                                                                                                                                                                                                                                                                                                   | Database instance, Data Guard                           |
| NSSn | Redo Transport NSS1 Process                          | Acts as a slave for LGWR when SYNC transport is configured for a remote standby destination                 | NSSn can run as multiple processes, where <i>n</i> is 1-9 or A-V.<br><b>See Also:</b> <i>Oracle Data Guard Concepts and Administration</i>                                                                                                                                                                                                                                                                                                                                                                                                                   | Database instance, Data Guard                           |
| NSVn | Data Guard Broker NetSlave Process                   | Performs broker network communications between databases in a Data Guard environment                        | NSVn is created when a Data Guard broker configuration is enabled. There can be as many NSVn processes (where <i>n</i> is 0-9 and A-U) created as there are databases in the Data Guard broker configuration.                                                                                                                                                                                                                                                                                                                                                | Database instance, Data Guard                           |



**Table F–1 (Cont.) Background Processes**

| Name         | Expanded Name                            | Short Description                                                                                                               | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | External Properties                    |
|--------------|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| OCF <i>n</i> | ASM CF Connection Pool Process           | Maintains a connection to the ASM instance for metadata operations                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Database and ASM instances             |
| On <i>nn</i> | ASM Connection Pool Process              | Maintains a connection to the ASM instance for metadata operations                                                              | On <i>nn</i> slave processes are spawned on demand. These processes communicate with the ASM instance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Database and ASM instances             |
| PING         | Interconnect Latency Measurement Process | Assesses latencies associated with communications for each pair of cluster instances                                            | Every few seconds, the process in one instance sends messages to each instance. The message is received by PING on the target instance. The time for the round trip is measured and collected.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Database and ASM instances, Oracle RAC |
| PMON         | Process Monitor                          | Monitors the other background processes and performs process recovery when a server or dispatcher process terminates abnormally | <p>PMON periodically performs cleanup of all the following:</p> <ul style="list-style-type: none"> <li>Processes that died abnormally</li> <li>Sessions that were killed</li> <li>Detached transactions that have exceeded their idle timeout</li> <li>Detached network connections which have exceeded their idle timeout</li> </ul> <p>In addition, PMON monitors, spawns, and stops the following as needed:</p> <ul style="list-style-type: none"> <li>Dispatcher and shared server processes</li> <li>Job queue processes</li> <li>Pooled server processes for database resident connection pooling</li> <li>Restartable background processes</li> </ul> <p>PMON is also responsible for registering information about the instance and dispatcher processes with the network listener.</p> <p><b>See Also:</b> <i>Oracle Database Concepts</i> and <i>Oracle Database Net Services Administrator's Guide</i></p> | Database and ASM instances             |
| P <i>nnn</i> | Parallel Query Slave Process             | Perform parallel execution of a SQL statement (query, DML, or DDL)                                                              | <p>Parallel Query has two components: a foreground process that acts as query coordinator and a set of parallel slaves (P<i>nnn</i>) that are background processes. These background processes are spawned or reused during the start of a parallel statement. They receive and carry out units of work sent from the query coordinator.</p> <p>The maximum number of P<i>nnn</i> processes is controlled by the initialization parameter PARALLEL_MAX_SERVERS. Slave processes are numbered from 0 to the PARALLEL_MAX_SERVERS setting. If the query is a GV\$ query, then these background processes are numbered backward, starting from PZ99.</p>                                                                                                                                                                                                                                                                  | Database and ASM instances             |
| PR <i>nn</i> | Parallel Recovery Process                | Performs tasks assigned by the coordinator process performing parallel recovery                                                 | PR <i>nn</i> serves as a slave process for the coordinator process performing parallel media recovery and carries out tasks assigned by the coordinator. The default number of these processes is based on number of CPUs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Database instance                      |
| PSP0         | Process Spawner Process                  | Spawns Oracle background processes after initial instance startup                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Database and ASM instances             |

**Table F–1 (Cont.) Background Processes**

| Name        | Expanded Name                     | Short Description                                                                                                   | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | External Properties                 |
|-------------|-----------------------------------|---------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| QMNC        | AQ Coordinator Process            | Monitors AQ                                                                                                         | QMNC is responsible for facilitating various background activities required by AQ and Oracle Streams: time management of messages, management of nonpersistent queues, cleanup of resources, and so on. QMNC dynamically spawns <i>Qnnn</i> processes as needed for performing these tasks.<br><br>Note that if the AQ_TM_PROCESSES initialization parameter is set to 0, this process will not start. The database writes the following message to the alert log: WARNING: AQ_TM_PROCESSES is set to 0. System might be adversely affected.                                                                                                                                                                                                                       | Database instance, Advanced Queuing |
| <i>Qnnn</i> | AQ Server Class Process           | Performs various AQ-related background task for QMNC                                                                | <i>Qnnn</i> acts as a slave process for QMNC and carry out tasks assigned by QMNC. The number of these processes is dynamically managed by QMNC based on load.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Database instance                   |
| RBAL        | ASM Rebalance Master Process      | Coordinates rebalance activity                                                                                      | In an ASM instance, it coordinates rebalance activity for disk groups. In a database instances, it manages ASM disk groups.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Database and ASM instances          |
| RCBG        | Result Cache Background Process   | Handles result cache messages                                                                                       | This process is used for handling invalidation and other messages generated by server processes attached to other instances in Oracle RAC.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Database instance, Oracle RAC       |
| RECO        | Recoverer Process                 | Resolves distributed transactions that are pending because of a network or system failure in a distributed database | RECO uses the information in the pending transaction table to finalize the status of in-doubt transactions. At timed intervals, the local RECO attempts to connect to remote databases and automatically complete the commit or rollback of the local portion of any pending distributed transactions. All transactions automatically resolved by RECO are removed from the pending transaction table.<br><br><b>See Also:</b> <i>Oracle Database Concepts</i> and <i>Oracle Database Net Services Administrator's Guide</i>                                                                                                                                                                                                                                       | Database instance                   |
| RMSn        | Oracle RAC Management Process     | Performs manageability tasks for Oracle RAC                                                                         | RMSn performs a variety of tasks, including creating resources related to Oracle RAC when new instances are added to a cluster.<br><br><b>See Also:</b> <i>Oracle Real Application Clusters Administration and Deployment Guide</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Database instance, Oracle RAC       |
| <i>Rnnn</i> | ASM Block Remap Slave Process     | Remaps a block with a read error                                                                                    | A database instance reading from an ASM disk group can encounter an error during a read. If possible, ASM asynchronously schedules a <i>Rnnn</i> slave process to remap this bad block from a mirror copy.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ASM instance                        |
| RPnn        | Capture Processing Worker Process | Processes a set of workload capture files                                                                           | RPnn are worker processes spawned by calling DBMS_WORKLOAD_REPLAY.PROCESS_CAPTURE(capture_dir, parallel_level). Each worker process is assigned a set of workload capture files to process.<br><br>Worker processes execute in parallel without needing to communicate with each other. After each process is finished processing its assigned files, it exits and informs its parent process.<br><br>The number of worker processes is controlled by the parallel_level parameter of DBMS_WORKLOAD_REPLAY.PROCESS_CAPTURE. By default, parallel_level is null. Then, the number of worker processes is computed as follows:<br><br>SELECT VALUE<br>FROM V\$PARAMETER<br>WHERE NAME='cpu_count';<br><br>When parallel_level is 1, no worker processes are spawned. | Database instance                   |

**Table F–1 (Cont.) Background Processes**

| Name        | Expanded Name                         | Short Description                                                                                                                                                                                   | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | External Properties                   |
|-------------|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| RSM0        | Data Guard Broker Worker Process      | Performs monitoring management tasks related to Data Guard on behalf of DMON                                                                                                                        | The process is created when a Data Guard broker configuration is enabled.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Database instance, Data Guard         |
| RSMN        | Remote Slave Monitor Process          | Manages background slave process creation and communication on remote instances in Oracle RAC                                                                                                       | This background process manages the creation of slave processes and the communication with their coordinators and peers. These background slave processes perform tasks on behalf of a coordinating process running in another cluster instance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Database instance, Oracle RAC         |
| RVWR        | Recovery Writer Process               | Writes flashback data to the flashback logs in the fast recovery area                                                                                                                               | RVWR writes flashback data from the flashback buffer in the SGA to the flashback logs. RVWR also creates flashback logs and performs some tasks for flashback log automatic management.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Database instance, Flashback Database |
| SMCO        | Space Management Coordinator Process  | Coordinates the execution of various space management tasks                                                                                                                                         | This background process coordinates the execution of various space management tasks, including proactive space allocation and space reclamation. SMCO dynamically spawns slave processes ( <i>Wnnn</i> ) to implement these tasks.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Database instance                     |
| SMON        | System Monitor Process                | Performs critical tasks such as instance recovery and dead transaction recovery, and maintenance tasks such as temporary space reclamation, data dictionary cleanup, and undo tablespace management | <p>SMON performs many database maintenance tasks, including the following:</p> <ul style="list-style-type: none"> <li>■ Creates and manages the temporary tablespace metadata</li> <li>■ Reclaims space used by orphaned temporary segments</li> <li>■ Maintains the undo tablespace by online, offline, and shrinking the undo segments based on undo space usage statistics</li> <li>■ Cleans up the data dictionary when it is in a transient and inconsistent state</li> <li>■ Maintains the SCN to time mapping table used to support Oracle Flashback features</li> </ul> <p>In an Oracle RAC database, the SMON process of one instance can perform instance recovery for other instances that have failed.</p> <p>SMON is resilient to internal and external errors raised during background activities.</p> <p><b>See Also:</b> <i>Oracle Database Concepts</i></p>                                                                                                                                                                 | Database instance                     |
| <i>Snnn</i> | Shared Server Process                 | Handles client requests in the shared server architecture                                                                                                                                           | <p>In the shared server architecture, clients connect to a dispatcher process, which creates a virtual circuit for each connection. When the client sends data to the server, the dispatcher receives the data into the virtual circuit and places the active circuit on the common queue to be picked up by an idle shared server. The shared server then reads the data from the virtual circuit and performs the database work necessary to complete the request. When the shared server must send data to the client, the server writes the data back into the virtual circuit and the dispatcher sends the data to the client. After the shared server completes the client request, the server releases the virtual circuit back to the dispatcher and is free to handle other clients.</p> <p>Several initialization parameters relate to shared servers. The principal parameters are: DISPATCHERS, SHARED_SERVERS, MAX_SHARED_SERVERS, LOCAL_LISTENER, REMOTE_LISTENER.</p> <p><b>See Also:</b> <i>Oracle Database Concepts</i></p> | Database instance, shared servers     |
| TEMn        | ASM disk Test Error Emulation Process | Emulates I/O errors on ASM disks through named events                                                                                                                                               | I/O errors can be emulated on ASM disk I/O through named events. The scope can be the process, instance, or even cluster. Optionally, a set of AUs can be chosen for error emulation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | ASM instance                          |

**Table F–1 (Cont.) Background Processes**

| Name         | Expanded Name                                  | Short Description                                                                                              | Long Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | External Properties        |
|--------------|------------------------------------------------|----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| VBG <i>n</i> | Volume Background Process                      | Communicates between the ASM instance and the operating system volume driver                                   | VBG <i>n</i> handles messages originating from the volume driver in the operating system and sends them to the ASM instance.<br><br>VBG <i>n</i> can run as multiple processes, where <i>n</i> is 0-9.                                                                                                                                                                                                                                                                                                                                                                               | ASM instance               |
| VDBG         | Volume Driver Process                          | Forwards ASM requests to perform various volume-related tasks                                                  | VDBG handles requests to lock or unlock an extent for rebalancing, volume resize, disk offline, add or drop a disk, force and dismount disk group to the Dynamic Volume Manager driver.                                                                                                                                                                                                                                                                                                                                                                                              | ASM instance               |
| VKRM         | Virtual Scheduler for Resource Manager Process | Serves as centralized scheduler for Resource Manager activity                                                  | VKRM manages the CPU scheduling for all managed Oracle processes. The process schedules managed processes in accordance with an active resource plan.                                                                                                                                                                                                                                                                                                                                                                                                                                | Database instance          |
| VKTM         | Virtual Keeper of Time Process                 | Provides a wall clock time and reference time for time interval measurements                                   | VKTM acts as a time publisher for an Oracle instance. VKTM publishes two sets of time: a wall clock time using a seconds interval and a higher resolution time (which is not wall clock time) for interval measurements. The VKTM timer service centralizes time tracking and offloads multiple timer calls from other clients.                                                                                                                                                                                                                                                      | Database and ASM instances |
| VMBO         | Volume Membership Process                      | Maintains cluster membership on behalf of the ASM volume driver                                                | This process membership in the cluster as an I/O-capable client on behalf of the ASM volume driver.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | ASM instance               |
| Vnnn         | ASM Volume I/O Slave Process                   | Initializes ASM volume contents during creation                                                                | This process is responsible for initializing the ASM volume during creation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ASM instance               |
| Wnnn         | Space Management Slave Process                 | Performs various background space management tasks, including proactive space allocation and space reclamation | Wnnn processes are slave processes dynamically spawned by SMCO to perform space management tasks in the background. These tasks include preallocating space into locally managed tablespace and SecureFiles segments based on space usage growth analysis, and reclaiming space from dropped segments. At most 10 Wnnn slaves can run on one database instance. After being started, the slave acts as an autonomous agent. After it finishes task execution, it automatically picks up another task from the queue. The process terminates itself after being idle for a long time. | Database instance          |
| XDMG         | Exadata Automation Manager                     | Initiates automation tasks involved in managing Exadata storage                                                | XDMG monitors all configured Exadata cells for state changes, such as a bad disk getting replaced, and performs the required tasks for such events. Its primary tasks are to watch for inaccessible disks and cells and when they become accessible again, and to initiate the ASM ONLINE operation. The ONLINE operation is handled by XDWK.                                                                                                                                                                                                                                        | ASM instance, Exadata      |
| XDWK         | Exadata Automation Manager                     | Performs automation tasks requested by XDMG                                                                    | XDWK gets started when asynchronous actions such as ONLINE, DROP, and ADD an ASM disk are requested by XDMG. After a 5 minute period of inactivity, this process will shut itself down.                                                                                                                                                                                                                                                                                                                                                                                              | ASM instance, Exadata      |
| Xnnn         | ASM Disk Expel Slave Process                   | Performs ASM post-rebalance activities                                                                         | This process expels dropped disks at the end of an ASM rebalance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | ASM instance               |

<sup>1</sup> This background process is available starting with Oracle Database 11g Release 2 (11.2.0.2).

---

# Index

## A

ACTIVE\_INSTANCE\_COUNT initialization  
parameter, 1-19

ALL\_ALL\_TABLES view, 2-5

ALL\_APPLY view, 2-8

ALL\_APPLY\_CHANGE\_HANDLERS view, 2-9

ALL\_APPLY\_CONFLICT\_COLUMNS view, 2-10

ALL\_APPLY\_DML\_HANDLERS view, 2-10

ALL\_APPLY\_ENQUEUE view, 2-11

ALL\_APPLY\_ERROR view, 2-12

ALL\_APPLY\_ERROR\_MESSAGES view, 2-12

ALL\_APPLY\_EXECUTE view, 2-13

ALL\_APPLY\_KEY\_COLUMNS view, 2-13

ALL\_APPLY\_PARAMETERS view, 2-14

ALL\_APPLY\_PROGRESS view, 2-14

ALL\_APPLY\_TABLE\_COLUMNS view, 2-15

ALL\_ARGUMENTS view, 2-16

ALL\_ASSEMBLIES view, 2-17

ALL\_ASSOCIATIONS view, 2-18

ALL\_AUDIT\_POLICIES view, 2-18

ALL\_AUDIT\_POLICY\_COLUMNS view, 2-20

ALL\_AW\_PS view, 2-20

ALL\_AWS view, 2-20

ALL\_BASE\_TABLE\_MVIEWS view, 2-21

ALL\_CAPTURE view, 2-22

ALL\_CAPTURE\_EXTRA\_ATTRIBUTES view, 2-23

ALL\_CAPTURE\_PARAMETERS view, 2-24

ALL\_CAPTURE\_PREPARED\_DATABASE  
view, 2-24

ALL\_CAPTURE\_PREPARED\_SCHEMAS view, 2-25

ALL\_CAPTURE\_PREPARED\_TABLES view, 2-26

ALL\_CATALOG view, 2-27

ALL\_CHANGE\_PROPAGATION\_SETS view, 2-27  
CHANGE\_PROPAGATION\_SETS

synonym, 3-115

ALL\_CHANGE\_PROPAGATIONS view, 2-27

CHANGE\_PROPAGATIONS synonym, 3-115

ALL\_CHANGE\_SETS view, 2-28

CHANGE\_SETS synonym, 3-115

ALL\_CHANGE\_SOURCES view, 2-28

CHANGE\_SOURCES synonym, 3-115

ALL\_CHANGE\_TABLES view, 2-29

CHANGE\_TABLES synonym, 3-115

ALL\_CLUSTER\_HASH\_EXPRESSIONS view, 2-29

ALL\_CLUSTERS view, 2-30

ALL\_COL\_COMMENTS view, 2-31

ALL\_COL\_PENDING\_STATS view, 2-31

ALL\_COL\_PRIVS view, 2-32

ALL\_COL\_PRIVS\_MADE view, 2-33

ALL\_COL\_PRIVS\_RECD view, 2-33

ALL\_COLL\_TYPES view, 2-34

ALL\_CONS\_COLUMNS view, 2-34

ALL\_CONS\_OBJ\_COLUMNS view, 2-35

ALL\_CONSTRAINTS view, 2-35

ALL\_CONTEXT view, 2-37

ALL\_CUBE\_ATTR\_VISIBILITY view, 2-38

ALL\_CUBE\_ATTRIBUTES view, 2-38

ALL\_CUBE\_BUILD\_PROCESSES view, 2-39

ALL\_CUBE\_CALCULATED\_MEMBERS view, 2-39

ALL\_CUBE\_DIM\_LEVELS view, 2-40

ALL\_CUBE\_DIM\_MODELS view, 2-40

ALL\_CUBE\_DIM\_VIEW\_COLUMNS view, 2-41

ALL\_CUBE\_DIM\_VIEWS view, 2-41

ALL\_CUBE\_DIMENSIONALITY view, 2-42

ALL\_CUBE\_DIMENSIONS view, 2-42

ALL\_CUBE\_HIER\_LEVELS view, 2-43

ALL\_CUBE\_HIER\_VIEW\_COLUMNS view, 2-43

ALL\_CUBE\_HIER\_VIEWS view, 2-44

ALL\_CUBE\_HIERARCHIES view, 2-45

ALL\_CUBE\_MEASURES view, 2-46

ALL\_CUBE\_VIEW\_COLUMNS view, 2-46

ALL\_CUBE\_VIEWS view, 2-47

ALL\_CUBES view, 2-47

ALL\_DB\_LINKS view, 2-48

ALL\_DEF\_AUDIT\_OPTS view, 2-48

ALL\_DEPENDENCIES view, 2-49

ALL\_DEQUEUE\_QUEUES view, 2-50

ALL\_DIM\_ATTRIBUTES view, 2-50

ALL\_DIM\_CHILD\_OF view, 2-51

ALL\_DIM\_HIERARCHIES view, 2-51

ALL\_DIM\_JOIN\_KEY view, 2-52

ALL\_DIM\_LEVEL\_KEY view, 2-52

ALL\_DIM\_LEVELS view, 2-52

ALL\_DIMENSIONS view, 2-53

ALL\_DIRECTORIES view, 2-53

ALL\_EDITION\_COMMENTS view, 2-53

ALL\_EDITIONING\_VIEW\_COLS view, 2-54

ALL\_EDITIONING\_VIEW\_COLS\_AE view, 2-54

ALL\_EDITIONING\_VIEWS view, 2-55

ALL\_EDITIONING\_VIEWS\_AE view, 2-55

ALL\_EDITIONS view, 2-56

ALL\_ENCRYPTED\_COLUMNS view, 2-56  
 ALL\_ERRORS view, 2-57  
 ALL\_ERRORS\_AE view, 2-58  
 ALL\_EVALUATION\_CONTEXT\_TABLES view, 2-58  
 ALL\_EVALUATION\_CONTEXT\_VARS view, 2-59  
 ALL\_EVALUATION\_CONTEXTS view, 2-59  
 ALL\_EXTERNAL\_LOCATIONS view, 2-60  
 ALL\_EXTERNAL\_TABLES view, 2-60  
 ALL\_FILE\_GROUP\_EXPORT\_INFO view, 2-61  
 ALL\_FILE\_GROUP\_FILES view, 2-62  
 ALL\_FILE\_GROUP\_TABLES view, 2-62  
 ALL\_FILE\_GROUP\_TABLESPACES view, 2-63  
 ALL\_FILE\_GROUP\_VERSIONS view, 2-63  
 ALL\_FILE\_GROUPS view, 2-64  
 ALL\_HISTOGRAMS synonym for ALL\_TAB\_HISTOGRAMS, 2-64  
 ALL\_IDENTIFIERS view, 2-64  
 ALL\_IND\_COLUMNS view, 2-65  
 ALL\_IND\_EXPRESSIONS view, 2-66  
 ALL\_IND\_PARTITIONS view, 2-66  
 ALL\_IND\_PENDING\_STATS view, 2-69  
 ALL\_IND\_STATISTICS view, 2-69  
 ALL\_IND\_SUBPARTITIONS view, 2-70  
 ALL\_INDEXES view, 2-72  
 ALL\_INDEXTYPE\_ARRAYTYPES view, 2-76  
 ALL\_INDEXTYPE\_COMMENTS view, 2-76  
 ALL\_INDEXTYPE\_OPERATORS view, 2-77  
 ALL\_INDEXTYPES view, 2-77  
 ALL\_INTERNAL\_TRIGGERS view, 2-78  
 ALL\_JAVA\_ARGUMENTS view, 2-78  
 ALL\_JAVA\_CLASSES view, 2-79  
 ALL\_JAVA\_COMPILER\_OPTIONS view, 2-80  
 ALL\_JAVA\_DERIVATIONS view, 2-80  
 ALL\_JAVA\_FIELDS view, 2-81  
 ALL\_JAVA\_IMPLEMENTATIONS view, 2-82  
 ALL\_JAVA\_INNERS view, 2-82  
 ALL\_JAVA\_LAYOUTS view, 2-83  
 ALL\_JAVA\_METHODS view, 2-84  
 ALL\_JAVA\_NCOMPS view, 2-85  
 ALL\_JAVA\_RESOLVERS view, 2-85  
 ALL\_JAVA\_THROWS view, 2-86  
 ALL\_JOBS synonym for USER\_JOBS view, 2-86  
 ALL\_JOIN\_IND\_COLUMNS view, 2-87  
 ALL\_LIBRARIES view, 2-87  
 ALL\_LOB\_PARTITIONS view, 2-88  
 ALL\_LOB\_SUBPARTITIONS view, 2-90  
 ALL\_LOB\_TEMPLATES view, 2-92  
 ALL\_LOBS view, 2-93  
 ALL\_LOG\_GROUP\_COLUMNS view, 2-95  
 ALL\_LOG\_GROUPS view, 2-95  
 ALL\_MEASURE\_FOLDER\_CONTENTS view, 2-96  
 ALL\_MEASURE\_FOLDERS view, 2-96  
 ALL\_METHOD\_PARAMS view, 2-97  
 ALL\_METHOD\_RESULTS view, 2-98  
 ALL\_MINING\_MODEL\_ATTRIBUTES view, 2-98  
 ALL\_MINING\_MODEL\_SETTINGS view, 2-99  
 ALL\_MINING\_MODELS view, 2-100  
 ALL\_MP\_GRAPH\_WORKSPACES view, 2-3  
 ALL\_MP\_PARENT\_WORKSPACES view, 2-3  
 ALL\_MVIEW\_AGGREGATES view, 2-101  
 ALL\_MVIEW\_ANALYSIS view, 2-102  
 ALL\_MVIEW\_COMMENTS view, 2-103  
 ALL\_MVIEW\_DETAIL\_PARTITION view, 2-103  
 ALL\_MVIEW\_DETAIL\_RELATIONS view, 2-104  
 ALL\_MVIEW\_DETAIL\_SUBPARTITION view, 2-105  
 ALL\_MVIEW\_JOINS view, 2-105  
 ALL\_MVIEW\_KEYS view, 2-106  
 ALL\_MVIEW\_LOGS view, 2-107  
 ALL\_MVIEW\_REFRESH\_TIMES view, 2-107  
 ALL\_MVIEWS view, 2-108  
 ALL\_NESTED\_TABLE\_COLS view, 2-111  
 ALL\_NESTED\_TABLES view, 2-113  
 ALL\_OBJ\_COLATTRS view, 2-113  
 ALL\_OBJECT\_TABLES view, 2-114  
 ALL\_OBJECTS view, 2-117  
 ALL\_OBJECTS\_AE view, 2-117  
 ALL\_OPANCILLARY view, 2-118  
 ALL\_OPARGUMENTS view, 2-119  
 ALL\_OPBINDINGS view, 2-119  
 ALL\_OPERATOR\_COMMENTS view, 2-120  
 ALL\_OPERATORS view, 2-120  
 ALL\_OUTLINE\_HINTS synonym for USER\_OUTLINE\_HINTS view, 2-121  
 ALL\_OUTLINES synonym for USER\_OUTLINES view, 2-121  
 ALL\_PART\_COL\_STATISTICS view, 3-1  
 ALL\_PART\_HISTOGRAMS view, 3-2  
 ALL\_PART\_INDEXES view, 3-3  
 ALL\_PART\_KEY\_COLUMNS view, 3-5  
 ALL\_PART\_LOBS view, 3-5  
 ALL\_PART\_TABLES view, 3-8  
 ALL\_PARTIAL\_DROP\_TABS view, 3-11  
 ALL\_PENDING\_CONV\_TABLES view, 3-11  
 ALL\_PLSQL\_OBJECT\_SETTINGS view, 3-11  
 ALL\_POLICIES view, 3-12  
 ALL\_POLICY\_CONTEXTS view, 3-13  
 ALL\_POLICY\_GROUPS view, 3-14  
 ALL\_PROCEDURES view, 3-14  
 ALL\_PROPAGATION view, 3-15  
 ALL\_PUBLISHED\_COLUMNS synonym for USER\_PUBLISHED\_COLUMNS view, 3-16  
 ALL\_QUEUE\_SCHEDULES view, 3-16  
 ALL\_QUEUE\_SUBSCRIBERS view, 3-18  
 ALL\_QUEUE\_TABLES view, 3-18  
 ALL\_QUEUES view, 3-19  
 ALL\_REFRESH view, 3-20  
 ALL\_REFRESH\_CHILDREN view, 3-21  
 ALL\_REFRESH\_DEPENDENCIES view, 3-21  
 ALL\_REFS view, 3-22  
 ALL\_REGISTERED\_MVIEWS view, 3-22  
 ALL\_REGISTRY\_BANNERS view, 3-23  
 ALL\_REMOVED\_WORKSPACES view, 2-3  
 ALL\_REPCAT view, 2-2  
 ALL\_REPCAT\_REFRESH\_TEMPLATES view, 2-2  
 ALL\_REPCAT\_TEMPLATE\_OBJECTS view, 2-2  
 ALL\_REPCAT\_TEMPLATE\_PARAMS view, 2-2  
 ALL\_REPCAT\_TEMPLATE\_SITES view, 2-2  
 ALL\_REPCAT\_USER\_AUTHORIZATIONS

view, 2-2

ALL\_REPCAT\_USER\_PARM\_VALUES view, 2-2

ALL\_REPCATALOG view, 2-2

ALL\_REPCOLUMN view, 2-2

ALL\_REPCOLUMN\_GROUP view, 2-2

ALL\_REPCONFLICT view, 2-2

ALL\_REPDDL view, 2-2

ALL\_REPFLAVOR\_COLUMNS view, 2-2

ALL\_REPFLAVOR\_OBJECTS view, 2-2

ALL\_REPFLAVORS view, 2-2

ALL\_REPGENERATED view, 2-2

ALL\_REPGENOBJECTS view, 2-2

ALL\_REPGROUP view, 2-2

ALL\_REPGROUP\_PRIVILEGES view, 2-2

ALL\_REPGROUPED\_COLUMN view, 2-2

ALL\_REPKEY\_COLUMNS view, 2-2

ALL\_REPOBJECT view, 2-2

ALL\_REPPARAMETER\_COLUMN view, 2-2

ALL\_REPPRIORITY view, 2-2

ALL\_REPPRIORITY\_GROUP view, 2-2

ALL\_REPPROP view, 2-2

ALL\_REPRESOL\_STATS\_CONTROL view, 2-2

ALL\_REPRESOLUTION view, 2-2

ALL\_REPRESOLUTION\_METHOD view, 2-2

ALL\_REPRESOLUTION\_STATISTICS view, 2-2

ALL\_REPSHEMA view, 2-2

ALL\_REPSITES view, 2-2

ALL\_REWRITE\_EQUIVALENCES view, 3-23

ALL\_RULE\_SET\_RULES view, 3-24

ALL\_RULE\_SETS view, 3-24

ALL\_RULES view, 3-25

ALL\_SCHEDULER\_CHAIN\_RULES view, 3-25

ALL\_SCHEDULER\_CHAIN\_STEPS view, 3-26

ALL\_SCHEDULER\_CHAINS view, 3-27

ALL\_SCHEDULER\_CREDENTIALS view, 3-28

ALL\_SCHEDULER\_DB\_DESTS view, 3-28

ALL\_SCHEDULER\_DESTS view, 3-29

ALL\_SCHEDULER\_EXTERNAL\_DESTS view, 3-29

ALL\_SCHEDULER\_FILE\_WATCHERS view, 3-30

ALL\_SCHEDULER\_GLOBAL\_ATTRIBUTE view, 3-31

ALL\_SCHEDULER\_GROUP\_MEMBERS view, 3-31

ALL\_SCHEDULER\_GROUPS view, 3-31

ALL\_SCHEDULER\_JOB\_ARGS view, 3-32

ALL\_SCHEDULER\_JOB\_CLASSES view, 3-33

ALL\_SCHEDULER\_JOB\_DESTS view, 3-33

ALL\_SCHEDULER\_JOB\_LOG view, 3-34

ALL\_SCHEDULER\_JOB\_RUN\_DETAILS view, 3-35

ALL\_SCHEDULER\_JOBS view, 3-36

ALL\_SCHEDULER\_NOTIFICATIONS view, 3-39

ALL\_SCHEDULER\_PROGRAM\_ARGS view, 3-40

ALL\_SCHEDULER\_PROGRAMS view, 3-41

ALL\_SCHEDULER\_REMOTE\_DATABASES view, 3-42

ALL\_SCHEDULER\_REMOTE\_JOBSTATE view, 3-42

ALL\_SCHEDULER\_RUNNING\_CHAINS view, 3-43

ALL\_SCHEDULER\_RUNNING\_JOBS view, 3-44

ALL\_SCHEDULER\_SCHEDULES view, 3-45

ALL\_SCHEDULER\_WINDOW\_DETAILS view, 3-46

ALL\_SCHEDULER\_WINDOW\_GROUPS view, 3-47

ALL\_SCHEDULER\_WINDOW\_LOG view, 3-47

ALL\_SCHEDULER\_WINDOWS view, 3-48

ALL\_SCHEDULER\_WINDOWGROUP\_MEMBERS view, 3-49

ALL\_SEC\_RELEVANT\_COLS view, 3-49

ALL\_SECONDARY\_OBJECTS view, 3-49

ALL\_SEQUENCES view, 3-50

ALL\_SERVICES view, 3-50

ALL\_SOURCE view, 3-51

ALL\_SOURCE\_AE view, 3-52

ALL\_SOURCE\_TABLES synonym for USER\_SOURCE\_TABLES view, 3-52

ALL\_SQLJ\_TYPE\_ATTRS view, 3-52

ALL\_SQLJ\_TYPE\_METHODS view, 3-53

ALL\_SQLJ\_TYPES view, 3-54

ALL\_SQLSET view, 3-55

ALL\_SQLSET\_BINDS view, 3-55

ALL\_SQLSET\_PLANS view, 3-56

ALL\_SQLSET\_REFERENCES view, 3-59

ALL\_SQLSET\_STATEMENTS view, 3-60

ALL\_STAT\_EXTENSIONS view, 3-61

ALL\_STORED\_SETTINGS view, 3-62

ALL\_STREAMS\_COLUMNS view, 3-62

ALL\_STREAMS\_GLOBAL\_RULES view, 3-63

ALL\_STREAMS\_MESSAGE\_CONSUMERS view, 3-64

ALL\_STREAMS\_MESSAGE\_RULES view, 3-64

ALL\_STREAMS\_NEWLY\_SUPPORTED view, 3-65

ALL\_STREAMS\_RULES view, 3-65

ALL\_STREAMS\_SCHEMA\_RULES view, 3-67

ALL\_STREAMS\_STMT\_HANDLERS view, 3-67

ALL\_STREAMS\_STMTS view, 3-68

ALL\_STREAMS\_TABLE\_RULES view, 3-68

ALL\_STREAMS\_TRANSFORM\_FUNCTION view, 3-70

ALL\_STREAMS\_UNSUPPORTED view, 3-70

ALL\_SUBPART\_COL\_STATISTICS view, 3-71

ALL\_SUBPART\_HISTOGRAMS view, 3-72

ALL\_SUBPART\_KEY\_COLUMNS view, 3-73

ALL\_SUBPARTITION\_TEMPLATES view, 3-73

ALL\_SUBSCRIBED\_COLUMNS synonym for USER\_SUBSCRIBED\_COLUMNS view, 3-74

ALL\_SUBSCRIBED\_TABLES synonym for USER\_SUBSCRIBED\_TABLES view, 3-74

ALL\_SUBSCRIPTIONS synonym for USER\_SUBSCRIPTIONS view, 3-74

ALL\_SUMDELTA view, 3-74

ALL\_SYNC\_CAPTURE view, 3-74

ALL\_SYNC\_CAPTURE\_PREPARED\_TABS view, 3-75

ALL\_SYNC\_CAPTURE\_TABLES view, 3-75

ALL\_SYNONYMS view, 3-75

ALL\_TAB\_COL\_STATISTICS view, 3-77

ALL\_TAB\_COLS view, 3-77

ALL\_TAB\_COLUMNS view, 3-79

ALL\_TAB\_COMMENTS view, 3-81

ALL\_TAB\_HISTGRM\_PENDING\_STATS view, 3-81

- ALL\_TAB\_HISTOGRAMS view, 3-82
  - ALL\_HISTOGRAMS synonym, 2-64
- ALL\_TAB\_MODIFICATIONS view, 3-82
- ALL\_TAB\_PARTITIONS view, 3-83
- ALL\_TAB\_PENDING\_STATS view, 3-86
- ALL\_TAB\_PRIVS view, 3-86
- ALL\_TAB\_PRIVS\_MADE view, 3-87
- ALL\_TAB\_PRIVS\_RECD view, 3-87
- ALL\_TAB\_STAT\_PREFS view, 3-88
- ALL\_TAB\_STATISTICS view, 3-88
- ALL\_TAB\_STATS\_HISTORY view, 3-89
- ALL\_TAB\_SUBPARTITIONS view, 3-89
- ALL\_TABLES view, 3-91
- ALL\_TRIGGER\_COLS view, 3-94
- ALL\_TRIGGER\_ORDERING view, 3-95
- ALL\_TRIGGERS view, 3-96
- ALL\_TSTZ\_TAB\_COLS view, 3-97
- ALL\_TSTZ\_TABLES view, 3-98
- ALL\_TYPE\_ATTRS view, 3-98
- ALL\_TYPE\_METHODS view, 3-99
- ALL\_TYPE\_VERSIONS view, 3-100
- ALL\_TYPES view, 3-101
- ALL\_UNUSED\_COL\_TABS view, 3-101
- ALL\_UPDATABLE\_COLUMNS view, 3-102
- ALL\_USERS view, 3-102
- ALL\_USTATS view, 3-103
- ALL\_VARRAYS view, 3-103
- ALL\_VERSION\_HVIEW view, 2-3
- ALL\_VIEWS view, 3-104
- ALL\_VIEWS\_AE view, 3-105
- ALL\_WARNING\_SETTINGS view, 3-105
- ALL\_WM\_CONS\_COLUMNS view, 2-3
- ALL\_WM\_CONSTRAINTS view, 2-3
- ALL\_WM\_IND\_COLUMNS view, 2-3
- ALL\_WM\_IND\_EXPRESSIONS view, 2-3
- ALL\_WM\_LOCKED\_TABLES view, 2-3
- ALL\_WM\_MODIFIED\_TABLES view, 2-3
- ALL\_WM\_RIC\_INFO view, 2-3
- ALL\_WM\_TAB\_TRIGGERS view, 2-3
- ALL\_WM\_VERSIONED\_TABLES view, 2-3
- ALL\_WM\_VT\_ERRORS view, 2-3
- ALL\_WORKSPACE\_PRIVS view, 2-3
- ALL\_WORKSPACE\_SAVEPOINTS view, 2-3
- ALL\_WORKSPACES view, 2-3
- ALL\_XML\_INDEXES view, 3-106
- ALL\_XML\_SCHEMAS view, 3-107
- ALL\_XML\_TAB\_COLS view, 3-108
- ALL\_XML\_TABLES view, 3-109
- ALL\_XML\_VIEW\_COLS view, 3-109
- ALL\_XML\_VIEWS view, 3-110
- ALL\_XSTREAM\_INBOUND view, 3-110
- ALL\_XSTREAM\_INBOUND\_PROGRESS view, 3-111
- ALL\_XSTREAM\_OUTBOUND view, 3-112
- ALL\_XSTREAM\_OUTBOUND\_PROGRESS view, 3-113
- ALL\_XSTREAM\_RULES view, 3-113
- ALLOCATE EXTENT clause
  - of ALTER TABLE
    - instance number, 1-77

- ALTER DATABASE statement
  - ADD LOGFILE, 1-172
  - ENABLE THREAD, 1-172
  - THREAD, 1-172
- ALTER TABLE statement
  - allocating extents, 1-77
- ANALYZE statement, 2-72, 2-111, 3-77, 3-79, 3-91, 5-44, 5-61, 6-17, 6-19, 6-87, 6-102, 6-103, 6-105
- AQ\_TM\_PROCESSES initialization parameter, 1-20
- ARCHIVE LOG START statement
  - automatic archiving, 1-87
- ARCHIVE\_LAG\_TARGET initialization parameter, 1-21
- archived redo logs
  - destination file, 1-87
  - storage device, 1-87, 1-93
- ARCHIVELOG mode, 1-87
  - archiving destination, 1-87, 1-93
- ASM\_DISKGROUPS initialization parameter, 1-21
- ASM\_DISKSTRING initialization parameter, 1-22
- ASM\_POWER\_LIMIT initialization parameter, 1-23
- ASM\_PREFERRED\_READ\_FAILURE\_GROUPS initialization parameter, 1-23
- AUDIT\_ACTIONS table, 3-114
- AUDIT\_FILE\_DEST initialization parameter, 1-23
- AUDIT\_SYS\_OPERATIONS initialization parameter, 1-24
- AUDIT\_SYSLOG\_LEVEL initialization parameter, 1-24
- AUDIT\_TRAIL initialization parameter, 1-25
- authenticating remote clients, 1-147
- authenticating users, 1-124
- AWR\_SNAPSHOT\_TIME\_OFFSET initialization parameter, 1-26

## B

- BACKGROUND\_CORE\_DUMP initialization parameter, 1-27
- BACKGROUND\_DUMP\_DEST initialization parameter, 1-27
- BACKUP\_TAPE\_IO\_SLAVES initialization parameter, 1-28
- BITMAP\_MERGE\_AREA\_SIZE initialization parameter, 1-29
- BLANK\_TRIMMING initialization parameter, 1-29
- blocks
  - redo log, 1-98
  - size, 1-43, 1-46, 1-53

## C

- cache
  - dictionary, 8-93, 8-94
  - statistics, 1-98
- CAT synonym for USER\_CATALOG view, 3-114
- CATALOG view, 3-115
- CATALOG.SQL script, B-1
  - creating V\$ views, 7-1
- CATBLOCK.SQL script, B-2



- CATCLUST.SQL script, B-1
- CATDWGRD.SQL script, B-4
- CATEXP7.SQL script, B-2
- CATHS.SQL script, B-2
- CATIO.SQL script, B-2
- CATJAVA.SQL script, B-5
- CATNOADT.SQL script, B-4
- CATNOAUD.SQL script, B-4
- CATNOHS.SQL script, B-4
- CATNOPRT.SQL script, B-4
- CATNOSVM.SQL script, B-4
- CATNSNMP.SQL script, B-4
- CATOCTK.SQL script, B-2
- CATPROC.SQL script, B-1
- CATQUEUE.SQL script, B-2
- CATREP.SQL script, B-2
- CATUPGRD.SQL script, B-5
- CHAINED\_ROWS table, 3-115
- CHANGE\_PROPAGATION\_SETS synonym for ALL\_CHANGE\_PROPAGATION\_SETS view, 3-115
- CHANGE\_PROPAGATIONS synonym for ALL\_CHANGE\_PROPAGATIONS view, 3-115
- CHANGE\_SETS synonym for ALL\_CHANGE\_SETS view, 3-115
- CHANGE\_SOURCES synonym for ALL\_CHANGE\_SOURCES view, 3-115
- CHANGE\_TABLES synonym for ALL\_CHANGE\_TABLES view, 3-115
- characters
  - numeric group separators, 1-111
- checkpoints
  - checkpoint interval, 1-98
  - statistics, 1-98
- CIRCUITS initialization parameter, 1-30
- CLIENT\_RESULT\_CACHE\_LAG initialization parameter, 1-30
- CLIENT\_RESULT\_CACHE\_SIZE initialization parameter, 1-30
- CLIENT\_RESULT\_CACHE\_STATS\$ view, 3-116
- CLU synonym for USER\_CLUSTERS view, 3-116
- CLUSTER\_DATABASE initialization parameter, 1-31
- CLUSTER\_DATABASE\_INSTANCES initialization parameter, 1-31
- CLUSTER\_INTERCONNECTS initialization parameter, 1-32
- COL view, 3-116
- COLS synonym for USER\_TAB\_COLUMNS view, 3-116
- COMMIT\_LOGGING initialization parameter, 1-33
- COMMIT\_POINT\_STRENGTH initialization parameter, 1-33
- COMMIT\_WAIT initialization parameter, 1-34
- COMMIT\_WRITE initialization parameter, 1-34
- COMPATIBLE initialization parameter, 1-35
- contention
  - block-level, 9-94
- control files
  - names, 1-37
  - specifying, 1-37

- CONTROL\_FILE\_RECORD\_KEEP\_TIME
  - initialization parameter, 1-36
- CONTROL\_FILES initialization parameter, 1-36
- CONTROL\_MANAGEMENT\_PACK\_ACCESS
  - initialization parameter, 1-37
- CORE\_DUMP\_DEST initialization parameter, 1-38
- cost-based optimization, 1-122
  - favoring IN-list iterators, 1-121
- CPU\_COUNT initialization parameter, 1-38
- CREATE TABLE statement
  - FREELIST GROUPS clause, 1-77
- CREATE\_BITMAP\_AREA\_SIZE initialization parameter, 1-39
- CREATE\_STORED\_OUTLINES initialization parameter, 1-39
- creating
  - a database
    - setting block size, 1-43, 1-46, 1-53
- currency, 1-105, 1-106
  - international currency symbol, 1-109
- CURSOR\_BIND\_CAPTURE\_DESTINATION
  - initialization parameter, 1-40
- CURSOR\_SHARING initialization parameter, 1-41
- CURSOR\_SPACE\_FOR\_TIME initialization parameter, 1-41
- cursors
  - OPEN\_CURSORS initialization parameter, 1-117
  - shared pool, 1-161

## D

- data blocks
  - reading multiple, 1-50
  - size of, 1-43, 1-46, 1-53
- data dictionary, 2-1
  - cache, 8-93, 8-94
  - scripts, B-2
  - SQL scripts, B-1
  - tables, 2-1
  - views
    - overview, 2-1
    - user views, 2-1
- database writer process (DBWR)
  - checkpoint, 1-98
- DATABASE\_PROPERTIES view, 3-116
- databases
  - database limits, A-1
  - default language, 1-110
  - resource limits, 1-148, 1-149
- datafiles
  - maximum number, 1-51
  - parameter, 1-51
- dates
  - language used for, 1-108, 1-114, 1-115
  - setting SYSDATE, 1-72
  - TO\_CHAR function, 1-107
  - TO\_DATE function, 1-107
- DB\_BLOCK\_BUFFERS initialization parameter, 1-43
- DB\_BLOCK\_CHECKING initialization parameter, 1-44

DB\_BLOCK\_CHECKSUM initialization  
     parameter, 1-44  
 DB\_BLOCK\_SIZE initialization parameter, 1-45  
 DB\_CACHE\_ADVICE initialization parameter, 1-46  
 DB\_CACHE\_SIZE initialization parameter, 1-47  
 DB\_CREATE\_FILE\_DEST initialization  
     parameter, 1-47  
 DB\_CREATE\_ONLINE\_LOG\_DEST\_# initialization  
     parameter, 1-48  
 DB\_DOMAIN initialization parameter, 1-48  
 DB\_FILE\_MULTIBLOCK\_READ\_COUNT  
     initialization parameter, 1-49  
 DB\_FILE\_NAME\_CONVERT initialization  
     parameter, 1-50  
 DB\_FILES initialization parameter, 1-51  
 DB\_FLASH\_CACHE\_FILE initialization  
     parameter, 1-52  
 DB\_FLASH\_CACHE\_SIZE initialization  
     parameter, 1-52  
 DB\_FLASHBACK\_RETENTION\_TARGET  
     initialization parameter, 1-53  
 DB\_KEEP\_CACHE\_SIZE initialization  
     parameter, 1-53  
 DB\_LOST\_WRITE\_PROTECT initialization  
     parameter, 1-53  
 DB\_NAME initialization parameter, 1-54  
 DB\_#K\_CACHE\_SIZE initialization parameter, 1-42  
 DB\_RECOVERY\_FILE\_DEST initialization  
     parameter, 1-55  
 DB\_RECOVERY\_FILE\_DEST\_SIZE initialization  
     parameter, 1-55  
 DB\_RECYCLE\_CACHE\_SIZE initialization  
     parameter, 1-56  
 DB\_SECUREFILE initialization parameter, 1-56  
 DB\_ULTRA\_SAFE initialization parameter, 1-57  
 DB\_UNIQUE\_NAME initialization parameter, 1-58  
 DB\_UNRECOVERABLE\_SCN\_TRACKING  
     initialization parameter, 1-58  
 DB\_WRITER\_PROCESSES initialization  
     parameter, 1-59  
 DBA\_2PC\_NEIGHBORS view, 4-1  
 DBA\_2PC\_PENDING view, 4-1  
 DBA\_ADDM\_FDG\_BREAKDOWN view, 4-2  
 DBA\_ADDM\_FINDINGS view, 4-2  
 DBA\_ADDM\_INSTANCES view, 4-3  
 DBA\_ADDM\_SYSTEM\_DIRECTIVES view, 4-4  
 DBA\_ADDM\_TASK\_DIRECTIVES view, 4-4  
 DBA\_ADDM\_TASKS view, 4-5  
 DBA\_ADVISOR\_ACTIONS view, 4-7  
 DBA\_ADVISOR\_COMMANDS view, 4-8  
 DBA\_ADVISOR\_DEF\_PARAMETERS view, 4-8  
 DBA\_ADVISOR\_DEFINITIONS view, 4-9  
 DBA\_ADVISOR\_DIR\_DEFINITIONS view, 4-9  
 DBA\_ADVISOR\_DIR\_INSTANCES view, 4-10  
 DBA\_ADVISOR\_DIR\_TASK\_INST view, 4-10  
 DBA\_ADVISOR\_EXEC\_PARAMETERS view, 4-11  
 DBA\_ADVISOR\_EXECUTION\_TYPES view, 4-12  
 DBA\_ADVISOR\_EXECUTIONS view, 4-12  
 DBA\_ADVISOR\_FDG\_BREAKDOWN view, 4-13  
 DBA\_ADVISOR\_FINDING\_NAMES view, 4-13  
 DBA\_ADVISOR\_FINDINGS view, 4-13  
 DBA\_ADVISOR\_JOURNAL view, 4-14  
 DBA\_ADVISOR\_LOG view, 4-15  
 DBA\_ADVISOR\_OBJECT\_TYPES view, 4-15  
 DBA\_ADVISOR\_OBJECTS view, 4-16  
 DBA\_ADVISOR\_PARAMETERS view, 4-17  
 DBA\_ADVISOR\_RATIONALE view, 4-18  
 DBA\_ADVISOR\_RECOMMENDATIONS view, 4-19  
 DBA\_ADVISOR\_SQLA\_REC\_SUM view, 4-20  
 DBA\_ADVISOR\_SQLA\_TABLES view, 4-21  
 DBA\_ADVISOR\_SQLA\_WK\_MAP view, 4-21  
 DBA\_ADVISOR\_SQLA\_WK\_STMTS view, 4-21  
 DBA\_ADVISOR\_SQLPLANS view, 4-23  
 DBA\_ADVISOR\_SQLSTATS view, 4-25  
 DBA\_ADVISOR\_SQLW\_JOURNAL view, 4-26  
 DBA\_ADVISOR\_SQLW\_PARAMETERS view, 4-27  
 DBA\_ADVISOR\_SQLW\_STMTS view, 4-27  
 DBA\_ADVISOR\_SQLW\_SUM view, 4-28  
 DBA\_ADVISOR\_SQLW\_TABLES view, 4-29  
 DBA\_ADVISOR\_SQLW\_TEMPLATES view, 4-29  
 DBA\_ADVISOR\_TASKS view, 4-30  
 DBA\_ADVISOR\_TEMPLATES view, 4-31  
 DBA\_ADVISOR\_USAGE view, 4-32  
 DBA\_ALERT\_HISTORY view, 4-32  
 DBA\_ALL\_TABLES view, 4-33  
 DBA\_APPLICATION\_ROLES view, 4-33  
 DBA\_APPLY view, 4-33  
 DBA\_APPLY\_CHANGE\_HANDLERS view, 4-33  
 DBA\_APPLY\_CONFLICT\_COLUMNS view, 4-33  
 DBA\_APPLY\_DML\_HANDLERS view, 4-34  
 DBA\_APPLY\_ENQUEUE view, 4-34  
 DBA\_APPLY\_ERROR view, 4-34  
 DBA\_APPLY\_ERROR\_MESSAGES view, 4-34  
 DBA\_APPLY\_EXECUTE view, 4-34  
 DBA\_APPLY\_INSTANTIATED\_GLOBAL  
     view, 4-34  
 DBA\_APPLY\_INSTANTIATED\_OBJECTS  
     view, 4-35  
 DBA\_APPLY\_INSTANTIATED\_SCHEMAS  
     view, 4-35  
 DBA\_APPLY\_KEY\_COLUMNS view, 4-35  
 DBA\_APPLY\_OBJECT\_DEPENDENCIES view, 4-35  
 DBA\_APPLY\_PARAMETERS view, 4-36  
 DBA\_APPLY\_PROGRESS view, 4-36  
 DBA\_APPLY\_SPILL\_TXN view, 4-36  
 DBA\_APPLY\_TABLE\_COLUMNS view, 4-36  
 DBA\_APPLY\_VALUE\_DEPENDENCIES view, 4-37  
 DBA\_AQ\_AGENT\_PRIVS view, 4-37  
 DBA\_AQ\_AGENTS view, 4-37  
 DBA\_ARGUMENTS view, 4-37  
 DBA\_ASSEMBLIES view, 4-38  
 DBA\_ASSOCIATIONS view, 4-38  
 DBA\_ATTRIBUTE\_TRANSFORMATIONS  
     view, 4-38  
 DBA\_AUDIT\_EXISTS view, 4-38  
 DBA\_AUDIT\_MGMT\_CLEAN\_EVENTS view, 4-40  
 DBA\_AUDIT\_MGMT\_CLEANUP\_JOBS view, 4-40  
 DBA\_AUDIT\_MGMT\_CONFIG\_PARAMS  
     view, 4-40  
 DBA\_AUDIT\_MGMT\_LAST\_ARCH\_TS view, 4-41

DBA\_AUDIT\_OBJECT view, 4-41  
 DBA\_AUDIT\_POLICIES view, 4-43  
 DBA\_AUDIT\_POLICY\_COLUMNS view, 4-43  
 DBA\_AUDIT\_SESSION view, 4-43  
 DBA\_AUDIT\_STATEMENT view, 4-44  
 DBA\_AUDIT\_TRAIL view, 4-45  
 DBA\_AUTO\_SEGADV\_CTL view, 4-47  
 DBA\_AUTO\_SEGADV\_SUMMARY view, 4-48  
 DBA\_AUTOTASK\_CLIENT view, 4-48  
 DBA\_AUTOTASK\_CLIENT\_HISTORY view, 4-49  
 DBA\_AUTOTASK\_CLIENT\_JOB view, 4-50  
 DBA\_AUTOTASK\_JOB\_HISTORY view, 4-50  
 DBA\_AUTOTASK\_OPERATION view, 4-51  
 DBA\_AUTOTASK\_SCHEDULE view, 4-51  
 DBA\_AUTOTASK\_TASK view, 4-51  
 DBA\_AUTOTASK\_WINDOW\_CLIENTS view, 4-54  
 DBA\_AUTOTASK\_WINDOW\_HISTORY view, 4-55  
 DBA\_AW\_PS view, 4-55  
 DBA\_AWS view, 4-55  
 DBA\_BASE\_TABLE\_MVIEWS view, 4-55  
 DBA\_BLOCKERS view, 4-55  
 DBA\_CAPTURE view, 4-55  
 DBA\_CAPTURE\_EXTRA\_ATTRIBUTES view, 4-55  
 DBA\_CAPTURE\_PARAMETERS view, 4-56  
 DBA\_CAPTURE\_PREPARED\_DATABASE  
     view, 4-56  
 DBA\_CAPTURE\_PREPARED\_SCHEMAS  
     view, 4-56  
 DBA\_CAPTURE\_PREPARED\_TABLES view, 4-56  
 DBA\_CATALOG view, 4-56  
 DBA\_CHANGE\_NOTIFICATION\_REGS view, 4-57  
 DBA\_CLU\_COLUMNS view, 4-57  
 DBA\_CLUSTER\_HASH\_EXPRESSIONS view, 4-57  
 DBA\_CLUSTERS view, 4-57  
 DBA\_COL\_COMMENTS view, 4-58  
 DBA\_COL\_PENDING\_STATS view, 4-58  
 DBA\_COL\_PRIVS view, 4-58  
 DBA\_COLL\_TYPES view, 4-58  
 DBA\_COMMON\_AUDIT\_TRAIL view, 4-58  
 DBA\_COMPARISON view, 4-60  
 DBA\_COMPARISON\_COLUMNS view, 4-61  
 DBA\_COMPARISON\_ROW\_DIF view, 4-62  
 DBA\_COMPARISON\_SCAN view, 4-62  
 DBA\_COMPARISON\_SCAN\_VALUES view, 4-63  
 DBA\_CONNECT\_ROLE\_GRANTEES view, 4-63  
 DBA\_CONS\_OBJ\_COLUMNS view, 4-64  
 DBA\_CONSTRAINTS view, 4-64  
 DBA\_CONTEXT view, 4-64  
 DBA\_CPOOL\_INFO view, 4-64  
 DBA\_CPU\_USAGE\_STATISTICS view, 4-64  
 DBA\_CQ\_NOTIFICATION\_QUERIES view, 4-65  
 DBA\_CUBE\_ATTR\_VISIBILITY view, 4-65  
 DBA\_CUBE\_ATTRIBUTES view, 4-65  
 DBA\_CUBE\_BUILD\_PROCESSES view, 4-65  
 DBA\_CUBE\_CALCULATED\_MEMBERS view, 4-66  
 DBA\_CUBE\_DIM\_LEVELS view, 4-66  
 DBA\_CUBE\_DIM\_MODELS view, 4-66  
 DBA\_CUBE\_DIM\_VIEW\_COLUMNS view, 4-66  
 DBA\_CUBE\_DIM\_VIEWS view, 4-66  
 DBA\_CUBE\_DIMENSIONALITY view, 4-66  
 DBA\_CUBE\_DIMENSIONS view, 4-66  
 DBA\_CUBE\_HIER\_LEVELS view, 4-66  
 DBA\_CUBE\_HIER\_VIEW\_COLUMNS view, 4-67  
 DBA\_CUBE\_HIER\_VIEWS view, 4-67  
 DBA\_CUBE\_HIERARCHIES view, 4-67  
 DBA\_CUBE\_MEASURES view, 4-67  
 DBA\_CUBE\_VIEW\_COLUMNS view, 4-67  
 DBA\_CUBE\_VIEWS view, 4-67  
 DBA\_CUBES view, 4-67  
 DBA\_DATA\_FILES view, 4-68  
 DBA\_DATAPUMP\_JOBS view, 4-68  
 DBA\_DATAPUMP\_SESSIONS view, 4-69  
 DBA\_DB\_LINKS view, 4-69  
 DBA\_DDL\_LOCKS view, 4-69  
 DBA\_DEPENDENCIES view, 4-70  
 DBA\_DIM\_ATTRIBUTES view, 4-70  
 DBA\_DIM\_CHILD\_OF view, 4-70  
 DBA\_DIM\_HIERARCHIES view, 4-70  
 DBA\_DIM\_JOIN\_KEY view, 4-70  
 DBA\_DIM\_LEVEL\_KEY view, 4-71  
 DBA\_DIM\_LEVELS view, 4-71  
 DBA\_DIMENSIONS view, 4-71  
 DBA\_DIRECTORIES view, 4-71  
 DBA\_DML\_LOCKS view, 4-71  
 DBA\_DMT\_FREE\_SPACE view, 4-72  
 DBA\_DMT\_USED\_EXTENTS view, 4-72  
 DBA\_EDITION\_COMMENTS view, 4-72  
 DBA\_EDITIONING\_VIEW\_COLS view, 4-72  
 DBA\_EDITIONING\_VIEW\_COLS\_AE view, 4-72  
 DBA\_EDITIONING\_VIEWS view, 4-73  
 DBA\_EDITIONING\_VIEWS\_AE view, 4-73  
 DBA\_EDITIONS view, 4-73  
 DBA\_ENABLED\_AGGREGATIONS view, 4-73  
 DBA\_ENABLED\_TRACES view, 4-73  
 DBA\_ENCRYPTED\_COLUMNS view, 4-74  
 DBA\_EPG\_DAD\_AUTHORIZATION view, 4-74  
 DBA\_ERRORS view, 4-74  
 DBA\_ERRORS\_AE view, 4-74  
 DBA\_EVALUATION\_CONTEXT\_TABLES  
     view, 4-74  
 DBA\_EVALUATION\_CONTEXT\_VARS view, 4-75  
 DBA\_EVALUATION\_CONTEXTS view, 4-75  
 DBA\_EXP\_FILES view, 4-75  
 DBA\_EXP\_OBJECTS view, 4-75  
 DBA\_EXP\_VERSION view, 4-75  
 DBA\_EXTENTS view, 4-75  
 DBA\_EXTERNAL\_LOCATIONS view, 4-76  
 DBA\_EXTERNAL\_TABLES view, 4-76  
 DBA\_FEATURE\_USAGE\_STATISTICS view, 4-76  
 DBA\_FGA\_AUDIT\_TRAIL view, 4-81  
 DBA\_FILE\_GROUP\_EXPORT\_INFO view, 4-82  
 DBA\_FILE\_GROUP\_FILES view, 4-82  
 DBA\_FILE\_GROUP\_TABLES view, 4-82  
 DBA\_FILE\_GROUP\_TABLESPACES view, 4-82  
 DBA\_FILE\_GROUP\_VERSIONS view, 4-82  
 DBA\_FILE\_GROUPS view, 4-83  
 DBA\_FLASHBACK\_ARCHIVE view, 4-83  
 DBA\_FLASHBACK\_ARCHIVE\_TABLES view, 4-83  
 DBA\_FLASHBACK\_ARCHIVE\_TS view, 4-84  
 DBA\_FLASHBACK\_TXN\_REPORT view, 4-84

DBA\_FLASHBACK\_TXN\_STATE view, 4-84  
 DBA\_FREE\_SPACE view, 4-85  
 DBA\_FREE\_SPACE\_COALESCED view, 4-85  
 DBA\_HIGH\_WATER\_MARK\_STATISTICS  
     view, 4-86  
 DBA\_HIST\_ACTIVE\_SESS\_HISTORY view, 4-86  
 DBA\_HIST\_BASELINE view, 4-90  
 DBA\_HIST\_BASELINE\_DETAILS view, 4-91  
 DBA\_HIST\_BASELINE\_METADATA view, 4-92  
 DBA\_HIST\_BASELINE\_TEMPLATE view, 4-92  
 DBA\_HIST\_BG\_EVENT\_SUMMARY view, 4-93  
 DBA\_HIST\_BUFFER\_POOL\_STAT view, 4-93  
 DBA\_HIST\_BUFFERED\_QUEUES view, 4-94  
 DBA\_HIST\_BUFFERED\_SUBSCRIBERS view, 4-95  
 DBA\_HIST\_CLUSTER\_INTERCON view, 4-96  
 DBA\_HIST\_COLORED\_SQL view, 4-96  
 DBA\_HIST\_COMP\_IOSTAT view, 4-97  
 DBA\_HIST\_CR\_BLOCK\_SERVER view, 4-97  
 DBA\_HIST\_CURRENT\_BLOCK\_SERVER  
     view, 4-98  
 DBA\_HIST\_DATABASE\_INSTANCE view, 4-99  
 DBA\_HIST\_DATAFILE view, 4-99  
 DBA\_HIST\_DB\_CACHE\_ADVICE view, 4-99  
 DBA\_HIST\_DISPATCHER view, 4-100  
 DBA\_HIST\_DLM\_MISC view, 4-100  
 DBA\_HIST\_DYN\_REMASTER\_STATS view, 4-101  
 DBA\_HIST\_ENQUEUE\_STAT view, 4-101  
 DBA\_HIST\_EVENT\_HISTOGRAM view, 4-102  
 DBA\_HIST\_EVENT\_NAME view, 4-102  
 DBA\_HIST\_FILEMETRIC\_HISTORY view, 4-102  
 DBA\_HIST\_FILESTATXS view, 4-103  
 DBA\_HIST\_IC\_CLIENT\_STATS view, 4-104  
 DBA\_HIST\_IC\_DEVICE\_STATS view, 4-104  
 DBA\_HIST\_INST\_CACHE\_TRANSFER view, 4-105  
 DBA\_HIST\_INSTANCE\_RECOVERY view, 4-106  
 DBA\_HIST\_INTERCONNECT\_PINGS view, 4-107  
 DBA\_HIST\_IOSTAT\_DETAIL view, 4-108  
 DBA\_HIST\_IOSTAT\_FILETYPE view, 4-109  
 DBA\_HIST\_IOSTAT\_FILETYPE\_NAME view, 4-109  
 DBA\_HIST\_IOSTAT\_FUNCTION view, 4-110  
 DBA\_HIST\_IOSTAT\_FUNCTION\_NAME  
     view, 4-110  
 DBA\_HIST\_JAVA\_POOL\_ADVICE view, 4-110  
 DBA\_HIST\_LATCH view, 5-1  
 DBA\_HIST\_LATCH\_CHILDREN view, 5-1  
 DBA\_HIST\_LATCH\_MISSES\_SUMMARY view, 5-2  
 DBA\_HIST\_LATCH\_NAME view, 5-2  
 DBA\_HIST\_LATCH\_PARENT view, 5-3  
 DBA\_HIST\_LIBRARYCACHE view, 5-3  
 DBA\_HIST\_LOG view, 5-4  
 DBA\_HIST\_MEM\_DYNAMIC\_COMP view, 5-5  
 DBA\_HIST\_MEMORY\_RESIZE\_OPS view, 5-6  
 DBA\_HIST\_MEMORY\_TARGET\_ADVICE  
     view, 5-6  
 DBA\_HIST\_METRIC\_NAME view, 5-7  
 DBA\_HIST\_MTTR\_TARGET\_ADVICE view, 5-7  
 DBA\_HIST\_MUTEX\_SLEEP view, 5-8  
 DBA\_HIST\_OPTIMIZER\_ENV view, 5-8  
 DBA\_HIST\_OSTAT view, 5-9  
 DBA\_HIST\_OSTAT\_NAME view, 5-9  
 DBA\_HIST\_PARAMETER view, 5-9  
 DBA\_HIST\_PARAMETER\_NAME view, 5-10  
 DBA\_HIST\_PERSISTENT\_QMN\_CACHE  
     view, 5-10  
 DBA\_HIST\_PERSISTENT\_QUEUES view, 5-11  
 DBA\_HIST\_PERSISTENT\_SUBS view, 5-12  
 DBA\_HIST\_PGA\_TARGET\_ADVICE view, 5-13  
 DBA\_HIST\_PGASTAT view, 5-13  
 DBA\_HIST\_PLAN\_OPERATION\_NAME view, 5-14  
 DBA\_HIST\_PLAN\_OPTION\_NAME view, 5-14  
 DBA\_HIST\_PROCESS\_MEM\_SUMMARY  
     view, 5-15  
 DBA\_HIST\_RESOURCE\_LIMIT view, 5-15  
 DBA\_HIST\_ROWCACHE\_SUMMARY view, 5-16  
 DBA\_HIST\_RSRC\_CONSUMER\_GROUP view, 5-16  
 DBA\_HIST\_RSRC\_PLAN view, 5-18  
 DBA\_HIST\_RULE\_SET view, 5-19  
 DBA\_HIST\_SEG\_STAT view, 5-19  
 DBA\_HIST\_SEG\_STAT\_OBJ view, 5-21  
 DBA\_HIST\_SERVICE\_NAME view, 5-21  
 DBA\_HIST\_SERVICE\_STAT view, 5-22  
 DBA\_HIST\_SERVICE\_WAIT\_CLASS view, 5-22  
 DBA\_HIST\_SESS\_TIME\_STATS view, 5-22  
 DBA\_HIST\_SESSMETRIC\_HISTORY view, 5-23  
 DBA\_HIST\_SGA view, 5-23  
 DBA\_HIST\_SGA\_TARGET\_ADVICE view, 5-24  
 DBA\_HIST\_SGASTAT view, 5-24  
 DBA\_HIST\_SHARED\_POOL\_ADVICE view, 5-24  
 DBA\_HIST\_SHARED\_SERVER\_SUMMARY  
     view, 5-25  
 DBA\_HIST\_SNAP\_ERROR view, 5-26  
 DBA\_HIST\_SNAPSHOT view, 5-26  
 DBA\_HIST\_SQL\_BIND\_METADATA view, 5-27  
 DBA\_HIST\_SQL\_PLAN view, 5-27  
 DBA\_HIST\_SQL\_SUMMARY view, 5-29  
 DBA\_HIST\_SQL\_WORKAREA\_HSTGRM  
     view, 5-29  
 DBA\_HIST\_SQLBIND view, 5-30  
 DBA\_HIST\_SQLCOMMAND\_NAME view, 5-31  
 DBA\_HIST\_SQLSTAT view, 5-31  
 DBA\_HIST\_SQLTEXT view, 5-34  
 DBA\_HIST\_STAT\_NAME view, 5-34  
 DBA\_HIST\_STREAMS\_APPLY\_SUM view, 5-35  
 DBA\_HIST\_STREAMS\_CAPTURE view, 5-35  
 DBA\_HIST\_STREAMS\_POOL\_ADVICE view, 5-36  
 DBA\_HIST\_SYS\_TIME\_MODEL view, 5-36  
 DBA\_HIST\_SYSMETRIC\_HISTORY view, 5-37  
 DBA\_HIST\_SYSMETRIC\_SUMMARY view, 5-37  
 DBA\_HIST\_SYSSTAT view, 5-38  
 DBA\_HIST\_SYSTEM\_EVENT view, 5-38  
 DBA\_HIST\_TABLESPACE\_STAT view, 5-38  
 DBA\_HIST\_TBSPC\_SPACE\_USAGE view, 5-39  
 DBA\_HIST\_TEMPFILE view, 5-39  
 DBA\_HIST\_TEMPSTATXS view, 5-39  
 DBA\_HIST\_THREAD view, 5-40  
 DBA\_HIST\_TOPLEVELCALL\_NAME view, 5-40  
 DBA\_HIST\_UNDOSTAT view, 5-41  
 DBA\_HIST\_WAITCLASSMET\_HISTORY view, 5-42  
 DBA\_HIST\_WAITSTAT view, 5-42  
 DBA\_HIST\_WR\_CONTROL view, 5-43

DBA\_HISTOGRAMS synonym for DBA\_TAB\_HISTOGRAMS, 5-43  
 DBA\_IDENTIFIERS view, 5-43  
 DBA\_IND\_COLUMNS view, 5-43  
 DBA\_IND\_EXPRESSIONS view, 5-43  
 DBA\_IND\_PARTITIONS view, 5-43  
 DBA\_IND\_PENDING\_STATS view, 5-44  
 DBA\_IND\_STATISTICS view, 5-44  
 DBA\_IND\_SUBPARTITIONS view, 5-44  
 DBA\_INDEXES view, 5-44  
     collecting statistics for, 5-44  
 DBA\_INDEXTYPE\_ARRAYTYPES view, 5-44  
 DBA\_INDEXTYPE\_COMMENTS view, 5-44  
 DBA\_INDEXTYPE\_OPERATORS view, 5-44  
 DBA\_INDEXTYPES view, 5-45  
 DBA\_INTERNAL\_TRIGGERS view, 5-45  
 DBA\_JAVA\_ARGUMENTS view, 5-45  
 DBA\_JAVA\_CLASSES view, 5-45  
 DBA\_JAVA\_COMPILER\_OPTIONS view, 5-45  
 DBA\_JAVA\_DERIVATIONS view, 5-45  
 DBA\_JAVA\_FIELDS view, 5-45  
 DBA\_JAVA\_IMPLEMENTATIONS view, 5-45  
 DBA\_JAVA\_INNERS view, 5-46  
 DBA\_JAVA\_LAYOUTS view, 5-46  
 DBA\_JAVA\_METHODS view, 5-46  
 DBA\_JAVA\_NCOMPS view, 5-46  
 DBA\_JAVA\_POLICY view, 5-46  
 DBA\_JAVA\_RESOLVERS view, 5-47  
 DBA\_JAVA\_THROWS view, 5-47  
 DBA\_JOBS view, 5-47  
 DBA\_JOBS\_RUNNING view, 5-48  
 DBA\_JOIN\_IND\_COLUMNS view, 5-48  
 DBA\_KGLLOCK view, 5-48  
 DBA\_LIBRARIES view, 5-48  
 DBA\_LMT\_FREE\_SPACE view, 5-49  
 DBA\_LMT\_USED\_EXTENTS view, 5-49  
 DBA\_LOB\_PARTITIONS view, 5-49  
 DBA\_LOB\_SUBPARTITIONS view, 5-49  
 DBA\_LOB\_TEMPLATES view, 5-49  
 DBA\_LOBS view, 5-49  
 DBA\_LOCK view, 5-50  
     DBA\_LOCKS synonym, 5-50  
 DBA\_LOCK\_INTERNAL view, 5-50  
 DBA\_LOCKS synonym for DBA\_LOCK view, 5-50  
 DBA\_LOG\_GROUP\_COLUMNS view, 5-50  
 DBA\_LOG\_GROUPS view, 5-50  
 DBA\_LOGMNR\_LOG view, 5-51  
 DBA\_LOGMNR\_PURGED\_LOG view, 5-51  
 DBA\_LOGMNR\_SESSION view, 5-52  
 DBA\_LOGSTDBY\_EVENTS view, 5-52  
 DBA\_LOGSTDBY\_HISTORY view, 5-53  
 DBA\_LOGSTDBY\_LOG view, 5-54  
 DBA\_LOGSTDBY\_NOT\_UNIQUE view, 5-55  
 DBA\_LOGSTDBY\_PARAMETERS view, 5-56  
 DBA\_LOGSTDBY\_PROGRESS view, 5-57  
 DBA\_LOGSTDBY\_SKIP view, 5-57  
 DBA\_LOGSTDBY\_SKIP\_TRANSACTION view, 5-57  
 DBA\_LOGSTDBY\_UNSUPPORTED view, 5-57  
 DBA\_LOGSTDBY\_UNSUPPORTED\_TABLE view, 5-58  
 LOGSTDBY\_UNSUPPORTED\_TABLES synonym, 6-49  
 DBA\_MEASURE\_FOLDER\_CONTENTS view, 5-58  
 DBA\_MEASURE\_FOLDERS view, 5-58  
 DBA\_METHOD\_PARAMS view, 5-58  
 DBA\_METHOD\_RESULTS view, 5-59  
 DBA\_MINING\_MODEL\_ATTRIBUTES view, 5-59  
 DBA\_MINING\_MODEL\_SETTINGS view, 5-59  
 DBA\_MINING\_MODELS view, 5-59  
 DBA\_MVIEW\_AGGREGATES view, 5-59  
 DBA\_MVIEW\_ANALYSIS view, 5-59  
 DBA\_MVIEW\_COMMENTS view, 5-59  
 DBA\_MVIEW\_DETAIL\_PARTITION view, 5-60  
 DBA\_MVIEW\_DETAIL\_RELATIONS view, 5-60  
 DBA\_MVIEW\_DETAIL\_SUBPARTITION view, 5-60  
 DBA\_MVIEW\_JOINS view, 5-60  
 DBA\_MVIEW\_KEYS view, 5-60  
 DBA\_MVIEW\_LOG\_FILTER\_COLS view, 5-60  
 DBA\_MVIEW\_LOGS view, 5-60  
 DBA\_MVIEW\_REFRESH\_TIMES view, 5-60  
 DBA\_MVIEWS view, 5-61  
 DBA\_NESTED\_TABLE\_COLS view, 5-61  
 DBA\_NESTED\_TABLES view, 5-61  
 DBA\_NETWORK\_ACL\_PRIVILEGES view, 5-61  
 DBA\_NETWORK\_ACLS view, 5-61  
 DBA\_OBJ\_AUDIT\_OPTS view, 5-62  
 DBA\_OBJ\_COLATTRS view, 5-62  
 DBA\_OBJECT\_SIZE view, 5-63  
 DBA\_OBJECT\_TABLES view, 5-63  
 DBA\_OBJECTS view, 5-63  
 DBA\_OBJECTS\_AE view, 5-63  
 DBA\_OPANCILLARY view, 5-63  
 DBA\_OPARGUMENTS view, 5-63  
 DBA\_OPBINDINGS view, 5-64  
 DBA\_OPERATOR\_COMMENTS view, 5-64  
 DBA\_OPERATORS view, 5-64  
 DBA\_OPTSTAT\_OPERATIONS view, 5-64  
 DBA\_ORPHAN\_KEY\_TABLE view, 5-64  
 DBA\_OUTLINE\_HINTS view, 5-65  
 DBA\_OUTLINES view, 5-65  
 DBA\_OUTSTANDING\_ALERTS view, 5-66  
 DBA\_PARALLEL\_EXECUTE\_CHUNKS view, 5-67  
 DBA\_PARALLEL\_EXECUTE\_TASKS view, 5-67  
 DBA\_PART\_COL\_STATISTICS view, 5-68  
 DBA\_PART\_HISTOGRAMS view, 5-69  
 DBA\_PART\_INDEXES view, 5-69  
 DBA\_PART\_KEY\_COLUMNS view, 5-69  
 DBA\_PART\_LOBS view, 5-69  
 DBA\_PART\_TABLES view, 5-69  
 DBA\_PARTIAL\_DROP\_TABS view, 5-69  
 DBA\_PENDING\_CONV\_TABLES view, 5-69  
 DBA\_PENDING\_TRANSACTIONS view, 5-70  
 DBA\_PLSQL\_OBJECT\_SETTINGS view, 5-70  
 DBA\_POLICIES view, 5-70  
 DBA\_POLICY\_CONTEXTS view, 5-70  
 DBA\_POLICY\_GROUPS view, 5-70  
 DBA\_PRIV\_AUDIT\_OPTS view, 5-70  
 DBA\_PROCEDURES view, 5-71  
 DBA\_PROFILES view, 5-71

DBA\_PROPAGATION view, 5-71  
 DBA\_PROXIES view, 5-71  
 DBA\_PUBLISHED\_COLUMNS view, 5-72  
 DBA\_QUEUE\_SCHEDULES view, 5-72  
 DBA\_QUEUE\_SUBSCRIBERS view, 5-72  
 DBA\_QUEUE\_TABLES view, 5-73  
 DBA\_QUEUES view, 5-73  
 DBA\_RCHILD view, 5-73  
 DBA\_RECOVERABLE\_SCRIPT view, 5-73  
 DBA\_RECOVERABLE\_SCRIPT\_BLOCKS view, 5-73  
 DBA\_RECOVERABLE\_SCRIPT\_ERRORS view, 5-74  
 DBA\_RECOVERABLE\_SCRIPT\_HIST view, 5-74  
 DBA\_RECOVERABLE\_SCRIPT\_PARAMS view, 5-74  
 DBA\_RECYCLEBIN view, 5-75  
 DBA\_REDEFINITION\_ERRORS view, 5-76  
 DBA\_REDEFINITION\_OBJECTS view, 5-76  
 DBA\_REFRESH view, 5-77  
 DBA\_REFRESH\_CHILDREN view, 5-77  
 DBA\_REFS view, 5-77  
 DBA\_REGISTERED\_ARCHIVED\_LOG view, 5-77  
 DBA\_REGISTERED\_MVIEW\_GROUPS view, 5-78  
 DBA\_REGISTERED\_MVIEWS view, 5-78  
 DBA\_REGISTRY view, 5-78  
 DBA\_REGISTRY\_HIERARCHY view, 5-79  
 DBA\_REGISTRY\_HISTORY view, 5-80  
 DBA\_REGISTRY\_LOG view, 5-80  
 DBA\_REPAIR\_TABLE view, 5-80  
 DBA\_REPCAT view, 2-2  
 DBA\_REPCAT\_EXCEPTIONS view, 2-2  
 DBA\_REPCAT\_REFRESH\_TEMPLATES view, 2-2  
 DBA\_REPCAT\_TEMPLATE\_OBJECTS view, 2-2  
 DBA\_REPCAT\_TEMPLATE\_PARS view, 2-2  
 DBA\_REPCAT\_TEMPLATE\_SITES view, 2-2  
 DBA\_REPCAT\_USER\_AUTHORIZATIONS view, 2-2  
 DBA\_REPCAT\_USER\_PARM\_VALUES view, 2-2  
 DBA\_REPCATLOG view, 2-2  
 DBA\_REPCOLUMN view, 2-2  
 DBA\_REPCOLUMN\_GROUP view, 2-2  
 DBA\_REPCONFLICT view, 2-2  
 DBA\_REPDDL view, 2-2  
 DBA\_REPEXTENSIONS view, 2-2  
 DBA\_REPFLAVOR\_COLUMNS view, 2-2  
 DBA\_REPFLAVOR\_OBJECTS view, 2-2  
 DBA\_REPFLAVORS view, 2-2  
 DBA\_REPGENERATED view, 2-2  
 DBA\_REPGENOBJECTS view, 2-2  
 DBA\_REPGROUP view, 2-2  
 DBA\_REPGROUP\_PRIVILEGES view, 2-2  
 DBA\_REPGROUPED\_COLUMN view, 2-2  
 DBA\_REPKKEY\_COLUMNS view, 2-2  
 DBA\_REPOBJECT view, 2-2  
 DBA\_REPPARAMETER\_COLUMN view, 2-2  
 DBA\_REPPRIORITY view, 2-2  
 DBA\_REPPRIORITY\_GROUP view, 2-2  
 DBA\_REPPROP view, 2-2  
 DBA\_REPRESOL\_STATS\_CONTROL view, 2-2  
 DBA\_REPRESOLUTION view, 2-2  
 DBA\_REPRESOLUTION\_METHOD view, 2-2  
 DBA\_REPRESOLUTION\_STATISTICS view, 2-2  
 DBA\_REPSHEMA view, 2-2  
 DBA\_REPSITES view, 2-2  
 DBA\_REPSITES\_NEW view, 2-2  
 DBA\_RESOURCE\_INCARNATIONS view, 5-81  
 DBA\_RESUMABLE view, 5-81  
 DBA\_REWRITE\_EQUIVALENCES view, 5-82  
 DBA\_RGROU view, 5-82  
 DBA\_ROLE\_PRIVS view, 5-83  
 DBA\_ROLES view, 5-83  
 DBA\_ROLLBACK\_SEGS view, 5-83  
 DBA\_RSRC\_CATEGORIES view, 5-84  
 DBA\_RSRC\_CONSUMER\_GROUP\_PRIVS view, 5-84  
 DBA\_RSRC\_CONSUMER\_GROUPS view, 5-85  
 DBA\_RSRC\_GROUP\_MAPPINGS view, 5-85  
 DBA\_RSRC\_IO\_CALIBRATE view, 5-85  
 DBA\_RSRC\_MANAGER\_SYSTEM\_PRIVS view, 5-86  
 DBA\_RSRC\_MAPPING\_PRIORITY view, 5-86  
 DBA\_RSRC\_PLAN\_DIRECTIVES view, 5-87  
 DBA\_RSRC\_PLANS view, 5-88  
 DBA\_RULE\_SET\_RULES view, 5-89  
 DBA\_RULE\_SETS view, 5-89  
 DBA\_RULES view, 5-89  
 DBA\_SCHEDULER\_CHAIN\_RULES view, 5-89  
 DBA\_SCHEDULER\_CHAIN\_STEPS view, 5-89  
 DBA\_SCHEDULER\_CHAINS view, 5-89  
 DBA\_SCHEDULER\_CREDENTIALS view, 5-89  
 DBA\_SCHEDULER\_DB\_DESTS view, 5-90  
 DBA\_SCHEDULER\_DESTS view, 5-90  
 DBA\_SCHEDULER\_EXTERNAL\_DESTS view, 5-90  
 DBA\_SCHEDULER\_FILE\_WATCHERS view, 5-90  
 DBA\_SCHEDULER\_GLOBAL\_ATTRIBUTE view, 5-90  
 DBA\_SCHEDULER\_GROUP\_MEMBERS view, 5-90  
 DBA\_SCHEDULER\_GROUPS view, 5-90  
 DBA\_SCHEDULER\_JOB\_ARGS view, 5-91  
 DBA\_SCHEDULER\_JOB\_CLASSES view, 5-91  
 DBA\_SCHEDULER\_JOB\_DESTS view, 5-91  
 DBA\_SCHEDULER\_JOB\_LOG view, 5-91  
 DBA\_SCHEDULER\_JOB\_ROLES view, 5-91  
 DBA\_SCHEDULER\_JOB\_RUN\_DETAILS view, 5-92  
 DBA\_SCHEDULER\_JOBS view, 5-92  
 DBA\_SCHEDULER\_NOTIFICATIONS view, 5-93  
 DBA\_SCHEDULER\_PROGRAM\_ARGS view, 5-93  
 DBA\_SCHEDULER\_PROGRAMS view, 5-93  
 DBA\_SCHEDULER\_REMOTE\_DATABASES view, 5-93  
 DBA\_SCHEDULER\_REMOTE\_JOBSTATE view, 5-93  
 DBA\_SCHEDULER\_RUNNING\_CHAINS view, 5-93  
 DBA\_SCHEDULER\_RUNNING\_JOBS view, 5-93  
 DBA\_SCHEDULER\_SCHEDULES view, 5-94  
 DBA\_SCHEDULER\_WINDOW\_DETAILS view, 5-94  
 DBA\_SCHEDULER\_WINDOW\_GROUPS view, 5-94

DBA\_SCHEDULER\_WINDOW\_LOG view, 5-94  
 DBA\_SCHEDULER\_WINDOWS view, 5-94  
 DBA\_SCHEDULER\_WINGROUP\_MEMBERS view, 5-94  
 DBA\_SEC\_RELEVANT\_COLS view, 5-94  
 DBA\_SECONDARY\_OBJECTS view, 5-95  
 DBA\_SEGMENTS view, 5-95  
 DBA\_SEGMENTS\_OLD view, 5-96  
 DBA\_SEQUENCES view, 5-97  
 DBA\_SERVER\_REGISTRY view, 5-97  
 DBA\_SERVICES view, 5-98  
 DBA\_SOURCE view, 5-98  
 DBA\_SOURCE\_AE view, 5-98  
 DBA\_SOURCE\_TABLES view, 5-98  
 DBA\_SQL\_MANAGEMENT\_CONFIG view, 5-98  
 DBA\_SQL\_PATCHES view, 5-99  
 DBA\_SQL\_PLAN\_BASELINES view, 5-99  
 DBA\_SQL\_PROFILES view, 5-100  
 DBA\_SQLJ\_TYPE\_ATTRS view, 5-101  
 DBA\_SQLJ\_TYPE\_METHODS view, 5-101  
 DBA\_SQLJ\_TYPES view, 5-101  
 DBA\_SQLSET view, 5-102  
 DBA\_SQLSET\_BINDS view, 5-102  
 DBA\_SQLSET\_PLANS view, 5-102  
 DBA\_SQLSET\_REFERENCES view, 5-102  
 DBA\_SQLSET\_STATEMENTS view, 5-102  
 DBA\_SQLTUNE\_BINDS view, 5-102  
 DBA\_SQLTUNE\_PLANS view, 5-102  
 DBA\_SQLTUNE\_RATIONALE\_PLAN view, 5-105  
 DBA\_SQLTUNE\_STATISTICS view, 5-105  
 DBA\_SSCR\_CAPTURE view, 5-106  
 DBA\_SSCR\_RESTORE view, 5-106  
 DBA\_STAT\_EXTENSIONS view, 5-107  
 DBA\_STMT\_AUDIT\_OPTS view, 5-107  
 DBA\_STORED\_SETTINGS view, 5-107  
 DBA\_STREAMS\_ADD\_COLUMN view, 6-1  
 DBA\_STREAMS\_ADMINISTRATOR view, 6-1  
 DBA\_STREAMS\_COLUMNS view, 6-2  
 DBA\_STREAMS\_DELETE\_COLUMN view, 6-2  
 DBA\_STREAMS\_GLOBAL\_RULES view, 6-2  
 DBA\_STREAMS\_KEEP\_COLUMNS view, 6-2  
 DBA\_STREAMS\_MESSAGE\_CONSUMERS view, 6-3  
 DBA\_STREAMS\_MESSAGE\_RULES view, 6-3  
 DBA\_STREAMS\_NEWLY\_SUPPORTED view, 6-3  
 DBA\_STREAMS\_RENAME\_COLUMN view, 6-3  
 DBA\_STREAMS\_RENAME\_SCHEMA view, 6-4  
 DBA\_STREAMS\_RENAME\_TABLE view, 6-4  
 DBA\_STREAMS\_RULES view, 6-4  
 DBA\_STREAMS\_SCHEMA\_RULES view, 6-4  
 DBA\_STREAMS\_SPLIT\_MERGE view, 6-4  
 DBA\_STREAMS\_SPLIT\_MERGE\_HIST view, 6-6  
 DBA\_STREAMS\_STMT\_HANDLERS view, 6-8  
 DBA\_STREAMS\_STMTS view, 6-8  
 DBA\_STREAMS\_TABLE\_RULES view, 6-8  
 DBA\_STREAMS\_TP\_COMPONENT view, 6-8  
 DBA\_STREAMS\_TP\_COMPONENT\_LINK view, 6-9  
 DBA\_STREAMS\_TP\_COMPONENT\_STAT view, 6-9  
 DBA\_STREAMS\_TP\_DATABASE view, 6-10  
 DBA\_STREAMS\_TP\_PATH\_BOTTLENECK view, 6-10  
 DBA\_STREAMS\_TP\_PATH\_STAT view, 6-11  
 DBA\_STREAMS\_TRANSFORM\_FUNCTION view, 6-11  
 DBA\_STREAMS\_TRANSFORMATIONS view, 6-11  
 DBA\_STREAMS\_UNSUPPORTED view, 6-12  
 DBA\_SUBPART\_COL\_STATISTICS view, 6-13  
 DBA\_SUBPART\_HISTOGRAMS view, 6-13  
 DBA\_SUBPART\_KEY\_COLUMNS view, 6-13  
 DBA\_SUBPARTITION\_TEMPLATES view, 6-13  
 DBA\_SUBSCR\_REGISTRATIONS view, 6-13  
 DBA\_SUBSCRIBED\_COLUMNS view, 6-14  
 DBA\_SUBSCRIBED\_TABLES view, 6-15  
 DBA\_SUBSCRIPTIONS view, 6-15  
 DBA\_SYNC\_CAPTURE view, 6-16  
 DBA\_SYNC\_CAPTURE\_PREPARED\_TABS view, 6-16  
 DBA\_SYNC\_CAPTURE\_TABLES view, 6-16  
 DBA\_SYNONYMS view, 6-16  
 DBA\_SYS\_PRIVS view, 6-16  
 DBA\_TAB\_COL\_STATISTICS view, 6-17  
 DBA\_TAB\_COLS view, 6-17  
 DBA\_TAB\_COLUMNS view, 6-17  
 DBA\_TAB\_COMMENTS view, 6-17  
 DBA\_TAB\_HISTGRM\_PENDING\_STATS view, 6-17  
 DBA\_TAB\_HISTOGRAMS view, 6-17  
     DBA\_HISTOGRAMS synonym, 5-43  
 DBA\_TAB\_MODIFICATIONS view, 6-17  
 DBA\_TAB\_PARTITIONS view, 6-18  
 DBA\_TAB\_PENDING\_STATS view, 6-18  
 DBA\_TAB\_PRIVS view, 6-18  
 DBA\_TAB\_STAT\_PREFS view, 6-18  
 DBA\_TAB\_STATISTICS view, 6-18  
 DBA\_TAB\_STATS\_HISTORY view, 6-19  
 DBA\_TAB\_SUBPARTITIONS view, 6-19  
 DBA\_TABLES view, 6-19  
 DBA\_TABLESPACE\_GROUPS view, 6-19  
 DBA\_TABLESPACE\_THRESHOLDS view, 6-19  
 DBA\_TABLESPACE\_USAGE\_METRICS view, 6-20  
 DBA\_TABLESPACES view, 6-20  
 DBA\_TEMP\_FILES view, 6-22  
 DBA\_TEMP\_FREE\_SPACE view, 6-22  
 DBA\_THRESHOLDS view, 6-23  
 DBA\_TRANSFORMATIONS view, 6-24  
 DBA\_TRIGGER\_COLS view, 6-24  
 DBA\_TRIGGER\_ORDERING view, 6-24  
 DBA\_TRIGGERS view, 6-24  
 DBA\_TS\_QUOTAS view, 6-24  
 DBA\_TSM\_DESTINATION view, 6-25  
 DBA\_TSM\_SOURCE view, 6-25  
 DBA\_TSTZ\_TAB\_COLS view, 6-26  
 DBA\_TSTZ\_TABLES view, 6-26  
 DBA\_TUNE\_MVIEW view, 6-26  
 DBA\_TYPE\_ATTRS view, 6-27  
 DBA\_TYPE\_METHODS view, 6-27  
 DBA\_TYPE\_VERSIONS view, 6-27  
 DBA\_TYPES view, 6-27

- DBA\_UNDO\_EXTENTS view, 6-27
- DBA\_UNUSED\_COL\_TABS view, 6-28
- DBA\_UPDATABLE\_COLUMNS view, 6-28
- DBA\_USERS view, 6-28
- DBA\_USERS\_WITH\_DEFPWD view, 6-29
- DBA\_USTATS view, 6-29
- DBA\_VARRAYS view, 6-29
- DBA\_VIEWS view, 6-29
- DBA\_VIEWS\_AE view, 6-30
- DBA\_WAITERS view, 6-30
- DBA\_WALLET\_ACLS view, 6-30
- DBA\_WARNING\_SETTINGS view, 6-30
- DBA\_WM\_SYS\_PRIVS view, 2-3
- DBA\_WM\_VT\_ERRORS view, 2-3
- DBA\_WORKLOAD\_CAPTURES view, 6-30
- DBA\_WORKLOAD\_CONNECTION\_MAP view, 6-32
- DBA\_WORKLOAD\_FILTERS view, 6-32
- DBA\_WORKLOAD\_REPLAY\_DIVERGENCE view, 6-33
- DBA\_WORKLOAD\_REPLAYS view, 6-34
- DBA\_WORKSPACE\_SESSIONS view, 2-3
- DBA\_WORKSPACES view, 2-3
- DBA\_XML\_INDEXES view, 6-36
- DBA\_XML\_SCHEMAS view, 6-36
- DBA\_XML\_TAB\_COLS view, 6-36
- DBA\_XML\_TABLES view, 6-36
- DBA\_XML\_VIEW\_COLS view, 6-36
- DBA\_XML\_VIEWS view, 6-37
- DBA\_XSTREAM\_ADMINISTRATOR view, 6-37
- DBA\_XSTREAM\_INBOUND view, 6-37
- DBA\_XSTREAM\_INBOUND\_PROGRESS view, 6-37
- DBA\_XSTREAM\_OUT\_SUPPORT\_MODE view, 6-37
- DBA\_XSTREAM\_OUTBOUND view, 6-38
- DBA\_XSTREAM\_OUTBOUND\_PROGRESS view, 6-38
- DBA\_XSTREAM\_RULES view, 6-38
- DBFS\_CONTENT view, 6-38
- DBFS\_CONTENT\_PROPERTIES view, 6-40
- DBMS\_ALERT\_INFO view, 6-40
- DBMS\_LOCK\_ALLOCATED view, 6-40
- DBMSIOTC.SQL script, B-2
- DBMSPOOL.SQL script, B-2
- DBWR\_IO\_SLAVES initialization parameter, 1-59
- DDL\_LOCK\_TIMEOUT initialization parameter, 1-60
- DEFCALL view, 2-2
- DEFCALLDEST view, 2-2
- DEFDEFAULTDEST view, 2-2
- DEFERRCOUNT view, 2-2
- DEFERRED\_SEGMENT\_CREATION initialization parameter, 1-60
- DEFERROR view, 2-2
- DEFLOB view, 2-2
- DEFPROPAGATOR view, 2-3
- DEFSCHEDULE view, 2-3
- DEFTRAN view, 2-3
- DEFTRANDEST view, 2-3

- DEPTREE view, 6-40
- destination
  - archiving redo log files, 1-87
  - overriding default, 1-87
  - USER\_DUMP\_DEST, 1-178
- DG\_BROKER\_CONFIG\_FILE*n* initialization parameter, 1-60
- DG\_BROKER\_START initialization parameter, 1-61
- DIAGNOSTIC\_DEST initialization parameter, 1-61
- DICT synonym for DICTIONARY, 6-41
- DICT\_COLUMNS view, 6-41
- DICTIONARY view, 6-41
  - DICT synonym, 6-41
- disk drives
  - archiving destination, 1-87
- DISK\_ASYNC\_IO initialization parameter, 1-62
- dispatcher processes
  - maximum number, 1-101
- DISPATCHERS initialization parameter, 1-63
- distinguished name, 1-142
- DISTRIBUTED\_LOCK\_TIMEOUT initialization parameter, 1-66
- DM\_USER\_MODELS view, 6-41
- DML\_LOCKS initialization parameter, 1-66
- DOCUMENT\_LINKS view, 6-43
- downgrading
  - scripts, B-4
- DST\_UPGRADE\_INSERT\_CONV initialization parameter, 1-67
- dump files, 1-102
- dynamic performance tables
  - CATALOG.SQL script, 7-1
  - public synonyms (V\$), 7-2
  - views (V\_\$), 7-2

## E

---

- embedded initialization parameter files, 1-75
- ENABLE\_DDL\_LOGGING initialization parameter, 1-68
- enqueuees
  - AJV snapshot refresh, D-2
  - ALTER SYSTEM SET PARAMETER = VALUE, D-2
  - backup/restore, D-1
  - being written redo log, D-3
  - bind, D-1
  - buffer cache management, D-1
  - controlfile transaction, D-1
  - cross-instance call invocation, D-1
  - database mount, D-1
  - datafile, D-1
  - direct loader index creation, D-1
  - disabling, 1-66
  - distributed recovery process, D-1
  - distributed transaction, D-1
  - DML, D-2
  - extend table, D-2
  - file set, D-1
  - high-water lock, D-1



- instance attribute lock, D-3
- instance number, D-1
- instance recovery, D-1
- instance registration lock, D-3
- instance state, D-2
- job queue, D-2
- library cache invalidation, D-2
- library cache lock, D-2
- library cache pin, D-2
- log start or switch, D-2
- media recovery, D-2
- mount definition, D-2
- object reuse, D-2
- parallel slave synchronization, D-2
- parallel slaves, D-2
- password file, D-2
- process startup, D-2
- redo log "kick", D-2
- redo thread, D-2
- row cache, D-2
- row wait, D-2
- sequence number, D-2
- sequence number value, D-2
- SMON, D-2
- sort segment, D-2
- space management transaction, D-2
- synchronized replication, D-2
- system commit number, D-2
- temporary segment, D-2
- temporary table, D-2
- temporary table object, D-2
- thread checkpoint, D-2
- transaction, D-2
- transaction recovery, D-2
- undo segment, serialization, D-3
- user name, D-3
- user-defined locks, D-3
- enterprise roles, 1-142
- ERROR\_SIZE view, 6-43
- EVENT initialization parameter, 1-68
- EXCEPTIONS table, 6-43
- extent
  - allocating to instance, 1-77

## F

---

- FAL\_CLIENT initialization parameter, 1-68
- FAL\_SERVER initialization parameter, 1-69
- FAST\_START\_MTTR\_TARGET initialization parameter, 1-69
- FAST\_START\_PARALLEL\_ROLLBACK initialization parameter, 1-70
- FILE\_MAPPING initialization parameter, 1-70
- FILEIO\_NETWORK\_ADAPTERS initialization parameter, 1-71
- filenames
  - case significance, 1-4
- FILESYSTEMIO\_OPTIONS initialization parameter, 1-71
- FIXED\_DATE initialization parameter, 1-71

- FLASHBACK\_TRANSACTION\_QUERY view, 6-43
- free space list
  - locating space, 1-77
- FREELIST GROUPS clause, 1-77

## G

---

- GCS\_SERVER\_PROCESSES initialization parameter, 1-72
- GLOBAL\_CONTEXT\_POOL\_SIZE initialization parameter, 1-72
- GLOBAL\_NAME view, 6-44
- GLOBAL\_NAMES initialization parameter, 1-73
- GLOBAL\_TXN\_PROCESSES initialization parameter, 1-73
- GV\$ views
  - for Real Application Clusters, 7-2

## H

---

- HASH\_AREA\_SIZE initialization parameter, 1-74
- Heterogeneous Services
  - agents, 1-75
- HI\_SHARED\_MEMORY\_ADDRESS initialization parameter, 1-74
- hints
  - precedence over initialization parameter settings, 1-163
- HS\_ALL\_CAPS view, 6-44
- HS\_ALL\_DD view, 6-44
- HS\_ALL\_INITS view, 6-45
- HS\_AUTOREGISTER initialization parameter, 1-75
- HS\_BASE\_CAPS view, 6-45
- HS\_BASE\_DD view, 6-45
- HS\_CLASS\_CAPS view, 6-45
- HS\_CLASS\_DD view, 6-46
- HS\_CLASS\_INIT view, 6-46
- HS\_FDS\_CLASS view, 6-46
- HS\_FDS\_INST view, 6-46
- HS\_INST\_CAPS view, 6-47
- HS\_INST\_DD view, 6-47
- HS\_INST\_INIT view, 6-47

## I

---

- IDEPTREE view, 6-48
- IFILE initialization parameter, 1-5, 1-75
- IND synonym for USER\_INDEXES view, 6-48
- INDEX\_HISTOGRAM view, 6-48
- INDEX\_STATS view, 6-48
- initialization parameter file
  - common file, 1-75
  - embedded, 1-75
  - INITDW.ORA
  - line continuation character, 1-5
  - overview, 1-3
- initialization parameters
  - ACTIVE\_INSTANCE\_COUNT, 1-19
  - altering, 1-6
  - AQ\_TM\_PROCESSES, 1-20
  - ARCHIVE\_LAG\_TARGET, 1-21

ASM\_DISKGROUPS, 1-21  
 ASM\_DISKSTRING, 1-22  
 ASM\_POWER\_LIMIT, 1-23  
 ASM\_PREFERRED\_READ\_FAILURE\_GROUPS, 1-23  
 AUDIT\_FILE\_DEST, 1-23  
 AUDIT\_SYS\_OPERATIONS, 1-24  
 AUDIT\_SYSLOG\_LEVEL, 1-24  
 AUDIT\_TRAIL, 1-25  
 AWR\_SNAPSHOT\_TIME\_OFFSET, 1-26  
 BACKGROUND\_CORE\_DUMP, 1-27  
 BACKGROUND\_DUMP\_DEST, 1-27  
 BACKUP\_TAPE\_IO\_SLAVES, 1-28  
 basic, 1-3  
 BITMAP\_MERGE\_AREA\_SIZE, 1-29  
 BLANK\_TRIMMING, 1-29  
 case significance in filenames, 1-4  
 CIRCUITS, 1-30  
 CLIENT\_RESULT\_CACHE\_LAG, 1-30  
 CLIENT\_RESULT\_CACHE\_SIZE, 1-30  
 CLUSTER\_DATABASE, 1-31  
 CLUSTER\_DATABASE\_INSTANCES, 1-31  
 CLUSTER\_INTERCONNECTS, 1-32  
 COMMIT\_LOGGING, 1-33  
 COMMIT\_POINT\_STRENGTH, 1-33  
 COMMIT\_WAIT, 1-34  
 COMMIT\_WRITE, 1-34  
 COMPATIBLE, 1-35  
 CONTROL\_FILE\_RECORD\_KEEP\_TIME, 1-36  
 CONTROL\_FILES, 1-36  
 CONTROL\_MANAGEMENT\_PACK\_ACCESS, 1-37  
 CORE\_DUMP\_DEST, 1-38  
 CPU\_COUNT, 1-38  
 CREATE\_BITMAP\_AREA\_SIZE, 1-39  
 CREATE\_STORED\_OUTLINES, 1-39  
 CURSOR\_BIND\_CAPTURE\_DESTINATION, 1-40  
 CURSOR\_SHARING, 1-41  
 CURSOR\_SPACE\_FOR\_TIME, 1-41  
 DB\_BLOCK\_BUFFERS, 1-43  
 DB\_BLOCK\_CHECKING, 1-44  
 DB\_BLOCK\_CHECKSUM, 1-44  
 DB\_BLOCK\_SIZE, 1-45  
 DB\_CACHE\_ADVICE, 1-46  
 DB\_CACHE\_SIZE, 1-47  
 DB\_CREATE\_FILE\_DEST, 1-47  
 DB\_CREATE\_ONLINE\_LOG\_DEST\_n, 1-48  
 DB\_DOMAIN, 1-48  
 DB\_FILE\_MULTIBLOCK\_READ\_COUNT, 1-49  
 DB\_FILE\_NAME\_CONVERT, 1-50  
 DB\_FILES, 1-51  
 DB\_FLASH\_CACHE\_FILE, 1-52  
 DB\_FLASH\_CACHE\_SIZE, 1-52  
 DB\_FLASHBACK\_RETENTION\_TARGET, 1-53  
 DB\_KEEP\_CACHE\_SIZE, 1-53  
 DB\_LOST\_WRITE\_PROTECT, 1-53  
 DB\_NAME, 1-54  
 DB\_nK\_CACHE\_SIZE, 1-42  
 DB\_RECOVERY\_FILE\_DEST, 1-55  
 DB\_RECOVERY\_FILE\_DEST\_SIZE, 1-55  
 DB\_RECYCLE\_CACHE\_SIZE, 1-56  
 DB\_SECUREFILE, 1-56  
 DB\_ULTRA\_SAFE, 1-57  
 DB\_UNIQUE\_NAME, 1-58  
 DB\_UNRECOVERABLE\_SCN\_TRACKING, 1-58  
 DB\_WRITER\_PROCESSES, 1-59  
 DBWR\_IO\_SLAVES, 1-59  
 DDL\_LOCK\_TIMEOUT, 1-60  
 DEFERRED\_SEGMENT\_CREATION, 1-60  
 derived, 1-2  
 DG\_BROKER\_CONFIG\_FILEn, 1-60  
 DG\_BROKER\_START, 1-61  
 DIAGNOSTIC\_DEST, 1-61  
 DISK\_ASYNC\_IO, 1-62  
 DISPATCHERS, 1-63  
 display current settings, 1-17  
 DISTRIBUTED\_LOCK\_TIMEOUT, 1-66  
 DML\_LOCKS, 1-66  
 DST\_UPGRADE\_INSERT\_CONV, 1-67  
 embedded initialization parameter files, 1-5  
 ENABLE\_DDL\_LOGGING, 1-68  
 EVENT, 1-68  
 FAL\_CLIENT, 1-68  
 FAL\_SERVER, 1-69  
 FAST\_START\_MTTR\_TARGET, 1-69  
 FAST\_START\_PARALLEL\_ROLLBACK, 1-70  
 FILE\_MAPPING, 1-70  
 FILEIO\_NETWORK\_ADAPTERS, 1-71  
 FILESYSTEMIO\_OPTIONS, 1-71  
 FIXED\_DATE, 1-71  
 functional category, 1-6  
 GCS\_SERVER\_PROCESSES, 1-72  
 GLOBAL\_CONTEXT\_POOL\_SIZE, 1-72  
 GLOBAL\_NAMES, 1-73  
 GLOBAL\_TXN\_PROCESSES, 1-73  
 HASH\_AREA\_SIZE, 1-74  
 HI\_SHARED\_MEMORY\_ADDRESS, 1-74  
 HS\_AUTOREGISTER, 1-75  
 IFILE, 1-5, 1-75  
 INSTANCE\_GROUPS, 1-76  
 INSTANCE\_NAME, 1-76  
 INSTANCE\_NUMBER, 1-77  
 INSTANCE\_TYPE, 1-77  
 JAVA\_JIT\_ENABLED, 1-78  
 JAVA\_MAX\_SESSIONSPACE\_SIZE, 1-78  
 JAVA\_POOL\_SIZE, 1-79  
 JAVA\_SOFT\_SESSIONSPACE\_LIMIT, 1-79  
 JOB\_QUEUE\_PROCESSES, 1-80  
 LARGE\_POOL\_SIZE, 1-80  
 LDAP\_DIRECTORY\_ACCESS, 1-81  
 LDAP\_DIRECTORY\_SYSAUTH, 1-82  
 LICENSE\_MAX\_SESSIONS, 1-82  
 LICENSE\_MAX\_USERS, 1-83  
 LICENSE\_SESSIONS\_WARNING, 1-83  
 LISTENER\_NETWORKS, 1-84  
 LOCAL\_LISTENER, 1-85  
 LOCK\_NAME\_SPACE, 1-85  
 LOCK\_SGA, 1-86  
 LOG\_ARCHIVE\_CONFIG, 1-86

LOG\_ARCHIVE\_DEST, 1-87  
 LOG\_ARCHIVE\_DEST\_1, 1-88  
 LOG\_ARCHIVE\_DEST\_STATE\_1, 1-91  
 LOG\_ARCHIVE\_DUPLEX\_DEST, 1-92  
 LOG\_ARCHIVE\_FORMAT, 1-93  
 LOG\_ARCHIVE\_LOCAL\_FIRST, 1-94  
 LOG\_ARCHIVE\_MAX\_PROCESSES, 1-95  
 LOG\_ARCHIVE\_MIN\_SUCCEED\_DEST, 1-95  
 LOG\_ARCHIVE\_TRACE, 1-96  
 LOG\_BUFFER, 1-97  
 LOG\_CHECKPOINT\_INTERVAL, 1-98  
 LOG\_CHECKPOINT\_TIMEOUT, 1-99  
 LOG\_CHECKPOINTS\_TO\_ALERT, 1-100  
 LOG\_FILE\_NAME\_CONVERT, 1-100  
 MAX\_DISPATCHERS, 1-101  
 MAX\_DUMP\_FILE\_SIZE, 1-101  
 MAX\_ENABLED\_ROLES, 1-102  
 MAX\_SHARED\_SERVERS, 1-102  
 MEMORY\_MAX\_TARGET, 1-103  
 MEMORY\_TARGET, 1-103  
 modifiable, 1-12  
 NLS\_CALENDAR, 1-104  
 NLS\_COMP, 1-105  
 NLS\_CURRENCY, 1-106  
 NLS\_DATE\_FORMAT, 1-107  
 NLS\_DATE\_LANGUAGE, 1-107  
 NLS\_DUAL\_CURRENCY, 1-108  
 NLS\_ISO\_CURRENCY, 1-109  
 NLS\_LANGUAGE, 1-109  
 NLS\_LENGTH\_SEMANTICS, 1-110  
 NLS\_NCHAR\_CONV\_EXCP, 1-111  
 NLS\_NUMERIC\_CHARACTERS, 1-111  
 NLS\_SORT, 1-112  
 NLS\_TERRITORY, 1-113  
 NLS\_TIMESTAMP\_FORMAT, 1-114  
 NLS\_TIMESTAMP\_TZ\_FORMAT, 1-114  
 O7\_DICTIONARY\_ACCESSIBILITY, 1-115  
 OBJECT\_CACHE\_MAX\_SIZE\_PERCENT, 1-116  
 OBJECT\_CACHE\_OPTIMAL\_SIZE, 1-116  
 OLAP\_PAGE\_POOL\_SIZE, 1-117  
 OPEN\_CURSORS, 1-117  
 OPEN\_LINKS, 1-117  
 OPEN\_LINKS\_PER\_INSTANCE, 1-118  
 operating system-dependent values, 1-2  
 OPTIMIZER\_CAPTURE\_SQL\_PLAN\_ BASELINES, 1-119  
 OPTIMIZER\_DYNAMIC\_SAMPLING, 1-119  
 OPTIMIZER\_FEATURES\_ENABLE, 1-119  
 OPTIMIZER\_INDEX\_CACHING, 1-121  
 OPTIMIZER\_INDEX\_COST\_ADJ, 1-121  
 OPTIMIZER\_MODE, 1-122  
 OPTIMIZER\_SECURE\_VIEW\_MERGING, 1-123  
 OPTIMIZER\_USE\_INVISIBLE\_INDEXES, 1-123  
 OPTIMIZER\_USE\_PENDING\_ STATISTICS, 1-124  
 OPTIMIZER\_USE\_SQL\_PLAN\_ BASELINES, 1-124  
 OS\_AUTHENT\_PREFIX, 1-124  
 OS\_ROLES, 1-125  
 PARALLEL\_ADAPTIVE\_MULTI\_USER, 1-126  
 PARALLEL\_AUTOMATIC\_TUNING, 1-126  
 PARALLEL\_DEGREE\_LIMIT, 1-127  
 PARALLEL\_DEGREE\_POLICY, 1-127  
 PARALLEL\_EXECUTION\_MESSAGE\_ SIZE, 1-128  
 PARALLEL\_FORCE\_LOCAL, 1-129  
 PARALLEL\_INSTANCE\_GROUP, 1-129  
 PARALLEL\_IO\_CAP\_ENABLED, 1-130  
 PARALLEL\_MAX\_SERVERS, 1-130  
 PARALLEL\_MIN\_PERCENT, 1-131  
 PARALLEL\_MIN\_SERVERS, 1-132  
 PARALLEL\_MIN\_TIME\_THRESHOLD, 1-132  
 PARALLEL\_SERVERS\_TARGET, 1-133  
 PARALLEL\_THREADS\_PER\_CPU, 1-133  
 parameter files, 1-3  
 performance tuning, 1-2  
 PGA\_AGGREGATE\_TARGET, 1-134  
 PLSCOPE\_SETTINGS, 1-135  
 PLSQL\_CCFLAGS, 1-135  
 PLSQL\_CODE\_TYPE, 1-136  
 PLSQL\_DEBUG, 1-136  
 PLSQL\_OPTIMIZE\_LEVEL, 1-137  
 PLSQL\_V2\_COMPATIBILITY, 1-138  
 PLSQL\_WARNINGS, 1-138  
 PRE\_PAGE\_SGA, 1-140  
 PROCESSES, 1-140  
 QUERY\_REWRITE\_ENABLED, 1-141  
 QUERY\_REWRITE\_INTEGRITY, 1-142  
 RDBMS\_SERVER\_DN, 1-142  
 READ\_ONLY\_OPEN\_DELAYED, 1-143  
 RECOVERY\_PARALLELISM, 1-143  
 RECYCLEBIN, 1-144  
 REDO\_TRANSPORT\_USER, 1-144  
 REMOTE\_DEPENDENCIES\_MODE, 1-145  
 REMOTE\_LISTENER, 1-145  
 REMOTE\_LOGIN\_PASSWORDFILE, 1-146  
 REMOTE\_OS\_AUTHENT, 1-146  
 REMOTE\_OS\_ROLES, 1-147  
 REPLICATION\_DEPENDENCY\_ TRACKING, 1-147  
 RESOURCE\_LIMIT, 1-148  
 RESOURCE\_MANAGER\_CPU\_ ALLOCATION, 1-148  
 RESOURCE\_MANAGER\_PLAN, 1-149  
 RESULT\_CACHE\_MAX\_RESULT, 1-149  
 RESULT\_CACHE\_MAX\_SIZE, 1-150  
 RESULT\_CACHE\_MODE, 1-150  
 RESULT\_CACHE\_REMOTE\_ EXPIRATION, 1-151  
 RESUMABLE\_TIMEOUT, 1-151  
 ROLLBACK\_SEGMENTS, 1-151  
 SEC\_CASE\_SENSITIVE\_LOGON, 1-152  
 SEC\_MAX\_FAILED\_LOGIN\_ATTEMPTS, 1-153  
 SEC\_PROTOCOL\_ERROR\_FURTHER\_ ACTION, 1-153  
 SEC\_PROTOCOL\_ERROR\_TRACE\_ ACTION, 1-154  
 SEC\_RETURN\_SERVER\_RELEASE\_ BANNER, 1-154  
 SERIAL\_REUSE, 1-155

- SERVICE\_NAMES, 1-156
- SESSION\_CACHED\_CURSORS, 1-156
- SESSION\_MAX\_OPEN\_FILES, 1-157
- SESSIONS, 1-157
- SGA\_MAX\_SIZE, 1-158
- SGA\_TARGET, 1-158
- SHADOW\_CORE\_DUMP, 1-159
- SHARED\_MEMORY\_ADDRESS, 1-160
- SHARED\_POOL\_RESERVED\_SIZE, 1-160
- SHARED\_POOL\_SIZE, 1-161
- SHARED\_SERVER\_SESSIONS, 1-162
- SHARED\_SERVERS, 1-162
- SKIP\_UNUSABLE\_INDEXES, 1-163
- SMTP\_OUT\_SERVER, 1-163
- SORT\_AREA\_RETAINED\_SIZE, 1-164
- SORT\_AREA\_SIZE, 1-165
- specifying in initialization parameter files, 1-4
- SPFILE, 1-166
- SQL\_TRACE, 1-166
- SQL92\_SECURITY, 1-167
- SQLTUNE\_CATEGORY, 1-168
- STANDBY\_ARCHIVE\_DEST, 1-168
- STANDBY\_FILE\_MANAGEMENT, 1-168
- STAR\_TRANSFORMATION\_ENABLED, 1-169
- STATISTICS\_LEVEL, 1-170
- STREAMS\_POOL\_SIZE, 1-171
- TAPE\_ASYNC\_IO, 1-171
- THREAD, 1-172
- TIMED\_OS\_STATISTICS, 1-172
- TIMED\_STATISTICS, 1-173
- TRACE\_ENABLED, 1-173
- TRACEFILE\_IDENTIFIER, 1-174
- TRANSACTIONS, 1-175
- TRANSACTIONS\_PER\_ROLLBACK\_SEGMENT, 1-175
- UNDO\_MANAGEMENT, 1-176
- UNDO\_RETENTION, 1-176
- UNDO\_TABLESPACE, 1-177
- USE\_INDIRECT\_DATA\_BUFFERS, 1-177
- USER\_DUMP\_DEST, 1-178
- UTL\_FILE\_DIR, 1-179
- variable, 1-2
- WORKAREA\_SIZE\_POLICY, 1-179
- XML\_DB\_EVENTS, 1-180
- INITJVM.SQL script, B-5
- INIT.ORA file. *See* initialization parameter file
- IN-list iterators
  - optimizer use of, 1-121
- inserts
  - locating free space, 1-77
- INST\_ID column, 7-2
- INSTANCE clause
  - of ALTER TABLE
    - allocating extents, 1-77
- INSTANCE\_GROUPS initialization parameter, 1-76
- INSTANCE\_NAME initialization parameter, 1-76
- INSTANCE\_NUMBER initialization parameter, 1-77
- INSTANCE\_TYPE initialization parameter, 1-77
- instances
  - checkpoint, 1-98

- startup order, 1-77
- I/O
  - reading multiple blocks, 1-50
  - redo log files, 1-98

## J

---

- Java initialization parameters
  - JAVA\_MAX\_SESSIONSPACE\_SIZE, 1-78
  - JAVA\_POOL\_SIZE, 1-79
  - JAVA\_SOFT\_SESSIONSPACE\_LIMIT, 1-79
- Java scripts, B-5
- JAVA\_JIT\_ENABLED initialization parameter, 1-78
- JAVA\_MAX\_SESSIONSPACE\_SIZE initialization parameter, 1-78
- JAVA\_POOL\_SIZE initialization parameter, 1-79
- JAVA\_SOFT\_SESSIONSPACE\_LIMIT initialization parameter, 1-79
- JOB\_QUEUE\_PROCESSES initialization parameter, 1-80

## L

---

- language
  - database default language, 1-110
- LARGE\_POOL\_SIZE initialization parameter, 1-80
- LDAP\_DIRECTORY\_ACCESS initialization parameter, 1-81
- LDAP\_DIRECTORY\_SYSAUTH initialization parameter, 1-82
- LICENSE\_MAX\_SESSIONS initialization parameter, 1-82
- LICENSE\_MAX\_USERS initialization parameter, 1-83
- LICENSE\_SESSIONS\_WARNING initialization parameter, 1-83
- licenses
  - maximum sessions, 1-83
  - maximum users, 1-83
  - warning for concurrent user sessions, 1-84
- limits on the database, A-1
- linguistic sorts, 1-112
- LISTENER\_NETWORKS initialization parameter, 1-84
- local currency, 1-105, 1-106
- LOCAL\_LISTENER initialization parameter, 1-85
- LOCK\_NAME\_SPACE initialization parameter, 1-85
- LOCK\_SGA initialization parameter, 1-86
- locks
  - names, C-4
- LOG\_ARCHIVE\_CONFIG initialization parameter, 1-86
- LOG\_ARCHIVE\_DEST initialization parameter, 1-87
- LOG\_ARCHIVE\_DEST\_1 initialization parameter, 1-88
- LOG\_ARCHIVE\_DEST\_STATE\_1 initialization parameter, 1-91
- LOG\_ARCHIVE\_DUPLEX\_DEST initialization parameter, 1-92

- LOG\_ARCHIVE\_FORMAT initialization
  - parameter, 1-93
- LOG\_ARCHIVE\_LOCAL\_FIRST initialization
  - parameter, 1-94
- LOG\_ARCHIVE\_MAX\_PROCESSES initialization
  - parameter, 1-95
- LOG\_ARCHIVE\_MIN\_SUCCEED\_DEST initialization
  - parameter, 1-95
- LOG\_ARCHIVE\_TRACE initialization
  - parameter, 1-96
- LOG\_BUFFER initialization parameter, 1-97
- LOG\_CHECKPOINT\_INTERVAL initialization
  - parameter, 1-98
- LOG\_CHECKPOINT\_TIMEOUT initialization
  - parameter, 1-99
- LOG\_CHECKPOINTS\_TO\_ALERT initialization
  - parameter, 1-100
- LOG\_FILE\_NAME\_CONVERT initialization
  - parameter, 1-100
- LOGSTDBY\_UNSUPPORTED\_TABLES synonym for
  - DBA\_LOGSTDBY\_UNSUPPORTED\_TABLE
  - view, 6-49
- lowercase significance, 1-4

## M

---

- MAP\_OBJECT table, 6-50
- MAX\_DISPATCHERS initialization
  - parameter, 1-101
- MAX\_DUMP\_FILE\_SIZE initialization
  - parameter, 1-101
- MAX\_ENABLED\_ROLES initialization
  - parameter, 1-102
- MAX\_SHARED\_SERVERS initialization
  - parameter, 1-102
- memory
  - amount used for sorting, 1-164
  - virtual, 1-2
- MEMORY\_MAX\_TARGET initialization
  - parameter, 1-103
- MEMORY\_TARGET initialization parameter, 1-103
- monitor
  - performance, 1-98
- multiple-process systems
  - number of processes, 1-141

## N

---

- NLS\_CALENDAR initialization parameter, 1-104
- NLS\_COMP initialization parameter, 1-105
- NLS\_CURRENCY initialization parameter, 1-106
  - defined by NLS\_TERRITORY, 1-113
- NLS\_DATABASE\_PARAMETERS view, 6-50
- NLS\_DATE\_FORMAT initialization
  - parameter, 1-107
  - defined by NLS\_NUMERIC\_
  - CHARACTERS, 1-111
  - defined by NLS\_TERRITORY, 1-113
- NLS\_DATE\_LANGUAGE initialization
  - parameter, 1-107

- NLS\_DUAL\_CURRENCY initialization
  - parameter, 1-108
- NLS\_INSTANCE\_PARAMETERS view, 6-50
- NLS\_ISO\_CURRENCY initialization
  - parameter, 1-109
  - defined by NLS\_TERRITORY, 1-113
- NLS\_LANGUAGE initialization parameter, 1-109
- NLS\_LENGTH\_SEMANTICS initialization
  - parameter, 1-110
- NLS\_NCHAR\_CONV\_EXCP initialization
  - parameter, 1-111
- NLS\_NUMERIC\_CHARACTERS initialization
  - parameter, 1-111
- NLS\_SESSION\_PARAMETERS view, 6-50
- NLS\_SORT initialization parameter, 1-112
- NLS\_TERRITORY initialization parameter, 1-113
- NLS\_TIME\_FORMAT, 8-46
- NLS\_TIME\_TZ\_FORMAT, 8-46
- NLS\_TIMESTAMP\_FORMAT initialization
  - parameter, 1-114
- NLS\_TIMESTAMP\_TZ\_FORMAT initialization
  - parameter, 1-114
- numeric group separators, 1-111

## O

---

- O7\_DICTIONARY\_ACCESSIBILITY initialization
  - parameter, 1-115
- OBJ synonym for USER\_OBJECTS view, 6-51
- OBJECT\_CACHE\_MAX\_SIZE\_PERCENT
  - initialization parameter, 1-116
- OBJECT\_CACHE\_OPTIMAL\_SIZE initialization
  - parameter, 1-116
- objects
  - data dictionary, 2-1
- OLAP\_PAGE\_POOL\_SIZE initialization
  - parameter, 1-117
- online redo log
  - archiving mode, 1-87
  - block, 1-98
  - file size, 1-98
  - setting checkpoint interval, 1-98
- OPEN\_CURSORS initialization parameter, 1-117
- OPEN\_LINKS initialization parameter, 1-117
- OPEN\_LINKS\_PER\_INSTANCE initialization
  - parameter, 1-118
- operating system
  - authenticating remote clients, 1-147
  - authenticating users and passwords, 1-124
  - dependent parameters, 1-2
  - roles for remote clients, 1-147
- optimization
  - trading cursor space for time, 1-42
- OPTIMIZER\_CAPTURE\_SQL\_PLAN\_BASELINES
  - initialization parameter, 1-119
- OPTIMIZER\_DYNAMIC\_SAMPLING initialization
  - parameter, 1-119
- OPTIMIZER\_FEATURES\_ENABLE initialization
  - parameter, 1-119
- OPTIMIZER\_INDEX\_CACHING initialization

- parameter, 1-121
- OPTIMIZER\_INDEX\_COST\_ADJ initialization
  - parameter, 1-121
- OPTIMIZER\_MODE initialization parameter, 1-122
- OPTIMIZER\_SECURE\_VIEW\_MERGING
  - initialization parameter, 1-123
- OPTIMIZER\_USE\_INVISIBLE\_INDEXES
  - initialization parameter, 1-123
- OPTIMIZER\_USE\_PENDING\_STATISTICS
  - initialization parameter, 1-124
- OPTIMIZER\_USE\_SQL\_PLAN\_BASELINES
  - initialization parameter, 1-124
- ORPHAN\_KEY\_TABLE table. *See* DBA\_ORPHAN\_KEY\_TABLE view
- OS\_AUTHENT\_PREFIX initialization
  - parameter, 1-124
- OS\_ROLES initialization parameter, 1-125

## P

---

- parallel query
  - maximum number of instances, 1-128
  - maximum number of servers, 1-131
  - minimum number of queries, 1-132
- PARALLEL\_ADAPTIVE\_MULTI\_USER initialization
  - parameter, 1-126
- PARALLEL\_AUTOMATIC\_TUNING initialization
  - parameter, 1-126
- PARALLEL\_DEGREE\_LIMIT initialization
  - parameter, 1-127
- PARALLEL\_DEGREE\_POLICY initialization
  - parameter, 1-127
- PARALLEL\_EXECUTION\_MESSAGE\_SIZE
  - initialization parameter, 1-128
- PARALLEL\_FORCE\_LOCAL initialization
  - parameter, 1-129
- PARALLEL\_INSTANCE\_GROUP initialization
  - parameter, 1-129
- PARALLEL\_IO\_CAP\_ENABLED initialization
  - parameter, 1-130
- PARALLEL\_MAX\_SERVERS initialization
  - parameter, 1-130
- PARALLEL\_MIN\_PERCENT initialization
  - parameter, 1-131
- PARALLEL\_MIN\_SERVERS initialization
  - parameter, 1-132
- PARALLEL\_MIN\_TIME\_THRESHOLD initialization
  - parameter, 1-132
- PARALLEL\_SERVERS\_TARGET initialization
  - parameter, 1-133
- PARALLEL\_THREADS\_PER\_CPU initialization
  - parameter, 1-133
- passwords
  - authenticating, 1-124, 1-147
  - REMOTE\_LOGIN\_PASSWORDFILE initialization
    - parameter, 1-146
- PATH\_VIEW view, 6-51
- performance, 1-2
  - shared pool, 1-161
- PGA\_AGGREGATE\_TARGET initialization

- parameter, 1-134
- PLAN\_TABLE table, 6-51
- PLSCOPE\_SETTINGS initialization parameter, 1-135
- PLSQL\_CCFLAGS initialization parameter, 1-135
- PLSQL\_CODE\_TYPE initialization parameter, 1-136
- PLSQL\_DEBUG initialization parameter, 1-136
- PLSQL\_OPTIMIZE\_LEVEL initialization
  - parameter, 1-137
- PLSQL\_V2\_COMPATIBILITY initialization
  - parameter, 1-138
- PLSQL\_WARNINGS initialization parameter, 1-138
- PLUGGABLE\_SET\_CHECK view, 6-54
- PRE\_PAGE\_SGA initialization parameter, 1-140
- privileges
  - remote login, 1-146
  - RESTRICTED\_SESSION privilege, 1-83, 1-84
  - table-level select privileges, 1-167
- procedures
  - shared pool, 1-161
- processes
  - dispatcher process maximum number, 1-101
  - maximum shared server processes, 1-103
  - number of server processes, 1-78, 1-79, 1-162, 1-163
  - recovery, 1-143
  - trace files, 1-178
  - user processes, 1-141
- PROCESSES initialization parameter, 1-140
- PRODUCT\_COMPONENT\_VERSION view, 6-55
- profiles
  - resource limits, 1-148, 1-149
- PROXY\_USERS view, 6-55
- PSTUBTBL table, 6-55
- PUBLIC clause
  - of ALTER DATABASE
    - thread of redo, 1-172
- PUBLIC\_DEPENDENCY view, 6-56
- PUBLICSYN view, 6-56

## Q

---

- queries
  - hints, 1-122
- QUERY\_REWRITE\_ENABLED initialization
  - parameter, 1-141
- QUERY\_REWRITE\_INTEGRITY initialization
  - parameter, 1-142
- QUEUE\_PRIVILEGES view, 6-56

## R

---

- RC\_ARCHIVED\_LOG view, 2-4
- RC\_BACKUP\_ARCHIVELOG\_DETAILS view, 2-4
- RC\_BACKUP\_ARCHIVELOG\_SUMMARY
  - view, 2-4
- RC\_BACKUP\_CONTROLFILE view, 2-4
- RC\_BACKUP\_CONTROLFILE\_DETAILS view, 2-4
- RC\_BACKUP\_CONTROLFILE\_SUMMARY
  - view, 2-4
- RC\_BACKUP\_COPY\_DETAILS view, 2-4

- RC\_BACKUP\_COPY\_SUMMARY view, 2-4
- RC\_BACKUP\_CORRUPTION view, 2-4
- RC\_BACKUP\_DATAFILE view, 2-4
- RC\_BACKUP\_DATAFILE\_DETAILS view, 2-4
- RC\_BACKUP\_DATAFILE\_SUMMARY view, 2-4
- RC\_BACKUP\_FILES view, 2-4
- RC\_BACKUP\_PIECE view, 2-4
- RC\_BACKUP\_PIECE\_DETAILS view, 2-4
- RC\_BACKUP\_REDOLOG view, 2-4
- RC\_BACKUP\_SET view, 2-4
- RC\_BACKUP\_SET\_DETAILS view, 2-4
- RC\_BACKUP\_SET\_SUMMARY view, 2-4
- RC\_BACKUP\_SPFILE view, 2-4
- RC\_BACKUP\_SPFILE\_DETAILS view, 2-4
- RC\_BACKUP\_SPFILE\_SUMMARY view, 2-4
- RC\_CHECKPOINT view, 2-4
- RC\_CONTROLFILE\_COPY view, 2-4
- RC\_COPY\_CORRUPTION view, 2-4
- RC\_DATABASE view, 2-4
- RC\_DATABASE\_BLOCK\_CORRUPTION view, 2-4
- RC\_DATABASE\_INCARNATION view, 2-4
- RC\_DATAFILE view, 2-4
- RC\_DATAFILE\_COPY view, 2-4
- RC\_LOG\_HISTORY view, 2-4
- RC\_OFFLINE\_RANGE view, 2-4
- RC\_PROXY\_ARCHIVEDLOG view, 2-4
- RC\_PROXY\_ARCHIVELOG\_DETAILS view, 2-4
- RC\_PROXY\_ARCHIVELOG\_SUMMARY view, 2-4
- RC\_PROXY\_CONTROLFILE view, 2-4
- RC\_PROXY\_COPY\_DETAILS view, 2-4
- RC\_PROXY\_COPY\_SUMMARY view, 2-4
- RC\_PROXY\_DATAFILE view, 2-4
- RC\_REDO\_LOG view, 2-4
- RC\_REDO\_THREAD view, 2-4
- RC\_RESTORE\_POINT view, 2-4
- RC\_RESYNC view, 2-4
- RC\_RMAN\_BACKUP\_JOB\_DETAILS view, 2-4
- RC\_RMAN\_BACKUP\_SUBJOB\_DETAILS view, 2-4
- RC\_RMAN\_BACKUP\_TYPE view, 2-4
- RC\_RMAN\_CONFIGURATION view, 2-4
- RC\_RMAN\_OUTPUT view, 2-4
- RC\_RMAN\_STATUS view, 2-4
- RC\_SITE view, 2-4
- RC\_STORED\_SCRIPT view, 2-5
- RC\_STORED\_SCRIPT\_LINE view, 2-5
- RC\_TABLESPACE view, 2-5
- RC\_TEMPFILE view, 2-5
- RC\_UNUSABLE\_BACKUPFILE\_DETAILS view, 2-5
- RDBMS\_SERVER\_DN initialization
  - parameter, 1-142
- READ\_ONLY\_OPEN\_DELAYED initialization
  - parameter, 1-143
- Real Application Clusters
  - dynamic performance views, 7-2
  - initialization parameters
    - CIRCUITS, 1-30
    - CLUSTER\_DATABASE, 1-31
    - CLUSTER\_DATABASE\_INSTANCES, 1-31
    - CLUSTER\_INTERCONNECTS, 1-32
    - DISPATCHERS, 1-63
    - FAST\_START\_PARALLEL\_ROLLBACK, 1-70
    - PARALLEL\_ADAPTIVE\_MULTI\_
      - USER, 1-126
    - PARALLEL\_AUTOMATIC\_TUNING, 1-126
    - PARALLEL\_EXECUTION\_MESSAGE\_
      - SIZE, 1-128
    - PARALLEL\_INSTANCE\_GROUP, 1-129
    - PARALLEL\_MAX\_SERVERS, 1-130
    - PARALLEL\_MIN\_PERCENT, 1-131
    - PARALLEL\_MIN\_SERVERS, 1-132
    - PARALLEL\_THREADS\_PER\_CPU, 1-133
  - recovery
    - number of required processes, 1-143
  - RECOVERY\_PARALLELISM initialization
    - parameter, 1-143
  - RECYCLEBIN initialization parameter, 1-144
  - RECYCLEBIN synonym for USER\_RECYCLEBIN
    - view, 6-56
  - redo logs
    - buffer size, 1-98
  - redo thread, 1-172
  - REDO\_TRANSPORT\_USER initialization
    - parameter, 1-144
  - remote clients
    - authenticating, 1-147
  - remote logins, 1-146
  - REMOTE\_DEPENDENCIES\_MODE initialization
    - parameter, 1-145
  - REMOTE\_LISTENER initialization parameter, 1-145
  - REMOTE\_LOGIN\_PASSWORDFILE initialization
    - parameter, 1-146
  - REMOTE\_OS\_AUTHENT initialization
    - parameter, 1-146
  - REMOTE\_OS\_ROLES initialization parameter, 1-147
  - REPAIR\_TABLE table. *See* DBA\_REPAIR\_TABLE
    - view
  - REPLICATION\_DEPENDENCY\_TRACKING
    - initialization parameter, 1-147
  - REPORT\_COMPONENTS view, 6-57
  - REPORT\_FILES view, 6-57
  - REPORT\_FORMATS view, 6-57
  - resource limits for profiles, 1-148, 1-149
  - RESOURCE\_COST view, 6-58
  - RESOURCE\_LIMIT initialization parameter, 1-148
  - RESOURCE\_MANAGER\_CPU\_ALLOCATION
    - initialization parameter, 1-148
  - RESOURCE\_MANAGER\_PLAN initialization
    - parameter, 1-149
  - RESOURCE\_MAP table, 6-58
  - RESOURCE\_VIEW view, 6-58
  - RESULT\_CACHE\_MAX\_RESULT initialization
    - parameter, 1-149
  - RESULT\_CACHE\_MAX\_SIZE initialization
    - parameter, 1-150
  - RESULT\_CACHE\_MODE initialization
    - parameter, 1-150
  - RESULT\_CACHE\_REMOTE\_EXPIRATION
    - initialization parameter, 1-151
  - RESUMABLE\_TIMEOUT initialization
    - parameter, 1-151

- RMJVM.SQL script, B-5
- ROLE\_ROLE\_PRIVS view, 6-59
- ROLE\_SYS\_PRIVS view, 6-59
- ROLE\_TAB\_PRIVS view, 6-59
- ROLE\_WM\_PRIVS view, 2-3
- roles, 1-125
  - remote clients, 1-147
- ROLLBACK\_SEGMENTS initialization
  - parameter, 1-151

## S

- SCHEDULER\_BATCH\_ERRORS view, 6-59
- scripts

- CATALOG.SQL, B-1
- CATBLOCK.SQL, B-2
- CATCLUST.SQL, B-1
- CATDWGRD.SQL, B-4
- CATEXP7.SQL, B-2
- CATHS.SQL, B-2
- CATIO.SQL, B-2
- CATJAVA.SQL, B-5
- CATNOADT.SQL, B-4
- CATNOAUD.SQL, B-4
- CATNOHS.SQL, B-4
- CATNOPRT.SQL, B-4
- CATNOSVM.SQL, B-4
- CATNSNMP.SQL, B-4
- CATOCTK.SQL, B-2
- CATPROC.SQL, B-1
- CATQUEUE.SQL, B-2
- CATREP.SQL, B-2
- CATUPGRD.SQL, B-5
- data dictionary, B-2
- DBMSIOTC.SQL, B-2
- DBMSPOOL.SQL, B-2
- downgrading, B-4
- INITJVM.SQL, B-5
- Java, B-5
- RMJVM.SQL, B-5
- SQL scripts, B-1
- upgrading, B-4
- USERLOCK.SQL, B-2
- UTLBSTAT.SQL, B-2
- UTLCHN1.SQL, B-3
- UTLCONST.SQL, B-3
- UTLDTREE.SQL, B-3
- UTLESTAT.SQL, B-2
- UTLEXPT1.SQL, B-3
- UTLIP.SQL, B-3
- UTLIRP.SQL, B-3
- UTLLOCKT.SQL, B-3
- UTLPWDMG.SQL, B-3
- UTLRP.SQL, B-3
- UTLSAMPL.SQL, B-3
- UTLSCLN.SQL, B-3
- UTLTKPRF.SQL, B-4
- UTLU111I.SQL, B-5
- UTLU111S.SQL, B-5
- UTLVALID.SQL, B-4

- UTLXPLAN.SQL, B-4
- SEC\_CASE\_SENSITIVE\_LOGON initialization
  - parameter, 1-152
- SEC\_MAX\_FAILED\_LOGIN\_ATTEMPTS
  - initialization parameter, 1-153
- SEC\_PROTOCOL\_ERROR\_FURTHER\_ACTION
  - initialization parameter, 1-153
- SEC\_PROTOCOL\_ERROR\_TRACE\_ACTION
  - initialization parameter, 1-154
- SEC\_RETURN\_SERVER\_RELEASE\_BANNER
  - initialization parameter, 1-154
- SEQ synonym for USER\_SEQUENCES view, 6-60
- SERIAL\_REUSE initialization parameter, 1-155
- server parameter file
  - overview, 1-3
- server processes
  - number, 1-78, 1-79, 1-162, 1-163
- SERVICE\_NAMES initialization parameter, 1-156
- SESSION\_CACHED\_CURSORS initialization
  - parameter, 1-156
- SESSION\_CONTEXT view, 6-60
- SESSION\_MAX\_OPEN\_FILES initialization
  - parameter, 1-157
- SESSION\_PRIVS view, 6-60
- SESSION\_ROLES view, 6-60
- SESSIONS initialization parameter, 1-157
- SGA\_MAX\_SIZE initialization parameter, 1-158
- SGA\_TARGET initialization parameter, 1-158
- SHADOW\_CORE\_DUMP initialization
  - parameter, 1-159
- shared server
  - SESSIONS initialization parameter, 1-157
- shared server processes
  - maximum number, 1-103
- SHARED\_MEMORY\_ADDRESS initialization
  - parameter, 1-160
- SHARED\_POOL\_RESERVED\_SIZE initialization
  - parameter, 1-160
- SHARED\_POOL\_SIZE initialization
  - parameter, 1-161
- SHARED\_SERVER\_SESSIONS initialization
  - parameter, 1-162
- SHARED\_SERVERS initialization parameter, 1-162
- SHOW PARAMETERS command, 1-17
- SKIP\_UNUSABLE\_INDEXES initialization
  - parameter, 1-163
- SMTP\_OUT\_SERVER initialization parameter, 1-163
- SORT\_AREA\_RETAINED\_SIZE initialization
  - parameter, 1-164
- SORT\_AREA\_SIZE initialization parameter, 1-165
- sorting
  - maximum memory, 1-164
  - ORDER BY queries, 1-112
- SOURCE\_SIZE view, 6-60
- SPFILE initialization parameter, 1-166
- SQL scripts
  - creating the data dictionary, B-1
  - optional, B-2
  - required, B-1
- SQL\_TRACE initialization parameter, 1-166



- SQL92\_SECURITY initialization parameter, 1-167
- SQLTUNE\_CATEGORY initialization
  - parameter, 1-168
- STANDBY\_ARCHIVE\_DEST initialization
  - parameter, 1-168
- STANDBY\_FILE\_MANAGEMENT initialization
  - parameter, 1-168
- STAR\_TRANSFORMATION\_ENABLED initialization
  - parameter, 1-169
- starting up
  - instance number, 1-77
  - startup order, 1-77
- statistics
  - background checkpoints completed, E-2
  - background checkpoints started, E-2
  - background timeouts, E-2
  - branch node splits, E-2
  - buffer is not pinned count, E-2
  - buffer is pinned count, E-2
  - bytes received via SQL\*Net from client, E-2
  - bytes received via SQL\*Net from dblink, E-2
  - bytes sent via SQL\*Net to client, E-2
  - bytes sent via SQL\*Net to dblink, E-2
  - Cached Commit SCN referenced, E-2
  - calls to get snapshot scn
    - kcmgss, E-2
  - calls to kcmgas, E-3
  - calls to kcmgcs, E-3
  - calls to kcmgrs, E-3
  - change write time, E-3
  - cleanouts and rollbacks - consistent read gets, E-3
  - cleanouts only - consistent read gets, E-3
  - cluster key scan block gets, E-3
  - cluster key scans, E-3
  - cold recycle reads, E-3
  - commit cleanout failures
    - block lost, E-3
    - buffer being written, E-3
    - callback failure, E-3
    - cannot pin, E-3
    - hot backup in progress, E-3
    - write disabled, E-3
  - commit cleanouts, E-3
  - commit cleanouts successfully completed, E-3
  - Commit SCN cached, E-3
  - consistent changes, E-3
  - consistent gets, E-4
  - consistent gets direct, E-4
  - consistent gets from cache, E-4
  - CPU used by this session, E-4
  - CPU used when call started, E-4
  - CR blocks created, E-4
  - current blocks converted for CR, E-4
  - cursor authentications, E-4
  - data blocks consistent reads - undo records
    - applied, E-4
  - db block changes, E-4
  - db block gets, E-4
  - db block gets direct, E-4
  - db block gets from cache, E-4
  - DBWR buffers scanned, E-5
  - DBWR checkpoint buffers written, E-5
  - DBWR checkpoints, 1-98, E-5
  - DBWR cross instance writes, E-5
  - DBWR free buffers found, E-5
  - DBWR lru scans, E-5
  - DBWR make free requests, E-5
  - DBWR revisited being-written buffer, E-5
  - DBWR summed scan depth, E-5
  - DBWR transaction table writes, E-5
  - DBWR undo block writes, E-5
  - DDL statements parallelized, E-5
  - deferred (CURRENT) block cleanout
    - applications, E-5
  - DFO trees parallelized, E-5
  - dirty buffers inspected, E-5
  - DML statements parallelized, E-5
  - enqueue conversions, E-6
  - enqueue deadlocks, E-6
  - enqueue releases, E-6
  - enqueue requests, E-6
  - enqueue timeouts, E-6
  - enqueue waits, E-6
  - exchange deadlocks, E-6
  - execute count, E-6
  - flash cache eviction: aged out, E-6
  - flash cache eviction: buffer pinned, E-6
  - flash cache eviction: invalidated, E-6
  - flash cache insert skip: corrupt, E-6
  - flash cache insert skip: DBWR overloaded, E-6
  - flash cache insert skip: exists, E-6
  - flash cache insert skip: modification, E-6
  - flash cache insert skip: not current, E-6
  - flash cache insert skip: not useful, E-6
  - flash cache inserts, E-6
  - flashback log write bytes, E-6
  - flashback log writes, E-6
  - free buffer inspected, E-6
  - free buffer requested, E-7
  - global cache blocks corrupt, E-7
  - global cache convert time, E-7
  - global cache convert timeouts, E-7
  - global cache converts, E-7
  - global cache cr block log flush time, E-7
  - global cache cr block receive time, E-7
  - global cache cr block send time, E-7
  - global cache cr block serve time, E-7
  - global cache cr blocks served, E-7
  - global cache cr requests blocked, E-7
  - global cache cr timeouts, E-7
  - global cache defers, E-7
  - global cache freelist waits, E-7
  - global cache get time, E-7
  - global cache gets, E-7
  - global cache prepare failures, E-7
  - global lock async converts, E-7
  - global lock async gets, E-7
  - global lock convert time, E-8
  - global lock get time, E-8
  - global lock releases, E-8

- global lock sync converts, E-8
- global lock sync gets, E-8
- hot buffers moved to head of LRU, E-8
- immediate (CR) block cleanout applications, E-8
- immediate (CURRENT) block cleanout applications, E-8
- index fast full scans (direct read), E-8
- index fast full scans (full), E-8
- index fast full scans (rowid ranges), E-8
- instance recovery database freeze count, E-8
- kcmccs called get current scn, E-8
- kcmccs read scn without going to DLM, E-8
- kcmggs waited for batching, E-8
- leaf node splits, E-8
- lob reads, E-8
- lob writes, E-8
- lob writes unaligned, E-8
- logons cumulative, E-8
- logons current, E-8
- messages received, E-9
- messages sent, E-9
- native hash arithmetic execute, E-9
- native hash arithmetic fail, E-9
- next scns gotten without going to DLM, E-9
- no buffer to keep pinned count, E-9
- no work - consistent read gets, E-9
- opened cursors cumulative, E-9
- opened cursors current, E-9
- opens of replaced files, E-9
- opens requiring cache replacement, E-9
- operating system
  - OS All other sleep time, E-9
  - OS Chars read and written, E-9
  - OS Data page fault sleep time, E-9
  - OS Input blocks, E-9
  - OS Involuntary context switches, E-9
  - OS Kernel page fault sleep time, E-9
  - OS Major page faults, E-9
  - OS Messages received, E-9
  - OS Messages sent, E-9
  - OS Minor page faults, E-9
  - OS Other system trap CPU time, E-10
  - OS Output blocks, E-10
  - OS Process heap time, E-10
  - OS Signals received, E-10
  - OS Swaps, E-10
  - OS System call CPU time, E-10
  - OS System calls, E-10
  - OS Text page fault sleep time, E-10
  - OS User level CPU time, E-10
  - OS User lock wait sleep time, E-10
  - OS Voluntary context switches, E-10
  - OS Wait-cpu (latency) time, E-10
  - Process stack size, E-10
- Parallel operations downgraded 1 to 25 pct, E-10
- Parallel operations downgraded 25 to 50 pct, E-10
- Parallel operations downgraded 50 to 75 pct, E-10
- Parallel operations downgraded 75 to 99 pct, E-10
- Parallel operations downgraded to serial, E-10
- Parallel operations not downgraded, E-10
- parse count (describe), E-10
- parse count (hard), E-10
- parse count (total), E-11
- parse time cpu, E-11
- parse time elapsed, E-11
- physical read bytes, E-11
- physical read flash cache hits, E-11
- physical read IO requests, E-11
- physical read requests optimized, E-11
- physical read total bytes, E-11
- physical read total IO requests, E-11
- physical read total multi block requests, E-11
- physical reads, E-11
- physical reads cache, E-11
- physical reads cache prefetch, E-11
- physical reads direct, E-11
- physical reads direct (lob), E-11
- physical reads direct temporary tablespace, E-11
- physical reads for flashback new, E-12
- physical reads prefetch warmup, E-12
- physical write bytes, E-12
- physical write IO requests, E-12
- physical write total bytes, E-12
- physical write total IO requests, E-12
- physical write total multi block requests, E-12
- physical writes, E-12
- physical writes direct, E-12
- physical writes direct (lob), E-12
- physical writes direct temporary tablespace, E-12
- physical writes from cache, E-12
- physical writes non checkpoint, E-12
- pinned buffers inspected, E-13
- prefetched blocks aged out before use, E-13
- process last non-idle time, E-13
- PX local messages recv'd, E-13
- PX local messages sent, E-13
- PX remote messages recv'd, E-13
- PX remote messages sent, E-13
- queries parallelized, E-13
- recovery array read time, E-13
- recovery array reads, E-13
- recovery blocks read, E-13
- recovery blocks read for lost write detection, E-13
- recovery blocks skipped lost write checks, E-13
- recursive calls, E-13
- recursive cpu usage, E-13
- redo blocks checksummed by FG (exclusive), E-13
- redo blocks checksummed by LGWR, E-13
- redo blocks written, E-13
- redo buffer allocation retries, E-13
- redo entries, E-14
- redo entries for lost write detection, E-14
- redo log space requests, E-14
- redo log space wait time, E-14
- redo ordering marks, E-14
- redo size, E-14

- redo size for lost write detection, E-14
- redo synch time, E-14
- redo synch writes, E-14
- redo wastage, E-14
- redo write time, E-14
- redo writer latching time, E-14
- redo writes, E-14
- remote instance undo block writes, E-15
- remote instance undo header writes, E-15
- rollback changes - undo records applied, E-15
- rollbacks only - consistent read gets, E-15
- rows fetched via callback, E-15
- serializable aborts, E-15
- session connect time, E-15
- session cursor cache count, E-15
- session cursor cache hits, E-15
- session logical reads, E-15
- session pga memory, E-15
- session pga memory max, E-15
- session stored procedure space, E-15
- session uga memory, E-15
- session uga memory max, E-15
- shared io pool buffer get failure, E-15
- shared io pool buffer get success, E-15
- sorts (disk), E-16
- sorts (memory), E-16
- sorts (rows), E-16
- SQL\*Net roundtrips to/from client, E-16
- SQL\*Net roundtrips to/from dblink, E-16
- summed dirty queue length, E-16
- switch current to new buffer, E-16
- table fetch by rowid, E-16
- table fetch continued row, E-16
- table scan blocks gotten, E-16
- table scan rows gotten, E-16
- table scans (cache partitions), E-16
- table scans (direct read), E-17
- table scans (long tables), E-17
- table scans (rowid ranges), E-17
- table scans (short tables), E-17
- timed, 1-173
- total file opens, E-17
- transaction lock background get time, E-17
- transaction lock background gets, E-17
- transaction lock foreground requests, E-17
- transaction lock foreground wait time, E-17
- transaction rollbacks, E-17
- transaction tables consistent read rollbacks, E-17
- transaction tables consistent reads - undo records applied, E-17
- Unnecessary process cleanup for SCN batching, E-17
- user calls, E-17
- user commits, E-17
- user rollbacks, E-18
- write clones created in background, E-18
- write clones created in foreground, E-18
- STATISTICS\_LEVEL initialization parameter, 1-170
- STMT\_AUDIT\_OPTION\_MAP table, 6-60
- STREAMS\_POOL\_SIZE initialization

- parameter, 1-171
- switch redo log file, 1-98
- SYN synonym for USER\_SYNONYMS view, 6-61
- SYNONYMS view, 6-61
- SYS\_OBJECTS view, 6-61
- SYSCATALOG view, 6-61
- SYSFILES view, 6-61
- SYSSEGOBJ view, 6-61
- system global area, 1-2
  - buffer areas, 1-98
- system performance, 1-2
- SYSTEM\_PRIVILEGE\_MAP table, 6-61

## T

---

- TAB view, 6-62
- TABLE\_PRIVILEGE\_MAP table, 6-62
- tables
  - data dictionary, 2-1
  - DML locks, 1-66
  - locating free space, 1-77
- TABQUOTAS view, 6-62
- TABS synonym for USER\_TABLES view, 6-62
- tape archiving destination, 1-87
- TAPE\_ASYNC\_IO initialization parameter, 1-171
- territory, 1-108, 1-113
- THREAD initialization parameter, 1-172
- TIMED\_OS\_STATISTICS initialization
  - parameter, 1-172
- TIMED\_STATISTICS initialization parameter, 1-173
  - file read/write statistics, 7-99, 9-85
- TO\_CHAR function, 1-107
- TO\_DATE function, 1-107
- trace files
  - destination, 1-178
  - maximum size, 1-102
- TRACE\_ENABLED initialization parameter, 1-173
- TRACEFILE\_IDENTIFIER initialization
  - parameter, 1-174
- transactions
  - data locking, 1-66
- TRANSACTIONS initialization parameter, 1-175
  - DML locks, 1-66
- TRANSACTIONS\_PER\_ROLLBACK\_SEGMENT
  - initialization parameter, 1-175
- TRUSTED\_SERVERS view, 6-62
- TS\_PITR\_CHECK view, 6-63
- TS\_PITR\_OBJECTS TO\_BE\_DROPPED view, 6-63

## U

---

- UNDO\_MANAGEMENT initialization
  - parameter, 1-176
- UNDO\_RETENTION initialization parameter, 1-176
- UNDO\_TABLESPACE initialization
  - parameter, 1-177
- UNI\_PLUGGABLE\_SET\_CHECK view, 6-63
- updates
  - locating free space, 1-77
- upgrading

- scripts, B-4
- uppercase characters, 1-4
- USE\_INDIRECT\_DATA\_BUFFERS initialization
  - parameter, 1-177
- user processes
  - trace files, 1-178
- USER\_ADDM\_FDG\_BREAKDOWN view, 6-64
- USER\_ADDM\_FINDINGS view, 6-64
- USER\_ADDM\_INSTANCES view, 6-64
- USER\_ADDM\_TASKS view, 6-64
- USER\_ADVISOR\_ACTIONS view, 6-64
- USER\_ADVISOR\_DIR\_TASK\_INST view, 6-65
- USER\_ADVISOR\_EXEC\_PARAMETERS view, 6-65
- USER\_ADVISOR\_EXECUTIONS view, 6-65
- USER\_ADVISOR\_FDG\_BREAKDOWN view, 6-65
- USER\_ADVISOR\_FINDINGS view, 6-65
- USER\_ADVISOR\_JOURNAL view, 6-65
- USER\_ADVISOR\_LOG view, 6-65
- USER\_ADVISOR\_OBJECTS view, 6-66
- USER\_ADVISOR\_PARAMETERS view, 6-66
- USER\_ADVISOR\_RATIONALE view, 6-66
- USER\_ADVISOR\_RECOMMENDATIONS
  - view, 6-66
- USER\_ADVISOR\_SQLA\_REC\_SUM view, 6-66
- USER\_ADVISOR\_SQLA\_TABLES view, 6-66
- USER\_ADVISOR\_SQLA\_WK\_MAP view, 6-66
- USER\_ADVISOR\_SQLA\_WK\_STMTS view, 6-67
- USER\_ADVISOR\_SQLPLANS view, 6-67
- USER\_ADVISOR\_SQLSTATS view, 6-67
- USER\_ADVISOR\_SQLW\_JOURNAL view, 6-67
- USER\_ADVISOR\_SQLW\_PARAMETERS view, 6-67
- USER\_ADVISOR\_SQLW\_STMTS view, 6-67
- USER\_ADVISOR\_SQLW\_SUM view, 6-67
- USER\_ADVISOR\_SQLW\_TABLES view, 6-68
- USER\_ADVISOR\_SQLW\_TEMPLATES view, 6-68
- USER\_ADVISOR\_TASKS view, 6-68
- USER\_ADVISOR\_TEMPLATES view, 6-68
- USER\_ALL\_TABLES view, 6-68
- USER\_AQ\_AGENT\_PRIVS view, 6-68
- USER\_ARGUMENTS view, 6-68
- USER\_ASSEMBLIES view, 6-69
- USER\_ASSOCIATIONS view, 6-69
- USER\_ATTRIBUTE\_TRANSFORMATIONS
  - view, 6-69
- USER\_AUDIT\_OBJECT view, 6-69
- USER\_AUDIT\_POLICIES view, 6-69
- USER\_AUDIT\_POLICY\_COLUMNS view, 6-69
- USER\_AUDIT\_SESSION view, 6-69
- USER\_AUDIT\_STATEMENT view, 6-70
- USER\_AUDIT\_TRAIL view, 6-70
- USER\_AW\_PS view, 6-70
- USER\_AWS view, 6-70
- USER\_BASE\_TABLE\_MVIEWS view, 6-70
- USER\_CATALOG view, 6-70
  - CAT synonym, 3-114
- USER\_CHANGE\_NOTIFICATION\_REGS
  - view, 6-70
- USER\_CLU\_COLUMNS view, 6-70
- USER\_CLUSTER\_HASH\_EXPRESSIONS view, 6-71
- USER\_CLUSTERS view, 6-71
  - CLU synonym, 3-116
- USER\_COL\_COMMENTS view, 6-71
- USER\_COL\_PENDING\_STATS view, 6-71
- USER\_COL\_PRIVS view, 6-71
- USER\_COL\_PRIVS\_MADE view, 6-71
- USER\_COL\_PRIVS\_RECD view, 6-71
- USER\_COLL\_TYPES view, 6-72
- USER\_COMPARISON view, 6-72
- USER\_COMPARISON\_COLUMNS view, 6-72
- USER\_COMPARISON\_ROW\_DIF view, 6-72
- USER\_COMPARISON\_SCAN view, 6-72
- USER\_COMPARISON\_SCAN\_VALUES view, 6-72
- USER\_CONS\_COLUMNS view, 6-72
- USER\_CONS\_OBJ\_COLUMNS view, 6-72
- USER\_CONSTRAINTS view, 6-73
- USER\_CQ\_NOTIFICATION\_QUERIES view, 6-73
- USER\_CUBE\_ATTR\_VISIBILITY view, 6-73
- USER\_CUBE\_ATTRIBUTES view, 6-73
- USER\_CUBE\_BUILD\_PROCESSES view, 6-73
- USER\_CUBE\_CALCULATED\_MEMBERS
  - view, 6-73
- USER\_CUBE\_DIM\_LEVELS view, 6-73
- USER\_CUBE\_DIM\_MODELS view, 6-73
- USER\_CUBE\_DIM\_VIEW\_COLUMNS view, 6-74
- USER\_CUBE\_DIM\_VIEWS view, 6-74
- USER\_CUBE\_DIMENSIONALITY view, 6-74
- USER\_CUBE\_DIMENSIONS view, 6-74
- USER\_CUBE\_HIER\_LEVELS view, 6-74
- USER\_CUBE\_HIER\_VIEW\_COLUMNS view, 6-74
- USER\_CUBE\_HIER\_VIEWS view, 6-74
- USER\_CUBE\_HIERARCHIES view, 6-74
- USER\_CUBE\_MEASURES view, 6-74
- USER\_CUBE\_VIEW\_COLUMNS view, 6-75
- USER\_CUBE\_VIEWS view, 6-75
- USER\_CUBES view, 6-75
- USER\_DATAPUMP\_JOBS view, 6-75
- USER\_DB\_LINKS view, 6-75
- USER\_DBFS\_HS\_FILES view, 6-75
- USER\_DEPENDENCIES view, 6-76
- USER\_DIM\_ATTRIBUTES view, 6-76
- USER\_DIM\_CHILD\_OF view, 6-76
- USER\_DIM\_HIERARCHIES view, 6-76
- USER\_DIM\_JOIN\_KEY view, 6-76
- USER\_DIM\_LEVEL\_KEY view, 6-76
- USER\_DIM\_LEVELS view, 6-76
- USER\_DIMENSIONS view, 6-76
- USER\_DUMP\_DEST initialization parameter, 1-178
- USER\_EDITIONING\_VIEW\_COLS view, 6-76
- USER\_EDITIONING\_VIEW\_COLS\_AE view, 6-77
- USER\_EDITIONING\_VIEWS view, 6-77
- USER\_EDITIONING\_VIEWS\_AE view, 6-77
- USER\_ENCRYPTED\_COLUMNS view, 6-77
- USER\_EPG\_DAD\_AUTHORIZATION view, 6-77
- USER\_ERRORS view, 6-77
- USER\_ERRORS\_AE view, 6-77
- USER\_EVALUATION\_CONTEXT\_TABLES
  - view, 6-78
- USER\_EVALUATION\_CONTEXT\_VARS view, 6-78
- USER\_EVALUATION\_CONTEXTS view, 6-78
- USER\_EXTENTS view, 6-78

USER\_EXTERNAL\_LOCATIONS view, 6-78  
 USER\_EXTERNAL\_TABLES view, 6-78  
 USER\_FILE\_GROUP\_EXPORT\_INFO view, 6-78  
 USER\_FILE\_GROUP\_FILES view, 6-79  
 USER\_FILE\_GROUP\_TABLES view, 6-79  
 USER\_FILE\_GROUP\_TABLESPACES view, 6-79  
 USER\_FILE\_GROUP\_VERSIONS view, 6-79  
 USER\_FILE\_GROUPS view, 6-79  
 USER\_FLASHBACK\_ARCHIVE view, 6-79  
 USER\_FLASHBACK\_ARCHIVE\_TABLES view, 6-80  
 USER\_FLASHBACK\_TXN\_REPORT view, 6-80  
 USER\_FLASHBACK\_TXN\_STATE view, 6-80  
 USER\_FREE\_SPACE view, 6-80  
 USER\_HISTOGRAMS synonym for USER\_TAB\_HISTOGRAMS, 6-80  
 USER\_IDENTIFIERS view, 6-80  
 USER\_IND\_COLUMNS view, 6-80  
 USER\_IND\_EXPRESSIONS view, 6-81  
 USER\_IND\_PARTITIONS view, 6-81  
 USER\_IND\_PENDING\_STATS view, 6-81  
 USER\_IND\_STATISTICS view, 6-81  
 USER\_IND\_SUBPARTITIONS view, 6-81  
 USER\_INDEXES view, 6-81  
     IND synonym, 6-48  
 USER\_INDEXTYPE\_ARRAYTYPES view, 6-81  
 USER\_INDEXTYPE\_COMMENTS view, 6-81  
 USER\_INDEXTYPE\_OPERATORS view, 6-82  
 USER\_INDEXTYPES view, 6-82  
 USER\_INTERNAL\_TRIGGERS view, 6-82  
 USER\_JAVA\_ARGUMENTS view, 6-82  
 USER\_JAVA\_CLASSES view, 6-82  
 USER\_JAVA\_COMPILER\_OPTIONS view, 6-82  
 USER\_JAVA\_DERIVATIONS view, 6-82  
 USER\_JAVA\_FIELDS view, 6-83  
 USER\_JAVA\_IMPLEMENTATIONS view, 6-83  
 USER\_JAVA\_INNERS view, 6-83  
 USER\_JAVA\_LAYOUTS view, 6-83  
 USER\_JAVA\_METHODS view, 6-83  
 USER\_JAVA\_NCOMPS view, 6-83  
 USER\_JAVA\_POLICY view, 6-83  
 USER\_JAVA\_RESOLVERS view, 6-84  
 USER\_JAVA\_THROWS view, 6-84  
 USER\_JOBS view, 6-84  
     ALL\_JOBS synonym, 2-86  
 USER\_JOIN\_IND\_COLUMNS view, 6-84  
 USER\_LIBRARIES view, 6-84  
 USER\_LOB\_PARTITIONS view, 6-84  
 USER\_LOB\_SUBPARTITIONS view, 6-84  
 USER\_LOB\_TEMPLATES view, 6-84  
 USER\_LOBS view, 6-85  
 USER\_LOG\_GROUP\_COLUMNS view, 6-85  
 USER\_LOG\_GROUPS view, 6-85  
 USER\_MEASURE\_FOLDER\_CONTENTS view, 6-85  
 USER\_MEASURE\_FOLDERS view, 6-85  
 USER\_METHOD\_PARAMS view, 6-85  
 USER\_METHOD\_RESULTS view, 6-85  
 USER\_MINING\_MODEL\_ATTRIBUTES view, 6-85  
 USER\_MINING\_MODEL\_SETTINGS view, 6-86  
 USER\_MINING\_MODELS view, 6-86  
 USER\_MP\_GRAPH\_WORKSPACES view, 2-3  
 USER\_MP\_PARENT\_WORKSPACES view, 2-3  
 USER\_MVIEW\_AGGREGATES view, 6-86  
 USER\_MVIEW\_ANALYSIS view, 6-86  
 USER\_MVIEW\_COMMENTS view, 6-86  
 USER\_MVIEW\_DETAIL\_PARTITION view, 6-86  
 USER\_MVIEW\_DETAIL\_RELATIONS view, 6-87  
 USER\_MVIEW\_DETAIL\_SUBPARTITION view, 6-87  
 USER\_MVIEW\_JOINS view, 6-87  
 USER\_MVIEW\_KEYS view, 6-87  
 USER\_MVIEW\_LOGS view, 6-87  
 USER\_MVIEW\_REFRESH\_TIMES view, 6-87  
 USER\_MVIEWS view, 6-87  
 USER\_NESTED\_TABLE\_COLS view, 6-87  
 USER\_NESTED\_TABLES view, 6-88  
 USER\_NETWORK\_ACL\_PRIVILEGES view, 6-88  
 USER\_OBJ\_AUDIT\_OPTS view, 6-88  
 USER\_OBJ\_COLATTRS view, 6-88  
 USER\_OBJECT\_SIZE view, 6-88  
 USER\_OBJECT\_TABLES view, 6-88  
 USER\_OBJECTS view, 6-88  
     OBJ synonym, 6-51  
 USER\_OBJECTS\_AE view, 6-89  
 USER\_OPANCILLARY view, 6-89  
 USER\_OPARGUMENTS view, 6-89  
 USER\_OPBINDINGS view, 6-89  
 USER\_OPERATOR\_COMMENTS view, 6-89  
 USER\_OPERATORS view, 6-89  
 USER\_OUTLINE\_HINTS view, 6-89  
     ALL\_OUTLINE\_HINTS synonym, 2-121  
 USER\_OUTLINES view, 6-89  
     ALL\_OUTLINES synonym, 2-121  
 USER\_PARALLEL\_EXECUTE\_CHUNKS view, 6-90  
 USER\_PARALLEL\_EXECUTE\_TASKS view, 6-90  
 USER\_PART\_COL\_STATISTICS view, 6-90  
 USER\_PART\_HISTOGRAMS view, 6-90  
 USER\_PART\_INDEXES view, 6-90  
 USER\_PART\_KEY\_COLUMNS view, 6-90  
 USER\_PART\_LOBS view, 6-90  
 USER\_PART\_TABLES view, 6-91  
 USER\_PARTIAL\_DROP\_TABS view, 6-91  
 USER\_PASSWORD\_LIMITS view, 6-91  
 USER\_PENDING\_CONV\_TABLES view, 6-91  
 USER\_PLSQL\_OBJECT\_SETTINGS view, 6-91  
 USER\_POLICIES view, 6-91  
 USER\_POLICY\_CONTEXTS view, 6-91  
 USER\_POLICY\_GROUPS view, 6-92  
 USER\_PROCEDURES view, 6-92  
 USER\_PROXIES view, 6-92  
 USER\_PUBLISHED\_COLUMNS view, 6-92  
     ALL\_PUBLISHED\_COLUMNS synonym, 3-16  
 USER\_QUEUE\_SCHEDULES view, 6-92  
 USER\_QUEUE\_SUBSCRIBERS view, 6-92  
 USER\_QUEUE\_TABLES view, 6-92  
 USER\_QUEUES view, 6-93  
 USER\_RECYCLEBIN view, 6-93  
     RECYCLEBIN synonym, 6-56  
 USER\_REFRESH view, 6-93  
 USER\_REFRESH\_CHILDREN view, 6-93

USER\_REFS view, 6-93  
 USER\_REGISTERED\_MVIEWS view, 6-93  
 USER\_REGISTRY view, 6-93  
 USER\_REMOVED\_WORKSPACES view, 2-3  
 USER\_REPCAT view, 2-2  
 USER\_REPCAT\_REFRESH\_TEMPLATES view, 2-2  
 USER\_REPCAT\_TEMPLATE\_OBJECTS view, 2-2  
 USER\_REPCAT\_TEMPLATE\_PARMS view, 2-2  
 USER\_REPCAT\_TEMPLATE\_SITES view, 2-2  
 USER\_REPCAT\_USER\_AUTHORIZATION view, 2-2  
 USER\_REPCAT\_USER\_PARM\_VALUES view, 2-2  
 USER\_REPCATLOG view, 2-2  
 USER\_REPCOLUMN view, 2-2  
 USER\_REPCOLUMN\_GROUP view, 2-2  
 USER\_REPCONFLICT view, 2-2  
 USER\_REPDDL view, 2-2  
 USER\_REPFLAVOR\_COLUMNS view, 2-2  
 USER\_REPFLAVOR\_OBJECTS view, 2-2  
 USER\_REPFLAVORS view, 2-2  
 USER\_REPGENERATED view, 2-2  
 USER\_REPGENOBJECTS view, 2-2  
 USER\_REPGROUP view, 2-2  
 USER\_REPGROUP\_PRIVILEGES view, 2-2  
 USER\_REPGROUPED\_COLUMN view, 2-2  
 USER\_REPKEY\_COLUMNS view, 2-2  
 USER\_REPOBJECT view, 2-2  
 USER\_REPPARAMETER\_COLUMN view, 2-2  
 USER\_REPPRIORITY view, 2-2  
 USER\_REPPRIORITY\_GROUP view, 2-2  
 USER\_REPPROP view, 2-2  
 USER\_REPRESOL\_STATS\_CONTROL view, 2-2  
 USER\_REPRESOLUTION view, 2-2  
 USER\_REPRESOLUTION\_METHOD view, 2-2  
 USER\_REPRESOLUTION\_STATISTICS view, 2-2  
 USER\_REPSHEMA view, 2-2  
 USER\_REPSITES view, 2-2  
 USER\_RESOURCE\_LIMITS view, 6-93  
 USER\_RESUMABLE view, 6-94  
 USER\_REWRITE\_EQUIVALENCES view, 6-94  
 USER\_ROLE\_PRIVS view, 6-94  
 USER\_RSRC\_CONSUMER\_GROUP\_PRIVS view, 6-94  
 USER\_RSRC\_MANAGER\_SYSTEM\_PRIVS view, 6-94  
 USER\_RULE\_SET\_RULES view, 6-94  
 USER\_RULE\_SETS view, 6-95  
 USER\_RULES view, 6-95  
 USER\_SCHEDULER\_CHAIN\_RULES view, 6-95  
 USER\_SCHEDULER\_CHAIN\_STEPS view, 6-95  
 USER\_SCHEDULER\_CHAINS view, 6-95  
 USER\_SCHEDULER\_CREDENTIALS view, 6-95  
 USER\_SCHEDULER\_DB\_DESTS view, 6-95  
 USER\_SCHEDULER\_DESTS view, 6-96  
 USER\_SCHEDULER\_FILE\_WATCHERS view, 6-96  
 USER\_SCHEDULER\_GROUP\_MEMBERS view, 6-96  
 USER\_SCHEDULER\_GROUPS view, 6-96  
 USER\_SCHEDULER\_JOB\_ARGS view, 6-96  
 USER\_SCHEDULER\_JOB\_DESTS view, 6-96  
 USER\_SCHEDULER\_JOB\_LOG view, 6-96  
 USER\_SCHEDULER\_JOB\_RUN\_DETAILS view, 6-97  
 USER\_SCHEDULER\_JOBS view, 6-97  
 USER\_SCHEDULER\_NOTIFICATIONS view, 6-97  
 USER\_SCHEDULER\_PROGRAM\_ARGS view, 6-97  
 USER\_SCHEDULER\_PROGRAMS view, 6-97  
 USER\_SCHEDULER\_REMOTE\_JOBSTATE view, 6-97  
 USER\_SCHEDULER\_RUNNING\_CHAINS view, 6-97  
 USER\_SCHEDULER\_RUNNING\_JOBS view, 6-98  
 USER\_SCHEDULER\_SCHEDULES view, 6-98  
 USER\_SEC\_RELEVANT\_COLS view, 6-98  
 USER\_SECONDARY\_OBJECTS view, 6-98  
 USER\_SEGMENTS view, 6-98  
 USER\_SEQUENCES view, 6-98  
     SEQ synonym, 6-60  
 USER\_SOURCE view, 6-98  
 USER\_SOURCE\_AE view, 6-99  
 USER\_SOURCE\_TABLES view, 6-99  
     ALL\_SOURCE\_TABLES synonym, 3-52  
 USER\_SQLJ\_TYPE\_ATTRS view, 6-99  
 USER\_SQLJ\_TYPE\_METHODS view, 6-99  
 USER\_SQLJ\_TYPES view, 6-99  
 USER\_SQLSET view, 6-99  
 USER\_SQLSET\_BINDS view, 6-99  
 USER\_SQLSET\_PLANS view, 6-100  
 USER\_SQLSET\_REFERENCES view, 6-100  
 USER\_SQLSET\_STATEMENTS view, 6-100  
 USER\_SQLTUNE\_BINDS view, 6-100  
 USER\_SQLTUNE\_PLANS view, 6-100  
 USER\_SQLTUNE\_RATIONALE\_PLAN view, 6-100  
 USER\_SQLTUNE\_STATISTICS view, 6-100  
 USER\_STAT\_EXTENSIONS view, 6-101  
 USER\_STORED\_SETTINGS view, 6-101  
 USER\_SUBPART\_COL\_STATISTICS view, 6-101  
 USER\_SUBPART\_HISTOGRAMS view, 6-101  
 USER\_SUBPART\_KEY\_COLUMNS view, 6-101  
 USER\_SUBPARTITION\_TEMPLATES view, 6-101  
 USER\_SUBSCR\_REGISTRATIONS view, 6-101  
 USER\_SUBSCRIBED\_COLUMNS view, 6-102  
     ALL\_SUBSCRIBED\_COLUMNS synonym, 3-74  
 USER\_SUBSCRIBED\_TABLES view, 6-102  
     ALL\_SUBSCRIBED\_TABLES synonym, 3-74  
 USER\_SUBSCRIPTIONS view, 6-102  
     ALL\_SUBSCRIPTIONS synonym, 3-74  
 USER\_SYNONYMS view, 6-102  
     SYN synonym, 6-61  
 USER\_SYS\_PRIVS view, 6-102  
 USER\_TAB\_COL\_STATISTICS view, 6-102  
 USER\_TAB\_COLS view, 6-102  
 USER\_TAB\_COLUMNS view, 6-103  
     COLS synonym, 3-116  
 USER\_TAB\_COMMENTS view, 6-103  
 USER\_TAB\_HISTGRM\_PENDING\_STATS view, 6-103  
 USER\_TAB\_HISTOGRAMS view, 6-103  
     USER\_HISTOGRAMS synonym, 6-80  
 USER\_TAB\_MODIFICATIONS view, 6-103

- USER\_TAB\_PARTITIONS view, 6-103
- USER\_TAB\_PENDING\_STATS view, 6-104
- USER\_TAB\_PRIVS view, 6-104
- USER\_TAB\_PRIVS\_MADE view, 6-104
- USER\_TAB\_PRIVS\_RECD view, 6-104
- USER\_TAB\_STAT\_PREFS view, 6-104
- USER\_TAB\_STATISTICS view, 6-104
- USER\_TAB\_STATS\_HISTORY view, 6-104
- USER\_TAB\_SUBPARTITIONS view, 6-104
- USER\_TABLES view, 6-105
  - TABS synonym, 6-62
- USER\_TABLESPACES view, 6-105
- USER\_TRANSFORMATIONS view, 6-105
- USER\_TRIGGER\_COLS view, 6-105
- USER\_TRIGGER\_ORDERING view, 6-105
- USER\_TRIGGERS view, 6-105
- USER\_TS\_QUOTAS view, 6-106
- USER\_TSTZ\_TAB\_COLS view, 6-106
- USER\_TSTZ\_TABLES view, 6-106
- USER\_TUNE\_MVIEW view, 6-106
- USER\_TYPE\_ATTRS view, 6-106
- USER\_TYPE\_METHODS view, 6-106
- USER\_TYPE\_VERSIONS view, 6-106
- USER\_TYPES view, 6-107
- USER\_UNUSED\_COL\_TABS view, 6-107
- USER\_UPDATABLE\_COLUMNS view, 6-107
- USER\_USERS view, 6-107
- USER\_USTATS view, 6-107
- USER\_VARRAYS view, 6-107
- USER\_VIEWS view, 6-107
- USER\_VIEWS\_AE view, 6-108
- USER\_WARNING\_SETTINGS view, 6-108
- USER\_WM\_CONS\_COLUMNS view, 2-3
- USER\_WM\_CONSTRAINTS view, 2-3
- USER\_WM\_IND\_COLUMNS view, 2-3
- USER\_WM\_IND\_EXPRESSIONS view, 2-3
- USER\_WM\_LOCKED\_TABLES view, 2-3
- USER\_WM\_MODIFIED\_TABLES view, 2-3
- USER\_WM\_PRIVS view, 2-3
- USER\_WM\_RIC\_INFO view, 2-3
- USER\_WM\_TAB\_TRIGGERS view, 2-3
- USER\_WM\_VERSIONED\_TABLES view, 2-3
- USER\_WM\_VT\_ERRORS view, 2-3
- USER\_WORKSPACE\_PRIVS view, 2-3
- USER\_WORKSPACE\_SAVEPOINTS view, 2-3
- USER\_WORKSPACES view, 2-3
- USER\_XML\_INDEXES view, 6-108
- USER\_XML\_SCHEMAS view, 6-108
- USER\_XML\_TAB\_COLS view, 6-108
- USER\_XML\_TABLES view, 6-108
- USER\_XML\_VIEW\_COLS view, 6-108
- USER\_XML\_VIEWS view, 6-108
- USERLOCK.SQL script, B-2
- users
  - authenticating, 1-124
  - multiple, 1-66
- UTL\_FILE\_DIR initialization parameter, 1-179
- UTLBSTAT.SQL script, B-2
- UTLCHN1.SQL script, B-3
- UTLCONST.SQL script, B-3

- UTLDTREE.SQL script, 6-40, 6-48, B-3
- UTLESTAT.SQL script, B-2
- UTLEXPT1.SQL script, B-3
- UTLIP.SQL script, B-3
- UTLIRP.SQL script, B-3
- UTLLOCKT.SQL script, B-3
- UTLPWDMG.SQL script, B-3
- UTLRP.SQL script, B-3
- UTLSAMPL.SQL script, B-3
- UTLSCLN.SQL script, B-3
- UTLTkPRF.SQL script, B-4
- UTLU111I.SQL script, B-5
- UTLU111S.SQL script, B-5
- UTLVALID.SQL script, B-4
- UTLXPLAN.SQL script, B-4

## V

---

- V\$ACCESS view, 7-2
- V\$ACTIVE\_INSTANCES view, 7-2
- V\$ACTIVE\_SERVICES view, 7-3
- V\$ACTIVE\_SESS\_POOL\_MTH view, 7-3
- V\$ACTIVE\_SESSION\_HISTORY view, 7-3
- V\$ADVISOR\_PROGRESS view, 7-7
- V\$ALERT\_TYPES view, 7-8
- V\$AQ view, 7-8
- V\$ARCHIVE view, 7-9
- V\$ARCHIVE\_DEST view, 7-9
- V\$ARCHIVE\_DEST\_STATUS view, 7-12
- V\$ARCHIVE\_GAP view, 7-14
- V\$ARCHIVE\_PROCESSES view, 7-14
- V\$ARCHIVED\_LOG view, 7-14
- V\$ASM\_ACFS\_ENCRYPTION\_INFO view, 7-16
- V\$ASM\_ACFS\_SECURITY\_INFO view, 7-17
- V\$ASM\_ACFSSNAPSHOTS view, 7-17
- V\$ASM\_ACFSVOLUMES view, 7-17
- V\$ASM\_ALIAS view, 7-17
- V\$ASM\_ATTRIBUTE view, 7-18
- V\$ASM\_CLIENT view, 7-18
- V\$ASM\_DISK view, 7-19
- V\$ASM\_DISK\_IOSTAT view, 7-22
- V\$ASM\_DISK\_STAT view, 7-22
- V\$ASM\_DISKGROUP view, 7-23
- V\$ASM\_DISKGROUP\_STAT view, 7-24
- V\$ASM\_FILE view, 7-24
- V\$ASM\_FILESYSTEM view, 7-25
- V\$ASM\_OPERATION view, 7-26
- V\$ASM\_TEMPLATE view, 7-27
- V\$ASM\_USER view, 7-27
- V\$ASM\_USERGROUP view, 7-27
- V\$ASM\_USERGROUP\_MEMBER view, 7-28
- V\$ASM\_VOLUME view, 7-28
- V\$ASM\_VOLUME\_STAT view, 7-29
- V\$AW\_AGGREGATE\_OP view, 7-29
- V\$AW\_ALLOCATE\_OP view, 7-29
- V\$AW\_CALC view, 7-30
- V\$AW\_LONGOPS view, 7-30
- V\$AW\_OLAP view, 7-31
- V\$AW\_SESSION\_INFO view, 7-32
- V\$BACKUP view, 7-32

V\$BACKUP\_ARCHIVELOG\_DETAILS view, 7-33  
V\$BACKUP\_ARCHIVELOG\_SUMMARY view, 7-33  
V\$BACKUP\_ASYNC\_IO view, 7-34  
V\$BACKUP\_CONTROLFILE\_DETAILS view, 7-35  
V\$BACKUP\_CONTROLFILE\_SUMMARY view, 7-35  
V\$BACKUP\_COPY\_DETAILS view, 7-36  
V\$BACKUP\_COPY\_SUMMARY view, 7-37  
V\$BACKUP\_CORRUPTION view, 7-37  
V\$BACKUP\_DATAFILE view, 7-38  
V\$BACKUP\_DATAFILE\_DETAILS view, 7-39  
V\$BACKUP\_DATAFILE\_SUMMARY view, 7-40  
V\$BACKUP\_DEVICE view, 7-40  
V\$BACKUP\_FILES view, 7-41  
V\$BACKUP\_PIECE view, 7-43  
V\$BACKUP\_PIECE\_DETAILS view, 7-44  
V\$BACKUP\_REDOLOG view, 7-45  
V\$BACKUP\_SET view, 7-46  
V\$BACKUP\_SET\_DETAILS view, 7-46  
V\$BACKUP\_SET\_SUMMARY view, 7-48  
V\$BACKUP\_SFILE view, 7-48  
V\$BACKUP\_SFILE\_DETAILS view, 7-48  
V\$BACKUP\_SFILE\_SUMMARY view, 7-49  
V\$BACKUP\_SYNC\_IO view, 7-49  
V\$BGPROCESS view, 7-50  
V\$BH view, 7-50  
V\$BLOCK\_CHANGE\_TRACKING view, 7-51  
V\$BLOCKING QUIESCE view, 7-51  
V\$BUFFER\_POOL view, 7-52  
V\$BUFFER\_POOL\_STATISTICS view, 7-52  
V\$BUFFERED\_PUBLISHERS view, 7-53  
V\$BUFFERED\_QUEUES view, 7-54  
V\$BUFFERED\_SUBSCRIBERS view, 7-55  
V\$CACHE view, 7-56  
V\$CACHE\_LOCK view, 7-57  
V\$CACHE\_TRANSFER view, 7-59  
V\$CIRCUIT view, 7-59  
V\$CLASS\_CACHE\_TRANSFER view, 7-60  
V\$CLIENT\_STATS view, 7-61  
V\$CLUSTER\_INTERCONNECTS view, 7-61  
V\$CONFIGURED\_INTERCONNECTS view, 7-61  
V\$CONTEXT view, 7-62  
V\$CONTROLFILE view, 7-62  
V\$CONTROLFILE\_RECORD\_SECTION view, 7-62  
V\$COPY\_CORRUPTION view, 7-63  
V\$CORRUPT\_XID\_LIST view, 7-64  
V\$CPOOL\_CC\_INFO view, 7-64  
V\$CPOOL\_CC\_STATS view, 7-64  
V\$CPOOL\_CONN\_INFO view, 7-65  
V\$CPOOL\_STATS view, 7-65  
V\$CR\_BLOCK\_SERVER view, 7-66  
V\$CURRENT\_BLOCK\_SERVER view, 7-67  
V\$DATABASE view, 7-68  
V\$DATABASE\_BLOCK\_CORRUPTION view, 7-73  
V\$DATABASE\_INCARNATION view, 7-73  
V\$DATAFILE view, 7-74  
V\$DATAFILE\_COPY view, 7-75  
V\$DATAFILE\_HEADER view, 7-77  
V\$DATAGUARD\_CONFIG view, 7-78  
V\$DATAGUARD\_STATS view, 7-78  
V\$DATAGUARD\_STATUS view, 7-79  
V\$DB\_CACHE\_ADVICE view, 7-79  
V\$DB\_OBJECT\_CACHE view, 7-80  
V\$DB\_PIPES view, 7-81  
V\$DB\_TRANSPORTABLE\_PLATFORM view, 7-81  
V\$DBFILE view, 7-81  
V\$DBLINK view, 7-82  
V\$DELETED\_OBJECT view, 7-82  
V\$DISPATCHER view, 7-83  
V\$DISPATCHER\_CONFIG view, 7-84  
V\$DISPATCHER\_RATE view, 7-85  
V\$DNFS\_CHANNELS view, 7-88  
V\$DNFS\_FILES view, 7-88  
V\$DNFS\_SERVERS view, 7-89  
V\$DNFS\_STATS view, 7-89  
V\$DYNAMIC\_REMASTER\_STATS view, 7-90  
V\$EMON view, 7-90  
V\$ENABLEDPRIVS view, 7-91  
V\$ENCRYPTED\_TABLESPACES view, 7-91  
V\$ENCRYPTION\_WALLET view, 7-92  
V\$ENQUEUE\_LOCK view, 7-92  
V\$ENQUEUE\_STAT view, 7-93  
V\$ENQUEUE\_STATISTICS view, 7-93  
V\$EVENT\_HISTOGRAM view, 7-94  
V\$EVENT\_NAME view, 7-94  
V\$EVENTMETRIC view, 7-94  
V\$EXECUTION view, 7-95  
V\$FALSE\_PING view, 7-95  
V\$FAST\_START\_SERVERS view, 7-96  
V\$FAST\_START\_TRANSACTIONS view, 7-96  
V\$FILE\_CACHE\_TRANSFER view, 7-97  
V\$FILE\_HISTOGRAM view, 7-97  
V\$FILEMETRIC view, 7-97  
V\$FILEMETRIC\_HISTORY view, 7-98  
V\$FILESIZE\_USAGE view, 7-98  
V\$FILESTAT view, 7-99  
V\$FIXED\_TABLE view, 7-99  
V\$FIXED\_VIEW\_DEFINITION view, 7-99  
V\$FLASHBACK\_DATABASE\_LOG view, 7-100  
V\$FLASHBACK\_DATABASE\_LOGFILE view, 7-100  
V\$FLASHBACK\_DATABASE\_STAT view, 7-100  
V\$FLASHBACK\_TXN\_GRAPH view, 7-101  
V\$FLASHBACK\_TXN\_MODS view, 7-101  
V\$FOREIGN\_ARCHIVED\_LOG view, 7-102  
V\$FS\_FAILOVER\_STATS view, 7-104  
V\$GC\_ELEMENT view, 7-104  
V\$GC\_ELEMENTS\_WITH\_COLLISIONS view, 7-105  
V\$GCSHVMMASTER\_INFO view, 7-105  
V\$GCSPFMASTER\_INFO view, 7-105  
V\$GES\_BLOCKING\_ENQUEUE view, 7-105  
V\$GES\_CONVERT\_LOCAL view, 7-106  
V\$GES\_CONVERT\_REMOTE view, 7-107  
V\$GES\_ENQUEUE view, 7-108  
V\$GES\_LATCH view, 7-108  
V\$GES\_RESOURCE view, 7-109  
V\$GES\_STATISTICS view, 7-109  
V\$GLOBAL\_BLOCKED\_LOCKS view, 7-109



V\$GLOBAL\_TRANSACTION view, 7-109  
 V\$HM\_CHECK view, 7-110  
 V\$HM\_CHECK\_PARAM view, 7-111  
 V\$HM\_FINDING view, 7-111  
 V\$HM\_INFO view, 7-112  
 V\$HM\_RECOMMENDATION view, 7-112  
 V\$HM\_RUN view, 7-113  
 V\$HS\_AGENT view, 7-113  
 V\$HS\_PARAMETER view, 7-114  
 V\$HS\_SESSION view, 7-114  
 V\$HVMaster\_INFO view, 7-114  
 V\$INDEXED\_FIXED\_COLUMN view, 8-1  
 V\$INSTANCE view, 8-1  
 V\$INSTANCE\_CACHE\_TRANSFER view, 8-2  
 V\$INSTANCE\_RECOVERY view, 8-3  
 V\$IO\_CALIBRATION\_STATUS view, 8-5  
 V\$IOFUNCMETRIC view, 8-5  
 V\$IOFUNCMETRIC\_HISTORY view, 8-5  
 V\$Iostat\_CONSUMER\_GROUP view, 8-6  
 V\$Iostat\_FILE view, 8-6  
 V\$Iostat\_FUNCTION view, 8-7  
 V\$Iostat\_FUNCTION\_DETAIL view, 8-8  
 V\$Iostat\_NETWORK view, 8-9  
 V\$JAVA\_LIBRARY\_CACHE\_MEMORY view, 8-9  
 V\$JAVA\_POOL\_ADVICE view, 8-9  
 V\$LATCH view, 8-10  
 V\$LATCH\_CHILDREN view, 8-11  
 V\$LATCH\_MISSES view, 8-11  
 V\$LATCH\_PARENT view, 8-12  
 V\$LATCHHOLDER view, 8-12  
 V\$LATCHNAME view, 8-12  
 V\$LIBCACHE\_LOCKS view, 8-12  
 V\$LIBRARY\_CACHE\_MEMORY view, 8-13  
 V\$LIBRARYCACHE view, 8-13  
 V\$LICENSE view, 8-14  
 V\$LOADISTAT view, 8-14  
 V\$LOADPSTAT view, 8-15  
 V\$LOCK view, 8-15  
 V\$LOCK\_ACTIVITY view, 8-16  
 V\$LOCK\_TYPE view, 8-16  
 V\$LOCKED\_OBJECT view, 8-17  
 V\$LOG view, 8-17  
 V\$LOG\_HISTORY view, 8-18  
 V\$LOGFILE view, 8-18  
 V\$LOGHIST view, 8-19  
 V\$LOGMNR\_CONTENTS view, 8-19  
 V\$LOGMNR\_DICTIONARY view, 8-23  
 V\$LOGMNR\_DICTIONARY\_LOAD view, 8-24  
 V\$LOGMNR\_LATCH view, 8-24  
 V\$LOGMNR\_LOGS view, 8-25  
 V\$LOGMNR\_PARAMETERS view, 8-26  
 V\$LOGMNR\_PROCESS view, 8-26  
 V\$LOGMNR\_SESSION view, 8-27  
 V\$LOGMNR\_STATS view, 8-28  
 V\$LOGSTDBY view, 8-29  
 V\$LOGSTDBY\_PROCESS view, 8-30  
 V\$LOGSTDBY\_PROGRESS view, 8-31  
 V\$LOGSTDBY\_STATE view, 8-31  
 V\$LOGSTDBY\_STATS view, 8-31  
 V\$LOGSTDBY\_TRANSACTION view, 8-33  
 V\$MANAGED\_STANDBY view, 8-34  
 V\$MAP\_COMP\_LIST view, 8-35  
 V\$MAP\_ELEMENT view, 8-35  
 V\$MAP\_EXT\_ELEMENT view, 8-36  
 V\$MAP\_FILE view, 8-36  
 V\$MAP\_FILE\_EXTENT view, 8-37  
 V\$MAP\_FILE\_IO\_STACK view, 8-37  
 V\$MAP\_LIBRARY view, 8-38  
 V\$MAP\_SUBELEMENT view, 8-38  
 V\$MEMORY\_CURRENT\_RESIZE\_OPS view, 8-38  
 V\$MEMORY\_DYNAMIC\_COMPONENTS view, 8-39  
 V\$MEMORY\_RESIZE\_OPS view, 8-40  
 V\$MEMORY\_TARGET\_ADVICE view, 8-40  
 V\$METRIC view, 8-41  
 V\$METRIC\_HISTORY view, 8-42  
 V\$METRICGROUP view, 8-42  
 V\$METRICNAME view, 8-43  
 V\$MTTR\_TARGET\_ADVICE view, 8-43  
 V\$MUTEX\_SLEEP view, 8-43  
 V\$MUTEX\_SLEEP\_HISTORY view, 8-44  
 V\$MVREFRESH view, 8-44  
 V\$MYSTAT view, 8-45  
 V\$NFS\_CLIENTS view, 8-45  
 V\$NFS\_LOCKS view, 8-45  
 V\$NFS\_OPEN\_FILES view, 8-45  
 V\$NLS\_PARAMETERS view, 8-46  
 V\$NLS\_VALID\_VALUES view, 8-46  
 V\$OBJECT\_DEPENDENCY view, 8-46  
 V\$OBJECT\_PRIVILEGE view, 8-47  
 V\$OBJECT\_USAGE view, 8-47  
 V\$OBsolete\_BACKUP\_FILES view, 8-47  
 V\$OBsolete\_PARAMETER view, 8-49  
 V\$OFFLINE\_RANGE view, 8-49  
 V\$OPEN\_CURSOR view, 8-50  
 V\$OPTION view, 8-50  
 V\$OSSTAT view, 8-51  
 V\$PARALLEL\_DEGREE\_LIMIT\_MTH view, 8-52  
 V\$PARAMETER view, 8-52  
 V\$PARAMETER\_VALID\_VALUES view, 8-53  
 V\$PARAMETER2 view, 8-53  
 V\$PERSISTENT\_PUBLISHERS view, 8-55  
 V\$PERSISTENT\_QMN\_CACHE view, 8-55  
 V\$PERSISTENT\_QUEUES view, 8-56  
 V\$PERSISTENT\_SUBSCRIBERS view, 8-57  
 V\$PGA\_TARGET\_ADVICE view, 8-58  
 V\$PGA\_TARGET\_ADVICE\_HISTOGRAM view, 8-59  
 V\$PGASTAT view, 8-60  
 V\$PQ\_SESSTAT view, 8-61  
 V\$PQ\_SLAVE view, 8-62  
 V\$PQ\_SYSSTAT view, 8-62  
 V\$PQ\_TQSTAT view, 8-63  
 V\$PROCESS view, 8-64  
 V\$PROCESS\_MEMORY view, 8-64  
 V\$PROPAGATION\_RECEIVER view, 8-65  
 V\$PROPAGATION\_SENDER view, 8-65  
 V\$PROXY\_ARCHIVEDLOG view, 8-67  
 V\$PROXY\_ARCHIVELOG\_DETAILS view, 8-68  
 V\$PROXY\_ARCHIVELOG\_SUMMARY view, 8-68

V\$PROXY\_COPY\_DETAILS view, 8-69  
 V\$PROXY\_COPY\_SUMMARY view, 8-70  
 V\$PROXY\_DATAFILE view, 8-70  
 V\$PWFILERS view, 8-72  
 V\$PX\_INSTANCE\_GROUP view, 8-72  
 V\$PX\_PROCESS view, 8-73  
 V\$PX\_PROCESS\_SYSSTAT view, 8-73  
 V\$PX\_SESSION view, 8-74  
 V\$PX\_SESSSTAT view, 8-75  
 V\$QMON\_COORDINATOR\_STATS view, 8-75  
 V\$QMON\_SERVER\_STATS view, 8-76  
 V\$QMON\_TASK\_STATS view, 8-77  
 V\$QMON\_TASKS view, 8-77  
 V\$QUEUE view, 8-78  
 V\$QUEUEING\_MTH view, 8-78  
 V\$RECOVER\_FILE view, 8-78  
 V\$RECOVERY\_AREA\_USAGE view, 8-78  
 V\$RECOVERY\_FILE\_DEST view, 8-79  
 V\$RECOVERY\_FILE\_STATUS view, 8-79  
 V\$RECOVERY\_LOG view, 8-80  
 V\$RECOVERY\_PROGRESS view, 8-80  
 V\$RECOVERY\_STATUS view, 8-80  
 V\$REDO\_DEST\_RESP\_HISTOGRAM view, 8-81  
 V\$REPLPROP view, 8-81  
 V\$REPLQUEUE view, 8-82  
 V\$REQDIST view, 8-83  
 V\$RESERVED\_WORDS view, 8-83  
 V\$RESOURCE view, 8-83  
 V\$RESOURCE\_LIMIT view, 8-84  
 V\$RESTORE\_POINT view, 8-84  
 V\$RESULT\_CACHE\_DEPENDENCY view, 8-85  
 V\$RESULT\_CACHE\_MEMORY view, 8-85  
 V\$RESULT\_CACHE\_OBJECTS view, 8-85  
 V\$RESULT\_CACHE\_STATISTICS view, 8-86  
 V\$RMAN\_BACKUP\_JOB\_DETAILS view, 8-87  
 V\$RMAN\_BACKUP\_SUBJOB\_DETAILS view, 8-88  
 V\$RMAN\_BACKUP\_TYPE view, 8-89  
 V\$RMAN\_COMPRESSION\_ALGORITHM view, 8-90  
 V\$RMAN\_CONFIGURATION view, 8-90  
 V\$RMAN\_ENCRYPTION\_ALGORITHMS view, 8-91  
 V\$RMAN\_OUTPUT view, 8-91  
 V\$RMAN\_STATUS view, 8-91  
 V\$ROLLNAME view, 8-92  
 V\$ROLLSTAT view, 8-92  
 V\$ROWCACHE view, 8-93  
 V\$ROWCACHE\_PARENT view, 8-94  
 V\$ROWCACHE\_SUBORDINATE view, 8-94  
 V\$RSRC\_CONS\_GROUP\_HISTORY view, 8-95  
 V\$RSRC\_CONSUMER\_GROUP view, 8-96  
 V\$RSRC\_CONSUMER\_GROUP\_CPU\_MTH view, 8-98  
 V\$RSRC\_PLAN view, 8-99  
 V\$RSRC\_PLAN\_CPU\_MTH view, 8-100  
 V\$RSRC\_PLAN\_HISTORY view, 8-100  
 V\$RSRC\_SESSION\_INFO view, 8-101  
 V\$RSRCMGRMETRIC view, 8-104  
 V\$RSRCMGRMETRIC\_HISTORY view, 8-105  
 V\$RULE view, 8-105  
 V\$RULE\_SET view, 8-105  
 V\$RULE\_SET\_AGGREGATE\_STATS view, 8-106  
 V\$\$SCHEDULER\_RUNNING\_JOBS view, 9-1  
 V\$SECUREFILE\_TIMER view, 9-1  
 V\$SEGMENT\_STATISTICS view, 9-2  
 V\$SEGSTAT view, 9-2  
 V\$SEGSTAT\_NAME view, 9-2  
 V\$SERV\_MOD\_ACT\_STATS view, 9-3  
 V\$SERVICE\_EVENT view, 9-3  
 V\$SERVICE\_STATS view, 9-3  
 V\$SERVICE\_WAIT\_CLASS view, 9-4  
 V\$SERVICEMETRIC view, 9-4  
 V\$SERVICEMETRIC\_HISTORY view, 9-5  
 V\$SERVICES view, 9-5  
 V\$SES\_OPTIMIZER\_ENV view, 9-6  
 V\$SESS\_IO view, 9-6  
 V\$SESS\_TIME\_MODEL view, 9-6  
 V\$SESSION view, 9-8  
 V\$SESSION\_BLOCKERS view, 9-15  
 V\$SESSION\_CONNECT\_INFO view, 9-15  
 V\$SESSION\_CURSOR\_CACHE view, 9-16  
 V\$SESSION\_EVENT view, 9-16, C-1  
 V\$SESSION\_FIX\_CONTROL view, 9-17  
 V\$SESSION\_LONGOPS view, 9-17  
 V\$SESSION\_OBJECT\_CACHE view, 9-18  
 V\$SESSION\_WAIT view, 9-19, C-1  
 V\$SESSION\_WAIT\_CLASS view, 9-20  
 V\$SESSION\_WAIT\_HISTORY view, 9-21  
 V\$SESSMETRIC view, 9-21  
 V\$SESSTAT view, 9-21, E-1  
 V\$SGA view, 9-22  
 V\$SGA\_CURRENT\_RESIZE\_OPS view, 9-22  
 V\$SGA\_DYNAMIC\_COMPONENTS view, 9-22  
 V\$SGA\_DYNAMIC\_FREE\_MEMORY view, 9-23  
 V\$SGA\_RESIZE\_OPS view, 9-23  
 V\$SGA\_TARGET\_ADVICE view, 9-24  
 V\$SGAINFO view, 9-24  
 V\$SGASTAT view, 9-24  
 V\$SHARED\_POOL\_ADVICE view, 9-25  
 V\$SHARED\_POOL\_RESERVED view, 9-25  
 V\$SHARED\_SERVER view, 9-26  
 V\$SHARED\_SERVER\_MONITOR view, 9-26  
 V\$SORT\_SEGMENT view, 9-27  
 V\$SPPARAMETER view, 9-28  
 V\$SQL view, 9-28  
 V\$SQL\_BIND\_CAPTURE view, 9-31  
 V\$SQL\_BIND\_DATA view, 9-32  
 V\$SQL\_BIND\_METADATA view, 9-33  
 V\$SQL\_CS\_HISTOGRAM view, 9-33  
 V\$SQL\_CS\_SELECTIVITY view, 9-33  
 V\$SQL\_CS\_STATISTICS view, 9-34  
 V\$SQL\_CURSOR view, 9-34  
 V\$SQL\_JOIN\_FILTER view, 9-35  
 V\$SQL\_MONITOR view, 9-35  
 V\$SQL\_OPTIMIZER\_ENV view, 9-38  
 V\$SQL\_PLAN view, 9-38  
 V\$SQL\_PLAN\_MONITOR view, 9-40  
 V\$SQL\_PLAN\_STATISTICS view, 9-42  
 V\$SQL\_PLAN\_STATISTICS\_ALL view, 9-43  
 V\$SQL\_REDIRECTION view, 9-46

- V\$SQL\_SHARED\_CURSOR view, 9-46
- V\$SQL\_SHARED\_MEMORY view, 9-49
- V\$SQL\_WORKAREA view, 9-49
- V\$SQL\_WORKAREA\_ACTIVE view, 9-50
- V\$SQL\_WORKAREA\_HISTOGRAM view, 9-52
- V\$SQLAREA view, 9-52
- V\$SQLAREA\_PLAN\_HASH view, 9-55
- V\$SQLCOMMAND view, 9-58
- V\$SQLFN\_ARG\_METADATA view, 9-58
- V\$SQLFN\_METADATA view, 9-58
- V\$SQLSTATS view, 9-59
- V\$SQLSTATS\_PLAN\_HASH view, 9-61
- V\$SQLTEXT view, 9-61
- V\$SQLTEXT\_WITH\_NEWLINES view, 9-61
- V\$STANDBY\_EVENT\_HISTOGRAM view, 9-62
- V\$STANDBY\_LOG view, 9-62
- V\$STATISTICS\_LEVEL view, 9-63
- V\$STATNAME view, 9-63, E-1
- V\$STREAMS\_APPLY\_COORDINATOR view, 9-64
- V\$STREAMS\_APPLY\_READER view, 9-65
- V\$STREAMS\_APPLY\_SERVER view, 9-67
- V\$STREAMS\_CAPTURE view, 9-69
- V\$STREAMS\_MESSAGE\_TRACKING view, 9-71
- V\$STREAMS\_POOL\_ADVICE view, 9-72
- V\$STREAMS\_POOL\_STATISTICS view, 9-73
- V\$STREAMS\_TRANSACTION view, 9-73
- V\$SUBCACHE view, 9-74
- V\$SUBSCR\_REGISTRATION\_STATS view, 9-74
- V\$SYS\_OPTIMIZER\_ENV view, 9-75
- V\$SYS\_TIME\_MODEL view, 9-76
- V\$SYSAUX\_OCCUPANTS view, 9-76
- V\$SYSMETRIC view, 9-76
- V\$SYSMETRIC\_HISTORY view, 9-77
- V\$SYSMETRIC\_SUMMARY view, 9-77
- V\$SYSSTAT view, 9-77, E-1
- V\$SYSTEM\_CURSOR\_CACHE view, 9-78
- V\$SYSTEM\_EVENT view, 9-78, C-1
- V\$SYSTEM\_FIX\_CONTROL view, 9-79
- V\$SYSTEM\_PARAMETER view, 9-79
- V\$SYSTEM\_PARAMETER2 view, 9-80
- V\$SYSTEM\_WAIT\_CLASS view, 9-81
- V\$TABLESPACE view, 9-82
- V\$TEMP\_CACHE\_TRANSFER view, 9-82
- V\$TEMP\_EXTENT\_MAP view, 9-83
- V\$TEMP\_EXTENT\_POOL view, 9-83
- V\$TEMP\_SPACE\_HEADER view, 9-83
- V\$TEMPFILE view, 9-84
- V\$TEMPORARY\_LOBS view, 9-84
- V\$TEMPSEG\_USAGE view, 9-84
- V\$TEMPSTAT view, 9-85
- V\$THREAD view, 9-85
- V\$THRESHOLD\_TYPES view, 9-86
- V\$TIMER view, 9-86
- V\$TIMEZONE\_NAMES view, 9-87
- V\$TOPLEVELCALL view, 9-87
- V\$TRANSACTION view, 9-87
- V\$TRANSACTION\_ENQUEUE view, 9-88
- V\$TRANSPORTABLE\_PLATFORM view, 9-89
- V\$TYPE\_SIZE view, 9-89
- V\$UNDOSTAT view, 9-89

- V\$UNUSABLE\_BACKUPFILE\_DETAILS view, 9-90
- V\$VERSION view, 9-91
- V\$VPD\_POLICY view, 9-91
- V\$WAIT\_CHAINS view, 9-92
- V\$WAITCLASSMETRIC view, 9-93
- V\$WAITCLASSMETRIC\_HISTORY view, 9-93
- V\$WAITSTAT view, 9-94
- V\$WALLET view, 9-94
- V\$WORKLOAD\_REPLAY\_THREAD view, 9-94
- V\$XML\_AUDIT\_TRAIL view, 9-95
- V\$XSTREAM\_CAPTURE view, 9-97
- V\$XSTREAM\_MESSAGE\_TRACKING view, 9-100
- V\$XSTREAM\_OUTBOUND\_SERVER view, 9-100
- V\$XSTREAM\_TRANSACTION view, 9-103

## views

- data dictionary views, 2-1

## W

### wait events

- alter system set dispatcher, C-5
- batched allocate scn lock request, C-5
- BFILE check if exists, C-5
- BFILE check if open, C-5
- BFILE closure, C-5
- BFILE get length, C-6
- BFILE get name object, C-6
- BFILE get path object, C-6
- BFILE internal seek, C-6
- BFILE open, C-6
- BFILE read, C-7
- broadcast mesg queue transition, C-7
- broadcast mesg recovery queue transition, C-7
- buffer busy waits, C-7
- buffer deadlock, C-8
- buffer latch, C-8
- buffer read retry, C-8
- checkpoint completed, C-9
- cleanup of aborted processes, C-9
- controlfile parallel write, C-9
- controlfile sequential read, C-9
- controlfile single write, C-10
- cursor: mutex S, C-10
- cursor: mutex X, C-10
- cursor: pin S, C-11
- cursor: pin S wait on X, C-11
- cursor: pin X, C-11
- Data Guard Broker: single instance, C-12
- Data Guard: process cleanup, C-11
- Data Guard: process exit, C-12
- db file parallel read, C-12
- db file parallel write, C-12
- db file scattered read, C-12
- db file sequential read, C-13
- db file single write, C-13
- DFS db file lock, C-13
- DFS lock handle, C-13
- direct path read, C-14
- direct path sync, C-14
- direct path write, C-14

- Disk file operations I/O, C-15
- dispatcher shutdown, C-15
- dispatcher timer, C-15
- duplicate cluster key, C-15
- enq: OW - initialization, C-16
- enq: OW - termination, C-16
- enqueue, C-16
- flashback buf free by RVWR, C-16
- flashback logfile sync, C-16
- free buffer waits, C-17
- free global transaction table entry, C-17
- free process state object, C-17
- gc recovery quiesce, C-17
- GCS lock open S, C-18
- GCS lock open X, C-18
- gcs remastering wait for drop pkey, C-18
- global cache busy, C-18
- global cache freelist, C-19
- global cache lock cleanup, C-19
- inactive session, C-19
- inactive transaction branch, C-19
- index block split, C-19
- instance state change, C-20
- io done, C-20
- kcl bg acks, C-20
- ksxr wait for mount shared, C-21
- ktm: instance recovery, C-21
- latch activity, C-21
- latch free, C-21
- library cache load lock, C-22
- library cache lock, C-22
- library cache pin, C-22
- LMON global data update, C-23
- lock manager wait for remote message, C-23
- Log archive I/O, C-23
- log buffer space, C-23
- log file parallel write, C-23
- log file sequential read, C-24
- log file single write, C-24
- log file switch (archiving needed), C-24
- log file switch (checkpoint incomplete), C-24
- log file switch (clearing log file), C-25
- log file switch (private strand flush incomplete), C-25
- log file switch completion, C-25
- log file sync, C-25
- log switch/archive, C-25
- optimizer stats update retry, C-25
- parallel recovery change buffer free, C-26
- parallel recovery control message reply, C-26
- parallel recovery coord send blocked, C-26
- parallel recovery coord wait for reply, C-26
- parallel recovery coordinator waits for slave cleanup, C-26
- parallel recovery read buffer free, C-26
- parallel recovery slave next change, C-26
- pending global transaction(s), C-27
- pipe get, C-27
- pipe put, C-27
- PL/SQL lock timer, C-27
- pmon timer, C-27
- prewarm transfer retry, C-28
- prior process spawner to be cleaned up, C-28
- process startup, C-28
- PX dequeue wait, C-28
- PX qref latch, C-29
- PX server shutdown, C-29
- PX signal server, C-29
- rdbms ipc message, C-29
- rdbms ipc message block, C-29
- rdbms ipc reply, C-30
- read by other session, C-30
- recovery read, C-30
- resmgr:become active, C-30
- resmgr:cpu quantum, C-31
- resmgr:pq queued, C-31
- rolling migration: cluster quiesce, C-31
- row cache lock, C-31
- RVWR wait for flashback copy, C-32
- sbtbufinfo, C-32
- sbtgetbuf, C-32
- sbtmapbuf, C-32
- sbtrelbuf, C-32
- scginq AST call, C-32
- SGA: allocation forcing component growth, C-32
- SGA: MMAN sleep for component shrink, C-33
- SGA: sga\_target resize, C-33
- Shared IO Pool Memory, C-33
- shared server idle event, C-33
- single-task message, C-33
- smon timer, C-33
- SQL\*Net break/reset to client, C-34
- SQL\*Net break/reset to dblink, C-34
- SQL\*Net message from client, C-34
- SQL\*Net message from dblink, C-34
- SQL\*Net message to client, C-35
- SQL\*Net message to dblink, C-35
- SQL\*Net more data from client, C-35
- SQL\*Net more data from dblink, C-35
- SQL\*Net more data to client, C-36
- SQL\*Net more data to dblink, C-36
- Streams AQ: waiting for messages in the queue, C-36
- switch logfile command, C-36
- timer in sksawt, C-37
- transaction, C-37
- unbound tx, C-37
- undo segment extension, C-38
- undo segment recovery, C-38
- undo segment tx slot, C-38
- undo\_retention publish retry, C-37
- virtual circuit status, C-38
- virtual circuit wait, C-38
- WCR: replay client notify, C-39
- WCR: replay clock, C-39
- WCR: replay lock order, C-39
- WCR: replay paused, C-39
- WCR: Sync context busy, C-39
- WMON goes to sleep, C-40
- write complete waits, C-40

- writes stopped by instance recovery or database suspension, C-40
- WM\_COMPRESS\_BATCH\_SIZES view, 2-3
- WM\_COMPRESSIBLE\_TABLES view, 2-3
- WM\_EVENTS\_INFO view, 2-3
- WM\_INSTALLATION view, 2-3
- WM\_REPLICATION\_INFO view, 2-3
- WORKAREA\_SIZE\_POLICY initialization parameter, 1-179

## **X**

---

- XML\_DB\_EVENTS initialization parameter, 1-180
- XS\_SESSION\_ROLES view, 6-109

