

Endeca® Workbench

Installation Guide

Version 2.1.1 • November 2011



Contents

Preface.....	7
About this guide.....	7
Who should use this guide.....	7
Conventions used in this guide.....	8
Contacting Endeca Customer Support.....	8
Chapter 1: Before you install.....	9
Endeca Workbench overview.....	9
System requirements.....	9
Compatibility with Endeca components.....	10
Configuring Internet Explorer for Adobe Flash.....	10
Recommended reading.....	10
Installer file names.....	11
Chapter 2: Installing Endeca Workbench.....	13
Windows installation procedures.....	13
Creating a user for the Endeca services on Windows.....	13
Installation steps on Windows.....	14
Silent installation steps on Windows.....	15
UNIX installation procedures.....	16
Installation steps on UNIX.....	16
Silent installation steps on UNIX.....	18
Verifying your Endeca Workbench installation.....	19
Package contents and directory structure.....	20
Chapter 3: After you install.....	23
About the Endeca Tools Service.....	23
About starting the Endeca Tools Service from initab.....	23
Starting and stopping the Endeca Tools Service on Windows.....	24
Starting and stopping the Endeca Tools Service on UNIX.....	24
Chapter 4: Additional installation tasks.....	25
Content Assembler API.....	25
Installation procedures for the Content Assembler for Java.....	25
Installation procedures for the Content Assembler for the RAD Toolkit for ASP.NET.....	26
Installation package contents.....	28
Chapter 5: Uninstalling Endeca Workbench.....	31
Uninstalling Endeca Workbench on Windows.....	31
Uninstalling Endeca Workbench on UNIX.....	31
Chapter 6: Uninstalling the Content Assembler API.....	33
Uninstalling the Content Assembler API for Java.....	33
Uninstalling the Content Assembler API for the RAD Toolkit for ASP.NET.....	33
Chapter 7: Uninstalling the Content Assembler reference application.....	35
Uninstalling the Content Assembler reference application for Java.....	35
Uninstalling the Content Assembler reference application for the RAD Toolkit for ASP.NET.....	35
Appendix A: Full List of Documentation Resources.....	37
General Endeca documentation.....	37
MDEX Engine documentation.....	37
Presentation API documentation.....	38
Platform Services documentation.....	38

Endeca Workbench documentation.....	39
Content Assembler API documentation.....	40
Content Acquisition System (CAS) documentation.....	40
Rapid Application Development (RAD) Toolkit documentation.....	41
Documentation for other packages.....	42
Appendix B: Endeca Environment Variables and Port Usage.....	45
Endeca environment variables.....	45
Endeca ports.....	47



Copyright and disclaimer

Product specifications are subject to change without notice and do not represent a commitment on the part of Endeca Technologies, Inc. The software described in this document is furnished under a license agreement. The software may not be reverse engineered, decompiled, or otherwise manipulated for purposes of obtaining the source code. The software may be used or copied only in accordance with the terms of the license agreement. It is against the law to copy the software on any medium except as specifically allowed in the license agreement.

No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose without the express written permission of Endeca Technologies, Inc.

Copyright © 2003-2011 Endeca Technologies, Inc. All rights reserved. Printed in USA.

Portions of this document and the software are subject to third-party rights, including:

Corda PopChart® and Corda Builder™ Copyright © 1996-2005 Corda Technologies, Inc.

Outside In® Search Export Copyright © 2011 Oracle. All rights reserved.

Rosette® Linguistics Platform Copyright © 2000-2011 Basis Technology Corp. All rights reserved.

Teragram Language Identification Software Copyright © 1997-2005 Teragram Corporation. All rights reserved.

Trademarks

Endeca, the Endeca logo, Guided Navigation, MDEX Engine, Find/Analyze/Understand, Guided Summarization, Every Day Discovery, Find Analyze and Understand Information in Ways Never Before Possible, Endeca Latitude, Endeca InFront, Endeca Profind, Endeca Navigation Engine, Don't Stop at Search, and other Endeca product names referenced herein are registered trademarks or trademarks of Endeca Technologies, Inc. in the United States and other jurisdictions. All other product names, company names, marks, logos, and symbols are trademarks of their respective owners.

The software may be covered by one or more of the following patents: US Patent 7035864, US Patent 7062483, US Patent 7325201, US Patent 7428528, US Patent 7567957, US Patent 7617184, US Patent 7856454, US Patent 7912823, US Patent 8005643, US Patent 8019752, US Patent 8024327, US Patent 8051073, US Patent 8051084, Australian Standard Patent 2001268095, Republic of Korea Patent 0797232, Chinese Patent for Invention CN10461159C, Hong Kong Patent HK1072114, European Patent EP1459206, European Patent EP1502205B1, and other patents pending.

Preface

Endeca® InFront enables businesses to deliver targeted experiences for any customer, every time, in any channel. Utilizing all underlying product data and content, businesses are able to influence customer behavior regardless of where or how customers choose to engage — online, in-store, or on-the-go. And with integrated analytics and agile business-user tools, InFront solutions help businesses adapt to changing market needs, influence customer behavior across channels, and dynamically manage a relevant and targeted experience for every customer, every time.

InFront Workbench with Experience Manager provides a single, flexible platform to create, deliver, and manage content-rich, multichannel customer experiences. Experience Manager allows non-technical users to control how, where, when, and what type of content is presented in response to any search, category selection, or facet refinement.

At the core of InFront is the Endeca MDEX Engine,™ a hybrid search-analytical database specifically designed for high-performance exploration and discovery. InFront Integrator provides a set of extensible mechanisms to bring both structured data and unstructured content into the MDEX Engine from a variety of source systems. InFront Assembler dynamically assembles content from any resource and seamlessly combines it with results from the MDEX Engine.

These components — along with additional modules for SEO, Social, and Mobile channel support — make up the core of Endeca InFront, a customer experience management platform focused on delivering the most relevant, targeted, and optimized experience for every customer, at every step, across all customer touch points.

About this guide

This guide contains installation instructions for setting up Endeca Workbench on Windows, UNIX, and Linux.

This guide assumes that you have read the *Endeca Getting Started Guide* (for Information Access Platform users) or the *Endeca Commerce Suite Getting Started Guide* (for Endeca Commerce Suite users). This guide covers installation procedures for Endeca Workbench and the Content Assembler API. For information about installing other Endeca components, please refer to the appropriate Installation Guide.

Who should use this guide

This guide is intended for developers who are building applications using the Endeca Information Access Platform, as well as for system administrators managing the Endeca Information Access Platform on Windows, UNIX, or Linux.



Note: Unless otherwise indicated, whenever this document specifies UNIX, it applies to Linux as well.

Conventions used in this guide

This guide uses the following typographical conventions:

Code examples, inline references to code elements, file names, and user input are set in monospace font. In the case of long lines of code, or when inline monospace text occurs at the end of a line, the following symbol is used to show that the content continues on to the next line: `~`

When copying and pasting such examples, ensure that any occurrences of the symbol and the corresponding line break are deleted and any remaining space is closed up.

Contacting Endeca Customer Support

The Endeca Support Center provides registered users with important information regarding Endeca software, implementation questions, product and solution help, training and professional services consultation as well as overall news and updates from Endeca.

You can contact Endeca Standard Customer Support through the Support section of the Endeca Developer Network (EDeN) at <http://eden.endeca.com>.



Chapter 1

Before you install

This section provides an overview of Endeca Workbench, system requirements, and other information you need to know before installing.

Endeca Workbench overview

Endeca Workbench is a suite of tools that brings together best-in-class Web-site management capabilities including merchandising, Content Spotlighting, search configuration, and usage reporting.

In addition to these powerful tools for business users, Endeca Workbench provides features for system administrators to configure the resources used by an Endeca implementation, monitor its status, start and stop system processes, and download an implementation's instance configuration for debugging and troubleshooting purposes.

The Endeca Workbench package contains the following components:

- Endeca Tools Service
- The appropriate edition of Endeca Workbench for the product you purchased.

In addition, the installation includes a version of the Endeca JSP reference application, which serves as the default preview application in Endeca Workbench.

System requirements

The machine you install your Endeca software on must meet the following operating system and software requirements.

Hardware requirements

The hardware requirements for Endeca Workbench 2.1 are the same as Endeca MDEX Engine version 6.1.x. For details, see the *Endeca MDEX Engine Installation Guide*.

Supported operating systems

Endeca Workbench 2.1 is supported on the same operating systems as Endeca MDEX Engine version 6.1.x. For details, see the *Endeca MDEX Engine Installation Guide*.

Software requirements

Endeca Workbench is a Web-based application that supports Internet Explorer versions 6 and 7.

Endeca Workbench requires Adobe Flash Player 9 or higher.

Supported Languages

Endeca Workbench input fields do not support international characters. The application is intended for English-only use.

Compatibility with Endeca components

Endeca Workbench requires Endeca MDEX Engine and Platform Services. You can install the Endeca MDEX Engine and Platform Services packages either before or after you install the Endeca Workbench package.

To determine the compatibility of Workbench with other Endeca installation packages, see the *Endeca InFront Compatibility Matrix* available on EDeN.

Configuring Internet Explorer for Adobe Flash

If you have Internet Explorer Enhanced Security Configuration installed on a Windows 2003 Server, you may experience difficulty viewing any Adobe flash-enabled pages due to conflicts between the security configuration and Adobe Flash. Flash-enabled pages include Page Builder and the CAS Console for Endeca Workbench.

In particular, the security conflicts may cause the following issues:

- The CAS Console may not display, or display as a blank page, when you click the **Data Sources** link.
- The Workbench logo may display with a white box surrounding the image. This results in odd display behavior when dialog boxes appear in Page Builder. Instead of Page Builder appearing dimmed in the background, Page Builder disappears from the background entirely while the dialog box is present.

To configure Workbench for Adobe Flash extensions:

1. Start Internet Explorer and select **Tools > Internet Options**.
2. Click on the **Security** tab.
3. Click **Custom Level**.
4. Under ActiveX controls and plugins, locate the **Binary and script behaviors** setting, and select the **Enable** option.
5. Click **OK**.

Recommended reading

Before installing, Endeca recommends that you read the following documents for important information about the release.

Getting Started Guide

The *Endeca Getting Started Guide* gives an overview of Endeca components and includes information about configuration scenarios. After installing all the components in your Endeca deployment, read this guide for information on verifying your installation. You can download the *Endeca Getting Started Guide* from the Downloads section of the Endeca Developer Network (EDeN) at <http://eden.endeca.com>.

Release Notes

Refer to the Endeca release notes for information about new features, changed features, and bug fixes for this release. You can download the release notes (README.txt) from the Knowledge Base section of the Endeca Developer Network (EDeN) at <http://eden.endeca.com>. After installation, release notes are also available in the following location:

- Windows: C:\Endeca\Workbench\version
- UNIX: *installation_directory/endeca/Workbench/version*

Migration Guide

Refer to the *Endeca Workbench Migration Guide* for information about migrating your implementation from a previous version of Endeca software. You can download the *Endeca Workbench Migration Guide* from the Downloads section of the Endeca Developer Network (EDeN) at <http://eden.endeca.com>.

Installer file names

Endeca installation packages and executables are named according to a common convention.

The installer file names follow the format:

componentname_version_arch-OS

For example:

mdex_614_x86_64pc-linux.sh

The *componentname* is the component identifier for the component being installed. In the example installer, *mdex* is the identifier for Endeca MDEX Engine.

The *version* is the release version, without periods. In the example installer, 614 identifies Endeca MDEX Engine version 6.1.4.

The *arch-OS* is the architecture and operating system identifier for the component being installed. In the example installer, *x86_64pc-linux* identifies the file as an installer for the 64-bit Linux platform. The following table lists the *arch-OS* identifiers and their platforms:

arch-OS identifier	Installation platform
x86_64pc-linux	Linux running on 64-bit Intel processors
sparc_64-solaris	Solaris running on 64-bit Sparc processors
x86_64pc-win32	Windows running on 64-bit Intel processors

arch-OS identifier	Installation platform
i86pc-win32	Windows running on 32-bit Intel processors  Note: The Endeca MDEX Engine and Endeca Workbench are only supported on 64-bit based hardware and operating systems. There are no Windows 32-bit installers for the MDEX Engine or Endeca Workbench.



Chapter 2

Installing Endeca Workbench

This section contains the installation procedure and describes the contents of the installation directory.

Windows installation procedures

This section contains the Endeca Workbench installation procedures for Windows.

Creating a user for the Endeca services on Windows

You must run the Endeca services as a specified user, for which you can control permissions.

You are asked to provide information about this Endeca services user during the installation process. Endeca recommends that you create a user account called `endeca` that has the proper file and directory permissions to access all necessary files for your application, and that you set up your Endeca Tools Service to run under this account. However, you can use any user that you prefer, as long as it meets these requirements.

To create the user `endeca`:

1. Ensure that you have administrator privileges on the local machine.
2. From the Windows Control Panel, select **Computer Management** > **Administrative Tools**.
3. In the tree pane of the Computer Management window, select **System Tools** > **Local Users and Groups**.
4. Right-click **Users** and select **New User**.
5. In the **New User** dialog box, do the following:
 - a) Enter `endeca` for both the User name and the Full name.
 - b) Optionally, enter a description.
 - c) Set a password for user `endeca`.



Note: The user must have a non-blank password, because the installer will not accept a blank password for the services user.

- d) Uncheck **User must change password at next logon**.
- e) Select **Password never expires**.

6. Click **Create** to create the new user, and then **Close** to exit the dialog box.
7. Close the Computer Management window, but do not exit Administrative Tools.

8. From Administrative Tools, do the following:
 - a) Open **Local Security Policy**.
 - b) In the Local Security Settings window, select **Local Policies > User Rights Assignments**.
 - c) From the list of policies on the right, open **Log on as a Service**.
 - d) Add user `endeaca` to the list of users that can register a process as a service.
 - e) Close the dialog box and exit Administrative Tools.
9. Restart your computer for the changes to take effect.

Installation steps on Windows

This section describes how to install the Endeca software for the first time on a system, or after you have removed a previous version following the upgrade instructions in the *Endeca Migration Guide*.

Use the following prerequisites before installing:

- Ensure that you have administrator privileges on the local machine.
- The user name that is used to start the Endeca services must exist and have a non-blank password.
- Close all running programs.

During the installation, you are asked to provide the host name and the port of the EAC Central Server in your environment. If you do not have this information, or if you change the EAC host or port after installation, you can update the configuration via the EAC Settings page in Endeca Workbench. For details, see the *Endeca Workbench Help*.

To install Endeca Workbench on Windows:

1. In your local environment, locate the Endeca Workbench installer that you downloaded from the Endeca Developer Network (EDeN).
2. Double-click the installer file. Depending on your product, this file can be any of the following:
 - `iapworkbench_version_arch-OS.exe` for IAP Workbench
 - `merchworkbench_version_arch-OS.exe` for Merchandising Workbench
 - `pubworkbench_version_arch-OS.exe` for Publishing Workbench
3. Click **Next** to begin the installation wizard.
4. On the Copyright and Legal screen, click **Next**.
5. In the Destination Folder screen, either accept the default installation location and click **Next** or click **Change** and browse to the directory where you want to install the Endeca software. Endeca recommends that you accept the default location (`C:\Endeca\Workbench`).

The wizard displays both the required and available disk space for the target directory chosen. Endeca Workbench requires approximately 208 MB of disk space.



Note: If you do not use the default location, and you are installing more than one Endeca product on the same machine, ensure that you install each product to a separate location.

6. In the first Endeca Tools Service Information screen, do the following:
 - a) Enter the user name and password to use when launching the Endeca Tools Service.
 - b) Update the user domain if necessary.
 - c) Click **Next**.
7. In the second Endeca Tools Service Information screen, confirm or change the default values for the ports Endeca Workbench uses for HTTP and server shutdown, then click **Next**.

8. In the Endeca Workbench Information screen, do the following:
 - a) Specify the fully qualified domain name of the host on which the EAC Central Server will be installed in the staging environment. This may be either your local machine, or a remote one.



Note: Endeca does not recommend that Endeca Workbench connects to the EAC Central Server that is being used in the production environment.

- b) Confirm or change the default value for the EAC Central Server port.
- c) Click **Next**.

9. In the Completing the Setup Wizard screen, click **Next**.
10. When the installation is complete, click **Finish**.

The installation wizard installs Endeca Workbench, sets the `ENDECA_TOOLS_ROOT` and `ENDECA_TOOLS_CONF` environment variables, and starts the Endeca Tools Service.

Related Links

[Creating a user for the Endeca services on Windows](#) on page 13

You must run the Endeca services as a specified user, for which you can control permissions.

Silent installation steps on Windows

The silent installer is useful if you want to add the installation of Endeca Workbench to your own install script, or push out the installation on multiple machines.

Use the following prerequisites before installing:

- Ensure that you have administrator privileges on the local machine.
- The user name that is used to start the Endeca services must exist and have a non-blank password.
- Close all running programs.

During the installation, you are asked to provide the host name and the port of the EAC Central Server in your environment. If you do not have this information, or if you change the EAC host or port after installation, you can update the configuration via the EAC Settings page in Endeca Workbench. For details, see the *Endeca Workbench Help*.

The silent installer is not interactive and is available for both Windows and UNIX.

To launch the silent installer on Windows:

1. From a command prompt, navigate to the directory where you downloaded the installer.
2. Issue a command similar to the following:

```
nameworkbench_version_arch-OS.exe /s USERNAME=endecea PASSWORD=endeicapwd
CONFIRMPASSWORD=endeicapwd EACHOST=localhost
```

Replace *name* with the name of the Workbench edition you purchased (iap, merch, or pub). The options that you can pass to the command line installer are as follows:

Option	Description
TARGETDIR	Optional. The absolute path to the directory where you want to install Endeca Workbench. The default location is <code>C:\Endeca\Workbench</code> .



Note: If you do not use the default location, and you are installing more than one Endeca product on the same machine, ensure that you install each product to a separate location.

Option	Description
USERNAME	Required. The user name to use when launching the Endeca Tools Service. The user must already exist.
PASSWORD	Required. The password for the Endeca Tools Service user.
CONFIRMPASSWORD	Required. Confirm the password for the Endeca Tools Service user.
DOMAINNAME	Optional. The Windows domain for the Endeca Tools Service user. The default is the domain the current user is logged in to.
SERVICEPORT	Optional. The port on which Endeca Workbench accepts HTTP connections. The default is 8006.
SHUTDOWNPORT	Optional. The shutdown port for the Endeca Tools Service. The default is 8084.
EACHHOST	Required. The fully qualified name, including domain information, of the host on which the EAC Central Server will be installed in the staging environment. This may be either your local machine, or a remote one.
 EACPORT	Note: Endeca does not recommend that Endeca Workbench connects to the EAC Central Server that is being used in the production environment.
EACPORT	Optional. The port on which EAC Central Server accepts HTTP connections. The default is 8888.

The command line call returns immediately, but the installer continues to run for a few minutes in the background as it installs Endeca Workbench, sets the `ENDECA_TOOLS_ROOT` and `ENDECA_TOOLS_CONF` environment variables, and starts the Endeca Tools Service.

Here is a more detailed example of a silent installation command on Windows for IAP Workbench:

```
iapworkbench_version_arch-OS.exe /s TARGETDIR=C:\Endeca\Workbench
USERNAME=endeca PASSWORD=endecapwd CONFIRMPASSWORD=endecapwd
DOMAINNAME=MYDOMAIN SERVICEPORT=8006 SHUTDOWNPORT=8084
EACHHOST=dataproc.example.com EACPORT=8888
```

UNIX installation procedures

This section contains the Endeca Workbench installation procedures for UNIX.

Installation steps on UNIX

The Endeca software is distributed as a self-extracting tar file and install script. It can be installed at any location.

During the installation, you are asked to provide the host name and the port of the EAC Central Server in your environment. If you do not have this information, or if you change the EAC host or port after installation, you can update the configuration via the EAC Settings page in Endeca Workbench. For details, see the *Endeca Workbench Help*.

To install Endeca Workbench on UNIX:

1. Determine where you will install the Endeca system. In this procedure, we assume this is the `/usr/local` directory.
2. Locate the Endeca installation file. This procedure assumes the location is `/downloads`. Depending on your product, this file can be any of the following:
 - `iapworkbench_version_arch-OS.sh` for Endeca Workbench
 - `merchworkbench_version_arch-OS.sh` for Merchandising Workbench
 - `pubworkbench_version_arch-OS.sh` for Publishing Workbench

3. Assuming the locations used in steps 1 and 2, run the install script with the following command, substituting the appropriate file name from the step above:

```
/downloads/iapworkbench_version_arch-OS.sh --target /usr/local
```

4. The copyright and legal information displays. Scroll to the end.
As the installation is being unpacked, a series of dots serves as a progress monitor. The unpacking may take several minutes. After the unpacking, you are asked a series of configuration questions.



Note: Where applicable, the default value for each option is shown. However, to accept the default you must manually enter that value in the installer.

5. Enter the fully qualified name, including domain information, of the host on which Endeca Workbench will be running. The default is the name of the machine you are installing on.
6. Enter the port for the Endeca Tools Service, which is the port on which Endeca Workbench accepts HTTP connections.
7. Enter the shutdown port for the Endeca Tools Service.
8. Enter the fully qualified name, including domain information, of the host on which the EAC Central Server will be installed in the staging environment. This may be either your local machine, or a remote one.



Note: Endeca does not recommend that Endeca Workbench connects to the EAC Central Server that is being used in the production environment.

9. Enter the port for the Endeca Application Controller, which is the port on which EAC Central Server accepts HTTP connections.

When the installation is complete, the screen displays a reminder message about setting the environment variables similar to the following:

```
Please run the following command to set your environment variables:
```

```
Bourne, Bash or Korn:
      source /usr/local/endeca/Workbench/workspace/setup/installer_sh.ini

csh or tcsh:
      source /usr/local/endeca/Workbench/workspace/setup/installer_csh.ini
```

The command referenced in the message sets the `ENDECA_TOOLS_ROOT` and `ENDECA_TOOLS_CONF` environment variables for the current user. Generally this command should be placed in a script run at the startup of the shell so the variables are set for future use.

After running the installer, you also need to start the Endeca Tools Service.

Related Links

[Starting and stopping the Endeca Tools Service on UNIX](#) on page 24

The Endeca Tools Service is installed with Endeca Workbench but the UNIX installation does not automatically start the service.

Silent installation steps on UNIX

The silent installer is useful if you want to add the installation of Endeca Workbench to your own install script, or push out the installation on multiple machines.

During the installation, you are asked to provide the host name and the port of the EAC Central Server in your environment. If you do not have this information, or if you change the EAC host or port after installation, you can update the configuration via the EAC Settings page in Endeca Workbench. For details, see the *Endeca Workbench Help*.

The silent installer is not interactive and is available for both Windows and UNIX.

To launch the silent installer on UNIX:

1. From a command prompt, navigate to the directory where you downloaded the installer.
2. Create a new text file named `workbench_install_config.txt`.
3. In the file, specify the value for each configurable option on its own line, in the order in which they appear in the interactive installer. For example:

```
workbench.example.com
8006
8084
dataproc.example.com
8888
```

The options are as follows:

Line number	Description
1	The fully qualified name, including domain information, of the host on which Endeca Workbench will be running. This should be the name of the local machine. In the example, this is specified as <code>workbench.example.com</code> .
2	The port on which Endeca Workbench accepts HTTP connections. In the example, this is specified as <code>8006</code> .
3	The shutdown port for the Endeca Tools Service. In the example, this is specified as <code>8084</code> .
4	The fully qualified name, including domain information, of the host on which the EAC Central Server will be installed in the staging environment. This may be either your local machine, or a remote one. In the example, this is specified as <code>dataproc.example.com</code> .
5	 Note: Endeca does not recommend that Endeca Workbench connects to the EAC Central Server that is being used in the production environment.
5	The port on which EAC Central Server accepts HTTP connections. In the example, this is specified as <code>8888</code> .



Note: Do not include the line numbers in your configuration file. You must specify a value for each option. Even if you want to use the default, you must specify that value to the installer.

4. Issue the following command:

```
./nameworkbench_version_arch-OS.sh --silent --target /usr/local <
workbench_install_config.txt
```

Replace *name* with the name of the Workbench edition you purchased (iap, merch, or pub). Replace /usr/local with the location to which you want to install.

When the installation is complete, the screen displays a reminder message about setting the environment variables similar to the following:

```
Please run the following command to set your environment variables:
```

```
Bourne, Bash or Korn:
```

```
source /usr/local/endeca/Workbench/workspace/setup/installer_sh.ini
```

```
csh or tcsh:
```

```
source /usr/local/endeca/Workbench/workspace/setup/installer_csh.ini
```

The command referenced in the message sets the ENDECA_TOOLS_ROOT and ENDECA_TOOLS_CONF environment variables for the current user. If you are scripting the install, add this command after the installation to set up the environment variables properly. Additionally, this command should be placed in a script run at the startup of the shell so the variables are set for future use.

After running the installer, you also need to start the Endeca Tools Service.

Related Links

[Starting and stopping the Endeca Tools Service on UNIX](#) on page 24

The Endeca Tools Service is installed with Endeca Workbench but the UNIX installation does not automatically start the service.

Verifying your Endeca Workbench installation

When you have completed the installation, you can do a simple check to make sure that Endeca Workbench is installed correctly.

Before you can access Endeca Workbench, the Endeca Tools Service must be running.

To verify your Workbench installation:

1. Open Internet Explorer and enter the following URL:

```
http://host:8006
```

Replace *host* with the name of your Endeca Workbench server and 8006 with the Endeca Workbench port if you specified a different port.

If Endeca Workbench has been successfully installed, the Endeca Workbench login screen displays.

2. Optionally, log in with the default **Username**: admin and **Password**: admin.



Note: If you have not yet provisioned an application, you only have access to the EAC Admin Console and EAC Settings within Endeca Workbench. For information about configuring a sample application, see the *Endeca Getting Started Guide*.

Package contents and directory structure

This topic describes in detail the directories that are created in the Endeca Workbench installation.

The `Workbench` directory is the top-level directory for Endeca Workbench. Its sub-directories are described below.

Root directory

The `Workbench/version` directory is the root directory for Endeca Workbench. This is the `ENDECA_TOOLS_ROOT` directory, which contains the release notes (`README.txt`) and the following directories:

Directory	Contents
<code>/conf/dtd</code>	The document type definitions (DTDs) for Endeca XML configuration files.
<code>/conf/schema</code>	The Page Builder editor and content schema files (XSDs).
<code>/doc</code>	The <i>Endeca Third-Party Software Usage and Licenses</i> . Additional documentation is available from the Endeca Developer Network (EDeN) at http://eden.endeca.com .
<code>/j2sdk</code>	Version 6 of the Java Platform Standard Edition Development Kit (JDK).
<code>/reference</code>	The <code>pagebuilderEditorSDK.zip</code> archive, which includes the Page Builder Editor SDK as well as sample editor files and generated ActionScript documentation. The contents are described in detail in the <i>Page Builder Developer's Guide</i> .
<code>/server</code>	The Web applications that run inside the Endeca Tools Service, including Endeca Workbench, the Workbench Help Infocenter, and the Endeca JSP reference application.
<code>/workspace-template</code>	A set of files that you can use to create another copy of the workspace on UNIX (using <code>\$ENDECA_TOOLS_ROOT/setup/create_workbench_workspace.sh</code>) or to restore the default settings to your current workspace.

Workspace directory

The `Workbench/workspace` directory is the `ENDECA_TOOLS_CONF` directory and contains the following directories:

Directory	Contents
<code>/conf</code>	Configuration files for Endeca Workbench and the Endeca Tools Service.
<code>/logs</code>	Logs for Endeca Workbench and the Endeca Tools Service.
<code>/reports</code>	The default directory for reports to be viewed in Endeca Workbench.

Directory	Contents
/state	Storage for the instance configuration for Endeca applications being managed by Endeca Workbench, as well as the Endeca Workbench database.
/temp	Temporary storage for Endeca Workbench and the Endeca Tools Service.
/work	The Endeca Tools Service cache. This is not part of the Endeca Workbench installation but is created when you first run the Endeca Tools Service.



Chapter 3

After you install

After installing Endeca Workbench, you may need to run or configure the Endeca Tools Service.

About the Endeca Tools Service

The Endeca Tools Service is a Servlet container that runs Endeca Workbench, the Workbench Help Infocenter, and a version of the Endeca JSP reference application, which serves as the default preview application in Endeca Workbench.

About starting the Endeca Tools Service from inittab

In a UNIX development environment, the Endeca Tools Service can be started from the command line. In a UNIX production environment, however, Endeca recommends that it be started by `init` from `inittab`.

The UNIX version of Endeca Workbench contains a file named `endeaca_run.sh` that is in the `$ENDECA_TOOLS_ROOT/server/bin` directory. This is a version of `startup.sh` that calls `run` instead of `start` and redirects `stdout` and `stderr` to `$ENDECA_TOOLS_CONF/logs/catalina.out`.

You can write a script that is referenced in `inittab`. The script sets environment variables and then calls `endeaca_run.sh`. When writing your script, it is recommended as a best practice that you run the Endeca Tools Service as a user other than root. When running the service as a non-root user, you can set a `USER` environment variable that will be inherited by other scripts.

This sample script (named `start_endeca_tools_service.sh`) sets the `ENDECA_USER` variable to the “`endeaca`” user, sets the `INSTALLER_SH` variable to the path of the environment variables script and sources it, and then does an `su` to change to the “`endeaca`” user:

```
#!/bin/sh
ENDECA_USER=endeaca
INSTALLER_SH=/usr/local/endeaca/Workbench/workspace/setup/installer_sh.ini
# We want to use installer_sh.ini variables in this script,
# so we source it here
source $INSTALLER_SH
# change to user endeaca
su $ENDECA_USER -c "/bin/sh -c \"source $INSTALLER_SH; \
cd $ENDECA_TOOLS_CONF/work; exec env USER=$ENDECA_USER \
$ENDECA_TOOLS_ROOT/server/bin/endeaca_run.sh\""
```

On Solaris platforms, replace "source" with "." because `source` is not a command in the Bourne shell. The `start_endeca_tools_service.sh` script is then referenced in `inittab` with an entry similar to this example.

```
et:2345:respawn:/usr/local/endeca/Workbench/workspace/setup/start_endeca_tools_service.sh
```

When writing your startup script, keep in mind that it is server-specific, and therefore its details (such as paths and user names) depend on the configuration of your server.

Starting and stopping the Endeca Tools Service on Windows

The Endeca Tools Service is installed with Endeca Workbench and automatically started on Windows when installation is complete.

The service is also set to start up automatically when the computer boots up.

To manage the Endeca Tools Service after installation:

1. Go to **Start > Control Panel > Administrative Tools > Services**.
2. In the **Windows Services** editor, select the **Endeca Tools Service**.
3. Click **Stop** or **Restart**.

Starting and stopping the Endeca Tools Service on UNIX

The Endeca Tools Service is installed with Endeca Workbench but the UNIX installation does not automatically start the service.

To manage the Endeca Tools Service after installation:

- Start the Endeca Tools Service with the following command:
 `$ENDECA_TOOLS_ROOT/server/bin/startup.sh`
- Stop the Endeca Tools Service with the following command:
 `$ENDECA_TOOLS_ROOT/server/bin/shutdown.sh`



Chapter 4

Additional installation tasks

If you are installing the Merchandising or Publishing edition of Endeca Workbench, you also need to install the Content Assembler API.

Content Assembler API

The Content Assembler API provides a simple interface to access template-driven content for rendering in Web-based applications.

The Content Assembler API enables a Web application to query the MDEX Engine and retrieve the appropriate dynamic content based on a user's navigation state or other triggers. The Content Assembler returns both Endeca query results familiar from the Presentation API or RAD API as well as a content item object that encapsulates the page configuration specified by the content administrator. All the content for a page, including the results of any additional queries needed for spotlighting or merchandising, are wrapped in the content item object, simplifying the logic in the front-end application by reducing the need to manage sub-queries in the application layer.

Related Links

[Installation procedures for the Content Assembler for Java](#) on page 25

To determine the appropriate Content Assembler version to install, see the *Endeca InFront Compatibility Matrix* available on EDeN.

[Installation procedures for the Content Assembler for the RAD Toolkit for ASP.NET](#) on page 26

To determine the appropriate Content Assembler version to install, see the *Endeca InFront Compatibility Matrix* available on EDeN.

[Installation package contents](#) on page 28

This topic describes in detail the directories that are created in the Content Assembler API installation.

Installation procedures for the Content Assembler for Java

To determine the appropriate Content Assembler version to install, see the *Endeca InFront Compatibility Matrix* available on EDeN.

Prerequisites for installing the Content Assembler API

Before you install the Content Assembler API and reference application for Java, ensure that you have the following requirements in place.

The Content Assembler API requires that you have the following components installed:

- Endeca Presentation API for Java
- Endeca Workbench, if you wish to run the Content Assembler reference application in the Endeca Tools service

The Content Assembler API for Java is supported for all hardware and operating system platforms that are supported by Endeca Workbench.

The Content Assembler API requires Java 1.4 or later.

Installing the Content Assembler API for Java

The Content Assembler API and reference application for Java are distributed in a ZIP package.

Before you install the Content Assembler API, you should first ensure that the Endeca Commerce Suite is installed, including the Presentation API for Java. For details about installing the Endeca Commerce Suite and running the Content Assembler reference application, see the *Endeca Commerce Suite Getting Started Guide*.

To install the Content Assembler API:

1. In your local environment, locate the Content Assembler API package that you downloaded from the Endeca Developer Network (EDeN) at <http://eden.endeca.com>.
The Content Assembler API package is named `ContentAssemblerAPIJava-version.zip`, where `version` is the version number of the Content Assembler API.
2. Extract the ZIP file. Endeca recommends that you extract the file into the Endeca directory. In a default installation, this is `C:\Endeca` (on Windows) or `/usr/local/endeca` (on UNIX).

Before writing applications using the Content Assembler API, you must place the `endeca-content-version.jar` file in your application's classpath.

After you have installed the Content Assembler API, you can deploy the reference application. For details regarding this process, see the *Endeca Commerce Suite Getting Started Guide*.

Installation procedures for the Content Assembler for the RAD Toolkit for ASP.NET

To determine the appropriate Content Assembler version to install, see the *Endeca InFront Compatibility Matrix* available on EDeN.

Prerequisites for installing the Content Assembler API

This topic provides system requirements for installing the Content Assembler API and reference application for the RAD Toolkit for ASP.NET.

The Content Assembler API is supported for Windows Server 2003 and Windows Server 2008 R2.

The following software must be installed before you install the Content Assembler API for the RAD Toolkit for ASP.NET:

- Microsoft .NET Framework. The following versions are supported: 2.0 with SP1, 3.0, and 3.5 (including the 32-bit and 64-bit versions).
- Microsoft Visual Studio 2005 with Service Pack 1 (any edition) or Visual Studio 2008.
- On machines running the Content Assembler reference application, you need Internet Information Services (IIS) 5.1 or later.

Installing the Content Assembler API for the RAD Toolkit for ASP.NET

This section describes how to install the Content Assembler API for the RAD Toolkit for ASP.NET.



Note: The RAD Toolkit for ASP.NET and the Endeca Presentation and Logging APIs for .NET version assemblies are part of the Content Assembler API installation. When building applications using the Content Assembler API, you must use the assemblies that are included in the Content Assembler API installation.

To install the Content Assembler API for the RAD Toolkit for ASP.NET:

1. In your local environment, locate the Content Assembler API package that you downloaded from the Endeca Developer Network (EDeN) at <http://eden.endeca.com>.
The Content Assembler API package is named ContentAssemblerRADNET-version.msi, where *version* is the version number of the Content Assembler API.
2. Double click the installation file, and on the **Welcome** screen, click **Next**.
3. On the **Select Installation Folder** screen, either accept the default installation location, or click **Browse...** and browse to the directory where you want to install. Endeca recommends that you accept the default installation path of C:\Endeca\ContentAssemblerAPIs\RAD Toolkit for ASP.NET\version .
4. On the **Ready to Install** screen, click **Install**.
5. Click **Finish**.

To complete setup of your development environment for the Content Assembler API, add the Endeca server controls and assemblies to Visual Studio.

After you have installed the Content Assembler API, you can deploy the reference application. For details regarding this process, see the *Endeca Commerce Suite Getting Started Guide*.

Adding the Content Assembler API for the RAD Toolkit for ASP.NET to Visual Studio

This procedure adds the Endeca data source controls and Endeca user interface controls to the Toolbox window of Visual Studio and also adds references from your Web site project to Endeca assemblies.

This procedure describes how to add the RAD Toolkit and Content Assembler API to Visual Studio 2005. The procedure may be slightly different in Visual Studio 2008.

To add the RAD Toolkit for ASP.NET and the Content Assembler API to Visual Studio:

1. Start Visual Studio and open your Web site.
2. In the **Toolbox** window, right-click and select **Add Tab**.
3. Type Endeca Content Assembler API.
4. Right-click in the grey box under the entry for the Content Assembler API.
The grey box contains the text "There are no usable controls in this group..."
5. Select **Choose Items...**
After a short delay, the **Choose Toolbox Items** dialog box displays.
6. On the **.NET Framework Components** tab of the **Choose Toolbox Items** dialog box, click **Browse....**
7. Browse to the bin directory of your Content Assembler API installation. In a typical installation, this is C:\Endeca\ContentAssemblerAPIs\RAD Toolkit for ASP.NET\version\bin\
8. Select `Endeca.Web.Content.dll` and click **Open**.

9. Repeat the previous step for `Endeca.Web.dll` and `Endeca.Web.UI.WebControls.dll`.
10. Click **OK**.
The Endeca data source controls, user interface controls, and Content Assembler controls display in the **Toolbox** under Endeca Content Assembler.
11. In the **Solution Explorer** window, right-click your Web site.
12. Select **Add Reference....**
13. In the **Add Reference** dialog, select the **Browse** tab.
14. Browse to the `bin` directory of your Content Assembler API installation.
15. Select `Endeca.Data.Content.dll`, `Endeca.Data.dll`, `Endeca.Logging.dll`, `Endeca.Navigation.AccessControl.dll`, and `Endeca.Navigation.dll`. You do not need to select `Endeca.Web.Content.dll`, `Endeca.Web.dll` or `Endeca.Web.UI.WebControls.dll`.
Visual Studio copies the selected files into the Web site project.

Installation package contents

This topic describes in detail the directories that are created in the Content Assembler API installation.

Java

The `ContentAssemblerAPIs/Java/version` directory contains the release notes for the Content Assembler API for Java (`README_CAJ.txt`) and the following directories:

Directory	Contents
<code>/doc</code>	The <i>Endeca Third-Party Software Usage and Licenses</i> , Content Assembler API reference documentation, and the XML schema documents for templates and for the page configurations generated by the Page Builder (in the <code>schemas</code> subdirectory). Additional documentation is available from the Endeca Developer Network (EDeN) at http://eden.endeca.com .
<code>/lib</code>	The Content Assembler API, distributed as a Jar file.
<code>/reference</code>	The sample context file (<code>ContentAssemblerRefApp.xml</code>) and the <code>thumbnails.xml</code> file for the Content Assembler reference application.
<code>/reference/ContentAssemblerRefApp</code>	The Content Assembler reference application.
<code>/reference/pagebuilder_wine_app</code>	The Content Assembler reference application data.
<code>reference/tag_handlers</code>	The sampler tag handler package <code>endeca-content-2.1.0-samples.jar</code> and an associated sample template.
<code>/reference/thumbnails</code>	Thumbnail images for use with the sample templates included in the Content Assembler reference application.

.NET

The `\ContentAssemblerAPIs\RAD Toolkit for ASP.NET\version` directory contains the release notes for the RAD Toolkit for ASP.NET (`README_RAD.txt`) and the Content Assembler API (`README_CARN.txt`) as well as the following directories:

Directory	Contents
<code>\bin</code>	The assemblies for the Content Assembler API for the RAD Toolkit for ASP.NET.
<code>\doc</code>	The <i>Endeca Third-Party Software Usage and Licenses</i> , Content Assembler API reference documentation, and the XML schema documents for templates and for the page configurations generated by the Page Builder (in the <code>schemas</code> subdirectory). Additional documentation is available from the Endeca Developer Network (EDeN) at http://eden.endeca.com .
<code>\reference\ContentAssemblerRefApp</code>	The Content Assembler reference application for the RAD Toolkit for ASP.NET.
<code>\reference\context_files</code>	The <code>thumbnails.xml</code> file for the Content Assembler reference application.
<code>\reference\pagebuilder_wine_app</code>	The Content Assembler reference application data.
<code>reference\tag_handlers</code>	The sample tag handler package <code>Endeca.Data.Content.Sample.dll</code> along with the source code for the tag handler and an associated sample template.
<code>\reference\thumbnails</code>	Thumbnail images for use with the sample templates included in the Content Assembler reference application.



Chapter 5

Uninstalling Endeca Workbench

This section contains the procedures for uninstalling the package on Windows and UNIX.

Uninstalling Endeca Workbench on Windows

Follow these steps to uninstall Endeca Workbench from your Windows machine.

The uninstall process creates a backup of the `ENDECA_TOOLS_CONF` (workspace) directory then removes Endeca Workbench and the Endeca Tools Service from the machine. If you have any files that you want to retain from the Endeca Workbench directory that are not in this directory, copy them to a safe location before you begin the uninstall process.

To uninstall Endeca Workbench from your Windows machine:

1. From the Windows Control Panel, select **Add or Remove Programs**.
2. Select **Endeca Workbench** from the list of installed software.
3. Click **Remove**.
The installation wizard displays.
4. Confirm that **Uninstall** is selected, then click **Next** twice.
5. When uninstallation has completed, click **Finish** to exit the wizard.

Uninstalling Endeca Workbench on UNIX

Follow these steps to uninstall Endeca Workbench from your UNIX machine.

Before you begin the uninstall process, back up any files that you want to retain from the Endeca Workbench directory. In particular, it is recommended that you preserve the contents of the `ENDECA_TOOLS_CONF` (workspace) directory.

Make sure that you stop all Endeca processes (including the Endeca Tools Service) before uninstalling the Endeca software.

To uninstall Endeca Workbench from your UNIX machine:

1. Issue an `rm` command as in this example:
`rm -rf endeca/Workbench/version`
2. Unset any environment variables (such as `ENDECA_TOOLS_ROOT` and `ENDECA_TOOLS_CONF`) that reference directories that no longer exist.



Chapter 6

Uninstalling the Content Assembler API

This section contains the procedures for uninstalling the Content Assembler API for both Java and the RAD Toolkit for ASP.NET.

Uninstalling the Content Assembler API for Java

You can uninstall the Content Assembler API for Java from your system by deleting the installed directories.

To uninstall the Content Assembler API:

1. Locate the `ContentAssemblerAPIs/Java` directory. In a typical installation this is in your Endeca directory, that is, `C:\Endeca\ContentAssemblerAPIs\Java` (on Windows) or `/usr/local/endeca/ContentAssemblerAPIs/Java` (on UNIX).
2. Delete the `ContentAssemblerAPIs\Java` directory along with its contents.



Note: Deleting this directory will also remove the Content Assembler reference application for Java unless you have moved the `ContentAssemblerAPIs\Java\version\reference` directory to another location.

Uninstalling the Content Assembler API for the RAD Toolkit for ASP.NET

This section describes how to uninstall the Content Assembler for the RAD Toolkit for ASP.NET from a system.

To uninstall the Content Assembler API for the RAD Toolkit for ASP.NET:

1. From the Windows Control Panel, select **Add or Remove Programs**.
2. Select **Endeca Content Assembler API for RAD .NET** from the list of installed software.
3. Click **Remove** and click **Yes** to confirm the removal.
4. Start Visual Studio and open your Web site.
5. In the Toolbox window, right-click the **Endeca Content Assembler API** tab and select **Delete Tab**.



Chapter 7

Uninstalling the Content Assembler reference application

This section contains the procedures for uninstalling the Content Assembler reference application for both Java and the RAD Toolkit for ASP.NET.

Uninstalling the Content Assembler reference application for Java

The following steps assume that you installed the reference application in the Endeca Tools service.

To uninstall the Content Assembler reference application:

1. Stop the Endeca Tools service.
2. Navigate to %ENDECA_TOOLS_CONF%\conf\Standalone\localhost (on Windows) or \$ENDECA_TOOLS_CONF/conf/Standalone/localhost (on UNIX).
3. Locate and delete the ContentAssemblerRefApp.xml file.
4. Locate and delete the Content Assembler reference application directory along with its contents.
In a typical installation this is
C:\Endeca\ContentAssemblerAPIs\Java\version\reference\ContentAssemblerRefApp
(on Windows) or
/usr/local/endeca/ContentAssemblerAPIs/Java/version/reference/ContentAssemblerRefApp
(on UNIX).
5. Start the Endeca Tools service.

Uninstalling the Content Assembler reference application for the RAD Toolkit for ASP.NET

If you wish to uninstall the Content Assembler reference application, remove the virtual directories in IIS.

To uninstall the Content Assembler reference application for the RAD Toolkit for ASP.NET:

1. From the Windows Control Panel, select **Administrative Tools > Internet Information Services Manager**.

2. In the IIS tree pane, expand the machine icon for the local machine, then expand the **Web Sites** directory.
3. Select **Default Web Site**.
4. In the right pane, right-click **ContentAssemblerRefApp**, or the name of your application's site, click **Delete**, and click **Yes** to confirm the deletion.
5. Close the Internet Information Services window.



Appendix A

Full List of Documentation Resources

This section describes the documentation related to each platform component. Only essential documentation is included with the product installation, but all Endeca documentation is available on the Endeca Developer Network (EDeN) for browsing or download, either individually or as part of an overall Documentation package.

General Endeca documentation

The following table lists the documentation that applies across multiple Endeca packages.

Title	Description
<i>Endeca Getting Started Guide</i>	Overview of Endeca components including information about configuration scenarios.
<i>Endeca Concepts Guide</i>	Introduction to the Endeca Information Access Platform. Covers the key concepts underlying Endeca applications.
<i>Endeca Administrator's Guide</i>	Describes tasks involved in administering and maintaining applications built upon the Endeca Information Access Platform. It bridges the gap between the work performed by the Endeca Services team and the issues that system administrators encounter when maintaining the system.
<i>Endeca Glossary</i>	A reference for Endeca terms and definitions.
<i>Endeca Third-Party Software Usage and Licenses</i>	Provides copyright, license agreement, and/or disclaimer of warranty information for the third-party software packages that Endeca incorporates.

MDEX Engine documentation

The following table lists the documentation related to the MDEX Engine package.

Title	Description
<i>Analytics Guide</i>	Provides an overview of Endeca Analytics and describes the Analytics and Charting APIs, date and time properties, and key properties.

Title	Description
<i>Basic Development Guide</i>	Provides information about working with records, dimensions, and basic search features.
<i>Advanced Development Guide</i>	Covers such topics as Endeca Query Language (EQL), record filters, bulk export, spelling correction, phrasing, relevance ranking, and dynamic business rules.
<i>MDEX Engine Installation Guide</i>	Provides a brief overview of the Endeca MDEX Engine, details installation procedures, and describes how to configure the licensing keys for the Language Pack. Covers both Windows and Linux/UNIX system requirements and installation procedures.
<i>MDEX Engine Migration Guide</i>	Provides information on migrating from previous versions of Endeca software.
<i>Partial Updates Guide</i>	A guide to preparing and running partial updates in your Endeca application.
<i>Performance Tuning Guide</i>	Provides guidelines on monitoring and tuning the performance of the Endeca MDEX Engine. Contains tips on resolving associated operational issues.
<i>Web Services and XQuery Developer's Guide</i>	Describes how to use Web services and XQuery for Endeca. Web services and XQuery for Endeca provides Endeca application developers with a flexible, extensible, and standards-compliant query processing solution.
<i>MDEX Engine Release Notes</i>	Details the changes specific to this release, including bug fixes and new features.

Presentation API documentation

The following table lists the documentation for the Presentation API package.

Title	Description
<i>Presentation API for Java Reference (Javadoc)</i>	The Java reference documentation for the Endeca Presentation, Analytics, and Charting APIs.
<i>Presentation API for .NET Reference</i>	The .NET reference documentation for the Endeca Presentation, Analytics, and Charting APIs.
<i>Logging API for Java Reference (Javadoc)</i>	The Java reference documentation for the Endeca Logging API.
<i>Logging API for .NET Reference</i>	The .NET reference documentation for the Endeca Logging API.

Platform Services documentation

The following table lists the documentation related to the Platform Services package.

Title	Description
<i>Content Adapter Developer's Guide</i>	Describes how to write Java manipulators and content adapters using the Endeca Content Adapter Development Kit.
<i>Control System Guide</i>	Provides information on using the Endeca Control System, including communicating with the JCD service and running control scripts.
<i>EAC Guide</i>	Describes the tasks involved in managing implementations using the Endeca Application Controller.
<i>Forge Guide</i>	The essential reference for developers of the back-end of Endeca applications (the instance configuration), including Forge pipeline-related tasks.
<i>Log Server and Report Generator Guide</i>	Describes how to configure and run the Endeca Log Server and the Report Generator.
<i>Platform Services Installation Guide</i>	Describes how to install the Endeca Platform Services software, the Endeca Document Conversion Module, and the optional Corda software. Covers both Windows and Linux/UNIX system requirements and installation procedures.
<i>Security Guide</i>	Describes how to implement user authentication and how to structure your data to limit access to only those users with the correct permissions.
<i>Data Foundry Expression Reference</i>	Describes the Data Foundry expression language, used in record manipulators in Developer Studio.
<i>Developer Studio Help</i>	Help (including context-sensitive help) for using Endeca Developer Studio to define all aspects of your instance configuration, including properties, dimensions, and pipelines.
<i>Forge API Guide for Perl</i>	Describes the classes and methods you can incorporate into Perl manipulators in Developer Studio. You can use Perl manipulators in pipelines to manipulate records.
<i>XML Reference</i>	Describes the XML elements contained in the XML and DTD files of the Endeca Information Transformation Layer.
<i>API reference documentation (Javadoc and .NET API reference)</i>	The reference documentation for the Endeca Presentation, Logging, Analytics, and Charting APIs.

Endeca Workbench documentation

The following table lists the documentation related to the Endeca Workbench package.

Title	Description
<i>Endeca Workbench Administrator's Guide</i>	The essential guide for administrators of Endeca implementations and application developers who maintain and customize Workbench instances.
<i>Endeca Workbench User's Guide</i>	The essential guide for business users of Endeca Workbench. Describes enhancements business users can make to Endeca

Title	Description
	implementations with a focus on working with dynamic business rules, search configuration, and reports.
<i>Endeca Workbench Installation Guide</i>	Describes how to install the Endeca Workbench software. Covers both Windows and Linux/UNIX system requirements and installation procedures.
<i>Endeca Workbench Migration Guide</i>	Provides information on migrating from previous versions of Endeca software.
<i>Endeca Workbench Help</i>	Help (including context-sensitive help) for using Endeca Workbench to perform business-user tasks and administer an Endeca implementation. There are versions for each Workbench edition.
<i>Endeca Workbench Release Notes</i>	Details the changes specific to this release, including bug fixes and new features.

Content Assembler API documentation

The following table lists the documentation related to the Content Assembler API, used in conjunction with the Page Builder component of Endeca Workbench.

Title	Description
<i>Page Builder Developer's Guide</i>	Describes the process of developing templates and other supporting tasks to enable content administrators to configure dynamic landing pages using the Endeca Page Builder. Also describes extending Page Builder functionality with community editors.
<i>Content Assembler API Developer's Guide</i>	Describes the process of developing applications with cartridges (for use with the Endeca Page Builder), including usage of the Content Assembler API and an overview of the reference applications. Also describes extending Content Assembler functionality with community tag handlers. There are versions for Java and .NET.
<i>API reference documentation (Javadoc and .NET API reference)</i>	The reference documentation for the Endeca Content Assembler APIs.
<i>Page Builder Editor API reference</i>	The reference documentation for the Page Builder Editor API, part of the Page Builder Editor SDK.
<i>Content Assembler Release Notes</i>	Details the changes specific to this release, including bug fixes and new features.

Content Acquisition System (CAS) documentation

The following table lists the documentation related to the Content Acquisition System (CAS) package.

Title	Description
<i>CAS Console Help</i>	Describes the tasks involved in managing various data sources including file systems, Documentum repositories, and other CMS repositories using the CAS Console for Endeca Workbench.
<i>CAS Developer's Guide</i>	Provides an overview of the Endeca Content Acquisition System, including the Endeca CAS Server, the Component Instance Manager, and the Record Store. The guide also explains how to create a Forge pipeline that utilizes the source data gathered from file system and CMS crawls.
<i>CAS Extension API Guide</i>	Describes how to implement, test, and package CAS extensions using the CAS Extension API.
<i>CAS Installation Guide</i>	Describes how to install the Endeca CAS software. Covers both Windows and Linux/UNIX system requirements and installation procedures.
<i>CAS Migration Guide</i>	Describes the major migration tasks for the suite of CAS components.
<i>CAS API Guide</i>	Provides reference information about the Endeca CAS Server API, the Component Instance Manager API, and the Record Store API.
<i>CMS Connector Guides</i>	Describe the tasks involved in enabling and configuring the various CMS connectors for use with the CAS Server. These guides are available only from the Product Downloads section of the Endeca Developer Network (EDeN).
<i>Web Crawler Guide</i>	Describes the major tasks involved in configuring the Endeca Web Crawler and using it to run crawls that gather source data from Web sites.
<i>CAS Release Announcement</i>	Describes the major new features in this release.
<i>CAS Release Notes</i>	Details the changes specific to this release, including bug fixes and new features.

Rapid Application Development (RAD) Toolkit documentation

The following table lists the documentation related to the Rapid Application Development (RAD) Toolkit for ASP.NET.

Title	Description
<i>RAD Toolkit Developer's Guide</i>	The essential guide for developers of the front-end of Endeca applications (primarily API-related tasks). Also includes information about installation tasks.
<i>RAD Toolkit Release Announcement</i>	Describes the major new features in this release.

Title	Description
<i>RAD Toolkit Release Notes</i>	Details the changes specific to this release, including bug fixes and new features.
<i>API reference documentation (.NET API reference)</i>	The reference documentation for the Endeca RAD API. See also the Input Types and Output Types diagrams for additional information about the API.

Documentation for other packages

The following table lists the documentation related to other Endeca packages.

Deployment Template

Title	Description
<i>Deployment Template Usage Guide</i>	Describes the Deployment Template directories and script functionality, and identifies touch-points where developers may need to configure or extend the template for their projects.
<i>Release Notes (CHANGES)</i>	Details the changes specific to this release, including bug fixes and new features.

Developer Studio

Title	Description
<i>Developer Studio Installation Guide</i>	Provides an overview of Developer Studio and describes system requirements and installation procedures.
<i>Developer Studio Help</i>	Help (including context-sensitive help) for using Endeca Developer Studio to define all aspects of your instance configuration, including properties, dimensions, and pipelines.
<i>Data Foundry Expression Reference</i>	Describes the Data Foundry expression language, used in record manipulators in Developer Studio.
<i>Forge API Guide for Perl</i>	Describes the classes and methods you can incorporate into Perl manipulators in Developer Studio. You can use Perl manipulators in pipelines to manipulate records.
<i>XML Reference</i>	Describes the XML elements contained in the XML and DTD files of the Endeca Information Transformation Layer.

Search Engine Optimization Module

Title	Description
<i>Sitemap Generator Developer's Guide</i>	Describes the Endeca Sitemap Generator and provides instructions for using it to generate sitemaps for an Endeca application.
<i>URL Optimization API Developer's Guide</i>	Describes the major tasks involved in developing an application that utilizes the Endeca URL Optimization API. There are

Title	Description
	versions for Java, the Presentation API for ASP.NET, and the RAD Toolkit for ASP.NET.
<i>API reference documentation (Javadoc and .NET API reference)</i>	The reference documentation for the URL Optimization APIs.



Appendix B

Endeca Environment Variables and Port Usage

This section lists all the environment variables and ports used by the Endeca software. Depending on which components you have installed, not all of them may apply to your implementation.

Endeca environment variables

The Endeca installation programs create several environment variables.

For each variable, the first value listed is the path if you accept the default installation path on Windows (under `C:\Endeca\product`) and use a per-machine installation. The default paths for a per-user installation will be rooted in the `%USERPROFILE%` directory.

The second value is the path within your installation directory on UNIX. For example, if you install Endeca to `/usr/local/`, the full path of `ENDECA_ROOT` would be `/usr/local/endeca/Platform-Services/version` in your environment.

In addition to creating the variables below, the installation may add Endeca directories to the `PATH` variable.



Note: For the MDEX Engine installation, environment and `PATH` variables are set by running the `mindex_setup` scripts provided by the installation. See the *MDEX Engine Installation Guide* for more information.

MDEX Engine variables

The following variable is used by the MDEX Engine:

Variable	Description	Default value
<code>ENDECA_MDEX_ROOT</code>	Specifies the path of the MDEX Engine root directory.	<ul style="list-style-type: none"><code>C:\Endeca\MDEX\version</code><code>endeca/MDEX/version</code>

Platform Services variables

The following variables are used by the Platform Services:

Variable	Description	Default value
ENDECA_ROOT	Specifies the path of the Platform Services root directory.	<ul style="list-style-type: none"> • C:\Endeca\PlatformServices\version • endeca/PlatformServices/version
ENDECA_REFERENCE_DIR	Specifies the path of the directory that contains the Endeca reference implementations, such as the sample wine project and the JSP and .NET UI references.	<ul style="list-style-type: none"> • C:\Endeca\PlatformServices\reference • endeca/PlatformServices/reference
ENDECA_CONF	Specifies the path of the workspace directory for the Endeca HTTP service, which contains configuration files, logs, and temporary storage directories.	<ul style="list-style-type: none"> • C:\Endeca\PlatformServices\workspace • endeca/PlatformServices/workspace
PERLLIB	Specifies the path of the perl root directory and its directory of libraries.	<ul style="list-style-type: none"> • %ENDECA_ROOT%\perl and %ENDECA_ROOT%\perl\5.8.3\lib • \$ENDECA_ROOT/lib/perl:\$ENDECA_ROOT/lib/perl/Control:\$ENDECA_ROOT/perl/lib:\$ENDECA_ROOT/perl/lib/site_perl
PERL5LIB	Same as the PERLLIB variable.	Same as the PERLLIB variable.
UnixUtils	Specifies the path of the utilities directory, which contains Windows versions of some UNIX common utilities.	<ul style="list-style-type: none"> • %ENDECA_ROOT%\utilities • not available on UNIX

Endeca Workbench variables

The following variables are used by the Endeca Workbench:

Variable	Description	Default value
ENDECA_TOOLS_ROOT	Specifies the path of the Endeca Workbench root directory.	<ul style="list-style-type: none"> • C:\Endeca\Workbench\version • endeca/Workbench/version
ENDECA_TOOLS_CONF	Specifies the path of the workspace directory for the Endeca Tools Service, which	<ul style="list-style-type: none"> • C:\Endeca\Workbench\workspace • endeca/Workbench/workspace

Variable	Description	Default value
	contains configuration files, logs, and temporary storage directories.	

Other variables

Other variables used by Endeca include the following:

Variable	Description	Default value
ENDECA_PROJECT_DIR	Specifies the path of the deployed application. This variable is set and used by the Endeca Deployment Template.	Value is taken from user input at installation time.
ENDECA_PROJECT_NAME	Specifies the project name that is used, for example, as the JCD job prefix for jobs defined in the project's Job Control Daemon. This variable is set and used by the Endeca Deployment Template.	Value is taken from user input at installation time.

Endeca ports

This topic describes the ports used by the Endeca packages and their default port numbers.

You can replace any of the default port numbers with numbers of your own, as long as they do not conflict with an existing port on your machine. Port numbers can be no larger than 32767.

Service ports

Port	Default
Endeca Tools Service port	8006
Endeca Tools Service SSL port	8446
Endeca Tools Service shutdown port	8084
CAS Service port	8500
CAS Service shutdown port	8506
Endeca HTTP Service port	8888
Endeca HTTP Service SSL port	8443
Endeca HTTP Service shutdown port	8090
Endeca Control System JCD port	8088

Port	Default
 Note: The JCD is deprecated.	

Deployment Template ports

These are the port numbers suggested by the Deployment Template installation, but you can specify any other port when you deploy your application.

Port	Default
Dgraph1 user query port	15000
Dgraph2 user query port	15001
Agraph1 user query port (Agraph deployments only)	14000
Agraph2 user query port (Agraph deployments only)	14001
Forge server (Agraph deployments with Parallel Forge only)	14099
Endeca Logging and Reporting Server port	15010
 Note: The Logging Server port number can be no larger than 32767.	

Reference implementation ports

These port numbers are used in the configuration files that ship with the reference implementation (sample_wine_data).

Port	Default
Endeca MDEX Engine user query port	8000
Endeca Logging and Reporting Server port	8002
 Note: The Logging Server port number can be no larger than 32767. In the JSP reference implementation, the default Logging server port number is larger by 2 than the corresponding Dgraph port number. For example, for the Dgraph port 15000, the default port for the Logging Server in the reference implementation is 15002. For the Dgraph port 15001, the default port for the Logging Server in the reference implementation is 15003. (This assumes that the Logging Server is running on the same host as the MDEX Engine.)	

Index

C

Content Assembler API
installing 26, 27
package contents 28
directory structure 28
documentation 40
for Java 26
for RAD Toolkit for ASP.NET 27
overview 25

Content Assembler API for Java
system prerequisites 26
uninstalling 33

Content Assembler API for the RAD Toolkit for ASP.NET
installing 27
system prerequisites 26
uninstalling 33
adding to Visual Studio 27

Content Assembler reference application
uninstalling 35
installing 26, 27

D

directory structure 20
documentation
Content Acquisition System (CAS) 41
Content Assembler API 40
Deployment Template 42
MDEX Engine 38
Platform Services 39
RAD Toolkit 42
Developer Studio 42
Endeca Workbench 40
general 37
Presentation API 38
SEO Module 43

E

Endeca environment variables 45
Endeca ports 47
Endeca Workbench
documentation 39
overview 9

I

installation
on UNIX 16
on Windows 14
silent 15, 18
verifying 19
Installation
additional tasks

P

package contents 20
ports 47
used by Deployment Template 48
used by Endeca Tools Service and HTTP service 47
used by reference implementation 48
prerequisites 10

S

silent installation
on UNIX 18
on Windows 15
system prerequisites 26
system requirements 9, 10

U

uninstalling
Content Assembler API for Java 33
Content Assembler API for the RAD Toolkit for ASP.NET 33
Content Assembler reference application 35
on UNIX 31
on Windows 31

V

verifying installation 19

