

Managing Remote Systems in Oracle® Solaris 11.4

ORACLE®

Part No: E61010
November 2020

Part No: E61010

Copyright © 2002, 2020, Oracle and/or its affiliates.

License Restrictions Warranty/Consequential Damages Disclaimer

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Trademark Notice

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

Third-Party Content, Products, and Services Disclaimer

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Pre-General Availability Draft Label and Publication Date

Pre-General Availability: 2020-01-15

Pre-General Availability Draft Documentation Notice

If this document is in public or private pre-General Availability status:

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

Oracle Confidential Label

ORACLE CONFIDENTIAL. For authorized use only. Do not distribute to third parties.

Revenue Recognition Notice

If this document is in private pre-General Availability status:

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Référence: E61010

Copyright © 2002, 2020, Oracle et/ou ses affiliés.

Restrictions de licence/Avis d'exclusion de responsabilité en cas de dommage indirect et/ou consécutif

Ce logiciel et la documentation qui l'accompagne sont protégés par les lois sur la propriété intellectuelle. Ils sont concédés sous licence et soumis à des restrictions d'utilisation et de divulgation. Sauf stipulation expresse de votre contrat de licence ou de la loi, vous ne pouvez pas copier, reproduire, traduire, diffuser, modifier, accorder de licence, transmettre, distribuer, exposer, exécuter, publier ou afficher le logiciel, même partiellement, sous quelque forme et par quelque procédé que ce soit. Par ailleurs, il est interdit de procéder à toute ingénierie inverse du logiciel, de le désassembler ou de le décompiler, excepté à des fins d'interopérabilité avec des logiciels tiers ou tel que prescrit par la loi.

Exonération de garantie

Les informations fournies dans ce document sont susceptibles de modification sans préavis. Par ailleurs, Oracle Corporation ne garantit pas qu'elles soient exemptes d'erreurs et vous invite, le cas échéant, à lui en faire part par écrit.

Avis sur la limitation des droits

Si ce logiciel, ou la documentation qui l'accompagne, est livré sous licence au Gouvernement des Etats-Unis, ou à quiconque qui aurait souscrit la licence de ce logiciel pour le compte du Gouvernement des Etats-Unis, la notice suivante s'applique :

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

Avis sur les applications dangereuses

Ce logiciel ou matériel a été développé pour un usage général dans le cadre d'applications de gestion des informations. Ce logiciel ou matériel n'est pas conçu ni n'est destiné à être utilisé dans des applications à risque, notamment dans des applications pouvant causer un risque de dommages corporels. Si vous utilisez ce logiciel ou matériel dans le cadre d'applications dangereuses, il est de votre responsabilité de prendre toutes les mesures de secours, de sauvegarde, de redondance et autres mesures nécessaires à son utilisation dans des conditions optimales de sécurité. Oracle Corporation et ses affiliés déclinent toute responsabilité quant aux dommages causés par l'utilisation de ce logiciel ou matériel pour des applications dangereuses.

Marques

Oracle et Java sont des marques déposées d'Oracle Corporation et/ou de ses affiliés. Tout autre nom mentionné peut correspondre à des marques appartenant à d'autres propriétaires qu'Oracle.

Intel et Intel Inside sont des marques ou des marques déposées d'Intel Corporation. Toutes les marques SPARC sont utilisées sous licence et sont des marques ou des marques déposées de SPARC International, Inc. AMD, Epyc, et le logo AMD sont des marques ou des marques déposées d'Advanced Micro Devices. UNIX est une marque déposée de The Open Group.

Avis d'exclusion de responsabilité concernant les services, produits et contenu tiers

Ce logiciel ou matériel et la documentation qui l'accompagne peuvent fournir des informations ou des liens donnant accès à des contenus, des produits et des services émanant de tiers. Oracle Corporation et ses affiliés déclinent toute responsabilité ou garantie expresse quant aux contenus, produits ou services émanant de tiers, sauf mention contraire stipulée dans un contrat entre vous et Oracle. En aucun cas, Oracle Corporation et ses affiliés ne sauraient être tenus pour responsables des pertes subies, des coûts occasionnés ou des dommages causés par l'accès à des contenus, produits ou services tiers, ou à leur utilisation, sauf mention contraire stipulée dans un contrat entre vous et Oracle.

Date de publication et mention de la version préliminaire de Disponibilité Générale ("Pre-GA")

Version préliminaire de Disponibilité Générale ("Pre-GA") : 15.01.2020

Avis sur la version préliminaire de Disponibilité Générale ("Pre-GA") de la documentation

Si ce document est fourni dans la Version préliminaire de Disponibilité Générale ("Pre-GA") à caractère public ou privé :

Cette documentation est fournie dans la Version préliminaire de Disponibilité Générale ("Pre-GA") et uniquement à des fins de démonstration et d'usage à titre préliminaire de la version finale. Celle-ci n'est pas toujours spécifique du matériel informatique sur lequel vous utilisez ce logiciel. Oracle Corporation et ses affiliés déclinent expressément toute responsabilité ou garantie expresse quant au contenu de cette documentation. Oracle Corporation et ses affiliés ne sauraient en aucun cas être tenus pour responsables des pertes subies, des coûts occasionnés ou des dommages causés par l'utilisation de cette documentation.

Mention sur les informations confidentielles Oracle

INFORMATIONS CONFIDENTIELLES ORACLE. Destinées uniquement à un usage autorisé. Ne pas distribuer à des tiers.

Avis sur la reconnaissance du revenu

Si ce document est fourni dans la Version préliminaire de Disponibilité Générale ("Pre-GA") à caractère privé :

Les informations contenues dans ce document sont fournies à titre informatif uniquement et doivent être prises en compte en votre qualité de membre du customer advisory board ou conformément à votre contrat d'essai de Version préliminaire de Disponibilité Générale ("Pre-GA") uniquement. Ce document ne constitue en aucun cas un engagement à fournir des composants, du code ou des fonctionnalités et ne doit pas être retenu comme base d'une quelconque décision d'achat. Le développement, la commercialisation et la mise à disposition des fonctions ou fonctionnalités décrites restent à la seule discrétion d'Oracle.

Ce document contient des informations qui sont la propriété exclusive d'Oracle, qu'il s'agisse de la version électronique ou imprimée. Votre accès à ce contenu confidentiel et son utilisation sont soumis aux termes de vos contrats, Contrat-Cadre Oracle (OMA), Contrat de Licence et de Services Oracle (OLSA), Contrat Réseau Partenaires Oracle (OPN), contrat de distribution Oracle ou de tout autre contrat de licence en vigueur que vous avez signé et que vous vous engagez à respecter. Ce document et son contenu ne peuvent en aucun cas être communiqués, copiés, reproduits ou distribués à une personne extérieure à Oracle sans le consentement écrit d'Oracle. Ce document ne fait pas partie de votre contrat de licence. Par ailleurs, il ne peut être intégré à aucun accord contractuel avec Oracle ou ses filiales ou ses affiliés.

Accessibilité de la documentation

Pour plus d'informations sur l'engagement d'Oracle pour l'accessibilité de la documentation, visitez le site Web Oracle Accessibility Program, à l'adresse : <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Accès aux services de support Oracle

Les clients Oracle qui ont souscrit un contrat de support ont accès au support électronique via My Oracle Support. Pour plus d'informations, visitez le site <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> ou le site <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> si vous êtes malentendant.

Contents

Using This Documentation	9
1 About Managing Remote Systems	11
What Is the FTP Server?	11
What Is a Remote System?	11
About FTP Servers	11
ProFTPD Components	12
ProFTPD Commands	12
ProFTPD Files	13
ProFTPD User	13
2 Administering the FTP Server	15
Task Map for Administering the FTP Server	15
Administering the FTP Server	15
▼ How to Start an FTP Server Using SMF	16
▼ How to Shut Down the FTP Server Using SMF	16
▼ How to Shut Down the FTP Connection	16
▼ How to Change the ProFTPD Configuration	17
3 Accessing Remote Systems	19
Task Map for Accessing Remote Systems	19
Accessing a Remote System by Using Secure Shell	20
▼ How to Access a Remote System by Using Secure Shell	20
Logging In to a Remote System to Copy a File (sftp)	21
Essential sftp Commands	21
▼ How to Open and Close an sftp Connection to a Remote System	22
▼ How to Copy Files From a Remote System (sftp)	23
▼ How to Copy Files to a Remote System (sftp)	24

Remote Copying With the scp Command	25
Security Considerations for Copy Operations	25
Specifying the Source and Target for Copy Operations	26
▼ How to Copy a File Between Two Systems (scp)	26
Index	29

Using This Documentation

- **Overview** – Describes how to administer and use the FTP service to transfer files.
- **Audience** – System administrators.
- **Required knowledge** – Basic and some advanced network administration skills.

Product Documentation Library

Documentation and resources for this product and related products are available at <http://www.oracle.com/pls/topic/lookup?ctx=E37838-01>.

Feedback

Provide feedback about this documentation at <http://www.oracle.com/goto/docfeedback>.

◆◆◆ CHAPTER 1

About Managing Remote Systems

This chapter includes information about working with remote files.

- “What Is the FTP Server?” on page 11
- “What Is a Remote System?” on page 11
- “About FTP Servers” on page 11
- “ProFTPD Components” on page 12

What Is the FTP Server?

The Oracle Solaris release includes ProFTPD. The software implements the server side of the FTP protocol, which is widely used for distribution of bulk data over the Internet. For more information about the ProFPTD project, see <http://www.proftpd.org>.

What Is a Remote System?

For the purpose of this chapter, a *remote system* is a workstation or server that is connected to the local system with any type of physical network and configured for TCP/IP communication.

On systems running an Oracle Solaris release, TCP/IP configuration is established automatically during startup. For more information, see [Administering TCP/IP Networks, IPMP, and IP Tunnels in Oracle Solaris 11.4](#).

About FTP Servers

The old FTP server based on the wu-ftp distribution has been replaced by the proftpd server. The migration of configuration information from the old service to the new is described in `/usr/share/doc/proftpd/proftpd_migration.txt`.

The Oracle Solaris version of ProFTPD runs in stand-alone mode by default.

ProFTPD Components

The following section provides information about the commands, files, and other important components of the ProFTPD service. You can find additional documentation for the ProFTPD service in the `/usr/share/doc/proftpd` directory on a system running the Oracle Solaris 11.4 release.

ProFTPD Commands

The following table describes the commands and daemons that are associated with the ProFTPD service.

TABLE 1 ProFTPD Commands

File Name	Function
<code>/usr/bin/ftp</code>	Provides the user interface to the ProFTPD service. See the ftp(1) man page for more information.
<code>/usr/bin/ftpcount</code>	Shows the current number of connections per server, as well as per virtual host or anonymous configuration. See the ftpcount(1) man page for more information.
<code>/usr/bin/ftpdctl</code>	Controls the <code>proftpd</code> service daemon. See the ftpdctl(8) man page for more information.
<code>/usr/bin/ftptop</code>	Displays the current status of FTP sessions in a continuously updating format. See the ftptop(1) man page for more information.
<code>/usr/bin/ftpwho</code>	Shows process information for all active <code>proftpd</code> connections and a count of all connected users to each server. See the ftpwho(1) man page for more information.
<code>/usr/sbin/ftprestart</code>	Restarts FTP connections by using the <code>ftpsht -R</code> command. See the ftpsht(8) man page for more information.
<code>/usr/sbin/ftpscrub</code>	Removes processes that are no longer live from the scoreboard file on demand. See the ftpscrub(8) man page and http://www.proftpd.org/docs/howto/Scoreboard.html for more information.
<code>/usr/sbin/ftpsht</code>	Shuts down FTP connections at a given time. See the ftpsht(8) man page for more information.
<code>/usr/lib/inet/proftpd</code>	Provides FTP services. See the proftpd(8) man page for more information.

ProFTPD Files

The following table lists many of the files associated with the ProFTPD service and their functions.

TABLE 2 ProFTPD Files

File Name	Function
<code>~/.ftpaccess</code>	Provides an additional control mechanism for each virtual host. The file should be placed in the home directory for the virtual host. See http://www.castaglia.org/proftpd/doc/devel-guide/internals/ftpaccess.html for more information.
<code>/etc/proftpd.conf</code>	Includes most of the configuration parameters that need to be defined in order for the ProFTPD service to function.
<code>/etc/shutmsg</code>	Includes information used by the <code>ftpsht</code> command.
<code>/etc/ftpd/ftpusers</code>	Lists the users to be disallowed FTP login privileges. Provided for backward compatibility with the <code>wu-ftp</code> service.
<code>/var/log/xferlog</code>	Lists log information for ProFTPD.
<code>/var/run/proftpd.scoreboard</code>	Includes tracking information for each current session, which is used by commands like <code>ftpcount</code> , <code>ftptop</code> , and <code>ftpwho</code> . See http://www.proftpd.org/docs/howto/Scoreboard.html for more information.

ProFTPD User

A user and a group named `ftp` are created by the ProFTPD installation process. The ProFTPD server runs under these credentials.

◆◆◆ CHAPTER 2

Administering the FTP Server

This chapter includes tasks to set up and administer an FTP server.

- [“Task Map for Administering the FTP Server” on page 15](#)
- [“Administering the FTP Server” on page 15](#)

Task Map for Administering the FTP Server

The following table describes the procedures that are needed to use the FTP server.

TABLE 3 Administering the FTP Server (Task Map)

Task	Description	For Instructions
Start the FTP server.	Do after configuring the <code>proftpd.conf</code> file.	“How to Start an FTP Server Using SMF” on page 16
Stop the FTP server.	Do before configuring the <code>proftpd.conf</code> file.	“How to Shut Down the FTP Server Using SMF” on page 16
Shut down the FTP server connections.	Runs the <code>ftpsht</code> to shut down the FTP connections during file system maintenance or other events that do not require that the service be stopped but access to the files needs to be denied.	“How to Shut Down the FTP Connection” on page 16
Reconfigure the FTP server.	Do when configuring the <code>proftpd.conf</code> file.	“How to Change the ProFTPD Configuration” on page 17

Administering the FTP Server

The following procedures show how to start and stop the FTP server, how to disable the FTP connection, and how to make changes to the ProFTPD configuration file.

▼ How to Start an FTP Server Using SMF

1. **Become an administrator.**

For more information, see [“Using Your Assigned Administrative Rights” in *Securing Users and Processes in Oracle Solaris 11.4*](#).

2. **Start the FTP server.**

```
# svcadm enable network/ftp
```

▼ How to Shut Down the FTP Server Using SMF

1. **Become an administrator.**

For more information, see [“Using Your Assigned Administrative Rights” in *Securing Users and Processes in Oracle Solaris 11.4*](#).

2. **Stop the FTP server.**

```
# svcadm disable network/ftp
```

▼ How to Shut Down the FTP Connection

The `ftpshut` command closes down the FTP server at a particular time. Use this procedure if you want to stop serving FTP only, but not stop the daemon so that it can report when the service is not available to clients. The `ftpshut` command will block connections and stop the current connection, but not shutdown the server daemon itself.

When you run `ftpshut`, a file is generated from command-line options that specify when shutdown occurs, the point at which new connections are refused, and when existing connections are dropped. Users are notified of a server shutdown based on this information. The location of the file that is created by `ftpshut` is `/etc/shutmsg`.

1. **Become an administrator.**

For more information, see [“Using Your Assigned Administrative Rights” in *Securing Users and Processes in Oracle Solaris 11.4*](#).

2. **Run the `ftpshut` command.**

```
# ftpshut [-l min] [-d min] time [warning-message...]
```


ftpshut	Command that provides a procedure for notifying users that the FTP server is shutting down.
-l	Flag that is used to adjust the time that new connections to the FTP server are denied
-d	Flag that is used to adjust the time that existing connections to the FTP server are disconnected
time	Shutdown time that is specified by the word <i>now</i> for immediate shutdown, or in one of two formats (<i>+ number</i> or <i>HHMM</i>) for a future shutdown
[warning-message...]	Shutdown notification message; see the ftpshut(8) man page for more information

3. Restore access to the files.

Use the `ftprestart` command to restart the connections to the FTP server. For further information, see `ftpshut(8)` and `ftprestart(8)`.

▼ How to Change the ProFTPD Configuration

Most configuration variations are made by making changes to the `/etc/proftpd.conf` file. Use the following steps when making changes to this file.

1. Become an administrator.

For more information, see [“Using Your Assigned Administrative Rights” in *Securing Users and Processes in Oracle Solaris 11.4*](#).

2. Make changes to the configuration file.

See the examples below for suggestions about what information to add to the configuration file.

3. Restart the FTP server.

```
# svcadm restart network/ftp
```

Example 1 ProFTPD Configuration File Changes for a Virtual Host

For a virtual host that is using a fixed IP address, use the following directive. You may add multiple IP addresses separated by spaces if needed.

```
<VirtualHost 192.0.2.0>
  ServerName "My virtual FTP server"
</VirtualHost>
```

Example 2 ProFTPD Configuration File Changes for Anonymous Access

To provide anonymous ftp access to your site, use these directives:

```
# Deny login access
<Limit LOGIN>
  DenyAll
</Limit>

<Anonymous ~ftp>

# Allow anonymous logins
<Limit LOGIN>
  AllowAll
</Limit> ....
</Anonymous>
```

◆◆◆ CHAPTER 3

Accessing Remote Systems

This chapter describes all the tasks that are required to log in to remote systems and work with their files. This is a list of the topics in this chapter.

- [“Task Map for Accessing Remote Systems” on page 19](#)
- [“Accessing a Remote System by Using Secure Shell” on page 20](#)
- [“Logging In to a Remote System to Copy a File \(sftp\)” on page 21](#)
- [“Remote Copying With the scp Command” on page 25](#)

Task Map for Accessing Remote Systems

This chapter provides tasks that are described in the following table. You can use these tasks to log in and copy files from remote systems.

TABLE 4 Accessing Remote Systems (Task Map)

Task	Description	For Instructions
Working on a remote system by using secure shell.	Uses the <code>ssh</code> command to access a remote system.	“How to Access a Remote System by Using Secure Shell” on page 20
Log in to a remote system (sftp) to access files.	Uses the <code>sftp</code> command to send and receive files on a remote system.	“How to Open and Close an sftp Connection to a Remote System” on page 22 “How to Copy Files From a Remote System (sftp)” on page 23 “How to Copy Files to a Remote System (sftp)” on page 24
Copy remote files with <code>scp</code> .	Uses the <code>scp</code> command to copy files to and from a remote system.	“How to Copy a File Between Two Systems (scp)” on page 26

Accessing a Remote System by Using Secure Shell

The Secure Shell feature of Oracle Solaris provides secure access to a remote system over an unsecured network. In Secure Shell, authentication is provided by the use of passwords and public keys. All network traffic is encrypted. Secure Shell prevents an intruder from intercepting the communication.

Authentication establishes your identity. Authentication for `ssh` logins is provided by a combination of system passwords and public host keys. Authentication operations can be performed either by the remote system or by the network environment. The `/etc/ssh_known_hosts` file and the `~/.ssh/known_hosts` file contain the list of known host keys on the system or account. By default, the `ssh` command verifies the remote host's key. If there is no host key for the remote host in either file, the user is asked whether they trust the new remote host's key. If the user confirms, the remote host's key is then added to the user's `~/.ssh/known_hosts` file before the user is prompted for their password.

For more information about Secure Shell authentication, refer to [“About Secure Shell” in *Managing Secure Shell Access in Oracle Solaris 11.4*](#).

▼ How to Access a Remote System by Using Secure Shell

1. Log in to a remote system.

```
# ssh [-l login-name] hostname | login-name@hostname
```

login-name Non-default user name which can be used to log in to the remote system

hostname Name of the remote system

If the system's host key is verified, the user is prompted for the password. If the password is typed incorrectly, the user is prompted for the password again.

If the login to the system is successful, information about the user's last remote login to the system is displayed. The information displayed might include the version of the operating system running on the remote system, latest failed login attempts, and a notification about new email waiting for the user in the user's home directory.

2. Log out of a remote system.

Use one of the following commands to log out of the remote system:

- `exit`

- `logout`
- `Control-D`

Example 3 Working on a Remote System by Using `ssh`

The following example shows the output of a remote login to `host1`. The system's host key has not been identified in either the `/etc/ssh_known_hosts` file or the `~/.ssh/known_hosts` file. The user has typed an incorrect password at the first attempt.

```
# ssh -l amy host1
The authenticity of host 'host1 (10:120:100:12)' can't be established.
RSA key fingerprint is 06:55:4d:4e:d2:4a:e6:d9:8a:c4:13:15:18:9a:ef:dd.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added 'host1' (RSA) to the list of known hosts.
Password:
Password:
Warning: 1 failed authentication attempt at Wed Jun 27 12:47 2012 since
last successful authentication.

Last login: Wed Jun 27 12:19:04 2012 from host2.example
Oracle Corporation      SunOS 5.11      11.1      June 2012
# exit
```

Logging In to a Remote System to Copy a File (sftp)

The `sftp` command is an interactive file transfer program with a user interface similar to `ftp`. However, `sftp` uses the SSH File Transfer Protocol to create a secure connection to the server. The `sftp` command does not include all options available with the `ftp` command.

Essential `sftp` Commands

The following list describes the essential `sftp` commands.

<code>sftp remote-system</code>	Establishes an <code>sftp</code> connection to a remote system. For instructions, see “How to Open and Close an <code>sftp</code> Connection to a Remote System” on page 22.
<code>sftp remote-system:file</code>	Copies the named <i>file</i> from <i>remote-system</i> .

<code>bye</code>	Quits the <code>sftp</code> session.
<code>help</code>	Lists all <code>sftp</code> commands.
<code>ls</code>	Lists the contents of the remote working directory.
<code>lls</code>	Lists the contents of the local working directory.
<code>pwd</code>	Displays the name of the remote working directory.
<code>cd</code>	Changes the remote working directory.
<code>lcd</code>	Changes the local working directory.
<code>mkdir</code>	Creates a directory on the remote system.
<code>rmdir</code>	Deletes a directory on the remote system.
<code>get</code>	Copies a file from the remote working directory to the local working directory.
<code>put</code>	Copies a file from the local working directory to the remote working directory.
<code>delete</code>	Deletes a file from the remote working directory.

For more information, see the [sftp\(1\)](#) man page.

▼ How to Open and Close an `sftp` Connection to a Remote System

1. **Open a connection to a remote system by using the `sftp` command.**

```
$ sftp remote-system
```

If the connection succeeds, a confirmation message and prompt are displayed.

2. **If prompted, type your password.**

```
Password: password
```

If the `sftp` interface accepts your password, it displays a confirmation message and the `(sftp>)` prompt.

You can now use any of the commands that are supplied by the sftp interface, including help. The principal commands are summarized in [“Essential sftp Commands” on page 21](#).

3. Close the sftp connection.

```
sftp> bye
```

Example 4 Opening an sftp Connection to a Remote System

This sftp session was established to connect to the remote system host1:

```
$ sftp host1
Connecting to host1.
Password: password
sftp>
```

▼ How to Copy Files From a Remote System (sftp)

1. Establish an sftp connection.

See [“How to Open and Close an sftp Connection to a Remote System” on page 22](#).

2. (Optional) Change to a directory on the local system where you want the files copied to.

```
sftp> lcd target-directory
```

3. Change to the source directory.

```
sftp> cd source-directory
```

4. Ensure that you have read permission for the source files.

```
sftp> ls -l
```

5. To copy a file, use the get command.

Metacharacters may be used with the get command.

```
sftp> get filename
```

6. Close the sftp connection.

```
sftp> bye
```

Example 5 Copying a File From a Remote System (sftp)

In this example, the user opens an sftp connection to the system host1, and uses the get command to copy a single file from the /tmp directory.

```
$ sftp host1
Connecting to host1...
Password: xxx
sftp> lcd /tmp
sftp> cd /tmp
sftp> ls
filea
files
ps_data
sftp> get filea
/tmp/filea          100% 494    0.5KB/s   00:00
sftp> bye
```

▼ How to Copy Files to a Remote System (sftp)

1. Change to the source directory on the local system.

The directory from which you type the sftp command is the local working directory and thus the source directory for this operation.

2. Establish an sftp connection.

See [“How to Open and Close an sftp Connection to a Remote System”](#) on page 22.

3. You can change to the target directory.

```
sftp> cd target-directory
```

4. Ensure that you have write permission in the target directory.

```
sftp> ls -l target-directory
```

5. To copy a single file, use the put command.

Metacharacters may be used with the get command.

```
sftp> put filename
```


6. Close the sftp connection.

```
sftp> bye
```

Example 6 Copying a File to a Remote System (sftp)

In this example, the user opens an sftp connection to the system host1, and uses the put command to copy a file from their system to the /tmp directory on system host1.

```
$ cd /tmp
$ sftp host1
Password: xxx
sftp> cd /tmp
sftp> put filef
uploading filef to /tmp/filef
filef                               100% 325      0.3KB/s   00:00
sftp> ls
filea
filef
files
sftp> bye
```

Remote Copying With the scp Command

The scp command copies files or directories between a local and a remote system or between two remote systems. You can use this command from a remote system (after logging in with the ssh command) or from the local system. The scp command uses ssh for data transfer. Thus, the scp command uses the same authentication and provides the same security as the ssh command.

With scp, you can perform the following remote copy operations:

- Copy a file or directory from your local system to a remote system
- Copy a file or directory from a remote system to your local system
- Copy a file or directory between remote systems from your local system

Security Considerations for Copy Operations

To copy files or directories between systems, you must have permission to log in and copy files.

The `scp` command, as a component of the `ssh` command, requires that you have either a user account or host key access to the target system. For more information, see [“About Secure Shell” in *Managing Secure Shell Access in Oracle Solaris 11.4*](#).



Caution - Both the `cp` and `scp` commands can overwrite files without warning. Ensure that file names are correct before executing the command.

Specifying the Source and Target for Copy Operations

With the `scp` command, you can specify the source (the file or directory to be copied) and the target (the location in which to copy the file or directory). You can shorten the path strings by using the tilde character (`~`) and the shell wildcard characters (`*`, `?`, and so forth).

The tilde character (`~`) is expanded by all shell programs to be the current user's home directory. The current user is the user under which the shell is executing. If the home directory for the user `jack` is `/export/home/jack`, then for the user `jack`, `~/myfile.txt` expands to `/export/home/jack/myfile.txt`.

This expansion also works for remote paths. If the user `jack` wants to copy a file from his home directory, then these three path descriptions are equivalent:

- `host3:/export/home/jack/myfile.txt`
- `host3:~/myfile.txt`
- `host3:myfile.txt`

This expansion is also useful when referring to another user's remote home directory. In this case, you would include the user's name after the tilde character. For the user `jack`, `host3:~jill/myfile.txt` is equivalent to `host3:/export/home/jill/myfile.txt`, but it is shorter to type.

▼ How to Copy a File Between Two Systems (scp)

1. Ensure that you have permission to copy files on the target system.

The `scp` command requires authentication. Depending upon the method of authentication used, you must have either an account on the target system, or an authorized public key on the target system. You should at least have read permission on the source system and write permission on the target system.



Caution - If you do not have an account on the target system, or if the target system is not configured to allow public keys, you will receive an authentication error. For example:

```
$ scp host3:/var/tmp/testdir/letter.txt .
Permission denied (gssapi-keyex,gssapi-with-mic,publickey,keyboard-interactive)
```

Ensure that you have either a user account or public key access configured on the target system for authentication. See [“About Secure Shell” in *Managing Secure Shell Access in Oracle Solaris 11.4*](#).

2. Determine the location of the source and target.

If you don't know the path of the source or target, you can first log in to the remote system with the ssh command, as described in [“Accessing a Remote System by Using Secure Shell” on page 20](#). Then, navigate through the remote system until you find the location. You can then perform the next step without logging out of the remote system.

3. Copy the file or directory.

```
$ scp [-r] [[user1@]hostname1:]file1 ... [[user2@]hostname2:]file2
```

-r	Use to recursively copy entire directories.
user1, user2	Login account to use on the remote host.
hostname1, hostname2	The names of the remote host from or to which the file is to be copied.
file1	The file name or directory name to be copied. Several source file names may be included on one command line.
file2	The destination file name or directory name.

Example 7 Using the scp Command to Copy a Remote File to a Local System

In this example, scp is used to copy the file `letter.doc` from the `/home/jones` directory of the remote system `host1` to the working directory on the local system.

```
$ scp host1:/home/jones/letter.doc .
The authenticity of host 'host1 (192.0.2.0)' can't be established.
RSA key fingerprint is b4:88:7b:cf:f5:23:d3:ad:0b:14:22:31:74:7b:6c:74.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '192.0.2.0' (RSA) to the list of known hosts.
Password:
```

```
letter.txt          100% |*****|      23      00:00
$
```

In this example, this is the first time the system `host1` is accessed, hence, the RSA key fingerprint message.

Here, the "." symbol at the end of the command line refers to the current working directory on the local system.

Example 8 Using the `scp` Command to Copy a Local File to a Remote System

In this example, `scp` is used to copy the file `notice.doc` from the home directory (`/home/smith`) of the local system `earth` to the `/home/jones` directory of the remote system, `host1`.

```
$ scp notice.doc host1:/home/jones
Password:
notice.doc          100% |*****|       0      00:00
```

Because no remote file name is provided, the file `notice.doc` is copied into the `/home/jones` directory with the same name.

In the following example, the `scp` operation from the previous example is repeated, but `scp` is executed from a different working directory on the local system (`/tmp`). Note the use of the "~" symbol to refer to the current user's home directory:

```
$ scp ~/notice.doc host1:/home/jones
Password:
notice.doc          100% |*****|       0      00:00
```

Index

Numbers and Symbols

~ (tilde)

abbreviated path names, 26

A

authentication

remote logins

using sftp command, 22

C

copying files (remote)

using scp command, 25

using sftp command, 22

E

/etc/ftpd/ftpusers file

description, 13

/etc/proftpd.conf file

description, 13

/etc/shutmsg file

description, 13

F

~/ .ftpaccess file

description, 13

files and file systems

abbreviated path names, 26

ftp command

description, 12

ftpcount command

description, 12

ftpdctl command

description, 12

ftprestart command

description, 12

ftpscrub command

description, 12

ftpshut command

description, 12

ftptop command

description, 12

ftpusers file

description, 13

ftpwho command

description, 12

G

get command (sftp)

example, 24

L

logging in

remote logins

opening sftp connection, 22, 23

sftp command, 22

O

opening remote system connections, 22, 23

P

- passwords
 - authentication for remote logins
 - sftp command, 22
- path names
 - scp command
 - absolute or abbreviated, 26
 - tilde (~) in, 26
- permissions
 - copying requirements, 26
- proftpd daemon
 - description, 12
- proftpd.conf file
 - description, 13
- proftpd.scoreboard file
 - description, 13
- put command (sftp)
 - example, 25

R

- remote file copying
 - using scp command, 25
 - using sftp command, 22
- remote logins
 - opening sftp connection, 22
 - sftp commands, 22
- remote systems
 - definition, 11
 - remote file copying
 - using scp command, 25
 - using sftp command, 22

S

- scp command, 25
 - copying between local and remote systems, 26
 - copying directories, 27
 - description, 25, 25
 - path names
 - absolute or abbreviated, 26

- security issues, 25
- specifying source and target, 26
- security
 - copy operation issues, 25
- sftp command
 - command descriptions, 22
 - opening remote system connections, 22
 - overview, 21
- sftp sessions
 - copying files
 - from a remote system, 23
 - to a remote system, 24
 - opening remote system connections, 23
- shutmsg file
 - description, 13

T

- tilde (~)
 - abbreviated path names, 26

U

- /usr/bin/ftp command
 - description, 12
- /usr/bin/ftpcount command
 - description, 12
- /usr/bin/ftpdctl command
 - description, 12
- /usr/bin/ftptop command
 - description, 12
- /usr/bin/ftpwho command
 - description, 12
- /usr/lib/inet/proftpd daemon
 - description, 12
- /usr/sbin/ftprestart command
 - description, 12
- /usr/sbin/ftpscrub command
 - description, 12
- /usr/sbin/ftpsht command
 - description, 12

V

/var/log/xferlog file

description, 13

/var/run/proftpd.scoreboard file

description, 13

