

Introduction to Oracle® Solaris 11.4 Virtual Environments

ORACLE®

Part No: E61037
September 2020

Part No: E61037

Copyright © 2011, 2020, Oracle and/or its affiliates.

License Restrictions Warranty/Consequential Damages Disclaimer

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Trademark Notice

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

Third-Party Content, Products, and Services Disclaimer

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Pre-General Availability Draft Label and Publication Date

Pre-General Availability: 2020-01-15

Pre-General Availability Draft Documentation Notice

If this document is in public or private pre-General Availability status:

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

Oracle Confidential Label

ORACLE CONFIDENTIAL. For authorized use only. Do not distribute to third parties.

Revenue Recognition Notice

If this document is in private pre-General Availability status:

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your pre-General Availability trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Référence: E61037

Copyright © 2011, 2020, Oracle et/ou ses affiliés.

Restrictions de licence/Avis d'exclusion de responsabilité en cas de dommage indirect et/ou consécutif

Ce logiciel et la documentation qui l'accompagne sont protégés par les lois sur la propriété intellectuelle. Ils sont concédés sous licence et soumis à des restrictions d'utilisation et de divulgation. Sauf stipulation expresse de votre contrat de licence ou de la loi, vous ne pouvez pas copier, reproduire, traduire, diffuser, modifier, accorder de licence, transmettre, distribuer, exposer, exécuter, publier ou afficher le logiciel, même partiellement, sous quelque forme et par quelque procédé que ce soit. Par ailleurs, il est interdit de procéder à toute ingénierie inverse du logiciel, de le désassembler ou de le décompiler, excepté à des fins d'interopérabilité avec des logiciels tiers ou tel que prescrit par la loi.

Exonération de garantie

Les informations fournies dans ce document sont susceptibles de modification sans préavis. Par ailleurs, Oracle Corporation ne garantit pas qu'elles soient exemptes d'erreurs et vous invite, le cas échéant, à lui en faire part par écrit.

Avis sur la limitation des droits

Si ce logiciel, ou la documentation qui l'accompagne, est livré sous licence au Gouvernement des Etats-Unis, ou à quiconque qui aurait souscrit la licence de ce logiciel pour le compte du Gouvernement des Etats-Unis, la notice suivante s'applique :

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

Avis sur les applications dangereuses

Ce logiciel ou matériel a été développé pour un usage général dans le cadre d'applications de gestion des informations. Ce logiciel ou matériel n'est pas conçu ni n'est destiné à être utilisé dans des applications à risque, notamment dans des applications pouvant causer un risque de dommages corporels. Si vous utilisez ce logiciel ou matériel dans le cadre d'applications dangereuses, il est de votre responsabilité de prendre toutes les mesures de secours, de sauvegarde, de redondance et autres mesures nécessaires à son utilisation dans des conditions optimales de sécurité. Oracle Corporation et ses affiliés déclinent toute responsabilité quant aux dommages causés par l'utilisation de ce logiciel ou matériel pour des applications dangereuses.

Marques

Oracle et Java sont des marques déposées d'Oracle Corporation et/ou de ses affiliés. Tout autre nom mentionné peut correspondre à des marques appartenant à d'autres propriétaires qu'Oracle.

Intel et Intel Inside sont des marques ou des marques déposées d'Intel Corporation. Toutes les marques SPARC sont utilisées sous licence et sont des marques ou des marques déposées de SPARC International, Inc. AMD, Epyc, et le logo AMD sont des marques ou des marques déposées d'Advanced Micro Devices. UNIX est une marque déposée de The Open Group.

Avis d'exclusion de responsabilité concernant les services, produits et contenu tiers

Ce logiciel ou matériel et la documentation qui l'accompagne peuvent fournir des informations ou des liens donnant accès à des contenus, des produits et des services émanant de tiers. Oracle Corporation et ses affiliés déclinent toute responsabilité ou garantie expresse quant aux contenus, produits ou services émanant de tiers, sauf mention contraire stipulée dans un contrat entre vous et Oracle. En aucun cas, Oracle Corporation et ses affiliés ne sauraient être tenus pour responsables des pertes subies, des coûts occasionnés ou des dommages causés par l'accès à des contenus, produits ou services tiers, ou à leur utilisation, sauf mention contraire stipulée dans un contrat entre vous et Oracle.

Date de publication et mention de la version préliminaire de Disponibilité Générale ("Pre-GA")

Version préliminaire de Disponibilité Générale ("Pre-GA") : 15.01.2020

Avis sur la version préliminaire de Disponibilité Générale ("Pre-GA") de la documentation

Si ce document est fourni dans la Version préliminaire de Disponibilité Générale ("Pre-GA") à caractère public ou privé :

Cette documentation est fournie dans la Version préliminaire de Disponibilité Générale ("Pre-GA") et uniquement à des fins de démonstration et d'usage à titre préliminaire de la version finale. Celle-ci n'est pas toujours spécifique du matériel informatique sur lequel vous utilisez ce logiciel. Oracle Corporation et ses affiliés déclinent expressément toute responsabilité ou garantie expresse quant au contenu de cette documentation. Oracle Corporation et ses affiliés ne sauraient en aucun cas être tenus pour responsables des pertes subies, des coûts occasionnés ou des dommages causés par l'utilisation de cette documentation.

Mention sur les informations confidentielles Oracle

INFORMATIONS CONFIDENTIELLES ORACLE. Destinées uniquement à un usage autorisé. Ne pas distribuer à des tiers.

Avis sur la reconnaissance du revenu

Si ce document est fourni dans la Version préliminaire de Disponibilité Générale ("Pre-GA") à caractère privé :

Les informations contenues dans ce document sont fournies à titre informatif uniquement et doivent être prises en compte en votre qualité de membre du customer advisory board ou conformément à votre contrat d'essai de Version préliminaire de Disponibilité Générale ("Pre-GA") uniquement. Ce document ne constitue en aucun cas un engagement à fournir des composants, du code ou des fonctionnalités et ne doit pas être retenu comme base d'une quelconque décision d'achat. Le développement, la commercialisation et la mise à disposition des fonctions ou fonctionnalités décrites restent à la seule discrétion d'Oracle.

Ce document contient des informations qui sont la propriété exclusive d'Oracle, qu'il s'agisse de la version électronique ou imprimée. Votre accès à ce contenu confidentiel et son utilisation sont soumis aux termes de vos contrats, Contrat-Cadre Oracle (OMA), Contrat de Licence et de Services Oracle (OLSA), Contrat Réseau Partenaires Oracle (OPN), contrat de distribution Oracle ou de tout autre contrat de licence en vigueur que vous avez signé et que vous vous engagez à respecter. Ce document et son contenu ne peuvent en aucun cas être communiqués, copiés, reproduits ou distribués à une personne extérieure à Oracle sans le consentement écrit d'Oracle. Ce document ne fait pas partie de votre contrat de licence. Par ailleurs, il ne peut être intégré à aucun accord contractuel avec Oracle ou ses filiales ou ses affiliés.

Accessibilité de la documentation

Pour plus d'informations sur l'engagement d'Oracle pour l'accessibilité de la documentation, visitez le site Web Oracle Accessibility Program, à l'adresse : <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Accès aux services de support Oracle

Les clients Oracle qui ont souscrit un contrat de support ont accès au support électronique via My Oracle Support. Pour plus d'informations, visitez le site <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> ou le site <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> si vous êtes malentendant.

Contents

- Using This Documentation** 9

- 1 Overview of Oracle Solaris 11.4 Virtualization Environments** 11
 - Oracle Solaris 11.4 Virtualization Technologies 11
 - Virtualization Technology Models 12
 - Choosing Your Virtualization Level 13
 - Compute Virtualization 13
 - Network Virtualization 16
 - Oracle Solaris Zones Overview 17
 - Oracle VM Server for SPARC Overview 18
 - Oracle VM Server for x86 Overview 20

- 2 Combining Virtualization Technologies in Oracle Solaris 11.4** 21
 - Goals of a Combined Virtualized Environment on a SPARC T5-2 System 21
 - Implementing the Combined Virtualized Configuration 23
 - Implementation Assumptions 23
 - Configure and Install the Oracle VM Server for SPARC Software 24
 - Configure and Install Oracle Solaris Zones 25
 - Configure and Install Oracle Solaris Kernel Zones 25
 - Create Zones That Run Legacy Solaris Systems in Virtual Oracle Solaris 10 Environments 26
 - Related References 26

Using This Documentation

- **Overview** – Describes the software virtualization technologies that are available with the Oracle Solaris operating system (Oracle Solaris OS)
- **Audience** – System architects and system administrators who are responsible for designing virtualization environments and purchasing virtualization technologies
- **Required knowledge** – System architects and system administrators must have a working knowledge of UNIX systems and the Oracle Solaris OS

Product Documentation Library

Documentation and resources for this product and related products are available at https://docs.oracle.com/cd/E37838_01/.

Feedback

Provide feedback about this documentation at <http://www.oracle.com/goto/docfeedback>.

Overview of Oracle Solaris 11.4 Virtualization Environments

This chapter briefly describes virtualization concepts and provides an overview of virtualization technologies in Oracle Solaris 11.4.

This chapter covers the following topics:

- [“Oracle Solaris 11.4 Virtualization Technologies” on page 11](#)
- [“Oracle Solaris Zones Overview” on page 17](#)
- [“Oracle VM Server for SPARC Overview” on page 18](#)
- [“Oracle VM Server for x86 Overview” on page 20](#)

Oracle Solaris 11.4 Virtualization Technologies

The core purpose of virtualization is to enable a computing environment to run multiple independent systems at the same time. Virtualization simplifies data center management and increases workload density to use more of the computing capacity of servers.

Virtualization reduces costs through the sharing of hardware, infrastructure, and administration. Benefits include the following:

- Increasing the utilization of hardware
- Enabling greater flexibility in resource allocation
- Reducing data center power requirements
- Minimizing management costs
- Lowering the cost of ownership
- Providing administrative and resource boundaries between applications on a system
- Quickly provisioning virtual compute environments from templates and clones
- Providing layered security and isolation

Oracle Solaris 11.4 enables you to take advantage of several virtualization technology models to suit your data center requirements.

Virtualization Technology Models

The virtualization models are described by means of the following competing characteristics:

- The amount of execution environment isolation
- The amount of resource flexibility

The more isolation that a model provides, the less resource flexibility it provides. The more resource flexibility that a model provides, the less isolation it provides. Because these characteristics compete, they *cannot* be maximized by a single model.

You can use the Oracle Solaris 11.4 operating system with one or more of the following virtualization technologies, listed in order of increasing execution isolation and decreasing resource flexibility:

- *Operating system virtualization* provides one or more isolated execution environments in a single operating system instance. Each environment contains what appears to be a private copy of the operating system in a container. The operating system virtualization model provides near-native performance and flexibility, and has a much smaller disk, RAM, and CPU footprint than either virtual machines or physical domains. However, the operating system virtualization model provides the least amount of execution environment isolation.

Oracle Solaris 11.4 provides this virtualization model by means of the Oracle Solaris Zones feature.

- *Virtual machines* can be used to run multiple operating system instances with a single set of hardware resources. Each virtual machine that you create runs its own operating system. You can run various operating systems in this way. A software or firmware hypervisor creates the illusion that each guest operating system instance is running on its own separate system. Virtual machines provide less resource flexibility than a machine that uses operating system virtualization, but virtual machines do provide more isolation.

Oracle Solaris 11.4 provides this virtualization model by means of Oracle VM Server for SPARC, Oracle VM Server for x86, and Oracle VM VirtualBox. Note that running Oracle VM VirtualBox and Oracle Solaris Kernel Zones on the Oracle Solaris x86 system at the same time is not supported.

For information about using Oracle VM VirtualBox, see the [Oracle VM VirtualBox documentation \(https://www.virtualbox.org/wiki/Documentation\)](https://www.virtualbox.org/wiki/Documentation).

- *Hardware partitions*, also known as *physical domains*, provide physical separation between the running operating system and its separate set of resources and power. Because this model does not use a hypervisor, it provides bare-metal performance. This virtualization model provides the most isolation, but it is much less flexible with resource configuration than either the virtual machines or operating system virtualization model.

Oracle provides this type of virtualization on Oracle's SPARC M-Series servers. For more information, see the [SPARC Servers Documentation \(https://www.oracle.com/servers/technologies/enterprise-sparc-servers-resources.html\)](https://www.oracle.com/servers/technologies/enterprise-sparc-servers-resources.html).


Choosing Your Virtualization Level

The following sections describe two levels of virtualization to consider:

- **Compute virtualization** – Virtualization at the operating system and physical domain level
- **Network virtualization** – Virtualization at the networking subsystem level


Compute Virtualization

You can use one or more virtualization technologies to maximize workload density. For example, you could configure multiple zones to run within Oracle VM Server for SPARC logical domains in one or more physical domains of a SPARC M-Series system to leverage the strengths of the different virtualization technologies.



Oracle Solaris 11.4 virtualization technologies provide a different emphasis in the degree of isolation of each instance of the operating system versus flexibility. More isolation leads to less sharing of system resources.

- Physical domains on Oracle SPARC M-Series servers let you deploy different Oracle Solaris operating systems to electrically isolated domains. Each domain provides separation and isolation from the other domains on the M-Series server at the socket level, or at the board level to provide electrical isolation. Each domain can run a different version of the Oracle Solaris operating system that is supported by the hardware.
- Oracle VM VirtualBox helps you develop and test software in heterogeneous environments. Oracle VM VirtualBox enables you to run unmodified 32-bit and 64-bit operating systems as virtual machines on Intel and AMD processors directly on your existing operating system.
- Oracle VM Server for x86 enables you to deploy a server with heterogeneous operating systems, including supported versions of the Oracle Solaris operating system as guests.
- Oracle VM Server for SPARC enables you to migrate Solaris 8, Solaris 9, Oracle Solaris 10, and Oracle Solaris SPARC workloads and to deploy different Oracle Solaris environments on supported SPARC T-Series and SPARC M-Series systems.
- Oracle Solaris Kernel Zones can run many instances per host to share system resources but still provide independence of the kernel zone from the global zone and the host itself. This configuration enables you to run multiple versions of Oracle Solaris and provides enhanced security to the operating system instances and its applications.
- Oracle Solaris Zones shares the kernel among the instances to maximize the efficiency and scalability of workloads and to migrate Oracle Solaris 11 and Oracle Solaris 11.4 workloads.

FIGURE 2 Virtualization Products

Network Virtualization

The Oracle Solaris 11.4 operating system provides support for several of the following network virtualization features, some of which implement new IEEE standards:

- Using OSI stack features such as aggregations, edge virtual bridging, data center bridging, flows, tunnels, and VXLANs. See [Chapter 1, “Summary of Oracle Solaris Network Administration” in *Strategies for Network Administration in Oracle Solaris 11.4*](#).
- Using a virtual NIC as a data link layer network device to enhance management efficiency, abstraction, and the performance of networked objects between multiple zones and logical domains. See [“Configuring the Components of a Virtual Network” in *Managing Network Virtualization and Network Resources in Oracle Solaris 11.4*](#).
- Managing network devices that support the single root I/O virtualization (SR-IOV) feature. See [“Using Single Root I/O Virtualization With VNICs” in *Managing Network Virtualization and Network Resources in Oracle Solaris 11.4*](#).
- Using an elastic virtual switch as a distributed virtual switch to expand network virtualization capabilities by enabling you to manage virtual switches across multiple systems. Elastic virtual switches enable you to deploy virtual networks that span multiple hosts within either a multi-tenant cloud environment or a data center. See [Chapter 6,](#)

[“Administering Elastic Virtual Switches”](#) in *Managing Network Virtualization and Network Resources in Oracle Solaris 11.4*.

Oracle Solaris Zones Overview

The Oracle Solaris Zones feature virtualizes operating system services and provides an isolated and secure environment for running applications. A *zone* is a virtualized operating system environment that is created within a single instance of the Oracle Solaris OS.

When you create a zone, you produce an application execution environment in which processes are isolated from the rest of the system. This isolation prevents processes that are running in one zone from monitoring or affecting processes that are running in other zones. Even a process that runs with root credentials *cannot* view or affect activity in other zones. With Oracle Solaris Zones, you can maintain the one-application-per-server deployment model while simultaneously sharing hardware resources.

A zone also provides an abstract layer that separates applications from the physical attributes of the machine on which they are deployed. An example of an attribute is the physical device path.

Zones can be used on any machine that runs the Oracle Solaris 10, Oracle Solaris 11, or Oracle Solaris 11.4 operating system. The number of zones that can be effectively hosted on a single system is determined by the following:

- The size of the system
- The total resource requirements of the application software that runs in all of the zones

Oracle Solaris Zones and Oracle Solaris 10 Zones are complete runtime environments for applications. A zone provides a virtual mapping from the application to the platform resources. Zones permit application components to be isolated from one another even though the zones share a single instance of the Oracle Solaris OS. The Oracle Solaris resource management feature permits you to explicitly allocate the amount and type of resources that a workload receives.

An Oracle Solaris Kernel Zone runs a zone that has a separate kernel and operating system installation from the global zone or the host that runs the kernel zone. Because of the separate kernel and operating system installation, kernel zones are more independent than other zones and provide enhanced security of the operating system instances and its applications. System processes are handled in the kernel zone's separate process ID table and are not shared with the global zone.

For more information, see [Creating and Using Oracle Solaris Kernel Zones](#) and [Chapter 1, “Oracle Solaris Zones Introduction”](#) in *Introduction to Oracle Solaris Zones*.

A zone establishes boundaries for resource consumption, such as CPU usage. You can expand these boundaries to adapt to the changing processing requirements of the application that runs in the zone.

solaris branded zones can provide near-native performance. There is no layer of overhead required to pass virtual I/O requests to physical devices and no emulation of privileged instructions. Also, because there is only one kernel, only one copy of the kernel must be kept on disk and in RAM.

For additional isolation and security, you can configure *immutable zones*, which are zones that have a read-only root (/) file system. Immutable zones enable you to "lock down" zones, which means that system files cannot be modified, even by a privileged user in a zone.

Oracle Solaris 10 Zones enable you to run Oracle Solaris 10 applications on the Oracle Solaris 11 OS. Applications run unmodified in the secure environment that is provided by the non-global zone. Using a `solaris10` branded non-global zone enables you to use an Oracle Solaris 10 system to develop, test, and deploy applications. Workloads that run within these branded zones can take advantage of the enhancements made to the kernel and use some of the innovative technologies available only in the Oracle Solaris 11 release.

For more information about using zones, Oracle Solaris 10 Zones, and resource management, see [Administering Resource Management in Oracle Solaris 11.3](#) and [Resource Management and Oracle Solaris Zones Developer's Guide](#).

For more information about zones and resource management, see the following documents:

- [Introduction to Oracle Solaris Zones](#)
- [Creating and Using Oracle Solaris Zones](#)
- [Creating and Using Oracle Solaris Kernel Zones](#)
- [Administering Resource Management in Oracle Solaris 11.4](#)
- [Oracle Solaris Zones Configuration Resources](#)
- [Resource Management and Oracle Solaris Zones Developer's Guide](#)

Oracle VM Server for SPARC Overview

Oracle VM Server for SPARC (formerly Sun Logical Domains) is the SPARC hypervisor virtualization solution for simultaneously running multiple operating system instances on a single physical domain. A *physical domain* is the scope of resources that are managed by a single Oracle VM Server for SPARC instance. A physical domain might be a complete physical system as is the case of supported SPARC T-Series platforms. Or, it might be either the entire system or a subset of the system as is the case of supported SPARC M-Series platforms or supported Fujitsu SPARC M12 or Fujitsu M10 systems.

Using the Oracle VM Server for SPARC software on Oracle SPARC platforms, you can create up to 128 virtual servers, called *logical domains*, on a single physical domain. This kind of configuration enables you to take advantage of the massive thread scale offered by SPARC T-Series and SPARC M-Series servers and the Oracle Solaris OS. You can also use operating system-level virtualization features, such as zones, with Oracle VM Server for SPARC.

Each logical domain has its own operating system and identity within a single physical domain, and comprises a discrete logical grouping of resources, such as:

- Kernel, patches, and tuning parameters
- User accounts and administrators
- Disks
- Network interfaces, MAC addresses, and IP addresses
- PCIe slots, buses, and end-point devices
- PCIe SR-IOV physical functions and virtual functions

You can create, destroy, stop, start, reboot, and live migrate each domain independently of one another without requiring a power cycle or reboot of the server or domain. You can also reconfigure resources such as CPUs or memory on domains in this way.

You can run a variety of application software in different domains and keep them independent for performance and security purposes. Each domain is only permitted to monitor and interact with those server resources that are made available to it by the hypervisor. The Logical Domains Manager enables you to create virtual machines and assign hardware resources to them. The Logical Domains Manager runs in the *control domain*. The hypervisor partitions the server and provides subsets of server resources to each independent virtual machine. This partitioning and provisioning is the fundamental mechanism for creating logical domains.

The hypervisor software also provides logical domain channels (LDCs) that enable logical domains to communicate with each other. Oracle VM Server for SPARC uses LDCs to off-load I/O handling for guest virtual machines to Oracle Solaris *service domains*, which provide virtual network and disk device services. These service domains leverage the Oracle Solaris features for performance and availability to provide virtual I/O, and make it possible to use a small, efficient hypervisor kernel compared to monolithic designs. You can configure more than one service domain to eliminate single points of failure and to provide high availability. For information about the domain roles, see [“Roles for Domains” in Oracle VM Server for SPARC 3.3 Administration Guide](#).

The *service processor (SP)*, also known as the *system controller (SC)*, monitors and runs the physical machine, but it does not manage the logical domains. The Logical Domains Manager manages the logical domains. In addition, you can use the browser-based Oracle VM Manager or Oracle Enterprise Manager Ops Center to provision and manage virtual environments, physical server pools, and storage and network resources on x86 and SPARC platforms.

For more information about Logical Domains Manager and Oracle VM Server for SPARC, see [Oracle VM Server for SPARC \(https://docs.oracle.com/en/virtualization/oracle-vm-server-sparc/\)](https://docs.oracle.com/en/virtualization/oracle-vm-server-sparc/). For information about Oracle VM Manager, see [Oracle VM Server for x86 and Oracle VM Manager \(https://docs.oracle.com/en/virtualization/oracle-vm/index.html\)](https://docs.oracle.com/en/virtualization/oracle-vm/index.html). For information about Oracle Enterprise Manager Ops Center, see [Enterprise Manager Cloud Control \(https://www.oracle.com/enterprise-manager/technologies/\)](https://www.oracle.com/enterprise-manager/technologies/).

Oracle VM Server for x86 Overview

Oracle VM Server for x86 is the x86 virtualization solution for simultaneously running multiple operating system instances on a single machine. Oracle VM Server for x86 is based on the open source Xen project. The Oracle VM Server for x86 software supports a privileged domain (`dom0`) to manage guest domains and unprivileged guest domains (also called `domUs`) to run workloads. As with the Oracle VM Server for SPARC control domain, the `dom0` domain permits the use of a small and efficient hypervisor and enhances availability. The Oracle VM Server for x86 software supports the running of the Oracle Solaris OS in guest domains. Oracle Solaris guest domains can use operating system level virtualization features, such as zones.

Oracle VM Server for x86 uses an administration tool called Oracle VM Manager that enables you to use a browser to do the following:

- Provision and manage virtual machines
- Arrange physical servers into pools
- Apply resource management policies
- Manage network and storage resources

Oracle VM Manager can also be used with Oracle VM Server for SPARC systems. For information about using the Oracle VM Manager with Oracle VM Server for SPARC, see https://docs.oracle.com/cd/E50245_01/E50246/html/vmrns-sparc.html.

For more information about the Oracle VM Server for x86 product, see the [Oracle VM Server for x86 and Oracle VM Manager \(https://docs.oracle.com/en/virtualization/oracle-vm/index.html\)](https://docs.oracle.com/en/virtualization/oracle-vm/index.html).

Combining Virtualization Technologies in Oracle Solaris 11.4

This chapter illustrates, at a high level, the implementation of a virtual environment that consolidates existing systems with virtualized and non-virtualized elements onto a single SPARC T5-2 system. The new system configuration uses Oracle VM Server for SPARC, Oracle Solaris Zones, and Oracle Solaris Kernel Zones to run virtual instances of different versions of the Oracle Solaris OS.


Note - You could also implement this configuration on a SPARC T4, SPARC T7, SPARC T8, SPARC M5, SPARC M6, SPARC M7, or SPARC M8 system.

Goals of a Combined Virtualized Environment on a SPARC T5-2 System

This chapter describes an example consolidation of existing systems that contain some virtual elements. By implementing this consolidation, you would accomplish the following goals:

- Consolidate existing Oracle Solaris 11, Oracle Solaris 10, and Solaris 8 servers onto a single SPARC server.
- Increase hardware and software efficiency and streamline system maintenance through the exclusive use of virtual environments.
- Run applications with different SRUs or update schedules on the same server by using Oracle Solaris kernel zones.
- Maintain isolation and perform application monitoring by running each application in its own zone or guest domain.

FIGURE 3 Mapping Existing Systems Onto a Single SPARC T5-2 System



The following migrations and consolidations are performed:

- Two Oracle Solaris 11.1 systems, sol11-sys1 and sol11-sys2, run in the Oracle Solaris 11.3 guest domains ldg1 and ldg4. The guest domains ldg1 and ldg4 host applications in native Oracle Solaris zones and kernel zones.
- The Solaris 8 system sol8-sys1 runs on an Oracle Solaris 10 guest domain ldg3.
- Two Solaris 8 systems, sol8-sys2 and sol8-sys3, are migrated onto the solaris8 zones in an Oracle Solaris 10 guest domain ldg2.

The high-level tasks to perform the consolidation into virtual environments are described in the following sections.

Implementing the Combined Virtualized Configuration

This section describes the steps to implement the virtualized environment shown in [Figure 3, “Mapping Existing Systems Onto a Single SPARC T5-2 System,”](#) on page 22. A systems overview and background requirements are described in [“Implementation Assumptions”](#) on page 23.

The following tasks are required to implement the combined virtualized solution:

1. [“Configure and Install the Oracle VM Server for SPARC Software”](#) on page 24
2. [“Configure and Install Oracle Solaris Zones”](#) on page 25
3. [“Configure and Install Oracle Solaris Kernel Zones”](#) on page 25
4. [“Create Zones That Run Legacy Solaris Systems in Virtual Oracle Solaris 10 Environments”](#) on page 26

Implementation Assumptions

Review the following overview and requirements prior to implementing your virtualized environment.

- The Oracle Solaris 11.3 operating system, which includes the Oracle VM Server for SPARC software, is installed on the SPARC T5-2 host called `system`.
- The system firmware on `system` supports Oracle VM Server for SPARC and Oracle Solaris Kernel Zones.

To verify that you have the correct versions of the software and firmware installed, run the following commands:

```
pkg install entire
```

Shows whether the server runs at least the Oracle Solaris 11.3 operating system.

```
ldm -V
```

Shows whether the server runs at least the Logical Domains Manager 3.3 software and at least version 9.5.1 of the system firmware.

If your SPARC T5-2 system is not current, see the following documentation for information about installing and upgrading the Oracle Solaris OS, Oracle VM Server for SPARC software, and SPARC system firmware:

- [Automatically Installing Oracle Solaris 11.4 Systems](#)
- [Oracle VM Server for SPARC 3.6 Installation Guide](#)

Configure and Install the Oracle VM Server for SPARC Software

Use this procedure to configure and install the Oracle VM Server for SPARC software.

1. **Configure services and the Oracle VM Server for SPARC control domain.**

Set up the control domain services on the SPARC T5-2 system. See [Oracle VM Server for SPARC 3.6 Installation Guide](#).

For information about Oracle VM Server for SPARC security features, see "Oracle VM Server for SPARC Security" in [Oracle VM Server for SPARC 3.6 Administration Guide](#).

2. **Configure and install the Oracle VM Server for SPARC guest domains.**

Create and start the following guest domains:

- a. `ldg1` – Runs the Oracle Solaris 11.3 operating system. `ldg1` hosts the following zones:
 - `zone1`, a `solaris` branded zone which runs a database application
 - `zone2`, a `solaris` branded zone which runs a web server application
 - `kzone1`, a `solaris-kz` branded zone, or kernel zone, that hosts an application running a different SRU from the rest of the server
- b. `ldg2` – Runs the Oracle Solaris 10 operating system and hosts the following zones:
 - `sol8-zone2`, a `solaris8` branded zone running a legacy application
 - `sol8-zone3`, a `solaris8` branded zone running a legacy application
- c. `ldg3` – Runs the Oracle Solaris 10 operating system
- d. `ldg4` – Runs the Oracle Solaris 11.3 operating system and hosts the following zones:
 - `zone3`, a `solaris` branded zone that hosts user logins
 - `kzone2`, a `solaris-kz` branded zone that runs another application managed on a monthly, rather than quarterly cycle

See "Creating and Starting a Guest Domain" in [Oracle VM Server for SPARC 3.6 Administration Guide](#).

After the guest domains are started, you can install the appropriate version of the Oracle Solaris OS software on the `ldg1`, `ldg2`, `ldg3` and `ldg4` guest domains. See "Installing Oracle Solaris OS on a Guest Domain" in [Oracle VM Server for SPARC 3.6 Administration Guide](#).

3. **Convert the legacy Solaris 8 system `sol8-sys1` to a logical domain on a SPARC T5-2 system.**

Use the Oracle VM Server for SPARC `ldmp2v` command to convert an existing physical Solaris 8 system onto a logical domain running Oracle Solaris 10. You can convert an Solaris 8, Solaris 9, or Oracle Solaris 10 system to a virtual system that runs the Oracle Solaris 10 operating system in a logical domain on a SPARC T5-2 system. See [Oracle VM](#)

Server for SPARC Physical-to-Virtual Conversion Tool" in *Oracle VM Server for SPARC 3.3 Administration Guide*.

Configure and Install Oracle Solaris Zones

Use this procedure to configure and install Oracle Solaris Zones.

1. Configure Oracle Solaris zones in the guest domains.

Create the following zones in the specified guest domains:

- zone1 – Hosts a database in the `ldg1` guest domain
- zone2 – Hosts a web server in the `ldg1` guest domain
- zone3 – Hosts user login data in the `ldg4` guest domain

See “How to Create and Deploy a Non-Global Zone” in *Creating and Using Oracle Solaris Zones*.

2. Install the zones.

See “Installing a Non-Global Zone” in *Creating and Using Oracle Solaris Zones*.

Configure and Install Oracle Solaris Kernel Zones

Use this procedure to configure and install Oracle Solaris Kernel Zones.

1. Configure the Oracle Solaris kernel zones in the guest domains.

Create the following kernel zones:

- `kzone1` – Hosts an application requiring a different Oracle Solaris 11.3 SRU than other system components. `kzone1` is hosted in the guest domain `ldg1`.
- `kzone2` – Hosts an application requiring an independent updating cycle. `kzone2` is hosted in the guest domain `ldg4`.

See “Configuring the Oracle Solaris Kernel Zone” in *Creating and Using Oracle Solaris Kernel Zones*.

2. Install each kernel zone by using a kernel zone direct installation.

See “Directly Installing a Kernel Zone” in *Creating and Using Oracle Solaris Kernel Zones*.

Create Zones That Run Legacy Solaris Systems in Virtual Oracle Solaris 10 Environments

Use this procedure to create zones that run legacy Solaris systems in virtual Oracle Solaris 10.

1. **Configure Solaris legacy containers.**

Configure Solaris legacy containers to migrate the Solaris 8 systems `sol8-sys1` and `sol8-sys2` onto the zone `sol8-zone` hosted in an Oracle Solaris 10 guest domain. The `sol8-zone` runs the Solaris 8 environment. See [Chapter 4, “Configuring a solaris8 Zone” in *System Administration Guide: Oracle Solaris 8 Containers*](#).

2. **Install the Solaris legacy containers.**

See [Chapter 5, “Installing the solaris8 Zone” in *System Administration Guide: Oracle Solaris 8 Containers*](#).

Related References

For further information about virtualization in Oracle Solaris OS systems, see the following references:

Oracle Solaris OS Virtualization and Networking

[Configuring and Managing Network Components in Oracle Solaris 11.4](#)

[Managing Network Virtualization and Network Resources in Oracle Solaris 11.4](#)

Oracle VM Server for SPARC – [Oracle VM Server for SPARC 3.6 Documentation Library](#)

Oracle Solaris Zones

[Introduction to Oracle Solaris Zones](#)

[Creating and Using Oracle Solaris Zones](#)

[Creating and Using Oracle Solaris Kernel Zones](#)

[Administering Resource Management in Oracle Solaris 11.4](#)

[Oracle Solaris Zones Configuration Resources](#)

[Resource Management and Oracle Solaris Zones Developer’s Guide](#)

Solaris Legacy Containers

[System Administration Guide: Oracle Solaris 8 Containers](#)

[System Administration Guide: Oracle Solaris 9 Containers](#)