

Oracle® Agile Product Lifecycle Management for Process

Web Services Guide
Extensibility Pack 3.0
Part No. E37997-01

February 2013

Copyrights and Trademarks

Oracle Agile Product Lifecycle Management for Process Web Services Guide, Extensibility Pack 3.0

E37997-01

Copyright © 1995, 2013, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are “commercial computer software” or “commercial technical data” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle and Java are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

DOCUMENT CONTROL

Change Record

Date	Author	Change Reference
June-08	Oracle	Initial release
Oct-08	Oracle	Second release, part no. E13873-01
Mar-09	Oracle	Third release, part no. E14211-01
Dec-09	Oracle	Fourth release, part no. E16288-01
Nov-10	Oracle	Fifth release, part no. E18954-01
Dec-11	Oracle	Sixth release, part no. E26557-01
Dec-11	Oracle	Seventh release, part no. E26557-02
Aug-12	Oracle	Eighth release, part no. E36339-01
Sept-12	Oracle	Ninth release, part no. E37238-01
Mar-13	Oracle	Tenth release, part no. E37997-01

CONTENTS

About This Manual

Oracle Agile Product Lifecycle Management for Process Documentation	xxi
Audience	xxi
Variability of Installations	xxi
Documentation Accessibility	xxii
Accessibility of Code Examples in Documentation	xxii
Accessibility of Links to External Web Sites in Documentation	xxii
TTY Access to Oracle Support Services	xxii
Related Documents	xxii
Document Conventions	xxiv

Chapter 1 Using the Web Services Application Programming Interface

Web Services Application Programming Interface Overview	1-1
Supported Oracle Agile PLM for Process Versions	1-2
Versioning the Web Services	1-2
Supported Web Services Contracts	1-3
General Spec Services	1-3
SCRM Services	1-3
Nutrition Services	1-3
Custom Data Services	1-4
Cost Services	1-4
Bill of Materials Services	1-4
Spec Relationship Services	1-5
Specification Services	1-5
EQ Services	1-5
PQS Services	1-6
PQM Services	1-6
CSS Services	1-7
Custom Web Services	1-7
Common Response Headers	1-7

Chapter 2 Setting Up the Application Programming Interface

Pre-requisites	2-1
Registering Windows Communication Foundation	2-1
Deploying the API Code	2-2
Adding the Web Services API Files	2-2
Adding a Virtual Directory to IIS	2-2
Configuration File Changes	2-3
config\DeployedConfig.config	2-3
config\Custom\EnvironmentSettings.config	2-3
config\Custom\CustomerSettings.config	2-3
Notes	2-3
config\environmentvariables.config	2-4
Determining the Authentication Approach	2-4
Option 1—Using one single declared PLM for Process user for all the web service calls	2-4
Option 2—Specifying a PLM for Process user for each web service call	2-4
Step 1—Installing certificates for the web server	2-5
Step 2—Setting up the service credentials configuration	2-5
Step 3—Setting the wsHttpBinding configuration	2-6

Step 4—Setting the service bindings configuration. 2-6
 Verifying the Installation 2-7

Chapter 3 Using the General Spec Services Web Services

Overview of General Spec Services. 3-1
 Service Endpoint Locations. 3-1
 v24 endpoint 3-1
 v25 endpoint 3-2
 v30 endpoint 3-2
 Get Spec Summary. 3-3
 Description 3-3
 Input 3-3
 Output. 3-3
 Possible Result Codes 3-4
 Notes 3-4
 Get Spec Numbers For Criteria. 3-5
 Description 3-5
 Input 3-5
 Output. 3-6
 Possible Result Codes 3-7
 Notes 3-7
 Save Spec Cross References 3-8
 Description 3-8
 Input 3-8
 Output. 3-8
 Possible Result Codes 3-9
 Notes 3-9
 Get GSM Percent Breakdown 3-10
 Description 3-10
 Specification Types 3-10
 Input 3-10
 Output. 3-10
 Possible Result Codes 3-12
 Notes 3-12
 Get Compliance Data. 3-13
 Description 3-13
 Specification Types 3-13
 Input 3-13
 Output. 3-14
 Possible Result Codes 3-15
 Notes 3-15

Chapter 4 Using the SCRM Services Web Service

Overview of SCRM Services 4-1
 Service Endpoint Locations. 4-1
 v24 endpoint 4-1
 v25 endpoint 4-1
 v30 endpoint 4-2
 Get Company 4-2
 Description 4-2
 Input 4-2
 Output. 4-2

Possible Result Codes	4-3
Notes	4-3
Get Facility	4-4
Description	4-4
Input	4-4
Output	4-4
Possible Result Codes	4-5
Notes	4-5
Get SCRM Sourcing Approval	4-6
Description	4-6
Input	4-6
Output	4-6
Possible Result Codes	4-8
Notes	4-8

Chapter 5 Using the Nutrition Service Web Services

Overview of Nutrition Service	5-1
Service Endpoint Locations	5-1
v24 endpoint	5-1
v25 endpoint	5-2
v30 endpoint	5-2
Get Nutrient Items per 100g	5-3
Description	5-3
Input	5-3
Output	5-3
Possible Result Codes	5-4
Notes	5-4
Save Nutrient Analysis	5-5
Description	5-5
Input	5-5
Output	5-6
Possible Result Codes	5-6
Notes	5-7
Get Nutrient Analysis	5-8
Description	5-8
Input	5-8
Output	5-8
Possible Result Codes	5-9
Notes	5-9
Get Nutrient Composite	5-10
Description	5-10
Input	5-10
Output	5-10
Possible Result Codes	5-11
Notes	5-12

Chapter 6 Using the Cost Services Web Service

Overview of Cost Services	7-1
Service Endpoint Location(s)	7-1
v24 endpoint	7-1
v25 endpoint	7-1
v30 endpoint	7-1

Save DWB Spec Cost	7-2
Description	7-2
Input	7-2
Output	7-2
Possible Result Codes	7-3
Notes	7-3

Chapter 7 Using the Custom Data Services Web Services

Overview of Custom Data Services	6-2
Service endpoint location(s)	6-3
v24 endpoint	6-3
v25 endpoint	6-3
v30 endpoint	6-3
Get Custom Section Schema	6-4
Description	6-4
Input	6-4
Output	6-4
Possible Result Codes	6-4
Get Spec Custom Sections	6-5
Description	6-5
Input	6-5
Output	6-5
Possible Result Codes	6-6
Notes	6-6
Get Spec Extended Attributes	6-7
Description	6-7
Input	6-7
Output	6-7
Possible Result Codes	6-8
Notes	6-8
Get SCRM Custom Sections	6-9
Description	6-9
Company Profile	6-9
Facility Profile	6-9
Specification Related Sourcing Approval	6-10
Non-Specification Related Sourcing Approval	6-10
Input	6-10
Output	6-11
Possible Result Codes	6-11
Notes	6-12
Get SCRM Extended Attributes	6-13
Description	6-13
Company Profile	6-13
Facility Profile	6-13
Specification Related Sourcing Approval	6-13
Non-Specification Related Sourcing Approval	6-13
Input	6-13
Output	6-14
Possible Result Codes	6-14
Notes	6-14
Save Custom Lookup	6-15
Description	6-15
Input	6-15

Output	6-15
Possible Result Codes	6-15
Notes	6-16
Get Custom Sections MetaData	6-17
Description	6-17
Input	6-17
Output	6-17
Possible Result Codes	6-18
Notes	6-18
Get Extended Attributes MetaData	6-19
Description	6-19
Input	6-19
Output	6-19
Possible Result Codes	6-19
Notes	6-20
Get EQ Custom Sections	6-21
Description	6-21
Input	6-21
Output	6-21
Possible Result Codes	6-21
Notes	6-22
Get EQ Extended Attributes	6-23
Description	6-23
Input	6-23
Output	6-23
Possible Result Codes	6-23
Notes	6-24
Get Calculated Custom Section	6-25
Description	6-25
Input	6-25
Input Overrides	6-25
Output	6-27
Possible Result Codes	6-27
Notes	6-28
Get PQM Custom Sections	6-29
Description	6-29
Input	6-29
Output	6-29
Possible Result Codes	6-30
Add PQM Custom Sections	6-31
Description	6-31
Input	6-31
Output	6-31
Possible Result Codes	6-32
Notes	6-32
Delete PQM Custom Sections	6-33
Description	6-33
Input	6-33
Output	6-33
Possible Result Codes	6-33
Notes	6-34

Update PQM Custom Section	6-35
Description	6-35
Input	6-35
Output	6-35
Possible Result Codes	6-36
Notes	6-36

Chapter 8 Using the Bill of Materials Web Service

Overview of Bill of Materials	8-1
Service Endpoint Locations	8-1
v24 endpoint	8-1
v25 endpoint	8-1
v30 endpoint	8-1
Get Output BOM	8-3
Description	8-3
Input	8-3
Output	8-3
Possible Result Codes	8-6
Notes	8-7
Get Formulation BOM	8-8
Description	8-8
Input	8-8
Output	8-8
Possible Result Codes	8-10
Notes	8-10
Get Formulation Step BOM	8-11
Description	8-11
Input	8-11
Output	8-11
Possible Result Codes	8-14
Notes	8-14

Chapter 9 Using the Spec Relationship Services

Overview of Spec Relationship Services	9-1
Service Endpoint Locations	9-2
v24 endpoint	9-2
v25 endpoint	9-2
v25 endpoint	9-2
Get Formulation Relationships	9-3
Description	9-3
Input	9-3
Output	9-3
Possible Result Codes	9-4
Notes	9-4
Get Material Relationships	9-5
Description	9-5
Input	9-5
Output	9-5
Possible Result Codes	9-6
Notes	9-7
Get Menu Item Relationships	9-8
Description	9-8

Input	9-8
Output	9-8
Possible Result Codes	9-10
Notes	9-10
Get Nutrient Profile Relationships	9-11
Description	9-11
Input	9-11
Output	9-11
Possible Result Codes	9-12
Notes	9-12
Get Packaging Relationships	9-13
Description	9-13
Input	9-13
Output	9-13
Possible Result Codes	9-14
Notes	9-14
Get Printed Packaging Relationships	9-15
Description	9-15
Input	9-15
Output	9-15
Possible Result Codes	9-16
Notes	9-16
Get Product Relationships	9-17
Description	9-17
Input	9-17
Output	9-17
Possible Result Codes	9-18
Notes	9-18
Get Trade Spec Relationships	9-19
Description	9-19
Input	9-19
Output	9-19
Possible Result Codes	9-21
Notes	9-21

Chapter 10 Using the Specification Services Web Services

Overview of Specification Services	10-1
Service Endpoint Locations	10-1
v24 endpoint	10-1
v25 endpoint	10-1
v30 endpoint	10-1
Get Activity	10-2
Description	10-2
Input	10-2
Output	10-2
Possible Result Codes	10-3
Notes	10-3
Get Spec Ingredient Statements	10-4
Description	10-4
Input	10-4
Output	10-4

Possible Result Codes	10-5
Notes	10-5

Chapter 11 Using the EQ Services Web Services

Overview of EQServices	11-1
Service Endpoint Locations.....	11-1
v24 endpoint	11-1
v25 endpoint	11-1
v30 endpoint	11-2
Get EQ Compliance Items.....	11-2
Description	11-2
Input	11-2
Output.....	11-2
Possible Result Codes.....	11-3
Notes	11-3
Get EQ Summary Info.....	11-4
Description	11-4
Input	11-4
Output.....	11-4
Possible Result Codes.....	11-5
Notes	11-5
Get EQ Nutrition Info.....	11-6
Description	11-6
Input	11-6
Output.....	11-6
Possible Result Codes.....	11-6
Notes	11-7
Get EQ Breakdown Info	11-8
Description	11-8
Input	11-8
Output.....	11-8
Possible Result Codes.....	11-8
Notes	11-9
Get EQ Numbers For Criteria.....	11-10
Description	11-10
Input	11-10
Output.....	11-10
Possible Result Codes.....	11-10
Notes	11-11

Chapter 12 Using the PQS Services Web Services

Overview of PQSServices	12-1
Service Endpoint Locations.....	12-1
v24 endpoint	12-1
v25 endpoint	12-1
v30 endpoint	12-1
Save PQS Sample	12-2
Description	12-2
Input	12-2
Output.....	12-3
Possible Result Codes.....	12-3
Notes	12-5

Chapter 13 Using the PQM Services Web Services

Overview of PQMServices..... 13-2

 Service Endpoint Locations..... 13-3

 v30 endpoint..... 13-3

Get PQM Summary..... 13-4

 Description..... 13-4

 Input..... 13-4

 Output..... 13-4

 Possible Result Codes..... 13-6

 Notes..... 13-6

Create PQM Issues..... 13-7

 Description..... 13-7

 Input..... 13-7

 Output..... 13-8

 Possible Result Codes..... 13-8

 Notes..... 13-10

Update PQM Issues..... 13-11

 Description..... 13-11

 Input..... 13-11

 Output..... 13-12

 Possible Result Codes..... 13-12

 Notes..... 13-13

Create PQM Actions..... 13-14

 Description..... 13-14

 Input..... 13-14

 Output..... 13-15

 Possible Result Codes..... 13-15

 Notes..... 13-17

Update PQM Actions..... 13-18

 Description..... 13-18

 Input..... 13-18

 Output..... 13-18

 Possible Result Codes..... 13-19

 Notes..... 13-20

Create PQM Audits..... 13-21

 Description..... 13-21

 Input..... 13-21

 Output..... 13-22

 Possible Result Codes..... 13-22

 Notes..... 13-24

Update PQM Audits..... 13-25

 Description..... 13-25

 Input..... 13-25

 Output..... 13-25

 Possible Result Codes..... 13-26

 Notes..... 13-27

Get Suppliers..... 13-28

 Description..... 13-28

 Input..... 13-28

 Output..... 13-28

 Possible Result Codes..... 13-29

 Notes..... 13-29

Add Suppliers	13-30
Description	13-30
Input	13-30
Output	13-30
Possible Result Codes	13-31
Notes	13-32
Delete Suppliers	13-33
Description	13-33
Input	13-33
Output	13-33
Possible Result Codes	13-33
Notes	13-35
Get Affected Items	13-36
Description	13-36
Input	13-36
Output	13-36
Possible Result Codes	13-37
Notes	13-38
Add Affected Items	13-39
Description	13-39
Input	13-39
Output	13-42
Possible Result Codes	13-42
Notes	13-44
Delete Affected Items	13-45
Description	13-45
Input	13-45
Output	13-45
Possible Result Codes	13-45
Notes	13-46
Get PQM Item By Criteria	13-47
Description	13-47
Input	13-47
Output	13-48
Possible Result Codes	13-48
Notes	13-48
Get Related Items	13-49
Description	13-49
Input	13-49
Output	13-49
Possible Result Codes	13-50
Notes	13-50
Add Related Items	13-51
Description	13-51
Input	13-51
Output	13-51
Possible Result Codes	13-51
Notes	13-52
Delete Related Items	13-53
Description	13-53
Input	13-53
Output	13-53

Possible Result Codes	13-53
Notes	13-54
Get Supporting Document IDs	13-55
Description	13-55
Input	13-55
Output	13-55
Possible Result Codes	13-56
Notes	13-56
Get URL Supporting Document	13-58
Description	13-58
Input	13-58
Output	13-58
Possible Result Codes	13-59
Notes	13-59
Add URL Supporting Documents	13-60
Description	13-60
Input	13-60
Output	13-60
Possible Result Codes	13-61
Notes	13-61
Delete URL Supporting Documents	13-62
Description	13-62
Input	13-62
Output	13-62
Possible Result Codes	13-62
Notes	13-63
Add Supporting Document Attachment	13-64
Description	13-64
Input	13-64
Output	13-64
Possible Result Codes	13-65
Notes	13-65
Delete Supporting Document Attachment	13-66
Description	13-66
Input	13-66
Output	13-66
Possible Result Codes	13-66
Notes	13-67
Get Rich Text Supporting Document	13-68
Description	13-68
Input	13-68
Output	13-68
Possible Result Codes	13-69
Notes	13-69
Add Rich Text Supporting Document	13-70
Description	13-70
Input	13-70
Output	13-70
Possible Result Codes	13-70
Notes	13-71

Delete Rich Text Supporting Documents	13-72
Description	13-72
Input	13-72
Output	13-72
Possible Result Codes	13-72
Notes	13-73
Get DRL Document	13-74
Description	13-74
Input	13-74
Output	13-74
Possible Result Codes	13-75
Notes	13-75
Add DRL Document	13-76
Description	13-76
Input	13-76
Output	13-76
Possible Result Codes	13-77
Notes	13-77
Delete DRL Documents	13-78
Input	13-78
Output	13-78
Possible Result Codes	13-79
Notes	13-79
Add DRL Catalog	13-80
Description	13-80
Input	13-80
Output	13-80
Possible Result Codes	13-80
Notes	13-81
Delete DRL Catalogs	13-82
Description	13-82
Input	13-82
Output	13-82
Possible Result Codes	13-83
Notes	13-83
Get Attachment	13-84
Description	13-84
Input	13-84
Output	13-84
Possible Result Codes	13-85
Add Attachment Procedure	13-86
Description	13-86
Input	13-86
Output	13-86
Possible Result Codes	13-86
Notes	13-87
Delete Attachment Procedures	13-88
Description	13-88
Input	13-88
Output	13-88
Possible Result Codes	13-88
Notes	13-89

Add Cross References	13-90
Description	13-90
Input	13-90
Output	13-90
Possible Result Codes	13-90
Notes	13-91
Delete Cross References	13-92
Description	13-92
Input	13-92
Output	13-92
Possible Result Codes	13-92
Notes	13-94
Update Cross References	13-95
Description	13-95
Input	13-95
Output	13-95
Possible Result Codes	13-96
Notes	13-97

Chapter 14 Using the CSS Services Web Service

Overview of CSS Services	14-1
Service Endpoint Locations	14-1
v25 endpoint	14-1
v30 endpoint	14-1
SendResponse	14-2
Description	14-2
Input	14-2
tHeader	14-2
tMessage	14-2

Appendix A Special Conditions, Status Codes, and Core Objects

Special Conditions	A-1
Condition A - No Issue Specified in Input Criteria	A-1
Condition B - Business Unit Visibility	A-1
Condition C - Allow Only Approved Spec	A-1
Condition D - Specification Types	A-2
Condition E - Specification Identifier Input Formats	A-2
Condition F - Max Records Retrieved	A-2
Condition G - Max Records Allowed For Save	A-2
Condition H - InFoodsCode	A-3
Condition I - SCRM Entity Input	A-4
Condition J - Allow Only Approved Entity	A-4
Condition K - Invalid Company Input Formats	A-4
Condition L - Invalid Facility Input Formats	A-4
Condition M - Invalid EQ Input Formats	A-4
Condition N - Invalid Security Privileges	A-4
Condition O - Invalid Custom Sections MetaData Input Formats	A-5
Condition P - Invalid Extended Attributes MetaData Input Formats	A-5
Condition Q - PQM Item Identifier Formats	A-5
Status Codes	A-6
Core Objects	A-7
tSpecIdentifierCriterion	A-10
Subtypes	A-10
tSpecificationNumber	A-10
Supertype	A-10

tCrossReference	A-10
Supertype	A-10
Schema Component Representation	A-11
tExtCrossReference	A-11
Supertype	A-11
tSpecificationIdentifier	A-11
tQueryOptions	A-12
DateRange	A-12
Subtypes	A-12
Schema Component Representation	A-12
ModifiedBetweenDateRange	A-13
Supertype	A-13
CreatedBetweenDateRange	A-13
Supertype	A-13
tSpecificationSummaryWrapper	A-13
tSpecificationSummary	A-14
tCostItem	A-14
tSCRMEntity	A-14
tSCRMCompany	A-15
tSCRMFacility	A-15
tSCRMEntityIdentifier	A-15
Subtypes	A-15
tSCRMEntityNumber	A-15
tSCRMEntityCrossRef	A-16
Supertype	A-16
Schema Component Representation	A-16
tExtSCRMEntityCrossRef	A-16
Supertype	A-16
tSCRMEntityIdentifier	A-16
Subtypes	A-17
tSCRMEntityNumber	A-17
Supertype	A-17
tSCRMEntityCrossRef	A-17
Supertype	A-17
Schema Component Representation	A-17
tFacility	A-18
tFacilityInfo	A-18
tCompany	A-18
tCompanyInfo	A-19
tSCRMAddress	A-19
tSCRMAdministrativeInfo	A-20
tSCRMBusinessUnits	A-20
tSpecRelatedSourcingApprovalInfo	A-20
tSCRMSourcingApprovalInfo	A-20
tCustomLookup	A-21
tNutrientDataWrapper	A-21
tNutrientItem	A-21
tActivityInfo	A-22
tActivitySummary	A-22
tPrimaryActionItemInfo	A-22
tRelatedItemInfo	A-23
tIDName	A-23
tCustomSectionMetaDataInputCriteria	A-23
Subtypes	A-23
tCustomSectionID	A-23
Supertype	A-23
tCustomSectionNumber	A-24
Supertype	A-24
tCustomSection	A-24
tCustomSectionRow	A-24
tCustomSectionColumn	A-24

tExtendedAttribute	A-25
tSpecIngredientStatementInfo	A-25
tEQNumber	A-25
tEQExtendedAttribute	A-25
tExtension	A-26
Extended Attribute Types Schema	A-26
tEQComplianceInfo	A-26
tEQIdentifier	A-27
tComplianceItem	A-27
tComplianceItemContained	A-27
tEQSummary	A-27
tSupplierContactInfo	A-28
tCompanyContactInfo	A-28
tEQIdentifier	A-28
tNutrientInfo	A-28
tEQCriteriaItem	A-29
tLegacySystem	A-29
tPQMItemIdentifier	A-29
tExtCrossReference	A-30
Supertype	A-30
tPQMItemType	A-30
tCommonLookup	A-30
tPqmCommonSummary	A-30
tPqmIssueSpecificSummary	A-31
tPqmActionSpecificSummary	A-31
tPqmAuditSpecificSummary	A-31
tPQMAssociatedProject	A-32
tBasePQMItemSearchIdentifier	A-32
tCrossReference	A-32
Supertype	A-32
tPQMItemSearchIdentifier	A-32
Supertype	A-32
tIssueDetails	A-33
tActionDetails	A-34
tAssociatedNPDProject	A-35
tAuditDetails	A-35
tPQMItemSupplierIdentifier	A-36
tPQMItemSupplier	A-37
tSourceSystemIdentifier	A-37
tPQMItemSupplierSearchIdentifier	A-37
Subtypes	A-37
tSourceSystemPQMItemSupplierIdentifier	A-37
Supertype	A-37
tSCRMEntityCrossRefPQMItemSupplierIdentifier	A-38
Supertype	A-38
tSCRMEntityNumberPQMItemSupplierIdentifier	A-38
Supertype	A-38
tPQMItemAffectedItemsResult	A-38
tPQMAffectedItem	A-38
Subtypes	A-38
tIssueAffectedItem	A-39
Supertype	A-39
tAffectedItemInput	A-40
Supertypes	A-40
tPQMAffectedItemIdentifier	A-41
Subtypes	A-41
tPQMAffectedItemGSMIdentifier	A-41
Supertype	A-41
tPQMAffectedItemSourceSystemIdentifier	A-41
Supertype	A-41

tIssueAffectedItemInput	A-42
Supertype	A-42
Subtypes	A-42
tNCRAffectedItemInput	A-42
Supertype	A-43
tPQMSearchCriteria	A-44
tSupplierSearchIdentifier	A-44
tExternalSupplierSearchIdentifier	A-45
tSCRMSupplierSearchIdentifier	A-45
tRelatedPQMItemsWrapper	A-45
tRelatedPQMItem	A-45
Subtypes	A-45
tRelatedPQMActionItem	A-46
Supertype	A-46
tRelatedPQMAuditItem	A-46
Supertype	A-46
tCommonIdentifier	A-46
Subtypes	A-46
tDRLDocumentIdentifier	A-47
Supertype	A-47
tDRLCatalogIdentifier	A-47
Supertype	A-47
tAttachmentsWrapper	A-47
tDRLCatalog	A-48
tPQMSupportingDocWrapper	A-48
tRichTextDoc	A-48
tNewRichTextDoc	A-49
tURLSource	A-49
tNewURLSource	A-49
tDRLDocument	A-50
tAttachment	A-50
Subtype	A-50
tSupportingDocAttachment	A-51
Supertype	A-51
tNewAttachment	A-51
tNewAttachmentsWrapper	A-52
tCustomSectionInstance	A-52

ABOUT THIS MANUAL

Oracle Agile Product Lifecycle Management for Process Documentation

The *Agile Product Lifecycle Management for Process Web Services Guide* explains how to use install and configure the Web Services API, and provides documentation of each available web service.

To use this document, you should have a basic familiarity with web services software development, and the Oracle Agile PLM for Process configuration files and user interface. The information presented for each web service is intended to give a business and technical view of the inputs, outputs, and possible results of the web service call. Contract details, such as detailed WSDL and XSD information is not presented here — rather, they are available from the web service metadata or from the provided WSDL and XSD files. This Preface contains these topics:

- ❑ Audience
- ❑ Variability of Installations
- ❑ Related Documents
- ❑ Document Conventions

Audience

This guide is intended for client programmers involved with integrating Oracle Agile Product Lifecycle Management for Process. Information about using Oracle Agile PLM for Process resides in application-specific user guides. Information about administering Oracle Agile PLM for Process resides in the *Oracle Agile Product Lifecycle Management for Process Administrator User Guide*.

Variability of Installations

Descriptions and illustrations of the Agile PLM for Process user interface included in this manual may not match your installation. The user interface of Agile PLM for Process applications and the features included can vary greatly depending on such variables as:

- ❑ Which applications your organization has purchased and installed
- ❑ Configuration settings that may turn features off or on
- ❑ Customization specific to your organization
- ❑ Security settings as they apply to the system and your user account

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

TTY Access to Oracle Support Services

To reach AT&T Customer Assistants, dial 711 or 1.800.855.2880. An AT&T Customer Assistant will relay information between the customer and Oracle Support Services at 1.800.223.1711. Complete instructions for using the AT&T relay services are available at <http://www.consumer.att.com/relay/tty/standard2.html>. After the AT&T Customer Assistant contacts Oracle Support Services, an Oracle Support Services engineer will handle technical issues and provide customer support according to the Oracle service request process.

Related Documents

For more information, see the following documents in the Oracle Agile Product Lifecycle Management for Process Extensibility Pack documentation set:

- ❑ *Agile Product Lifecycle Management for Process Extensibility Guide*
- ❑ *Agile Product Lifecycle Management for Process Data Administration Toolkit Guide*
- ❑ *Agile Product Lifecycle Management for Process Print Extensibility Guide*
- ❑ *Agile Product Lifecycle Management for Process Custom Section Denormalization Guide*

- ❑ *Agile Product Lifecycle Management for Process Extended Attribute Denormalization Guide*
- ❑ *Agile Product Lifecycle Management for Process Custom Report Configuration Guide*
- ❑ *Agile Product Lifecycle Management for Process Navigation Configuration Guide*
- ❑ *Agile Product Lifecycle Management for Process Extended Attribute Calculation Guide*
- ❑ *Agile Product Lifecycle Management for Process Release Notes*

Notes and other documentation are posted on Oracle Technology Network (OTN) at this location:

<http://www.oracle.com/technetwork/documentation/agile-085940.html#plmprocess>

Document Conventions

The following formatting elements appear in Oracle Agile PLM for Process documentation.

Element	Meaning
Helvetica Condensed, 9 pt. bold type	A user interface (UI) element that a procedure is instructing you to click, select, or type into. For example, buttons or text entry fields.
9 pt. monospace font	Code samples
10 pt. monospace font	File names or directory names
<i>Blue italic font</i>	The linked portion of a cross-reference. Click it to go to the referenced heading, table, or figure.
Minion Typeface, Title Case	A named UI element that a procedure is describing but not instructing you to click, select, or type into.
<hr/> Note Minion 11.5 pt, with faint blue bar over & under <hr/>	Alerts you to supplemental information.
<hr/> Caution! Minion 11.5 pt, with faint red bar over & under <hr/>	Alerts you to possible data loss, breaches of security, or other more serious problems.
<hr/> Important Minion 11.5 pt, with thick red bar over & under <hr/>	Alerts you to supplementary information that is essential to the completion of a task.

Using the Web Services Application Programming Interface

This chapter describes the Web Services Application Programming Interface that is used with Oracle Agile Product Lifecycle Management for Process. Topics in this chapter include:

- ❑ *Web Services Application Programming Interface Overview*
 - ❑ *Versioning the Web Services*
 - ❑ *Supported Web Services Contracts*
 - ❑ *Common Response Headers*
-

Web Services Application Programming Interface Overview

Oracle Agile Product Lifecycle Management (PLM) for Process allows programmatic access to your organization's data using Oracle Agile PLM for Process Web Services API.

The API consists of a set of standardized, fully supported web services to provide clients with simple, rich, and secure integration capabilities. Each service is granular in nature, focused on delivering a specific business function. Consumers of the API will be able to compose multiple services as needed to meet larger business function needs.

Each major release of the Web Services API maintains backward compatibility with the previous release, allowing previous client integrations to remain unchanged, whenever possible. Any contract changes are only made in the new versions of the web services.

The Web Services are deployed into and hosted by the Integration web application. Several configuration file changes must be made to enable the web services, which determine the authentication & authorization mechanism that should be used for web service calls, as well as some other options. Additionally, a new virtual directory must be added in IIS within the Integration web application.

For installation and configuration details, please refer to Chapter 2, [Setting Up the Application Programming Interface](#).

Supported Oracle Agile PLM for Process Versions

To use the Web Services available in this release, you must be using Oracle Agile PLM for Process version 6.1.1 or greater.

Versioning the Web Services

To allow previous client implementations of the Web Service API to remain unchanged, yet still provide for new features, the release contains separate versions of the previous services and new versions of the full feature set.

Previous versions of the web services have no data contract changes, and the service endpoints remain unchanged.

This should allow previous client implementations to continue working as is. However, clients wishing to use new capability of the web service calls must implement the v30 versions.

The primary change that clients and integrators will see is that there are now three service endpoints for any pre-existing services:

- ❑ v21—The v21 web services are now deprecated.
- ❑ v24—The v24 web services will remain unchanged and support the previous functionality. They will be deprecated in an upcoming release.
- ❑ v25—The v25 web services will remain unchanged and support the previous functionality.
- ❑ v30—The v30 web services will support any relevant pre-existing functionality along with new operations and contract changes.

Each service version has its own endpoint, and therefore its own WSDL. For example, the following endpoints exist for GeneralSpecServices:

- ❑ v24 endpoint

`http://<servername>/Integration/ProdikaContracts/Specification/Common/v24/GeneralSpecServices.svc`

- ❑ v25 endpoint

`http://<servername>/Integration/ProdikaContracts/Specification/Common/v25/GeneralSpecServices.svc`

- ❑ v30 endpoint

`http://<servername>/Integration/ProdikaContracts/Specification/Common/v30/GeneralSpecServices.svc`

Clients and integrators that are new to the Web Service API are encouraged to implement the v30 versions only.

Supported Web Services Contracts

General Spec Services

General Spec Services provides operations that act on Global Specification Management (GSM) specifications.

Operations	v24	v25	v30	Notes
GetSpecSummary	●	●	●	v25 includes an IsTemplate return value.
GetSpecNumbersForCriteria	●	●	●	v25 includes an IncludeSpecTemplates search criterion.
SaveSpecCrossReferences	●	●	●	
GetGSMPercentBreakdown	●	●	●	
GetComplianceData	●	●	●	

See Chapter 3, *Using the General Spec Services Web Services* for more information.

SCRM Services

SCRM Services provides operations that act on Supply Chain Relationship Management (SCRM) sourcing approvals, companies, and facilities.

Operations	v24	v25	v30	Notes
GetCompany	●	●	●	
GetFacility	●	●	●	
GetSCRMSourcingApproval	●	●	●	

See Chapter 4, *Using the SCRM Services Web Service* for more information.

Nutrition Services

Nutrition Services provides nutrition and Nutrition Surveillance Management (NSM) related operations.

Operations	v24	v25	v30	Notes
GetNutrientItemsPer100g	●	●	●	
SaveNutrientAnalysis	●	●	●	
GetNutrientAnalysis	●	●	●	
GetNutrientComposite	●	●	●	

See Chapter 5, *Using the Nutrition Service Web Services* for more information.

Custom Data Services

Custom Data Services provides operations related to extended attributes and custom sections.

Operations	v24	v25	v30	Notes
GetCustomSectionSchema	●	●	●	
GetSpecCustomSections	●	●	●	
GetSpecExtendedAttributes	●	●	●	
GetSCRMCustomSections	●	●	●	
GetSCRMExtendedAttributes	●	●	●	
SaveCustomLookup	●	●	●	
GetCustomSectionsMetaData	●	●	●	
GetExtendedAttributesMetaData	●	●	●	
GetEQCustomSections	●	●	●	
GetEQExtendedAttributes	●	●	●	
GetCalculatedCustomSection	●	●	●	
GetPQMCustomSections			●	
AddPQMCustomSections			●	
DeletePQMCustomSections			●	
UpdatePQMCustomSection			●	

See Chapter 6, *Using the Custom Data Services Web Services* for more information.

Cost Services

Cost Services provides formulation specification costing related capabilities.

Operations	v24	v25	v30	Notes
SaveDWBSpecCost	●	●	●	

See Chapter 7, *Using the Cost Services Web Service* for more information.

Bill of Materials Services

Bill of Materials Services provide operations related to a process specification's Bill of Materials (BOM).

Operations	v24	v25	v30	Notes
GetOutputBOM	●	●	●	
GetFormulationBOM	●	●	●	
GetFormulationStepBOM			●	

See Chapter 8, *Using the Bill of Materials Web Service* for more information.

Spec Relationship Services

Spec Relationship Services provides operations that define a specification's related specification listing.

Operations	v24	v25	v30	Notes
GetProductRelationships	●	●	●	
GetMaterialRelationships	●	●	●	
GetIngredientRelationships			●	Forv3.0 GetMaterialRelationships was renamed GetIngredientRelationships.
GetPackagingRelationships	●	●	●	
GetPrintedPackagingRelationships	●	●	●	
GetFormulationRelationships	●	●	●	
GetNutrientProfileRelationships	●	●	●	
GetTradeSpecRelationships	●	●	●	
GetMenuItemRelationships	●	●	●	

See Chapter 9, *Using the Spec Relationship Services* for more information.

Specification Services

Specification Services provides operations that act on individual specification types.

Operations	v24	v25	v30	Notes
GetActivity	●	●	●	
GetSpecIngredientStatements	●	●	●	

See Chapter 10, *Using the Specification Services Web Services* for more information.

EQ Services

EQ Services provides operations related to eQuestionnaire (eQ).

Operations	v24	v25	v30	Notes
GetEQComplianceItems	●	●	●	
GetEQSummaryInfo	●	●	●	
GetEQNutritionInfo	●	●	●	
GetEQBreakdownInfo	●	●	●	
GetEQNumbersForCriteria	●	●	●	

See Chapter 11, *Using the EQ Services Web Services* for more information.

PQS Services

PQS Services provides operations related to Product Quality Scorecard (PQS).

Operations	v24	v25	v30	Notes
SavePqsSamples	●	●	●	

See Chapter 12, *Using the PQS Services Web Services* for more information.

PQM Services

PQM Services provides operations related to Product Quality Management (PQM).

Operations	v24	v25	v30	Notes
GetPQMSummary			●	
CreatePQMIssues			●	
UpdatePQMIssues			●	
CreatePQMActions			●	
UpdatePQMActions			●	
CreatePQMAudits			●	
UpdatePQMAudits			●	
GetSuppliers			●	
AddSuppliers			●	
DeleteSuppliers			●	
GetAffectedItems			●	
AddAffectedItems			●	
DeleteAffectedItems			●	
GetPQMItemByCriteria			●	
GetRelatedItems			●	
AddRelatedItems			●	
DeleteRelatedItems			●	
GetSupportingDocumentIDs			●	
GetURLSupportingDocument			●	
AddURLSupportingDocument			●	
DeleteURLSupportingDocuments			●	
AddSupportingDocumentAttachment			●	
DeleteSupportingDocumentAttachments			●	
GetRichTextSupportingDocument			●	
AddRichTextSupportingDocument			●	
DeleteRichTextSupportingDocuments			●	
GetDRLDocument			●	
AddDRLDocument			●	
DeleteDRLDocuments			●	
AddDRLCatalog			●	

Operations	v24	v25	v30	Notes
DeleteDRLCatalogs			●	
GetAttachment			●	
AddAttachmentProcedure			●	
DeleteAttachmentProcedures			●	
AddCrossReferences			●	
DeleteCrossReferences			●	
UpdateCrossReferences			●	

See Chapter 13, *Using the PQM Services Web Services* for more information.

CSS Services

CSS Services provides operations related to Content Synchronization and Syndication (CSS).

Operations	v24	v25	v30	Notes
SendResponse		●	●	

See Chapter 14, *Using the CSS Services Web Service* for more information.

Custom Web Services

Please see the Reference Implementation for more information about custom web services.

Common Response Headers

Each web service includes a common response in the SOAP Header. This common response consists of the following:

- ❑ **Result Code**—A string value representing the overall result of the web service call (for instance, `RESULT_NO_ERRORS`, `RESULT_INVALID_INPUT`, etc.). Possible values of the result code are documented for each web service.
- ❑ **List of Messages**—List of warning or error messages that provide details for any issues that occur when calling each web service. Each message has a message code, severity, and a description. Possible message codes and descriptions are documented for each web service.

Setting Up the Application Programming Interface

This chapter describes the setup process for the Application Programming Interface. Topics in this chapter include:

- *Pre-requisites*
 - *Deploying the API Code*
 - *Configuration File Changes*
 - *Verifying the Installation*
-

Pre-requisites

Oracle Agile PLM for Process Web Services Application Programming Interface (API) requires Microsoft .NET Framework 3.5 and Windows Communication Foundation (WCF). These must be installed on the machine that will be hosting the Integration web application, which will host the web services.

Registering Windows Communication Foundation

To register Windows Communication Foundation:

- 1** Install Microsoft .NET Framework 3.5.
- 2** Register the Windows Communication Foundation.
 - a** Navigate to C:\WINDOWS\Microsoft.NET\Framework\v3.0\Windows Communication Foundation.
 - b** Run the following command to register this service and update your machine.config file: **ServiceModelReg.exe -i**
- 3** Verify .svc files are mapped in IIS.
 - a** IIS->Integration->Properties->Virtual Directory->Configuration
 - b** If .svc files are not mapped, run **ServiceModelReg.exe /s:W3SVC**

Deploying the API Code

Adding the Web Services API Files

Add the API files to an existing Oracle Agile PLM for Process environment:

To add the API files:

- 1** Extract all files from the extensibility pack 3.0 file to a temporary folder.
- 2** Switch to this temporary folder in Windows command prompt, and run the command: `FileCompressionHelper.exe -d`
- 3** From the temporary folder, copy the contents of the Integration folder within Web folder to the Prodika\web\Integration folder of your Oracle Agile PLM for Process installation.
 - a** Make sure to include the web.config file.
 - b** Overwrite existing files with the same name.

Note If deploying API on a 64-bit machine, please remove System.Web.dll and System.Web.xml from <PLM4P-install-folder>\Web\Integration\bin.

Adding a Virtual Directory to IIS

To add a new ProdikaContracts virtual directory to IIS:

- 1** In the Internet Information Services Manager, find the virtual directory for the Integration web application.
- 2** Right click and select **New>Virtual Directory**.
- 3** Enter the following values in the wizard:
 - a** Alias: 'ProdikaContracts'
 - b** Path: <PLM4P-install-folder>\Web\Integration\Contracts\Prodika
 - c** Permissions: Read
- 4** In the Internet Information Services Manager, find the new virtual directory for ProdikaContracts.
- 5** Right click and select **Properties**.
- 6** In the properties dialog, change the Execute Permissions field to 'Scripts Only' and then click **OK**.
- 7** Restart IIS.

Configuration File Changes

Update the following configuration files to enable the Web Services API:

config\DeployedConfig.config

Place the following configuration in the DeployedConfig node:

```
<ProdikaAPI>
  <ConfigInfo
    configReplace="file:%CONFIG_HOME%\environmentvariables.config"
    configExtends="file:%CONFIG_HOME%\Custom\EnvironmentSettings.config,EnvironmentSettings/ProdikaAPI/ConfigInfo" />
  </ProdikaAPI>
```

config\Custom\EnvironmentSettings.config

Note The UserID and Password settings have been changed to pull data entered in the SetupAssistant. Be sure to configure the username and password entries (Prodika.ProdikaAPI.SysUser and Prodika.ProdikaAPI.SysPassword) using the SetupAssistant tool in Agile PLM for Process 6.1.1.

Place the following configuration in the EnvironmentSettings node:

```
<ProdikaAPI>
  <ConfigInfo configChildKey="key">
    <add key="UserID" value="Prodika.ProdikaAPI.SysUser" />
    <add key="Password" value="Prodika.ProdikaAPI.SysPassword" />
    <add key="IsUseTrustedAuth"
      value="@@VAR:Prodika.ProdikaAPI.IsUseTrustedAuth@" />
    <add key="IsLoginBypassOn"
      value="@@VAR:Prodika.ProdikaAPI.IsLoginBypassOn@" />
  </ConfigInfo>
</ProdikaAPI>
```

config\Custom\CustomerSettings.config

Place the following configuration in the /CustomerSettings/Core/Prodika/Services node:

```
<ProdikaAPIConfigService refscope="Application"
  factory="Singleton:Xeno.Prodika.ProdikaAPI.Services.ProdikaAPIConfigServiceFactory,ProdikaAPILib" >
  <envvar name="MaxRecordCountGet" value="250" />
  <envvar name="MaxRecordCountSave" value="250" />
  <envvar name="ApprovedWorkflowName" value="Is Approved" />
  <envvar name="SCRMApprovedWorkflowName" value="Is Approved" />
</ProdikaAPIConfigService>
```

Notes

- *MaxRecordCountGet*—Value to limit top-level records returned by web service Get operations

- *MaxRecordCountSave*—Value to limit number of records for Save operations
- *ApprovedWorkflowName*—Value can be set to the appropriate Workflow Tag name that is used in WFA to declare a step as Approved or Official
- *SCRMAApprovedWorkflowName*—Value can be set to the appropriate Workflow Tag name that is used in WFA to declare a step in SCRМ workflow as Approved or Official

config\environmentvariables.config

Determining the Authentication Approach

The Web Services adhere to all security permission rules that are present in the core application, such as Spec read permissions, Business Unit visibility/security, and more. For instance, the GetSpecSummary web service will not return a spec that the user does not have valid Read permissions to. The permissions are evaluated against the PLM for Process user that is calling the web service. The web services API can therefore be set up for user authentication in two different ways, which has implications on the configuration required:

Option 1—Using one single declared PLM for Process user for all the web service calls

This user is specified by the `Prodika.ProdikaAPI.SysUser` value, which is set by the Setup Assistant. Each web service call authenticates to the application, and evaluates permissions, with this user account. This option is the simplest to set up, as it requires no extra configuration steps, and is typically used when systems are communicating (via web services) without regard to individual permissions.

When using one single declared PLM for Process user for *all* the web service calls, the following configuration entries would need to be added to the `environmentvariables.config` file:

```
Prodika.ProdikaAPI.IsLoginBypassOn=true  
Prodika.ProdikaAPI.IsUseTrustedAuth=true
```

Option 2—Specifying a PLM for Process user for each web service call

The user account must be supplied to each web service call by the client application, using the `ClientCredentials` of the client. You must set the `environmentvariables` configuration as follows: `IsLoginBypassOn=false`, which will ignore then `Prodika.ProdikaAPI.SysUser` value. To configure this option, you will have to install a web site certificate for IIS, and make additional configuration changes.

When specifying a PLM for Process user for each web service call, the following configuration entries would need to be added to the `environmentvariables.config` file:

```
Prodika.ProdikaAPI.IsLoginBypassOn=false
Prodika.ProdikaAPI.IsUseTrustedAuth=true
```

Additionally, the following four set up steps must be implemented for this option:

Step 1—Installing certificates for the web server

Before the web service APIs can support UsernamePasswordValidator authentication for every call, a web site certificate must be installed. This certificate is used to encrypt the messages transferred between the clients and web server. Internet Information Server (IIS), integrated wizard can be used to request and install a site certificate.

- For IIS 6.0 on Windows Server 2003 platform, please refer to the following article to see the detail about the installation:
“How To: Install Imported Certificates on a Web Server in Windows Server 2003” found at <http://support.microsoft.com/kb/816794>
- For IIS 7 on Windows Server 2008, please refer to the following article:
"Import a Server Certificate (IIS 7)" found at <http://technet.microsoft.com/en-us/library/cc732785%28WS.10%29.aspx>

Step 2—Setting up the service credentials configuration

Add a new configuration or modify an existing configuration node in:

```
<WEB_ROOT>\Integration\web.config
```

Node:

```
/configuration/system.serviceModel/behaviors/
serviceBehaviors/behavior/serviceCredentials
```

The following is a sample of <serviceCredentials> node:

```
<serviceCredentials>
  <serviceCertificate findValue="ApI_Cert"
    storeLocation="LocalMachine"
    x509FindType="FindBySubjectName" storeName="My" />
  <userNameAuthentication
    userNamePasswordValidationMode="Custom" customUserNamePasswordVali
    idatorType="WCFPlatformExtensions.WCFProdikaUserNamePasswordVali
    dator,ProdikaAPILib"/>
</serviceCredentials>
```

You should modify the <serviceCertificate> node to adapt the information of the certificate installed in [Step 1—Installing certificates for the web server](#) on page 2-5.

For more information about how to config this node, please refer to the following article:

<**serviceCertificate**> of <**serviceCredentials**> found at
<http://msdn.microsoft.com/en-us/library/ms731340.aspx>

Note If this node already exists in the configuration file, do not add another node. Instead, modify the information based on the original configuration.

Step 3—Setting the wsHttpBinding configuration

Add a new <wsHttpBinding> configuration node in:

```
<WEB_ROOT>\Integration\web.config
```

Node:

```
/configuration/system.serviceModel/bindings/
```

The following is a sample of <wsHttpBinding> node:

```
<wsHttpBinding>
  <binding name="prodikaAPIBinding">
    <security mode="Message">
      <message clientCredentialType="UserName" />
    </security>
  </binding>
```

Make sure the “Name” attribute of the <binding> node is unique in the whole <wsHttpBinding> node. This value will be used in [Step 4—Setting the service bindings configuration](#) on page 2-6.

Step 4—Setting the service bindings configuration

Open the configuration file:

```
<WEB_ROOT>\Integration\Contracts\Prodika\web.config
```

For each <endpoint> sub-node like shown in below of /configuration/system.serviceModel/services/service nodes,

```
<endpoint binding="basicHttpBinding" contract="..." />
```

update to:

```
<endpoint binding="wsHttpBinding"
bindingConfiguration="prodikaAPIBinding" contract="..." />
```

The value of the “bindingConfiguration” attribute should equal the value of “name” attribute configured in [Step 3—Setting the wsHttpBinding configuration](#) on page 2-6.

Verifying the Installation

The final steps in setting up the API are verifying that the web services are accessible and that they are working.

To verify that the web services are accessible, bring up the services in Internet Explorer:

- 1** Launch Internet Explorer.
- 2** In the Address bar, type in:

```
http://<servername>/Integration/ProdikaContracts/  
Specification/Common/v30/GeneralSpecServices.svc
```

- 3** You should see a page titled GeneralSpecServices Service.
 - a** If you see the page, the web services are accessible.
 - b** If you do not see the page, please review the installation and configuration.

To verify the web services are operational, you will need to execute a web service call and get a result. Various web service clients provide this functionality. If you can call the web service and get a result, the set up process is complete.

Using the General Spec Services Web Services

This chapter describes the General Spec Services web service. Topics in this chapter include:

- ❑ Overview of General Spec Services
- ❑ Get Spec Summary
- ❑ Get Spec Numbers For Criteria
- ❑ Save Spec Cross References
- ❑ Get GSM Percent Breakdown
- ❑ Get Compliance Data

Overview of General Spec Services

GeneralSpecServices provides operations that act on Global Specification Management (GSM) specifications. The following operations are supported:

Operation	v24	v25	v30	Description
Get Spec Summary on page 3-3	●	●	●	Returns the specification summary data and cross references for a given list of specifications
Get Spec Numbers For Criteria on page 3-5	●	●	●	Returns the specification number and cross references for specifications matching several input criteria
Save Spec Cross References on page 3-8	●	●	●	Creates, updates, and deletes cross references for a given specification
Get GSM Percent Breakdown on page 3-10	●	●	●	Returns percent breakdown information for a list of specifications
Get Compliance Data on page 3-13	●	●	●	Returns compliance data for a given list of specifications

Service Endpoint Locations

v24 endpoint

`http://<servername>/Integration/ProdikaContracts/Specification/Common/v24/GeneralSpecServices.svc`

v25 endpoint

http://<servername>/Integration/ProdikaContracts/Specification/Common/
v25/GeneralSpecServices.svc

v30 endpoint

http://<servername>/Integration/ProdikaContracts/Specification/Common/
v30/GeneralSpecServices.svc

Get Spec Summary

Description

Use the GetSpecSummary web service to retrieve specification summary information for a given list of specifications.

Input

- 1 Allow Only Approved Spec—Specifications returned must be in an Approved status. (See [Condition C - Allow Only Approved Spec](#) on page A-1.)
- 2 A list of specification numbers, cross references, or a combination of either.

Table 3-1: Input

Name	Type	Description
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an Approved status False—Specifications returned may be in any status
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects. See tSpecIdentifierCriterion on page A-10.

Output

The following specification summary data is returned for each specification:

- Name
- ShortName
- SpecificationIdentifier
 - SpecNumber and IssueNumber
 - List of Cross References—The cross reference consists of SystemID, EquivalentValue, Description, Status, and UOM
- SpecType (four digit specification type code; see [Condition D - Specification Types](#) on page A-2)
- Status
- Category
- SubCategory
- Group
- Originator
- EffectiveDate
- InactiveDate

Note If any date field is empty or “null”, the field is automatically populated with the maximum date value of 12/31/9999. The user interface will not show the date or will show it as “-----”.

- Supercedes
- ReasonForChange
- IsTemplate (v25 and v30 only)

Table 3-2: Output

Name	Type	Description
tSpecificationSummary Wrapper	tSpecificationSummary Wrapper[]	Array of tSpecificationSummaryWrapper objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 3-3: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request.
RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number, issue number) format is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	SPEC_SUMMARY_RETRIEVAL_ERROR	Returned if an unexpected exception occurs when loading a specification.

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, F detailed in [Special Conditions](#) on page A-1.

Get Spec Numbers For Criteria

Description

Use the Get Spec Numbers for Criteria service to search for specifications using various predefined search criteria. The service returns a list of matching specification numbers (specification number, issue number, and list of cross references).

Input

The following input criteria are available as search criteria:

- 1 Allow Only Approved Spec—Restricts results to specifications in an Approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.
 - True—Specifications returned must be in an “Approved” status
 - False—Specifications returned may be in any status
- 2 Spec Created/Modified Date Range—Restrict results to specifications created or modified in the given date range
 - Date Range Type —CreatedBetweenDateRange or ModifiedBetweenDateRange; **required**
 - Start Date —Datetime; **required**
 - End Date —Datetime; optional (if no End Date is provided, any specification date after the Start Date will be returned)
- 3 Originators—Restricts search results to specifications created by any user in the list of originators
 - Originator Type—OriginatorUserNames list or OriginatorExternalIDs list
 - OriginatorUserNames—List of strings representing the specification originator UserNames. These are login names.
 - OriginatorExternalIDs—List of strings representing the specification originator User External IDs
- 4 Spec Status—Restricts results to specifications whose statuses **contain** any of the listed workflow statuses. For example, “Draft” will also return “Draft Review”.
 - Spec Status name
 - If Allow Only Approved Spec is set to True and a Spec Status is provided, both values must resolve for a specification to be returned
- 5 Spec Name —Restricts results to specifications with a specification name **containing** the given string
- 6 Short Name—Restricts results to specifications with a specification short name **containing** the given string
- 7 Spec Types—Restricts results to specifications types in given list of specification types
 - Specification type must be four digits

- Possible specification type values: See [Condition D - Specification Types](#) on page A-2
- 8** Cross Reference—Restricts results to specifications **containing** the given cross reference System ID and Equivalent Code
- 9** IncludeSpecTemplates—v25 and v30 only; Search results include specification templates. For v24, by default, excludes templates from search results.

Table 3-4: Input

Name	Type	Description
QueryOptions	tQueryOptions	Contains search criteria

Output

A list of Specification Identifiers (tSpecificationIdentifier) that contain the following:

- SpecificationNumber
 - Spec Number
 - Issue Number
- List of Cross References
 - SystemId
 - Description
 - UOM
 - Status
 - Equivalent Value

Table 3-5: Output

Name	Type	Description
specificationIdentifiers	tSpecificationIdentifier []	Array of tSpecificationIdentifier

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 3-6: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters passed in
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ORIGINATOR_TYPE	Must be of type OriginatorUserNames or OriginatorExternalIDs
	INVALID_SPEC_TYPE	Must be numeric; four digits
	INVALID_DATE_RANGE	CreatedBetweenDateRange or ModifiedBetweenDateRange expected Start date required and must be prior to (optional) End date
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	SPEC_SUMMARY_RETRIEVAL_ERROR	Occurs when an unexpected exception occurs when loading a specification

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, D, E2, F in [Special Conditions](#) on page A-1.

Save Spec Cross References

Description

Use the SaveSpecCrossReferences web service to modify a given specification's list of cross references. The web service takes a list of cross reference change items, which may be Adds, Updates, and/or Deletes. It then applies those modifications to a given specification's cross references. Results of the web service call include a list of all specifications that have been affected, along with the newly updated list of cross references.

Any added or updated cross reference will have its Externally Managed flag set to that cross reference's default Externally Managed value.

Specifications that the user does not have workflow 'Write' permissions for will not be modified.

Input

- 1 tSpecIdentifierCriterion—The specification to modify. **Required.**
- 2 List of Cross Reference change items (CrossRefUpdateItem). At least one is **required**. Allowed types:
 - AddCrossReference
 - NewCrossReference
 - UpdateCrossReference
 - OriginalCrossReference
 - ReplacementCrossReference
 - DeleteCrossReference
 - RemoveCrossReference

Output

The result will be a list of specifications (SpecUpdatedWrappers) affected by the cross reference changes. For each specification affected, the results will include the full cross reference list. See Condition #1 in [Condition A - No Issue Specified in Input Criteria](#) on page A-1.

- 1 SpecUpdatedWrapper
 - SpecificationIdentifier
 - SpecNumber and IssueNumber
 - List of Cross References—The cross reference consists of SystemID, EquivalentValue, Description, UOM, and Status

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 3-7: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters passed in
	INVALID_CROSS_REFERENCE	Cross Reference (SystemID, Equivalent) or Specification Number input is required. See <i>Condition E - Specification Identifier Input Formats</i> on page A-2.
	NO_SPEC_FOUND	This may be caused by several factors. Details of the error will be provided in the Message Description. <ul style="list-style-type: none"> Unable to locate specification with given input A Delete cross reference references a cross reference that does not exist on a specification An Add cross reference is adding a cross reference that already exists An Add cross reference is adding a cross references with a status of New, Inactive, or Archived An Update cross reference is updating a cross reference where the status of the replacement cross reference is New, Inactive, or Archived Referencing an unknown system ID Referencing an unknown specification type Equivalent length is invalid
	INVALID_SECURITY_PRIVILEGES	User must have role [EXTERNALLY_MANAGED_CROSS_REF_ADMIN] to modify cross references
RESULT_FAILURE	SPEC_LOAD_ERROR	Occurs when an unexpected exception occurs loading a specification
	UNKNOWN_ERROR	Unknown exception retrieving specification relationships

Notes

See Conditions A.1, A.2, B.1, D, E, F in *Special Conditions* on page A-1.

Get GSM Percent Breakdown

Description

The GetGSMPercentBreakdown service returns percent breakdown information for a list of specifications.

The web service respects:

- ❑ GSM BU Security
- ❑ WFA Permissions
- ❑ Formula Classifications

It returns the following pieces of data for each % breakdown:

- Breakdown Summary Information
- Breakdown Description
- Restrictions
- Formula Classifications
- Tags
- Breakdown Details
- Component Name
- Component ID (Unless it is free text)
- Component Description
- Component COO
- Component Complies With
- Component Formulation Amount
- Component Min Amount
- Component Max Amount
- Component Total Solids
- Component Function
- Component Critical Flag

Specification Types

Compliance information is returned for the following specification types:

- ❑ Product Specification
- ❑ Material Specification
- ❑ Trade Specification

Input

- 1 tSpecInputCriteria—A standard list of spec identifiers (specification #, issue #, or Cross Reference items)

Output

- 1 SpecFormulaBreakdown
 - tSpecificationIdentifier SpecificationIdentifier
 - tFormulaBreakdowns[] FormulaBreakdowns
 - a tFormulaBreakdowns consist of the following:
 - tBreakdown[] breakdowns
 - boolean IsProprietary
 - boolean PublishToSupplierPortal
 - boolean IsMasterFormula

- DateTime CreationDate
 - string Description
 - tRestriction[] Restrictions (may be a string/alias, or may need other information)
 - string[] FormulationClassifications
- b** tBreakdowns consist of the following:
- string Name
 - string Description
 - string Caption (free text only)
 - tBreakdownSource breakdownSource {Material Spec, FIC Term, FoodItemCatalog, FreeText}
 - double PercentFormulation
 - double MinRange
 - double MaxRange
 - boolean IsCritical
 - integer SequenceNumber
 - tComplianceItem[] CompliesWith
 - tCountry[] CountriesOfOrigin
 - string ComponentFunction
- c** tCountry consists of the following:
- string CountryID
 - string CountryName
 - string ISOCode
 - integer ISONumericCode

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 3-8: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	SPEC_PERCENTBREAKDOWN_RETRIEVAL_ERROR	Returned if an unexpected exception occurs when loading specification %breakdown information

Notes

See Conditions A.1, A.2, B, C.1, C.2, D.1 (1004, 2147, 6501), E.1, E.2, F in [Special Conditions](#) on page A-1.

Get Compliance Data

Description

Use the GetComplianceData web service to retrieve compliance information for a given list of specifications. The specification identifier passed in can include IncludeCompliesWith, IncludeAllergens, IncludeAdditives, and IncludeIntolerances. When these are set to True, the compliance items for that type are included. Otherwise, the compliance items for that type will not be included.

The service returns the following:

- Complies With Items
- Allergens Know to Contain Item, Max/100g and Source/Comments
- Allergens May Contain Item, Max/100g and Source/Comments
- Allergens Does Not Contain Item
- Intolerances Know to Contain Item, Max/100g and Source/Comments
- Intolerances May Contain Item, Max/100g and Source/Comments
- Intolerances Does Not Contain Item
- Additives Know to Contain Item, Max/100g and Source/Comments
- Additives May Contain Item, Max/100g and Source/Comments
- Additives Does Not Contain Item

Specification Types

Compliance information is returned for the following specification types:

- Menu Item specification
- Product specification
- Material specification
- Process specification (in v5.2 or less)
- Trade specification

Input

- 1 Specification Identifier (spec number or cross reference)
- 2 Combine Like Items (Boolean)
IncludeCompliesWith, IncludeAllergens, IncludeAdditives,
IncludeIntolerances

- True—Include this item selection data
 - False—Do not include this item selection data
- 3** Allow Only Approved Spec—Top-level specification returned must be in an “Approved” status (For more information see [Condition C - Allow Only Approved Spec](#) on page A-1).

Output

- 1** Each OutputItem in the OutputItems list includes:
- tSpecComplianceInfo[] complianceSpecs
- 2** Each tSpecComplianceInfo includes:
- tSpecificationIdentifier SpecificationIdentifier
 - tComplianceItem[] CompliesWith
 - tComplianceItemContained[] AllergensContained
 - tComplianceItemContained[] AdditivesContained
 - tComplianceItemContained[] IntolerancesContained
 - tComplianceItem[] AllergensNotContained
 - tComplianceItem[] AdditivesNotContained
 - tComplianceItem[] IntolerancesNotContained
 - tComplianceItemContained[] AllergensPossiblyContained
 - tComplianceItemContained[] AdditivesPossiblyContained
 - tComplianceItemContained[] IntolerancesPossiblyContained
- 3** Each tComplianceItemContained structure includes:
- tComplianceItem ComplianceItem
 - string Name
 - string ExternalID
 - tMeasurement MaxPer100Grams
 - double Value
 - tUOM UOM
 - Output Summary
 - Ref tSpecComplianceInfo structure
 - Input Summary

- Input Items—List of input items. Each Input item will include:
 - Specification Identifier (Spec Number-Issue Number or Cross References, IncludeCompliesWith, IncludeAllergens, IncludeAdditives, IncludeIntolerances)

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 3-9: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_INPUT	A valid SpecInputCriteria is required
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	BOM_ITEM_CALCULATION_ERROR	Occurs when an Input UOM category differs from the batch UOM category and it does not have a Density defined
RESULT_FAILURE	UNKNOWN_ERROR	Unexpected exception occurs when formatting the output items

Notes

See Conditions A.1, A.2, C.1, C.2, E, F in [Special Conditions](#) on page A-1.

Using the SCRM Services Web Service

This chapter describes the *SCRMServices* web service. Topics in this chapter include:

- *Overview of SCRM Services*
- *Get Company*
- *Get Facility*
- *Get SCRM Sourcing Approval*

Overview of SCRM Services

SCRMServices provides operations that act on Supply Chain Relationship Management (SCRM) sourcing approvals (specification-related and non specification-related), companies, and facilities. The following operations are supported:

Operation	v24	v25	v30	Description
Get Company on page 4-2	●	●	●	Returns SCRM company information, company hierarchies, and facilities for given company identifiers
Get Facility on page 4-4	●	●	●	Returns SCRM facility information and related sourcing approvals for given facility identifiers
Get SCRM Sourcing Approval on page 4-6	●	●	●	Returns specification-related or non specification-related sourcing approval information for given sourcing approval identifiers

Service Endpoint Locations

v24 endpoint

`http://<servername>/Integration/ProdikaContracts/SCRM/v24/SCRMServices.svc`

v25 endpoint

`http://<servername>/Integration/ProdikaContracts/SCRM/v25/SCRMServices.svc`

v30 endpoint

http://<servername>/Integration/ProdikaContracts/SCRM/v30/SCRMServices.svc

Get Company

Description

Use the GetCompany web service to retrieve the company profiles for a given list of companies.

Input

- 1 A list of company numbers, cross references, or a combination of either

Table 4-1: Input

Name	Type	Description
CompanyIdentifiers	tSCRMENTityIdentifier []	Array of one or more tSCRMENTityIdentifier objects

Output

The following company profile data is returned for each company:

- Company Profile Number
- Company Name
- Company business units and corresponding business unit status
- Postal Address (address 1, address 2, City, State, Postal Code, Country)
- Street Address (address 1, address 2, City, State, Postal Code, Country)
- Website
- Phone
- Fax
- Cross References
- Special Attributes
- Special Notes
- Parent Companies (Collection of parent company number only)
- Child Companies (Collection of child company number only)
- Facilities (Collection of facility numbers only)

Table 4-2: Output

Name	Type	Description
Companies	tCompany []	Array of tCompany objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 4-3: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request.
RESULT_INVALID_INPUT	INVALID_COMPANY_NUMBER	Company number input format is invalid. See #1 of Condition K - Invalid Company Input Formats on page A-4.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) format is invalid. See # 2 of Condition K - Invalid Company Input Formats on page A-4.
	NO_COMPANY_FOUND	Occurs if any company cannot be found for the input criteria (the service will continue to process remaining criteria).
	NOT_ENOUGH_PRIVILEGES	Occurs if the API user has no read permission to companies returned for the input criteria.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.

Notes

See Conditions F.1, K.1, and K.2 in [Special Conditions](#) on page A-1.

Get Facility

Description

Use the GetFacility web service to retrieve the facility profiles for a given list of facilities.

Input

A list of facility numbers, cross references, or a combination of either

Table 4-4: Input

Name	Type	Description
FacilityIdentifiers	tSCRMEntityIdentifier []	Array of one or more tSCRMEntityIdentifier objects

Output

The following facility profile data is returned for each facility:

- Facility Profile Number
- Facility Name
- Facility business units and corresponding business unit status
- Postal Address (address 1, address 2, City, State, Postal Code, Country)
- Street Address (address 1, address 2, City, State, Postal Code, Country)
- Website
- Phone
- Fax
- Cross References
- Special Attributes
- Special Notes
- Specification Related Sourcing Approvals (Collection of pkids, sourcing approval Number and GSM specification number)
- Non Specification Related Sourcing Approvals (Collection of pkids and sourcing approval number)

Table 4-5: Output

Name	Type	Description
Facilities	tFacility []	Array of tFacility objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 4-6: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request.
RESULT_INVALID_INPUT	INVALID_FACILITY_NUMBER	Facility number input format is invalid. See #1 of Condition L - Invalid Facility Input Formats on page A-4.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) format is invalid. See # 2 of Condition L - Invalid Facility Input Formats on page A-4.
	NO_FACILITY_FOUND	Occurs if any facility cannot be found for the input criteria (the service will continue to process remaining criteria).
	NOT_ENOUGH_PRIVILEGES	Occurs if the API user has no read permission to companies returned for the input criteria.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.

Notes

See Conditions L.1, L.2, and F.1 in [Special Conditions](#) on page A-1.

Get SCRM Sourcing Approval

Description

Use the GetSCRMSourcingApproval web service to retrieve sourcing approval information. The service returns specification-related or non specification-related sourcing approval information for given sourcing approval identifiers.

Input

- 1 A list of sourcing approval PKIDs or sourcing approval numbers.
- 2 Allow Only Approved Entity—Specification-related sourcing approvals returned must be in an “Approved” workflow status (Non specification-related sourcing approvals ignore this setting). (See [Condition J - Allow Only Approved Entity](#) on page A-4).

Table 4-7: Input

Name	Type	Description
AllowOnlyApprovedEntity	boolean	True—Specification-related sourcing approvals returned must be in an Approved status. False—Specification-related sourcing approvals returned may be in any status. See Condition J - Allow Only Approved Entity on page A-4 for details.
SourcingApprovalIdentifier	tSCRMSourcingApproval Identifier[]	Array of one or more sourcing approval PKIDs or sourcing approval numbers.

Output

- 1 Each specification-related sourcing approval includes:
 - Source Company Number
 - Source Company Cross Reference(s)
 - Source Facility Number
 - Source Facility Cross Reference
 - Specification Number
 - Specification Cross Reference(s)
 - Receiving Facilities (collection of facility numbers, facility names, and cross references)
 - Status
 - Supplier Item Number
 - Supplier Signed Boolean
 - Supplier Signed Date
 - Supplier Signed Text
 - Sourcing Type

- Protocol ID
- Class
- Notes
- QA Assigned (usernames)
- SC Assigned (usernames)

2 Each non-specification related sourcing approval includes:

- Source Company Number
- Source Facility Number
- Source Company Cross References
- Source Facility Cross References
- Item/Service Description
- Receiving Facilities (collection of facility numbers, facility names, and cross references)
- Status
- Sourcing Type
- Class
- Notes
- QA Assigned (usernames)
- SC Assigned (usernames)

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 4-8: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters passed in (SCRM identifier is not a tSCRMSourcingApprovalPKID or tSCRMSourcingApprovalNumber type)
	INVALID_PKID	A valid Sourcing Approval PKID is required
	INVALID_SCRMENTITY_NUMBER	Occurs if you enter a sourcing approval number. A valid Sourcing Approval number is required.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	UNKNOWN_ERROR	Occurs when an unexpected exception happens when formatting the output items

Notes

See Conditions F1, I1, and I2 in [Special Conditions](#) on page A-1.

CHAPTER 5

Using the Nutrition Service Web Services

This chapter describes the Nutrition Service web service. Topics in this chapter include:

- Overview of Nutrition Service
- Get Nutrient Items per 100g
- Save Nutrient Analysis
- Get Nutrient Analysis
- Get Nutrient Composite

Overview of Nutrition Service

NutritionService provides nutrition and Nutrition Surveillance Management (NSM) related operations. The following operations are supported:

Operation	v24	v25	v30	Description
Get Nutrient Items per 100g on page 5-3	●	●	●	Returns the Nutrient Items for a given list of specifications
Save Nutrient Analysis on page 5-5	●*	●*	●*	Saves nutrient analysis data (nutrient sample and nutrient item values) for a specification. *v24 added two new fields to analysis input
Get Nutrient Analysis on page 5-8	●	●	●	Returns the Nutrient Analysis summary and list of Nutrient Items for a given nutrient analysis number
Get Nutrient Composite on page 5-10	●	●	●	Returns the Nutrient Composite summary, list of Analyses that make up the composite, and the list resulting Nutrient Items for a given nutrient composite number

Service Endpoint Locations

v24 endpoint

http://<servername>/Integration/ProdikaContracts/Nutrition/v24/
NutritionService.svc

v25 endpoint

http://<servername>/Integration/ProdikaContracts/Nutrition/v25/
NutritionService.svc

v30 endpoint

http://<servername>/Integration/ProdikaContracts/Nutrition/v30/
NutritionService.svc

Get Nutrient Items per 100g

Description

The Get Nutrient Items per 100g web method gets a list of nutrient items for each of the specified GSM specifications. For material and product specifications, nutrient items are retrieved from the nutrient composition. For trade and menu item specifications, nutrient items are retrieved from the active nutrient profile. Additionally, the nutrient items from a given nutrient profile specification can also be retrieved.

Input

- 1 AllowOnlyApprovedSpec flag—If included and set to “True,” only approved specifications will be included in the output. See [Condition C - Allow Only Approved Spec](#) on page A-1 for more information.
- 2 Array named specIdentifierCriterion of type tSpecIdentifierCriterion—The identifiers can refer to any GSM specification type that associates with nutrient profiles or nutrient compositions. See [tSpecIdentifierCriterion](#) on page A-10 for more information.

Table 5-1: Input

Name	Type	Description
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an Approved status False—Specifications returned may be in any status
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects

Output

The only output is an array named NutrientData. The elements are of type tNutrientDataWrapper (see [tNutrientDataWrapper](#) on page A-21 for more information). Each tNutrientDataWrapper element lists the nutrient items for one specification. Each nutrient item contains:

- InfoodsCode—The InFoodsID value of the nutrient. See [Condition H - InFoodsCode](#) on page A-3.
- ValuePer100Gms—The numerical value for 100 grams
- UOM—Unit of measure
 - ISOCode—The ISO code of the unit of measure. If no ISO code is available for the UOM, this field should not be used and the Abbreviation field should be populated.
 - ID—The unit of measure identification number.
 - Abbreviation—The abbreviation of the UOM to use. This field is only referenced if the ISOCode is not used.

- Source—The name of the location/source the nutrient analysis was produced. Uses the name column from the NutritionalOrigin table.
- Comments—Additional comments about this particular nutrient.

Table 5-2: Output

Name	Type	Description
NutrientData	tNutrientDataWrapper	Nutrient items for one specification

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 5-3: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_FAILURE	UNEXPECTED_RESULT	Unexpected exception occurs when loading specification information
RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_SPEC_TYPE	The specification type is not supported
	NO_VALID_PARAMETERS	No valid parameters used
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, D.1 (Types: 1004, 2147, 5750, 5816, 6500, 6501), E, F, and H in [Special Conditions](#) on page A-1.

Save Nutrient Analysis

Description

Use the SaveNutrientAnalysis web service to import new nutrient analysis entries into NSM. For a given specification, the web service takes a list of NutrientSamples, which includes a specification number, SCRM facility, a list of business units, and a list of nutrient items.

Results of the web service call include an overall success indicator and a list of all nutrient analyses that have been imported. Each nutrient analysis result contains a system-generated analysis number and the sample number used as input.

Input

Input is a list of tNutrientSample objects. Each NutrientSample contains a SampleSummary and a list of NutrientItems.

- SampleSummary
 - SampleNumber—The number to assign to the nutrient analysis
 - SampleType—Type name to assign to the nutrient analysis
 - GtinUPC—GTIN UPC value
 - SpecNumber—The specification to associate this nutrient analysis to. May be a SpecNumber-IssueNumber or a cross reference. If using a cross reference and the cross reference is associated to multiple specifications, an error will occur.
 - SourceFacility—The SCRM facility to associate this nutrient analysis to. May be an facility number or cross reference. If the cross reference is associated to multiple facilities, an error will occur.
 - BusinessUnits—List of business units to associate the analysis to. Each business unit entry must contain the full business unit alias (for example, “CPI North America Retail”).
 - AnalysisDate
 - SentToLabDate—Optional; Available for v24 only
 - ReceivedFromLabDate—Optional; Available for v24 only
 - Description—Text field
- NutrientItems—List of nutrient items. Each nutrient item contains:
 - InfoodsCode—The InFoodsID value of the nutrient. See [Condition H - InFoodsCode](#) on page A-3.
 - ValuePer100Gms—The numerical value for 100 grams
 - UOM—Unit of measure
 - ISOCODE—The ISO code of the unit of measure. If no ISO code is available for the UOM, this field should not be used and the Abbreviation field should be populated.

- ID—Not used
- Abbreviation—The abbreviation of the UOM to use. This field is only referenced if the ISOCode is not used.
- Source—The name of the location/source the nutrient analysis was produced. Uses the name column from the NutritionalOrigin table.
- Comments—Text field

Output

The result will be an overall success indicator and a list of all nutrient analyses that have been imported.

- IsSuccessful—True or False
- Results—List of NutrientAnalysisResult objects. Each NutrientAnalysisResult object provides a system generated AnalysisNumber for the newly imported nutrient analysis, and its corresponding SampleNumber used as input.
- AnalysisNumber—System generated reference number for the nutrient analysis
- SampleNumber—Number used as input to assign to the nutrient analysis

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 5-4: Result codes

Result Code	Possible Messages or Warnings	Comments
INVALID_INPUT	INVALID_SECURITY_PRIVILEGES	User must have role [NUTRIENT_ANALYSIS_CREATOR] to save nutrient analysis data
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 5-4: Result codes (continued)

Result Code	Possible Messages or Warnings	Comments
RESULT_INVALID_INPUT	NUTRITION_SAMPLE_INVALID	Nutrient sample required
	NUTRITION_ANALYSIS_INVALID	No valid parameters for nutrient analysis
	MAX_RECORDS_SAVED	Maximum records count allowed for nutrient analysis records save exceeded. Request rejected.
	NUTRITION_ANALYSIS_INVALID_SAMPLENUMBER	Nutrient analysis Sample Number input invalid (must be 50 alphanumeric characters or less)
	NUTRITION_ANALYSIS_INVALID_SAMPLETYPE	Nutrient analysis Sample Type input invalid (must be 50 alphanumeric characters or less)
	NUTRITION_ANALYSIS_INVALID_DESCRIPTION	Nutrient analysis Description length invalid (must be 1024 alphanumeric characters or less)
	NUTRITION_ANALYSIS_INVALID_GTINUPC	Nutrient analysis GTINUPC input invalid (must be 14 alphanumeric characters or less)
	NUTRITION_ANALYSIS_INVALID_SCRM_FACILITY	Nutrient analysis SCRM source Facility input invalid. See Condition I - SCRM Entity Input on page A-4.
	NUTRIENT_ANALYSIS_INVALID_BUSINESS_UNIT	No business unit found for given alias
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
	NUTRIENT_ITEM_INVALID_COMMENT	Nutrient item Comments must be 512 alphanumeric characters or less
	NUTRIENT_ITEM_INVALID_UOM	Unit of measure not found for given ISOCode or abbreviation
	NUTRIENT_ITEM_INVALID_INFOODS_CODE	No Infoods Code found for given input value
	NUTRIENT_ITEM_INVALID_SOURCE	Provide Source cannot be found
UNKNOWN_ERROR	Unknown error retrieving SCRM facility information	
RESULT_FAILURE	NUTRIENT_SAMPLE_SAVE_ERROR	Unknown error saving nutrient analysis

Notes

See Conditions A.1, A.2, E, G, H, and I in [Special Conditions](#) on page A-1.

Get Nutrient Analysis

Description

Use the GetNutrientAnalysis web service to retrieve the Nutrient Analysis summary and list of Nutrient Items for a given nutrient analysis number. The associated SCRM facility information will only be returned if the calling user has access permission to the facility.

Input

- 1 A nutrient analysis number

Table 5-5: Input

Name	Type	Description
AnalysisNumber	String Max length = 8	Unique numerical identifier for the nutrient analysis. Required.

Output

- NutrientAnalysisSummary
 - AnalysisNumber —System-assigned analysis number
 - SampleNumber—User-defined number for the sample. This can be alpha or numeric.
 - Description—Description of the analysis
 - specificationIdentifier
 - Spec # and Issue #
 - List of Cross References
 - GTIN_UPC—GTIN UPC value
 - SampleType —User-defined field denoting the type of sample, such as raw material or finished product
 - Facility—The facility where the sample is sourced
 - HasAccessToSourceFacility—Set to false if user does not have access to the source facility
 - List of BusinessUnits—List of business units to associate the analysis to. Each business unit entry must contain the full business unit alias (for example, “CPI North America Retail”).
 - AnalysisDate
 - LastUpdateDate
 - SentToLabDate
 - ReceivedFromLabDate
 - Originator (Name, ExternalId)

- List of Nutrient Items. Each nutrient item contains:
 - InfoodsCode—The InFoodsID value of the nutrient. See [Condition H - InFoodsCode](#) on page A-3.
 - ValuePer100Gms—The numerical value for 100 grams
 - UOM—Unit of measure
 - ISOCode—The ISO code of the unit of measure. If no ISO code is available for the UOM, this field should not be used and the Abbreviation field should be populated.
 - ID—The unit of measure identification number
 - Abbreviation—The abbreviation of the UOM to use. This field is only referenced if the ISOCode is not used.
 - Source—The name of the location/source the nutrient analysis was produced. Uses the name column from the NutritionalOrigin table.
 - Comments—Additional comments about this particular nutrient

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 5-6: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occur processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	NUTRITION_ANALYSIS_NUMBER_INVALID	Nutrient Analysis Number is required. Nutrient Analysis Number length must not be more than 8 characters
	NUTRITION_ANALYSIS_NOT_FOUND	No nutrient analysis found with given nutrient analysis number
	INVALID_SECURITY_PRIVILEGES	If user does not have permission for the nutrient analysis' related specification

Notes

See Conditions B (for the nutrient analysis' related specification) and H in [Special Conditions](#) on page A-1.

Get Nutrient Composite

Description

Use the GetNutrientComposite web service to retrieve the Nutrient Composite summary, list of Analyses that make up the Composite, and the list resulting Nutrient Items for a given nutrient composite number. The resulting nutrient items list is a composite of the nutrient analyses according to their weighted values. Each resulting nutrient item returned does not include the source or comments data.

The nutrient composite information will only be returned if the calling user has access to the associated Specification.

Input

- 1 A nutrient analysis number

Table 5-7: Input

Name	Type	Description
CompositeNumber	String Max length = 10	Unique numerical identifier for the nutrient composite. Required.

Output

The following Nutrient Composite data is returned:

- NutrientCompositeSummary
 - CompositeNumber
 - Title
 - Description
 - SpecificationIdentifier
 - Spec # and Issue #
 - List of Cross References
 - List of BusinessUnits
 - CompositeDate
 - LastUpdateDate
 - Originator (Name, ExternalId)
- List of Weighted Nutrient Analyses

- Each Weighted Analysis has:
 - Analysis Number
 - Specification Identifier
 - Analysis Date
 - Weighting
 - Comments
- List of Nutrient Items. Each nutrient item has:
 - InfoodsCode—The InFoodsID value of the nutrient. See [Condition H - InFoodsCode](#) on page A-3.
 - ValuePer100Gms—The numerical value for 100 grams
 - UOM—Unit of measure
 - ISOCode—The ISO code of the unit of measure. If no ISO code is available for the UOM, this field should not be used and the Abbreviation field should be populated.
 - ID—The unit of measure identification number
 - Abbreviation—The abbreviation of the UOM to use. This field is only referenced if the ISOCode is not used.
 - Source—The name of the location/source the nutrient analysis was produced. Uses the name column from the NutritionalOrigin table.
 - Comments—Text field

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 5-8: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occur processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	NUTRITION_COMPOSITE_NUMBER_INVALID	Nutrient Composite Number is required. Nutrient Composite Number length must not be more than 10 characters.
	NUTRITION_COMPOSITE_NOT_FOUND	No nutrient composite found with given nutrient composite number
	INVALID_SECURITY_PRIVILEGES	If user does not have permission for the composite's specification

Notes

See Conditions B (for the nutrient composite's related specification) and H in [Special Conditions](#) on page A-1.

Using the Cost Services Web Service

This chapter describes the Cost Services web service. Topics in this chapter include:

- Overview of Cost Services
- Save DWB Spec Cost

Overview of Cost Services

CostServices provides formulation specification costing related capabilities. The following operations are supported:

Operation	v24	v25	v30	Description
Save DWB Spec Cost on page 7-2	●	●	●	Imports specification costing information for formulation specifications calculations based on cost type, SCRM entity, and more.

Service Endpoint Location(s)

v24 endpoint

<http://<servername>/Integration/ProdikaContracts/DWB/v24/CostServices.svc>

v25 endpoint

<http://<servername>/Integration/ProdikaContracts/DWB/v25/CostServices.svc>

v30 endpoint

<http://<servername>/Integration/ProdikaContracts/DWB/v30/CostServices.svc>

Save DWB Spec Cost

Description

SaveDWBSpecCost saves costing data for specifications used as inputs in formulation specification calculations. Multiple cost items can be sent in one message group, where the Timestamp input value determines cost availability. Each cost item is categorized by the SCRM entity, cost type grouping, specification, and currency. Formulation specifications can pull in the data imported through this web service by refreshing the application cache.

Input

Table 7-1: Input

Name	Description
CostCulture	Optional description of the culture
MessageID	This alphanumeric value must be unique. It helps prevent the same cost data being imported twice.
OrganizationalUnitID	Optional key for a business unit
PrincipalName	Optional name
Timestamp	Current time
CostItems	Array of tCostItem, as described on tCostItem on page A-14

Output

Table 7-2: Output

Name	Description
SequenceNumber	Unique ID assigned to this cost import
NumberOfItemsImported	This number should match the number of tCostItem nodes in the input. See tCostItem on page A-14 for more information.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 7-3: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	INVALID_MESSAGE_ID	The input message ID must be unique across all calls, and must be 128 characters or less
	NO_VALID_PARAMETERS	Invalid Cost message - no data passed
	MAX_RECORDS_SAVED	Maximum records count allowed for save exceeded. Request rejected.
	INVALID_COST_MESSAGE_COST_CULTURE	Optional, must be <= 10 characters
	INVALID_COST_MESSAGE_ORGUNITID	Optional, must be <= 48 characters
	INVALID_COST_MESSAGE_PRINCIPAL_NAME	Optional, must be <= 100 characters
	INVALID_COST_ITEMS_INPUT	No cost items to import
RESULT_FAILURE	UNEXPECTED_RESULT	The description explains the problem
	INVALID_CURRENCY	No currency has the specified ISO code
	INVALID_UOM_ISO_CODE	No unit of measure was found for an ISO code
	INVALID_COST_TYPE	Cost Type must be <= 12 characters
	INVALID_COSTITEM_EQUIVALENT	Optional; must be <= 24 characters
	INVALID_SCRM_ENTITY	Invalid SCRM Facility input; SCRM Facility could not be found
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.

Notes

See Conditions E, G, and I in [Special Conditions](#) on page A-1.

Using the Custom Data Services Web Services

This chapter describes the Custom Data Services web service. Topics in this chapter include:

- ❑ *Overview of Custom Data Services*
 - ❑ *Service endpoint location(s)*
 - ❑ *Get Spec Custom Sections*
 - ❑ *Get Spec Extended Attributes*
 - ❑ *Get SCRM Custom Sections*
 - ❑ *Get SCRM Extended Attributes*
 - ❑ *Save Custom Lookup*
 - ❑ *Get Custom Sections MetaData*
 - ❑ *Get Extended Attributes MetaData*
 - ❑ *Get EQ Custom Sections*
 - ❑ *Get EQ Extended Attributes*
 - ❑ *Get Calculated Custom Section*
 - ❑ *Get PQM Custom Sections*
 - ❑ *Add PQM Custom Sections*
 - ❑ *Delete PQM Custom Sections*
 - ❑ *Update PQM Custom Section*
-

Overview of Custom Data Services

CustomDataServices provides operations related to extended attributes and custom sections. The following operations are supported:

Operation	v24	v25	v30	Description
Service endpoint location(s) on page 6-3	●	●	●	Returns an XML Schema describing the specified custom sections format expected when calling one of the other getXCustomSections web services.
Get Spec Custom Sections on page 6-5	●	●	●	Returns the specified custom section data for the given specifications if the user has read permissions. The resulting custom section XML is unique for each custom section type/template.
Get Spec Extended Attributes on page 6-7	●	●	●	Returns all extended attributes for the given GSM specifications.
Get SCRM Custom Sections on page 6-9	●	●	●	Returns the specified custom section data for the given companies, facilities, or sourcing approvals.
Get SCRM Extended Attributes on page 6-13	●	●	●	Returns all extended attribute data for the given companies, facilities, or sourcing approvals.
Save Custom Lookup on page 6-15	●	●	●	Updates the custom import lookup table, used by qualitative lookup extended attributes, with the provided lookup entries.
Get Custom Sections MetaData on page 6-17	●	●	●	Returns custom section meta data describing various attributes of the given custom section.
Get Extended Attributes MetaData on page 6-19	●	●	●	Returns extended attribute meta data describing various attributes of the given extended attribute.
Get EQ Custom Sections on page 6-21	●	●	●	Returns the specified custom section data for the given eQuestionnaire.
Get EQ Extended Attributes on page 6-23	●	●	●	Returns all extended attribute data for the given eQuestionnaire.
Get Calculated Custom Section on page 6-25	●	●	●	Returns a calculated version of a custom section for a given custom section number and GSM specification. Data can be provided to override existing specification data used in the calculation.
Get PQM Custom Sections on page 6-29			●	Retrieves custom section data for specified PQM items
Add PQM Custom Sections on page 6-31			●	Adds custom section data to specified PQM items
Delete PQM Custom Sections on page 6-33			●	Removes existing custom sections from specified PQM items
Update PQM Custom Section on page 6-35			●	Updates existing custom section data of specified PQM items

Service endpoint location(s)

v24 endpoint

<http://<servername>/Integration/ProdikaContracts/Common/v24/CustomDataServices.svc>

v25 endpoint

<http://<servername>/Integration/ProdikaContracts/Common/v25/CustomDataServices.svc>

v30 endpoint

<http://<servername>/Integration/ProdikaContracts/Common/v30/CustomDataServices.svc>

Get Custom Section Schema

Description

This web method gets an XML schema describing a custom section. (See <http://www.w3.org/XML/Schema> for the XML Schema specification.) Custom sections are composed of rows and columns of extended attributes. Extended attributes are of a limited number of types. Oracle Agile PLM for Process API supplies an XML schema file (ExtendedAttributeTypes.xsd) that specifies those types.

Input

Table 6-1: Input

Name	Description
CustomSectionID	A unique ID number assigned to a custom section when it is created. The editor label for this value is: "Section Number."

Output

Table 6-2: Output

Name	Description
customSectionID	The ID number passed as input
Schema	An XML schema describing the custom section

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-3: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	INVALID_CUSTOM_SECTION_NUMBER	Invalid Custom Section number
RESULT_FAILURE	UNEXPECTED_RESULT	The custom section ID number is invalid or the request could not be processed. The description explains the problem.

Get Spec Custom Sections

Description

This method gets custom section data for GSM specifications. The query is limited to the identified specifications and custom section types. Not all specified specifications may have every specified custom section type.

Input

Table 6-4: Input

Name	Description
CustomSectionNumbers	Array of custom section ID numbers
AllowOnlyApprovedSpec	If set to true, only the latest Approved issue number is retrieved, if one exists (see Condition C - Allow Only Approved Spec on page A-1).
specIdentifierCriterion	Array of tSpecIdentifierCriterion. These identify which specifications to query. For more information see tSpecIdentifierCriterion on page A-10.

Output

A tCustomSectionSpec element is returned for each specification that is found. These have two sub-elements:

- 1 SpecificationNumber—Identifies a specification that matched one input. It is of type tSpecificationNumber, as explained in [tSpecificationNumber](#) on page A-10.
- 2 Sections—Lists any custom sections of the types specified in the input that belong to the specification. Within “Sections” is one or more tCustomSectionSpec elements. There is one per custom section found. Each tCustomSectionSpec has a tExtension element containing an Any element. The nodes under this conform to the XML schema returned by GetCustomSectionSchema (see [Get Custom Section Schema](#) on page 6-4).

The sub-node is the section name. It in turn contains a node per row. Row nodes contain one node per column. Column nodes contain the actual values.

To summarize, the hierarchy is: Sections / tExtension / Any / <section-type> / <row_name> / <column_name> / <extended-attribute-type> / Value. The first column contains labels instead of values.

Object Level Security is evaluated for each custom section returned based on the web service user. Custom sections without appropriate security privileges are removed from the results, and include the INVALID_SECURITY_PRIVILEGES message.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-5: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition G - Max Records Allowed For Save on page A-2.
	INVALID_SECURITY_PRIVILEGES	User must have role [EXTERNALLY_MANAGED_CROSS_REF_ADMIN] to modify cross references. User does not have access to requested custom section.
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	Missing criteria or custom section number
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
RESULT_FAILURE	UNEXPECTED_RESULT	The custom section ID number is invalid or the request could not be processed. The description explains the problem.
	CUSTOM_SECTION_RETRIEVAL_ERROR	Unknown error getting custom section data

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get Spec Extended Attributes

Description

This web method gets extended attribute data for GSM specifications.

Input

- 1 A list of specification numbers, cross references, or a combination of either
- 2 Allow Only Approved Spec—Specifications returned must be in an Approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 6-6: Input

Name	Type	Description
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an Approved status False—Specifications returned may be in any status
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects. See tSpecIdentifierCriterion on page A-10.

Output

A tExtendedAttributeSpec element is returned for each specification that is found. These have two sub-elements:

- 1 SpecificationNumber—Identifies a specification that matched one input. It is of type tSpecificationNumber.
- 2 ExtendedAttributes—Lists any extended attributes that belong to the specification inside the Any node. Each attribute has a Value element. The body is the value. An ISO code for the unit of measure is in the unit of measure (UOM) attribute. Oracle Agile PLM for Process API supplies an XML schema file (ExtendedAttributeTypes.xsd) that specifies the format for each extended attribute type.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-7: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_FAILURE	UNEXPECTED_RESULT	The custom section ID number is invalid or the request could not be processed. The description explains the problem.
	SPEC_LOAD_ERROR	Unexpected exception loading specifications
	UNKNOWN_ERROR	Unknown error getting extended attributes data
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	Missing criteria or custom section number
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNING	EXTENDED_ATTRIBUTE_GENERATION_ERROR	Error generating extended attribute XML data for specification
	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition G - Max Records Allowed For Save on page A-2.

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get SCRM Custom Sections

Description

This method gets custom section data for SCRM companies, facilities, and sourcing approvals. The query is limited to the identified companies, facilities, sourcing approvals, and custom section types. Not all specified companies, facilities, and sourcing approvals may have every specified custom section type.

The inputs and outputs for each SCRM object are listed below:

Company Profile

Table 6-8: Input and Output

Input	Output
CompanyNumber/CompanyCrossReference	Custom Section message matching the specification custom section message
CustomSectionNumbers	

Facility Profile

Table 6-9: Input and Output

Input	Output
FacilityNumber/FacilityCrossReference	Custom Section message matching the specification custom section message
CustomSectionNumbers	

Specification Related Sourcing Approval

Table 6-10: Input, Output, and Security

Input	Output	Security
Sourcing Approval Number/ PKID	Custom Section message matching the specification custom section message	GSM Business Unit and Object Level Security
CustomSectionNumbers		
AllowOnlyApprovedEntity (optional)	boolean	<p>True—Sourcing approvals returned must be in an Approved status. An approved status is determined by a configurable tag. Refer to config\Custom\CustomizerSettings.config on page 2-3 for more information.</p> <p>False—Sourcing approvals returned may be in any status.</p> <p>This input applies only to sourcing approvals. It is ignored when pulling data from companies or facilities.</p>

Non-Specification Related Sourcing Approval

Table 6-11: Input, Output, and Security

Input	Output	Security
Sourcing Approval Number/ PKID	Custom Section message matching the specification custom section message	Object Level Security
CustomSectionNumbers		
Allow Only Approved Entity (optional)	Input for non-specification related sourcing approval.	

Input

- 1 **SCRMEntityInputCriteria**—Include a set of SCRM entities which may be SCRMCompany, SCRMFacility or SCRMSourcingApproval.
- 2 **CustomSectionNumbers**—Include a list of custom section numbers needed to retrieve from the entities which match the criteria in SCRMEntityInputCriteria.
- 3 **Allow Only Approved Entity (optional)**:
 - True—Sourcing approvals returned must be in an Approved status. An approved status is determined by a configurable tag.
 - False—Sourcing approvals returned may be in any status.

Output

Each tSCRMCustomSection in the CustomSections list will include:

- 1 EntityInfo—If the entity is a company or facility, this field will include the entity number and cross references. For a sourcing approval entity, this field will include the sourcing approval PKID.
- 2 Sections—Lists any custom sections of the types specified in the input that belong to the entity.

Each [Sections] node has one or more Extension elements containing an [Any] element.

The sub-node is the section name. It in turn contains a node per row. Row nodes contain one node per column. Column nodes contain the actual values.

To summarize, the hierarchy is:

Sections / tExtension / Any / <section-type> / <row_name> / <column_name >/ <extended-attribute-type> / Value.

The first column contains labels instead of values.

Object Level Security is evaluated for each custom section returned based on the web service user. Custom sections without appropriate security privileges are removed from the results, and include the INVALID_SECURITY_PRIVILEGES message.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-12: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	CUSTOM_SECTION_RETRIEVAL_ERROR	Occurs if cannot retrieve custom sections or if current user has no read permission about matching entity

Table 6-12: Result codes (continued)

RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	Missing criteria or custom section number(s)
	INVALID_SCRMENTITY_NUMBER	Entity number is not a 7 digit number
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PKID	PKID input is not a valid sourcing approval (specification-related and non-specification related) PKID
	INVALID_CUSTOM_SECTION_NUMBER	Custom Section numbers are required

Notes

See Conditions F.1, I.1, and I.2 in [Special Conditions](#) on page A-1. For specification related sourcing approvals, see B.1.

Get SCRM Extended Attributes

Description

The GetSCRMExtendedAttributes web service pulls all extended attributes on a company, facility, or sourcing approval.

The inputs and outputs for each SCRM object are listed below:

Company Profile

Table 6-13: Input and Output

Input	Output
Company Identifier (CompanyNumber/ CompanyCrossReference)	Group of Extended Attributes matching the specification extended attributes message

Facility Profile

Table 6-14: Input and Output

Input	Output
FacilityNumber/FacilityCrossReference	Group of Extended Attributes matching the specification extended attributes message

Specification Related Sourcing Approval

Table 6-15: Input, Output, and Security

Input	Output	Security
Sourcing Approval Number/ PKID	Group of Extended Attributes matching the specification extended attributes message	GSM Business Unit and Object Level Security
Allow Only Approved Entity (optional)		

Non-Specification Related Sourcing Approval

Table 6-16: Input, Output, and Security

Input	Output	Security
Sourcing Approval Number/ PKID	Group of Extended Attributes matching the specification extended attributes message	Object Level Security
Allow Only Approved Entity (optional)		

Input

- 1 SCRMEntityInputCriteria—Include a set of SCRM entities which may be SCRMCompany, SCRMFacility or SCRMSourcingApproval.
- 2 Allow Only Approved Entity (optional)
 - True—Sourcing approvals returned must be in an Approved status. An approved status is determined by a configurable tag.
 - False—Sourcing approvals returned may be in any status.

Output

A tSCRMExtendedAttributes element is returned for each SCRM entity that is found. These have two sub-elements:

- 1 EntityInfo—If the entity is a company or facility, this field will include the entity number and cross references. For a sourcing approval entity, this field will include the sourcing approval PKID.
- 2 ExtendedAttributes—Lists any extended attributes that belong to the entity inside the [Any] node. Each attribute has a Value element. The body is the value. An ISO code for the unit of measure (UOM) is in the unit of measure attribute. Oracle Agile PLM for Process API supplies an XML schema file (ExtendedAttributeTypes.xsd) that specifies the format for each extended attribute type.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-17: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	SCRMEntityInputCriteria missing or input format is invalid
	INVALID_SCRMENTITY_NUMBER	Entity number is not a 7 digit number
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See I.2.b of Condition I - SCRM Entity Input on page A-4.
	INVALID_PKID	PKID input is not a valid sourcing approval (specification-related and non-specification related) PKID
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	SCRM_EXTENDEDATTRIBUTES_LOAD_ERROR	Occurs if cannot retrieve Extended Attributes or if the current user has no read permission about matching entity

Notes

See Conditions F.1, I.1, and I.2 in [Special Conditions](#) on page A-1. For specification related sourcing approvals, see B.1.

Save Custom Lookup

Description

This web method adds items to the lookup lists used by qualitative lookup extended attributes. Those extended attributes refer to a category of lookups that are displayed as checkboxes, radio buttons, or other types of lists in the user interface.

Multiple lookup items may be added in each call. Lookup items must have a category, name, external ID, sequence, and status. If the category does not already exist, it is created.

Input

The only input is an array named CustomLookup of type tCustomLookup. See [tCustomLookup](#) on page A-21 for more information. Category, SequenceID and Status are required fields.

Output

The only output is a flag named IsSuccessful. It is “True” if no errors occurred while saving the new lookup options.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-18: Result codes

Result Code	Possible Messages or Warnings	Comments
INVALID_INPUT	INVALID_SECURITY_PRIVILEGES	User must have role [DATA_ADMIN] or [SUPER_DATA_ADMIN] to save custom lookup data
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_FAILURE	UNEXPECTED_RESULT	The custom section ID number is invalid or the request could not be processed. The description explains the problem.

Table 6-18: Result codes (continued)

Result Code	Possible Messages or Warnings	Comments
RESULT_INVALID_INPUT	MAX_RECORDS_SAVED	Maximum records count allowed for save exceeded. Request rejected.
	CUSTOM_LOOKUP_CATEGORY_INVALID	Category required with maximum length of 150 characters
	CUSTOM_LOOKUP_EXTERNALID_INVALID	ExternalID must be <= 80 characters
	CUSTOM_LOOKUP_VALUE_INVALID	Value must be <= 150 characters
	CUSTOM_LOOKUP_STATUS_INVALID	Status must be 0 (Inactive) or 1 (Active)
	CUSTOM_LOOKUP_INVALID	tCustomLookup must contain data
	CUSTOM_LOOKUP_SEQUENCE_INVALID	Sequence must be numeric and <= 4 digits

Notes

See Condition G in *Special Conditions* on page A-1.

Get Custom Sections MetaData

Description

Use the GetCustomSectionsMetaData web service to retrieve the custom section profiles for a given custom section.

Input

- 1 A custom section ID or a custom section number.

Table 6-19: Input

Name	Type	Description
customSectionMetaDataInputCriteria	tCustomSectionMetaDataInputCriteria	A tCustomSectionMetaDataInputCriteria object

Output

The following custom section profile data is returned for each custom section:

- Custom Section Number
- Custom Section ID
- Custom Section Dynamic Tags
- Custom Section Hide Header
- Custom Section Row (Sequence, ID and Dynamic Tags)
- Custom Section Column (Sequence, ID, Width, Print Width, and Dynamic Tags)

Table 6-20: Output

Name	Type	Description
customSections	tCustomSection[]	Array of tCustomSection objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-21: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occur processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters
	CUSTOM_SECTION_ID_INVALID	Custom Section ID input format is invalid. See #1 of Condition O - Invalid Custom Sections MetaData Input Formats on page A-5.
	CUSTOM_SECTION_NUMBER_INVALID	Custom Section Number input format is invalid. See #2 of Condition O - Invalid Custom Sections MetaData Input Formats on page A-5.
	INVALID_INPUT_CRITERIA_NUMBER	Input type is neither tCustomSectionID nor tCustomSectionNumber
	NO_CUSTOM_SECTION_FOUND	Occurs if any custom section cannot be found for the input criteria (the service will continue to process remaining criteria)

Notes

See Conditions O1 and O2 in [Special Conditions](#) on page A-1.

Get Extended Attributes MetaData

Description

Use the GetExtendedAttributesMetaData web service to retrieve the extended attribute profiles for a given extended attribute.

Input

- 1 An extended attribute ID.

Table 6-22: Input

Name	Type	Description
extendedAttributeID	string	Extended Attribute ID

Output

The following extended attribute profile data is returned for each extended attribute:

- Extended Attribute ID
- Extended Attribute Dynamic Tags

Table 6-23: Output

Name	Type	Description
extendedAttributes	tExtendedAttribute []	Array of tExtendedAttribute objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-24: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occur processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters
	EXTENDED_ATTRIBUTE_ID_INVALID	Extended Attribute ID input format is invalid. See Condition P - Invalid Extended Attributes MetaData Input Formats on page A-5.
RESULT_WARNINGS	NO_EXTENDED_ATTRIBUTE_FOUND	Occurs if any extended attribute cannot be found for the input criteria (the service will continue to process remaining criteria)

Notes

See Condition P in *Special Conditions* on page A-1. If the Extended Attribute is distinct, there will be an extra value called “Is Distinct” returned in Dynamic Tags.

Get EQ Custom Sections

Description

Use the GetEQCustomSections web service to retrieve the eQ custom section profiles for a given eQ.

Input

- 1 An eQ number and a list of custom section numbers.

Table 6-25: Input

Name	Type	Description
eqNumber	tEQNumber	An tEQNumber object
csNumbers	string []	A list of eQ custom section numbers

Output

The following eQ custom section profile data is returned for each eQ:

- EQ Number
- tExtension (Any, MustUnderstand and MustUnderstandSpecified)

Table 6-26: Output

Name	Type	Description
sections	List<tExtension>	Array of tExtension objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-27: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occur processing request

Table 6-27: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters
	INVALID_EQ_NUMBER	EQ Number input format is invalid. See Condition M - Invalid EQ Input Formats on page A-4.
	EQ_CUSTOM_SECTION_NUMBER_INVALID	EQ Custom Section Number input format is invalid. See #2 of Condition O - Invalid Custom Sections MetaData Input Formats on page A-5.
	INVALID_SECURITY_PRIVILEGES	Occurs if the API user has no read permission to eQ returned for the input criteria. See Condition N - Invalid Security Privileges on page A-4.
RESULT_WARNINGS	NO_EQ_FOUND	Occurs if any eQ cannot be found for the input criteria (the service will continue to process remaining criteria)

Notes

See Conditions M1, N1, N2, and O2 in [Special Conditions](#) on page A-1.

Get EQ Extended Attributes

Description

Use the GetEQExtendedAttributes web service to retrieve the eQ extended attribute profiles for a given list of eQs.

Input

- 1 A list of eQ Numbers.

Table 6-28: Input

Name	Type	Description
eqNumber	tEQNumber	A list of tEQNumber objects

Output

The following eQ extended attribute profile data is returned for each eQ:

- EQ Number
- tExtension (Any, MustUnderstand and MustUnderstandSpecified)

Table 6-29: Output

Name	Type	Description
extensions	tEQExtendedAttribute[]	Array of tEQExtendedAttribute objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-30: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occur processing request

Table 6-30: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters
	INVALID_EQ_NUMBER	EQ Number input format is invalid. See Condition M - Invalid EQ Input Formats on page A-4.
	INVALID_SECURITY_PRIVILEGES	Occurs if the API user has no read permission to eQ returned for the input criteria. See Condition N - Invalid Security Privileges on page A-4.
RESULT_WARNINGS	NO_EQ_FOUND	Occurs if any eQ cannot be found for the input criteria (the service will continue to process remaining criteria)

Notes

See Conditions M1, N1, and N2 in [Special Conditions](#) on page A-1.

Get Calculated Custom Section

Description

The GetCalculatedCustomSection web service provides the ability to retrieve and recalculate custom section data for a given specification with additional overridable parameters. The calculated custom section data is not preserved on the specification.

Input

- 1 A specification number or cross reference
- 2 Custom Section ID
- 3 A list of custom section column IDs
- 4 A list of custom section row IDs
- 5 A set of overridable properties to be used by calculation scripts

Table 6-31: Input

Name	Type	Description
CustomSectionID	string	A custom section ID
HostSpecificationIdentification	tSpecIdentifierCriterion	tCrossReference: cross reference of a spec tSpecificationNumber: specification number of a spec
HostContext	tSpecIdentifierCriterion	The HostContext field is currently a placeholder, and is not used
ColumnIDs	String[]	An array of column Ids that a resulting custom section will have. If not specified, no column filter will be applied.
RowIDs	String[]	An array of row Ids that a resulting custom section will have. If not specified, no row filter will be applied.
Overrides	tOverrideParameterHolder	A holder for overridable specification properties. See Input Overrides for detailed list of overridable properties.

Input Overrides

Table 6-32: Input Overrides

Name	Type	Description
NutrientItems	tNutrientItemInput[]	An array of nutrients to be overridden. If a nutrient is present on a specification, its value will be overridden if it is specified in this array.
AllergensMustContain	tComplianceItemContained[]	An array of “must contain” allergens to be overridden
AllergensMayContain	tComplianceItemContained[]	An array of “may contain” allergens to be overridden

Table 6-32: Input Overrides

AdditivesMustContain	tComplianceItemContained[]	An array of “must contain” additives to be overridden
AdditivesMayContain	tComplianceItemContained[]	An array of “may contain” additives to be overridden
SensitivitiesMustContain	tComplianceItemContained[]	An array of “must contain” sensitivities/intolerances to be overridden
SensitivitiesMayContain	tComplianceItemContained[]	An array of “may contain” sensitivities/intolerances to be overridden
ExtendedAttributes	tExtendedAttributeBase[]	An array of distinct extended attributes to be overridden. The following types can be specified: <ul style="list-style-type: none"> • tExtendedAttributeText • tExtendedAttributeDate • tExtendedAttributeNumeric • tExtendedAttributeQuantitativeRange • tExtendedAttributeQualitative • tExtendedAttributeBoolean
PercentTotalSolids	double	A decimal representation of a percent of a specification total solids
EdiblePortion	double	A decimal representation of a percent of a specification edible portion
DensityMass	tMeasurement	Mass portion of a specification density
DensityVolume	tMeasurement	Volume portion of a specification density
AmountPerServing	tMeasurement	Amount per serving of a specification
ReferencedAmount	tMeasurement	Reference amount of a specification
TareWeightRefWeight	tMeasurement	Tare weights reference weight of a specification
TareWeight	tMeasurement	Tare weight of a specification
TareWeightBase	double	Tare weight base amount of a specification

Output

The following Custom section data is returned:

- A custom section (See the GetSpecCustomSection web service output for details)
- List of resulting calculation errors

Table 6-33: Output

Name	Type	Description
CustomSectionSpecs	tCustomSectionSpec[]	Array of one custom section specification
CalculationErrors	String[]	Array of calculation errors produced by calculation process

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-34: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occur processing request
RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of <i>Condition E - Specification Identifier Input Formats</i> on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of <i>Condition E - Specification Identifier Input Formats</i> on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) format is invalid. See #2 of <i>Condition E - Specification Identifier Input Formats</i> on page A-2.
	INVALID_INPUT_CRITERIA_NUMBER	Input criteria is too broad. It has to match only one specification.
	INVALID_SECURITY_PRIVILEGES	Current user does not have access to the custom section for the given specification
	INVALID_CUSTOM_SECTION_NUMBER	Invalid custom section number
RESULT_FAILURE	UNKNOWN_SCHEMA_GENERATION_ERROR	Occurs when an unexpected exception occurs during a call of a web service

Notes

The web service provides the ability to override values on distinct extended attributes only. There is no ability to override values on a particular cell unless it holds a distinct attribute.

Although the web service calculates and returns repeatable rows, filtering around these rows is not supported, as repeatable rows cannot be uniquely identified.

The web service currently does not support custom section calculations for Theoretical Outputs.

Any additional calculations on a specification (i.e. BOM calculation, per serving calculation) that are typically done through the **Calculate** button on the UI will not be performed.

Get PQM Custom Sections

Description

Use GetPQMCustomSections web service to retrieve custom section data for PQM items.

Input

Table 6-35: Input

Name	Type	Description
PQMItemIdentifiers	tPQMItemSearchIdentifier[]	Array of one or more tPQMItemSearchIdentifier objects
CustomSectionNumbers	string[]	Array of one or more existing custom section numbers
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier

Output

Table 6-36: Output

Name	Type	Description
PQMCustomSections	tPQMCustomSection[]	Array of tPQMCustomSection objects

Each tPQMCustomSection returned will include:

- 1 PQMItemIdentifier
- 2 CustomSections - a list of tExtension objects representing custom sections in the types specified in the input belonging to the PQM item. Each tExtension contains an Any element, and the hierarchy conforms to the XML schema returned by GetCustomSectionSchema web service.

Table 6-37: tPQMCustomSection

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	
CustomSections	tExtension[]	

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-38: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER	Missing PQM item identifier or custom section number
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_ITEM_PKID	PQM item PKID input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	CUSTOM_SECTION_NUMBER_INVALID	Custom section number input is invalid
	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed
RESULT_FAILURE	CUSTOM_SECTION_RETRIEVAL_ERROR	Returned if an unexpected exception occurs while processing request
	INVALID_SECURITY_PRIVILEGES	User must have [PQM_ADMIN] role or WFA read permission to retrieve PQM item; User must meet the security access level to view the custom sections
	NO_CUSTOM_SECTION_FOUND	Custom section input not found on PQM item
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input identifier

Add PQM Custom Sections

Description

Use AddPQMCustomSections web service to add custom section data to specified PQM items.

Note When adding a custom section to PQM item, all the columns and rows in “Active” status will be added, including those without the “Add this item when section is created” tag.

Input

Table 6-39: Input

Name	Type	Description
PQMItemIdentifiers	tPQMItemSearchIdentifier[]	Array of one or more tPQMItemSearchIdentifier objects
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
CustomSectionInstances	tCustomSectionInstance[]	Array of one or more tCustomSectionInstance objects

Each tCustomSectionInstance object contains section number and a tExtension element holding the custom section data. The hierarchy under tExtension element is: tExtension/Any/<section-name>/<row_name>/<column_name>/<extended-attribute-type>/Value. The hierarchy must confront to the XML schema returned by GetCustomSectionSchema web service.

Table 6-40: tCustomSectionInstance

Name	Type	Description
CustomSectionNumber	string	
Content	tExtension	

Output

An overall success indicator and a list of tPQMItemIdentifier objects representing the PQM items changed will be returned.

If all the custom sections input are successfully added, the overall result is success. Else, the overall result is fail and the changes will not be saved.

Table 6-41: tPQMCustomSection

Name	Type	Description
IsSuccessful	boolean	
PQMItemsAffected	tPQMItemIdentifier[]	Array of one or more PQM items which have been changed

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-42: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	Missing PQM item identifier or custom section instance
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_ITEM_PKID	PQM item PKID input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	CUSTOM_SECTION_NUMBER_INVALID	Custom section number input is invalid or custom section already exists on the PQM item
	MAX_RECORDS_SAVED	Returned when the number of custom section instances input exceeds the max number allowed to save
RESULT_FAILURE	CUSTOM_SECTION_RETRIEVAL_ERROR	Returned if an unexpected exception occurs while processing request
	INVALID_SECURITY_PRIVILEGES	User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item; User also must have [ADD_CUSTOM_SECTION] role to add custom sections
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input identifier

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

User must have [ADD_CUSTOM_SECTION] role to add a custom section.

Delete PQM Custom Sections

Description

Use DeletePQMCustomSections web service to remove existing custom sections from specified PQM items.

Input

Table 6-43: Input

Name	Type	Description
PQMItemIdentifiers	tPQMItemSearchIdentifier[]	Array of one or more tPQMItemSearchIdentifier objects
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
CustomSectionNumbers	string[]	Array of one or more existing custom section numbers

Output

An overall success indicator and a list of tPQMItemIdentifier objects representing the PQM items changed will be returned.

If all the custom sections are successfully removed, the overall result is success. Otherwise the overall result is fail and the changes will not be saved.

Table 6-44: Output

Name	Type	Description
IsSuccessful	boolean	
PQMItemsAffected	tPQMItemIdentifier[]	Array of one or more PQM items which have been changed

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-45: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 6-45: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	Missing PQM item identifier or custom section number
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_ITEM_PKID	PQM item PKID input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	CUSTOM_SECTION_NUMBER_INVALID	Custom section number input is invalid
	MAX_RECORDS_SAVED	Returned when the number of custom section instances input exceeds the max number allowed to save
RESULT_FAILURE	CUSTOM_SECTION_RETRIEVAL_ERROR	Returned if an unexpected exception occurs while processing request
	INVALID_SECURITY_PRIVILEGES	User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item; User also must have [REMOVE_CUSTOM_SECTION] role to delete custom sections
	NO_CUSTOM_SECTION_FOUND	Custom section input not found on PQM item
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input identifier

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

User must have [REMOVE_CUSTOM_SECTION] role to delete a custom section.

Update PQM Custom Section

Description

Use UpdatePQMCustomSections web service to update existing custom section data of specified PQM items.

Input

Table 6-46: Input

Name	Type	Description
PQMItemIdentifiers	tPQMItemSearchIdentifier[]	Array of one or more tPQMItemSearchIdentifier objects
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
CustomSectionInstances	tCustomSectionInstance[]	Array of one or more tCustomSectionInstance objects

Each tCustomSectionInstance object contains section number and a tExtension element holding the custom section data. The hierarchy under tExtension element is: tExtension/Any/<section-name>/<row_name>/<column_name>/<extended-attribute-type>/Value. The hierarchy must confront to the XML schema returned by GetCustomSectionSchema web service.

Output

An overall success indicator and a list of tPQMItemIdentifier objects representing the PQM items changed will be returned.

If all the custom sections are updated successfully, the overall result is success. Else the overall result is fail and the changes will not be saved.

Table 6-47: Output

Name	Type	Description
IsSuccessful	boolean	
PQMItemsAffected	tPQMItemIdentifier[]	Array of one or more PQM items which have been changed

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 6-48: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	Missing PQM item identifier or custom section instance
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	CUSTOM_SECTION_NUMBER_INVALID	Custom section number input is invalid
	MAX_RECORDS_SAVED	Returned when the number of custom section instances input exceeds the max number allowed to save
RESULT_FAILURE	CUSTOM_SECTION_RETRIEVAL_ERROR	Returned if an unexpected exception occurs while processing request
	INVALID_SECURITY_PRIVILEGES	User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input identifier

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

Using the Bill of Materials Web Service

This chapter describes the Bill of Materials web service. Topics in this chapter include:

- ❑ Overview of Bill of Materials
- ❑ Get Output BOM
- ❑ Get Formulation BOM
- ❑ Get Formulation Step BOM

Overview of Bill of Materials

BillOfMaterials provide capabilities related to a formulation specification's Bill of Materials (BOM) information. The following operations are supported:

Operation	v24	v25	v30	Description
Get Output BOM on page 8-3	●	●	●	Returns the bill of materials data for a given material specification which is an output of a formulation specification.
Get Formulation BOM on page 8-8	●	●	●	Returns the bill of materials data for a given formulation specification.
Get Formulation Step BOM on page 8-11	●	●	●	Returns a list of steps, BOM inputs (including consume from step outputs), and outputs for a given formulation specification.

Service Endpoint Locations

v24 endpoint

[http://<servername>/Integration/ProdikaContracts/ Specification/Formulation /v24/ BillOfMaterialsServices.svc](http://<servername>/Integration/ProdikaContracts/Specification/Formulation/v24/BillOfMaterialsServices.svc)

v25 endpoint

[http://<servername>/Integration/ProdikaContracts/ Specification/Formulation /v25/ BillOfMaterialsServices.svc](http://<servername>/Integration/ProdikaContracts/Specification/Formulation/v25/BillOfMaterialsServices.svc)

v30 endpoint

[http://<servername>/Integration/ProdikaContracts/ Specification/Formulation /v30/ BillOfMaterialsServices.svc](http://<servername>/Integration/ProdikaContracts/Specification/Formulation/v30/BillOfMaterialsServices.svc)

Get Output BOM

Description

Use the GetOutputBOM web service to retrieve the Bill of Materials (BOM) for a given material specification which is an output of formulation specifications. The specification identifier passed in can optionally include a context (specification identifier) which limits the BOM information to a certain formulation specification by that context. If a context is not given, BOM data for all available formulation specifications containing that output will be returned.

A Boolean parameter, CombineLikeItems, is used to determine if the same formula item used in multiple steps of a formulation specification to produce the output material will be returned as one combined row, or as unique rows.

Business unit visibility will be enforceable via the standard API configuration options, but will only be used for determining visibility to the top level specification. All BOM input items will be returned, regardless of BU visibility.

Results will consist of a list of OutputItems for the matching input criteria. Each OutputItem will consist of a list of tBillOfMaterialsContainer items. tBillOfMaterialsContainer has OutSummary, InputSummary, and Context. The context is the formulation specification generating the output item. Also if an input Item A has a context (formulation specification), the input items generate item A from that formulation specification will be returned recursively.

See the [Output](#) section below for details of the data that each context specific Output specification in the result will include.

Input

- 1 Specification Identifier (specification number or cross reference)
- 2 Specification Context (specification identifier)—Optional; if used, limits the Output BOM information to the BOM data from the producing specification matching the context.
- 3 Combine Like Items (Boolean)
 - True—Combines identical formula items used in multiple steps into one.
 - False—Displays each as a unique item; does not combine.
- 4 Allow Only Approved Spec—Top level specification returned to must be in an Approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Output

Each OutputItem in the OutputItems list will include:

- 1 Specification Identifier
- 2 List of tBillOfMaterialsContainer object

Each tBillOfMaterialsContainer will include:

- 1** Context—The context for the output material is the formulation specification that produced it
- 2** Output Summary
 - Output type (string)
 - Product, By-product, Waste, or Reference
 - Beginning Batch Size (Quantity and UOM)
 - Processing Loss Factor
 - Approximate Yield (Quantity and UOM)
 - Beginning Percent Total Solids
 - Water Gain/Loss Factor
 - Final Percent Total Solids
 - Final Density (Mass and volume conversion)
- 3** Input Summary
 - Input Items —List of input items. Each Input item will include:
 - Specification Identifier
 - BOM Annotation—Not used if CombineLikeItems is True
 - Quantity Details
 - Quantity
 - UOM
 - Percent
 - Gain/Loss Factor
 - Quantity Range—Include the max and min quantities of the input when the formulation calculation path set to "Quantity Range". Not used for other calculation paths.
 - Max
 - Quantity
 - UOM
 - Min
 - Quantity
 - UOM
 - Yield Range—Include the max and min quantities of the input when the formulation calculation path is set to "Yield Range". Not used for other calculation paths.
 - Max
 - Quantity
 - UOM

- Min
 - Quantity
 - UOM
- Percent Factor Range—Include the max and min percent factors of the input when the formulation calculation path is set to "Percent Range". Not used for other calculation paths.
 - Max
 - Min
- Yield Details
 - Quantity
 - UOM
 - Percent
- Alternate Input Items—List of alternate input items. Each Alternate will consist of:
 - List of Original Spec Identifier
 - List of Substitute Material items. Each Substitute Material will include:
 - Substitute Material identifier
 - Producing Spec Context
 - Substitute Factor
 - Gain Loss Factor
 - Description
- Packaging Materials
 - Spec Identifier
 - Packaging Type
 - Units: Quantity
 - UOM
 - UOM Category
 - Scrap Factor
 - Quantity Range—Include the max and min quantities of the packaging materials when the formulation calculation path is set to "Quantity Range". Not used for other calculation paths.
 - Max
 - Quantity
 - UOM
 - Min
 - Quantity
 - UOM

- Yield Range—Include the max and min quantities of the packaging materials when the formulation calculation path is set to "Yield Range". Not used for other calculation paths.
 - Max
 - Quantity
 - UOM
 - Min
 - Quantity
 - UOM
- Percent Factor Range—Include the max and min percent factors of the packaging materials when the formulation calculation path is set to "Percent Range". Not used for other calculation paths.
 - Max
 - Min
- Alternate Packaging Materials
 - Original Material Spec Identifier
 - Substitute Material
 - Substitute Material Identifier
 - Producing Spec Content
 - Substitute Factor
 - Gain Loss Factor
 - Description

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 8-1: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 8-1: Result codes (continued)

RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is invalid. See #2 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_INPUT	A valid tBOMInputCriteria is required
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	UNSUPPORTED_SPEC_TYPE	Specification (specification number-issue number) must be a material specification
	BOM_ITEM_CALCULATION_ERROR	Occurs when an Input UOM category differs from the batch UOM category and it does not have a Density defined
RESULT_FAILURE	UNKNOWN_ERROR	Occurs when an unexpected exception happens when formatting the output items

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, and E in [Special Conditions](#) on page A-1.

Packaging Items, Alternate Packaging Items, and Alternate Input Items do not respect “CombineLikeItems”.

Get Formulation BOM

Description

Use the GetFormulationBOM web service to retrieve all the formulation outputs with their Bill of Materials (BOM) data for one or more formulation(s) specifications.

A Boolean parameter, CombineLikeItems, is used to determine if the same formula item used in multiple steps of a formulation specification to produce the output material will be returned as one combined row, or as unique rows.

Business unit visibility will be enforceable via the standard API configuration options, but will only be used for determining visibility to the top level specification. All BOM input items will be returned, regardless of BU visibility.

Results will consist of a list of formulation specifications for the matching input criteria. Each formulation specification will consist of a list of outputItems. See the [Get Output BOM](#) on page 8-3 for the details information about OutputItem.

Input

- 1 Specification Identifier (specification number or cross reference)
- 2 Combine Like Items (Boolean)
 - True —Combines identical formula items used in multiple steps into one.
 - False—Displays each as a unique item; does not combine.
- 3 Allow Only Approved Spec: Specifications returned to must be in an Approved status (see [Condition C - Allow Only Approved Spec](#) on page A-1)

Output

The following Formulation Specification data is returned for each specification:

- 1 specificationIdentifier
 - Spec # and Issue #
 - List of Cross References
- 2 Array Of tOutputItem outputItems
 - Specification Identifier
 - List of tBillOfMaterialsContainer object
 - OutputSummary
 - Context—Formulation specification
 - Output Summary
 - Output type (string): combination of Product, By-product, Waste, or Reference
 - Beginning Batch Size (quantity & UOM)
 - Processing Loss Factor

- Approximate Yield (quantity & UOM)
- Beginning Percent Total Solids
- Water Gain/Loss Factor
- Min/Max Formula Values
- Final Percent Total Solids
- Final Density (mass & volume conversion)
- InputSummary
 - Array of tInputItems: Input Item
 - Specification Identifier
 - BOM Annotation-Not used if CombineLikeItems is True
 - Quantity Details
 - Quantity
 - UOM
 - Percent
 - Gain/Loss Factor
 - Yield Details
 - Quantity
 - UOM
 - Percent
 - Array of tAlternateInputItems: Alternate Input
 - List of Original Spec Identifier
 - List of Substitute Material items.
 - Substitute Material identifier
 - Producing Spec Context—Not used
 - Substitute Factor
 - Gain/Loss Factor
 - Description
 - Array of tBOMPackagingMaterials: Packaging Material
 - Specification Identifier
 - UOM
 - UOMCategory
 - PackagingType
 - ScrapFactor
 - Units: Quantity
 - Array of tAlternateInputItems: Alternate Packaging Material
 - List of Original Spec Identifier
 - List of Substitute Material items

- Substitute Material identifier
 - Producing Spec Context (not used pre 6.0)
 - Substitute Factor
 - Gain Lost Factor
- Description

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 8-2: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is invalid. See #2 of Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	SPEC_SUMMARY_RETRIEVAL_ERROR	Occurs when an unexpected exception occurs loading a specification

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, and E in [Special Conditions](#) on page A-1.

Packaging Items, Alternate Packaging Items, and Alternate Input Items do not respect “CombineLikeItems”.

Get Formulation Step BOM

Description

Use the GetFormulationStepBOM to retrieve a list of steps, BOM inputs (including consume from step outputs), and outputs.

Input

- 1 A list of specification numbers, cross references, or a combination of either
- 2 Allow Only Approved Spec—Specifications returned to must be in an Approved status

Table 8-3: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	<ul style="list-style-type: none"> • True: Specifications returned to must be in an Approved status • False: Specifications returned may be in any status

Output

The following Specification Step data is returned for each spec:

- 1 Step Details
 - Step PKID—System generated unique identifier for the Step
 - Step Number
 - Step Name
 - Step Instructions
- 2 Step Behavior
 - Behavior Type
 - Behavior Name

Table 8-4: Output

Name	Type	Description
FormulationSteps	tFormulationStep []	Array of tFormulationStep objects

The following Input BOM data is returned for each Input BOM item/Step combination. In other words if an item was used in three separate steps, it should be represented in three rows, with the step differentiating between them. The items include 'consume from step' items, which are outputs from other steps that are used as inputs.

- PKID for Line—System generated unique identifier for the row

- Spec Identifier
 - Spec Number—Including Spec Number and Issue Number
 - Cross References
 - Spec PKID
 - Spec Name
- Step Number—The step for the BOM input. If the input item is used in multiple steps then there should be multiple rows.
- Sequence Number—The order in which is used to sort on the UI
- BOM Annotation—Inline comments of the BOM input
- %Batch
- Quantity Details
 - Quantity
 - Quantity UOM
 - Quantity in the base mass UOM—Value that it is stored in
 - Quantity in the base volume UOM—Value that it is stored in. Only available if density is defined.
- Gain/Loss
- Yield Details
 - Yield
 - Yield UOM
 - Yield in the base mass UOM
 - Yield in the base volume UOM
- Extended Cost

The values below should be taken from the Material Basis if they exist, if not then from the Material itself.

- Spec Number
- Spec Issue
- Spec Name
- Total Solids
- Density Details
 - Density Quantity (mass)
 - Density Quantity UOM (mass)
 - Density Quantity (volume)
 - Density Quantity UOM (volume)
 - Density Quantity in base mass
 - Density Quantity in base volume
- Cost—Including Price (double), Currency (string), and PerValue (tMeasurement)

Table 8-5: Input Items

Name	Type	Description
InputItems	tSpecificationBOMInputWrapper []	Array of tSpecificationBOMInputWrapper objects

The following are the outputs and their associated input and output steps:

- PKID for Line—System generated unique identifier for the row
- Spec Identifier
 - Spec Number—Including Spec Number and Issue Number
 - Cross References
 - Spec PKID
 - Spec Name
- Output Step Number
- Input Step Number—If the output is used as an input, this represents the step number
- Sequence Number—The order in which is used to sort on the UI
- Quantity Details
 - Quantity
 - Quantity UOM
 - Quantity in the base mass UOM—Value that it is stored in.
 - Quantity in the base volume UOM—Value that it is stored in. Only available if density is defined.
- Yield Details
 - Yield
 - Yield UOM
 - Yield in the base mass UOM
 - Yield in the base volume UOM
- Output Type—Internal, External, Referenced

The Below values should be taken from the material itself:

- Spec Number
- Spec Issue
- Spec Name
- Process Gain/Loss
- Water Gain/Loss
- Total Solids
- Density Details
 - Density Quantity (mass)

- Density Quantity UOM(mass)
- Density Quantity (volume)
- Density Quantity UOM (volume)
- Density Quantity in base mass
- Density Quantity in base volume

Table 8-6: Output Items

Name	Type	Description
OutputItems	tSpecificationBOMOutputWrapper [Array of tSpecificationBOMOutputWrapper objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 8-7: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number, issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	NO_SPEC_FOUND	Occurs if any specification cannot be found for the input criteria (the service will continue to process remaining criteria).
RESULT_FAILURE	SPEC_SUMMARY_RETRIEVAL_ERROR	Occurs when an unexpected exception occurs loading a specification

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, and E in [Special Conditions](#) on page A-1.

Using the Spec Relationship Services

This chapter describes the Spec Relationship web service. The operations contained herein were once contained in the GeneralServices - GetSpecRelationships web service, and are now broken out into individual operations for each specification type. Topics in this chapter include:

- ❑ *Overview of Spec Relationship Services*
- ❑ *Get Formulation Relationships*
- ❑ *Get Material Relationships*
- ❑ *Get Menu Item Relationships*
- ❑ *Get Nutrient Profile Relationships*
- ❑ *Get Packaging Relationships*
- ❑ *Get Printed Packaging Relationships*
- ❑ *Get Product Relationships*
- ❑ *Get Trade Spec Relationships*

Overview of Spec Relationship Services

SpecRelationship Services provides operations that describe a specification's relationship to other specifications. Specification identifiers are returned for each relationship, and in some cases, contextual information such as quantities, units of measure, and relationships. The following operations are supported:

Operation	Description
Get Formulation Relationships on page 9-3	Returns given formulation specifications' relationships to GSM activities, master specifications, and owned and linked associated specifications.
Get Material Relationships on page 9-5	Returns given material specifications' relationships to packing configuration specifications, parent trade specifications, parent formulation specifications, GSM activities, master specifications, and owned and linked associated specifications.
Get Menu Item Relationships on page 9-8	Returns given menu item specifications' relationships to packaging materials, alternate packaging materials, menu item build items, alternate menu item build items, nutrient profiles, GSM activities, and owned and linked associated specifications.
Get Nutrient Profile Relationships on page 9-11	Returns given nutrient profiles' relationships to various related specifications and GSM activities.

Operation	Description
Get Packaging Relationships on page 9-13	Returns given packaging specifications' relationships to printed packaging specifications, sub components, packing configurations specifications, equipment specifications, GSM activities, and master specifications.
Get Printed Packaging Relationships on page 9-15	Returns given printed packaging specifications' relationships to parent packaging specifications, GSM activities, and master specifications.
Get Product Relationships on page 9-17	Returns given product specifications' relationships to packing configuration specifications, GSM activities, master specifications, and owned and linked associated specifications.
Get Trade Spec Relationships on page 9-19	Returns given trade specifications' relationships to parent trade specifications, next lower level trade specifications, packaging specifications, printed packaging specifications, the related material specification, nutrient profiles, GSM activities, master specifications, and owned and linked associated specifications.

Service Endpoint Locations

v24 endpoint

<http://<servername>/Integration/ProdikaContracts/Specification/Common/v24/SpecRelationshipServices.svc>

v25 endpoint

<http://<servername>/Integration/ProdikaContracts/Specification/Common/v25/SpecRelationshipServices.svc>

v25 endpoint

<http://<servername>/Integration/ProdikaContracts/Specification/Common/v30/SpecRelationshipServices.svc>

Get Formulation Relationships

Description

Use the GetFormulationRelationships web service to retrieve related specification information for a given formulation specification. The service returns given formulation specifications' relationships to GSM activities, master specifications, and owned and linked associated specifications.

Detailed Bill of Material Inputs and Outputs information is available in [Using the Bill of Materials Web Service](#) on page 8-1.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 9-1: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following specification data is returned:

- 1 Specification Identifier
 - Specification Number
 - Cross References
- 2 GSM Activities
 - Activity Type
 - Description
 - Status
 - Relationship
- 3 Explicit Master Specs
 - Specification Identifier (specification number, cross references)
- 4 Owned Associated Specifications
 - Specification Identifier (specification number, cross references)
 - Association
 - Comments
- 5 Linked Associated Specifications
 - Specification Identifier (specification number, cross references)

- Association
- Comments

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 9-2: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	UNSUPPORTED_SPEC_TYPE	A specification type used as input is not supported
RESULT_FAILURE	SPEC_LOAD_ERROR	Occurs when an unexpected exception occurs when loading a specification
	UNKNOWN_ERROR	Occurs when an unexpected exception happens when formatting the output items

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get Material Relationships

Description

Use the GetMaterialRelationships web service to retrieve related specification information for a given material specification. Returns given material specifications' relationships to packing configuration specifications, parent trade specifications, parent formulation specifications, GSM activities, master specifications, and owned and linked associated specifications.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 9-3: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following specification data is returned:

- 1 Specification Identifier
 - Specification Number
 - Cross References
- 2 Packing Configuration Specifications
 - Specification Identifier (specification number, cross references)
 - Comments
 - Equivalent
- 3 Parent Trade Specifications
 - Specification Identifier (specification number, cross references)
 - Context Specification Identifier
- 4 Parent Formulation Specifications
 - Specification Identifier (specification number, cross references)
- 5 GSM Activities
 - Activity Type
 - Description
 - Status
 - Relationship

- 6** Explicit Master Specifications
 - Specification Identifier (specification number, cross references)
- 7** Owned Associated Specifications
 - Specification Identifier (specification number, cross references)
 - Association
 - Comments
- 8** Linked Associated Specifications
 - Specification Identifier (specification number, cross references)
 - Association
 - Comments

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 9-4: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is invalid. See Condition E - Specification Identifier Input Formats on page A-2.

Table 9-4: Result codes (continued)

RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	UNSUPPORTED_SPEC_TYPE	A specification type used as input is not supported
RESULT_FAILURE	SPEC_LOAD_ERROR	Occurs when an unexpected exception occurs when loading a specification
	UNKNOWN_ERROR	Occurs when an unexpected exception happens when formatting the output items

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get Menu Item Relationships

Description

Use the GetMenuItemRelationships web service to retrieve related specification information for a given menu item specification. The service returns given menu item specifications' relationships to packaging materials, alternate packaging materials, menu item build items, alternate menu item build items, nutrient profiles, GSM activities, and owned and linked associated specifications.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 9-5: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following specification data is returned:

- 1 Specification Identifier
 - Specification Number
 - Cross References
- 2 Packaging Materials
 - Specification Type (packaging, printed packaging)
 - Specification Identifier (specification number, cross references)
 - Packaging Type (Inner, Intermediate, Outer, Label)
 - Units
 - UOM
 - Scrap Factor
- 3 Alternate Packaging Materials
 - Specification Type (packaging, printed packaging)
 - Specification Identifier (specification number, cross references)
 - Packaging Type (Inner, Intermediate, Outer, Label)
 - Units
 - UOM
 - Scrap Factor
 - Substitutes

- 4** Menu Item Build Items
 - Specification Identifier (specification number, cross references)
 - Quantity
 - UOM
 - Comments
- 5** Alternate Menu Item Build Items
 - Specification Identifier (specification number, cross references)
 - Original Spec Identifier
 - Substitution Factor
 - Description
- 6** Nutrient Profiles
 - Specification Identifier (specification number, cross references)
 - IsActive
 - EffectiveDate
 - Status
- 7** GSM Activities
 - Activity Type
 - Description
 - Status
 - Relationship
- 8** Owned Associated Specifications
 - Specification Identifier (specification number, cross references)
 - Association
 - Comments
- 9** Linked Associated Specifications
 - Specification Identifier (specification number, cross references)
 - Association
 - Comments

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 9-6: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See #2 of Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	UNSUPPORTED_SPEC_TYPE	A specification type used as input is not supported
RESULT_FAILURE	SPEC_LOAD_ERROR	Occurs when an unexpected exception occurs when loading a specification
	UNKNOWN_ERROR	Occurs when an unexpected exception happens when formatting the output items

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get Nutrient Profile Relationships

Description

Use the GetNutrientProfileRelationships web service to retrieve related specification information for a given nutrient profile specification. This service returns given Nutrient Profile(s) relationships to various related specifications and GSM activities.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 9-7: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following specification data is returned:

- 1 Specification Identifier
 - Specification Number
 - Cross References
- 2 Related Specifications
 - Specification Identifier (specification number, cross references)
 - Specification Type
- 3 GSM Activities
 - Activity Type
 - Description
 - Status
 - Relationship

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 9-8: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	UNSUPPORTED_SPEC_TYPE	A specification type used as input is not supported
RESULT_FAILURE	SPEC_LOAD_ERROR	Occurs when an unexpected exception occurs when loading a specification
	UNKNOWN_ERROR	Occurs when an unexpected exception happens when formatting the output items

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get Packaging Relationships

Description

Use the GetPackagingRelationships web service to retrieve related specification information for a given packaging specification. This service returns given packaging specifications' relationships to printed packaging specifications, sub components, packing configurations specifications, equipment specifications, GSM activities, and master specifications.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 9-9: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following specification data is returned:

- 1 Specification Identifier
 - Specification Number
 - Cross References
- 2 Printed Packaging Specifications
 - Specification Identifier (specification number, cross references)
- 3 Sub Components
 - Specification Identifier (specification number, cross references)
 - Packaging Type (Inner, Intermediate, Outer, Label)
 - Units
 - UOM
- 4 Packing Configuration Specifications
 - Specification Identifier (specification number, cross references)
 - Equivalent
 - Comments
- 5 Equipment Specifications
 - Specification Identifier (specification number, cross references)
- 6 Explicit Master Specifications
 - Specification Identifier (specification number, cross references)

- 7 GSM Activities
- Activity Type
 - Description
 - Status
 - Relationship

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 9-10: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See #2 of Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	UNSUPPORTED_SPEC_TYPE	A specification type used as input is not supported
RESULT_FAILURE	SPEC_LOAD_ERROR	Occurs when an unexpected exception occurs when loading a specification
	UNKNOWN_ERROR	Unknown exception occurs while retrieving specification relationships

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get Printed Packaging Relationships

Description

Use the GetPrintedPackagingRelationships web service to retrieve related specification information for a given printed packaging specification. The service returns given printed packaging specifications' relationships to parent packaging specifications, GSM activities, and master specifications.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 9-11: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following specification data is returned:

- 1 Specification Identifier
 - Specification Number
 - Cross References
- 2 Parent Packaging Material Specifications
 - Specification Identifier (specification number, cross references)
- 3 Explicit Master Specs
 - Specification Identifier (specification number, cross references)
- 4 GSM Activities
 - Activity Type
 - Description
 - Status
 - Relationship

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 9-12: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See #2 of Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	UNSUPPORTED_SPEC_TYPE	A specification type used as input is not supported
RESULT_FAILURE	SPEC_LOAD_ERROR	Occurs when an unexpected exception occurs when loading a specification
	UNKNOWN_ERROR	Unknown exception occurs while retrieving specification relationships

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get Product Relationships

Description

Use the GetProductRelationships web service to retrieve related specification information for a given product specification. The service returns given product specifications' relationships to packing configuration specifications, GSM activities, master specifications, and owned and linked associated specifications.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 9-13: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following specification data is returned:

- 1 Specification Identifier
 - Specification Number
 - Cross References
- 2 Packing Configuration Specifications
 - Specification Identifier (specification number, cross references)
 - Comments
 - Equivalent
- 3 GSM Activities
 - Activity Type
 - Description
 - Status
 - Relationship
- 4 Explicit Master Specifications
 - Specification Identifier (specification number, cross references)
- 5 Owned Associated Specifications
 - Specification Identifier (specification number, cross references)
 - Association
 - Comments

6 Linked Associated Specifications

- Specification Identifier (specification number, cross references)
- Association
- Comments

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 9-14: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See #2 of Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	UNSUPPORTED_SPEC_TYPE	A specification type used as input is not supported
RESULT_FAILURE	SPEC_LOAD_ERROR	Occurs when an unexpected exception occurs when loading a specification
	UNKNOWN_ERROR	Unknown exception occurs while retrieving specification relationships

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get Trade Spec Relationships

Description

Use the GetTradeSpecRelationships web service to retrieve related specification information for a given trade specification. The service returns given trade specifications' relationships to parent trade specifications, next lower level trade specifications, packaging specifications, printed packaging specifications, the related material specification, nutrient profiles, GSM activities, master specifications, and owned and linked associated specifications.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 9-15: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following specification data is returned:

- 1 Specification Identifier
 - Specification Number
 - Cross References
- 2 Trade Parent Trade Items
 - Specification Identifier (specification number, cross references)
 - GTIN/UPC/EAN
- 3 Trade Child Trade Items
 - Specification Identifier (specification number, cross references)
 - GTIN/UPC/EAN
 - Quantity
- 4 Packaging Materials
 - Specification Identifier (specification number, cross references)
 - SpecType (packaging, printed packaging)
 - Packaging Type (Inner, Intermediate, Outer, Label)
 - Units
 - UOM
 - Scrap Factor

- 5** Alternate Packaging Materials
 - Specification Identifier (specification number, cross references)
 - Packaging Type (Inner, Intermediate, Outer, Label)
 - Units
 - UOM
 - Scrap Factor
 - Substitutes For
 - Spec Type (packaging, printed packaging)
- 6** Material Specification
 - Specification Identifier (specification number, cross references)
 - Context Specification Identifier
 - Quantity
 - UOM
- 7** Nutrient Profiles
 - Specification Identifier (specification number, cross references)
 - IsActive
 - EffectiveDate
 - Status
- 8** GSM Activities
 - Activity Type
 - Description
 - Status
 - Relationship
- 9** Explicit Master Specs
 - Specification Identifier (specification number, cross references)
- 10** Owned Associated Specifications
 - Specification Identifier (specification number, cross references)
 - Association
 - Comments
- 11** Linked Associated Specifications
 - Specification Identifier (specification number, cross references)
 - Association
 - Comments

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 9-16: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid request parameters
	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See #2 of Condition E - Specification Identifier Input Formats on page A-2.
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
	UNSUPPORTED_SPEC_TYPE	A specification type used as input is not supported
RESULT_FAILURE	SPEC_LOAD_ERROR	Occurs when an unexpected exception occurs when loading a specification
	UNKNOWN_ERROR	Unknown exception occurs while retrieving specification relationships

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Using the Specification Services Web Services

This chapter describes the Specification Services web service. Topics in this chapter include:

- ❑ Overview of Specification Services
- ❑ Get Activity
- ❑ Get Spec Ingredient Statements

Overview of Specification Services

SpecificationServices provides specific operations that act on individual specification types. The following operations are supported:

Operation	Description
Get Activity on page 10-2	Returns the primary and related activity specifications for a given list of specifications.
Get Spec Ingredient Statements on page 10-4	Returns ingredient statement information for a given list of (ingredient, product, and nutrient profile) specifications.

Service Endpoint Locations

v24 endpoint

`http://<servername>/Integration/ProdikaContracts/Specification/v24/SpecificationServices.svc`

v25 endpoint

`http://<servername>/Integration/ProdikaContracts/Specification/v25/SpecificationServices.svc`

v30 endpoint

`http://<servername>/Integration/ProdikaContracts/Specification/v30/SpecificationServices.svc`

Get Activity

Description

Use the GetActivity web service to retrieve activity info for a given list of activity specifications or for associated activities for a given list of specifications.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 10-1: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following activity data is returned for each activity:

- 1 Activity Summary Information
 - Activity Title
 - Activity # (Spec #-Issue #)
 - Activity Type (ID, Name)
 - Originator
 - Status
 - Special Notes
 - Spec Reader Notification Flag
 - Effective Date
 - Inactive Date
 - Last Edit Date
- 2 Primary Action Item Information
 - Primary Item Name
 - Primary Item # (Spec #-Issue #)
 - Item Status Dependent flag
- 3 Related Items information
 - Specification Type (ID, Name)
 - Related Item Name
 - Related Item (Spec #-Issue #)

- Status
- Comments

Table 10-2: Output

Name	Type	Description
ActivityInfos	tActivitySpecContainer []	Array of tActivitySpecContainer objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 10-3: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See #2 of Condition E - Specification Identifier Input Formats on page A-2.
	NOT_ENOUGH_PRIVILEGES	Occurs only when API user has no read permission to any specification qualified for the input criteria
	NO_SPEC_FOUND	Occurs if any specification cannot be found for the input criteria
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E, and F in [Special Conditions](#) on page A-1.

Get Spec Ingredient Statements

Description

Use the GetSpecIngredientStatements web service to retrieve the ingredient statements for a given list of specifications.

Note This service is only supported for material specifications, product specifications, and nutrient profiles as defined in [Condition D - Specification Types](#) on page A-2.

Input

- 1 A list of specification numbers, cross references, or a combination of either.
- 2 Allow Only Approved Spec—Specifications returned must be in an approved status. See [Condition C - Allow Only Approved Spec](#) on page A-1.

Table 10-4: Input

Name	Type	Description
specIdentifierCriterion	tSpecIdentifierCriterion[]	Array of one or more tSpecIdentifierCriterion objects
AllowOnlyApprovedSpec	boolean	True—Specifications returned must be in an “Approved” status False—Specifications returned may be in any status

Output

The following specification ingredient statements are returned for each supported specification:

- 1 Specification Identifier
 - Specification Number
 - Cross References
- 2 Ingredient statement
- 3 Combined statement

Table 10-5: Output

Name	Type	Description
SpecIngredientStatement Infos	tSpecIngredientStatement Info []	Array of tSpecIngredientStatementInfo objects

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 10-6: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_ISSUE_NUMBER	Issue input (issue number) format is invalid. See #1 of Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See #2 of Condition E - Specification Identifier Input Formats on page A-2.
	NOT_ENOUGH_PRIVILEGES	Occurs only when API user has no read permission to any specification qualified for the input criteria
	NO_SPEC_FOUND	Occurs if any specification cannot be found for the input criteria
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.

Notes

See Conditions A.1, A.2, B.1, C.1, C.2, E and F in [Special Conditions](#) on page A-1.

Using the EQ Services Web Services

This chapter describes the EQ Services web service. Topics in this chapter include:

- ❑ *Overview of EQServices*
- ❑ *Get EQ Compliance Items*
- ❑ *Get EQ Summary Info*
- ❑ *Get EQ Nutrition Info*
- ❑ *Get EQ Breakdown Info*
- ❑ *Get EQ Numbers For Criteria*

Overview of EQServices

EQServices provides operations that act on EQ items. The following operations are supported:

Operation	Description
Get EQ Compliance Items on page 11-2	Returns compliance data for a given list of EQs
Get EQ Summary Info on page 11-4	Returns the EQ summary information for a given list of EQs
Get EQ Nutrition Info on page 11-6	Returns the Nutrient Items for a given list of EQs
Get EQ Breakdown Info on page 11-8	Returns percent breakdown information for a given list of EQs
Get EQ Numbers For Criteria on page 11-10	Returns the EQ identifiers for EQs matching several input search criteria

Service Endpoint Locations

v24 endpoint

`http://<servername>/Integration/ProdikaContracts/EQ/v24/EQServices.svc`

v25 endpoint

`http://<servername>/Integration/ProdikaContracts/EQ/v25/EQServices.svc`

v30 endpoint

http://<servername>/Integration/ProdikaContracts/EQ/v30/EQServices.svc

Get EQ Compliance Items

Description

Use the GetEQComplianceItems web service to retrieve the EQ compliance for a given EQ. This service can be used for material, product, and trade questionnaire types.

Input

- 1 EQ number list

Table 11-1: Input

Name	Type	Description
eqNumbers	tEQNumber[]	An tEQNumber object

Output

The following EQ compliance data is returned for each EQ:

- 1 Questionnaire Number
- 2 Compliance values (Allergens, Additives, Intolerances (know to contain, does not contain))

Table 11-2: Output

Name	Type	Description
eqComplianceInfo	tEQComplianceInfo	EQ compliance details

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 11-3: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters
	INVALID_EQ_NUMBER	EQ Number input format is invalid. See Condition M - Invalid EQ Input Formats on page A-4.
	INVALID_SECURITY_PRIVILEGES	If the API user has no read permission to EQ returned for the input criteria. See Condition N - Invalid Security Privileges on page A-4.
	NO_EQ_FOUND	Occurs if any EQ cannot be found for the input criteria (the service will continue to process remaining criteria)

Notes

See Conditions M1, N1, and N2 in [Special Conditions](#) on page A-1.

Get EQ Summary Info

Description

Use the GetEQSummaryInfo web service to retrieve the EQ summary for a given EQ. This service can be used for all available eQ types (material, product, printed packaging, packaging, and trade).

Input

- 1 EQ number list

Table 11-4: Input

Name	Type	Description
eqNumbers	tEQNumber[]	A tEQNumber object

Output

The following EQ summary data is returned for each EQ:

- Questionnaire Number
- Questionnaire Label
- Questionnaire Type
- Status
- Date Sent
- Due Date
- Date Received
- Supplier Initiated?
- Imported?
- Comments
- Primary Owner
- Additional Administrators
- Supplier Contact Information (Contact Name, Company Name, Prodika SCRM #, email address)
- Company Contact Information (Contact Name, email address)
- Material Name

Table 11-5: Output

Name	Type	Description
EQSummaryInfo	tEQSummaryInfo[]	EQ summary details

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 11-6: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters
	INVALID_EQ_NUMBER	EQ Number input format is invalid. See Condition M - Invalid EQ Input Formats on page A-4.
	INVALID_SECURITY_PRIVILEGES	If the API user has no read permission to EQ returned for the input criteria. See Condition N - Invalid Security Privileges on page A-4.
	NO_EQ_FOUND	Occurs if any EQ cannot be found for the input criteria (the service will continue to process remaining criteria)

Notes

See Conditions M1, N1, and N2 in [Special Conditions](#) on page A-1.

Get EQ Nutrition Info

Description

Use the GetEQNutritionInfo web service to retrieve the EQ nutrition for a given EQ. This service can be used for material, product, and trade questionnaire types.

Input

- 1 EQ number list

Table 11-7: Input

Name	Type	Description
eqNumbers	tEQNumber[]	A tEQNumber object

Output

The following EQ nutrition data is returned for each EQ:

- 1 Questionnaire Number
- 2 Nutrient Values

Table 11-8: Output

Name	Type	Description
NutrientInfo	tNutrientInfo[]	EQ nutrient details

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 11-9: Result codes

Message Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 11-9: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters
	INVALID_EQ_NUMBER	EQ Number input format is invalid. See Condition M - Invalid EQ Input Formats on page A-4.
	INVALID_SECURITY_PRIVILEGES	If the API user has no read permission to EQ returned for the input criteria. See Condition N - Invalid Security Privileges on page A-4.
	NO_EQ_FOUND	Occurs if any EQ cannot be found for the input criteria (the service will continue to process remaining criteria)

Notes

See Conditions M1, N1, and N2 in [Special Conditions](#) on page A-1.

Get EQ Breakdown Info

Description

Use the GetEQBreakdownInfo web service to retrieve the EQ breakdown for a given EQ. This service can be used for material, product, and trade questionnaire types.

Input

- 1 EQ number list

Table 11-10: Input

Name	Type	Description
eqNumbers	tEQNumber[]	A tEQNumber object

Output

The following EQ breakdown data is returned for each EQ:

- 1 Questionnaire Number
- 2 Breakdown Message

Table 11-11: Output

Name	Type	Description
EQFormulaBreakdown	tEQFormulaBreakdown[]	EQ breakdown details

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 11-12: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 11-12: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters
	INVALID_EQ_NUMBER	EQ Number input format is invalid. See Condition M - Invalid EQ Input Formats on page A-4.
	INVALID_SECURITY_PRIVILEGES	If the API user has no read permission to EQ returned for the input criteria. See Condition N - Invalid Security Privileges on page A-4.
	NO_EQ_FOUND	Occurs if any EQ cannot be found for the input criteria (the service will continue to process remaining criteria)

Notes

See Conditions M1, N1, and N2 in [Special Conditions](#) on page A-1.

Get EQ Numbers For Criteria

Description

Use the GetEQByCriteria web service to retrieve the EQ numbers for a given EQ. This service can be used for all available eQ types (material, product, printed packaging, packaging, and trade).

Input

The following input criteria are available as search criteria:

Table 11-13: Input

Name	Type	Description
eqInputCriteria	tEQInputCriteria	EQ input criteria

Output

The following EQ number data is returned for each EQ:

- 1 Questionnaire Number
- 2 EQ Types ID—Restricts results to questionnaire types in given list of questionnaire types

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 11-14: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 11-14: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	No valid parameters
	INVALID_EQ_NUMBER	EQ Number input format is invalid. See Condition M - Invalid EQ Input Formats on page A-4.
	INVALID_SECURITY_PRIVILEGES	If the API user has no read permission to EQ returned for the input criteria. See Condition N - Invalid Security Privileges on page A-4.
	NO_EQ_FOUND	Occurs if any EQ cannot be found for the input criteria (the service will continue to process remaining criteria)
	INVALID_EQ_STATUS	EQ status must be New, Sent, In Progress, Submitted
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.

Notes

See Conditions F1, M1, N1, and N2 in [Special Conditions](#) on page A-1.

Using the PQS Services Web Services

This chapter describes the PQS Services web service. Topics in this chapter include:

- *Overview of PQSServices*
 - *Save PQS Sample*
-

Overview of PQSServices

PQSServices provides operations that act on PQS lot samples. The following operations are supported:

Operation	Description
Save PQS Sample on page 12-2	Creates PQS lot samples and returns a sample number for each new sample created

Service Endpoint Locations

v24 endpoint

http://<servername>/Integration/ProdikaContracts/PQS/v24/PQSServices.svc

v25 endpoint

http://<servername>/Integration/ProdikaContracts/PQS/v25/PQSServices.svc

v30 endpoint

http://<servername>/Integration/ProdikaContracts/PQS/v30/PQSServices.svc

Save PQS Sample

Description

Use the SavePqsSamples web service to import new PQS lot sample entries into PQS. Lot sample data includes the associated GSM specification, SCRM facilities (Source, Receiving, and Location Facilities), PQS sample type, and more.

Results of the web service call include an overall success indicator and a list of all lot samples that have been created. Each lot sample contains a system-generated SampleNumber and the specification used as input.

Input

- 1** Specification—SpecIdentifierCriterion. It can be SpecNumber or IssueNumber.
 - a** Specification Number
 - SpecNumber—Required, must be seven digits. Specification names matching the entry are displayed to the right of the field.
 - IssueNumber—Required, must be three digits. IssueNumber should match SpecNumber entry.
- 2** SourceFacility—SCRMEntityIdentifier
 - a** SCRMEntityNumber
 - EntityNumber—String, seven digits, facility or company number. Company/Facility name matching the entry are displayed to the right of the field.
- 3** ReceivingFacility—SCRMEntityIdentifier
- 4** SampleType—String, 32 characters or fewer
- 5** Location—SCRMEntityIdentifier
- 6** InternalAlias—String, 15 characters or fewer
- 7** CodeDate—String, 35 characters or fewer
- 8** GTINUPCEAN—String, 14 characters or fewer
- 9** ManufactureDate—Datetime
- 10** Use-ThroughDate—Datetime
- 11** LogReceiving#—String, 20 characters or fewer
- 12** WaybillInvoice#—String, 20 characters or fewer
- 13** Quantity—Float
- 14** QuantityLookup—String, 150 characters or fewer
- 15** Temperature—Float
- 16** ReceivingCondition—String, 400 characters or fewer
- 17** DateReceived—Datetime
- 18** ScheduledEvaluation—Datetime
- 19** Notes—String, 1024 characters or fewer

Output

The result will be an overall success indicator with a list of all lot samples that have been created.

- 1 IsSuccessful—True or False
- 2 Results—List of lot sample result objects. Each sample provides a system generated Sample#.
 - a Sample#—System generated number for the lot samples
 - b Specification Identifier—SpecNumber used as input to assign to the lot samples, along with any related cross references

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 12-1: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 12-1: Result codes

RESULT_INVALID_INPUT	INVALID_SPEC_NUMBER	Specification number input (specification number, issue number) format is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_SPEC_TYPE	Specification should be of type Material, Menu, Product, or Trade
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_SOURCE_FACILITY	SCRM source facility input invalid: input format is invalid, facility is not found, or more than one facility is found
	INVALID_RECEIVING_FACILITY	SCRM receiving facility input invalid: input format is invalid, facility is not found, or more than one facility is found
	INVALID_SAMPLETYPE	Sample type input invalid: <ul style="list-style-type: none"> • Must be 15 alphanumeric characters or fewer • Must be an existing Sample Type lookup value
	INVALID_LOCATION	SCRM location facility input invalid: input format is invalid, facility is not found, or more than one facility is found
	INVALID_INTERNAL_ALIAS	Internal alias input is invalid; must be 15 alphanumeric characters or fewer
	INVALID_CODE_DATE	Code date input is invalid; must be 35 alphanumeric characters or fewer
	INVALID_GTINUPCEAN	GTIN/UPC/EAN input is invalid; must be 14 alphanumeric characters or fewer

Table 12-1: Result codes

	INVALID_LOG_RECEIVING_NUMBER	LogReceiving# input invalid; must be 20 alphanumeric characters or fewer
	INVALID_WAYBILL_INVOICE_NUMBER	WaybillInvoice# input invalid; must be 20 alphanumeric characters or fewer
	INVALID_QUANTITY	<ul style="list-style-type: none"> Quantity value must be greater than 0 Quantity is required when a Quantity UOM is specified Quantity UOM is required when a Quantity is specified
	INVALID_QUANTITY_LOOKUP	Quantity Lookup input invalid; must be 150 alphanumeric characters or fewer, or no PQS Quantity Lookup value is found for given input
	INVALID_TEMPERATURE	Temperature input invalid; temperature UOM must be Celsius or Fahrenheit (ISOCode value CE or FA)
	INVALID_UOM	Valid UOM format required, or UOM not found for given input data
	INVALID_UOM_STATUS	UOM must be in an assignable status
	INVALID_RECEIVING_CONDITION	ReceivingCondition input invalid; must be 400 alphanumeric characters or fewer
	INVALID_NOTES	Notes input invalid; must be 1024 alphanumeric characters or fewer
	NO_SPEC_FOUND	No specification found for specification identifier or specification cross reference
	NOT_ENOUGH_PRIVILEGES	User does not have permissions to add PQS samples. Doing so requires the [PQS_SAMPLE_CREATOR] role.
	UNKNOWN_ERROR	Unknown error retrieving SCRM facility information
RESULT_FAILURE	SAVE_ERROR	Unexpected error occurred attempting to save PQS samples

Notes

See Conditions A, C, E, G, and L in *Special Conditions* on page A-1.

Using the PQM Services Web Services

This chapter describes the PQM Services web service. Topics in this chapter include:

- ❑ *Overview of PQMServices*
- ❑ *Get PQM Summary*
- ❑ *Create PQM Issues*
- ❑ *Update PQM Issues*
- ❑ *Create PQM Actions*
- ❑ *Update PQM Actions*
- ❑ *Create PQM Audits*
- ❑ *Update PQM Audits*
- ❑ *Get Suppliers*
- ❑ *Add Suppliers*
- ❑ *Delete Suppliers*
- ❑ *Get Affected Items*
- ❑ *Add Affected Items*
- ❑ *Delete Affected Items*
- ❑ *Get PQM Item By Criteria*
- ❑ *Get Related Items*
- ❑ *Add Related Items*
- ❑ *Delete Related Items*
- ❑ *Get Supporting Document IDs*
- ❑ *Get URL Supporting Document*
- ❑ *Add URL Supporting Documents*
- ❑ *Delete URL Supporting Documents*
- ❑ *Add Supporting Document Attachment*
- ❑ *Delete Supporting Document Attachment*
- ❑ *Get Rich Text Supporting Document*
- ❑ *Add Rich Text Supporting Document*
- ❑ *Delete Rich Text Supporting Documents*
- ❑ *Get DRL Document*
- ❑ *Add DRL Document*
- ❑ *Delete DRL Documents*
- ❑ *Add DRL Catalog*

- ❑ *Delete DRL Catalogs*
- ❑ *Get Attachment*
- ❑ *Add Attachment Procedure*
- ❑ *Delete Attachment Procedures*
- ❑ *Add Cross References*
- ❑ *Delete Cross References*
- ❑ *Update Cross References*

Overview of PQMServices

PQMServices provides operations that act on PQM actions, audits, and issues. The following operations are supported:

Operation	v30	Description
<i>Get PQM Summary</i> on page 13-4	●	Returns summary information for PQM items
<i>Create PQM Issues</i> on page 13-7	●	Adds new PQM issues
<i>Update PQM Issues</i> on page 13-11	●	Updates PQM issues
<i>Create PQM Actions</i> on page 13-14	●	Adds new PQM actions
<i>Update PQM Actions</i> on page 13-18	●	Updates PQM actions
<i>Create PQM Audits</i> on page 13-21	●	Adds new PQM audits
<i>Update PQM Audits</i> on page 13-25	●	Updates PQM audits
<i>Get Suppliers</i> on page 13-28	●	Returns suppliers for PQM items
<i>Add Suppliers</i> on page 13-30	●	Adds suppliers to PQM
<i>Delete Suppliers</i> on page 13-33	●	Deletes suppliers from PQM
<i>Get Affected Items</i> on page 13-36	●	Returns affected items for PQM items
<i>Add Affected Items</i> on page 13-39	●	Adds affected items to a PQM item
<i>Delete Affected Items</i> on page 13-45	●	Deleted affected items from a PQM item
<i>Get PQM Item By Criteria</i> on page 13-47	●	Retrieves a list of PQM items
<i>Get Related Items</i> on page 13-49	●	Retrieves the various related items for specified PQM items
<i>Add Related Items</i> on page 13-51	●	Adds existing PQM Actions, Issues, and Audits as related items for given PQM items
<i>Delete Related Items</i> on page 13-53	●	Removes the existing related items from given PQM items
<i>Get Supporting Document IDs</i> on page 13-55	●	Retrieves the supporting documents identifiers of specified PQM items, including supporting document attachments, URLs, rich text, DRL catalogs, and DRL documents
<i>Get URL Supporting Document</i> on page 13-58	●	Retrieves a URL supporting document
<i>Add URL Supporting Documents</i> on page 13-60	●	Adds a URL supporting document to existing PQM items

Operation	v30	Description
Delete URL Supporting Documents on page 13-62	●	Deletes a URL supporting document from existing PQM items
Add Supporting Document Attachment on page 13-64	●	Adds an attachment file to an existing attachments procedure on a PQM item
Delete Supporting Document Attachment on page 13-66	●	Delete existing supporting document attachments from a PQM item
Get Rich Text Supporting Document on page 13-68	●	Retrieves a rich text supporting document
Add Rich Text Supporting Document on page 13-70	●	Adds a rich text supporting document to existing PQM items
Delete Rich Text Supporting Documents on page 13-72	●	Deletes existing rich text supporting documents from a PQM item
Get DRL Document on page 13-74	●	Retrieves a DRL document
Add DRL Document on page 13-76	●	Adds a DRL document to existing PQM items
Delete DRL Documents on page 13-78	●	Deletes existing DRL documents from a PQM item
Add DRL Catalog on page 13-80	●	Adds a DRL catalog to existing PQM items
Delete DRL Catalogs on page 13-82	●	Deletes existing DRL catalogs from a PQM item
Get Attachment on page 13-84	●	Retrieves an attachment file of supporting document or DRL document.
Add Attachment Procedure on page 13-86	●	Adds an attachment procedure to an existing PQM item
Delete Attachment Procedures on page 13-88	●	Deletes existing supporting documents from a PQM item
Add Cross References on page 13-90	●	Adds cross references to a PQM item
Delete Cross References on page 13-92	●	Deletes cross references from a PQM item
Update Cross References on page 13-95	●	Updates cross references to a PQM item

Service Endpoint Locations

v30 endpoint

`http://<servername>/Integration/ProdikaContracts/PQM/v30/PQMServices.svc`

Get PQM Summary

Description

Use the GetPQMSummary web service to retrieve a list of summary information for auctions, audits, and issues.

Input

- 1 PQMItemSearchIdentifiers—A list of tPQMItemSearchIdentifier
- 2 RestrictToStatusWithBehaviorIDs—A list of the workflow status behaviorIDs

Table 13-1: Input

Name	Type	Description
PQMItemSearchIdentifiers	tPQMItemSearchIdentifier[]	Array of tPQMItemSearchIdentifier
RestrictToStatusWithBehaviorIDs	Int[]	Array of workflow tag behavior IDs of allowed PQM object

Output

The result will be list of summary information objects.

- 1 GetPQMSummary—An array of tPqmSummaryWrapper objects.
- 2 tPqmSummaryWrapper is composed of the following 2 parts:

Table 13-2: Output, tPqmSummaryWrapper

Name	Type	Description
PqmCommonSummary	tPqmCommonSummary	PQM summary information shared by all PQM types
PqmSpecificSummary	<ul style="list-style-type: none"> • tPqmIssueSpecificSummary or • tPqmActionSpecificSummary or • tPqmAuditSpecificSummary 	PQM summary information only related with specific PQM types. Data could be one of the following implementations: <ul style="list-style-type: none"> • ItPqmIssueSpecificSummary • ItPqmActionSpecificSummary • ItPqmAuditSpecificSummary

- 1 tPqmCommonSummary
 - tPQMItemIdentifier PQMItemIdentifier
 - string Description
 - string Originator
 - string ProcessTemplate
 - tCommonLookup[] ProductLines
 - Name
 - OptionalValue

- tCommonLookup [] Customers
 - Name
 - OptionalValue
 - bool IsTemplate
 - DateTime CreatedDate
 - DateTime CompletedDate
 - DateTime ReleasedDate
 - DateTime SubmittedDate
- 2** tPqmIssueSpecificSummary
- DateTime OccurrenceDate
 - DateTime ExpectedResolutionDate
 - tCommonLookup Severity
 - tCommonLookup Resolution
- 3** tPqmActionSpecificSummary
- string PreventativeAction
 - string RootCauseAnalysis
 - tPQMAssociatedProject AssociatedProject
 - string ProjectName
 - string ProjectOwner
 - string ProjectNumber
- 4** tPqmAuditSpecificSummary
- DateTime PlannedAuditDate
 - DateTime ActualAuditDate
 - tCommonLookup AuditResult

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-3: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference)
	INVALID_PQM_ITEM_PKID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type; must only be one of the four valid values: ALL, ACTION, AUDIT, ISSUE
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	PQM_RETRIEVAL_ERROR	Returned if an unexpected exception occurs when loading a PQM object's supplier information

Notes

See Conditions E, F, and Q in [Special Conditions](#) on page A-1.

Create PQM Issues

Description

Use the CreatePQMIssues web service to add new PQM issues.

Input

The input is tCreatePQMIssueRequest, including the following properties:

Table 13-4: Input

Name	Type	Description
IssueSummaryCreateWrappers	tIssueSummaryCreateWrapper[]	List of basic PQM issue summary information and issue template identifier

tIssueSummaryCreateWrapper is composed of the following parts:

Table 13-5: tIssueSummaryCreateWrapper

Name	Type	Description
IssueDetail	tIssueDetails	Basic PQM issue summary information (issue number not included)
IsFromTemplate	boolean	Optional field. Set this value as true to create from template; Default value is false
PQMTemplateIdentifier	tBasePQMItemSearchIdentifier	Optional. Issue template identifier If you create a PQM issue from template, the field is required in validation
CrossRefs	tExtCrossReference []	Optional. Important: When creating from template, if this value is not provided, the template cross reference setting is used. If this value is provided, this input is used to replace the value in the template.

tIssueDetails is composed of the following parts:

Table 13-6: tIssueDetails

Name	Type	Description
IssueTitle	string	Required; PQM item title
IssueDescription	string	PQM issue description
IssueType	string	Required Name of issue type as defined in ADMN>>PQM>>Issue
WorkflowTemplateName	string	Required
WorkflowStepBehaviorID	integer	Required Used with WorkflowTemplateName to retrieve the workflow status

Table 13-6: tIssueDetails

Originator	tOriginatorIdentifier	User login name or external ID as defined in ADMN 1 of the 2 (user login name or external ID) is required and only 1 is allowed
OccurenceDate	DateTime	
ExpectedResolutionDate	DateTime	
Severity	string	Name of severity. This should be an Active value defined in Admin>>PQM>>Severity
Resolution	string	Name of resolution. This should be an Active value defined in Admin>>PQM>> Resolution.
ProductLines	string[]	Name of product line. This should be an Active value defined in Admin>>PQM>> Product Lines
Customers	string[]	Customer name. This should be a Active value defined in Admin>>PQM>> Customers
CreateDate	DateTime	
CompleteDate	DateTime	
ReleasedDate	DateTime	
SubmittedDate	DateTime	

Output

CreatePQMIssues returns a status (bool) and array of tPQMItemidentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-7: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER S	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference) IssueDetails should not be empty.
	INVALID_PQM_ITEM_PK ID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.

Table 13-7: Result codes

RESULT_INVALID_INPUT (continued)	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type; must be only one of the four valid values: All, Action, Audit, Issue
	CANNOT_OVERRIDE_TEMPLATE	Occurs if a user without the Override Template role attempts to create from template; cannot override the locked fields
	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when user does not have create issue permission, or If a user without the Override Template role attempts to create from template; cannot override the locked fields
	INVALID_PQM_TEMPLATE	If IsFromTemplate is true, must have a PQMTemplateIdentifier, and should have 1 (and only 1) issue template found based on PQMTemplateIdentifier
	INVALID_PQM_TITLE	Issue/action/audit title should not be empty or exceed the max length 256
	INVALID_PQM_DESCRIPTION	Issue/action/audit description should not exceed the max length 4000
	INVALID_PQM_ISSUE_TYPE	Issue type should not be empty and should be a value in system
	INVALID_PQM_WORKFLOW_TEMPLATE_NAME	WorkflowTemplateName can't be empty PQM issue workflow template name {WorkflowTemplateName} should be defined in system
	INVALID_PQM_WORKFLOW_STEP_BEHAVIORID	WorkflowStepBehaviorID cannot be empty. No valid PQM template steps or multiple PQM template steps found with behavior: {WorkflowStepBehaviorID}

Table 13-7: Result codes

RESULT_INVALID_INPUT (continued)	INVALID_ORIGINATOR	<ul style="list-style-type: none"> • Should be a value defined in system • Originator should not be empty and can only accept 1 userName or 1 external ID • This field is required
	INVALID_PQM_ISSUE_SEVERITY	No Data found in commonlookup table for name:{Severity}
	INVALID_PQM_ISSUE_RESOLUTION	No Data found in commonlookup table for name: {Resolution}
	INVALID_PQM_PRODUCTLINES	No Data found in commonlookup table for name:{PRODUCT LINE}
	INVALID_PQM_CUSTOMERS	No Data found in commonlookup table for name:{Customer}
	PQM_WORKFLOW_ERROR	Error occurs when running workflow, may be caused by invalid input/system crash
RESULT_FAILURE	SAVE_PQM_ISSUE_ERROR	Unexpected exception occurs when attempting to save PQM issue

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Update PQM Issues

Description

Use the UpdatePQMIssues web service to update PQM issues.

Input

The input is tUpdatePQMIssueRequest, including the following properties:

Table 13-8: Input

Name	Type	Description
IssueSummaryUpdateWrappers	tIssueSummaryUpdateWrapper[]	List of basic PQM issue summary information and issue template identifier

tIssueSummaryUpdateWrapper is composed by following parts:

Table 13-9: tIssueSummaryUpdateWrapper

Name	Type	Description
IssueDetails	tIssueDetails	Basic PQM issue summary information (issue number not included)
PqmItemIdentifier	tBasePQMItemSearchIdentifier	Required Issue identifier
RestrictToStatusWithBehaviorIDs	int[]	An array of workflow tag behavior IDs of allowed PQM object

tIssueDetails is composed by following parts:

Table 13-10: tIssueDetails

Name	Type	Description
IssueTitle	string	Required; PQM item title
IssueDescription	string	PQM item description
IssueType	string	Required; name of Issue type defined in ADMN
WorkflowTemplateName	string	Required
WorkflowStepBehaviorID	integer	Required; used with WorkflowTemplateName to retrieve the workflow status
Originator	tOriginatorIdentifier	User login name or external ID Defined in ADMN 1 of the 2 (user login name or external ID) is required and only 1 is allowed
OccurrenceDate	DateTime	
ExpectedResolutionDate	DateTime	
Severity	string	An Active value defined in Admin>>PQM>>Severity
Resolution	string	An Active value defined in Admin>>PQM>> Resolution

Table 13-10: tIssueDetails

ProductLines	String[]	An Active value defined in Admin>>PQM>> Product Lines
Customers	String[]	An Active value defined in Admin>>PQM>> Customers
CreateDate	DateTime	
CompleteDate	DateTime	
ReleasedDate	DateTime	
SubmittedDate	DateTime	

Output

UpdatePQMIssues returns status (bool) and array of tPQMItemidentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-11: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER S	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference) IssueDetails should not be empty.
	INVALID_PQM_ITEM_PK ID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_N UMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFER E	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	UPDATE_DUPLICATE_P QM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not Allowed.

Table 13-11: Result codes

RESULT_INVALID_INPUT (continued)	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when user does not have permission to update the issue
	INVALID_PQM_TITLE	Issue/action/audit title should not be empty or exceed the max length 256
	INVALID_PQM_DESCRIPTION	Issue/action/audit description should not exceed the max length 4000
	INVALID_PQM_ISSUE_TYPE	Issue type should not be empty and should be a value in system
	INVALID_PQM_WORKFLOW_TEMPLATE_NAME	WorkflowTemplateName can't be empty PQM issue workflow template name {WorkflowTemplateName} should be defined in system
	INVALID_PQM_WORKFLOW_STEP_BEHAVIORID	WorkflowStepBehaviorID can't be empty. No valid PQM template steps or multiple PQM template steps found with behavior: {WorkflowStepBehaviorID}
	INVALID_ORIGINATOR	<ul style="list-style-type: none"> Should be a value defined in system Originator should not be empty and can only accept 1 userName or 1 external ID This field is required
	INVALID_PQM_ISSUE_SEVERITY	No Data found in commonlookup table for with name:{Severity}
	INVALID_PQM_ISSUE_RESOLUTION	No Data found in commonlookup table for with name: {ResolutionDisposition}
	INVALID_PQM_PRODUCT_LINES	No Data found in commonlookup table for with name:{PRODUCT LINE}
	INVALID_PQM_CUSTOMERS	No Data found in commonlookup table for with name:{Customer}
	PQM_WORKFLOW_ERROR	Error occurs when running workflow, may be caused by invalid input/system crash
RESULT_FAILURE	SAVE_PQM_ISSUE_ERROR	Occurs when attempting to save PQM issue

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Create PQM Actions

Description

Use the CreatePQMActions web service to add new PQM actions.

Input

The input is tCreatePQMActionRequest, including the following properties:

Table 13-12: Input

Name	Type	Description
ActionSummaryCreateWrappers	tActionSummaryCreateWrapper []	List of basic PQM action summary information and action template identifier

tActionSummaryCreateWrapper is composed by following parts:

Table 13-13: tIssueSummaryUpdateWrapper

Name	Type	Description
ActionDetails	tActionDetails	Basic PQM action summary information (action number not included)
IsFromTemplate	boolean	<ul style="list-style-type: none"> Optional Set this value as true if you want to create from template Default value is false
PQMTemplateIdentifier	tBasePQMItemSearchIdentifier	<ul style="list-style-type: none"> Optional Action template identifier If you create a PQM action from a template, the field is required
CrossRefs	tExtCrossReference	Optional Important: When you create from template, if this value is not provided, the template cross reference setting is used. If this value is provided, this input is used to replace the value in the template.

tActionDetails composed by following parts:

Table 13-14: tActionDetails

Name	Type	Description
ProblemStatement	string	Required; PQM action title
ActionDescription	string	PQM action description
ActionType	string	Required; name of Action type defined in ADMN
WorkflowTemplateName	string	Required
WorkflowStepBehaviorID	integer	Required; used with WorkflowTemplateName to retrieve the workflow status

Table 13-14: tActionDetails

Originator	tOriginatorIdentifier	User login name or external ID Defined in ADMN 1 of the 2 (user login name or external ID) is required and only 1 is allowed
ProductLines	String[]	An Active value defined in Admin>>PQM>> Product Lines
Customers	String[]	An Active value defined in Admin>>PQM>> Customers
PreventativeAction	string	
RootCauseAnalysis	string	
AssociatedNPDProject	tAssociatedNPDProject	Important: If the associated project is from our NPD system, then you must set SourceSystemID = 'NPD', and set ItemInternalID as NPD project PKID or set NPDProjectNum as NPD project number
CreateDate	DateTime	
CompleteDate	DateTime	
ReleasedDate	DateTime	
SubmittedDate	DateTime	

Output

CreatePQMActions returns status (bool) and array of tPQMItemidentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-15: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-15: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference) IssueDetails should not be empty.
	INVALID_PQM_ITEM_PKID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when user does not have create action permission or If a user without Override Template role attempts to create from template; cannot override the locked fields
	INVALID_PQM_TEMPLATE	If IsFromTemplate is true, it must have a PQMTemplateIdentifier, and should have 1(and only 1) action template found based on PQMTemplateIdentifier
	INVALID_PQM_TITLE	Issue/action/audit title should not be empty or exceed the max length 256
	INVALID_PQM_DESCRIPTION	Issue/action/audit description should not exceed the max length 4000
	INVALID_PQM_ACTION_TYPE	Action type should not be empty and should be a value in system
INVALID_PQM_WORKFLOW_TEMPLATE_NAME	WorkflowTemplateName can't be empty PQM action workflow template name {WorkflowTemplateName} should be defined in system	

Table 13-15: Result codes

RESULT_INVALID_INPUT (continued)	INVALID_PQM_WORKFLOW_STEP_BEHAVIORID	WorkflowStepBehaviorID can't be empty. No valid PQM template steps or multiple PQM template steps found with behavior: {WorkflowStepBehaviorID}
	INVALID_ORIGINATOR	<ul style="list-style-type: none"> • Should be a value defined in system • Originator should not be empty and can only accept 1 userName or 1 external ID • Required
	INVALID_PQM_PREVENTIVE_ACTION	Exceeds the max length 4000
	INVALID_PQM_ROOTCAUSE_ANALYSIS	Exceeds the max length 4000
	INVALID_SOURCE_SYSTEM_ID	Exceeds the max length
	INVALID_ITEM_INTERNAL_ID	Exceeds the max length
	INVALID_ITEM_EXTERNAL_ID	Exceeds the max length
	INVALID_ASSOCIATED_NPD_PROJECT	IF SourceSystemID is NPD, either a valid ItemInternalID or a valid NPD Project Number should be provided
	INVALID_PQM_PRODUC TLINES	No Data found in commonlookup table for with name:{PRODUCT LINE}
	INVALID_PQM_CUSTOMERS	No Data found in commonlookup table for with name:{Customer}
	PQM_WORKFLOW_ERROR	Error occurs when running workflow, may be caused by invalid input/system crash
RESULT_FAILURE	SAVE_PQM_ACTION_ERROR	Unexpected exception occurs when attempting to save PQM action

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Update PQM Actions

Description

Use the UpdatePQMActions web service to update PQM actions.

Input

The input is tUpdatePQMActionRequest, including the following properties:

Table 13-16: Input

Name	Type	Description
ActionSummaryUpdateWrappers	tActionSummaryUpdateWrapper[]	List of basic PQM action summary information and action template identifier

tActionSummaryUpdateWrapper is composed by following parts:

Table 13-17: tActionSummaryUpdateWrapper

Name	Type	Description
ActionDetails	tActionDetails	Basic PQM action summary information (action number not included)
PQMItemIdentifier	tBasePQMItemSearchIdentifier	<ul style="list-style-type: none"> • Required • Action identifier
RestrictToStatusWithBehaviorIDs	int[]	Array of workflow tag behavior IDs of allowed PQM object

Output

UpdatePQMActions returns status (bool) and array of tPQMItemIdentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-18: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference) IssueDetails should not be empty.
	INVALID_PQM_ITEM_PKID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	UPDATE_DUPLICATE_PQM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not Allowed.
	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when user does not have permission to update the action
	INVALID_PQM_TITLE	Issue/action/audit title should not be empty or exceed the max length 256
	INVALID_PQM_DESCRIPTION	Issue/action/audit description should not exceed the max length 4000
	INVALID_PQM_ACTION_TYPE	Action type should not be empty and should be a value in system
INVALID_PQM_WORKFLOW_TEMPLATE_NAME	WorkflowTemplateName can't be empty PQM action workflow template name {WorkflowTemplateName} should be defined in system	

Table 13-18: Result codes

RESULT_INVALID_INPUT (continued)	INVALID_PQM_WORKFLOW_STEP_BEHAVIORID	WorkflowStepBehaviorID can't be empty. No valid PQM template steps or multiple PQM template steps found with behavior: {WorkflowStepBehaviorID}
	INVALID_ORIGINATOR	<ul style="list-style-type: none"> • Should be a value defined in system • Originator should not be empty and can only accept 1 userName or 1 external ID • Required
	INVALID_PQM_PREVENTIVE_ACTION	Exceeds the max length 4000
	INVALID_PQM_ROOTCAUSE_ANALYSIS	Exceeds the max length 4000
	INVALID_SOURCE_SYSTEM_ID	Exceeds the max length
	INVALID_ITEM_INTERNAL_ID	Exceeds the max length
	INVALID_ITEM_EXTERNAL_ID	Exceeds the max length
	INVALID_PQM_PRODUCT_LINES	No Data found in commonlookup table for with name:{PRODUCT LINE}
	INVALID_PQM_CUSTOMERS	No Data found in commonlookup table for with name:{Customer}
	PQM_WORKFLOW_ERROR	Error occurs when running workflow, may be caused by invalid input/system crash
RESULT_FAILURE	SAVE_PQM_ACTION_ERROR	Unexpected exception occurs when attempting to save PQM action

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Create PQM Audits

Description

Use the CreatePQMAudits web service to add new PQM audits.

Input

The input is tCreatePQMAuditRequest, including the following properties:

Table 13-19: Input

Name	Type	Description
AuditSummaryCreateWrappers	tAuditSummaryCreateWrapper[]	List of basic PQM audit summary information and audit template identifier

tAuditSummaryCreateWrapper is composed of the following parts:

Table 13-20: tAuditSummaryCreateWrapper

Name	Type	Description
AuditDetails	tAuditDetails	Basic PQM audit summary information (audit number not included)
IsFromTemplate	boolean	<ul style="list-style-type: none"> Optional Set this value as true if you want to create from template Default value is false
PQMTemplateIdentifier	tBasePQMItemSearchIdentifier	<ul style="list-style-type: none"> Optional Audit template identifier If creating PQM audit from template, the field is required in validation
CrossRefs	tExtCrossReference	Optional Important: When creating from template, if this value is not provided, will use the template cross reference setting. If this value is provided, will use this input to replace the value in the template.

tAuditDetails is composed by following parts:

Table 13-21: tAuditDetails

Name	Type	Description
AuditTitle	string	Required; PQM audit title
AuditDescription	string	PQM audit description
AuditType	string	Required; name of Audit type defined in ADMN
WorkflowTemplateName	string	Required

Table 13-21: tAuditDetails

WorkflowStepBehaviorID	integer	<ul style="list-style-type: none"> • Required • Used with WorkflowTemplateName to retrieve the workflow status • If multiple value returned, report error
Originator	tOriginatorIdentifier	<ul style="list-style-type: none"> • User login name or external ID • Defined in ADMN • 1 of the 2 (user login name or external ID) is required and only 1 is allowed
PlannedAuditDate	DateTime	•
ProductLines	string[]	An Active value defined in Admin>>PQM>> Product Lines
Customers	string[]	An Active value defined in Admin>>PQM>> Customers
AuditResult	string	An Active value defined in Admin>>PQM>> Audit Result
CreateDate	DateTime	
CompleteDate	DateTime	
ReleasedDate	DateTime	
SubmittedDate	DateTime	

Output

CreatePQMAudits returns status (bool) and array of tPQMItemidentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-22: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-22: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference) IssueDetails should not be empty.
	INVALID_PQM_ITEM_PKID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when user does not have create audit permission Or If a user without Override Template role to create from template, cannot override the locked fields
	INVALID_PQM_TEMPLATE	If IsFromTemplate is true, must have a PQMTemplateIdentifier, and should have 1(and only 1) audit template found based on PQMTemplateIdentifier
	INVALID_PQM_TITLE	Issue/action/audit title should not be empty or exceed the max length 256
	INVALID_PQM_DESCRIPTION	Issue/action/audit description should not exceed the max length 4000
INVALID_PQM_AUDIT_TYPE	Audit type should not be empty and should be a value in system	

Table 13-22: Result codes

RESULT_INVALID_INPUT (continued)	INVALID_PQM_WORKFLOW_TEMPLATE_NAME	WorkflowTemplateName can't be empty PQM audit workflow template name {WorkflowTemplateName} should be defined in system
	INVALID_PQM_WORKFLOW_STEP_BEHAVIORID	WorkflowStepBehaviorID can't be empty. No valid PQM template steps or multiple PQM template steps found with behavior: {WorkflowStepBehaviorID}
	INVALID_ORIGINATOR	<ul style="list-style-type: none"> • Should be a value defined in system • Originator should not be empty and can only accept 1 userName or 1 external ID • Required
	INVALID_PQM_AUDIT_RESULT	No Data found in commonlookup table for with name: {audit result}
	INVALID_PQM_PRODUCT_LINES	No Data found in commonlookup table for with name:{PRODUCT LINE}
	INVALID_PQM_CUSTOMERS	No Data found in commonlookup table for with name:{Customer}
	PQM_WORKFLOW_ERROR	Error occurs when running workflow, may be caused by invalid input/system crash
RESULT_FAILURE	SAVE_PQM_AUDIT_ERROR	Unexpected exception occurs when attempting to save PQM audit

Notes

See Conditions E and Q in [Special Conditions](#) on page A-1.

Update PQM Audits

Description

Use the UpdatePQMAudits web service to update PQM audits.

Input

The input is tUpdatePQMAuditRequest, including the following properties:

Table 13-23: Input

Name	Type	Description
AuditSummaryUpdateWrappers	tAuditSummaryUpdateWrapper[]	List of basic PQM audit summary information and audit template identifier

tAuditSummaryUpdateWrapper composed by following parts:

Table 13-24: tAuditSummaryUpdateWrapper

Name	Type	Description
AuditDetails	tAuditDetails	Basic PQM audit summary information (audit number not included)
pqmItemIdentifier	tBasePQMItemSearchIdentifier	<ul style="list-style-type: none"> • Required • Audit identifier
RestrictToStatusWithBehaviorIDs	int[]	Array of workflow tag behavior IDs of allowed PQM object

Output

CreatePQMAudits returns status (bool) and array of tPQMItemIdentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-25: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference) IssueDetails should not be empty.
	INVALID_PQM_ITEM_PKID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	UPDATE_DUPLICATE_PQM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not allowed.

Table 13-25: Result codes

RESULT_INVALID_INPUT (continued)	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when user does not have permission to update the audit
	INVALID_PQM_TITLE	Issue/action/audit title should not be empty or exceed the max length 256
	INVALID_PQM_DESCRIPTION	Issue/action/audit description should not exceed the max length 4000
	INVALID_PQM_AUDIT_TYPE	Audit type should not be empty and should be a value in system
	INVALID_PQM_WORKFLOW_TEMPLATE_NAME	WorkflowTemplateName can't be empty PQM audit workflow template name {WorkflowTemplateName} should be defined in system
	INVALID_PQM_WORKFLOW_STEP_BEHAVIORID	WorkflowStepBehaviorID can't be empty. No valid PQM template steps or multiple PQM template steps found with behavior: {WorkflowStepBehaviorID}
	INVALID_ORIGINATOR	<ul style="list-style-type: none"> • Should be a value defined in system • Originator should not be empty and can only accept 1 userName or 1 external ID • Required
	INVALID_PQM_AUDIT_RESULT	No Data found in commonlookup table for with name:{audit result}
	INVALID_PQM_PRODUCT_LINES	No Data found in commonlookup table for with name:{PRODUCT LINE}
	INVALID_PQM_CUSTOMERS	No Data found in commonlookup table for with name:{Customer}
PQM_WORKFLOW_ERROR	Error occurs when running workflow, may be caused by invalid input/system crash	
RESULT_FAILURE	SAVE_PQM_AUDIT_ERROR	Unexpected exception occurs when attempting to save PQM audit

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Get Suppliers

Description

Use the GetSuppliers web service to retrieve suppliers for PQM items.

Input

- 1 PQMItemSearchIdentifiers—A list of tPQMItemSearchIdentifier
- 2 RestrictToStatusWithBehaviorIDs—A list of the workflow status behaviorID

Table 13-26: Input

Name	Type	Description
PQMItemSearchIdentifiers	tPQMItemSearchIdentifier[]	Array of tPQMItemSearchIdentifier
RestrictToStatusWithBehaviorIDs	Int[]	Array of workflow tag behavior IDs of allowed PQM object

Output

GetSuppliers returns array of tPQMItemSupplierIdentifier

- 1 tPQMItemSupplierIdentifier
 - tPQMItemIdentifier PQMItemIdentifier
 - tPQMItemSupplier[] PQMItemSuppliers
- 2 tPQMItemSupplier
 - tSourceSystemIdentifier SourceSystemIdentifier
 - string CompanyDescription
 - string FacilityDescription
- 3 tSourceSystemIdentifier
 - string ItemInternalID
 - string ItemExternalID
 - string ItemType
 - string SourceSystemID

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-27: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference)
	INVALID_PQM_ITEM_PKID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type, could only be one of the 4 values: ALL, ACTION, AUDIT, ISSUE
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	PQM_RETRIEVAL_ERROR	Returned if an unexpected exception occurs when loading a PQM object's summary information

Notes

See Conditions E, F, and Q in [Special Conditions](#) on page A-1.

Add Suppliers

Description

Use the AddSuppliers web service to add PQM suppliers.

Input

The input contains an array of tAddDeleteSuppliersInputWrapper[].

tAddDeleteSuppliersInputWrapper is composed of the following fields:

Table 13-28: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	An input in a PQM web service to identifier a PQM item
RestrictToStatusWithBehaviorIDs	Int[]	Array of workflow tag behavior IDs of allowed PQM object
Suppliers	tPQMItemSupplierSearchIdentifier []	<ul style="list-style-type: none"> tSourceSystemPQMItemSupplierIdentifier tSCRMEntityNumberPQMItemSupplierIdentifier tSCRMEntityCrossRefPQMItemSupplierIdentifier <p>Important: If the supplier is already in our system, it is strongly recommended to use tSCRMEntityNumberPQMItemSupplierIdentifier or tSCRMEntityCrossRefPQMItemSupplierIdentifier to add it.</p> <p>tSourceSystemPQMItemSupplierIdentifier is designed for third party systems data. Using it incorrectly to add a SCRM company/facility may cause a UI crash if using v611 default implementation.</p>

- 1 tSourceSystemPQMItemSupplierIdentifier extends tPQMItemSupplierSearchIdentifier
 - tSourceSystemIdentifier
- 2 tSCRMEntityNumberPQMItemSupplierIdentifier extends tPQMItemSupplierSearchIdentifier
 - tSCRMEntityNumber
- 3 tSCRMEntityCrossRefPQMItemSupplierIdentifier extends tPQMItemSupplierSearchIdentifier
 - tSCRMEntityCrossRef

Output

AddSuppliers service returns status (bool) and array of tPQMItemIdentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-29: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	PQMItemIdentifier is empty(at least one field is required, Pkid, item number, crossreference) AffectedItemIdentifiers should not be empty.
	INVALID_PQM_ITEM_PKID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type, could only be one of the 4 values: ALL, ACTION, AUDIT, ISSUE
	UPDATE_DUPLICATE_PQM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not allowed.

Table 13-29: Result codes

RESULT_INVALID_INPUT continued	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when the user does not have permission to update the PQM object: {pqm identifier}
	INVALID_PQM_SUPPLIER_IDENTIFIER	Occurs when any field in SourceSystemIdentifier exceeds the max length, including: ItemType, ItemInternalID, ItemExternalID, and SourceSystemID. At least one field is ItemInternalID, ItemExternalID. The Supplier to be added has already been attached to the PQM item. Added a new scenario which also returns INVALID_SUPPLIER_IDENTIFIER: If using tSCRMEntityCrossRefPQMItemSupplierIdentifier or tSCRMEntityNumberPQMItemSupplierIdentifier to identify a supplier, a SCRM company/facility should be found.
RESULT_FAILURE	ADD_PQM_SUPPLIERS_ERROR	An unexpected exception occurs when attempting to add PQM suppliers

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Delete Suppliers

Description

Use the DeleteSuppliers web service to delete PQM suppliers.

Input

The input contains an array of tAddDeleteSuppliersInputWrapper[].

tAddDeleteSuppliersInputWrapper is composed of the following fields:

Table 13-30: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	An input in a PQM web service to identify a PQM item
RestrictToStatusWithBehaviorIDs	Int[]	Array of workflow tag behavior IDs of allowed PQM object
Suppliers	tPQMItemSupplierSearchIdentifier []	<ul style="list-style-type: none"> tSourceSystemPQMItemSupplierIdentifier tSCRMEntityNumberPQMItemSupplierIdentifier tSCRMEntityCrossRefPQMItemSupplierIdentifier

Output

DeleteSuppliers service returns status (bool) and array of tPQMItemIdentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-31: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-31: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER S	PQMItemIdentifier is empty(at least one field is required, Pkid, item number, crossreference) AffectedItemIdentifiers should not be empty.
	INVALID_PQM_ITEM_PK ID	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_N UMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERE NCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TY PE	Invalid item type,could only be one of the 4 values: ALL, ACTION, AUDIT, ISSUE
	UPDATE_DUPLICATE_P QM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not allowed.

Table 13-31: Result codes

RESULT_INVALID_INPUT continued	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when the user does not have permission to update the PQM object: {pqm identifier}
	INVALID_PQM_SUPPLIER_IDENTIFIER	Occurs when any field in SourceSystemIdentifier exceeds the max length, including: ItemType, ItemInternalID, ItemExternalID, and SourceSystemID. At least one field is ItemInternalID, ItemExternalID. The Supplier to be added has already been attached to the PQM item. Adds a new scenario which also returns INVALID_SUPPLIER_IDENTIFIER If using tSCRMEntityCrossRefPQMItemSupplierIdentifier or tSCRMEntityNumberPQMItemSupplierIdentifier to identifier a supplier, a SCRM company/facility should be found.
RESULT_FAILURE	DELETE_PQM_SUPPLIER_S_ERROR	An unexpected exception occurs when attempting to remove PQM suppliers

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Get Affected Items

Description

Use the GetAffectedItems web service to retrieve affected items for PQM items.

Input

- 1 PQMItemSearchIdentifiers—A list of tPQMItemSearchIdentifier
- 2 RestrictToStatusWithBehaviorIDs—A list of the workflow status behaviorIDs

Table 13-32: Input

Name	Type	Description
PQMItemSearchIdentifiers	tPQMItemSearchIdentifier[]	Array of tPQMItemSearchIdentifier
RestrictToStatusWithBehaviorIDs	Int[]	Array of workflow tag behavior IDs of allowed PQM object

Output

- 1 GetAffectedItems returns array of tPQMItemAffectedItemsResult.
- 2 tPQMItemAffectedItemsResult composed by the following 2 parts:

Table 13-33: Output

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	Represents a PQM item identifying information used as output, includes the Pqm number and a list of cross references (SystemId and Equivalent), etc.
AffectedItems	tPQMAffectedItem[]	PQM affected item detail information only related with specific PQM types. Could be one of the following implementations: <ul style="list-style-type: none"> • tPQMAffectedItem • tIssueAffectedItem

- 1 tPQMItemAffectedItemsResult
 - tPQMItemIdentifier PQMItemIdentifier
 - tPQMAffectedItem []AffectedItems
- 2 tPQMAffectedItem
 - string RevisionFoundItemNumber
 - string RevisionFoundItemRevision
 - string RevisionFoundComment
 - string RevisionFixedItemNumber
 - string RevisionFixedItemRevision
 - string RevisionFoundItemInternalID

- string RevisionFoundItemExternalID
 - string RevisionFixedItemInternalID
 - string RevisionFixedItemExternalID
 - string ItemType
 - string SourceSystemID
 - string Description
- 3** ItIssueAffectedItem extends ItPQMAffectedItem
- tcommonlookup FailureType
 - tMeasurement QuantityAffected
 - string AdditionalDisplayIdentifier
 - PQMItemSupplier siteAffected
 - string ConformanceItemDescription
 - string ConformanceItemID
 - string ConformanceItemDescriptionExtended
 - tMeasurement QtySuspected
 - string SerialLotNum
 - tMeasurement QtyChecked
 - string ContainmentActions
 - string RMANum
 - Date ConformingMaterialDate

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-34: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-34: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference)
	INVALID_PQM_ITEM_PKID	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type,could only be one of the 4 values: ALL, ACTION, AUDIT, ISSUE
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	PQM_RETRIEVAL_ERROR	An unexpected exception occurs when loading a PQM object affected items information

Notes

See Conditions E, F, and Q in [Special Conditions](#) on page A-1.

Add Affected Items

Description

Use the AddAffectedItems web service to add affected items to a PQM item.

Input

The input is an array of tAddAffectedItemInputWrapper.

tAddAffectedItemInputWrapper is composed of the following three fields:

Table 13-35: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	An input in a PQM web service to identifier a PQM item
RestrictToStatusWithBehaviorIDs	Int[]	Array of workflow tag behavior IDs of allowed PQM object
AffectedItems	tAffectedItemInput []	Could be the 3 types: <ul style="list-style-type: none"> • tAffectedItemInput: used for general purpose • tIssueAffectedInpt: used to add more fields for PQM issue • tNCRAffectedInpt: used to add more field for PQM issue NCR type

tAffectedItemInput is composed of the following fields:

Table 13-36: tAffectedItemInput

Name	Type	Description
AffectedItemIdentifier	tPQMAffectedItemIdentifier	Affected item identifier Could be 2 sub types: <ul style="list-style-type: none"> • tPQMAffectedItemSourceSystemIdentifier is used to identify affected items from third party system It is strongly recommended to use tPQMAffectedItemGSMIdentifier if the affected item is GSM Spec. Incorrect use of tPQMAffectedItemSourceSystemIdentifier may lead to UI crash if using default config in v6.1.1. <ul style="list-style-type: none"> • tPQMAffectedItemGSMIdentifier is used to identify the affected item using GSM Spec Identifier Criterion
RevisionFoundComment	string	Comments of the affected item

tPQMAffectedItemGSMIdentifier is composed of the 2 fields:

Table 13-37: tPQMAffectedItemGSMIdentifier

Name	Type	Description
AffectedGSMSpecFound	tSpecIdentifierCriterion	Identifies the affected GSM specification that was found
AffectedGSMSpecFixed	tSpecIdentifierCriterion	Identifies the affected GSM specification that was fixed

tPQMAffectedItemSourceSystemIdentifier is composed of the following fields:

Table 13-38: tPQMAffectedItemSourceSystemIdentifier

Name	Type	Description
SourceSystemID	string	SourceSystemID of the affected item
RevisionFoundItemNumber	string	ItemNumber of the affected item found
RevisionFoundItemRevision	string	Revision of the affected item found
RevisionFixedItemNumber	string	ItemNumber of the affected item fixed
RevisionFixedItemRevision	string	Revision of the affected item fixed
RevisionFoundItemInternalID	string	ItemInternalID of the affected item found
RevisionFoundItemExternalID	string	ExternalID of the affected item found
RevisionFixedItemInternalID	string	ItemInternalID of the affected item fixed
RevisionFixedItemExternalID	string	ExternalID of the affected item fixed
ItemType	string	ItemType of the affected item

tIssueAffectedItemInput is composed of the following fields:

Table 13-39: tIssueAffectedItemInput

Name	Type	Description
AffectedItemIdentifier	tPQMAffectedItemIdentifier	Affected item identifier Could be 2 sub types: <ul style="list-style-type: none"> tPQMAffectedItemSourceSystemIdentifier is used to identify affected items from third party system. It is strongly recommended to use tPQMAffectedItemGSMIdentifier if the affected item is GSM Spec. Incorrect use of tPQMAffectedItemSourceSystemIdentifier may lead to UI crash if using default config in v6.1.1. <ul style="list-style-type: none"> tPQMAffectedItemGSMIdentifier is used to identify the affected item using GSM Spec Identifier Criterion.
RevisionFoundComment	string	Comments of the affected item
FailureType	string	FailureType of the issue affected item
QuantityAffected	tMeasurement	QuantityAffected of the issue affected item
SiteAffected	tPQMItemSupplierSearchIdentifier	SiteAffected of the issue affected item

tNCRAffectedItemInput is composed of the following fields:

Table 13-40: tNCRAffectedItemInput

Name	Type	Description
AffectedItemIdentifier	tPQMAffectedItemIdentifier	Affected item identifier Could be 2 sub types: <ul style="list-style-type: none"> tPQMAffectedItemSourceSystemIdentifier is used to identify affected items from third party system. It is strongly recommended to use tPQMAffectedItemGSMIdentifier if the affected item is GSM Spec. Incorrect use of tPQMAffectedItemSourceSystemIdentifier may lead to UI crash if using default config in v6.1.1. tPQMAffectedItemGSMIdentifier is used to identifier the affected item using GSM Spec Identifier Criterion.
RevisionFoundComment	string	Comments of the affected item
FailureType	string	FailureType of the issue affected item
QuantityAffected	tMeasurement	QuantityAffected of the issue affected item

Table 13-40: tNCRAffectedItemInput

SiteAffected	tPQMItemSupplierSearch Identifier	SiteAffected of the issue affected item
ConformanceItemIdentifier	tConformanceItemIdentifier	ConformanceItemIdentifier of the NCR issue affected item
QtySuspected	tMeasurement	QtySuspected of the NCR issue affected item
SerialLotNum	string	SerialLotNum of the NCR issue affected item
QtyChecked	tMeasurement	QtyChecked of the NCR issue affected item
ContainmentAction	string	ContainmentActions of the NCR issue affected item
RMA Num	string	RMA Num of the NCR issue affected item
ConformingMaterialDate	Date Time	ConformingMaterialDate of the NCR issue affected item

Output

AddAffectedItems service returns status (bool) and array of tPQMItemIdentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-41: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference) IssueDetails should not be empty
	INVALID_PQM_ITEM_PKID	PQM Item PKID input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.

Table 13-41: Result codes

RESULT_INVALID_INPUT continued	INVALID_CROSS_REFERENC	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type, could only be one of the 4 values: ALL, ACTION, AUDIT, ISSUE
	UPDATE_DUPLICATE_PQM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not allowed
	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when the user does not have permission to update the PQM object: {pqm identifier}
	INVALID_PQM_AFFECTED_ITEM_SOURCE_SYSTEM_IDENTIFIER	Occurs when any field in AffectedItemIdentifier exceeds the max length, including: <ul style="list-style-type: none"> • ItemType • RevisionFixedItemExternalID • RevisionFixedItemInternalID • RevisionFixedItemNumber • RevisionFixedItemRevision • RevisionFoundItemExternalID • RevisionFoundItemInternalID • RevisionFoundItemNumber • RevisionFoundItemRevision • SourceSystemID
	INVALID_PQM_SUPPLIER_IDENTIFIER	Any fields in Site affected exceed the max length.
	INVALID_FailureType	FailureType exceeds the maxlength
	INVALID_ContainmentActions	ContainmentActions exceeds the maxlength
	INVALID_RMANum	RMANum exceeds the maxlength
	INVALID_SerialLotNum	SerialLotNum exceeds the maxlength
INVALID_ConformanceItemInternalID	ConformanceItemInternalID exceeds the maxlength	

Table 13-41: Result codes

RESULT_INVALID_INPUT continued	INVALID_MEASUREMENT	UOM should not be empty
	INVALID_PQM_AFFECTED_ITEM_INPUT	No GSM Spec Found for AffectedGSMSpecFound: AffectedGSMSpecFound Multiple GSM Specs Found for AffectedGSMSpecFixed: AffectedGSMSpecFixed No GSM Spec Found for ConformanceItemIdentifier:{ConformanceItemIdentifier} Multiple GSM Specs Found for ConformanceItemIdentifier:{ConformanceItemIdentifier}
	INVALID_PQM_AFFECTED_ITEM_INPUT_TYPE	Pass in tIssueAffectedInput type to a non PQM-issue object Or Pass in tNCRAffectedInput type to a non PQM -issue_Non Conformance object
	INVALID_PQM_SITE_AFFECTED	
	INVALID_PQM_FAILURE_TYPE	No Data found in commonlookup table for name: {PQMFailureType}
	ADD_PQM_SUPPLIERS_ERROR	An unexpected exception occurs when attempting to add PQM suppliers
	RESULT_FAILURE	ADD_PQM_AFFECTED_ITEMS_ERROR

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Delete Affected Items

Description

Use the DeleteAffectedItems web service to delete affected items from a PQM item.

Input

Table 13-42: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	An input in a PQM web service to identify a PQM item
RestrictToStatusWithBehaviorIDs	Int[]	Array of workflow tag behavior IDs of allowed PQM object
AffectedItemIdentifiers	tPQMAffectedItemIdentifier[]	<ul style="list-style-type: none"> tPQMAffectedItemSourceSystemIdentifier tPQMAffectedItemGSMIdentifier

Output

DeleteAffectedItems service returns the status (bool) and array of tPQMItemIdentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-43: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	PQMItemIdentifier is empty(at least one field is required, Pkid, item number, crossreference) AffectedItemIdentifiers should not be empty.
	INVALID_PQM_ITEM_PKID	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.

Table 13-43: Result codes

RESULT_INVALID_INPUT continued	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type; could only be one of the 4 values: ALL, ACTION, AUDIT, ISSUE
	UPDATE_DUPLICATE_PQM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not allowed
	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when the user does not have permission to update the PQM object: {pqm identifier}
	INVALID_PQM_AFFECTED_ITEM_SOURCE_SYSTEM_IDENTIFIER	Any field in AffectedItemIdentifier exceed the max length, including: ItemType <ul style="list-style-type: none"> • RevisionFixedItemExternalID • RevisionFixedItemInternalID • RevisionFixedItemNumber • RevisionFixedItemRevision • RevisionFoundItemExternalID • RevisionFoundItemInternalID • RevisionFoundItemNumber • RevisionFoundItemRevision • SourceSystemID At least one field is required: RevisionFoundItemInternalID, RevisionFoundItemExternalID, RevisionFoundItemNumber
	INVALID_PQM_AFFECTED_ITEM_INPUT	No GSM Spec Found for AffectedGSMSpecFound:+ AffectedGSMSpecFound
RESULT_FAILURE	DELETE_PQM_AFFECTED_ITEMS_ERROR	An unexpected exception occurs when attempting to add PQM affected items

Notes

See Conditions E and Q in [Special Conditions](#) on page A-1.

Get PQM Item By Criteria

Description

Use the GetPQMItemByCriteria to retrieve a list of PQM items.

Input

The input is tGetPQMItemByCriteriaRequest, including the following properties:

Table 13-44: Input

Name	Type	Description
IncludePQMActions	boolean	
ActionTypes	string[]	Valid action type names defined in ADMN>PQM>Action Type
IncludePQMAudits	boolean	
AuditTypes	string[]	Valid audit type names defined in ADMN>PQM>Audit Type
IncludePQMIssues	boolean	
IssueTypes	string[]	Should be valid issue type names defined in ADMN>PQM>Issue Type
Title	string	PQM item title
Description	string	The whole or part of PQM item description
ProductLines	string[]	Valid product line names defined in Admin>PQM> Product Lines
Customers	string[]	Should be valid customer names defined in ADMN>PQM>Customers
Originators	tUser[]	Array of originators
Owners	tUser[]	Array of owners
IssueSeverity	string	Should be a valid severity value for issue items
Suppliers	tSupplierSearchIdentifier []	Array of supplier search identifiers
Status	string[]	PQM workflow status names
RestrictToStatusWithIDs	integer[]	Array of workflow tag behavior IDs

tSupplierSearchIdentifier contains the following properties:

- tExternalSupplierSearchIdentifier ExternalSearchIdentifier
 - string InternalItemID
 - string ExternalItemID
 - string SourceSystemID
 - string ItemType
- tSCRMSupplierSearchIdentifier SCRMSearchIdentifier
 - tSCRMEntityNumber SCRMEntityNum

- tSCRMEntityCrossRef SCRMEntityCrossRef
- string SCRMEntityPKID

tUser contains following properties which are defined in Nutrition Services:

- string Name —The UserName used for login
- string ExternalId

Output

GetPQMItemByCriteria returns array of tPQMItemIdentifier objects.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-45: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	INVALID_SUPPLIER_IDENTIFIER	Each supplier search identifier should only contain either external supplier search identifier or SCRM supplier search identifier
	INVALID_USER_IDENTIFIER	Each tUser object should only contain either UserName or ExternalId
RESULT_WARNINGS	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	PQM_ITEM_RETRIEVAL_ERROR	Returned if an unexpected exception occurs when loading a PQM item

Notes

See Condition F in [Special Conditions](#) on page A-1.

Get Related Items

Description

Use the GetRelatedItems web service to retrieve the various related items for specified PQM items.

Input

- 1 A list of PQM item identifiers and one or more workflow status tag behavior IDs.

Table 13-46: Input

Name	Type	Description
PQMItemIdentifiers	tPQMItemSearchIdentifier[]	Array of one or more tPQMItemSearchIdentifier objects
RestrictToStatusWithIDs	int[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier

Output

The GetRelatedItems web service returns list of tRelatedPQMItemsWrapper objects.

Table 13-47: Input

Name	Type	Description
RelatedPQMItemsWrappers	tRelatedPQMItemsWrapper[]	Array of one or more tRelatedPQMItemsWrapper objects

tRelatedPQMItemsWrapper contains a PQM item's identifier and its related items depending on the item type:

- Related items of action returned: related issues, related actions, and related audits
- Related items of issue returned: related actions, related audits
- Related items of audit returned: related issues, related actions

Here are the definitions:

- 1 tRelatedPQMItemsWrapper
 - tPQMItemIdentifier PQMItemIdentifier
 - tRelatedPQMItem[] RelatedIssues
 - tRelatedPQMItem[] RelatedActions
 - tRelatedPQMItem[] RelatedAudits
- 2 tRelatedPQMItem
 - tPQMItemIdentifier PQMItemIdentifier
 - string ExtendedDescription

- 3 tRelatedPQMAuditItem: tRelatedPQMItem
 - Date PlannedAuditDate
- 4 tRelatedPQMActionItem: tRelatedPQMItem
 - string Relationship//Relationship of Child or Parent
- 5 tRelatedPQMItemIssueItem: tRelatedPQMItem

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-48: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	Missing PQM item identifier
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.
RESULT_FAILURE	PQM_ITEM_RETRIEVAL_ERROR	Unhandled error happened when loading PQM items
	NO_PQM_ITEM_FOUND	Returned if no PQM item was found for the input identifier

Notes

User must have [PQM_ADMIN] role or WFA read permission to retrieve the PQM item.

See Condition F in [Special Conditions](#) on page A-1.

Add Related Items

Description

Use the AddRelatedItems web service to add existing PQM Actions, Issues, and Audits as related items for given PQM items.

Input

Table 13-49: Input

Name	Type	Description
PQMItemIdentifiers	tPQMItemSearchIdentifier[]	Specify the PQM items to edit
RelatedItemIdentifiers	tPQMItemSearchIdentifier[]	Specify the existing related PQM items to add
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier

Output

An overall success indicator and a list of tPQMItemIdentifier objects representing the PQM items changed will be returned.

Table 13-50: Output

Name	Type	Description
IsSuccessful	boolean	
PQMItemsAffected	tPQMItemIdentifier[]	Array of one or more PQM items which have been changed

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-51: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-51: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	Missing PQM item identifier or related item identifiers
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	MAX_RECORDS_SAVED	Maximum records count allowed for save exceeded
RESULT_FAILURE	CANNOT_ADD_RELATED_ITEM	See additional notes below
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input identifier

Notes

- 1 AddRelatedItems web service adds related items depending on the type of input item.
 - Related items add to issue: none
 - Related items add to action: issue, action, and audit
 - Related items add to audit: issue, action
- 2 User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

Delete Related Items

Description

Use the DeleteRelatedItems web service to remove the existing related items from given PQM items.

Input

Table 13-52: Input

Name	Type	Description
PQMItemIdentifiers	tPQMItemSearchIdentifier[]	Specify the PQM items to edit
RelatedItemIdentifiers	tPQMItemSearchIdentifier[]	Specify the existing related PQM items to remove
RestrictToStatusWithIDs	Integer	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier

Output

An overall success indicator and a list of tPQMItemIdentifier objects representing the PQM items affected will be returned.

Table 13-53: Output

Name	Type	Description
IsSuccessful	boolean	
PQMItemsAffected	tPQMItemIdentifier[]	Array of one or more PQM items which have been changed

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-54: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-54: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	Missing PQM item identifier or related item identifiers
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	MAX_RECORDS_SAVED	Maximum records count allowed for save exceeded
RESULT_FAILURE	CANNOT_REMOVE_RELATED_ITEM	See additional notes below
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input identifier

Notes

- 1 DeleteRelatedItems web service removes related items depending on the type of input item.
 - Related items remove from issue: none
 - Related items remove from action: issue, action (only action items with Child relationship can be removed)
 - Related items remove from audit: issue, action
- 2 User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

Get Supporting Document IDs

Description

Use the GetSupportingDocumentIDs web service to retrieve the supporting documents identifiers of specified PQM items, including supporting document attachments, URLs, rich text, DRL catalogs, and DRL documents.

Input

A list of PQM item identifiers and one or more workflow status tag behavior IDs.

Table 13-55: Input

Name	Type	Description
PQMItemIdentifiers	tPQMItemSearchIdentifier[]	Array of one or more tPQMItemSearchIdentifier objects
RestrictToStatusWithIDs	int[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier

Output

A list of tPQMSupportingDocWrapper will be returned. Each tPQMSupportingDocWrapper contains:

- 1 tPQMItemIdentifier PQMItemIdentifier
- 2 tAttachmentsWrapper[] SupportingDocuments
- 3 tCommonIdentifier[] RichTextIdentifiers
- 4 tCommonIdentifier[] URLSourceIdentifiers
- 5 tDRLDocumentIdentifiers[] DRLDocumentIdentifiers
- 6 tDRLCatalog[] DRLCatalogs

tCommonIdentifier contains following members:

- string PKID
- string Title

tDRLDocumentIdentifier: tCommonIdentifier

- ItSpecificationNumber DocumentID

tDRLCatalogIdentifier: tCommonIdentifier

- String ExternalID

1 tAttachmentsWrapper

Table 13-56: tAttachmentsWrapper

Name	Type	Description
Identifier	tCommonIdentifier	
SecurityClassification	string	
CreationDate	DateTime	
Attachments	tCommonIdentifier[]	

2 tDRLCatalog

Table 13-57: tDRLCatalog

Name	Type	Description
CatalogIdentifier	tDRLCatalogIdentifier	
DRLDocuments	tDRLDocumentIdentifier []	Returned if DRL catalog is visible to user

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-58: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER S	Missing PQM item identifiers
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	MAX_RECORDS_RETRIEVED	Occurs if the number of records retrieved exceeds the maximum records allowed. See Condition F - Max Records Retrieved on page A-2.

Notes

User must have [PQM_ADMIN] role or WFA read permission to retrieve the PQM item.

User must have [DRL_VIEWER] role to retrieve the sub-nodes (including DRL catalogs and documents) of DRL catalog.

See Condition F in *Special Conditions* on page A-1.

Get URL Supporting Document

Description

Use the GetURLSupportingDocument service to retrieve a URL supporting document.

Input

Table 13-59: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
PKID	string	The PKID of URL supporting document is required

Output

A tPQMItemIdentifier object and tURLSource object with following members would be returned.

Table 13-60: Output

Name	Type	Description
Identifier	tCommonIdentifier	
EffectiveDate	DateTime	
InactiveDate	DateTime	
UploadDate	DateTime	
URLPath	string	
PubToSupplierPortal	boolean	
IsProprietary	boolean	
ExpireDateNotify	boolean	
ExpireDateNotifyNumDays	integer	

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-61: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The tPQMItemSearchIdentifier or PKID input is missing
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PKID_INPUT	The URL source PKID input is invalid
RESULT_WARNINGS	PQM_ITEM_RETRIEVAL_ERROR	Return if unhandled error happened when processing the request

Notes

User must have [PQM_ADMIN] role or WFA read permission to retrieve the PQM item.

See Conditions E and Q in [Special Conditions](#) on page A-1.

Add URL Supporting Documents

Description

Use the AddURLSupportingDocument service to add a URL supporting document to existing PQM items.

Input

Table 13-62: Input

Name	Type	Description
PQMSearchIdentifiers	tPQMItemSearchIdentifier[]	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
NewURLSource	tNewURLSource	

tNewURLSource contains following members:

Table 13-63: tNewURLSource

Name	Type	Description
Title	string	Required
EffectiveDate	DateTime	
InactiveDate	DateTime	Should not be earlier than the effective date
URLPath	string	Required. Should start with http://
PubToSupplierPortal	boolean	
IsProprietary	boolean	
ExpireDateNotify	boolean	
ExpireDateNotifyNumDays	integer	

Output

An overall success indicator and a list of tPQMItemIdentifier objects will be returned.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-64: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The tPQMItemSearchIdentifier objects or tNewURLSource object input is missing
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_URL_SOURCE	The tNewURLSource object input is invalid
	MAX_RECORDS_SAVED	Returned when the number of custom section instances input exceeds the max number allowed to save
RESULT_FAILURE	INVALID_SECURITY_PRIVILEGES	See additional notes below
	CANNOT_ADD_SUPPORTING_DOC	Return if unhandled error happened when processing the request

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

See Conditions E and Q in [Special Conditions](#) on page A-1.

Delete URL Supporting Documents

Description

Use the DeleteURLSupportingDocuments to delete existing URL supporting documents from a PQM item.

Input

Table 13-65: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithIDs	Int[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
PKIDs	string[]	The PKID(s) of URL supporting documents to remove

Output

An overall success indicator and a tPQMItemIdentifier object will be returned.

If all the supporting documents input are successfully removed, the overall result is success. Else, the overall result is fail and the changes will not be saved.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-66: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-66: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The PQMItemIdentifier or PKIDs input is missing
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_PKID	PQM item PKID input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The URL source PKID input is invalid
	MAX_RECORDS_SAVED	Returned when the number of rich text PKID input exceeds the max number allowed to save
RESULT_FAILURE	CANNOT_REMOVE_SUPPORTING_DOC	Unexpected exception occurs when attempting to processing request
	INVALID_SECURITY_PRIVILEGES	See additional notes below
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

User must have read access to the URL supporting documents input.

See Condition Q in [Special Conditions](#) on page A-1.

Add Supporting Document Attachment

Description

Use the AddSupportingDocumentAttachment web service to add an attachment file to an existing attachments procedure on a PQM item.

Input

Table 13-67: Input

Name	Type	Description
PQMSearchIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
ProcedureID	string	The PKID of attachments procedure
NewAttachment	tNewAttachment	

Each tNewAttachment contains following members:

Table 13-68: tNewAttachment

Name	Type	Description
BlobStream	type[]	Required
Title	string	Required
FileName	string	Required
FileType	string	Required
Owner	tUser	
EffectiveDate	DateTime	
InactiveDate	DateTime	Should not be earlier than the effective date
PubToSupplierPortal	boolean	
IsProprietary	boolean	
ExpireDateNotify	boolean	
ExpireDateNotifyNumDays	integer	

Output

The output data includes a success indicator, a tPQMItemIdentifier object, and a tAttachmentsWrapper object representing the attachments procedure changed will be returned.

The attachment is not added successfully, the changes will not be saved.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-69: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The tPQMItemSearchIdentifier objects or tDRLCatalogIdentifier object input is missing
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The procedure ID input is invalid
	INVALID_ATTACHMENT	The supporting document attachment input is invalid
RESULT_FAILURE	INVALID_SECURITY_PRIVILEGES	See additional notes below
	CANNOT_ADD_SUPPORTING_DOC	Return if unhandled error happened when processing the request

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

See Condition Q in [Special Conditions](#) on page A-1.

Delete Supporting Document Attachment

Description

Use the DeleteSupportingDocumentAttachments web service to delete existing supporting document attachments from a PQM item.

Input

Table 13-70: Input

Name	Type	Description
PPQMItemIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
PKIDs	string[]	The PKID(s) of supporting document attachments to remove

Output

An overall success indicator and a tPQMItemIdentifier object will be returned.

If all the supporting documents input are successfully removed, the overall result is success. Otherwise, the overall result is fail and the changes will not be saved.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-71: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-71: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The PQMItemIdentifier or PKIDs input is missing
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_PKID	PQM item PKID input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The supporting document attachment PKID input is invalid
	MAX_RECORDS_SAVED	Returned when the number of rich text PKID input exceeds the max number allowed to save
RESULT_FAILURE	CANNOT_REMOVE_SUPPORTING_DOC	Unexpected exception occurs when attempting to processing request
	INVALID_SECURITY_PRIVILEGES	See additional notes below
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

User must have read access to the parent attachment procedures which hold the supporting document attachments input.

See Condition Q in [Special Conditions](#) on page A-1.

Get Rich Text Supporting Document

Description

Use the GetRichTextSupportingDocument web service to retrieve a rich text supporting document.

Input

Table 13-72: Input

Name	Type	Description
PPQMItemIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
PKID	string	The PKID of rich text supporting document is required

Output

A tPQMItemIdentifier object and a tRichTextDoc object with following members would be returned.

Table 13-73: Output

Name	Type	Description
Identifier	tCommonIdentifier	Including PKID and title
CreationDate	DateTime	The creation date of this rich text supporting document
Content	string	The html data content of the rich text supporting document

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-74: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The PQMItemSearchIdentifier or PKID input is missing
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The rich text PKID input is invalid
RESULT_WARNINGS	PQM_ITEM_RETRIEVAL_ERROR	Returned if unhandled error happened when processing the request

Notes

See Condition Q in [Special Conditions](#) on page A-1.

Add Rich Text Supporting Document

Description

Use the AddRichTextSupportingDocument service to add a rich text supporting document to existing PQM items.

Input

Table 13-75: Input

Name	Type	Description
PQMSearchIdentifiers	tPQMItemSearchIdentifier	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
NewRichTextDoc	tNewRichTextDoc	

tNewRichTextDoc contains following members:

Table 13-76: tNewRichTextDoc

Name	Type	Description
Title	string	Required
Content	string	
KeyWords	string	

Output

An overall success indicator and a list of tPQMItemIdentifier objects will be returned.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-77: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-77: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The tPQMItemSearchIdentifier objects or tNewRichTextDoc object input is missing
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_RICH_TEXT_DOC	The tNewRichTextDoc object input is invalid
	MAX_RECORDS_SAVED	Returned when the number of custom section instances input exceeds the max number allowed to save
RESULT_FAILURE	INVALID_SECURITY_PRIVILEGES	See additional notes below
	CANNOT_ADD_SUPPORTING_DOC	Return if unhandled error happened when processing the request

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

Delete Rich Text Supporting Documents

Description

Use the DeleteRichTextSupportingDocuments to delete existing rich text supporting documents from a PQM item.

Input

Table 13-78: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
PKIDs	string[]	The PKID(s) of rich text supporting documents to remove

Output

An overall success indicator and a tPQMItemIdentifier object will be returned.

If all the supporting documents input are successfully removed, the overall result is success. Otherwise, the overall result is fail and the changes will not be saved.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-79: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-79: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The PQMItemIdentifier or PKIDs input is missing
	INVALID_PQM_ITEM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The rich text PKID input is invalid
	MAX_RECORDS_SAVED	Returned when the number of rich text PKID input exceeds the max number allowed to save
RESULT_FAILURE	CANNOT_REMOVE_SUPPORTING_DOC	Unexpected exception occurs when attempting to processing request
	INVALID_SECURITY_PRIVILEGES	See additional notes below
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

User must have read access to the rich text supporting documents input.

Get DRL Document

Description

Use the GetDRLDocument service to retrieve a DRL document.

Input

Table 13-80: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
PKID	string	The PKID of DRL Document

Output

A tPQMItemIdentifier object and a tDRLDocument object with following members would be returned.

Table 13-81: Output

Name	Type	Description
DocumentIdentifier	tDRLDocumentIdentifier	
Description	string	
Classifications	string	
Version	string	
Originator	tUser	
DocumentDate	DateTime	
ExpirationDate	DateTime	
PubToSupplierPortal	boolean	
ExpireDateNotify	boolean	
ExpireDateNotifyNumDays	integer	
Attachments	tCommonIdentifier[]	

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-82: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The tPQMItemSearchIdentifier or PKID input is missing
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_SECURITY_PRIVILEGES	User has no permission to view the PQM item or DRL document
	INVALID_PKID_INPUT	The DRL document PKID input is invalid
RESULT_WARNINGS	PQM_ITEM_RETRIEVAL_ERROR	Return if unhandled error happened when processing the request

Notes

User must have [PQM_ADMIN] role or WFA read permission to retrieve the PQM item.

User must have [DRL_VIEWER] role to retrieve the DRL document.

Add DRL Document

Description

Use the AddDRLDocument service to add a DRL document to existing PQM items.

Input

Table 13-83: Input

Name	Type	Description
PQMSearchIdentifiers	tPQMItemSearchIdentifier[]	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
DRLDocumentIdentifier	tDRLDocumentIdentifier	

Each tDRLDocumentIdentifier specifies DRL documents according to following rules:

- 1 If the PKID value is given, the DRL document with the same PKID would be added;
- 2 When the DocumentID is given,
 - a If both DocumentNumber and IssueNumber are given, the DRL document with the same DocumentID will be added;
 - b If DocumentNumber is given while IssueNumber is not, all DRL documents with the same DocumentNumber will be added;
- 3 When the Title is given, all DRL documents with the same title will be added.

Output

An overall success indicator and a list of tPQMItemIdentifier objects will be returned.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-84: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The tPQMItemSearchIdentifier objects or tDRLDocumentIdentifier object input is missing
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The DRL document PKID input is invalid
	INVALID_DOCUMENT_ID	The DRL document ID input is invalid
	MAX_RECORDS_SAVED	Returned when the number of rich text PKID input exceeds the max number allowed to save
RESULT_FAILURE	INVALID_SECURITY_PRIVILEGES	See additional notes below
	CANNOT_ADD_SUPPORTING_DOC	Return if unhandled error happened when processing the request

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

Delete DRL Documents

Use the DeleteDRLDocuments service to delete existing DRL documents from a PQM item.

Input

Table 13-85: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier[]	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
DRLDocumentIdentifiers	tDRLDocumentIdentifier[]	The identifier of DRL document to remove

Each tDRLDocumentIdentifier specifies DRL documents according to following rules:

- 1** If the PKID value is given, the DRL document with the same PKID would be removed;
- 2** When the DocumentID is given,
 - a** If both DocumentNumber and IssueNumber are given, the DRL document with the same DocumentID will be removed;
 - b** If DocumentNumber is given while IssueNumber is not, all DRL documents with the same DocumentNumber will be removed;
- 3** When the Title is given, all DRL documents with the same title will be removed.

Output

An overall success indicator and a tPQMItemIdentifier object will be returned.

If all the supporting documents input are successfully removed, the overall result is success. Else, the overall result is fail and the changes will not be saved.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-86: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	The PQMItemIdentifier or PKIDs input is missing
	INVALID_PQM_ITEM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The DRL document PKID input is invalid
	INVALID_DOCUMENT_ID	The DRL document ID input is invalid
	MAX_RECORDS_SAVED	Returned when the number of rich text PKID input exceeds the max number allowed to save
RESULT_FAILURE	CANNOT_REMOVE_SUPPORTING_DOC	unexpected exception occurs when attempting to processing request
	INVALID_SECURITY_PRIVILEGES	See additional notes below
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

Add DRL Catalog

Description

Use the AddDRLCatalog service to add a DRL catalog to existing PQM items.

Input

Table 13-87: Input

Name	Type	Description
PQMSearchIdentifiers	tPQMItemSearchIdentifier[]	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
DRLCatalogIdentifier	tDRLCatalogIdentifier	

Each tDRLCatalogIdentifier object specifies DRL catalogs according to following rules:

- 1 When the PKID is given, the DRL catalog with the same PKID will be added;
- 2 When the external ID is given, the DRL catalog with the same external ID will be added;
- 3 When the title is given, all DRL catalogs with the same title will be added.

Output

An overall success indicator and a list of tPQMItemIdentifier objects will be returned.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-88: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-88: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The tPQMItemSearchIdentifier objects or tDRLCatalogIdentifier object input is missing
	INVALID_PQM_PKID	The DRL catalog PKID input is invalid
	INVALID_EXTERNAL_ID	The DRL catalog external ID input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The DRL document PKID input is invalid
	INVALID_EXTERNAL_ID	The DRL catalog external ID input is invalid
	MAX_RECORDS_SAVED	Returned when the number of PQMSearchIdentifiers input exceeds the max number allowed to save
RESULT_FAILURE	INVALID_SECURITY_PRIVILEGES	See additional notes below
	CANNOT_ADD_SUPPORTING_DOC	Returned if unhandled error happened when processing the request

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

Delete DRL Catalogs

Description

Use the DeleteDRLCatalogs to delete existing DRL catalogs from a PQM item.

Input

Table 13-89: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier[]	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
DRLCatalogIdentifiers	tDRLCatalogIdentifier[]	The identifiers of DRL catalog to remove

Each tDRLCatalogIdentifier object specifies DRL catalogs according to following rules:

- 1 When the PKID is given, the DRL catalog with the same PKID will be removed;
- 2 When the external ID is given, the DRL catalog with the same external ID will be removed;
- 3 When the title is given, all DRL catalogs with the same title will be removed.

Output

An overall success indicator and a tPQMItemIdentifier object will be returned.

If all the supporting documents input are successfully removed, the overall result is success. Else, the overall result is fail and the changes will not be saved.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-90: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETERS	The PQMItemIdentifier or DRL catalog identifiers input is missing
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_ITEM_PKID	PQM item PKID input is invalid
	INVALID_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The DRL catalog PKID input is invalid
	INVALID_EXTERNAL_ID	The DRL catalog external ID input is invalid
	MAX_RECORDS_SAVED	Returned when the number of DRL catalog identifiers input exceeds the max number allowed to save
RESULT_FAILURE	CANNOT_REMOVE_SUPPORTING_DOC	Unexpected exception occurs when attempting to processing request
	INVALID_SECURITY_PRIVILEGES	See additional notes below
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

Get Attachment

Description

Use the GetAttachment service to retrieve an attachment file of supporting document or DRL document.

Input

Table 13-91: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier[]	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
PKID	string	The PKID of attachment document

Output

A tPQMItemIdentifier object along with a tAttachment object or tSupportingDocumentAttachment object would be returned.

Each tAttachment object contains following members:

Table 13-92: tAttachment

Name	Type	Description
Identifier	tCommonIdentifier	
Path	string	
PKID	string	The PKID of attachment document
FileSize	long	
FileName	string	
BlobStream	Byte[]	

tSupportingDocumentAttachment: tAttachment is defined as:

Table 13-93: tSupportingDocumentAttachment

Name	Type	Description
FileType	string	
Owner	tUser	
EffectiveDate	DateTime	
InactiveDate	DateTime	
UploadDate	DateTime	
PubToSupplierPortal	boolean	
IsProprietary	boolean	
ExpireDateNotify	boolean	
ExpireDateNotifyNumDays	integer	

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-94: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The PKID or tPQMItemSearchIdentifier input is missing
	INVALID_PKID_INPUT	The attachment PKID input is invalid
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_SECURITY_PRIVILEGES	User has no permission to view the PQM item or attachment document
RESULT_WARNINGS	PQM_ITEM_RETRIEVAL_ERROR	Return if unhandled error happened when processing the request

Add Attachment Procedure

Description

Use the AddAttachmentProcedure service to add a attachment procedure to an existing PQM item.

Input

Table 13-95: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier[]	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
NewAttachmentProcedure	tNewAttachmentsWrapper	

Each tNewAttachmentsWrapper object contains following members:

Table 13-96: tNewAttachmentsWrapper

Name	Type	Description
SecurityClassification	EnumSecurityClassifications	Required. Could be Undefined, Contextual, or NonContextual
NewAttachments	tNewAttachment[]	

Output

An overall success indicator and a list of tPQMItemIdentifier objects will be returned.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-97: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-97: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The tPQMItemSearchIdentifier object or tNewAttachmentsWrapper object input is missing
	INVALID_PQM_PKID	PQM item PKID input is invalid
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_ATTACHMENT	The tNewAttachmentsWrapper input is invalid
RESULT_FAILURE	INVALID_SECURITY_PRIVILEGES	See additional notes below
	CANNOT_ADD_SUPPORTING_DOC	Return if unhandled error happened when processing the request

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

Delete Attachment Procedures

Description

Use the DeleteAttachmentProcedures web service to delete existing supporting documents from a PQM item.

Input

Table 13-98: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier[]	
RestrictToStatusWithIDs	integer[]	Array of one or more workflow status tag behavior IDs to restrict the PQM items found using the PQMItemIdentifier
PKIDs	string[]	The PKID(s) of attachments procedures to remove

Output

An overall success indicator and a tPQMItemIdentifier object will be returned.

If all the supporting documents input are successfully removed, the overall result is success. Otherwise, the overall result is fail and the changes will not be saved.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-99: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-99: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	The PQMItemIdentifier or PKIDs input is missing
	INVALID_PQM_ITEM_NUMBER	PQM item number input is invalid
	INVALID_PQM_ITEM_PKID	PQM item PKID input is invalid
	INVALID_PQM_CROSS_REFERENCE	Cross reference input is invalid
	INVALID_PKID_INPUT	The attachments procedure PKID input is invalid
	MAX_RECORDS_SAVED	The tNewAttachmentsWrapper input is invalid
RESULT_FAILURE	CANNOT_REMOVE_SUPPORTING_DOC	An unexpected exception occurs when attempting to processing request
	INVALID_SECURITY_PRIVILEGES	See additional notes below
	NO_PQM_ITEM_FOUND	Returned if no PQM item found for the input

Notes

User must have [PQM_ADMIN] role or WFA read and write permissions to edit the PQM item.

User must have read access to the attachment procedures input.

Add Cross References

Description

Use the AddCrossReferences web service to add cross references to a PQM item.

Input

The input is an array of tAddCrossReferencesInputWrapper.

tAddCrossReferencesInputWrapper is composed of the following three fields:

Table 13-100: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithBehaviorIDs	int []	An array of workflow tag behavior IDs of allowed PQM object
CrossRefs	tExtCrossReference[]	

Output

The result will be status (bool) and a list of PQMs (tPQMItemIdentifier) affected by the cross reference changes. For each PQM affected, the results include the full cross reference list.

AddCrossReferences returns array of tPQMItemIdentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-101: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-101: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	NPQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference). CrossReferenceInputs should not be empty.
	INVALID_PQM_ITEM_PKID	PQM Item pkid input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type, could only be one of the 4 values: ALL, ACTION, AUDIT, ISSUE
	NO_PQM_CROSS_REFERENCE_FOUND	The cross reference to be added must contain a System ID and Equipment and a valid status defined in system
	UPDATE_DUPLICATE_PQM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not allowed.
	NO_PQM_CROSS_REFERENCE_FOUND	Trying to add Duplicate Cross Reference {0} to the PQM item: {1}
	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when the user does not have permission to update the PQM object: {pqm identifier}
INVALID_SECURITY_PRIVILEGES	User must have role [EXTERNALLY_MANAGED_CROSS_REF_ADMIN] to modify externally managed cross references	
RESULT_FAILURE	ADD_PQM_CROSS_REFERENCES_ERROR	Occurs when an unexpected exception occurs adding cross references to a PQM

Notes

See Conditions E and Q in [Special Conditions](#) on page A-1.

Delete Cross References

Description

Use the DeleteCrossReferences web service to delete cross references from a PQM item.

Input

The input is an array of tDeleteCrossReferencesInput.

tDeleteCrossReferencesInput is composed of the following three fields:

Table 13-102: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithBehaviorIDs	int[]	An array of workflow tag behavior IDs of allowed PQM object
CrossRefs	tCrossReference []	

Output

The result will be status (bool) and a list of PQMs (tPQMItemIdentifier) affected by the cross reference changes. For each PQM affected, the results include the full cross reference list.

DeleteCrossReferences returns array of tPQMItemIdentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-103: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request

Table 13-103: Result codes

RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference). CrossReferenceInputs should not be empty.
	INVALID_PQM_ITEM_PKID	PQM Item pkid input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type, could only be one of the 4 values: ALL, ACTION, AUDIT, ISSUE
	NO_PQM_CROSS_REFERENCE_FOUND	The cross reference to be removed must contain a System ID and Equipment
	UPDATE_DUPLICATE_PQM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not allowed
	NO_PQM_CROSS_REFERENCE_FOUND	Trying to remove Duplicate Cross Reference {0} from the PQM item: {1} Cross Reference ({0}) to be removed didn't exist on PQM item({1})
	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_ROLE_ERROR	Occurs when the user does not have permission to update the PQM object: {pqm identifier}
INVALID_SECURITY_PRIVILEGES	User must have role [EXTERNALLY_MANAGED_CROSS_REF_ADMIN] to modify externally managed cross references	
RESULT_FAILURE	DELETE_PQM_CROSS_REFERENCES_ERROR	Occurs when an unexpected exception occurs removing cross references from a PQM item

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Update Cross References

Description

Use the UpdateCrossReferences web service to update cross references to a PQM item.

Input

The input is an array of tUpdateCrossReferencesInputWrapper. tUpdateCrossReferencesInputWrapper is composed of the following three fields:

Table 13-104: Input

Name	Type	Description
PQMItemIdentifier	tPQMItemSearchIdentifier	
RestrictToStatusWithBehaviorIDs	int[]	An array of workflow tag behavior IDs of allowed PQM object
UpdateCrossRefDetails	tUpdateCrossRefDetail []	

tUpdateCrossRefDetail contains:

- tCrossReference OriginalCrossRef
- tExtCrossReference NewCrossRef

Output

The result will be status (bool) and a list of PQMs (tPQMItemIdentifier) affected by the cross reference changes. For each PQM affected, the results include the full cross reference list.

UpdateCrossReferences returns array of tPQMItemIdentifier.

Possible Result Codes

The response header will contain a result code, indicating the overall status of the web service call. A list of detailed messages will also be provided, with individual message codes, severities, and descriptions. The following result codes may occur:

Table 13-105: Result codes

Result Code	Possible Messages or Warnings	Comments
RESULT_NO_ERRORS	N/A	No errors occurred while processing request
RESULT_INVALID_INPUT	NO_VALID_PARAMETER_S	PQMItemIdentifier is empty (at least one field is required, Pkid, item number, crossreference) UpdateCrossReferenceInputs should not be empty. UpdateCrossRefDetails should not be empty.
	INVALID_PQM_ITEM_PKID	PQM Item pkid input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_PQM_ITEM_NUMBER	PQM Item number input (issue number/action number/audit number) format is invalid. See Condition Q - PQM Item Identifier Formats on page A-5.
	INVALID_CROSS_REFERENCE	Cross Reference input (SystemID, Equivalent) is required. When adding or updating a cross reference, SystemID and Status must be defined in system. See Condition E - Specification Identifier Input Formats on page A-2.
	INVALID_PQM_ITEM_TYPE	Invalid item type, could only be one of the 4 values: ALL, ACTION, AUDIT, ISSUE
	NO_PQM_CROSS_REFERENCE_FOUND	The cross reference to be removed must contain a System ID and Equipment. The cross reference to be added must contain a System ID and Equipment and a valid status defined in system. Cross Reference [{0} and {1}] must contain the same System ID and Equivalent.
	UPDATE_DUPLICATE_PQM_ITEM_ERROR	Update a PQM item: {0} Multiple times is not allowed.

Table 13-105: Result codes

RESULT_INVALID_INPUT continued	NO_PQM_CROSS_REFER ENCE_FOUND	Trying to add Duplicate Cross Reference {0} to the PQM item: {1}
	MAX_RECORDS_SAVED	Occurs if the number of records to be created exceeds the maximum records allowed
	INSUFFICIENT_PQM_RO LE_ERROR	Occurs when the user does not have permission to update the PQM object: {pqm identifier}
	INVALID_SECURITY_ PRIVILEGES	User must have role [EXTERNALLY_MANAGED_CROSS_REF_ADMIN] to modify externally managed cross references
RESULT_FAILURE	UPDATE_PQM_CROSS_R EFERENCES_ERROR	Occurs when an unexpected exception occurs updating cross references of a PQM item

Notes

See Conditions E and Q in *Special Conditions* on page A-1.

Using the CSS Services Web Service

This chapter describes the CSS Services web service. Topics in this chapter include:

- Overview of CSS Services
- *SendResponse*

Overview of CSS Services

CSS Services provide capabilities related to a Transactive Item Publication (TIP). The following operations are supported:

Operation	v24	v25	v30	Description
SendResponse on page 14-2		●	●	Used to asynchronously update a syndicated TIP's status, and provide a Cross Reference to add to the TIP.

Service Endpoint Locations

v25 endpoint

<http://<servername>/Integration/ProdikaContracts/CSS/CSSServices.svc>

v30 endpoint

<http://<servername>/Integration/ProdikaContracts/CSS/CSSServices.svc>

SendResponse

Description

The CSS Send Response web service allows external systems to asynchronously update the status of syndicated TIP. A list of Cross References can be included in the message to be added to the specification that contains the TIP. The web service message is serialized and saved as an XML file in the relevant CSS directory for the CSS Reconciler to process.

Input

The following input criteria are available:

Table 14-1: Input

Name	Type	Description
crossReference	tLegacySystem	Array of tLegacySystem, as described in <i>tLegacySystem</i> on page A-29
header	tHeader	Message header, as described below
message	tMessage	Array of tMessage, as described below

tHeader

Represents header information for the TIP

Table 14-2: Objects

Name	Description
dateSent	The time stamp of the TIP sent out by CSS.
messageIdentifier	The unique identifier and correlation of the message sent out by CSS.
receiver	The registered syndicate target system identifier.
sender	The registered syndicate source system (Agile PLM for Process) identifier.

tMessage

Represents a syndicate message

Table 14-3: Objects

Name	Description
code	Identifies the syndicate result status, following this rule: 1: New 2: Pending 4: Successful 8 or 600: Failed
description	Syndicate result message from the target system.
severity	Extendable field for customer; not used by core functionality.

Special Conditions, Status Codes, and Core Objects

This appendix contains a list of special conditions, status codes, and core objects.

Special Conditions

Condition A - No Issue Specified in Input Criteria

- 1 Because multiple specifications may reference the same Cross Reference, calling this service using a Cross Reference may return more than one specification.
- 2 If a Cross Reference (or a Spec Number without an Issue Number) is used as input, the latest Issue Number is retrieved. Additionally, if AllowOnlyApprovedSpec is set to “True,” only the latest Approved issue number is retrieved, if one exists (see Condition C, below).

Condition B - Business Unit Visibility

- 1 Business unit visibility rules are enforced to restrict access to specifications. The user calling the web service will not be able to retrieve specification information for specifications outside of his/her business unit access.

Condition C - Allow Only Approved Spec

- 1 Restricts results to only return specifications that are in an Approved workflow status. Uses a configurable SystemAction name that can be modified through configuration settings. Validates this system action is associated to the workflow status of the specification.

Note This requires workflow tags to be set up on workflows indicating which workflow status should be considered as Approved.

- 2 If a Spec Input criterion includes the Spec Number and Issue Number, and Allow Only Approved Spec is set to “True,” the specification will only be returned if the workflow status it is in has the associated system action.

Condition D - Specification Types

1 Possible specification type values:

- 1004—Material specification
- 1005—Master specifications
- 1006 —Labeling specification
- 1009—Packaging material specification
- 1010—Delivered material packing specification
- 2076—Packing configuration
- 2121—Printed packaging specification
- 2147—Trade specification
- 2280—Equipment specification
- 5750—Nutrient profile
- 5816—Formulation specification
- 6500—Menu Item specification
- 6501—Product specification

Condition E - Specification Identifier Input Formats

1 SpecificationNumber

- SpecNumber—**Required**; must be seven digits
- IssueNumber—**Optional**; if provided must be three digits

2 Cross Reference format allowed

- SystemId—**Required**
- Equivalent Value—**Required**

Condition F - Max Records Retrieved

- ### **1** Maximum record count was exceeded. Additional records may be available, but only the maximum record count of records will be returned. Maximum record count settings are configurable.

Condition G - Max Records Allowed For Save

- ### **1** Allowable maximum record count for Saves was exceeded. Maximum record count settings are configurable.

Condition H - InFoodsCode

Run the following SQL query to retrieve the list of InFoods IDs:

```
select ml.Name, p.InFoodsID, p.UNID, p.SequenceNumber
from
    comStandardNutrientProperties p
    inner join comStdNutrientPropertiesML ml
    on ml.fkStandardNutrientProperties = p.pkid
    and langID = 0 and Status = 1
order by ml.name
```

Figure A-1: Some common InFoods IDs

Name	InFoods ID	UNID	Sequence
Calcium	CA	CA	350
Calories	ENERC_KCAL	ENERC_KCAL	10
Carbohydrate (Available)	CHOAVL	CHOAVL	45
Carbohydrates	CHOCDF	CHOCDF	40
Cholesterol	CHOLE	CHOLE	190
Dietary Fiber	FIBTS	FIBTS	50
Energy kJ	ENERC_KJ	ENERC_KJ	20
Iron	FE	FE	370
Polyunsaturated Fat	FAPU	FAPU	150
Potassium	K	K	400
Protein	PROCNT	PROCNT	30
Protein (Nx6.25)	PROCNT_NX625	PROCNTx625	32
Saturated Fat	FASAT	FASAT	130
Sodium	NA	NA	410
Total Fat	FAT	FAT	120
Total solids	TTLSOLID	TTLSOLID	205
Total Sugar	SUGAR	SUGAR	70
Trans Fatty Acid	FATRAN	FATRAN	180
Vitamin A - IU	VITA_IU	VITA_IU	223
Vitamin A - Total	VITA-	VITA-	220
Vitamin C	VITC	VITC	290
Vitamin D	VITD-	VITD-	300
Vitamin E	VITE	VITE	310
Vitamin K	VITK	VITK	330
Zinc	ZN	ZN	420

Condition I - SCRM Entity Input

- 1 tSCRMEntity must be a tSCRMFacility
 - a tSCRMFacility
 - tSCRMEntityIdentifier facilityIdentifier
- 2 tSCRMEntityIdentifier must be a tSCRMEntityNumber or tSCRMEntityCrossRef
 - a tSCRMEntityNumber
 - EntityNumber (string, seven characters) - Oracle Agile PLM facility or company number
 - b tSCRMEntityCrossRef
 - SystemID (string, 100 characters)
 - EquivalentValue (string, 100 characters)

Condition J - Allow Only Approved Entity

- 1 Setting value to true restricts the results to only return specification-related sourcing approvals that are in an approved workflow status. Non specification-related sourcing approvals are not affected by this setting.
- 2 Uses a configurable workflow tag name that can be modified through a configuration setting (see Chapter 2, [Configuration File Changes](#) section, using the SCRMApprovedWorkflowName variable). Validates this workflow tag is associated to the workflow status of the sourcing approval.

Note Note this requires workflow tags to be set up on workflows indicating which workflow status should be considered as approved.

Condition K - Invalid Company Input Formats

- 1 Company Number format allowed: **Required**; must be 7 digits
- 2 Cross Reference format allowed: SystemId and EquivalentValue are required

Condition L - Invalid Facility Input Formats

- 1 Facility Number format allowed: **Required**; must be 7 digits
- 2 Cross Reference format allowed: SystemId and EquivalentValue are required

Condition M - Invalid EQ Input Formats

- 1 EQ Number format allowed: **Required**; must be 7 digits

Condition N - Invalid Security Privileges

- 1 Must be EQ owner or Additional Administrators
- 2 All EQ types are accepted except Get Compliance Items, Get Breakdown Info, and Get Nutrition info, which are only accepted for material, product, and trade questionnaires

Condition O - Invalid Custom Sections MetaData Input Formats

- 1 Custom Section ID format allowed: Optional; not more than 24 digits
- 2 Custom Section Number format allowed: Optional; not more than 8 digits

Condition P - Invalid Extended Attributes MetaData Input Formats

- 1 Extended Attribute ID format allowed: Required; not more than 24 digits

Condition Q - PQM Item Identifier Formats

- 1 ItemNumber: Issue Number, Action Number, or Audit Number; 8 digits
- 2 ItemPKID: Issue PKID, Action PKID, or Audit PKID; 10 characters
- 3 CrossReference: CrossReference values on issue, action, or audit

Status Codes

Status codes determine how the user interface displays an item. The codes are detailed in the table below:

Table A-1: Status Codes

Code	Status	Description
0	Inactive	The item may not be assigned but may be searched
1	Active	The item is assignable and searchable
-1	Archived	The item is neither assignable nor searchable

Core Objects

This section provides a list of some of the core objects exposed in the API. Please refer to the XSDs for more detail.

- [tSpecIdentifierCriterion](#) on page A-10
- [tSpecificationNumber](#) on page A-10
- [tCrossReference](#) on page A-10
- [tExtCrossReference](#) on page A-11
- [tSpecificationIdentifier](#) on page A-11
- [tQueryOptions](#) on page A-12
- [DateRange](#) on page A-12
- [ModifiedBetweenDateRange](#) on page A-13
- [CreatedBetweenDateRange](#) on page A-13
- [tSpecificationSummaryWrapper](#) on page A-13
- [tSpecificationSummary](#) on page A-14
- [tCostItem](#) on page A-14
- [tSCRMEntity](#) on page A-14
- [tSCRMCompany](#) on page A-15
- [tSCRMFacility](#) on page A-15
- [tSCRMEntityIdentifier](#) on page A-15
- [tSCRMEntityNumber](#) on page A-15
- [tSCRMEntityCrossRef](#) on page A-16
- [tExtSCRMEntityCrossRef](#) on page A-16
- [tSCRMEntityIdentifier](#) on page A-16
- [tSCRMEntityNumber](#) on page A-17
- [tSCRMEntityCrossRef](#) on page A-17
- [tFacility](#) on page A-18
- [tFacilityInfo](#) on page A-18
- [tCompany](#) on page A-18
- [tCompanyInfo](#) on page A-19
- [tSCRMAddress](#) on page A-19
- [tSCRMAdministrativeInfo](#) on page A-20
- [tSCRMBusinessUnits](#) on page A-20
- [tSpecRelatedSourcingApprovalInfo](#) on page A-20
- [tSCRMSourcingApprovalInfo](#) on page A-20
- [tCustomLookup](#) on page A-21
- [tNutrientDataWrapper](#) on page A-21
- [tNutrientItem](#) on page A-21
- [tActivityInfo](#) on page A-22

- [tActivitySummary](#) on page A-22
- [tPrimaryActionItemInfo](#) on page A-22
- [tRelatedItemInfo](#) on page A-23
- [tIDName](#) on page A-23
- [tCustomSectionMetaDataInputCriteria](#) on page A-23
- [tCustomSectionID](#) on page A-23
- [tCustomSectionNumber](#) on page A-24
- [tCustomSection](#) on page A-24
- [tCustomSectionRow](#) on page A-24
- [tCustomSectionColumn](#) on page A-24
- [tExtendedAttribute](#) on page A-25
- [tSpecIngredientStatementInfo](#) on page A-25
- [tEQNumber](#) on page A-25
- [tEQExtendedAttribute](#) on page A-25
- [tExtension](#) on page A-26
- [tEQComplianceInfo](#) on page A-26
- [tEQIdentifier](#) on page A-27
- [tComplianceItem](#) on page A-27
- [tComplianceItemContained](#) on page A-27
- [tEQSummary](#) on page A-27
- [tSupplierContactInfo](#) on page A-28
- [tCompanyContactInfo](#) on page A-28
- [tEQIdentifier](#) on page A-28
- [tNutrientInfo](#) on page A-28
- [tEQCriteriaItem](#) on page A-29
- [tLegacySystem](#) on page A-29
- [tPQMItemIdentifier](#) on page A-29
- [tExtCrossReference](#) on page A-30
- [tPQMItemType](#) on page A-30
- [tCommonLookup](#) on page A-30
- [tPqmCommonSummary](#) on page A-30
- [tPqmIssueSpecificSummary](#) on page A-31
- [tPqmActionSpecificSummary](#) on page A-31
- [tPqmAuditSpecificSummary](#) on page A-31
- [tPQMAssociatedProject](#) on page A-32
- [tBasePQMItemSearchIdentifier](#) on page A-32
- [tCrossReference](#) on page A-32
- [tPQMItemSearchIdentifier](#) on page A-32
- [tIssueDetails](#) on page A-33

- [tActionDetails](#) on page A-34
- [tAssociatedNPDProject](#) on page A-35
- [tAuditDetails](#) on page A-35
- [tPQMItemSupplierIdentifier](#) on page A-36
- [tPQMItemSupplier](#) on page A-37
- [tSourceSystemIdentifier](#) on page A-37
- [tPQMItemSupplierSearchIdentifier](#) on page A-37
- [tSourceSystemPQMItemSupplierIdentifier](#) on page A-37
- [tSCRMEntityCrossRefPQMItemSupplierIdentifier](#) on page A-38
- [tSCRMEntityNumberPQMItemSupplierIdentifier](#) on page A-38
- [tPQMItemAffectedItemsResult](#) on page A-38
- [tPQMAffectedItem](#) on page A-38
- [tIssueAffectedItem](#) on page A-39
- [tAffectedItemInput](#) on page A-40
- [tPQMAffectedItemIdentifier](#) on page A-41
- [tPQMAffectedItemGSMIdentifier](#) on page A-41
- [tPQMAffectedItemSourceSystemIdentifier](#) on page A-41
- [tIssueAffectedItemInput](#) on page A-42
- [tNCRAffectedItemInput](#) on page A-42
- [tPQMSearchCriteria](#) on page A-44
- [tSupplierSearchIdentifier](#) on page A-44
- [tExternalSupplierSearchIdentifier](#) on page A-45
- [tSCRMSupplierSearchIdentifier](#) on page A-45
- [tRelatedPQMItemsWrapper](#) on page A-45
- [tRelatedPQMItem](#) on page A-45
- [tRelatedPQMActionItem](#) on page A-46
- [tRelatedPQMAuditItem](#) on page A-46
- [tCommonIdentifier](#) on page A-46
- [tDRLDocumentIdentifier](#) on page A-47
- [tDRLCatalogIdentifier](#) on page A-47
- [tAttachmentsWrapper](#) on page A-47
- [tDRLCatalog](#) on page A-48
- [tPQMSupportingDocWrapper](#) on page A-48
- [tRichTextDoc](#) on page A-48
- [tNewRichTextDoc](#) on page A-49
- [tURLSource](#) on page A-49
- [tNewURLSource](#) on page A-49
- [tDRLDocument](#) on page A-50
- [tAttachment](#) on page A-50

- [tSupportingDocAttachment](#) on page A-51
- [tNewAttachment](#) on page A-51
- [tNewAttachmentsWrapper](#) on page A-52
- [tCustomSectionInstance](#) on page A-52

tSpecIdentifierCriterion

Abstract object that represents specification identifying information used as input criteria, such as the specification number and issue number or a cross reference (SystemId and Equivalent)

Subtypes

- tSpecificationNumber
- tCrossReference

tSpecificationNumber

Represents a specification’s Spec Number and the (optional) Issue Number

Supertype

tSpecIdentifierCriterion

Table A-2: Objects

Name	Type	Description
SpecNumber	string	Specification number; 7 digits
IssueNumber	string	Issue number; optional; 3 digits

tCrossReference

Represents a specification’s cross references (SystemId and Equivalent) and is used in input to identify a GSM specification.

Supertype

tSpecIdentifierCriterion

Table A-3: Objects

Name	Type	Description
SystemId	string	ID of a third-party system; 50 characters
EquivalentValue	string	ID of a GSM specification in a third-party system; 50 characters

Schema Component Representation

```
<xs:complexType name="tCrossReference">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:tSpecIdentifierCriterion">
      <xs:sequence>
        <xs:element name="SystemId" type="xs:string"
nillable="true"/>
        <xs:element name="EquivalentValue"
type="xs:string" nillable="true"/>
        <xs:element name="Extension"
type="q1:tExtension" minOccurs="0" nillable="true"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

tExtCrossReference

Represents a specification's cross references (SystemId and Equivalent) and is used in output.

Supertype

tCrossReference

Table A-4: Objects

Name	Type	Description
SystemId	string	ID of a third-party system; 50 characters
EquivalentValue	string	ID of a GSM specification in a third-party system; 50 characters
Description	string	Description of third-party system; 256 characters
Status	string	A valid status defined in system; 40 characters
UOMs	tUOM[]	An array of valid UOMs defined in system

tSpecificationIdentifier

Represents specification identifying information used as output, includes the specification number and issue number, and a list of cross references (SystemId and Equivalent).

Table A-5: Objects

Name	Type	Description
SpecificationNumber	tSpecificationNumber (See tSpecificationNumber on page A-10)	SpecNumber IssueNumber
CrossReferences	tExtCrossReference[] (See tExtCrossReference on page A-11)	SystemId, EquivalentValue, Status, Description, and UOMs

tQueryOptions

Represents search criteria options.

Table A-6: Objects

Name	Type	Description
AllowOnlyApprovedSpec	boolean	See Condition C - Allow Only Approved Spec on page A-1
CrossReference	tCrossReference (See tCrossReference on page A-10)	Specification cross reference
DateRange	DateRange (See DateRange on page A-12)	CreatedBetweenDateRange or ModifiedBetweenDateRange
IncludeSpecTemplates (v25 and v30 only)	boolean	Search results include specification templates. (For v24, by default, excludes templates from search results.)
Originators	Originators	List of usernames or user external IDs. These are login names.
SpecName	string	Name of specification
ShortName	string	Short name of specification. Only returned if ShortName is enabled through the core application FeatureConfig.
SpecStatus	string[]	List of specification workflow statuses
SpecTypes	string[]	List of four digit specification type values. See Condition D - Specification Types on page A-2.

DateRange

Abstract object that represents a date range (Start Date and End Date)

Subtypes

- ModifiedBetweenDateRange
- CreatedBetweenDateRange

Table A-7: Objects

Name	Type	Description
StartDate	datetime	Start date for search; required
EndDate	datetime	Optional

Schema Component Representation

```
<xs:complexType name="DateRange">
  <xs:sequence>
    <xs:element name="StartDate" type="xs:dateTime" />
    <xs:element minOccurs="0" name="EndDate" type="xs:dateTime" />
  </xs:sequence>
</xs:complexType>
```

ModifiedBetweenDateRange

Date range used to evaluate a specification's modified date

Supertype

- DateRange

Table A-8: Objects

Name	Type	Description
StartDate	datetime	Start date for search; required
EndDate	datetime	Optional

CreatedBetweenDateRange

Date range used to evaluate a specification's created date

Supertype

- DateRange

Table A-9: Objects

Name	Type	Description
StartDate	datetime	Start date for search; required
EndDate	datetime	Optional

tSpecificationSummaryWrapper

- Wrapper object that contains a tSpecificationSummary.

Table A-10: Objects

Name	Type	Description
SpecSummary	tSpecificationSummary (See tSpecificationSummary on page A-14)	Specification Summary object

tSpecificationSummary

- Represents common Specification Summary data.

Table A-11: Objects

Name	Type	Description
Name	string	Specification name
ShortName	string	Specification short name; will not be included if feature configuration for short name is disabled
specificationIdentifier	tSpecificationIdentifier (See tSpecificationIdentifier on page A-11)	Spec Number, Issue Number, and list of cross references
SpecType	integer	Specification type (4 digit code)
Status	string	Workflow status
Category	string	Specification taxonomy category
SubCategory	string	Specification taxonomy subcategory
Group	string	Specification taxonomy group
Originator	string	Specification originator's last name and first name
EffectiveDate	datetime	Specification's Effective Date
InactiveDate	datetime	Specification's Inactive Date
Supercedes	string	Specification supercedes value
ReasonForChange	string	Specification Reason for change value
IsTemplate (v25 and v30 only)	boolean	Indicates if the specification is a template

tCostItem

This represents a cost item displayed in GSM.

Table A-12: Objects

Name	Type	Description
SpecCostCrossReference	tCrossReference (See tCrossReference on page A-10)	Cross reference of the specification to modify
Currency	string	ISO code for the currency to use
CostType	string	
SCRMENTITY	tSCRMENTITY (See tSCRMENTITY on page A-14)	SCRMENTITY Facility to associate the specification cost to; required
Cost	double	The new cost value; required
CostUOM	string	ISO code
EffectiveDate	dateTime	When the value goes into effect; required

tSCRMENTITY

This is an abstract base class for SCRMENTITY items

tSCRMCompany

This is a tSCRMEntity that identifies an SCRM company

Table A-13: Objects

Name	Type	Description
companyIdentifier	tSCRMEntityIdentifier (See tSCRMEntityIdentifier on page A-15)	Identifies one company

tSCRMFacility

This is a tSCRMEntity that identifies an SCRM facility

Table A-14: Objects

Name	Type	Description
companyIdentifier	tSCRMEntityIdentifier (See tSCRMEntityIdentifier on page A-15)	Identifies one facility

tSCRMEntityIdentifier

Abstract object that represents entity identifying information used as input criteria, such as a facility number OR a cross reference (SystemId and Equivalent)

Subtypes

- tSCRMEntityNumber
- tSCRMEntityCrossRef

tSCRMEntityNumber

This is a tSCRMEntityIdentifier that identifies an entity number, such as facility number

Table A-15: Objects

Name	Type	Description
EntityNumber	string	Facility profile number

tSCRMEntityCrossRef

This is a facility’s cross references (SystemId and Equivalent) and is used in input to identify a SCRMEntityCrossRef specification.

Supertype

tSCRMEntityIdentifier

Table A-16: Objects

Name	Type	Description
SystemId	string	ID of a third-party
EquivalentValue	string	ID of an SCRMEntityCrossRef item in a third-party system

Schema Component Representation

```
<xs:complexType name="tSCRMEntityCrossRef">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:tSCRMEntityIdentifier">
      <xs:sequence>
        <xs:element name="SystemId" type="xs:string"
nillable="true"/>
        <xs:element name="EquivalentValue" type="xs:string"
nillable="true"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

tExtSCRMEntityCrossRef

This is a facility’s cross references (SystemId and Equivalent) and is used in output.

Supertype

tSCRMEntityCross Ref

Table A-17: Objects

Name	Type	Description
SystemId	string	ID of a third-party
EquivalentValue	string	ID of an SCRMEntityCrossRef item in a third-party system
Status	string	Valid status defined in system; 40 characters

tSCRMEntityIdentifier

Abstract object that represents entity identifying information used as input criteria, such as a facility number OR a cross reference (SystemId and Equivalent)

Subtypes

- tSCRMEntityNumber
- tSCRMEntityCrossRef

tSCRMEntityNumber

Represents an entity number, such as a facility or company number

Supertype

tSCRMEntityIdentifier

Table A-18: Objects

Name	Type	Description
EntityNumber	string	Facility or company profile number

tSCRMEntityCrossRef

Represents a facility's or company's cross references (SystemId and Equivalent)

Supertype

tSCRMEntityIdentifier

Table A-19: Objects

Name	Type	Description
SystemId	string	ID of a third-party
EquivalentValue	string	ID of an SCRMEntity in a third-party system

Schema Component Representation

```
<xs:complexType name="tSCRMEntityCrossRef">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:tSCRMEntityIdentifier">
      <xs:sequence>
        <xs:element name="SystemId" type="xs:string"
nillable="true"/>
        <xs:element name="EquivalentValue" type="xs:string"
nillable="true"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

tFacility

Represents a facility used by output

Table A-20: Objects

Name	Type	Description
SystemId	string	ID of a third-party
EquivalentValue	string	ID of an SCRM item in a third-party system
FacilityInfo	tFacilityInfo	See tFacilityInfo on page A-18
AdministrativeInfo	tSCRMAdministrativeInfo	See tSCRMAdministrativeInfo on page A-20
BusinessUnits	tSCRMBusinessUnits[]	See tSCRMBusinessUnits on page A-20
CrossRefs	tExtSCRMEntityCrossRef []	See tSCRMEntityCrossRef on page A-17
SpecRelatedSourcingApprovals	tSpecRelatedSourcingApprovalInfo []	See tSpecRelatedSourcingApprovalInfo on page A-20
NonSpecRelatedSourcingApprovals	tSCRMSourcingApprovalInfo	See tSCRMSourcingApprovalInfo on page A-20

tFacilityInfo

Represents general facility Summary data

Table A-21: Objects

Name	Type	Description
Number	string	Facility profile number
Name	string	Facility name
WebSite	string	Facility website
Phone	string	Facility phone
Fax	string	Facility fax
StreetAddress	tSCRMAddress	Facility street address
PostalAddress	tSCRMAddress	Facility postal address

tCompany

Represents a company used by output

Table A-22: Objects

Name	Type	Description
Number	string	Facility profile number
Name	string	Facility name
WebSite	string	Facility website
Phone	string	Facility phone
Fax	string	Facility fax
StreetAddress	tSCRMAddress	Facility street address

Table A-22: Objects

PostalAddress	tSCRMAddress	Facility postal address
CompanyInfo	tCompanyInfo	See tCompanyInfo on page A-19
AdministrativeInfo	tSCRMAdministrativeInfo	See tSCRMAdministrativeInfo on page A-20
BusinessUnits	tSCRMBusinessUnits[]	See tSCRMBusinessUnits on page A-20
ParentCompanies	tSCRMEntityNumber[]	A collection of parent companies for a company
ChildCompanies	tSCRMEntityNumber[]	A collection of child companies for a company
CrossRefs	tExtSCRMEntityCrossRef[]	A collection of cross references for a company
Facilities	tSCRMEntityNumber[]	A collection of facilities associated with a company

tCompanyInfo

Represents general company Summary data

Table A-23: Objects

Name	Type	Description
Number	string	Company profile number
Name	string	Company name
WebSite	string	Company website
Phone	string	Company phone
Fax	string	Company fax
StreetAddress	tSCRMAddress	Company street address
PostalAddress	tSCRMAddress	Company postal address

tSCRMAddress

Represents an address

Table A-24: Objects

Name	Type	Description
Street1	string	Street address or a postal address
Street2	string	Street address or a postal address
City	string	City of a street address or a postal address
State	string	State or province of a street address or a postal address
PostalCode	string	Postal code of a street address or a postal address
Country	string	Country of a street address or a postal address

tSCRMAministrativeInfo

Represents entity administrative information

Table A-25: Objects

Name	Type	Description
specialAttributes	string[]	Special attributes for a facility or company
specialNotes	string	Special notes for a facility or company

tSCRMBusinessUnits

Represents business units associated with an entity

Table A-26: Objects

Name	Type	Description
Names	string[]	Business unit names
Status	string	Status for business units

tSpecRelatedSourcingApprovalInfo

Represents specification-related sourcing approval information for a facility

Table A-27: Objects

Name	Type	Description
Number	string	Sourcing approval number
PKID	string	Sourcing approval PKID
SpecNumber	string	Related specification number

tSCRMSourcingApprovalInfo

Represents non-specification related sourcing approval information for a facility

Table A-28: Objects

Name	Type	Description
Number	string	Sourcing approval number
PKID	string	Sourcing approval PKID

tCustomLookup

This describes one custom lookup option used by qualitative lookup extended attributes

Table A-29: Objects

Name	Type	Description
Category	string	Each extended attribute displays one category of options. This is the name of one category. The name does not have to already exist.
Value	string	The text displayed for this custom lookup option
ExternalId	string	A key for this option from a third-party system
Sequence	integer	The user interface displays options by sequence number. Lower numbers display before higher ones.
Status	integer	See Status Codes on page A-6

tNutrientDataWrapper

This describes the nutrient items for one specification

Table A-30: Objects

Name	Type	Description
specificationIdentifier	tSpecificationIdentifier (See tSpecificationIdentifier on page A-11)	Specification number, issue number, and list of cross references
SpecType	integer	A specification type code. See Condition D - Specification Types on page A-2.
NutrientItems	tNutrientItem[] (See tNutrientItem on page A-21)	Nutrient items for the specification

tNutrientItem

This describes one nutrient item for one specification

Table A-31: Objects

Name	Type	Description
InfoodsCode	string	INFOODS tag name for the type of nutrient
ValuePer100Gms	double	The amount of the nutrient per 100g of the item
UOM	tUOM	ISO code, ID, and abbreviated name for the unit for ValuePer100Gms
Source	string	Source description
Comments	string	Additional notes

tActivityInfo

Represents activity information used as output

Table A-32: Objects

Name	Type	Description
ActivitySummary	tActivitySummary	Activity summary
PrimaryActionItemInfo	tPrimaryActionItemInfo	Activity primary action item
RelatedItemInfos	tRelatedItemInfo[]	An array of activity related items

tActivitySummary

Represents an activity summary information

Table A-33: Objects

Name	Type	Description
Title	string	Activity title
Number	tSpecificationNumber	Activity number
Type	tIDName	Activity type
Originator	string	Activity originator
Status	string	Activity status
SpecialNotes	string	Special notes
SpecReaderNotificationFlag	boolean	Notify specification reader of this activity
EffectiveDate	DateTime	Effective date
InactiveDate	DateTime	Inactive date
LastEditDate	DateTime	Last edit date

tPrimaryActionItemInfo

Represents an activity primary action item

Table A-34: Objects

Name	Type	Description
ItemName	string	Primary action item name
ItemNumber	tSpecificationNumber	Primary action item number
ItemStatusDependentFlag	boolean	Specification status is dependent on the status of this activity.

tRelatedItemInfo

Represents an activity related item

Table A-35: Objects

Name	Type	Description
Type	tIDName	Related item type
Name	string	Related item name
Number	tSpecificationNumber	Related item number
Status	string	Related item status
Comments	string	Related item comments

tIDName

Represents a combination of ID and Name (value).

Table A-36: Objects

Name	Type	Description
ID	string	ID part of a list item
Name	string	Name/Value part of a list item

tCustomSectionMetaDataInputCriteria

Abstract object that represents custom section identifying information used as input criteria, such as the custom section id OR custom section number

Subtypes

- tCustomSectionID
- tCustomSectionNumber

tCustomSectionID

Represents an entity ID, such as custom section ID

Supertype

tCustomSectionMetaDataInputCriteria

Table A-37: Objects

Name	Type	Description
customSectionID	string	Custom section profile ID

tCustomSectionNumber

Represents an entity number, such as custom section number

Supertype

tCustomSectionMetaDataInputCriteria

Table A-38: Objects

Name	Type	Description
customSectionNumber	string	Custom section profile number

tCustomSection

Represents a custom section used by output

Table A-39: Objects

Name	Type	Description
Number	string	Custom section number
ID	string	Custom section ID
DynamicTags	string[]	Custom section dynamic tags
HideHeader	boolean	Custom section Hide Header
customSectionRows	tCustomSectionRow[]	See tCustomSectionRow on page A-24
customSectionColumns	tCustomSectionColumn[]	See tCustomSectionColumn on page A-24

tCustomSectionRow

Represents general custom section row summary data

Table A-40: Objects

Name	Type	Description
Sequence	int	Custom section row sequence
ID	string	Custom section row ID
DynamicTags	string[]	Custom section row dynamic tags

tCustomSectionColumn

Represents general custom section column summary data

Table A-41: Objects

Name	Type	Description
Sequence	int	Custom section column sequence
ID	string	Custom section column ID
Width	int	Custom section column width
PrintWidth	double	Custom section column print width
DynamicTags	string[]	Custom section column dynamic tags

tExtendedAttribute

Represents an extended attribute used by output

Table A-42: Objects

Name	Type	Description
ID	string	Extended attribute ID
DynamicTags	string[]	Extended attribute dynamic tags

tSpecIngredientStatementInfo

Represents specification material statement information used as output

Table A-43: Objects

Name	Type	Description
SpecificationIdentifier	tSpecificationIdentifier (See tSpecificationIdentifier on page A-11)	A specification identifier
IngredientStatement	string	A material statement for the specification
CombinedStatement	string	A combined statement for the specification

tEQNumber

Represents an entity ID, such as custom section ID or extended attribute ID

Table A-44: Objects

Name	Type	Description
EQNumber	string	EQ number

tEQExtendedAttribute

Represents an eQ extended attribute used by output

Table A-45: Objects

Name	Type	Description
eqNumber	tEQNumber	EQ number
extension	tExtension	See tExtension on page A-26

tExtension

Represents general eQ extended attribute summary data

Table A-46: Objects

Name	Type	Description
Any	XmlElement	See <i>Extended Attribute Types Schema</i> on page A-26
MustUnderstand	int	
MustUnderstandSpecified	boolean	

Extended Attribute Types Schema

Please see the Extended Attribute type schema document, *ExtendedAttributeTypes.xsd*, located in the Web\Integration\Contracts\Prodika\Schema folder for details

tEQComplianceInfo

Represents an EQ compliance data

Table A-47: Objects

Name	Type	Description
eqIdentifier	tEQIdentifier	EQ Number and type
ComplianceWith	tComplianceItem	Compliance name and external ID
AllergensContained	tComplianceItemContained	Compliance name and Measurement and Source
AdditivesContained	tComplianceItemContained	Compliance name and Measurement and Source
IntolerancesContained	tComplianceItemContained	Compliance name and Measurement and Source
AllergensNotContained	tComplianceItem	Compliance name and external ID
AdditivesNotContained	tComplianceItem	Compliance name and external ID
IntoleranceNotContained	tComplianceItem	Compliance name and external ID
AllergensPossiblyContained	tComplianceItemContained	Compliance name and Measurement and Source
AdditivesPossiblyContained	tComplianceItemContained	Compliance name and Measurement and Source
IntolerancesPossiblyContained	tComplianceItemContained	Compliance name and Measurement and Source
AllergensFreeText	String	Allergens free text
IntolerancesFreeText	String	Intolerance free text
AdditivesFreeText	String	Additives free text

tEQIdentifier

Represents EQ number and type information used by output

Table A-48: Objects

Name	Type	Description
EQNumber	string	EQ number
ModelTypeID	string	EQ type

tComplianceItem

Represents EQ compliance name information used by output

Table A-49: Objects

Name	Type	Description
Name	string	Compliance with value
ExternalID	string	External ID

tComplianceItemContained

Represents EQ compliance items information used by output

Table A-50: Objects

Name	Type	Description
ComplianceItem	tComplianceItem	Allergen or Intolerance or Additive value
MaxPer100Grams	tMeasurement	Allergen or Intolerance or Additive measurement
Source	string	Allergen or Intolerance or Additive Source

tEQSummary

Represents EQ summary data

Table A-51: Objects

Name	Type	Description
EQNumber	string	EQ number
EQLabel	string	EQ label
EQType	string	EQ type
Status	string	EQ status
DateSent	DateTime	EQ send data to supplier
DueDate	DateTime	EQ due date
DateReceived	DateTime	EQ receive data from supplier
IsSupplierInitiated	boolean	Is or not supplier initiated
IsImported	boolean	Is or not imported to GSM
Comments	string	EQ comments
PrimaryOwner	String	EQ primary owner

Table A-51: Objects

AdditionalAdmins	String	EQ additional administrators
SupplierContactInfo	tSupplierContactInfo	Supplier contact information
CompanyContactInfo	tCompanyContactInfo	Supplier contact information
MaterialName	string	Imported specification value

tSupplierContactInfo

Represents EQ supplier contact information used by output

Table A-52: Objects

Name	Type	Description
ContactName	string	Contact name
CompanyName	string	Company name
ProdikaSCRMNo	string	Prodika SCRM#
EmailAddress	string	Email address

tCompanyContactInfo

Represents EQ supplier company contact information used by output

Table A-53: Objects

Name	Type	Description
ContactName	string	Supplier contact name
CompanyName	string	Supplier company name

tEQIdentifier

Represent EQ number and type information used by output

Table A-54: Objects

Name	Type	Description
EQNumber	string	EQ number
ModelTypeID	string	EQ type

tNutrientInfo

Represent an EQ nutrient data

Table A-55: Objects

Name	Type	Description
EQIdentifier	tEQIdentifier	EQ number and type
NutrientItems	tNutrientItem[]	EQ nutrient details

tEQCriteriaItem

Represents an EQ criteria item data

Table A-56: Objects

Name	Type	Description
EQIdentifier	tEQIdentifier	EQ number and type

tLegacySystem

Represents a syndicate target system

Table A-57: Objects

Name	Description
externallyManaged	Identifies whether this cross reference value is managed externally.
referenceNumber	Identifies the reference number of the TIP item in the syndicate target system.
systemName	Identifies the syndicate target system code in Agile PLM for Process.

tPQMItemIdentifier

Represents PQM item identifying information used as output; includes the PQM number and a list of cross references (SystemId and Equivalent).

Table A-58: Objects

Name	Type	Description
ItemNumber	string	PQM item number
ItemPKID	string	PQM item pkid
CrossReferences	tExtCrossReference	PQM item cross references
Title	string	PQM item title
WorkflowStatus	string	PQM item workflow status description
PqmType	string	Indicate the PQM item type (issue/ action/audit)
PqmSubType	PQMItemType	PQM item sub type

tExtCrossReference

Represents a PQM item’s cross references (SystemId and Equivalent, Status) in output and also in the input of Adding PQM Cross Reference.

Supertype

- tCrossReference

Table A-59: Objects

Name	Type	Description
SystemId	string	ID of a third-party system; 50 characters
EquivalentValue	string	ID of a PQM item in a third-party system; 50 characters
Status	string	The status of the item
ExtManaged	boolean	Indicates whether it is managed by external system

tPQMItemType

Represents a PQM item’s sub type.

Table A-60: Objects

Name	Type	Description
Name	string	Sub type name
Abbreviation	string	ID of a PQM item in a third-party system; 50 characters
SystemType	tCommonLookup	See tCommonLookup, below

tCommonLookup

Contains 2 fields (Name and Optional Value)

Table A-61: Objects

Name	Type	Description
Name	string	
OptionalValue	string	

tPqmCommonSummary

Represents PQM item summary information which existed in all 3 types (issue, action, audit).

Table A-62: Objects

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	PQM item identifier
Description	string	PQM item description
Originator	string	PQM item originator
ProcessTemplate	string	PQM item workflow template
ProductLines	tCommonLookup[]	PQM item product lines

Table A-62: Objects

Customers	tCommonLookup[]	PQM item customers
IsTemplate	bool	True if it is a PQM item template
CreatedDate	DateTime	PQM item CreatedDate
CompletedDate	DateTime	PQM item CompletedDate
ReleasedDate	DateTime	PQM item ReleasedDate
SubmittedDate	DateTime	PQM item SubmittedDate

tPqmlIssueSpecificSummary

Represents PQM item summary information which only existed in a PQM issue.

Table A-63: Objects

Name	Type	Description
OccurrenceDate	DateTime	PQM item OccurrenceDate
ExpectedResolutionDate	DateTime	PQM item ExpectedResolutionDate
Severity	tCommonLookup	PQM item Severity
Resolution	tCommonLookup	PQM item Resolution

tPqmActionSpecificSummary

Represents PQM item summary information which only existed in a PQM action.

Table A-64: Objects

Name	Type	Description
PreventativeAction	string	PQM item PreventativeAction
RootCauseAnalysis	string	PQM item RootCauseAnalysis
AssociatedProject	tPQMAssociatedProject	PQM item AssociatedProject
Resolution	tCommonLookup	PQM item Resolution

tPqmAuditSpecificSummary

Represents PQM item summary information which only existed in a PAM audit.

Table A-65: Objects

Name	Type	Description
PlannedAuditDate	DateTime	PQM item PlannedAuditDate
ActualAuditDate	DateTime	PQM item ActualAuditDate
AuditResult	tCommonLookup	PQM item AuditResult

tPQMAssociatedProject

Represents an Associated Project of a PQM action.

Table A-66: Objects

Name	Type	Description
ProjectNumber	string	Associated Project Number
ProjectName	string	Associated Project Name
ProjectOwner	string	Associated Project Owner

tBasePQMItemSearchIdentifier

An input in a PQM web service used to identify a PQM item.

Table A-67: Objects

Name	Type	Description
ItemNumber	integer	PQM item number
ItemPKID	string	PQM item pkid
ProjectOwner	tCrossReference	Associated Project Owner

tCrossReference

Represents a PQM’s cross references (SystemId and Equivalent,) in input.

Supertype

- tCrossReference

Table A-68: Objects

Name	Type	Description
SystemId	string	ID of a third-party system; 50 characters
EquivalentValue	string	ID of a PQM item in a third-party system; 50 characters

tPQMItemSearchIdentifier

An input in a PQM web service to identify a PQM item.

Supertype

- tBasePQMItemSearchIdentifier

Table A-69: Objects

Name	Type	Description
SystemId	string	ID of a third-party system; 50 characters

Table A-69: Objects

EquivalentValue	string	ID of a PQM item in a third-party system; 50 characters
Status	string	The status of the item
ExtManaged	boolean	Indicated whether it is managed by an external system
ItemType	string	Only 4 values allowed: ISSUE, ACTION, AUDIT, ALL

IssueDetails

Contains all the issue summary details information used for create/update issue summary.

Table A-70: Objects

Name	Type	Description
IssueTitle	string	PQM item title max 256 characters; required
IssueDescription	string	PQM item description max 4000 characters
IssueType	string	Name of Issue type defined in admin; required
WorkflowTemplateName	string	A value in the system; required
WorkflowStepBehaviorID	int	A value in the system; required Use this value and WorkflowTemplateName to retrieve the workflow status. If multiple values are returned, report error.
Originator	tOriginatorIdentifier	User login name or external ID, defined in admin 1 of the 2 (user login name and external id) is required and only one is allowed
OccurrenceDate	DateTime	
ExpectedResolutionDate	DateTime	
Severity	string	Severity name An Active value defined in Admin>>PQM>>Severity
Resolution	string	Resolution name An Active value defined in Admin>>PQM>> Resolution
ProductLines	String[]	Product Line Names An Active value defined in Admin>>PQM>> ProductLines
Customers	String[]	Customers names An Active value defined in Admin>>PQM>> Customers

Table A-70: Objects

CreateDate	DateTime	Optional, If provided, should override after save.
CompleteDate	DateTime	Optional, If provided, should override after save.
ReleasedDate	DateTime	Optional, If provided, should override after save.
SubmittedDate	DateTime	Optional, If provided, should override after save.

tActionDetails

Contains all the action summary details information used for create/update action summary.

Table A-71: Objects

Name	Type	Description
ProblemStatement	string	PQM item title max 256 required
ActionDescription	string	PQM item description max 4000 characters
ActionType	string	Name of Issue type defined in admin; required
WorkflowTemplateName	string	A value in the system; required
WorkflowStepBehaviorID	int	A value in the system; required Use this value and WorkflowTemplateName to retrieve the workflow status. If multiple values are returned, report error.
Originator	tOriginatorIdentifier	User login name or external ID, defined in admin 1 of the 2 (user login name and external id) is required and only one is allowed
ProductLines	String[]	Product Line Names An Active value defined in Admin>>PQM>> ProductLines
Customers	String[]	Customer names An Active value defined in Admin>>PQM>> Customers
PreventativeAction	string	Preventative action description Max: 4000 characters
RootCauseAnalysis	string	Root Cause Analysis Description Max: 4000 characters

Table A-71: Objects

AssociatedNPDProject	tAssociatedNPDProject	Used to identifier the associated NPD project
CreateDate	DateTime	Optional, If provided, should override after save.
CompleteDate	DateTime	Optional, If provided, should override after save.
ReleasedDate	DateTime	Optional, If provided, should override after save.
SubmittedDate	DateTime	Optional, If provided, should override after save.

tAssociatedNPDProject

Used to identifier the Associated NPD project.

Table A-72: Objects

Name	Type	Description
ItemInternalID	string	NPD project internal ID
NPDProjectNum	string	NPD project number
ItemExternalID	string	NPD project external ID
SourceSystemID	string	“NPD” if it is from v6.1.1 or any other external system ID

tAuditDetails

Contains all the audit summary details information used for create/update audit summary.

Table A-73: Objects

Name	Type	Description
AuditTitle	string	PQM item title max 256 required
AuditDescription	string	PQM item description max 4000 characters
AuditType	string	Name of Issue type defined in admin; required
WorkflowTemplateName	string	A value in the system; required
WorkflowStepBehaviorID	int	A value in the system; required Use this value and WorkflowTemplateName to retrieve the workflow status. If multiple values are returned, report error.

Table A-73: Objects

Originator	tOriginatorIdentifier	User login name or external ID, defined in admin 1 of the 2 (user login name and external id) is required and only one is allowed
PlannedAuditDate	DateTime	Valid date
ProductLines	String[]	Product Line Names An Active value defined in Admin>>PQM>> ProductLines
Customers	String[]	Customer names An Active value defined in Admin>>PQM>> Customers
AuditResult	string	Audit Result Description An Active value defined in Admin>>PQM>> Audit Result
CreateDate	DateTime	Optional, If provided, should override after save.
CompleteDate	DateTime	Optional, If provided, should override after save.
ReleasedDate	DateTime	Optional, If provided, should override after save.
SubmittedDate	DateTime	Optional, If provided, should override after save.

tPQMItemSupplierIdentifier

Output of get Supplier API, contains a tPQMItemIdentifier and an array of tPQMItemSupplier[].

Table A-74: Objects

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	See tPQMItemIdentifier on page A-29
PQMItemSuppliers	tPQMItemSupplier[]	An array of PQM Item Supplier Object which belongs to the PQM item

tPQMItemSupplier

Represents a PQM supplier info, as an output.

Table A-75: Objects

Name	Type	Description
SourceSystemIdentifier	tSourceSystemIdentifier	See <i>tSourceSystemIdentifier</i> on page A-37
CompanyDescription	string	PQM supplier company description
FacilityDescription	string	PQM supplier facility description

tSourceSystemIdentifier

Represents a PQM supplier info, as an output.

Table A-76: Objects

Name	Type	Description
ItemInternalID	string	An item's (could be GSM specification or SCRM company/facility) internal ID
ItemExternalID	string	A item's external ID
ItemType	string	A item's item type
SourceSystemID	string	The source system ID; if from SCRM, the value should be "SCRM"

tPQMItemSupplierSearchIdentifier

Abstract object that represents PQM supplier identifying information used as input criteria, such as the SCRM entity number or a cross reference (System ID and Equivalent) or source system information.

Subtypes

- tSourceSystemPQMItemSupplierIdentifier
- tSCRMEntityCrossRefPQMItemSupplierIdentifier
- tSCRMEntityNumberPQMItemSupplierIdentifier

tSourceSystemPQMItemSupplierIdentifier

Represents a PQM supplier's source system information.

Supertype

- tPQMItemSupplierSearchIdentifier

Table A-77: Objects

Name	Type	Description
SourceSystemIdentifier	tSourceSystemIdentifier	Source system identifier

tSCRMEntityCrossRefPQMItemSupplierIdentifier

Represents a PQM supplier using company/facility cross reference.

Supertype

- tPQMItemSupplierSearchIdentifier

Table A-78: Objects

Name	Type	Description
ScrmEntityCrossRef	tSCRMEntityCrossRef	Company/facility cross reference

tSCRMEntityNumberPQMItemSupplierIdentifier

Represents a PQM supplier using company/facility entity number.

Supertype

- tPQMItemSupplierSearchIdentifier

Table A-79: Objects

Name	Type	Description
ScrmEntityNumber	tSCRMEntityNumber	Entity number

tPQMItemAffectedItemsResult

Output of get Affected Items API, contains a tPQMItemIdentifier and an array of tPQMAffectedItem [].

Table A-80: Objects

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	See tPQMItemIdentifier on page A-29
AffectedItems	tPQMAffectedItem []	An array of PQM Item affected items Object which belongs to the PQM item

tPQMAffectedItem

Represents a PQM affected item info, as an output.

Subtypes

- tIssueAffectedItem

Table A-81: Objects

Name	Type	Description
SourceSystemID	string	PQM affected item source system Id. If it is a GSM specification, should be 'GSM'
RevisionFoundItemNumber	string	Item Number of the affected item found
RevisionFoundItemRevision	string	Item revision of the affected item found

Table A-81: Objects

RevisionFixedItemNumber	string	Item Number of the affected item fixed
RevisionFixedItemRevision	string	Item revision of the affected item fixed
RevisionFoundItemInternalID	string	Item internal ID of the affected item found
RevisionFoundItemExternalID	string	Item external ID of the affected item found
RevisionFixedItemInternalID	string	Item internal ID of the affected item fixed
RevisionFixedItemExternalID	string	Item external ID of the affected item fixed
ItemType	string	Item type of the affected item
RevisionFoundComment	string	Comments

tIssueAffectedItem

Represents a PQM issue affected item info, as an output.

Supertype

- tPQMAffectedItem

Table A-82: Objects

Name	Type	Description
SourceSystemID	string	PQM affected item source system ID. If it is a GSM specification, should be 'GSM'
RevisionFoundItemNumber	string	Item Number of the affected item found
RevisionFoundItemRevision	string	Item revision of the affected item found
RevisionFixedItemNumber	string	Item Number of the affected item fixed
RevisionFixedItemRevision	string	Item revision of the affected item fixed
RevisionFoundItemInternalID	string	Item internal ID of the affected item found
RevisionFoundItemExternalID	string	Item external ID of the affected item found
RevisionFixedItemInternalID	string	Item internal ID of the affected item fixed
RevisionFixedItemExternalID	string	Item external ID of the affected item fixed
ItemType	string	Item type of the affected item
RevisionFoundComment	string	Comments
FailureType	tCommonLookup	Failure type of the affected item
AdditionalDisplayIdentifier	string	AdditionalDisplayIdentifier of the affected item
SiteAffected	tPQMItemSupplier	Site Affected of the affected item

Table A-82: Objects

QuantityAffected	tMeasurement	Quantity Affected of the affected item
ConformanceItemDescription	string	Conformance Item Description of the affected item
ConformanceItemID	string	Conformance Item ID of the affected item
ConformanceItemDescriptionExtended	string	Conformance Item Description Extended of the affected item
QtySuspected	tMeasurement	Qty Suspected of the affected item
SerialLotNum	string	Serial Lot Num of the affected item
QtyChecked	tMeasurement	QtyChecked of the affected item
ContainmentActions	string	Containment Actions of the affected item
RMA Num	string	RMA Num of the affected item
ConformingMaterialDate	DateTime	Conforming Material Date of the affected item

tAffectedItemInput

Represents an affected item; used in Add Affected Item as a input.

Supertypes

- tIssueAffectedItemInput
- tNCRAffectedItemInput

Table A-83: Objects

Name	Type	Description
AffectedItemIdentifier	tPQMAffectedItemIdentifier	<p>Affected item identifier</p> <p>Could be 2 sub types:</p> <ul style="list-style-type: none"> • tPQMAffectedItemSourceSystemId entifier is major used to identify affected items from third party system. <p>It is strongly recommended to use tPQMAffectedItemGSMIdentifier if the affected item is GSM Spec, incorrect use of tPQMAffectedItemSourceSystemId entifier may lead to UI crash if using default config in v6.1.1.</p> <ul style="list-style-type: none"> • tPQMAffectedItemGSMIdentifier is used to identify the affected item using GSM Spec Identifier Criterion
RevisionFoundComment	string	Comments of the affected item

tPQMAffectedItemIdentifier

Affected item identifier, as a input.

Subtypes

- tPQMAffectedItemGSMIdentifier
- tPQMAffectedItemSourceSystemIdentifier

tPQMAffectedItemGSMIdentifier

tPQMAffectedItemGSMIdentifier is used to identify the affected item using GSM Spec Identifier Criterion.

Supertype

- tPQMAffectedItemIdentifier

Table A-84: Objects

Name	Type	Description
AffectedGSMSpecFound	tSpecIdentifierCriterion	Identify the Affected GSM spec found
AffectedGSMSpecFixed	tSpecIdentifierCriterion	Identify the Affected GSM spec fixed

tPQMAffectedItemSourceSystemIdentifier

tPQMAffectedItemSourceSystemIdentifier is used to identify affected items from third party systems.

It is strongly recommended that you use tPQMAffectedItemGSMIdentifier if the affected item is GSM Spec. Incorrect use of tPQMAffectedItemSourceSystemIdentifier may lead to a UI crash if using default configuration in version 6.1.1.

Supertype

- tPQMAffectedItemIdentifier

Table A-85: Objects

Name	Type	Description
SourceSystemID	string	SourceSystemID of the affected item
RevisionFoundItemNumber	string	ItemNumber of the affected item found
RevisionFoundItemRevision	string	Revision of the affected item found
RevisionFixedItemNumber	string	ItemNumber of the affected item fixed
RevisionFixedItemRevision	string	Revision of the affected item fixed
RevisionFoundItemInternalID	string	ItemInternalID of the affected item found

Table A-85: Objects

RevisionFoundItemExternalID	string	ExternalID of the affected item found
RevisionFixedItemInternalID	string	ItemInternalID of the affected item fixed
RevisionFixedItemExternalID	string	ExternalID of the affected item fixed
ItemType	string	ItemType of the affected item

tIssueAffectedItemInput

Issue Affected item input, as an input.

Supertype

- tAffectedItemInput

Subtypes

- tNCRAffectedItemInput

Table A-86: Objects

Name	Type	Description
AffectedItemIdentifier	tPQMAffectedItemIdentifier	Affected item identifier Could be 2 sub types: <ul style="list-style-type: none"> • tPQMAffectedItemSourceSystemIdentifier is major used to identify affected items from third party system. It is strongly recommended to use tPQMAffectedItemGSMIdentifier if the affected item is GSM Spec, incorrect use of tPQMAffectedItemSourceSystemIdentifier may lead to UI crash if using default config in v6.1.1. <ul style="list-style-type: none"> • tPQMAffectedItemGSMIdentifier is used to identify the affected item using GSM Spec Identifier Criterion
RevisionFoundComment	string	Comments of the affected item
FailureType	string	FailureType of the issue affected item
QuantityAffected	tMeasurement	QuantityAffected of the issue affected item
SiteAffected	tPQMItemSupplierSearchIdentifier	SiteAffected of the issue affected item

tNCRAffectedItemInput

NCR Issue Affected item input, as an input.

Supertype

- tAffectedItemInput
- tIssueAffectedItemInput

Table A-87: Objects

Name	Type	Description
AffectedItemIdentifier	tPQMAffectedItemIdentifier	Affected item identifier Could be 2 sub types: <ul style="list-style-type: none"> • tPQMAffectedItemSourceSystemIdentifier is major used to identify affected items from third party system. It is strongly recommended to use tPQMAffectedItemGSMIdentifier if the affected item is GSM Spec, incorrect use of tPQMAffectedItemSourceSystemIdentifier may lead to UI crash if using default config in v6.1.1. <ul style="list-style-type: none"> • tPQMAffectedItemGSMIdentifier is used to identify the affected item using GSM Spec Identifier Criterion
RevisionFoundComment	string	Comments of the affected item
FailureType	string	FailureType of the issue affected item
QuantityAffected	tMeasurement	QuantityAffected of the issue affected item
SiteAffected	tPQMItemSupplierSearchIdentifier	SiteAffected of the issue affected item
ConformanceItemIdentifier	tConformanceItemIdentifier	ConformanceItemIdentifier of the NCR issue affected item
QtySuspected	tMeasurement	QtySuspected of the NCR issue affected item
SerialLotNum	string	SerialLotNum of the NCR issue affected item
QtyChecked	tMeasurement	QtyChecked of the NCR issue affected item
ContainmentAction	string	ContainmentActions of the NCR issue affected item
RMA Num	string	RMA Num of the NCR issue affected item
ConformingMaterialDate	DateTime	ConformingMaterialDate of the NCR issue affected item

tPQMSearchCriteria

Represents the search criteria of PQM items.

Table A-88: Objects

Name	Type	Description
IncludePQMActions	bool	Include PQM actions or not
ActionTypes	string[]	Should be valid action type names defined in ADMN>>PQM>>Action Type
IncludePQMAudits	bool	Include PQM audits or not
AuditTypes	string[]	Should be valid audit type names defined in ADMN>>PQM>>Audit Type
IncludePQMIssues	bool	Include PQM issues or not
IssueTypes	string[]	Should be valid issue type names defined in ADMN>>PQM>>Issue Type
Title	string	PQM item title
Description	string	The whole or part of PQM item description
ProductLines	string[]	Should be valid product line names defined in Admin>>PQM>>Product Lines
Customers	string[]	Should be valid customer names defined in ADMN>>PQM>>Customers
Originators	tUser[]	Array of originators
Owners	tUser[]	Array of owners
IssueSeverity	string	Should be a valid severity value for issue items
Suppliers	tSupplierSearchIdentifier[]	Array of supplier search identifiers
Status	string[]	PQM workflow status names
RestrictToStatusWithIDs	int[]	Array of workflow tag behavior IDs

tSupplierSearchIdentifier

Represents the supplier identifying information used as input. A supplier could be either an external supplier (represented by tExternalSupplierSearchIdentifier) or a SCRM supplier (represented by tSCRMSupplierSearchIdentifier).

Table A-89: Objects

Name	Type	Description
ExternalSearchIdentifier	tExternalSupplierSearchIdentifier	Identifies a supplier from external system
SCRMSearchIdentifier	tSCRMSupplierSearchIdentifier	Identifies a supplier from SCRM

tExternalSupplierSearchIdentifier

Represents the identifying information of supplier from external system.

Table A-90: Objects

Name	Type	Description
InternalItemID	string	Internal ID defined for the supplier
ExternalItemID	string	ID of the supplier in the source system
SourceSystemID	string	ID of the source system
ItemType	string	Item type of the supplier

tSCRMSupplierSearchIdentifier

Represents the identifying information of supplier from SCRM. The supplier could be a company or a facility.

Table A-91: Objects

Name	Type	Description
SCRMEntityPKID	string	PKID of SCRM company or facility
SCRMEntityNum	tSCRMEntityNumber	Number of SCRM company or facility
SCRMEntityCrossRef	tSCRMEntityCrossRef	Including system ID and equivalent value

tRelatedPQMItemsWrapper

Represents the information about the related items of PQM item used as output.

Table A-92: Objects

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	Identifier of PQM item
RelatedIssues	tRelatedPQMIssueItem[]	Array of one or more relates issue items
RelatedActions	tRelatedPQMActionItem[]	Array of one or more related action items
RelatedAudits	tRelatedPQMAuditItem[]	Array of one or more related audit items

tRelatedPQMItem

Represents a related PQM item.

Subtypes

- tRelatedPQMIssueItem
- tRelatedPQMActionItem

- tRelatedPQMAuditItem

Table A-93: Objects

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	Identifier of PQM item
ExtendedDescription	string	This is the value retrieved from the PQMRelatedItemFormatPlugin

tRelatedPQMActionItem

Represents a related PQM action item.

Supertype

tRelatedPQMItem

Table A-94: Objects

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	Inherited
ExtendedDescription	string	Inherited
Relationship	string	The relationship of PQM items, could be Child or Parent

tRelatedPQMAuditItem

Represents a related PQM audit item.

Supertype

tRelatedPQMItem

Table A-95: Objects

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	Inherited
ExtendedDescription	string	Inherited
PlannedAuditDate	DateTime	The planned audit date

tCommonIdentifier

Represents the common identifying information of supporting document item.

Subtypes

- tDRLDocumentIdentifier
- tDRLCatalogIdentifier

Table A-96: Objects

Name	Type	Description
PKID	string	The PKID of supporting document item
Title	string	The title of supporting document item

tDRLDocumentIdentifier

Represents the identifying information of DRL document.

Supertype

- tCommonIdentifier

Table A-97: Objects

Name	Type	Description
PKID	string	Inherited
Title	string	Inherited
DocumentID	tSpecificationNumber	The document ID of DRL document, including the SpecNumber and IssueNumber

tDRLCatalogIdentifier

Represents the identifying information of DRL catalog.

Supertype

tCommonIdentifier

Table A-98: Objects

Name	Type	Description
PKID	string	Inherited
Title	string	Inherited
ExternalID	string	The external ID of DRL catalog

tAttachmentsWrapper

Represents the information of an attachment procedure used as output.

Table A-99: Objects

Name	Type	Description
Identifier	tCommonIdentifier	Identifier of attachment procedure
CreationDate	DateTime	Creation date of attachment procedure
SecurityClassification	string	Security classification name of attachment procedure
Attachments	tCommonIdentifier[]	Identifiers of the attachments in the procedure

tDRLCatalog

Represents the information of DRL catalog used as output.

Table A-100: Objects

Name	Type	Description
CatalogIdentifier	tDRLCatalogIdentifier	Identifier of DRL catalog
DRLDocuments	tDRLDocumentIdentifier []	Identifiers of DRL documents in the catalog

tPQMSupportingDocWrapper

Represents the supporting documents of a PQM item used as output.

Table A-101: Objects

Name	Type	Description
PQMItemIdentifier	tPQMItemIdentifier	Identifier of PQM item
SupportingDocuments	tAttachmentsWrapper[]	Attachment procedures added to the PQM item
RichTextIdentifiers	tCommonIdentifier[]	Identifiers of rich text supporting documents added to the PQM item
URLSourceIdentifiers	tCommonIdentifier[]	Identifiers of URL supporting documents added to the PQM item
DRLDocumentIdentifiers	tDRLDocumentIdentifier []	Identifiers of DRL documents added to the PQM item
DRLCatalogs	tDRLCatalog[]	DRL catalogs added to the PQM item

tRichTextDoc

Represents a rich text supporting document used as output.

Table A-102: Objects

Name	Type	Description
Identifier	tCommonIdentifier	Identifier of the rich text supporting document
CreationDate	DateTime	Creation date of the rich text supporting document
Content	string	The HTML data of the rich text supporting

tNewRichTextDoc

Represents a new rich text supporting document used as input.

Table A-103: Objects

Name	Type	Description
Title	string	Title of the rich text supporting document, required
Content	string	HTML data of the rich text supporting document
KeyWords	string	Keywords of the rich text supporting document

tURLSource

Represents a URL supporting document used as output.

Table A-104: Objects

Name	Type	Description
Identifier	tCommonIdentifier	Identifier of the URL supporting document
EffectiveDate	DateTime	URL supporting document effective date
InactiveDate	DateTime	URL supporting document inactive date
UploadDate	DateTime	URL supporting document upload date
URLPath	string	URL path value of the supporting document
PubToSupplierPortal	boolean	This supporting document is published to Supplier Portal or not
IsProprietary	boolean	This supporting document is proprietary or not
ExpireDateNotify	boolean	Send notification before the expire date or not
ExpireDateNotifyNumDays	int	Specify the number of days in advance the expire notification will be sent

tNewURLSource

Represents a new URL supporting document used as input.

Table A-105: Objects

Name	Type	Description
Title	string	URL supporting document title, required
EffectiveDate	DateTime	URL supporting document effective date
InactiveDate	DateTime	URL supporting document inactive date, no earlier than the effective date

Table A-105: Objects

URLPath	string	URL path value, required
PubToSupplierPortal	boolean	This supporting document is published to Supplier Portal or not
IsProprietary	boolean	This supporting document is proprietary or not
ExpireDateNotify	boolean	Send notification before the expire date or not
ExpireDateNotifyNumDays	int	Specify the number of days in advance the expire notification will be sent

tDRLDocument

Represents a DRL document used as output.

Table A-106: Objects

Name	Type	Description
DocumentIdentifier	tDRLDocumentIdentifier	DRL document identifier
Description	string	DRL document description
Classifications	string[]	Classifications of the DRL document
Version	string	DRL document version
Originator	tUser	Originator of the DRL document
DocumentDate	DateTime	DRL document creation date
ExpirationDate	DateTime	DRL document expiration date
PubToSupplierPortal	boolean	This supporting document is published to Supplier Portal or not
ExpireDateNotify	boolean	Send notification before the expire date or not
ExpireDateNotifyNumDays	int	Specify the number of days in advance the expire notification will be sent
Attachments	tCommonIdentifier[]	Attachment identifiers of the DRL document

tAttachment

Represents an attachment document.

Subtype

tSupportingDocAttachment

Table A-107: Objects

Name	Type	Description
Identifier	tCommonIdentifier	Attachment identifier

Table A-107: Objects

FileName	string	File name of the attachment
FileSize	long	File size of the attachment
Path	string	File path of the attachment
BlobStream	Byte[]	Content data of the attachment

tSupportingDocAttachment

Represents an attachment document of procedure.

Supertype

tAttachment

Table A-108: Objects

Name	Type	Description
Identifier	tCommonIdentifier	Inherited
FileName	string	Inherited
FileSize	long	Inherited
Path	string	Inherited
BlobStream	Byte[]	Inherited
FileType	string	File type of the attachment
Owner	tUser	Owner of the attachment
EffectiveDate	DateTime	Attachment effective date
InactiveDate	DateTime	Attachment inactive date
UploadDate	DateTime	Attachment upload date
PubToSupplierPortal	boolean	This attachment is published to Supplier Portal or not
IsProprietary	boolean	This attachment is proprietary or not
ExpireDateNotify	boolean	Send notification before the expire date or not
ExpireDateNotifyNumDays	int	Specify the number of days in advance the expire notification will be sent

tNewAttachment

Represents a new attachment document as input.

Table A-109: Objects

Name	Type	Description
Title	string	Attachment title, required
FileName	string	File name of the attachment, required
FileType	string	File type of the attachment, required
Owner	tUser	Attachment owner
EffectiveDate	DateTime	Attachment effective date
InactiveDate	DateTime	Attachment inactive date

Table A-109: Objects

IsProprietary	boolean	This supporting document is proprietary or not
PubToSupplierPortal	boolean	This DRL document is published to supplier portal or not
ExpireDateNotify	boolean	Send notification before the expire date or not
ExpireDateNotifyNumDays	int	Specify the number of days in advance the expire notification will be sent
BlobStream	Byte[]	Content data of the attachment, required

tNewAttachmentsWrapper

Represents a new attachment procedure used as input.

Table A-110: Objects

Name	Type	Description
SecurityClassification	EnumSecurityClassifications	Security classification of attachment procedure
NewAttachments	tNewAttachment[]	Array of one or more new attachment documents

tCustomSectionInstance

Represents an instance of custom section.

Table A-111: Objects

Name	Type	Description
CustomSectionNumber	string	Custom section number
Content	tExtension	The xml data represents the custom section instance