

Oracle Financial Services  
Regulatory Reporting  
**Administration Guide NZ STR**

*Release 2.4*  
*October 2013*





Oracle Financial Services  
Regulatory Reporting  
**Administration Guide NZ STR**

*Release 2.4*  
*October 2013*

Document Control Number: 9MN11-2.4-01-04  
Document Number: AG-13-RR-004-2.4-01

Oracle Financial Services Software, Inc.  
1900 Oracle Way  
Reston, VA 20190

Document Number: AG-13-RR-004-2.4-01  
First Edition (October 2013)

**Copyright ©1996-2013, Oracle and/or its affiliates. All rights reserved.**

Printed in U.S.A. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without the prior written permission.

**Trademarks**

Oracle is a registered trademark of Oracle Corporation and/or its affiliates.  
Other names may be trademarks of their respective owners.

Oracle Financial Services Software, Inc.  
1900 Oracle Way  
Reston, VA 20190  
*Phone:* (703) 478-9000  
*Fax:* (703) 318-6340  
*Internet:* [www.oracle.com/financialservices](http://www.oracle.com/financialservices)

---

# Contents

---

<b>List of Tables .....</b>	<b>v</b>
<b>About This Guide .....</b>	<b>vii</b>
Who Should Use this Guide .....	vii
How this Guide is Organized .....	vii
Where to Find More Information .....	viii
Conventions Used in this Guide .....	viii
<b>CHAPTER 1      <i>Creating a User</i> .....</b>	<b>11</b>
<b>CHAPTER 2      <i>Loading the Static Data into OFSRR Application</i> .....</b>	<b>15</b>
<b>CHAPTER 3      <i>Integrating OFSRR Application with OFSECM/Oracle Mantas 5.x Application</i> .....</b>	<b>17</b>
<b>CHAPTER 4      <i>Configuring Report Lock Period</i> .....</b>	<b>19</b>



---

---

# *List of Tables*

---

Table 1. Conventions Used in this Guide .....	viii
---	------



---

# About This Guide

This guide provides comprehensive instructions to perform administration activities to configure the Oracle Financial Services Regulatory Reporting (herein referred to as OFSRR).

This chapter focuses on the following topics:

- Who Should Use this Guide
- How this Guide is Organized
- Where to Find More Information
- Conventions Used in this Guide

## Who Should Use this Guide

The *Oracle Financial Services Regulatory Reporting Administration Guide NZ STR* is designed for use by Oracle Financial Services application users. Their roles and responsibilities, as they operate within the OFSRR application, include the following:

- **System Administrator:** This user configures, maintains, and adjusts the system and is usually an employee of a specific Oracle Financial Services client. The System Administrator maintains user accounts and roles, archives data, and loads data feeds.

## How this Guide is Organized

The *Oracle Financial Services Regulatory Reporting 2.4 Administration Guide NZ STR*, includes the following topics:

- Chapter 1, *Creating a User*, describes the steps involved in user creation.
- Chapter 2, *Loading the Static Data into OFSRR Application*, explains the steps involved in loading static data.
- Chapter 3, *Integrating OFSRR Application with OFSECM/Oracle Mantas 5.x Application*, explains the steps involved in integration of RR application with OFSECM application.
- Chapter 4, *Configuring Report Lock Period*, explains the steps to configure the report lock time period.

## Where to Find More Information

For more information on OFSRR, refer to the following documents:

- *Oracle Financial Services Regulatory Reporting Installation Guide, Release 2.4*
- *Oracle Financial Services Regulatory Reporting Data Model Reference Guide, Release 2.4*
- *Oracle Financial Services Regulatory Reporting User Guide, Release 2.4*
- *Oracle Financial Services Regulatory Reporting Web Services Guide, Release 2.4*
- *Oracle Financial Services Regulatory Reporting Release Notes, Release 2.4*

To find additional information about how Oracle Financial Services solves real business problems, see our website at [www.oracle.com/financialservices](http://www.oracle.com/financialservices).

## Conventions Used in this Guide

Table 1 lists the conventions used in this guide.

**Table 1. Conventions Used in this Guide**

Convention	Meaning
<i>Italics</i>	<ul style="list-style-type: none"><li>● Names of books, chapters, and sections as references</li><li>● Emphasis</li></ul>
<b>Bold</b>	<ul style="list-style-type: none"><li>● Object of an action (menu names, field names, options, button names) in a step-by-step procedure</li><li>● Commands typed at a prompt</li><li>● User input</li></ul>
Monospace	<ul style="list-style-type: none"><li>● Directories and subdirectories</li><li>● File names and extensions</li><li>● Process names</li><li>● Code sample, including keywords and variables within text and as separate paragraphs, and user-defined program elements within text</li></ul>
<Variable>	Substitute input value

Users must be created with appropriate roles to access the OFSRR application. For more information on roles, refer *Oracle Financial Services Regulatory Reporting User Guide*. For more information on creating users, refer *Oracle Financial Services Analytical Application Infrastructure User Manual*.

To create users, follow these steps:

1. Create a User by logging into the OFSRR application as SYSADMN. For more information, refer section *User Maintenance* in *OFSAAI User Manual*.  
**Note:** If you are Integrating OFSRR with OFSECM then do not create OFSRR administration user. The OFSECM administration user to be used for OFSRR administration as well.
2. Authorize the User by logging into the application as SYSAUTH. For more information, refer section *User Authorization* in *OFSAAI User Manual*.
3. Create a User Group by logging into the OFSRR application as SYSADMN. For more information, refer section *User Group Maintenance* in *OFSAAI User Manual*.
4. Map the User Group to the OFSRR Information Domain. For more information, refer section *User Group Domain Map* in *OFSAAI User Manual*.

5. Map the User Group to the appropriate Role. For more information, refer section *User Group Role Map* in *OFSAAI User Manual*.
  - a. For creating a Supervisor user, map *Reg Report Supervisor Rol* and *Access to New Zealand STR roles*.
  - b. For creating an Analyst user, map *Reg Report Analyst Role* and *Access to New Zealand STR roles*.
  - c. For creating an Admin user, map *Reg Report Admin Role role*.

**Note:** You can add more than one user in one User Group, who is mapped to one type of role of the same application (for example, you can create more than one Analyst user in OFSRR). Mapping different roles of same application to a User Group (for example, Analyst and Supervisor role of OFSRR) and assigning user is not supported. But mapping different roles of different applications (for example, Executive role of OFSECM and Analyst role of OFSRR) is supported.

6. Authorize the mapping of User Group to Information Domain and Roles by logging into the application as SYSAUTH. For more information refer section *User Group Authorization* in *OFSAAI User Manual*.
7. Map User to created User Group. For more information, refer *User to User Group* section in *OFSAAI User Manual*.

**Note:**

- a. Map OFSECM administration User to OFSRR admin group created to get OFSRR administration privileges.
- b. If you are integrating OFSRR with OFSECM, then additionally map the corresponding OFSECM users to appropriate OFSRR User Group. For example, map OFSECM Analyst user to OFSRR Analyst User Group or OFSECM Supervisor user to OFSRR Supervisor User Group. By doing this,

the OFSRR application can be accessed directly from the **Regulatory Reporting** main menu of the OFSECM application by logging in as OFSECM user. The standalone OFSRR application can be accessed by both OFSRR and OFSECM users.

8. Authorize the mapping of User to User Group by logging into the application as SYSAUTH. For more information refer section *User Group Authorization* in *OFSAAI User Manual*.
9. To add client specific security attributes to OFSRR system, navigate to <ftpshare path>/STAGE/Excelupload/Templates, the <ftpshare path> is the same path given in variable APP\_DRIVE\_TM while installing OFSAAI. For more information, refer *Oracle Financial Services Analytical Applications Infrastructure Installation and Configuration Guide*.
10. Download the following Excel sheets to Windows machine from the path given in the previous step:
  - a. DIM\_DOMAIN1.xlsx
  - b. DIM\_DOMAIN2.xlsx
  - c. DIM\_DOMAIN3.xlsx
  - d. DIM\_DOMAIN4.xlsx
  - e. DIM\_DOMAIN5.xlsx
11. Add data in each excel sheet as per your report requirement by referring to *Oracle Financial Services Regulatory Reporting Data Model Reference Guide*.
  - a. DIM\_DOMAIN1.xlsx is to be filled with Jurisdictions which are all available in OFSECM application. For more information refer section, *Security Attribute1 Static Information* in *Data Model Reference Guide*.
  - b. DIM\_DOMAIN2.xlsx is to be filled with Business Domains which are all available in OFSECM application. For more information refer section, *Security Attribute2 Static Information* in *Data Model Reference Guide*.
  - c. DIM\_DOMAIN3.xlsx is to be filled with Case Type and Case SubType which are all available in OFSECM application. For more information refer section, *Security Attribute3 Static Information* in *Data Model Reference Guide*.
  - d. DIM\_DOMAIN4.xlsx is to be filled with Organizations which are all available in OFSECM application. For more information refer section, *Security Attribute4 Static Information* in *Data Model Reference Guide*.
  - e. DIM\_DOMAIN5.xlsx is to be filled with Scenario Classes which are all available in OFSECM application. For more information refer section, *Security Attribute5 Static Information* in *Data Model Reference Guide*.
12. Login to OFSRR application as Admin user created in the previous step.
13. Navigate to Unified Metadata Manager > Data Entry Forms and Queries > Excel Upload, a new screen pops up with an Excel Upload page.

**Note:** After logging into the application, make sure the OFSRR application Information Domain is selected from the drop-down list at the left hand corner of the page.
14. Click **Browse** button under Excel File to Upload section.
15. Select any one of the excel sheet.
16. Click on Arrow button next to Browse button.
17. Preview the data created under Preview section.
18. In Excel - Entity Mappings section, click **Arrow** button.

19. Select the table name same as name of the excel sheet.
20. Click **Upload**.
21. Click **OK** on the popup window displaying the message *Successfully uploaded data*.

**Note:** Scan the Webapplication Server logs for any errors after uploading each excel sheet. For example, for Oracle Weblogic , it is `wls.out`, for Websphere, it is `Systemout.log` and `Systemerr.log`.

22. Close the Excel upload page.

23. Click **FCCM** (Incase OFSRR is installed on top of OFSECM) or **Regulatory Reporting** ( In case of Stand alone). If it is stand alone installation then a new page with a drop-down list displays having all the OFSRR users created in the previous steps. If OFSRR is installed on top of ECM then on the new page navigate to Administration menu > User Administration > Regulatory Report User's Attribute Administration. This will take you to a drop-down list with all the OFSRR users created. Assign attributes to each user from each drop-down.
24. Close the **Regulatory Report User's Attribute Administration** screen.
25. Logout from the OFSRR application.
26. Login with each created user in the OFSRR application, the application will open password reset page when the user login for the first time immediate after creation or every time SYSADMN user reset the password for various reasons , Example: forgot password, Password locked etc.
27. Reset the password. The OFSRR application Login page displays. You must log into the application using the new password.
28. Click **Regulatory Reporting** link in case of standalone installation. The OFSRR application page displays. Click **FCCM** link in case OFSRR is installed on top of OFSECM, the Regulatory Reporting tab will be available in one of the tabs in the new page.

**Note:** Follow the steps mentioned above whenever a new user is added or modified (for User Details, User Group mapping, Roles mapping, Security Attribute mapping, and Password Change) in the OFSRR application.

# *Loading the Static Data into OFSRR Application*

OFSRR application uses the following client provided data as per their business requirements:

- Reporting Entity Details
- Reporting Entity Location
- Reporting Person Information
- Reporting Institution
- User Information
- Holiday Details
- Branch information

Follow these steps to load the above data into OFSRR application:

1. Download following excel sheets to Windows machine for the templates from <ftpshare path>/STAGE/Excelupload/Templates. The path for <ftpshare path> is the same path as given in variable placeholder ##FTPSHARE\_PATH## in GRC\_InstallConfig.xml.
  - a. DIM\_REPORTING\_ENTITY\_DTLS.xlsx
  - b. DIM\_REPORTING\_ENTITY\_LOC.xlsx
  - c. DIM\_REPORTING\_PERSON.xlsx
  - d. DIM\_INSTITUTION.xlsx
  - e. DIM\_USERS.xlsx
  - f. DIM\_HOLIDAY\_MAINTENANCE.xlsx
  - g. FCT\_BRANCH\_INFO.xlsx
2. Add data in each excel sheet as per your installation requirement by referring to the *Oracle Financial Services Regulatory Reporting Data Model Reference Guide*.
  - a. DIM\_REPORTING\_ENTITY\_DTLS.xlsx: For more information, refer section *Reporting Entity Details* in *Datamodel Reference Guide*.
  - b. DIM\_REPORTING\_ENTITY\_LOC.xlsx: For more information, refer section *Reporting Entity Location* in *Datamodel Reference Guide*.
  - c. DIM\_REPORTING\_PERSON.xlsx: For more information, refer section *Reporting Person Information* in *Datamodel Reference Guide*.
  - d. DIM\_INSTITUTION.xlsx: For more information, refer section *Reporting Institution Information* in *Datamodel Reference Guide*.

- e. DIM\_USERS.xlsx: For more information, refer section *User information* in *Datamodel Reference Guide*.
  - f. DIM\_HOLIDAY\_MAINTENANCE.xlsx: For more information, refer section *Holiday Maintenance* in *Datamodel Reference Guide*.
  - g. FCT\_BRANCH\_INFO.xlsx: For more information, refer section *Branch Information* in *Datamodel Reference Guide*.
3. Login to the OFSRR application as Admin user created in the previous step.

**Note:** After logging into the application, make sure the OFSRR application Information Domain is selected from the drop-down list at the left hand corner of the page.
  4. Navigate to Unified Metadata Manager > Data Entry Forms and Queries > Excel Upload, a new screen pops up with an Excel Upload page.
  5. Click **Browse** button under **Excel File to Upload** section, upload all excel sheets created in the previous step.

**Note:** The data must be loaded in the same order as given in step 1.

**Note:** Scan the Webapplication Server logs for any errors after uploading each excel sheet. For example, for Oracle Weblogic , it is wls.out, and for Websphere, it is Systemout.log and Systemerr.log.
  6. Close the Excel upload page.

# *Integrating OFSRR Application with OFSECM/Oracle Mantas 5.x Application*

OFSECM / Oracle Mantas 5.x applications can be integrated with OFSRR to post alerts/cases to generate reports with Webservice Calls. To know more about Webservices, refer *Oracle Financial Services Regulatory Reporting Webservices Guide*. Both OFSECM/Oracle Mantas 5.x and OFSRR application must be configured to use this webservice. This is an optional configuration and is required only when you want to integrate OFSRR with OFSECM/Oracle Mantas 5.x.

1. For OFSRR:

The OFSRR application's Webservice is already configured with a default user name and password. This default password must be reset before performing the OFSRR and OFSECM/Oracle Mantas 5.x integration. This step is mandatory from security aspect.

a. To update password, perform the following steps:

i. Log in as Administrator user.

ii. Navigate to **Administration > Regulatory Report Web Service**.

iii. Enter the User ID as ruser. Do not add any other user name.

iv. Enter any desired password.

v. Click **Save**.

b. By default, OFSRR Web Service is configured to capture the data coming from OFSECM. If OFSRR is to be configured to accept data from Oracle Mantas 5.x, then execute the following SQL using OFSRR atomic schema user:

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1='N' WHERE V_ATTRIBUTE_NAME1='ECM
FLAG' ;
COMMIT;
```

2. For OFSECM:

a. Login to the OFSECM application as Administration User.

b. Navigate to FCCM > Administration > Manage Installation Parameters.

c. Select **Deployment Based** in the Parameter Category drop-down list.

d. Select **Regulatory Report Solution Web Service** from the Parameter Name drop-down list.

e. Set Param Value text box = Y.

f. Click **Save**.

g. Select **Used for Design** in the parameter category.

- h. Select **Application Server** in the parameter name.
  - i. Update the OFSRR web service URL by setting Attribute 4 Value: = <OFSRR URL>/services/InitiateRequest.
  - j. Click **Save**.
  - k. To update OFSRR Webservice password in OFSECM, Navigate to FCCM > Administration > RRS Password Encryption
  - l. Enter the same password set in OFSRR side and Click **OK**.
  - m. Logout from the application.
3. For Oracle Mantas 5.x
- a. Update the variables in <Oracle Mantas Home>/alert\_management/alert\_mgmt/WEB-INF/classes/conf/mantas\_cfg/install.cfg as below

```
#RRS Web Service parameters
rrs.userid=rruser
rrs.password= <Encrypt the same password given in step 1 using Change Password Utility of Oracle Mantas 5.x>
rrs.service.url=<OFSRR URL>/services/InitiateRequest
rrs.version=2.4
```

then recreate the war file and deploy in the web application server.
  - b. By default, OFSRR Web Service is configured to capture data coming from OFSECM. If OFSRR is to be configured to accept data from Oracle Mantas 5.x, then execute the following SQL using OFSRR atomic schema user:

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1='N' WHERE V_ATTRIBUTE_NAME1='ECM FLAG';
COMMIT;
```

## *Configuring Report Lock Period*

If any user forgets to logoff from the OFSRR application or if the OFSRR screen is closed while accessing a report, the report gets locked for a pre configured duration. By default, the duration is sixty minutes. This duration can be altered as per your requirement.

Execute the following SQL using OFSRR atomic schema user:

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1= '<DURATION IN MINUTES>'
WHERE V_ATTRIBUTE_NAME1= 'LOCK PERIOD IN MINUTES';
COMMIT;
```





