

**Oracle® Database Mobile Server**

Message Reference

Release 11.3

**E40367-01**

August 2013

Copyright © 2012, 2013, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

---

---

# Contents

<b>Preface</b> .....	v
Audience .....	v
Documentation Accessibility .....	v
Related Documents .....	v
Conventions .....	v
<b>1 Messages</b>	
1.1 Oracle Database Mobile Server Messages .....	1-1
1.1.1 Abnormal Condition .....	1-2
1.1.1.1 Cause .....	1-2
1.1.1.2 Action .....	1-2
1.1.2 About Java Access Class Exceptions .....	1-2
1.1.3 Oracle Customer Support .....	1-2
1.2 Exception Error Codes and Messages .....	1-3
1.2.1 OSEException Error Messages .....	1-3
1.2.2 BGException Error Messages .....	1-4
1.3 CNS 9000–9099 Mobile Sync Error Messages .....	1-6
1.4 CNS 9100–9199 Transport Errors .....	1-9
1.5 CNS 9200–9299 Secure Socket Layer (SSL) Errors .....	1-11
1.6 CNS 9300–9399 Automatic Synchronization Errors .....	1-11
1.7 CONS 10001–10100 Consolidator Messages .....	1-15
1.8 CONSPERF 10001-10100 Consperf Error Messages .....	1-24
1.9 OMS 3000–3099 Oracle Mobile Manager Messages .....	1-27
1.10 OMS 3100–3599 Errors from the oracle.lite.web.resource Package .....	1-28
1.11 OMS 10000–10200 Oracle General Messages .....	1-30
1.12 OMS 20500–20600 Packaging Wizard Messages .....	1-36
1.13 OMS 21000–21999 Errors reported by the Tools classes in oracle.lite.web.tools .....	1-37

## Index



---

---

# Preface

This preface introduces you to the *Oracle Database Mobile Server Message Reference*, discussing the intended audience, documentation accessibility, and structure of this document.

## Audience

This manual is intended for application developers as the primary audience and for database administrators who are interested in application development as the secondary audience.

## Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

### Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

## Related Documents

Use the following manual as reference when installing and configuring a WebLogic application server:

- *Oracle® Fusion Middleware Installation Guide for Oracle WebLogic Server*

## Conventions

The following conventions are also used in this manual:

Convention	Meaning
. . .	Vertical ellipsis points in an example mean that information not directly related to the example has been omitted.
...	Horizontal ellipsis points in statements or commands mean that parts of the statement or command not directly related to the example have been omitted

<b>Convention</b>	<b>Meaning</b>
<b>boldface text</b>	Boldface type in text indicates a term defined in the text, the glossary, or in both locations.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.
<i>italic monospace</i>	<p>Italic monospace type indicates a variable in a code example that you must replace. For example:</p> <pre>Driver=<i>install_dir</i>/lib/libtten.sl</pre> <p>Replace <i>install_dir</i> with the path of your TimesTen installation directory.</p>
< >	Angle brackets enclose user-supplied names.
[ ]	Brackets enclose optional clauses from which you can choose one or none.

The following sections list the Oracle Database Mobile Server thrown exceptions and returned error messages:

- [Section 1.1, "Oracle Database Mobile Server Messages"](#)
- [Section 1.2, "Exception Error Codes and Messages"](#)
- [Section 1.3, "CNS 9000–9099 Mobile Sync Error Messages"](#)
- [Section 1.4, "CNS 9100–9199 Transport Errors"](#)
- [Section 1.5, "CNS 9200–9299 Secure Socket Layer \(SSL\) Errors"](#)
- [Section 1.6, "CNS 9300–9399 Automatic Synchronization Errors"](#)
- [Section 1.7, "CONS 10001–10100 Consolidator Messages"](#)
- [Section 1.8, "CONSPERF 10001–10100 Consp perf Error Messages"](#)
- [Section 1.9, "OMS 3000–3099 Oracle Mobile Manager Messages"](#)
- [Section 1.10, "OMS 3100–3599 Errors from the oracle.lite.web.resource Package"](#)
- [Section 1.11, "OMS 10000–10200 Oracle General Messages"](#)
- [Section 1.12, "OMS 20500–20600 Packaging Wizard Messages"](#)
- [Section 1.13, "OMS 21000–21999 Errors reported by the Tools classes in oracle.lite.web.tools."](#)

## 1.1 Oracle Database Mobile Server Messages

Each message code follows the format *Product ID-nnnnn*, where *nnnnn* is an integer. Messages specific to an operating system or another Oracle product are not listed here, although the message code may be listed with a reference to another Oracle document.

Each description contains the message number and text as well as the following:

### Error message text

**Cause:** a description of the possible causes of the error.

**Action:** a description of the possible actions you can take to resolve the error.

Items in the error message text which appears in curly braces, for example, **{publication name}**, are replaced with values for objects which are then returned by the error message.

## 1.1.1 Abnormal Condition

Sometimes you may encounter an error that is known as an abnormal condition. These are errors for which the exact cause is not clear. The following sections describe the probable causes of abnormal conditions and the actions you can take to solve them.

### 1.1.1.1 Cause

Abnormal conditions may arise from one of the following causes:

- An invalid user action.
- A bug in the component prevented the requested task from completing.

### 1.1.1.2 Action

You should first contact your DBA and/or system administrator to determine if the message was caused by something other than Oracle Database Mobile Server. If you determine that the message was not the result of user error or a system problem, you should take the following steps:

- Write down the message number and its text.
- Write down the circumstances that led up to the message. Try to recall the actions you took, the objects involved (if any), and the exact sequence of keys that you pressed prior to the message.
- Call [Oracle Customer Support](#) for assistance.

## 1.1.2 About Java Access Class Exceptions

The Java Access Class errors are processed through the Java exception handling mechanism. Errors appear with names such as the following:

```
oracle.pol.jac.POLGroupNotFoundException
```

There are no error codes associated with these Java exceptions. If an internal error code causes a Java exception, the general `oracle.pol.jac.POLException` appears and the internal error code that caused the exception is reported.

## 1.1.3 Oracle Customer Support

Some errors (such as internal errors) require you to call Oracle Customer Support to report the error. When you call Customer Support, you should have the following information available:

- Your name, company, and Oracle Support ID number.
- The hardware, operating system, and release number of the operating system on which Oracle Database Mobile Server is running.
- The complete version number of Oracle Database Mobile Server that you were using when you encountered the error, including revision number and port release number, if any.
- All other products and version numbers in use when the error occurred.
- If you encountered one or more error codes or messages, the exact code numbers and message texts, in the order they appeared.
- A description of the problem, including any unusual conditions.
- The problem severity, according to the following codes:

- 1 = Program not usable. Critical impact on operations of a production system.
- 2 = Program not usable. Operations severely restricted.
- 3 = Program usable with limited functions. Not critical to overall operations.
- 4 = Problem circumvented by customer. Minimal effect, if any, on operations.

## 1.2 Exception Error Codes and Messages

When using the Oracle Database Mobile Server APIs, you may receive an error message from an exception. This section describes all errors that can be thrown within the Oracle Database Mobile Server APIs.

- [Section 1.2.1, "OSEException Error Messages"](#)
- [Section 1.2.2, "BGException Error Messages"](#)

### 1.2.1 OSEException Error Messages

[Table 1–1](#) lists the error codes and messages that can be returned in the OSEException class.

**Table 1–1 OSEException Error Messages**

Error number	Error Code	Error Message
-12000	SYNC_CANCELED	Sync was canceled.
-12001	UNEXPECTED_OPCODE	Expecting opcode <i>&lt;opcode&gt;</i> , received <i>&lt;opcode&gt;</i> .
-12002	DATABASE_NOT_FOUND	Could not find database <i>&lt;database_name&gt;</i> .
-12003	USER_NOT_SPECIFIED	User is not specified and the last user was not saved.
-12004	PASSWORD_NOT_SPECIFIED	Password is not specified and was not saved for user <i>&lt;username&gt;</i> .
-12005	INVALID_DML_TYPE	Received invalid record DML type <i>&lt;dml_type&gt;</i> .
-12006	INVALID_OPCODE	Received invalid opcode <i>&lt;opcode&gt;</i> .
-12008	OPCODE_LENGTH_UNDERRUN	<i>&lt;numbytes&gt;</i> bytes for opcode <i>&lt;opcode&gt;</i> have not been read.
-12011	PLUGIN_EXCEPTION	Plugin has thrown an exception, see the cause.
-12012	INVALID_SYNC_DIRECTION	Invalid sync direction specified: <i>&lt;sync_direction&gt;</i> .
-12016	INVALID_TRANSPORT_TYPE	Invalid transport type specified: <i>&lt;transport_type&gt;</i> .
-12017	PLUGIN_ID_NOT_FOUND	Could not find plugin with id <i>&lt;id&gt;</i> .
-12018	UNEXPECTED_BLOB_DATA	Got a record with BLOBs for a plugin that does not support BLOBs.
-12019	PUBLICATION_NOT_FOUND	Could not find publication <i>&lt;publication_name&gt;</i> .
-12021	SNAPSHOT_ID_NOT_FOUND	Could not find snapshot with id <i>&lt;id&gt;</i> .
-12023	SNAPSHOT_ID_EXISTS	Snapshot with id <i>&lt;id&gt;</i> already exists.
-12024	OPCODE_OUT_OF_SEQUENCE	Opcode <i>&lt;opcode&gt;</i> was not expected at this time.
-12030	ENCRYPTION_ID_MISMATCH	Sent encryption id <i>&lt;id&gt;</i> + 1 does not match received <i>&lt;id&gt;</i> .
-12031	UNENCRYPTED_DATA	Received erroneous unencrypted data.
-12032	UNCOMPRESSED_DATA	Received erroneous uncompressed data.

**Table 1–1 (Cont.) OSEException Error Messages**

Error number	Error Code	Error Message
-12034	INVALID_ENCRYPTION_TYPE	Invalid encryption type specified: <i>&lt;encryption_type&gt;</i> .
-12035	HTTP_RESPONSE	Unsuccessful HTTP response
-12038	SERVER_ERROR	Server error, id = <i>&lt;id&gt;</i> .
-12039	INTERNAL_ERROR	Internal error has occurred (see the cause).
-12040	MISSING_DEFAULT_DATABASE	Plugin is missing default database needed to create snapshot.
-12043	PUBLICATION_ID_NOT_FOUND	Could not find publication with id <i>&lt;id&gt;</i> .
-12044	PLUGIN_CLASS_NOT_FOUND	Could not find plugin class <i>&lt;class_name&gt;</i> .
-12047	INVALID_PRIORITY	Invalid priority specified: <i>&lt;priority&gt;</i> .
-12100	PLUGIN_CLASS_INIT_FAILED	Failed to initialize plugin class <i>&lt;class_name&gt;</i> .
-12101	EMPTY_PASSWORD	Blank password is not allowed.
-12102	PUBLICATION_ID_MISMATCH	Publication id <i>&lt;id&gt;</i> for snapshot with id <i>&lt;id&gt;</i> does not match publication id <i>&lt;id&gt;</i> in the current transaction.
-12103	INVALID_STRING_LENGTH	Invalid string length <i>&lt;number&gt;</i> received in opcode <i>&lt;opcode&gt;</i> .
-12104	ERR_CREDENTIALS	Failed to get credentials from the server (the current credentials are invalid or missing).
-12105	EMPTY_USER	User name cannot be blank.

## 1.2.2 BGException Error Messages

Table 1–2 lists the error codes and messages that can be returned in the BGException class.

**Table 1–2 BGException Error Messages**

Message Number	Message Constant	Message
12000	BG_MSG_AGENT_STARTED	Info: Sync agent has been started
12001	BG_MSG_AGENT_STOPPED	Info: Sync agent has been stopped
12002	BG_MSG_AGENT_PAUSED	Info: Sync agent has been paused
12003	BG_MSG_AGENT_RESUMED	Info: Sync agent has been resumed
12004	BG_MSG_COMPOSE_STARTED	Info: Compose of priority %d has started for the database %s.
12005	BG_MSG_COMPOSE_FINISHED	Info: Compose of priority %d has finished for the database %s.
12006	BG_MSG_SYNC_STARTED	Info: Sync of priority %d has started for publications %s.
12007	BG_MSG_SYNC_FINISHED	Info: Sync of priority %d has finished for publications %s.
12008	BG_MSG_APPLY_STARTED	Info: Apply has started for database %s.
12009	BG_MSG_APPLY_FINISHED	Info: Apply has finished for database %s.
12010	BG_MSG_SERVER_NOTIFICATION	Info: Server notification of priority %d has been received for publication %s.
12011	BG_MSG_NETWORK_CHANGED	Info: Network has changed from %s to %s.

**Table 1–2 (Cont.) BGException Error Messages**

Message Number	Message Constant	Message
12012	BG_MSG_BG_MSG_NO_NETWORK	Info: No network available.
12013	BG_MSG_NETWORK_EVAL	Info: Evaluated network, name: %s, speed: %ld mbps, ping: %ld ms.
12014	BG_MSG_TRACE	Info: Trace message: %s
12015	BG_MSG_UNKNOWN_VALUE	Info: Unknown
12200	BG_MSG_BATTERY_LOW	Warning: Battery power is low (%d%).
12201	BG_MSG_MEMORY_LOW	Warning: Memory is low (%ld bytes are available).
-12500	BG_ERR_COMPOSE	Error: Compose of priority %d has failed for database %s.
-12501	BG_ERR_SYNC	Error: Sync of priority %d has failed for publications %s.
-12502	BG_ERR_APPLY_FAILED	Error: Apply has failed for database %s.
-12503	BG_ERR_RULE_LOAD	Error: Could not load automatic synchronization rule %s for publication %s.
-12504	BG_ERR_RULE_EVAL	Error: Failed to evaluate automatic synchronization rule %s for publication %s.
-12505	BG_ERR_NET_MANAGER	Error: Network manager error has occurred.
-12506	BG_ERR_PWR_MANAGER	Error: Power manager error has occurred.
-12507	BG_ERR_INTERNAL	Error: Internal error has occurred.
-12508	BG_ERR_PLAT_RULE_IN_NON_PLAT_DB	Error: Found platform rule %s in non-platform database %s.
-12509	BG_ERR_NET_AUTODIAL	Error: Failed to establish dialup connection.
-12510	BG_ERR_SERVER_NOTIFICATION	Error: Failed to process server notification of priority %d for publication %s.
-12511	BG_ERR_CONTROL_CONNECTION	Error: Control connection to the agent is closed due to an error.
-12512	BG_ERR_INVALID_COMMAND	Error: Invalid control command received: %d.
-12513	BG_ERR_INVALID_SERVER_NOTIFICATION	Error: Invalid server notification received: %s.
-12514	BG_ERR_ACTIVE_CONNECTIONS	Error: Cannot stop the agent because %d active connection(s) are present.
-12516	BG_ERR_CANNOT_ACCEPT_CTRL	Error: The agent cannot accept control command %s because it is in state %s.
-12517	BG_ERR_PLATFORM_DB_NOT_FOUND	Could not find platform database.
-12518	BG_ERR_INVALID_RULE_TYPE	Invalid rule type: %s.
-12519	BG_ERR_INVALID_RULE_SUBTYPE	Invalid rule subtype: %s.
-12520	BG_ERR_INVALID_RULE_CLASS	Invalid rule class: %s.
-12521	BG_ERR_INVALID_RULE_SUBTYPE_TYPE	Invalid rule subtype %s for type: %s.
-12522	BG_ERR_INVALID_DATE_FORMAT	Invalid date format: %s.
-12523	BG_ERR_INVALID_EVENT_SUBTYPE	Invalid subtype %s for an event rule: %s.
-12524	BG_ERR_INVALID_COND_SUBTYPE	Invalid subtype %s for a condition rule: %s.
-12525	BG_ERR_INVALID_EVENT_TYPE	Invalid type %s for an event rule: %s.

**Table 1–2 (Cont.) BGException Error Messages**

Message Number	Message Constant	Message
-12526	BG_ERR_INVALID_COND_TYPE	Invalid type %s for a condition rule: %s.
-12527	BG_ERR_MISSING_QUERY	Query is missing for a SQL rule.
-12528	BG_ERR_DUPLICATE_PLATFORM_DB	Found duplicate platform databases: %s and %s.
-12529	BG_ERR_ANOTHER_INSTANCE	Cannot start the sync agent because another instance is already running.
-12530	BG_ERR_UNSUPPORTED	%s is not supported.
-12531	BG_ERR_INVALID_NUM_PARAM	Invalid number parameter specified: %d.
-12532	BG_ERR_INVALID_STR_PARAM	Invalid string parameter specified: %d.
-12533	BG_ERR_INVALID_WAIT_STATUS	Invalid status to wait for: %d.
-12534	BG_ERR_INVALID_SESSION	Invalid session handle provided.
-12535	BG_ERR_WAIT_TIMEOUT	Control operation has timed out.
-12536	BG_ERR_AGENT_NOT_RUNNING	Operation \"%s\" cannot be performed because sync agent is not running.
-12537	BG_ERR_TOO_MANY_READERS	Cannot create message reader because the allowed maximum of %d running readers will be exceeded.
-12538	BG_ERR_READER_CANCELED	Message reader was canceled from another thread.
-12539	BG_ERR_AGENT_DISABLED	Cannot start sync agent because it has been disabled.
-12540	BG_ERR_NO_BG_PUBS	No background sync enabled publications were found on the client.
-12541	BG_ERR_RULE_EVAL_DB_LOCKED	Failed to evaluate rules for database %s because it is locked by an application.
-12542	BG_ERR_INVALID_PARAM	Invalid parameter specified: %d.
-12543	BG_ERR_START	Failed to start the Sync Agent. See the cause for more information.
-12544	BG_ERR_STOP	Failed to stop the Sync Agent. See the cause for more information.
-12545	BG_ERR_PAUSE	Failed to pause the Sync Agent. See the cause for more information.
-12546	BG_ERR_RESUME	Failed to resume the Sync Agent. See the cause for more information.
-12547	BG_ERR_FATAL	Sync Agent encountered fatal error or cannot be stopped.

## 1.3 CNS 9000–9099 Mobile Sync Error Messages

### CNS-9000 Internal Error

**Cause:** Unrecoverable internal error has occurred.

**Action:** Contact your system administrator.

### CNS-9001 Out of memory

**Cause:** Cannot allocate memory from the system.

**Action:** Increase available system memory either by closing other applications or increasing physical or virtual memory size.

**CNS-9002 General memory error**

**Cause:** Either your memory is corrupt or you have run out of memory.

**Action:** Increase available memory and restart Msync.

**CNS-9003 Memory resize error**

**Cause:** Out of memory.

**Action:** Increase memory.

**CNS-9007 Cannot create new OKAPI class**

**Cause:** Class exists, out of memory, or there are too many objects in the database.

**Action:** Drop the database tables created outside of the synchronization process that have the same name as the synchronization snapshots.

**CNS-9008 Cannot create new OKAPI group**

**Cause:** Group exists, out of memory, or too many objects in the database.

**Action:** Ensure database is created by synchronizing with Mobile Sync that the file system is not full.

**CNS-9010 Cannot set new OKAPI object attribute**

**Cause:** Corrupted database, or out of memory.

**Action:** Delete database and resynchronize.

**CNS-9011 General error on application deployment**

**Cause:** Application file exists locally already, or is too large.

**Action:** Delete excess files to increase disk capacity

**CNS-9012 Application deployment directory not found**

**Cause:** Destination directory not found.

**Action:** Create the directory where the application should reside and resynchronize. See the *"Packaging Wizard"* chapter in the *Oracle Database Mobile Server Developer's Guide*.

**CNS-9013 General error on index creation**

**Cause:** An invalid index was specified.

**Action:** Check the server side index definition using the `CV$ALL_PUBLICATION_INDEX` system catalog view. See the *"System Catalog View"* Appendix of the *Oracle Database Mobile Server Developer's Guide*.

**CNS-9015 General error on shared library open/close**

**Cause:** Shared library does not exist or has become corrupted.

**Action:** Re-install shared libraries.

**CNS-9019 General compression error**

**Cause:** An unrecoverable error has occurred while compressing or decompressing data.

**Action:** Contact your system administrator.

**CNS-9022 Server/Client format mismatch**

**Cause:** The server does not support the current version of the client.

**Action:** Upgrade server or client so that both versions match.

**CNS-9023 Network disconnected during sync, check network is active**

**Cause:** The network connection to the mobile server has been severed.

**Action:** Check to see if your device has an active network connection.

**CNS-9024 Network disconnected during sync, check network is active.**

**Cause:** The network disconnected during the sync.

**Action:** Check to see if the network is active.

**CNS-9025 Server internal error.**

**Cause:** The server has reported an error during the synchronization process.

**Action:** Contact your system administrator.

**CNS-9026 Wrong username or password.**

**Cause:** Login failed because of an incorrect username or password.

**Action:** Check login name and password and resynchronize.

**CNS-9028 Compressed file access error.**

**Cause:** Cannot open temporary compressed data.

**Action:** Check disk space and ensure no other process is purging temp files during sync.

**CNS-9029 Invalid Object**

**Cause:** Cannot open temporary compressed data.

**Action:** Check disk space and ensure no other process is purging temporary files during synchronization.

**CNS-9030 Server and client versions do not match**

**Cause:** Server sent a bad sync packet to the client.

**Action:** Check version of server or reinstall the mobile client from the mobile server.

**CNS-9031 Cannot open file (Application Deployment)**

**Cause:** Disk failure or other system problems.

**Action:** Check file system.

**CNS-9032 User has cancelled Sync**

**Cause:** The user cancelled the synchronization process.

**Action:** None needed.

**CNS-9033 SQL command execution error.**

**Cause:** Failed to execute a SQL command sent by the server.

**Action:** Contact your system administrator.

**CNS-9034 Java class bundling error.**

**Cause:** Java classes for the Java Stored Procedure were not packaged correctly.

**Action:** Contact your system administrator.

**CNS-9035 Primary key info does not match.**

**Cause:** There is a primary key mismatch between the client and the server.

**Action:** Contact your system administrator.

**CNS-9036 Table not found for index item.**

**Cause:** Table not found for index item.

**Action:** Contact your system administrator.

**CNS-9037 Column not found for index item.**

**Cause:** Column not found for index item.

**Action:** Contact your system administrator.

**CNS-9038 Not enough memory for creating index.**

**Cause:** Failed to allocate memory during index creation.

**Action:** Increase your system/program memory.

**CNS-9039 ValidateDB error.**

**Cause:** Failed to validate the mobile client database file.

**Action:** Contact your system administrator.

**CNS-9040 ValidateDB executable not found.**

**Cause:** The validatedatabase file could not be located in the binary directory.

**Action:** Contact your system administrator.

**CNS-9041 EncrypDB failed.**

**Cause:** Failed to encrypt the mobile client database file.

**Action:** Contact your system administrator.

**CNS-9042 EncrypDB executable not found.**

**Cause:** The encryptdb file could not be located in the binary directory.

**Action:** Contact your system administrator.

**CNS-9043 Server busy. Try sync later.**

**Cause:** The mobile server is busy processing other synchronization requests.

**Action:** Wait for some time and sync again.

**CNS-9070 Duplicate Client Instance**

**Cause:** Another instance of the Sync Client is already running. Only one Sync Client is allowed to execute at a time.

**Action:** Either switch to the original instance, or terminate the original instance and start a new instance.

## 1.4 CNS 9100–9199 Transport Errors

**CNS-9100 HTTP pipe general error**

**Cause:** Failed to send or receive data from the mobile server.

**Action:** Ensure that your network connection is active.

**CNS-9101 Wrong hostname or network is not active**

**Cause:** Could not locate the mobile server.

**Action:** Check server name, DNS servers and the network connection.

**CNS-9102 Server could not be located**

**Cause:** gethostbyname failed.

**Action:** Check DNS settings of client machine.

**CNS-9103 HTTP cannot find host error**

**Cause:** Proxy server could not be located.

**Action:** Check proxy server hostname and DNS server.

**CNS-9104 Wrong IP address or hostname**

**Cause:** Specified IP address or hostname may be incorrect.

**Action:** Check your network connection, if the network is active, contact your system administrator.

**CNS-9105 HTTP cannot find proxy error**

**Cause:** Proxy server may be down or unreachable.

**Action:** Restart proxy server or verify proxy hostname.

**CNS-9106 HTTP send error.**

**Cause:** The network connection has been severed.

**Action:** Check network connection and verify the mobile server version.

**CNS-9107 Network disconnected during sync**

**Cause:** Specified IP address or hostname may be incorrect. This error can occur if you are using SSL and the certificate is not valid.

**Action:** Check your mobile server URL; ensure that you have an active network connection.

**CNS-9108 HTTP page not found.**

**Cause:** Specified mobile server URL is not correct. This error may occur if you have a proxy server in your network.

**Action:** Check mobile server and proxy server.

**CNS-9109 Network disconnected during sync**

**Cause:** Specified IP address or hostname may be incorrect. This error can occur if you are using SSL and the certificate is not valid.

**Action:** Check your mobile server URL; ensure that you have an active network connection.

**CNS-9110 HTTP pipe interpreted during transfer**

**Cause:** Specified mobile server URL is not correct. This error may occur if you have a proxy server in your network.

**Action:** Check mobile server and proxy server.

**CNS-9111 HTTP network library not found**

**Cause:** Oracle Database Mobile Server is not properly installed.

**Action:** Re-install Oracle Database Mobile Server.

**CNS-9112 HTTP resume error**

**Cause:** An internal error has occurred during the recovery process.

**Action:** Ensure that you have a compatible version of the mobile server.

**CNS-9113 HTTP page not found, check URL subdirectory**

**Cause:** HTTP page not found.

**Action:** Check URL subdirectory.

## 1.5 CNS 9200–9299 Secure Socket Layer (SSL) Errors

### CNS-9200 Internal SSL error

**Cause:** Network disconnected during synchronization.

**Action:** Check operating system, re-install the SSL components.

### CNS-9203 Error creating the SSL credential

**Cause:** Failed to make a SSL (Secure Socket Layer) connection to the mobile server.

**Action:** Check SSL settings in the mobile server configuration file.

## 1.6 CNS 9300-9399 Automatic Synchronization Errors

These errors are received if a problem occurred within an automatic synchronization event.

### CNS-9300 Internal error in Sync Agent

**Cause:** Internal error occurred in the Sync Agent, which caused it to halt.

**Action:** Look at the file `autosyncerr.txt` file located in the same directory as the Sync Agent executable. Call Customer Support for assistance.

### CNS-9301 Error in loading the rule <rule\_name> for pub

<publication\_name>: <internal error message>

**Cause:** The given rule stored on the server has an incorrect or invalid XML content. The rule will be ignored and Sync Agent will continue running.

**Action:** You can connect to look at the sync agent logs in the `bglog` directory for a more detailed error message. Then, check the given rule on the server for validity, modify the rule, and re-sync with a regular synchronization (`msync`).

### CNS-9302 Error in evaluating the rule <rule\_name> for pub

<publication\_name>: <internal error message>

**Cause:** Error occurred during evaluation of the given rule. Internal causes can be different depending on the kind of rule. Sync agent will continue running.

**Action:** Connect to `conscli.odb` for your user and check the `C$BG_SYNC_LOG` table for the internal error message pertaining to this error. If the cause is not obvious, call Customer Support for assistance.

### CNS-9303 Failed to establish dialup connection

**Cause:** When the `autosync` network rule that specifies dialup was evaluated and no other network connection was detected, the dialup failed to establish connection.

**Action:** Connect to the `conscli.odb` for your user and check for the network script of type "NETCONFIG" that is stored in the `C$SCRIPTS` table. Check the script for the names of all dialup connections. If they are not correct, fix the script on the server and re-synchronize with a regular synchronize (`msync`). Otherwise, check your dialup network settings.

### CNS-9304 Error in evaluating network state: <network\_layer\_error>

**Cause:** Sync Agent encountered an error when evaluating the system network state either during startup or when network has changed. Sync Agent will continue running.

**Action:** Connect to `conscli.odb` for your user and check the `C$BG_SYNC_LOG` table for the contents of the internal error message pertaining to this error. Check your network settings. Otherwise, call Customer Support for assistance.

**CNS-9305 Error in evaluating system power state: <power\_mgmt\_error>**

**Cause:** Sync Agent encountered an error when evaluating the system power state either during startup or when the power has changed. Sync Agent will continue running.

**Action:** Connect to `conscli.odb` for your user and check the `C$BG_SYNC_LOG` table for the contents of internal error message pertaining to this error. Check your system power settings. Otherwise, call customer support for assistance.

**CNS-9306 Invalid server notification message**

**Cause:** Sync agent has received an invalid notification message from the server. The message will be ignored and sync agent will continue running.

**Action:** Connect to `conscli.odb` for your user and check the `C$BG_SYNC_LOG` table for the details of this message. Call Customer Support for assistance.

**CNS-9307 Database is not initialized**

**Cause:** Metadata required for automatic sync is not present in `conscli.odb` for your user. Sync Agent is not able to run.

**Action:** Ensure that automatic sync publications are set up correctly on the server side and automatic sync is enabled for each publication. After that, re-synchronize with a regular synchronization (`msync`).

**CNS-9308 Sync agent is already running**

**Cause:** When trying to start, Sync Agent detects that another instance of it is already running.

**Action:** No action required. You can check that the running instance is functioning correctly.

**CNS-9309 Failed to start Sync Agent**

**Cause:** Sync Agent control API has failed to start Sync Agent due to some internal error.

**Action:** Stop or terminate all Oracle Database Mobile Server processes--such as `dmagent`, Sync Agent, `msql`, `msync`, and so on--and any user application using Oracle Database Mobile Server. Then, restart the Sync Agent. If the error still occurs, call Customer Support for assistance.

**CNS-9310 Sync agent is not running**

**Cause:** When trying to retrieve the Sync Agent status, the Sync Agent is not running.

**Action:** Start Sync Agent.

**CNS -9311 More than one instance of Sync Agent is running**

**Cause:** Sync Agent control API has detected that more than one instance of the Sync Agent is running.

**Action:** Call Customer Support for assistance.

**CNS-9312 Failed to stop sync agent**

**Cause:** The Control API has failed to stop the Sync Agent due to some internal error.

**Action:** Call the stop Control API with the kill option. If the situation repeats or additional problems occur, call Customer Support for assistance.

#### **CNS-9313 Error getting Sync Agent status**

**Cause:** Failed to retrieve Sync Agent status, even though sync agent is running.

**Action:** Retrieve the status again. If the same error occurs, call Customer Support for assistance.

#### **CNS-9314 Error getting application message**

**Cause:** Internal error has occurred during the read of Sync Agent messages by the application.

**Action:** Repeat the message read. If it fails again, call Customer Support for assistance.

#### **CNS-9315 No auto-sync publication items**

**Cause:** Sync Agent is not able to execute because no automatic synchronization publication items were found on the client.

**Action:** If automatic synchronization is needed, enable automatic synchronization for the publication you use on the server and re-synchronize with a regular synchronization (msync).

#### **CNS-9316 Sync Agent is disabled**

**Cause:** Sync Agent is not able to run because it is disabled.

**Action:** Enable the Sync Agent through control APIs or manually by setting `BGSYNC.DISABLE=NO` in `OSE.INI` file. Restart the Sync Agent.

#### **CNS-9317 Operation timed out**

**Cause:** Control API operation has exceeded time limit allotted for it.

**Action:** Retry operation. If you still receive the same error, call Customer Support for assistance.

#### **CNS-9318 Application message read was canceled**

**Cause:** The application thread receives this error when a message read is canceled from another thread while reading Sync Agent messages.

**Action:** No action required.

#### **CNS-9400 (No Network)**

**Cause:** Sync Agent has not detected a network connection.

**Action:**

#### **CNS-9401 Network changed from <network\_name> to <network\_name>**

**Cause:** Sync Agent has detected a network change from one network (<network\_name>) to another (<network\_name>).

**Action:**

#### **CNS-9500 Idle**

**Cause:**

**Action:**

#### **CNS-9501 Waiting on condition**

**Cause:**

**Action:**

**CNS-9502 Waiting for task**

**Cause:**

**Action:**

**CNS-9510 Starting Prepare**

**Cause:**

**Action:**

**CNS-9511 Preparing**

**Cause:**

**Action:**

**CNS-9512 Finished Prepare**

**Cause:**

**Action:**

**CNS-9513 Starting Send**

**Cause:**

**Action:**

**CNS-9514 Sending**

**Cause:**

**Action:**

**CNS-9515 Finished Sending**

**Cause:**

**Action:**

**CNS-9516 Starting Receive**

**Cause:**

**Action:**

**CNS-9517 Receiving**

**Cause:**

**Action:**

**CNS-9518 Finished Receive**

**Cause:**

**Action:**

**CNS-9519 Starting Process**

**Cause:**

**Action:**

**CNS-9520 Processing**

**Cause:**

**Action:**

**CNS-9521 Finished Process****Cause:****Action:****CNS-9524 Finished****Cause:****Action:**

## 1.7 CONS 10001–10100 Consolidator Messages

**CONS-10001: Oracle Consolidator Message Generator and Processor** Syntax: java MGPApp <delay> <restart> <schema> <password>**Cause:** A syntax error is found in the command when starting MGPApp or mgp.bat.**Action:** Check the command line for MGPApp or within mgp.bat.**CONS-10002: Exception on close() caught in MGPP/apply thread****Cause:** Error displayed with the message may vary due to circumstances.**Action:** Fix the error listed and try again. If the problem persists, contact your administrator.**CONS-10003: Exception on new MGPP# {apply phase thread #} ,reason: {Java exception}****Cause:** Error displayed with the message may vary due to circumstances.**Action:** Fix the error listed and try again. If the problem persists, contact your administrator.**CONS-10004: USER\_INVALID in Consolidator auth; Logon denied****Cause:** Either the user does not exist, or the username or password is misspelled.**Action:** Check the spelling of the username and password and try again. If the spelling is correct, it means the user does not exist. Re-create the user and try again.**CONS-10005: USER\_NOT\_FOUND in Consolidator auth; Logon denied****Cause:** Either the user does not exist, or the username or password is misspelled.**Action:** Check the spelling of the username and password and try again. If the spelling is correct, it means the user does not exist. Re-create the user and try again.**CONS-10006: Invalid username/password; logon denied****Cause:** Either the user does not exist, or the username or password is misspelled.**Action:** Check the spelling of the username and password and try again. If the spelling is correct, it means the user does not exist. Re-create the user and try again.**CONS-10007: Feature not implemented****Cause:** The feature that is being used is not implemented.**Action:** Stop using the feature. If further help is needed, contact your administrator.**CONS-10008: Could not find publication item version for client {client name} , publication item {publication item name}**

**Cause:** The user has not subscribed to any publication or publication item, or the name of the publication for which subscription is intended is misspelled.

**Action:** Check the spelling of the client and the publication. If no publication has been subscribed, subscribe to a publication and try again.

**CONS-10009: Could not find publication for client {client name} , publication item {publication item name}**

**Cause:** The user has not subscribed to any publication or publication item, or the name of the publication for which subscription is intended is misspelled.

**Action:** Check the spelling of the client and the publication. If no publication has been subscribed, subscribe to a publication and try again.

**CONS-10010: Must instantiate {publication name} for at least one client before MetaData can be generated**

**Cause:** The publication is not instantiated, or the name of the publication that is intended to be instantiated is misspelled.

**Action:** Check the spelling of the publication. If no publication has been instantiated, instantiate a publication and try again.

**CONS-10011: Publication Item {publication item name} doesn't exist**

**Cause:** The publication item that is being referred to does not exist, or the name of the publication item is misspelled.

**Action:** Check the spelling of the publication item. If the publication does not exist, create the publication item. After that also add the publication item to the corresponding publication.

**CONS-10012: Cannot find Publication Item view {publication item name} in ALL\_VIEWS**

**Cause:** The publication item that is being referred to does not exist, or the name of the publication item is misspelled.

**Action:** Check the spelling of the publication item. If the publication does not exist, create the publication item. After that also add the publication item to the corresponding publication.

**CONS-10013 : Could not find publication {publication name}**

**Cause:** The publication that is being referred to does not exist, or the name of the publication is misspelled.

**Action:** Check the spelling of the publication. If it does not exist, create the publication.

**CONS-10014: Weight must be: 0 <= weight < 1024**

**Cause:** The weight that is being set on an publication item is either smaller than 0 or greater than 1023.

**Action:** Change the weight and add the publication item again.

**CONS-10015: Could not find parent table for {owner}.{view name}**

**Cause:** A view-based publication item is being added to an publication while a hint was not provided for the view's parent table.

**Action:** Call `ParentHint ()` to associate the view and the parent table.

**CONS-10016: {publication item name} is not an item of {publication name}**

**Cause:** The publication item that is being referred to does not exist in the publication, or the name of the publication item is misspelled.

**Action:** Verify the existence or correct the spelling of the publication item and try again.

**CONS-10017: {publication name} is not subscribed to {subscription name} or is already instantiated**

**Cause:** Trying to drop a subscription that has not been subscribed or to instantiate a subscription that has already been instantiated.

**Action:** None.

**CONS-10018: Cannot create Fast Refresh publication item {publication item name} because primary keys for {owner}.{store name} not found**

**Cause:** Primary keys on the publication item is needed for Fast Refresh but there are none.

**Action:** Create primary key for the publication item or use `CreateVirtualPKColumn ()` to create virtual primary key(s).

**CONS-10019: Primary key hint for the parent table {owner}.{store name} not found**

**Cause:** Primary keys on the parent table of the publication item has to be notified about for Fast Refresh but it has not been done.

**Action:** Call `PrimaryKeyHint ()` for each of the primary keys on the parent table.

**CONS-10020: Parent table for {owner}.{store name} must be set through ParentHint() API**

**Cause:** When a view publication item is used, the parent table of the view must be specified with `ParentHint ()`, but it has not; or the parent table name was misspelled.

**Action:** Call `ParentHint ()` to set the parent table of the publication item.

**CONS-10021: {client name} is not subscribed to {publication name}**

**Cause:** While trying to retrieve information about the publication for the client, no relationship was found between the client and the publication.

**Action:** Verify the client name and the publication's spelling, and their relationship and try again.

**CONS-10022: {client name} is not a Consolidator client**

**Cause:** While trying to retrieve information about the client, no such client is found.

**Action:** Verify the client name. If the spelling is correct, that means there is no such user and it must be created.

**CONS-10023: Multiple publication items with the same store found for (store,client) ({store name},{client name})**

**Cause:** The store name of a publication item must be unique, but this has been violated since more than one publication item has the same store name.

**Action:** Remove or modify the publication item and try again.

**CONS-10024: Protocol Error: U not followed by u**

**Cause:** Internal error.

**Action:** Report this to [Oracle Customer Support](#).

**CONS-10025: Unrecognized event {0}**

**Cause:** Internal error.

**Action:** Report this to [Oracle Customer Support](#).

**CONS-10026: Can't select by tranid, seqno from IN QUEUE {publication item name}**

**Cause:** Internal error.

**Action:** Report this to [Oracle Customer Support](#).

**CONS-10027: Conflict resolution rule must be either S (server wins) or C (client wins)**

**Cause:** The only available options for resolution rule are 'S' or 'C' and something other than that has been used.

**Action:** Change it to 'S' or 'C' and try again.

**CONS-10028: Publication name must be unique: {publication name} already exists**

**Cause:** A publication with the same name already exists.

**Action:** Use a different name and try again.

**CONS-10029: ENFORCE\_RI MUST BE 'Y' or 'N' or NULL**

**Cause:** When calling CreatePublicationItem, a value other than 'Y', 'N', or NULL has been used for ENFORCE\_RI.

**Action:** Use 'Y', 'N', or NULL and try again.

**CONS-10030: Publication item: {publication item} is already added to {publication}**

**Cause:** The user is trying to add a publication item to a publication, and the publication item has already been added.

**Action:** No action required.

**CONS-10031: Cannot instantiate publication {publication name} for client {client name} :: parameter <{subscription parameter}> not set**

**Cause:** The user is trying to instantiate an publication and the parameter of the publication has not been set

**Action:** Set the parameter and try again.

**CONS-10032: Publication item: {publication item name} cannot be updatable, primary keys for {owner}.{store name} not found**

**Cause:** The primary key for the publication item is needed but it does not exist.

**Action:** Add a primary key for the publication item and try again.

**CONS-10033: Parent table {owner}.{store name} not published for {owner}.{store name} view**

**Cause:** The parent table of the view has not been published.

**Action:** Use CreatePublicationItem () to publish the parent table and try again.

**CONS-10034: Cannot create publication item :: remote connection cannot be NULL**

**Cause:** The user has submitted NULL for the remote database URL.

**Action:** Change that to a valid URL and try again.

**CONS-10035: Database Connection Timeout**

**Cause:** The database connection has been idle for too long and was closed by the database.

**Action:** Call OpenConnection () to reestablish the connection.

**CONS-10036: Publication item name exceeds maximum supported length {length}**

**Cause:** The name used for the publication item is longer than the maximum supported length.

**Action:** Use a name shorter than the mentioned length and try again.

**CONS-10037: {type} {name} already exists**

**Cause:** Trying to create the named object that already exists.

**Action:** Depending on your intention, you can:

1. Ignore this error if it is for creating the same object.
2. Use the corresponding API to remove the named object first and try again.
3. Use another name.

**CONS-10038: Found {number of the same} resources, expected 1 of {resource type} {resource name}**

**Cause:** Unexpected table state for C\$RESOURCES or C\$SCRIPTS found.

**Action:** Verify that the above tables and their indexes are valid. If not, re-create the tables or indexes. Contact [Oracle Customer Support](#).

**CONS-10039: {type} {name} NOT FOUND**

**Cause:** Trying to refer to the named resource but it is not found.

**Action:** When calling `getSqlScript/isSqlScriptModified` or removing a script from a publication, no action needed. For adding, ensure the presence of the script.

**CONS-10040: {type} {name} already added to {publication}**

**Cause:** Trying to add the named object that is already added.

**Action:** Depending on your intention, you can:

1. Ignore this error if it is for adding the same object.
2. Use the corresponding API to remove the named object first and try again.
3. Use another name.

**CONS-10041: {type} {name} is not part of {publication}**

**Cause:** Trying to remove the named object from the named publication while the named object does not exist in the publication.

**Action:** Check the spelling. If the spelling is correct, you can ignore this error message.

**CONS-10042: Internal Consolidator Error. {error message}**

**Cause:** Internal error.

**Action:** Report this to [Oracle Customer Support](#).

**CONS-10043: Publication item refresh mode change from <refresh mode 1> to <refresh mode 2> not supported**

**Cause:** When calling API `setTemplateItemMetadata`, switching from refresh mode 1 to refresh mode 2 is not supported.

**Action:** Correct it in the `TemplateItemMetadata` and try again.

**CONS-10043: Publication item refresh mode change from <refresh mode 1> to <refresh mode 2> not supported**

**Cause:** When calling API setTemplateItemMetadata, switching from refresh mode 1 to refresh mode 2 is not supported.

**Action:** Correct it in the TemplateItemMetadata and try again.

**CONS-10044: Invalid {type} columns specified for {publication item}**

**Cause:** Either the format or the number of the columns specified does not match the publication item.

**Action:** Check and fix the columns and the publication item and try again.

**CONS-10045: Invalid restricting predicate specified for {publication item}**

**Cause:** The restricting predicate submitted is invalid.

**Action:** Fix the restricting predicate and try again.

**CONS-10046: Invalid PL/SQL {type} <{module}> specified: {error message}**

**Cause:** The referred type module is invalid. The error message was generated during execution.

**Action:** Study the error message and fix the type module and try again.

**CONS-10047: Client\_storage\_type is invalid**

**Cause:** The specified Client\_storage\_type is invalid.

**Action:** Check and fix it, and try again. For a list of the supported Client\_storage\_type, refer the *Consolidator API Specification*.

**CONS-10048: {type}: {name} not found**

**Cause:** The referred object not found.

**Action:** Ensure the spelling is correct. Correct it and try again. If trying to drop the referred object, since the object does not exist, you can ignore this error.

**CONS-10049: Consolidator Exception: {error message}**

**Cause:** Java exception during execution of Consolidator java code.

**Action:** Fix the error by following the error message. Otherwise, contact [Oracle Customer Support](#).

**CONS-10050: Rollback failure: {error}**

**Cause:** Error occurred while rolling back a connection.

**Action:** Fix the error by following the error message. If it is an Oracle Server error message (prefix with ORA), refer the Oracle Server documentation.

**CONS-10051: Invalid refresh mode {mode} for {publication}. Supported modes are: 'F' - fast, 'C' - complete, or 'Q' -queue**

**Cause:** The mode submitted is unsupported.

**Action:** Try it again with one of the supported modes.

**CONS-10052: Server Busy: maximum number of wait period exceeded**

**Cause:** MAX number of clients in the waiting stack exceeded MAX\_NUM\_CLIENT\_WAITING (default 1000 ).

**Action:** Increase MAX\_NUM\_CLIENT\_WAITING in mobile.ora or wait for the server to process queued clients and sync again.

**CONS-10053: DeviceManager message: Device is not enabled**

**Cause:** Disabled device

**Action:** Enable device

**CONS-10054: WINDOW\_SIZE cannot be less than 1**

**Cause:** WINDOW\_SIZE is less than 1

**Action:** Adjust WINDOW\_SIZE

**CONS-10055: INCREMENT\_BY cannot be 0**

**Cause:** Sequence parameter INCREMENT\_BY cannot be zero.

**Action:** Adjust to non zero value.

**CONS-10056: Unrecognized sequence mode**

**Cause:** Invalid sequence mode.

**Action:** Specify sequence mode to be either "OA\_SEQ" or "NA\_SEQ".

**CONS-10057: Unrecognized sequence property**

**Cause:** Invalid sequence property.

**Action:** Specify valid properties as : NAME, MIN\_VALUE, WINDOW\_SIZE, THRESHOLD, INCREMENT\_BY, SEQUENCE\_MODE.

**CONS-10058: WINDOW\_SIZE cannot be less than or equal to THRESHOLD**

**Cause:** WINDOW\_SIZE is less than or equal to THRESHOLD.

**Action:** Adjust WINDOW\_SIZE or THRESHOLD values.

**CONS-10059: WINDOW\_SIZE cannot be less than or equal to INCREMENT\_BY**

**Cause:** WINDOW\_SIZE is less than or equal to INCREMENT\_BY.

**Action:** Adjust WINDOW\_SIZE or INCREMENT\_BY values.

**CONS-10060: INCREMENT\_BY cannot be greater than THRESHOLD**

**Cause:** INCREMENT\_BY is greater than THRESHOLD.

**Action:** Adjust INCREMENT\_BY or THRESHOLD values.

**CONS-10061: MIN\_VALUE cannot be set lower than the previous MIN\_VALUE**

**Cause:** MIN\_VALUE is set lower than the previous MIN\_VALUE.

**Action:** Adjust MIN\_VALUE.

**CONS-10062: INCREMENT\_BY cannot be changed**

**Cause:** INCREMENT\_BY cannot be changed.

**Action:**

**CONS-10063: THRESHOLD cannot be less than 0**

**Cause:** THRESHOLD cannot be less than 0.

**Action:** Adjust threshold.

**CONS-10064: Syntax: java oracle.lite.sync.upgradeAToB <Schema> <Password>  
<from> <to>**

**Cause:** Syntax error for upgrade usage.

**Action:**

**CONS-10065: Supported versions:**

**Cause:** Upgrade from A to B supported versions

**Action:**

**CONS-10066: Invalid upgrade order: <from> version has to be prior to <to> version**

**Cause:** Invalid upgrade order  
**Action:** Adjust < from> or <to>

**CONS-10067: Unrecognized version:: {0}**

**Cause:** Unrecognized version  
**Action:**

**CONS-10068: Upgrade completed successfully**

**Cause:** Upgrade completed successfully  
**Action:**

**CONS-10069: Sync rule parameter <{0}> is not set**

**Cause:** Sync rule parameter is not set.  
**Action:**

**CONS-10070: {0} is queue-based publication item: shared map is not allowed**

**Cause:** For queue-based publication item, shared map is not allowed.  
**Action:**

**CONS-10071: Script {1} of type {0} not found**

**Cause:** Missing script of some type.  
**Action:** Provide script.

**CONS-10072: Sequence {0} not found**

**Cause:** Missing sequence.  
**Action:** Provide sequence.

**CONS-10073: Sequence {0} not found for client {1}**

**Cause:** Missing sequence for a particular client.  
**Action:** Provide sequence for this particular client.

**CONS-10074: Sequence {0} is already used by another publication**

**Cause:** Certain sequence is already used by another publication.  
**Action:** Adjust sequence.

**CONS-10075: Complete refresh triggered during HIGH PRIORITY session**

**Cause:** Complete refresh triggered during HIGH PRIORITY session.  
**Action:**

**CONS-10076: Device is not upgradable**

**Cause:** Device is not upgradable.  
**Action:**

**CONS-10077: Complete refresh triggered during an automatic sync session**

**Cause:** Complete refresh triggered during an automatic sync session.  
**Action:** User-initiated sync should be performed.

**CONS-10078: Mismatched txnid in Z and z ({0} and {1})**

**Cause:** Mismatched transaction id in Z and z opcode.  
**Action:**

**CONS-10079: Mismatched priority in Z and z ({0} and {1})**

**Cause:** Mismatched priority in Z and z opcode.

**Action:**

**CONS-10080: Apply aborted for client {0} as resultant apply errors cannot be handled at this stage**

**Cause:** Apply aborted for certain client as resultant apply errors cannot be handled at this stage.

**Action:**

**CONS-10081: Another thread is applying transactions for client {0}. Will skip apply**

**Cause:** Another thread is applying transactions for certain client. Will skip apply.

**Action:**

**CONS-10082: {0} is a reserved database name and cannot be used for registration**

**Cause:** Used a reserved database name and cannot be used for registration.

**Action:**

**CONS-10083: Database change is not permitted for a publication item. Publication item: {0}**

**Cause:** Database change is not permitted for certain publication item.

**Action:**

**CONS-10084: Database {0} not found**

**Cause:** Database not found.

**Action:**

**CONS-10085: An internal error was encountered during encrypt/decrypt of information for a database. Error Code: {0}**

**Cause:** An internal error was encountered during encrypt/decrypt of information for a database with error code.

**Action:**

**CONS-10086: The publication item database ({0}) does not match that for the publication ({1})**

**Cause:** The publication item database does not match that for the publication.

**Action:**

**CONS-10087: The database is already registered under another name**

**Cause:** The database is already registered under another name.

**Action:**

**CONS-10088: The database is already registered to a different installation**

**Cause:** The database is already registered to a different installation.

**Action:**

**CONS-10089: Schema version of database is {0} which is different from that of main repository {1}**

**Cause:** Schema version of database is different from that of main repository.

**Action:**

**CONS-10090: Parent hint is not complete for base table {0}.{1}**

**Cause:** Parent hint is not complete for certain base table.

**Action:**

**CONS-10091: Member authentication failed**

**Cause:** Member credentials supplied during sync were invalid.

**Action:**

**CONS-10092: No association exists between USER '{0}' and MEMBER '{1}'.**

**Cause:** Invalid association between certain user and certain member.

**Action:**

**CONS-10093: Apply will be skipped for client {0}. Cause={1}**

**Cause:** Apply will be skipped for certain client.

**Action:**

**CONS-10094: Publication item {0} store name {1} is longer than MAX supported <{2}>.**

**Cause:** Store name name is too long.

**Action:** Create a synonym with a shorter name and publish the synonym.

**CONS-10095: Cannot add or modify virtual primary key for a published store:: {0}.{1}**

**Cause:** Virtual primary key already exists for the store.

**Action:** Remove the store from any publications before creating or modifying any virtual primary keys.

**CONS-10096: Plugin for creator id <{0}> is not properly registered**

**Cause:** Internal error.

**Action:** Report this to [Oracle Customer Support](#).

**CONS-10097: OSE plugin ({0} , {1}) is not registered**

**Cause:** Internal error.

**Action:** Report this to [Oracle Customer Support](#).

**CONS-10098: OSE plugin ({0} , {1}) is already registered with creator id = {2}**

**Cause:** Internal error.

**Action:** Report this to [Oracle Customer Support](#).

**CONS-10099: Client uploaded transaction id greater than upper bound of {0}**

**Cause:** Internal sync protocol error.

**Action:** Report this to [Oracle Customer Support](#).

**CONS-10100: Client uploaded database id great than upper bound of {0}**

**Cause:** Internal sync protocol error.

**Action:** Report this to [Oracle Customer Support](#).

## 1.8 CONSPERF 10001-10100 Consp perf Error Messages

**CONSPERF-10001: MOBILESCHEMA is null**

**Cause:** A value was not passed for the mobile server schema owner.

**Action:** The MOBILESCHEMA parameter must be passed with a valid mobile server schema owner.

**CONSPERF-10002: PUBLICATION is null**

**Cause:** A value was not passed for the publication name.

**Action:** The PUBLICATION parameter must be passed with a valid publication name.

**CONSPERF-10003: Unable to write plan for {publication name}**

**Cause:** An unexpected error occurred while trying to write the explain plan output file.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10004: Unable to retrieve plan data for {publication item name}**

**Cause:** An unexpected error occurred while trying to retrieve the explain plan results from the mobile server repository.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10005: Unable to connect to the database. Check**

**CONNECTSTRING:{connectstring} | SVCENAME:{service name}],  
MOBILESCHEMA:{schema name}, MOBILEPASSWORD:{password}.**

**Cause:** Consp perf failed to connect to the mobile server repository.

**Action:** Verify CONNECTSTRING or SVCENAME parameters. If these are correct, verify MOBILESCHEMA and MOBILEPASSWORD parameters. If these are correct, verify that database is available.

**CONSPERF-10006: Unable to determine Consolidator version**

**Cause:** An unexpected error occurred while retrieving the Consolidator version from the mobile server repository.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10007: Invalid client identifier {client identifier}**

**Cause:** Consp perf could not find the specified client identifier in the mobile server repository.

**Action:** The CLIENTID parameter must be passed with a valid mobile user.

**CONSPERF-10008: Unable to set client subscription parameters for {publication item name}**

**Cause:** An unexpected error occurred while setting subscription parameters for the publication item listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10009: Client identifier is not set**

**Cause:** A value was not passed for the mobile user.

**Action:** The CLIENTID parameter must be passed with a valid mobile user.

**CONSPERF-10010: Unable to execute profile for {publication item name}**

**Cause:** An unexpected error occurred while executing the timing profile for the publication item listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10011: Unable to execute plan for {publication name}**

**Cause:** An unexpected error occurred while executing the explain plan for the publication listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10012: Unable to create base view for {publication item name}**

**Cause:** An unexpected error occurred while creating the base view for the publication item listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10013: Unable to execute tuning for {publication name}**

**Cause:** An unexpected error occurred while executing tuning for the publication listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10014: Unable to clear profile for {publication item name}**

**Cause:** An unexpected error occurred while clearing tuning settings from the mobile server repository for the publication item listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10015: Unable to retrieve dirty count for client {client name} and publication item {publication item name}**

**Cause:** An unexpected error occurred while retrieving the outbound records for the mobile user and publication item listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10016: Unable to retrieve subscription count for client {client name} and publication item {publication item name}**

**Cause:** An unexpected error occurred while retrieving the subscription count for the mobile user and publication item listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10017: Unable to execute query for publication item {publication item name} with template {query template identifier} as {query}**

**Cause:** An unexpected error occurred while executing timing for the publication item and template listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10018: Unable to build publication for {publication name}**

**Cause:** An unexpected error occurred while gathering meta-data for the publication listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10019: Unable to verify base view for {publication item name}**

**Cause:** An unexpected error occurred while verifying whether a base view can be used for the publication item listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10020: Unable to retrieve query types for {publication item name}**

**Cause:** An unexpected error occurred while retrieving profiled query templates from the mobile server repository for the publication item listed.

**Action:** Check the exception stack trace for possible causes.

**CONSPERF-10021: Unable to resolve table name for {owner}.{store name}**

**Cause:** An unexpected error occurred while resolving the table name for the object owner and name listed.

**Action:** Verify that the object owner and name point to a valid database table. Check the exception stack for possible causes.

**CONSPERF-10022: Unable to locate publication items for {publication name}**

**Cause:** Unable to retrieve any publication items for the publication listed.

**Action:** Verify that the publication name listed is a valid publication. If so, verify that the publication name listed has at least one publication item added to it.

**CONSPERF-10024: Invalid parameter passed {Consp perf parameter}**

**Cause:** An unrecognized parameter was passed to Consp perf.

**Action:** Check the spelling of the parameter listed, and refer to the documentation for a complete list of valid parameters. Running Consp perf without any arguments will also list the valid parameters.

**CONSPERF-10025: Unable to generate plan for {publication item name}**

**Cause:** An unexpected error occurred while generating explain plan data in the mobile server repository. The database running out of tablespace or rollback extents most likely causes this.

**Action:** Check the exception stack trace for possible causes. If necessary, increase the tablespace or rollback extents.

**CONSPERF-10026: Unable to generate statistics for {publication name}**

**Cause:** An unexpected error occurred while analyzing the mobile server objects. The most likely cause of this is the mobile server schema owner lacking the necessary privileges.

**Action:** Check the exception stack trace for possible causes. If necessary, assign the required privileges to the mobile server schema owner.

**CONSPERF-10027: Unable to suspend MGP. Please wait and try again when MGP is not processing and clients are not synchronizing.**

**Cause:** Consp perf was unable to suspend the MGP compose phase while gathering statistics. This will occur if the MGP is currently in the compose phase or if a client is synchronizing, and Consp perf is run with the GATHERSTATS parameter.

**Action:** Wait for the MGP to complete processing and for all clients to complete synchronizing, before running Consp perf with GATHERSTATS enabled.

**CONSPERF-10028: Unable to clear temporary data from {table name}**

**Cause:** An unexpected error occurred while clearing plan data from the mobile server repository. The most likely cause of this is the database running out of rollback extents.

**Action:** Check the exception stack trace for possible causes. If necessary, increase the rollback extents.

## 1.9 OMS 3000–3099 Oracle Mobile Manager Messages

**OMS-03000: ACCESS DENIED - USER UNAUTHORIZED**

**Cause:** The user has been granted access by the administrator, but the user's connection privilege has not been raised to administrative privilege.

**Action:** Use the Mobile Manager to edit the user’s privileges. Change the user’s privilege to Administrator.

**OMS-03001: Error retrieving {attribute} for {object}**

**Cause:** There was a server-side error while retrieving the specified information for the specified system object.

**Action:** Turn debugging on at the server side for more detail.

**OMS-03002: Error retrieving {object}**

**Cause:** There was a server side error while retrieving the specified information.

**Action:** Turn debugging on at the server side for more detail.

**OMS-03004: {object} not created! This User/Group already exists!**

**Cause:** The object the administrator is attempting to create would overwrite an already existing object in the system.

**Action:** Either edit the existing object or create a new one with a unique name.

**OMS-03005: Unable to find any Entries that Match Your Criteria**

**Cause:** The Mobile Manager cannot find any entries in the repository that match your query.

**Action:** Use more general criteria for the search, or use no criteria to return all objects of the given type in the repository.

**OMS-03007: The Administrator cannot be removed from the System**

**Cause:** The administrator cannot be removed from the system.

**Action:** Do not attempt to remove the specified user from the system.

**OMS-03008: The Mobile Manager cannot create a User that already exists!**

**Cause:** The user that you attempted to create already exists in the system.

**Action:** Modify the existing user.

**OMS-03009: Invalid file format!**

**Cause:** JAR file is wrong.

**Action:** Must use JAR file from Packaging wizard.

**OMS-03010: The application already exists.**

**Cause:** The application already exists in the system.

**Action:** Delete previous one before trying to create a new one.

**OMS-03013: You cannot remove yourself from the system.**

**Cause:** You cannot remove yourself from the system.

**Action:** Do not attempt to remove the specified user from the system.

## 1.10 OMS 3100–3599 Errors from the oracle.lite.web.resource Package

**OMS-03100: {resource} does not exist**

**Cause:** The specified resource does not exist in the system.

**Action:** Create the desired resource and re-run the script.

**OMS-03101: Parameter, {parameter name}, not registered**

**Cause:** The snapshot parameter is not registered with the server.

**Action:** Ensure that the parameter is registered on the server.

**OMS-03102: {field} cannot be null**

**Cause:** The user name or password cannot be null.

**Action:** Verify that the user name and password contain values.

**OMS-03103: Platform value is invalid.**

**Cause:** Platform value passed is invalid.

**Action:** Pass valid Platform value.

**OMS-03108: Invalid Username and/or Password.**

**Cause:** The username and password entered for the database that you wish to import are incorrect.

**Action:** Try importing again with the correct username and password.

**OMS-03110: Username or password cannot be an Oracle Database reserved word**

**Cause:** The username and password entered for the mobile server repository database that you wish to import are Oracle database reserved words.

**Action:** Try importing again with the correct username and password.

**OMS-03111: Password cannot be an Oracle database reserved word**

**Cause:** The password entered for the mobile server database that you wish to import is an Oracle database reserved word.

**Action:** Try importing again with the correct password.

**OMS-03112: Password contains special characters**

**Cause:** The password entered for the mobile server database that you wish to import contains special characters.

**Action:** Try importing again with the correct password.

**OMS-03113: Password cannot be more than 28 characters**

**Cause:** The password entered for the mobile server database that you wish to import is more than 28 characters.

**Action:** Try importing again with the correct password.

**OMS-03114: User {0} could not be created**

**Cause:** User cannot be created.

**Action:** Check the mobile server log for the error.

**OMS-03500: {0} does not exist.**

**Cause:** The specified resource does not exist in the system.

**Action:** Create the desired resource and re-run the script again.

**OMS-03501: Parameter, {0}, not registered.**

**Cause:** The snapshot parameter has not been registered with the server.

**Action:** Ensure that the parameter you are registering on the server

**OMS-03502: {0} cannot be empty.**

**Cause:** The username or password cannot be null.

**Action:** Check the username or password of the user and ensure that it contains a value.

**OMS-03503: Platform value is invalid.**

**Cause:** Examine the Platform value passed.

**Action:** Pass a valid Platform value.

**OMS-03504: User {0} does not have required privileges.**

**Cause:** User with does not have required privileges to perform this operation.

**Action:** Pass a valid user with User privilege level.

**OMS-03505: User {0} not found in the mobile server repository.**

**Cause:** User not found in the repository.

**Action:** Pass a valid user.

**OMS-03507: Privilege cannot be changed. User {0} is assigned to an Application.**

**Cause:** Privilege for user cannot be changed as it is assigned to an Application and/or a Group.

**Action:** Remove the associated Application(s) and/or Group(s) from the User before changing the privilege.

**OMS-03508: Privilege cannot be changed. User {0} is assigned to a Group.**

**Cause:** Privilege for user cannot be changed as it is assigned to an Application and/or a Group.

**Action:** Remove the associated Application(s) and/or Group(s) from the User before changing the privilege.

**OMS-03509: The user name {0} does not exist in the repository, please check the user name.**

**Cause:** The user name provides does not exist in the repository.

**Action:** Ensure the user name is correct.

**OMS-03510: Username cannot be empty.**

**Cause:** The username cannot be null.

**Action:** Check the username of the user and ensure that it contains a value.

**OMS-03512: Mobile Server user authentication error.**

**Cause:** The User(s) cannot be authenticated from the mobile server.

**Action:** Check the mobile server log for the error.

**OMS-03513: The group name {0} does not exist in the repository, please check the group name.**

**Cause:** The user name provides does not exist in the repository.

**Action:** Ensure the user name is correct.

## 1.11 OMS 10000–10200 Oracle General Messages

**OMS-10001: Cannot write to a closed stream**

**Cause:** User tried to write data to a stream that is already closed.

**Action:** Re-open the stream before writing data.

**OMS-10002: Cannot read from a closed stream**

**Cause:** User tried to read data from a stream that is already closed.

**Action:** Re-open the stream before reading.

**OMS-10003: Input buffer is either 'null' or empty**

**Cause:** Invalid parameter is passed to the write method of the stream.

**Action:** Verify the validity of your input buffer.

**OMS-10004: Buffer not large enough to hold data**

**Cause:** The input buffer is too small to hold the data the user attempts to read.

**Action:** Increase the buffer size and read the data again.

**OMS-10005: File Name is 'null' or empty**

**Cause:** User tried to open a stream with an invalid file name.

**Action:** Provide correct file name and open the stream.

**OMS-10006: Failed to open {file name} ({error code})**

**Cause:** System could not locate the specified file.

**Action:** Verify the existence of the file in the file system.

**OMS-10007: Failed to create directory {directory name}**

**Cause:** The directory may already exist in the system.

**Action:** Verify the existence of the directory.

**OMS-10008: Failed to remove directory {directory name}**

**Cause:** The directory may not be empty.

**Action:** Delete all files in the directory before deleting the directory.

**OMS-10009: File write error ({error code})**

**Cause:** System failed to write the data to the file.

**Action:** Verify the validity of your input buffer.

**OMS-10010: File truncation failed ({error code})**

**Cause:** System could not truncate the file.

**Action:** The file may be opened by another user. Close all open references to the file.

**OMS-10011: Invalid stream handle**

**Cause:** Stream handle used for the operation is invalid.

**Action:** Re-open the file (stream).

**OMS-10012: A directory {directory name} already exists**

**Cause:** You attempted to create a directory that already exists.

**Action:** Select a different name for the new directory.

**OMS-10013: Directory {directory name} is not empty**

**Cause:** You attempted to delete a directory that is not empty (contains other directories and/or files).

**Action:** Delete all files from the directory before deleting the directory itself.

**OMS-10014: Access violation: Cannot delete root directory**

**Cause:** You attempted to delete the root directory.

**Action:** This action is not permitted.

**OMS-10015: Directory {directory name} not found**

**Cause:** System could not locate the specified directory.

**Action:** Verify the existence of the directory.

**OMS-10016: File {file name} not found**

**Cause:** File may not exist.

**Action:** Check for the existence of the file.

**OMS-10017: Failed to mount file system on {service name}**

**Cause:** The specified TNS name (DSN) may not exist.

**Action:** Verify the TNS name (DSN) and try again.

**OMS-10018: The syntax of the command is incorrect**

**Cause:** The number of arguments specified with the command is incorrect.

**Action:** Re-execute the command with the correct syntax.

**OMS-10019: Command not recognized**

**Cause:** You specified a command that is not supported by the tool.

**Action:** Check the syntax of the command.

**OMS-10020: Script file processed completely**

**Cause:** The script file executed completely, with no errors.

**Action:** No action necessary, this message is informative only.

**OMS-10021: Cannot delete file {file name}**

**Cause:** User attempted to delete an open file.

**Action:** Close the file before deleting it.

**OMS-10022: File system not initialized**

**Cause:** User tried to open a file from an unmounted file system.

**Action:** Mount the file system and try again.

**OMS-10023: Unable to connect to the Application Repository**

**Cause:** Mobile server could not connect to the repository.

**Action:** Provide a valid user name and password for the repository user.

**OMS-10024: Failed to load script file**

**Cause:** The path to the script file is invalid.

**Action:** Check the path of the script file and ensure that you have read access privileges on the file.

**OMS-10025: Syntax error at line {line number}**

**Cause:** The script file contains an error at the specified line.

**Action:** Correct the error in the script file and re-execute the command.

**OMS-10026: Syntax error at line {line number}, expected {keyword}**

**Cause:** A keyword, other than the given keyword, is in the script file at the specified line.

**Action:** Correct the error in the script file and re-execute the command.

**OMS-10101: Mobile Server Security Violation!**

**Cause:** User attempted to access a protected URL.

**Action:** Contact your system administrator to grant proper access.

**OMS-10102: Logon session for {user name} has expired!**

**Cause:** The browser idle time exceeded the logon expiration time.

**Action:** Log on again.

**OMS-10104: You are not authorized to access this URL**

**Cause:** User attempted to access a protected URL.

**Action:** Contact the system administrator to get proper access.

**OMS-10106: Failed to logon to Mobile Server!**

**Cause:** Logon information may be incorrect.

**Action:** Provide correct information.

**OMS-10107: The logon information provided for {user name} is incorrect**

**Cause:** Logon information may be incorrect.

**Action:** Provide correct information.

**OMS-10108: Please verify your username, password and try again!**

**Cause:** Logon information may be incorrect.

**Action:** Provide correct information.

**OMS-10109: Mobile Server could not locate requested URL**

**Cause:** System could not locate the URL specified by the user.

**Action:** Check the URL and try again.

**OMS-10110: Mobile Server could not locate requested URL {URL}**

**Cause:** System could not locate the URL specified by the user.

**Action:** Check the URL and try again.

**OMS-10111: Please contact the application vendor**

**Cause:** An error occurred in your application.

**Action:** Contact the application vendor.

**OMS-10113: Mobile Server Error**

**Cause:** User action caused an error.

**Action:** See the details displayed on your browser.

**OMS-10116: The Mobile Server is down!**

**Cause:** The mobile server may be down.

**Action:** Contact the system administrator.

**OMS-10117: Please contact your system administrator**

**Cause:** An error occurred in your system.

**Action:** Contact the system administrator.

**OMS-10118: Mobile server is not running**

**Cause:** The mobile server may be down.

**Action:** Contact your system administrator.

**OMS-10121: Please provide valid information**

**Cause:** Incorrect logon information provided.

**Action:** Provide valid information.

**OMS-10122: Application Suspended!**

**Cause:** The application has been suspended by the administrator

**Action:** Try again at a later time. If the application is not available, contact your system administrator.

**OMS-10123: The application {0} you are trying to access is suspended by your administrator.**

**Cause:** The application has been suspended by the administrator

**Action:** Try again at a later time. If the application is not available, contact your system administrator.

**OMS-10124: You do not have enough privileges to logon to the System**

**Cause:** User does not have `CONNECT` privilege to log on to the system.

**Action:** Contact your system administrator for this privilege.

**OMS-10125: Unable to change password**

**Cause:** The system cannot change your password. Either the current password is incorrect, or the new passwords do not match.

**Action:** Verify that you specified the correct current password. If you entered the new password twice, ensure the values match. Retry the operation.

**OMS-10126: Unable to save preferences**

**Cause:** The system cannot save your new user preferences. This is due to invalid input, or a more serious system error.

**Action:** Verify your input to ensure you specified legal values for your preferences. If this is the case, and you still receive this message, contact the system administrator. The system administrator should turn on the mobile server log messages to obtain more detailed information regarding the cause of this problem.

**OMS-10127: Password not changed: new password is identical to old password**

**Cause:** The system cannot change your password. The new password cannot be the same as the old password.

**Action:** Select a password that is different from your current password and retry the operation.

**OMS-10131: Version not available.**

**Cause:** The mobile server version was not available.

**Action:** Contact your system administrator.

**OMS-10132: You cannot login to an account with Administrator privileges from {0}.**

**Cause:** User cannot login to an account with Administrator privileges from this IP address.

**Action:** Login from a different IP address.

**OMS-10133: Mobile Server MGP Process Busy**

**Cause:** When MGP is busy process user changes, the mobile server is not available for synchronization.

**Action:** Try to synchronize at a later time. Contact the administrator if you still cannot synchronize.

**OMS-10135: You do not have access on any Mobile Application**

**Cause:** User do not have access on any mobile application.

**Action:** Contact the system administrator.

**OMS-10136: Not enough privileges to perform this operation**

**Cause:** User does not have CONNECT privilege to logon to the System.

**Action:** Contact your system administrator to grant connect privilege.

**OMS-10137: The Mobile Server is terminating!**

**Cause:** The System administrator has started graceful shutdown of the server.

**Action:** Wait for the server to be available again.

**OMS-10341: Password should start with a alphabet.**

**Cause:** During the change password if the password does not starts with a alphabet.

**Action:** Enter a password which starts with alphabet.

**OMS-10342: Class Not Found sync again as application file sync may have failed or please contact your system administrator.**

**Cause:** Class no the client side is not found or file sync failed.

**Action:** Sync again or contact the administrator.

**OMS-10143: You do not have Administrator privileges to logon to the System.**

**Cause:** User does not have the Administrator privilege to logon to the System.

**Action:** Contact your system administrator to grant connect privilege.

**OMS-10144: Invalid Current Password.**

**Cause:** You have provided an incorrect password.

**Action:** Provide the current password.

**OMS-10147: Invalid Authentication Request**

**Cause:** Out of request Error, Invalid Mac.

**Action:** Providing info that authentication request is invalid.

**OMS-10148: Invalid Username and/or Password. for user {0}**

**Cause:** Owner Credentials Are Invalid.

**Action:** Providing info to the user.

**OMS-10149: Could not find the common access card configuration file**

**Cause:** The Common Access Card (PKCS11) configuration file is not present at the expected location.

**Action:** Contact your system administrator to configure your system to use with smart card.

**OMS-10150: Could not read data from the common access card**

**Cause:** Software could not read data from common access card.

**Action:** Ensure that the common access card is inserted properly in the card reader.

**OMS-10151: Error in connecting to card reader or corrupt smart card configuration file**

**Cause:** The software could not connect to the common access card reader, either because the reader is not properly connected, or the common access card configuration file is corrupt.

**Action:** Ensure that the common access card reader is properly connected to the system. If it is, then contact your system administrator to configure your system to use with common access cards.

**OMS-10152: Logging in using a Common Access Card requires Java Runtime Version 1.5 or higher.**

**Cause:** The current Java runtime environment does not have the correct libraries to access the Common Access Card.

**Action:** Install JRE 1.5.

## 1.12 OMS 20500–20600 Packaging Wizard Messages

**OMS-20501: At Line ({line number}, {column number}) in file {file name} {additional message information}**

**Cause:** The XML file is not well-formed.

**Action:** Examine the XML file using a text or XML editor.

**OMS-20502: Packaging Wizard failed {additional message information}**

**Cause:** Failed to publish due to network or authorization reasons.

**Action:** Examine the file `wtgpack.log` in the mobile server root directory for more information.

**OMS-20503: Packaging Wizard failed**

**Cause:** Failed to publish due to network or authorization failure, or a non-valid XML file.

**Action:** Examine the file `wtgpack.log` in the mobile server root directory for more information.

**OMS-20504: Publishing failed. Check wtgpack.log file for more detail**

**Cause:** Failed to publish due to network or authorization failure, or a non-valid XML file.

**Action:** Examine the file `wtgpack.log` in the mobile server bin directory for more information.

**OMS-20505: Cannot find wtgos.dll in the system path. Help will not be available**

**Cause:** The file, `wtgos.dll`, is required to view the context-sensitive HTML help documentation.

**Action:** Ensure `wtgos.dll` is in the mobile server bin directory.

**OMS-20506: Application already exists, use -o to override with the new settings**

**Cause:** The application definition already exist on the server.

**Action:** Use `-o` to override the existing definition on the server.

**OMS-20507: The Application {0} does not exist, please check the application name**

**Cause:** the application name that user provides, does not exists in the workspace xml file.

**Action:** Ensure the application name is correct, note the application is case-sensitive.

**OMS-20508: Invalid JAR file, it does not contain the web.xml file**

**Cause:** Packaged application JAR file contains web.xml must include web.xml, which contains the application definition.

**Action:** Ensure the web.xml file exists in the JAR file

**OMS-20509: Unable to contact Mobile Server. Make sure that you have specified the correct Mobile Server URL and that the server has been launched properly.**

**Cause:** Mobile server started at the admin port only, the administrator has not logged in yet.

**Action:** Ensure the server is running completely with the database user's username and password.

## 1.13 OMS 21000–21999 Errors reported by the Tools classes in oracle.lite.web.tools.

**OMS-21000: File Name or Application Id cannot be null**

**Cause:** The FileName cannot be null.

**Action:** Examine the File name passed.

**OMS-21001: File {0} cannot be found**

**Cause:** The specified file does not exist in the system.

**Action:** Contact your system administrator.

**OMS-21002: Application Id cannot be null**

**Cause:** Application Id cannot be null.

**Action:** Examine the Application Id passed.

**OMS-21003: Job class could not be found**

**Cause:** Unable to find job class.

**Action:** Contact your system administrator.

**OMS-21004: Error in retrieving Sequence**

**Cause:** Error in retrieving Sequence.

**Action:** Contact your system administrator.

**OMS-21005: Data saved successfully, Unable to refresh data**

**Cause:** Data saved successfully, Unable to refresh data.

**Action:** Contact your system administrator.

**OMS-21006: Error in getting data**

**Cause:** Error in getting data.

**Action:** Contact your system administrator.

**OMS-21007: This Application cannot be used in online mode**

**Cause:** The administrator attempted to use this application in on-line mode.

**Action:** Use this application in off-line mode only.

**OMS-21008: Job can only be scheduled for future time**

**Cause:** Job can only be scheduled for future time.

**Action:** Change Date/Time.

**OMS-21009: Error in saving file**

**Cause:** Error in saving file.

**Action:** Contact your system administrator.

**OMS-21500: File {filename} does not contain a valid SSL Certificate**

**Cause:** File does not contain a valid SSL certificate for SSL communication with mobile server.

**Action:** Contact your system administrator and ensure that a valid SSL certificate is uploaded to the mobile server repository.

**OMS-21501: This Feature is only available in SSL mode**

**Cause:** This feature is only available if server is running in SSL mode.

**Action:** Contact your system administrator.

## C

---

Consolidator messages, 1-15  
Conserf messages, 1-24  
Customer support  
    contacting, 1-1

## M

---

Mobile Manager messages, 1-27  
mobile server  
    contacting customer support, 1-1  
Msync error messages, 1-6

## P

---

packaging wizard  
    messages, 1-36

## S

---

Secure Socket Layer messages, 1-11  
SSL errors, 1-11

## T

---

Tools classes errors, 1-37  
Transport errors, 1-9

