

Oracle® Configuration Manager

Collection Overview

Release 12.1.2

E48300-04

June 2015

Oracle Configuration Manager Collection Overview, Release 12.1.2

E48300-04

Copyright © 2008, 2015, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface	xix
Audience	xix
Documentation Accessibility	xix
Related Documents	xix
Conventions	xix
What's Changed	xx
1 Introduction	
2 Host Collections	
2.1 File Systems.....	2-1
2.2 Hardware	2-1
2.3 Hardware Component	2-1
2.4 Hardware CPU.....	2-2
2.5 Host User Defined Products.....	2-2
2.6 I/O Devices.....	2-2
2.7 Installed Firmware.....	2-2
2.8 Installed OS Patches	2-2
2.9 Network Information Configuration	2-2
2.10 Operating System.....	2-3
2.11 Operating System Components	2-3
2.12 Operating System Modules	2-3
2.13 Operating System Properties	2-3
2.14 Operating System Registered Software	2-3
2.15 Operating System ULIMITs	2-4
3 JD Edwards Collections	
3.1 JD Edwards Enterprise One	3-1
3.1.1 Data Sources	3-1
3.1.2 Environments	3-2
3.1.3 Data Server (F9650).....	3-2
3.1.4 Deployment Servers (F9650)	3-2
3.1.5 Crystal Enterprise CMS	3-2
3.1.6 Enterprise Servers (F9650)	3-2
3.1.7 Crystal Enterprise Web Server.....	3-3

3.1.8	Web Servers (F9650)	3-3
3.1.9	Windows Terminal Server (F9650).....	3-3
3.1.10	Path Codes	3-3
3.1.11	Updates	3-4
3.1.12	Data Indicators.....	3-4
3.2	JD Edwards Enterprise One Collaborative Portal.....	3-4
3.2.1	Standalone Agent Managed Instances.....	3-4
3.2.2	Standalone Agent Managed Instances Attributes.....	3-4
3.2.3	Standalone Agent Managed Instance JAS INI.....	3-4
3.2.4	Standalone Agent Managed Instances JDBJ INI	3-5
3.2.5	Standalone Agent Managed Instances JDE INI.....	3-5
3.3	JD Edwards Enterprise One Enterprise Server.....	3-5
3.3.1	Standalone Agent Managed Instances.....	3-5
3.3.2	Standalone Agent Managed Instance Attributes	3-5
3.3.3	Standalone Agent Managed Instance JDE INI	3-5
3.4	JD Edwards Enterprise One Management Console.....	3-5
3.4.1	Management Console Agent.....	3-5
3.4.2	Management Console Agent Attributes.....	3-6
3.4.3	Management Console JAS INI	3-6
3.4.4	Management Console JDBC INI.....	3-6
3.4.5	Management Console Managed Homes	3-6
3.4.6	Management Console Managed Instances.....	3-6
3.5	JD Edwards Enterprise One PIM Synch Server.....	3-6
3.5.1	Standalone Agent Managed Instances.....	3-6
3.5.2	Standalone Agent Managed Instance Attributes	3-6
3.5.3	Standalone Agent Managed Instance JAS INI.....	3-7
3.5.4	Standalone Agent Managed Instance JDBJ INI.....	3-7
3.6	JD Edwards Enterprise One Standalone Agent.....	3-7
3.6.1	Standalone Agent.....	3-7
3.6.2	Standalone Agent Attributes.....	3-7
3.6.3	Standalone Agent Managed Instances.....	3-7
3.7	JD Edwards Enterprise One Transaction Server	3-7
3.7.1	Standalone Agent Managed Instances.....	3-7
3.7.2	Standalone Agent Managed Instance Attributes	3-8
3.7.3	Standalone Agent Managed Instance JAS INI.....	3-8
3.7.4	Standalone Agent Managed Instance JDBJ INI.....	3-8
3.8	JD Edwards Enterprise One Web Server.....	3-8
3.8.1	Standalone Agent Managed Instances.....	3-8
3.8.2	Standalone Agent Managed Instance Attributes	3-8
3.8.3	Standalone Agent Managed Instance JAS INI.....	3-8
3.8.4	Standalone Agent Managed Instance JDBJ INI.....	3-9

4 Oracle Application Server Collections

4.1	Application Deployment	4-1
4.1.1	Application Configuration	4-1
4.2	FTP Application	4-1
4.2.1	General	4-1

4.3	IAS Configuration.....	4-2
4.3.1	Console.....	4-2
4.3.2	DCM Auto Archive Check.....	4-2
4.3.3	Debug Log Level Check.....	4-2
4.3.4	Log Level Check.....	4-2
4.4	JServ.....	4-2
4.4.1	Configuration Files.....	4-2
4.4.2	JServ Zones.....	4-3
4.5	OC4J.....	4-3
4.5.1	Applications.....	4-3
4.5.2	Configuration Files.....	4-3
4.5.3	Connection Pools.....	4-3
4.5.4	Data Sources.....	4-3
4.5.5	Deployed Applications.....	4-3
4.5.6	Global Web Module Settings.....	4-3
4.5.7	Log Growth Check.....	4-3
4.5.8	Managed Data Sources.....	4-4
4.5.9	Modules.....	4-4
4.5.10	Native Data Sources.....	4-4
4.5.11	Port Ranges.....	4-4
4.5.12	Resource Usage.....	4-4
4.5.13	Web Module Settings.....	4-4
4.5.14	Web Module URLs.....	4-4
4.6	Oracle Application Server.....	4-4
4.6.1	Configuration Files.....	4-4
4.6.2	Console.....	4-5
4.6.3	DCM.....	4-5
4.6.4	Deployed Applications.....	4-5
4.6.5	General.....	4-5
4.6.6	Components.....	4-5
4.6.7	OPMN.....	4-5
4.7	Oracle HTTP Server.....	4-5
4.7.1	Configuration Files.....	4-5
4.7.2	General.....	4-6
4.7.3	File Permission Check.....	4-6
4.7.4	Identity Check.....	4-6
4.7.5	Listen Addresses.....	4-6
4.7.6	Log Growth Check.....	4-6
4.7.7	Log Level Check.....	4-6
4.7.8	Performance Related.....	4-7
4.7.9	SSL Ciphers Suite Settings.....	4-7
4.7.10	Virtual Hosts.....	4-7
4.8	Oracle iAS Farm.....	4-7
4.8.1	Farm Configuration.....	4-7
4.9	Oracle Internet Directory.....	4-7
4.9.1	Oracle Internet Directory Configuration.....	4-7
4.10	Web Cache Server.....	4-8

4.10.1	Cluster Information	4-8
4.10.2	Cluster Members	4-8
4.10.3	Configuration Files	4-8
4.10.4	File Permission Check	4-8
4.10.5	Identity Check	4-8
4.10.6	Listening Ports	4-8
4.10.7	Log Growth Check	4-9
4.10.8	Log Level Check	4-9
4.10.9	Operations Ports	4-9
4.10.10	Origin Servers	4-9
4.10.11	Performance Related	4-9
4.10.12	Site Aliases	4-9
4.10.13	Host Mappings	4-9

5 Oracle Beehive Site Configuration Collections

5.1	Application Server	5-1
5.2	CalDAV Application	5-1
5.2.1	General	5-1
5.3	Calendar Applications	5-1
5.3.1	Calendar Application HTTP Server Configuration	5-1
5.4	Calendar Server	5-1
5.4.1	Calendar Server Basic Configuration	5-2
5.4.2	Calendar Configuration	5-2
5.4.3	Calendar Server Configuration	5-2
5.5	Conference Application	5-2
5.5.1	General	5-2
5.6	Database	5-2
5.7	HTTP Server	5-2
5.8	LDAP	5-2
5.9	OC4J	5-3
5.10	Virtual Server	5-3
5.11	VoiceMessage Application Configuration	5-3
5.11.1	General	5-3
5.11.2	Facility Properties	5-3

6 Oracle BPEL Process Manager Collections

6.1	BPEL Domain Configuration Properties	6-1
6.2	BPEL General Configuration Properties	6-1
6.3	BPEL Cluster Configuration Properties	6-1
6.4	BPEL Dehydration Store Configuration Properties	6-1
6.5	Instance Information	6-1

7 Oracle Business Intelligence (BI) Collections

7.1	Oracle Business Intelligence (BI) Analytics Server	7-1
7.1.1	BI Analytics Server Configuration Parameters	7-1
7.2	Oracle Business Intelligence (BI) Cluster Controller	7-2

7.2.1	BI Cluster Controller Configuration Parameters	7-2
7.2.2	BI DAC Server Properties	7-2
7.2.3	BI DAC ETL Summary	7-2
7.3	Oracle Business Intelligence (BI) DAC	7-3
7.3.1	BI DAC Server Properties	7-3
7.3.2	BI DAC ETL Summary	7-3
7.4	Oracle Business Intelligence (BI) Instance	7-3
7.5	Oracle Business Intelligence (BI) Presentation Server	7-3
7.5.1	BI Presentation Server Configuration Parameters	7-4
7.5.2	BI Presentation Server Alerts Configurations	7-4
7.5.3	BI Presentation Server Cache Configurations	7-4
7.5.4	BI Presentation Server Charts Configurations.....	7-4
7.5.5	BI Presentation Server Client Configurations.....	7-4
7.5.6	BI Presentation Server Display Configurations	7-5
7.5.7	BI Presentation Server Marketing Configurations.....	7-5
7.5.8	BI Presentation Server Other Configurations	7-5
7.5.9	BI Presentation Server Report Cache Configurations	7-5
7.5.10	BI Presentation Server State Pool Configurations.....	7-5
7.5.11	BI Presentation Server Thread Pool Configurations.....	7-5
7.5.12	BI Presentation Server XML Cache Defaults	7-5
7.6	Oracle Business Intelligence (BI) Scheduler Server.....	7-6
7.6.1	BI Scheduler.....	7-6
7.6.2	BI Schedule IBOTS.....	7-6
7.6.3	BI Scheduler Mail.....	7-7
7.6.4	Instance Information	7-7
7.7	Oracle Business Intelligence (BI) Web Plugin.....	7-7
7.7.1	BI Web Plugin.....	7-7

8 Oracle Cloud Control Collections

8.1	Oracle Agent Deployment Configuration	8-1
8.1.1	MGMT_ECM_EMD_JAVA_PARAMS	8-1

9 Oracle Coherence Collections

9.1	Oracle Coherence	9-1
-----	------------------------	-----

10 Oracle Collaboration Suite Collections

10.1	IM Application	10-1
10.1.1	General	10-1
10.2	PushMail Application	10-1
10.2.1	General	10-1
10.3	Real-Time Collaboration	10-1
10.3.1	Real-Time Collaboration Command-Line Control Configuration	10-1
10.4	WebDAV Application	10-2
10.4.1	General	10-2
10.4.2	Default Welcome Docs.....	10-2
10.5	Workspaces Application	10-2

10.5.1	General	10-2
10.6	XMPP Application	10-2
10.6.1	General	10-2
10.6.2	Domain Names	10-2
10.6.3	Search Fields	10-2
10.6.4	Supported Agents	10-3

11 Oracle Configuration Manager Collections

11.1	Oracle Configuration Manager Package Versions	11-1
11.2	Oracle Configuration Manager Parameter Values	11-1

12 Oracle Data Integrator Collections

12.1	Oracle Data Integrator Agent	12-1
12.2	Oracle Data Integrator Console	12-1
12.3	Oracle Data Integrator SDK Web	12-1

13 Oracle Database and Database-Related Collections

13.1	Automatic Storage Management	13-1
13.1.1	ASM Instance Properties	13-1
13.2	Database Instance	13-1
13.2.1	ASM Disk	13-1
13.2.2	Control Files	13-2
13.2.3	CPU Usage Statistics	13-2
13.2.4	Data Files	13-2
13.2.5	Database Autotask Client	13-2
13.2.6	Database Components	13-2
13.2.7	Database Configuration Version	13-3
13.2.8	Database License	13-3
13.2.9	Database Options	13-3
13.2.10	Database Scheduler Jobs	13-3
13.2.11	Database Users	13-3
13.2.12	DB Invalid Objects	13-3
13.2.13	Feature Usage	13-4
13.2.14	High Availability - General Information	13-4
13.2.15	High Availability - RMAN Configuration	13-4
13.2.16	High Water Mark Statistics	13-4
13.2.17	Initialization Parameters	13-4
13.2.18	Instance Information	13-5
13.2.19	Redo Logs	13-5
13.2.20	Rollback Segments	13-5
13.2.21	STATS Pack Configuration	13-6
13.2.22	System Global Area	13-6
13.2.23	Tablespaces	13-6
13.3	Oracle Cluster	13-6
13.3.1	Cluster Manager Configuration	13-6
13.3.2	High Availability Cluster Interconnect	13-7

13.3.3	Server Configuration.....	13-7
13.4	Oracle Listener.....	13-7
13.4.1	Listener Status	13-7
13.5	Real Application Cluster Database.....	13-7
13.5.1	ASM Disk	13-7
13.5.2	Control Files.....	13-7
13.5.3	CPU Usage.....	13-8
13.5.4	Data Files.....	13-8
13.5.5	Database Autotask Client	13-8
13.5.6	Database Components	13-8
13.5.7	Database Configuration Version	13-8
13.5.8	Database License.....	13-8
13.5.9	Database Options.....	13-9
13.5.10	Database Scheduler Jobs	13-9
13.5.11	Database Users	13-9
13.5.12	DB Invalid Objects	13-9
13.5.13	Feature Usage	13-9
13.5.14	High Availability - General Information.....	13-10
13.5.15	High Availability - RMAN Configuration	13-10
13.5.16	High-Water Mark Statistics	13-10
13.5.17	Instance Information	13-10
13.5.18	Redo Logs	13-11
13.5.19	Rollback Segments.....	13-11
13.5.20	STATS Pack Configuration.....	13-11
13.5.21	Tablespaces	13-11
13.5.22	Voting Disk.....	13-12

14 Oracle E-Business Suite Collections

14.1	Contract Management Server Database	14-1
14.1.1	CM Admin and Group Database Information	14-1
14.1.2	CM Database Information	14-1
14.1.3	CM Admin and group Database upgrade Version history	14-1
14.2	Contract Management Server	14-1
14.2.1	Contract Manager Configuration Parameters	14-1
14.3	DeviceManagement Application.....	14-2
14.3.1	Blocked Devices	14-2
14.3.2	General	14-2
14.4	Oracle Concurrent Manager.....	14-2
14.4.1	Concurrent Processing Package Versions	14-2
14.4.2	Concurrent Processing Profile Options	14-2
14.4.3	ICM Settings	14-3
14.4.4	Concurrent Managers (Service Instances).....	14-3
14.4.5	Specialization Rules.....	14-3
14.4.6	Summary Configuration.....	14-3
14.4.7	Workshifts for Concurrent Managers	14-3
14.5	Oracle E-Business Suite.....	14-4
14.5.1	Number of Active Users	14-4

14.5.2	Applied Patches (January to December) - Collected by Month.....	14-4
14.5.3	Applications Customer Forms.....	14-4
14.5.4	Applications System Summary.....	14-4
14.5.5	Applications Topology.....	14-4
14.5.6	Comprising Patches (January to December) - Collected by Month.....	14-4
14.5.7	Component Version.....	14-4
14.5.8	Configuration Version.....	14-5
14.5.9	Custom Alert Information.....	14-5
14.5.10	Custom Applications.....	14-5
14.5.11	Profile Options Registered Under Custom Application.....	14-5
14.5.12	Custom Audit Group Information.....	14-5
14.5.13	Custom Database Objects.....	14-5
14.5.14	Custom Hooks.....	14-5
14.5.15	Custom Message Count.....	14-5
14.5.16	Custom Objects Owned by Apps.....	14-6
14.5.17	Custom Request Sets.....	14-6
14.5.18	Responsibility Count.....	14-6
14.5.19	Custom Triggers.....	14-6
14.5.20	Custom Value Sets - Table Validated.....	14-6
14.5.21	Custom Value Sets (Other than Table Validated).....	14-6
14.5.22	Custom Workflows.....	14-6
14.5.23	Registered Data Groups.....	14-6
14.5.24	Database Version.....	14-6
14.5.25	End-Dated Users.....	14-7
14.5.26	Generic Service Components.....	14-7
14.5.27	Generic Service Component Parameters.....	14-7
14.5.28	High Priority Patches Not Applied.....	14-7
14.5.29	JTF Hooks.....	14-7
14.5.30	Localization Modules.....	14-7
14.5.31	NLS Language Support.....	14-7
14.5.32	Other Customizations.....	14-8
14.5.33	Patchset Information.....	14-8
14.5.34	Printers.....	14-8
14.5.35	Printer Drivers.....	14-8
14.5.36	User Profile Options.....	14-8
14.5.37	Technology Stack Inventory (DB).....	14-8
14.6	Oracle E-Business Suite Infrastructure.....	14-8
14.6.1	Appsweb Configuration.....	14-8
14.6.2	Appsweb Configuration Metadata.....	14-9
14.6.3	Applications Context Files.....	14-9
14.6.4	Dbc File.....	14-9
14.6.5	Dbc File Meta.....	14-9
14.6.6	Custom Context Variables.....	14-9
14.6.7	Environments Context Variables.....	14-9
14.6.8	Global Context Variables.....	14-9
14.6.9	Host Context Variables.....	14-10
14.6.10	Install Context Variables.....	14-10

14.6.11	Processes Context Variables.....	14-10
14.6.12	System Context Variables.....	14-10
14.6.13	Technology Stack Inventory (File System).....	14-10
14.6.14	Workflow Mailer Configuration.....	14-10
14.6.15	Workflow Mailer Configuration Metadata.....	14-11
14.7	Search Application.....	14-11
14.7.1	General.....	14-11
14.8	TimeManagement Application.....	14-11
14.8.1	General.....	14-11
14.9	UserDirectory Application.....	14-11
14.9.1	Attribute.....	14-11
14.9.2	Configuration Parameters.....	14-11
14.9.3	Custom Attributes.....	14-12

15 Oracle Enterprise Manager Cloud Control Management Collections

15.1	Oracle Enterprise Manager Cloud Control Management Agent.....	15-1
15.1.1	Agent Configuration Parameters.....	15-1
15.1.2	Java Parameters.....	15-2
15.1.3	Log Parameters.....	15-2
15.1.4	Perl Parameters.....	15-2
15.2	Oracle Enterprise Manager Cloud Control Management Repository.....	15-2
15.2.1	EM Metrics.....	15-2
15.2.2	EM Repository Monitory Agents.....	15-2
15.2.3	EM Repository Monitored Beacons.....	15-2
15.2.4	EM Repository Configuration Parameters.....	15-3
15.2.5	Object Privileges.....	15-3
15.2.6	OMS Name.....	15-3
15.3	Oracle Enterprise Manager Cloud Control Management Service.....	15-3
15.3.1	OMS Configuration Parameters.....	15-3

16 Oracle Exadata Storage Server Software Collections

16.1	CELL Celldisk Configuration.....	16-1
16.2	CELL Griddisk Configuration.....	16-1
16.3	CELL IORM Configuration.....	16-2
16.4	CELL LUN Configuration.....	16-2
16.5	CELL Physical Disk Configuration.....	16-3
16.6	Exadata Bugs Fixed.....	16-3
16.7	Oracle Cell Configuration.....	16-3

17 Oracle Forms Collections

17.1	General Information.....	17-1
------	--------------------------	------

18 Oracle Fusion Applications Instance Collections

18.1	Oracle Fusion Applications Instance.....	18-1
18.2	Oracle Fusion Applications Product Family.....	18-1

18.2.1	Country Specific Localization Features	18-1
18.2.2	Data Fix Script Execution History	18-1
18.2.3	Enabled Languages.....	18-1
18.2.4	Functionally Configured Options	18-1
18.2.5	Multi-Tenancy	18-1
18.2.6	Target Version	18-2
18.3	Oracle Fusion Applications Product	18-2
18.3.1	Functionally Configured Options	18-2
18.3.2	Logical Business Area (LBA).....	18-2
18.3.3	Target Version	18-2
18.4	Oracle Fusion Applications Cluster Application	18-2
18.5	Oracle Fusion Applications J2EE Application	18-2
18.5.1	Target Version	18-2
18.5.2	WebLogic Application Configuration	18-2

19 Oracle Home Collections

19.1	Dependency Rules	19-1
19.2	Oracle Oneoff Patches	19-1
19.3	Oracle Oneoff Patches Bugs Fixed.....	19-1
19.4	Oracle Oneoff Patches Components.....	19-1
19.5	Oracle Software Components	19-1
19.6	Oracle Software Patchsets.....	19-2
19.7	Oracle Versioned Patches	19-2

20 Oracle Hyperion Enterprise Performance Management System Collections

20.1	Oracle Enterprise Performance Management System.....	20-1
20.1.1	Database Connection.....	20-1
20.1.2	Instance Information	20-1
20.2	Oracle's Hyperion Shared Services	20-1
20.2.1	Database Connection.....	20-1
20.2.2	Instance Information	20-1
20.2.3	Security Options Setting	20-1
20.2.4	Security Service Providers.....	20-1
20.2.5	Web Application Deployment	20-2
20.3	Oracle Hyperion Enterprise Performance Management Workspace, Fusion Edition...	20-2
20.3.1	Database Connection.....	20-2
20.3.2	Instance Information	20-2
20.3.3	Web Application Deployment	20-2
20.4	Oracle Hyperion Enterprise Performance Management Architect, Fusion Edition	20-2
20.4.1	Database Connection.....	20-2
20.4.2	Instance Information	20-2
20.4.3	Web Application Deployment	20-2
20.5	Oracle Hyperion Calculation Manager.....	20-3
20.5.1	Database Connection.....	20-3
20.5.2	Instance Information	20-3
20.5.3	Web Application Deployment	20-3
20.6	Oracle Essbase Server.....	20-3

20.6.1	Instance Information	20-3
20.7	Oracle Essbase Administration Services.....	20-3
20.7.1	Instance Information	20-3
20.7.2	Web Application Deployment	20-4
20.8	Oracle Hyperion Provider Services.....	20-4
20.8.1	Instance Information	20-4
20.8.2	Web Application Deployment	20-4
20.9	Hyperion Reporting and Analysis Framework.....	20-4
20.9.1	Database Connection.....	20-4
20.9.2	Instance Information	20-4
20.9.3	Web Application Deployment	20-4
20.10	Hyperion Web Analysis.....	20-4
20.10.1	Instance Information	20-4
20.10.2	Web Application Deployment	20-4
20.11	Oracle Hyperion Financial Reporting, Fusion Edition.....	20-5
20.11.1	Instance Information	20-5
20.11.2	Web Application Deployment	20-5
20.12	Oracle Hyperion Financial Management, Fusion Edition	20-5
20.12.1	Database Connection.....	20-5
20.12.2	Instance Information	20-5
20.13	Oracle Hyperion Planning, Fusion Edition.....	20-5
20.13.1	Business Rules	20-5
20.13.2	Database Connection.....	20-5
20.13.3	Instance Information	20-5
20.13.4	Web Application Deployment	20-6
20.14	Oracle Hyperion Profitability and Cost Management, Fusion Edition	20-6
20.14.1	Database Connection.....	20-6
20.14.2	Instance Information	20-6
20.14.3	Web Application Deployment	20-6
20.15	Oracle Hyperion Performance Scorecard, Fusion Edition.....	20-6
20.15.1	Database Connection.....	20-6
20.15.2	Instance Information	20-6
20.15.3	Web Application Deployment	20-6
20.16	Oracle Hyperion Financial Data Quality Management ERP Integration Adapter for Oracle Applications, Fusion Edition	20-6
20.16.1	Database Connection.....	20-7
20.16.2	Instance Information	20-7
20.16.3	Web Application Deployment	20-7

21 Oracle Identity Management Collections

21.1	Directory Integration Platform	21-1
21.1.1	Directory Integration Platform Configuration	21-1
21.1.2	Admin Server Details	21-1
21.1.3	WebLogic Application Configuration	21-1
21.2	Oracle Access Manager	21-1
21.3	Oracle Adaptive Access Manager	21-1
21.4	Oracle Identity Federation.....	21-2

21.4.1	Server Configurations	21-2
21.4.2	Data Store Configurations	21-2
21.4.3	Identity Provider Configurations	21-2
21.4.4	Identity Provider SAML 2.0 Assertion Properties	21-3
21.4.5	Identity Provider SAML 2.0 Protocol Properties	21-3
21.4.6	Identity Provider SAML 1.0 Assertion and Protocol Properties.....	21-4
21.4.7	Identity Provider WSFed 1.1 Properties.....	21-4
21.4.8	Service Provider Configurations	21-4
21.4.9	Service Provider SAML 2.0 Assertion Properties	21-5
21.4.10	Service Provider SAML 2.0 Protocol Properties.....	21-5
21.4.11	Service Provider SAML 1.x Assertion and Protocol Properties.....	21-6
21.4.12	Service Provider WSFed 1.1 Properties	21-6
21.4.13	Admin Server Details	21-6
21.4.14	WebLogic Application Configuration	21-6
21.5	Oracle Identity Manager	21-6
21.6	Oracle Internet Directory	21-6
21.6.1	Oracle Internet Directory General Configurations	21-6
21.6.2	Oracle Internet Directory Performance Configurations.....	21-7
21.6.3	Oracle Internet Directory SASL Configurations	21-7
21.6.4	Oracle Internet Directory Statistics Configurations.....	21-7
21.6.5	Oracle Internet Directory Log Configurations	21-7
21.6.6	Admin Server Details	21-7
21.7	Oracle Virtual Directory.....	21-8
21.7.1	Server Configuration.....	21-8
21.7.2	Search Configuration.....	21-8
21.7.3	Schema Locations.....	21-8
21.7.4	Listener Configuration.....	21-8
21.7.5	Administration Server Details	21-8

22 Oracle Portal Collections

22.1	Oracle Portal	22-1
------	---------------------	------

23 Oracle Reports Collections

23.1	Oracle Reports Application	23-1
23.2	Oracle Reports Server.....	23-1

24 Oracle Retail Collections

24.1	Oracle Retail Active Retail Intelligence Application	24-1
24.2	Oracle Retail Allocation Java Application.....	24-1
24.3	Oracle Retail Back Office Java Application	24-1
24.4	Oracle Retail Central Office Java Application	24-1
24.5	Oracle Retail Markdown Optimization	24-1
24.6	Oracle Retail Workspace.....	24-1
24.7	Oracle Retail Data Warehouse Database	24-2
24.8	Oracle Retail Merchandising System Application	24-2
24.9	Oracle Retail Returns Management Java Application.....	24-2

24.10	Oracle Retail Price Management Java Application.....	24-2
24.11	Oracle Retail Warehouse Management System Application.....	24-2
24.12	Oracle Retail Invoice Matching Java Application	24-2
24.13	Oracle RPAS Global Domain.....	24-2
24.14	Oracle Retail Predictive Application Server	24-2
24.15	Oracle RPAS Sub Domain.....	24-2
24.16	Oracle Retail Store Inventory Management Java Application	24-2
24.17	Oracle Retail Integration Bus Java Application.....	24-3

25 Oracle WebCenter Collections

25.1	Oracle WebCenter.....	25-1
25.2	Oracle WebCenter Activity Graph	25-1
25.3	Oracle WebCenter Analytics Collector	25-1
25.4	Oracle WebCenter Discussions Server.....	25-1
25.5	Oracle WebCenter Personalization	25-1
25.6	Oracle WebCenter Portlet Server.....	25-1
25.7	Oracle WebCenter Content.....	25-1

26 Oracle WebLogic Collections

26.1	Oracle WebLogic Server.....	26-1
26.1.1	General Server Configuration.....	26-1
26.1.2	Virtual Host Configuration	26-1
26.1.3	Jolt Connection Pools Configuration	26-2
26.1.4	Work Manager Configuration	26-2
26.1.5	Startup and Shutdown Classes Configuration.....	26-2
26.1.6	JDBC DataSource Configuration	26-2
26.1.7	JDBC Multi-DataSource Configuration.....	26-2
26.1.8	JMS Connection Factory Configuration	26-2
26.1.9	JMS Topic Configuration	26-3
26.1.10	JMS Queue Configuration	26-3
26.1.11	Resource Configuration	26-3
26.2	Oracle WebLogic Install.....	26-3
26.2.1	Oracle WebLogic Product Components.....	26-3

27 PeopleSoft Collections

27.1	PeopleSoft Application Server	27-1
27.1.1	Application Server Analytics Parameters	27-1
27.1.2	Application Server Cache Parameters	27-1
27.1.3	Application Server Configuration Parameters.....	27-1
27.1.4	Application Server Database Parameters.....	27-1
27.1.5	Application Server Domain Parameters.....	27-2
27.1.6	Application Server Integration Broker Parameters	27-2
27.1.7	Application Server Interface Driver Parameters.....	27-2
27.1.8	Application Server Jolt Listener Parameters.....	27-2
27.1.9	Application Server Jolt Relay Parameters	27-2
27.1.10	Application Server Message Broker Dispatcher Parameters.....	27-2

27.1.11	Application Server Message Broker Handler Parameters	27-2
27.1.12	Application Server Options Parameters.....	27-3
27.1.13	Application Server Optimization Engine Parameters.....	27-3
27.1.14	Application Server People Code Debugger Parameters	27-3
27.1.15	Application Server PPM Server Parameters	27-3
27.1.16	Application Server PSBRKDSP Server Parameters	27-3
27.1.17	Application Server PSBRKHND Server Parameters	27-3
27.1.18	Application Server PSPUBDSP Server Parameters.....	27-4
27.1.19	Application Server PSPUBHND Server Parameters	27-4
27.1.20	Application Server PSSUBDSP Server Parameters.....	27-4
27.1.21	Application Server PSSUBHND Server Parameters.....	27-4
27.1.22	Application Server PUB-SUB Servers Parameters	27-4
27.1.23	Application Server QCK Server Parameters.....	27-5
27.1.24	Application Server Query Server Parameters	27-5
27.1.25	Application Server Remote Call Parameters	27-5
27.1.26	Application Server REN Server Parameters	27-5
27.1.27	Application Server SAM Server Parameters.....	27-5
27.1.28	Application Server Security Parameters	27-5
27.1.29	Application Server Service Configuration	27-5
27.1.30	Application Server Slave Parameters.....	27-6
27.1.31	Application Server SMTP Parameters	27-6
27.1.32	Application Server Startup Parameters.....	27-7
27.1.33	Application Server Tools Parameters	27-7
27.1.34	Application Server Trace Parameters	27-7
27.1.35	Application Server Workstation Parameters	27-7
27.1.36	Integration Broker Gateway.....	27-8
27.1.37	Integration Broker Handler Slaves.....	27-8
27.1.38	Integration Broker Message Nodes.....	27-8
27.1.39	Integration Broker Node Connector Properties	27-8
27.1.40	Integration Broker Node Properties.....	27-9
27.1.41	Integration Broker Publication Handler Slaves.....	27-9
27.1.42	Integration Broker Subscription Handler Slaves	27-9
27.2	PeopleSoft Batch Server	27-9
27.2.1	Active Process Server Status	27-9
27.2.2	Batch Server Application Engine Parameters.....	27-9
27.2.3	Batch Server Cache Parameters	27-10
27.2.4	Batch Server Crystal Parameters	27-10
27.2.5	Batch Server Data Mover Parameters	27-10
27.2.6	Batch Server Database Parameters	27-10
27.2.7	Batch Server Distribution Agent Parameters.....	27-10
27.2.8	Batch Server Integration Broker Parameters.....	27-10
27.2.9	Batch Server Configuration Parameters	27-10
27.2.10	Batch Server Interface Driver Parameters	27-10
27.2.11	Batch Server nVision Parameters	27-10
27.2.12	Batch Server Optimization Engine Parameters	27-11
27.2.13	Batch Server Process Scheduler Parameters	27-11
27.2.14	Batch Server Remote Parameters.....	27-11

27.2.15	Batch Server SMTP Parameters	27-11
27.2.16	Batch Server SQR Parameters	27-12
27.2.17	Batch Server Startup Parameters	27-12
27.2.18	Batch Server Tools Parameters	27-12
27.2.19	Batch Server Trace Parameters	27-12
27.2.20	Batch Server Tuxedo Parameters.....	27-13
27.2.21	Process Scheduler Notification	27-13
27.2.22	Process Scheduler Sequence Numbers	27-13
27.2.23	Process Scheduler Server Category.....	27-13
27.2.24	Process Scheduler Server Class.....	27-13
27.2.25	Process Scheduler Server Operations	27-13
27.2.26	Process Scheduler System Options	27-14
27.2.27	Process Server Definition.....	27-14
27.3	PeopleSoft Database	27-14
27.3.1	Database Database Parameters	27-14
27.3.2	Database Installation System Options	27-15
27.3.3	Database Language Parameters.....	27-15
27.3.4	Database Options.....	27-15
27.3.5	Database Patch Parameters	27-15
27.3.6	Database Version Parameters	27-15
27.3.7	HCM Database Info.....	27-15
27.3.8	HCM LN XFER ID Values	27-15
27.3.9	Online Marketing Syncids.....	27-15
27.3.10	PTWEBSERVER Last Psswd Change.....	27-15
27.3.11	Record Counts.....	27-15
27.3.12	Record Exclusions.....	27-16
27.4	PeopleSoft Web Server	27-16
27.4.1	Web Server Configuration Parameters.....	27-16
27.4.2	Web Server Information Parameters.....	27-20

28 Primavera Collections

28.1	APPLICATION_GENERAL	28-1
28.2	APP_LIMITS	28-1
28.3	AUTHENTICATION.....	28-1
28.4	CONNPOOL.....	28-1
28.5	DATA_LIMITS	28-2
28.6	DBSESSION	28-2
28.7	DB_CONNECTION.....	28-2
28.8	DOC_REPOSITORY	28-2
28.9	EARNEDVALUEPREFS.....	28-3
28.10	EMAIL_NOTIFICATIONS	28-3
28.11	GROUP_SERVER.....	28-3
28.12	JAVA_OS.....	28-3
28.13	JAVA_PLUGIN	28-3
28.14	LOGSETTINGS.....	28-3
28.15	PERFMON	28-4
28.16	PREFS_OTHER.....	28-4

28.17	SERVICES.....	28-4
28.18	THREADPOOL	28-5
28.19	TIMESHEET_CONNECTION.....	28-5
28.20	TIMESHEET_OPTS.....	28-5
28.21	TRACER	28-5
28.22	USERSECURITY.....	28-6
28.23	WORKFLOW_REPOSITORY	28-6
28.24	WORKTIME_DATE.....	28-6

29 Siebel Collections

29.1	Siebel Component.....	29-1
29.1.1	Siebel Component Configuration.....	29-1
29.2	Siebel Component Group	29-1
29.2.1	Siebel Component Group Configuration	29-2
29.3	Siebel Enterprise.....	29-2
29.3.1	Siebel Enterprise Configuration	29-2
29.3.2	Siebel Upgrade	29-2
29.4	Siebel Gateway	29-3
29.4.1	Siebel Gateway Configuration.....	29-3
29.5	Siebel Server.....	29-3
29.5.1	Siebel Server System Configuration.....	29-3
29.5.2	Siebel Server General Configuration	29-3

30 SOA Infrastructure Collections

30.1	Instance Information	30-1
------	----------------------------	------

31 User Messaging Service Collections

31.1	User Messaging E-Mail Driver.....	31-1
31.2	User Messaging Proxy Driver	31-1
31.3	User Messaging Service	31-1
31.4	User Messaging SMPP Driver.....	31-1
31.5	User Messaging VoiceXML Driver.....	31-1
31.6	User Messaging Worklist Driver	31-1
31.7	User Messaging XMPP Driver	31-2

Preface

This manual lists the configuration categories and their associated items for the target types from which Oracle Configuration Manager collects data.

Audience

This document is intended for all users of Oracle Configuration Manager.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

For more information, see the following documents in the Oracle Configuration Manager documentation set:

- *Oracle Configuration Manager Installation and Administration Guide*
- *Oracle Configuration Manager Quick Start Guide*

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

What's Changed

This table provides a brief overview of the document changes for the latest publication of the *Oracle® Configuration Manager Collection Overview*:

Part Number	Change Summary
E48300-03	Updated for OCM 12.1.2.
E48300-02	Updated for OCM 12.1.

Introduction

This document lists the configuration items collected by Oracle Configuration Manager. The configuration information is grouped according to target types such as the host, Oracle Database, Oracle E-Business Suite, and so on.

Host Collections

The Host collections include the following:

2.1 File Systems

- Resource Name
- Mount Location
- Type
- Mount Options
- Disk Space (GB)
- Local Drive
- Available Disk Space (GB)

2.2 Hardware

- Host Name
- Domain
- Vendor Name
- System Config
- Machine Architecture
- Clock Frequency (MHz)
- Memory Size (MB)
- Local Disk Space (GB)
- CPU Count
- CPU Board Count
- I/O Card Count
- Fan Count
- Power Supply Count
- Boot Disk Volume Serial Number
- System BIOS
- System Serial Number
- Available Local Disk Space (GB)
- Available Memory (MB)

2.3 Hardware Component

- Name
- Manufacturer
- Type
- Size in Bytes
- Part Number
- Serial Number

PCI ID
Model
Revision
Location

2.4 Hardware CPU

Vendor Name
Frequency (MHz)
ECache (MB)
IMPL
Revision
Mask
Siblings

2.5 Host User Defined Products

Product Name
Product Version
Product Vendor
Product Type

2.6 I/O Devices

Name
Vendor Name
Frequency (MHz)
Bus
Revision

2.7 Installed Firmware

Note: This metric is only collected by the Oracle Enterprise Manager
Ops Center Harvester.

Description
Type
Version
Installation Date
Provider
Release Date

2.8 Installed OS Patches

ID
Vendor
Applied Packages

2.9 Network Information Configuration

Name

Flags
Maximum Transfer Unit
INET Address
Mask
Broadcast Address
MAC Address
Hostname Aliases
Description
Default Gateway
DHCP Enabled

2.10 Operating System

Name
Vendor Name
Base Version
Update Level
Distributor Version
Max Swap Space (MB)
Address Length (bits)
Platform ID
Maximum Process Virtual Memory (MB)
Timezone
Timezone Region
Timezone Delta

2.11 Operating System Components

Name
Type
Version
Installation Date
Description

2.12 Operating System Modules

Name
Size (Bytes)
Referring Modules

2.13 Operating System Properties

Name
Source
Value

2.14 Operating System Registered Software

ID
Name
Vendor Name
Version
Installation Date
Installed Location

Description
Vendor Specific Information

2.15 Operating System ULIMITs

CPU Time
File Blocks
Data Blocks
Stack
Coredump
Number of Files
Virtual Memory

JD Edwards Collections

The JD Edwards collections include the following:

3.1 JD Edwards Enterprise One

The configuration categories and their associated configuration items for the JD Edwards Enterprise One target type follow.

3.1.1 Data Sources

- Data Source Server Location
- Data Source Location
- Data Source Name
- Release
- Server
- Library Name
- OCM Data Source
- AS400 BLOB Data Source
- Decimal Shift
- Julian Date
- Use Table Owner
- Object Owner
- DLL Name
- Data Source Type
- Data Source Type Description
- Data Source Use
- Support Updates
- Platform Type
- Data Class
- Database Name
- Database Instance
- Port
- JDBNET
- Unicode
- LOB Support
- TNS_ODBC_JDBNET Data Source
- Future Use OCM3
- Future Use OCMC
- Future Use LL
- Future Use OMUI
- Future Use OMCC
- Future Use DSFC30

Future Use DSFC10
Future Use ENHV
Future Use DSFF1

3.1.2 Environments

Environment
Description
Release
Path Code
JITI
Change
Developer
WAN Configured
Detached Mode
Environment Code 3

3.1.3 Data Server (F9650)

Server
Server Description
Release
Platform
Platform Description
Location
Data Source Type
Data Source Type Description

3.1.4 Deployment Servers (F9650)

Server
Server Description
Release
Platform
Platform Description
Location
Server Share Path
Primary Deployment Server

3.1.5 Crystal Enterprise CMS

Server
Server Description
Release
Platform
Platform Description
Location
User

3.1.6 Enterprise Servers (F9650)

Server
Port Number
Server Description
Release

Platform
Platform Description
Location
Logical Machine Name
Data Source Type
Data Source Type Description
Server Map Data Source
Server Share Path
Deployment Server Name

3.1.7 Crystal Enterprise Web Server

Server
Port Number
Server Description
Release
Platform
Platform Description
Location

3.1.8 Web Servers (F9650)

Server
Port Number
Server Description
Release
Platform
Platform Description
Location
Primary JAS Server
Protocol
Server URL
Default Login
Installation Path
Deployment Server

3.1.9 Windows Terminal Server (F9650)

Server
Server Description
Release
Platform
Platform Description
Location

3.1.10 Path Codes

Path Code
Description
Machine Key
Server Share Path
Status Code
Merge Option
Release
Database Type

Data Source
UNC Flag

3.1.11 Updates

Update Name
Release
From Release
To Release
Update Description
Update Type
Update Type Description
Date

3.1.12 Data Indicators

Usage Data Indicator Type
Description
Release
Metric ID
Description
Value 1
Value 2

3.2 JD Edwards Enterprise One Collaborative Portal

The configuration categories and their associated configuration items for the JD Edwards Enterprise One Collaborative Portal target type follow.

3.2.1 Standalone Agent Managed Instances

Standalone Agent Install Location
Instance Name
Instance Target Type
Instance Target Type Description

3.2.2 Standalone Agent Managed Instances Attributes

Standalone Agent Install Location
Instance Name
Instance Target Type
Instance Attribute
Instance Attribute Description
Instance Attribute Value

3.2.3 Standalone Agent Managed Instance JAS INI

Standalone Agent Install Location
Instance Name
Instance Target Type
Section
Item
Value

3.2.4 Standalone Agent Managed Instances JDBJ INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

3.2.5 Standalone Agent Managed Instances JDE INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

3.3 JD Edwards Enterprise One Enterprise Server

The configuration categories and their associated configuration items for the JD Edwards Enterprise One Enterprise Server target type follow.

3.3.1 Standalone Agent Managed Instances

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Target Type Description

3.3.2 Standalone Agent Managed Instance Attributes

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Attribute
- Instance Attribute Description
- Instance Attribute Value

3.3.3 Standalone Agent Managed Instance JDE INI

- Instance Name
- Instance Target Type
- Section
- Item
- Value

3.4 JD Edwards Enterprise One Management Console

The configuration categories and their associated configuration items for the JD Edwards Enterprise One Management Console target type follow.

3.4.1 Management Console Agent

- Management Console Install Location

3.4.2 Management Console Agent Attributes

- Management Console Install Location
- Agent Attribute
- Agent Attribute Description
- Agent Attribute Value

3.4.3 Management Console JAS INI

- Management Console Install Location
- Section
- Item
- Value

3.4.4 Management Console JDBC INI

- Management Console Install Location
- Section
- Item
- Value

3.4.5 Management Console Managed Homes

- Management Console Install Location
- Managed Home Host
- Managed Home Install Location

3.4.6 Management Console Managed Instances

- Management Console Install Location
- Managed Home Host
- Managed Home Install Location
- Instance Name
- Instance Target Type
- Instance Target Type Description

3.5 JD Edwards Enterprise One PIM Synch Server

The configuration categories and their associated configuration items for the JD Edwards Enterprise One PIM Synch Server target type follow.

3.5.1 Standalone Agent Managed Instances

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Target Type Description

3.5.2 Standalone Agent Managed Instance Attributes

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Attribute
- Instance Attribute Description
- Instance Attribute Value

3.5.3 Standalone Agent Managed Instance JAS INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

3.5.4 Standalone Agent Managed Instance JDBJ INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

3.6 JD Edwards Enterprise One Standalone Agent

The configuration categories and their associated configuration items for the JD Edwards Enterprise One Standalone Agent target type follow.

3.6.1 Standalone Agent

- Standalone Agent Install Location

3.6.2 Standalone Agent Attributes

- Standalone Agent Install Location
- Agent Attribute
- Agent Attribute Description
- Agent Attribute Value

3.6.3 Standalone Agent Managed Instances

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Target Type Description

3.7 JD Edwards Enterprise One Transaction Server

The configuration categories and their associated configuration items for the JD Edwards Enterprise One Transaction Server target type follow.

3.7.1 Standalone Agent Managed Instances

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Target Type Description

3.7.2 Standalone Agent Managed Instance Attributes

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Attribute
- Instance Attribute Description
- Instance Attribute Value

3.7.3 Standalone Agent Managed Instance JAS INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

3.7.4 Standalone Agent Managed Instance JDBJ INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

3.8 JD Edwards Enterprise One Web Server

The configuration categories and their associated configuration items for the JD Edwards Enterprise One Web Server target type follow.

3.8.1 Standalone Agent Managed Instances

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Target Type Description

3.8.2 Standalone Agent Managed Instance Attributes

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Attribute
- Instance Attribute Description
- Instance Attribute Value

3.8.3 Standalone Agent Managed Instance JAS INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

3.8.4 Standalone Agent Managed Instance JDBJ INI

Standalone Agent Install Location
Instance Name
Instance Target Type
Section
Item
Value

Oracle Application Server Collections

The Oracle Application Server collections include the following:

Note: On all Windows platforms, the Configuration files metric for the specified targets in the Oracle Fusion Middleware Application Server Release 11 instance are only partially collected:

Web Cache Server
OC4J
Oracle HTTP Server

4.1 Application Deployment

The configuration categories and their associated configuration items for the Application Deployment target type follow.

4.1.1 Application Configuration

Path
Deployment Order
Type

4.2 FTP Application

The configuration categories and their associated configuration items for the FTP Application target type follow.

4.2.1 General

Channel Security
Data Connection Port
DMS Instrumentation
FTP Server Enabled
Max DC Port Count
Port
Session Timeout
Upload BufferSize
Default DataPort
Listening Point
Default Command Characterset
Internal IP

4.3 IAS Configuration

The configuration categories and their associated configuration items for the IAS Configuration target type follow.

4.3.1 Console

Protocol for Agent
Host for Agent
Port for Agent
Path for Agent
Protocol for Application Server Control
Host for Application Server Control
Port for Application Server Control

4.3.2 DCM Auto Archive Check

Column	Description	Collected From
Count	Whether auto archive is enabled for DCM (enabled if the value is not zero)	Output of the <code>dcmcctl set</code> command, Auto Archive Count parameter

4.3.3 Debug Log Level Check

Column	Description	Collected From
Component Codes	OPMN components to configure logging for	"Comp" attribute of the "debug" tag in <code>opmn.xml</code>
Rotation Size	Size at which to rotate the log	"Rotation-size" attribute of the "debug" tag in <code>opmn.xml</code>

4.3.4 Log Level Check

Column	Description	Collected From
Element	OPMN component ("notification-server" or "process-manager")	Name of the tag in <code>opmn.xml</code>
Level	Logging level for the component	"Level" attribute of the tag
Rotation Size	Size at which to rotate the log	"Rotation-size" attribute of the tag

4.4 JServ

The configuration categories and their associated configuration items for the JServ target type follow.

4.4.1 Configuration Files

Name
Name
Size (Bytes)
Modification Time

4.4.2 JServ Zones

Zone Name

4.5 OC4J

The configuration categories and their associated configuration items for the OC4J target type follow.

4.5.1 Applications

Application
Parent Application

4.5.2 Configuration Files

Display File Path Name
File Path Name
File Size (Bytes)
Modification Time

4.5.3 Connection Pools

Name
Application
Class
JDBC URL

4.5.4 Data Sources

Name
Application
JNDI Location
Class
JDBC Driver
JDBC URL

4.5.5 Deployed Applications

Application Name

4.5.6 Global Web Module Settings

JSP Mode

4.5.7 Log Growth Check

Column	Description	Collected From
Java Options	Command-line Java startup options	"Java-options" module data from the "start-parameters" category of an OC4J component in opmn.xml
OC4J Options	Command-line OC4J startup options	"OC4J-options" module data from the "start-parameters" category of an OC4J component in opmn.xml

4.5.8 Managed Data Sources

- Name
- Application
- JNDI Location
- Connection Pool

4.5.9 Modules

- Application
- Module
- Module Type

4.5.10 Native Data Sources

- Name
- Application
- JNDI Location
- Class
- JDBC URL

4.5.11 Port Ranges

- Service
- Port Range

4.5.12 Resource Usage

- Starting Heap Size (MB)
- Maximum Heap Size (MB)
- Number of JVMs

4.5.13 Web Module Settings

- Application
- Module
- JSP Mode
- Session Timeout (seconds)
- Can Be Distributed

4.5.14 Web Module URLs

- Module
- Application
- URL Mapping
- Load on Startup

4.6 Oracle Application Server

The configuration categories and their associated configuration items for the Oracle Application Server target type follow.

4.6.1 Configuration Files

- Name
- Name

Size (Bytes)
Modification Time

4.6.2 Console

Protocol for Agent
Host for Agent
Port for Agent
Path for Agent
Protocol for Application Server Control
Host for Application Server Control
Port for Application Server Control

4.6.3 DCM

DCM Repository Type

4.6.4 Deployed Applications

OC4J Instance
Name

4.6.5 General

Install Type
Infrastructure Database
Version

4.6.6 Components

Display Name
Type
Name

4.6.7 OPMN

Request Port
Remote Port
Local Port
Use SSL
Log Level for ONS
Log Level for Process Manager

4.7 Oracle HTTP Server

The configuration categories and their associated configuration items for the Oracle HTTP Server target type follow.

4.7.1 Configuration Files

File Path
File Path Name
File Size (Bytes)
Modification Time

4.7.2 General

Document Root
Default Port
Server Name

4.7.3 File Permission Check

Column	Description
File Path	File Path
File Mode	UNIX file permissions
User ID	UNIX file owner
Group ID	UNIX file group

4.7.4 Identity Check

Column	Description	Collected From
Virtual Host	Virtual host name	Argument to a VirtualHost directive in httpd.conf
User ID	UNIX user that handles requests for this virtual host	Value of a User directive in httpd.conf
Group ID	UNIX group that handles requests for this virtual host	Value of a Group directive in httpd.conf

4.7.5 Listen Addresses

Listening IP Address
Listening Port
Listening Protocol

4.7.6 Log Growth Check

Column	Description	Collected From
Virtual Host	Virtual host name	Argument to a VirtualHost directive in httpd.conf
Log Name	Log type, either CustomLog, ErrorLog, or TransferLog	Name of the directive in httpd.conf
Value	Value of the directive (log path and information about how to append to the log)	Not Applicable

4.7.7 Log Level Check

Column	Description	Collected From
Virtual Host	Virtual host name	Argument to a VirtualHost directive in httpd.conf

Column	Description	Collected From
Directive	Either LogLevel, SSLLogLevel, RewriteLogLevel, ScriptLog, or PlsqlLogEnable	Not Applicable
Value	Value of the directive (the logging level)	Not Applicable

4.7.8 Performance Related

Maximum Requests Processed Simultaneously
 Maximum Requests Handled by Each Child Process
 Maximum Spare Processes
 Minimum Spare Processes
 Processes to Create at Startup
 Allow Multiple Requests per Connection
 Maximum Requests per Connection
 Connection Timeout (seconds)
 SSL Session Timeout (seconds)
 DNS Hostname in Access Log
 Error Logging Level
 mod_oc4j Load Balancing Policy
 Size of OC4J Connection Cache

4.7.9 SSL Ciphers Suite Settings

SSL Virtual Host
 Cipher Suite

4.7.10 Virtual Hosts

IP Address
 Port
 Host
 Type

4.8 Oracle iAS Farm

The configuration categories and their associated configuration items for the Oracle iAS Farm target type follow.

4.8.1 Farm Configuration

Farm Name
 Version

4.9 Oracle Internet Directory

The configuration categories and their associated configuration items for the Oracle Internet Directory target type follow.

4.9.1 Oracle Internet Directory Configuration

Oracle Internet Directory Connect Descriptor
 Oracle Internet Directory Host
 Oracle Internet Directory Port

Oracle Internet Directory Secure Port

4.10 Web Cache Server

The configuration categories and their associated configuration items for the Web Cache Server target type follow.

4.10.1 Cluster Information

Cluster Name

4.10.2 Cluster Members

Host Name
Oracle Home
Capacity

4.10.3 Configuration Files

Display Name
Name
Size (Bytes)
Modification Time

4.10.4 File Permission Check

Column	Description
File Path	File Path
File Mode	UNIX file permissions
User ID	UNIX file owner
Group ID	UNIX file group

4.10.5 Identity Check

Column	Description	Collected From
User ID	UNIX user that Web Cache runs as	USERID attribute of the IDENTITY tag in webcache.xml
Group ID	UNIX group that Web Cache runs as	GROUPID attribute of the IDENTITY tag in webcache.xml

4.10.6 Listening Ports

IP Address
Port
Protocol

4.10.7 Log Growth Check

Column	Description	Collected From
Log Name	Event log rollover frequency	FREQUENCY attribute of the ROLLOVER tag (child of the EVENTLOG tag) in webcache.xml
Value	Access log rollover frequency	ROLLOVERNAME attribute of the ACCESSLOG tag in webcache.xml

4.10.8 Log Level Check

Column	Description	Collected From
Verbosity	Event log verbosity	LEVEL attribute of the VERBOSITY tag in webcache.xml
IO Logger	Whether the IO logger is enabled	ENABLED attribute of the IOLOGGER tag in webcache.xml

4.10.9 Operations Ports

Type
IP Address
Port
Protocol

4.10.10 Origin Servers

Name
Port
Protocol
Capacity

4.10.11 Performance Related

Cache Memory Limit (MB)
Maximum Incoming Connections
Keep Alive Timeout (seconds)
Origin Server Timeout (minutes)

4.10.12 Site Aliases

Site Name
Site Port
Site URL
Alias Name
Alias Port
Alias URL

4.10.13 Host Mappings

Site Name
Site Port
Site URL
Origin Server Name

Origin Server Port

Oracle Beehive Site Configuration Collections

The Oracle Beehive Site Configuration collections include the following:

5.1 Application Server

- Primary Host Name
- Application Server Instance
- Oracle Home
- Timezone
- OPMN Local Port
- OPMN Remote Port
- OPMN Request Port

5.2 CalDAV Application

The configuration categories and their associated configuration items for the CalDAV Application target type follow.

5.2.1 General

- Collection Browsing Enabled
- Default Future Time Period In Day
- Default Past Time Period In Day

5.3 Calendar Applications

The configuration categories and their associated configuration items for the Calendar Applications target type follow.

5.3.1 Calendar Application HTTP Server Configuration

- Category Name
- Property Name
- Property Value

5.4 Calendar Server

The configuration categories and their associated configuration items for the Calendar Server target type follow.

5.4.1 Calendar Server Basic Configuration

- Calendar
- Server Host
- Port

5.4.2 Calendar Configuration

- Calendar Log Level
- Calendar Maximum LDAP Connection

5.4.3 Calendar Server Configuration

- Category Name
- Property Name
- Property Value

5.5 Conference Application

The configuration categories and their associated configuration items for the Conference Application target type follow.

5.5.1 General

- Default Dialout Call Timeout
- Default Participant Codec
- Default SIP Participant Codec
- Default Voice Participant Mode
- OWC Host Wait Session Timeout
- OWC Log Flush Period
- OWC Media Host Service Bus Address Prefix
- OWC Media Host Service Load Balance Bus Address Suffix
- OWC Roster Service Bus Address Prefix
- OWC Roster Service Load Balance Bus Address Suffix
- OWC Use Remote Media Sessions
- SIPP STN Gateway IP Address
- SIPP STN Gateway Port

5.6 Database

- Type
- Connect Descriptor
- Schema Name

5.7 HTTP Server

- Primary Host Name
- Application Server Instance
- HTTP Server

5.8 LDAP

- Type
- HostName

Port
SSL Port

5.9 OC4J

Primary Host Name
Application Server Instance
OC4J Name

5.10 Virtual Server

BTI Client Port
BTI Secure Client Port
FTP Port
HTTP Port
HTTP SSL Enabled
HTTP SSL Port
IMAP Port
IMAP SSL Enabled
IMAP SSL Port
Server Name
SMTP Authentication Required
SMTP Port
SMTP SSL Enabled
SMTP SSL Port
XMPP Port
XMPP SSL Enabled
XMPP SSL Port

5.11 VoiceMessage Application Configuration

The configuration categories and their associated configuration items for the VoiceMessage Application Configuration target type follow.

5.11.1 General

VoiceMessage Property

5.11.2 Facility Properties

Facility CollabId

Oracle BPEL Process Manager Collections

The Oracle Business Process Execution Language (BPEL) Process Manager collections include the following:

6.1 BPEL Domain Configuration Properties

- Audit Threshold
- Datasource JNDI
- Domain Name
- DP Policy
- DSP Maximum Request Depth
- DSP Maximum Threads
- DSP Minimum Threads
- Invocation thread allocation factor
- Transaction JNDI

6.2 BPEL General Configuration Properties

- SOAP CALLBK URL
- SOAP URL

6.3 BPEL Cluster Configuration Properties

- Cluster Enabled
- Cluster Name
- Multicast Address
- Multicast Port

6.4 BPEL Dehydration Store Configuration Properties

- Datasource JNDI
- Connection Pool Name
- Host
- Port
- Service Name

6.5 Instance Information

- Version

Oracle Business Intelligence (BI) Collections

The Oracle Business Intelligence (BI) collections include the following:

7.1 Oracle Business Intelligence (BI) Analytics Server

The configuration categories and their associated configuration items for the Oracle BI Analytics Server target type follow.

7.1.1 BI Analytics Server Configuration Parameters

- Product Version
- Cache Enable
- Cache Replace Algorithm
- Maximum Rows Per Cache Entry
- Maximum Cache Entry Size
- Maximum Cache Entries
- Maximum Global Cache Entries
- Cache Poll Seconds
- Locale
- Sort Memory Size
- Sort Buffer Increment Size
- Sort Memory Size
- SSL
- RPC Service or Port Number
- Maximum Session Limit
- Server Thread Range
- DB Gateway Thread Stack Size
- Maximum Expanded Sub Query Predicates
- Maximum Query Plan Cache Entries
- Maximum Drill Down Info Cache Entries
- Maximum Drill Down Query Cache Entries
- Enable DB Hints
- Cluster Participant
- Disconnected
- ODBC350
- OCI7
- OCI8e
- OCI8i
- OCI10g
- DB2CLI
- DB2CLI35
- NQXML

XMLA
Strong Date Time Check

7.2 Oracle Business Intelligence (BI) Cluster Controller

The configuration categories and their associated configuration items for the Oracle BI Cluster Controller target type follow.

7.2.1 BI Cluster Controller Configuration Parameters

Product Version
Enable Controller
Primary Controller
Servers
Server Poll Seconds
Controller Poll Seconds
Client Server Port
Client Controller Port
Monitor Controller Port
Monitor Server Port
Schedulers
SSL
SSL Certificate File
SSL Private-Key File
SSL PK Pass Phrase File
SSL PK Pass Phrase Program
SSL Verify Peer
SSL CA Certificate Directory
SSL CA Certificate File
SSL Cert Verification Depth

7.2.2 BI DAC Server Properties

Product Version
Type
Connect String
Host
Port
Database User Name
JDBC Driver
JDBC URL
EMail Host
EMail Protocol
EMail User
EMail Address

7.2.3 BI DAC ETL Summary

Step Name
SRCDB Name
Trgt DB Name
Step Type Name
Phase Name
Exec Name
RS Status

Server Name
RS Status Desc
RS Start TS
RS End TS
RS Success Rows
RS Failed Rows
RS Error Code

7.3 Oracle Business Intelligence (BI) DAC

The configuration categories and their associated configuration items for the Oracle BI DAC target type follow.

7.3.1 BI DAC Server Properties

Product Version
Type
Connect String
Host
Port
Database User Name
JDBC Driver
JDBC URL
EMail Host
EMail Protocol
EMail User
EMail Address

7.3.2 BI DAC ETL Summary

Step Name
SRCDB Name
Trgt DB Name
Step Type Name
Phase Name
Exec Name
RS Status
Server Name
RS Status Desc
RS Start TS
RS End TS
RS Success Rows
RS Failed Rows
RS Error Code

7.4 Oracle Business Intelligence (BI) Instance

Version

7.5 Oracle Business Intelligence (BI) Presentation Server

The configuration categories and their associated configuration items for the Oracle BI Presentation Server target type follow.

7.5.1 BI Presentation Server Configuration Parameters

- Product Version
- Configuration Directory
- Connection Expire Minutes
- Connection Maximum Concurrent Establish
- Corba Lib Directory
- CSV Charset
- Data Directory
- Debug Startup
- Default Message Directory
- Disconnected
- Disconnected Directory
- Drillability Status
- DSN
- Enable 508
- Force Refresh
- Java Home
- Maintenance Mode
- On Demand Answers
- Persistent Storage State
- System Subject Area
- Use Replication
- Allowed Languages
- Allowed Locale

7.5.2 BI Presentation Server Alerts Configurations

- Content Delivery Mode
- Default Delivery Disposition
- Default Delivery Format
- Embed Resources Inline
- Enabled
- Force 7bit ASCII Attachment Names
- Ignore Webcat Delivery Profiles
- MHTML Mime Type
- Schedule Server
- Session Cleanup Frequency Seconds
- Session Timeout Seconds
- UpperCase Recipient Names

7.5.3 BI Presentation Server Cache Configurations

- Cache Refresh Optimize

7.5.4 BI Presentation Server Charts Configurations

- Default Image Type
- Maximum Completion Time (Seconds)
- Maximum Processing Threads

7.5.5 BI Presentation Server Client Configurations

- Auto Flush Enabled
- SSO Server Variable
- SSO Strip Windows Domain

7.5.6 BI Presentation Server Display Configurations

- Allow Remember Password
- Collapsible Sections Default
- Dashboard Inline Load
- Disable Pivot Table Auto Preview
- ShowPage Tabs Always
- Show Section Headings Default
- Maximum DropDown Values
- Reload Inline

7.5.7 BI Presentation Server Marketing Configurations

- Marketing FunctionShip Fixed Random
- Marketing FunctionShip Percent Random
- Marketing Use BOM
- Marketing Wrap Column Headers
- Marketing Cache Use Temp Table

7.5.8 BI Presentation Server Other Configurations

- Admin URL
- Server URL
- Volume
- Web URL
- Catalog Path
- Completely Disable
- Preload DBG Help
- Listener

7.5.9 BI Presentation Server Report Cache Configurations

- Disk Resave Minutes
- Memory Buckets
- Memory Cleanup Interval Minutes
- Verify Reloaded Entry Key

7.5.10 BI Presentation Server State Pool Configurations

- Memory Buckets
- Memory Minimum Bucket Size
- Verify Reloaded Entry Key

7.5.11 BI Presentation Server Thread Pool Configurations

- Idle Thread Timeout Secs
- Worker Thread Size Kb
- Maximum Threads
- Worker Thread Size Kb

7.5.12 BI Presentation Server XML Cache Defaults

- Memory Buckets
- Memory Minimum Bucket Size
- Verify Reloaded Entry Key

7.6 Oracle Business Intelligence (BI) Scheduler Server

The configuration categories and their associated configuration items for the Oracle BI Scheduler Server target type follow.

7.6.1 BI Scheduler

- Product Version
- Admin Name
- Bulk Fetch Buffer Size
- CLI Type
- Cluster Port
- DSN
- Default Script Path
- Log All SQL Statements
- Maximum Exec Threads
- Minimum Exec Threads
- Number of DB Connections
- Part Of Cluster
- Pause On Startup
- Pool Timeout
- Pool Username
- Port String
- Purge Inst Days
- Purge Interval Minutes
- Scheduler Script Path
- Target Type
- Temp Path
- Table Error Messages
- Table Instances
- Table Jobs
- Table Parameters
- Java Host Server
- Certificate PrivateKey FileName
- Certificate FileName
- Certificate Verify Depth
- Passphrase FileName
- Use SSL
- Verify Peer
- Script RPC Port
- Auth PWD
- Auth User
- Server
- Service
- System

7.6.2 BI Schedule IBOTS

- Debug
- Keep Error Log Files
- Log Purge Days
- Log Directory
- Maximum Delivery SleepSecs
- Maximum Global SleepSecs
- Maximum Request SleepSecs
- MaxRows Times Columns

Minimum Delivery Sleep Secs
Minimum Global Sleep Secs
Minimum Request Sleep Secs
Number Of Delivery Retries
Number Of Global Retries
Number Of Request Retries
Web Server

7.6.3 BI Scheduler Mail

From
Max Recipients
Password
SMTP Port
SMTP Server
Sender
SMTP CA Certificate Directory
SMTP CA Certificate Verification Depth
Try
Use Bcc
Use SSL

7.6.4 Instance Information

Version

7.7 Oracle Business Intelligence (BI) Web Plugin

The configuration categories and their associated configuration items for the Oracle BI Web Plugin target type follow.

7.7.1 BI Web Plugin

Product Version
Data Directory
Temporary Directory
Address
Port
Certificate Validation Depth
Credential Alias
SSL Version
SSL Enabled Dir
Key Store Path

Oracle Cloud Control Collections

The Oracle Cloud Control collections include the following:

8.1 Oracle Agent Deployment Configuration

The configuration categories and their associated configuration items for the Oracle Agent Deployment Configuration target type follow.

8.1.1 MGMT_ECM_EMD_JAVA_PARAMS

- Java Home
- Class path and classpath.lst
- Host class path
- Java options
- Java definitions
- Java Version - Collects the Agent Java Version

Oracle Coherence Collections

The Oracle Coherence collections include the following:

9.1 Oracle Coherence

ECM Associations
Target Version

Oracle Collaboration Suite Collections

The Collaboration Suite collections include the following:

10.1 IM Application

The configuration categories and their associated configuration items for the IM Application target type follow.

10.1.1 General

- IM Buffer Stage Size
- IM Purging Period Timer
- IM EndPointDeath Detection Time
- Pending Messages Limit

10.2 PushMail Application

The configuration categories and their associated configuration items for the PushMail Application target type follow.

10.2.1 General

- Days Message Available
- Heartbeat Interval
- IMAP Connection Live Time
- Max Concurrent Users
- Max Inbox Messages
- Max Message Size

10.3 Real-Time Collaboration

The configuration categories and their associated configuration items for the Real-Time Collaboration target type follow.

10.3.1 Real-Time Collaboration Command-Line Control Configuration

- Property Name
- Property Value

10.4 WebDAV Application

The configuration categories and their associated configuration items for the WebDAV Application target type follow.

10.4.1 General

- Authentication Scheme
- Browser Session Timeout
- DAVClient Session Timeout
- DepthLimit
- Display Last ModifiedBy
- Display Last ModifiedOn
- Display Lock Status
- Display Versioning Status
- DMS Instrumentation
- Download BufferSize
- MinimumLock Timeout
- Upload BufferSize
- User Preference Refresh Time
- WebDAV Server Enabled

10.4.2 Default Welcome Docs

Default Welcome Docs

10.5 Workspaces Application

The configuration categories and their associated configuration items for the Workspaces Application target type follow.

10.5.1 General

- Db Download BufferSize
- Db Upload BufferSize

10.6 XMPP Application

The configuration categories and their associated configuration items for the XMPP Application target type follow.

10.6.1 General

- Language
- XMPP Port
- XMPP SSL Port
- XMPP Timer KeepAliveTime

10.6.2 Domain Names

Domain Names

10.6.3 Search Fields

Search Fields

10.6.4 Supported Agents

Supported Agents

Oracle Configuration Manager Collections

The Oracle Configuration Manager collections include the following:

11.1 Oracle Configuration Manager Package Versions

- Package Name
- Package Version
- Build Date
- Package Platform
- Package Architecture

11.2 Oracle Configuration Manager Parameter Values

- Parameter Name
- Parameter Category
- Parameter Value
- File Name

Oracle Data Integrator Collections

The Oracle Data Integrator collections include the following:

12.1 Oracle Data Integrator Agent

J2EE Application Config
Target Version

12.2 Oracle Data Integrator Console

J2EE Application Config
Target Version

12.3 Oracle Data Integrator SDK Web

J2EE Application Config
Target Version

Oracle Database and Database-Related Collections

The Oracle Database and Database-Related collections include the following:

Note: For Oracle Database installations prior to 9.0, the Oracle inventory data cannot be collected. This is because the collection mechanism relies on the newer XML format for the product inventory which is available for 9.0 and later versions.

13.1 Automatic Storage Management

The configuration categories and their associated configuration items for the Automatic Storage Management target type follow.

13.1.1 ASM Instance Properties

Host
Port
SID

13.2 Database Instance

The configuration categories and their associated configuration items for the Database Instance target type follow.

13.2.1 ASM Disk

This metric captures ASM Disks details which has status other than MEMBER.

This metric is applicable to the following versions of the database: 10.1.*, 10.2.*, 11.1.*, 11.2.*, and higher.

Name	Description	Data Type	Sample Value
Disk Number	Disk Number	NUMBER	1
Group Number	Group Number	NUMBER	1
Header Status	Header Status	VARCHAR2	UNKNOWN
Instance ID	Instance ID	NUMBER	1
Path	Path	VARCHAR2	ORCL:VOL3

13.2.2 Control Files

This metric is applicable to all supported versions of the database.

- Change Number
- Creation Date
- File Name
- Modification Date
- OS Storage
- Sequence Number
- Status

13.2.3 CPU Usage Statistics

This metric is applicable to the following supported versions of the database: 10.2.*, 11.1.*, 11.2.*, and higher.

- CPU core count of the database
- CPU count of the database
- CPU socket count of the database
- Database ID
- Time at which the CPU usage changed
- Version

13.2.4 Data Files

This metric is applicable to all supported versions of the database.

- Autoextensible
- File Name
- Increment
- Initial Size
- Maximum File Size
- OS Storage
- Size
- Status

13.2.5 Database Autotask Client

This metric is applicable to the following versions of the database: 11.1.*, 11.2.*, and higher.

- Client Name
- Status

13.2.6 Database Components

This metric is applicable to all supported versions of the database except for version 8.1.7.

- Component ID
- Component Name
- Namespace
- Schema
- Status
- Version

13.2.7 Database Configuration Version

This metric is applicable to all supported versions of the database.

Installed Version
Collection Version

13.2.8 Database License

This metric is applicable to all supported versions of the database.

Session Current
Session Maximum
Sessions Highwater
Sessions Warning
Users Maximum

13.2.9 Database Options

This metric is applicable to all supported versions of the database.

Name
Selected

13.2.10 Database Scheduler Jobs

This metric is applicable to the following versions of the database: 10.1.* and 10.2.*.

This metric captures GATHER_STATS_JOB details from DBA_SCHEDULER_JOBS.

Name	Description	Data Type	Sample Value
Job Name	Job Name	VARCHAR2	GATHER_STATS_JOB
Owner	Owner of the object	VARCHAR2	SYS
Schedule Name	Scheduler Name	VARCHAR2	MAINTENANCE_WINDOW_GROUP
State	State	VARCHAR2	SCHEDULED

13.2.11 Database Users

This metric is applicable to all supported versions of the database.

Created
Default Tablespace
Default Temporary Tablespace
Expiry Date
Profile
User ID
User Name

13.2.12 DB Invalid Objects

This metric is applicable to all supported versions of the database.

This metric captures owner-wise count of the invalid objects for the database.

Name	Description	Data Type	Sample Value
Invalid Objects Count	Count of invalid objects	NUMBER	2
Owner	Owner of the object	VARCHAR2	SYSMAN

13.2.13 Feature Usage

This metric is applicable to all supported versions of the database.

Aux Count
Currently Used
Database ID
Detected Usages
Ever Used
Feature Information
First Usage Date
Last Sample Date
Last Sample Period
Last Usage Date
Name
Total Samples
Version

13.2.14 High Availability - General Information

This metric is applicable to all supported versions of the database.

Database Role
Dbid
Flashback On
Force Logging
Log Mode
Supplemental Logging

13.2.15 High Availability - RMAN Configuration

This metric is applicable to all supported versions of the database except for version 8.1.7.

Name
Value

13.2.16 High Water Mark Statistics

This metric is applicable to the following versions of the database: 10.1.*, 10.2.*, 11.1.*, 11.2.*, and higher.

Database ID
Highwater
Last Value
Name
Version

13.2.17 Initialization Parameters

This metric is applicable to all supported versions of the database.

Default
Name
Value

13.2.18 Instance Information

This metric is applicable to all supported versions of the database.

Archive Log Mode
Creation Date
Database Version
Database Character Set
Database Name
Database Vault Status Code
Default Temporary Tablespace
Edition
Global Name
Host
Instance Name
Instance Startup Time
Is 64bit
National Character Set
Read Only Mode
Release
Release Status
Restricted Mode
Supplemental Logging for LogMiner
Version

13.2.19 Redo Logs

This metric is applicable to all supported versions of the database.

Archived
File Name
First Change SCN
Group Number
Log Size
Members
OS Storage
Sequence Number
Status
Thread Number
Type

13.2.20 Rollback Segments

This metric is applicable to all supported versions of the database.

Average Active
Average Shrink
Extents
High Water Mark Size
Initial Size
Maximum Extents
Minimum Extents
Name

- Next Size
- Optimal Size
- Percent Increase
- Shrinks
- Size
- Status
- Tablespace Name
- Wraps

13.2.21 STATS Pack Configuration

This metric is applicable to all supported versions of the database.

- Is Installed
- Snapshot Frequency

13.2.22 System Global Area

This metric is applicable to all supported versions of the database.

- Name
- Size

13.2.23 Tablespaces

This metric is applicable to all supported versions of the database.

- Allocation Type
- Big File
- Block Size
- Contents
- Extent Management
- Increment
- Initial Extent
- Logging
- Maximum Extents
- Minimum Extent Size
- Minimum Extents
- Next Extent
- Segment Space Management
- Size
- Status
- Tablespace Name
- Used Size

13.3 Oracle Cluster

The configuration categories and their associated configuration items for the Oracle Cluster target type follow.

13.3.1 Cluster Manager Configuration

- Property
- Value
- Config File

13.3.2 High Availability Cluster Interconnect

Interface Name
Node Name
Subnet
IP Address
Is Public

13.3.3 Server Configuration

Property
Value
Config File

13.4 Oracle Listener

The configuration categories and their associated configuration items for the Oracle Listener target type follow.

13.4.1 Listener Status

TNS Address
Alias
Version
Start Date
Trace Level
Security
SNMP Status
SID List

13.5 Real Application Cluster Database

The configuration categories and their associated configuration items for the Real Application Cluster Database target type follow.

13.5.1 ASM Disk

This metric captures ASM Disks details which has status other than MEMBER.

This metric is applicable to the following versions of the database: 10.1.*, 10.2.*, 11.1.*, 11.2.*, and higher.

Name	Description	Data Type	Sample Value
Instance ID	Instance ID	NUMBER	1
Group Number	Group Number	NUMBER	1
Disk Number	Disk Number	NUMBER	1
Header Status	Header Status	VARCHAR2	UNKNOWN
Path	Path	VARCHAR2	ORCL:VOL3

13.5.2 Control Files

This metric is applicable to all supported versions of the database.

Creation Date

File Name
Status

13.5.3 CPU Usage

This metric is applicable to the following supported versions of the database: 10.2.*, 11.1.*, 11.2.*, and higher.

CPU core count of the database
CPU count of the database
CPU socket count of the database
Database ID
Time at which the CPU usage changed
Version

13.5.4 Data Files

This metric is applicable to all supported versions of the database.

Autoextensible
Database Name
File Name
Increment
Maximum File Size
OS Storage
Status

13.5.5 Database Autotask Client

This metric is applicable to the following versions of the database: 11.1.*, 11.2.*, and higher.

Client Name
Status

13.5.6 Database Components

This metric is applicable to all supported versions of the database except for version 8.1.7.

Component ID
Component Name
Namespace
Schema
Status
Version

13.5.7 Database Configuration Version

This metric is applicable to all supported versions of the database.

Collection Version
Installed Version

13.5.8 Database License

This metric is applicable to all supported versions of the database.

Session Maximum
Sessions Highwater
Sessions Warning
Users Maximum

13.5.9 Database Options

This metric is applicable to all supported versions of the database.

Name
Selected

13.5.10 Database Scheduler Jobs

This metric is applicable to the following versions of the database: 10.1.* and 10.2.*.

This metric captures GATHER_STATS_JOB details from DBA_SCHEDULER_JOBS.

Name	Description	Data Type	Sample Value
Owner	Owner of the object	VARCHAR2	SYS
Job Name	Job Name	VARCHAR2	GATHER_STATS_JOB
State	State	VARCHAR2	SCHEDULED
Schedule Name	Scheduler Name	VARCHAR2	MAINTENANCE_WINDOW_GROUP

13.5.11 Database Users

This metric is applicable to all supported versions of the database.

Created
Default Tablespace
Expiry Date
Profile
Default Temporary Tablespace
User ID
User Name

13.5.12 DB Invalid Objects

This metric is applicable to all supported versions of the database.

This metric captures owner-wise count of the invalid objects for the database.

Name	Description	Data Type	Sample Value
Owner	Owner of the object	VARCHAR2	SYSMAN
Invalid Objects Count	Count of invalid objects	NUMBER	2

13.5.13 Feature Usage

This metric is applicable to all supported versions of the database.

Aux Count
Currently Used
Database ID
Detected Usages
Ever Used

- Feature Information
- First Usage Date
- Last Sample Date
- Last Sample Period
- Last Usage Date
- Name
- Total Samples
- Version

13.5.14 High Availability - General Information

This metric is applicable to all supported versions of the database.

- Database Role
- Dbid
- Flashback On
- Force Logging
- Log Mode

13.5.15 High Availability - RMAN Configuration

This metric is applicable to all supported versions of the database except for version 8.1.7.

- Name
- Value

13.5.16 High-Water Mark Statistics

This metric is applicable to the following versions of the database: 10.1.*, 10.2.*, 11.1.*, 11.2.*, and higher.

- Database ID
- Highwater
- Last Value
- Name
- Version

13.5.17 Instance Information

This metric is applicable to all supported versions of the database.

- Archive Log Mode
- Creation Date
- Database Character Set
- Database Name
- Database Version
- Default Temporary Tablespace
- Edition
- Host
- Is 64bit
- Global Name
- Instance Name
- Instance Startup Time
- National Character Set
- Read Only Mode
- Release

Release Status
Restricted Mode
Supplemental Logging
Version

13.5.18 Redo Logs

This metric is applicable to all supported versions of the database.

Archived
File Name
First Change SCN
Group Num
Log Size
Members
OS Storage
Sequence Num
Status
Thread Number
Type

13.5.19 Rollback Segments

This metric is applicable to all supported versions of the database.

Average Active
Average Shrink
Extents
High Water Mark Size
Initial Size
Next Size
Maximum Extents
Minimum Extents
Name
Optimal Size
Percent Increase
Shrinks
Size
Status
Tablespace Name
Wraps

13.5.20 STATS Pack Configuration

This metric is applicable to all supported versions of the database.

Is Installed
Snapshot Frequency

13.5.21 Tablespaces

This metric is applicable to all supported versions of the database.

Allocation Type
Big File
Block Size
Contents

Extent Management
Increment
Initial Extent
Logging
Maximum Extents
Minimum Extent Size
Minimum Extents
Next Extent
Segment Space Management
Size
Status
Tablespace Name
Tablespace Used Size

13.5.22 Voting Disk

This metric is applicable to the following supported versions of the database: 10.2.*, 11.1.*, 11.2.*, and higher.

This metric captures all the clusterware voting disk locations for Real Application Cluster Database.

Name	Description	Data Type	Sample Value
Voting Disk Location	Voting Disk Location on Real Application Cluster Database	VARCHAR2	/oradbshare/storage/vdisk

Oracle E-Business Suite Collections

The Oracle E-Business Suite collections include the following:

14.1 Contract Management Server Database

The configuration categories and their associated configuration items for the Contract Management Server Database target type follow.

14.1.1 CM Admin and Group Database Information

- Database Name
- JNDI Name
- User Name
- Connect String
- Project Count
- User count

14.1.2 CM Database Information

- DB Service Type
- Schedule DB Type
- Boot strap Connect String
- Database version and OS

14.1.3 CM Admin and group Database upgrade Version history

- Database Name
- From Version
- To Version
- Date Converted
- Remarks
- Conversion Status

14.2 Contract Management Server

The configuration categories and their associated configuration items for the Contract Management Server target type follow.

14.2.1 Contract Manager Configuration Parameters

- Web Version
- Ear Size

EAR Date
Build ID
Word Version
Word Operational on Server
MS Word version on server
Word Scratch Location
App Server Host Name
App Server Type
Domain Home
Protocol
Web Port
SMTP Server
JDK Path
JVM Max Heap Size
Session Time out
XML Session Timeout
Repository Type
Repository URL Host
Authentication Mode
LDAP Host
LDAP Port
LDAP User
Is Standalone
Print Debug Level
Report Images Location
Contract Manager Home

14.3 DeviceManagement Application

The configuration categories and their associated configuration items for the DeviceManagement Application target type follow.

14.3.1 Blocked Devices

Device ID
Description

14.3.2 General

Uncertified Device Allowed

14.4 Oracle Concurrent Manager

The configuration categories and their associated configuration items for the Oracle Concurrent Manager target type follow.

14.4.1 Concurrent Processing Package Versions

Package
Type
Version

14.4.2 Concurrent Processing Profile Options

Profile Option Name

Profile Option ID
Profile Option Value
Level ID
Application Short Name
User Profile Option Name
SQL Validation
Description

14.4.3 ICM Settings

Name
Value

14.4.4 Concurrent Managers (Service Instances)

Application ID
Concurrent Queue Name
Service
Application Short Name
Target Node
Target
Primary
Secondary
Enabled
Cache Size
Resource Consumer Group
Program Library
Diagnostic Level
Sleep Seconds

14.4.5 Specialization Rules

Manager
Action
Type
Object

14.4.6 Summary Configuration

Setting
Status

14.4.7 Workshifts for Concurrent Managers

User Concurrent Queue Name
Time Period Application ID
Concurrent Time Period Name
Time Period App Short Name
Description
Minimum Processes
Maximum Processes
Sleep Seconds
Service Parameters

14.5 Oracle E-Business Suite

The configuration categories and their associated configuration items for the Oracle E-Business Suite target type follow.

14.5.1 Number of Active Users

Number of Active Users

14.5.2 Applied Patches (January to December) - Collected by Month

Applied Patch ID
Patch Number
Patch Type
Applied Date

14.5.3 Applications Customer Forms

Menu Name
Sequence
Submenu
Function Name
Type
Prompt
Description
Application Short Name
Form Name

14.5.4 Applications System Summary

Applications System Name
Release Name
Multi-Organization Flag
Multi-Lingual Flag
Multi-Currency Flag

14.5.5 Applications Topology

Node Name
Platform
Administration
Database
Concurrent Processing
Forms
Web

14.5.6 Comprising Patches (January to December) - Collected by Month

Applied Patch ID
Patch Name

14.5.7 Component Version

Component
Version

14.5.8 Configuration Version

Installed Version
Collection Version

14.5.9 Custom Alert Information

Alert Name
Alert
Application Short Name
Table Name
Description

14.5.10 Custom Applications

Application Short Name
Application Name
Basepath

14.5.11 Profile Options Registered Under Custom Application

Profile Option Name
Application Short Name
User Profile Option Name
SQL Validation
Description

14.5.12 Custom Audit Group Information

Table Name
Table Value
Enabled
Application Short Name
Group Name
Description
User Table Name

14.5.13 Custom Database Objects

Object Name
Object Type
Owner
Status

14.5.14 Custom Hooks

Module
Call Package
Call Procedure

14.5.15 Custom Message Count

Application Short Name
Number Of Custom Messages

14.5.16 Custom Objects Owned by Apps

Object Name
Object Type
Owner
Status

14.5.17 Custom Request Sets

Request Set Name
User Request Set Name
Request Set
Application Short Name

14.5.18 Responsibility Count

Application Short Name
Number of User Defined Responsibilities

14.5.19 Custom Triggers

Trigger Name
Object Type
Owner
Status

14.5.20 Custom Value Sets - Table Validated

Flex Value Set Name
Description
Meaning

14.5.21 Custom Value Sets (Other than Table Validated)

Flex Value Set Name
Description
Meaning

14.5.22 Custom Workflows

Object
Type
Description

14.5.23 Registered Data Groups

Data Group ID
Data Group Name
Default Group Flag
Creation Date

14.5.24 Database Version

Banner

14.5.25 End-Dated Users

Number of End-Dated Users

14.5.26 Generic Service Components

Component ID
Component Name
Component Type
Component Type Display Name
Concurrent Queue Name
Concurrent Queue Display Name
Container Type
Container Type Display Name
Inbound Agent Name
Inbound Agent Display Name
Outbound Agent Name
Outbound Agent Display Name
Startup Mode
Startup Mode Display Name

14.5.27 Generic Service Component Parameters

Component Parameter ID
Parameter Name
Parameter Display Name
Parameter Value
Default Parameter Value
Encrypted Flag
Allow Reload Flag

14.5.28 High Priority Patches Not Applied

Bug Number
Release
Baseline

14.5.29 JTF Hooks

Number of Custom JTF Hooks

14.5.30 Localization Modules

Application Short Name
Oracle User Name
Module Short Name
Module Version
Status
Last Update Date

14.5.31 NLS Language Support

Installed Flag
Language Code
NLS Language

14.5.32 Other Customizations

- Function Name
- User Function Name
- Type
- Application Name
- HTML Call

14.5.33 Patchset Information

- Application Short Name
- Application Name
- Patch Level
- Creation Date
- Product Version
- Status

14.5.34 Printers

- Printer Name
- Printer Type

14.5.35 Printer Drivers

- Printer Driver Name
- Description

14.5.36 User Profile Options

- Profile Option Name
- Profile Option ID
- Profile Option Value
- Level ID
- Application Short Name
- User Profile Option Name
- SQL Validation
- Description

14.5.37 Technology Stack Inventory (DB)

- Technology Components
- Component Version/Value

14.6 Oracle E-Business Suite Infrastructure

The configuration categories and their associated configuration items for the Oracle E-Business Suite Infrastructure target type follow.

14.6.1 Appsweb Configuration

- Section
- Property Name
- Property Value

14.6.2 Appsweb Configuration Metadata

- Display File Path
- File Path
- File Size
- Modification Time
- File Mode
- File Owner

14.6.3 Applications Context Files

- Path
- Node Name
- Context Name
- Context Type
- Version

14.6.4 Dbc File

- Property Name
- Property Value

14.6.5 Dbc File Meta

- Display File Path
- File Path
- File Size
- Modification Time
- File Mode
- File Owner

14.6.6 Custom Context Variables

- Path
- Node Name
- OA Var
- Type
- OA Var Value
- OA Var Name
- Category

14.6.7 Environments Context Variables

- Path
- Node Name
- OA Var
- Type
- OA Var Value
- OA Var Name
- Category

14.6.8 Global Context Variables

- Path
- Node Name
- OA Var

Type
OA Var Value
OA Var Name
Category

14.6.9 Host Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

14.6.10 Install Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

14.6.11 Processes Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

14.6.12 System Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

14.6.13 Technology Stack Inventory (File System)

Tier
Technology Components
Component Version/Value

14.6.14 Workflow Mailer Configuration

Property Name
Property Value

14.6.15 Workflow Mailer Configuration Metadata

- Display File Path
- File Path
- File Size
- Modification Time
- File Mode
- File Owner

14.7 Search Application

The configuration categories and their associated configuration items for the Search Application target type follow.

14.7.1 General

- Cached Page Max Length
- Case Sensitive
- Crawl Calendars Enabled
- Crawl Emails Enabled
- Exclude Regex
- Max Results
- Max Search Duration
- Recovery
- Sync Frequency
- Two DB Mode
- Wildcard Char

14.8 TimeManagement Application

The configuration categories and their associated configuration items for the TimeManagement Application target type follow.

14.8.1 General

- Enable Dynamic Participants
- Enable Presence Integration
- Enable External Participant Notification Delivery
- Enable Generic Class Of BusinessEvents

14.9 UserDirectory Application

The configuration categories and their associated configuration items for the UserDirectory Application target type follow.

14.9.1 Attribute

- Name
- Type
- Subtype

14.9.2 Configuration Parameters

- Max Entity Address Count
- SuperMax Entity Address Count

14.9.3 Custom Attributes

Name

Description

Oracle Enterprise Manager Cloud Control Management Collections

The Oracle Enterprise Manager Cloud Control Management collections include the following:

15.1 Oracle Enterprise Manager Cloud Control Management Agent

The configuration categories and their associated configuration items for the Oracle Enterprise Manager Cloud Control Management Agent target type follow.

15.1.1 Agent Configuration Parameters

- Agent URL
- Agent Version
- Repository URL
- Agent Timezone
- Metric Browser Enabled
- Upload Interval (Mins)
- Upload Backoff%
- Upload Timeout (secs)
- Upload File Size (kb)
- Maximum Size Allowed Upload Directory (MB)
- Maximum Number of Files Allowed in Upload Directory (MB)
- Maximum Amount% of Disk Allowed in Upload Directory (MB)
- Agent Listening on All NICS
- Agent Listening on All NICS
- SSL Session Cache Enabled
- Timeout Primary Header (Secs)
- Timeout Secondary Headers (Secs)
- Timeout Body (Secs)
- Dynamic Property Timeout (Secs)
- Timeout for RAC Database (Secs)
- Timeout for Database (Secs)
- OMS Version Agent Connects to
- Character Set Used by OMS
- Protocol Version Used by OMS
- Email Address for OOB
- Email Gateway for OOB
- Email from Address

15.1.2 Java Parameters

- Java Home
- Class Path and classpath.lst
- Host Class Path
- Java Definitions

15.1.3 Log Parameters

- Maximum Log Size (MB)
- Maximum Rolls for Log File
- Maximum Trace File Size (MB)
- Maximum Rolls for Trace File

15.1.4 Perl Parameters

- Perl Binary Home
- Perl Trace Level

15.2 Oracle Enterprise Manager Cloud Control Management Repository

The configuration categories and their associated configuration items for the Oracle Enterprise Manager Cloud Control Management Repository target type follow.

15.2.1 EM Metrics

Target Level Feature Usage

- Feature ID
- Feature name
- Is license pack
- Target type
- Used count
- Not used count

Feature Usage

- Name
- Version
- Currently Used
- Ever Used
- First Usage Date
- Aux Count
- Feature Info
- Total Samples
- Last Usage Date
- Last Sample Date
- Last Sample Period
- Detected Usages

15.2.2 EM Repository Monitory Agents

- Agent Name

15.2.3 EM Repository Monitored Beacons

- Beacon Name

15.2.4 EM Repository Configuration Parameters

Type of Repository
Repository Version

15.2.5 Object Privileges

This metric captures EXECUTE permissions for SYSMAN on UTL_FILE, UTL_SMTP and UTL_TCP objects. If the Cloud Control Repository owner SYSMAN is not explicitly granted EXECUTE on the UTL_FILE, UTL_SMTP and UTL_TCP packages, it will break several major functionalists of Grid or DB Control.

Name	Description	Data Type	Sample Value
Grantee	Name of Grantee	VARCHAR2	SYSMAN
Privilege	Kind of Privilege	VARCHAR2	EXECUTE
Table Name	Name of the table	VARCHAR2	UTL_FILE
Grantor	Name of Grantor	VARCHAR2	SYS
Owner	Name of Owner	VARCHAR2	SYS

15.2.6 OMS Name

Names of OMS Connecting to Repository
ORACLE_HOME of the OMS

15.3 Oracle Enterprise Manager Cloud Control Management Service

The configuration categories and their associated configuration items for the Oracle Enterprise Manager Cloud Control Management Service target type follow.

15.3.1 OMS Configuration Parameters

Server Name
Server Port
HTTPS Port
Server Host
Ping Command
OOB Shutdown
OOB Crash
Large Repository
Repository User
Repository Server
Repository Port
Repository SID
Repository Connect String
Email Address
Email from Address
Email from Name
Email Gateway
IP UI Enable
Public Servlet Enabled
iSqlPlus URL
iSqlPlus WebDBA URL
Dump Modules

EM Keyfile Location

Oracle Exadata Storage Server Software Collections

The Oracle Exadata Storage Server Software (Exadata Cell) collections include the following:

16.1 CELL Celldisk Configuration

Attribute	Description
Name	Unique name of the cell disk
Celldisk Comment	User comment for the cell disk
Creation Time	Time stamp when the cell disk was created
Device Name	Operating system device name of the LUN used by the cell disk
Device Partition	Operating system device name of the partition that is used by the cell disk
Error Count	Number of errors that occurred on the cell disk
Free Space (GB)	Amount of unused space available on the cell disk
ID	Global unique identifier (GUID) that is generated when the cell disk is created
LUN	ID of the LUN on which the cell disk is located
Raid Level	Value of the RAID level that is currently used on the LUN, for example, RAID 0.
Celldisk Size (GB)	Total size of the cell disk
Celldisk Status	Current status of the cell disk, such as normal or importRequired

16.2 CELL Griddisk Configuration

Attribute	Description
Griddisk Name	Unique name of the grid disk
Available To	Names of the clients that can access this grid disk
Cell Disk	Name of the cell disk that contains the grid disk
Griddisk Comment	User-supplied text string
Creation Time	Time stamp when the grid disk was created

Attribute	Description
Error Count	Count of hardware errors detected by the cell disk containing this grid disk
ID	Global unique identifier (GUID) that is generated when the grid disk is created
Lowest Offset (MB)	Lowest byte offset of the grid disk on the physical disk
Griddisk Size (MB)	Total size of the grid disk
Griddisk Status	Current status of the grid disk, such as <code>active</code> , <code>inactive</code> , <code>not present</code> , or <code>importRequired</code>

16.3 CELL IORM Configuration

Attribute	Description
IO Resource Plan Name	Unique name of the interdatabase plan. The name value is automatically set to <code>cellname_IORMPLAN</code> .
Category Plan	Allocation plan for the categories set up in the databases using the cell
DB Plan	Allocation plan for the databases using the cell
Status	Current status of the interdatabase plan, either <code>active</code> or <code>inactive</code> .

16.4 CELL LUN Configuration

Attribute	Description
LUN Name	Unique name assigned to the LUN. This might be different (or extended from) the LUN ID if the ID is not unique.
Cell Disk	Name of the cell disk associated with the LUN. This is empty if the LUN is not associated with a cell disk.
Device Name	Operating system device name for the LUN, for example, <code>/dev/cciss/c1d5</code>
ID	Identifier assigned by the system
System LUN	If value is <code>TRUE</code> , then the disk is a system disk. If the value is <code>FALSE</code> , then the disk is not a system disk, and only has data on it.
Auto Create	Indicator whether the LUN was automatically created. Values are <code>TRUE</code> or <code>FALSE</code> . Single-disk LUNs are automatically created when disks without LUNs are converted to cell disks. For example, <code>CREATE DISK ALL</code> creates single-disk LUNs for all physical disks without LUNs. These single-disk LUNs have this attribute set to <code>TRUE</code> .
LUN Size (GB)	Raw size of the LUN before being converted to a cell disk
Physical Devices	Physical disk names that form the LUN
Raid Level	Value of the RAID level that is used on the LUN, for example, <code>RAID 0</code> .
LUN Status	Status of the LUN, which can be <code>normal</code> , <code>warning</code> , or <code>critical</code> .

16.5 CELL Physical Disk Configuration

Attribute	Description
Physical Disk Name	Unique name of the physical disk
ID	Identifier assigned by the system
LUN	List of LUNs converted from this physical disk
Insert Time	Time that the disk was inserted
Disk Size (GB)	Size of the disk in bytes
Physical Disk Status	Status of the physical disk. Values can be normal, warning, or critical.

16.6 Exadata Bugs Fixed

Attribute	Description
ID	Identifier for Oracle Exadata Storage Server
Bug Number	Bug number for Oracle Exadata Storage Server

16.7 Oracle Cell Configuration

Attribute	Description
Cell Name	Unique name for the cell
BMC Type	Name and version of the BMC
Cell Version	Version of the cell software
CPU Count	Number of CPUs on the cell
Fan Count	Count of working fans and total fans, displayed as working/total
ID	Global unique identifier (GUID) supplied by the hardware vendor
Interconnect Count	Number of network interconnects
IORM Boost	Ratio of the cumulative number of positions in the I/O queue that were skipped because of IORM scheduling to the number of I/Os that were scheduled. This ratio is calculated by sampling the changes each minute in the two numbers.
IP Address 1	IP address 1 for the cell
IP Address 2	IP address 2 for the cell
IP Address 3	IP address 3 for the cell
IP Address 4	IP address 4 for the cell
Kernel Version	Version of the host kernel software
Make Model	Make and mode of the cell hardware supplied by the vendor
Metric History Days	Number of days that metric history, alert history, and ADR files are retained. The default is 7 days.
Power Count	Count of power supplies, displayed as working/total. Not available on HP hardware.

Oracle Forms Collections

The Oracle Forms collections include the following

17.1 General Information

ECM Associations
Target Version

Oracle Fusion Applications Instance Collections

The Oracle Fusion Applications Instance collections include the following:

18.1 Oracle Fusion Applications Instance

Target Version

18.2 Oracle Fusion Applications Product Family

The configuration categories and their associated configuration items for the Oracle Fusion Applications Product Family Collections target type follow.

18.2.1 Country Specific Localization Features

Offering Name
Module Name
Module Type
Is Used
Is Loaded

18.2.2 Data Fix Script Execution History

Script Name
Version
Execution ID
Timestamp

18.2.3 Enabled Languages

Language Code
Is Installed

18.2.4 Functionally Configured Options

Option Name

18.2.5 Multi-Tenancy

Is Multi-Tenant

18.2.6 Target Version

Target Version

18.3 Oracle Fusion Applications Product

The configuration categories and their associated configuration items for the Oracle Fusion Applications Product Collections target type follow.

18.3.1 Functionally Configured Options

Option Name

18.3.2 Logical Business Area (LBA)

Product Name
LBA Name

18.3.3 Target Version

Target Version

18.4 Oracle Fusion Applications Cluster Application

Target Version

18.5 Oracle Fusion Applications J2EE Application

The configuration categories and their associated configuration items for the Oracle Fusion Applications J2EE Application Collections target type follow.

18.5.1 Target Version

Target Version

18.5.2 WebLogic Application Configuration

Path
Load Order
Type

Oracle Home Collections

The Oracle Home collections include the following:

19.1 Dependency Rules

- Referencer Name
- Referencer Version
- Dependee Name
- Dependee Version

19.2 Oracle Oneoff Patches

- ID
- Is Rollbackable
- XML Inventory Location
- Installer Version
- Timestamp

19.3 Oracle Oneoff Patches Bugs Fixed

- Id
- Bug Number

19.4 Oracle Oneoff Patches Components

- Id
- Component Name
- Version

19.5 Oracle Software Components

- Name
- Version
- Description
- External Name
- Languages
- Installed Location
- Installer Version
- Minimum Deinstaller Version
- Is Toplevel
- Timestamp

Patch Version

19.6 Oracle Software Patchsets

Name
Version
Description
External Name
Installed Location
Minimum Installer Version
Timestamp

19.7 Oracle Versioned Patches

Name
Version
Patchset Name
Patchset Version
Description
External Name
Languages
Installed Location
Minimum Deinstaller Version
Timestamp

Oracle Hyperion Enterprise Performance Management System Collections

The Oracle Hyperion Enterprise Performance Management (EPM) System collections include the following:

20.1 Oracle Enterprise Performance Management System

The configuration categories and their associated configuration items for the Oracle Enterprise Performance Management System target type follow.

20.1.1 Database Connection

JDBC URL

20.1.2 Instance Information

Version

20.2 Oracle's Hyperion Shared Services

The configuration categories and their associated configuration items for the Oracle's Hyperion Shared Services target type follow.

20.2.1 Database Connection

Database Type
JDBC URL

20.2.2 Instance Information

Version

20.2.3 Security Options Setting

Token Timeout
Logging Level
Delegated User Management

20.2.4 Security Service Providers

Name

Type
Host
Port
SSL Enabled
Base DN
Id Attribute
Trusted

20.2.5 Web Application Deployment

Application Server Type
LWA Host
LWA Port

20.3 Oracle Hyperion Enterprise Performance Management Workspace, Fusion Edition

The configuration categories and their associated configuration items for the Oracle Hyperion Enterprise Performance Management Workspace, Fusion Edition target type follow.

20.3.1 Database Connection

Database Type
JDBC URL

20.3.2 Instance Information

Version

20.3.3 Web Application Deployment

Application Server Type
LWA Host
LWA Port

20.4 Oracle Hyperion Enterprise Performance Management Architect, Fusion Edition

The configuration categories and their associated configuration items for the Hyperion Enterprise Performance Management Architect, Fusion Edition target type follow.

20.4.1 Database Connection

Database Type
JDBC URL

20.4.2 Instance Information

Version

20.4.3 Web Application Deployment

Application Server Type

LWA Host
LWA Port

20.5 Oracle Hyperion Calculation Manager

The configuration categories and their associated configuration items for the Oracle Hyperion Calculation Manager target type follow.

20.5.1 Database Connection

Database Type
JDBC URL

20.5.2 Instance Information

Version

20.5.3 Web Application Deployment

Application Server Type
LWA Host
LWA Port

20.6 Oracle Essbase Server

The configuration categories and their associated configuration items for the Oracle Essbase Server target type follow.

20.6.1 Instance Information

Version
32-64 mode
Essbase App Location
ESSLANG
Agent Port
App Start Port
App End Port
Server Thread
Agent Threads
Net Retry
Net Delay
Dynamic Calculator Cache
BlockSize

20.7 Oracle Essbase Administration Services

The configuration categories and their associated configuration items for the Oracle Essbase Administration Services target type follow.

20.7.1 Instance Information

Version

20.7.2 Web Application Deployment

- Application Server Type
- LWA Host
- LWA Port

20.8 Oracle Hyperion Provider Services

The configuration categories and their associated configuration items for the Oracle Hyperion Provider Services target type follow.

20.8.1 Instance Information

- Version

20.8.2 Web Application Deployment

- Application Server Type
- LWA Host
- LWA Port

20.9 Hyperion Reporting and Analysis Framework

The configuration categories and their associated configuration items for the Hyperion Reporting and Analysis Framework target type follow.

20.9.1 Database Connection

- Database Type
- JDBC URL

20.9.2 Instance Information

- Version

20.9.3 Web Application Deployment

- Application Server Type
- LWA Host
- LWA Port

20.10 Hyperion Web Analysis

The configuration categories and their associated configuration items for the Hyperion Web Analysis target type follow.

20.10.1 Instance Information

- Version

20.10.2 Web Application Deployment

- Application Server Type
- LWA Host
- LWA Port

20.11 Oracle Hyperion Financial Reporting, Fusion Edition

The configuration categories and their associated configuration items for the Oracle Hyperion Financial Reporting, Fusion Edition type follow.

20.11.1 Instance Information

Version

20.11.2 Web Application Deployment

Application Server Type
LWA Host
LWA Port

20.12 Oracle Hyperion Financial Management, Fusion Edition

The configuration categories and their associated configuration items for the Oracle Hyperion Financial Management, Fusion Edition type follow.

20.12.1 Database Connection

Database Type
OLEDB Driver

20.12.2 Instance Information

Version
DCOM User

20.13 Oracle Hyperion Planning, Fusion Edition

The configuration categories and their associated configuration items for the Oracle Hyperion Planning, Fusion Edition target type follow.

20.13.1 Business Rules

MYOLAP_Enabled
Css_refresh
Launch_log_dateformat
Launch_log_Log_Calc_script
Launch_log_filename
HBR_Cache
HBR_Cache_refresh_rate
Plugin_data_refresh_rate

20.13.2 Database Connection

Database Type
JDBC URL

20.13.3 Instance Information

Version

20.13.4 Web Application Deployment

Application Server Type
LWA Host
LWA Port

20.14 Oracle Hyperion Profitability and Cost Management, Fusion Edition

The configuration categories and their associated configuration items for the Oracle Hyperion Profitability and Cost Management, Fusion Edition target type follow.

20.14.1 Database Connection

Database Type
JDBC URL

20.14.2 Instance Information

Version

20.14.3 Web Application Deployment

Application Server Type
LWA Host
LWA Port

20.15 Oracle Hyperion Performance Scorecard, Fusion Edition

The configuration categories and their associated configuration items for the Oracle Hyperion Performance Scorecard, Fusion Edition target type follow.

20.15.1 Database Connection

Database Type
JDBC URL

20.15.2 Instance Information

Version

20.15.3 Web Application Deployment

Application Server Type
LWA Host
LWA Port

20.16 Oracle Hyperion Financial Data Quality Management ERP Integration Adapter for Oracle Applications, Fusion Edition

The configuration categories and their associated configuration items for the Oracle Hyperion Financial Data Quality Management ERP Integration Adapter for Oracle Applications, Fusion Edition (ERP Integrator) target type follow.

20.16.1 Database Connection

Database Type
JDBC URL

20.16.2 Instance Information

Version

20.16.3 Web Application Deployment

Application Server Type
LWA Host
LWA Port

Oracle Identity Management Collections

As a prerequisite for Oracle Identity Management Collections, the user is required to log on to Fusion Middleware Enterprise Manager Console once before running the configuration collection.

The Oracle Identity Management collections include the following:

21.1 Directory Integration Platform

The configuration categories and their associated configuration items for the Directory Integration Platform target type follow:

21.1.1 Directory Integration Platform Configuration

- Oracle Internet Directory Host
- Oracle Internet Directory Port
- SSL Mode
- Refresh Interval

21.1.2 Admin Server Details

- Admin Server Host
- Admin Server Port
- WebLogic Domain Name

21.1.3 WebLogic Application Configuration

- Path
- Load Order
- Type

21.2 Oracle Access Manager

- ECM Associations
- J2EE Application Config
- Target Version

21.3 Oracle Adaptive Access Manager

- ECM Associations
- J2EE Application Config
- Target Version

21.4 Oracle Identity Federation

The configuration categories and their associated configuration items for the Oracle Identity Federation target type follow:

21.4.1 Server Configurations

- Server Host Name
- Server Port
- Port - SSL Enabled
- Port - Force SSL
- SOAP Port
- SOAP Port - SSL Enabled
- SOAP Port - Force SSL
- SOAP Port - Require Client Certificate
- Server Clock Drift (sec)
- Session Timeout (sec)
- Request Timeout (sec)
- Default XML Data Encryption Algorithm
- Logout Option - Fail on Error
- Logout Option - Return Status
- Logout Option - Local Logout Only
- Logout Option - Parallel Logout
- Maximum SOAP Connections
- Maximum SOAP Connections per Server
- Proxy Host
- Proxy Port
- Proxy Username
- Non-Proxy Hosts

21.4.2 Data Store Configurations

- Federation Store LDAP Connection URL
- Federation Store LDAP Bind DN
- User Federation Record context
- LDAP Container Object Class
- Unique Federation ID Attribute
- Federation Store LDAP Maximum Connections
- Federation Store LDAP Connection Wait Timeout (sec)
- Federation Store RDBMS JNDI Name
- User Store LDAP Connection URL
- User Store LDAP Bind DN
- LDAP User ID Attribute
- LDAP User Description Attribute
- Person Object Class
- Base DN
- User Store LDAP Maximum Connections
- User Store LDAP Connection Wait Timeout (sec)
- User Store RDBMS JNDI Name
- User Store RDBMS Login Table
- RDBMS User ID Attribute
- RDBMS User Description Attribute

21.4.3 Identity Provider Configurations

- Enable Identity Provider

Provider ID
 Assertion Validity (sec)
 Re-authenticate After (sec)
 Send Signed Assertion
 Artifact Timeout (sec)
 Enable Common Domain
 Common Domain URL
 Common Domain Cookie Domain
 Common Domain Cookie Lifetime (day)
 SSO User Opt-In/Out Mode
 Opt-In/Out User Attribute
 Opt-In/Out Attribute Value
 Re-authenticate when Missing User Session Attributes

21.4.4 Identity Provider SAML 2.0 Assertion Properties

Enabled NameID Formats
 Default NameID Format
 Get Value from User Session for X.509 Subject Name
 Get Value from User Session for Email Address
 Get Value from User Session for Windows Domain Qualified Name
 Get Value from User Session for Kerberos Principal Name
 Get Value from User Session for Unspecified
 Get Value from User Session for Custom
 User Attribute Mapping for X.509 Subject Name
 User Attribute Mapping for Email Address
 User Attribute Mapping for Windows Domain Qualified Name
 User Attribute Mapping for Kerberos Principal Name
 User Attribute Mapping for Kerberos Principal Name
 User Attribute Mapping for Custom
 Name of the Custom Format
 Federation Creation User Consent URL
 Force User Consent
 Send Encrypted Assertions
 Send Encrypted Assertions
 Send Encrypted NameID
 Send Signed Assertion

21.4.5 Identity Provider SAML 2.0 Protocol Properties

Enable SAML 2.0 Protocol
 Enable Register NameID Protocol
 Enable Federation Termination Protocol
 Enable Attribute Query Responder
 User Identity Federation for Attribute Response
 Enable Authentication Query Responder
 Enable Assertion ID Responder
 Enable Protocol Bindings
 Default Binding
 Default SSO Response Binding
 Authentication Request message to Require Signed
 Request | XML/HTTP Post message to Require Signed
 Request | URL/HTTP Redirect message to Require Signed
 Request | XML/SOAP message to Require Signed
 Response | XML/HTTP Post message to Require Signed

Response | URL/HTTP Redirect message to Require Signed
Response | XML/SOAP message to Require Signed
Request | XML/HTTP Post message to Send Signed
Request | URL/HTTP Redirect message to Send Signed
Request | XML/SOAP message to Send Signed
Response | XML/HTTP Post message to Send Signed
Response | URL/HTTP Redirect message to Send Signed
Response | XML/SOAP message to Send Signed
Response (Assertion) | XML/HTTP Post message to Send Signed
Response (Assertion) | XML/SOAP message to Send Signed

21.4.6 Identity Provider SAML 1.0 Assertion and Protocol Properties

Enabled NameID Formats
Default NameID Format
Get Value from User Session for X.509 Subject Name
Get Value from User Session for Email Address
Get Value from User Session for Windows Domain Qualified Name
Get Value from User Session for Unspecified
Get Value from User Session for Custom
User Attribute Mapping for X.509 Subject Name
User Attribute Mapping for Email Address
User Attribute Mapping for Windows Domain Qualified Name
User Attribute Mapping for Unspecified
User Attribute Mapping for Custom
Name of the Custom Format
Send Signed Assertion
Enable SAML 1.1 Protocol
Enable SAML 1.0 Protocol
Enable Attribute Query Responder
Enable Authentication Query Responder
Enable Assertion ID Responder
SSO Response Binding
Request | XML/SOAP message to Require Signed
Response (Assertion) | XML/HTTP Post message to Send Signed
Response (Assertion) | XML/SOAP message to Send Signed

21.4.7 Identity Provider WSFed 1.1 Properties

Enable WS-Federation 1.1 Protocol
SSO Token Type
Use Microsoft Web Browser Federated SSO Profile

21.4.8 Service Provider Configurations

Service Provider Configurations
Provider ID
Enable Map Assertion to User Account
Anonymous User ID
Ignore Unknown Conditions
Require Signed Assertions
Default SSO Identity Provider
Enable IdP Discovery Service URL
IdP Discovery Service URL
Enable Common Domain Service

Common Domain Service URL
 Enable Attribute Requester Service
 Default Attribute Authority
 DN Pattern | Identity Provider
 Authentication Mechanism | Identity Provider

21.4.9 Service Provider SAML 2.0 Assertion Properties

Map User via Federated Identity
 Enable Auto Account Linking
 Map User via Attribute Query
 Attribute Query
 Map User via NameID
 Enabled NameID Formats
 User Attribute Mapping for X.509 Subject Name
 User Attribute Mapping for Email Address
 User Attribute Mapping for Windows Domain Qualified Name
 User Attribute Mapping for Kerberos Principal Name
 User Attribute Mapping for Unspecified
 User Attribute Mapping for Custom
 Name of the Custom Format
 Error when User Mapping Fails
 Error when User Mapping Fails
 Required Signed Assertion

21.4.10 Service Provider SAML 2.0 Protocol Properties

Enable SAML 2.0 Protocol Enabled
 Enable Register NameID Protocol
 Enable Federation Termination Protocol
 Send Encrypted NameIDs
 Send Encrypted Attributes
 Allow Federation Creation
 User Consent URL
 Force User Consent
 Enable Protocol Bindings
 Default Binding
 Default SSO Request Binding
 Default SSO Response Binding
 Default Authentication Request NameID Format
 Request Authentication Context Mechanism
 Request Authentication Context Comparison
 Request Authentication Context Comparison
 Request | XML/HTTP Post message to Send Signed
 Request | URL/HTTP Redirect message to Send Signed
 Request | XML/SOAP message to Send Signed
 Response | XML/HTTP Post message to Send Signed
 Response | URL/HTTP Redirect message to Send Signed
 Response | XML/SOAP message to Send Signed
 Request | XML/HTTP Post message to Require Signed
 Request | URL/HTTP Redirect message to Require Signed
 Request | XML/SOAP message to Require Signed
 Response | XML/HTTP Post message to Require Signed
 Response | URL/HTTP Redirect message to Require Signed
 Response | XML/SOAP message to Require Signed

Response (Assertion) | XML/HTTP Post message to Require Signed
Response (Assertion) | XML/SOAP message to Require Signed

21.4.11 Service Provider SAML 1.x Assertion and Protocol Properties

Map User via Attribute Query
Map User via Attribute Query
Map User via NameID
Enabled NameID Formats
User Attribute Mapping for X.509 Subject Name
User Attribute Mapping for Email Address
User Attribute Mapping for Windows Domain Qualified Name
User Attribute Mapping for Unspecified
User Attribute Mapping for Custom
Name of the Custom Format
Error when User Mapping Fails
Ignore Unknown Condition
Required Signed Assertion
Enable SAML 1.0 Protocol
Enable SAML 1.1 Protocol
Enable Protocol Binding
Enable Protocol Binding
Response (Assertion) | XML/HTTP Post message to Require Signed
Response (Assertion) | XML/SOAP message to Require Signed

21.4.12 Service Provider WSFed 1.1 Properties

Enable WD-Federation 1.1 Protocol

21.4.13 Admin Server Details

Admin Server Host
Admin Server Port
WebLogic Domain Name

21.4.14 WebLogic Application Configuration

Path
Load Order
Type

21.5 Oracle Identity Manager

ECM Associations
J2EE Application Config
Target Version

21.6 Oracle Internet Directory

The configuration categories and their associated configuration items for the Oracle Internet Directory target type follow:

21.6.1 Oracle Internet Directory General Configurations

Server Mode

Max number of entries returned by search
Max time allowed for a search to complete
Anonymous Bind
SDump Flag
SSL Interop Mode

21.6.2 Oracle Internet Directory Performance Configurations

Number of OID LDAP Server Processes
Number of DB Connections per Server Process
Enable Entry Cache
Maximum Entries in Entry Cache
Maximum Entry Size in Cache (byte)
Maximum Entry Cache Size (bytes)
Number of users in privilege Group membership Cache
LDAP Idle Connection Timeout (sec)
OID Server Network Read/Write Retry Timeout (sec)
Maximum number of LDAP connections per Server Process
Max Time for Server process to respond to Dispatcher process (sec)
Number of Dispatcher Threads per Server Process
Number of Plugin Threads per Server Process
Enable Change Log Generation
Enable Group Cache

21.6.3 Oracle Internet Directory SASL Configurations

Authentication Mode
Cipher Choice
External SASL Authentication
Authentication Mechanism

21.6.4 Oracle Internet Directory Statistics Configurations

Stats Flag
Stats Frequency (min)
Security Event Tracking
User Statistics Collection
Event Levels

21.6.5 Oracle Internet Directory Log Configurations

Debug Level
Operations Enabled for Debug
Maximum Log File Size
Maximum Files in Rotation

21.6.6 Admin Server Details

Admin Server Host
Admin Server Port
WebLogic Domain Name

21.7 Oracle Virtual Directory

The configuration categories and their associated configuration items for the Oracle Virtual Directory target type follow:

21.7.1 Server Configuration

- ACL Check
- DoS Active
- DoS Rate Period
- Exempt IP Addresses
- Exempt Subjects
- Maximum inactive connection timeouts
- Maximum Connections
- Maximum Connections per IP
- Maximum Connections per Subject
- Maximum Operations per Connection
- Schema Check

21.7.2 Search Configuration

- Anonymous Search Limit
- Authenticated Search Limit
- Persistent Search

21.7.3 Schema Locations

- Schema Locations

21.7.4 Listener Configuration

- Listener Name
- Listener Type
- Listener Version
- Listener Active
- Listener Host
- Listener Port
- Threads
- Group URL
- SSL Enabled
- SSL Authentication Type
- SSL Trust Store
- SSL Key Store
- SSL Protocol
- SSL Ciphers

21.7.5 Administration Server Details

- Admin Server Host
- Admin Server Port
- WebLogic Domain Name

Oracle Portal Collections

The Oracle Portal collections include the following:

22.1 Oracle Portal

ECM Associations
Target Version

Oracle Reports Collections

The Oracle Reports collections include the following:

23.1 Oracle Reports Application

ECM Associations
Target Version

23.2 Oracle Reports Server

ECM Associations
Target Version

Oracle Retail Collections

The Oracle Retail collections include the following:

24.1 Oracle Retail Active Retail Intelligence Application

Version
Install Date

24.2 Oracle Retail Allocation Java Application

Version
Install Date

24.3 Oracle Retail Back Office Java Application

Version
Install Date
Application Name
AppServer Instance Profile
Deployment Stack

24.4 Oracle Retail Central Office Java Application

Version
Install Date
Application Name
AppServer Instance Profile
Deployment Stack

24.5 Oracle Retail Markdown Optimization

Version
Install Date

24.6 Oracle Retail Workspace

Version
Install Date
Build Number

24.7 Oracle Retail Data Warehouse Database

Version
Install Date

24.8 Oracle Retail Merchandising System Application

Version
Install Date

24.9 Oracle Retail Returns Management Java Application

Version
Install Date
Application Name
AppServer Instance Profile
Deployment Stack

24.10 Oracle Retail Price Management Java Application

Version
Install Date

24.11 Oracle Retail Warehouse Management System Application

Version
Install Date

24.12 Oracle Retail Invoice Matching Java Application

Version
Install Date

24.13 Oracle RPAS Global Domain

Dimension

24.14 Oracle Retail Predictive Application Server

Module
Release
Release Date

24.15 Oracle RPAS Sub Domain

Position

24.16 Oracle Retail Store Inventory Management Java Application

Version
Install Date

24.17 Oracle Retail Integration Bus Java Application

Application Name
Application Type
Database URL
Database User
JNDI URL
JNDI Factory
JNDI User
JMS Server Home
JMS URL
JMS Port
JMS User
OAS Instance Name
OC4J Instance Name
Kernel Version
Functional Artifact Version
RIB PAK Version

Oracle WebCenter Collections

The Oracle WebCenter collections include the following:

25.1 Oracle WebCenter

ECM Associations
Target Version

25.2 Oracle WebCenter Activity Graph

ECM Associations
Target Version

25.3 Oracle WebCenter Analytics Collector

ECM Associations
Target Version

25.4 Oracle WebCenter Discussions Server

ECM Associations
Target Version

25.5 Oracle WebCenter Personalization

ECM Associations
Target Version

25.6 Oracle WebCenter Portlet Server

ECM Associations
Target Version

25.7 Oracle WebCenter Content

Version

Oracle WebLogic Collections

The Oracle WebLogic collections include the following:

26.1 Oracle WebLogic Server

The configuration categories and their associated configuration items for the Oracle WebLogic Server target type follow.

26.1.1 General Server Configuration

- Listen Port
- Administration Port
- Native IO Enabled
- Maximum Open Sockets
- Stuck Thread Maximum Time
- Stuck Thread Timer Interval
- Accept Backlog
- Login Timeout
- Managed Server Independence Enabled
- Low Memory GC Threshold
- Low Memory Granularity Level
- Low Memory Sample Size
- Low Memory Time Interval
- SSL Listen Port
- SSL Login Timeout
- Cluster Name
- Cluster Weight
- Machine Name

26.1.2 Virtual Host Configuration

- Name
- Deployment Order
- Front End Host
- Front End HTTP Port
- Front End HTTPS Port
- Virtual Host Names
- Network Access Point
- Log File Name
- Logging Enabled
- Maximum Post Size

26.1.3 Jolt Connection Pools Configuration

- Name
- Primary Addresses
- Failover Addresses
- Minimum Pool Size
- Maximum Pool Size
- Receive Timeout

26.1.4 Work Manager Configuration

- Name
- Ignore Stuck Threads
- Minimum Threads
- Maximum Threads
- Request Class Type
- Request Class Name
- Capacity Constraint

26.1.5 Startup and Shutdown Classes Configuration

- Name
- Type
- Class Name
- Deployment Order

26.1.6 JDBC DataSource Configuration

- Name
- JNDI Name
- Row Prefetch Enabled
- Row Prefetch Size
- Two Phase Commit Enabled
- URL
- Driver Name
- Capacity Increment
- Initial Capacity
- Maximum Capacity
- Connection Reserve Timeout
- Inactive Connection Timeout
- Statement Cache Size

26.1.7 JDBC Multi-DataSource Configuration

- Name
- JNDI Name
- Algorithm Type
- Datasource List

26.1.8 JMS Connection Factory Configuration

- Name
- Module Name
- JNDI Name
- Transaction Timeout
- Acknowledge Policy

Maximum Messages
Send Timeout

26.1.9 JMS Topic Configuration

Name
Module Name
JNDI Name
Maximum Message Size
Maximum Bytes
Maximum Messages
Multicast Port

26.1.10 JMS Queue Configuration

Name
Module Name
JNDI Name
Maximum Message Size
Maximum Bytes
Maximum Messages

26.1.11 Resource Configuration

Start Heap
Maximum Heap

26.2 Oracle WebLogic Install

The configuration categories and their associated configuration items for the Oracle WebLogic Install target type follow.

26.2.1 Oracle WebLogic Product Components

Name
Version
Sub Component Names

PeopleSoft Collections

Oracle Configuration Manager collects configuration data for multiple PeopleTools/application releases and the data described in this chapter may not be applicable to all combinations. Because of this restriction, configurations may not show all possible data to be collected.

User IDs and passwords are never intentionally captured as part of the collection process. A value of *empty* or *not empty* is returned when User IDs and passwords are evaluated.

The PeopleSoft collections include the following:

27.1 PeopleSoft Application Server

The configuration categories and their associated configuration items for the PeopleSoft Application Server target type follow.

27.1.1 Application Server Analytics Parameters

- Maximum Instances
- Minimum Instances

27.1.2 Application Server Cache Parameters

- Maximum Cache Memory Settings

27.1.3 Application Server Configuration Parameters

- Configuration Path
- Domain
- GUID
- Host Name
- PeopleSoft Configuration Home
- State

27.1.4 Application Server Database Parameters

- Enable Database Monitoring
- PeopleSoft Database Maximum Cursors
- Sybase Packet Size Options
- Use Local Oracle Database Options

27.1.5 Application Server Domain Parameters

- Add to Path
- Allow Dynamic Changes
- Domain ID
- Log Fence
- Restartable
- Spawn Threshold
- Trace-Log File Character Set

27.1.6 Application Server Integration Broker Parameters

- Integration Broker Profile Information
- Message View Size
- Minimum Message Size for Compression
- Thread Pool Size

27.1.7 Application Server Interface Driver Parameters

- SCP Locale

27.1.8 Application Server Jolt Listener Parameters

- Address
- Client Cleanup Timeout
- Client Connection Mode
- Clients per Handler
- Encryption
- Initialize Timeout
- Jolt Compression Threshold
- Maximum Handlers
- Minimum Handlers
- Port

27.1.9 Application Server Jolt Relay Parameters

- Listener Address
- Listener Port

27.1.10 Application Server Message Broker Dispatcher Parameters

- Allowed Consecutive Service Failures
- Dispatch List Multiplier
- Dispatcher Queue Maximum Queue Size
- Handler Status Check Count
- Maximum Ping Interval
- Memory Queue Refresh Rate
- Ping Rate
- Recycle Count
- Restart Period
- Scan Interval

27.1.11 Application Server Message Broker Handler Parameters

- Allowed Consecutive Service Failures
- Maximum Instances

Maximum Retries
Minimum Instances
Recycle Count
Service Timeout

27.1.12 Application Server Options Parameters

Allowed Consecutive Service Failures
Auto Select Prompts
Maximum Fetch Size
Maximum Instances
Minimum Instances
Recycle Count
Service Timeout
Tuxedo Queue Size

27.1.13 Application Server Optimization Engine Parameters

Maximum Instances
Optimized Maximum General Services
Service Timeout

27.1.14 Application Server People Code Debugger Parameters

Debugger Message Log Enable
PSDBGSRV Listener Port

27.1.15 Application Server PPM Server Parameters

Maximum Instances
Minimum Instances

27.1.16 Application Server PSBRKDSP Server Parameters

The PSBRKDSP Server parameters may have multiple occurrences.

Allowed Consecutive Service Failures
Dispatch List Multiplier
Dispatcher Queue Maximum Queue Size
Memory Queue Refresh Rate
Queues
Recycle Count
Restart Period
Scan Interval

27.1.17 Application Server PSBRKHND Server Parameters

The PSBRKHND Server parameters may have multiple occurrences.

Allowed Consecutive Service Failures
Maximum Instances
Maximum Retries
Minimum Instances
Recycle Count
Service Timeout

27.1.18 Application Server PSPUBDSP Server Parameters

The PSPUBDSP Server parameters may have multiple occurrences.

- Allowed Consecutive Service Failures
- Dispatch List Multiplier
- Dispatcher Queue Maximum Queue Size
- Maximum Ping Interval
- Memory Queue Refresh Rate
- Ping Rate
- Queues
- Recycle Count
- Restart Period
- Scan Interval

27.1.19 Application Server PSPUBHND Server Parameters

The PSPUBHND Server parameters may have multiple occurrences.

- Allowed Consecutive Service Failures
- Maximum Instances
- Maximum Retries
- Minimum Instances
- Recycle Count
- Service Timeout
- Thread Pool Size

27.1.20 Application Server PSSUBDSP Server Parameters

The PSSUBDSP Server parameters may have multiple occurrences.

- Allowed Consecutive Service Failures
- Dispatch List Multiplier
- Dispatcher Queue Maximum Queue Size
- Memory Queue Refresh Rate
- Queues
- Recycle Count
- Restart Period
- Scan Interval

27.1.21 Application Server PSSUBHND Server Parameters

The PSSUBHND Server parameters may have multiple occurrences.

- Allowed Consecutive Service Failures
- Maximum Instances
- Maximum Retries
- Minimum Instances
- Recycle Count
- Service Timeout

27.1.22 Application Server PUB-SUB Servers Parameters

- Domain Slave Mode
- Load Balance Interval
- Message Segment from Database
- Persistent Cursors on DB2 OS390
- Serial Recycle

27.1.23 Application Server QCK Server Parameters

- Allowed Consecutive Service Failures
- Maximum Fetch Size
- Maximum Instances
- Minimum Instances
- Recycle Count
- Service Time Out

27.1.24 Application Server Query Server Parameters

- Allowed Consecutive Service Failures
- Maximum Fetch Size
- Maximum Instances
- Minimum Instances
- Recycle Count
- Service Time Out
- Use Dirty-Read

27.1.25 Application Server Remote Call Parameters

- RCCBL Redirect

27.1.26 Application Server REN Server Parameters

- Default Authentication Token
- Default HTTP Port
- Default HTTPS Port
- IO Buffer Size
- Log Severity Level

27.1.27 Application Server SAM Server Parameters

- Allowed Consecutive Service Failures
- Maximum Fetch Size
- Maximum Instances
- Minimum Instances
- Recycle Count
- Service Timeout

27.1.28 Application Server Security Parameters

- Domain Connection Password (empty/not empty returned)
- Validate Signon with Database

27.1.29 Application Server Service Configuration

When an Application Server is configured, the features are captured in the psappserv.ubx file. The metric collects all the application server features/ processes and the enabled value during an application server configuration. The listing of all features allows GSC to analyze the features enabled and the process configurations that are active within the domain. The metric is a name value pair that lists all Application Server processes and whether the feature is enabled or not.

For example, the following features appear in a PeopleSoft 8.51 application server collection:

Feature Name	Enabled
Pub/Sub Servers	False
Quick Server	True
Query Servers	True
Jolt	True
Jolt Relay	False
WSL	False
PC Debugger	True
Event Notification	True
MCF Servers	True
Perf Collator	True
Analytic Servers	True
Domains Gateway	True

The specific list for your version of PeopleTools may be different from this example.

27.1.30 Application Server Slave Parameters

This metric captures failover configuration for Integration Broker. Dynamic slaves are configured in conjunction with domain failover. If a slave domain has the highest priority within a failover group, it can dynamically change to a master during failover. Dynamic slaves can be configured in the Failover Configuration page in the Service Operations Monitor.

Failover Flag
 Failover Time
 Machine
 Path
 Reset Priority
 Slavemode

27.1.31 Application Server SMTP Parameters

SMTP Blackberry Reply To
 SMTP Character Set
 SMTP Client Certification Alias
 SMTP Client Certification Alias 1
 SMTP Encoding DLL
 SMTP Guaranteed
 SMTP Port
 SMTP Port 1
 SMTP Send Time
 SMTP Sender
 SMTP Server
 SMTP Server 1
 SMTP Source Machine
 SMTP SSL Port
 SMTP SSL Port 1
 SMTP Trace
 SMTP Use SSL

SMTP Use SSL 1

27.1.32 Application Server Startup Parameters

Connect ID (empty/not empty returned)
Connect Password (empty/not empty returned)
Database Name
Database Type
Domain Connection Password (empty/not empty returned)
Server Name
Standby DB Name
Standby DB Type
Standby User ID (empty/not empty returned)
Standby User Password (empty/not empty returned)
User ID (empty/not empty returned)
User Password (empty/not empty returned)

27.1.33 Application Server Tools Parameters

Add to Class Path
Character Set
Database Flags
Enable PPM Agent
Java Virtual Machine Options
Non-proxy Hosts
Proxy Host
Proxy Port
Suppress Application Error Box
Suppress SQL Error
Usage Monitoring State

27.1.34 Application Server Trace Parameters

Dump Manager Objects at Crash
Dump Memory Image at Crash
Log Error Report
Mail Error Report
Trace AE
Trace Analytic
Trace Analytic Mask
Trace PC
Trace PC Mask
Trace PIA
Trace PIA Mask
Trace PPM
Trace PPR
Trace PPR Mask
Trace SQL
Trace SQL Mask

27.1.35 Application Server Workstation Parameters

Address
Client Cleanup Timeout
Encryption

- Initialization Timeout
- Maximum Clients per Handler
- Maximum Handlers
- Minimum Handlers
- Port
- Tuxedo Compression Threshold

27.1.36 Integration Broker Gateway

- Connector URL
- IB SSL
- Integration Gateway ID
- Local Flag
- Version

27.1.37 Integration Broker Handler Slaves

- Application Server Path
- IB Transaction ID
- Machine
- Queue Name
- Queue Sequence ID
- Slave Process Name
- Sub Channel

27.1.38 Integration Broker Message Nodes

- Active Node
- Description
- IB Node Name
- Local Default Flag
- Local Node
- Node Type
- Non-Repudiation
- Routing Type
- Segment Aware
- Target Location
- Use External UserID
- Version

27.1.39 Integration Broker Node Connector Properties

All connector properties and values will be listed in the collection. Properties will vary based on connector type.

- Data Type Description
- Description
- Node Name
- Property ID
- Property Name
- Required Flag
- Sequence Number
- Value

27.1.40 Integration Broker Node Properties

Node Name
Node Type
Property Name
Property Value

27.1.41 Integration Broker Publication Handler Slaves Parameters

App Server Path
IB Transaction ID
Machine
Queue Name
Queue Sequence ID
Segment Index
Slave Process Name
Sub Queue
Subscribing Node

27.1.42 Integration Broker Subscription Handler Slaves

Application Server Path
IB Transaction ID
Machine
Queue Name
Queue Sequence ID
Segment Index
Slave Process Name
Sub Queue

27.2 PeopleSoft Batch Server

The configuration categories and their associated configuration items for the PeopleSoft Batch Server target type follow.

27.2.1 Active Process Server Status

These parameters will have multiple occurrences.

Application Engine Tuxedo Service
Disk Space
Master Scheduler Status
Maximum CPU Usage Required
Minimum Memory Required
Optimization Engine Tuxedo Service
Process Threshold
Server Hostname
Server Name
Sort Order
Use Application Engine Tuxedo Service

27.2.2 Batch Server Application Engine Parameters

Allowed Consecutive Service Failures
Maximum Fetch Size
Maximum Instances

Recycle Count
Scheduled Query Dirty-Read

27.2.3 Batch Server Cache Parameters

Cache Base Directory
Maximum Cache Memory

27.2.4 Batch Server Crystal Parameters

Crystal Execute Path
Trace
Trace File

27.2.5 Batch Server Data Mover Parameters

Input Directory
Last Scripts Directory
Log Directory
Output Directory

27.2.6 Batch Server Database Parameters

Enable Database Monitoring
Sybase Packet Size
Use Local Oracle Database

27.2.7 Batch Server Distribution Agent Parameters

Allowed Consecutive Service Failures
Maximum Fetch Size
Maximum Instances
Minimum Instances
Recycle Count

27.2.8 Batch Server Integration Broker Parameters

Minimum Message Size for Compression

27.2.9 Batch Server Configuration Parameters

Configuration Path
Domain
GUID
Host Name
PeopleSoft Configuration Home
State

27.2.10 Batch Server Interface Driver Parameters

SCP Locale

27.2.11 Batch Server nVision Parameters

As Of Date for Labels
Drill Down Directory

- Enable Drill Down for File
- Enable Poll Dialogs
- Instance Directory
- Layout Directory
- Macro Directory
- Poll Dialog Seconds
- Retrieve Active Tree Labels
- Save Temporary File
- Style Directory
- Template Directory
- Trace Level
- Use Excel Automation

27.2.12 Batch Server Optimization Engine Parameters

- Maximum Instances
- Optimization Maximum General Services
- Service Timeout

27.2.13 Batch Server Process Scheduler Parameters

- Allow Dynamic Changes
- Authentication Timeout
- COBOL Bin Binaries Path
- COBOL File
- Crystal Report Writer Report Path
- Database Bin
- Default Printer
- File Chunk Size
- Log Directory
- Log Fence
- Log Output Directory
- Log Space Threshold
- Maximum Reconnect Attempt
- Output Directory Optional Extension
- Process Server Name
- Reconnection Interval
- Temporary
- Tool Bin
- Tool Bin Server
- Trace-Log File Character Set
- Update Table Stats on Purge
- WinWord

27.2.14 Batch Server Remote Parameters

- Remote Call COBOL Redirect
- Remote Call COBOL Timeout

27.2.15 Batch Server SMTP Parameters

- SMTP Character Set
- SMTP Client Certificate Alias
- SMTP Client Certificate Alias 1
- SMTP Encoding DLL

- SMTP Port
- SMTP Port 1
- SMTP Send Time
- SMTP Sender
- SMTP Server
- SMTP Server 1
- SMTP Source Machine
- SMTP SSL Port
- SMTP SSL Port 1
- SMTP Trace
- SMTP Use SSL
- SMTP Use SSL 1

27.2.16 Batch Server SQR Parameters

- Enhanced HTML
- PeopleSoft SQR 1
- PeopleSoft SQR 2
- PeopleSoft SQR 3
- PeopleSoft SQR 4
- PeopleSoft SQR Flags
- Print Log
- SQR Bin

27.2.17 Batch Server Startup Parameters

- Connect ID (empty/not empty returned)
- Connect Password (empty/not empty returned)
- Database Name
- Database Type
- Server Name
- Standby DB Name
- Standby DB Type
- Standby User ID (empty/not empty returned)
- Standby User Password (empty/not empty returned)
- User ID (empty/not empty returned)
- User Password (empty/not empty returned)

27.2.18 Batch Server Tools Parameters

- Add to Class Path
- Character Set
- Database Flags
- Enable PPM Agent
- Java VM Options
- Non-proxy Hosts
- Proxy Host
- Proxy Port
- Suppress Application Error Box

27.2.19 Batch Server Trace Parameters

- Trace Application Engine
- Trace File
- Trace Option

Trace Option Mask
Trace PeopleCode
Trace PPM
Trace SQL

27.2.20 Batch Server Tuxedo Parameters

Add to Path
Grace Period
Maximum Restart Attempt
Restartable
Spawn Threshold

27.2.21 Process Scheduler Notification

Distribution ID
Distribution ID Type
Notify Disabled
Notify On Error
Notify When Down
Notify When Started
Notify When Suspended
Server Name

27.2.22 Process Scheduler Sequence Numbers

Line Sequence Number
Maximum Sequence Number
Minimum Sequence Number
Sequence Key
Sequence Number

27.2.23 Process Scheduler Server Category

Maximum Concurrent Processes
Process Category
Process Priority
Server Name

27.2.24 Process Scheduler Server Class

These parameters will have multiple occurrences.

Maximum Concurrent Processes
Operating System
Process Priority
Process Type
Server Name

27.2.25 Process Scheduler Server Operations

Day of Week
End Time
Server Name
Start Time

27.2.26 Process Scheduler System Options

- Arc Processed
- Operating System
- PT Retention Days
- Purge Next
- Purge Process Files
- Purge Recurrence Name
- Recurrence
- Retention Days
- System Load Balancing
- Version Number

27.2.27 Process Server Definition

These parameters will have multiple occurrences.

- Daemon Enabled
- Daemon Procedure Group
- Daemon Recycle Count
- Daemon Sleep Time
- Description
- Distribution Node Name
- Heartbeat
- Interval for Transfer Attempt
- Maximum API Aware Tasks
- Maximum API Unaware Tasks per Cycle
- Maximum CPU Usage Required
- Maximum Transfer Retries
- Minimum Memory Required
- Operating System
- Process Notification Required
- Redistribute Workload Option
- Server Load Balancing Option
- Server Name
- Sleep Time
- Transfer Log Files to Content
- Version

27.3 PeopleSoft Database

The configuration categories and their associated configuration items for the PeopleSoft Database target type follow.

27.3.1 Database Database Parameters

- Database Host Name
- Database Name
- Database Server Name
- Database Server Name Microsoft SQL
- Database Type
- GUID
- License Code
- License Group
- Long Name
- Maintenance Log Valid

Owner ID
PS Application Home
PeopleTools Patch Level
Product Category
Short Name
System Type
Unicode

27.3.2 Database Installation System Options

Maximum Rows to Scroll

27.3.3 Database Language Parameters

Language

27.3.4 Database Options

Language
Platform Compatibility

27.3.5 Database Patch Parameters

Database Fix By
Database Maintenance Log Type
Database Update ID

27.3.6 Database Version Parameters

PeopleTools Release
PeopleTools Release Bin
Version

27.3.7 HCM Database Info

Lcl Policy Max Aid Year

27.3.8 HCM LN XFER ID Values

Aid Year
EC TransID

27.3.9 Online Marketing Syncids

Profile Name
Sync ID

27.3.10 PTWEBSERVER Last Psswd Change

Last Password Change
Operator ID

27.3.11 Record Counts

Count
Record Name

27.3.12 Record Exclusions

Record Exclusions

27.4 PeopleSoft Web Server

The configuration categories and their associated configuration items for the PeopleSoft Web Server target type follow.

27.4.1 Web Server Configuration Parameters

- Allow Unregistered Content
- Application Server
- Audit Password (empty/not empty returned)
- Authentication Token Domain
- Authentication Token Enabled Page
- Authentication User HTTP Interval
- Browser Check
- Browser Configuration Error
- Browser Configuration Error HTML
- Browser ID Last in Database
- Browser URL
- Bypass Signon
- Cache Generated HTML
- Cache Menu on Web Server
- Cache Purge All Hit Count
- Cache Purge Stale Interval
- Cache Target Content
- Change Password on Expire (empty/not empty returned)
- Change Password on Warn (empty/not empty returned)
- Chart File System
- Chart URL
- Check for Duplicate Cookies
- Compress Cache Files
- Compress Mime Types
- Compress Query
- Compress Report Output
- Compress Report Output Netscape
- Compress Response
- Configuration Last Modified Date
- Configuration Path
- Connection Information
- Cookie Rule 0 Delete
- Cookie Rule 0 Domain
- Cookie Rule 0 Name
- Cookie Rule 0 Proxied
- Cookie Rule 0 Secure
- Cookie Rule 1 Delete
- Cookie Rule 1 Name
- Cookie Rule 1 Proxied
- Cookie Rule 1 Secure
- Cookie Rule 2 Delete
- Cookie Rule 2 Name
- Cookie Rule 2 Proxied
- Cookie Rule 2 Secure

Cookie Rule 3 Delete
Cookie Rule 3 Name
Cookie Rule 3 Proxied
Cookie Rule 3 Secure
Cookies Not Passed
Cookies Passed
Cookies Required Page
CSS File System
CSS URL
Custom Headers
Date/Time configuration.properties Last Updated
Debug Inline Java Script
Debug Inline Style Sheet
Debug Overlap
Debug Save File
Debug Show Layout
Default Port
Default Password (empty/not empty returned)
Default Scheme
Default User ID (empty/not empty returned)
Default XML Link Password (empty/not empty returned)
Default XML Link User ID (empty/not empty returned)
Delete Cookies On Logout
Description in Database
Domain Connection Password (empty/not empty returned)
Enable Browser Cache
Enable Debug Dump File
Enable New Window
Enable No Version
Enable PPM Agent
Enable Processing Wait
Enable Recent Search
Enable Recent Search on Web Server
Enable Report Repository
Enable Trace
Exception Page
Expire Page
Expire Page Content Name
Generate HTML for Testing
Help URL
Ignore Parameter Template
Image File System
Image URL
Integration Broker AS2V (empty/not empty returned)
Integration Broker FTPS Key (empty/not empty returned)
Integration Broker IG Connection
Integration Broker IG Connector AM Target Connector URL
Integration Broker IG Connector Default Remote Connect
Integration Broker IG Connector IB Target Connector
Integration Broker IG Connector Prefix
Integration Broker IG Connector SMTP Target Connector Host
Integration Broker IG Create Sequence Acks To
Integration Broker IG Default Server Localnode
Integration Broker IG DTD Lookup
Integration Broker IG Errorlog Filename

Integration Broker IG Errorlog Max Number Backup Files
Integration Broker IG Errorlog Max Size
Integration Broker IG File Connector Password (empty/not empty returned)
Integration Broker IG Generic Fault Namespace
Integration Broker IG Host
Integration Broker IG Install Directory
Integration Broker IG ISC Password (empty/not empty returned)
Integration Broker IG ISC <nodename> Password (empty/not empty returned)
Integration Broker IG ISC <nodename> Server URL
Integration Broker IG ISC <nodename> Tools Release
Integration Broker IG ISC <nodename> User ID (empty/not empty returned)
Integration Broker IG ISC Server URL
Integration Broker IG ISC Tools Release
Integration Broker IG ISC User ID (empty/not empty returned)
Integration Broker IG JMS Provider JNDI Factory MQSeries
Integration Broker IG JMS Provider JNDI Factory Weblogic
Integration Broker IG Log Background Image
Integration Broker IG Log Level
Integration Broker IG Message Log Filename
Integration Broker IG Message Log Max Number Backup Files
Integration Broker IG Message Log Max Size
Integration Broker IG Profile Information
Integration Broker IG Secure Virtual Requests
Integration Broker IG Transaction Log Directory
Integration Broker IG Version
Integration Broker IG Virtual Synchronization
Integration Broker IG WSRM Create Sequence ACK STO
Integration Broker Secure File Key Store Password (empty/not empty returned)
Integration Broker Secure File Key Store Path
Is Clustering Configured
Java Class Path
Java Home
Java Vendor
Java Version
Java Virtual Machine Information
Java Virtual Machine Name
Joltpooling
JS File System
JS URL
Logout Page
Maximum Saved State
MCF Authentication Failure Page
New Signon Session
No Default Signon For Workflow
No Exit Help
Operating System Architecture
Operating System Name
Operating System Version
Options
Pagelet Error Page
Password Expired Page
Password Warning Page
Pattern
PeopleSoft Discovery Client Name
PeopleSoft Discovery Complete

PeopleSoft Discovery Domain Name
PeopleSoft Discovery JVM ID
PeopleSoft Discovery Listener Address
PeopleSoft Discovery Listener Host
PeopleSoft Discovery Listener Port
PeopleSoft Discovery Listener Port Enabled
PeopleSoft Discovery Maximum Inactive Interval
PeopleSoft Discovery PeopleTools Release
PeopleSoft Discovery Server Information
PeopleSoft Discovery Servlet Context Name
PeopleSoft Discovery Session Cookie Domain
PeopleSoft Discovery Session Cookie Name
PeopleSoft Discovery Site Name
PeopleSoft Discovery SSL Listener Address
PeopleSoft Discovery SSL Listener Host
PeopleSoft Discovery SSL Listener Port
PeopleSoft Discovery SSL Listener Port Enabled
PeopleSoft Server
PeopleSoft Web Server Name
PeopleTools Performance Test Page URL
Physical Path
PIA Java Command Line Properties
Portal Accept Compressed Encodings
Portal Cache Home Page on Browser
Portal Cache Objects
Portal Cache Stale Interval
Portal Compress Response
Portal Debug Cache
Portal Detail Error Page
Portal Home Page Stale Interval
Portal HTTP Port
Portal HTTPS Port
Portal Servlet Session Cookie Name
Portal Target Error Page
Portal Use Cached Proxied Java Script
Portal Use HTTP for Same Server
PPM Console
PPM Monitor Buffer Size
PPM Trace
Proxied
Public Session Timeout
Redirect Page
Relative URL
Report Repository Path
Reverse Proxy (protocol, host, port, http, https)
Safemode Forced
Save Confirm Display Time
Secure
Session Time Out
Signon Error Page
Signon Page
Signon Result Document Page
Signon Trace Page
Single Thread NS
Site Cache Configured

- SSL Required
- SSL Required Page
- Start Page
- Start Page Script
- State Discard Interval
- Status Block Time Out
- Testing
- Thread Delay
- Timeout Warning Script
- Trace Monitoring Server
- Trace PPM Agent
- Tuxedo RCV Timeout
- Tuxedo Send Timeout
- Tuxnet Disconnect Timeout
- User Directory
- User ID Cookie Age
- User Profile Page
- Use Secure Cookie with SSL
- Version
- View File Title
- Warning Time Out
- Web Password (empty/not empty returned)
- Web Profile
- Web Profile Name
- Web Server Command Line
- Web Server Jolt Settings
- Web User ID
- XML Link Use HTTP for Same Server

27.4.2 Web Server Information Parameters

- Application Directory
- Cell Node Server
- Configuration Path
- Domain
- Dynamic Configuration Reload
- GUID
- Host Name
- OBIEE Servers
- Parallel Loading
- Site
- State

Primavera Collections

The Primavera collections include the following:

28.1 APPLICATION_GENERAL

- AllowAutoSummarizeOption
- BuildId
- CompressAppletComm
- CompressHtml
- EnableXSSFilter
- IgnoreDST

28.2 APP_LIMITS

- ExcelImportMaxFileSize
- ExcelImportMaxTrans
- MaxActionCodeValues
- MaxActsPerActView
- MaxAppletMemory
- MaxMRUListItems
- MaxPortletsPerDashboard
- MaxProjectActivityCodes
- MaxProjectsInPortfolio
- MaxProjsPerPortfView
- MaxRPSpreadsheetProjs

28.3 AUTHENTICATION

- AuthMode
- ContextPathOverride
- ServerAndPortOverride
- UserNameHeaderKey

28.4 CONNPOOL

- DbId
- DBName
- ConnectionPool_Type
- PMR_FetchSize
- PMR_LeaseRequestWaitTimeout
- PMR_MaintenanceFrequency

PMR_MaxConnections
PMR_MaxLeaseDuration
PMR_RenewableFreeLimit
PMR_RenewableLeases
PMR_ResizeRate
PMR_TraceSQL

28.5 DATA_LIMITS

dbId
DBName
MaxActCodesPerProject
MAXactivityCodeTreeLevels
MaxActivityIDLength
MaxBaselinesPerProject
MaxCostAcctTreeLevels
MaxCostAccountIDLength
MAXEPSTreeLevels
MaxOBSTreeLevels
MAXProjectCodeTreeLevels
MaxProjectIDLength
MAXResourceCodeTreeLevels
MaxResourceIDLength
MaxResourceTreeLevels
MaxRoleIDLength
MaxRoleTreeLevels
MaxRSRCTreeLevels
MaxTSResourceHourFlag
MaxTimesheetResourceHours
MaxWBSCodeLength
MaxWBSTreeLevels

28.6 DBSESSION

DbId
DBName
SessionSettings_Setting1
SessionSettings_Setting2
SessionSettings_Setting3
SessionSettings_Setting4
SessionSettings_Setting5

28.7 DB_CONNECTION

DbId
DBName
Description
PublicGroupId
URL

28.8 DOC_REPOSITORY

DbId
DBName

EnableConnectionPooling
MaxConnections
URL

28.9 EARNEDVALUEPREFS

dbId
DBName
EVCalculation
EvComputeType
EvEtcComputeType
EvEtcUserValue
EvUserPct

28.10 EMAIL_NOTIFICATIONS

InitiationNotifications
InvitationNotifications
IssueNotifications
NotifFromEmailOverride

28.11 GROUP_SERVER

DbId
DBName
GroupServer_Port
GroupServer_Protocol
GroupServer_Server
GroupServer_URL

28.12 JAVA_OS

java_class_path
java_library_path
java_vm_name
java_vm_version
os_arch
os_name
os_version

28.13 JAVA_PLUGIN

JavaPluginURL_FF
JavaPluginURL_IE
JavaPluginVersionID_FF
JavaPluginVersionID_IE
JnlpJreVersion

28.14 LOGSETTINGS

Asynchronous
ConsoleLoggerEnabled
ConsoleLoggerSevLvl

EmailLoggerEnabled
EmailLoggerSubject
FileLoggerArchiveNum
FileLoggerEnabled
FileLoggerHTML
FileLoggerLogFileSize
FileLoggerSeverityLevel

28.15 PERFMON

PerfMonEnabled
PerfMonMonitorHost
PerfMonMonitorPort
PerfMonUpdateInterval

28.16 PREFS_OTHER

BaselineUseAtCompletionValue
BLUseBudgetValWithPlanDate
CompletedActTimeWindow
CurrencyId
DatabaseVersion
dbId
DBName
EnablePasswordPolicy
ExpeditionRootUrl
IncExpensesInEVFlag
NonlaborIsMaterial
PreferencesFromSettingsTable
ProjArchEnabledFlag
SummarizeByCalendar
SummByFinancialPeriods
TasksrcSumPeriodType
TaskSumPeriodTyp

28.17 SERVICES

SvcAsynchJobsGraceTime
SvcAsynchJobsPurgeInterval
SvcCollabSyncSvcSynItvl
SvcConfigMgmtColEbl
SvcConfigMgmtCollTime
SvcLicenseSvcExpCheckRate
SvcLicenseSvcUpdateRate
SvcMailSvcMaxQueueLength
SvcMailSvcSendInterval
SvcMailSvcSmtpport
SvcNextKeySvcMaxCacheKys
SvcNextKeyServiceRefRate
SvcPerfMaxSummNodeCnt
SvcPerfUseEntpSumm
SvcPrdPerfConcThreads
SvcPrdPerfEnabled
SvcPrdPerfExecutionItvl

SvcProjHchyCacheLmt
 SvProjHchyCachePolicy
 SvcProjHchyCacheMaintFreq
 SvcRegSvePort
 SvcRgeSveRefreshRate
 SvcRegSveStalePeriod
 SSAThisPrdCoreThreads
 SSAThisPrdEnabled
 SSAThisPrdExecIntvl
 SvcTimestampSvcRefreshRate
 SvcWebSchedActSchedMode
 SvcWebSchedASAPCleanupRate
 SvcWebSchedConcSched
 SvcWebSchedEnabaled
 SvcWebSchedSchedulingIntvl

28.18 THREADPOOL

MaintFreq
 MaxTaskDuration
 LRMaxTaskDurationLR
 NumThreads

28.19 TIMESHEET_CONNECTION

TimesheetCodebase
 TimesheetURL

28.20 TIMESHEET_OPTS

dbId
 DBName
 LogCompletedActFlag
 LogFutureTSFlag
 LogHrsAfter ActFinishFlag
 LogHrsBeforeActStartFlag
 LogNotStartedActFlag
 DefaultTSApprovalMgr
 Level2TSApprovalOrder
 EnableTSAudit
 TSHourDigits
 TimesheetDailyFlag
 TSApprovalLevels
 ResourceUseTSFlag
 RsrcSelfAddFlag
 NotStartedActTimeWindow
 PastTimesheetPeriods
 AllowUserTimePeriodFlag

28.21 TRACER

TracerEnabled
 TracerServerName
 TracerSocketPort

28.22 USERSECURITY

DbId
DBName
AllowMultiSessionUser
LogLoginAttempts
LoginLockoutCount
LoginLockoutDuration

28.23 WORKFLOW_REPOSITORY

DbId
DBName
WRep_ConnectionTestPeriod
WRep_EnableConnectionPooling
WRep_MaxConnections
WRep_Timeout

28.24 WORKTIME_DATE

dbId
DBName
ActivityDefaultDuration
WeekStartDay
HoursPerDay
HoursPerMonth
HoursPerWeek
HoursPerYear

Siebel Collections

The Siebel collections include the following:

29.1 Siebel Component

The configuration categories and their associated configuration items for the Siebel Component target type follow.

Note: The relationship between the deployment of a Siebel Server and dependent database is collected only for Oracle database.

29.1.1 Siebel Component Configuration

This metric captures details for the Siebel Component Configuration in parameter pairs of Property Name and Property Value. Not all Siebel components contain the same set of parameters so the actual output may vary from one component to another. For example, an Application Object Manager (AOM) component may have different parameters than a Transaction Router component. This generic pairing of Property Name and Property Value allows for any parameter to be captured for all Siebel components.

Following is an example of parameter pairs for the SCCObjMgr_enu component:

Property Name	Property Value
datasource	ServerDataSrc
host	sdchpi01
maxtasks	500
maxmtservers	10
SIEBEL_ENTERPRISE	sia80
SIEBEL_COMPNAME	SCCObjMgr_enu

29.2 Siebel Component Group

The configuration categories and their associated configuration items for the Siebel Component Group target type follow.

29.2.1 Siebel Component Group Configuration

This metric captures details for the Siebel Component Group Configuration in parameter pairs of Property Name and Property Value. This is similar in nature to the Siebel Component Configuration, however the Component Groups will have the same Property Names for all groups (though the Property Values may be different). A Component Group Configuration is not the same as a Siebel component definition, although some of the same parameter names may appear.

Following is an example of parameter pairs for the Call Center component group:

Property Name	Property Value
SIEBEL_COMPGROUP	CallCenter
SIEBEL_ENTERPRISE	sia80
SIEBEL_GATEWAY	sdcp520a001

29.3 Siebel Enterprise

The configuration categories and their associated configuration items for the Siebel Enterprise target type follow.

29.3.1 Siebel Enterprise Configuration

This metric captures details for the Siebel Enterprise Configuration in parameter pairs of Property Name and Property Value. The Property Names are parameters that are appropriate for or affect the entire Siebel Enterprise. This would include Siebel Enterprise parameters as well as Siebel Named Subsystems. Named Subsystem Property Names are in the format of:

SubSys_<datasrc><parameter>

where

<datasrc> is the Siebel data source name, and

<parameter> is the parameter name in that Siebel data source

Following is an example of parameter pairs for a Siebel Enterprise:

Property Name	Property Value
filesystem	vol1/sia80ora/siebsrvr/fs
secadptmode	DB
secadptname	DBSecAdpt
SIEBEL_GATEWAY	sdchpi01
SubSys_DBSecAdptdatasourcename	ServerDataSrc
SubSys_GatewayDataSrcdsconnectstring	sdchpi01:3220
SubSys_ServerDataSrcdsmaxcursorsize	-1
tableowner	usia05

29.3.2 Siebel Upgrade

This metric represents a list and history of all Fix Packs and Quick Fixes that have been applied to the Siebel system. The upgrade.txt file that contains this information is located in the \$SIEBEL_HOME directory and the data present in this file is collected using Perl file siebel_upgrade.pl.

UPGRADE_NUMBER	ACTION	FIX_PACK_VERSION	QUICK_FIX	DATA_TIME
1	INSTALLED	7.8.2.16	Not Applicable	Wed Feb 02 11:04:53 GMT-07:00 2011
2	INSTALLED	7.8.2.16	QFTEST	Wed Feb 09 11:04:53 GMT-07:00 2011

29.4 Siebel Gateway

The configuration categories and their associated configuration items for the Siebel Gateway target type follow.

29.4.1 Siebel Gateway Configuration

This metric captures details for the Siebel Gateway Configuration in parameter pairs of Property Name and Property Value. The Property Names are parameters that are appropriate for or affect the Siebel Gateway.

Following is an example of parameter pairs for a Siebel Gateway:

Property Name	Property Value
host	sdchpi01
SIEBEL_GATEWAY	sdchpi01

29.5 Siebel Server

The configuration categories and their associated configuration items for the Siebel Server target type follow.

29.5.1 Siebel Server System Configuration

This metric captures details for the Siebel Server System Configuration in parameter pairs of Property Name and Property Value. The Property Names gathered for this section contains the Siebel server parameter names while the Property Values are those specific to the settings for this Siebel server.

Following is an example of parameter pairs for a Siebel Server System Configuration:

Property Name	Property Value
host	sdchpi01
logdir	/vol1/sia80ora/siebsrvr/enterprises/sia80/srvr1/log
rootdir	/vol1/sia80ora/siebsrvr
SIEBEL_ENTERPRISE	sia80
SIEBEL_SERVER	srvr1

29.5.2 Siebel Server General Configuration

This metric captures details for the Siebel Server General Configuration in parameter pairs of Property Name and Property Value. The Property Names gathered for this section are not necessarily Siebel server parameter settings, but could contain applicable details for the Siebel server which might be found in other files on the server (such as base.txt). These Property Names would be associated with their corresponding Property Values.

Following is an example of parameter pairs for a Siebel Server General Configuration:

Property Name	Property Value
Base File Contents	8.0.0.2 SIA [20412] LANG_INDEPENDENT
Enabled Languages	enu;fra;

SOA Infrastructure Collections

The Service-Oriented Architecture (SOA) Infrastructure collections include the following:

30.1 Instance Information

Version

User Messaging Service Collections

The User Messaging Service collections include the following:

31.1 User Messaging E-Mail Driver

ECM Associations
J2EE Application Config
Target Version

31.2 User Messaging Proxy Driver

ECM Associations
J2EE Application Config
Target Version

31.3 User Messaging Service

ECM Associations
J2EE Application Config
Target Version

31.4 User Messaging SMPP Driver

ECM Associations
J2EE Application Config
Target Version

31.5 User Messaging VoiceXML Driver

ECM Associations
J2EE Application Config
Target Version

31.6 User Messaging Worklist Driver

ECM Associations
J2EE Application Config
Target Version

31.7 User Messaging XMPP Driver

ECM Associations
J2EE Application Config
Target Version