

Oracle Endeca Commerce

Tools and Frameworks Installation Guide

Version 11.0 • January 2014



Contents

- Preface.....7**
 - About this guide.....7
 - Who should use this guide.....7
 - Conventions used in this guide.....7
 - Contacting Oracle Support.....8

- Chapter 1: Before You Install.....9**
 - About Oracle Endeca Tools and Frameworks.....9
 - Supported operating systems and Web browsers.....9
 - Endeca software requirements.....9

- Chapter 2: Installing Oracle Endeca Tools and Frameworks.....11**
 - Setting the Endeca environment variables.....11
 - Installing Oracle Endeca Tools and Frameworks on Windows.....11
 - Creating the Endeca Tools Service.....12
 - Configuring the Endeca Tools Service to run under an endeca user.....13
 - Starting and stopping the Endeca Tools Service on Windows.....14
 - Running Oracle Endeca Tools and Frameworks from the included batch files.....14
 - Installing Oracle Endeca Tools and Frameworks silently on Windows.....15
 - Installing Oracle Endeca Tools and Frameworks on UNIX.....15
 - Starting the Workbench process automatically on UNIX.....17
 - Starting and stopping the Workbench process on UNIX.....17
 - Installing Oracle Endeca Tools and Frameworks silently on UNIX.....18
 - Package contents.....19
 - Troubleshooting Oracle Endeca Tools and Frameworks.....21

- Chapter 3: Deploying a Reference Application.....23**
 - About the Discover Electronics reference application.....23
 - About multichannel support23
 - Deploying the Discover Electronics reference application using Forge.....24
 - Deploying the Discover Electronics reference application using CAS.....25
 - Verifying your Tools and Frameworks configuration.....26
 - About logging and reporting in the reference application.....27

- Chapter 4: Uninstalling Oracle Endeca Tools and Frameworks.....29**
 - Uninstalling a deployed application.....29
 - Uninstalling Oracle Endeca Tools and Frameworks on Windows.....29
 - Uninstalling Oracle Endeca Tools and Frameworks silently on Windows.....30
 - Uninstalling Oracle Endeca Tools and Frameworks on UNIX.....31
 - Uninstalling Oracle Endeca Tools and Frameworks silently on UNIX.....32

- Appendix A: Endeca Tools Service Scripts.....33**
 - Endeca Tools Service scripts.....33

- Appendix B: Endeca Tools Service and EAC Ports Reference.....35**
 - About the Endeca Tools Service ports.....35
 - Changing the Endeca Tools Service port.....35
 - Changing the Endeca Tools Service Promotion port.....36
 - Changing the Endeca Tools Service SSL port.....37
 - Changing the Endeca Tools Service shutdown port.....37
 - Updating Workbench to use non-default EAC settings.....38

- Appendix C: Communicating with the MDEX Engine.....39**
 - Setting up a cross-domain policy file.....39
 - Updating Assembler host configuration.....40

Copyright and disclaimer

Copyright © 2003, 2014, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Preface

Oracle Endeca Commerce is the most effective way for your customers to dynamically explore your storefront and find relevant and desired items quickly. An industry-leading faceted search and Guided Navigation solution, Oracle Endeca Commerce enables businesses to help guide and influence customers in each step of their search experience. At the core of Oracle Endeca Commerce is the MDEX Engine™, a hybrid search-analytical database specifically designed for high-performance exploration and discovery. The Endeca Content Acquisition System provides a set of extensible mechanisms to bring both structured data and unstructured content into the MDEX Engine from a variety of source systems. Endeca Assembler dynamically assembles content from any resource and seamlessly combines it into results that can be rendered for display.

Oracle Endeca Experience Manager is a single, flexible solution that enables you to create, deliver, and manage content-rich, cross-channel customer experiences. It also enables non-technical business users to deliver targeted, user-centric online experiences in a scalable way — creating always-relevant customer interactions that increase conversion rates and accelerate cross-channel sales. Non-technical users can determine the conditions for displaying content in response to any search, category selection, or facet refinement.

About this guide

This guide contains installation instructions for setting up Oracle Endeca Tools and Frameworks on Windows, Linux, Solaris, and UNIX.

Who should use this guide

This guide is intended for users installing Oracle Endeca Tools and Frameworks on Windows, Linux, Solaris, or UNIX.



Note: Unless otherwise indicated, whenever this document specifies UNIX, it applies to Linux and Solaris.

Conventions used in this guide

This guide uses the following typographical conventions:

Code examples, inline references to code elements, file names, and user input are set in `monospace` font. In the case of long lines of code, or when inline monospace text occurs at the end of a line, the following symbol is used to show that the content continues on to the next line: ~

When copying and pasting such examples, ensure that any occurrences of the symbol and the corresponding line break are deleted and any remaining space is closed up.

Contacting Oracle Support

Oracle Support provides registered users with important information regarding Oracle Endeca software, implementation questions, product and solution help, as well as overall news and updates.

You can contact Oracle Support through Oracle's Support portal, My Oracle Support at <https://support.oracle.com>.

Chapter 1

Before You Install

This section provides an overview of Oracle Endeca Tools and Frameworks, including system requirements, package contents, and other information that you need to know before installing.

About Oracle Endeca Tools and Frameworks

Oracle Endeca Tools and Frameworks enable the dynamic presentation of content across all channels.

Deployments that use Oracle Endeca Experience Manager require the Tools and Frameworks package for Oracle Endeca Commerce with Experience Manager. Deployments that do not include Experience Manager require the Tools and Frameworks package for Oracle Endeca Commerce with Guided Search.

Both versions of the package include the following:

- Oracle Endeca Workbench, a tools suite that enables merchandising, Content Spotlighting, and search configuration for cross-channel applications
- The Endeca Assembler, an API for controlling the presentation of commerce sites and collecting usage information across all channels
- The Endeca Tools Service
- The Endeca Deployment Template, a collection of operational components that provides a starting point for developing and deploying Endeca applications.
- The Discover Electronics reference application

Supported operating systems and Web browsers

See *Oracle Endeca Commerce Supported Environments and Compatibility* on the Oracle Technology Network for information on supported operating systems and Web browsers.

Endeca software requirements

This section lists the Endeca components that must be installed on your machine prior to installing the Tools and Frameworks.

The Oracle Endeca Tools and Frameworks require the following Endeca components:

- MDEX Engine

- Platform Services

To determine the compatibility of your Endeca components, see *Oracle Endeca Commerce Supported Environments and Compatibility*, available on the Oracle Technology Network.

Chapter 2

Installing Oracle Endeca Tools and Frameworks

This section describes how to install Oracle Endeca Tools and Frameworks on your machine. The steps in this guide are based on all Endeca components being installed on the same machine.

Setting the Endeca environment variables

Before you install Oracle Endeca Tools and Frameworks, you must set the `ENDECA_TOOLS_ROOT` and `ENDECA_TOOLS_CONF` environment variables.

To set the environment variables:

1. Set `%ENDECA_TOOLS_ROOT%` (`$ENDECA_TOOLS_ROOT` on UNIX) to your Tools and Frameworks installation directory.
By default, this is `C:\Endeca\ToolsAndFrameworks\<version>` on Windows, or `/usr/local/endeca/ToolsAndFrameworks/<version>` on UNIX.
2. Set `%ENDECA_TOOLS_CONF%` (`$ENDECA_TOOLS_CONF` on UNIX) to your Tools and Frameworks workspace directory.
By default, this is `C:\Endeca\ToolsAndFrameworks\<version>\server\workspace` on Windows, or `/usr/local/endeca/ToolsAndFrameworks/<version>/server/workspace` on UNIX.

Installing Oracle Endeca Tools and Frameworks on Windows

To install Oracle Endeca Tools and Frameworks, extract the ZIP archive to your Endeca directory and install the software.

To install the Oracle Endeca Tools and Frameworks:

1. If you have an earlier version of Oracle Endeca Tools and Frameworks, follow the steps in [Uninstalling Oracle Endeca Tools and Frameworks on Windows](#) on page 29 to remove it before installing the Tools and Frameworks.
2. In your local environment, locate the Endeca Tools and Frameworks software that you downloaded from the Oracle Software Delivery Cloud.
3. Extract the Tools and Frameworks package to a local directory.
4. Navigate to the `\cd\Disk1\install` directory and double-click the `setup.exe` installer file to start the wizard.

The Welcome screen displays.

5. Click **Next** to begin the installation process.
6. Read the License Agreement and click **I accept the License Terms and Export Restrictions**.
7. If this is the first product that you have installed on this machine using the Oracle Universal Installer, the Specify Inventory directory screen appears. Specify the directory where the Oracle Universal Installer should place inventory files and directories. Oracle recommends that you accept the default path.

The Installer uses the Oracle Inventory directory to store inventory information in files and subdirectories. This directory contains permanent and product specific files. Ensure that the files in this folder are not deleted or modified, as this would make patching or upgrading impossible.

Click **Next**

8. Choose the installation type, and click **Next**.
The **Complete Installation** includes the reference application; the **Minimal Installation** does not.
9. Specify a name and a path where you want to install Tools and Frameworks. Oracle recommends `C:\Endeca\ToolsAndFrameworks` as your path. This is the path that Oracle refers to as your default path throughout the Oracle Endeca Commerce documentation.

Click **Next**.



Note: If you are reinstalling Tools and Frameworks and you receive a message that the name is in use, click **Installed Products** and remove the previous instance of the name from your Oracle Inventory.

10. Enter an *admin* password and confirm the password.
The admin user is the default administrator user for Tools and Frameworks.

Click **Next**

11. When the Summary screen appears, click **Install**.
12. When the End of Installation screen appears, click **Exit**.

After installing Tools and Frameworks, you must create and configure the Endeca Tools Service, or alternately run the Tools and Frameworks from the included batch files.

Related Links

[About the Endeca Tools Service ports](#) on page 35

You can change the default ports for the Endeca Tools Service, as long as you choose a new port that is not being used.

[Creating the Endeca Tools Service](#) on page 12

You can choose to run the Tools and Frameworks as a Windows service.

[Running Oracle Endeca Tools and Frameworks from the included batch files](#) on page 14

If you do not wish to create the Endeca Tools Service, you can start or stop the Tools and Frameworks directly by running the included batch files.

Creating the Endeca Tools Service

You can choose to run the Tools and Frameworks as a Windows service.

Before starting the Endeca Tools Service, Endeca recommends creating an "endeca" user for whom you can control permissions, and modifying your Endeca Tools Service to run under that user. The user running `install_service.bat` and the Endeca Tools Service must have administrator privileges.

To create the Endeca Tools Service:

1. Navigate to your Endeca installation directory.
By default, this should be `C:\Endeca\ToolsAndFrameworks\<version>`.
2. Install the Endeca Tools Service by running `server\bin\install_service.bat`.
This creates the Endeca Tools Service and configures it to run under the current user profile.

After you have created the Endeca Tools Service, you must configure it to run under the `endeca` user.



Note: By default, Workbench runs on port 8006 of your machine. If port 8006 is unavailable on your machine, you must change this to a different port. Additionally, if you are not running the Endeca Application Controller on `localhost:8888`, you must update the EAC configuration for Workbench.

Related Links

[Updating Workbench to use non-default EAC settings](#) on page 38

If the Endeca Application Controller is not running at the default location of `localhost:8888`, you must update this information in the `%ENDECA_TOOLS_CONF%\conf\webstudio.properties` file (`$ENDECA_TOOLS_CONF/conf/webstudio.properties` on UNIX).

[Endeca Tools Service Scripts](#) on page 33

This section covers the Endeca Tools Service scripts.

[Endeca Tools Service and EAC Ports Reference](#) on page 35

This section covers the steps required to change the Endeca Tools Service and EAC ports from the default values.

Configuring the Endeca Tools Service to run under an `endeca` user

You can modify the Endeca Tools Service to run under a designated `endeca` user, rather than using the current user profile.

Once you have initialized your Endeca Tools Service you can create a new user and configure the service to run under that user. Doing so automatically grants the user permission to log on as a service.

Oracle recommends that you create a user account called `endeca` that has the proper file and directory permissions to access all necessary files for your application, and that you set up your Endeca Tools Service to run under this account. However, you can use any user that you prefer, as long as it meets these requirements.

To configure the Endeca Tools Service to run under an `endeca` user:

1. Create an `endeca` user:
 - a) Ensure that you have administrator privileges on the local machine.
 - b) Go to **Start > Administrative Tools > Computer Management > System Tools > Local Users and Groups > Users**.
 - c) Right click and select **New User...**
 - d) Create an Administrator user named `endeca`.



Important: To run the Endeca Tools service under the `endeca` user, you must set a password for the user.

2. Configure the Endeca Tools Service to run under the `endeca` user:
 - a) Go to **Start > Control Panel > Administrative Tools > Services**.

- b) In the **Windows Services** editor, select the **Endeca Tools Service**.
 - c) From the Endeca Tools Service, right-click and select **Properties** from the drop-down menu. The **Endeca Tools Service Properties** window appears.
 - d) Switch to the **Log On** tab.
 - e) Select the **This account:** radio button.
 - f) Enter `endeca` in the **This account:** field and the password you set for the `endeca` user in the **Password:** and **Confirm Password:** fields.
A dialog box appears, notifying you that the `endeca` user has been given service permissions.
 - g) Click **OK** to close the dialog box.
 - h) Click **OK** to save your changes to the Endeca Tools Service.
3. Start the Endeca Tools Service.

After you have configured the Endeca Tools Service, you can provision the Discover Electronics reference application using the Deployment Template.

Starting and stopping the Endeca Tools Service on Windows

Once you have created the Endeca Tools Service, it starts automatically when you boot up Windows. You must stop and later restart the service to make certain modifications to your Tools and Frameworks installation.

When you first install the service, you must manually start it. Afterwards, the service is set to start up automatically when the computer boots up.

To manage the Endeca Tools Service after installation:

1. Go to **Start > Control Panel > Administrative Tools > Services**.
2. In the **Windows Services** editor, select the **Endeca Tools Service**.
3. Click **Stop** or **Restart**.

Running Oracle Endeca Tools and Frameworks from the included batch files

If you do not wish to create the Endeca Tools Service, you can start or stop the Tools and Frameworks directly by running the included batch files.



Note: For any topics that refer to starting or stopping the Endeca Tools Service, run the corresponding batch script instead.

To start or stop the Tools and Frameworks from the included batch files:

1. Navigate to your Endeca installation directory.
By default, this should be `C:\Endeca\ToolsAndFrameworks\<version>`.
2. Navigate to the `server\bin` directory.
3. To start the Tools and Frameworks, run `run.bat`.
This script sets the Endeca environment variables in the current command window and initializes the Apache Tomcat Web server, with Workbench running on `localhost:8006`.
4. To stop the Tools and Frameworks, run `stop.bat`.
This script shuts down the Apache Tomcat Web server.

Once the Tools and Frameworks are running, you can provision the Discover Electronics reference application using the Deployment Template.



Note: By default, Workbench runs on port 8006 of your machine. If port 8006 is unavailable on your machine, you must change this to a different port. Additionally, if you are not running the Endeca Application Controller on `localhost:8888`, you must update the EAC configuration for Workbench.

Installing Oracle Endeca Tools and Frameworks silently on Windows

The silent installer is useful if you want to add the Tools and Frameworks installation to an install script, or push out the installation on multiple machines.

The syntax to run the silent installation is the following:

```
silent_install.bat <FULL_PATH_TO_RESPONSE_FILE> <ORACLE_HOME_NAME> <ORACLE_HOME_LOCATION> <ADMIN_USER_PASSWORD>
```

where the options have the following values. Note that all the options are required.

Option	Description
FULL_PATH_TO_RESPONSE_FILE	The full path to response file which is used by the silent installer. For example, <code>C:\Users\myname\Documents\ToolsAndFrameworks-version-win64-xmgr-installer\cd\Disk1\install\silent_response.rsp</code> .
ORACLE_HOME_NAME	A string value which represents your ORACLE_HOME. For example <code>ToolsandFrameworks</code>
ORACLE_HOME_LOCATION	The location where you would like to install the product. For example, <code>C:\Endeca\ToolsAndFrameworks</code> .
ADMIN_USER_PASSWORD	This is the password that the admin uses to log in to Workbench.

Before you begin, review and the `install\silent_response.rsp` file in a text editor. All the settings in the file are optional.

To start the silent installer

1. From a command prompt, navigate to the directory where you downloaded the installer.
2. Issue the `silent_install.bat` command and specify all the options described above.

Example

```
silent_install.bat C:\Users\mine\Documents\ToolsAndFrameworks-11.0.0-win64-xmgr-installer\cd\Disk1\install\silent_response.rsp toolsandframeworks c:\Endeca\ToolsAndFrameworks admin
```

Installing Oracle Endeca Tools and Frameworks on UNIX

To install Oracle Endeca Tools and Frameworks, extract the package to your Endeca directory and run the included `runinstaller` script.

If you have an earlier version of Oracle Endeca Tools and Frameworks, you must follow the steps in the *Oracle Endeca Tools and Frameworks Installation Guide* to remove it before installing the latest version.

To install Oracle Endeca Tools and Frameworks:

1. Download the Tools and Frameworks package from the Oracle Software Delivery Cloud.
2. Extract the Tools and Frameworks package to a local directory.
3. Navigate to the `/cd/Disk1/install` directory.



Note: Verify that the files have executable permissions.

4. Run `runinstaller.sh`.
The Welcome screen displays.
5. Click **Next** to begin the installation process.
6. Read the License Agreement and click **I accept the License Terms and Export Restrictions**.
7. If this is the first product that you have installed on this machine using the Oracle Universal Installer, the Specify Inventory directory screen appears.
 - a) Specify the directory where the Oracle Universal Installer should place inventory files and directories. Oracle recommends that you accept the default path.

The Installer uses the Oracle Inventory directory to store inventory information in files and subdirectories. This directory contains permanent and product specific files. Ensure that the files in this folder are not deleted or modified, as this would make patching or upgrading impossible.
 - b) Specify the UNIX group name that should own the base directory.
You must specify a UNIX group name that has permission to update, install, and deinstall Oracle software. Members of this group must have write permissions to the base directory chosen.
 - c) Click **Next**
8. Choose the installation type, and click **Next**.
The **Complete Installation** includes the reference application; the **Minimal Installation** does not.
9. Specify a name and a path where you want to install Tools and Frameworks. Oracle recommends `/usr/local/endeca/ToolsAndFrameworks` as your path. This is the path that Oracle refers to as your default path throughout the Oracle Endeca Commerce documentation.

Click **Next**.



Note: If you are reinstalling Tools and Frameworks and you receive a message that the name is in use, click **Installed Products** and remove the previous instance of the name from your Oracle Inventory.

10. Enter an *admin* password and confirm the password.
The admin user is the default administrator user for Tools and Frameworks.

Click **Next**
11. When the Summary screen appears, click **Install**.
12. When the End of Installation screen appears, click **Exit**.



Note: If you receive a warning that a new inventory has been created but not yet registered, then you must register the new inventory. Run the `/myname/oraInventory/orainstRoot.sh` script with root privileges. If you do not register the inventory, you might not be able to update or patch the

products you installed or uninstall Tools and Frameworks silently. Run the script as the `root` user or using `sudo` with permissions to run the file.

13. Navigate to the `server/bin` directory.

14. Run `startup.sh`.

This script sets the environment variables for your Tools and Frameworks installation and initializes the Apache Tomcat Web server, with Workbench running on `localhost:8006` as a background process.

To manage the Workbench process after installation:

- Start the Workbench process with the `startup.sh` script.
- Stop the Workbench process with the `shutdown.sh` script.

Once the Tools and Frameworks are running, you can provision the Discover Electronics reference application using the Deployment Template.



Note: By default, Workbench runs on port 8006 of your machine. If port 8006 is unavailable on your machine, you must change this to a different port. Additionally, if you are not running the Endeca Application Controller on `localhost:8888`, you must update the EAC configuration for Workbench.

Related Links

[About the Endeca Tools Service ports](#) on page 35

You can change the default ports for the Endeca Tools Service, as long as you choose a new port that is not being used.

[Starting the Workbench process automatically on UNIX](#) on page 17

In a UNIX development environment, the Workbench process can be started from the command line. In a UNIX production environment, however, Oracle recommends configuring the included `workbench-init.d.sh` script to start Workbench automatically.

Starting the Workbench process automatically on UNIX

In a UNIX development environment, the Workbench process can be started from the command line. In a UNIX production environment, however, Oracle recommends configuring the included `workbench-init.d.sh` script to start Workbench automatically.

To start the Workbench process automatically on UNIX:

1. Navigate to the `server/bin` directory within your Tools and Frameworks installation directory.
By default, this is `/usr/local/endeca/ToolsAndFrameworks/<version>/server/bin`.
2. Open the `workbench-init.d.sh` script.
3. Follow the instructions within the script to configure it for your environment.

Starting and stopping the Workbench process on UNIX

You must stop and later restart the Workbench process to make certain modifications to your Tools and Frameworks installation.

You must configure the `workbench-init-d.sh` script before using the commands outlined below.

When using the following commands, you may be prompted to enter the password for the system user that Workbench runs under.

- Start the Workbench process with the following command:
`/sbin/service workbench start`
- Stop the Workbench process with the following command:
`/sbin/service workbench stop`

Installing Oracle Endeca Tools and Frameworks silently on UNIX

The silent installer is useful if you want to add the Tools and Frameworks installation to an install script, or push out the installation on multiple machines.

The syntax to run the silent installation is the following:

```
silent_install.sh <FULL_PATH_TO_RESPONSE_FILE> <ORACLE_HOME_NAME> <ORACLE_HOME_LOCATION> <ADMIN_USER_PASSWORD>
```

where the options have the following values. Note that all the options are required.

Option	Description
FULL_PATH_TO_RESPONSE_FILE	The full path to response file which is used by the silent installer. For example, <code>/localdisk/myname/cd/Disk1/install/silent_response.rsp</code> .
ORACLE_HOME_NAME	A string value which represents your ORACLE_HOME. For example <code>ToolsandFrameworks</code>
ORACLE_HOME_LOCATION	The location where you would like to install the product. For example, <code>/usr/local/endeca/ToolsAndFrameworks</code> .
ADMIN_USER_PASSWORD	This is the password that the admin uses to log in to Workbench.

Before you begin, review the `install/silent_response.rsp` file in a text editor. Only `UNIX_GROUP_NAME` is required. You can accept the default value as `dba` or replace it with a value of your own.

To start the silent installer

1. From a command prompt, navigate to the directory where you downloaded the installer.
2. Issue the `silent_install.sh` command and specify all the options described above.

Example

```
silent_install.sh /localdisk/myname/cd/Disk1/install/silent_response.rsp  
ToolAndFrameworks /usr/local/endeca/ToolsAndFrameworks admin
```

If you receive a warning that a new inventory has been created but not yet registered, then you must register the new inventory. Run the `/myname/oraInventory/orainstRoot.sh` script with root privileges. If you do not register the inventory, you might not be able to update or patch the products you installed or uninstall Tools and Frameworks silently. Run the script as the `root` user or using `sudo` with permissions to run the file.

Package contents

Oracle Endeca Tools and Frameworks are available for both Oracle Endeca Guided Search and Oracle Endeca Experience Manager.

Core package components

Both distribution packages contain the following resources on Windows and UNIX:

File / Directory	Contents
admin/bin	Contains batch or shell scripts for running Workbench administration tasks such as importing and exporting users.
admin/conf	Contains configuration files for Workbench administration scripts.
admin/lib	Contains libraries to support the Workbench administration scripts.
admin/logs	Contains logs that are generated from running Workbench administration scripts.
assembler/apidoc	Contains the <i>Endeca Assembler API Reference (Javadoc)</i> .
assembler/lib	Contains the Assembler and its dependencies, including the URL Optimization API for Java.
config_import_api/apidoc	Contains the <i>Endeca Configuration Import API Reference (Javadoc)</i> .
config_import_api/lib	Contains the Endeca Configuration Import API.
credential_store/bin	Contains scripts for creating and maintaining credentials using Oracle Platform Security Services.
credential_store/lib	Contains libraries to support Oracle Platform Security Services.
deployment_template	Contains the Deployment Template and accompanying API References (Javadoc).
migration/lib	Contains libraries to support the Workbench migration script.
migration/workbench	Contains the Workbench migration script (<code>migrate_workbench</code>), a configuration file for the script, and a configuration file that specifies log-level settings for the migration operations.
reference/cookbook	Contains sample code and documentation for implementing advanced Oracle Endeca Commerce features in the Discover Electronics reference application.
reference/discover-data	Contains the data and Endeca application configuration for the Discover Electronics reference application. This

File / Directory	Contents
	application is configured to process the source data using Forge.
reference/discover-data/cartridge_templates	Reference application templates designed to enable content administrators to configure pages for applications.
reference/discover-data/ifcr	Sample content for the reference application.
reference/discover-data-catalog-integration	Contains data and Endeca application configuration for the Deployment Template Module for Product Catalog Integration. This application integrates data records, dimension values, precedence rules, and schema information from product catalog systems into Endeca search applications.
reference/discover-electronics	The source code for a live instance of the Discover Electronics application including renderers and configuration files, provided for reference purposes.
reference/discover-electronics-authoring	The source code for an authoring instance of the Discover Electronics application including renderers and configuration files, provided for reference purposes.
reference/discover-service	Contains the Assembler service as configured for a live instance of the Discover Electronics application.
reference/discover-service-authoring	Contains the Assembler service as configured for an authoring instance of the Discover Electronics application.
reference/endeca_jspref	A data explorer Web application that you can use to verify and browse your data.
server/apache-tomcat-6.0.32	The Apache Tomcat Web application container for Endeca Workbench.
server/bin	Contains batch or shell scripts for running the Endeca Tools Service, which sets environment variables and initializes the Tomcat application container.
server/j2sdk	The Java 2 Software Development Kit, version 1.7.
server/webapps	Contains the Workbench, Endeca Configuration Repository, and related tools.
server/workspace	The workspace into which you deploy applications to run in the Endeca Tools Service.
sitemap_generator/bin	Contains the .bat and .sh scripts used to run the Sitemap Generator from the command line.
sitemap_generator/conf	Contains all files necessary to configure the Sitemap Generator.
sitemap_generator/lib	Contains the Sitemap Generator classes packaged in endeca-sitemapgen-<version>.jar, which must

File / Directory	Contents
	be included in the Java classpath when running the Sitemap Generator.
sitemap_generator/samples	Contains sample sitemaps that have been generated using different configuration settings.

Oracle Endeca Experience Manager components

In addition to the contents described above, the Tools and Frameworks package specific to Oracle Endeca Experience Manager also includes the following resources:

File / Directory	Contents
editor_sdk	Contains the SDK for developing custom editors for use with the Experience Manager tool in Oracle Endeca Workbench.
reference/media-mdex-cas	Contains the data and Endeca application configuration for populating the Media MDEX Engine with Discover Electronics media using CAS.

Related Links

[Endeca Tools Service scripts](#) on page 33

The Windows and UNIX versions of the Tools and Frameworks archive contain scripts for running the Endeca Tools Service.

Troubleshooting Oracle Endeca Tools and Frameworks

This section provides an overview of how to address possible problems with your Tools and Frameworks installation.

Error	Solution
Discover Electronics reference application not displaying data	If your MDEX Engine is not running on localhost:15002, you must modify the Assembler context files so that the Assembler can query the MDEX for data. See "Communicating with the MDEX Engine" for details.
Experience Manager editors display but are inactive, "Loading...", or are not configurable	If you are not accessing Workbench from the same hostname specified for the MDEX, you must create a cross-domain policy file, as described in Setting up a cross-domain policy file on page 39. Additionally, both the EAC configuration in the <app dir>\config\script\AuthoringDgraphCluster.xml file and the data service configuration in the <app dir>\config\editors_config\services\dataservice.json file must have the same host and port configuration in order for Experience Manager editors to function correctly.

Error	Solution
Experience Manager displays red warning boxes instead of editors	This behavior indicates that required editors are either not present or are incorrectly configured in the editor configuration file, located in the deployed application directory under <app dir>\config\editors_config\editors.xml. Updates to this file can be pushed to the deployed application by running the <app dir>\control\set_editors_config script.

Deploying a Reference Application

After installing Oracle Endeca Commerce, you can deploy a reference application to process a test data set and examine it in an Endeca front-end application.

About the Discover Electronics reference application

Tools and Frameworks provides a reference application called the Discover Electronics reference application. You can deploy the Discover Electronics reference application using the Deployment Template, then provision the application, run a baseline update, and view the data set in the front-end application.

About multichannel support

In Tools and Frameworks 3.1.0 and later, the Discover Electronics reference application has been augmented to demonstrate best practices for multichannel implementations.

Supported devices

The Discover Electronics reference application is supported on the following mobile browsers:

- Mobile Safari
- Google Android
- BlackBerry (OS 6 or later)
- Skyfire (iOS/Android)

The following browsers are partially supported (some features such as JavaScript, auto-suggest, and cosmetic issues may not work as designed):

- BlackBerry (OS 5)
- Firefox Mobile (Android)

Deploying the Discover Electronics reference application using Forge

As part of the deployment process, the source data in `reference\discover-data` is copied to the `<installation_path>\Endeca\Apps\Discover`, and Forge processes the source data as part of the baseline update.

Before you begin, you must install Tools and Frameworks using the **Complete Installation** type of installation.

The indexed data is loaded into two separate Dgraph instances. One is an authoring instance Dgraph and the other is a live Dgraph for the application.

To deploy the Discover Electronics reference application:

1. Ensure that the Endeca Tools Service is running.
2. If you haven't already, create a directory for deployed Endeca applications, such as `C:\Endeca\Apps` on Windows, or `/usr/local/endeca/apps` on UNIX.
3. Run the Deployment Template to create the application:
 - a) Open a command prompt or command shell.
 - b) Navigate to the `<installation_path>\ToolsAndFrameworks\<version>\deployment_template\bin` directory on Windows, or `<installation_path>/ToolsAndFrameworks/<version>/deployment_template/bin` on UNIX.
 - c) Run the `deploy` script with the `--app` flag and an argument that specifies the path to the `deploy.xml` descriptor file:
For example:


```
C:\Endeca\ToolsAndFrameworks\11.0.0\deployment_template\bin>deploy
--app C:\Endeca\ToolsAndFrameworks\11.0.0\reference\discover-data\deploy.xml
```
 - d) Confirm the Platform Services installation directory.
 - e) Select `y` to install a base application.
 - f) Specify `Discover` as the application name.



Note: The application configuration depends on this name and case sensitivity is important.

- g) Specify the application directory previously created for Endeca applications. This is typically a directory, such as `C:\Endeca\Apps` on Windows or `/usr/local/endeca/apps` on UNIX.
- h) Specify the EAC port and then Oracle recommends using the default values for subsequent prompts about port values and the Oracle Wallet.
- i) Specify the path to the location where you can export your application content to, or press **Enter** to accept the default path of `../../server/workspace/state/repository`.
4. Navigate to the `control` directory of your new deployed application.
This is located under your application directory, for example: `C:\Endeca\Apps\Discover\control` on Windows.
5. Run the `initialize_services` script.
This script does the following:
 - Provisions the application in the Endeca Application Controller.
 - Uploads sample templates and configuration to the application.
 - Uploads sample content and media to the application. (This action occurs only if you are using Experience Manager.)

6. Run the `load_baseline_test_data` script.
7. Run the `baseline_update` script.
8. Run the `promote_content` script.
9. Confirm that the Discover Electronics reference applications are running:
 - Navigate to `http://localhost:8006/discover-authoring` to view the authoring version of the Discover application.
 - Navigate to `http://localhost:8006/discover` to view the live version of the Discover application.

Deploying the Discover Electronics reference application using CAS

You can deploy the Discover Electronics reference application by provisioning it using the Deployment Template and running a baseline update. In this procedure, the Deployment Template copies the source data in `reference\discover-data-cas` to the `C:\Endeca\Apps\Discover` directory, and CAS processes the source data as part of the baseline update.

Before you begin, you must install Tools and Frameworks using the **Complete Installation** type of installation.

To deploy the Discover Electronics reference application using CAS:

1. Ensure that Install the Content Acquisition System is installed. (See the *Endeca CAS Installation Guide*.)
2. Ensure that the Endeca Tools Service is running.
3. If you haven't already, create a directory for deployed Endeca applications, such as `C:\Endeca\Apps` on Windows, or `/usr/local/endeca/apps` on UNIX.
4. Run the Deployment Template to create the application:
 - a) Open a command prompt or command shell.
 - b) Navigate to the `<installation path>\ToolsAndFrameworks\<version>\deployment_template\bin` directory on Windows, or the equivalent path on UNIX.
 - c) Run the `deploy` script with the `--app` flag and an argument that specifies the path to the `deploy.xml` descriptor file that uses CAS.

For example:

```
C:\Endeca\ToolsAndFrameworks\11.0.0\deployment_template\bin>deploy
--app C:\Endeca\ToolsAndFrameworks\11.0.0\reference\discover-data-cas\de-
ploy.xml
```

- d) Press **Enter** to confirm your Platform Services installation directory.
- e) Specify `n` when prompted to install a base deployment.



Note: This configuration is different from deploying using Forge. When using CAS, you must specify `no` to this prompt.

- f) Specify `Discover` as the application name.



Note: The application configuration depends on this name and case sensitivity is important.

- g) Specify the application directory previously created for Endeca applications. This is typically a directory, such as `C:\Endeca\Apps` on Windows or `/usr/local/endeca/apps` on UNIX.

- h) Specify the EAC port and then you can press **Enter** to accept the default values for subsequent prompts about port values and the Oracle Wallet. (Oracle recommends using the default values.)
 - i) Specify the path to the location where you can export your application content to, or press **Enter** to accept the default path of `../../server/workspace/state/repository`.
 - j) Specify the path to the CAS installation directory and specify the Endeca CAS Service port.
5. Navigate to the `control` directory of the new deployed application.
This is located under your application directory, for example: `C:\Endeca\Apps\Discover\control` on Windows.
 6. Run the `initialize_services` script.
This script does the following:
 - Provisions the application in the Endeca Application Controller.
 - Uploads sample templates and configuration to the application.
 - Uploads sample content and media to the application. (This action occurs only if you are using Experience Manager.)
 7. Run the `load_baseline_test_data` script.
 8. Run the `baseline_update` script.
 9. Run the `promote_content` script.
 10. Confirm that the Discover Electronics reference applications are running:
 - Navigate to `http://localhost:8006/discover-authoring` to view the authoring version of the Discover Electronics application.
 - Navigate to `http://localhost:8006/discover` to view the live version of the Discover Electronics application.

Verifying your Tools and Frameworks configuration

Once you have deployed the Discover Electronics reference application, you should verify that all included Tools and Frameworks components are correctly configured for your environment.

To verify that your Tools and Frameworks installation is correctly configured:

1. Confirm that the Discover Electronics reference application is running by navigating to `http://<hostname>:8006/discover-authoring` in your browser, or to the appropriate port if you changed the default value. In this release, be sure to replace `<hostname>` with the actual host name rather than `localhost`.
2. Navigate away from the home page by selecting the **Price Range > Over 1000** dimension value. A **Top Rated Products** spotlight appears in the right sidebar with a set of results. You will modify this cartridge in later steps.
3. Confirm that Oracle Endeca Workbench is running by navigating to `http://localhost:8006` in your browser, or to the appropriate port if you changed the default value.
4. Log in to Workbench.
5. Confirm that the Discover Electronics reference application has been deployed.
The application drop-down on the left side of the top menu bar should display the **Discover** application.
6. Open the **Rule Manager** or **Experience Manager** tool.
7. Navigate to the **Top Rated Products** spotlight cartridge and confirm that the editors are available and able to send and receive information from the MDEX Engine:

- | Option | Description |
|---------------------------|---|
| Experience Manager | <ol style="list-style-type: none"> 1. In the Content tree, expand Web > General > Pages > Default Browse Page. 2. In the Content Details Panel, select rightContent > Top Rated Products. 3. Verify the editors, confirming that they display correctly and do not show warning messages. |
| Rule Manager | <ol style="list-style-type: none"> 1. In the Content tree, expand Right Column Spotlights > Top Rated Products. 2. Verify the editors, confirming that they display correctly and do not show warning messages. |
8. Change the spotlighted records:
 - a) In the editor panel, click the **Edit Query** button.
 - b) Under **Applied Filters**, click **Clear All**.
 - c) Click the **camera.color** dimension.
 - d) Select the **Pink** dimension value.
 - e) Click **Save Selection**.
 9. Click the **Save Changes** button in the upper-right corner of the screen. This displays the following message at the bottom of the Rule Manager or Experience Manager pane:


```
Success: Last publish to the MDEX Engine completed at <date> <time>
```
 10. Navigate to `http://<host>:<port>/discover-authoring` in your browser.
 11. Navigate away from the home page by selecting the **Price Range > Over 1000** dimension value. The **Top Rated Products** spotlight shows only pink results.

About logging and reporting in the reference application

By default, Oracle Endeca Tools and Frameworks is configured to log certain events within the Assembler and collect this information in daily, weekly, and monthly reports.

You can view the reports for the reference application by navigating to the current day, daily, or weekly reports under the **View Reports** tool in Workbench.

For information on configuring logging requests specific to your own Assembler application, see the *Assembler Application Developer's Guide*.

For information on generating log files and reports, see the *Platform Services Log Server and Report Generator Guide*.

Uninstalling Oracle Endeca Tools and Frameworks

This section describes how to uninstall Oracle Endeca Tools and Frameworks from Windows and UNIX.

Uninstalling a deployed application

You should remove any deployed applications from the Endeca Application Controller prior to deleting the application directory.

The steps provided below outline the removal of a deployed application from Oracle Endeca Tools and Frameworks.

To remove a deployed application:

1. Remove the application from the Endeca Application Controller:
 - a) In a command prompt window, list the current applications by running `eaccmd list-apps`.
 - b) Navigate to the `<app dir>\control` directory.
For the Discover Electronics reference application installed using the suggested directory paths, this is `C:\Endeca\apps\Discover\control` (on Windows) or `/usr/local/endeca/apps/Discover/control` (on UNIX).
 - c) Remove the application by running `runcommand --remove-app`.
This removes the specified application and its configuration in Workbench.
 - d) List the current applications again by running `eaccmd list-apps`.
The selected application should no longer display.
2. Navigate to `C:\Endeca\apps` (on Windows) or `/usr/local/endeca/apps` (on UNIX).
3. Delete the selected application directory.
For the Discover Electronics reference application, this is the `Discover` directory.

Uninstalling Oracle Endeca Tools and Frameworks on Windows

Oracle Endeca Tools and Frameworks must be manually uninstalled, including removing the Endeca Tools Service.

Before uninstalling the Tools and Frameworks, you should remove any deployed applications.

To uninstall Oracle Endeca Tools and Frameworks on Windows:

1. Remove the Endeca Tools Service:
 - a) Stop the Endeca Tools Service.
 - b) Navigate to your %ENDECA_TOOLS_ROOT% directory.
By default, this is C:\Endeca\ToolsAndFrameworks\<version>.
 - c) Navigate to the server\bin directory.
 - d) Run `uninstall_service.bat` to remove the service.

2. Copy the `ToolsAndFrameworks\<version>\server\workspace` directory to a back up location that is outside the Endeca installation directory.
(You can use this content later in migration scenarios.)

3. If you still have the Tools and Frameworks installer on your machine, follow these steps. If you do not, then skip to the next step.
 - a) Navigate to the `\cd\Disk1\install` directory and double-click the `setup.exe` installer file to start the wizard.
The Welcome screen displays.
 - b) Click **Deinstall Products...**
 - c) In the Inventory dialog box, select **Oracle Commerce Tools and Frameworks with <Experience Manager/Guided Search>**, and click **Remove...**
 - d) Click **Yes** to confirm that you want to remove Tools and Frameworks and the reference applications.



Note: If you leave the Services window open after removing the Endeca Tools Service, it does not update to show that the service has been removed until you close and re-open it.



Note: This removes the reference application from the inventory. You should have already removed the reference application and any other applications from your deployment before you started uninstalling.

- e) When the installer completes the uninstall, click **Close**.
4. Navigate to the Endeca installation directory, for example C:\Endeca.
5. Delete the `ToolsAndFrameworks` directory.

Uninstalling Oracle Endeca Tools and Frameworks silently on Windows

The silent uninstaller is useful if you want to remove the Tools and Frameworks installation using a script, or remove the installation on multiple machines.

The syntax to run the silent uninstaller is the following:

```
silent_uninstall.bat <FULL_PATH_TO_RESPONSE_FILE> <ORACLE_HOME_NAME> <ORACLE_HOME_LOCATION>
```

where the options have the following values. Note that all the options are required.

Option	Description
FULL_PATH_TO_RESPONSE_FILE	The full path to response file which is used by the silent uninstaller. For example, C:\Users\myname\Documents\ToolsAndFrameworks-version-win64-

Option	Description
	<code>xmgr-installer\cd\Disk1\install\silent_response.rsp</code> .
ORACLE_HOME_NAME	A string value which represents your ORACLE_HOME. For example <code>ToolsandFrameworks</code>
ORACLE_HOME_LOCATION	The location from which you are removing the product. For example, <code>C:\Endeca\ToolsAndFrameworks</code> .

Before you begin, review and edit the `install\silent_response.rsp` file in a text editor with values that are appropriate for your site.

To start the silent uninstaller

1. From a command prompt, navigate to the directory where you downloaded the installer.
2. Issue the `silent_uninstall.bat` command and specify all the options described above.

Example

```
silent_uninstall.bat C:\Users\mine\Documents\ToolsAndFrameworks-11.0.0-win64
-xmgr-installer\cd\Disk1\install\silent_response.rsp toolsandframeworks
C:\Endeca\ToolsAndFrameworks
```

Uninstalling Oracle Endeca Tools and Frameworks on UNIX

Oracle Endeca Tools and Frameworks must be manually uninstalled.

Before uninstalling the Tools and Frameworks, you should remove any deployed applications.

To uninstall Oracle Endeca Tools and Frameworks on UNIX:

1. If you still have the Tools and Frameworks installer on your machine, follow these steps. If you do not, then skip to the next step.
 - a) Navigate to the `/cd/Disk1/install` directory and run the `runinstaller.sh` installer file to start the wizard. The Welcome screen displays.
 - b) Click **Deinstall Products...**
 - c) In the Inventory dialog box, select **Oracle Commerce Tools and Frameworks with <Experience Manager/Guided Search>**, and click **Remove...**
 - d) Click **Yes** to confirm that you want to remove Tools and Frameworks and the reference applications.



Note: This removes the reference application from the inventory. You should have already removed the reference application and any other applications from your deployment before you started uninstalling.

- e) When the installer completes the uninstall, click **Close**.
2. Navigate to `/usr/local/endeca`.
 3. Delete your `ToolsAndFrameworks` directory.

Uninstalling Oracle Endeca Tools and Frameworks silently on UNIX

The silent uninstaller is useful if you want to remove the Tools and Frameworks installation using a script, or remove the installation on multiple machines.

The syntax to run the silent uninstaller is the following:

```
silent_uninstall.sh <FULL_PATH_TO_RESPONSE_FILE> <ORACLE_HOME_NAME> <ORACLE_HOME_LOCATION>
```

where the options have the following values. Note that all the options are required.

Option	Description
FULL_PATH_TO_RESPONSE_FILE	The full path to response file which is used by the silent uninstaller. For example, /localdisk/myname/cd/Disk1/install/silent_response.rsp.
ORACLE_HOME_NAME	A string value which represents your ORACLE_HOME. For example ToolsandFrameworks
ORACLE_HOME_LOCATION	The location from which you are removing the product. For example, /usr/local/endecca/ToolsAndFrameworks.

Before you begin, review and edit the `install/silent_response.rsp` file in a text editor with values that are appropriate for your site.

To start the silent uninstaller

1. From a command prompt, navigate to the directory where you downloaded the installer.
2. Issue the `silent_uninstall.sh` command and specify all the options described above.

Example

```
silent_uninstall.sh /localdisk/myname/cd/Disk1/install/silent_response.rsp  
ToolAndFrameworks /usr/local/endecca/ToolsAndFrameworks
```

Appendix A

Endeca Tools Service Scripts

This section covers the Endeca Tools Service scripts.

Endeca Tools Service scripts

The Windows and UNIX versions of the Tools and Frameworks archive contain scripts for running the Endeca Tools Service.

The following scripts are located in the `server/bin` directory of your Tools and Frameworks installation:

Script	Function
<code>run.bat</code> or <code>startup.sh</code>	Installation script for setting variables and initializing the Tomcat application container.
<code>install_service.bat</code>	On Windows, installs the Endeca Tools Service.
<code>setenv.bat</code>	Script for setting environment variables, called by <code>run.bat</code> .
<code>stop.bat</code> or <code>shutdown.sh</code>	Shuts down Workbench and the Tomcat application container.
<code>start_service.bat</code>	On Windows, starts the Endeca Tools Service.
<code>stop_service.bat</code>	On Windows, stops the Endeca Tools Service.
<code>uninstall_service.bat</code>	On Windows, removes the Endeca Tools Service.
<code>workbench.sh</code>	On UNIX, controls the Workbench process.
<code>workbench-init.d.sh</code>	On UNIX, can be configured to start Workbench automatically.

Appendix B

Endeca Tools Service and EAC Ports Reference

This section covers the steps required to change the Endeca Tools Service and EAC ports from the default values.

About the Endeca Tools Service ports

You can change the default ports for the Endeca Tools Service, as long as you choose a new port that is not being used.

The ports on which the Endeca Tools Service and Endeca Workbench listen are specified in the `server.xml` file, which is located in the `%ENDECA_TOOLS_CONF%\conf` directory (`$ENDECA_TOOLS_CONF/conf` for UNIX).

The `server.xml` file also specifies the default server port. The default values are:

- Port 8006 for the Endeca Tools Service port.
- Port 8007 for the Endeca Tools Service Promotion port.
- Port 8446 for the Endeca Tools Service SSL port.
- Port 8084 for the Endeca Tools Service shutdown port.

Additionally, the Endeca Tools Service port is listed in the `%ENDECA_TOOLS_CONF%\conf\webstudio.properties` file (`$ENDECA_TOOLS_CONF/conf/webstudio.properties` on UNIX).

Changing the Endeca Tools Service port

You can change the Endeca Tools Service port by editing the `server.xml` file located in the `%ENDECA_TOOLS_CONF%\conf` directory (`$ENDECA_TOOLS_CONF/conf` on UNIX). You must also update this information in the `%ENDECA_TOOLS_CONF%\conf\webstudio.properties` file.

To change the Endeca Tools Service port:

1. Stop the Endeca Tools Service.
2. Open the `%ENDECA_TOOLS_CONF%\conf\server.xml` file in a text editor.
3. Find the non-SSL HTTP/1.1 Connector element:

```
<!-- Define a non-SSL HTTP/1.1 Connector on port 8006 -->
<Connector port="8006" maxHttpHeaderSize="8192"
  maxThreads="150" minSpareThreads="25" maxSpareThreads="75"
  enableLookups="true" redirectPort="8446" acceptCount="10"
```

```
connectionTimeout="60000" disableUploadTimeout="true" debug="0"
URIEncoding="UTF-8" />
```

4. Change the number in the port attribute to the new port you want Workbench to use.



Note: You must choose a port not already in use.

5. Save and close the `server.xml` file.
6. Open the `%ENDECA_TOOLS_CONF%\conf\webstudio.properties` file in a text editor (`$ENDECA_TOOLS_CONF/conf/webstudio.properties` on UNIX).
7. Find the line that specifies `com.endeca.webstudio.port`:


```
# This must be set to a non-SSL port, even if you are using the
# SSL version of Endeca Workbench
com.endeca.webstudio.port=8006
```
8. Change the port number to the new port that you specified in Step 4.
9. Save and close the file.
10. In your application, and the Discover Electronics reference application, change the Endeca Tools Service Promotion port by doing the following:
 - a) Open the `<application name>\WEB-INF\assembler.properties` file in a text editor. For example, in the Discover Electronics reference application (on Windows) this file is in `C:\Endeca\ToolsAndFrameworks\3.1.0\reference\discover-electronics-authoring\WEB-INF\assembler.properties`
 - b) Find the `workbench.publishing.serverPort` property and change the value to the new port you want to use.
 - c) Save and close the `assembler.properties` file.
11. Start the Endeca Tools Service.

Changing the Endeca Tools Service Promotion port

You can change the Endeca Tools Service Promotion port by editing the `server.xml` file located in the `%ENDECA_TOOLS_CONF%\conf` directory (`$ENDECA_TOOLS_CONF/conf` on UNIX). You must also update this information in the `%ENDECA_TOOLS_CONF%\conf\webstudio.properties` file.

To change the Endeca Tools Service Promotion port:

1. Stop the Endeca Tools Service.
2. Open the `%ENDECA_TOOLS_CONF%\conf\webstudio.properties` file in a text editor (`$ENDECA_TOOLS_CONF/conf/webstudio.properties` on UNIX).
3. Find the line that specifies `com.endeca.webstudio.promotion.port`:


```
# Port opened for promotion of content from Workbench to
# Live Environments.
com.endeca.webstudio.promotion.port=8007
```
4. Change the port number to the new port you want Workbench to use.
5. Save and close the file.
6. In your application, and the Discover Electronics reference application, change the Endeca Tools Service Promotion port by doing the following:
 - a) Open the `<application name>\WEB-INF\assembler.properties` file in a text editor.

For example, in the Discover Electronics reference application (on Windows) this file is in
 C:\Endeca\ToolsAndFrameworks\3.1.0\reference\discover-electronics-authoring\WEB-INF\assembler.properties

- b) Find the `workbench.publishing.serverPort` property and change the value to the new port you want to use.
 - c) Save and close the `assembler.properties` file.
7. Start the Endeca Tools Service.

Changing the Endeca Tools Service SSL port

You can change the Endeca Tools Service SSL port by editing the `server.xml` file located in the `%ENDECA_TOOLS_CONF%\conf` directory (`$ENDECA_TOOLS_CONF/conf` on UNIX). You must also update this information in the `%ENDECA_TOOLS_CONF%\conf\webstudio.properties` file.

To change the Endeca Tools Service SSL port:

1. Stop the Endeca Tools Service.
2. Open the `%ENDECA_TOOLS_CONF%\conf\server.xml` file in a text editor.
3. Find the SSL HTTP/1.1 Connector element:

```
<Connector port="8446" SSLEnabled="true"
  protocol="org.apache.coyote.http11.Http11Protocol"
  maxPostSize="0"
  maxThreads="150" scheme="https" secure="true"
  clientAuth="false" sslProtocol="TLS"
  keystoreFile="conf/eac.ks" keystorePass="eacpass"
  truststoreFile="conf/ca.ks" truststorePass="eacpass"
 />
```

4. Change the number in the port attribute to the new SSL port you want the Endeca Tools Service to use.



Note: You must choose a port not already in use.

5. Save and close the `server.xml` file.
6. Save and close the file.
7. Start the Endeca Tools Service.

Changing the Endeca Tools Service shutdown port

You can change the Endeca Tools Service shutdown port by editing the `server.xml` file located in the `%ENDECA_TOOLS_CONF%\conf` directory (`$ENDECA_TOOLS_CONF/conf` on UNIX). This port is used internally by the Endeca Tools service software. It is typically only necessary to change it in cases where you have port number conflicts.

To change the Endeca Tools Service shutdown port:

1. Stop the Endeca Tools Service.
2. Open the `server.xml` file in a text editor.
3. Find the `Server` element in the file:

```
<!-- Note: A "Server" is not itself a "Container", so you may not
  define subcomponents such as "Valves" at this level.
  Documentation at /docs/config/server.html
```

```
-->  
<Server port="8084" shutdown="SHUTDOWN" >
```

4. Change the number in the port attribute to the new port you want to use.



Note: You must choose a port not already in use.

5. Save and close the `server.xml` file.
6. Start the Endeca Tools Service.

Updating Workbench to use non-default EAC settings

If the Endeca Application Controller is not running at the default location of `localhost:8888`, you must update this information in the `%ENDECA_TOOLS_CONF%\conf\webstudio.properties` file (`$ENDECA_TOOLS_CONF/conf/webstudio.properties` on UNIX).

To update the Workbench EAC information:

1. Stop the Endeca Tools Service.
2. Open the `webstudio.properties` file in a text editor.
3. Find the lines that specify the EAC server and port:

```
# The EAC Central Server that this Workbench uses  
com.endeca.webstudio.eac.hostname=localhost  
com.endeca.webstudio.eac.port=8888
```

4. Replace `localhost` with the hostname of the EAC host.
5. Replace `8888` with the EAC port.
6. Save and close the file.
7. Start the Endeca Tools Service.

Appendix C

Communicating with the MDEX Engine

This section covers configuring the Tools and Frameworks to communicate with the MDEX Engine and MDEX Web services.

Setting up a cross-domain policy file

By default, MDEX Web services are accessible from Experience Manager and other Endeca Workbench tools only if the MDEX Engine and Workbench are hosted on the same domain.

For example, if Workbench is hosted on `apps.example.com`, the MDEX must also be accessible at `apps.example.com`, and Experience Manager must be configured to access the MDEX Engine at `"apps.example.com"`. Using the host's IP address or an alias hostname, such as `"localhost"` causes a "Security Error" alert box to appear in Experience Manager when an editor attempts to access the MDEX Engine.

If the MDEX Engine is hosted on a different domain from Workbench, you must set up a cross-domain policy file on the MDEX Engine server. These steps apply to any Flex client application that communicates with an MDEX Engine via Web services.

To configure cross-domain access to MDEX Web services from a Flex client:

1. Navigate to the `/conf/dtd/xform` directory of your MDEX Engine installation, for example:
`C:\Endeca\MDEX\6.4.0\conf\dtd\xform`
2. Create an Adobe Flash cross-domain policy file, `crossdomain.xml`.
3. Configure your `crossdomain.xml` file to grant access to all domains hosting instances of Workbench.

An example is provided below:

```
<?xml version="1.0"?>
<!DOCTYPE cross-domain-policy SYSTEM "http://www.macromedia.com/xml/dtds/cross-
domain-policy.dtd">
<cross-domain-policy>
  <allow-access-from domain="*.example.com" />
  <allow-http-request-headers-from domain="*" headers="SOAPAction" />
</cross-domain-policy>
```

- The `<allow-access-from>` element grants access to the local MDEX Web service from a set of domains. The `domain` attribute may be specific, or may include a wildcard, as shown above. You can include any number of `<allow-access-from>` elements, each for a different domain.
- The `<allow-http-request-headers-from>` element as specified above is required. It enables Flash clients to communicate with the MDEX using the SOAP protocol.

For a complete specification of the cross-domain policy file format, please see the Adobe documentation at http://www.adobe.com/devnet/articles/crossdomain_policy_file_spec.html.

Updating Assembler host configuration

By default, the Assembler properties files use `localhost` as the host value for Workbench, MDEX Engine, and Log Server. If you are not installing Tools and Frameworks and the MDEX Engine on the same machine, you must update these files with fully qualified host names to ensure that the components can communicate.

To update the Assembler host configuration:

1. Navigate to the `reference` subdirectory of your Tools and Frameworks installation directory.
By default, this is `C:\Endeca\ToolsAndFrameworks\<version>\reference` on Windows, or `/usr/local/endeca/ToolsAndFrameworks/<version>/reference` on UNIX.
2. Navigate to the `discover-service\WEB-INF` directory.
3. In a text editor, open the `assembler.properties` file.
4. Find the lines that specify the Workbench, MDEX Engine, and Log Server host:

```
workbench.host=localhost  
mdex.host=localhost  
logserver.host=localhost
```

5. Modify the properties to specify the fully qualified name of the host machine.
6. Save and close the file.
7. Repeat Steps 4-6 for the following Assembler property files:
 - `reference\discover-electronics\WEB-INF\assembler.properties`
 - `reference\discover-service-authoring\WEB-INF\assembler.properties`
 - `reference\discover-electronics-authoring\WEB-INF\assembler.properties`

Index

A

Assembler configuration
localhost 40
updating 40

C

cross-domain policy file 39
crossdomain.xml 39

E

EAC port, updating 38
Endeca software requirements 9
Endeca Tools Service
batch files 14
changing user 13
configuring 13
creating a user 13
default ports 35
installing 13
scripts 33
starting 14
stopping 14
environment variables
setting 11

I

installing
Endeca Tools Service 13
environment variables 11
UNIX 16
verifying 26

L

logging
about 27

O

Oracle Endeca Tools and Frameworks
about 9
installing 16

Oracle Endeca Tools and Frameworks (*continued*)
packaging 19

P

packaging 33
prerequisites 9

R

reference application
uninstalling 29
reporting
about 27
requirements
Endeca software requirements 9

S

software requirements 9

T

troubleshooting 21

U

uninstalling
reference application 29
UNIX 31
Windows 29
UNIX
starting Workbench automatically 17

V

verifying the installation 26

W

Windows, creating Endeca Tools Service on 13
Workbench port 35
Workbench process
starting 17
starting automatically 17
stopping 17

