

# Oracle® Enterprise Data Quality

Security Group Filtering

Release 11g R1 (11.1.1.7)

E40047-02

October 2013

---

This document describes a sample Oracle Enterprise Data Quality (EDQ) plug-in script that performs custom, run-time filtering of user authorization groups, based on the user's location as determined by IP address.

## 1 Background

This plug-in is designed to address legislative requirements that state that some data must not be taken out of a particular country. In particular, a user logging on from a different country must not be able to view or access the restricted data, even if they would normally have sufficient privileges to do so.

Project access in EDQ is normally controlled by assigning users and projects to **groups**. Both users and projects may have multiple groups. A user has access to a project if they are a member of at least one of the project's groups as assigned to the project in Director. The plug-in described here operates at run-time to filter the groups assigned to a user, based on the user's IP address at the time they log on.

For this script to work as intended, projects should be assigned to groups based upon their data access restrictions. That is, all projects that may only be accessed from within country A should be assigned to one group, projects that may only be accessed from country B should be assigned to a second group. Any projects with no country-based access restrictions can be made available to all groups. Users can then be granted access to each group as usual, and the plug-in script will provide per-session, IP address-based filtering of the groups actually available to a user.

This script can be configured to filter user authorizations based on either IPv4 or IPv6 addresses. It is not possible to filter on both IPv4 and IPv6 addresses at the same time.

---

**Note:** Users with the Add Project permission (usually administrators and power users) always have access to all projects. This bypasses the group system and is unaffected by this plug-in. By default, the Administrators and Project Owners user groups have this permission. It is possible to circumvent this issue by removing the Add Project permission from all users once all the system has been fully configured. If it is necessary to create further projects in the future, a user can be granted the Add Project permission as a temporary measure.

---

## 2 The Authorizations Filter Plug-In

This plug-in consists of a JavaScript plug-in script plus configuration data that can be provided either as an Extensible Markup Language (XML) file or as a

comma-separated list. The user can activate the plug-in and select which type of configuration file is to be used by editing the `security.properties` file in the EDQ server configuration directory.

## 2.1 Installation

The plug-in is installed by adding files to, and editing files in, the `oedq.local.home` configuration directory. The location of this directory is determined during installation. On a typical WebLogic platform, the path is usually as follows:

```
/middleware/user_projects/domains/your_domain/edq/oedq.local.home
```

To install the filter:

1. Create a new script file, `userfilter.js`, in the `oedq.local.home` configuration directory.
2. Place the JavaScript code from [Section 3, "The Filter Script"](#) into `userfilter.js`.
3. Create a new file to hold the IP address filtering rules in your configuration directory. Filter rules can be expressed either in comma-separated values (CSV) format, in which case your rules file should be named `ipranges.csv`, or in XML format, in which case your rules file should be named `ipranges.xml`. You will add data to these files in the configuration step, described in [Section 2.2, "Configuration."](#)

4. Edit the `security.properties` file in the `oedq.local.home` configuration directory, or create it if it does not already exist, and add the line:

```
user.filter.scriptfile = userfilter.js
```

5. Add one of the two following lines to `security.properties`. If you want to use the XML version of the configuration file, add:

```
user.filter.xfile = ipranges.xml
```

If you wish to use the CSV version of the configuration file, add:

```
user.filter.cfile = ipranges.csv
```

6. Restart the application server so that it can pick up the new settings from the properties files.

## 2.2 Configuration

This plug-in can accept configuration data either in XML or CSV format. In either case, the configuration data maps a group to one or more IP ranges that correspond to permitted access locations. If a user logs on to the system from an IP address outside the permitted ranges, the associated group will be blocked from the user for the duration of the session.

The data in these files can be edited to modify the location-based filtering of project access. When editing the data, whichever file format is used, the following points should be remembered:

- If a group is not mentioned in the configuration file, no location-based filtering will be applied to it.
- The IP address ranges in the files are those that are allowed to access projects in the associated groups. To allow access to a group from more locations, add an IP range or widen the scope of an existing IP range. To disallow access to a group

from some locations, remove the corresponding IP address range, or narrow the scope of the relevant range.

### 2.2.1 XML File Format

The XML configuration file has the following structure:

```
<ipranges>
<group name="name">
<iprange start="x" end="y"/>
...
</group>
...
</ipranges>
```

The configuration data consists of one or more `<group>` elements, where each group is identified by name. Each group specifies one or more IP address ranges that are permitted access to the projects in that group. An address range is specified as an `<iprange>` element, with a start and an end attribute defining the limits of the address range. In this way, multiple valid IP address ranges can be configured for each group.

All the group/IP range mapping data in the file must be contained within the `<ipranges>` tag.

For example, suppose an XML configuration file contains the following data:

```
<ipranges>
<group name="group1">
<iprange start="1.1.1.0" end="1.1.1.20" />
<iprange start="10.1.0.0" end="10.1.0.255" />
</group>
<group name="group2">
<iprange start="10.8.1.0" end="10.8.1.125" />
</group>
</ipranges>
```

This configuration data means that:

- Projects that belong to `group1` can only be accessed by logging on from an IP address that is either in the range 1.1.1.0 to 1.1.1.20 or in the range 10.1.0.0 to 10.1.0.225.
- Projects that belong to `group2` can only be accessed by logging on from an IP address in the range 10.8.1.0 to 10.8.1.125.

If a group is not specified in the configuration file, access to projects in that group will not be controlled by IP address. For example, user access to projects belonging to a third group named `group3` will be unaffected by this script and configuration data.

### 2.2.2 CSV File Format

The CSV configuration file format specifies one group/address range mapping per line. Each line consists of three comma-separated fields, as follows:

group name, start of address range, end of address range

For example, suppose a CSV configuration file contains the following data:

```
group1, 1.1.1.0, 1.1.1.20
group2, 10.8.1.0, 10.8.1.125
group1, 10.1.0.0, 10.1.0.255
```

This configuration file is functionally identical the sample XML file in [Section 2.2.1, "XML File Format."](#) That is:

- Projects that belong to group1 can only be accessed by logging on from an IP address that is *either* in the range 1.1.1.0 to 1.1.1.20 *or* in the range 10.1.0.0 to 10.1.0.225.
- Projects that belong to group2 can only be accessed by logging on from an IP address in the range 10.8.1.0 to 10.8.1.125.

It is not necessary for all the valid IP address ranges for a group to be specified on adjacent lines. Again, if a group is not present within the file, no IP address filtering will be performed for that group.

### 3 The Filter Script

The filter script is as follows:

```
// User filter test which reads CSV or XML
// =====
addLibrary("logging");
addLibrary("io");

// Main filtering function for the script
// =====
function filter(user, ip)
{
    logger.log(Level.INFO,
        "Filtering user {0} from IP {1}",user.getUserName(), ip);
    var xprop = props["user.filter.xfile"];
    var cprop = props["user.filter.cfile"];
    var cfile = cprop == null ? null : findFile(cprop);
    var xfile = xprop == null ? null : findFile(xprop);

    if (cfile == null && xfile == null)
    {
        logger.log(Level.INFO, "No IP range files available");
        return true;
    }

    // Process CSV file
    // =====
    if (cfile != null)
    {
        // CSV file has group name and IP start/end on each line; a group
        // matches if the IP is in any of the ranges
        var hash= new Object();
        var rdr= IO.createCSVReader(cfile);
        var arr;

        while ((arr = rdr.read()) != null)
        {
            // Ignore lines with too few fields
            if (arr.length >= 3)
            {
                // Store group in hash once only
                var grp= trim(arr[0]);
                var start = trim(arr[1]);
                var end= trim(arr[2]);
```

```

    if (hash[grp] == null)
    {
        hash[grp] = false;
    }

    if (ipInRange(ip, start, end))
    {
        hash[grp] = true;
    }
}

// Now reject any groups which did not match
for (var g in hash)
{
    if (!hash[g])
    {
        user.removeGroupByName(g);
    }
}

// Process XML file
// XML schema is:
//
//<ipranges>
//<group name="name">
//<iprange start="x" end="y"/>
//...
//</group>
//...
// </ipranges>
//
// The purifyXML call here removes the <?xml ...?> header
// which E4X does not like
// =====
if (xfile != null) {
    var xml= new
    XML(XMLTransformer.purifyXML(IO.load(xfile)));
    var grps= xml.group;
    var ng= grps.length();
    for (var i = 0; i < ng; i++)
    {
        var grp = grps[i];
        var ranges = grp.iprange;
        var ok= false;

        for (var j = 0; j < ranges.length(); j++)
        {
            var range = ranges[j];
            if (ipInRange(ip, range.@start, range.@end))
            {
                ok = true;
                break;
            }
        }

        if (!ok)
        {

```

```

user.removeGroupName(grp.@name);
}
}
}
return true;
}

// Trim function
// =====
function trim(a)
{
return a.replace(/ /g, '');
}

```

## 4 Audience

This document is intended for system administrators responsible for the security settings of user authorization groups.

## 5 Related Documents

For more information, see the following documents in the documentation set:

- *Oracle Enterprise Data Quality Installation Guide*
- *Oracle Enterprise Data Quality Server Administration Guide*

See the latest version of this and all documents in the Oracle Enterprise Data Quality Documentation website at:

[http://download.oracle.com/docs/cd/E48549\\_01/index.htm](http://download.oracle.com/docs/cd/E48549_01/index.htm)

Also, see the latest version of the *EDQ Online Help*, bundled with EDQ.

## 6 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

### Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

---

Oracle Enterprise Data Quality Security Group Filtering, Release 11g R1 (11.1.1.7)  
E40047-02

Copyright © 2006, 2013, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition

Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

