

Gateway Documentation - Unit Holder Deal  
Oracle FLEXCUBE Investor Servicing  
Release FCIS\_12.0.3.0.0  
[April] [2014]



# Table Of Contents

---

<b>1. BACKGROUND</b>	<b>1</b>
<b>2. FCISUHDeal</b>	<b>2</b>
<b>2.1. AuthorizeUHDeal</b>	<b>2</b>
2.1.1. <i>UT-AuthorizeUHDeal-Req-Full-MSG.xsd</i>	2
2.1.2. <i>UT-AuthorizeUHDeal-Req-IO-MSG.xsd</i>	16
2.1.3. <i>UT-AuthorizeUHDeal-Res-Full-MSG.xsd</i>	23
2.1.4. <i>UT-AuthorizeUHDeal-Res-PK-MSG.xsd</i>	39
<b>2.2. CreateUHDeal</b>	<b>48</b>
2.2.1. <i>UT-CreateUHDeal-Req-Full-MSG.xsd</i>	48
2.2.2. <i>UT-CreateUHDeal-Req-IO-MSG.xsd</i>	62
2.2.3. <i>UT-CreateUHDeal-Res-Full-MSG.xsd</i>	73
2.2.4. <i>UT-CreateUHDeal-Res-PK-MSG.xsd</i>	89
<b>2.3. DeleteUHDeal</b>	<b>102</b>
2.3.1. <i>UT-DeleteUHDeal-Req-Full-MSG.xsd</i>	102
2.3.2. <i>UT-DeleteUHDeal-Req-IO-MSG.xsd</i>	116
2.3.3. <i>UT-DeleteUHDeal-Res-Full-MSG.xsd</i>	122
2.3.4. <i>UT-DeleteUHDeal-Res-PK-MSG.xsd</i>	138
<b>2.4. ModifyUHDeal</b>	<b>146</b>
2.4.1. <i>UT-ModifyUHDeal-Req-Full-MSG.xsd</i>	146
2.4.2. <i>UT-ModifyUHDeal-Req-IO-MSG.xsd</i>	160
2.4.3. <i>UT-ModifyUHDeal-Res-Full-MSG.xsd</i>	168
2.4.4. <i>UT-ModifyUHDeal-Res-PK-MSG.xsd</i>	184
<b>2.5. QueryUHDeal</b>	<b>194</b>
2.5.1. <i>UT-QueryUHDeal-Req-IO-MSG.xsd</i>	194
2.5.2. <i>UT-QueryUHDeal-Res-Full-MSG.xsd</i>	200

# 1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.

The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

**1. Inbound application integration** – used when any external system needs to add, modify or query information within FLEXCUBE UBS

**2. Outbound application integration**– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCISUHDeal of UT-Module

## 2.FCISUHDeal

Unit Holder Deal Unit Holder Deal

### 2.1.AuthorizeUHDeal

Authorize UHDeal

#### 2.1.1.UT-AuthorizeUHDeal-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Dealinfo-Full*

*UH\_CIF*

*NAME*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

POLICY\_NUMBER  
 DEALBASEDON  
 TAX\_TYPE  
 LOADESC  
 AMOUNTORPERCENTAGE  
 LOCAL\_CALC\_METHOD  
 PRODUCT\_NAME  
 FUNDNAME  
 DESCRIPTION  
 MAKER  
 MAKERSTAMP  
 CHECKER  
 CHECKERSTAMP  
 MODNO  
 TXNSTAT  
 AUTHSTAT  
 Unitholderdealtblb  
     SLABSEQ  
     OVERRIDEO  
 Unitholderdealtblc  
     OVERRIDEO

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)**Dealinfo-Full**

Attribute	Description
Name	Dealinfo-Full
Datatype	
Description	

[TOP](#)**UH\_CIF**

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**DEAL\_TRANSACTION\_NUMBER**

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**APPLY\_AT\_CIF\_LEVEL**

Attribute	Description
-----------	-------------

Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## APPLYDEALAT

<b>Attribute</b>	<b>Description</b>	
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	L,G,F,P

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,C

[TOP](#)

## EFFECTIVE\_START\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_START_DATE	
Datatype	Date	
Description	Indicates Effective Start Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_END\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LOADGROUPID

Attribute	Description	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## FUND\_ID

Attribute	Description	
Name	FUND ID	
Datatype	String	
Description	Indicates Fund Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

## LOAD\_ID

Attribute	Description	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## MODULE\_ID

Attribute	Description	
Name	MODULE_ID	
Datatype	String	
Description	Indicates Module Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

## PRODUCT\_ID

Attribute	Description	
Name	PRODUCT_ID	
Datatype	String	

Description	Indicates Product Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## POLICY\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## DEALBASEDON

<b>Attribute</b>	<b>Description</b>	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TAX\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,D,I

[TOP](#)

## LOADDESC

<b>Attribute</b>	<b>Description</b>	
Name	LOADDESC	
Datatype	String	
Description	Indicates Load Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## AMOUNTORPERCENTAGE

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTORPERCENTAGE	
Datatype	String	
Description	Indicates Amount or percentage	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## LOCAL\_CALC\_METHOD

<b>Attribute</b>	<b>Description</b>	
Name	LOCAL_CALC_METHOD	
Datatype	String	
Description	Indicates load calculation menthod	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## PRODUCT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_NAME	
Datatype	String	
Description	Indicates Product name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FUNDNAME

<b>Attribute</b>	<b>Description</b>	
Name	FUNDNAME	
Datatype	String	
Description	Indicates Fund name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

**DESCRIPTION**

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date-Time Stamp	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date-Time Stamp	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Unitholderdealtblb

Attribute	Description	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SLABSEQ

<b>Attribute</b>	<b>Description</b>	
Name	SLABSEQ	
Datatype	Number	
Description	Indicates Slab Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## OVERRIDE TO

<b>Attribute</b>	<b>Description</b>	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## Unitholderdealtblc

<b>Attribute</b>	<b>Description</b>	
Name	Unitholderdealtblc	
Datatype		
Description	Indicates Unit holder deal details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## OVERRIDE TO

<b>Attribute</b>	<b>Description</b>	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## 2.1.2.UT-AuthorizeUHDeal-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Dealinfo-IO

DEAL\_TRANSACTION\_NUMBER

CHECKER

CHECKERSTAMP

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)**Dealinfo-IO**

Attribute	Description
Name	Dealinfo-IO
Datatype	
Description	

[TOP](#)**DEAL\_TRANSACTION\_NUMBER**

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**CHECKERSTAMP**

Attribute	Description
-----------	-------------

Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.1.3.UT-AuthorizeUHDeal-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Dealinfo-Full*

*UH\_CIF*

*NAME*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

*LOADDESC*

*AMOUNTORPERCENTAGE*

*LOCAL\_CALC\_METHOD*

*PRODUCT\_NAME*  
*FUNDNAME*  
*DESCRIPTION*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Unitholderdealtblb*  
     *SLABSEQ*  
     *OVERRIDEO*  
*Unitholderdealtblc*  
     *OVERRIDEO*  
*FCUBS\_ERROR\_RESP*  
     *ERROR*  
         *ECODE*  
         *EDESC*  
*FCUBS\_WARNING\_RESP*  
     *WARNING*  
         *WCODE*  
         *WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-Full

Attribute	Description
Name	Dealinfo-Full
Datatype	
Description	

[TOP](#)

## UH\_CIF

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**APPLY\_AT\_CIF\_LEVEL**

Attribute		Description
Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	Attribute	Description
	minOccurs	1

**APPLYDEALAT**

Attribute		Description
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	L,G,F,P

**STATUS**

Attribute		Description
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,C

**EFFECTIVE\_START\_DATE**

Attribute		Description
Name	EFFECTIVE_START_DATE	
Datatype	Date	
Description	Indicates Effective Start Date	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTIVE\_END\_DATE**

Attribute		Description
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LOADGROUPID

<b>Attribute</b>	<b>Description</b>	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FUND\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FUND_ID	
Datatype	String	
Description	Indicates Fund Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## LOAD\_ID

<b>Attribute</b>	<b>Description</b>	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>	
Name	MODULE_ID	
Datatype	String	
Description	Indicates Module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

Attribute	Description	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## POLICY\_NUMBER

Attribute	Description	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## DEALBASEDON

Attribute	Description	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TAX\_TYPE

Attribute	Description	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,D,I

[TOP](#)

## LOADDESC

Attribute	Description
Name	LOADDESC

Datatype	String	
Description	Indicates Load Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## AMOUNTORPERCENTAGE

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTORPERCENTAGE	
Datatype	String	
Description	Indicates Amount or percentage	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## LOCAL\_CALC\_METHOD

<b>Attribute</b>	<b>Description</b>	
Name	LOCAL_CALC_METHOD	
Datatype	String	
Description	Indicates load calculation method	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## PRODUCT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_NAME	
Datatype	String	
Description	Indicates Product name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FUNDNAME

<b>Attribute</b>	<b>Description</b>	
Name	FUNDNAME	
Datatype	String	
Description	Indicates Fund name	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Unitholderdealtblb

Attribute	Description	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SLABSEQ

Attribute	Description	
Name	SLABSEQ	
Datatype	Number	
Description	Indicates Slab Number	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## OVERRIDE TO

Attribute	Description	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## Unitholderdealtblc

Attribute	Description	
Name	Unitholderdealtblc	
Datatype		
Description	Indicates Unit holder deal details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## OVERRIDE TO

Attribute	Description	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description				
Name	FCUBS_ERROR_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description				
Name	FCUBS_WARNING_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.1.4.UT-AuthorizeUHDeal-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*ADDL*  
     *PARAM*  
         *NAME*  
         *VALUE*  
*FCUBS\_BODY*  
     *CHOICE*  
         *Dealinfo-PK*  
             *DEAL\_TRANSACTION\_NUMBER*  
         *Dealinfo-IO*  
             *DEAL\_TRANSACTION\_NUMBER*  
             *CHECKER*  
             *CHECKERSTAMP*  
             *MODNO*  
*FCUBS\_ERROR\_RESP*  
     *ERROR*  
         *ECODE*  
         *EDESC*  
*FCUBS\_WARNING\_RESP*  
     *WARNING*  
         *WCODE*  
         *WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute		Description
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	
	minOccurs	0
	nullable	true
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	
	minOccurs	0
	nullable	true
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute		Description
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	
	minOccurs	0
	nullable	true
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## CHOICE

<b>Attribute</b>	<b>Description</b>
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Dealinfo-PK

<b>Attribute</b>	<b>Description</b>	
Name	Dealinfo-PK	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

<b>Attribute</b>	<b>Description</b>
Name	DEAL_TRANSACTION_NUMBER
Datatype	String
Description	Indicates Deal Transaction Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## Dealinfo-IO

<b>Attribute</b>	<b>Description</b>	
Name	Dealinfo-IO	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.2.CreateUHDeal

Create UHDeal

### 2.2.1.UT-CreateUHDeal-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Dealinfo-Full*

*UH\_CIF*

*NAME*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

LOADDESC  
 AMOUNTORPERCENTAGE  
 LOCAL\_CALC\_METHOD  
 PRODUCT\_NAME  
 FUNDNAME  
 DESCRIPTION  
 MAKER  
 MAKERSTAMP  
 CHECKER  
 CHECKERSTAMP  
 MODNO  
 TXNSTAT  
 AUTHSTAT  
 Unitholderdealtblb  
     SLABSEQ  
     OVERRIDEO  
 Unitholderdealtblc  
     OVERRIDEO

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
-----------	-------------

Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-Full

Attribute	Description
Name	Dealinfo-Full
Datatype	
Description	

[TOP](#)

## UH\_CIF

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## APPLY\_AT\_CIF\_LEVEL

Attribute	Description	
Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	Attribute	Description
	minOccurs	1

**APPLYDEALAT**

Attribute	Description	
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	L,G,F,P

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,C

**EFFECTIVE\_START\_DATE**

Attribute	Description	
Name	EFFECTIVE_START_DATE	
Datatype	Date	
Description	Indicates Effective Start Date	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTIVE\_END\_DATE**

Attribute	Description	
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	
Attributes	Attribute	Description
	minOccurs	1

**LOADGROUPID**

Attribute	Description	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FUND\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FUND_ID	
Datatype	String	
Description	Indicates Fund Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## LOAD\_ID

<b>Attribute</b>	<b>Description</b>	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>	
Name	MODULE_ID	
Datatype	String	
Description	Indicates Module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

**POLICY\_NUMBER**

Attribute	Description	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**DEALBASEDON**

Attribute	Description	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**TAX\_TYPE**

Attribute	Description	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,D,I

**LOADDESC**

Attribute	Description	
Name	LOADDESC	
Datatype	String	
Description	Indicates Load Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**AMOUNTORPERCENTAGE**

Attribute	Description	
Name	AMOUNTORPERCENTAGE	
Datatype	String	
Description	Indicates Amount or percentage	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## LOCAL\_CALC\_METHOD

Attribute	Description	
Name	LOCAL_CALC_METHOD	
Datatype	String	
Description	Indicates load calculation method	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## PRODUCT\_NAME

Attribute	Description	
Name	PRODUCT_NAME	
Datatype	String	
Description	Indicates Product name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FUNDNAME

Attribute	Description	
Name	FUNDNAME	
Datatype	String	
Description	Indicates Fund name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date-Time Stamp	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Unitholderdealtblb

<b>Attribute</b>	<b>Description</b>	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SLABSEQ

Attribute	Description				
Name	SLABSEQ				
Datatype	Number				
Description	Indicates Slab Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## OVERRIDE TO

Attribute	Description				
Name	OVERRIDE TO				
Datatype	Number				
Description	Indicates Override To				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## Unitholderdealtblc

Attribute	Description						
Name	Unitholderdealtblc						
Datatype							
Description	Indicates Unit holder deal details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## OVERRIDE TO

Attribute	Description				
Name	OVERRIDE TO				
Datatype	Number				
Description	Indicates Override To				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## 2.2.2.UT-CreateUHDeal-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Dealinfo-IO*

*UH\_CIF*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

*Unitholderdealtblb*

*SLABSEQ*

*OVERRIDE\_TO*

*Unitholderdealtblc*

[OVERRIDE TO](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
	Attribute	Description					
	minOccurs	0					
nillable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
	Attribute	Description					
	minOccurs	0					
nillable	true						

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

## Dealinfo-IO

Attribute	Description	
Name	Dealinfo-IO	
Datatype		
Description		

[TOP](#)

## UH\_CIF

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## APPLY\_AT\_CIF\_LEVEL

Attribute	Description	
Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## APPLYDEALAT

Attribute	Description	
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	L,G,F,P

[TOP](#)

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,C

[TOP](#)

## EFFECTIVE\_START\_DATE

Attribute	Description				
Name	EFFECTIVE_START_DATE				
Datatype	Date				
Description	Indicates Effective Start Date				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## EFFECTIVE\_END\_DATE

Attribute	Description				
Name	EFFECTIVE_END_DATE				
Datatype	Date				
Description	Indicates Effective End Date				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## LOADGROUPID

Attribute	Description				
Name	LOADGROUPID				
Datatype	String				
Description	Indicates Load Group Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## FUND\_ID

Attribute	Description				
Name	FUND_ID				
Datatype	String				
Description	Indicates Fund Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

## LOAD\_ID

Attribute	Description
Name	LOAD_ID
Datatype	Number
Description	Indicates Load Id

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>	
Name	MODULE_ID	
Datatype	String	
Description	Indicates module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## POLICY\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## DEALBASEDON

<b>Attribute</b>	<b>Description</b>	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**TAX\_TYPE**

Attribute	Description	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,D,I

**Unitholderdealtblb**

Attribute	Description	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**SLABSEQ**

Attribute	Description	
Name	SLABSEQ	
Datatype	Number	
Description	Indicates Slab Number	
Attributes	Attribute	Description
	minOccurs	1

**OVERRIDEO**

Attribute	Description	
Name	OVERRIDEO	
Datatype	Number	
Description	Indicates Override To	
Attributes	Attribute	Description
	minOccurs	1

**Unitholderdealtblc**

Attribute	Description	
Name	Unitholderdealtblc	
Datatype		
Description	Indicates Unit holder deal details	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## OVERRIDE TO

<b>Attribute</b>	<b>Description</b>	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

### 2.2.3.UT-CreateUHDeal-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Dealinfo-Full*

*UH\_CIF*

*NAME*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

*LOADDESC*

*AMOUNTORPERCENTAGE*

*LOCAL\_CALC\_METHOD*

*PRODUCT\_NAME*  
*FUNDNAME*  
*DESCRIPTION*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Unitholderdealtblb*  
     *SLABSEQ*  
     *OVERRIDEO*  
*Unitholderdealtblc*  
     *OVERRIDEO*  
*FCUBS\_ERROR\_RESP*  
     *ERROR*  
         *ECODE*  
         *EDESC*  
*FCUBS\_WARNING\_RESP*  
     *WARNING*  
         *WCODE*  
         *WDESC*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-Full

Attribute	Description
Name	Dealinfo-Full
Datatype	
Description	

[TOP](#)

## UH\_CIF

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**APPLY\_AT\_CIF\_LEVEL**

Attribute	Description	
Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	Attribute	Description
	minOccurs	1

**APPLYDEALAT**

Attribute	Description	
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	L,G,F,P

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,C

**EFFECTIVE\_START\_DATE**

Attribute	Description	
Name	EFFECTIVE_START_DATE	
Datatype	Date	
Description	Indicates Effective Start Date	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTIVE\_END\_DATE**

Attribute	Description	
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LOADGROUPID

<b>Attribute</b>	<b>Description</b>	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FUND\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FUND_ID	
Datatype	String	
Description	Indicates Fund Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## LOAD\_ID

<b>Attribute</b>	<b>Description</b>	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>	
Name	MODULE_ID	
Datatype	String	
Description	Indicates Module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

Attribute	Description	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## POLICY\_NUMBER

Attribute	Description	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## DEALBASEDON

Attribute	Description	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TAX\_TYPE

Attribute	Description	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,D,I

[TOP](#)

## LOADDESC

Attribute	Description
Name	LOADDESC

Datatype	String	
Description	Indicates Load Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## AMOUNTORPERCENTAGE

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTORPERCENTAGE	
Datatype	String	
Description	Indicates Amount or percentage	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## LOCAL\_CALC\_METHOD

<b>Attribute</b>	<b>Description</b>	
Name	LOCAL_CALC_METHOD	
Datatype	String	
Description	Indicates load calculation method	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## PRODUCT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_NAME	
Datatype	String	
Description	Indicates Product name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FUNDNAME

<b>Attribute</b>	<b>Description</b>	
Name	FUNDNAME	
Datatype	String	
Description	Indicates Fund name	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Unitholderdealtblb

Attribute	Description	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SLABSEQ

Attribute	Description	
Name	SLABSEQ	
Datatype	Number	
Description	Indicates Slab Number	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## OVERRIDE TO

Attribute	Description	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## Unitholderdealtblc

Attribute	Description	
Name	Unitholderdealtblc	
Datatype		
Description	Indicates Unit holder deal details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## OVERRIDE TO

Attribute	Description	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description				
Name	FCUBS_ERROR_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description				
Name	FCUBS_WARNING_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.2.4.UT-CreateUHDeal-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Dealinfo-PK*

*DEAL\_TRANSACTION\_NUMBER*

*Dealinfo-IO*

*UH\_CIF*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

*Unitholderdealtblb*

SLABSEQ  
 OVERRIDETO  
 Unitholderdealtblc  
 OVERRIDETO  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Dealinfo-PK

Attribute	Description	
Name	Dealinfo-PK	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Dealinfo-IO

Attribute	Description	
Name	Dealinfo-IO	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UH\_CIF

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description				
Name	DEAL_TRANSACTION_NUMBER				
Datatype	String				
Description	Indicates Deal Transaction Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## APPLY\_AT\_CIF\_LEVEL

Attribute	Description				
Name	APPLY_AT_CIF_LEVEL				
Datatype	Number				
Description	Indicates Apply at CIF level				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## APPLYDEALAT

Attribute	Description				
Name	APPLYDEALAT				
Datatype	String				
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>L,G,F,P</td></tr></tbody></table>	Restrictions	Description	enumeration	L,G,F,P
	Restrictions	Description			
enumeration	L,G,F,P				

[TOP](#)

## STATUS

Attribute	Description				
Name	STATUS				
Datatype	String				
Description	Indicates Status, A for Active, C for Cancelled				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>A,C</td></tr></tbody></table>	Restrictions	Description	enumeration	A,C
	Restrictions	Description			
enumeration	A,C				

[TOP](#)

## EFFECTIVE\_START\_DATE

Attribute	Description
Name	EFFECTIVE_START_DATE
Datatype	Date

Description	Indicates Effective Start Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_END\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LOADGROUPID

<b>Attribute</b>	<b>Description</b>	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FUND\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FUND_ID	
Datatype	String	
Description	Indicates Fund Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## LOAD\_ID

<b>Attribute</b>	<b>Description</b>	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MODULE_ID	
Datatype	String	
Description	Indicates module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## POLICY\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## DEALBASEDON

<b>Attribute</b>	<b>Description</b>	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TAX\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,D,I

[TOP](#)

### Unitholderdealtblb

<b>Attribute</b>	<b>Description</b>	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

### SLABSEQ

<b>Attribute</b>	<b>Description</b>	
Name	SLABSEQ	
Datatype	Number	
Description	Indicates Slab Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

### OVERRIDE TO

<b>Attribute</b>	<b>Description</b>	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

### Unitholderdealtblc

<b>Attribute</b>	<b>Description</b>	
Name	Unitholderdealtblc	
Datatype		
Description	Indicates Unit holder deal details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

### OVERRIDE TO

<b>Attribute</b>	<b>Description</b>	
Name	OVERRIDE TO	

Datatype	Number	
Description	Indicates Override To	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.3.DeleteUHDeal

Delete UHDeal

### 2.3.1.UT-DeleteUHDeal-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Dealinfo-Full*

*UH\_CIF*

*NAME*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

LOADDESC  
 AMOUNTORPERCENTAGE  
 LOCAL\_CALC\_METHOD  
 PRODUCT\_NAME  
 FUNDNAME  
 DESCRIPTION  
 MAKER  
 MAKERSTAMP  
 CHECKER  
 CHECKERSTAMP  
 MODNO  
 TXNSTAT  
 AUTHSTAT  
 Unitholderdealtblb  
     SLABSEQ  
     OVERRIDEO  
 Unitholderdealtblc  
     OVERRIDEO

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
-----------	-------------

Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-Full

Attribute	Description
Name	Dealinfo-Full
Datatype	
Description	

[TOP](#)

## UH\_CIF

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## APPLY\_AT\_CIF\_LEVEL

Attribute	Description	
Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	Attribute	Description
	minOccurs	1

**APPLYDEALAT**

Attribute	Description	
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	L,G,F,P

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,C

**EFFECTIVE\_START\_DATE**

Attribute	Description	
Name	EFFECTIVE_START_DATE	
Datatype	Date	
Description	Indicates Effective Start Date	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTIVE\_END\_DATE**

Attribute	Description	
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	
Attributes	Attribute	Description
	minOccurs	1

**LOADGROUPID**

Attribute	Description	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FUND\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FUND_ID	
Datatype	String	
Description	Indicates Fund Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## LOAD\_ID

<b>Attribute</b>	<b>Description</b>	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>	
Name	MODULE_ID	
Datatype	String	
Description	Indicates Module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)**POLICY\_NUMBER**

Attribute	Description	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**DEALBASEDON**

Attribute	Description	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**TAX\_TYPE**

Attribute	Description	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,D,I

[TOP](#)**LOADDESC**

Attribute	Description	
Name	LOADDESC	
Datatype	String	
Description	Indicates Load Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**AMOUNTORPERCENTAGE**

Attribute	Description	
Name	AMOUNTORPERCENTAGE	
Datatype	String	
Description	Indicates Amount or percentage	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## LOCAL\_CALC\_METHOD

Attribute	Description	
Name	LOCAL_CALC_METHOD	
Datatype	String	
Description	Indicates load calculation menthod	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## PRODUCT\_NAME

Attribute	Description	
Name	PRODUCT_NAME	
Datatype	String	
Description	Indicates Product name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FUNDNAME

Attribute	Description	
Name	FUNDNAME	
Datatype	String	
Description	Indicates Fund name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date-Time Stamp	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Unitholderdealtblb

<b>Attribute</b>	<b>Description</b>	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SLABSEQ

Attribute	Description				
Name	SLABSEQ				
Datatype	Number				
Description	Indicates Slab Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## OVERRIDE TO

Attribute	Description				
Name	OVERRIDE TO				
Datatype	Number				
Description	Indicates Override To				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## Unit holder dealt blc

Attribute	Description						
Name	Unit holder dealt blc						
Datatype							
Description	Indicates Unit holder deal details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## OVERRIDE TO

Attribute	Description				
Name	OVERRIDE TO				
Datatype	Number				
Description	Indicates Override To				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## 2.3.2.UT-DeleteUHDeal-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Dealinfo-IO

DEAL\_TRANSACTION\_NUMBER

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-IO

Attribute	Description
Name	Dealinfo-IO
Datatype	
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

### 2.3.3.UT-DeleteUHDeal-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Dealinfo-Full*

*UH\_CIF*

*NAME*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

*LOADDESC*

*AMOUNTORPERCENTAGE*

*LOCAL\_CALC\_METHOD*

PRODUCT\_NAME  
 FUNDFNAME  
 DESCRIPTION  
 MAKER  
 MAKERSTAMP  
 CHECKER  
 CHECKERSTAMP  
 MODNO  
 TXNSTAT  
 AUTHSTAT  
 Unitholderdealtblb  
 SLABSEQ  
 OVERRIDETO  
 Unitholderdealtblc  
 OVERRIDETO  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-Full

Attribute	Description
Name	Dealinfo-Full
Datatype	
Description	

[TOP](#)

## UH\_CIF

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**APPLY\_AT\_CIF\_LEVEL**

Attribute	Description	
Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	Attribute	Description
	minOccurs	1

**APPLYDEALAT**

Attribute	Description	
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	L,G,F,P

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,C

**EFFECTIVE\_START\_DATE**

Attribute	Description	
Name	EFFECTIVE_START_DATE	
Datatype	Date	
Description	Indicates Effective Start Date	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTIVE\_END\_DATE**

Attribute	Description	
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LOADGROUPID

<b>Attribute</b>	<b>Description</b>	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FUND\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FUND_ID	
Datatype	String	
Description	Indicates Fund Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## LOAD\_ID

<b>Attribute</b>	<b>Description</b>	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>	
Name	MODULE_ID	
Datatype	String	
Description	Indicates Module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

Attribute	Description	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## POLICY\_NUMBER

Attribute	Description	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## DEALBASEDON

Attribute	Description	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TAX\_TYPE

Attribute	Description	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,D,I

[TOP](#)

## LOADDESC

Attribute	Description
Name	LOADDESC

Datatype	String	
Description	Indicates Load Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## AMOUNTORPERCENTAGE

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTORPERCENTAGE	
Datatype	String	
Description	Indicates Amount or percentage	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## LOCAL\_CALC\_METHOD

<b>Attribute</b>	<b>Description</b>	
Name	LOCAL_CALC_METHOD	
Datatype	String	
Description	Indicates load calculation method	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## PRODUCT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_NAME	
Datatype	String	
Description	Indicates Product name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FUNDNAME

<b>Attribute</b>	<b>Description</b>	
Name	FUNDNAME	
Datatype	String	
Description	Indicates Fund name	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Unitholderdealtblb

Attribute	Description	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SLABSEQ

Attribute	Description	
Name	SLABSEQ	
Datatype	Number	
Description	Indicates Slab Number	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## OVERRIDE TO

Attribute	Description	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## Unitholderdealtblc

Attribute	Description	
Name	Unitholderdealtblc	
Datatype		
Description	Indicates Unit holder deal details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## OVERRIDE TO

Attribute	Description	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.3.4.UT-DeleteUHDeal-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*ADDL*  
     *PARAM*  
         *NAME*  
         *VALUE*  
*FCUBS\_BODY*  
     *CHOICE*  
         *Dealinfo-PK*  
             *DEAL\_TRANSACTION\_NUMBER*  
         *Dealinfo-IO*  
             *DEAL\_TRANSACTION\_NUMBER*  
*FCUBS\_ERROR\_RESP*  
     *ERROR*  
         *ECODE*  
         *EDESC*  
*FCUBS\_WARNING\_RESP*  
     *WARNING*  
         *WCODE*  
         *WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## SOURCE\_USERID

Attribute	Description						
Name	SOURCE_USERID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
	minOccurs	0			
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
	minOccurs	0			
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
-----------	-------------

Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Dealinfo-PK

Attribute	Description	
Name	Dealinfo-PK	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description
Name	DEAL_TRANSACTION_NUMBER
Datatype	String
Description	Indicates Deal Transaction Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## Dealinfo-IO

<b>Attribute</b>	<b>Description</b>	
Name	Dealinfo-IO	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE

Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.4.ModifyUHDeal

Modify UHDeal

### 2.4.1.UT-ModifyUHDeal-Req-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Dealinfo-Full*

*UH\_CIF*

*NAME*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

LOADDESC  
 AMOUNTORPERCENTAGE  
 LOCAL\_CALC\_METHOD  
 PRODUCT\_NAME  
 FUNDNAME  
 DESCRIPTION  
 MAKER  
 MAKERSTAMP  
 CHECKER  
 CHECKERSTAMP  
 MODNO  
 TXNSTAT  
 AUTHSTAT  
 Unitholderdealtblb  
     SLABSEQ  
     OVERRIDEO  
 Unitholderdealtblc  
     OVERRIDEO

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
-----------	-------------

Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-Full

Attribute	Description
Name	Dealinfo-Full
Datatype	
Description	

[TOP](#)

## UH\_CIF

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## APPLY\_AT\_CIF\_LEVEL

Attribute	Description	
Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	Attribute	Description
	minOccurs	1

**APPLYDEALAT**

Attribute	Description	
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	L,G,F,P

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,C

**EFFECTIVE\_START\_DATE**

Attribute	Description	
Name	EFFECTIVE_START_DATE	
Datatype	Date	
Description	Indicates Effective Start Date	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTIVE\_END\_DATE**

Attribute	Description	
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	
Attributes	Attribute	Description
	minOccurs	1

**LOADGROUPID**

Attribute	Description	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FUND\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FUND_ID	
Datatype	String	
Description	Indicates Fund Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## LOAD\_ID

<b>Attribute</b>	<b>Description</b>	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>	
Name	MODULE_ID	
Datatype	String	
Description	Indicates Module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)**POLICY\_NUMBER**

Attribute	Description	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**DEALBASEDON**

Attribute	Description	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**TAX\_TYPE**

Attribute	Description	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,D,I

[TOP](#)**LOADDESC**

Attribute	Description	
Name	LOADDESC	
Datatype	String	
Description	Indicates Load Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**AMOUNTORPERCENTAGE**

Attribute	Description	
Name	AMOUNTORPERCENTAGE	
Datatype	String	
Description	Indicates Amount or percentage	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## LOCAL\_CALC\_METHOD

Attribute	Description	
Name	LOCAL_CALC_METHOD	
Datatype	String	
Description	Indicates load calculation method	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## PRODUCT\_NAME

Attribute	Description	
Name	PRODUCT_NAME	
Datatype	String	
Description	Indicates Product name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FUNDNAME

Attribute	Description	
Name	FUNDNAME	
Datatype	String	
Description	Indicates Fund name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date-Time Stamp	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Unitholderdealtblb

<b>Attribute</b>	<b>Description</b>	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SLABSEQ

Attribute	Description				
Name	SLABSEQ				
Datatype	Number				
Description	Indicates Slab Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## OVERRIDE TO

Attribute	Description				
Name	OVERRIDE TO				
Datatype	Number				
Description	Indicates Override To				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## Unitholderdealtblc

Attribute	Description						
Name	Unitholderdealtblc						
Datatype							
Description	Indicates Unit holder deal details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## OVERRIDE TO

Attribute	Description				
Name	OVERRIDE TO				
Datatype	Number				
Description	Indicates Override To				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## 2.4.2.UT-ModifyUHDeal-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Dealinfo-IO*

DEAL\_TRANSACTION\_NUMBER

STATUS

EFFECTIVE\_END\_DATE

MAKER

MAKERSTAMP

*Unitholderdealtblb*

SLABSEQ

OVERRIDE

*Unitholderdealtblc*

OVERRIDE

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description
Name	SOURCE_OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-IO

Attribute	Description
Name	Dealinfo-IO
Datatype	
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description				
Name	DEAL_TRANSACTION_NUMBER				
Datatype	String				
Description	Indicates Unit Holder CIF Number				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## STATUS

Attribute	Description				
Name	STATUS				
Datatype	String				
Description	Indicates Deal Transaction Number				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>A,C</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	A,C
	Restrictions	Description			
enumeration	A,C				

**EFFECTIVE\_END\_DATE**

Attribute	Description	
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	
Attributes	Attribute	Description
	minOccurs	0

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**Unitholderdealtblb**

Attribute	Description	
Name	Unitholderdealtblb	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

**SLABSEQ**

Attribute	Description	
Name	SLABSEQ	
Datatype	Number	

Description	Indicates Slab Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## OVERRIDE TO

<b>Attribute</b>	<b>Description</b>	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Unitholderdealtblc

<b>Attribute</b>	<b>Description</b>	
Name	Unitholderdealtblc	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## OVERRIDE TO

<b>Attribute</b>	<b>Description</b>	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.4.3.UT-ModifyUHDeal-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Dealinfo-Full*

*UH\_CIF*

*NAME*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

*LOADDESC*

*AMOUNTORPERCENTAGE*

*LOCAL\_CALC\_METHOD*

PRODUCT\_NAME  
 FUNDFNAME  
 DESCRIPTION  
 MAKER  
 MAKERSTAMP  
 CHECKER  
 CHECKERSTAMP  
 MODNO  
 TXNSTAT  
 AUTHSTAT  
 Unitholderdealtblb  
 SLABSEQ  
 OVERRIDETO  
 Unitholderdealtblc  
 OVERRIDETO  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-Full

Attribute	Description
Name	Dealinfo-Full
Datatype	
Description	

[TOP](#)

## UH\_CIF

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**APPLY\_AT\_CIF\_LEVEL**

Attribute		Description
Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	Attribute	Description
	minOccurs	1

**APPLYDEALAT**

Attribute		Description
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	L,G,F,P

**STATUS**

Attribute		Description
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,C

**EFFECTIVE\_START\_DATE**

Attribute		Description
Name	EFFECTIVE_START_DATE	
Datatype	Date	
Description	Indicates Effective Start Date	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTIVE\_END\_DATE**

Attribute		Description
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LOADGROUPID

<b>Attribute</b>	<b>Description</b>	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FUND\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FUND_ID	
Datatype	String	
Description	Indicates Fund Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## LOAD\_ID

<b>Attribute</b>	<b>Description</b>	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>	
Name	MODULE_ID	
Datatype	String	
Description	Indicates Module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

Attribute	Description	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## POLICY\_NUMBER

Attribute	Description	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## DEALBASEDON

Attribute	Description	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TAX\_TYPE

Attribute	Description	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,D,I

[TOP](#)

## LOADDESC

Attribute	Description
Name	LOADDESC

Datatype	String	
Description	Indicates Load Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## AMOUNTORPERCENTAGE

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTORPERCENTAGE	
Datatype	String	
Description	Indicates Amount or percentage	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## LOCAL\_CALC\_METHOD

<b>Attribute</b>	<b>Description</b>	
Name	LOCAL_CALC_METHOD	
Datatype	String	
Description	Indicates load calculation method	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## PRODUCT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_NAME	
Datatype	String	
Description	Indicates Product name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FUNDNAME

<b>Attribute</b>	<b>Description</b>	
Name	FUNDNAME	
Datatype	String	
Description	Indicates Fund name	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date-Time Stamp	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Unitholderdealtblb

Attribute	Description	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SLABSEQ

Attribute	Description	
Name	SLABSEQ	
Datatype	Number	
Description	Indicates Slab Number	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## OVERRIDE TO

Attribute	Description	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## Unitholderdealtblc

Attribute	Description	
Name	Unitholderdealtblc	
Datatype		
Description	Indicates Unit holder deal details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## OVERRIDE TO

Attribute	Description	
Name	OVERRIDE TO	
Datatype	Number	
Description	Indicates Override To	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description				
Name	FCUBS_ERROR_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description				
Name	FCUBS_WARNING_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.4.4.UT-ModifyUHDeal-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Dealinfo-PK*  
*DEAL\_TRANSACTION\_NUMBER*  
*Dealinfo-IO*  
*DEAL\_TRANSACTION\_NUMBER*  
*STATUS*  
*EFFECTIVE\_END\_DATE*  
*MAKER*  
*MAKERSTAMP*  
*Unitholderdealtblb*  
*SLABSEQ*  
*OVERRIDETO*  
*Unitholderdealtblc*  
*OVERRIDETO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)**VALUE**

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)**FCUBS\_BODY**

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)**CHOICE**

Attribute	Description	
Name	CHOICE	
Datatype		
Description		

[TOP](#)**Dealinfo-PK**

Attribute	Description	
Name	Dealinfo-PK	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**DEAL\_TRANSACTION\_NUMBER**

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**Dealinfo-IO**

Attribute	Description	
Name	Dealinfo-IO	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**DEAL\_TRANSACTION\_NUMBER**

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,C

**EFFECTIVE\_END\_DATE**

Attribute	Description
Name	EFFECTIVE_END_DATE

Datatype	Date	
Description	Indicates Effective End Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## Unitholderdealtblb

<b>Attribute</b>	<b>Description</b>	
Name	Unitholderdealtblb	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## SLABSEQ

<b>Attribute</b>	<b>Description</b>	
Name	SLABSEQ	
Datatype	Number	
Description	Indicates Slab Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## OVERRIDE

Attribute	Description	
Name	OVERRIDE	
Datatype	Number	
Description	Indicates Override To	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Unitholderdealtblc

Attribute	Description	
Name	Unitholderdealtblc	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## OVERRIDE

Attribute	Description	
Name	OVERRIDE	
Datatype	Number	
Description	Indicates Override To	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description				
Name	FCUBS_WARNING_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.5.QueryUHDeal

Query UHDeal

### 2.5.1.UT-QueryUHDeal-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Dealinfo-IO*

*DEAL\_TRANSACTION\_NUMBER*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## Dealinfo-IO

Attribute	Description
Name	Dealinfo-IO
Datatype	
Description	

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## 2.5.2.UT-QueryUHDeal-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Dealinfo-IO*

*DEAL\_TRANSACTION\_NUMBER*

*Dealinfo-Full*

*UH\_CIF*

*NAME*

*DEAL\_TRANSACTION\_NUMBER*

*APPLY\_AT\_CIF\_LEVEL*

*APPLYDEALAT*

*STATUS*

*EFFECTIVE\_START\_DATE*

*EFFECTIVE\_END\_DATE*

*LOADGROUPID*

*FUND\_ID*

*LOAD\_ID*

*MODULE\_ID*

*PRODUCT\_ID*

*POLICY\_NUMBER*

*DEALBASEDON*

*TAX\_TYPE*

LOADESC  
 AMOUNTORPERCENTAGE  
 LOCAL\_CALC\_METHOD  
 PRODUCT\_NAME  
 FUNDNAME  
 DESCRIPTION  
 MAKER  
 MAKERSTAMP  
 CHECKER  
 CHECKERSTAMP  
 MODNO  
 TXNSTAT  
 AUTHSTAT  
 Unitholderdealtblb  
 SLABSEQ  
 OVERRIDETO  
 Unitholderdealtblc  
 OVERRIDETO  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Dealinfo-IO

Attribute	Description	
Name	Dealinfo-IO	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DEAL\_TRANSACTION\_NUMBER

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Dealinfo-Full

Attribute	Description	
Name	Dealinfo-Full	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**UH\_CIF**

Attribute	Description	
Name	UH_CIF	
Datatype	String	
Description	Indicates Unit Holder CIF Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**NAME**

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)**DEAL\_TRANSACTION\_NUMBER**

Attribute	Description	
Name	DEAL_TRANSACTION_NUMBER	
Datatype	String	
Description	Indicates Deal Transaction Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**APPLY\_AT\_CIF\_LEVEL**

Attribute	Description	
Name	APPLY_AT_CIF_LEVEL	
Datatype	Number	
Description	Indicates Apply at CIF level	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)**APPLYDEALAT**

Attribute	Description	
Name	APPLYDEALAT	
Datatype	String	
Description	Indicates Apply Deal At, L for Load Level, G for Load Group Level, F for Fund Level, P for Product Level	
Attributes	Attribute	Description
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	L,G,F,P

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status, A for Active, C for Cancelled	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,C

[TOP](#)

## EFFECTIVE\_START\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_START_DATE	
Datatype	Date	
Description	Indicates Effective Start Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_END\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_END_DATE	
Datatype	Date	
Description	Indicates Effective End Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LOADGROUPID

<b>Attribute</b>	<b>Description</b>	
Name	LOADGROUPID	
Datatype	String	
Description	Indicates Load Group Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## FUND\_ID

<b>Attribute</b>	<b>Description</b>
Name	FUND_ID

Datatype	String	
Description	Indicates Fund Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## LOAD\_ID

<b>Attribute</b>	<b>Description</b>	
Name	LOAD_ID	
Datatype	Number	
Description	Indicates Load Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## MODULE\_ID

<b>Attribute</b>	<b>Description</b>	
Name	MODULE_ID	
Datatype	String	
Description	Indicates Module Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## PRODUCT\_ID

<b>Attribute</b>	<b>Description</b>	
Name	PRODUCT_ID	
Datatype	String	
Description	Indicates Product Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## POLICY\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	POLICY_NUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## DEALBASEDON

<b>Attribute</b>	<b>Description</b>	
Name	DEALBASEDON	
Datatype	String	
Description	Indicates Deal Based On	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TAX\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	TAX_TYPE	
Datatype	String	
Description	Indicates Tax Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,D,I

[TOP](#)

## LOADDESC

<b>Attribute</b>	<b>Description</b>	
Name	LOADDESC	
Datatype	String	
Description	Indicates Load Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## AMOUNTORPERCENTAGE

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTORPERCENTAGE	
Datatype	String	
Description	Indicates Amount or percentage	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

**LOCAL\_CALC\_METHOD**

Attribute	Description	
Name	LOCAL_CALC_METHOD	
Datatype	String	
Description	Indicates load calculation method	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**PRODUCT\_NAME**

Attribute	Description	
Name	PRODUCT_NAME	
Datatype	String	
Description	Indicates Product name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**FUNDNAME**

Attribute	Description	
Name	FUNDNAME	
Datatype	String	
Description	Indicates Fund name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**DESCRIPTION**

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date-Time Stamp	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date-Time Stamp	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Unitholderdealtblb

<b>Attribute</b>	<b>Description</b>	
Name	Unitholderdealtblb	
Datatype		
Description	Indicates Unit Holder Deal Details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SLABSEQ

<b>Attribute</b>	<b>Description</b>	
Name	SLABSEQ	
Datatype	Number	
Description	Indicates Slab Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## OVERRIDE

Attribute	Description				
Name	OVERRIDE				
Datatype	Number				
Description	Indicates Override To				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## UnitHolderDealBlc

Attribute	Description						
Name	UnitHolderDealBlc						
Datatype							
Description	Indicates Unit holder deal details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## OVERRIDE

Attribute	Description				
Name	OVERRIDE				
Datatype	Number				
Description	Indicates Override To				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description				
Name	FCUBS_ERROR_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description				
Name	FCUBS_WARNING_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



Unit Holder  
[April] [2014]

Oracle Financial Services software Limited  
Oracle Park  
Off Western Express Highway  
Goregaon (East)  
Mumbai, Maharashtra 400 063  
India

Worldwide Inquiries:  
Phone: +91 22 6718 3000  
Fax: +91 22 6718 3001  
[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)

Copyright © [2007], [2013], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

**U.S. GOVERNMENT END USERS:** Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.