

Gateway Documentation - ELSecuritiesService
Oracle FLEXCUBE Universal Banking
Release FCELCM_1.1.13
[October] [2013]



Table Of Contents

1. BACKGROUND	1
2. ELSecuritiesService	2
2.1. SecuritiesAuthorize	2
2.1.1. GE-SecuritiesAuthorize-Req-Full-MSG.xsd	2
2.1.2. GE-SecuritiesAuthorize-Req-IO-MSG.xsd	15
2.1.3. GE-SecuritiesAuthorize-Res-Full-MSG.xsd	22
2.1.4. GE-SecuritiesAuthorize-Res-PK-MSG.xsd	38
2.2. SecuritiesClose	54
2.2.1. GE-SecuritiesClose-Req-Full-MSG.xsd	54
2.2.2. GE-SecuritiesClose-Req-IO-MSG.xsd	67
2.2.3. GE-SecuritiesClose-Res-Full-MSG.xsd	74
2.2.4. GE-SecuritiesClose-Res-PK-MSG.xsd	90
2.3. SecuritiesDelete	106
2.3.1. GE-SecuritiesDelete-Req-Full-MSG.xsd	106
2.3.2. GE-SecuritiesDelete-Req-IO-MSG.xsd	119
2.3.3. GE-SecuritiesDelete-Res-Full-MSG.xsd	126
2.3.4. GE-SecuritiesDelete-Res-PK-MSG.xsd	142
2.4. SecuritiesModify	158
2.4.1. GE-SecuritiesModify-Req-Full-MSG.xsd	158
2.4.2. GE-SecuritiesModify-Req-IO-MSG.xsd	171
2.4.3. GE-SecuritiesModify-Res-Full-MSG.xsd	184
2.4.4. GE-SecuritiesModify-Res-PK-MSG.xsd	206
2.5. SecuritiesNew	229
2.5.1. GE-SecuritiesNew-Req-Full-MSG.xsd	229
2.5.2. GE-SecuritiesNew-Req-IO-MSG.xsd	242
2.5.3. GE-SecuritiesNew-Res-Full-MSG.xsd	255
2.5.4. GE-SecuritiesNew-Res-PK-MSG.xsd	270
2.6. SecuritiesQuery	278
2.6.1. GE-SecuritiesQuery-Req-IO-MSG.xsd	278
2.6.2. GE-SecuritiesQuery-Res-Full-MSG.xsd	285
2.7. SecuritiesReopen	301
2.7.1. GE-SecuritiesReopen-Req-Full-MSG.xsd	301
2.7.2. GE-SecuritiesReopen-Req-IO-MSG.xsd	314
2.7.3. GE-SecuritiesReopen-Res-Full-MSG.xsd	321
2.7.4. GE-SecuritiesReopen-Res-PK-MSG.xsd	337

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.

The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in ELSecuritiesService of EL-Module

2.ELSecuritiesService

ELSecuritiesServiceELSecuritiesService

2.1.SecuritiesAuthorize

Authorisation Of Securities

2.1.1.GE-SecuritiesAuthorize-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-Full

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH
 USERREFNO
 SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	Restrictions
	pattern [a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	Restrictions
	enumeration FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.1.2.GE-SecuritiesAuthorize-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-IO

SECURITYCODE

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.1.3.GE-SecuritiesAuthorize-Res-Full-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
SecurityMaster-IO
SECURITYCODE
MODNO
SecurityMaster-Full
SECURITYCODE
DESCRIPTION
ISSUER
FACEVALUE
CURRENCY
PRICEINCREASESENSITIVITY
PRICEDECREASESENSITIVITY
STARTDATE
EXPIRYDATE
EQUITYBASE
LIMIT
NOMINALVALUEBASED
COLLATERALTYPE
LIABILITYBRANCH
USERREFNO

SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description
-----------	-------------

Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	This indicates the code for the error encountered.

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.1.4.GE-SecuritiesAuthorize-Res-PK-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
SecurityMaster-PK
SECURITYCODE
MODNO
SecurityMaster-IO
SECURITYCODE
MODNO
SecurityMaster-Full
SECURITYCODE
DESCRIPTION
ISSUER
FACEVALUE
CURRENCY
PRICEINCREASESENSITIVITY
PRICEDECREASESENSITIVITY
STARTDATE
EXPIRYDATE
EQUITYBASE
LIMIT
NOMINALVALUEBASED

COLLATERALTYPE
 LIABILITYBRANCH
 USERREFNO
 SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z 0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	This node is to be used for Additional information about a message.

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-PK

Attribute	Description
Name	SecurityMaster-PK
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description
-----------	-------------

Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description
-----------	-------------

Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description
-----------	-------------

Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description
-----------	-------------

Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)**FCUBS_WARNING_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.2.SecuritiesClose

Closure Of Securities

2.2.1.GE-SecuritiesClose-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-Full

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**SOURCE_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z 0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description
Name	PRICEDECREASESENSITIVITY

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description
Name	SecurityPrice

Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.2.2.GE-SecuritiesClose-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-IO

SECURITYCODE

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.2.3.GE-SecuritiesClose-Res-Full-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
SecurityMaster-IO
SECURITYCODE
MODNO
SecurityMaster-Full
SECURITYCODE
DESCRIPTION
ISSUER
FACEVALUE
CURRENCY
PRICEINCREASESENSITIVITY
PRICEDECREASESENSITIVITY
STARTDATE
EXPIRYDATE
EQUITYBASE
LIMIT
NOMINALVALUEBASED
COLLATERALTYPE
LIABILITYBRANCH
USERREFNO

SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	Restrictions
	pattern [a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description
-----------	-------------

Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	This indicates the code for the error encountered.

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.2.4.GE-SecuritiesClose-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

CHOICE

SecurityMaster-PK

SECURITYCODE

MODNO

SecurityMaster-IO

SECURITYCODE

MODNO

SecurityMaster-Full

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE
 LIABILITYBRANCH
 USERREFNO
 SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z 0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	This node is to be used for Additional information about a message.

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-PK

Attribute	Description
Name	SecurityMaster-PK
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description
-----------	-------------

Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description
-----------	-------------

Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description
-----------	-------------

Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description
-----------	-------------

Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)**FCUBS_WARNING_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.3.SecuritiesDelete

Deletion Of Securities

2.3.1.GE-SecuritiesDelete-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-Full

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**SOURCE_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z 0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description
Name	PRICEDECREASESENSITIVITY

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description
Name	SecurityPrice

Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.3.2.GE-SecuritiesDelete-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-IO

SECURITYCODE

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.3.3.GE-SecuritiesDelete-Res-Full-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
SecurityMaster-IO
SECURITYCODE
MODNO
SecurityMaster-Full
SECURITYCODE
DESCRIPTION
ISSUER
FACEVALUE
CURRENCY
PRICEINCREASESENSITIVITY
PRICEDECREASESENSITIVITY
STARTDATE
EXPIRYDATE
EQUITYBASE
LIMIT
NOMINALVALUEBASED
COLLATERALTYPE
LIABILITYBRANCH
USERREFNO

SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	Restrictions
	pattern [a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description	
Name	SecurityMaster-Full	
Datatype		
Description		

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description
-----------	-------------

Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	This indicates the code for the error encountered.

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.3.4.GE-SecuritiesDelete-Res-PK-MSG.xsd

```
FCUBS_HEADER
  SOURCE
  UBSCOMP
  MSGID
  CORRELID
  USERID
  BRANCH
  MODULEID
  SERVICE
  OPERATION
  SOURCE_OPERATION
  SOURCE_USERID
  DESTINATION
  MULTITRIPID
  FUNCTIONID
  ACTION
  MSGSTAT
  ADDL
    PARAM
      NAME
      VALUE
FCUBS_BODY
  CHOICE
    SecurityMaster-IO
      SECURITYCODE
      MODNO
    SecurityMaster-PK
      SECURITYCODE
      MODNO
    SecurityMaster-Full
      SECURITYCODE
      DESCRIPTION
      ISSUER
      FACEVALUE
      CURRENCY
      PRICEINCREASESENSITIVITY
      PRICEDECREASESENSITIVITY
      STARTDATE
      EXPIRYDATE
      EQUITYBASE
      LIMIT
      NOMINALVALUEBASED
```


COLLATERALTYPE
 LIABILITYBRANCH
 USERREFNO
 SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z 0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	This node is to be used for Additional information about a message.

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-PK

Attribute	Description
Name	SecurityMaster-PK
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description
-----------	-------------

Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description
-----------	-------------

Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description
-----------	-------------

Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description
-----------	-------------

Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)**FCUBS_WARNING_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.4.SecuritiesModify

Modification Of Securities

2.4.1.GE-SecuritiesModify-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-Full

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**SOURCE_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z 0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description
Name	PRICEDECREASESENSITIVITY

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**SecurityPrice**

Attribute	Description
Name	SecurityPrice

Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.4.2.GE-SecuritiesModify-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-IO

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description
------------------	--------------------

Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description
Name	FACEVALUE
Datatype	Number
Description	

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**STARTDATE**

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPIRYDATE**

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EQUITYBASE**

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIMIT**

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**NOMINALVALUEBASED**

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.4.3.GE-SecuritiesModify-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

CHOICE

SecurityMaster-IO

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE

MAKERID

MAKERDTSTAMP

CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 SecurityMaster-Full
 SECURITYCODE
 DESCRIPTION
 ISSUER
 FACEVALUE
 CURRENCY
 PRICEINCREASESENSITIVITY
 PRICEDECREASESENSITIVITY
 STARTDATE
 EXPIRYDATE
 EQUITYBASE
 LIMIT
 NOMINALVALUEBASED
 COLLATERALTYPE
 LIABILITYBRANCH
 USERREFNO
 SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE

EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z 0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description
Name	ACTION
Datatype	String

Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
-----------	-------------

Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description
Name	FACEVALUE
Datatype	Number
Description	

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**STARTDATE**

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPIRYDATE**

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EQUITYBASE**

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIMIT**

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**NOMINALVALUEBASED**

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description
-----------	-------------

Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**PRICEINCREASESENSITIVITY**

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PRICEDECREASESENSITIVITY**

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**STARTDATE**

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPIRYDATE**

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EQUITYBASE**

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)**LASTPRICECHANGEDDATE**

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS_ERROR_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)**FCUBS_WARNING_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	

Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.4.4.GE-SecuritiesModify-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

CHOICE

SecurityMaster-PK

SECURITYCODE

MODNO

SecurityMaster-IO

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 SecurityMaster-Full
 SECURITYCODE
 DESCRIPTION
 ISSUER
 FACEVALUE
 CURRENCY
 PRICEINCREASESENSITIVITY
 PRICEDECREASESENSITIVITY
 STARTDATE
 EXPIRYDATE
 EQUITYBASE
 LIMIT
 NOMINALVALUEBASED
 COLLATERALTYPE
 LIABILITYBRANCH
 USERREFNO
 SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

[FCUBS_ERROR_RESP](#)
[ERROR](#)
[ECODE](#)
[EDESC](#)
[FCUBS_WARNING_RESP](#)
[WARNING](#)
[WCODE](#)
[WDESC](#)

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	Restrictions
	pattern [a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	Restrictions
	enumeration FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description
------------------	--------------------

Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-PK

Attribute	Description
Name	SecurityMaster-PK
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description				
Name	SECURITYCODE				
Datatype	String				
Description					
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>19</td></tr> </table>	Restrictions	Description	maxLength	19
Restrictions	Description				
maxLength	19				

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description
Name	FACEVALUE
Datatype	Number
Description	

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**STARTDATE**

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPIRYDATE**

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EQUITYBASE**

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIMIT**

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**NOMINALVALUEBASED**

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	This indicates the code for the error encountered.

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.5.SecuritiesNew

Creation Of Securities

2.5.1.GE-SecuritiesNew-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-Full

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z 0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description
Name	PRICEDECREASESENSITIVITY

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description
Name	SecurityPrice

Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.5.2.GE-SecuritiesNew-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-IO

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description
------------------	--------------------

Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description				
Name	SECURITYCODE				
Datatype	String				
Description					
Attributes	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>1</td></tr> </table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>19</td></tr> </table>	Restrictions	Description	maxLength	19
Restrictions	Description				
maxLength	19				

[TOP](#)

DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	String				
Description					
Attributes	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>1</td></tr> </table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description
Name	FACEVALUE
Datatype	Number
Description	

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**STARTDATE**

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPIRYDATE**

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EQUITYBASE**

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIMIT**

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**NOMINALVALUEBASED**

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.5.3.GE-SecuritiesNew-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

CHOICE

SecurityMaster-Full

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE

MAKERID

MAKERDTSTAMP

CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z 0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z 0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description
-----------	-------------

Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description
------------------	--------------------

Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute		Description
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute		Description
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute		Description
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

*FCUBS_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION**SOURCE_OPERATION**SOURCE_USERID**DESTINATION**MULTITRIPID**FUNCTIONID**ACTION**MSGSTAT**ADDL**PARAM**NAME**VALUE**FCUBS_BODY**CHOICE**SecurityMaster-PK**SECURITYCODE**MODNO**FCUBS_ERROR_RESP**ERROR**ECODE**EDESC**FCUBS_WARNING_RESP**WARNING**WCODE**WDESC***FCUBS_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE

Datatype	
Description	

[TOP](#)

SecurityMaster-PK

Attribute	Description
Name	SecurityMaster-PK
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	This indicates the code for the error encountered.

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)**FCUBS_WARNING_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.6.SecuritiesQuery

Query Securities

2.6.1.GE-SecuritiesQuery-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-IO

SECURITYCODE

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.6.2.GE-SecuritiesQuery-Res-Full-MSG.xsd

FCUBS_HEADER

- SOURCE*
- UBSCOMP*
- MSGID*
- CORRELID*
- USERID*
- BRANCH*
- MODULEID*
- SERVICE*
- OPERATION*
- SOURCE_OPERATION*
- SOURCE_USERID*
- DESTINATION*
- MULTITRIPID*
- FUNCTIONID*
- ACTION*
- MSGSTAT*
- ADDL*
 - PARAM*
 - NAME*
 - VALUE*

FCUBS_BODY

- CHOICE*
 - SecurityMaster-IO*
 - SECURITYCODE*
 - MODNO*
 - SecurityMaster-Full*
 - SECURITYCODE*
 - DESCRIPTION*
 - ISSUER*
 - FACEVALUE*
 - CURRENCY*
 - PRICEINCREASESENSITIVITY*
 - PRICEDECREASESENSITIVITY*
 - STARTDATE*
 - EXPIRYDATE*
 - EQUITYBASE*
 - LIMIT*
 - NOMINALVALUEBASED*
 - COLLATERALTYPE*
 - LIABILITYBRANCH*
 - USERREFNO*

SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description	
Name	SecurityMaster-Full	
Datatype		
Description		

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description
-----------	-------------

Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	This indicates the code for the error encountered.

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.7.SecuritiesReopen

Reopen Securities

2.7.1.GE-SecuritiesReopen-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-Full

SECURITYCODE

DESCRIPTION

ISSUER

FACEVALUE

CURRENCY

PRICEINCREASESENSITIVITY

PRICEDECREASESENSITIVITY

STARTDATE

EXPIRYDATE

EQUITYBASE

LIMIT

NOMINALVALUEBASED

COLLATERALTYPE

LIABILITYBRANCH

USERREFNO

SOURCE

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**SOURCE_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z 0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description
Name	PRICEDECREASESENSITIVITY

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description
Name	SecurityPrice

Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.7.2.GE-SecuritiesReopen-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

SecurityMaster-IO

SECURITYCODE

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.7.3.GE-SecuritiesReopen-Res-Full-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
SecurityMaster-IO
SECURITYCODE
MODNO
SecurityMaster-Full
SECURITYCODE
DESCRIPTION
ISSUER
FACEVALUE
CURRENCY
PRICEINCREASESENSITIVITY
PRICEDECREASESENSITIVITY
STARTDATE
EXPIRYDATE
EQUITYBASE
LIMIT
NOMINALVALUEBASED
COLLATERALTYPE
LIABILITYBRANCH
USERREFNO

SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description
Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description
-----------	-------------

Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description	
Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description	
Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	This indicates the code for the error encountered.

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.7.4.GE-SecuritiesReopen-Res-PK-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
SecurityMaster-PK
SECURITYCODE
MODNO
SecurityMaster-IO
SECURITYCODE
MODNO
SecurityMaster-Full
SECURITYCODE
DESCRIPTION
ISSUER
FACEVALUE
CURRENCY
PRICEINCREASESENSITIVITY
PRICEDECREASESENSITIVITY
STARTDATE
EXPIRYDATE
EQUITYBASE
LIMIT
NOMINALVALUEBASED

COLLATERALTYPE
 LIABILITYBRANCH
 USERREFNO
 SOURCE
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 SecurityPrice
 SECURITY
 PRICECODE
 MARKETPRICE
 LASTPRICECHANGEDDATE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z 0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z 0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	This node is to be used for Additional information about a message.

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

SecurityMaster-PK

Attribute	Description
Name	SecurityMaster-PK
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-IO

Attribute	Description
Name	SecurityMaster-IO
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SecurityMaster-Full

Attribute	Description
-----------	-------------

Name	SecurityMaster-Full
Datatype	
Description	

[TOP](#)

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FACEVALUE

Attribute	Description	
Name	FACEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

CURRENCY

Attribute	Description
-----------	-------------

Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

PRICEINCREASESENSITIVITY

Attribute	Description	
Name	PRICEINCREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRICEDECREASESENSITIVITY

Attribute	Description	
Name	PRICEDECREASESENSITIVITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPIRYDATE

Attribute	Description	
Name	EXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EQUITYBASE

Attribute	Description
-----------	-------------

Name	EQUITYBASE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOMINALVALUEBASED

Attribute	Description	
Name	NOMINALVALUEBASED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALTYPE

Attribute	Description	
Name	COLLATERALTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LIABILITYBRANCH

Attribute	Description	
Name	LIABILITYBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

SecurityPrice

Attribute	Description	
Name	SecurityPrice	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

SECURITY

Attribute	Description
Name	SECURITY
Datatype	Number
Description	

[TOP](#)

PRICECODE

Attribute	Description	
Name	PRICECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

MARKETPRICE

Attribute	Description
-----------	-------------

Name	MARKETPRICE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LASTPRICECHANGEDDATE

Attribute	Description	
Name	LASTPRICECHANGEDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)**FCUBS_WARNING_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)



ELCoreService
[October] [2013]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2013], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.