

Gateway Documentation - Term Deposit Address Maintenance Service
Oracle FLEXCUBE Universal Banking Release 11.3.83.02.0
Release FCUBS_11.3.2.0.0LA
[April] [2014]



Table Of Contents

1. BACKGROUND	1
2. FCUBSTDAAddrService	2
2.1. ModifyTDAddress	2
2.1.1. <i>TD-Addr-Modify-Req-MSG.xsd</i>	2
2.1.2. <i>TD-Addr-Modify-Res-PK-MSG.xsd</i>	15

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.

The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSTDAAddrService of Core-Module

2.FCUBSTDAAddrService

Term Deposit Address Maintenance ServiceTerm Deposit Address Maintenance Service

2.1.ModifyTDAddress

Modification of Term Deposit

2.1.1.TD-Addr-Modify-Req-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

TDAddress

XREF

CUSTACNO

BRN

CUSTACCADDRESS

MEDIA

LOC

LANG

NAME

DEFAULTADDR

COUNTRY

ADDRLN1

ADDRLN2

[ADDRLN3](#)
[ADDRLN4](#)
[TESTKEYWORD](#)
[DELIVERYBY](#)
[SENDBYEMAIL](#)
[ADDHOLDMAIL](#)
[ANSWERBACK](#)
[MSGADDRESS](#)
[MODULE](#)
[MSGTYPE](#)
[COPIES](#)
[FORMAT](#)
[PRADD](#)

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
	Attribute	Description					
	minOccurs	0					
nillable	true						

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for defining a Term Deposit address that needs to be modified

[TOP](#)

TDAddress

Attribute	Description
Name	TDAddress
Datatype	
Description	Indicates Term Deposits Address details

[TOP](#)

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	This specifies the Customer Account number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

[TOP](#)

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

CUSTACCADDRESS

Attribute	Description
Name	CUSTACCADDRESS
Datatype	
Description	Indicates the Customer Account Address details

[TOP](#)

MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description	Indicates the media.	
Restrictions	Restrictions	Description
	maxLength	15
	minLength	1

[TOP](#)

LOC

Attribute	Description	
Name	LOC	
Datatype	String	
Description	Indicates the location.	
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description	Indicates the language of the Customer.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

[TOP](#)

NAME

Attribute	Description
------------------	--------------------

Name	NAME
Datatype	String
Description	

[TOP](#)

DEFAULTADDR

Attribute	Description	
Name	DEFAULTADDR	
Datatype	String	
Description	Indicates the Default Address preference Y for Yes;N for No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description	Indicates the Country to which the Customer belongs to.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3
	pattern	[A-Z]*

[TOP](#)

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description	Indicates the first line of the address	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description	Indicates the second line of the address	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description	Indicates the third line of the address	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ADDRLN4

Attribute	Description	
Name	ADDRLN4	
Datatype	String	
Description	Indicates the fourth line of the address	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

TESTKEYWORD

Attribute	Description	
Name	TESTKEYWORD	
Datatype	String	
Description	Indicates the test word allotted to the customer. This field is applicable only if the message is transmitted through Telex	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

DELIVERYBY

Attribute	Description	
Name	DELIVERYBY	
Datatype	String	
Description	Indicates the mode of delivery.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

SENDBYEMAIL

Attribute	Description	
Name	SENDBYEMAIL	
Datatype	String	
Description	Indicates if the advice needs to be sent by email. If the option is checked the email address can be captured in the first address line	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

ADDHOLDMAIL

Attribute	Description	
Name	ADDHOLDMAIL	
Datatype	String	
Description	If this option is checked, then all the mail advice generated for this customer and location would have the hold mail text displayed on top of the message. As a consequence, these mail advices would not be dispatched to the customer unless required.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

ANSWERBACK

Attribute	Description	
Name	ANSWERBACK	
Datatype	String	
Description	Indicates the answer back code for the customer. This field is applicable only if the message is transmitted through Telex	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

MSGADDRESS

Attribute	Description	
Name	MSGADDRESS	
Datatype		
Description	Indicates the address for the message to be sent	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description	Indicates The Module	
Restrictions	Restrictions	Description
	maxLength	2
	minLength	1

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description	Indicates the Message type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

COPIES

Attribute	Description	
Name	COPIES	
Datatype	Number	
Description	Indicates the Number of copies.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	0
	totalDigits	2

FORMAT

Attribute	Description	
Name	FORMAT	
Datatype	String	
Description	Indicates the Message format type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

PRADD

Attribute	Description	
Name	PRADD	
Datatype	String	
Description	Indicates the Primary Address. Y for Yes;N for No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

2.1.2.TD-Addr-Modify-Res-PK-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
TDAddress
XREF
CUSTACNO
BRN
CUSTACCADDRESS
MEDIA
LOC
LANG
NAME
DEFAULTADDR
COUNTRY
ADDRLN1
ADDRLN2
ADDRLN3
ADDRLN4
TESTKEYWORD
DELIVERYBY
SENDBYEMAIL

ADDHOLDMAIL
 ANSWERBACK
 MSGADDRESS
 MODULE
 MSGTYPE
 COPIES
 FORMAT
 PRADD
 TAddress-PK
 XREF
 CUSTACNO
 BRN
 MEDIA
 LOC
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing primary information of the Term Deposit address details that are successfully modified in FLEXCUBE UBS

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

TDAddress

Attribute	Description
Name	TDAddress
Datatype	
Description	Indicates Term Deposits Customer Address details

[TOP](#)

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	This specifies the Customer Account number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates the Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

CUSTACCADDRESS

Attribute	Description
Name	CUSTACCADDRESS
Datatype	
Description	Indicates the Customer Account Address details

MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description	Indicates the media.	
Restrictions	Restrictions	Description
	maxLength	15
	minLength	1

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	Indicates the location.

Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description	Indicates the language of the Customer.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

DEFAULTADDR

Attribute	Description	
Name	DEFAULTADDR	
Datatype	String	
Description	Indicates the Default Address preference Y for Yes;N for No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description	Indicates the Country to which the Customer belongs to.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3
	pattern	[A-Z]*

[TOP](#)

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description	Indicates the first line of the address	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description	Indicates the second line of the address	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description	Indicates the third line of the address	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ADDRLN4

Attribute	Description	
Name	ADDRLN4	
Datatype	String	
Description	Indicates the fourth line of the address	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

TESTKEYWORD

Attribute	Description
-----------	-------------

Name	TESTKEYWORD	
Datatype	String	
Description	Indicates the test word allotted to the customer. This field is applicable only if the message is transmitted through Telex	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

DELIVERYBY

Attribute	Description	
Name	DELIVERYBY	
Datatype	String	
Description	Indicates the mode of delivery.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

SENDBYEMAIL

Attribute	Description	
Name	SENDBYEMAIL	
Datatype	String	
Description	Indicates if the advice needs to be sent by email. If the option is checked the email address can be captured in the first address line	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

ADDHOLDMAIL

Attribute	Description	
Name	ADDHOLDMAIL	
Datatype	String	
Description	If this option is checked, then all the mail advice generated for this customer and location would have the hold mail text displayed on top of the message. As a consequence, these mail advices would not be dispatched to the customer unless required.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

ANSWERBACK

Attribute	Description
------------------	--------------------

Name	ANSWERBACK	
Datatype	String	
Description	Indicates the answer back code for the customer. This field is applicable only if the message is transmitted through Telex	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

MSGADDRESS

Attribute	Description	
Name	MSGADDRESS	
Datatype		
Description	Indicates the address for the message to be sent	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description	Indicates The Module	
Restrictions	Restrictions	Description
	maxLength	2
	minLength	1

[TOP](#)

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description	Indicates the Message type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

COPIES

Attribute	Description	
Name	COPIES	
Datatype	Number	
Description	Indicates the Number of copies.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	0
	totalDigits	2

[TOP](#)

FORMAT

Attribute	Description	
Name	FORMAT	
Datatype	String	
Description	Indicates the Message format type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

PRADD

Attribute	Description	
Name	PRADD	
Datatype	String	
Description	Indicates the Primary Address. Y for Yes;N for No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

TDAddress-PK

Attribute	Description
Name	TDAddress-PK
Datatype	
Description	Indicates Term Deposits Customer Address-PK details

[TOP](#)

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

CUSTACNO

Attribute	Description						
Name	CUSTACNO						
Datatype	String						
Description	This specifies the Customer Account number.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	20	pattern	[a-zA-Z0-9]*
	Restrictions	Description					
	maxLength	20					
pattern	[a-zA-Z0-9]*						

[TOP](#)

BRN

Attribute	Description						
Name	BRN						
Datatype	String						
Description	Indicates the Branch						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

MEDIA

Attribute	Description						
Name	MEDIA						
Datatype	String						
Description	Indicates the media.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	15	minLength	1
	Restrictions	Description					
	maxLength	15					
minLength	1						

[TOP](#)

LOC

Attribute	Description				
Name	LOC				
Datatype	String				
Description	Indicates the location.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
	Restrictions	Description			
maxLength	15				

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



**Term Deposit Address Maintenance Service
[April] [2014]**

**Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India**

**Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/**

Copyright © [2013], [2014], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.