



API Reference Guide
Release 9.0

May 2015

Contents

Getting Started	9
Recommendations	9
Requirements	9
Integration Functions Overview	11
Function Invocation.....	13
Invocation Parameters.....	13
global_properties Object.....	14
Login Function	17
Invocation Syntax	17
Invocation Parameters.....	17
Output Parameters.....	18
Output Examples	18
Logout Function	21
Invocation Syntax	21
Output Example.....	21
GetActivityAssignments Function.....	23
Invocation Parameters.....	23
Invocation Example.....	23
Input Parameters	23
Input Examples.....	27
Output Parameters.....	29
Output Example.....	32
UpdateResourceEffort Function	35
Invocation Parameters.....	35
Invocation Example.....	35
Input Parameters	36
Input Example.....	46
Output Parameters.....	50
Output Examples	53
UpdateActivity Function	55
Invocation Parameters.....	55
Invocation Example.....	55
Input Parameters	55
Input Examples.....	62
Output Parameters.....	65
Output Example.....	66

GetFinanceData Function	69
Invocation Parameters	69
Invocation Example	69
Input Parameters	69
Input Examples	75
Output Parameters	78
Output Example	78
Automated Data Upload	79
receivedata Function	79
Invocation Syntax	79
Invocation Example	80
Invocation Parameters	80
Output	84
Output Examples	84
getstatus Function	85
Invocation Syntax	85
Invocation Example	85
Output	85
Output Examples	85
Project CRUD APIs	87
Create Function	87
Invocation Syntax	87
Invocation Examples	87
Invocation Parameters	88
Input Parameters	88
Input Examples	89
Input Example in XML Format	90
Input Example in JSON Format	94
Output Examples	98
Output Example in XML Format	98
Output Example in JSON format	98
Create_Template Function	99
Invocation Syntax	99
Invocation Examples	99
Invocation Parameters	99
Input Parameters	100
Input Examples	101
Input Example in XML Format	102
Input Example in JSON Format	102
create_template function Output	102
Output Examples	102
Output Example in XML Format	102
Output Example in JSON Format	106
Update Function	110
Invocation Syntax	110
Invocation Examples	110

Invocation Parameters.....	110
Input Examples.....	112
Input Example in XML Format	112
Input Example in JSON Format.....	115
Output Examples.....	121
Output in XML Format.....	121
Output in JSON Format	122
Update_template Function	122
Invocation Syntax.....	122
Invocation Examples	123
Invocation Parameters.....	123
Input Parameters	123
Input Examples.....	124
Input Example in XML Format	124
Input Example in JSON Format.....	125
Output	125
Output Examples	125
Output Example in XML Format.....	125
Output Example in JSON Format.....	130
Delete Function	130
Invocation Syntax.....	131
Invocation Examples	131
Invocation Parameters.....	131
Input Parameters	131
Input Examples.....	133
Input Example in XML Format	133
Input Example in JSON Format.....	133
Output Examples.....	134
Output in XML Format	134
Output in JSON Format	135
Delete_template Function	135
Invocation Syntax.....	136
Invocation Examples	136
Invocation Parameters.....	136
Input Parameters	137
Input Examples.....	138
Input Example in XML Format	138
Input Example in JSON Format.....	138
Output	138
Output Examples	138
Output Example in XML Format.....	139
Output Example in JSON Format	139
Search Function	140
Invocation Syntax.....	140
Invocation Examples	140
Invocation Parameters.....	140
Input Parameters	141
Input Examples.....	142
Input Example in XML Format	142
Input Example in JSON Format.....	144

Output Examples	146
Output Example in XML Format	146
Output Example in JSON Format	153
Search_template Function	159
Invocation Syntax	159
Invocation Examples	159
Invocation Parameters	159
Input Parameters	160
Input Examples	161
Input Example in XML Format	161
Input Example in JSON Format	161
Output Examples	162
Output Example in XML Format	162
Output Example in JSON Format	164
Project Finance CRUD APIs	167
Finance	167
Search Function	167
Invocation Syntax	167
Invocation Examples	168
Invocation Parameters	168
Input Parameters	168
Input Examples	169
Input Example in XML Format	169
Input Example in JSON Format	171
Output Examples	173
Output Example in XML Format	173
Output Example in JSON Format	178
Update Function	185
Invocation Syntax	185
Invocation Examples	185
Invocation Parameters	185
Input Examples	187
Input Example in XML Format	187
Input Example in JSON Format	190
Output Examples	192
Output Example in XML Format	192
Output Example in JSON Format	193
Finance Structure	193
Search Function	193
Invocation Syntax	194
Invocation Examples	194
Invocation Parameters	194
Input Parameters	194
Input Examples	195
Input Example in XML Format	195
Input Example in JSON Format	196

Output Examples	197
Output Example in XML Format.....	197
Output Example in JSON Format	209
Finance Snapshot	210
Create Function	210
Invocation Syntax	210
Invocation Example	211
Invocation Parameters	211
Input Parameters.....	211
Input Examples	212
Input Example in XML Format.....	212
Input Example in JSON Format	214
Output Examples	215
Output Example in XML Format.....	215
Output Example in JSON Format	215
Update Function	216
Invocation Syntax	216
Invocation Examples	216
Invocation Parameters	216
Input Examples	218
Input Example in XML Format.....	218
Input Example in JSON Format	221
Output Examples	224
Output Example in XML Format.....	224
Output Example in JSON Format	227
Search Function	227
Invocation Syntax	227
Invocation Examples	227
Invocation Parameters	228
Input Parameters.....	228
Input Examples	229
Input Example in XML Format.....	229
Input Example in JSON Format	232
Output Examples	234
Output Examples in XML Format.....	234
Output Example in JSON Format	242
Delete Function	258
Invocation Syntax	258
Invocation Examples	258
Invocation Parameters	258
Input Parameters.....	258
Input Examples	260
Input Example in XML Format.....	260
Input Example in JSON Format	261
Output Examples	261

Output in XML Format	261
Output in JSON Format	262
Downloading CRUD Templates	262
Timesheet Functions	265
getTimesheetData Function	265
Invocation Syntax	265
Invocation Parameters.....	265
Input Parameters	266
Input Example in JSON Format.....	270
Output	272
Output example	272
getTimesheetCorrections Function	272
Invocation Syntax	272
Invocation Parameters.....	273
Input Parameters	273
Input Example in JSON Format.....	273
Output	275
Output Example.....	275
Preconfigured Remote Reports	276
Invoking Remote Reports	276
Input	277
Output	277
Legal Notices	289

Getting Started

This document provides details useful when designing, programming, deploying, and troubleshooting Web-enabled applications for your Oracle Instantis EnterpriseTrack account. EnterpriseTrack includes an Integration module that allows you to create customized applications that:

- ▶ Obtain activity assignment data
- ▶ Obtain the Project Finances Element Monthly Detail report
- ▶ Update activity data
- ▶ Update effort data
- ▶ Enable automatic data uploads
- ▶ Create, search, update, and delete a project
- ▶ Create, search, update, and delete project finances
- ▶ Generate the Timesheet Detail Report programmatically.

This document also includes details on preconfigured, web-enabled reports that do not require any software development (programming) effort.

In This Section

Recommendations	9
Requirements	9

Recommendations

Before developing any Web service software, you should be familiar with:

- ▶ A programming language or environment for developing Web service applications
- ▶ The fundamentals of Web services (for an overview, go to <http://www.w3schools.com/webservices/default.asp> (see <http://www.w3schools.com/webservices/default.asp> - <http://www.w3schools.com/webservices/default.asp>))
- ▶ The JSON data format (for an overview, go to <http://www.w3schools.com/json/default.asp> (see <http://www.w3schools.com/json/default.asp> - <http://www.w3schools.com/json/default.asp>))

Requirements

Before developing any EnterpriseTrack-specific Web service software, you should:

- ▶ Be familiar with the EnterpriseTrack product, especially those areas you want to manipulate using the Integration functions.
- ▶ Confirm that you have a valid EnterpriseTrack integration user account (login ID and password).
- ▶ To use the financial report related integration function, verify that you have permission to execute the financial report from an interactive session.
- ▶ To use the Timesheet Detail report related integration function, verify that you have permission to execute the timesheet report from an interactive session.
- ▶ To use CRUD functions on the project entity, ensure you also have permissions to generate the templates from the EnterpriseTrack Administration module.
- ▶ To update effort or activity using the integration functions, verify that you have permission to update activities for the project.
- ▶ Verify that you have the **Execute APIs** permission.
- ▶ If invoking the function for someone other than yourself, verify that you have the **Execute APIs as Proxy** permission.
- ▶ To update effort using the Integration functions, also verify the following:
- ▶ If you will be updating efforts for yourself, verify that you have the necessary permissions required to perform this operation interactively.
- ▶ If you will be updating efforts for someone other than yourself, verify that you have the necessary permissions required to perform this operation interactively.

Integration Functions Overview

This chapter describes the integration functions available in EnterpriseTrack.

The following Web service capabilities are supported:

- ▶ Login Function
This function provides the necessary authentication data to your EnterpriseTrack account and starts your Web services session.
- ▶ Logout Function
This function terminates your Web services session.
- ▶ GetActivityAssignments Function
This function fetches the activity information that corresponds to the search criteria (filter data) you specify in the input parameters.
- ▶ UpdateResourceEffort Function
This function updates the effort based on the details you specify in the input parameters.
- ▶ UpdateActivity Function
This function updates the activity data based on the details you specify in the input parameters.
- ▶ GetFinanceData Function
This function fetches the data that is equivalent to the "Project Finances Element Monthly Detail Report" and corresponds to the search criteria you specify in the input parameters.
- ▶ Timesheet Detail Report
The following functions support the Timesheet Detail Report programmatically.
 - ▶ GetTimesheetData Function
This function fetches data for the Timesheet Detail report.
 - ▶ GetTimesheetCorrections Function
This function fetches correction data for the Timesheet Detail report.
- ▶ Automated Data Upload
 - ▶ receivedata Function
This function generates a unique ID for the data upload and uploads the data files
 - ▶ getstatus Function
This function displays the status of the data upload.
- ▶ Project CRUD Operations
The following functions support create, update, delete, and search operations on a project entity in EnterpriseTrack.
 - ▶ Create
The create function allows you to create one or more projects in EnterpriseTrack.
 - ▶ Create_template

The `create_template` function allows you to retrieve a template for project creation. This can be used to define data for creating a project in EnterpriseTrack.

- ▶ **Update**

The `update` function allows you to update one or more projects in EnterpriseTrack.

- ▶ **Update_template**

The `update_template` function allows you to retrieve a template for updating a project. This can be used to define data for updating a project in EnterpriseTrack.

- ▶ **Delete**

The `delete` function allows you to delete one or more projects in EnterpriseTrack.

- ▶ **Delete_template**

The `delete_template` function allows you to retrieve a template for project deletion. This can be used to define data for deleting a project in EnterpriseTrack.

- ▶ **Search**

The `search` function allows you to find one or more projects in EnterpriseTrack.

- ▶ **Search_template**

The `search_template` function allows you to retrieve a template for searching a project. This can be used to define data for searching a project in EnterpriseTrack.

- ▶ **Project Finance CRUD Operations**

- ▶ **Finance**

Update and search operations are supported on project finances.

- ▶ **Finance Structure**

Search operation is supported on project finance structure.

- ▶ **Finance Snapshot**

Create, update, search, and delete operations are supported on finance snapshot.

- ▶ **Preconfigured Remote Reports**

This is a collection of advanced reports that extract data to be used for integration purposes. These reports do not require any software development and can merely be invoked using a URL.

Note: The capitalization used in the name of the Web services functions as described in this document is provided solely to improve clarity and readability—the functions themselves, and their parameters, use all lowercase letters unless otherwise noted.

In This Section

Function Invocation.....	13
global_properties Object	14

Function Invocation

All *programmable* functions are invoked using a SiteWand symbolic submission. (Invocation details for non-programmable capabilities are described in the section.)

An Integration Login relies on the following path:

`https://<server>/SiteWand/Submission/<account_name>/integration/login`

Once successfully logged in, the Integration functions rely on the following path:

`<api_session>`

where:

Placeholder	Description
<code><server></code>	Specifies the IP address or hostname of the server hosting your EnterpriseTrack instance.
<code><account_name></code>	Specifies the account name (or company name) of your EnterpriseTrack instance.
<code><api_session></code>	Specifies the session URL associated with your Integration login. This value is obtained when successfully completing a Login function and the value is similar to the following. <code>https://ABC.example.com/SiteWand/Submission/F_xer34afd2f</code>

The invocation parameters for each function are provided as detailed for each function.

Note: The `/SiteWand/Submission` portion of the URL *is* case sensitive.

Invocation Parameters

The parameters for the invocation of the Login function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or Constant	Description
<code>api_name</code>	String	<code><api_name></code>	Specifies the name of the API. The following APIs are supported: ▶ Create ▶ Search ▶ Update ▶ Delete

			▶ Create_template ▶ Search_template ▶ Update_template ▶ Delete_template
output_type	String	<output_type>	Specifies the data format for the output. Supported formats include: ▶ JSON ▶ XML Note: Functions prior to Release 8.7 support only JSON format.
user_login_id	String	<login_id>	Specifies your EnterpriseTrack login ID. The case sensitivity for this value conforms to that used by your EnterpriseTrack system.
password	String	<pwd>	Specifies the password corresponding to your EnterpriseTrack login ID. The case sensitivity for this value conforms to that used by your EnterpriseTrack system.

global_properties Object

Most of the functions rely on input parameters to specify the search criteria (filter data), or to provide the updates to the EnterpriseTrack data. Conversely, many of the functions rely on output parameters as the mechanism to deliver those results.

To ensure compatibility with the configuration of EnterpriseTrack, the `global_properties` object is included in this collection of parameters. The settings specified in this object perform the necessary "translations" of the data (specified by the other parameters) into the formats compatible with EnterpriseTrack.

Since the majority of the functions use JSON data format, the details are presented in the following table as name/value pairs. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
api_version	String	Yes	et-integration-api-1.0	Specifies the version number of the Integration API software.

char_set	String	Yes	<char_set>	Specifies the character set that EnterpriseTrack is deployed on. Typically, utf-8 is specified.
date_format	String	Optionally required (see description)	<date_format>	Required only if date parameters are used by the Integration function. Specifies the date format that EnterpriseTrack uses. Typically, yyyy/MM/dd is specified.
effort_unit	String	Not applicable	<effort_unit>	Output parameter. Specifies the unit of measurement for effort.
language	String	No	<lang>	Specifies the language that EnterpriseTrack uses. If no value is specified, the language is set to that used for the Login session.

Login Function

The Login function provides the necessary authentication data to your EnterpriseTrack account and, if successful, starts your Web services session.

The other Integration functions can be successfully invoked *only* after the Login function is successful. Once you are logged in, you can invoke any number of Integration functions. POST is the only recommended option. When you are finished with your Web service interactions you should invoke the Logout function. In the event you fail to log out, you will automatically be logged out after the same period of inactivity as an interactive session.

Note: You may have any number and combination of interactive (browser) and Web services sessions.

In This Section

Invocation Syntax	17
Invocation Parameters	17
Output Parameters	18

Invocation Syntax

The syntax for the invocation of the Login function is as follows:

```
https://<server>/SiteWand/Submission/<account_name>/integration/  
login?api_name=login&output_type=  
<output_type>&user_login_id=<login_id>
```

Invocation Parameters

The parameters for the invocation of the Login function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or Constant	Description
api_name	String	<api_name>	Specifies the name of the API. The following APIs are supported: ▶ Create ▶ Search ▶ Update ▶ Delete ▶ Create_template

			▶ Search_template ▶ Update_template ▶ Delete_template
output_type	String	<output_type>	Specifies the data format for the output. Supported formats include: ▶ JSON ▶ XML Note: Functions prior to Release 8.7 support only JSON format.
user_login_id	String	<login_id>	Specifies your EnterpriseTrack login ID. The case sensitivity for this value conforms to that used by your EnterpriseTrack system.
password	String	<pwd>	Specifies the password corresponding to your EnterpriseTrack login ID. The case sensitivity for this value conforms to that used by your EnterpriseTrack system.

Output Parameters

The results of the Login function are provided in JSON data format. The following table details the name/value pairs.

Name	Data Type	Description
result_code	String	Provides the result code for the completion status of the function.
result_reason	String	If the function is successful, NULL results. Otherwise, the reason for the error is returned.
api_url	String	If the function is successful, the <i>session</i> URL is returned. Otherwise, NULL is returned. The <api_session> value that is returned is used by each of the programmable Integration functions.

Output Examples

The results from a successful Login are similar to the following:

```
{
  "result_code": "SUCCESS",
  "result_reason": "",
  "api_url": "https://ABC.example.com/SiteWand/Submission/F_xer34afd
2f"
}
```

The results from a failed Login are similar to the following:

```
{
  "result_code": "ERR_AUTHENTICATION",
  "result_reason": "You specified invalid login information."
  "api_url": "",
}
```


Logout Function

The Logout function terminates your Web services session. This function should always be invoked when you have concluded your Web-service based interactions with your EnterpriseTrack account. In the event you fail to log out, you will automatically be logged out after the same period of inactivity as an interactive session.

Name	Data Type	Placeholder or Constant	Description
api_name	String	logout	Specifies the name of the Integration function.

In This Section

Invocation Syntax	21
Output Example.....	21

Invocation Syntax

The syntax for the invocation of the Logout function is as follows:

`<api_session>?api_name=logout`

Note: There are no input or output parameters for the Logout function.

Output Example

If the Logout function is successful, you are merely logged out of your current Web services session.

GetActivityAssignments Function

The GetActivityAssignments function fetches the activity information that corresponds to the search criteria (filter data) you specify in the input parameters.

In This Section

Invocation Parameters.....	23
Input Parameters.....	23
Output Parameters	29

Invocation Parameters

The parameters for the invocation of the GetActivityAssignments function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or Constant	Description
api_name	String	getactivityassignments	Specifies the name of the Integration function.
input_type	String	JSON	Specifies the data format for the input.
output_type	String	JSON	Specifies the data format for the output.
input_data	String	<i><input_params></i>	Specifies the location of the input parameters. This value is case sensitive.

Invocation Example

The syntax for the invocation of the GetActivityAssignments function is as follows:

```
<api_session>?api_name=getactivityassignments&input_type=JSON  
&output_type=JSON&input_data=<input_params>
```

Input Parameters

The input parameters described in the following table provide the search criteria (filter data) used to identify the data you want. This information should be provided in the JSON formatted data specified by *<input_params>*. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> specifies the global settings for your EnterpriseTrack instance. See "global_properties Object" for details.
application_data	Object	Yes	Not applicable	This <i>object</i> specifies the search criteria. See "application_data" for details.
application_data				
resource_descriptor	Object	Yes	Not applicable	This <i>object</i> specifies the resource. An error results in the event a matching resource cannot be found. See "resource_descriptor" for details.
start_date_from	Date	No	<start_from>	Specifies the beginning date for the range of start dates. This filters on actual (if present) or planned activity dates.
start_date_to	Date	No	<start_to>	Specifies the ending date for the range of start dates. This filters on actual (if present) or planned activity dates.
end_date_from	Date	No	<end_from>	Specifies the beginning date for the range of end dates. This filters on actual (if present) or planned activity dates.
end_date_to	Date	No	<end_to>	Specifies the ending date for the range of end dates. This filters on actual (if present) or planned activity dates.

include_external_wa	Boolean	No	<incl_external>	Indicates whether or not to consider external activities. Valid values are: TRUE FALSE
include_closed_wa	Boolean	No	<incl_closed>	Indicates whether or not to include closed activities. Valid values are: TRUE FALSE (default)
max_rows	Integer	No	<max_rows>	Specifies the maximum number of rows of data to be fetched. The default value is 20.
resource_descriptor A value for at least one of the following parameters must be provided.				
resource_id	String	No	<resource_ID>	Specifies the resource ID. If: A resource_id value is specified Then: All other parameters are ignored. Otherwise: The other resource_descriptor parameters will be used to help identify the resource.

resource_login_id	String	No	<resource_login_ID>	Specifies the login ID. If: A resource_id value <i>is not</i> specified -and if- A resource_login_id value <i>is</i> specified Then: All other parameters are ignored. Otherwise: The other resource_descriptor parameters will be used to help identify the resource.
resource_email	String	No	<resource_email>	Specifies the e-mail address. If: A resource_id value <i>is not</i> specified -and if- A resource_login_id value <i>is not</i> specified -and if- A resource_email value <i>is</i> specified Then: All other parameters are ignored <i>unless</i> multiple resources use the same e-mail address. Otherwise: The other resource_descriptor parameters will be used to help identify the resource.

resource_last_name	String	No	<resource_last_name>	Specifies the last name. If: A resource_id value <i>is not</i> specified -and if- A resource_login_id value <i>is not</i> specified -and if- A resource_email value <i>is not</i> specified, or multiple resources have the same e-mail address Then: The combination of the resource_last_name and resource_first_name values are used to identify the resource. Otherwise: The resource cannot be found and an error results.
resource_first_name	String	No	<resource_first_name>	Specifies the first name.

Input Examples

The syntax for the GetActivityAssignments data input parameters is as follows:

```
{
  "global_properties":
  {
    "char_set": "<char_set>",
    "date_format": "<date_format>",
    "language": "<lang>"
    "api_version": "et-integration-api-1.0",
  },
  "application_data":
  {
    "resource_descriptor":
    {
      "resource_id": "<resource_ID>",
```

```
        "resource_login_id": "<resource_login_ID>",
        "resource_email": "<resource_email>",
        "resource_first_name": "<resource_first_name>",
        "resource_last_name": "<resource_last_name>"
    },
    "start_date_from": "<start_from>",
    "start_date_to": "<start_to>",
    "end_date_from": "<end_from>",
    "end_date_to": "<end_to>",
    "include_external_wa": "<incl_external>",
    "include_closed_wa": "<incl_closed>",
    "max_rows": "<max_rows>"
}
}
```

This is an example with values for the placeholders:

```
{
  "global_properties":
  {
    "char_set": "utf-8",
    "date_format": "yyyy/mm/dd",
    "language": "en"
    "api_version": "et-integration-api-1.0",
  },

  "application_data":
  {
    "resource_descriptor":
    {
      "resource_id": "GHGHG545TRT",
      "resource_login_id": "ashish_nathani",
      "resource_email": "john.smith@example.com",
      "resource_first_name": "john",
      "resource_last_name": "smith"
    },
    "start_date_from": "2011/12/01",
    "start_date_to": "2011/12/31",
    "end_date_from": "2011/12/01",
    "end_date_to": "2011/12/31",
    "include_external_wa": "TRUE",
    "include_closed_wa": "FALSE",
    "max_rows": "20"
  }
}
```

Output Parameters

The results of the GetActivityAssignments function are provided in JSON data format. The following table details the name/value pairs.

Name	Data Type	Description
global_properties	Object	This <i>object</i> lists the global settings for your EnterpriseTrack instance. See "global_properties Object" for details.
application_data	Object	This <i>object</i> lists your search criteria and provides the results. See "application_data" for details.
application_data		
et_transaction_id	String	Provides the unique EnterpriseTrack transaction ID that is stored in the audit tables.
result_code	String	Provides the result code for the completion status of the function.
result_reason	String	If the function is successful, NULL is returned. Otherwise, the reason for the error is returned.
activity_descriptor_list	Object	This <i>object</i> contains the lists of activities corresponding to the search criteria you specified. See "activity_descriptor_list" for details.
activity_descriptor_list		
resource_descriptor	Object	This <i>object</i> specifies the resource. See "resource_descriptor" for details.
total_assignments	Integer	Provides the total number of assignments for the specified resource.
rows_returned	Integer	Specifies the number of activities actually returned. This could be different from the number of total assignments due to the restrictions imposed by the max_rows value you specified in the input parameters.
activity_descriptor	Array of Objects	These <i>objects</i> contain the details of an activity. See "activity_descriptor" for details.
project_descriptor	Object	This <i>object</i> provides the details of the project. See "project_descriptor" for details.
resource_descriptor		

resource_id	String	Specifies the resource ID.
resource_login_id	String	Specifies the login ID.
resource_email	String	Specifies the e-mail address.
resource_last_name	String	Specifies the last name.
resource_first_name	String	Specifies the first name.
activity_descriptor		
activity_id	String	Provides the ID for the activity.
activity_name	String	Provides the name of the activity.
activity_desc	String	Provides the comments associated with the activity.
activity_type	String	Provides the type of the activity.
activity_planned_start_date	Date	Provides the planned start date of the activity. In some cases, this value may be NULL.
activity_planned_end_date	Date	Provides the planned end date of the activity. In some cases, this value may be NULL.
activity_actual_start_date	Date	Provides the actual start date of the activity.
activity_actual_end_date	Date	Provides the actual end date of the activity.
activity_actual_efforts	Number	Provides the actual effort for the activity.
activity_remaining_efforts	Number	Provides the computed remaining effort for the activity.
activity_planned_efforts	Number	Provides the planned effort for the activity.
activity_percent_completion	Number	Provides the percentage completion of the activity.
activity_owner_info	String	Specifies the name(s) of the activity owner. The format is last name, comma, a space, first name, a space, and then the role enclosed in parentheses. Multiple values should be separated by semicolons. For example: John, Smith (Project Manager); John, Jones (Network Admin).

activity_ baseline_start_date	Date	Provides the baseline start date for the activity.
activity_ baseline_end_date	Date	Provides the baseline end date for the activity.
activity_planned_ effort_type	String	Provides the planned effort type for the activity.
activity_actual_ effort_type	String	Provides the actual effort type for the activity.
status_descriptor	Object	This <i>object</i> specifies the status of the activity. See "status_descriptor" for details.
role_descriptor	Object	This <i>object</i> provides details about the role. See "role_descriptor" for details.
activity_external	String	Indicates whether or not the activity is tracked outside of the EnterpriseTrack. Expected values are: ▶ YES ▶ NO
activity_ external_id	String	Provides the external ID if the activity is tracked outside of the EnterpriseTrack. This value is typically NULL when the value for activity_assignment_external is NO.
project_descriptor	Object	This <i>object</i> provides the project details. See "project_descriptor" for details.
status_descriptor		
status_id	String	Provides the ID of the status.
status_desc	String	Provides the description of the status.
role_descriptor		
role_id	String	Provides the ID of the role.
role_desc	String	Provides the description of the role.
project_descriptor		
project_id	Integer	Provides the ID for the project.
project_name	String	Provides the name for the project.
project_manager	String	Provides the name of the manager of the project.
project_status	String	Provides the status of the project.

project_program	String	Provides the names of the programs associated with the project.
-----------------	--------	---

Output Example

The syntax for the JSON formatted parameters from a successful GetActivityAssignments function is similar to the following.

```
{
  "global_properties":
  {
    "char_set": "<some_character_set>",
    "date_format": "<some_date_format>",
    "effort_unit": "<some_units_for_effort>",
    "language": "<some_language>"
    "api_version": "et-integration-api-1.0",
  },

  "application_data":
  {
    "et_transaction_id": "<unique_transaction_ID>",
    "result_code": "<result_code>",
    "result_reason": "<result_reason>",
    "activity_descriptor_list":
    {
      "resource_descriptor":
      {
        "resource_id": "<some_value>",
        "resource_login_id": "<some_value>",
        "resource_email": "<some_value>",
        "resource_last_name": "<some_value>",
        "resource_first_name": "<some_value>"
      },
      "total_assignments": "<number_of_activities>",
      "rows_returned": "<number_of_rows_returned>",
      "activity_descriptor":
      [
        {
          "activity_id": "<ID_1>",
          "activity_name": "<activity_name>",
          "activity_desc": "<activity_description>",
          "activity_type": "<activity_type>",
          "activity_planned_start_date": "<some_date>",
          "activity_planned_end_date": "<some_date>",
```

```
"activity_actual_start_date": "<some_date>",
"activity_actual_end_date": "<some_date>",
"activity_actual_efforts": "<actual_efforts_value>",
"activity_remaining_efforts": "<remaining_efforts_value>",
"activity_planned_efforts": "<planned_efforts_value>",
"activity_percent_completion": "<some_value>",
"activity_owner_info": "<list_of_owners>",
"activity_baseline_start_date": "<some_date>",
"activity_baseline_end_date": "<some_date>",
"activity_planned_effort_type": "<PET_value>",
"activity_actual_effort_type": "<AET_value>",
"status_descriptor":
{
    "status_id": "<status_ID>",
    "status_desc": "<status_description>"
},
"role_descriptor":
{
    "role_id": "<role_ID>",
    "role_desc": "<role_description>"
},
"activity_external": "<yes|no>",
"activity_external_id": "<some_ID>",
"project_descriptor":
{
    "project_id": "<project_ID>",
    "project_name": "<project_name>",
    "project_manager": "<project_manager_name>",
    "project_status": "<project_status>",
    "project_program": "<list_of_program_names>"
}
},
{
    "activity_id": "<ID_2>",
    "activity_name": "<activity_name>",
    "activity_desc": "<activity_description>",
    "activity_type": "<activity_type>",
    "activity_planned_start_date": "<some_date>",
    "activity_planned_end_date": "<some_date>",
    "activity_actual_start_date": "<some_date>",
    "activity_actual_end_date": "<some_date>",
    "activity_actual_efforts": "<actual_efforts_value>",
    "activity_remaining_efforts": "<remaining_efforts_value>",
    "activity_planned_efforts": "<planned_efforts_value>",
    "activity_percent_completion": "<some_value>",
```

```
"activity_owner_info": "<list_of_owners>",
"activity_baseline_start_date": "<some_date>",
"activity_baseline_end_date": "<some_date>",
"activity_planned_effort_type": "<PET_value>",
"activity_actual_effort_type": "<AET_value>",
"status_descriptor":
{
    "status_id": "<status_ID>",
    "status_desc": "<status_description>"
},
"role_descriptor":
{
    "role_id": "<role_ID>",
    "role_desc": "<role_description>"
},
"activity_external": "<yes|no>",
"activity_external_id": "<some_ID>",
"project_descriptor":
{
    "project_id": "<project_ID>",
    "project_name": "<project_name>",
    "project_manager": "<project_manager_name>",
    "project_status": "<project_status>",
    "project_program": "<list_of_program_names>"
}
}
]
}
}
```

UpdateResourceEffort Function

The UpdateResourceEffort function updates the effort for an activity based on the details you specify in the input parameters.

In This Section

Invocation Parameters.....	35
Input Parameters.....	36
Output Parameters	50

Invocation Parameters

The parameters for the invocation of the UpdateResourceEffort function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or Constant	Description
api_name	String	UpdateResourceEffort	Specifies the name of the Integration function.
input_type	String	JSON	Specifies the data format for the input parameters.
output_type	String	JSON	Specifies the data format for the output parameters.
input_data	String	<input_params>	Specifies the location of the input parameters. This value is case sensitive.

Invocation Example

The syntax for the invocation of the UpdateResourceEffort function is as follows:

```
<api_session>?api_name=updateresourceeffort&input_type=JSON  
&output_type=JSON&input_data=<input_params>
```

Input Parameters

The input parameters described in the following table provide the search criteria (filter data) to identify the activity, as well as to specify the updated effort data you want to commit. This information should be provided in the JSON formatted data specified by `<input_params>`. Unless otherwise specified, all values are not case sensitive.

Note: This function includes a "test" feature (see **test_mode**) that allows you to verify that the information you include in the input parameters can be successfully committed. Since there is no mechanism to "roll back" invalid data, you are encouraged to "test" the data before actually committing any updates.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> specifies the global settings for your EnterpriseTrack instance. See the "global_properties Object" for details.
application_data	Object	Yes	Not applicable	This <i>object</i> specifies the search criteria as well as the revised effort data. See "application_data" for details.
application_data				
source_application_descriptor	Object	Yes	Not applicable	This object specifies the information you want stored in the audit tables. See "source_application_descriptor" for details.
security_descriptor	Object	Yes	Not applicable	This object specifies the authentication information to be verified. See "security_descriptor" for details.
resource_descriptor	Object	Yes	Not applicable	This <i>object</i> specifies the resource. An error results in the event a matching resource cannot be found. See "resource_descriptor" for details.

project_descriptor	Object	Optionally required (see description)	Not applicable	Required only if operation_type has one of the following values: ▶ INTERNAL_ACTIVITY ▶ EXTERNAL_ACTIVITY ▶ PROJECT_TIME This object specifies the project details. See "project_descriptor" for details.
time_category_descriptor	Object	Optionally required (see description)	Not applicable	Required only if operation_type has one of the following values: ▶ NON_PROJECT_TIME ▶ NON_WORKING_TIME This object specifies the category information for the effort. See "time_category_descriptor" for details.
operation_type	String	Yes	<op_type>	Specifies the type of operation. Valid values are: ▶ INTERNAL_ACTIVITY ▶ EXTERNAL_ACTIVITY ▶ PROJECT_TIME ▶ NON_PROJECT ▶ NON_WORKING_TIME
test_mode	Boolean	No	<test_mode>	Indicates whether or not this invocation of the function is merely a test. Valid values are: ▶ TRUE ▶ FALSE (default) If test_mode is FALSE, then the updates will be committed in the EnterpriseTrack database.
source_application_descriptor				
source_app	String	Yes	<source_App>	Specifies the name of the source application.
source_ref_unique_id	String	Yes	<source_ID>	Specifies the ID of the caller of the Integration function.

source_ref_description	String	Yes	<source_desc>	Specifies the description of the caller of the Integration function.
source_ref_type	String	Yes	<source_type>	Specifies the reference type of the caller of the Integration function.
security_descriptor				
authorization_policy	String	Yes	<auth_policy>	Specifies the authorization policy to be used. Valid values are: ▶ AUTHORIZE_WITH_LOGIN_RESOURCE - Execute using the permissions of the logged in Integration user. ▶ AUTHORIZE_WITH_RECORD_LOCATOR_RESOURCE - Execute using the permissions of the resource specified in resource_descriptor. ▶ AUTHORIZE_WITH_AUTHORIZATION_POLICY_GIVEN_RESOURCE - Execute using the permissions of the resource specified in authorization_policy_given_resource_descriptor.

authorization_policy_given_resource_descriptor	Object	Optionally required (see description)	Not applicable	Required only if authorization_policy has the following value: ▶ AUTHORIZE_WITH_AUTHORIZATION_POLICY_GIVEN_RESOURCE - This <i>object</i> specifies the resource whose permissions should be used to execute the function. See "authorization_policy_given_resource_descriptor" for details.
authorization_policy_given_resource_descriptor				
resource_id	String	No	<auth_resource_ID>	Specifies the resource ID of the authorized resource. If a resource_id value is specified then all other parameters are ignored. Otherwise, the other resource_descriptor parameters will be used to help identify the resource.
resource_login_id	String	No	<auth_resource_login_ID>	Specifies the login ID of the authorized resource. If a resource_id value is not specified and if a resource_login_id value is specified, then all other parameters are ignored. Otherwise, the other resource_descriptor parameters will be used to help identify the resource.

resource_email	String	No	<auth_resource_email >	Specifies the e-mail address of the authorized resource. If a resource_id value is not specified and if a resource_login_id value is not specified and if a resource_email value is specified, then all other parameters are ignored unless multiple resources use the same e-mail address. Otherwise, the other resource_descriptor parameters will be used to help identify the resource.
resource_last_name	String	No	<auth_resource_last_name>	Specifies the last name of the authorized resource. If, a resource_id value is <i>not</i> specified and if a resource_login_id value is <i>not</i> specified and if a resource_email value is <i>not</i> specified, or multiple resources have the same e-mail address, then the combination of the resource_last_name and resource_first_name values are used to identify the resource. Otherwise, the resource cannot be found and an error results.
resource_first_name	String	No	<auth_resource_first_name >	Specifies the first name of the authorized resource.

resource_descriptor				
A value for at least one of the parameters must be provided.				
resource_id	String	No	<resource_ID >	Specifies the resource ID of the resource. If a resource_id value is specified then all other parameters are ignored. Otherwise, the other resource_descriptor parameters will be used to help identify the resource.
resource_login_id	String	No	<resource_log in_ID>	Specifies the login ID of the resource. If a resource_id value <i>is not</i> specified and if a resource_login_id value <i>is</i> specified then all other parameters are ignored. Otherwise, the other resource_descriptor parameters will be used to help identify the resource.
resource_email	String	No	<resource_e mail>	Specifies the e-mail address of the resource. If a resource_id value <i>is not</i> specified and if a resource_login_id value <i>is not</i> specified and if a resource_email value <i>is</i> specified, then all other parameters are ignored <i>unless</i> multiple resources use the same e-mail address. Otherwise the other resource_descriptor parameters will be used to help identify the resource.

resource_last_name	String	No	<resource_last_name>	Specifies the last name of the resource. If a resource_id value <i>is not</i> specified and if a resource_login_id value <i>is not</i> specified and if a resource_email value <i>is not</i> specified, or multiple resources have the same e-mail address, then the combination of the resource_last_name and resource_first_name values are used to identify the resource. Otherwise, the resource cannot be found and an error results.
resource_first_name	String	No	<resource_first_name>	Specifies the first name of the resource.
project_descriptor				
All of the values can be NULL if you do not want to filter on the project. If you want to filter on a project, either the project_id and the project_name should be specified. If the project_id and the project_name are both NULL, the project will default to "Operations Project." An error results if there is no project with the name "Operations Project."				
project_id	String	No	<project_ID>	Specifies the ID for the project. If specified and there are no matches, an error results.
project_name	String	No	<project_name>	Specifies the name for the project. If a project_id value <i>is not</i> specified and if a project_name value <i>is</i> specified, then this data used to help identify the project. An error results if a match is not found.
project_manager	String	No	<project_manager>	Specifies the name of the manager of the project.

project_status	String	No	<project_status>	Specifies the status of the project. Valid values match those configured for your EnterpriseTrack application and there is no default value. Some examples of the status for are project are: ▶ Active ▶ On Hold ▶ Canceled ▶ Completed-Post Realization ▶ Closed-In Realization
project_program	String	No	<project_program>	Specifies the name of the program associated with the project.
activity_descriptor	Object	Yes	Not applicable	This object specifies the details of the activity. At least one value must be specified. See "activity_descriptor" for details.
time_category_descriptor	Object	Yes	Not applicable	This object specifies the category for the effort. See "time_category_descriptor" for details.

activity_descriptor				
activity_id	String	Yes	<act_id>	Specifies the activity ID to match. The value is not case sensitive. For internal activities, this corresponds to the EnterpriseTrack activity ID. For external activities, this corresponds to the unique ID assigned for the activities tracked outside of the EnterpriseTrack. For miscellaneous activities, this corresponds to the Enterprise category name. An error results if no matching activity ID for the specified resource is found.
activity_desc	String	No	<act_desc>	Specifies the external activity description to match. For internal or miscellaneous activities, this can be NULL. For external activities, this should match the name of the activity assigned in the EnterpriseTrack.
role_descriptor	Object	Yes	Not applicable	This object specifies the role. See "role_descriptor" for details.
effort_descriptor or	Object	Yes	Not applicable	This object specifies the effort details. See "effort_descriptor" for details.
role_descriptor				
All of the values can be NULL if you do not want to filter on the role. If the role_id and the role_desc are both NULL and the resource has multiple roles in the specified project, an error results.				
role_id	String	No	<role_ID>	Specifies the role ID to match. An error results if no matching role ID for the specified resource is found.

role_desc	String	No	<role_ID>	Specifies the role description to match. An error results if no matching role description for the specified resource is found.
effort_descriptor				
update_action_code	String	Yes	<action_code>	Specifies how the values (for total_hours and overtime_hours) should be used. Valid values are: ▶ REPLACE - Replace disregards the existing value and updates using the new value. ▶ INCREMENT - Increment adds the new value to the existing value, then updates using the new sum.
date	Date	Yes	<date>	Specifies the date to be assigned to the effort. If the effort is tracked using EnterpriseTrack timesheets, then the effort will be revised for the specified date. Otherwise if the effort is tracked as activities, then either the effort will be revised for the week in which the date occurs, or the date will be ignored, and the effort will be revised for that activity.
total_hours	Integer	Yes	<total_hrs>	Specifies the number of non-overtime hours to include. See update_action_code for additional detail.
overtime_hours	Integer	No	<ot_hrs>	Specifies the number of overtime hours to include. See update_action_code for additional detail.

notes	String	No	<notes>	Specifies the remarks to be included with the effort. If activities are tracked using EnterpriseTrack timesheets, the note will be appended to the timesheet notes. Otherwise, the note will be appended to the activity comments.
time_category_descriptor				
time_category_desc	String	Optionally required (see description)	<time_cat>	Required only if operation_type has one of the following values: ▶ NON_PROJECT ▶ NON_WORKING_TIME Specifies the description of the category.
effort_descriptor	Object	Yes	Not applicable	This object specifies the effort details. See "effort_descriptor" for details.

Input Example

The syntax for the UpdateResourceEffort data input parameters is as follows:

```
{
  "global_properties":
  {
    "char_set": "<char_set>",
    "date_format": "<date_format>",
    "language": "<lang>",
    "api_version": "et-integration-api-1.0",
  },

  "application_data":
  {
    "source_application_descriptor":
    {
      "source_app": "<source_App>",
      "source_ref_unique_id": "<source_ID>",
      "source_ref_description": "<source_desc>",
      "source_ref_type": "<source_type>"
    }
  }
}
```

```
},
"security_descriptor":
{
    "authorization_policy": "<auth_policy>",
    "authorization_policy_given_resource_descriptor":
    {
        "resource_id": "<auth_resource_ID>",
        "resource_login_id": "<auth_resource_login_ID>",
        "resource_email": "<auth_resource_email>",
        "resource_first_name": "<auth_resource_last_name>",
        "resource_last_name": "<auth_resource_first_name>"
    }
},
"resource_descriptor":
{
    "resource_id": "<resource_ID>",
    "resource_login_id": "<resource_login_ID>",
    "resource_email": "<resource_email>",
    "resource_first_name": "<resource_last_name>",
    "resource_last_name": "<resource_first_name>"
},
"project_descriptor":
{
    "project_id": "<project_ID>",
    "project_name": "<project_name>",
    "project_manager": "<project_manager>",
    "project_status": "<project_status>",
    "project_program": "<project_program>",
    "activity_descriptor":
    {
        "activity_id": "<act_id>",
        "activity_desc": "<act_desc>",
        "role_descriptor":
        {
            "role_id": "<role_ID>",
            "role_desc": "<role_desc>"
        },
        "effort_descriptor":
        {
            "update_action_code": "<action_code>",
            "date": "<date>",
            "total_hours": "<total_hrs>",
            "overtime_hours": "<ot_hrs>",
            "notes": "<notes>"
        }
    }
}
```

```
    },
    "time_category_descriptor":
    {
        "time_category_desc": "<time_desc>",
        "effort_descriptor":
        {
            "update_action_code": "<action_code>",
            "date": "<date>",
            "total_hours": "<total_hrs>",
            "overtime_hours": "<ot_hrs>",
            "notes": "<notes>"
        }
    }
},
"time_category_descriptor":
{
    "time_category_desc": "<time_desc>",
    "effort_descriptor":
    {
        "update_action_code": "<action_code>",
        "date": "<date>",
        "total_hours": "<total_hrs>",
        "overtime_hours": "<ot_hrs>",
        "notes": "<notes>"
    }
},
"operation_type": "<op_type>",
"test_mode": "<test_mode>"
}
}
```

This is an example with values for the placeholders.

```
{
  "global_properties":
  {
    "char_set": "ISO-8859-1",
    "date_format": "yyyy/MM/dd",
    "language": "en"
    "api_version": "et-integration-api-1.0",
  },

  "application_data":
  {
    "source_application_descriptor":
    {
```

```
        "source_app": "hp quality center",
        "source_ref_unique_id": "WEWEWW1222",
        "source_ref_description": "this is related to new calls",
        "source_ref_type": "support call"
    },
    "security_descriptor":
    {
        "authorization_policy": "authorize_with_login_resource",
        "authorization_policy_given_resource_descriptor":
        {
            "resource_id": "",
            "resource_login_id": "",
            "resource_email": "",
            "resource_first_name": "don",
            "resource_last_name": "adams"
        }
    },
    "resource_descriptor":
    {
        "resource_id": "",
        "resource_login_id": "",
        "resource_email": "",
        "resource_first_name": "don",
        "resource_last_name": "adams"
    },
    "project_descriptor":
    {
        "project_id": "4",
        "project_name": "",
        "project_manager": "",
        "project_status": "",
        "project_program": "",
        "time_category_descriptor":
        {
            "time_category_desc": " ",
            "effort_descriptor":
            {
                "date": " ",
                "total_hours": " ",
                "overtime_hours": " ",
                "update_action_code": " ",
                "notes": " "
            }
        }
    },
    "activity_descriptor":
```

```
{
  "activity_id": "JXHQCCGSVHPC",
  "activity_desc": "new act",
  "role_descriptor": {
    "role_id": "",
    "role_desc": "Network Admin"
  },
  "effort_descriptor": {
    "update_action_code": "INCREMENT",
    "date": "2012/10/11",
    "total_hours": "10.5",
    "overtime_hours": "5",
    "notes": "some notes"
  },
  "operation_type": "EXTERNAL_ACTIVITY",
  "test_mode": "false"
}
```

Output Parameters

The results of the UpdateResourceEffort function are provided in JSON data format. The following table details the name/value pairs.

Name	Data Type	Description
global_properties	Object	This <i>object</i> lists the global settings for your EnterpriseTrack instance. See " global_properties Object (on page 14)" for details.
application_data	Object	This <i>object</i> provides the results. See "application_data" for details.
application_data		
et_transaction_id	String	This is the unique EnterpriseTrack transaction ID that is stored in the audit tables.
result_code	String	Provides the result code for the completion status of the function.
result_reason	String	If the function is successful, NULL is returned. Otherwise, the reason for the error is returned.

Name	Data Type	Description
project_descriptor	Object	This <i>object</i> contains the details of the project. See "project_descriptor" for details.
timesheet_descriptor	Object	This <i>object</i> contains the details of the timesheet. This is provided only if the effort is tracked using EnterpriseTrack timesheets. See "timesheet_descriptor" for details.
project_descriptor		
project_id	Integer	Provides the ID for the project.
project_name	String	Provides the name for the project.
project_manager	String	Provides the name of the manager of the project.
project_status	String	Provides the status of the project. Valid values match those configured for your EnterpriseTrack application and there is no default value. Some <i>examples</i> of the status for are project are: ▶ Active ▶ On Hold ▶ Cancelled ▶ Completed-Post Realization ▶ Closed-In Realization
project_program	String	Provides the name of the program associated with the project.
activity_descriptor	Object	This <i>object</i> contains the details of an activity. See "activity_descriptor" for details.
time_category_descriptor	Object	This <i>object</i> contains the details of the time category of an activity. See "time_category_descriptor" for details.
activity_descriptor		
activity_id	String	Provides the ID of the activity.
activity_desc	String	Provides the description of the activity.
activity_total_effort	Integer	Provides the total number of hours (to date) for the activity.
activity_name	String	Provides the name of the activity.

Name	Data Type	Description
time_category_descriptor		
time_category_desc	String	Provides the description of the time category.
effort_descriptor	Object	This <i>object</i> specifies the effort details. See "effort_descriptor" for details.
effort_descriptor		
update_action_code	String	Specifies how the values for total_hours and overtime_hours should be used. Valid values are: ▶ REPLACE Replace disregards the existing value and updates using the new value. ▶ INCREMENT Increment adds the new value to the existing value, then updates using the new sum.
date	Date	Specifies the date to be assigned to the effort. If: The effort is tracked using EnterpriseTrack timesheets, then the effort will be revised for the specified date. Else if: The effort is tracked as activities, then either: ▶ The effort will be revised for the week in which the date occurs. -or- ▶ The date will be ignored, and the effort will be revised for that activity.
total_hours	Integer	Specifies the number of non-overtime hours to include. See update_action_code for additional detail.
overtime_hours	Integer	Specifies the number of overtime hours to include. See update_action_code for additional detail.
notes	String	Specifies the remarks to be included with the effort. If: Activities are tracked using EnterpriseTrack timesheets, the note will be appended to the timesheet notes. Otherwise: The note will be appended to the activity comments.

Name	Data Type	Description
timesheet_descriptor		
timesheet_id	String	Provides the ID of the activity.
timesheet_start_date	Date	Provides the start date of the activity.
timesheet_end_date	Date	Provides the end date of the activity.
timesheet_total_hours	Integer	Provides the total number of hours (to date) for the activity.
timesheet_overtime_hours	Integer	Provides the total number of overtime hours (to date) for the activity
timesheet_approver	String	Provides the name of the timesheet approver.

Output Examples

The syntax for the JSON formatted parameters from a successful UpdateResourceEffort function is similar to the following.

```
{
  "global_properties":
  {
    "char_set": "<some_character_set>",
    "date_format": "<some_date_format>",
    "language": "<some_language>",
    "effort_unit": "<some_units_for_effort>"
    "api_version": "et-integration-api-1.0",
  },

  "application_data":
  {
    "et_transaction_id": "<some_unique_ID>",
    "result_code": "<result_code>",
    "result_reason": "<result_reason>",
    "project_descriptor":
    {
      "project_id": "<project_ID>",
      "project_name": "<project_name>",
      "project_manager": "<manager_name>",
```

```
    "project_status": "<project_status>",
    "project_program": "<list_of_program_names>",
    "activity_descriptor":
    {
        "activity_name": "<activity_name>",
        "activity_id": "<activity_ID>",
        "activity_total_effort": "<total_effort>"
    }
},
"timesheet_descriptor":
{
    "timesheet_id": "<timesheet_ID>",
    "timesheet_start_date": "<timesheet_start_date>",
    "timesheet_end_date": "<timesheet_end_date>",
    "timesheet_approver": "<timesheet_approver_name>",
    "timesheet_total_hours": "<total_hours>",
    "timesheet_overtime_hours": "<overtime_hours>"
}
}
```

UpdateActivity Function

The UpdateActivity function updates the activity data based on the details you specify in the input parameters.

In This Section

Invocation Parameters.....	55
Input Parameters.....	55
Output Parameters	65

Invocation Parameters

The parameters for the invocation of the UpdateActivity function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or Constant	Description
api_name	String	updateactivity	Specifies the name of the Integration function.
input_type	String	JSON	Specifies the data format for the input parameters.
output_type	String	JSON	Specifies the data format for the output parameters.
input_data	String	<input_params>	Specifies the location of the input parameters. This value is case sensitive.

Invocation Example

The syntax for the invocation of the UpdateActivity function is as follows:

```
<api_session>?api_name=updateactivity&input_type=JSON&output_type=JSON&input_data=<input_params>
```

Input Parameters

The input parameters described in the following table provide the search criteria (filter data) to identify the activity, as well as to specify the updated effort data you want to commit.

This information should be provided in the JSON formatted data specified by *<input_params>*. Unless otherwise specified, all values are not case sensitive.

Note: This function includes a "test" feature (see *test_mode*) that allows you to verify that the information you include in the input parameters can be successfully committed. Since there is no mechanism to "roll back" invalid data, you are encouraged to "test" the data before actually committing any updates.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	object	yes	Not applicable	This object specifies the global settings for your EnterpriseTrack instance. See "global_properties Object" for details.
application_data	Object	Yes	Not applicable	This object specifies the search criteria. See "application_data" for details.
application_data				
source_application_descriptor	Object	Yes	Not applicable	This <i>object</i> specifies the information you want stored in the audit table. See "source_application_descriptor" for details.
security_descriptor	Object	Yes	Not applicable	This <i>object</i> specifies the authentication information to be verified. See "security_descriptor" for details.
resource_descriptor	Object	Yes	Not applicable	This <i>object</i> specifies the resource. An error results in the event a matching resource cannot be found. See "resource_descriptor" for details.
project_descriptor	Object	Yes	Not applicable	This <i>object</i> specifies the project details. See "project_descriptor" for details.
operation_type	String	Yes	<i><op_type></i>	Specifies the type of operation. Valid values are: ▶ INTERNAL_ACTIVITY ▶ EXTERNAL_ACTIVITY

test_mode	Boolean	No	<test_mode>	Indicates whether or not this invocation of this function is merely a test. Valid values are: ▶ TRUE ▶ FALSE (default) If test_mode is FALSE, then the updates <i>will be committed</i> in the EnterpriseTrack database.
source_application_descriptor				
source_app	String	Yes	<source_App>	Specifies the name of the source application.
source_ref_unique_id	String	Yes	<source_ID>	Specifies the ID of the caller of the Integration function.
source_ref_description	String	Yes	<source_desc>	Specifies the description of the caller of the Integration function.
source_ref_type	String	Yes	<source_type>	Specifies the reference type of the caller of the Integration function.
security_descriptor				
authorization_policy	String	Yes	<auth_policy>	Specifies the authorization policy to be used. Valid values are: ▶ AUTHORIZE_WITH_LOGIN_RESOURCE - Execute using the permissions of the logged in Integration user. ▶ AUTHORIZE_WITH_RECORD_LOCATOR_RESOURCE - Execute using the permissions of the resource specified in resource_descriptor. ▶ AUTHORIZE_WITH_AUTHORIZATION_POLICY_GIVEN_RESOURCE - Execute using the permissions of the resource specified in authorization_policy_given_resource_descriptor.

authorization_policy_given_resource_descriptor	Object	Optionally required (see description)	Not applicable	Required only if <code>authorization_policy</code> has the <code>AUTHORIZE_WITH_AUTHORIZATION_POLICY_GIVEN_RESOURCE</code> value. This <i>object</i> specifies the resource whose permissions should be used to execute the function. See "<code>authorization_policy_given_resource_descriptor</code>" for details.
authorization_policy_given_resource_descriptor				
resource_id	String	No	<auth_resource_ID>	Specifies the resource ID of the authorized resource. If a <code>resource_id</code> value is specified, then all other parameters are ignored. Otherwise, the other <code>resource_descriptor</code> parameters will be used to help identify the resource.
resource_login_id	String	No	<auth_resource_login_ID>	Specifies the login ID of the authorized resource. If a <code>resource_id</code> value is <i>not</i> specified and if a <code>resource_login_id</code> value is specified then all other parameters are ignored. Otherwise, the other <code>resource_descriptor</code> parameters will be used to help identify the resource.
resource_email	String	No	<auth_resource_email >	Specifies the e-mail address of the authorized resource. If a <code>resource_id</code> and <code>resource_login_id</code> values are <i>not</i> specified and a <code>resource_email</code> value is specified, then all other parameters are ignored <i>unless</i> multiple resources use the same e-mail address. Otherwise, the other <code>resource_descriptor</code> parameters will be used to help identify the resource.

resource_last_name	String	No	<auth_resource_last_name>	Specifies the last name of the authorized resource. If a resource_id and resource_login_id values are <i>not</i> specified, and a resource_email value <i>is not</i> specified, or multiple resources have the same e-mail address, then the combination of the resource_last_name and resource_first_name values are used to identify the resource. Otherwise, the resource cannot be found and an error results.
resource_first_name	String	No	<auth_resource_first_name>	Specifies the first name of the authorized resource.
resource_descriptor:				
A value for at least one of the parameters must be provided.				
resource_id	String	No	<resource_ID>	Specifies the resource ID of the resource. If a resource_id value <i>is</i> specified then all other parameters are ignored. Otherwise, the other resource_descriptor parameters will be used to help identify the resource.
resource_login_id	String	No	<resource_login_ID>	Specifies the login ID of the resource. If a resource_id value <i>is not</i> specified and a resource_login_id value <i>is</i> specified, then all other parameters are ignored. Otherwise, the other resource_descriptor parameters will be used to help identify the resource.

resource_email	String	No	<resource_email>	Specifies the e-mail address of the resource. If resource_id and resource_login_id values are <i>not</i> specified, and a resource_email value <i>is</i> specified, then all other parameters are ignored <i>unless</i> multiple resources use the same e-mail address. Otherwise, the other resource_descriptor parameters will be used to help identify the resource.
resource_last_name	String	No	<resource_last_name>	Specifies the last name. If a resource_id value, and a resource_login_id value <i>are not</i> specified, and if a resource_email value <i>is not</i> specified, or multiple resources have the same e-mail address, then a combination of the resource_last_name and resource_first_name values are used to identify the resource. Otherwise, the resource cannot be found and an error results.
resource_first_name	String	No	<resource_first_name>	Specifies the first name.
project_descriptor				
All of the values can be NULL if you do not want to filter on the project. If you want to filter on a project, either the project_id and the project_name should be specified. If the project_id and the project_name are both NULL, the project will default to "Operations Project." An error results if there is no project with name Operations Project.				
project_id	String	No	<project_ID>	Specifies the ID for the project. If specified and there are no matches, an error results.

project_name	String	No	<project_name>	Specifies the name for the project. If a project_id value <i>is not</i> specified and a project_name value <i>is</i> specified, then this data used to help identify the project. An error results if a match is not found.
project_manager	String	No	<project_manager>	Specifies the name of the manager of the project.
project_status	String	No	<project_status>	Specifies the status of the project. Valid values match those configured for your EnterpriseTrack application and there is no default value. Some <i>examples</i> of the status for are project are: ▶ Active ▶ On Hold ▶ Cancelled ▶ Completed-Post Realization ▶ Closed-In Realization
project_program	String	No	<project_program>	Specifies the name of the program associated with the project.
activity_descriptor	Object	Yes	Not applicable	This <i>object</i> specifies the details of the activity. At least one value must be specified. See "activity_descriptor" for details.
activity_descriptor				
activity_id	String	Yes	<act_ID>	Specifies the activity ID to match. The value is <i>not</i> case sensitive. For internal activities, this corresponds to the EnterpriseTrack activity ID. For external activities, this corresponds to the unique ID assigned for the activities tracked outside of the EnterpriseTrack. For miscellaneous activities, this corresponds to the Enterprise category name. An error results if no matching activity ID for the specified resource is found.

activity_percent_completion	Number	No	<act_percent>	Specifies the percentage completion of the activity.
status_descriptor	Object	No	Not applicable	This <i>object</i> specifies the status of the activity. See "status_descriptor" for details.
status_descriptor				
status_id	String	No	<act_ID>	Provides the ID of the status.
status_desc	String	No	<act_desc>	Provides the description of the status.

Input Examples

The syntax for the UpdateActivity data input parameters is as follows:

```
{
  "global_properties":
  {
    "char_set": "<char_set>",
    "date_format": "<date_format>",
    "language": "<lang>"
    "api_version": "et-integration-api-1.0",
  },
  "application_data":
  {
    "source_application_descriptor":
    {
      "source_app": "<source_App>",
      "source_ref_unique_id": "<source_ID>",
      "source_ref_description": "<source_desc>",
      "source_ref_type": "<source_type>"
    },
    "security_descriptor":
    {
      "authorization_policy": "<auth_policy>",
      "authorization_policy_given_resource_descriptor":
      {
        "resource_id": "<auth_resource_ID>",
        "resource_login_id": "<auth_resource_login_ID>",
        "resource_email": "<auth_resource_email>",
        "resource_last_name": "<auth_resource_last_name>",
        "resource_first_name": "<auth_resource_first_name>"
      }
    }
  }
}
```

```
        }
    },
    "resource_descriptor":
    {
        "resource_id": "<resource_ID>",
        "resource_login_id": "<resource_login_ID>",
        "resource_email": "<resource_email>",
        "resource_last_name": "<resource_last_name>",
        "resource_first_name": "<resource_first_name>"
    },
    "project_descriptor":
    {
        "project_id": "<project_ID>",
        "project_name": "<project_name>",
        "project_manager": "<project_manager>",
        "project_status": "<project_status>",
        "project_program": "<project_program>",
        "activity_descriptor":
        {
            "activity_id": "<act_ID>",
            "activity_percent_completion": "<act_percent>",
            "status_descriptor":
            {
                "status_id": "<act_ID>",
                "status_desc": "<act_desc>"
            }
        }
    },
    "operation_type": "<op_type>",
    "test_mode": "<test_mode>"
}
}
```

This is an example with values for the placeholders.

```
{
  "global_properties":
  {
    "char_set": "ISO-8859-1",
    "date_format": "",
    "language": "en",
    "api_version": "et-integration-api-1.0",
  },
  "application_data":
  {
    "source_application_descriptor":
    {
      "source_app": "hp quality center",
      "source_ref_unique_id": "WEWEWW1222",
      "source_ref_description": "this is related to calls",
      "source_ref_type": "support call"
    },
    "security_descriptor":
    {

  "authorization_policy": "authorize_with_login_resource",
    "authorization_policy_given_resource_descriptor":
    {
      "resource_id": "JBCDQVW5QMV9F",
      "resource_login_id": "",
      "resource_email": "",
      "resource_first_name": "John",
      "resource_last_name": "Smith"
    }
    },
    "resource_descriptor":
    {
      "resource_id": "JBCDQVW5QMV9F",
      "resource_login_id": "",
      "resource_email": "",
      "resource_first_name": "",
      "resource_last_name": ""
    },
    "project_descriptor":
    {
      "project_id": "1",
      "project_name": "ExampleA",
      "activity_descriptor":
      {
        "activity_id": "JABC5V9JSF4SP",
        "activity_percent_completion": "38",
        "status_descriptor":
        {
```

```

        "status_id": "Closed",
        "status_desc": ""
    }
},
"operation_type": "INTERNAL_ACTIVITY",
"test_mode": "FALSE"
}
}

```

Output Parameters

The results of the UpdateActivity function are provided in JSON data format. The following table details the name/value pairs.

Name	Data Type	Description
global_properties	Object	This <i>object</i> lists the global settings for your EnterpriseTrack instance. See <i>global_properties Object</i> (on page 14) for more details.
application_data	Object	This <i>object</i> provides the results. See "application_data" for more details.
application_data		
et_transaction_id	String	Provides the unique EnterpriseTrack transaction ID that is stored in the audit tables.
result_code	String	Provides the result code for the completion status of the function.
result_reason	String	If the function is successful, NULL is returned. Otherwise, the reason for the error is returned.
project_descriptor	Object	This <i>object</i> provides the details of the project. See "project_descriptor" for details.
project_descriptor		
project_id	Integer	Provides the ID for the project.
project_name	String	Provides the name for the project.

Name	Data Type	Description
project_manager	String	Provides the name of the manager of the project.
project_status	String	Provides the status of the project.
project_program	String	Provides the names of the programs associated with the project.
activity_descriptor	Object	This <i>object</i> contains the details of an activity. See "activity_descriptor" for details.
activity_descriptor		
activity_id	String	Provides the ID for the activity.
activity_name	String	Provides the name of the activity.
activity_status	String	Provides the status of the activity.
activity_percent_completion	Number	Provides the percentage completion of the activity.
activity_actual_start_date	Date	Provides the actual start date of the activity.
activity_actual_end_date	Date	Provides the actual end date of the activity.

Output Example

This is an example of the JSON formatted parameters from a successful UpdateActivity function.

```
{
  "global_properties":
  {
    "char_set": "ISO-8859-1",
    "date_format": "MMM/dd/yyyy",
    "language": "en",
    "effort_unit": "hours"
    "api_version": "et-integration-api-1.0",
```

```
},  
  
"application_data":  
{  
  "et_transaction_id": "JCDEJ58N2QMKW",  
  "result_code": "SUCCESS",  
  "result_reason": "",  
  "project_descriptor":  
  {  
    "project_id": "1",  
    "project_name": "it_test",  
    "project_manager": "john, smith",  
    "project_status": "Active",  
    "project_program": "",  
    "activity_descriptor":  
    {  
      "activity_id": "JEFGRC SKL3DTH",  
      "activity_name": "Rollout Project Preparation",  
      "activity_status": "Open",  
      "activity_percent_completion": "63",  
      "activity_actual_start_date": "",  
      "activity_actual_end_date": ""  
    }  
  }  
}  
}
```


GetFinanceData Function

The GetFinanceData function fetches the data that is equivalent to the "Project Finances Element Monthly Detail Report" and corresponds to the search criteria (filter data) you specify in the input parameters.

In This Section

Invocation Parameters.....	69
Input Parameters.....	69
Output Parameters	78

Invocation Parameters

The parameters for the invocation of the GetFinanceData function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or Constant	Description
api_name	String	getfinancedata	Specifies the name of the Integration function.
output_type	String	<output_type>	CSV XLS
input_data	String	<input_params>	Specifies the location of the input parameters. This value is case sensitive.

Invocation Example

The syntax for the invocation of the GetFinanceData function is as follows:

```
<api_session>?api_name=getfinancedata&output_type=<output_type>
&input_data=<input_params>
```

Input Parameters

The input parameters described in the following table provide the search criteria (filter data) needed to identify the data you want. This information should be provided in the JSON formatted data specified by <input_params>. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> lists the global settings for your EnterpriseTrack instance. See "global_properties Object" for details.
application_data	Object	Yes	Not applicable	This <i>object</i> lists the search criteria and provides the results. See "application_data" for details.
application_data				
pcs	String	No	<pcs>	Specifies the initiative attribute for the project.
project_id	Integer	No	<project_ID>	Specifies the project ID.
project_name	String	No	<project_name>	Specifies the project name.
project_keyword	String	No	<project_keyword>	Specifies a keyword associated for the project.
project_status	String	No	<project_status>	Specifies one (or more) status values for the project. Multiple values should be separated by commas.
project_on_time_status	String	No	<project_on_time_status>	Specifies one (or more) status values for the project. Multiple values should be separated by commas.
project_org_descriptor	Object	No	Not applicable	This <i>object</i> specifies the organization information. See "project_org_descriptor" for details.

Name	Data Type	Value Required?	Placeholder or Constant	Description
project_start_date_from	Date	No	<start_from>	Specifies the beginning date for the range of start dates. This filters on actual (if present) or planned activity date.
project_start_date_to	Date	No	<start_to>	Specifies the beginning date for the range of start dates. This filters on actual (if present) or planned activity dates.
planned_realization_date_from	Date	No	<end_from>	Specifies the beginning date for the range of end dates. This filters on actual (if present) or planned activity dates.
planned_realization_date_to	Date	No	<end_to>	Specifies the ending date for the range of end dates. This filters on actual (if present) or planned activity dates.
project_classification_descriptor	Object	No	Not applicable	This <i>object</i> specifies the project classification. See "project_classification_descriptor" for details.
project_methodology_descriptor	Object	No	Not applicable	This <i>object</i> specifies the project methodology. See "project_methodology_descriptor" for details.
program	String	No	<program>	Restricts the search to include only those projects in this program.

Name	Data Type	Value Required?	Placeholder or Constant	Description
finance_detail_level	String	No	<detail_level>	Specifies the level of finance elements to report. Valid values are: ▶ Total (default) ▶ Group ▶ Category ▶ Element
show_upper_levels	Boolean	No	<show_levels>	If <code>finance_detail_level</code> has a value of <code>Category</code> , this indicates whether or not to include the group in the report. Value values are: ▶ TRUE (default) ▶ FALSE
rpt_currency	String	No	<currency>	Specifies the type of currency to use. The default is USD.
fin_templates	String	No	<template>	Specifies one (or more) finance templates to use. Multiple values should be separated by commas.
finance_date_range_from	Date	No	<range_from>	Specifies the beginning date for the finance data that is to be reported.
finance_date_range_to	Date	No	<range_to>	Specifies the ending date for the finance data that is to be reported.
finance_dataset	String	No	<dataset>	Specifies which data stream should be considered. Valid values are: ▶ CURRENT (default) ▶ PLAN

Name	Data Type	Value Required?	Placeholder or Constant	Description
finance_snapshot_name	String	No	<snapshot>	If finance_dataset has a value of PLAN, this specifies the name of the finance snapshot that should be used for the report.
starting_month	Date	No	<start_mo>	Specifies the beginning month to be shown in the month-by-month breakdown. The default is the beginning of the <i>previous</i> fiscal year.
no_of_months	Integer	No	<num_mo>	Specifies the number of months to be included in the month-by-month breakdown. The default is 36.
project_org_descriptor				
division	String	No	<division>	Specifies one (or more) level 1 fields configured for the project hierarchy. Multiple values should be separated by commas.
business_unit	String	No	<bus_unit>	Specifies one (or more) level 2 fields configured for the project hierarchy. Multiple values should be separated by commas.
sub_business_unit	String	No	<sub_unit>	Specifies one (or more) level 3 fields configured for the project hierarchy. Multiple values should be separated by commas.
location	String	No	<location>	Specifies one (or more) level 4 fields configured for the project hierarchy. Multiple values should be separated by commas.

Name	Data Type	Value Required?	Placeholder or Constant	Description
region	String	No	<region>	Specifies one (or more) level 5 fields configured for the project hierarchy. Multiple values should be separated by commas.
project_classification_descriptor				
project_source	String	No	<proj_source>	Specifies one or more project sources for the the associated <i>initiative</i> . Multiple values should be separated by commas.
functional_area	String	No	<proj_area>	Specifies one or more functional areas for the associated <i>initiative</i> . Multiple values should be separated by commas.
products	String	No	<products>	Specifies one or more products for the the associated <i>initiative</i> . Multiple values should be separated by commas..
process	String	No	<process>	Specifies one or more processes for the the associated <i>initiative</i> . Multiple values should be separated by commas.
project_methodology_descriptor				
phase_type	String	No	<phase_type>	Specifies one (or more) top level activities configured for the associated <i>initiative</i> . This field is dependent on the initiative and will be ignored is the initiative is NULL. Multiple values should be separated by commas.

Name	Data Type	Value Required?	Placeholder or Constant	Description
project_type	String	No	<proj_type>	Specifies one (or more) project types configured for the associated <i>initiative</i> . This field is dependent on the initiative and will be ignored if the initiative is NULL. Multiple values should be separated by commas.
roadmap	String	No	<roadmap>	Specifies one (or more) roadmaps configured for the associated <i>initiative</i> . This field is dependent on the initiative and will be ignored if the initiative is NULL. Multiple values should be separated by commas.

Input Examples

The syntax for the GetFinanceData data input parameters is as follows:

```
{
  "global_properties":
    {
      "char_set": "<char_set>",
      "date_format": "<date_format>",
      "language": "<lang>",
      "api_version": "et-integration-api-1.0",
    },
  "application_data":
    {
      "pcs": "<pcs>",
      "project_id": "<project_ID>",
      "project_name": "<project_name>",
      "project_keyword": "<project_keyword>",
      "project_status": "<project_status>",
      "project_on_time_status": "<project_one_time_status>",
    }
}
```

```
"project_org_descriptor":
{
    "division": "<division>",
    "business_unit": "<bus_unit>",
    "sub_business_unit": "<sub_unit>",
    "location": "<location>",
    "region": "<region>"
},
"project_start_date_from": "<start_from>",
"project_start_date_to": "<start_to>",
"planned_realization_date_from": "<end_from>",
"planned_realization_date_to": "<end_to>",
"project_classification_descriptor":
{
    "project_source": "<proj_source>",
    "functional_area": "<proj_area>",
    "products": "<products>",
    "process": "<process>"
},
"project_methodology_descriptor":
{
    "phase_type": "<phase_type>",
    "project_type": "<proj_type>",
    "roadmap": "<roadmap>"
},
"program": "<program>",
"finance_detail_level": "<detail_level>",
"show_upper_levels": "<show_levels>",
"rpt_currency": "<currency>",
"fin_templates": "<template>",
"finance_date_range_from": "<range_from>",
"finance_date_range_to": "<range_to>",
"finance_dataset": "<dataset>",
"finance_snapshot_name": "<snapshot>",
"starting_month": "<start_mo>",
"no_of_months": "<num_mo>"
}
}
```

This is an example with values for the placeholders.

```
{
  "global_properties":
  {
    "char_set": "utf-8",
```

```
        "date_format": "yyyy/MM/dd",
        "language": "en"
        "api_version": "et-integration-api-1.0",
    },

    "application_data":
    {
        "pcs": "it",
        "project_id": "1",
        "project_name": "",
        "project_keyword": "",
        "project_status": "",
        "project_on_time_status": "",
        "project_org_descriptor":
        {
            "division": "",
            "business_unit": "",
            "sub_business_unit": "",
            "location": "",
            "region": ""
        },
        "project_start_date_from": "",
        "project_start_date_to": "",
        "planned_realization_date_from": "",
        "planned_realization_date_to": "",
        "project_classification_descriptor":
        {
            "project_source": "",
            "functional_area": "",
            "products": "",
            "process": ""
        },
        "project_methodology_descriptor":
        {
            "phase_type": "",
            "project_type": "",
            "roadmap": ""
        },
        "program": "",
        "finance_detail_level": "TOTAL",
        "show_upper_levels": "TRUE",
        "rpt_currency": "",
        "fin_templates": "",
        "finance_date_range_from": "",
        "finance_date_range_to": "",
    }
}
```

```
        "finance_dataset": "CURRENT",
        "finance_snapshot_name": "PLAN",
        "starting_month": "",
        "no_of_months": "12"
    }
}
```

Output Parameters

The output of the GetFinanceData function is provided in a file that uses either CSV or XLS data format.

Output Example

The CSV and XLS files from a successful GetFinanceData function provide the data as two rows of data. The first row provides the names of the fields in the report, and the second row provides the values for the corresponding fields.

An exceptionally simplified excerpt from a CSV file is as follows:

```
Project Id,Project Name,Initiative,Project Status,...,Mar/2013,Apr/2013
4,COST_Basic_External,IT,Active,... 0.00,0.00
```

Automated Data Upload

Automated data upload enables you to set up programs to automatically upload data files and receive the response in a standard format. This data can be used to parse or interpret data with other third-party applications.

The following functions are used to perform automate data uploads:

- ▶ receivedata
- ▶ getStatus

In This Section

receivedata Function	79
getStatus Function	85

receivedata Function

Invoke the receivedata function to begin the automated data upload process by specifying the data upload files and generating a unique ID for the data upload process.

In This Section

Invocation Syntax	79
Invocation Example	80
Invocation Parameters.....	80
Output	84
Output Examples.....	84

Invocation Syntax

The syntax for the invocation of automated data upload is:

```
<form method=POST ENCTYPE="multipart/form-data"
action="http://<server>/SiteWand/Submission/<account_name>/dataupload/a
utomatedupload/receivedata">User Login <input type=text
name='user_login_id' value='' />Password <input type=password
name='password' value='' /> Delimiter <input type=text name='delimiter'
value=', ' /> Encoding <input name = "encoding_type" value="UTF-8">
Entity_Name1 <input type=text name='entity_name1' value='user' />
File_Name1 <input type=file name='file_name1' />Entity_Name2 <input
type=text name='entity_name2' value='user' /> File_Name2 <input type=file
name='file_name2' />
....
Entity_Name15 <input type=text name='entity_name15' value='user' />
File_Name15 <input type=file name='file_name15' /> <input type = 'submit'
value='Submit' /></form>
```

For detailed descriptions, see the invocation parameters.

Invocation Example

<https://abc123.com/SiteWand/Submission/jdoe/dataupload/automatedupload/receivedata?>

```
<form method=POST ENCTYPE="multipart/form-data"
action="http://abc123.com/SiteWand/Submission/jdoe/dataupload/automated
upload/receivedata">User Login <input type=text name='user_login_id'
value=jdoe/>Password<input type=password name='password' value=</>/>
Delimiter <input type=text name='delimiter' value=', ' /> Encoding <input
name = "encoding_type" value="UTF-8">Entity_Name1 <input type=text
name='entity_name1' value='project' />File_Name1 <input type=file
name='file_name1.zip' />Entity_Name2 <input type=text name='entity_name2'
value='user' />File_Name2 <input type=file name='file_name2.csv' /><input
type = 'submit' value='Submit' /></form>
```

Invocation Parameters

The following invocation parameters can be specified for receivedata:

Name	Description
<i>server</i>	Specifies the IP address or hostname of the server hosting your EnterpriseTrack instance.
<i>account_name</i>	Specifies the account name (or company name) of your Specifies your EnterpriseTrack login ID. The case sensitivity for this value conforms to that used by your EnterpriseTrack system.

Name	Description
<i>user_login_id</i>	Specifies your EnterpriseTrack login ID. The case sensitivity for this value conforms to that used by your EnterpriseTrack system.
<i>password</i>	Specifies the password corresponding to your EnterpriseTrack login ID. The case sensitivity for this value conforms to that used by your EnterpriseTrack system.
<i>encoding_type</i>	Specifies the character encoding type that is specific to your account. Possible values: UTF-8 , UTF-16, or ISO-8859-1.
<i>delimiter</i>	Specifies the csv delimiter. The possible values are: "," and ".".
<i>decimal_symbol</i>	Specifies the decimal symbol. The possible values are: "," and ".".
<i>trim_trailing_spaces</i>	Choose if you want to trim trailing spaces. You can select true or false.
<i>trim_leading_spaces</i>	Choose if you want to trim leading spaces. You can select true or false.
<i>entity_name <1> to entity_name <15></i>	The name of the entity being submitted for an upload. A maximum of 15 entities can be uploaded in a single instance. Each entity name must have a file_name associated with it. Refer to the table below for a list of entities that you can upload.
<i>file_name<1> to file_name <15></i>	The name of the file being uploaded. Data upload files must be submitted as .csv or .zip files. A maximum of 15 data files can be uploaded in a single instance.
<i>is_update_allowed</i>	Allows updates to data or only adding new projects/users to the system. Valid values are: ▶ True = (default) updates an existing record with new values from import data. Otherwise, adds a new record. ▶ False = Fails import for existing records. Otherwise adds new records.

Name	Description
Id	Unique id (Transaction id). This is required, when user wants to track transaction which was initiated earlier.
do_upload_on_error_records	Allows data upload on error records also. Valid values are: ▶ True = (default) The data will import only the error-free records. ▶ False = The data upload process will abort if error records are found.

Entity Name (entity_name <n>)	Possible Values
Ideas	Idea.
Charters	Charter
Charter Team	charter_team.
Charter Documents	charter_documents.
Projects	project
Project Team	project_team
Team Allocation	project_team_allocation
Project Dates	phase_date

Entity Name (entity_name <n>)	Possible Values
Aggregate/Yearly Finance	project_annualized_finance
Monthly Finance	project_finance
Aggregate/Yearly Finance Snapshot	project_annualized_finance_snapshot
Monthly Finance Snapshot	project_monthly_finance_snapshot
Documents	project_doc
Notes	project_note
Multiple Org Hierarchy	project_multiorg
Incremental Documents	project_incremental_docs
Incremental Monthly Finance	project_incremental_monthly_finance
Incremental Aggregate/Yearly Finance	project_incremental_annual_finance
Incremental Monthly Finance Snapshot	project_incremental_finance_snapshot
Incremental Aggregate/Yearly Finance Snapshot	project_annual_incremental_finance_snapshot
Incremental Notes	project_incremental_notes
Resources	User
Roles	user_role
Certifications	user_certification
Resource Update	UpdatedUsers
Role Update	UpdatedUserRoles

Entity Name (entity_name <n>)	Possible Values
Resource Certification Update	updated_user_certifications
Incremental Resource Certifications	user_incremental_certifications
Alignment 1	strategy_1 Add for all alignments configured in the account.
Measure	Measure
Measure Incremental Data	measure_data
Incremental Alignment	strategy_alignment

Note: The possible values for entity names (ex: entity_name 1/entity_name2 attributes) "entities_alignment_tree" value is always "" for all entities except for "alignment" entities.

Output

On successful login the receivedata function returns a unique ID value which can be used to check the status of the data upload.

Output Examples

If the data upload is received successfully, a response is received in the following format:

```
<response>
  <message>Received data successfully</message>
  <uniqueid>ZHR98374GT</uniqueid>
</response>
```

If authentication or data upload is not received successfully, a response is received in the following format:

```
<response>
  <error>invalid login ID or password.</error>
</response>
```

getstatus Function

The getstatus function displays the current status of the data upload process. The unique ID generated by the receivedata function is required to determine the status of the data upload.

In This Section

Invocation Syntax	85
Invocation Example	85
Output	85
Output Examples	85

Invocation Syntax

The syntax for the invocation of the status of the automated data upload is:

Note: Use the unique ID that was returned as part of the receivedata function as a parameter to get status.

`https://<server>/SiteWand/Submission/<account_name>/dataupload/automatedupload/getstatus?id=<receivedata_generated_unique id>`

Invocation Example

Using the unique ID generated from the previous example for receivedata function, a successful invocation of getstatus function displays as follows:

`https://abc123.com/SiteWand/Submission/jdoe/dataupload/automatedupload/getstatus?id= ZHR98374GT`

Output

If the data upload is successful, the unique ID and a successful message is displayed in XML format. If there are authentication errors or the data upload is not successful, and an error message is displayed in XML format.

Output Examples

On completing a data upload successfully, the following response displays:

```
<response>
  <status>Completed</status>
</response>
```

If the data upload process is ongoing, the following response displays for the unique ID:

```
<response>
  <status>In process</status>
</response>
```

The result from a successful project data upload in XML format is similar to the following.

```
<response>
  <status>Completed</status>
  <projects>
    <uploadstats>
      <errorrecords>0</errorrecords>
    </uploadstats>
  </projects>
</response>
```

For a file upload error, the output response in XML format displays as shown below:

```
<response>
  <status>Completed</status>
  <error type='upload'>
    <message>Error message</message>
  </error>
</response>
```

Project CRUD APIs

In This Section

Create Function.....	87
Create_Template Function	99
Update Function	110
Update_template Function	122
Delete Function	130
Delete_template Function.....	135
Search Function	140
Search_template Function.....	159

Create Function

The Create function allows you to create a project in EnterpriseTrack.

In This Section

Invocation Syntax	87
Invocation Parameters.....	88
Input Parameters.....	88
Input Examples	89
Output Examples.....	98

Invocation Syntax

The syntax for the invocation of the create function is as follows:

```
<api_session>?&request_data=<input_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in project15_create.xml and project15_create.json. Then the syntax for the create function is as follows:

```
<api_session>?&request_data=<tags specified in
project15_create.xml>&request_format=xml
```

```
<api_session>?&request_data=<tags specified in
project15_create.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the create function are described in the following table. Unless otherwise specified, all values are not case-sensitive.

Name	Data Type	Placeholder or constant	Description
<i>Request_data</i>	String	<i><input_data></i>	Specifies the input data for creating a project. For more details, See the Input Parameters.
<i>Request_format</i>	String	<i><request_format></i>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case-sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> lists the global settings for your EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See <i>Request_Data Table</i> below for more details.

Name	Data Type	Value Required?	Placeholder or Constant	Description
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the create template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	create	The name of the function.
Entity_type	String	Yes	project	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

Input examples in XML and JSON formats are provided below.

Note: You can retrieve the Create template from the Administration console, **Data Import Export** tab. Click on **Download Data Integration Templates**, select object parameters and click **Download** for the correct combination of data format and CRUD operation.

Input Example in XML Format

The following is an example of the input data for creating a project with a custom field and runtime fields:

```

<root>
  <global_properties>
    <char_set>ISO-8859-1</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <request_data>
    <request_type>create</request_type>
    <entity_type>project</entity_type>
    <output_format>xml</output_format>
    <value_delimiter>|</value_delimiter>
  </request_data>
  <app_data>
    <project>
      <project_number>
        <display_name>Project ID</display_name>
        <value>80001</value>
      </project_number>
      <pcs>
        <display_name>Initiative</display_name>
        <value>IT</value>
      </pcs>
      <project_name>
        <display_name>Project Name</display_name>
        <value>Integration Project - 1</value>
      </project_name>
      <calendar_id>
        <display_name>Calendar</display_name>
        <value>Standard US Calendar</value>
      </calendar_id>
      <status_descriptor/>
      <dates_descriptor>
        <start_date>
          <display_name>Actual Start Date</display_name>
          <value>2013/12/12</value>
        </start_date>
        <planned_realization_date>
          <display_name>Planned Project Realization
Date</display_name>
          <value>2014/12/12</value>
        </planned_realization_date>
        <planned_completion_date>
          <display_name>Planned Project Completion
Date</display_name>
          <value>2014/12/12</value>
        </planned_completion_date>
      </dates_descriptor>
      <org_descriptor>

```

```
<division>
  <display_name>Division</display_name>
  <value>Business Development</value>
</division>
<business_unit>
  <display_name>Business Unit</display_name>
  <value>Channels</value>
</business_unit>
<location>
  <display_name>Location</display_name>
  <value>Fairfield, CT</value>
</location>
<region>
  <display_name>Region</display_name>
  <value>North America</value>
</region>
</org_descriptor>
<classification_descriptor>
  <functional_area>
    <display_name>Functional Area</display_name>
    <value>Accounts Payable</value>
  </functional_area>
  <priority>
    <display_name>Risk</display_name>
    <value/>
  </priority>
  <process>
    <display_name>Process Area</display_name>
    <value/>
  </process>
  <project_source>
    <display_name>Project Source</display_name>
    <value/>
  </project_source>
</classification_descriptor>
<methodology_descriptor>
  <project_type>
    <display_name>Project Type</display_name>
    <value>IT</value>
  </project_type>
  <roadmap>
    <display_name>Roadmap</display_name>
    <value>AET Timesheet Test</value>
  </roadmap>
</methodology_descriptor>
<finance_descriptor>
  <currency_code>
    <display_name>Currency</display_name>
    <value>Euro</value>
```

```

    </currency_code>
    <fin_approval_template_id>
      <display_name>Finance Approval Template</display_name>
      <value/>
    </fin_approval_template_id>
    <fintemplateid>
      <display_name>Finance Template</display_name>
      <value>Default Global Finance Template</value>
    </fintemplateid>
  </finanace_descriptor>
</settings_descriptor/>
<team_member_descriptors>
<team_member_descriptor>
  <teammember_id>1</teammember_id>
  <role>
    <display_name>Project Manager</display_name>
    <value>pm_globalrole</value>
  </role>
  <resource_descriptor>
    <userid/>
    <login_id>jdoe</login_id>
    <email/>
    <first_name>John</first_name>
    <last_name>Doe</last_name>
  </resource_descriptor>
</team_member_descriptor>
</team_member_descriptors>
<custom_fields>
  <predefined_fields>
    <basic_d_field1>
      <display_name>Basic Date Label7</display_name>
      <value>2014/01/02</value>
    </basic_d_field1>
    <orgz_t_field2>
      <display_name>Project Tracking Details</display_name>
      <value>Late by 10 days</value>
    </orgz_t_field2>
    <classf_d_field1>
      <display_name>Project Validate Date</display_name>
      <value>2014/02/02</value>
    </classf_d_field1>
  </predefined_fields>
  <runtime_fields>
    <Project_custom_field_1>
      <display_name>Runtime custom Boolean field
1</display_name>
      <value/>
    </Project_custom_field_1>
  </runtime_fields>

```

```
        </custom_fields>
    </project>
</app_data>
</root>
```

Input Example in JSON Format

The following is an example of the input data for creating a project with a custom field and runtime fields:

```
{
  "char_set": "ISO-8859-1",
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "create",
    "entity_type": "project",
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project": [
      {
        "project_number": {
          "display_name": "Project ID",
          "value": "90001"
        },
        "pcs": {
          "display_name": "Initiative",
          "value": "IT"
        },
        "project_name": {
          "display_name": "Project Name",
          "value": "Integration Project 90001"
        },
        "calendar_id": {
          "display_name": "Calendar",
          "value": "Standard US Calendar"
        },
        "status_descriptor": {

```

```
"dates_descriptor": {
  "start_date": {
    "display_name": "Actual Start Date",
    "value": "2013/12/12"
  },
  "planned_realization_date": {
    "display_name": "Planned Project Realization Date",
    "value": "2014/12/12"
  },
  "planned_completion_date": {
    "display_name": "Planned Project Completion Date",
    "value": "2014/12/12"
  }
},
"org_descriptor": {
  "division": {
    "display_name": "Division",
    "value": "Business Development"
  },
  "business_unit": {
    "display_name": "Business Unit",
    "value": "Channels"
  },
  "location": {
    "display_name": "Location",
    "value": "Fairfield, CT"
  },
  "region": {
    "display_name": "Region",
    "value": "North America"
  }
},
"classification_descriptor": {
  "functional_area": {
    "display_name": "Functional Area",
    "value": "Accounts Payable"
  },
  "priority": {
    "display_name": "Risk",
    "value": ""
  },
  "process": {
    "display_name": "Process Area",
```

```
        "value": ""
    },
    "project_source": {
        "display_name": "Project Source",
        "value": ""
    }
},
"methodology_descriptor": {
    "project_type": {
        "display_name": "Project Type",
        "value": "IT"
    },
    "roadmap": {
        "display_name": "Roadmap",
        "value": "AET Timesheet Test"
    }
},
"finanace_descriptor": {
    "currency_code": {
        "display_name": "Currency",
        "value": "US Dollar"
    },
    "fin_approval_template_id": {
        "display_name": "Finance Approval Template",
        "value": ""
    },
    "fintemplateid": {
        "display_name": "Finance Template",
        "value": "Default Global Finance Template"
    }
},
"settings_descriptor": {

```

```
"team_member_descriptors": [  
  {  
    "teammember_id": "1",  
    "role": {  
      "display_name": "Project Manager",  
      "value": "pm_globalrole"  
    },  
    "resource_descriptor": {  
      "userid": "",  
      "login_id": "jdoe",  
      "email": "",  
      "first_name": "John",  
      "last_name": "Doe"  
    }  
  },  
],  
"custom_fields": {  
  "predefined_fields": {  
    "orgz_t_field2": {  
      "display_name": "Project Tracking Details",  
      "value": "Late by 10 days"  
    },  
  },  
  "runtime_fields": {  
    "Project_custom_field_1": {  
      "display_name": "Runtime custom Boolean field 1",  
      "value": ""  
    },  
  },  
}  
}
```

Output Examples

The following section provides output examples of the Create function in XML and JSON formats.

Output Example in XML Format

The following is an example of the response from the Create function in XML format.

```
<root>
  <global_properties>
    <char_set>ISO-8859-1</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <response_data>
    <request_type>create</request_type>
    <entity_type>project</entity_type>
    <response_code>99999</response_code>
    <response_desc>Project ID already exists</response_desc>
  </response_data>
  <app_data> </app_data>
</root>
```

Output Example in JSON format

The following is an example of the response from the Create function in JSON format:

```
{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0",
    "char_set": "ISO-8859-1"
  },
  "response_data": {
    "response_desc": "Project ID already exists",
    "request_type": "create",
    "response_code": "99999",
    "entity_type": "project"
  },
  "app_data": {"": []}
}
```

Create_Template Function

The create_template function allows you to retrieve a template for project creation. This can be used to define data for creating a project in EnterpriseTrack.

Alternatively, you can also download the template from the EnterpriseTrack Administration module. For more details, see **Downloading CRUD Templates** (on page 262).

In This Section

Invocation Syntax.....	99
Invocation Parameters.....	99
Input Parameters.....	100
Input Examples	101
create_template function Output.....	102

Invocation Syntax

Use the HTTP post method to submit data to the API session URL. You can either write a simple java code or use HTML form to post data the EnterpriseTrack URL.

Invocation Examples

Note: These examples are just samples and may not work in your deployment as your configuration may differ. You must first download the template using the UI, or programmatically request the template then add data to this template before posting to the server.

Example: JSON Format

```
{"global_properties": {"date_format": "MMM/dd/yyyy", "language": "en"}, "request_data": {"request_type": "create_template", "entity_type": "project", "initiative": "Six Sigma", "output_format": "json"}}
```

Example: XML Format

```
<?xml version="1.0" encoding="UTF-8"?><root><global_properties><date_format>MMM/dd/yyyy</date_format><language>en</language></global_properties><request_data><request_type>create_template</request_type><entity_type>project</entity_type><initiative>Six Sigma</initiative><output_format>xml</output_format></request_data></root>
```

Invocation Parameters

The parameters for the invocation of the create_template function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or constant	Description
<i>Request_data</i>	String	<code><input_data></code>	Specifies the input parameters for the request in the format specified in the <code>request_format</code> parameter. For more details, see the <i>Input Parameters</i> .
<i>Request_format</i>	String	<code><request_format></code>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table identify the data that can be specified in `<input_data>`. This information should be provided in JSON or XML formatted data. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
<code>global_properties</code>	Object	Yes	Not applicable	This <i>object</i> lists the global settings for your EnterpriseTrack instance.
<code>request_data</code>	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See "Request_Data Table" for more details.

Name	Data Type	Value Required?	Placeholder or Constant	Description
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate, it is recommended that you download the create template request from your EnterpriseTrack Administration module. For more details, see Downloading CRUD Templates (on page 262) on page .
Request_data Table				
Request_type	String	Yes	create_template	The name of the function.
Entity_type	String	Yes	project	The entity type on which the operation is being performed.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data for the create_template function in XML and JSON formats.

Input Example in XML Format

The following is an example of the input data specified to generate a create template for the project IT.

```
<root>
  <global_properties>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
  </global_properties>
  <request_data>
    <request_type>create_template</request_type>
    <initiative>IT</initiative>
    <entity_type>project</entity_type>
    <output_format>xml</output_format>
  </request_data>
</root>
```

Input Example in JSON Format

The following is an example of the input data specified to generate a create template for the project IT.

```
{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
  },
  "request_data": {
    "request_type": "create_template",
    "entity_type": "project",
    "initiative": "IT",
    "output_format": "json",
  }
}
```

create_template function Output

The output of the create_template function is a create template.

Output Examples

The following section provides examples of output from the create_template function in XML and JSON formats.

Output Example in XML Format

The following is an example of a create template generated for the Project IT with place holders:

```
<root>
  <global_properties>
    <char_set>ISO-8859-1</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <request_data>
    <request_type>create</request_type>
    <entity_type>project</entity_type>
    <output_format>xml</output_format>
    <value_delimiter>|</value_delimiter>
  </request_data>
```

```
<app_data>
  <project>
    <project_number>
      <display_name>Project ID</display_name>
      <value/>
    </project_number>
    <pcs>
      <display_name>Initiative</display_name>
      <value>IT</value>
    </pcs>
    <project_name>
      <display_name>Project Name</display_name>
      <value/>
    </project_name>
    <calendar_id>
      <display_name>Calendar</display_name>
      <value/>
    </calendar_id>
    <status_descriptor> </status_descriptor> <dates_descriptor>
<start_date>
  <display_name>Actual Start Date</display_name>
  <value/>
</start_date>
  <planned_realization_date>
    <display_name>Planned Project Realization Date</display_name>
    <value/>
  </planned_realization_date>
</dates_descriptor> <org_descriptor> <division>
  <display_name>Division</display_name>
  <value/>
</division>
  <business_unit>
    <display_name>Business Unit</display_name>
    <value/>
  </business_unit>
  <location>
    <display_name>Location</display_name>
    <value/>
  </location>
  <region>
    <display_name>Region</display_name>
    <value/>
  </region>
</org_descriptor> <classification_descriptor> <functional_area>
  <display_name>Functional Area</display_name>
  <value/>
</functional_area>
  <priority>
    <display_name>Risk</display_name>
```

```
        <value/>
    </priority>
    <process>
        <display_name>Process Area</display_name>
        <value/>
    </process>
    <project_source>
        <display_name>Project Source</display_name>
        <value/>
    </project_source>
    </classification_descriptor> <methodology_descriptor>
<project_type>
    <display_name>Project Type</display_name>
    <value/>
</project_type>
<roadmap>
    <display_name>Roadmap</display_name>
    <value/>
</roadmap>
</methodology_descriptor> <finance_descriptor> <currency_code>
    <display_name>Currency</display_name>
    <value/>
</currency_code>
<fintemplateid>
    <display_name>Finance Template</display_name>
    <value/>
</fintemplateid>
</finance_descriptor>
<settings_descriptor> </settings_descriptor>
<team_member_descriptors>
    <team_member_descriptor>
        <teammember_id>1</teammember_id>
        <role> <display_name>Project Manager</display_name>
            <value>pm_globalrole</value>
        </role> <resource_descriptor> <userid/>
            <login_id/>
            <email/>
            <first_name/>
            <last_name/>
        </resource_descriptor>
    </team_member_descriptor>
</team_member_descriptors>
```

```
<team_member_descriptor>
  <teammember_id>2</teammember_id>
    <role> <display_name>DBA</display_name>
      <value>Id_018IT_DBA_</value>
    </role> <resource_descriptor> <userid/>
      <login_id/>
      <email/>
      <first_name/>
      <last_name/>
    </resource_descriptor>
  </team_member_descriptor>
</team_member_descriptors>

  <custom_fields>
    <predefined_fields>
      <basic_d_field1>
        <display_name>Basic Date Label7</display_name>
        <value/>
      </basic_d_field1>
      <orgz_t_field1>
        <display_name>Project Tracking Details</display_name>
        <value/>
      </orgz_t_field1>
      <classf_d_field1>
        <display_name>Project Validate Date</display_name>
        <value/>
      </classf_d_field1>
    </predefined_fields>
    <runtime_fields>
      <Project_custom_field_1>
        <display_name>Runtime custom Boolean field
1</display_name>
        <value/>
      </Project_custom_field_1>
    </runtime_fields>
  </custom_fields>
</project>
</app_data>
</root>
```

Output Example in JSON Format

The following is an example of a create template generated for the Project IT with place holders:

```
{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
  },
}
```

```
"request_data": {
  "request_type": "create_template",
  "entity_type": "project",
  "initiative": "IT",
  "output_format": "json",
}
"app_data": {
  "project" {
    "project_number" {
      "display_name": "Project ID"
      "value": " "
    }
    "pcs" {
      "display_name": "Initiative"
      "value": "IT"
    }
    "project_name" {
      "display_name": "Project Name"
      "value": ""
    }
    "calendar_id" {
      "display_name": "Calendar"
      "value": ""
    }
    "status_descriptor": ""
    "dates_descriptor" {
      "start_date" {
        "display_name": "Actual Start Date"
        "value": ""
      }
      "planned_realization_date" {
        "display_name": "Planned Project Realization
Date"
        "value": ""
      }
    }
    "org_descriptor" {
      "division" {
        "display_name": "Division"
        "value": ""
      }
      "business_unit" {
        "display_name": "Business Unit"
        "value": ""
      }
    }
  }
}
```

```
    "location": {
      "display_name": "Location"
      "value": ""
    }
    "region": {
      "display_name": "Region"
      "value": ""
    }
  }
  "classification_descriptor": {
<functional_area>
    "display_name": "Functional Area"
    "value": ""
  </functional_area>
  <priority>
    "display_name": "Risk"
    "value": ""
  </priority>
  <process>
    "display_name": "Process Area"
    "value": ""
  </process>
  <project_source>
    "display_name": "Project Source"</display_name>
    "value": ""
  </project_source>
</classification_descriptor>
<methodology_descriptor>
  <project_type>
    "display_name": "Project Type"
    "value": ""
  </project_type>
  <roadmap>
    "display_name": "Roadmap"</display_name>
    "value": ""
  </roadmap>
</methodology_descriptor>
<finance_descriptor> <currency_code>
  "display_name": "Currency"
  "value": ""
</currency_code>
  <fintemplateid>
    "display_name": "Finance Template"
    "value": ""
  </fintemplateid>
</finanace_descriptor>
<settings_descriptor> </settings_descriptor>
```

```

    <team_member_descriptors>
  <team_member_descriptor>
  <teammember_id>1</teammember_id>
    <role> "display_name": "Project Manager"
      <value>pm_globalrole</value>
    </role> <resource_descriptor> <userid/>
      <login_id/>
      <email/>
      <first_name/>
      <last_name/>
    </resource_descriptor>
  </team_member_descriptor>
  <team_member_descriptor>
    <teammember_id>2</teammember_id>
      <role> "display_name": "DBA"
        "value": "Id_018IT_DBA_"
      </role> <resource_descriptor> <userid/>
        <login_id/>
        <email/>
        <first_name/>
        <last_name/>
      </resource_descriptor>
    </team_member_descriptor>
  </team_member_descriptors>
  <custom_fields> <predefined_fields>
    <basic_d_field1>
      "display_name": "Basic Date Label7"
      <value/>
    </basic_d_field1>
    <orgz_t_field1>
      "display_name": "Project Tracking Details"
      <value/>
    </orgz_t_field1>
    <classf_d_field1>
      "display_name": "Project Validate Date"
      <value/>
    </classf_d_field1>
  </predefined_fields>
  <runtime_fields>
    <Project_custom_field_1>
      "display_name": "Runtime custom Boolean field 1"
      "value": ""
    </Project_custom_field_1>
  </runtime_fields>
</custom_fields>
</project>
</app_data>
}

```

Update Function

The update function allows you to update a project in EnterpriseTrack.

In This Section

Invocation Syntax	110
Invocation Parameters.....	110
Input Examples	112
Output Examples.....	121

Invocation Syntax

The syntax for the invocation of the Update function is:

```
<api_session>?&request_data=<request_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, project15_update.xml and project15_update.json. Then the syntax for the update function is:

```
<api_session>?&request_data=<content of
project15_update.xml>&request_format=xml
```

```
<api_session>?&request_data=<content of
project15_update.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the update function are described in the following table. Unless otherwise specified, all values are not case-sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
<i>Request_data</i>	String	Yes	<i><input_data></i>	Specifies the input parameters for the request in the format specified in the request_format parameter. For more details, see the <i>Input Parameters</i> .
<i>Request_format</i>	String	Yes	<i><request_format></i>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Name	Data Type	Value Required?	Placeholder or constant	Description
global_properties	Object	Yes	Not applicable	This object lists the global settings for the EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See "Request_Data Table" below for more details.
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate, it is recommended that you download the update template from your EnterpriseTrack Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	update	The name of the function.
Entity_type	String	Yes	project	The entity on which the operation is being performed.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data for the Update function in XML and JSON formats.

Input Example in XML Format

The following is an example of the input data for the update function in XML format.

```
<root>
  <global_properties>
    <char_set>ISO-8859-1</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <request_data>
    <request_type>update</request_type>
    <entity_type>project</entity_type>
    <output_format>xml</output_format>
    <value_delimiter>|</value_delimiter>
  </request_data>
```

```

<app_data>
  <project>
    <project_number>
      <display_name>Project ID</display_name>
      <value>13</value>
    </project_number>
    <project_name>
      <display_name>Project Name</display_name>
      <value>Changed_project_name101</value>
    </project_name>
    <calendar_id>
      <display_name>Calendar</display_name>
      <value>4-Day Week Calendar</value>
    </calendar_id>
    <emailnotification_flag>
      <display_name>Send Email
Notifications</display_name>
      <value>No</value>
    </emailnotification_flag>
    <keywords>
      <display_name>keywords</display_name>
      <value>Cost Reduction</value>
    </keywords>
    <status_descriptor>
      <project_status>
        <display_name>Status</display_name>
        <value>Active</value>
      </project_status>
      <hold_start_date>
        <display_name>Hold Start Date</display_name>
        <value/>
      </hold_start_date>
      <hold_end_date>
        <display_name>Hold End Date</display_name>
        <value/>
      </hold_end_date>
      <percent_completion_type>
        <display_name>Percent Completion
Type</display_name>
        <value>Manual Mode</value>
      </percent_completion_type>
    </status_descriptor>
    <dates_descriptor/>
    <org_descriptor>
      <division>
        <display_name>Division</display_name>
        <value>Consumer Products</value>
      </division>
      <business_unit>

```

```
        <display_name>Business Unit</display_name>
        <value>Electronics</value>
    </business_unit>
    <location>
        <display_name>Location</display_name>
        <value>Bangalore</value>
    </location>
    <region>
        <display_name>Region</display_name>
        <value>South America</value>
    </region>
</org_descriptor>
<classification_descriptor>
    <functional_area>
        <display_name>Functional Area</display_name>
        <value>Information Systems</value>
    </functional_area>
    <priority>
        <display_name>Risk</display_name>
        <value>Low</value>
    </priority>
    <process>
        <display_name>Process Area</display_name>
        <value>Customer Service</value>
    </process>
    <project_source>
        <display_name>Project Source</display_name>
        <value>Finance</value>
    </project_source>
</classification_descriptor>
<methodology_descriptor/>
<finance_descriptor>
```

```

        <consider_for_finances>
            <display_name>Include in Financial
Calculations</display_name>
            <value>yes</value>
        </consider_for_finances>
        <fin_track_start_date>
            <display_name>Finance Tracking Start
Date</display_name>
            <value>2014/7/20</value>
        </fin_track_start_date>
    </finance_descriptor>
    <settings_descriptor>
        <default_laborexpensetype>
            <display_name>Default Labor Expense
Type</display_name>
            <value>OpEx (Operational Expense)</value>
        </default_laborexpensetype>
    </settings_descriptor>
    <custom_fields>
        <predefined_fields>
            <orgz_t_field2>
                <display_name>Project Tracking
Details</display_name>
                <value>Late by 10 days</value>
            </orgz_t_field2>
            <classf_d_field1>
                <display_name>Project Validate
Date</display_name>
                <value>2013/12/17</value>
            </classf_d_field1>
        </predefined_fields>
        <runtime_fields>
            <Project_custom_field_1>
                <display_name>Runtime custom Boolean
field 1</display_name>
                <value>Yes</value>
            </Project_custom_field_1>
        </runtime_fields>
    </custom_fields>
</project>
</app_data>
</root>

```

Input Example in JSON Format

The following is an example of the input data for the update function in JSON format:

```

{
  "global_properties": {

```

```
"char_set": "ISO-8859-1",
"date_format": "yyyy/MM/dd",
"language": "en",
"api_version": "9.0"
},
"request_data": {
  "request_type": "update",
  "entity_type": "project",
  "output_format": "json",
  "value_delimiter": "|"
},
"app_data": {
  "project": [
    {
      "project_number": {
        "display_name": "Project ID",
        "value": "53"
      },
      "project_name": {
        "display_name": "Project Name",
        "value": "Changed_project_name_501"
      },
      "calendar_id": {
        "display_name": "Calendar",
        "value": "4-Day Week Calendar"
      },
      "emailnotification_flag": {
        "display_name": "Send Email Notifications",
        "value": "No"
      },
      "keywords": {
        "display_name": "keywords",
        "value": "Cost Reduction"
      }
    },
```

```
"status_descriptor": {
  "project_status": {
    "display_name": "Status",
    "value": "Active"
  },
  "hold_start_date": {
    "display_name": "Hold Start Date",
    "value": ""
  },
  "hold_end_date": {
    "display_name": "Hold End Date",
    "value": ""
  },
  "percent_completion_type": {
    "display_name": "Percent Completion Type",
    "value": "Manual Mode"
  }
},
"dates_descriptor": {

},
"org_descriptor": {
  "division": {
    "display_name": "Division",
    "value": "Consumer Products"
  },
  "business_unit": {
    "display_name": "Business Unit",
    "value": "Electronics"
  },
  "location": {
    "display_name": "Location",
    "value": "Bangalore"
  },
}
```

```
    "region": {
      "display_name": "Region",
      "value": "South America"
    }
  },
  "classification_descriptor": {
    "functional_area": {
      "display_name": "Functional Area",
      "value": "Information Systems"
    },
    "priority": {
      "display_name": "Risk",
      "value": "Low"
    },
    "process": {
      "display_name": "Process Area",
      "value": "Customer Service"
    },
    "project_source": {
      "display_name": "Project Source",
      "value": "Finance"
    }
  },
  "methodology_descriptor": {
  },
  "finanace_descriptor": {
    "consider_for_finances": {
      "display_name": "Include in Financial Calculations",
      "value": ""
    },
    "fin_track_start_date": {
      "display_name": "Finance Tracking Start Date",
      "value": "2014/07/28"
    }
  }
}
```

```
    },
    "findata_flag": {
      "display_name": "How should shifting the Finance Tracking
Start Date affect Financial Data?",
      "value": "clear"
    },
    "currency_code": {
      "display_name": "Currency",
      "value": "Euro"
    },
    "changefindata": {
      "display_name": "Convert existing financial data from old
currency to new currency using conversion rates",
      "value": ""
    },
    "fin_edit_mode": {
      "display_name": "Finance Edit Mode",
      "value": "Monthly"
    },
    "financials_unlocked": {
      "display_name": "Finances Locked Globally",
      "value": ""
    },
    "fintemplateid": {
      "display_name": "Finance Template",
      "value": "Finance import export"
    },
    "initial_forecast_savings": {
      "display_name": "Initial Forecast Benefits",
      "value": "1000"
    },
    "initial_forecast_cost": {
      "display_name": "Initial Forecast Cost",
      "value": "2000"
    }
  }
```

```
    },
    "initial_forecast_nonrollup": {
      "display_name": "Initial Forecast Soft Dollar",
      "value": "3000"
    },
    "initial_forecast_group4": {
      "display_name": "Initial Forecast Group4",
      "value": "4000"
    },
    "Is_capitalized": {
      "display_name": "Is Capitalized",
      "value": "Yes"
    },
    "is_fin_lock_global": {
      "display_name": "Use Global Lock Month",
      "value": "Yes"
    },
    "project_fin_lock_date": {
      "display_name": "Project Finance Lock Month",
      "value": "2014/7/20"
    },
    "resource_computation_enabled": {
      "display_name": "Resource Computation Enabled",
      "value": "No"
    }
  },
  "settings_descriptor": {
    "default_laborexpensetype": {
      "display_name": "Default Labor Expense Type",
      "value": "OpEx (Operational Expense)"
    },
  },
},
"custom_fields": {
  "predefined_fields": {
```

```

    "orgz_t_field2": {
      "display_name": "Project Tracking Details",
      "value": "Late by 10 days"
    },
    "classf_d_field1": {
      "display_name": "Project Validate Date",
      "value": "2013/12/17"
    }
  },
  "runtime_fields": {
    "Project_custom_field_1": {
      "display_name": "Runtime custom Boolean field 1",
      "value": "Yes"
    },
  }
}

```

Output Examples

The following section provides examples of the update function in XML and JSON formats.

Output in XML Format

The following is an example of the response from the update function for updating a project in XML format.

```

<root> <global_properties> <char_set>ISO-8859-1</char_set>
  <date_format>yyyy/MM/dd</date_format>
  <language>en</language>
  <api_version>9.0</api_version>
</global_properties> <response_data>
<request_type>update</request_type>
  <entity_type>project</entity_type>
  <response_code>0</response_code>
  <response_desc/>
</response_data> <app_data> </app_data> </root>

```

Output in JSON Format

The following is an example of the response from the Update function for updating a project in JSON format.

```
{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0",
    "char_set": "ISO-8859-1"
  },
  "response_data": {
    "response_desc": "",
    "request_type": "update",
    "response_code": "0",
    "entity_type": "project"
  },
  "app_data": {"": []}
```

Update_template Function

The update_template function allows you to retrieve a template for updating a project. This can be used to define data for updating a project in EnterpriseTrack. Alternatively, you can also download a template from the EnterpriseTrack Administration module. For more details, see **Downloading CRUD Templates** (on page 262).

In This Section

Invocation Syntax.....	122
Invocation Parameters.....	123
Input Parameters.....	123
Input Examples	124
Output	125
Output Examples.....	125

Invocation Syntax

The syntax for the invocation of the update_template function is:

```
<api_session>?&request_data=<request_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, `project15_update_template.xml` and `project15_update_template.json`. Then the syntax for the update function is:

```
<api_session>?&request_data=<content of
project15_update_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<content of
project15_update_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the `update_template` function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
<i>Request_data</i>	String	Yes	<code><input_data></code>	Specifies the input data for updating a project. For more details, see the Input Parameters.
Request_form at	String	Yes	<code><request_format></code>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
<i>global_properties</i>	Object	Yes	<i>Not applicable</i>	This object lists the global settings for your EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See the Request_Data Table below for more details.

Name	Data Type	Value Required?	Placeholder or constant	Description
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the update_template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	update_template	The name of the function.
Entity_type	String	Yes	project	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter		Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data for the update_template function in XML and JSON formats.

Input Example in XML Format

The following is an example of the input data for the update_template function in XML format.

```
<root>
  <global_properties>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
  </global_properties>
  <request_data>
    <request_type>update_template</request_type>
    <initiative>IT</initiative>
    <entity_type>project</entity_type>
    <output_format>xml</output_format>
  </request_data>
</root>
```

Input Example in JSON Format

The following is an example of the input data for the update_template function in JSON format.

```
{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
  },
  "request_data": {
    "request_type": "update_template",
    "entity_type": "project",
    "initiative": "IT",
    "output_format": "json",
  }
}
```

Output

The output of the update_template function is an update_request_template.

Output Examples

The following section provides examples of output data generated from the update_template function in XML and JSON formats.

Output Example in XML Format

The following is an example of the data output from the update_template api in XML format.

```
<root> <global_properties> <char_set>ISO-8859-1</char_set>
  <date_format>yyyy/mm/dd</date_format>
  <language>en</language>
  <api_version>9.0</api_version>
</global_properties> <request_data>
<request_type>update</request_type>
  <entity_type>project</entity_type>
  <output_format>xml</output_format>
  <value_delimiter>|</value_delimiter>
</request_data> <app_data> <project> <project_number>
  <display_name>Project ID</display_name>
  <value/>
</project_number>
<project_name>
  <display_name>Project Name</display_name>
  <value/>
</project_name>
<calendar_id>
  <display_name>Calendar</display_name>
  <value/>
</calendar_id>
<emailnotification_flag>
  <display_name>Send Email Notifications</display_name>
  <value/>
</emailnotification_flag>
<keywords>
  <display_name>keywords</display_name>
  <value/>
</keywords>
<status_descriptor> <project_status>
  <display_name>Status</display_name>
  <value/>
</project_status>
<hold_start_date>
  <display_name>Hold Start Date</display_name>
  <value/>
</hold_start_date>
<hold_end_date>
  <display_name>Hold End Date</display_name>
  <value/>
</hold_end_date>
<percent_completion_type>
  <display_name>Percent Completion Type</display_name>
  <value/>
</percent_completion_type>
</status_descriptor> <org_descriptor> <division>
  <display_name>Division</display_name>
  <value/>
</division>
```

```
<business_unit>
  <display_name>Business Unit</display_name>
  <value/>
</business_unit>
<location>
  <display_name>Location</display_name>
  <value/>
</location>
<region>
  <display_name>Region</display_name>
  <value/>
</region>
</org_descriptor> <classification_descriptor> <functional_area>
  <display_name>Functional Area</display_name>
  <value/>
</functional_area>
<priority>
  <display_name>Risk</display_name>
  <value/>
</priority>
<process>
  <display_name>Process Area</display_name>
  <value/>
</process>
<project_source>
  <display_name>Project Source</display_name>
  <value/>
</project_source>
</classification_descriptor> <methodology_descriptor>
</methodology_descriptor>
<finanace_descriptor> <consider_for_finances>
  <display_name>Include in Financial Calculations</display_name>
  <value/>
</consider_for_finances>
<fin_track_start_date>
  <display_name>Finance Tracking Start Date</display_name>
  <value/>
</fin_track_start_date>
<findata_flag>
  <display_name>How should shifting the Finance Tracking Start
Date affect Financial Data?</display_name>
  <value/>
</findata_flag>
<currency_code>
  <display_name>Currency</display_name>
  <value/>
</currency_code>
<changefindata>
  <display_name>Convert existing financial data from old currency
```

```
to new currency using conversion rates</display_name>
  <value/>
</changefindata>
<fin_edit_mode>
  <display_name>Finance Edit Mode</display_name>
  <value/>
</fin_edit_mode>
<financials_unlocked>
  <display_name>Finances Locked Globally</display_name>
  <value/>
</financials_unlocked>
<fintemplateid>
  <display_name>Finance Template</display_name>
  <value/>
</fintemplateid>
<initial_forecast_savings>
  <display_name>Initial Forecast Benefits</display_name>
  <value/>
</initial_forecast_savings>
<initial_forecast_cost>
  <display_name>Initial Forecast Cost</display_name>
  <value/>
</initial_forecast_cost>
<initial_forecast_nonrollup>
  <display_name>Initial Forecast Soft Dollar</display_name>
  <value/>
</initial_forecast_nonrollup>
<initial_forecast_group4>
  <display_name>Initial Forecast Group4</display_name>
  <value/>
</initial_forecast_group4>
<Is_capitalized>
  <display_name>Is Capitalized</display_name>
  <value/>
</Is_capitalized>
<is_fin_lock_global>
  <display_name>Use Global Lock Month</display_name>
  <value/>
</is_fin_lock_global>
<project_fin_lock_date>
  <display_name>Project Finance Lock Month
(yyyy/mm/dd)</display_name>
  <value/>
</project_fin_lock_date>
<resource_computation_enabled>
  <display_name>Resource Computation Enabled</display_name>
  <value/>
</resource_computation_enabled>
</finanace_descriptor> <settings_descriptor>
```

```
<default_laborexpensetype>
  <display_name>Default Labor Expense Type</display_name>
  <value/>
</default_laborexpensetype>
<externalmode_datesduration>
  <display_name>Computation mode for dates and
duration</display_name>
  <value/>
</externalmode_datesduration>
<externalmode_durationeffort>
  <display_name>Computation mode for duration and
efforts</display_name>
  <value/>
</externalmode_durationeffort>
<externalmode_effortcost>
  <display_name>Computation mode for efforts and
cost</display_name>
  <value/>
</externalmode_effortcost>
<grace_period_for_completed_activities_in_ts>
  <display_name>Allowed Grace Period In Days For Completed
Activities</display_name>
  <value/>
</grace_period_for_completed_activities_in_ts>
<grace_period_for_future_activities_in_ts>
  <display_name>Allowed Grace Period In Days For Yet To Start
Activities</display_name>
  <value/>
</grace_period_for_future_activities_in_ts>
<is_capitalization_enabled>
  <display_name>Is Labor Cost Capitalization Enabled
?</display_name>
  <value/>
</is_capitalization_enabled>
<is_etc_enabled_for_timesheet>
  <display_name>Is Estimated Time To Complete Enabled For
Timesheets?</display_name>
  <value/>
</is_etc_enabled_for_timesheet>
<is_etc_required_for_timesheet>
  <display_name>Is Estimated Time To Complete Required For
Timesheets?</display_name>
  <value/>
</is_etc_required_for_timesheet>
<is_laborexpensetype_mandatory>
  <display_name>Is Labor Expense Type required for Activities
?</display_name>
  <value/>
</is_laborexpensetype_mandatory>
```

```
</settings_descriptor> <custom_fields> <predefined_fields>
  <orgz_t_field2>
    <display_name>Project Tracking Details</display_name>
    <value/>
  </orgz_t_field2>
  <classf_d_field1>
    <display_name>Project Validate Date</display_name>
    <value/>
  </classf_d_field1>
</predefined_fields> <runtime_fields> <Project_custom_field_1>
  <display_name>Runtime custom Boolean field 1</display_name>
  <value/>
</Project_custom_field_1>
</runtime_fields> </custom_fields> </project> </app_data> </root>
```

Output Example in JSON Format

The following is an example of the data output from the `update_template` api in JSON format.

```
{
  "global_properties": {
    "date_format": "",
    "language": "",
    "api_version": "",
    "char_set": ""
  },
  "response_data": {
    "response_desc": "[en] The supplied JSON is invalid.",
    "request_type": "unknown",
    "response_code": "2151",
    "entity_type": "unknown"
  },
  "app_data": {"": []}
}
```

Delete Function

The delete function allows you to delete a project in EnterpriseTrack.

In This Section

Invocation Syntax	131
Invocation Parameters.....	131
Input Parameters.....	131
Input Examples	133
Output Examples.....	134

Invocation Syntax

The syntax for the invocation of the delete function is:

```
<api_session>?&request_data=<request_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, project15_delete.xml and project15_delete.json. Then the syntax for the delete function is:

```
<api_session>?&request_data=<content of
project15_delete.xml>&request_format=xml
```

```
<api_session>?&request_data=<content of
project15_delete.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the delete function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
Request_data	String	Yes	<input_data>	Specifies the input data for deleting a project. For more details, see the Input Parameters.
Request_format	String	Yes	<request_format>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
<i>global_properties</i>	Object	Yes	<i>Not applicable</i>	This object lists the global settings for your EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See the Request_Data Table below for more details.
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the delete template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	delete	The name of the function.
Entity_type	String	Yes	project	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data for the delete function in XML and JSON formats.

Input Example in XML Format

The following example of input data deletes project ID 10770.

```
<root>
  <global_properties>
    <char_set>ISO-8859-1</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <request_data>
    <request_type>delete</request_type>
    <entity_type>project</entity_type>
    <output_format>xml</output_format>
    <value_delimiter>|</value_delimiter>
  </request_data>
  <app_data>
    <project>
      <project_number>
        <display_name>Project ID</display_name>
        <value>10770</value>
      </project_number>
      <project_name>
        <display_name>Project Name</display_name>
        <value/>
      </project_name>
      <delete_charter>
        <display_name>Delete Existing
Charter</display_name>
        <value>true</value>
      </delete_charter>
      <delete_idea>
        <display_name>Delete Existing Idea (if
any)</display_name>
        <value>true</value>
      </delete_idea>
    </project>
  </app_data>
</root>
```

Input Example in JSON Format

The following example of input data deletes project ID 10770.

```
{
  "global_properties": {
    "char_set": "ISO-8859-1",
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "delete",
    "entity_type": "project",
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project": [
      {
        "project_number": {
          "display_name": "Project ID",
          "value": "10800"
        },
        "project_name": {
          "display_name": "Project Name",
          "value": ""
        },
        "delete_charter": {
          "display_name": "Delete Existing Charter",
          "value": "true"
        },
        "delete_idea": {
          "display_name": "Delete Existing Idea (if any)",
          "value": "true"
        }
      }
    ]
  }
}
```

Output Examples

The following section provides examples of output data for the delete function in XML and JSON formats.

Output in XML Format

The following is an example of a successful deletion of a project in XML format:

```
<?xml version="1.0" encoding="UTF-8" ?>
```

```
- <root>
```

```

- <global_properties>
  <char_set>ISO-8859-1</char_set>
  <date_format>yyyy/MM/dd</date_format>
  <language>en</language>
  <api_version>9.0</api_version>
</global_properties>
- <response_data>
  <request_type>delete</request_type>
  <entity_type>project</entity_type>
  <response_code>0</response_code>
  <response_desc />
</response_data>
<app_data />
</root>

```

Output in JSON Format

The following is an example of a successful deletion of a project in JSON format:

```

{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0",
    "char_set": "ISO-8859-1"
  },
  "response_data": {
    "response_desc": "",
    "request_type": "delete",
    "response_code": "0",
    "entity_type": "project"
  },
  "app_data": {"": []}
}

```

Delete_template Function

The `delete_template` function allows you to retrieve a template for project deletion. This can be used to define data for deleting a project in EnterpriseTrack.

Alternatively, you can also download a template from the EnterpriseTrack Administration module. For more details, see **Downloading CRUD Templates** (on page 262) on page .

In This Section

Invocation Syntax.....	136
Invocation Parameters.....	136
Input Parameters.....	137
Input Examples	138
Output	138
Output Examples.....	138

Invocation Syntax

The syntax for the invocation of the delete_template function is as follows.

```
<api_session>?&request_data=<request_data>&request_format  
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, project15_delete_template.xml and project15_delete.json. Then the syntax for the delete_template function is as follows:

```
<api_session>?&request_data=<content of  
project15_delete_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<content of  
project15_delete_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the delete_template function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
Request_data	String	Yes	<input_data>	Specifies the input data for deleting a project. For more details, see the Input Parameters.
Request_format	String	Yes	<request_format>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
<i>global_properties</i>	Object	Yes	<i>Not applicable</i>	This object lists the global settings for your EnterpriseTrack instance.
<i>request_data</i>	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See the Request_Data Table below for more details.
<i>application_data</i>	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download delete_template from your EnterpriseTrack's Administration user interface. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	delete_template	The name of the function.
Entity_type	String	Yes	project	The entity being deleted.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data for the delete_template function in XML and JSON formats.

Input Example in XML Format

The following example of input data of delete_template function in XML format.

```
<root>
  <global_properties>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
  </global_properties>
  <request_data>
    <request_type>delete_template</request_type>
    <initiative>IT</initiative>
    <entity_type>project</entity_type>
    <output_format>xml</output_format>
  </request_data>
</root>
```

Input Example in JSON Format

The following example of input data of delete_template function in JSON format.

```
{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
  },
  "request_data": {
    "request_type": "delete_template",
    "entity_type": "project",
    "initiative": "IT",
    "output_format": "json",
  }
}
```

Output

The output of the delete_template function is a delete template.

Output Examples

The following section provides examples of output data generated from the delete_template in XML and JSON formats.

Output Example in XML Format

The following is an example of the output from the delete_template api, generated in XML format.

```
<root> <global_properties> <char_set>ISO-8859-1</char_set>
  <date_format>yyyy/MM/dd</date_format>
  <language>en</language>
  <api_version>9.0</api_version>
</global_properties> <request_data>
<request_type>delete</request_type>
  <entity_type>project</entity_type>
  <output_format>xml</output_format>
  <value_delimiter>|</value_delimiter>
</request_data> <app_data> <project> <project_number>
  <display_name>Project ID</display_name>
  <value/>
</project_number>
  <project_name>
  <display_name>Project Name</display_name>
  <value/>
</project_name>
  <delete_charter>
  <display_name>Delete Existing Charter</display_name>
  <value/>
</delete_charter>
  <delete_idea>
  <display_name>Delete Existing Idea (if any)</display_name>
  <value/>
</delete_idea>
</project> </app_data> </root>
```

Output Example in JSON Format

The following is an example of the output from the delete_template, generated in JSON format.

```
{
  "global_properties": {
    "date_format": "",
    "language": "",
    "api_version": "",
    "char_set": ""
  },
  "response_data": {
    "response_desc": "[en] The supplied JSON is invalid.",
    "request_type": "unknown",
    "response_code": "2151",
    "entity_type": "unknown"
  },
  "app_data": {"": []}}
```

Search Function

The search function allows you to search for a project in EnterpriseTrack.

In This Section

Invocation Syntax	140
Invocation Parameters.....	140
Input Parameters.....	141
Input Examples	142
Output Examples.....	146

Invocation Syntax

The syntax for the invocation of the search function is as follows.

```
<api_session>?&request_data=<request_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, project15_search.xml and project15_search.json. Then the syntax for the search function is as follows:

```
<api_session>?&request_data=<content specified in
project15_search.xml>&request_format=xml
```

```
<api_session>?&request_data=<content specified in
project15_search.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the search function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or constant	Description
<i>Request_data</i>	String	<i><input_data></i>	Specifies the input data for searching a project. For more details, see Input Parameters.
<i>Request_format</i>	String	<i><request_format></i>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> lists the global settings for your EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See <i>Request_Data Table</i> below for more details.
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the search template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	search	The name of the function.
Entity_type	String	Yes	project	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data specified for the Search function in XML and JSON formats.

Input Example in XML Format

The following is an example of input data of search function in XML format.

```

<root>
  <global_properties>
    <char_set>ISO-8859-1</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <request_data>
    <request_type>search</request_type>
    <entity_type>project</entity_type>
    <output_format>xml</output_format>
    <value_delimiter>|</value_delimiter>
  </request_data>
  <app_data>
    <project>
      <project_number>
        <display_name>Project ID</display_name>
        <value>14</value>
      </project_number>
      <project_name>
        <display_name>Project Name</display_name>
        <value/>
      </project_name>
      <status_descriptor>
        <project_status>
          <display_name>Status</display_name>
          <value/>
        </project_status>
      </status_descriptor>
      <project_start_date_from>
        <display_name>Project Start Date From
</display_name>
        <value/>
      </project_start_date_from>
      <project_start_date_to>
        <display_name>Project Start Date To</display_name>
        <value/>
      </project_start_date_to>
      <planned_realization_date_from>
        <display_name>Project Planned Realization Date
From</display_name>
        <value/>
      </planned_realization_date_from>
      <planned_realization_date_to>
        <display_name>Project Planned Realization Date
To</display_name>
        <value/>
      </planned_realization_date_to>
      <Project_manager>

```

```
<pm_user_id>
  <display_name>User ID</display_name>
  <value/>
</pm_user_id>
<pm_login_id>
  <display_name>Login ID</display_name>
  <value/>
</pm_login_id>
<pm_email>
  <display_name>EMail</display_name>
  <value/>
</pm_email>
<pm_first_name>
  <display_name>First Name</display_name>
  <value/>
</pm_first_name>
<pm_last_name>
  <display_name>Last Name</display_name>
  <value/>
</pm_last_name>
</Project_manager>
</project>
</app_data>
</root>
```

Input Example in JSON Format

The following is an example of input data of search function in JSON format.

```
{
  "global_properties": {
    "char_set": "ISO-8859-1",
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "search",
    "entity_type": "project",
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project": [
      {
        "project_number": {
          "display_name": "Project ID",
          "value": "5"
        }
      }
    ]
  }
}
```

```
"project_name": {
  "display_name": "Project Name",
  "value": ""
},
"status_descriptor": {
  "project_status": {
    "display_name": "Status",
    "value": ""
  }
},
"project_start_date_from": {
  "display_name": "Project Start Date From ",
  "value": ""
},
"project_start_date_to": {
  "display_name": "Project Start Date To",
  "value": ""
},
"planned_realization_date_from": {
  "display_name": "Project Planned Realization Date From",
  "value": ""
},
"planned_realization_date_to": {
  "display_name": "Project Planned Realization Date To",
  "value": ""
},
"project_manager": {
  "pm_user_id": {
    "display_name": "User ID",
    "value": ""
  },
  "pm_login_id": {
    "display_name": "Login ID",
    "value": ""
  },
  "pm_email": {
    "display_name": "EMail",
    "value": ""
  },
  "pm_first_name": {
    "display_name": "First Name",
    "value": ""
  },
  "pm_last_name": {
    "display_name": "Last Name",
    "value": ""
  }
}
}
```

```
}  
  }  
}
```

Output Examples

The following section provides examples of output generated by the Search function in XML and JSON formats.

Output Example in XML Format

The following example retrieves a project with Project ID = 14, in XML format.

```
<root> <global_properties> <char_set>ISO-8859-1</char_set>  
  <date_format>yyyy/MM/dd</date_format>  
  <language>en</language>  
  <api_version>9.0</api_version>  
</global_properties> <response_data>  
<request_type>search</request_type>  
  <entity_type>project</entity_type>  
  <response_code>0</response_code>  
  <response_desc/>  
</response_data> <app_data> <project> <project_number>  
  <display_name>Project ID</display_name>  
  <value>14</value>  
</project_number>  
<project_manager>  
  <display_name>Project Manager</display_name>  
  <value>LN_Roles_for_IT, FN_pm_globalrole_1_1</value>  
</project_manager>  
<pcs>  
  <display_name>Initiative</display_name>  
  <value>IT</value>  
</pcs>  
<project_name>  
  <display_name>Project Name</display_name>  
  <value>Instantis Social PPM pilot</value>  
</project_name>
```

```
<calendar_id>
  <display_name>Calendar</display_name>
  <value>Internal-7 Days Calendar</value>
</calendar_id>
<emailnotification_flag>
  <display_name>Send Email Notifications</display_name>
  <value>No</value>
</emailnotification_flag>
<keywords>
  <display_name>keywords</display_name>
  <value>_demo_</value>
</keywords>
<status_descriptor> <project_status>
  <display_name>Status</display_name>
  <value>Active</value>
</project_status>
  <percent_completion_type>
    <display_name>Percent Completion Type</display_name>
    <value>Count-based (Completed vs. Total Count for Immediate
Children)</value>
  </percent_completion_type>
</status_descriptor> <dates_descriptor> <start_date>
  <display_name>Actual Start Date</display_name>
  <value>2009/08/12</value>
</start_date>
  <planned_realization_date>
    <display_name>Planned Project Realization Date</display_name>
    <value>2009/12/05</value>
  </planned_realization_date>
  <actual_realization_date>
    <display_name>Actual Realization Date</display_name>
    <value/>
  </actual_realization_date>
  <planned_completion_date>
```

```
    <display_name>Planned Project Completion Date</display_name>
    <value>2010/12/05</value>
  </planned_completion_date>
  <completion_date>
    <display_name>Completion Date</display_name>
    <value/>
  </completion_date>
</dates_descriptor> <org_descriptor> <division>
  <display_name>Division</display_name>
  <value>Business Development</value>
</division>
<business_unit>
  <display_name>Business Unit</display_name>
  <value>Channels</value>
</business_unit>
<location>
  <display_name>Location</display_name>
  <value>Fairfield, CT</value>
</location>
<region>
  <display_name>Region</display_name>
  <value>North America</value>
</region>
</org_descriptor> <classification_descriptor> <functional_area>
  <display_name>Functional Area</display_name>
  <value>Accounts Payable</value>
</functional_area>
<priority>
  <display_name>Risk</display_name>
  <value/>
</priority>
<process>
  <display_name>Process Area</display_name>
  <value/>
```

```
</process>
<project_source>
  <display_name>Project Source</display_name>
  <value/>
</project_source>
</classification_descriptor>
<methodology_descriptor>
  <project_type>
    <display_name>Project Type</display_name>
    <value>IT</value>
  </project_type>
  <roadmap>
    <display_name>Roadmap</display_name>
    <value>IT Project I</value>
  </roadmap>
</methodology_descriptor>
<finance_descriptor>
  <consider_for_finances>
    <display_name>Include in Financial
Calculations</display_name>
    <value>Yes</value>
  </consider_for_finances>
  <fin_track_start_date>
    <display_name>Finance Tracking Start Date</display_name>
    <value>2009/12/05</value>
  </fin_track_start_date>
  <currency_code>
    <display_name>Currency</display_name>
    <value>US Dollar</value>
  </currency_code>
  <fin_edit_mode>
    <display_name>Finance Edit Mode</display_name>
    <value>Monthly</value>
  </fin_edit_mode>
```

```
<finance_lock_enforcement>
  <display_name>Finance Lock/Close Period
Enforcement</display_name>
  <value/>
</finance_lock_enforcement>
<financials_unlocked>
  <display_name>Finances Locked Globally</display_name>
  <value>No</value>
</financials_unlocked>
<fintemplateid>
  <display_name>Finance Template</display_name>
  <value>Default Global Finance Template</value>
</fintemplateid>
<initial_forecast_savings>
  <display_name>Initial Forecast Benefits</display_name>
  <value>$0.00</value>
</initial_forecast_savings>
<initial_forecast_cost>
  <display_name>Initial Forecast Cost</display_name>
  <value>$0.00</value>
</initial_forecast_cost>
<initial_forecast_nonrollup>
  <display_name>Initial Forecast Soft Dollar</display_name>
  <value>$0.00</value>
</initial_forecast_nonrollup>
<initial_forecast_group4>
  <display_name>Initial Forecast Group4</display_name>
  <value>$0.00</value>
</initial_forecast_group4>
<initial_forecast_total>
  <display_name>Initial Forecast Total</display_name>
  <value>$0.00</value>
</initial_forecast_total>
<Is_capitalized>
```

```
    <display_name>Is Capitalized</display_name>
    <value>Unspecified</value>
</Is_capitalized>
<is_fin_lock_global>
    <display_name>Use Global Lock Month</display_name>
    <value>Yes</value>
</is_fin_lock_global>
<project_fin_lock_date>
    <display_name>Project Finance Lock Month
(yyyy/mm/dd)</display_name>
    <value>1761/01/01</value>
</project_fin_lock_date>
<resource_computation_enabled>
    <display_name>Resource Computation Enabled</display_name>
    <value>No</value>
</resource_computation_enabled>
</finance_descriptor>
<settings_descriptor>
    <default_laborexpensetype>
        <display_name>Default Labor Expense Type</display_name>
        <value/>
    </default_laborexpensetype>
</settings_descriptor>
<team_member_descriptors>
    <team_member_descriptor>
        <teammember_id>1</teammember_id>
        <role> <display_name>Project Manager</display_name>
        <value>pm_globalrole</value>
        <resource_descriptor>
            <userid>JWS2WTH7X6WKT</userid>
            <login_id> JJones</login_id>
            <email>Janet.Jones@example.com </email>
            <first_name> Janet</first_name>
            <last_name> Jones</last_name>
```

```
        </resource_descriptor>
    <role>
        <display_name> DBA </display_name>
        <value> Id_018IT_DBA_ " </value>
    </role>
    <resource_descriptor>
        <login_id> jdoe </login_id>
        <first_name> Jane </first_name>
        <email> jane.doe@example.com </email>
        <last_name> Doe</last_name>
        <userid> JWS2VXH2GMS5M </userid>
    </role>
    </team_member_descriptor>
</team_member_descriptors>
<custom_fields>
    <predefined_fields>
        <basic_d_field1>
            <display_name>Basic Date Label7</display_name>
            <value/>
        </basic_d_field1>
        <orgz_t_field1>
            <display_name>Project On Track ?</display_name>
            <value>TRUE</value>
        </orgz_t_field1>
        <classf_d_field1>
            <display_name>Project Validate Date</display_name>
            <value>2003/05/06</value>
        </classf_d_field1>
    </predefined_fields>
    <runtime_fields>
        <Project_custom_field_1>
            <display_name>Runtime custom Boolean field 1</display_name>
            <value>Yes</value>
        </Project_custom_field_1>
```

```
</runtime_fields>  
</custom_fields> </project> </app_data> </root>
```

Output Example in JSON Format

The following example retrieves a project with Project ID = 14, in JSON format.

```
{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0",
    "char_set": "ISO-8859-1"
  },
  "response_data": {
    "response_desc": "",
    "request_type": "search",
    "response_code": "0",
    "entity_type": "project"
  },
  "app_data": {"project": [{
    "custom_fields": {
      "runtime_fields": {
        "Project_custom_field_1": {
          "display_name": "Runtime custom Boolean field 1",
          "value": "Yes"
        }
      },
      "predefined_fields": {
        "basic_d_field1": {
          "display_name": "Basic Date Label7",
          "value": ""
        },
        "orgz_t_field1": {
          "display_name": "Project On Track ?",
          "value": "TRUE"
        },
        "classf_d_field1": {
          "display_name": "Project Validate Date",
          "value": "2003/05/06"
        }
      }
    }
  ]},
  "dates_descriptor": {
    "actual_realization_date": {
      "display_name": "Actual Realization Date",
      "value": ""
    },
    "planned_completion_date": {
      "display_name": "Planned Project Completion Date",
      "value": "2009/10/12"
    },
    "completion_date": {
      "display_name": "Completion Date",
      "value": ""
    }
  },
}
```

```
    "planned_realization_date": {
      "display_name": "Planned Project Realization Date",
      "value": "2009/10/10"
    },
    "start_date": {
      "display_name": "Actual Start Date",
      "value": "2009/08/11"
    }
  },
  "calendar_id": {
    "display_name": "Calendar",
    "value": "Internal-7 Days Calendar"
  },
  "project_name": {
    "display_name": "Project Name",
    "value": "updated_name"
  },
  "keywords": {
    "display_name": "keywords",
    "value": "_demo_"
  },
  "org_descriptor": {
    "region": {
      "display_name": "Region",
      "value": "North America"
    },
    "business_unit": {
      "display_name": "Business Unit",
      "value": "Channels"
    },
    "division": {
      "display_name": "Division",
      "value": "Business Development"
    },
    "location": {
      "display_name": "Location",
      "value": "Fairfield, CT"
    }
  },
  "settings_descriptor": {
    "is_laborexpensetype_mandatory": {
      "display_name": "Is Labor Expense Type required for Activities ?",
      "value": "No"
    }
  },
  "project_number": {
    "display_name": "Project ID",
    "value": "14"
  },
}
```

```
"project_manager": {
  "display_name": "Project Manager",
  "value": "LN_Roles_for_IT, FN_pm_globalrole_1_1"
},
"classification_descriptor": {
  "process": {
    "display_name": "Process Area",
    "value": ""
  },
  "priority": {
    "display_name": "Risk",
    "value": ""
  },
  "functional_area": {
    "display_name": "Functional Area",
    "value": "Accounts Payable"
  },
  "project_source": {
    "display_name": "Project Source",
    "value": ""
  }
},
"methodology_descriptor": {
  "roadmap": {
    "display_name": "Roadmap",
    "value": "Development release I"
  },
  "project_type": {
    "display_name": "Project Type",
    "value": "IT"
  }
},
"status_descriptor": {
  "project_status": {
    "display_name": "Status",
    "value": "Active"
  },
  "percent_completion_type": {
    "display_name": "Percent Completion Type",
    "value": "Count-based (Completed vs. Total Count for Immediate
Children)"
  }
},
"finance_descriptor": {
  "fin_track_start_date": {
    "display_name": "Finance Tracking Start Date",
    "value": "2009/10/10"
  },
  "project_fin_lock_date": {
```

```
    "display_name": "Project Finance Lock Month (yyyy/mm/dd)",
    "value": "1761/01/01"
  },
  "is_fin_lock_global": {
    "display_name": "Use Global Lock Month",
    "value": "Yes"
  },
  "initial_forecast_nonrollup": {
    "display_name": "Initial Forecast Soft Dollar",
    "value": "$0.00"
  },
  "initial_forecast_savings": {
    "display_name": "Initial Forecast Benefits",
    "value": "$0.00"
  },
  "initial_forecast_total": {
    "display_name": "Initial Forecast Total",
    "value": "$0.00"
  },
  "fintemplateid": {
    "display_name": "Finance Template",
    "value": "Default Global Finance Template"
  },
  "initial_forecast_group4": {
    "display_name": "Initial Forecast Group4",
    "value": "$0.00"
  },
  "financials_unlocked": {
    "display_name": "Finances Locked Globally",
    "value": "No"
  },
  "resource_computation_enabled": {
    "display_name": "Resource Computation Enabled",
    "value": "No"
  },
  "initial_forecast_cost": {
    "display_name": "Initial Forecast Cost",
    "value": "$0.00"
  },
  "finance_lock_enforcement": {
    "display_name": "Finance Lock/Close Period Enforcement",
    "value": ""
  },
  "is_capitalized": {
    "display_name": "Is Capitalized",
    "value": "Unspecified"
  },
  "consider_for_finances": {
    "display_name": "Include in Financial Calculations",
```

```
        "value": "Yes"
      },
      "fin_edit_mode": {
        "display_name": "Finance Edit Mode",
        "value": "Monthly"
      },
      "currency_code": {
        "display_name": "Currency",
        "value": "US Dollar"
      }
    },
    "pcs": {
      "display_name": "Initiative",
      "value": "IT"
    },
    "emailnotification_flag": {
      "display_name": "Send Email Notifications",
      "value": "No"
    },
    "team_member_descriptors": {"team_member_descriptor": [
      {
        "role": {
          "display_name": "Project Manager",
          "value": "pm_globalrole"
        },
        "resource_descriptor": {
          "login_id": "JJones",
          "first_name": "Janet",
          "email": "Janet.Jones@example.com",
          "last_name": "Jones",
          "userid": "JWS2WTH7X6WKT"
        },
        "teammember_id": "1"
      },
      {
        "role": {
          "display_name": "DBA",
          "value": "Id_018IT_DBA_"
        },
        "resource_descriptor": {
          "login_id": "jdoe",
          "first_name": "Jane",
          "email": "jane.doe@example.com ",
          "last_name": "Doe",
          "userid": "JWS2VXH2GMS5M"
        }
      }
    ]}
  ]}]}
```

Search_template Function

The search_template function allows you to retrieve a template for searching a project. This can be used to define data for searching a project in EnterpriseTrack.

Alternatively, you can also download a template from the EnterpriseTrack Administration module. For more details, see **Downloading CRUD Templates** (on page 262).

In This Section

Invocation Syntax.....	159
Invocation Parameters.....	159
Input Parameters.....	160
Input Examples	161
Output Examples.....	162

Invocation Syntax

The syntax for the invocation of the search_template function is as follows:

```
<api_session>?&request_data=<request_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, project_search_template.xml and project_search.json. Then the syntax for the search template function is as follows:

```
<api_session>?&request_data=<tags specified in
project_search_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<tags specified in
project_search_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the search_template function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or constant	Description
<i>Request_data</i>	String	<i><input_data></i>	Specifies the input data for generating a search request. For more details, see Input Parameters.
<i>Request_format</i>	String	<i><request_format></i>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> lists the global settings for your EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See <i>Request Data Table</i> below for more details.
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the search_template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request Data Table				
Request_type	String	Yes	search_template	The name of the function.
Entity_type	String	Yes	project	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML

Name	Data Type	Value Required?	Placeholder or Constant	Description
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data for the search_template function in XML and JSON formats.

Input Example in XML Format

The following is an example of input data of search_template function in XML format.

```
<root>
  <global_properties>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
  </global_properties>
  <request_data>
    <request_type>search_template</request_type>
    <initiative>IT</initiative>
    <entity_type>project</entity_type>
    <output_format>xml</output_format>
  </request_data>
</root>
```

Input Example in JSON Format

The following is an example of input data of search_template function in JSON format.

```
{
  "global_properties": {
    "date_format": "yyyy/mm/dd",
    "language": "en",
  },
  "request_data": {
    "request_type": "search_template",
    "entity_type": "project",
    "initiative": "IT",
    "output_format": "json",
  }
}
```

Output Examples

The following section provides examples of output from the `search_template` function in XML and JSON formats.

Output Example in XML Format

The following is an example of the output generated from the `search_template` api in XML format based on your account configuration:

```
<root> <global_properties> <char_set>ISO-8859-1</char_set>
  <date_format>yyyy/MM/dd</date_format>
  <language>en</language>
  <api_version>9.0</api_version>
</global_properties> <request_data>
<request_type>search</request_type>
  <entity_type>project</entity_type>
  <output_format>xml</output_format>
  <value_delimiter>|</value_delimiter>
</request_data> <app_data> <project> <project_number>
  <display_name>Project ID</display_name>
  <value/>
</project_number>
  <project_name>
  <display_name>Project Name</display_name>
  <value/>
</project_name>
  <status_descriptor> <project_status>
    <display_name>Status</display_name>
    <value/>
  </project_status>
</status_descriptor> <project_start_date_from>
  <display_name>Project Start Date From </display_name>
  <value/>
</project_start_date_from>
  <project_start_date_to>
    <display_name>Project Start Date To</display_name>
```

```
    <value/>
  </project_start_date_to>
  <planned_realization_date_from>
    <display_name>Project Planned Realization Date
From</display_name>
    <value/>
  </planned_realization_date_from>
  <planned_realization_date_to>
    <display_name>Project Planned Realization Date To</display_name>
    <value/>
  </planned_realization_date_to>
  <Project_manager> <pm_user_id>
    <display_name>User ID</display_name>
    <value/>
  </pm_user_id>
  <pm_login_id>
    <display_name>Login ID</display_name>
    <value/>
  </pm_login_id>
  <pm_email>
    <display_name>EMail</display_name>
    <value/>
  </pm_email>
  <pm_first_name>
    <display_name>First Name</display_name>
    <value/>
  </pm_first_name>
  <pm_last_name>
    <display_name>Last Name</display_name>
    <value/>
  </pm_last_name>
</Project_manager> </project> </app_data> </root>
```

Output Example in JSON Format

The following is an example of the template generated from the `search_template` function in JSON format based on your account configuration:

```
"root":{
  "global_properties": {
    "char_set": "ISO-8859-1"
    "date_format": "yyyy/mm/dd"
    "language": "en"
    "api_version": "9.0"
  }
  "request_data" {
    "request_type": "search"
    "entity_type": "project"
    "output_format": "xml"
    "value_delimiter":""
  }
  "app_data": {
    "project": {
      "project_number": {
        "display_name": "Project ID"
        "value": ""
      }
      "project_name": {
        "display_name": "Project Name"
        "value": ""
      }
      "status_descriptor": {
        "project_status": {
          "display_name": "Status"
          "value": ""
        }
      }
    }
    "project_start_date_from": {
      "display_name": "Project Start Date From"
```

```
    "value": ""
  }
  "project_start_date_to": {
    "display_name": "Project Start_Date To"
    "value": ""
  }
  "planned_realization_date_from": {
    "display_name": "Project Planned Realization Date From"
    "value": ""
  }
  "planned_realization_date_to": {
    "display_name": "Project Planned Realization Date To"
    "value": ""
  }
  "Project_manager": {
    "pm_user_id": {
      "display_name": "User ID"
      "value": ""
    }
    "pm_login_id": {
      "display_name": "Login ID"
      "value": ""
    }
    "pm_email": {
      "display_name": "Email"
      "value": ""
    }
    "pm_first_name": {
      "display_name": "First Name"
      "value": ""
    }
    "pm_last_name": {
      "display_name": "Last Name"
      "value": ""
    }
  }
}
```

```
    }  
  }  
}  
}
```

Project Finance CRUD APIs

In This Section

Finance	167
Finance Structure	193
Finance Snapshot	210

Finance

This object contains current finance data for a given project. Finance data can be aggregate or monthly or yearly, based on finance template.

EnterpriseTrack allows the use of multiple, customized project finance templates which can vary in the number of groups, categories and elements they contain. The finance APIs are equally flexible to account for these customized project finance templates.

In This Section

Search Function	167
Update Function	185

Search Function

The search function allows you to search finance data for a project in EnterpriseTrack.

In This Section

Invocation Syntax	167
Invocation Parameters	168
Input Parameters	168
Input Examples	169
Output Examples	173

Invocation Syntax

The syntax for the invocation of the search function is as follows.

```
<api_session>?&request_data=<request_data>&request_format  
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, `project15_search.xml` and `project15_search.json`. Then the syntax for the search function is as follows:

```
<api_session>?&request_data=<content specified in  
project15_API_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<content specified in  
project15_API_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the search function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or constant	Description
<i>Request_data</i>	String	<code><input_data></code>	Specifies the input data for searching a project. For more details, see Input Parameters.
<i>Request_format</i>	String	<code><request_format></code>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> lists the global settings for your EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See <i>Request_Data Table</i> below for more details.

Name	Data Type	Value Required?	Placeholder or Constant	Description
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the search template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	search	The name of the function.
Entity_type	String	Yes	project_finance	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data specified for the Search function in XML and JSON formats.

Input Example in XML Format

The following is an example of input data for the search function in XML format.

```
<?xml version="1.0" encoding="utf-8"?>
<root>
```

```
<global_properties>
  <char_set>UTF-8</char_set>
  <date_format>yyyy/MM/dd</date_format>
  <language>en</language>
  <api_version>9.0</api_version>
</global_properties>
<request_data>
  <request_type>search</request_type>
  <entity_type>project_finance</entity_type>
  <output_format>xml</output_format>
  <value_delimiter>|</value_delimiter>
</request_data>
<app_data>
  <project_finance>
    <project_number>
      <display_name>Project ID</display_name>
      <value>10001</value>
    </project_number>
    <project_name>
      <display_name>Project Name</display_name>
      <value />
    </project_name>
    <finance_descriptor>
      <fin_search_mode>
        <display_name> Finance data search mode ( M for Monthly / Y for Yearly / A for
Aggregate) </display_name>
        <value>M</value>
      </fin_search_mode>
      <!-- Fill in monthly_search section , if finance_search_mode = M -->
      <monthly_search>
        <from_month>
          <display_name> From Month (yyyy/mm format). Keep empty to have start month as
fin track start month</display_name>
          <value />
        </from_month>
        <to_month>
          <display_name> To Month (yyyy/mm format). Keep empty if you do not know finance
data end month </display_name>
          <value />
        </to_month>
      </monthly_search>
      <!-- Fill in yearly_search section , if finance_search_mode = Y -->
```

```
<yearly_search>
  <from_year>
    <display_name> From year (yyyy format). Keep empty for fin track start
year</display_name>
    <value />
  </from_year>
  <to_year>
    <display_name> To year (yyyy format). Keep empty if you do not know finance
data end year </display_name>
    <value />
  </to_year>
</yearly_search>
<search_group>
  <group>
    <display_name>Group Name. Set to *, if you need all groups data</display_name>
    <value>*</value>
  </group>
  <search_category>
    <category>
      <display_name> Category Name. Use *. if you need all categories for a given
group.</display_name>
      <value>*</value>
    </category>
  <search_element>
    <element>
      <display_name> Element Name. Use *. if you need all element for selected
group and category. </display_name>
      <value>*</value>
    </element>
  </search_element>
</search_category>
</search_group>
</finance_descriptor>
</project_finance>
</app_data>
</root>
```

Input Example in JSON Format

The following is an example of input data for the search function in JSON format.

```
{
  "global_properties": {
    "char_set": "UTF-8",
    "date_format": "MMM/dd/yyyy",
```

```
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "search",
    "entity_type": "project_finance",
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project_finance": [{
      "project_number": {
        "display_name": "Project ID",
        "value": "10105"
      },
      "project_name": {
        "display_name": "Project Name",
        "value": ""
      },
      "finance_descriptor": {
        "fin_search_mode": {
          "display_name": "Finance Search Mode",
          "value": "A"
        },
        "monthly_search": {
          "from_month": {
            "display_name": "From (Start) Month for Searching.
Applicable only if fin_search_mode = M. (YYYY/MM Format)",
            "value": ""
          },
          "to_month": {
            "display_name": "To (End) Month for Searching.
Applicable only if fin_search_mode = M. (YYYY/MM Format)",
            "value": ""
          }
        },
        "yearly_search": {
          "from_year": {
            "display_name": "From (Start) Year for Searching.
Applicable only if fin_search_mode = Y. (YYYY Format)",
            "value": "2012"
          }
        }
      }
    }
  ]
}
```

```
        "to_year": {
            "display_name": "To (End) Year for Searching.
Applicable only if fin_search_mode = Y. (YYYY Format)",
            "value": "2013"
        },
    },
    "search_group": {
        "group": {
            "display_name": "Group Name. Set to *, if you need all
groups data",
            "value": "*"
        },
        "search_category": {
            "category": {
                "display_name": "Category Name. Use *. if you
need all categories for a given group.",
                "value": "*"
            },
            "search_element": {
                "element": {
                    "display_name": "Element Name. Use *. if
you need all element for selected group and category.",
                    "value": "*"
                }
            }
        }
    }
}

}]
}
```

Output Examples

The following section provides examples of output generated by the Search function in XML and JSON formats.

Output Example in XML Format

The following example retrieves a project finances in XML format.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
```

```
<char_set>UTF-8</char_set>
<date_format>yyyy/MM/dd</date_format>
<language>en</language>
<api_version>9.0</api_version>
</global_properties>
<response_data>
  <request_type>search</request_type>
  <entity_type>project_finance</entity_type>
  <response_code>0</response_code>
  <response_desc/>
</response_data>
<app_data>
  <project_finance>
    <project_number>
      <display_name>Project ID</display_name>
      <value>10001</value>
    </project_number>
    <project_name>
      <display_name>Project Name</display_name>

      <value>proj-10001-Roadmap_for_Corporate_and_Accts_Payable_SS_DMAICCAAPSS-define_six_sigma_
phase-Active-team1-2012-Type_PT_Project_Type_Using_CAAP_Roadmap</value>
    </project_name>
    <finance_descriptor>
      <finance_template>
        <display_name>finance_template</display_name>
        <value>Default Global Finance Template</value>
      </finance_template>
      <finance_template_version>
        <display_name>finance_template_version</display_name>
        <value>testdata_defaultGlobalFinTemplateVersionID</value>
      </finance_template_version>
      <fin_edit_mode>
        <display_name>Finance Edit Mode</display_name>
        <value>M</value>
      </fin_edit_mode>
      <finance_data>
        <data_monthly>
          <data_201201>
            <total>
              <display_name>Total</display_name>
              <value>962879.9</value>
            </total>
          </data_201201>
        </data_monthly>
      </finance_data>
    </project_finance>
  </app_data>
</response_data>
```

```

</total>
<savings>
  <display_name>Benefits</display_name>
  <value>489871.9</value>
  <s_cat1>
    <display_name>Category
1</display_name>
    <value>89871.9</value>
    <s_cat1_elem1>
      <display_name>Element
1</display_name>
      <value>2000.50</value>
    </s_cat1_elem1>
    <s_cat1_elem2>
      <display_name>Element
2</display_name>
    <no_of_elements>10</no_of_elements>
    <value>1203.4</value>
  </s_cat1_elem2>
  <s_cat1_elem3>
    <display_name>Element
3</display_name>
    <no_of_elements/>
    <value>6666.0</value>
  </s_cat1_elem3>
  <s_cat1_elem4>
    <display_name>Element
4</display_name>
    <no_of_elements/>
    <value>6666.0</value>
  </s_cat1_elem4>
  <s_cat1_elem5>
    <display_name>Element
5</display_name>
    <value>6666.0</value>
  </s_cat1_elem5>
</s_cat1>
<s_cat2>
  <display_name>Category
2</display_name>
  <value>100000</value>
  <s_cat2_elem1>

```

```

1</display_name>
<value>6666.0</value>
</s_cat2_elem1>
<s_cat2_elem2>
<display_name>Element
2</display_name>
<value>6666.0</value>
</s_cat2_elem2>
<s_cat2_elem3>
<display_name>Element
3</display_name>
<value>6666.0</value>
</s_cat2_elem3>
<s_cat2_elem4>
<display_name>Element
4</display_name>
<value>6666.0</value>
</s_cat2_elem4>
<s_cat2_elem5>
<display_name>Element
5</display_name>
<value>6666.0</value>
</s_cat2_elem5>
</s_cat2>
</savings>
<expenses>
<display_name>Cost</display_name>
<value>426992</value>
<e_cat1>
<display_name>Team Finance
Category</display_name>
<value>106992</value>
<e_cat1_elem1>
<display_name>Team
Standard Effort</display_name>
<no_of_elements>3232.50</no_of_elements>
<value>32325</value>
</e_cat1_elem1>
<e_cat1_elem2>
<display_name>Team
Overtime Effort</display_name>

```

```

        <no_of_elements/>
        <value>5333.0</value>
    </e_cat1_elem2>
    <e_cat1_elem3>

    <display_name>Timesheet Standard Effort</display_name>

        <no_of_elements/>
        <value>5333.0</value>
    </e_cat1_elem3>
    <e_cat1_elem4>

    <display_name>Timesheet Overtime Effort</display_name>

        <no_of_elements/>
        <value>5333.0</value>
    </e_cat1_elem4>
</e_cat1>
<e_cat2>
    <display_name>Activity
Non-Resource Finance Category</display_name>

    <value>80000</value>
    <e_cat2_elem1>

    <display_name>Fixed</display_name>

        <value>5333.0</value>
    </e_cat2_elem1>
    <e_cat2_elem2>

    <display_name>Material</display_name>

        <value>5333.0</value>
    </e_cat2_elem2>
    <e_cat2_elem3>

    <display_name>Other</display_name>

        <value>5333.0</value>
    </e_cat2_elem3>
</e_cat2>
<...>
</data_201212>
        </data_monthly>
    </finance_data>
</finance_descriptor>
</project_finance>
</app_data>

```

```
</root>
```

Output Example in JSON Format

The following example retrieves a project finances in JSON format.

```
{
  "global_properties": {
    "date_format": "MMM/dd/yyyy",
    "language": "en",
    "api_version": "9.0",
    "char_set": "UTF-8"
  },
  "response_data": {
    "response_desc": "",
    "request_type": "search",
    "response_code": "0",
    "entity_type": "project_finance"
  },
  "app_data": {"project_finance": [{
    "project_name": {
      "display_name": "Project Name",
      "value":
"proj-10105-Roadmap_for_Corporate_and_Accts_Payable_SS_DMAICCAAPSS-realization_six_sigma_phase-Realization-team1-2014-Type_PT_Project_Type_Using_CAAP_Roadmap"
    },
    "finance_descriptor": {
      "finance_template_version": {
        "display_name": "finance_template_version",
        "value": "testdata_defaultGlobalFinTemplateVersionID"
      },
      "finance_data": {"data_aggregate": {
        "total_id": "total",
        "value": "11750629.50",
        "group4": {
          "display_name": "Group4",
          "value": "4800000.00",
          "g4_cat1": {
            "display_name": "Category 1",
            "value": "960000.00",
            "g4_cat1_elem5": {
              "display_name": "Element 5",
              "value": "63996.00"
            }
          }
        }
      }
    }
  ]}
```

```
    },
    "g4_cat1_elem3": {
      "display_name": "Element 3",
      "value": "63996.00"
    },
    "g4_cat1_elem4": {
      "display_name": "Element 4",
      "value": "63996.00"
    },
    "g4_cat1_elem1": {
      "display_name": "Element 1",
      "value": "63996.00"
    },
    "g4_cat1_elem2": {
      "display_name": "Element 2",
      "value": "63996.00"
    }
  },
  "g4_cat2": {
    "g4_cat2_elem1": {
      "display_name": "Element 1",
      "value": "63996.00"
    },
    "display_name": "Category 2",
    "g4_cat2_elem2": {
      "display_name": "Element 2",
      "value": "63996.00"
    },
    "g4_cat2_elem3": {
      "display_name": "Element 3",
      "value": "63996.00"
    },
    "g4_cat2_elem4": {
      "display_name": "Element 4",
      "value": "63996.00"
    },
    "g4_cat2_elem5": {
      "display_name": "Element 5",
      "value": "63996.00"
    },
    "value": "960000.00"
  }
}
```

```
},
"nonrollup": {
  "display_name": "Soft Dollar",
  "value": "2400000.00",
  "p_cat2": {
    "p_cat2_elem1": {
      "display_name": "Element 1",
      "value": "31992.00"
    },
    "p_cat2_elem2": {
      "display_name": "Element 2",
      "value": "31992.00"
    },
    "display_name": "Category 2",
    "value": "480000.00",
    "p_cat2_elem5": {
      "display_name": "Element 5",
      "value": "31992.00"
    },
    "p_cat2_elem4": {
      "display_name": "Element 4",
      "value": "31992.00"
    },
    "p_cat2_elem3": {
      "display_name": "Element 3",
      "value": "31992.00"
    }
  },
  "p_cat1": {
    "display_name": "Category 1",
    "p_cat1_elem5": {
      "display_name": "Element 5",
      "value": "31992.00"
    },
    "p_cat1_elem4": {
      "display_name": "Element 4",
      "value": "31992.00"
    },
    "value": "480000.00",
    "p_cat1_elem1": {
      "display_name": "Element 1",
      "value": "31992.00"
    }
  }
}
```

```
    },
    "p_cat1_elem2": {
      "display_name": "Element 2",
      "value": "31992.00"
    },
    "p_cat1_elem3": {
      "display_name": "Element 3",
      "value": "31992.00"
    }
  }
},
"savings": {
  "display_name": "Benefits",
  "s_cat1": {
    "display_name": "Category 1",
    "value": "1040016.00",
    "s_cat1_elem1": {
      "display_name": "Element 1",
      "value": "0.00"
    },
    "s_cat1_elem2": {
      "display_name": "Element 2",
      "value": "0.00"
    },
    "s_cat1_elem3": {
      "display_name": "Element 3",
      "value": "79992.00"
    },
    "s_cat1_elem4": {
      "display_name": "Element 4",
      "value": "79992.00"
    },
    "s_cat1_elem5": {
      "display_name": "Element 5",
      "value": "79992.00"
    }
  },
  "s_cat2": {
    "display_name": "Category 2",
    "s_cat2_elem3": {
      "display_name": "Element 3",
      "value": "79992.00"
    }
  }
}
```

```
    },
    "value": "1046617.50",
    "s_cat2_elem2": {
      "display_name": "Element 2",
      "value": "600.00"
    },
    "s_cat2_elem5": {
      "display_name": "Element 5",
      "value": "79992.00"
    },
    "s_cat2_elem4": {
      "display_name": "Element 4",
      "value": "79992.00"
    },
    "s_cat2_elem1": {
      "display_name": "Element 1",
      "value": "6001.50"
    }
  },
  "value": "5686633.50"
},
"total_display_name": "Total",
"expenses": {
  "e_cat1": {
    "display_name": "Category 1",
    "e_cat1_elem1": {
      "display_name": "Team Standard Effort",
      "value": "0.00",
      "number_of_units": ""
    },
    "e_cat1_elem2": {
      "display_name": "Team Overtime Effort",
      "value": "63996.00",
      "number_of_units": ""
    },
    "e_cat1_elem3": {
      "display_name": "Timesheet Standard Effort",
      "value": "63996.00",
      "number_of_units": ""
    },
    "e_cat1_elem4": {
      "display_name": "Timesheet Overtime Effort",
```

```
        "value": "63996.00",
        "number_of_units": ""
    },
    "value": "896004.00"
},
"display_name": "Cost",
"e_cat3": {
    "display_name": "Res Based Different Config",
    "value": "960000.00",
    "e_cat3_elem1": {
        "display_name": "Team Standard Effort",
        "value": "192000.00",
        "number_of_units": ""
    },
    "e_cat3_elem2": {
        "display_name": "Team Overtime Effort",
        "value": "192000.00",
        "number_of_units": ""
    },
    "e_cat3_elem3": {
        "display_name": "Timesheet Standard Effort",
        "value": "192000.00",
        "number_of_units": ""
    },
    "e_cat3_elem4": {
        "display_name": "Timesheet Overtime Effort",
        "value": "192000.00",
        "number_of_units": ""
    }
},
"e_cat2": {
    "display_name": "Activity Non Res Different Config",
    "e_cat2_elem4": {
        "display_name": "Material",
        "value": "63996.00"
    },
    "value": "960000.00",
    "e_cat2_elem5": {
        "display_name": "Other Misc",
        "value": "63996.00"
    },
    "e_cat2_elem1": {
```

```
        "display_name": "Currency Element",
        "value": "63996.00"
    },
    "e_cat2_elem2": {
        "display_name": "Std Effort",
        "value": "63996.00",
        "number_of_units": ""
    },
    "e_cat2_elem3": {
        "display_name": "Dummy Fixed",
        "value": "63996.00"
    }
},
"value": "4736004.00",
"e_cat4": {
    "display_name": "Category 4",
    "value": "960000.00",
    "e_cat4_elem4": {
        "display_name": "Element4",
        "value": "192000.00"
    },
    "e_cat4_elem3": {
        "display_name": "Element3",
        "value": "192000.00"
    },
    "e_cat4_elem2": {
        "display_name": "Actual Overtime Effort",
        "value": "192000.00",
        "number_of_units": ""
    },
    "e_cat4_elem1": {
        "display_name": "Actual Standard Effort",
        "value": "192000.00",
        "number_of_units": ""
    }
}
}},
"fin_edit_mode": {
    "display_name": "Finance Edit Mode",
    "value": "A"
},
```

```
    "finance_template": {
      "display_name": "finance_template",
      "value": "Test1: 36M Monthly"
    }
  },
  "project_number": {
    "display_name": "Project ID",
    "value": "10105"
  }
}]]}
}
```

Update Function

The update function allows you to update finance data any time for a project in EnterpriseTrack.

In This Section

Invocation Syntax.....	185
Invocation Parameters.....	185
Input Examples	187
Output Examples.....	192

Invocation Syntax

The syntax for the invocation of the Update function is:

```
<api_session>?&request_data=<request_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, project15_update.xml and project15_update.json. Then the syntax for the update function is:

```
<api_session>?&request_data=<content of
project15_API_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<content of
project15_API_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the update function are described in the following table. Unless otherwise specified, all values are not case-sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
<i>Request_data</i>	String	Yes	<i><input_data></i>	Specifies the input parameters for the request in the format specified in the <i>request_format</i> parameter. For more details, see the <i>Input Parameters</i> .
<i>Request_format</i>	String	Yes	<i><request_format></i>	The data format of the request. Supported formats include: ▶ JSON ▶ XML
<i>global_properties</i>	Object	Yes	Not applicable	This object lists the global settings for the EnterpriseTrack instance.
<i>request_data</i>	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See "Request_Data Table" below for more details.
<i>application_data</i>	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate, it is recommended that you download the update template from your EnterpriseTrack Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
<i>Request_type</i>	String	Yes	<i>update</i>	The name of the function.
<i>Entity_type</i>	String	Yes	<i>project_finance</i>	The entity on which the operation is being performed.

Name	Data Type	Value Required?	Placeholder or constant	Description
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data for the Update function in XML and JSON formats.

Input Example in XML Format

The following is an example of the input data for the update function in XML format.

Note: After downloading the template for finance, you must copy the structure based on the project finance edit mode.

- If the project finance edit mode is Aggregate, copy the whole structure once under the <data_aggregate> tag.
- If the project finance edit mode is Monthly, copy and repeat the whole structure for each month in the <data_YYYYMM> tag. The value for MM (months) will depend on the project dates and the month for which data is being updated.
- If the project finance edit mode is Yearly, copy and repeat the whole structure for each year in the <data_YYYY> tag. The value for YYYY (years) will depend on the project dates and the year for which data is being updated.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <request_data>
```

```
<request_type>update</request_type>
<entity_type>project_finance</entity_type>
<output_format>xml</output_format>
<value_delimiter>|</value_delimiter>
</request_data>
<app_data>
  <project_finance>
    <project_number>
      <display_name>Project ID</display_name>
      <value>10002</value>
    </project_number>
    <project_name>
      <display_name>Project Name</display_name>
      <value/>
    </project_name>
    <finance_descriptor>
      <fin_edit_mode>
        <display_name> Finance data search mode ( M for Monthly / Y for
Yearly / A for Aggregate) </display_name>
        <value>M</value>
      </fin_edit_mode>
    </finance_descriptor>
    <finance_data>
      <data_201201>
        <Benefits>
          <display_name>Benefits</display_name>
          <s_cat1>
            <display_name>Category 1</display_name>
            <s_cat1_elem1>
              <display_name>Element 1
</display_name>
              <value>2000.50</value>
            </s_cat1_elem1>
            <s_cat1_elem2>
              <display_name> Element 2
</display_name>
              <number_of_units>10</number_of_units>
            </s_cat1_elem2>
          </s_cat1>
        </Benefits>
        <expenses>
          <display_name> Cost </display_name>
```

```

        <e_cat1>
            <display_name>Team Finance Category
</display_name>

            <value/>
            <e_cat1_elem1>
                <display_name>Team Standard
Effort</display_name>

                <number_of_units>10</number_of_units>
            </e_cat1_elem1>
        </e_cat1>
    </expenses>
</data_201201>
<data_201202>
    <Benefits>
        <display_name>Benefits</display_name>
        <s_cat1>
            <display_name>Category 1 </display_name>
            <s_cat1_elem1>
                <display_name>Element 1
</display_name>

                <value>2000.50</value>
            </s_cat1_elem1>
            <s_cat1_elem2>
                <display_name>Element 2
</display_name>

                <number_of_units>50</number_of_units>
            </s_cat1_elem2>
        </s_cat1>
    </Benefits>
    <expenses>
        <display_name> Cost </display_name>
        <e_cat1>
            <display_name>Team Finance Category
</display_name>

            <value/>
            <e_cat1_elem1>
                <display_name>Team Standard
Effort</display_name>

                <number_of_units>90</number_of_units>
            </e_cat1_elem1>
        </e_cat1>
    </expenses>
</data_201202>

```

```
        </finance_data>
    </project_finance>
</app_data>
</root>
```

Input Example in JSON Format

The following is an example of the input data for the update function in JSON format.

Note: After downloading the template for finance, you must copy the structure based on the project finance edit mode.

- If the project finance edit mode is Aggregate, copy the whole structure once under the <data_aggregate> tag.
 - If the project finance edit mode is Monthly, copy and repeat the whole structure for each month in the <data_YYYYMM> tag. The value for MM (months) will depend on the project dates and the month for which data is being updated.
 - If the project finance edit mode is Yearly, copy and repeat the whole structure for each year in the <data_YYYY> tag. The value for YYYY (years) will depend on the project dates and the year for which data is being updated.
-

```
{
  "global_properties": {
    "char_set": "UTF-8",
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "update",
    "entity_type": "project_finance",
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project_finance": [{
      "project_number": {
        "display_name": "Project ID",
        "value": "10101"
      },
      "project_name": { "display_name": "Project Name" },
      "finance_descriptor": {
        "fin_edit_mode": {
```

```
        "display_name": " Finance data search mode ( M for Monthly / Y for Yearly / A for
Aggregate) ",
        "value": "M"
    }
},
"finance_data": {
    "data_201401": {
        "savings": {
            "display_name": "Benefits",
            "s_cat1": {
                "display_name": "Category 1 ",
                "s_cat1_elem1": {
                    "display_name": "Element 1 ",
                    "value": "2000.50"
                },
                "s_cat1_elem2": {
                    "display_name": "Element 2",
                    "value": "10"
                }
            }
        }
    },
    "expenses": {
        "display_name": " Cost ",
        "e_cat1": {
            "display_name": "Category 1 ",
            "e_cat1_elem1": {
                "display_name": "Team Standard Effort ",
                "number_of_units": "3232.50"
            }
        }
    }
},
"data_201402": {
    "savings": {
        "display_name": "Benefits",
        "s_cat1": {
            "display_name": "Category 1 ",
            "s_cat1_elem1": {
                "display_name": "Element 1 ",
                "value": "2000.50"
            },
            "s_cat1_elem2": {
```

```
        "display_name": "Element 2 ",
        "value": "10"
    }
}
},
"expenses": {
    "display_name": " Cost ",
    "e_cat1": {
        "display_name": "Category 1 ",
        "e_cat1_elem1": {
            "display_name": "Team Standard Effort ",
            "number_of_units": "3232.50"
        }
    }
}
}
}
}
}
}
}
```

Output Examples

The following section provides examples of the update function in XML and JSON formats.

Output Example in XML Format

The following is an example of the response from the update function for updating finance data for a project in XML format.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <response_data>
    <request_type>update</request_type>
    <entity_type>project_finance</entity_type>
    <response_code>0</response_code>
    <response_desc/>
  </response_data>
```

```
<app_data/>
</root>
```

Output Example in JSON Format

The following is an example of the response from the Update function for updating finance data for a project in JSON format.

```
{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0",
    "char_set": "UTF-8"
  },
  "response_data": {
    "response_desc": "",
    "request_type": "update",
    "response_code": "0",
    "entity_type": "project_finance"
  },
  "app_data": {"": []}
}
```

Finance Structure

This object defines all attributes of each finance element, finance category, and finance group enabled for a given project.

In This Section

Search Function 193

Search Function

The search function allows you to retrieve the finance structure for a project in EnterpriseTrack.

In This Section

Invocation Syntax 194
Invocation Parameters..... 194
Input Parameters..... 194
Input Examples 195
Output Examples..... 197

Invocation Syntax

The syntax for the invocation of the search function is as follows.

```
<api_session>?&request_data=<request_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, project15_search.xml and project15_search.json. Then the syntax for the search function is as follows:

```
<api_session>?&request_data=<content specified in
project15_API_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<content specified in
project15_API_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the search function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or constant	Description
<i>Request_data</i>	String	<i><input_data></i>	Specifies the input data for searching a project. For more details, see Input Parameters.
<i>Request_format</i>	String	<i><request_format></i>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> lists the global settings for your EnterpriseTrack instance.

Name	Data Type	Value Required?	Placeholder or Constant	Description
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See <i>Request Data Table</i> below for more details.
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the search template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request Data Table				
Request_type	String	Yes	search	The name of the function.
Entity_type	String	Yes	project_finance_structure	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data specified for the Search function in XML and JSON formats.

Input Example in XML Format

The following is an example of input data for the search function in XML format.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <request_data>
    <request_type>search</request_type>
    <entity_type>project_finance_structure</entity_type>
    <output_format>xml</output_format>
    <value_delimiter>|</value_delimiter>
  </request_data>
  <app_data>
    <project_finance_structure>
      <project_number>
        <display_name>project_number</display_name>
        <value>11</value>
      </project_number>
      <project_name>
        <display_name>project_name</display_name>
        <value>Consumer Banking on mobile</value>
      </project_name>
      <finance_descriptor/>
    </project_finance_structure>
  </app_data>
</root>
```

Input Example in JSON Format

The following is an example of input data for the search function in JSON format.

```
{
  "global_properties": {
    "char_set": "UTF-8",
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "search",
    "entity_type": "project_finance_structure",
```

```
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project": [
      {
        "project_number": {
          "display_name": "Project ID",
          "value": "19"
        },
        "project_name": {
          "display_name": "Project Name",
          "value": "Analytics for commercial banking with B0"
        }
      }
    ]
  }
}
```

Output Examples

The following section provides examples of output generated by the Search function in XML and JSON formats.

Output Example in XML Format

The following example retrieves a project finance structure.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <response_data>
    <request_type>search</request_type>
    <entity_type>project_finance_structure</entity_type>
    <response_code>0</response_code>
    <response_desc/>
  </response_data>
  <app_data>
    <project_finance_structure>
```

```
<project_number>
  <display_name>Project ID</display_name>
  <value>11</value>
</project_number>
<project_name>
  <display_name>Project Name</display_name>
  <value>Consumer Banking on mobile</value>
</project_name>
<finance_descriptor>
  <fintemplate_id>
    <display_name>Finance Template</display_name>
    <value>Default Global Finance Template</value>
  </fintemplate_id>
  <fintemplate_version_id>
    <display_name>Finance Template Version</display_name>
    <value>testdata_defaultGlobalFinTemplateVersionID</value>
  </fintemplate_version_id>
  <fin_edit_mode>
    <display_name>Finance Edit Mode</display_name>
    <value>M</value>
  </fin_edit_mode>
  <finance_structure>
    <total>
      <display_name>FIX_ME</display_name>
    </total>
    <savings>
      <display_name>Benefits</display_name>
      <category_type>Currency</category_type>
      <mf_type>Static</mf_type>
      <mf_value>1</mf_value>
      <s_cat1>
        <display_name>Category 1</display_name>
        <category_type>Generic Finance
Category</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
        <s_cat1_elem1>
          <display_name>Element 1</display_name>

          <category_type>Currency</category_type>

          <mf_type>Static</mf_type>
          <mf_value>1</mf_value>
```

```

</s_cat1_elem1>
<s_cat1_elem2>
    <display_name>Element 2</display_name>

<category_type>Kilowatts</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</s_cat1_elem2>
<s_cat1_elem3>
    <display_name>Element 3</display_name>
    <category_type>Man

Hours</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</s_cat1_elem3>
<s_cat1_elem4>
    <display_name>Element 4</display_name>
    <category_type>Meters</category_type>
    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</s_cat1_elem4>
<s_cat1_elem5>
    <display_name>Element 5</display_name>

<category_type>Currency</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</s_cat1_elem5>
</s_cat1>
<s_cat2>
    <display_name>Category 2</display_name>
    <category_type>Generic Finance

Category</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
<s_cat2_elem1>
    <display_name>Element 1</display_name>

<category_type>Currency</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</s_cat2_elem1>
<s_cat2_elem2>

```

```

                                <display_name>Element 2</display_name>

<category_type>Currency</category_type>

                                <mf_type>Static</mf_type>
                                <mf_value>1</mf_value>
                                </s_cat2_elem2>
                                <s_cat2_elem3>
                                    <display_name>Element 3</display_name>

<category_type>Currency</category_type>

                                <mf_type>Static</mf_type>
                                <mf_value>1</mf_value>
                                </s_cat2_elem3>
                                <s_cat2_elem4>
                                    <display_name>Element 4</display_name>

<category_type>Currency</category_type>

                                <mf_type>Static</mf_type>
                                <mf_value>1</mf_value>
                                </s_cat2_elem4>
                                <s_cat2_elem5>
                                    <display_name>Element 5</display_name>

<category_type>Currency</category_type>

                                <mf_type>Static</mf_type>
                                <mf_value>1</mf_value>
                                </s_cat2_elem5>
                                </s_cat2>
                                </savings>
                                <expenses>
                                    <display_name>Cost</display_name>
                                    <category_type>Currency</category_type>
                                    <mf_type>Static</mf_type>
                                    <mf_value>-1</mf_value>
                                    <e_cat1>
                                        <display_name>Team Finance

Category</display_name>

                                        <category_type>Team Based

Category</category_type>

                                        <mf_type>Static</mf_type>
                                        <mf_value>1</mf_value>
                                        <e_cat1_elem1>
                                            <display_name>Team Standard
```

Effort</display_name>	<category_type>Standard
Effort</category_type>	<mf_type>Static</mf_type> <mf_value>1</mf_value>
	</e_cat1_elem1> <e_cat1_elem2>
	<display_name>Team Overtime
Effort</display_name>	<category_type>Overtime
Effort</category_type>	<mf_type>Static</mf_type> <mf_value>1</mf_value>
	</e_cat1_elem2> <e_cat1_elem3>
	<display_name>Timesheet Standard
Effort</display_name>	<category_type>Timesheet Standard
Effort</category_type>	<mf_type>Static</mf_type> <mf_value>1</mf_value>
	</e_cat1_elem3> <e_cat1_elem4>
	<display_name>Timesheet Overtime
Effort</display_name>	<category_type>Timesheet Overtime
Effort</category_type>	<mf_type>Static</mf_type> <mf_value>1</mf_value>
	</e_cat1_elem4> </e_cat1> <e_cat2>
	<display_name>Activity Non-Resource Finance
Category</display_name>	<category_type>Non-Resource Activity based
Finance Category</category_type>	<mf_type>Static</mf_type> <mf_value>1</mf_value> <e_cat2_elem1>
	<display_name>Fixed</display_name>
<category_type>Currency</category_type>	<mf_type>Static</mf_type>

```

        <mf_value>1</mf_value>
    </e_cat2_elem1>
    <e_cat2_elem2>
        <display_name>Material</display_name>

<category_type>Currency</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
    </e_cat2_elem2>
    <e_cat2_elem3>
        <display_name>Other</display_name>

<category_type>Currency</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
    </e_cat2_elem3>
</e_cat2>
<e_cat3>
    <display_name>Activity Resource Finance

Category</display_name>

    <category_type>Resource Activity based Finance

Category</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
    <e_cat3_elem1>
        <display_name>Actual Standard

Effort</display_name>

        <category_type>Standard

Effort</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
    </e_cat3_elem1>
    <e_cat3_elem2>
        <display_name>Actual Overtime

Effort</display_name>

        <category_type>Overtime

Effort</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
    </e_cat3_elem2>
    <e_cat3_elem3>
        <display_name>Timesheet Standard

Effort</display_name>
```

```

Effort</category_type>
    <category_type>Timesheet Standard
    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
  </e_cat3_elem3>
  <e_cat3_elem4>
    <display_name>Timesheet Overtime
Effort</display_name>
    <category_type>Timesheet Overtime
Effort</category_type>
    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
  </e_cat3_elem4>
</e_cat3>
<e_cat4>
  <display_name>Capital Expense</display_name>
  <category_type>Capital Expense - Resource
Activity based Finance Category</category_type>
  <mf_type>Static</mf_type>
  <mf_value>1</mf_value>
  <e_cat4_elem1>
    <display_name>Actual Standard
Effort</display_name>
    <category_type>Standard
Effort</category_type>
    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
  </e_cat4_elem1>
  <e_cat4_elem2>
    <display_name>Actual Overtime
Effort</display_name>
    <category_type>Overtime
Effort</category_type>
    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
  </e_cat4_elem2>
  <e_cat4_elem3>
    <display_name>Timesheet Standard
Effort</display_name>
    <category_type>Timesheet Standard
Effort</category_type>
    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>

```

	</e_cat4_elem3>
	<e_cat4_elem4>
Effort</display_name>	<display_name>Timesheet Overtime
	<category_type>Timesheet Overtime
Effort</category_type>	
	<mf_type>Static</mf_type>
	<mf_value>1</mf_value>
	</e_cat4_elem4>
	</e_cat4>
	<e_cat5>
Expense</display_name>	<display_name>Operational
	<category_type>Operational Expense - Resource
Activity based Finance Category</category_type>	
	<mf_type>Static</mf_type>
	<mf_value>1</mf_value>
	<e_cat5_elem1>
Effort</display_name>	<display_name>Actual Standard
	<category_type>Standard
Effort</category_type>	
	<mf_type>Static</mf_type>
	<mf_value>1</mf_value>
	</e_cat5_elem1>
	<e_cat5_elem2>
Effort</display_name>	<display_name>Actual Overtime
	<category_type>Overtime
Effort</category_type>	
	<mf_type>Static</mf_type>
	<mf_value>1</mf_value>
	</e_cat5_elem2>
	<e_cat5_elem3>
Effort</display_name>	<display_name>Timesheet Standard
	<category_type>Timesheet Standard
Effort</category_type>	
	<mf_type>Static</mf_type>
	<mf_value>1</mf_value>
	</e_cat5_elem3>
	<e_cat5_elem4>
	<display_name>Timesheet Overtime

```

Effort</display_name>
<category_type>Timesheet Overtime
Effort</category_type>
<mf_type>Static</mf_type>
<mf_value>1</mf_value>
</e_cat5_elem4>
</e_cat5>
</expenses>
<nonrollup>
  <display_name>Soft Dollar</display_name>
  <category_type>Currency</category_type>
  <mf_type>Static</mf_type>
  <mf_value>0</mf_value>
  <p_cat1>
    <display_name>Category 1</display_name>
    <category_type>Generic Finance
Category</category_type>
    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
    <p_cat1_elem1>
      <display_name>Element 1</display_name>
      <category_type>Currency</category_type>
      <mf_type>Static</mf_type>
      <mf_value>1</mf_value>
    </p_cat1_elem1>
    <p_cat1_elem2>
      <display_name>Element 2</display_name>
      <category_type>Currency</category_type>
      <mf_type>Static</mf_type>
      <mf_value>1</mf_value>
    </p_cat1_elem2>
    <p_cat1_elem3>
      <display_name>Element 3</display_name>
      <category_type>Currency</category_type>
      <mf_type>Static</mf_type>
      <mf_value>1</mf_value>
    </p_cat1_elem3>
    <p_cat1_elem4>
      <display_name>Element 4</display_name>

```

```
<category_type>Currency</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</p_cat1_elem4>
<p_cat1_elem5>
    <display_name>Element 5</display_name>

<category_type>Currency</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</p_cat1_elem5>
</p_cat1>
<p_cat2>
    <display_name>Category 2</display_name>
    <category_type>Generic Finance

Category</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
    <p_cat2_elem1>
        <display_name>Element 1</display_name>

<category_type>Currency</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</p_cat2_elem1>
<p_cat2_elem2>
    <display_name>Element 2</display_name>

<category_type>Currency</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</p_cat2_elem2>
<p_cat2_elem3>
    <display_name>Element 3</display_name>

<category_type>Currency</category_type>

    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
</p_cat2_elem3>
<p_cat2_elem4>
    <display_name>Element 4</display_name>

<category_type>Currency</category_type>
```

```

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
    </p_cat2_elem4>
    <p_cat2_elem5>
        <display_name>Element 5</display_name>

<category_type>Currency</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
    </p_cat2_elem5>
</p_cat2>
</nonrollup>
<group4>
    <display_name>Group4</display_name>
    <category_type>Currency</category_type>
    <mf_type>Static</mf_type>
    <mf_value>1</mf_value>
    <g4_cat1>
        <display_name>Category 1</display_name>
        <category_type>Generic Finance

Category</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
    <g4_cat1_elem1>
        <display_name>Element 1</display_name>

    <category_type>Currency</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
    </g4_cat1_elem1>
    <g4_cat1_elem2>
        <display_name>Element 2</display_name>

    <category_type>Currency</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>
    </g4_cat1_elem2>
    <g4_cat1_elem3>
        <display_name>Element 3</display_name>

    <category_type>Currency</category_type>

        <mf_type>Static</mf_type>
        <mf_value>1</mf_value>

```

```
</g4_cat1_elem3>
<g4_cat1_elem4>
  <display_name>Element 4</display_name>

<category_type>Currency</category_type>

  <mf_type>Static</mf_type>
  <mf_value>1</mf_value>
</g4_cat1_elem4>
<g4_cat1_elem5>
  <display_name>Element 5</display_name>

<category_type>Currency</category_type>

  <mf_type>Static</mf_type>
  <mf_value>1</mf_value>
</g4_cat1_elem5>
</g4_cat1>
<g4_cat2>
  <display_name>Category 2</display_name>
  <category_type>Generic Finance

Category</category_type>

  <mf_type>Static</mf_type>
  <mf_value>1</mf_value>
<g4_cat2_elem1>
  <display_name>Element 1</display_name>

<category_type>Currency</category_type>

  <mf_type>Static</mf_type>
  <mf_value>1</mf_value>
</g4_cat2_elem1>
<g4_cat2_elem2>
  <display_name>Element 2</display_name>

<category_type>Currency</category_type>

  <mf_type>Static</mf_type>
  <mf_value>1</mf_value>
</g4_cat2_elem2>
<g4_cat2_elem3>
  <display_name>Element 3</display_name>

<category_type>Currency</category_type>

  <mf_type>Static</mf_type>
  <mf_value>1</mf_value>
</g4_cat2_elem3>
```

```

                                <g4_cat2_elem4>
                                    <display_name>Element 4</display_name>

<category_type>Currency</category_type>

                                <mf_type>Static</mf_type>
                                <mf_value>1</mf_value>
                                </g4_cat2_elem4>
                                <g4_cat2_elem5>
                                    <display_name>Element 5</display_name>

<category_type>Currency</category_type>

                                <mf_type>Static</mf_type>
                                <mf_value>1</mf_value>
                                </g4_cat2_elem5>
                                </g4_cat2>
                                </group4>
                                </finance_structure>
                                </finance_descriptor>
                                </project_finance_structure>
                            </app_data>
                        </root>

```

Output Example in JSON Format

The following example retrieves a project finance structure.

```

{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0",
    "char_set": "UTF-8"
  },
  "response_data": {
    "response_desc": "",
    "request_type": "search",
    "response_code": "0",
    "entity_type": "project_finance_structure"
  },
  "app_data": {"project_finance_structure": [{
    "project_name": {
      "display_name": "Project Name",
      "value": "Analytics for commercial banking with B0"
    }
  ]}
}

```

```
    },
    "finance_descriptor": {
      "fin_edit_mode": {
        "display_name": "Finance Edit Mode",
        "value": "M"
      },
      "fintemplate_id": {
        "display_name": "Finance Template",
        "value": "Default Global Finance Template"
      },
      "fintemplate_version_id": {
        "display_name": "Finance Template Version",
        "value": "testdata_defaultGlobalFinTemplateVersionID"
      }
    },
    "project_number": {
      "display_name": "Project ID",
      "value": "19"
    }
  }
}
```

Finance Snapshot

This object contains finance data for a given snapshot. A project can have multiple finance snapshots, which are identified by unique name.

In This Section

Create Function.....	210
Update Function.....	216
Search Function	227
Delete Function	258

Create Function

The Create function allows you to create a project finance snapshot. You can create multiple project snapshots.

Invocation Syntax

The syntax for the invocation of the create function is as follows:

```
<api_session>?&request_data=<input_data>&request_format
=<request_format>
```

Invocation Example

Assume the input data has been specified in project15_create.xml and project15_create.json. Then the syntax for the create function is as follows:

```
<api_session>?&request_data=<tags specified in
project15_API_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<tags specified in
project15_API_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the create function are described in the following table. Unless otherwise specified, all values are not case-sensitive.

Name	Data Type	Placeholder or constant	Description
<i>Request_data</i>	String	<i><input_data></i>	Specifies the input data for creating a project. For more details, See the Input Parameters.
<i>Request_format</i>	String	<i><request_format></i>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case-sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> lists the global settings for your EnterpriseTrack instance.

Name	Data Type	Value Required?	Placeholder or Constant	Description
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See <i>Request Data Table</i> below for more details.
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the create template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request Data Table				
Request_type	String	Yes	create	The name of the function.
Entity_type	String	Yes	project_finance_snapshot	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

Input examples in XML and JSON formats are provided below.

Input Example in XML Format

The following is an example of the input data for creating a project finance snapshot in XML format:

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <request_data>
    <request_type>create</request_type>
    <entity_type>project_finance_snapshot</entity_type>
    <output_format>xml</output_format>
    <value_delimiter>|</value_delimiter>
  </request_data>
  <app_data>
    <project_finance_snapshot>
      <project_number>
        <display_name>Project ID</display_name>
        <value>10023</value>
      </project_number>
      <project_name>
        <display_name>Project Name</display_name>

        <value>proj-10023-Roadmap_for_Corporate_and_Accts_Payable_SS_DMAICCAAPSS-measure_six_sigma
_phase-Active-team2-2012-Type_PT_Project_Type_Using_CAAP_Roadmap</value>
      </project_name>
      <finance_descriptor>
        <snapshot_descriptor>
          <snapshot_name>
            <display_name>Snapshot Name</display_name>
            <value>First_Test_Snapshot_1</value>
          </snapshot_name>
          <snapshot_desc>
            <display_name>Snapshot Description </display_name>
            <value> this is snapshot created by integration
          </value>
          </snapshot_desc>
          <is_default_snapshot>
            <display_name> Is default snapshot ? ( Y/N)
          </display_name>
          <value>Y </value>
          </is_default_snapshot>
        </snapshot_descriptor>
      </finance_descriptor>
    </project_finance_snapshot>
  </app_data>
</root>
```

```
        </snapshot_descriptor>
      </finance_descriptor>
    </project_finance_snapshot>
  </app_data>
</root>
```

Input Example in JSON Format

The following is an example of the input data for creating a project finance snapshot in JSON format:

```
{
  "global_properties": {
    "char_set": "UTF-8",
    "date_format": "MMM/dd/yyyy",
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "create",
    "entity_type": "project_finance_snapshot",
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project_finance_snapshot": [{
      "project_number": {
        "display_name": "Project ID",
        "value": "10060"
      },
      "project_name": {
        "display_name": "Project Name",
        "value": ""
      },
      "finance_descriptor": {
        "snapshot_descriptor": {
          "snapshot_name": {
            "display_name": "Snapshot Name",
            "value": "First_Test_Snapshot_1"
          },
          "snapshot_desc": {
            "display_name": "snapshot_desc",
            "value": "Snapshot created using itegration"
          }
        }
      }
    ]
  }
}
```

```
        "is_default_snapshot": {
            "display_name": "Is Default snapshot",
            "value": "Y"
        }
    }
}
}]
}
```

Output Examples

The following section provides output examples of the Create function in XML and JSON formats.

Output Example in XML Format

The following is an example of the response from the Create function in XML format.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <response_data>
    <request_type>create</request_type>
    <entity_type>project_finance_snapshot</entity_type>
    <response_code>0</response_code>
    <response_desc/>
  </response_data>
  <app_data/>
</root>
```

Output Example in JSON Format

The following is an example of the response from the Create function in JSON format.

```
{
  "global_properties": {
    "date_format": "MMM/dd/yyyy",
    "language": "en",
    "api_version": "9.0",
    "char_set": "UTF-8"
  },
  "response_data": {
```

```
    "response_desc": "",
    "request_type": "create",
    "response_code": "0",
    "entity_type": "project_finance_snapshot"
  },
  "app_data": {"": []}
}
```

Update Function

The update function allows you to update a project finance snapshot in EnterpriseTrack. Project finance snapshot update consists of two parts:

- ▶ Snapshot metadata : Snapshot description or *is_default_snapshot* can be updated unconditionally.
- ▶ Snapshot finance data : This is driven by feature *is_snapshot_editable*. If feature is disabled, you cannot update finances for snapshot.

Invocation Syntax

The syntax for the invocation of the Update function is:

```
<api_session>?&request_data=<request_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, project15_update.xml and project15_update.json. Then the syntax for the update function is:

```
<api_session>?&request_data=<content of
project15_API_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<content of
project15_API_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the update function are described in the following table. Unless otherwise specified, all values are not case-sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
<i>Request_data</i>	String	Yes	<input_data>	Specifies the input parameters for the request in the format specified in the request_format parameter. For more details, see the <i>Input Parameters</i> .
<i>Request_format</i>	String	Yes	<request_format>	The data format of the request. Supported formats include: ▶ JSON ▶ XML
global_properties	Object	Yes	Not applicable	This object lists the global settings for the EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See "Request_Data Table" below for more details.
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate, it is recommended that you download the update template from your EnterpriseTrack Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	update	The name of the function.
Entity_type	String	Yes	project_finance_snapshot	The entity on which the operation is being performed.

Name	Data Type	Value Required?	Placeholder or constant	Description
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data for the Update function in XML and JSON formats.

Input Example in XML Format

The following is an example of the input data for the update function in XML format.

Note: After downloading the template for finance, you must copy the structure based on the project finance edit mode.

- If the project finance edit mode is Aggregate, copy the whole structure once under the <data_aggregate> tag.
- If the project finance edit mode is Monthly, copy and repeat the whole structure for each month in the <data_YYYYMM> tag. The value for MM (months) will depend on the project dates and the month for which data is being updated.
- If the project finance edit mode is Yearly, copy and repeat the whole structure for each year in the <data_YYYY> tag. The value for YYYY (years) will depend on the project dates and the year for which data is being updated.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
```

```
<request_data>
  <request_type>update</request_type>
  <entity_type>project_finance_snapshot</entity_type>
  <output_format>xml</output_format>
  <value_delimiter>|</value_delimiter>
</request_data>
<app_data>
  <project_finance_snapshot>
    <project_number>
      <display_name>Project ID</display_name>
      <value>10023</value>
    </project_number>
    <project_name>
      <display_name>Project Name</display_name>
      <value/>
    </project_name>
    <finance_descriptor>
      <fin_edit_mode>
        <display_name> Finance data search mode ( M for Monthly / Y for
Yearly / A for Aggregate) </display_name>
        <value>M</value>
      </fin_edit_mode>
      <snapshot_descriptor>
        <snapshot_name>
          <display_name>Snapshot Name</display_name>
          <value>First_Test_Snapshot_1</value>
        </snapshot_name>
        <snapshot_desc>
          <display_name>Snapshot Description</display_name>
          <value/>
        </snapshot_desc>
        <make_snapshot_current>
          <display_name>Make this Snapshot Default ? ( Y /
N)</display_name>
          <value>Y</value>
        </make_snapshot_current>
      </snapshot_descriptor>
    </finance_descriptor>
    <finance_data>
      <data_201201>
        <savings>
          <display_name>Benefits</display_name>
```

```

        <s_cat1>
            <display_name>Category 1 </display_name>
            <s_cat1_elem1>
                <display_name>Element 1
</display_name>
                <value>2000.50</value>
            </s_cat1_elem1>
            <s_cat1_elem2>
                <display_name> Element 2
</display_name>
                <number_of_units> 10
</number_of_units>
            </s_cat1_elem2>
        </s_cat1>
    </savings>
    <expenses>
        <display_name> Cost </display_name>
        <e_cat1>
            <display_name>Team Finance Category
</display_name>
            <e_cat1_elem1>
                <display_name>Team Standard Effort
</display_name>
                <number_of_units>10</number_of_units>
            </e_cat1_elem1>
        </e_cat1>
    </expenses>
</data_201201>
<data_201202>
    <savings>
        <display_name>Benefits</display_name>
        <s_cat1>
            <display_name> Category 1 </display_name>
            <s_cat1_elem1>
                <display_name> Element 1
</display_name>
                <value>2000.50</value>
            </s_cat1_elem1>
            <s_cat1_elem2>
                <display_name> Element 2
</display_name>
                <number_of_units> 20
</number_of_units>
```

```

        </s_cat1_elem2>
      </s_cat1>
    </savings>
    <expenses>
      <display_name> Cost </display_name>
      <e_cat1>
        <display_name>Team Finance
Category</display_name>
        <value/>
        <e_cat1_elem1>
          <display_name>Team Standard Effort
</display_name>
          <number_of_units>10</number_of_units>
        </e_cat1_elem1>
      </e_cat1>
    </expenses>
  </data_201202>
</finance_data>
</project_finance_snapshot>
</app_data>
</root>

```

Input Example in JSON Format

The following is an example of the input data for the update function in JSON format.

Note: After downloading the template for finance, you must copy the structure based on the project finance edit mode.

- If the project finance edit mode is Aggregate, copy the whole structure once under the <data_aggregate> tag.
- If the project finance edit mode is Monthly, copy and repeat the whole structure for each month in the <data_YYYYMM> tag. The value for MM (months) will depend on the project dates and the month for which data is being updated.
- If the project finance edit mode is Yearly, copy and repeat the whole structure for each year in the <data_YYYY> tag. The value for YYYY (years) will depend on the project dates and the year for which data is being updated.

```

{
  "global_properties": {
    "char_set": "UTF-8",
    "date_format": "yyyy/MM/dd",

```

```
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "update",
    "entity_type": "project_finance_snapshot",
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project_finance_snapshot": [{
      "project_number": {
        "display_name": "Project ID",
        "value": "10081"
      },
      "project_name": { "display_name": "Project Name" },
      "finance_descriptor": {
        "fin_edit_mode": {
          "display_name": " Finance data search mode ( M for Monthly / Y for Yearly / A for
Aggregate) ",
          "value": "Y"
        },
        "snapshot_descriptor": {
          "snapshot_name": {
            "display_name": "Snapshot Name",
            "value": "First_Test_Snapshot_a"
          },
          "snapshot_desc": { "display_name": "Snapshot Description" },
          "is_default_snapshot": {
            "display_name": "Make this Snapshot Default ? ( Y / N)",
            "value": "Y"
          }
        }
      }
    }],
    "finance_data": {
      "data_2013": {
        "savings": {
          "display_name": "Benefits",
          "s_cat1": {
            "display_name": "Category 1 ",
            "s_cat1_elem1": {
              "display_name": " Element 1 ",
```

```
        "value": "200.50"
      },
      "s_cat1_elem2": {
        "display_name": "  Element 2",
        "number_of_units": "10"
      }
    }
  },
  "expenses": {
    "display_name": " Cost ",
    "e_cat1": {
      "display_name": "Team Finance Category",
      "e_cat1_elem1": {
        "display_name": "Team Standard Effort ",
        "number_of_units": "10"
      }
    }
  }
},
"data_2014": {
  "savings": {
    "display_name": "Benefits",
    "s_cat1": {
      "display_name": "Category 1  ",
      "s_cat1_elem1": {
        "display_name": " Element 1 ",
        "value": "2000.50"
      },
      "s_cat1_elem2": {
        "display_name": " Element 2  ",
        "number_of_units": "10"
      }
    }
  }
},
"expenses": {
  "display_name": " Cost ",
  "e_cat1": {
    "display_name": "Team Finance Category ",
    "e_cat1_elem1": {
      "display_name": "Team Standard Effort ",
      "number_of_units": "10"
    }
  }
}
```

```
    }  
  }  
}  
}  
}]  
}  
  
}
```

Output Examples

The following section provides examples of the update function in XML and JSON formats.

Output Example in XML Format

The following is an example of the response from the update function for updating a project finance snapshot in XML format.

```
<?xml version="1.0" encoding="UTF-8"?>  
<root>  
  <global_properties>  
    <char_set>UTF-8</char_set>  
    <date_format>yyyy/MM/dd</date_format>  
    <language>en</language>  
    <api_version>9.0</api_version>  
  </global_properties>  
  <request_data>  
    <request_type>update</request_type>  
    <entity_type>project_finance_snapshot</entity_type>  
    <output_format>xml</output_format>  
    <value_delimiter>|</value_delimiter>  
  </request_data>  
  <app_data>  
    <project_finance_snapshot>  
      <project_number>  
        <display_name>Project ID</display_name>  
        <value>10023</value>  
      </project_number>  
      <project_name>  
        <display_name>Project Name</display_name>  
        <value/>  
      </project_name>  
      <finance_descriptor>  
        <fin_edit_mode>  
          <display_name> Finance data search mode ( M for Monthly / Y for
```

```

Yearly / A for Aggregate) </display_name>
    <value>M</value>
</fin_edit_mode>
<snapshot_descriptor>
    <snapshot_name>
        <display_name>Snapshot Name</display_name>
        <value>First_Test_Snapshot_1</value>
    </snapshot_name>
    <snapshot_desc>
        <display_name>Snapshot Description</display_name>
        <value/>
    </snapshot_desc>
    <make_snapshot_current>
        <display_name>Make this Snapshot Default ? ( Y /
N)</display_name>
        <value>Y</value>
    </make_snapshot_current>
</snapshot_descriptor>
</finance_descriptor>
<finance_data>
    <data_201201>
        <savings>
            <display_name>Benefits</display_name>
            <s_cat1>
                <display_name>Category 1 </display_name>
                <s_cat1_elem1>
                    <display_name>Element 1
</display_name>
                    <value>2000.50</value>
                </s_cat1_elem1>
                <s_cat1_elem2>
                    <display_name> Element 2
</display_name>
                    <number_of_units> 10
</number_of_units>
                </s_cat1_elem2>
            </s_cat1>
        </savings>
        <expenses>
            <display_name> Cost </display_name>
            <e_cat1>
                <display_name>Team Finance Category
</display_name>

```

```

                                <e_cat1_elem1>
                                    <display_name>Team Standard Effort
</display_name>
                                <number_of_units>10</number_of_units>
                                </e_cat1_elem1>
                            </e_cat1>
                        </expenses>
</data_201201>
<data_201202>
    <savings>
        <display_name>Benefits</display_name>
        <s_cat1>
            <display_name> Category 1  </display_name>
            <s_cat1_elem1>
                <display_name>  Element 1
</display_name>
                <value>2000.50</value>
            </s_cat1_elem1>
            <s_cat1_elem2>
                <display_name>  Element 2
</display_name>
                <number_of_units> 20
</number_of_units>
            </s_cat1_elem2>
        </s_cat1>
    </savings>
    <expenses>
        <display_name> Cost </display_name>
        <e_cat1>
            <display_name>Team Finance
Category</display_name>
            <value/>
            <e_cat1_elem1>
                <display_name>Team Standard Effort
</display_name>
                <number_of_units>10</number_of_units>
            </e_cat1_elem1>
        </e_cat1>
    </expenses>
</data_201202>
</finance_data>
</project_finance_snapshot>
</app_data>
```

```
</root>
```

Output Example in JSON Format

The following is an example of the response from the update function for updating a project finance snapshot in JSON format.

```
{
  "global_properties": {
    "date_format": "yyyy/MM/dd",
    "language": "en",
    "api_version": "9.0",
    "char_set": "UTF-8"
  },
  "response_data": {
    "response_desc": "",
    "request_type": "update",
    "response_code": "0",
    "entity_type": "project_finance_snapshot"
  },
  "app_data": {"": []}
}
```

Search Function

The search function allows you to search for finance data.

Invocation Syntax

The syntax for the invocation of the search function is as follows.

```
<api_session>?&request_data=<request_data>&request_format
=<request_format>
```

Invocation Examples

Assume the input data has been specified in files, project15_search.xml and project15_search.json. Then the syntax for the search function is as follows:

```
<api_session>?&request_data=<content specified in
project15_API_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<content specified in
project15_API_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the search function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or constant	Description
<i>Request_data</i>	String	<code><input_data></code>	Specifies the input data for searching a project. For more details, see Input Parameters.
<i>Request_format</i>	String	<code><request_format></code>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
global_properties	Object	Yes	Not applicable	This <i>object</i> lists the global settings for your EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See <i>Request_Data Table</i> below for more details.

Name	Data Type	Value Required?	Placeholder or Constant	Description
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the search template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	search	The name of the function.
Entity_type	String	Yes	project_finance_snapshot	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data specified for the Search function in XML and JSON formats.

Input Example in XML Format

The following is an example of the input data for the search function in XML format.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
```

```
<date_format>yyyy/MM/dd</date_format>
<language>en</language>
<api_version>9.0</api_version>
</global_properties>
<request_data>
  <request_type>search</request_type>
  <entity_type>project_finance_snapshot</entity_type>
  <output_format>xml</output_format>
  <value_delimiter>|</value_delimiter>
</request_data>
<app_data>
  <project_finance_snapshot>
    <project_number>
      <display_name>Project ID</display_name>
      <value>10023</value>
    </project_number>
    <project_name>
      <display_name>Project Name</display_name>
      <value/>
    </project_name>
    <finance_descriptor>
      <snapshot_descriptor>
        <snapshot_name>
          <name> Snapshot Name </name>
          <value> First_Test_Snapshot_1 </value>
        </snapshot_name>
      </snapshot_descriptor>
      <fin_search_mode>
        <display_name> Finance data search mode ( M for Monthly / Y for
Yearly / A for Aggregate) </display_name>
        <value>M</value>
      </fin_search_mode>
      <!-- Fill in monthly_search section , if finance_search_mode = M -->
      <monthly_search>
        <from_month>
          <display_name> From Month (yyyy/mm format). Keep empty
to have start month as fin track start month</display_name>
          <value/>
        </from_month>
        <to_month>
          <display_name> To Month (yyyy/mm format). Keep empty if
you do not know finance data end month </display_name>
```

```

        <value/>
    </to_month>
</monthly_search>
<!-- Fill in yearly_search section , if finance_search_mode = Y -->
<yearly_search>
    <from_year>
        <display_name> From year (yyyy format). Keep empty for
fin track start year</display_name>
        <value/>
    </from_year>
    <to_year>
        <display_name> To year (yyyy format). Keep empty if you
do not know finance data end year </display_name>
        <value/>
    </to_year>
</yearly_search>
<search_group>
    <group>
        <display_name>Group Name. Set to *, if you need all
groups data</display_name>
        <value>*</value>
    </group>
    <search_category>
        <category>
            <display_name> Category Name. Use *. if you need
all categories for a given group.</display_name>
            <value>*</value>
        </category>
        <search_element>
            <element>
                <display_name> Element Name. Use *. if
you need all element for selected group and category. </display_name>
                <value>*</value>
            </element>
        </search_element>
    </search_category>
</search_group>
</finance_descriptor>
</project_finance_snapshot>
</app_data>
</root>

```

Input Example in JSON Format

The following is an example of the input data for the search function in JSON format.

```
{
  "global_properties": {
    "char_set": "UTF-8",
    "date_format": "MMM/dd/yyyy",
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "search",
    "entity_type": "project_finance_snapshot",
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project_finance_snapshot": [{
      "project_number": {
        "display_name": "Project ID",
        "value": "10081"
      },
      "project_name": {
        "display_name": "Project Name",
        "value": ""
      },
      "finance_descriptor": {
        "fin_search_mode": {
          "display_name": "Finance Search Mode",
          "value": "Y"
        },
        "snapshot_name": {
          "display_name": "Snapshot Name",
          "value": "First_Test_Snapshot_a "
        },
        "monthly_search": {
          "from_month": {
            "display_name": "From (Start) Month for Searching.
Applicable only if fin_search_mode = M. (YYYY/MM Format)",
            "value": ""
          },
          "to_month": {
            "display_name": "To (End) Month for Searching.
```

```
Applicable only if fin_search_mode = M. (YYYY/MM Format)",
    "value": ""
  },
},
"yearly_search": {
  "from_year": {
    "display_name": "From (Start) Year for Searching.
Applicable only if fin_search_mode = Y. (YYYY Format)",
    "value": ""
  },
  "to_year": {
    "display_name": "To (End) Year for Searching.
Applicable only if fin_search_mode = Y. (YYYY Format)",
    "value": ""
  },
},
"search_group": {
  "group": {
    "display_name": "Group Name. Set to *, if you need all
groups data",
    "value": "*"
  },
  "search_category": {
    "category": {
      "display_name": "Category Name. Use *. if you
need all categories for a given group.",
      "value": "*"
    },
    "search_element": {
      "element": {
        "display_name": "Element Name. Use *. if
you need all element for selected group and category.",
        "value": "*"
      }
    }
  }
}
}
}
}
}
}
}
}
```

Output Examples

Output Examples in XML Format

The following is an example of the response from the search function in XML format.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <response_data>
    <request_type>search</request_type>
    <entity_type>project_finance_snapshot</entity_type>
    <response_code>0</response_code>
    <response_desc/>
  </response_data>
  <app_data>
    <project_finance_snapshot>
      <project_number>
        <display_name>Project ID</display_name>
        <value>10023</value>
      </project_number>
      <project_name>
        <display_name>Project Name</display_name>
        <value>proj-10023-Roadmap_for_Corporate_and_Accts_Payable_SS_DMAICCAAPSS-measure_six_sigma_phase-Active-team2-2012-Type_PT_Project_Type_Using_CAAP_Roadmap</value>
      </project_name>
      <finance_descriptor>
        <finance_template>
          <display_name>finance_template</display_name>
          <value>Default Global Finance Template</value>
        </finance_template>
        <finance_template_version>
          <display_name>finance_template_version</display_name>
          <value>testdata_defaultGlobalFinTemplateVersionID</value>
        </finance_template_version>
        <fin_edit_mode>
          <display_name>Finance Edit Mode</display_name>
```

```
        <value>M</value>
    </fin_edit_mode>
    <snapshot_name>
        <display_name>Snapshot Name</display_name>
        <value>First_Test_Snapshot_1</value>
    </snapshot_name>
    <snapshot_desc>
        <display_name>snapshot_desc</display_name>
        <value>this is snapshot created by integration</value>
    </snapshot_desc>
    <is_default_snapshot>
        <display_name>Is Default snapshot</display_name>
        <value>Yes</value>
    </is_default_snapshot>
    <is_editable_snapshot>
        <display_name>Is Editable Snapshot</display_name>
        <value>Yes</value>
    </is_editable_snapshot>
    <snapshot_created_by>
        <display_name>snapshot_created_by</display_name>
        <value>Configurator, Application</value>
    </snapshot_created_by>
    <snapshot_created_date>
        <display_name>snapshot_created_date</display_name>
        <value>2014/08/20</value>
    </snapshot_created_date>
    <snapshot_updated_by>
        <display_name>snapshot_updated_by</display_name>
        <value>Configurator, Application</value>
    </snapshot_updated_by>
    <snapshot_updated_date>
        <display_name>snapshot_updated_date</display_name>
        <value>2014/08/20</value>
    </snapshot_updated_date>
    <finance_data>
        <data_monthly>
            <data_201201>
                <total>
                    <display_name>Total</display_name>
                    <value>7739414.9</value>
                </total>
                <savings>
```

	<code><display_name>Benefits</display_name></code>
	<code><value>3798571.9</value></code>
	<code><s_cat1></code>
	<code> <display_name>Category</code>
<code>1</display_name></code>	<code> <value>679091.9</value></code>
	<code> <s_cat1_elem1></code>
	<code> <display_name>Element</code>
<code>1</display_name></code>	<code> <value>2000.50</value></code>
	<code> </s_cat1_elem1></code>
	<code> <s_cat1_elem2></code>
	<code> <display_name>Element</code>
<code>2</display_name></code>	<code> <no_of_elements/></code>
	<code> <value>1203.4</value></code>
	<code> </s_cat1_elem2></code>
	<code> <s_cat1_elem3></code>
	<code> <display_name>Element</code>
<code>3</display_name></code>	<code> <no_of_elements/></code>
	<code> <value>51991.0</value></code>
	<code> </s_cat1_elem3></code>
	<code> <s_cat1_elem4></code>
	<code> <display_name>Element</code>
<code>4</display_name></code>	<code> <no_of_elements/></code>
	<code> <value>51991.0</value></code>
	<code> </s_cat1_elem4></code>
	<code> <s_cat1_elem5></code>
	<code> <display_name>Element</code>
<code>5</display_name></code>	<code> <value>51991.0</value></code>
	<code> </s_cat1_elem5></code>
	<code></s_cat1></code>
	<code><s_cat2></code>
	<code> <display_name>Category</code>
<code>2</display_name></code>	<code> <value>779870</value></code>
	<code> <s_cat2_elem1></code>
	<code> <display_name>Element</code>
<code>1</display_name></code>	<code> <value>51991.0</value></code>

```

2</display_name>
3</display_name>
4</display_name>
5</display_name>
Category</display_name>
Standard Effort</display_name>
Overtime Effort</display_name>

</s_cat2_elem1>
<s_cat2_elem2>
  <display_name>Element
  <value>51991.0</value>
</s_cat2_elem2>
<s_cat2_elem3>
  <display_name>Element
  <value>51991.0</value>
</s_cat2_elem3>
<s_cat2_elem4>
  <display_name>Element
  <value>51991.0</value>
</s_cat2_elem4>
<s_cat2_elem5>
  <display_name>Element
  <value>51991.0</value>
</s_cat2_elem5>
</s_cat2>
</savings>
<expenses>
  <display_name>Cost</display_name>
  <value>3077987</value>
  <e_cat1>
    <display_name>Team Finance
    <value>582403</value>
    <e_cat1_elem1>
      <display_name>Team
      <no_of_elements/>
      <value>100</value>
    </e_cat1_elem1>
    <e_cat1_elem2>
      <display_name>Team
      <no_of_elements/>
      <value>41593.0</value>
    </e_cat1_elem2>
    <e_cat1_elem3>

```

```
<display_name>Timesheet Standard Effort</display_name>
                                <no_of_elements/>
                                <value>41593.0</value>
                                </e_cat1_elem3>
                                <e_cat1_elem4>

<display_name>Timesheet Overtime Effort</display_name>
                                <no_of_elements/>
                                <value>41593.0</value>
                                </e_cat1_elem4>
                                </e_cat1>
                                <e_cat2>
                                    <display_name>Activity
Non-Resource Finance Category</display_name>
                                    <value>623896</value>
                                    <e_cat2_elem1>

<display_name>Fixed</display_name>
                                    <value>41593.0</value>
                                    </e_cat2_elem1>
                                    <e_cat2_elem2>

<display_name>Material</display_name>
                                    <value>41593.0</value>
                                    </e_cat2_elem2>
                                    <e_cat2_elem3>

<display_name>Other</display_name>
                                    <value>41593.0</value>
                                    </e_cat2_elem3>
                                </e_cat2>
                                <e_cat3>
                                    <display_name>Activity
Resource Finance Category</display_name>
                                    <value>623896</value>
                                    <e_cat3_elem1>
                                        <display_name>Actual
Standard Effort</display_name>
                                        <no_of_elements/>

<value>124779.0</value>
                                        </e_cat3_elem1>
```

```
<e_cat3_elem2>
  <display_name>Actual
Overtime Effort</display_name>

  <no_of_elements/>

<value>124779.0</value>

</e_cat3_elem2>
<e_cat3_elem3>

<display_name>Timesheet Standard Effort</display_name>

  <no_of_elements/>

<value>124779.0</value>

</e_cat3_elem3>
<e_cat3_elem4>

<display_name>Timesheet Overtime Effort</display_name>

  <no_of_elements/>

<value>124779.0</value>

</e_cat3_elem4>
</e_cat3>
<e_cat4>
  <display_name>Capital
Expense</display_name>

  <value>623896</value>
  <e_cat4_elem1>
    <display_name>Actual
Standard Effort</display_name>

    <no_of_elements/>

    <value>124779.0</value>

  </e_cat4_elem1>
  <e_cat4_elem2>
    <display_name>Actual
Overtime Effort</display_name>

    <no_of_elements/>

    <value>124779.0</value>

  </e_cat4_elem2>
  <e_cat4_elem3>

<display_name>Timesheet Standard Effort</display_name>
```

```
<no_of_elements/>

<value>124779.0</value>

</e_cat4_elem3>
<e_cat4_elem4>

<display_name>Timesheet Overtime Effort</display_name>

<no_of_elements/>

<value>124779.0</value>

</e_cat4_elem4>
</e_cat4>
<e_cat5>
  <display_name>Operational
Expense</display_name>

  <value>623896</value>
  <e_cat5_elem1>
    <display_name>Actual
Standard Effort</display_name>

    <no_of_elements/>

    <value>124779.0</value>

    </e_cat5_elem1>
    <e_cat5_elem2>
      <display_name>Actual
Overtime Effort</display_name>

      <no_of_elements/>

      <value>124779.0</value>

      </e_cat5_elem2>
      <e_cat5_elem3>

<display_name>Timesheet Standard Effort</display_name>

      <no_of_elements/>

      <value>124779.0</value>

      </e_cat5_elem3>
      <e_cat5_elem4>

<display_name>Timesheet Overtime Effort</display_name>

      <no_of_elements/>

      <value>124779.0</value>
```

```

        </e_cat5_elem4>
      </e_cat5>
    </expenses>
    <nonrollup>
      <display_name>Soft
Dollar</display_name>

      <value>1559740</value>
      <p_cat1>
        <display_name>Category
1</display_name>

        <value>311948</value>
        <p_cat1_elem1>
          <display_name>Element
1</display_name>

          <value>20796.0</value>
        </p_cat1_elem1>
        <p_cat1_elem2>
          <display_name>Element
2</display_name>

          <value>20796.0</value>
        </p_cat1_elem2>
        <p_cat1_elem3>
          <display_name>Element
3</display_name>

          <value>20796.0</value>
        </p_cat1_elem3>
        <p_cat1_elem4>
          <display_name>Element
4</display_name>

          <value>20796.0</value>
        </p_cat1_elem4>
        <p_cat1_elem5>
          <display_name>Element
5</display_name>

          <value>20796.0</value>
        </p_cat1_elem5>
      </p_cat1>
      <p_cat2>
        <display_name>Category
2</display_name>

        <value>311948</value>
        <p_cat2_elem1>
          <display_name>Element

```

```
1</display_name>
                                <value>20796.0</value>
                                </p_cat2_elem1>
                                <p_cat2_elem2>
                                <display_name>Element
2</display_name>
                                <value>20796.0</value>
                                </p_cat2_elem2>
                                <p_cat2_elem3>
                                <display_name>Element
3</display_name>
                                <value>20796.0</value>
                                </p_cat2_elem3>
                                <p_cat2_elem4>
                                <display_name>Element
4</display_name>
                                <value>20796.0</value>
                                </p_cat2_elem4>
                                <p_cat2_elem5>
                                <display_name>Element
5</display_name>
                                <value>20796.0</value>
                                </p_cat2_elem5>
                                </p_cat2>
                                </nonrollup>
                                <....>
</data_201212>
                                </data_monthly>
                                </finance_data>
                                </finance_descriptor>
                                </project_finance_snapshot>
</app_data>
</root>
```

Output Example in JSON Format

The following is an example of the response from the search function in XML format.

```
{
  "global_properties": {
    "date_format": "MMM/dd/yyyy",
    "language": "en",
    "api_version": "9.0",
    "char_set": "UTF-8"
  },
}
```

```

"response_data": {
  "response_desc": "",
  "request_type": "search",
  "response_code": "0",
  "entity_type": "project_finance_snapshot"
},
"app_data": {"project_finance_snapshot": [{
  "project_name": {
    "display_name": "Project Name",
    "value":
"proj-10081-Roadmap_for_Corporate_and_Accts_Payable_SS_DMAICCAAPSS-improve_six_sigma_phase-C
losed-team2-2013-Type_PT_Project_Type_Using_CAAP_Roadmap"
  },
  "finance_descriptor": {
    "is_editable_snapshot": {
      "display_name": "Is Editable Snapshot",
      "value": "Yes"
    },
    "snapshot_name": {
      "display_name": "Snapshot Name",
      "value": "First_Test_Snapshot_a"
    },
    "finance_template_version": {
      "display_name": "finance_template_version",
      "value": "testdata_defaultGlobalFinTemplateVersionID"
    },
    "snapshot_created_date": {
      "display_name": "snapshot_created_date",
      "value": "Nov/24/2014"
    },
    "is_default_snapshot": {
      "display_name": "Is Default snapshot",
      "value": "Yes"
    },
    "finance_data": {"data_yearly": {
      "data_2013": {
        "total_id": "total",
        "value": "109429797.40",
        "group4": {
          "display_name": "Group4",
          "value": "44725600.00",
          "g4_cat1": {

```

```
"display_name": "Category 1",
"value": "8945120.00",
"g4_cat1_elem5": {
  "display_name": "Element 5",
  "value": "596340.00"
},
"g4_cat1_elem3": {
  "display_name": "Element 3",
  "value": "596340.00"
},
"g4_cat1_elem4": {
  "display_name": "Element 4",
  "value": "596340.00"
},
"g4_cat1_elem1": {
  "display_name": "Element 1",
  "value": "596340.00"
},
"g4_cat1_elem2": {
  "display_name": "Element 2",
  "value": "596340.00"
}
},
"g4_cat2": {
  "g4_cat2_elem1": {
    "display_name": "Element 1",
    "value": "596340.00"
  },
  "display_name": "Category 2",
  "g4_cat2_elem2": {
    "display_name": "Element 2",
    "value": "596340.00"
  },
  "g4_cat2_elem3": {
    "display_name": "Element 3",
    "value": "596340.00"
  },
  "g4_cat2_elem4": {
    "display_name": "Element 4",
    "value": "596340.00"
  },
  "g4_cat2_elem5": {
```

```
        "display_name": "Element 5",
        "value": "596340.00"
      },
      "value": "8945120.00"
    }
  },
  "nonrollup": {
    "display_name": "Soft Dollar",
    "value": "22362800.00",
    "p_cat2": {
      "p_cat2_elem1": {
        "display_name": "Element 1",
        "value": "298168.00"
      },
      "p_cat2_elem2": {
        "display_name": "Element 2",
        "value": "298168.00"
      },
      "display_name": "Category 2",
      "value": "4472560.00",
      "p_cat2_elem5": {
        "display_name": "Element 5",
        "value": "298168.00"
      },
      "p_cat2_elem4": {
        "display_name": "Element 4",
        "value": "298168.00"
      },
      "p_cat2_elem3": {
        "display_name": "Element 3",
        "value": "298168.00"
      }
    }
  },
  "p_cat1": {
    "display_name": "Category 1",
    "p_cat1_elem5": {
      "display_name": "Element 5",
      "value": "298168.00"
    },
    "p_cat1_elem4": {
      "display_name": "Element 4",
      "value": "298168.00"
    }
  }
}
```

```
    },
    "value": "4472560.00",
    "p_cat1_elem1": {
      "display_name": "Element 1",
      "value": "298168.00"
    },
    "p_cat1_elem2": {
      "display_name": "Element 2",
      "value": "298168.00"
    },
    "p_cat1_elem3": {
      "display_name": "Element 3",
      "value": "298168.00"
    }
  }
},
"savings": {
  "display_name": "Benefits",
  "s_cat1": {
    "display_name": "Category 1",
    "value": "9691765.40",
    "s_cat1_elem1": {
      "display_name": "Element 1",
      "value": "10.00"
    },
    "s_cat1_elem2": {
      "display_name": "Element 2",
      "value": "1203.40-20",
      "number_of_units": ""
    },
    "s_cat1_elem3": {
      "display_name": "Element 3",
      "value": "745424.00",
      "number_of_units": ""
    },
    "s_cat1_elem4": {
      "display_name": "Element 4",
      "value": "745424.00",
      "number_of_units": ""
    },
    "s_cat1_elem5": {
      "display_name": "Element 5",
```

```
      "value": "745424.00"
    },
  },
  "s_cat2": {
    "display_name": "Category 2",
    "s_cat2_elem3": {
      "display_name": "Element 3",
      "value": "745424.00"
    },
    },
    "value": "9690592.00",
    "s_cat2_elem2": {
      "display_name": "Element 2",
      "value": "30.00"
    },
    },
    "s_cat2_elem5": {
      "display_name": "Element 5",
      "value": "745424.00"
    },
    },
    "s_cat2_elem4": {
      "display_name": "Element 4",
      "value": "745424.00"
    },
    },
    "s_cat2_elem1": {
      "display_name": "Element 1",
      "value": "10.00"
    }
  },
  "value": "52926557.40"
},
"total_display_name": "Total",
"expenses": {
  "e_cat1": {
    "display_name": "Team Finance Category",
    "e_cat1_elem1": {
      "display_name": "Team Standard Effort",
      "value": "100.00~3232.50",
      "number_of_units": ""
    },
    },
    "e_cat1_elem2": {
      "display_name": "Team Overtime Effort",
      "value": "596340.00",
      "number_of_units": ""
    }
  }
}
```

```
    },
    "e_cat1_elem3": {
      "display_name": "Timesheet Standard Effort",
      "value": "596340.00",
      "number_of_units": ""
    },
    "e_cat1_elem4": {
      "display_name": "Timesheet Overtime Effort",
      "value": "596340.00",
      "number_of_units": ""
    },
    "value": "8348880.00"
  },
  "display_name": "Cost",
  "e_cat3": {
    "display_name": "Activity Resource Finance Category",
    "value": "8945120.00",
    "e_cat3_elem1": {
      "display_name": "Actual Standard Effort",
      "value": "1789024.00",
      "number_of_units": ""
    },
    "e_cat3_elem2": {
      "display_name": "Actual Overtime Effort",
      "value": "1789024.00",
      "number_of_units": ""
    },
    "e_cat3_elem3": {
      "display_name": "Timesheet Standard Effort",
      "value": "1789024.00",
      "number_of_units": ""
    },
    "e_cat3_elem4": {
      "display_name": "Timesheet Overtime Effort",
      "value": "1789024.00",
      "number_of_units": ""
    }
  },
  "e_cat2": {
    "display_name": "Activity Non-Resource Finance Category",
    "value": "8945120.00",
    "e_cat2_elem1": {
```

```
      "display_name": "Fixed",
      "value": "596340.00"
    },
    "e_cat2_elem2": {
      "display_name": "Material",
      "value": "596340.00"
    },
    "e_cat2_elem3": {
      "display_name": "Other",
      "value": "596340.00"
    }
  },
  "value": "44129360.00",
  "e_cat5": {
    "display_name": "Operational Expense",
    "e_cat5_elem4": {
      "display_name": "Timesheet Overtime Effort",
      "value": "1789024.00",
      "number_of_units": ""
    },
    "e_cat5_elem3": {
      "display_name": "Timesheet Standard Effort",
      "value": "1789024.00",
      "number_of_units": ""
    },
    "e_cat5_elem2": {
      "display_name": "Actual Overtime Effort",
      "value": "1789024.00",
      "number_of_units": ""
    },
    "e_cat5_elem1": {
      "display_name": "Actual Standard Effort",
      "value": "1789024.00",
      "number_of_units": ""
    }
  },
  "value": "8945120.00"
},
"e_cat4": {
  "display_name": "Capital Expense",
  "value": "8945120.00",
  "e_cat4_elem4": {
    "display_name": "Timesheet Overtime Effort",
```

```
        "value": "1789024.00",
        "number_of_units": ""
    },
    "e_cat4_elem3": {
        "display_name": "Timesheet Standard Effort",
        "value": "1789024.00",
        "number_of_units": ""
    },
    "e_cat4_elem2": {
        "display_name": "Actual Overtime Effort",
        "value": "1789024.00",
        "number_of_units": ""
    },
    "e_cat4_elem1": {
        "display_name": "Actual Standard Effort",
        "value": "1789024.00",
        "number_of_units": ""
    }
}
},
"data_2014": {
    "total_id": "total",
    "value": "221840307.40",
    "group4": {
        "display_name": "Group4",
        "value": "89451200.00",
        "g4_cat1": {
            "display_name": "Category 1",
            "value": "17890240.00",
            "g4_cat1_elem5": {
                "display_name": "Element 5",
                "value": "1192680.00"
            },
            "g4_cat1_elem3": {
                "display_name": "Element 3",
                "value": "1192680.00"
            },
            "g4_cat1_elem4": {
                "display_name": "Element 4",
                "value": "1192680.00"
            }
        },
    },
}
```

```
"g4_cat1_elem1": {
  "display_name": "Element 1",
  "value": "1192680.00"
},
"g4_cat1_elem2": {
  "display_name": "Element 2",
  "value": "1192680.00"
}
},
"g4_cat2": {
  "g4_cat2_elem1": {
    "display_name": "Element 1",
    "value": "1192680.00"
  },
  "display_name": "Category 2",
  "g4_cat2_elem2": {
    "display_name": "Element 2",
    "value": "1192680.00"
  },
  "g4_cat2_elem3": {
    "display_name": "Element 3",
    "value": "1192680.00"
  },
  "g4_cat2_elem4": {
    "display_name": "Element 4",
    "value": "1192680.00"
  },
  "g4_cat2_elem5": {
    "display_name": "Element 5",
    "value": "1192680.00"
  },
  "value": "17890240.00"
}
},
"nonrollup": {
  "display_name": "Soft Dollar",
  "value": "44725600.00",
  "p_cat2": {
    "p_cat2_elem1": {
      "display_name": "Element 1",
      "value": "596336.00"
    },
  },
}
```

```
"p_cat2_elem2": {
  "display_name": "Element 2",
  "value": "596336.00"
},
"display_name": "Category 2",
"value": "8945120.00",
"p_cat2_elem5": {
  "display_name": "Element 5",
  "value": "596336.00"
},
"p_cat2_elem4": {
  "display_name": "Element 4",
  "value": "596336.00"
},
"p_cat2_elem3": {
  "display_name": "Element 3",
  "value": "596336.00"
}
},
"p_cat1": {
  "display_name": "Category 1",
  "p_cat1_elem5": {
    "display_name": "Element 5",
    "value": "596336.00"
  },
  "p_cat1_elem4": {
    "display_name": "Element 4",
    "value": "596336.00"
  },
  "value": "8945120.00",
  "p_cat1_elem1": {
    "display_name": "Element 1",
    "value": "596336.00"
  },
  "p_cat1_elem2": {
    "display_name": "Element 2",
    "value": "596336.00"
  },
  "p_cat1_elem3": {
    "display_name": "Element 3",
    "value": "596336.00"
  }
}
```

```
    }
  },
  "savings": {
    "display_name": "Benefits",
    "s_cat1": {
      "display_name": "Category 1",
      "value": "19382527.40",
      "s_cat1_elem1": {
        "display_name": "Element 1",
        "value": "220.00"
      },
      "s_cat1_elem2": {
        "display_name": "Element 2",
        "value": "1203.40-10",
        "number_of_units": ""
      },
      "s_cat1_elem3": {
        "display_name": "Element 3",
        "value": "1490848.00",
        "number_of_units": ""
      },
      "s_cat1_elem4": {
        "display_name": "Element 4",
        "value": "1490848.00",
        "number_of_units": ""
      },
      "s_cat1_elem5": {
        "display_name": "Element 5",
        "value": "1490848.00"
      }
    },
    "s_cat2": {
      "display_name": "Category 2",
      "s_cat2_elem3": {
        "display_name": "Element 3",
        "value": "1490848.00"
      },
      "value": "22362800.00",
      "s_cat2_elem2": {
        "display_name": "Element 2",
        "value": "1490848.00"
      },
    },
```

```
    "s_cat2_elem5": {
      "display_name": "Element 5",
      "value": "1490848.00"
    },
    "s_cat2_elem4": {
      "display_name": "Element 4",
      "value": "1490848.00"
    },
    "s_cat2_elem1": {
      "display_name": "Element 1",
      "value": "1490848.00"
    }
  },
  "value": "108833727.40"
},
"total_display_name": "Total",
"expenses": {
  "e_cat1": {
    "display_name": "Team Finance Category",
    "e_cat1_elem1": {
      "display_name": "Team Standard Effort",
      "value": "100.00~3232.50",
      "number_of_units": ""
    },
    "e_cat1_elem2": {
      "display_name": "Team Overtime Effort",
      "value": "1192680.00",
      "number_of_units": ""
    },
    "e_cat1_elem3": {
      "display_name": "Timesheet Standard Effort",
      "value": "1192680.00",
      "number_of_units": ""
    },
    "e_cat1_elem4": {
      "display_name": "Timesheet Overtime Effort",
      "value": "1192680.00",
      "number_of_units": ""
    }
  },
  "value": "16697660.00"
},
"display_name": "Cost",
```

```
"e_cat3": {
  "display_name": "Activity Resource Finance Category",
  "value": "17890240.00",
  "e_cat3_elem1": {
    "display_name": "Actual Standard Effort",
    "value": "3578048.00",
    "number_of_units": ""
  },
  "e_cat3_elem2": {
    "display_name": "Actual Overtime Effort",
    "value": "3578048.00",
    "number_of_units": ""
  },
  "e_cat3_elem3": {
    "display_name": "Timesheet Standard Effort",
    "value": "3578048.00",
    "number_of_units": ""
  },
  "e_cat3_elem4": {
    "display_name": "Timesheet Overtime Effort",
    "value": "3578048.00",
    "number_of_units": ""
  }
},
"e_cat2": {
  "display_name": "Activity Non-Resource Finance Category",
  "value": "17890240.00",
  "e_cat2_elem1": {
    "display_name": "Fixed",
    "value": "1192680.00"
  },
  "e_cat2_elem2": {
    "display_name": "Material",
    "value": "1192680.00"
  },
  "e_cat2_elem3": {
    "display_name": "Other",
    "value": "1192680.00"
  }
},
"value": "88258620.00",
"e_cat5": {
```

```
"display_name": "Operational Expense",
"e_cat5_elem4": {
  "display_name": "Timesheet Overtime Effort",
  "value": "3578048.00",
  "number_of_units": ""
},
"e_cat5_elem3": {
  "display_name": "Timesheet Standard Effort",
  "value": "3578048.00",
  "number_of_units": ""
},
"e_cat5_elem2": {
  "display_name": "Actual Overtime Effort",
  "value": "3578048.00",
  "number_of_units": ""
},
"e_cat5_elem1": {
  "display_name": "Actual Standard Effort",
  "value": "3578048.00",
  "number_of_units": ""
},
"value": "17890240.00"
},
"e_cat4": {
  "display_name": "Capital Expense",
  "value": "17890240.00",
  "e_cat4_elem4": {
    "display_name": "Timesheet Overtime Effort",
    "value": "3578048.00",
    "number_of_units": ""
  },
  "e_cat4_elem3": {
    "display_name": "Timesheet Standard Effort",
    "value": "3578048.00",
    "number_of_units": ""
  },
  "e_cat4_elem2": {
    "display_name": "Actual Overtime Effort",
    "value": "3578048.00",
    "number_of_units": ""
  },
  "e_cat4_elem1": {
```

```
        "display_name": "Actual Standard Effort",
        "value": "3578048.00",
        "number_of_units": ""
      }
    }
  }
},
"fin_edit_mode": {
  "display_name": "Finance Edit Mode",
  "value": "Y"
},
"finance_template": {
  "display_name": "finance_template",
  "value": "Default Global Finance Template"
},
"snapshot_updated_date": {
  "display_name": "snapshot_updated_date",
  "value": "Nov/24/2014"
},
"snapshot_updated_by": {
  "display_name": "snapshot_updated_by",
  "value": "Configurator, System"
},
"snapshot_created_by": {
  "display_name": "snapshot_created_by",
  "value": "Configurator, System"
},
"snapshot_desc": {
  "display_name": "snapshot_desc",
  "value": "This is a new Snapshot"
}
},
"project_number": {
  "display_name": "Project ID",
  "value": "10081"
}
}
}}
```

Delete Function

The delete function allows you to delete a project finance snapshot in EnterpriseTrack.

Invocation Syntax

The syntax for the invocation of the delete function is:

```
<api_session>?&request_data=<request_data>&request_format  
=<request_format>
```

Invocation Examples

The syntax for the delete function is:

```
<api_session>?&request_data=<content of  
project15_API_template.xml>&request_format=xml
```

```
<api_session>?&request_data=<content of  
project15_API_template.json>&request_format=json
```

Invocation Parameters

The parameters for the invocation of the delete function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
Request_data	String	Yes	<input_data>	Specifies the input data for deleting a project. For more details, see the Input Parameters.
Request_format	String	Yes	<request_format>	The data format of the request. Supported formats include: ▶ JSON ▶ XML

Input Parameters

The parameters described in the following table provide the data to be specified. This information should be provided in JSON or XML file format. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or constant	Description
<i>global_properties</i>	Object	Yes	<i>Not applicable</i>	This object lists the global settings for your EnterpriseTrack instance.
request_data	Object	Yes	Not applicable	This object lists a fixed set of request attributes. See the Request_Data Table below for more details.
application_data	Object	Yes	Not applicable	The application data that is to be created depends on the configuration of your EnterpriseTrack account, and therefore the data is dynamic. To work with application data that is most current and accurate in real time, it is recommended that you download the delete template from your EnterpriseTrack's Administration module. For more details, see Downloading CRUD Templates (on page 262).
Request_Data Table				
Request_type	String	Yes	delete	The name of the function.
Entity_type	String	Yes	Project_finance_snapshot	The entity being created.
Output_format	String	Yes		The data format of the output. Supported formats include: ▶ JSON ▶ XML
Value_delimiter	String	Yes		The delimiter to be used to parse all strings in the input and output. For example, or comma.

Input Examples

The following section provides examples of input data for the delete function in XML and JSON formats.

Input Example in XML Format

The following example of input data deletes a project finance snapshot.

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <request_data>
    <request_type>delete</request_type>
    <entity_type>project_finance_snapshot</entity_type>
    <output_format>xml</output_format>
    <value_delimiter>|</value_delimiter>
  </request_data>
  <app_data>
    <project_finance_snapshot>
      <project_number>
        <display_name>Project ID</display_name>
        <value>10023</value>
      </project_number>
      <project_name>
        <display_name>Project Name</display_name>
        <value/>
      </project_name>
      <finance_descriptor>
        <snapshot_descriptor>
          <snapshot_name>
            <display_name>Snapshot Name</display_name>
            <value> First_Test_Snapshot_1</value>
          </snapshot_name>
        </snapshot_descriptor>
      </finance_descriptor>
    </project_finance_snapshot>
  </app_data>
</root>
```

Input Example in JSON Format

The following example of input data deletes a project finance snapshot.

```
{
  "global_properties": {
    "char_set": "UTF-8",
    "date_format": "MMM/dd/yyyy",
    "language": "en",
    "api_version": "9.0"
  },
  "request_data": {
    "request_type": "delete",
    "entity_type": "project_finance_snapshot",
    "output_format": "json",
    "value_delimiter": "|"
  },
  "app_data": {
    "project_finance_snapshot": [{
      "project_number": {
        "display_name": "Project ID",
        "value": "10101"
      },
      "project_name": {
        "display_name": "Project Name",
        "value": ""
      },
      "finance_descriptor": {
        "snapshot_name": {
          "display_name": "Snapshot Name",
          "value": "First_Test_Snapshot_3"
        }
      }
    }]
  }
}
```

Output Examples

The following section provides examples of output data for the delete function in XML and JSON formats.

Output in XML Format

The following is an example of a successful deletion of a project finance snapshot in XML format:

```
<?xml version="1.0" encoding="UTF-8"?>
<root>
  <global_properties>
    <char_set>UTF-8</char_set>
    <date_format>yyyy/MM/dd</date_format>
    <language>en</language>
    <api_version>9.0</api_version>
  </global_properties>
  <response_data>
    <request_type>delete</request_type>
    <entity_type>project_finance_snapshot</entity_type>
    <response_code>0</response_code>
    <response_desc/>
  </response_data>
  <app_data/>
</root>
```

Output in JSON Format

The following is an example of a successful deletion of a project finance snapshot in JSON format:

```
{
  "global_properties": {
    "date_format": "MMM/dd/yyyy",
    "language": "en",
    "api_version": "9.0",
    "char_set": "UTF-8"
  },
  "response_data": {
    "response_desc": "",
    "request_type": "delete",
    "response_code": "0",
    "entity_type": "project_finance_snapshot"
  },
  "app_data": {"": []}
}
```

Downloading CRUD Templates

The **Data Import and Export** tab in the EnterpriseTrack Administration module enables you to download two types of templates in real-time for a project entity, based on your EnterpriseTrack account configuration. They are:

- ▶ Templates for the CRUD functions
- ▶ Templates for request data for the CRUD functions

To download the CRUD templates, proceed as follows:

- 1) Log in to EnterpriseTrack with valid credentials.
- 2) Select **Go To, Administration, Data Import and Export** tab, and then **Download Templates**.
- 3) Select values for the following fields from the corresponding drop-down list:
 - ▶ **Initiative:** Select the initiative for the project entity.
 - ▶ **Languages:** Select your language. English is displayed by default.
 - ▶ **Data Format:** Select the data format in which the function is to be rendered. Choices include: JSON, and XML.
 - ▶ **Type:** Select the type of template that is to be downloaded. Choices include:
 - **Download Template**
Generates CRUD templates in XML and JSON formats.
 - **Download Request for Template**
Generates a request template in XML and JSON formats for each CRUD function. These request templates can be used to specify input data in the relevant CRUD function.
- 4) Select the **Download** button for the corresponding function.

If you chose **Download Template**, a create_request, update_request, search_request and delete_request file will be generated.

If you chose **Download Request for Template**, the following files will be generated: create_request_template, update_request_template, search_request_template and delete_request_template. You can use these files to specify input data for the relevant CRUD function.

Timesheet Functions

The Timesheet Detail report can be rendered to extract timesheet data or timesheet corrections data using the following functions respectively.

- ▶ GetTimesheetData
- ▶ GetTimesheetCorrections

In This Section

getTimesheetData Function.....265

getTimesheetCorrections Function272

getTimesheetData Function

The getTimesheetData function extracts timesheet data for the Timesheet Detail report.

In This Section

Invocation Syntax.....265

Invocation Parameters.....265

Input Parameters.....266

Input Example in JSON Format270

Output272

Output example272

Invocation Syntax

The syntax for the invocation of the getTimesheetData function is as follows.

```
<api_session>?api_name=getTimesheetData&output_type=<output_type>
&input_data=<input_params>
```

Invocation Parameters

The parameters for the invocation of the GetTimesheetData function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or constant	Description
api_name	String	getTimesheetData	The name of the timesheet function..

Name	Data Type	Placeholder or constant	Description
output_type	String	<output_type>	Specifies the data format of the output. The report output can be generated in the following formats: ▶ CSV ▶ XLSX
Input_data	String	<input_params>	The location of the input parameters file. This value is case sensitive.

Input Parameters

The input parameters described in the following table provide the search criteria (filter data) needed to identify the data for the Timesheet Detail report. This information should be provided in JSON formatted data specified by <input_params>. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Value Required?	Placeholder or Constant	Description
report_format	String	Yes	Not applicable	The report format. Corresponds to the Show Actual Effort breakdown at day level filter on the report. Valid values include: ▶ Summary ▶ Daily (default)
timesheet_from_date	Date	Yes		The start date of the Timesheet Detail report. Corresponds to the Timesheet From Date filter on the report.
timesheet_to_date	Date	Yes		The end date of the Timesheet Detail report. Corresponds to the Timesheet To Date filter on the report.
report_project_time	String			Corresponds to the Show Project Overhead Categories filter on the report. Defaults to Yes.

Name	Data Type	Value Required?	Placeholder or Constant	Description
report_non_project_and_non_working_time	String			Corresponds to the Show Non-project Overhead Categories filter on the report. Defaults to Yes.
report_activity_time	String			Corresponds to the Show Activity Details filter on the report. Defaults to Yes
report_zero_effort_rows	String			Corresponds to the Suppress rows where Actual Total Effort is zero filter on the report. Defaults to No.
report_cost	String			Corresponds to the Show Cost filter on the report. Defaults to Yes.
report_disabled_categories	String			Corresponds to the Include disabled Time Reporting Categories filter on the report. Defaults to Yes.
timesheet_statuses	String			Corresponds to the Timesheet Status filter on the report. Specify as comma-separated values.
timesheet_submitter	Object	Yes		Corresponds to the Submitter filter on the report. Enter the first name or the last name. The first matching resource will be used. Only one submitter can be specified on the report.
timesheet_approver	Object	Yes		Corresponds to the Approver filter on the report. Enter the first name or the last name. The first matching resource will be used. Only one approver can be specified on the report.
pcs	String			Corresponds to the Initiative filter on the report. Specify comma-separated values.
Project_id	String	Yes		Corresponds to the Project ID filter on the report.

Name	Data Type	Value Required?	Placeholder or Constant	Description
project_name	String			Corresponds to the Project Name filter on the report.
project_keyword	String			Corresponds to the Keyword filter on the report. Specify comma-separated values.
project_status	String			Corresponds to the Project Status filter on the report. Specify comma-separated values.
project_org_descriptior->division	String			Corresponds to the Division filter on the report. Specify comma-separated values.
project_org_descriptior->business_unit	String			Corresponds to the Business Unit filter on the report. Specify comma-separated values.
project_org_descriptior->sub_business_unit	String			Corresponds to the Sub unit filter on the report. Specify comma-separated values.
project_org_descriptior->location	String			Corresponds to the Location filter on the report. Specify comma-separated values.
project_org_descriptior->region	String			Corresponds to the Region filter on the report. Specify comma-separated values.
resource_login_id	String			Corresponds to the Login ID filter on the report.
resource_email	String			Corresponds to the Email filter on the report.
resource_last_name	String			Corresponds to the Last Name filter on the report.
resource_title	String			Corresponds to the Access Profile filter on the report. Specify multiple Access Profiles as comma-separated values.
resource_area_of_expertise	String			Corresponds to the Area of Expertise filter on the report.

Name	Data Type	Value Required?	Placeholder or Constant	Description
resource_manager	Object			Corresponds to the Manager filter on the report. Enter the first name or the last name. The first matching resource will be used. Multiple managers can be specified.
program	String			Corresponds to the Program filter on the report. Specify multiple programs as comma-separated values.
resource_org_descriptor->division	String			Corresponds to the Division filter on the report. Specify multiple divisions as comma-separated values.
resource_org_descriptor->business_unit	String			Corresponds to the Business Unit filter on the report. Specify multiple business units as comma-separated values.
resource_org_descriptor->sub_business_unit	String			Corresponds to the Sub unit filter on the report. Specify multiple sub units as comma-separated values.
resource_org_descriptor->location	String			Corresponds to the Location filter on the report. Specify multiple locations as comma-separated values.
resource_org_descriptor->region	String			Corresponds to the Region filter on the report. Specify multiple regions as comma-separated values.
labor_expense_type	String			Corresponds to the Labor Expense Type filter on the report. Specify multiple labor expense types as comma-separated values.
labor_expense_category	String			Corresponds to the Labor Expense Category filter on the report. Specify multiple labor expense categories as comma-separated values.

Name	Data Type	Value Required?	Placeholder or Constant	Description
report_currency		Yes		Corresponds to the Reporting Currency filter on the report. Defaults to the system currency unit.
output_custom_field_list				Corresponds to the Output Custom Fields filter on the report. Specify a list of custom fields to be included in the report output. Multiple custom fields can be specified as comma-separated values.

Input Example in JSON Format

The syntax for the GetTimesheetData data input parameters is as follows.

```
{
  "global_properties":{"char_set":"ISO-8859-1",
    "date_format":"yyyy/MM/dd",
    "language":"",
    "api_version":"et-integration-api-1.0"
  },
  "application_data":
  {
    "timesheet_from_date":"2014/02/01",
    "timesheet_to_date":"2014/02/28",
    "timesheet_status":"Approved,Submitted",
    "timesheet_submitter":{"first_name":"","last_name":""},
    "timesheet_approver":{"first_name":"","last_name":""},
    "pcs":"",
    "project_id":"",
    "project_name":"",
    "project_keyword":"",
    "project_status":"",
    "project_org_descriptor":
  }
```

```
{
  "division": "",
  "business_unit": "",
  "sub_business_unit": "",
  "location": "",
  "region": ""
},
"resource_login_id": "",
"resource_email": "",
"resource_last_name": "",
"resource_title": "",
"resource_area_of_expertise": "",
"resource_manager":
  [
    {"first_name": "", "last_name": ""},
    {"first_name": "", "last_name": ""}
  ],
"resource_org_descriptor":
{
  "division": "",
  "business_unit": "",
  "sub_business_unit": "",
  "location": "",
  "region": ""
},
"rpt_currency": "",
"labor_expense_type": "",
"labor_expense_category": "",
"program": "",
"report_format": "Daily",
"report_project_time": "Yes",
"report_non_project_and_non_working_time": "Yes",
"report_activity_time": "Yes",
"report_zero_effort_rows": "No",
```

```
    "report_cost": "Yes",
    "report_disabled_categories": "Yes",
    "output_custom_field_list": ""
  }
}
```

Output

The Timesheet Detail report data is output in CSV or XLSX formats based on the filter criteria specified.

Output example

The CSV and XLS files from a successful GetTimesheetData function provide the data as two rows of data. The first row provides the names of the fields in the report, and the second row provide the values for the corresponding fields.

An exceptionally simplified excerpt from a CSV file is as follows:

```
Location,Location Chargeback Code,Region,Region Chargeback Code,Project
Id,Project Name,Project Manager,Project Type,Actual Standard
Effort,Actual Standard Cost,
Fairfield CT,80,North America,10,TimeSheet Data Report,John
Doe,IT,10,0,150000
```

getTimesheetCorrections Function

Extracts the Timesheet Detail Report with corrections data.

In This Section

Invocation Syntax	272
Invocation Parameters.....	273
Input Parameters.....	273
Input Example in JSON Format	273
Output	275
Output Example.....	275

Invocation Syntax

The syntax for the invocation of the getTimesheetCorrections function is as follows.

```
<api_session>?api_name=getTimesheetCorrections&output_type=<output_type>
&input_data=<input_params>
```

Invocation Parameters

The parameters for the invocation of the GetTimesheetCorrections function are described in the following table. Unless otherwise specified, all values are not case sensitive.

Name	Data Type	Placeholder or constant	Description
api_name	String	<i>GetTimesheetCorrections</i>	The name of the timesheet function.
output_type	String	<output_type>	Specifies the data format of the output. The report output can be generated in the following formats: ▶ CSV ▶ XLSX
Input_data	String	<input_params>	The location of the input parameters file. This value is case sensitive.

Input Parameters

Input parameters for the Timesheet Detail Report with Corrections are identical to those listed in the table for the Timesheet Detail Report using the getTimesheetData API. Additionally, the following input parameters listed below must be specified for extracting the Timesheet Detail Report with Corrections.

Name	Data Type	Value Required?	Placeholder or Constant	Description
correction_from_date	Date	Yes	Not applicable	Corresponds to the Correction From Date filter on the report.
correction_to_date	Date	Yes	Not applicable	Corresponds to the Correction To Date filter on the report.

Input Example in JSON Format

The syntax for the GetTimesheetCorrections input parameters is as follows.

```
{
  "global_properties":{"char_set":"ISO-8859-1",
    "date_format":"yyyy/MM/dd",
    "language":"","
    "api_version":"et-integration-api-1.0"
```

```
},
"application_data":
{
    "timesheet_from_date":"2014/02/01",
    "timesheet_to_date":"2014/02/28",
    "correction_from_date":"2014/02/20",
    "correction_to_date":"2014/02/20",
    "timesheet_status":"Approved,Submitted",
    "timesheet_submitter":{"first_name":"","last_name":""},
    "timesheet_approver":{"first_name":"","last_name":""},
    "pcs":"","
    "project_id":"","
    "project_name":"","
    "project_keyword":"","
    "project_status":"","
    "project_org_descriptor":
    {
        "division":"","
        "business_unit":"","
        "sub_business_unit":"","
        "location":"","
        "region":""
    },
    "resource_login_id":"","
    "resource_email":"","
    "resource_last_name":"","
    "resource_title":"","
    "resource_area_of_expertise":"","
    "resource_manager":
    [
        {"first_name":"","last_name":""},
        {"first_name":"","last_name":""}
    ],
    "resource_org_descriptor":

```

```

{
    "division": "",
    "business_unit": "",
    "sub_business_unit": "",
    "location": "",
    "region": ""
},
"rpt_currency": "",
"labor_expense_type": "",
"labor_expense_category": "",
"program": "",
"report_format": "Daily",
"report_project_time": "Yes",
"report_non_project_and_non_working_time": "Yes",
"report_activity_time": "Yes",
"report_zero_effort_rows": "No",
"report_cost": "Yes",
"report_disabled_categories": "Yes",
"output_custom_field_list": ""
}
}

```

Output

The Timesheet Detail Report with corrections data is output in CSV or XLSX formats based on the filter criteria specified.

Output Example

The CSV and XLSX files from a successful GetTimesheetCorrections function provide the data as two rows of data. The first row provides the names of the fields in the report, and the second row provide the values for the corresponding fields.

An exceptionally simplified excerpt from a CSV file is as follows:

```

Location,Location Chargeback Code,Region,Region Chargeback Code,Project
Id,Project Name,Project Manager,Project Type,Actual Standard
Effort,Actual Standard Cost,
Fairfield CT,80,North America,10,TimeSheet Data Report,John
Doe,IT,10,0,150000

```

Preconfigured Remote Reports

EnterpriseTrack includes a collection of advanced reports that extract data to be used for integration purposes. This data can be used periodically, and programmatically, to import EnterpriseTrack updates to other third-party applications such as PeopleSoft, Oracle, Asset Management, ITSM systems, and so forth.

Several formats for the report output are supported, including Microsoft Excel, PDF and CSV.

Invoking Remote Reports

The syntax for the invocation of the Remote Reports is as follows.

```
https://<server>/Sitewand/Submission/<account_name>/etws/ReportRPC?  
login_id=<login_id>&report_name=<report_path>
```

where:

Placeholder	Description
<server>	Specifies the IP address or hostname of the server hosting your EnterpriseTrack instance.
<account_name>	Specifies the account name (or company name) of your EnterpriseTrack instance.
<login_id>	Specifies your EnterpriseTrack login ID. The case sensitivity for this value conforms to that used by your EnterpriseTrack system.
<pwd>	Specifies the password corresponding to your EnterpriseTrack login ID. The case sensitivity for this value conforms to that used by your EnterpriseTrack system.

Note: The /Sitewand/Submission portion of the URL *is* case sensitive. Unless otherwise noted, all other text in the URL *is not* case sensitive.

The following is an example with values for the placeholders:

```
https://ABC.example.com/Sitewand/Submission/CompanyDEF/etws/ReportRPC?  
login_id=jSmith&report_name=/Reports/Global/Reports/  
Listing Reports/Idea Listing
```

Input

Parameters cannot be passed to customize or filter the reports at the time of execution. The report should be set up with proper default filters prior to the execution of the remote report.

Output

The output of the function call is a stream of content type determined by the report's output. If the report output is HTML, then the output is a text/html stream. If the report output is Excel, then the output is a binary stream of content type application/vnd.ms-excel.

Note: Parameters cannot be passed for this functionality. The reports should be set up with the desired default filters prior to the execution of this function.

Result Code	Result Reason	Description	Corrective Action
ERR_APPROVED_TIME_SHEET_EXISTS	Once a timesheet has been approved, no updates can be made.	Timesheet already approved	From an interactive EnterpriseTrack session, re-open the timesheet. Then the update can be made from either an interactive session or using the Integration API.
ERR_AUTHENTICATION	You specified invalid login information.	Login failed	Specify valid (case-sensitive) values for both of the following:
	Login ID is required. Please provide a value.	Login ID required	▶ user_login_id=<login_id> ▶ password=<pwd>
	Password is required. Please provide a value.	Password required	Specify valid (case-sensitive) values for both of the following:
	The login ID/password combination is not valid. Please try again.	Password expired	Reset or obtain a new password.

Result Code	Result Reason	Description	Corrective Action
	Unauthorized access to the integrate-dispatcher.	Not logged in	Verify that you are logged in successfully before executing the API.
ERR_AUTHORIZATION_POLICY	Authorization policy cannot be blank.	Authorization policy required	Specify one of the following values: ▶ authorize_with_login_resource ▶ authorize_with_record_locator_resource ▶ authorize_with_authorization_policy_given_resource
	The authorization policy code passed is invalid, it should have the value as "authorize_with_login_resource", "authorize_with_record_locator_resource", or "authorize_with_authorization_policy_given_resource".	Invalid authorization policy	
	The user credentials (provided in Authorization_Policy_User_Source) do not match to any existing user in the system.	Could not authorize user	Specify valid (case-sensitive) values for both of the following: ▶ user_login_id=<login_id> ▶ password=<pwd>
	The user credentials provided does not have permission to Execute APIs as Proxy.	Insufficient permission for authorized user	Obtain the necessary permission(s).
	In case of timesheet operation, the authorization resource should be same as resource whose effort is being updated.	Users did not match	Log in with the credentials of the resource whose effort is being updated .

Result Code	Result Reason	Description	Corrective Action
ERR_BLANK_WORK_ASSIGNMENT_DESC	The activity name is missing.	Activity name required	Specify a value for activity name.
ERR_BLANK_WORK_ASSIGNMENT_ID	The external work assignment ID is missing.	External work assignment ID required	Specify a value for external work assignment ID.
ERR_BLANK_WORK_ASSIGNMENT_TYPE	The activity type is missing.	Activity type required	Specify a value for activity type.
ERR_CANNOT_ASSIGN_RESOURCE_AS_ACTIVITY_OWNER	Resource can not be assign as activity owner due to allowed role restriction for this activity.	Unable to assign given resource as activity owner.	Verify that the resource role has the necessary permission(s), or retry with a different role and resource.
ERR_INVALID_ACTIVITY_PERCENT_COMPLETION	The activity percent completion should have a valid numeric value between 0 and 100.	Invalid activity percent completion value	Verify that you specified an integer or floating point value between 0 and 100 (inclusive).
ERR_INVALID_ACTIVITY_STATUS	The activity status passed is not valid.	Invalid activity status	Determine what values are configured for your EnterpriseTrack application. Then, specify one of the configured values.
ERR_INVALID_AET_FOR_ACTIVITY	The activity AET should be one of Timesheet, Resource Level (Detail), or Resource Level (Summary).	Invalid activity effort type	Specify one of the following values: ▶ Timesheet ▶ Resource Level (Detail) ▶ Resource Level (Summary)
ERR_INVALID_API	The Integration function name that you specified is not valid.	Invalid function name	If you have not successfully logged in, all function names (other than Login) are

Result Code	Result Reason	Description	Corrective Action
	Integration function name is required. Please provide a value.	API function name required.	considered invalid. If your login succeeded, specify one of the following values: ▶ Logout ▶ GetActivityAssignments ▶ UpdateResourceEffort ▶ UpdateActivity ▶ GetFinanceData
ERR_INVALID_API_VERSION	The API version information you specified is not supported.	Invalid API version number	Specify the following value as et-integration-api-1.0.
	API version is missing. Please provide valid API version.	API version required.	
ERR_INVALID_CONFIG	The API '{api_name}', does not have any configured permission.	Invalid permission.	Obtain the necessary permission(s).
ERR_INVALID_CONFIG_ACTIVITY_TYPE	The associated project initiative does not have the activity type configured as "EXTERNAL_WA."	No matching external work assignment.	Contact your EnterpriseTrack administrator and request that the application be configured to allow integration activities.
	The work assignment type passed is invalid. It should have the value as INTERNAL or EXTERNAL.	Invalid work assignment type.	Contact your EnterpriseTrack administrator and request that the application be configured to allow integration activities.
ERR_INVALID_DATA	The format of your JSON data is not correct.	Invalid data format.	Verify that: ▶ The format you specified

Result Code	Result Reason	Description	Corrective Action
	Input data is required. Please provide a value.	Input data required.	corresponds to the format of the data you provided. ▶ The format of the data you provided conforms to the standard for that format. ▶ You have actually provided data, or included enough data to identify a unique result.
	The information provided did not identify a unique category for timesheet data.	More category data required.	
	Invalid location for char-set. It should be first attribute in global-properties.	Invalid char-set location.	
	Invalid char_set. System supports the format: {encoding_format}	Unsupported char-set	
	The date cannot be blank.	Date required	Specify a value for the date.
ERR_INVALID_DATE_FORMAT	The format of the data you provided does not correspond to the format specified in the global_properties object.	Invalid date format	Verify that the format you specified corresponds to the format of the data you provided.
	The date format cannot be blank.	Date format required	Specify a value for the date format.
ERR_INVALID_DATE_PERIOD	Data cannot be entered for the week earlier than project start week.	Date before project start date	Verify that the: ▶ Date is not earlier than the project start date. ▶ Date is not after the project realization date.
	Data cannot be entered for the week later than project realization week.	Date after project realization date	
ERR_INVALID_DIVISION	The values given for project {divisionUIName} field are not valid.	Invalid division	Specify a valid division.

Result Code	Result Reason	Description	Corrective Action
ERR_INVALID_FUNCTIONAL_AREA	The values given for project {functionalAreaUIName} field are not valid.	Invalid functional area	Specify a valid functional area.
ERR_INVALID_INCLUDE_CLOSED_WA	The include closed work assignment (include_closed_wa) passed is invalid. It should have the value of TRUE or FALSE.	Invalid include closed work assignment	Specify one of the following values: ▶ TRUE ▶ FALSE
ERR_INVALID_INCLUDE_EXTERNAL_WA	The include external work assignment (include_external_wa) passed is invalid. It should have the value of TRUE or FALSE.	Invalid include external work assignment	Specify one of the following values: ▶ TRUE ▶ FALSE
ERR_INVALID_LANGUAGE	The language ID passed is not supported.	Invalid language ID	Specify a valid language ID.
ERR_INVALID_LOCATION	The values given for project {locationUIName} field are not valid.	Invalid location	Specify a valid location.
ERR_INVALID_MAX_ROWS	The data provided for input max rows is not a valid number.	Invalid max rows	Verify that the max rows value is a positive integer.
ERR_INVALID_OPERATION_TYPE	The Work Assignment type passed is invalid, it should have the value as INTERNAL or EXTERNAL.	Invalid work assignment type	Specify one of the following values: ▶ INTERNAL ▶ EXTERNAL

Result Code	Result Reason	Description	Corrective Action
	The work assignment type passed is invalid. It should have the value of INTERNAL, EXTERNAL, PROJECT_TIME_CATEG, NON_PROJECT_TIME_CATEG, or NON_WORKING_TIME_CATEG.	Invalid work assignment type	Specify one of the following values: ▶ INTERNAL ▶ EXTERNAL_PROJECT_TIME_CATEG ▶ NON_PROJECT_TIME_CATEG ▶ NON_WORKING_TIME_CATEG
ERR_INVALID_OVERTIME_HOURS	Overtime hours is invalid. Please provide only positive numbers.	Invalid overtime hours format	Verify that: ▶ The value for the number of hours is a positive integer. ▶ Overtime hours do not exceed the total hours.
	The number of overtime hours cannot exceed the number of total hours.	Overtime hours exceed total hours	
ERR_INVALID_PCS	The values given for project "PCS" field are not valid.	Invalid PCS	Specify a valid PCS.
ERR_INVALID_PHASE	The values given for project {phaseUIName} field are not valid.	Invalid phase	Specify a valid phase.
ERR_INVALID_PROCESSES	The values given for project {processUIName} field are not valid.	Invalid process	Specify a valid process.
ERR_INVALID_PRODUCTS	The values given for project {productUIName} field are not valid.	Invalid product(s)	Specify a valid product(s).
ERR_INVALID_PROJECT	The project information you specified does not match any existing project.	No matching project found	Verify that all information you specified corresponds to an existing project.

Result Code	Result Reason	Description	Corrective Action
ERR_INVALID_PROJECT_ON_TIME_STATUS	The values given for project on time status field are not valid.	Invalid project on time status	Specify a valid project on time status.
ERR_INVALID_PROJECT_SOURCE	The values given for project {projectSourceUIName} field are not valid.	Invalid project source	Specify a valid project source.
ERR_INVALID_PROJECT_STATUS	The values given for project status field are not valid.	Invalid status	Determine what values are configured for your EnterpriseTrack application. Then, specify one of the configured values.
ERR_INVALID_PROJECT_TYPE	The values given for project type field are not valid.	Invalid project type	Specify a valid project type.
ERR_INVALID_REGION	The values given for project {regionUIName} field are not valid.	Invalid region	Specify a valid region.
ERR_INVALID_RESOURCE	The resource information you specified does not match any existing resource.	No matching resource found	Verify that all information you specified corresponds to an existing resource.
ERR_INVALID_ROADMAP	The values given for project {roadmapUIName} field are not valid.	Invalid roadmap	Specify a valid roadmap.
ERR_INVALID_ROLE	The role information you specified does not match any existing role.	No matching role found	Verify that all information you specified corresponds to an existing role.

Result Code	Result Reason	Description	Corrective Action
ERR_INVALID_TEAM_MEMBER	The combination of role and resource information you specified cannot be matched.	No match found for this combination of role and resource	Verify that all information you specified exists for the resource you specified.
ERR_INVALID_TOTAL_HOURS	Total hours is invalid. Please provide only positive numbers.	Invalid total hours format	Verify that the value for the number of hours is a positive integer.
ERR_INVALID_TOTAL_OVERTIME_HOURS	The data provided for the total or overtime hours is not an integer	Invalid total overtime hours format	Verify that the value for the number of hours is a positive integer.
ERR_INVALID_UPDATE_ACTION_CODE	The update action code that you specified is not supported.	Invalid update action code	Specify one of the following values: ► REPLACE ► INCREMENT
ERR_NO_DATA_TO_UPDATE	Both percent completion and activity status cannot be blank.	No data to update	Specify values for the percent completion and activity status.
ERR_NON_EXISTING_ACTIVITY	The activity ID you specified does not exist	Activity ID not found	Verify that you have specified a valid activity ID.
ERR_PERMISSION	Your credentials do not include permission to perform revisions to one (or more) of the following : <permission_name>	Insufficient permission.	Obtain the necessary permission(s) from your EnterpriseTrack administrator.
ERR_PROJECT_CLOSED	The current project status does not allow this operation.	Project closed.	Verify that you specified an Open (or equivalent) project.

Result Code	Result Reason	Description	Corrective Action
ERR_PROJECT_LOCKED	Updates are not allowed on this project since it has been locked for MS Project updates.	Project locked for MSP update	Once the synchronization is complete, you can try again.
ERR_RESOURCE_NOT_ACTIVITY_OWNER	The work assignment you specified is assigned to a different resource.	Resource not assigned to this activity	Verify that the activity you specified is assigned to the resource you specified.
ERR_TIMESHEET_ENTRY_NOT_ALLOWED	Timesheets are not enabled for this resource.	Timesheet disabled for this resource	Verify that timesheets are enabled for the resource.
	A manager is not assigned to the resource, therefore timesheets cannot be created.	Manager not assigned to resource	From an interactive EnterpriseTrack session, assign a manager to the resource, then try again.
	Timesheets are not enabled for this resource.	Resource cannot enter timesheet	From an interactive EnterpriseTrack session, enable the Can enter timesheet option for this resource or the project team.
	The user does not have adequate permission to enter Non Project/Non Working Time.	The user does not have permission for Non Project/Non Working Time	Obtain the necessary permission(s).
	The resource does not have permission to enter project level time.	Insufficient permission	Obtain the necessary permission(s).

Result Code	Result Reason	Description	Corrective Action
	Your credentials do not include permission to either create or edit timesheets for this resource.	Insufficient permission	Obtain the necessary permission(s).
	The resource does not have permission to enter activity level time.	Insufficient permission	Obtain the necessary permission(s).
ERR_TIMESHEET_EXCESS_HOURS	The number of hours cannot exceed the daily limit configured in EnterpriseTrack.	Number of hours exceeds daily limit	Verify the: ▶ Number of hours currently reported for the resource ▶ Maximum number of hours configured for your EnterpriseTrack instance
ERR_UNSUPPORTED_INPUT_FORMAT	The input format that you specified is not supported.	Invalid input format	Specify a valid data format for the following: input_type=<in_type> See the function documentation for supported formats.
	Input type is required. Please provide a value.	Input format required	Specify a value for the input type.
ERR_UNSUPPORTED_OUTPUT_FORMAT	The output format that you specified is not supported.	Invalid output format	Specify a valid data format for the following: output_type=<out_type> See the function documentation for supported formats.
	Output type is required. Please provide a value.	Output format required	Specify a value for the output type.

Result Code	Result Reason	Description	Corrective Action
ERR_UPDATE_ACTIVITY	(Message corresponds to that found in the EnterpriseTrack UI.)	Failed to update activity	Follow the recommendation.
ERR_WORK_ASSIGNMENT_LOCKED	Updates are permitted only to Open work assignments.	Closed work assignment	Verify that you have specified a work assignment that is open (or the equivalent).
SUCCESS	(Null)	Successful execution of Integration function.	No action required.
SYSTEM_ERROR	Operation has failed. Contact the system administrator.	Unexpected system error	Please contact system administrator.

Legal Notices

Oracle Instantis EnterpriseTrack API Reference Guide

Copyright © 2000, 2015, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software or hardware and documentation may provide access to or information on content, products and services from third-parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.