

Gateway Documentation - ELFacilityService
Oracle FLEXCUBE Universal Banking
Release FCELCM_1.1.13_FCUBS12_0_87_1.0
[August] [2014]



Table Of Contents

1. BACKGROUND	1
2. ELFacilityService	2
2.1. FacilityAuthorize	2
2.1.1. GE-FacilityAuthorize-Req-Full-MSG.xsd	2
2.1.2. GE-FacilityAuthorize-Req-IO-MSG.xsd	50
2.1.3. GE-FacilityAuthorize-Res-Full-MSG.xsd	97
2.1.4. GE-FacilityAuthorize-Res-PK-MSG.xsd	147
2.2. FacilityClose	238
2.2.1. GE-FacilityClose-Req-Full-MSG.xsd	238
2.2.2. GE-FacilityClose-Req-IO-MSG.xsd	286
2.2.3. GE-FacilityClose-Res-Full-MSG.xsd	333
2.2.4. GE-FacilityClose-Res-PK-MSG.xsd	383
2.3. FacilityCreate	474
2.3.1. GE-FacilityCreate-Req-Full-MSG.xsd	474
2.3.2. GE-FacilityCreate-Req-IO-MSG.xsd	522
2.3.3. GE-FacilityCreate-Res-Full-MSG.xsd	569
2.3.4. GE-FacilityCreate-Res-PK-MSG.xsd	618
2.4. FacilityDelete	709
2.4.1. GE-FacilityDelete-Req-Full-MSG.xsd	709
2.4.2. GE-FacilityDelete-Req-IO-MSG.xsd	757
2.4.3. GE-FacilityDelete-Res-Full-MSG.xsd	804
2.4.4. GE-FacilityDelete-Res-PK-MSG.xsd	854
2.5. FacilityQuery	945
2.5.1. GE-FacilityExecuteQuery-Req-IO-MSG.xsd	945
2.5.2. GE-FacilityExecuteQuery-Res-Full-MSG.xsd	952
2.6. FacilityModify	1002
2.6.1. GE-FacilityModify-Req-Full-MSG.xsd	1002
2.6.2. GE-FacilityModify-Req-IO-MSG.xsd	1050
2.6.3. GE-FacilityModify-Res-Full-MSG.xsd	1097
2.6.4. GE-FacilityModify-Res-PK-MSG.xsd	1146
2.7. FacilityReopen	1237
2.7.1. GE-FacilityReopen-Req-Full-MSG.xsd	1237
2.7.2. GE-FacilityReopen-Req-IO-MSG.xsd	1285
2.7.3. GE-FacilityReopen-Res-Full-MSG.xsd	1332
2.7.4. GE-FacilityReopen-Res-PK-MSG.xsd	1382
2.8. FacilityTransferAuthorize	1473
2.8.1. GE-FacilityTransferAuthorize-Req-Full-MSG.xsd	1473
2.8.2. GE-FacilityTransferAuthorize-Req-IO-MSG.xsd	1490
2.8.3. GE-FacilityTransferAuthorize-Res-Full-MSG.xsd	1497
2.8.4. GE-FacilityTransferAuthorize-Res-PK-MSG.xsd	1516
2.9. FacilityTransferClose	1524
2.9.1. GE-FacilityTransferClose-Req-Full-MSG.xsd	1524
2.9.2. GE-FacilityTransferClose-Req-IO-MSG.xsd	1541
2.9.3. GE-FacilityTransferClose-Res-Full-MSG.xsd	1548
2.9.4. GE-FacilityTransferClose-Res-PK-MSG.xsd	1567
2.10. FacilityTransferCreate	1575
2.10.1. GE-FacilityTransferCreate-Req-Full-MSG.xsd	1575
2.10.2. GE-FacilityTransferCreate-Req-IO-MSG.xsd	1592
2.10.3. GE-FacilityTransferCreate-Res-Full-MSG.xsd	1609
2.10.4. GE-FacilityTransferCreate-Res-PK-MSG.xsd	1628
2.11. FacilityTransferDelete	1636
2.11.1. GE-FacilityTransferDelete-Req-Full-MSG.xsd	1636
2.11.2. GE-FacilityTransferDelete-Req-IO-MSG.xsd	1653
2.11.3. GE-FacilityTransferDelete-Res-Full-MSG.xsd	1660

2.11.4. GE-FacilityTransferDelete-Res-PK-MSG.xsd	1679
2.12. FacilityTransferModify	1687
2.12.1. GE-FacilityTransferModify-Req-Full-MSG.xsd	1687
2.12.2. GE-FacilityTransferModify-Req-IO-MSG.xsd	1704
2.12.3. GE-FacilityTransferModify-Res-Full-MSG.xsd	1721
2.12.4. GE-FacilityTransferModify-Res-PK-MSG.xsd	1740
2.13. FacilityTransferQuery	1748
2.13.1. GE-FacilityTransferQuery-Req-IO-MSG.xsd	1748
2.13.2. GE-FacilityTransferQuery-Res-Full-MSG.xsd	1755
2.14. FacilityTransferReopen	1774
2.14.1. GE-FacilityTransferReopen-Req-Full-MSG.xsd	1774
2.14.2. GE-FacilityTransferReopen-Req-IO-MSG.xsd	1791
2.14.3. GE-FacilityTransferReopen-Res-Full-MSG.xsd	1798
2.14.4. GE-FacilityTransferReopen-Res-PK-MSG.xsd	1817

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.

The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in ELFacilityService of EL-Module

2.ELFacilityService

ELFacilityServiceELFacilityService

2.1.FacilityAuthorize

Authorisation Of Facility

2.1.1.GE-FacilityAuthorize-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT
REPORTINGAMOUNT
AVAILABLEAMOUNT
DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT

EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT

VALUEDATE
BOOKDATE
MODNO
FacilityPowerPocketLimits
FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO
FacilityCharge
FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO
FacilityCovenant
FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO
FacilityExposure
FACILITYID
EXPOSUREID
MODNO
FacilitySystemRestriction
FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT
FACILITYAMOUNTPOOLCCY
PERCENTAGEOFPOOL
PERCENTAGEOFCONTRACT
MODNO

FacilityExposureRestriction

FACILITY
EXPOSURE

FacilityMandate

MANDATETYPE
MINPERAVAL

FacilityUDEValues

FACILITY
UDEID
UDEVALUE
RATECODE
CODEUSAGE

UDFDETAILS

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTNAMT

Attribute	Description
Name	EXCEPTNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description	
Name	FACILITYID		
Datatype	Number		
Description			
Attributes	Attribute		Description
	minOccurs	0	

[TOP](#)**EXTSYSTEM**

Attribute		Description	
Name	EXTSYSTEM		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	50	

[TOP](#)**MODNO**

Attribute		Description	
Name	MODNO		
Datatype	Number		
Description			
Attributes	Attribute		Description
	minOccurs	0	

[TOP](#)**FacilityPoolLink**

Attribute		Description	
Name	FacilityPoolLink		
Datatype			
Description			
Attributes	Attribute		Description
	maxOccurs	unbounded	
	minOccurs	0	

[TOP](#)**LIABID**

Attribute		Description	
Name	LIABID		
Datatype	String		
Description			

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.1.2.GE-FacilityAuthorize-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD

NETTINGREQUIRED

UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD

MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
FACILITYID
LIMITDATE
LIMITAMOUNT
FacilityTenorRestriction
FACILITYID
TENOR
TENORMNEMONIC
LIMIT
UTILISATION
FROMPRV
TONEXT
LIABBRANH
FacilityCustomerRestriction
FACILITYID
CUSTOMERNO
FacilityBranchRestriction
FACILITYID
BRANCHCODE
FacilityProductRestriction
FACILITYID
PRODUCTCODE
FacilityCurrencyRestriction
FACILITYID
CCY
FacilityValueDateDetails
FACILITYID
LIMITAMOUNT
VALUEDATE
BOOKDATE
MODNO
FacilityPowerPocketLimits
FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT

ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT

FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description	This is the parent node for each parameter in the additional node.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

REVOLVINGLINE

Attribute	Description
Name	REVOLVINGLINE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description
Name	UNUTLCHARGEPERCT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
	Restrictions	Description
Restrictions	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description
------------------	--------------------

Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description
------------------	--------------------

Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

2.1.3.GE-FacilityAuthorize-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

MODNO

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN

COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO
FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE

FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_ERROR_RESP

ERROR
 ECODE
 EDESC

FCUBS_WARNING_RESP

WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-IO

Attribute	Description	
Name	Facility-IO	

Datatype	
Description	

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

Facility-Full

Attribute	Description
Name	Facility-Full
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTED AMOUNT

Attribute	Description	
Name	UNCOLLECTED AMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description
Name	FUNDED

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

PROCESSNO

Attribute		Description
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERREFNO

Attribute		Description
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute		Description
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute		Description
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute		Description
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description
Name	APPROVEDAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description
------------------	--------------------

Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description
------------------	--------------------

Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description
------------------	--------------------

Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**COVENANTID**

Attribute		Description
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MANDATORY**

Attribute		Description
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**PERIODCITY**

Attribute		Description
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)**PERIOD**

Attribute		Description
Name	PERIOD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)**FCUBS_WARNING_RESP**

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute		Description
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute		Description
Name	WCODE	

Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.1.4.GE-FacilityAuthorize-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-PK

LIABID

LINECODE

LINESERIAL

LIABNO

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT
AVAILABLEAMOUNT
DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE

DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT
FACILITYAMOUNTPOOLCCY
PERCENTAGEOFPOOL
PERCENTAGEOFCONTRACT
MODNO
FacilityExposureRestriction
FACILITY
EXPOSURE
FacilityMandate
MANDATETYPE
MINPERAVAL
FacilityUDEValues
FACILITY
UDEID
UDEVALUE
RATECODE
CODEUSAGE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Facility-Full
LINECODE
LINESERIAL
LIABNO
CCYREST
LINECCY
REVOLVINGLINE
LINESTARTDATE
LINEEXPIRYDATE
LASTNEWUTILDATE
AVAILABILITYFLAG
INTERNALREMARKS
LIMITAMOUNT
COLLATERALCONTRIBUTION
UNCOLLECTEDFUNDSLIMIT
REPORTINGAMOUNT
AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
 FacilityExposureRestriction
 FACILITY
 EXPOSURE
 FacilityMandate
 MANDATETYPE
 MINPERAVAL
 FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-PK

Attribute	Description
Name	Facility-PK

Datatype	
Description	

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO

Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTXNAMT

Attribute	Description	
Name	EXCEPTXNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description
Name	MAINLINEID

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description
------------------	--------------------

Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTACC

Attribute	Description				
Name	POWERPKTACC				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTAMT

Attribute	Description				
Name	POWERPKTAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTDT

Attribute	Description				
Name	POWERPKTDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)**CONSOLIDATEAMT**

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityCharge**

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ADMINCHARGETYPE**

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ADMINCHARGEPERCT

Attribute		Description
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGEAMT

Attribute		Description
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGETYPE

Attribute		Description
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UTLCHARGEPERCT

Attribute		Description
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGEAMT

Attribute		Description
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description
------------------	--------------------

Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description
------------------	--------------------

Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilitySystemRestriction**

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityUDEValues

Attribute		Description
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	
	maxOccurs	unbounded
	minOccurs	0

FACILITY

Attribute		Description
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	
	minOccurs	0

UDEID

Attribute		Description
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	30

UDEVALUE

Attribute		Description
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	
	minOccurs	0

RATECODE

Attribute		Description
Name	RATECODE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTXNAMT

Attribute	Description
Name	EXCEPTXNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTDLIMIT

Attribute	Description	
Name	DAYLIGHTDLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description	
Name	FACILITYID		
Datatype	Number		
Description			
Attributes	Attribute		Description
	minOccurs	0	

[TOP](#)**EXTSYSTEM**

Attribute		Description	
Name	EXTSYSTEM		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	50	

[TOP](#)**MODNO**

Attribute		Description	
Name	MODNO		
Datatype	Number		
Description			
Attributes	Attribute		Description
	minOccurs	0	

[TOP](#)**FacilityPoolLink**

Attribute		Description	
Name	FacilityPoolLink		
Datatype			
Description			
Attributes	Attribute		Description
	maxOccurs	unbounded	
	minOccurs	0	

[TOP](#)**LIABID**

Attribute		Description	
Name	LIABID		
Datatype	String		
Description			

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.2.FacilityClose

Closure Of Facility

2.2.1.GE-FacilityClose-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
FacilityExposureRestriction
 FACILITY
 EXPOSURE
FacilityMandate
 MANDATETYPE
 MINPERAVAL
FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTNAMT

Attribute	Description
Name	EXCEPTNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTDLIMIT

Attribute	Description	
Name	DAYLIGHTDLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.2.2.GE-FacilityClose-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD

NETTINGREQUIRED

UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD

MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO
FacilityPowerPocketLimits
 FACILITYID
 POWERPKTACC
 POWERPKTAMT
 POWERPKTDT

ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT

FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description	This is the parent node for each parameter in the additional node.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

REVOLVINGLINE

Attribute	Description
Name	REVOLVINGLINE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description				
Name	AVAILABLEAMOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFFIRSTOD

Attribute	Description				
Name	DATEOFFIRSTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFLASTOD

Attribute	Description				
Name	DATEOFLASTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

NETTINGREQUIRED

Attribute	Description				
Name	NETTINGREQUIRED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

UNADVISED

Attribute	Description				
Name	UNADVISED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description
Name	UNUTLCHARGEPERCT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityExposure**

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
	Restrictions	Description
Restrictions	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description
------------------	--------------------

Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description
------------------	--------------------

Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

2.2.3.GE-FacilityClose-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

MODNO

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN

COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO
FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE

FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_ERROR_RESP

ERROR
 ECODE
 EDESC

FCUBS_WARNING_RESP

WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-IO

Attribute	Description	
Name	Facility-IO	

Datatype	
Description	

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

Facility-Full

Attribute	Description
Name	Facility-Full
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTED AMOUNT

Attribute	Description	
Name	UNCOLLECTED AMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description
Name	FUNDED

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**PROCESSNO**

Attribute		Description	
Name	PROCESSNO		
Datatype	Number		
Description			
Attributes	Attribute		Description
	minOccurs	0	

[TOP](#)**USERREFNO**

Attribute		Description	
Name	USERREFNO		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	50	

[TOP](#)**CONVERSIONDATE**

Attribute		Description	
Name	CONVERSIONDATE		
Datatype	Date		
Description			
Attributes	Attribute		Description
	minOccurs	0	

[TOP](#)**TENORRESTTYPE**

Attribute		Description	
Name	TENORRESTTYPE		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	A,D	

[TOP](#)**CUSTOMERRESTTYPE**

Attribute		Description	
Name	CUSTOMERRESTTYPE		
Datatype	String		
Description			

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description
------------------	--------------------

Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CCY**

Attribute		Description
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityValueDateDetails**

Attribute		Description
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIMITAMOUNT**

Attribute		Description
Name	LIMITAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description
------------------	--------------------

Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description
------------------	--------------------

Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	This indicates the code for the error encountered.

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)**FCUBS_WARNING_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.2.4.GE-FacilityClose-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-PK

LIABID

LINECODE

LINESERIAL

LIABNO

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT
AVAILABLEAMOUNT
DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE

DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
FacilityExposureRestriction
 FACILITY
 EXPOSURE
FacilityMandate
 MANDATETYPE
 MINPERAVAL
FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
Facility-Full
 LINECODE
 LINESERIAL
 LIABNO
 CCYREST
 LINECCY
 REVOLVINGLINE
 LINESTARTDATE
 LINEEXPIRYDATE
 LASTNEWUTILDATE
 AVAILABILITYFLAG
 INTERNALREMARKS
 LIMITAMOUNT
 COLLATERALCONTRIBUTION
 UNCOLLECTEDFUNDSLIMIT
 REPORTINGAMOUNT
 AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
 FacilityExposureRestriction
 FACILITY
 EXPOSURE
 FacilityMandate
 MANDATETYPE
 MINPERAVAL
 FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-PK

Attribute	Description	
Name	Facility-PK	

Datatype	
Description	

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO

Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTXNAMT

Attribute	Description	
Name	EXCEPTXNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description
Name	MAINLINEID

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description
------------------	--------------------

Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTACC

Attribute	Description				
Name	POWERPKTACC				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTAMT

Attribute	Description				
Name	POWERPKTAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTDT

Attribute	Description				
Name	POWERPKTDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)**CONSOLIDATEAMT**

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityCharge**

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ADMINCHARGETYPE**

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ADMINCHARGEPERCT

Attribute		Description
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGEAMT

Attribute		Description
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGETYPE

Attribute		Description
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UTLCHARGEPERCT

Attribute		Description
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGEAMT

Attribute		Description
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description
------------------	--------------------

Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description
------------------	--------------------

Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityUDEValues

Attribute		Description
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITY

Attribute		Description
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UDEID

Attribute		Description
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

UDEVALUE

Attribute		Description
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

RATECODE

Attribute		Description
Name	RATECODE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTXNAMT

Attribute	Description
Name	EXCEPTXNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	This indicates the code for the error encountered.

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.3.FacilityCreate

Creation Of Facility

2.3.1.GE-FacilityCreate-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
FacilityExposureRestriction
 FACILITY
 EXPOSURE
FacilityMandate
 MANDATETYPE
 MINPERAVAL
FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTNAMT

Attribute	Description
Name	EXCEPTNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTDLIMIT

Attribute	Description	
Name	DAYLIGHTDLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.3.2.GE-FacilityCreate-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD

NETTINGREQUIRED

UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD

MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
FACILITYID
LIMITDATE
LIMITAMOUNT
FacilityTenorRestriction
FACILITYID
TENOR
TENORMNEMONIC
LIMIT
UTILISATION
FROMPRV
TONEXT
LIABBRANH
FacilityCustomerRestriction
FACILITYID
CUSTOMERNO
FacilityBranchRestriction
FACILITYID
BRANCHCODE
FacilityProductRestriction
FACILITYID
PRODUCTCODE
FacilityCurrencyRestriction
FACILITYID
CCY
FacilityValueDateDetails
FACILITYID
LIMITAMOUNT
VALUEDATE
BOOKDATE
MODNO
FacilityPowerPocketLimits
FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT

ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT

FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	String						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

SOURCE_USERID

Attribute	Description						
Name	SOURCE_USERID						
Datatype	String						
Description	This is the user id in the Source system who is performing the action.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description	This is the parent node for each parameter in the additional node.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

REVOLVINGLINE

Attribute	Description
Name	REVOLVINGLINE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description				
Name	AVAILABLEAMOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFFIRSTOD

Attribute	Description				
Name	DATEOFFIRSTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFLASTOD

Attribute	Description				
Name	DATEOFLASTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

NETTINGREQUIRED

Attribute	Description				
Name	NETTINGREQUIRED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

UNADVISED

Attribute	Description				
Name	UNADVISED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description
Name	USERDEFINESTATUS

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description
Name	UNUTLCHARGEPERCT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityExposure**

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
	Restrictions	Description
Restrictions	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description
------------------	--------------------

Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description
------------------	--------------------

Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

2.3.3.GE-FacilityCreate-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD

NETTINGREQUIRED

UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD

PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO
FacilityPowerPocketLimits
 FACILITYID
 POWERPKTACC

POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID

FACILITYCURRENCY
FACILITYAMOUNT
FACILITYAMOUNTPOOLCCY
PERCENTAGEOFPOOL
PERCENTAGEOFCONTRACT
MODNO

FacilityExposureRestriction

FACILITY
EXPOSURE

FacilityMandate

MANDATETYPE
MINPERAVAL

FacilityUDEValues

FACILITY
UDEID
UDEVALUE
RATECODE
CODEUSAGE

UDFDETAILS

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_ERROR_RESP

ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String

Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-Full

Attribute	Description
Name	Facility-Full

Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTXNAMT

Attribute	Description	
Name	EXCEPTXNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description
Name	MAINLINEID

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.3.4.GE-FacilityCreate-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-PK

LIABID

LINECODE

LINESERIAL

LIABNO

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT
AVAILABLEAMOUNT
DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE

DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT
FACILITYAMOUNTPOOLCCY
PERCENTAGEOFPOOL
PERCENTAGEOFCONTRACT
MODNO
FacilityExposureRestriction
FACILITY
EXPOSURE
FacilityMandate
MANDATETYPE
MINPERAVAL
FacilityUDEValues
FACILITY
UDEID
UDEVALUE
RATECODE
CODEUSAGE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Facility-Full
LINECODE
LINESERIAL
LIABNO
CCYREST
LINECCY
REVOLVINGLINE
LINESTARTDATE
LINEEXPIRYDATE
LASTNEWUTILDATE
AVAILABILITYFLAG
INTERNALREMARKS
LIMITAMOUNT
COLLATERALCONTRIBUTION
UNCOLLECTEDFUNDSLIMIT
REPORTINGAMOUNT
AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
 FacilityExposureRestriction
 FACILITY
 EXPOSURE
 FacilityMandate
 MANDATETYPE
 MINPERAVAL
 FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-PK

Attribute	Description	
Name	Facility-PK	

Datatype	
Description	

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO

Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTXNAMT

Attribute	Description	
Name	EXCEPTXNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description				
Name	EXCEPBREACH				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

CATEGORY

Attribute	Description				
Name	CATEGORY				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

EXTERNALREFNO

Attribute	Description				
Name	EXTERNALREFNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

PROCESSNO

Attribute	Description				
Name	PROCESSNO				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description
Name	MAINLINEID

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**RECSTAT**

Attribute	Description	
Name	RECSTAT	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description
------------------	--------------------

Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTACC

Attribute	Description				
Name	POWERPKTACC				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTAMT

Attribute	Description				
Name	POWERPKTAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTDT

Attribute	Description				
Name	POWERPKTDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)**CONSOLIDATEAMT**

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityCharge**

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ADMINCHARGETYPE**

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ADMINCHARGEPERCT

Attribute		Description
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGEAMT

Attribute		Description
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGETYPE

Attribute		Description
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UTLCHARGEPERCT

Attribute		Description
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGEAMT

Attribute		Description
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description
------------------	--------------------

Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description
------------------	--------------------

Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilitySystemRestriction**

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityUDEValues

Attribute		Description
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITY

Attribute		Description
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UDEID

Attribute		Description
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

UDEVALUE

Attribute		Description
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

RATECODE

Attribute		Description
Name	RATECODE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTNAMT

Attribute	Description
Name	EXCEPTNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.4.FacilityDelete

Deletion Of Facility

2.4.1.GE-FacilityDelete-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
FacilityExposureRestriction
 FACILITY
 EXPOSURE
FacilityMandate
 MANDATETYPE
 MINPERAVAL
FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTXNAMT

Attribute	Description
Name	EXCEPTXNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.4.2.GE-FacilityDelete-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD

NETTINGREQUIRED

UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD

MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
FACILITYID
LIMITDATE
LIMITAMOUNT
FacilityTenorRestriction
FACILITYID
TENOR
TENORMNEMONIC
LIMIT
UTILISATION
FROMPRV
TONEXT
LIABBRANH
FacilityCustomerRestriction
FACILITYID
CUSTOMERNO
FacilityBranchRestriction
FACILITYID
BRANCHCODE
FacilityProductRestriction
FACILITYID
PRODUCTCODE
FacilityCurrencyRestriction
FACILITYID
CCY
FacilityValueDateDetails
FACILITYID
LIMITAMOUNT
VALUEDATE
BOOKDATE
MODNO
FacilityPowerPocketLimits
FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT

ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT

FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	String						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

SOURCE_USERID

Attribute	Description						
Name	SOURCE_USERID						
Datatype	String						
Description	This is the user id in the Source system who is performing the action.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description	This is the parent node for each parameter in the additional node.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

LINE SERIAL

Attribute	Description	
Name	LINE SERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

REVOLVINGLINE

Attribute	Description
Name	REVOLVINGLINE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description				
Name	AVAILABLEAMOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFFIRSTOD

Attribute	Description				
Name	DATEOFFIRSTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFLASTOD

Attribute	Description				
Name	DATEOFLASTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

NETTINGREQUIRED

Attribute	Description				
Name	NETTINGREQUIRED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

UNADVISED

Attribute	Description				
Name	UNADVISED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description
Name	UNUTLCHARGEPERCT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityExposure**

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
	Restrictions	Description
Restrictions	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description
------------------	--------------------

Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description
------------------	--------------------

Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

2.4.3.GE-FacilityDelete-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LIABID

LINECODE

LINESERIAL

LIABNO

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT
AVAILABLEAMOUNT
DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE

DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE

BOOKDATE
MODNO
FacilityPowerPocketLimits
FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO
FacilityCharge
FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO
FacilityCovenant
FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO
FacilityExposure
FACILITYID
EXPOSUREID
MODNO
FacilitySystemRestriction
FACILITYID
EXTSYSTEM
MODNO
FacilityPoolLink

LIABID
 POOLID
 TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_ERROR_RESP

ERROR
 ECODE
 EDESC

FCUBS_WARNING_RESP

WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO
Datatype	
Description	

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

Facility-Full

Attribute	Description
Name	Facility-Full
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description
Name	LASTNEWUTILDATE

Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description
-----------	-------------

Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATEDTODAY

Attribute	Description				
Name	AMOUNTREINSTATEDTODAY				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description				
Name	UNCOLLECTEDAMOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

EXCESSTENOR

Attribute	Description				
Name	EXCESSTENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

LIABBR

Attribute	Description				
Name	LIABBR				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description
Name	AVAILMENTDATE

Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description
Name	COMMITMENTSETTLBRN

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**FROMPRV**

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description
------------------	--------------------

Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description				
Name	CCY				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

FacilityValueDateDetails

Attribute	Description						
Name	FacilityValueDateDetails						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

LIMITAMOUNT

Attribute	Description				
Name	LIMITAMOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

VALUEDATE

Attribute	Description				
Name	VALUEDATE				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
	Restrictions	Description
Restrictions	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description
------------------	--------------------

Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description
------------------	--------------------

Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description	Indicates the warning encountered.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.4.4.GE-FacilityDelete-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD

NETTINGREQUIRED

UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD

MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO
FacilityPowerPocketLimits
 FACILITYID
 POWERPKTACC
 POWERPKTAMT
 POWERPKTDT

ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT

FACILITYAMOUNTPOOLCCY
PERCENTAGEOFPOOL
PERCENTAGEOFCONTRACT
MODNO

FacilityExposureRestriction

FACILITY
EXPOSURE

FacilityMandate

MANDATETYPE
MINPERAVAL

FacilityUDEValues

FACILITY
UDEID
UDEVALUE
RATECODE
CODEUSAGE

UDFDETAILS

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

Facility-PK

LIABID
LINECODE
LINESERIAL
LIABNO

Facility-Full

LINECODE
LINESERIAL
LIABNO
CCYREST
LINECCY
REVOLVINGLINE
LINESTARTDATE
LINEEXPIRYDATE
LASTNEWUTILDATE
AVAILABILITYFLAG
INTERNALREMARKS
LIMITAMOUNT
COLLATERALCONTRIBUTION
UNCOLLECTEDFUNDSLIMIT
REPORTINGAMOUNT
AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
 FacilityExposureRestriction
 FACILITY
 EXPOSURE
 FacilityMandate
 MANDATETYPE
 MINPERAVAL
 FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO

Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTXNAMT

Attribute	Description	
Name	EXCEPTXNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description
Name	MAINLINEID

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description
------------------	--------------------

Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTACC

Attribute	Description				
Name	POWERPKTACC				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTAMT

Attribute	Description				
Name	POWERPKTAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTDT

Attribute	Description				
Name	POWERPKTDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ADMINCHARGEPERCT

Attribute		Description
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGEAMT

Attribute		Description
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGETYPE

Attribute		Description
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UTLCHARGEPERCT

Attribute		Description
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGEAMT

Attribute		Description
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description
------------------	--------------------

Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description
------------------	--------------------

Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilitySystemRestriction**

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityUDEValues

Attribute		Description
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITY

Attribute		Description
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UDEID

Attribute		Description
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

UDEVALUE

Attribute		Description
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

RATECODE

Attribute		Description
Name	RATECODE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

Facility-PK

Attribute	Description	
Name	Facility-PK	
Datatype		
Description		

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

Facility-Full

Attribute	Description
Name	Facility-Full
Datatype	
Description	

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

LINECCY

Attribute	Description
Name	LINECCY

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTXNAMT

Attribute	Description
Name	EXCEPTXNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.5.FacilityQuery

Query Of Facility

2.5.1.GE-FacilityExecuteQuery-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LIABID

LINECODE

LINESERIAL

LIABNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String

Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO

Datatype	
Description	

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

2.5.2.GE-FacilityExecuteQuery-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LIABID

LINECODE

LINESERIAL

LIABNO

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT
AVAILABLEAMOUNT
DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE

DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE

BOOKDATE
MODNO
FacilityPowerPocketLimits
FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO
FacilityCharge
FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO
FacilityCovenant
FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO
FacilityExposure
FACILITYID
EXPOSUREID
MODNO
FacilitySystemRestriction
FACILITYID
EXTSYSTEM
MODNO
FacilityPoolLink

LIABID
 POOLID
 TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_ERROR_RESP

ERROR
 ECODE
 EDESC

FCUBS_WARNING_RESP

WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO
Datatype	
Description	

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

Facility-Full

Attribute	Description
Name	Facility-Full
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	

Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description
-----------	-------------

Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATEDTODAY

Attribute	Description	
Name	AMOUNTREINSTATEDTODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description
Name	AVAILMENTDATE

Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description
Name	COMMITMENTSETTLBRN

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description
------------------	--------------------

Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description				
Name	CCY				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

FacilityValueDateDetails

Attribute	Description						
Name	FacilityValueDateDetails						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

LIMITAMOUNT

Attribute	Description				
Name	LIMITAMOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

VALUEDATE

Attribute	Description				
Name	VALUEDATE				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityExposure**

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
	Restrictions	Description
Restrictions	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description
------------------	--------------------

Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description
------------------	--------------------

Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description	Indicates the warning encountered.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.6.FacilityModify

Amendment Of Facility

2.6.1.GE-FacilityModify-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
FacilityExposureRestriction
 FACILITY
 EXPOSURE
FacilityMandate
 MANDATETYPE
 MINPERAVAL
FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTXNAMT

Attribute	Description
Name	EXCEPTXNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.6.2.GE-FacilityModify-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD

NETTINGREQUIRED

UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD

MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
FACILITYID
LIMITDATE
LIMITAMOUNT
FacilityTenorRestriction
FACILITYID
TENOR
TENORMNEMONIC
LIMIT
UTILISATION
FROMPRV
TONEXT
LIABBRANH
FacilityCustomerRestriction
FACILITYID
CUSTOMERNO
FacilityBranchRestriction
FACILITYID
BRANCHCODE
FacilityProductRestriction
FACILITYID
PRODUCTCODE
FacilityCurrencyRestriction
FACILITYID
CCY
FacilityValueDateDetails
FACILITYID
LIMITAMOUNT
VALUEDATE
BOOKDATE
MODNO
FacilityPowerPocketLimits
FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT

ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT

FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	String						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

SOURCE_USERID

Attribute	Description						
Name	SOURCE_USERID						
Datatype	String						
Description	This is the user id in the Source system who is performing the action.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description	This is the parent node for each parameter in the additional node.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description				
Name	AVAILABLEAMOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFFIRSTOD

Attribute	Description				
Name	DATEOFFIRSTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFLASTOD

Attribute	Description				
Name	DATEOFLASTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

NETTINGREQUIRED

Attribute	Description				
Name	NETTINGREQUIRED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

UNADVISED

Attribute	Description				
Name	UNADVISED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description
Name	USERDEFINESTATUS

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description
Name	UNUTLCHARGEPERCT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityExposure**

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
	Restrictions	Description
Restrictions	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description
------------------	--------------------

Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description
------------------	--------------------

Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

2.6.3.GE-FacilityModify-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD

NETTINGREQUIRED

UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD

PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO
FacilityPowerPocketLimits
 FACILITYID
 POWERPKTACC

POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID

FACILITYCURRENCY
FACILITYAMOUNT
FACILITYAMOUNTPOOLCCY
PERCENTAGEOFPOOL
PERCENTAGEOFCONTRACT
MODNO

FacilityExposureRestriction

FACILITY
EXPOSURE

FacilityMandate

MANDATETYPE
MINPERAVAL

FacilityUDEValues

FACILITY
UDEID
UDEVALUE
RATECODE
CODEUSAGE

UDFDETAILS

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_ERROR_RESP

ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String

Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-Full

Attribute	Description
Name	Facility-Full

Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTXNAMT

Attribute	Description	
Name	EXCEPTXNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description	
Name	MAINLINEID	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description
Name	FacilitySchedules
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.6.4.GE-FacilityModify-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-PK

LIABID

LINECODE

LINESERIAL

LIABNO

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT
AVAILABLEAMOUNT
DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE

DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
FacilityExposureRestriction
 FACILITY
 EXPOSURE
FacilityMandate
 MANDATETYPE
 MINPERAVAL
FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
Facility-Full
 LINECODE
 LINESERIAL
 LIABNO
 CCYREST
 LINECCY
 REVOLVINGLINE
 LINESTARTDATE
 LINEEXPIRYDATE
 LASTNEWUTILDATE
 AVAILABILITYFLAG
 INTERNALREMARKS
 LIMITAMOUNT
 COLLATERALCONTRIBUTION
 UNCOLLECTEDFUNDSLIMIT
 REPORTINGAMOUNT
 AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
 FacilityExposureRestriction
 FACILITY
 EXPOSURE
 FacilityMandate
 MANDATETYPE
 MINPERAVAL
 FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-PK

Attribute	Description	
Name	Facility-PK	

Datatype	
Description	

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO

Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTXNAMT

Attribute	Description	
Name	EXCEPTXNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description	
Name	MAINLINEID	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description
------------------	--------------------

Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTACC

Attribute	Description				
Name	POWERPKTACC				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTAMT

Attribute	Description				
Name	POWERPKTAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTDT

Attribute	Description				
Name	POWERPKTDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)**CONSOLIDATEAMT**

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityCharge**

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ADMINCHARGETYPE**

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ADMINCHARGEPERCT

Attribute		Description
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGEAMT

Attribute		Description
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGETYPE

Attribute		Description
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UTLCHARGEPERCT

Attribute		Description
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGEAMT

Attribute		Description
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description
------------------	--------------------

Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description
------------------	--------------------

Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilitySystemRestriction**

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTNAMT

Attribute	Description
Name	EXCEPTNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.7.FacilityReopen

Reopen Facility

2.7.1.GE-FacilityReopen-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
FacilityExposureRestriction
 FACILITY
 EXPOSURE
FacilityMandate
 MANDATETYPE
 MINPERAVAL
FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTNAMT

Attribute	Description
Name	EXCEPTNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description
Name	BRANCHRESTTYPE

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTDLIMIT

Attribute	Description	
Name	DAYLIGHTDLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description	
Name	FACILITYID		
Datatype	Number		
Description			
Attributes	Attribute		Description
	minOccurs	0	

[TOP](#)**EXTSYSTEM**

Attribute		Description	
Name	EXTSYSTEM		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	50	

[TOP](#)**MODNO**

Attribute		Description	
Name	MODNO		
Datatype	Number		
Description			
Attributes	Attribute		Description
	minOccurs	0	

[TOP](#)**FacilityPoolLink**

Attribute		Description	
Name	FacilityPoolLink		
Datatype			
Description			
Attributes	Attribute		Description
	maxOccurs	unbounded	
	minOccurs	0	

[TOP](#)**LIABID**

Attribute		Description	
Name	LIABID		
Datatype	String		
Description			

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.7.2.GE-FacilityReopen-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD

NETTINGREQUIRED

UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD

MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
FACILITYID
LIMITDATE
LIMITAMOUNT
FacilityTenorRestriction
FACILITYID
TENOR
TENORMNEMONIC
LIMIT
UTILISATION
FROMPRV
TONEXT
LIABBRANH
FacilityCustomerRestriction
FACILITYID
CUSTOMERNO
FacilityBranchRestriction
FACILITYID
BRANCHCODE
FacilityProductRestriction
FACILITYID
PRODUCTCODE
FacilityCurrencyRestriction
FACILITYID
CCY
FacilityValueDateDetails
FACILITYID
LIMITAMOUNT
VALUEDATE
BOOKDATE
MODNO
FacilityPowerPocketLimits
FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT

ACTION
CONSOLIDATEAMT
MODNO
FacilityCharge
FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO
FacilityCovenant
FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO
FacilityExposure
FACILITYID
EXPOSUREID
MODNO
FacilitySystemRestriction
FACILITYID
EXTSYSTEM
MODNO
FacilityPoolLink
LIABID
POOLID
TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT

FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	String						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

SOURCE_USERID

Attribute	Description						
Name	SOURCE_USERID						
Datatype	String						
Description	This is the user id in the Source system who is performing the action.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
	minOccurs	0			
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
	minOccurs	0			
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description	This is the parent node for each parameter in the additional node.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description				
Name	AVAILABLEAMOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFFIRSTOD

Attribute	Description				
Name	DATEOFFIRSTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

DATEOFLASTOD

Attribute	Description				
Name	DATEOFLASTOD				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

NETTINGREQUIRED

Attribute	Description				
Name	NETTINGREQUIRED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

UNADVISED

Attribute	Description				
Name	UNADVISED				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description
Name	USERDEFINESTATUS

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description
Name	UNUTLCHARGEPERCT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
	Restrictions	Description
Restrictions	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description
------------------	--------------------

Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description
------------------	--------------------

Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description
------------------	--------------------

Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

2.7.3.GE-FacilityReopen-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-IO

MODNO

Facility-Full

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT

AVAILABLEAMOUNT

DATEOFFIRSTOD

DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN

COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO
FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID
TYPE

FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO

FacilityExposureRestriction

FACILITY
 EXPOSURE

FacilityMandate

MANDATETYPE
 MINPERAVAL

FacilityUDEValues

FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE

UDFDETAILS

FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_ERROR_RESP

ERROR
 ECODE
 EDESC

FCUBS_WARNING_RESP

WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO

Datatype	
Description	

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

Facility-Full

Attribute	Description
Name	Facility-Full
Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**DATEOFLASTOD**

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**NETTINGREQUIRED**

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**UNADVISED**

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**TRANSFERAMOUNT**

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**DSPEFFLINEAMOUNT**

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTED AMOUNT

Attribute	Description	
Name	UNCOLLECTED AMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description
Name	FUNDED

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTNAMT

Attribute	Description	
Name	EXCEPTNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**PROCESSNO**

Attribute		Description
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**USERREFNO**

Attribute		Description
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**CONVERSIONDATE**

Attribute		Description
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TENORRESTTYPE**

Attribute		Description
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)**CUSTOMERRESTTYPE**

Attribute		Description
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description
Name	APPROVEDAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

[TOP](#)

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		

Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description
------------------	--------------------

Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CCY**

Attribute		Description
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityValueDateDetails**

Attribute		Description
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIMITAMOUNT**

Attribute		Description
Name	LIMITAMOUNT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	

Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description
------------------	--------------------

Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description
------------------	--------------------

Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXTSYSTEM

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)**FCUBS_WARNING_RESP**

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute		Description
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute		Description
Name	WCODE	

Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.7.4.GE-FacilityReopen-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Facility-PK

LIABID

LINECODE

LINESERIAL

LIABNO

Facility-IO

LINECODE

LINESERIAL

LIABNO

CCYREST

LINECCY

REVOLVINGLINE

LINESTARTDATE

LINEEXPIRYDATE

LASTNEWUTILDATE

AVAILABILITYFLAG

INTERNALREMARKS

LIMITAMOUNT

COLLATERALCONTRIBUTION

UNCOLLECTEDFUNDSLIMIT

REPORTINGAMOUNT
AVAILABLEAMOUNT
DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE

DAYLIGHTODLIMIT
COMMITMENTPRODUCT
COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
FACILITYBRANCHCODE
FACILITYID
FACILITYCURRENCY
FACILITYAMOUNT
FACILITYAMOUNTPOOLCCY
PERCENTAGEOFPOOL
PERCENTAGEOFCONTRACT
MODNO
FacilityExposureRestriction
FACILITY
EXPOSURE
FacilityMandate
MANDATETYPE
MINPERAVAL
FacilityUDEValues
FACILITY
UDEID
UDEVALUE
RATECODE
CODEUSAGE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Facility-Full
LINECODE
LINESERIAL
LIABNO
CCYREST
LINECCY
REVOLVINGLINE
LINESTARTDATE
LINEEXPIRYDATE
LASTNEWUTILDATE
AVAILABILITYFLAG
INTERNALREMARKS
LIMITAMOUNT
COLLATERALCONTRIBUTION
UNCOLLECTEDFUNDSLIMIT
REPORTINGAMOUNT
AVAILABLEAMOUNT

DATEOFFIRSTOD
DATEOFLASTOD
NETTINGREQUIRED
UNADVISED
TRANSFERAMOUNT
DSPEFFLINEAMOUNT
AMOUNTUTILISED TODAY
AMOUNTREINSTATED TODAY
UNCOLLECTEDAMOUNT
EXCESSTENOR
UTILISATION
LIABBR
COLLATERALPCT
BRN
LMTAMTBASIS
FUNDED
AVAILMENTDATE
EXCEPTXNAMT
USERDEFINESTATUS
BLOCKAMOUNT
TANKEDUTIL
NETTINGAMOUNT
EXCEPBREACH
CATEGORY
EXTERNALREFNO
PROCESSNO
USERREFNO
CONVERSIONDATE
TENORRESTTYPE
CUSTOMERRESTTYPE
PRODUCTRESTTYPE
BRANCHRESTTYPE
CCYRESTTYPE
EXTSYSTEMRESTTYPE
LIABID
MAINLINEID
DESCRIPTION
SHADOWLIMIT
APPROVEDAMT
DAYLIGHTLIMIT
USERDEFSTATCHANGEDDT
EXPRESTTYPE
DAYLIGHTODLIMIT
COMMITMENTPRODUCT

COMMITMENTSETTLBRN
COMMITMENTSETTLACC
BULKPMTREQD
PPCREFNO
PPCPROJECTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FacilitySchedules
 FACILITYID
 LIMITDATE
 LIMITAMOUNT
FacilityTenorRestriction
 FACILITYID
 TENOR
 TENORMNEMONIC
 LIMIT
 UTILISATION
 FROMPRV
 TONEXT
 LIABBRANH
FacilityCustomerRestriction
 FACILITYID
 CUSTOMERNO
FacilityBranchRestriction
 FACILITYID
 BRANCHCODE
FacilityProductRestriction
 FACILITYID
 PRODUCTCODE
FacilityCurrencyRestriction
 FACILITYID
 CCY
FacilityValueDateDetails
 FACILITYID
 LIMITAMOUNT
 VALUEDATE
 BOOKDATE
 MODNO

FacilityPowerPocketLimits

FACILITYID
POWERPKTACC
POWERPKTAMT
POWERPKTDT
ACTION
CONSOLIDATEAMT
MODNO

FacilityCharge

FACILITYID
ADMINCHARGETYPE
ADMINCHARGEPERCT
ADMINCHARGEAMT
UTLCHARGETYPE
UTLCHARGEPERCT
UTLCHARGEAMT
UNUTLCHARGETYPE
UNUTLCHARGEPERCT
UNUTLCHARGEAMT
MODNO

FacilityCovenant

FACILITYID
COVENANTID
MANDATORY
PERIODCITY
PERIOD
STARTDATE
GRACEDAYS
REVISIONDATE
NOTICEDAYS
COVENANTREFNO
REMARKS
MODNO

FacilityExposure

FACILITYID
EXPOSUREID
MODNO

FacilitySystemRestriction

FACILITYID
EXTSYSTEM
MODNO

FacilityPoolLink

LIABID
POOLID

TYPE
 FACILITYBRANCHCODE
 FACILITYID
 FACILITYCURRENCY
 FACILITYAMOUNT
 FACILITYAMOUNTPOOLCCY
 PERCENTAGEOFPOOL
 PERCENTAGEOFCONTRACT
 MODNO
 FacilityExposureRestriction
 FACILITY
 EXPOSURE
 FacilityMandate
 MANDATETYPE
 MINPERAVAL
 FacilityUDEValues
 FACILITY
 UDEID
 UDEVALUE
 RATECODE
 CODEUSAGE
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

Facility-PK

Attribute	Description	
Name	Facility-PK	

Datatype	
Description	

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

Facility-IO

Attribute	Description
Name	Facility-IO

Datatype	
Description	

[TOP](#)

LINECODE

Attribute	Description	
Name	LINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

LINESERIAL

Attribute	Description	
Name	LINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIABNO

Attribute	Description	
Name	LIABNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

CCYREST

Attribute	Description	
Name	CCYREST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINECCY

Attribute	Description	
Name	LINECCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

AVAILABILITYFLAG

Attribute	Description	
Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

[TOP](#)

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPTXNAMT

Attribute	Description	
Name	EXCEPTXNAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description				
Name	EXCEPBREACH				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

CATEGORY

Attribute	Description				
Name	CATEGORY				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

EXTERNALREFNO

Attribute	Description				
Name	EXTERNALREFNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

PROCESSNO

Attribute	Description				
Name	PROCESSNO				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

MAINLINEID

Attribute	Description
Name	MAINLINEID

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description	
Name	TENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TENORMNEMONIC

Attribute	Description	
Name	TENORMNEMONIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

LIMIT

Attribute	Description	
Name	LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMPRV

Attribute	Description	
Name	FROMPRV	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TONEXT

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBRANH

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

FacilityCustomerRestriction

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

CUSTOMERNO

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description
------------------	--------------------

Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description				
Name	LIMITAMOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

VALUEDATE

Attribute	Description				
Name	VALUEDATE				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

BOOKDATE

Attribute	Description				
Name	BOOKDATE				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description						
Name	FacilityPowerPocketLimits						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

FACILITYID

Attribute	Description				
Name	FACILITYID				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTACC

Attribute	Description				
Name	POWERPKTACC				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTAMT

Attribute	Description				
Name	POWERPKTAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

POWERPKTDT

Attribute	Description				
Name	POWERPKTDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ADMINCHARGEPERCT

Attribute		Description
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ADMINCHARGEAMT

Attribute		Description
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGETYPE

Attribute		Description
Name	UTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UTLCHARGEPERCT

Attribute		Description
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTLCHARGEAMT

Attribute		Description
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description
------------------	--------------------

Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description
------------------	--------------------

Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXPOSUREID**

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilitySystemRestriction**

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute	Description	
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPoolLink

Attribute	Description	
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

Facility-Full

Attribute	Description	
Name	Facility-Full	
Datatype		
Description		

[TOP](#)

LINECODE

Attribute	Description				
Name	LINECODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

[TOP](#)

LINESERIAL

Attribute	Description				
Name	LINESERIAL				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

LIABNO

Attribute	Description				
Name	LIABNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

CCYREST

Attribute	Description				
Name	CCYREST				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

LINECCY

Attribute	Description
Name	LINECCY
Datatype	String

Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

REVOLVINGLINE

Attribute	Description	
Name	REVOLVINGLINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

LINESTARTDATE

Attribute	Description	
Name	LINESTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LINEEXPIRYDATE

Attribute	Description	
Name	LINEEXPIRYDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LASTNEWUTILDATE

Attribute	Description	
Name	LASTNEWUTILDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABILITYFLAG

Attribute	Description
------------------	--------------------

Name	AVAILABILITYFLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

INTERNALREMARKS

Attribute	Description	
Name	INTERNALREMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COLLATERALCONTRIBUTION

Attribute	Description	
Name	COLLATERALCONTRIBUTION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNCOLLECTEDFUNDSLIMIT

Attribute	Description	
Name	UNCOLLECTEDFUNDSLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REPORTINGAMOUNT

Attribute	Description	
Name	REPORTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AVAILABLEAMOUNT

Attribute	Description	
Name	AVAILABLEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFFIRSTOD

Attribute	Description	
Name	DATEOFFIRSTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DATEOFLASTOD

Attribute	Description	
Name	DATEOFLASTOD	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGREQUIRED

Attribute	Description	
Name	NETTINGREQUIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UNADVISED

Attribute	Description	
Name	UNADVISED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DSPEFFLINEAMOUNT

Attribute	Description	
Name	DSPEFFLINEAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTUTILISED TODAY

Attribute	Description	
Name	AMOUNTUTILISED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AMOUNTREINSTATED TODAY

Attribute	Description	
Name	AMOUNTREINSTATED TODAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UNCOLLECTEDAMOUNT

Attribute	Description	
Name	UNCOLLECTEDAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCESSTENOR

Attribute	Description	
Name	EXCESSTENOR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

UTILISATION

Attribute	Description	
Name	UTILISATION	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

LIABBR

Attribute	Description	
Name	LIABBR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

COLLATERALPCT

Attribute	Description	
Name	COLLATERALPCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	A,L,M,

FUNDED

Attribute	Description	
Name	FUNDED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AVAILMENTDATE

Attribute	Description	
Name	AVAILMENTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXCEPTXNAMT

Attribute	Description
Name	EXCEPTXNAMT

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERDEFINESTATUS

Attribute	Description	
Name	USERDEFINESTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BLOCKAMOUNT

Attribute	Description	
Name	BLOCKAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TANKEDUTIL

Attribute	Description	
Name	TANKEDUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NETTINGAMOUNT

Attribute	Description	
Name	NETTINGAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXCEPBREACH

Attribute	Description	
Name	EXCEPBREACH	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CATEGORY

Attribute	Description	
Name	CATEGORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

EXTERNALREFNO

Attribute	Description	
Name	EXTERNALREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

PROCESSNO

Attribute	Description	
Name	PROCESSNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CONVERSIONDATE

Attribute	Description	
Name	CONVERSIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TENORRESTTYPE

Attribute	Description	
Name	TENORRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

CUSTOMERRESTTYPE

Attribute	Description	
Name	CUSTOMERRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

PRODUCTRESTTYPE

Attribute	Description	
Name	PRODUCTRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

BRANCHRESTTYPE

Attribute	Description	
Name	BRANCHRESTTYPE	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

CCYRESTTYPE

Attribute	Description	
Name	CCYRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

EXTSYSTEMRESTTYPE

Attribute	Description	
Name	EXTSYSTEMRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

MAINLINEID

Attribute	Description	
Name	MAINLINEID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

SHADOWLIMIT

Attribute	Description	
Name	SHADOWLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

APPROVEDAMT

Attribute	Description	
Name	APPROVEDAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

USERDEFSTATCHANGEDDT

Attribute	Description	
Name	USERDEFSTATCHANGEDDT	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPRESTTYPE

Attribute	Description	
Name	EXPRESTTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

[TOP](#)

DAYLIGHTODLIMIT

Attribute	Description	
Name	DAYLIGHTODLIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMMITMENTPRODUCT

Attribute	Description	
Name	COMMITMENTPRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLBRN

Attribute	Description	
Name	COMMITMENTSETTLBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

COMMITMENTSETTLACC

Attribute	Description	
Name	COMMITMENTSETTLACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

BULKPMTREQD

Attribute	Description	
Name	BULKPMTREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PPCREFNO

Attribute	Description	
Name	PPCREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

PPCPROJECTID

Attribute	Description	
Name	PPCPROJECTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FacilitySchedules

Attribute	Description	
Name	FacilitySchedules	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITDATE

Attribute	Description	
Name	LIMITDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityTenorRestriction

Attribute	Description	
Name	FacilityTenorRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TENOR

Attribute	Description				
Name	TENOR				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

TENORMNEMONIC

Attribute	Description				
Name	TENORMNEMONIC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

LIMIT

Attribute	Description				
Name	LIMIT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

UTILISATION

Attribute	Description				
Name	UTILISATION				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

FROMPRV

Attribute	Description				
Name	FROMPRV				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**TONEXT**

Attribute	Description	
Name	TONEXT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**LIABBRANH**

Attribute	Description	
Name	LIABBRANH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**FacilityCustomerRestriction**

Attribute	Description	
Name	FacilityCustomerRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CUSTOMERNO**

Attribute	Description	
Name	CUSTOMERNO	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FacilityBranchRestriction

Attribute	Description	
Name	FacilityBranchRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityProductRestriction

Attribute	Description	
Name	FacilityProductRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PRODUCTCODE

Attribute	Description	
Name	PRODUCTCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

FacilityCurrencyRestriction

Attribute	Description	
Name	FacilityCurrencyRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FacilityValueDateDetails

Attribute	Description	
Name	FacilityValueDateDetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LIMITAMOUNT

Attribute	Description	
Name	LIMITAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

VALUEDATE

Attribute	Description	
Name	VALUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

BOOKDATE

Attribute	Description	
Name	BOOKDATE	
Datatype	Date	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityPowerPocketLimits

Attribute	Description	
Name	FacilityPowerPocketLimits	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTACC

Attribute	Description	
Name	POWERPKTACC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTAMT

Attribute	Description	
Name	POWERPKTAMT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

POWERPKTDT

Attribute	Description	
Name	POWERPKTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CONSOLIDATEAMT

Attribute	Description	
Name	CONSOLIDATEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCharge

Attribute	Description	
Name	FacilityCharge	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGETYPE

Attribute	Description	
Name	ADMINCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ADMINCHARGEPERCT

Attribute	Description	
Name	ADMINCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ADMINCHARGEAMT

Attribute	Description	
Name	ADMINCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGETYPE

Attribute	Description	
Name	UTLCHARGETYPE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UTLCHARGEPERCT

Attribute	Description	
Name	UTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UTLCHARGEAMT

Attribute	Description	
Name	UTLCHARGEAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGETYPE

Attribute	Description	
Name	UNUTLCHARGETYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UNUTLCHARGEPERCT

Attribute	Description	
Name	UNUTLCHARGEPERCT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UNUTLCHARGEAMT

Attribute	Description	
Name	UNUTLCHARGEAMT	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityCovenant

Attribute	Description	
Name	FacilityCovenant	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTID

Attribute	Description	
Name	COVENANTID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

PERIODCITY

Attribute	Description	
Name	PERIODCITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Q,S,W,Y

[TOP](#)

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

STARTDATE

Attribute	Description	
Name	STARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

GRACEDAYS

Attribute	Description	
Name	GRACEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

REVISIONDATE

Attribute	Description	
Name	REVISIONDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NOTICEDAYS

Attribute	Description	
Name	NOTICEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COVENANTREFNO

Attribute	Description	
Name	COVENANTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilityExposure

Attribute	Description	
Name	FacilityExposure	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

EXPOSUREID

Attribute	Description	
Name	EXPOSUREID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FacilitySystemRestriction

Attribute	Description	
Name	FacilitySystemRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**FACILITYID**

Attribute		Description
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EXTSYSTEM**

Attribute		Description
Name	EXTSYSTEM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MODNO**

Attribute		Description
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FacilityPoolLink**

Attribute		Description
Name	FacilityPoolLink	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**LIABID**

Attribute		Description
Name	LIABID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

POOLID

Attribute	Description	
Name	POOLID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FACILITYBRANCHCODE

Attribute	Description	
Name	FACILITYBRANCHCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYID

Attribute	Description	
Name	FACILITYID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYCURRENCY

Attribute	Description	
Name	FACILITYCURRENCY	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FACILITYAMOUNT

Attribute	Description	
Name	FACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FACILITYAMOUNTPOOLCCY

Attribute	Description	
Name	FACILITYAMOUNTPOOLCCY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFPOOL

Attribute	Description	
Name	PERCENTAGEOFPOOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PERCENTAGEOFCONTRACT

Attribute	Description	
Name	PERCENTAGEOFCONTRACT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	

Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityExposureRestriction

Attribute	Description	
Name	FacilityExposureRestriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXPOSURE

Attribute	Description	
Name	EXPOSURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityMandate

Attribute	Description	
Name	FacilityMandate	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

MANDATETYPE

Attribute	Description	
Name	MANDATETYPE	
Datatype	String	

Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

MINPERAVAL

Attribute	Description	
Name	MINPERAVAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FacilityUDEValues

Attribute	Description	
Name	FacilityUDEValues	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FACILITY

Attribute	Description	
Name	FACILITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

UDEID

Attribute	Description	
Name	UDEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

UDEVALUE

Attribute	Description	
Name	UDEVALUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

CODEUSAGE

Attribute	Description	
Name	CODEUSAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.8.FacilityTransferAuthorize

Authorize FacilityTransfer

2.8.1.GE-FacilityTransferAuthorize-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT
 SOURCE
 USERREFERENCENO
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	
Datatype		
Description		

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYENDDT

Attribute	Description				
Name	TOFACILITYENDDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAMTOUNT

Attribute	Description				
Name	TOFACILITYAMTOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAVAILAMT

Attribute	Description				
Name	TOFACILITYAVAILAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

USERREFERENCENO

Attribute	Description				
Name	USERREFERENCENO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FromLiability

Attribute	Description	
Name	FromLiability	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description
-----------	-------------

Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.8.2.GE-FacilityTransferAuthorize-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-IO

TRANSFERREFNO

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-IO

Attribute	Description	
Name	FacilityTransfer-IO	
Datatype		
Description		

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.8.3.GE-FacilityTransferAuthorize-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT

SOURCE

USERREFERENCENO

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nilable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nilable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	

Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYENDDATE**

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYAMOUNT**

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYAVAILAMT**

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYCURRENCY**

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**TOFACILITYSTARTDT**

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYENDDT

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYAMTOUNT

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYAVAILAMT

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERREFERENCENO

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FromLiability

Attribute	Description
Name	FromLiability

Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

FROMLINESERIAL

Attribute		Description
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

ToLiability

Attribute		Description
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLIABILITYNO

Attribute		Description
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOLIABILITYNAME

Attribute		Description
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ToFacility

Attribute		Description
Name	ToFacility	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.8.4.GE-FacilityTransferAuthorize-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-PK

TRANSFERREFNO

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

FacilityTransfer-PK

Attribute	Description
Name	FacilityTransfer-PK

Datatype	
Description	

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)**FCUBS_WARNING_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.9.FacilityTransferClose

Close FacilityTransfer

2.9.1.GE-FacilityTransferClose-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT
 SOURCE
 USERREFERENCENO
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	
Datatype		
Description		

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYENDDT

Attribute	Description				
Name	TOFACILITYENDDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAMTOUNT

Attribute	Description				
Name	TOFACILITYAMTOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAVAILAMT

Attribute	Description				
Name	TOFACILITYAVAILAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

USERREFERENCENO

Attribute	Description				
Name	USERREFERENCENO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FromLiability

Attribute	Description	
Name	FromLiability	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description
-----------	-------------

Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.9.2.GE-FacilityTransferClose-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-IO

TRANSFERREFNO

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-IO

Attribute	Description	
Name	FacilityTransfer-IO	
Datatype		
Description		

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.9.3.GE-FacilityTransferClose-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT

SOURCE

USERREFERENCENO

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	

Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYENDDATE**

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYAMOUNT**

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYAVAILAMT**

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYCURRENCY**

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**TOFACILITYSTARTDT**

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYENDDT**

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAMTOUNT**

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAVAILAMT**

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**USERREFERENCENO**

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FromLiability

Attribute	Description
Name	FromLiability

Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.9.4.GE-FacilityTransferClose-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-PK

TRANSFERREFNO

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
------------------	--------------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-PK

Attribute	Description	
Name	FacilityTransfer-PK	

Datatype	
Description	

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
Attribute	Description						
maxOccurs	unbounded						
minOccurs	0						

[TOP](#)

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description	Indicates the warning encountered.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.10.FacilityTransferCreate

Create FacilityTransfer

2.10.1.GE-FacilityTransferCreate-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT
 SOURCE
 USERREFERENCENO
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	
Datatype		
Description		

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYENDDT

Attribute	Description				
Name	TOFACILITYENDDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAMTOUNT

Attribute	Description				
Name	TOFACILITYAMTOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAVAILAMT

Attribute	Description				
Name	TOFACILITYAVAILAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

USERREFERENCENO

Attribute	Description				
Name	USERREFERENCENO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FromLiability

Attribute	Description	
Name	FromLiability	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description
-----------	-------------

Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.10.2.GE-FacilityTransferCreate-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-IO

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT

SOURCE

USERREFERENCENO

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

FacilityTransfer-IO

Attribute	Description
Name	FacilityTransfer-IO
Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description
Name	EFFECTIVEFROMDATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYENDDT

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAMTOUNT**

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAVAILAMT**

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**USERREFERENCENO**

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FromLiability

Attribute	Description	
Name	FromLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

FROMLIABILITYNO

Attribute	Description
Name	FROMLIABILITYNO

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

2.10.3.GE-FacilityTransferCreate-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT

SOURCE

USERREFERENCENO

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	

Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYENDDATE**

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYAMOUNT**

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYAVAILAMT**

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYCURRENCY**

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**TOFACILITYSTARTDT**

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYENDDT**

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAMTOUNT**

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAVAILAMT**

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**USERREFERENCENO**

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FromLiability

Attribute	Description
Name	FromLiability

Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

FROMLINESERIAL

Attribute		Description
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

ToLiability

Attribute		Description
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLIABILITYNO

Attribute		Description
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOLIABILITYNAME

Attribute		Description
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ToFacility

Attribute		Description
Name	ToFacility	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.10.4.GE-FacilityTransferCreate-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-PK

TRANSFERREFNO

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-PK

Attribute	Description	
Name	FacilityTransfer-PK	

Datatype	
Description	

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.11.FacilityTransferDelete

Delete FacilityTransfer

2.11.1.GE-FacilityTransferDelete-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT
 SOURCE
 USERREFERENCENO
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	
Datatype		
Description		

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYENDDT

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYAMTOUNT

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYAVAILAMT

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERREFERENCENO

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FromLiability

Attribute	Description	
Name	FromLiability	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description
-----------	-------------

Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.11.2.GE-FacilityTransferDelete-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-IO

TRANSFERREFNO

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-IO

Attribute	Description	
Name	FacilityTransfer-IO	
Datatype		
Description		

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.11.3.GE-FacilityTransferDelete-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT

SOURCE

USERREFERENCENO

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	

Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYENDDATE**

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYAMOUNT**

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FROMFACILITYAVAILAMT**

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYCURRENCY**

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**TOFACILITYSTARTDT**

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYENDDT

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYAMTOUNT

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYAVAILAMT

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERREFERENCENO

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FromLiability

Attribute	Description
Name	FromLiability

Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.11.4.GE-FacilityTransferDelete-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-PK

TRANSFERREFNO

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-PK

Attribute	Description	
Name	FacilityTransfer-PK	

Datatype	
Description	

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
Attribute	Description						
maxOccurs	unbounded						
minOccurs	0						

[TOP](#)

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description	Indicates the warning encountered.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.12.FacilityTransferModify

Modify FacilityTransfer

2.12.1.GE-FacilityTransferModify-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT
 SOURCE
 USERREFERENCENO
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	
Datatype		
Description		

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYENDDT

Attribute	Description				
Name	TOFACILITYENDDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAMTOUNT

Attribute	Description				
Name	TOFACILITYAMTOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAVAILAMT

Attribute	Description				
Name	TOFACILITYAVAILAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

USERREFERENCENO

Attribute	Description				
Name	USERREFERENCENO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FromLiability

Attribute	Description	
Name	FromLiability	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description
-----------	-------------

Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.12.2.GE-FacilityTransferModify-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-IO

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT

SOURCE

USERREFERENCENO

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

FacilityTransfer-IO

Attribute	Description
Name	FacilityTransfer-IO
Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description
Name	EFFECTIVEFROMDATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYENDDT

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYAMTOUNT

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYAVAILAMT

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERREFERENCENO

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FromLiability

Attribute	Description	
Name	FromLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

FROMLIABILITYNO

Attribute	Description
Name	FROMLIABILITYNO

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

2.12.3.GE-FacilityTransferModify-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT

SOURCE

USERREFERENCENO

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	

Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYENDDT

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYAMTOUNT

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYAVAILAMT

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERREFERENCENO

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FromLiability

Attribute	Description
Name	FromLiability

Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

FROMLINESERIAL

Attribute		Description
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

ToLiability

Attribute		Description
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLIABILITYNO

Attribute		Description
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOLIABILITYNAME

Attribute		Description
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ToFacility

Attribute		Description
Name	ToFacility	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.12.4.GE-FacilityTransferModify-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-PK

TRANSFERREFNO

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

FacilityTransfer-PK

Attribute	Description
Name	FacilityTransfer-PK

Datatype	
Description	

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description	Indicates the warning encountered.				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.13.FacilityTransferQuery

Query FacilityTransfer

2.13.1.GE-FacilityTransferQuery-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-IO

TRANSFERREFNO

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-IO

Attribute	Description	
Name	FacilityTransfer-IO	
Datatype		
Description		

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.13.2.GE-FacilityTransferQuery-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT

SOURCE

USERREFERENCENO

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

FacilityTransfer-Full

Attribute	Description
Name	FacilityTransfer-Full

Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYENDDT**

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAMTOUNT**

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAVAILAMT**

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**USERREFERENCENO**

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FromLiability

Attribute	Description
Name	FromLiability

Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

FROMLINESERIAL

Attribute		Description
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

ToLiability

Attribute		Description
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLIABILITYNO

Attribute		Description
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOLIABILITYNAME

Attribute		Description
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ToFacility

Attribute		Description
Name	ToFacility	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.14.FacilityTransferReopen

Reopen FacilityTransfer

2.14.1.GE-FacilityTransferReopen-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT
 SOURCE
 USERREFERENCENO
 MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

FacilityTransfer-Full

Attribute	Description
Name	FacilityTransfer-Full
Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TOFACILITYENDDT

Attribute	Description				
Name	TOFACILITYENDDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAMTOUNT

Attribute	Description				
Name	TOFACILITYAMTOUNT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

TOFACILITYAVAILAMT

Attribute	Description				
Name	TOFACILITYAVAILAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

USERREFERENCENO

Attribute	Description				
Name	USERREFERENCENO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
	Restrictions	Description			
maxLength	50				

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

FromLiability

Attribute	Description	
Name	FromLiability	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

FIELD_NAME

Attribute	Description
-----------	-------------

Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

2.14.2.GE-FacilityTransferReopen-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-IO

TRANSFERREFNO

MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	Restrictions
	enumeration
	Description
	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attributes	Attribute
	minOccurs
	0
nillable	
true	
Restrictions	Restrictions
	pattern
	Description
	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attributes	Attribute
	minOccurs
	0
nillable	
true	
Restrictions	Restrictions
	pattern
	Description
	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-IO

Attribute	Description	
Name	FacilityTransfer-IO	
Datatype		
Description		

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

2.14.3.GE-FacilityTransferReopen-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-Full

EFFECTIVEFROMDATE

EFFECTIVETODATE

TRANSFERAMOUNT

REMARKS

EXPIRYSTATUS

BRANCH

TRANSFERREFNO

FROMFACILITYCURRENCY

FROMFACILITYSTARTDATE

FROMFACILITYENDDATE

FROMFACILITYAMOUNT

FROMFACILITYAVAILAMT

TOFACILITYCURRENCY

TOFACILITYSTARTDT

TOFACILITYENDDT

TOFACILITYAMTOUNT

TOFACILITYAVAILAMT

SOURCE

USERREFERENCENO

MAKERID
 MAKERDTSTAMP
 CHECKERID
 CHECKERDTSTAMP
 MODNO
 AUTHSTAT
 RECSTAT
 ONCEAUTH
 FromLiability
 FROMLIABILITYNO
 FROMLIABILITYNAME
 FromFacility
 FROMLINECODE
 FROMLINESERIAL
 ToLiability
 TOLIABILITYNO
 TOLIABILITYNAME
 ToFacility
 TOLINECODE
 TOLINESERIAL
 UDFDETAILS
 FUNCTIONID
 FIELD_NAME
 DATATYPE
 FIELD_VALUE
 VAL_TYPE
 FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
 FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description	The name of the additional parameter comes here.	

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description	The value of the additional parameter comes here.	

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

[TOP](#)

FacilityTransfer-Full

Attribute	Description	
Name	FacilityTransfer-Full	

Datatype	
Description	

[TOP](#)

EFFECTIVEFROMDATE

Attribute	Description	
Name	EFFECTIVEFROMDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

EFFECTIVETODATE

Attribute	Description	
Name	EFFECTIVETODATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TRANSFERAMOUNT

Attribute	Description	
Name	TRANSFERAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

EXPIRYSTATUS

Attribute	Description	
Name	EXPIRYSTATUS	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FROMFACILITYCURRENCY

Attribute	Description	
Name	FROMFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FROMFACILITYSTARTDATE

Attribute	Description	
Name	FROMFACILITYSTARTDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMFACILITYENDDATE

Attribute	Description	
Name	FROMFACILITYENDDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMFACILITYAMOUNT

Attribute	Description	
Name	FROMFACILITYAMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

FROMFACILITYAVAILAMT

Attribute	Description	
Name	FROMFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOFACILITYCURRENCY

Attribute	Description	
Name	TOFACILITYCURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOFACILITYSTARTDT

Attribute	Description	
Name	TOFACILITYSTARTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYENDDT**

Attribute	Description	
Name	TOFACILITYENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAMTOUNT**

Attribute	Description	
Name	TOFACILITYAMTOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TOFACILITYAVAILAMT**

Attribute	Description	
Name	TOFACILITYAVAILAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**USERREFERENCENO**

Attribute	Description	
Name	USERREFERENCENO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FromLiability

Attribute	Description
Name	FromLiability

Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLIABILITYNO

Attribute	Description	
Name	FROMLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

FROMLIABILITYNAME

Attribute	Description	
Name	FROMLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

FromFacility

Attribute	Description	
Name	FromFacility	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

FROMLINECODE

Attribute	Description	
Name	FROMLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

FROMLINESERIAL

Attribute	Description	
Name	FROMLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

ToLiability

Attribute	Description	
Name	ToLiability	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	1

TOLIABILITYNO

Attribute	Description	
Name	TOLIABILITYNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOLIABILITYNAME

Attribute	Description	
Name	TOLIABILITYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ToFacility

Attribute	Description	
Name	ToFacility	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

TOLINECODE

Attribute	Description	
Name	TOLINECODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

TOLINESERIAL

Attribute	Description	
Name	TOLINESERIAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description	This indicates the description of the error encountered.	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description	Indicates the warning encountered.	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)

2.14.4.GE-FacilityTransferReopen-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

FacilityTransfer-PK

TRANSFERREFNO

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description	This node is to be used for Additional information about a message.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description	This is the parent node for each parameter in the additional node.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	The name of the additional parameter comes here.

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	The value of the additional parameter comes here.

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

[TOP](#)

FacilityTransfer-PK

Attribute	Description
Name	FacilityTransfer-PK

Datatype	
Description	

[TOP](#)

TRANSFERREFNO

Attribute	Description	
Name	TRANSFERREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description	This indicates the type of error encountered.	
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description	This indicates the code for the error encountered.	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	This indicates the description of the error encountered.

[TOP](#)**FCUBS_WARNING_RESP**

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)**WARNING**

Attribute	Description				
Name	WARNING				
Datatype					
Description	Indicates the warning encountered.				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	This indicates the code for the warning encountered.

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	This indicates the description of the warning encountered

[TOP](#)



ELFacilityService
[August] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2014], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.